

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 08/04/2021

Version: 1.1

Reviewed on 08/04/2021

* 1 Identification

Product identifier

Product name: Magenta UV LED Flex Ink

Article number: 3C02xx

Details of the supplier of the safety data sheet

CET COLOR

4450 Commerce Dr. SW

Atlanta, GA 30336

404.228.1259

Manufacturer/Supplier:

CET COLOR

4450 Commerce Dr. SW

Atlanta, GA 30336

USA

Information department: info@cetcolor.com

Emergency telephone number: Verisk 3E US & Canada: +1 866 519 4752; Access Code: 335740

* 2 Hazard(s) identification

Classification of the substance or mixture

Acute Tox. 4 H302 Harmful if swallowed.

Skin Corr. 1C H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 1B H360 May damage fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Label elements

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



GHS05 GHS07 GHS08

Signal word

Danger

Hazard-determining components of labeling:

Tetrahydrofurfuryl Acrylate

4-(1-oxo-2-propenyl)-morpholine

Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

propylidynetrimethanol, propoxylated, esters with acrylic acid

Neopentylglycol(PO)₂ Diacrylate

Isobornyl Acrylate

Hazard statements

Harmful if swallowed.

Causes severe skin burns and eye damage.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 08/04/2021

Version: 1.1

Reviewed on 08/04/2021

Product name: Magenta UV LED Flex Ink

May cause an allergic skin reaction.

May damage fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

9 % of the mixture consists of component(s) of unknown toxicity.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

5117-12-4 4-(1-oxo-2-propenyl)-morpholine	10 - 25%
STOT RE 2, H373; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1, H317	
2399-48-6 Tetrahydrofurfuryl Acrylate	10 - 25%
Repr. 1B, H360; Skin Corr. 1C, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1, H317; Flam. Liq. 4, H227	
75980-60-8 Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	10 - 25%
Repr. 2, H361	
53879-54-2 propylidynetrimethanol, propoxylated, esters with acrylic acid	10 - 25%
Eye Irrit. 2A, H319; Skin Sens. 1, H317	
84170-74-1 Neopentylglycol(PO)2 Diacrylate	≥ 2.5 - ≤ 10%
Skin Sens. 1, H317	
5888-33-5 Isobournyl Acrylate	2.5 - 10%
Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	

— US —

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 08/04/2021

Version: 1.1

Reviewed on 08/04/2021

Product name: Magenta UV LED Flex Ink

4 First-aid measures

Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

Most important symptoms and effects, both acute and delayed No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents: Use fire fighting measures that suit the environment.

Special hazards arising from the substance or mixture No further relevant information available.

Advice for firefighters

Protective equipment: No special measures required.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Handling:

Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 08/04/2021

Version: 1.1

Reviewed on 08/04/2021

Product name: Magenta UV LED Flex Ink

Open and handle receptacle with care.

Prevent formation of aerosols.

Information about protection against explosions and fires: Keep respiratory protective device available.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep receptacle tightly sealed.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

Control parameters

Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 08/04/2021

Version: 1.1

Reviewed on 08/04/2021

Product name: Magenta UV LED Flex Ink

Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

Appearance:

Form:	Liquid
Color:	Magenta
Odor:	Characteristic
Odor threshold:	Not determined.

pH-value: Not determined.

Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.

Flash point: Not applicable.

Flammability (solid, gaseous): Not applicable.

Decomposition temperature: Not determined.

Auto igniting: Product is not selfigniting.

Danger of explosion: Product does not present an explosion hazard.

Explosion limits:

Lower:	Not determined.
Upper:	Not determined.

Vapor pressure: Not determined.

Density: Not determined.

Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.

Solubility in / Miscibility with

Water: Fully miscible.

Partition coefficient (n-octanol/water): Not determined.

Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

Other information No further relevant information available.

10 Stability and reactivity

Reactivity No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 08/04/2021

Version: 1.1

Reviewed on 08/04/2021

Product name: Magenta UV LED Flex Ink

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: No dangerous decomposition products known.

* 11 Toxicological information

Information on toxicological effects

Acute toxicity:

LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 < 463 mg/kg

5117-12-4 4-(1-oxo-2-propenyl)-morpholine

Oral LD50 500 mg/kg (ATE)

2399-48-6 Tetrahydrofurfuryl Acrylate

Oral LD50 928 mg/kg (rat)

53879-54-2 propylidynetrimethanol, propoxylated, esters with acrylic acid

Oral LD50 > 2,000 mg/kg (rat)

Primary irritant effect:

on the skin: Strong caustic effect on skin and mucous membranes.

on the eye: Strong caustic effect.

Sensitization: Sensitization possible through skin contact.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

Carcinogenic categories

IARC (International Agency for Research on Cancer)

108-88-3 Toluene: 3

123-35-3 Myrcene: 2B

100-41-4 ethylbenzene: 2B

127-19-5 N,N-dimethylacetamide: 2B

NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

Reproductive toxicity

2399-48-6 Tetrahydrofurfuryl Acrylate

Oral NOAEL 120 mg/kg/day (rat)

12 Ecological information

Toxicity

Aquatic toxicity: No further relevant information available.

Persistence and degradability No further relevant information available.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 08/04/2021

Version: 1.1

Reviewed on 08/04/2021

Product name: Magenta UV LED Flex Ink

Behavior in environmental systems:

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Ecotoxicological effects:

Remark: Toxic for fish

Additional ecological information:

General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods

Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

UN-Number

DOT

not regulated

IMDG, IATA

UN3082

UN proper shipping name

DOT

not regulated

IMDG

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Tetrahydrofurfuryl Acrylate, Neopentylglycol(PO)2 Diacrylate), MARINE POLLUTANT

IATA

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Tetrahydrofurfuryl Acrylate, Neopentylglycol(PO)2 Diacrylate)

Transport hazard class(es)

DOT

Class

not regulated

IMDG, IATA



Class

Label

9 Miscellaneous dangerous substances and articles

9

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 08/04/2021

Version: 1.1

Reviewed on 08/04/2021

Product name: Magenta UV LED Flex Ink

Packing group

DOT

not regulated

IMDG, IATA

III

Environmental hazards:

Marine pollutant:

Symbol (fish and tree)

Special marking (IATA):

Symbol (fish and tree)

Special precautions for user

Warning: Miscellaneous dangerous substances and articles

Hazard identification number (Kemler code): 90

EMS Number:

F-A,S-F

Stowage Category

A

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

Transport/Additional information:

IMDG

Limited quantities (LQ)

5L

Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

UN "Model Regulation":

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (TETRAHYDROFURFURYL ACRYLATE, NEOPENTYLGLYCOL(PO)2 DIACRYLATE), 9, III

*15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

SARA

Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

TSCA (Toxic Substances Control Act):

5117-12-4 4-(1-oxo-2-propenyl)-morpholine: ACTIVE

75980-60-8 Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide: ACTIVE

53879-54-2 propylidynetrimethanol, propoxylated, esters with acrylic acid: ACTIVE

84170-74-1 Neopentylglycol(PO)2 Diacrylate: ACTIVE

5888-33-5 Isobournyl Acrylate: ACTIVE

Hazardous Air Pollutants

108-88-3 Toluene

100-41-4 ethylbenzene

Proposition 65

Chemicals known to cause cancer:

123-35-3 Myrcene

100-41-4 ethylbenzene

127-19-5 N,N-dimethylacetamide

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

127-19-5 N,N-dimethylacetamide

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 08/04/2021

Version: 1.1

Reviewed on 08/04/2021

Product name: Magenta UV LED Flex Ink

Chemicals known to cause developmental toxicity:

108-88-3 Toluene

127-19-5 N,N-dimethylacetamide

Carcinogenic categories

EPA (Environmental Protection Agency)

110-82-7 cyclohexane: I

108-88-3 Toluene: II

100-41-4 ethylbenzene: D

TLV (Threshold Limit Value)

108-88-3 Toluene: A4

100-41-4 ethylbenzene: A3

127-19-5 N,N-dimethylacetamide: A4

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



GHS05 GHS07 GHS08

Signal word Danger

Hazard-determining components of labeling:

Tetrahydrofurfuryl Acrylate

4-(1-oxo-2-propenyl)-morpholine

Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

propylidynetrimethanol, propoxylated, esters with acrylic acid

Neopentylglycol(PO)₂ Diacrylate

Isobournyl Acrylate

Hazard statements

Harmful if swallowed.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

May damage fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 08/04/2021

Version: 1.1

Reviewed on 08/04/2021

Product name: Magenta UV LED Flex Ink

IF exposed or concerned: Get medical advice/attention.
 Specific treatment (see on this label).
 Get medical advice/attention if you feel unwell.
 If skin irritation or rash occurs: Get medical advice/attention.
 Wash contaminated clothing before reuse.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H227 Combustible liquid.
 H302 Harmful if swallowed.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H360 May damage fertility or the unborn child.
 H361 Suspected of damaging fertility or the unborn child.
 H373 May cause damage to organs through prolonged or repeated exposure.

Contact:

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 Flam. Liq. 4: Flammable liquids – Category 4
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Corr. 1C: Skin corrosion/irritation – Category 1C
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
 Skin Sens. 1: Skin sensitisation – Category 1
 Repr. 1B: Reproductive toxicity – Category 1B
 Repr. 2: Reproductive toxicity – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

*** Data compared to the previous version altered.**