

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12392574
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Puha; Teodor

Recoil management system for a gun

Abstract

A system is disclosed for extending a recoil impulse of a gun. The system elongates the recoil impulse to spread the recoil energy over time and reduce felt (i.e., peak) recoil force. Although the system adds weight to a gun, the system reduces felt recoil beyond what is possible by simply adding weight to a gun by using an inertial weight on a spring to absorb and release energy. To prevent shaking, the inertial weight system is tuned to a gun so that the inertial weight hits a pair of stops at certain points in the gun's discharge action cycle.

Inventors:	Puha; Teodor (Coeur D-Alene, ID)
Applicant:	Eight Holdings LLC (Coeu D-Alene, ID)
Family ID:	1000008766697
Assignee:	EIGHT HOLDINGS LLC (Coeur D'Alene, ID)
Appl. No.:	18/592882
Filed:	March 01, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250075995 A1	Mar. 06, 2025

Related U.S. Application Data

continuation parent-doc US 17528672 20211117 US 11946713 child-doc US 18592882
us-provisional-application US 63114840 20201117

Publication Classification

Int. Cl.: F41A25/12 (20060101); F41A3/88 (20060101); F41C27/22 (20060101)

U.S. Cl.:

CPC **F41A25/12** (20130101); **F41A3/88** (20130101); **F41C27/22** (20130101);

Field of Classification Search

CPC: F41A (3/86); F41A (3/88); F41A (25/10); F41A (25/12); F41A (25/14); F41A (21/36);
 F41A (5/02); F41A (5/10); F41A (5/14); F41C (27/22)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2679192	12/1953	Seeley	42/1.06	F41A 25/02
2685822	12/1953	Walton	89/44.01	F16F 7/116
3208348	12/1964	Lee	42/1.06	F41A 21/40
3683534	12/1971	Davis	42/1.06	F41C 23/06
4833808	12/1988	Strahan	42/1.06	F41A 21/28
4986018	12/1990	McDonald, Jr.	42/1.06	F41B 5/1426
5353681	12/1993	Sugg	89/43.01	F41A 25/16
8418389	12/2012	Lukman	42/1.06	F41A 5/34
9921022	12/2017	Noyce Merino	N/A	F41A 21/28
10415907	12/2018	Kincel	N/A	F41A 3/84

Primary Examiner: Klein; Gabriel J.

Attorney, Agent or Firm: Pitchford Fugett, PLLC

Background/Summary

CROSS-REFERENCES TO RELATED APPLICATIONS (1) This application claims priority to and hereby incorporates by reference in its entirety U.S. patent application Ser. No. 17/528,672 entitled “RECOIL MANAGEMENT SYSTEM FOR A GUN” filed on Nov. 17, 2021, which claims priority to U.S. Provisional Patent Application No. 63/114,840 entitled “INERTIA DELAY SYSTEM FOR A FIREARM” filed on Nov. 17, 2020. (2) A portion of the disclosure of this patent document contains material that is subject to copyright protection. The copyright owner has no objection to the reproduction of the patent document or the patent disclosure, as it appears in the U.S. Patent and Trademark Office patent file or records, but otherwise reserves all copyright rights whatsoever.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

(1) Not Applicable

REFERENCE TO SEQUENCE LISTING OR COMPUTER PROGRAM LISTING APPENDIX

(2) Not Applicable

BACKGROUND OF THE INVENTION

(3) The present invention relates generally to guns. More particularly, this invention pertains to systems and methods for reducing felt recoil in a gun.

(4) Guns such as firearms, black powder guns, and airguns produce recoil when discharged by

virtue of an energy release propelling a projectile and gases forward from the muzzle of the gun. Airguns release energy over a relatively large period of time which lengthens the recoil impulse, and modern firearms utilizing smokeless powder release energy over a relatively very short period of time which shortens the recoil impulse. Thus, perceived recoil (usually closely correlated with peak recoil force) is generally much higher for a firearm than for an airgun, even when the guns have the same weight and release the same amount of energy per shot. Still, some modern airguns are powerful enough to produce significant peak recoil force. Different semi-automatic action types can affect felt recoil (e.g., gas direct impingement systems generally having a lower felt recoil than recoil operated firearms), but most systems still experience a relatively high peak recoil force. Manual action types (e.g., bolt, pump, break, etc.) have the highest peak recoil force for a given cartridge. Recoil has several negative consequences such as pushing a shooter off target and bruising a shooter's shoulder when firing long guns (e.g., rifles, shotguns, and carbines).

BRIEF SUMMARY OF THE INVENTION

(5) Aspects of the present invention provide a system for extending a recoil impulse of a gun. The system elongates the recoil impulse to spread the recoil energy over time and reduce felt (i.e., peak) recoil force. Although the system adds weight to a gun, the system reduces felt recoil beyond what is possible by simply adding weight to a gun by using an inertial weight on a spring to absorb and release energy. To prevent shaking, the inertial weight system is tuned to a gun so that the inertial weight hits a pair of stops at certain points in the gun's discharge action cycle.

(6) In one aspect, the recoil management system for a gun includes an inertial weight stop, a weight spring, and an inertial weight. The inertial weight stop is configured to attach to a barrel of the gun. The barrel extends longitudinally along a longitudinal axis. The inertial weight stop is configured to extend radially outward from the barrel when the recoil management system is properly installed on the gun. The weight spring is configured to attach to the actual weight stop and extend longitudinally along the barrel of the gun from the inertial weight stop when the recoil management system is properly installed on the gun. The inertial weight is configured to attach to the weight spring and connect to the inertial weight stop via the weight spring when the recoil management system is properly installed on the gun such that longitudinal movement of the inertial weight relative to the barrel is controlled by the weight spring.

(7) In another aspect, a gun includes a recoil management system. The recoil management system includes an inertial weight stop, a weight spring, and an inertial weight. The inertial weight stop is configured to attach to a barrel of the gun. The barrel extends longitudinally along the longitudinal axis, and the inertial weight stop is configured to extend radially outward from the barrel (parentheses, e.g. away from the longitudinal axis). The weight spring is configured to attach to the inertial weight stop and extend longitudinally along the barrel of the gun from the inertial weight. The inertial weight is configured to attach to the weight spring and connect to the inertial weight stop via the weight spring such that longitudinal movement of the inertial weight relative to the barrel is controlled by the weight spring.

Description

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

(1) FIG. 1 is a side perspective view of a gun including an inertial recoil management system according to one embodiment of the invention.

(2) FIG. 2 is a top perspective view of the gun of FIG. 1.

(3) FIG. 3 is a cutaway side perspective view of the gun of FIG. 1.

(4) FIG. 4 is a side perspective cross section of the gun of FIG. 1 taken vertically along the longitudinal axis prior to a discharge action of the gun.

(5) FIG. 5 is a side perspective cross section of the gun of FIG. 1 taken vertically along the

longitudinal axis immediately after a discharge action of the gun has begun.

(6) FIG. 6 is a side perspective cross section of the gun of FIG. 1 taken vertically along the longitudinal axis upon a barrel stop of the gun making contact with an impact ring of the gun.

(7) FIG. 7 is a side perspective cross section of the gun of FIG. 1 taken vertically along the longitudinal axis upon an inertial weight of the gun making contact with a barrel stop of the gun during the discharge action of the gun.

(8) FIG. 8 is a side perspective cross section of the gun of FIG. 1 taken vertically along the longitudinal axis upon an inertial weight of the gun breaking contact with the breaking contact with a barrel stop of the gun during the discharge action of the gun while the bolt is back from the chamber of the gun.

(9) FIG. 9 is a side perspective partial diagram of the gun of FIG. 1 showing the components of the inertial recoil management system.

(10) Reference will now be made in detail to optional embodiments of the invention, examples of which are illustrated in accompanying drawings. Whenever possible, the same reference numbers are used in the drawing and in the description referring to the same or like parts.

DETAILED DESCRIPTION OF THE INVENTION

(11) While the making and using of various embodiments of the present invention are discussed in detail below, it should be appreciated that the present invention provides many applicable inventive concepts that can be embodied in a wide variety of specific contexts. The specific embodiments discussed herein are merely illustrative of specific ways to make and use the invention and do not delimit the scope of the invention.

(12) To facilitate the understanding of the embodiments described herein, a number of terms are defined below. The terms defined herein have meanings as commonly understood by a person of ordinary skill in the areas relevant to the present invention. Terms such as “a,” “an,” and “the” are not intended to refer to only a singular entity, but rather include the general class of which a specific example may be used for illustration. The terminology herein is used to describe specific embodiments of the invention, but their usage does not delimit the invention, except as set forth in the claims.

(13) As described herein, an upright position is considered to be the position of apparatus components while in proper operation or in a natural resting position and properly installed on a gun as described herein. Vertical, horizontal, above, below, side, top, bottom and other orientation terms are described with respect to this upright position during operation unless otherwise specified. The term “when” is used to specify orientation for relative positions of components, not as a temporal limitation of the claims or apparatus described and claimed herein unless otherwise specified. The terms “above,” “below,” “over,” and “under” mean “having an elevation or vertical height greater or lesser than” and are not intended to imply that one object or component is directly over or under another object or component. As described herein, the upright position of the recoil management system is when installed on a gun and the gun held in a generally horizontal firing ready position with the trigger below the action and the sights above the barrel as shown in FIG. 1.

(14) The phrase “in one embodiment,” as used herein does not necessarily refer to the same embodiment, although it may. Conditional language used herein, such as, among others, “can,” “might,” “may,” “e.g.,” and the like, unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments include, while other embodiments do not include, certain features, elements and/or states. Thus, such conditional language is not generally intended to imply that features, elements and/or states are in any way required for one or more embodiments or that one or more embodiments necessarily include logic for deciding, with or without operator input or prompting, whether these features, elements and/or states are included or are to be performed in any particular embodiment.

(15) Referring now to FIGS. 1-9, a gun **100** includes a recoil management system **101**. The gun **100** has a longitudinal axis **103** that is generally synonymous with a bore axis of the gun **100**. In one

embodiment, the gun **100** includes a barrel **105** in upper receiver (i.e., receiver) **107**, a stock (e.g., butt stock) **109**, and a bolt **111**. The barrel **105** extends longitudinally along the longitudinal axis **103**. A muzzle **131** of the barrel **105** forms a front or forward end of the gun **100**, and the stock **109** the back or rear of the gun **100**. It is contemplated that the gun **100** may include other parts such as a trigger, grip, magazine, sights, ammunition, a suppressor, and flash hider, and/or other accessories. As described and shown herein, it will be assumed that the recoil management system **101** has been properly installed on the gun **100**.

(16) In one embodiment, the recoil management system **101** includes an inertial weight stop **301**, a weight spring **303**, and an inertial weight **305**. The inertial weight stop **301** is configured to attach to the barrel **105** of the gun **100**. The inertial weight stop **301** is configured to extend radially outward from the barrel **105**. In one embodiment, the inertial weight stop **301** is attached to the barrel via corresponding threading in or on the inertial weight stop **301** and an outside surface of the barrel **105**. In another embodiment, the inertial weight stop **301** is attached to the barrel **105** via pins, welding, brazing. It is also contemplated that the inertial weight stop **301** may be integrally formed with the barrel **105**.

(17) The weight spring **303** is configured to attach to the inertial weight stop **301**. The inertial weight spring **303** extends longitudinally along the barrel **105** of the gun **100** from the inertial weight stop **301**. In one embodiment, the inertial weight **303** extends rearward from the inertial weight stop **301**. In one embodiment, the weight spring **303** is a stacked wave disc spring.

(18) The inertial weight **305** is configured to attach to the weight spring **303** and connect to the inertial weight stop **301** via the weight spring **303** such that longitudinal movement of the inertial weight **305** relative to the barrel **105** is controlled by the weight spring **303**. In one embodiment, the inertial weight **305** is a generally tubular annular body and is configured to surround a portion of the barrel **105** between the inertial weight stop **301** and a barrel stop of the gun **100**.

(19) In operation, the inertial weight **305** moves longitudinally relative to the barrel **105** alternatively impact or press upon via the inertial weight spring **303** the inertial weight stop **301** and a barrel stop **501** of the gun **100**. Referring now to FIG. 4, the gun **100** is shown for or prior to discharging the gun **100**. The inertial weight **305** is longitudinally spaced from the inertial weight stop **301** by the weight spring **303** such that the inertial weight **305** is in contact with the barrel stop **501** of the gun **100**. Referring to FIG. 5, upon discharging the gun which begins the discharge cycle (i.e., discharge, case ejection, and new cartridge loading for an automatic or semi-automatic firearm) or action of the gun **100** rearward longitudinal motion of the barrel **105** moves the barrel stop **501** of the gun **100** away from the inertial weight **305** while moving the inertial weight stop **301** closer to the inertial weight **305** and into contact with the inertial weight, compressing the weight spring **303** (either partially or entirely compressing the weight spring **303** depending on the spring design). Referring to FIG. 6, a barrel assembly of the gun **100** (e.g., barrel **105** and barrel stop **501** along with various other accessories and components determined by the action type of the gun **100**) contacts the front of the receiver **107** (i.e., in this gun design, the impact ring **503**), halting rearward longitudinal movement of the barrel assembly relative to the receiver **107**. Referring to FIG. 7, after the barrel assembly (i.e., in this action design, the barrel stop **501**) contacts the front of the receiver (i.e., in this gun action design the impact ring **503**), the inertial weight **305** is configured to contact barrel stop **501** to transfer energy from the inertial weight **305** to the barrel stop **501**, and through the impact ring **503**, receiver **107**, stock **109**, and other optional components of the gun **100** to a shooter or user of the gun **100**. That is, the inertial weight **305** breaks contact with the inertial weight stop **301**, and the weight spring **303** pushes the inertial weight into a forward face of the barrel stop **501** while the barrel stop is in contact with the impact ring **503**. Referring to FIG. 8, as the bolt **111** is unlocked from the barrel **105** (i.e., the chamber of the barrel assembly) and is moving rearward or reaches its rearward apex (before beginning to move forward), the inertial weight **305** breaks contact with the barrel stop **501** and moves forward toward the inertial weight stop **301** compressing the weight spring **303** and

potentially contacting the inertial weight stop **301** in some designs. The timing of the inertial weight **305** contacting the barrel stop **501** (e.g., front of receiver in a bolt action or pump action gun), breaking contact with the barrel stop **501**, and moving toward the inertial weight stop **301** is determined by a balance of factors, and the system **1010** should be tuned for each action type and ammunition type. The factors controlling the timing and force reductions in the gun **100** and system **101** include a spring rate of the weight spring **303**, a mass of the inertial weight **305**, a muzzle energy of the gun **100**, an initial or rest distance between the inertial weight **303** and the inertial weight stop **301**, an initial distance between the inertial weight **305** and the front of the receiver or barrel stop **501** (the distance is zero in the illustrated design of FIG. 4), a reciprocating distance **703** of the barrel assembly (i.e., initial distance between the barrel stop **501** and impact ring **503**), and a spring rate of a buffer spring (i.e., bolt return spring) of the gun **100**. In one embodiment, these factors are balanced such that the inertial weight **305** impacts the barrel stop **501** while the bolt **111** is moving rearward and ejecting a casing from the action of the gun **100**, and the barrel assembly and inertial weight return to an initial position before the bolt **111** begins moving forward to lock into the barrel assembly (typically reloading the gun with a new cartridge from a magazine as in the short recoil design used for illustration purposes herein).

(20) It is contemplated that the inertia based recoil management system disclosed herein may be used with many types of actions including short and long recoil actions, gas direct impingement actions, pump actions, bolt actions, break actions, and virtually any other type of action. In fixed barrel designs, the barrel stop **501** does not reciprocate into the receiver **107**, such that the front of the receiver is the barrel stop **501**. In one embodiment, the inertial weight is initially spaced away from the barrel stop **501** before discharge of the gun **100**. It is also contemplated that the barrel stop **501** may be an enlarged or machined area of the barrel **105** as opposed to a front end of the receiver such that the inertial weight **305** transfers energy to the barrel **105** and ultimately to the receiver **107**, stock **109**, and user.

(21) It is contemplated within the scope of the claims that the longitudinal axis **103** of the recoil management system **101** is not the same as the bore axis of the gun **100**. That is, in one embodiment, the recoil management system includes a tube or rod extending along the longitudinal axis **103**. The inertial weight **305**, spring **303**, and inertial weight stop **301** as well as a rear stop (e.g., barrel stop **501**) are mounted in or on the tube. The tube may be mounted to a rail system of the gun **100**, to the barrel **105**, or at an angle relative to the barrel **105**. The longitudinal axis **103** may be generally parallel to the barrel **103** or at an angle (typically downward) relative to the barrel **103**.

(22) This written description uses examples to disclose the invention and also to enable any person skilled in the art to practice the invention, including making and using any devices or systems and performing any incorporated methods. The patentable scope of the invention is defined by the claims, and may include other examples that occur to those skilled in the art. Such other examples are intended to be within the scope of the claims if they have structural elements that do not differ from the literal language of the claims, or if they include equivalent structural elements with insubstantial differences from the literal languages of the claims.

(23) It will be understood that the particular embodiments described herein are shown by way of illustration and not as limitations of the invention. The principal features of this invention may be employed in various embodiments without departing from the scope of the invention. Those of ordinary skill in the art will recognize numerous equivalents to the specific procedures described herein. Such equivalents are considered to be within the scope of this invention and are covered by the claims.

(24) All of the compositions and/or methods disclosed and claimed herein may be made and/or executed without undue experimentation in light of the present disclosure. While the compositions and methods of this invention have been described in terms of the embodiments included herein, it will be apparent to those of ordinary skill in the art that variations may be applied to the

compositions and/or methods and in the steps or in the sequence of steps of the method described herein without departing from the concept, spirit, and scope of the invention. All such similar substitutes and modifications apparent to those skilled in the art are deemed to be within the spirit, scope, and concept of the invention as defined by the appended claims.

(25) Thus, although there have been described particular embodiments of the present invention of a new and useful RECOIL MANAGEMENT SYSTEM FOR A GUN it is not intended that such references be construed as limitations upon the scope of this invention except as set forth in the following claims.

Claims

1. A recoil management system for a gun, said system comprising: an inertial weight stop configured to attach to a barrel of the gun, said barrel extending longitudinally along a longitudinal axis, and said inertial weight stop configured to extend radially outward from the barrel; a barrel stop configured to attach to the barrel and extend radially outward from the barrel, the barrel stop configured to halt rearward longitudinal movement of the barrel; and an inertial weight configured to surround a portion of the barrel between the inertial weight stop and the barrel stop, the inertial weight configured to move relative to the barrel so as to contact the barrel stop and transfer absorbed energy from the inertial weight to the barrel stop.
2. The recoil management system of claim 1, wherein: before discharging the gun, the inertial weight is longitudinally spaced from the inertial weight stop and in contact with the barrel stop.
3. The recoil management system of claim 1, wherein: upon discharging the gun, rearward longitudinal motion of the barrel moves the barrel stop of the gun rearward and away from the inertial weight while moving the inertial weight stop closer to the inertial weight.
4. The recoil management system of claim 3, wherein: upon discharging the gun, after a barrel assembly of the gun contacts an impact ring of the gun halting rearward longitudinal movement of the barrel assembly relative to a receiver of the gun, the inertial weight is configured to contact the barrel stop to transfer energy from the inertial weight to the barrel stop and the receiver.
5. The recoil management system of claim 1, wherein: the inertial weight is configured to be in contact with the barrel stop after discharging the gun and break contact with the barrel stop before a bolt of the gun begins moving forward after discharging the gun, during a discharge cycle of the gun.
6. The recoil management system of claim 1, wherein: the gun is calibrated such that the inertial weight contacts the barrel stop while a bolt of the gun is in a back position, unlocked from a chamber of the barrel.
7. The recoil management system of claim 1, wherein: the barrel and the inertial weight stop have corresponding threads for threading the inertial weight stop onto the barrel to attach the inertial weight stop to the barrel.
8. The recoil management system of claim 1, wherein: the barrel stop is a barrel stop of a short recoil action gun.
9. The recoil management system of claim 1, further comprising: a weight spring configured to connect in between the inertial weight stop and the inertial weight, the weight spring configured to extend longitudinally along the barrel; and the inertial weight is configured to translate longitudinally relative to the barrel via the weight spring, between the inertial weight stop and the barrel stop.
10. The recoil management system of claim 9, wherein: the inertial weight is configured to contact the inertial weight stop and the barrel stop for transferring energy therebetween.
11. The recoil management system of claim 9, wherein: the weight spring is a stacked wave disc spring.
12. The recoil management system of claim 1, wherein: the inertial weight is configured to absorb

energy from the barrel as the barrel moves longitudinally rearward, and transfer the absorbed energy to the barrel stop upon the inertial weight moving longitudinally rearward and contacting the barrel stop.

13. The recoil management system of claim 1, wherein: the barrel and the barrel stop are configured to form a barrel assembly; and the barrel assembly is configured to reciprocate longitudinally in a reciprocating distance between the barrel stop and an impact ring of a receiver.

14. The recoil management system of claim 1, wherein: the barrel stop is one of a front end of a receiver of the gun, an area of an enlarged external diameter of the barrel, or a radial protrusion from the barrel, and the barrel stop is integral with the barrel.

15. A gun, comprising: a barrel extending longitudinally along a longitudinal axis; and a recoil management system, comprising: an inertial weight stop connected to the barrel; a barrel stop connected to the barrel and extending radially outward from the barrel, the barrel stop configured to halt rearward longitudinal movement of the barrel; a weight spring connected to the inertial weight stop; and an inertial weight connected to the weight spring and surrounding a portion of the barrel between the inertial weight stop and the barrel stop, the inertial weight configured to move via the weight spring and contact the barrel stop so as to transfer absorbed energy from the inertial weight to the barrel stop.

16. The gun of claim 15, wherein: before discharging the gun, the inertial weight is longitudinally spaced from the inertial weight stop by the weight spring and in contact with the barrel stop.

17. The gun of claim 15, wherein: upon discharging the gun, rearward longitudinal motion of the barrel moves the barrel stop of the gun rearward and away from the inertial weight while moving the inertial weight stop closer to the inertial weight, compressing the weight spring.

18. The gun of claim 17, wherein: upon discharging the gun, after a barrel assembly of the gun contacts an impact ring of the gun halting rearward longitudinal movement of the barrel assembly relative to a receiver of the gun, the inertial weight is configured to contact the barrel stop to transfer energy from the inertial weight to the barrel stop and the receiver.

19. The gun of claim 15, wherein: the inertial weight is configured to be in contact with the barrel stop after discharging the gun and break contact with the barrel stop before a bolt of the gun begins moving forward after discharging the gun, during a discharge cycle of the gun.

20. The gun of claim 15, wherein: the gun is calibrated such that the inertial weight contacts the barrel stop before a bolt of the gun begins moving forward during a discharge cycle of the gun while the bolt is in a back position, unlocked from a chamber of the barrel.
