

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12392098
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Smolley; John

---

### Animal waste collecting assembly and method

---

#### Abstract

An animal waste collecting assembly includes a pole defining a handle. The pole is elongated and has a first end and a second end. A frame releasably engages and supports a plastic bag and includes a closed loop attached to and extending away from the second end of the pole. The closed loop has an end member positioned opposite of the pole. The end member is linear for a distance greater than 4.0 inches and is orientated perpendicular to a longitudinal axis of the pole. A plurality of tines is attached to and extends away from the end member. The tines are co-planar with respect to each other and lie in a plane angled back toward the pole. A clip is mounted on the pole adjacent to the second end. The clip releasably secures an edge of the plastic bag to the pole.

---

<b>Inventors:</b>	<b>Smolley; John (Maple Grove, MN)</b>
<b>Applicant:</b>	<b>Smolley; John (Maple Grove, MN)</b>
<b>Family ID:</b>	<b>1000008765057</b>
<b>Appl. No.:</b>	<b>17/881248</b>
<b>Filed:</b>	<b>August 04, 2022</b>

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20220372719 A1	Nov. 24, 2022

#### Related U.S. Application Data

continuation-in-part parent-doc US 16662727 20191024 US 11441280 child-doc US 17881248

---

#### Publication Classification

**Int. Cl.:** E01H1/12 (20060101)

**U.S. Cl.:**

CPC            **E01H1/1206** (20130101);

## **Field of Classification Search**

**CPC:**            E01H (1/1206); E01H (2001/1293)

---

## **References Cited**

### **U.S. PATENT DOCUMENTS**

<b>Patent No.</b>	<b>Issued Date</b>	<b>Patentee Name</b>	<b>U.S. Cl.</b>	<b>CPC</b>
3688483	12/1971	Hamilton	N/A	N/A
4138153	12/1978	Brown	N/A	N/A
8146967	12/2011	Brown	N/A	N/A
8684429	12/2013	Holub	N/A	N/A
9072280	12/2014	Ramouler	N/A	N/A
9347192	12/2015	Smith	N/A	N/A
9756836	12/2016	Coba	N/A	N/A
9999200	12/2017	Desimone	N/A	N/A
10006180	12/2017	Weber	N/A	N/A
10024011	12/2017	Griffin	N/A	N/A
11441280	12/2021	Smolley	N/A	E01H 1/1206
2004/0164568	12/2003	Diehl	N/A	N/A
2009/0072559	12/2008	Wilkerson	N/A	N/A

---

*Primary Examiner:* Vu; Stephen A

---

## **Background/Summary**

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This is a continuation in part and I hereby claim the benefit under 35 U.S.C., Section 120 of U.S. application Ser. No. 16/662,727 filed on Oct. 24, 2019.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

(1) Not Applicable

THE NAMES OF THE PARTIES TO A JOINT RESEARCH AGREEMENT

(2) Not Applicable

INCORPORATION-BY-REFERENCE OF MATERIAL SUBMITTED ON A COMPACT DISC  
OR AS A TEXT FILE VIA THE OFFICE ELECTRONIC FILING SYSTEM

(3) Not Applicable

STATEMENT REGARDING PRIOR DISCLOSURES BY THE INVENTOR OR JOINT  
INVENTOR

(4) Not Applicable

BACKGROUND OF THE INVENTION

(1) Field of the Invention

(5) The disclosure relates to animal waste collector and more particularly pertains to a new animal waste collector for effectively retrieving animal waste out of grass in such a manner that the animal

waste is not pushed into the grass and the animal waste is securely contained.

(2) Description of Related Art Including Information Disclosed Under 37 CFR 1.97 and 1.98

(6) The prior art relates to animal waste collectors in general and more particularly animal waste scooping devices for capturing animal waste within a disposable bag.

#### BRIEF SUMMARY OF THE INVENTION

(7) An embodiment of the disclosure meets the needs presented above by generally comprising a pole defining a handle. The pole is elongated and has a first end and a second end. A frame releasably engages and supports a plastic bag and includes a closed loop attached to and extending away from the second end of the pole. The closed loop has an end member positioned opposite of the pole. The end member is linear for a distance greater than 4.0 inches and is orientated perpendicular to a longitudinal axis of the pole. A plurality of tines is attached to and extends away from the end member. The tines are co-planar with respect to each other and lie in a plane angled back toward the pole. A clip is mounted on the pole adjacent to the second end and releasably secures an edge of the plastic bag adjacent to the pole.

(8) Another embodiment of the disclosure teaches a pole defining a handle which is elongated and has a first end and a second end. A frame configured to releasably engage and support a plastic bag includes a closed loop that is attached to and extends away from the second end of the pole. The closed loop has an end member positioned opposite of the pole. The end member is linear for a distance greater than 4.0 inches and is orientated perpendicular to a longitudinal axis of the pole. A plurality of tines is attached to and extends away from the end member. The tines are co-planar with respect to each other and lie in a same plane. An engagement member is mounted adjacent to the second end of the pole and is configured to releasably secure the plastic bag adjacent to the pole to retain the plastic bag in an open configuration. A receiver includes a bottom surface having a plurality of wells extending therein. The wells are aligned with each other and positioned such that each of the tines is simultaneously extendable into one of the wells. The receiver is configured to be urged against the plastic bag positioned between the tines and the receiver such that the tines impale the plastic bag.

(9) In another embodiment the disclosure teaches a method of positioning a plastic bag adjacent to a frame attached to a pole. The pole has a first end and a second end. The frame is positioned adjacent to the second end and includes a closed loop attached to and extending away from the second end of the pole. The closed loop has an end member positioned opposite of the pole that is linear for a distance greater than 4.0 inches and is orientated perpendicular to a longitudinal axis of the pole. A plurality of tines is attached to and extends away from the end member. The tines are co-planar with respect to each other and lay a plane angled back toward the pole. The tines are urged through the plastic bag at a location adjacent to a perimeter edge of the plastic bag. The bag is extended through the closed loop and an opposite edge of the bag relative to the tines is secured to the pole with a clip mounted on the pole adjacent to the second end. The clip is configured to releasably secure an edge of the plastic bag to the pole. A pair of spikes is extended through the bag. The spikes are attached to the frame and are positioned on opposite sides of the longitudinal axis with respect to each other. The spikes extend toward the pole. The tines are moved across a ground surface to engage and capture animal waste positioned on the ground surface such that the animal waste moves into the plastic bag.

(10) In yet another embodiment, the disclosure teaches a method of collecting animal waste including positioning a plastic bag on a frame attached to the pole and securing the plastic bag to the frame. The steps of securing the plastic bag on the frame includes extending a plurality of tines of the frame through the plastic bag adjacent to a perimeter edge of the plastic bag. The tines are co-planar with each other and positioned on an end member distal to the pole. An opposite edge of the plastic bag relative to the tines is attached to the frame proximate to the pole with an engagement member. The plastic bag is extended through a closed loop formed by the frame rearward of the tines and engagement member such that plastic bag remains in an open

configuration between the engagement member the tines. The tines are moved across a ground surface to engage and capture animal waste positioned on the ground surface such that the animal waste moves into the plastic bag. The plastic bag is thereafter removed from the frame and discarded.

(11) There has thus been outlined, rather broadly, the more important features of the disclosure in order that the detailed description thereof that follows may be better understood, and in order that the present contribution to the art may be better appreciated. There are additional features of the disclosure that will be described hereinafter and which will form the subject matter of the claims appended hereto.

(12) The objects of the disclosure, along with the various features of novelty which characterize the disclosure, are pointed out with particularity in the claims annexed to and forming a part of this disclosure.

---

## Description

### BRIEF DESCRIPTION OF SEVERAL VIEWS OF THE DRAWING(S)

(1) The disclosure will be better understood and objects other than those set forth above will become apparent when consideration is given to the following detailed description thereof. Such description makes reference to the annexed drawings wherein:

(2) FIG. 1 is a front isometric view of a animal waste collecting assembly and method according to an embodiment of the disclosure.

(3) FIG. 2 is a side view of an embodiment of the disclosure.

(4) FIG. 3 is a front isometric view of an embodiment of the disclosure.

(5) FIG. 4 is a front isometric view of an embodiment of the disclosure.

(6) FIG. 5 is a front isometric view of an embodiment of the disclosure.

(7) FIG. 6 is a front isometric view of an embodiment of the disclosure.

(8) FIG. 7 is a front isometric view of an embodiment of the disclosure.

(9) FIG. 8 is a side in-use view of an embodiment of the disclosure.

(10) FIG. 9 is a broken side view of an embodiment of the disclosure.

(11) FIG. 10 is a broken front view of an embodiment of the disclosure.

(12) FIG. 11 is a front isometric view of a second embodiment of the disclosure.

(13) FIG. 12 is a front view of an embodiment of the disclosure as shown in FIG. 11.

(14) FIG. 13 is a side view of an embodiment of the disclosure as shown in FIG. 11.

(15) FIG. 14 is a front isometric in-use view of an embodiment of the disclosure as shown in FIG. 11.

(16) FIG. 15 is a rear in-use view of an embodiment of the disclosure as shown in FIG. 11.

(17) FIG. 16 is a bottom and front isometric view of a third embodiment of the disclosure.

(18) FIG. 17 is a front view of the third embodiment of the disclosure.

(19) FIG. 18 is a side view of the third embodiment of the disclosure.

### DETAILED DESCRIPTION OF THE INVENTION

(20) With reference now to the drawings, and in particular to FIGS. 1 through 18 thereof, a new animal waste collector embodying the principles and concepts of an embodiment of the disclosure and generally designated by the reference numeral 10 will be described.

(21) As best illustrated in FIGS. 1 through 18, the animal waste collecting assembly 10 and method generally comprises a pole 12 that defines a handle. The pole 12 is elongated and has a first end 14 and a second end 15 with a length typically between 3.0 feet and 6.0 feet. For storage and transportation purposes, the pole 12 may have a break 16 therein to form a first portion 18 and a second portion 20 of the pole 12. The first 18 and second 20 portions are removably attached to each other. This may be achieved, for example, with a threaded male mating member 22 on the first

portion **18** being threadably engaged with a female mating member **24** extending into the second portion **20**. Alternatively, the pole **12** may be telescopic such that it has an adjustable length in a conventional manner.

(22) A frame **26** is configured to releasably engage and support a plastic bag **28**. The plastic bag **28** may be of the type typically used for grocery shopping and include a pair of handles **30**. The frame **26** includes a closed loop **32** that is attached to and extends away from the second end **15** of the pole **12**. The closed loop **32** has an end member **34** positioned opposite of the pole **12**. The end member **34** is linear for a distance greater than 4.0 inches and is orientated perpendicular to a longitudinal axis **36** of the pole **12**. The closed loop **32** may be formed by portions of the pole **12** or a coupler engaging the pole **12** and frame **26**.

(23) A plurality of tines **38** is attached to and extends away from the end member **34**. The tines **38** are co-planar with respect to each other. The tines **38** lay a plane that is angled back toward the pole **12**. The plane of the tines forms an angle **40** with respect to the longitudinal axis **36** between  $62^{\circ}$  and  $68^{\circ}$  and which more particularly be from  $65^{\circ}$  to  $67^{\circ}$ . As can be seen in FIG. **9**, this creates an angle **42** of between  $22^{\circ}$  and  $28^{\circ}$  with a ground surface **44**, wherein angle **42** is most preferably from  $23^{\circ}$  to  $25^{\circ}$ . These angles, **40** and **42**, facilitate the movement of the tines **38** across a ground surface as shown in FIG. **8** without the tines **38** digging into the ground surface **44**. The tines **38** may each extend away from the end member **34** between 1.0 inches and 4.0 inches.

(24) A receiver **46** is provided and includes a bottom surface **48** having a plurality of wells **50** extending therein. The wells **50** may or may not extend completely through the receiver **46**. The wells **50** are aligned with each other and are positioned such that each of the tines **38** is simultaneously extendable into one of the wells **50**. The receiver **46** is configured to be urged against the plastic bag **28** when such is positioned between the tines **38** and the receiver **46**. The receiver **46** presses against the plastic bag **28** such that the tines **38** impale the plastic bag **28** as shown in FIG. **5**. The bottom surface **48** is abutable against the end member **34** when the tines **38** are fully received by the receiver. The receiver **46** allows for safe mounting of the bag **28** onto the tines **38** while also ensures that a user of the assembly **10** need not touch the tines **38**. A securing member **52** is mounted on the receiver **46**. The securing member **52** releasably engages the pole **12** to secure the receiver **46** to the pole **12** in a stored condition. The securing member **52** may include a bracket, magnets, snaps, hook and loop fasteners and the like.

(25) A clip **54**, which defines an engagement member, is mounted on the pole **12** adjacent to the second end **15**. The clip **54** is configured to releasably secure an edge of the plastic bag **28** to the pole **12**. The clip **54** may comprise any conventional biased clip member to frictionally engage the plastic bag **28**. The clip **54** as shown may be preferred as it includes a fixed plate and a movable plate and therefore can be actuated with a person's thumb.

(26) A pair of spikes **56** is attached to the frame **26**. The spikes **56** are positioned on opposite sides of the longitudinal axis **36** with respect to each other. The spikes **56** extend in a direction away from the end member **34** and toward the pole **12**. The spikes **56** are configured to pierce and engage the plastic bag **28**. The spikes **56** typically have a length between 0.5 inches and 2.0 inches and have pointed free ends. The frame **26**, tines **38** and spikes **56** may be comprised of any sufficiently rigid material including plastics and composites, though metals may be preferred for their strength and resistance to breaking.

(27) The frame **26** includes a pair of side arms **58** that is attached to and extends away from the pole **12**. Each of the side arms **58** has one of the spikes **56** attached thereto. The side arms **58** each have a distal end **60** and a proximal end **62** relative to the pole **12**. The distal ends **60** of each of the side arms **58** are attached to the end member **34**. As can be seen in the Figures, the side arms **58** may be extended beyond the end member **34** to form outer ones of the tines **38**, though this is not necessary. The side arms **58** are positioned on opposite sides of the pole **12** longitudinal axis **36** relative to each other. Each of the side arms **58** has a bend **64** positioned between the distal end **60** and the proximal end **62** to define a first section **66** including the proximal end **62** and a second

section **68** including the distal end **60**. The first section **66** extends outwardly away from the pole **12** such an angle **70** formed between the first section **66** and the longitudinal axis **36** is equal to or less than  $90^\circ$  and greater than  $30^\circ$  and is typically between  $60^\circ$  and  $35^\circ$ . The second section **68** forms an inner angle **72** with the first section **66** that is equal to or greater than  $90^\circ$  and less than  $150^\circ$ , and which is typically between  $120^\circ$  and  $155^\circ$ . As can be seen in the figures, the second sections **68** may be orientated parallel to each other. However, it should be understood that each of the side arms **58** may be arcuately shaped from the pole **12** to the end member **34**. Each of the spikes **56** is positioned adjacent to a corresponding bend **64** in the side arms **58**. The spike **56** forms an acute angle **74** with a respective one of the first sections **66**. The distal ends **60** of the side arms **58** are rounded forwardly away from the longitudinal axis **36** as shown in FIGS. **2** and **9** to inhibit the plastic bag **28** from catching on the side arms **58**.

(28) In an embodiment found in FIGS. **11-15** demonstrates that the engagement member may comprise other structures aside from the clip **54**. Here, the engagement member comprises a notch **80** formed by a static structure. The term static structure is meant to mean that there is a lack of hinge point or other moving parts as is found in a clip. In this particular embodiment, the notch **80** is located at a convergence of a pair of lateral members **82**. The lateral members each include a terminal leg **84** whereby the terminal legs **84** are abutting and orientated parallel to each other to form the notch **80**. The terminal legs **84** may be attached to each other at a shared terminal end **86**. As can be seen in the FIG. **11**, the lateral members **82** may be comprised of a unitary piece of material, such as a metal or plastic material, wherein the lateral members **82** are bent to form the terminal legs **84** and the terminal end **86** is formed by a  $180^\circ$  bend. The notch **80** extends from an entrance **88** of the notch **80** to the terminal end **86**. The lateral members **82** are positioned adjacent to second end **15** of the pole **12** and to opposite side arms **54** of the frame **26** to urge together opposite edges of the entrance **88** to create friction at the entrance **88** to the notch **80**. As can be seen in FIG. **11**, the lateral members **82** may be bent in such a manner to retain tension on the notch **80** and the entrance **88** of the notch may include rounded corners to assist with guiding the plastic bag **28** between the terminal legs **84** as is shown in FIG. **15**.

(29) The embodiment of FIGS. **16-18** includes an engagement member utilizing one or more stakes **90**, attached to the frame **26** adjacent to the second end **15** of the pole **12**, and angled forward of the frame **26** to puncture the plastic bag **28** and retain it in place on the frame **26**. As can be seen best in FIG. **18** the stakes **90** may be angled backward, or toward the pole **12**, to help retain the plastic bag **28** on the frame **26**.

(30) In use, the plastic bag **28** is positioned adjacent to the frame **26** such that plastic bag **28** is positioned between the tines **38** and the receiver **46**. The receiver **46** is aligned with the tines **38** and is urged against the plastic bag **28** such that the tines **38** impale the plastic bag **28**. The bag **28** is then pushed through the closed loop **32** formed by the frame **26**. An opposite edge of the bag **28** is secured with the clip **54**, or engagement member. The plastic bag **28** is orientated such that its handles **30** extend laterally away from the frame **26**. The spikes **56** are then extended through the plastic bag **28** and the handles **30** may be wrapped around an adjacent spike **56**. The tines **38** are then moved across the ground surface **44** to engage and capture animal waste **78** positioned on the ground surface **44** such that the animal waste **78** moves into the plastic bag **28**. The user then removes the plastic bag **28** from the spikes **56** and then the tines **38** by gripping the handle **38** or edges of the plastic bag **28** and pulling the plastic bag **28** away from the frame **26**. This action also removes any animal waste from the tines **38** as the plastic bag **28** slides along the tines **38**. As the handles **30** are gripped, the clip **54** is opened to remove the plastic bag **28** completely from the assembly **10** such that it may be discarded.

(31) With respect to the above description then, it is to be realized that the optimum dimensional relationships for the parts of an embodiment enabled by the disclosure, to include variations in size, materials, shape, form, function and manner of operation, assembly and use, are deemed readily apparent and obvious to one skilled in the art, and all equivalent relationships to those illustrated in

the drawings and described in the specification are intended to be encompassed by an embodiment of the disclosure.

(32) Therefore, the foregoing is considered as illustrative only of the principles of the disclosure. Further, since numerous modifications and changes will readily occur to those skilled in the art, it is not desired to limit the disclosure to the exact construction and operation shown and described, and accordingly, all suitable modifications and equivalents may be resorted to, falling within the scope of the disclosure. In this patent document, the word “comprising” is used in its non-limiting sense to mean that items following the word are included, but items not specifically mentioned are not excluded. A reference to an element by the indefinite article “a” does not exclude the possibility that more than one of the element is present, unless the context clearly requires that there be only one of the elements.

## Claims

1. An animal waste collection assembly configured to collect animal waste in a plastic bag, the assembly comprising: a pole defining a handle, the pole being elongated and having a first end and a second end; a frame configured to releasably engage and support a plastic bag, the frame including a closed loop being attached to and extending away from the second end of the pole, the closed loop having an end member positioned opposite of the pole, the end member being linear for a distance greater than 4.0 inches and being orientated perpendicular to a longitudinal axis of the pole; a plurality of tines being attached to and extending away from the end member, the tines being co-planar with respect to each other, the tines lying a plane; an engagement member being mounted adjacent to the second end of the pole, the engagement member being configured to releasably secure the plastic bag adjacent to the pole to retain the plastic bag in an open configuration; and a receiver including a bottom surface having a plurality of wells extending therein, the wells being aligned with each other and being positioned such that each of the tines is simultaneously extendable into one of the wells, wherein the receiver is configured to be urged against the plastic bag positioned between the tines and the receiver such that the tines impale the plastic bag.

2. The animal waste collection assembly according to claim 1, wherein the plane of the tines is angled back toward the pole.

3. The animal waste collection assembly according to claim 2, wherein the plane forms an angle with respect to the longitudinal axis between 62° and 68°.

4. The animal waste collection assembly according to claim 1, wherein the bottom surface is abutable against the end member when the tines are fully received by the receiver.

5. The animal waste collection assembly according to claim 1, further including a securing member being mounted on the receiver, the securing member releasably engaging the pole to secure the receiver to the pole.

6. The animal waste collection assembly according to claim 1, further including a pair of spikes being attached to the frame, the spikes being positioned on opposite sides of the longitudinal axis with respect to each other, the spikes extending toward the pole, the spikes being configured to pierce and engage the plastic bag.

7. The animal waste collection assembly according to claim 6, wherein the spikes have a length between 0.5 inches and 2.0 inches.

8. The animal waste collection assembly according to claim 6, wherein the frame includes: a pair of side arms being attached to and extending away from the pole, each of the side arms having one of the spikes attached thereto, the side arms each having a distal end and a proximal end relative to the pole, the distal ends of each of the side arms being attached to the end member, the side arms being positioned on opposite sides of the longitudinal axis relative to each other, each of the side arms having: a bend positioned between the distal end and the proximal end to define a first section

including the proximal end and a second section including the distal end, the first section extending outwardly away from the pole such an angle formed between the first section and the longitudinal axis being equal to or less than  $90^{\circ}$  and greater than  $30^{\circ}$ ; and the second section forming an inner angle with the first section being equal to or greater than  $90^{\circ}$  and less than  $150^{\circ}$ .

9. The animal waste collection assembly according to claim 8, wherein each of the spikes being positioned adjacent to a corresponding bend in the side arms, each said spike forming an acute angle with a respective one of the first sections.

10. The animal waste collection assembly according to claim 9, wherein the plane of the tines is angled back toward the pole.

11. The animal waste collection assembly according to claim 10, wherein the plane forms an angle with respect to the longitudinal axis between  $62^{\circ}$  and  $68^{\circ}$ .

---