

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12395036
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Yamasaki; Yuta et al.

Motor and blower including the same

Abstract

A motor includes a rotor, a stator, a stator accommodating portion, a seal, and a lid. The stator opposes the rotor with a gap interposed radially inward. The stator accommodating portion accommodates the stator, includes an opening on one end surface in an axial direction, and has a tubular shape. The seal is filled in the stator accommodating portion. The lid covers the opening. The stator accommodating portion includes a cutout and a pullout piece. The cutout is recessed from one end in the axial direction to the other side in the axial direction, and a lead wire connected to the stator is pulled out. The pullout piece protrudes radially outward from a bottom of the cutout, and the lead wire is positioned between the lid and the pullout piece via an elastic portion on an end surface on one side in the axial direction of the pullout piece.

Inventors: Yamasaki; Yuta (Kyoto, JP), Aoi; Hideaki (Kyoto, JP), Yasumoto; Nobuaki (Kyoto, JP)

Applicant: Nidec Corporation (Kyoto, JP)

Family ID: 1000008766359

Assignee: NIDEC CORPORATION (Kyoto, JP)

Appl. No.: 18/128265

Filed: March 30, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230318392 A1	Oct. 05, 2023

Foreign Application Priority Data

JP	2022-060678	Mar. 31, 2022
JP	2022-060679	Mar. 31, 2022
JP	2022-060680	Mar. 31, 2022
JP	2022-060681	Mar. 31, 2022

Publication Classification

Int. Cl.: **H02K5/10** (20060101); **F04D25/06** (20060101); **H02K3/50** (20060101); **H02K11/33** (20160101); **H02K21/22** (20060101)

U.S. Cl.:

CPC **H02K5/10** (20130101); **F04D25/06** (20130101); **F04D25/0693** (20130101); **H02K3/50** (20130101); **H02K11/33** (20160101); **H02K21/22** (20130101); H02K2203/06 (20130101); H02K2211/03 (20130101)

Field of Classification Search

CPC: H02K (5/10); H02K (3/50); H02K (11/33); H02K (21/22); H02K (2203/06); H02K (2211/03); F04D (25/06); F04D (25/0613); F04D (25/0646); F04D (25/0693); F04D (29/083); F04D (29/522)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6291914	12/2000	Mukaiyama	310/68B	B62D 6/10
11165305	12/2020	Lee	N/A	H02K 5/10
11715987	12/2022	Ishikawa	310/88	H02K 9/19
2012/0269665	12/2011	Takeshita	417/420	F04D 19/002
2016/0380502	12/2015	Koiwai	310/71	H02K 3/44
2018/0252223	12/2017	Yamasaki	N/A	H02K 5/16
2018/0337567	12/2017	Yamasaki	N/A	H02K 5/10
2019/0013113	12/2018	Nakashima	N/A	H01B 7/00
2019/0305651	12/2018	Mao	N/A	H02K 21/14
2019/0334405	12/2018	Yamasaki	N/A	H02K 15/12
2021/0095679	12/2020	Uchino	N/A	F04D 25/08

Primary Examiner: Plakkoottam; Dominick L

Attorney, Agent or Firm: Keating & Bennett, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) The present application claims priority under 35 U.S.C. § 119 to Japanese Patent Application No. 2022-060678, Japanese Patent Application No. 2022-060679, Japanese Patent Application No. 2022-060680, and Japanese Patent Application No. 2022-060681 filed on Mar. 31, 2022, the entire contents of each application are hereby incorporated herein by reference.

1. FIELD OF THE INVENTION

(2) The present disclosure relates to a motor and a blower including a motor.

2. BACKGROUND

(3) A conventional motor includes a rotor, a stator, a stator accommodating portion (stator housing portion), and a sealing member (insulator). The rotor rotates about a rotation axis. The stator opposes the rotor with a gap interposed radially inward. The stator accommodating portion accommodates the stator. The sealing member is filled in the stator accommodating portion. A lead wire electrically connected to the stator is pulled out to an outside of the stator accommodating portion.

(4) A conventional motor includes a rotor, a stator, a circuit board, a stator accommodating portion (stator housing portion), and a sealing member (insulator). The rotor rotates about a rotation axis. The stator opposes the rotor with a gap interposed radially inward. The circuit board is connected to the stator and disposed on one side in an axial direction of the stator. The stator accommodating portion accommodates the stator and the circuit board, and has an opening on one end surface in the axial direction. The liquid sealing member is filled in the stator accommodating portion and is cured after a predetermined time elapses.

(5) A conventional motor includes a rotor, a stator, a circuit board, a stator accommodating portion (stator housing portion), and a sealing member (insulator). The rotor rotates about a rotation axis. The stator opposes the rotor with a gap interposed radially inward. The circuit board is connected to the stator and disposed on one side in an axial direction of the stator. The stator accommodating portion accommodates the stator and the circuit board, and has an opening on one end surface in the axial direction. The liquid sealing member is filled in the stator accommodating portion and is cured after a predetermined time elapses.

(6) A conventional blower includes a rotor, a stator, a circuit board, a stator accommodating portion (stator housing portion), and a sealing member (insulator). The rotor rotates about a rotation axis. The stator opposes the rotor with a gap interposed radially inward. The circuit board is connected to the stator and disposed on one side in an axial direction of the stator. The stator accommodating portion accommodates the stator and the circuit board. The sealing member is filled in the stator accommodating portion.

(7) However, in the conventional motor, there is a possibility that the uncured sealing member flows out of the stator accommodating portion along the lead wire.

(8) In the conventional motor, there is a possibility that the sealing member bulges and is cured along the radially inner surface of the stator accommodating portion, and a fillet is formed at the radially outer end part of the sealing member. When the fillet is formed, there is a possibility that a cover covering the opening of the stator accommodating portion and the fillet come into contact with each other, and the motor becomes large in the axial direction.

(9) In the conventional motor, there is a possibility that the sealing member bulges and is cured along the radially inner surface of the stator accommodating portion, and a fillet is formed at the radially outer end part of the sealing member. When the fillet is formed, there is a possibility that a cover covering the opening of the stator accommodating portion and the fillet come into contact with each other, and the motor becomes large in the axial direction.

(10) In the conventional blower, the sealing member hardly flows into the entire inside of the stator accommodating portion, and there is a possibility that assembly workability of the blower is deteriorated.

SUMMARY

(11) A motor according to a first preferred embodiment of the present disclosure includes a rotor, a stator, a stator accommodating portion, a seal, and a lid. The rotor is rotatable about a rotation axis. The stator opposes the rotor with a gap interposed radially inward. The stator accommodating portion accommodates the stator, includes an opening on one end surface in an axial direction, and has a tubular shape. The seal is filled in the stator accommodating portion. The lid covers the opening. The stator accommodating portion includes a cutout and a pullout piece. The cutout is recessed from one end in the axial direction to another side in the axial direction, and a lead wire connected to the stator is pulled out. The pullout piece protrudes radially outward from a bottom of the cutout, and the lead wire is positioned between the lid and the pullout piece via an elastic portion located on an end surface on one side in the axial direction of the pullout piece.

(12) A motor according to a second preferred embodiment of the present disclosure includes a rotor, a stator, a circuit board, a stator accommodating portion, a seal, and a lid. The rotor is rotatable about a rotation axis. The stator opposes the rotor with a gap interposed radially inward. The circuit board is connected to the stator and located on one side in an axial direction of the stator. The stator accommodating portion accommodates the stator and the circuit board, includes an opening on one end surface in the axial direction, and has a tubular shape. The seal is filled in the stator accommodating portion, and the lid covers the opening. One end in the axial direction of the stator accommodating portion is positioned on another side in the axial direction relative to another end in the axial direction of the lid on a radially inside relative to the stator accommodating portion.

(13) A motor according to a third preferred embodiment of the present disclosure includes a rotor, a stator, a circuit board, a stator accommodating portion, a seal, and a lid. The rotor is rotatable about a rotation axis. The stator opposes the rotor with a gap interposed radially inward. The circuit board is connected to the stator and located on one side in an axial direction of the stator. The stator accommodating portion accommodates the stator and the circuit board, includes an opening on one end surface in the axial direction, and has a tubular shape. The seal is filled in the stator accommodating portion, and the lid covers the opening. The stator includes a bearing holding portion. The bearing holding portion internally holds a bearing that rotatably supports a shaft extending along a rotation axis, and has a tubular shape. The circuit board includes a board through hole located on the rotation axis and penetrating in the axial direction. One end portion in the axial direction of the bearing holding portion is inserted into the board through hole and extends to one side in the axial direction relative to the circuit board. An oil repellent layer is provided on a radially outer surface of the bearing holding portion on one side in the axial direction relative to one end in the axial direction of the circuit board.

(14) A blower according to a fourth preferred embodiment of the present disclosure includes a rotor, a stator, a circuit board, a stator accommodating portion, a seal, a lid, an impeller, and a housing body. The rotor is rotatable about a rotation axis. The stator opposes the rotor with a gap interposed radially inward. The circuit board is connected to the stator and located on one side in an axial direction of the stator. The stator accommodating portion accommodates the stator and the circuit board, includes an opening on one end surface in the axial direction, and has a tubular shape. The seal is filled in the stator accommodating portion. The lid covers the opening. The impeller is fixed to the rotor and generates an airflow in the axial direction. The housing body has a tubular shape extending along the rotation axis, includes two end surfaces in the axial direction opened, and accommodates the motor and the impeller. The stator accommodating portion includes an accommodating recess. The accommodating recess is located at one end portion in the axial direction of the stator accommodating portion and is recessed radially outward from the radially inner surface. In the radial direction, a gap is between a radially outer edge of the circuit board and the accommodating recess.

(15) The above and other elements, features, steps, characteristics and advantages of the present

disclosure will become more apparent from the following detailed description of the example embodiments with reference to the attached drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a perspective view of a blower according to a first example embodiment of the present disclosure.
- (2) FIG. 2 is an exploded perspective view of the blower according to the first example embodiment of the present disclosure.
- (3) FIG. 3 is a longitudinal cross-sectional perspective view of the blower according to the first example embodiment of the present disclosure.
- (4) FIG. 4 is a longitudinal cross-sectional perspective view showing a portion of the blower according to the first example embodiment of the present disclosure in an enlarged manner.
- (5) FIG. 5 is a perspective view of a motor according to the first example embodiment of the present disclosure.
- (6) FIG. 6 is a top view of the motor according to the first example embodiment of the present disclosure.
- (7) FIG. 7 is a longitudinal cross-sectional perspective view of a stator accommodating portion of the motor according to the first example embodiment of the present disclosure.
- (8) FIG. 8 is a longitudinal cross-sectional view schematically showing a portion of the motor according to the first example embodiment of the present disclosure.
- (9) FIG. 9 is a longitudinal cross-sectional view schematically showing a portion of a motor according to a second example embodiment of the present disclosure.
- (10) FIG. 10 is a longitudinal cross-sectional view schematically showing a portion of a motor according to a third example embodiment of the present disclosure.

DETAILED DESCRIPTION

(11) Hereinafter, example embodiments of a first aspect of the present disclosure will be described in detail with reference to the drawings. In the present description, a direction in which a rotation axis J of a blower 1 extends is simply referred to as “axial” or “axial direction”, a direction orthogonal to the rotation axis J about the rotation axis J of the blower 1 is simply referred to as “radial” or “radial direction”, and a direction along an arc about the rotation axis J of the blower 1 is simply referred to as “circumferential” or “circumferential direction”. A cross section parallel to the axial direction is referred to as “longitudinal cross section”. The term “parallel” does not represent parallel in a strict sense, but includes substantially parallel.

(12) It is assumed that an axial direction is a vertical direction for the sake of convenience in description, and the shape and positional relation of each part or portion will be described on the assumption that the vertical direction in FIG. 1 is a vertical direction of the blower 1. For example, one side in the axial direction is defined as an upper side in the axial direction or an upper side. The other side in the axial direction is defined as a lower side in the axial direction or a lower side. One end in the axial direction is defined as an upper end, and the other end in the axial direction is defined as a lower end. One end surface in the axial direction is defined as an upper end surface, and the other end surface in the axial direction is defined as a lower end surface. The “upper side” of the blower 1 is an “intake side” and the “lower side” of the blower 1 is an “exhaust side”. It is to be noted that this definition of the vertical direction does not restrict the orientation and positional relation of the blower 1 when in use.

(13) FIGS. 1 and 2 are a perspective view and an exploded perspective view, respectively, of an example of the blower 1 according to the first example embodiment of the present disclosure. The blower 1 includes a motor 20, an impeller 30, and a housing 40.

(14) The impeller **30** is fixed to the motor **20** and rotates about the rotation axis J to generate an airflow on the lower side Z1 in the axial direction (the other side in the axial direction) along the rotation axis J.

(15) The housing **40** is formed in a tubular shape extending along the rotation axis J, and has a blowing flow path **41** in which both end surfaces in the axial direction are opened and an airflow internally circulates. The motor **20** and the impeller **30** are accommodated inside the housing **40**. The housing **40** has an exhaust port **42** on a lower end surface (the other end surface in the axial direction) (see FIG. 3) and an intake port **43** on an upper end side (one end surface in the axial direction).

(16) The housing **40** is configured by axially coupling an upper housing part **40a** and a lower housing part **40b**. The upper housing part **40a** and the lower housing part **40b** are resin molded articles. In the present example embodiment, the housing **40** can be divided into the upper housing part **40a** and the lower housing part **40b**, but the upper housing part **40a** and the lower housing part **40b** may be integrally formed. The upper housing part **40a** includes an upper body portion **401a**, a fixing part **402a**, and coupling parts **403a** and **403b**. The upper body portion **401a** extends in the axial direction and is formed in a tubular shape.

(17) The fixing part **402a** and the coupling parts **403a** and **403b** constitute a lid portion **27** that covers an opening **25a** (see FIG. 4) of a stator accommodating portion **25** described below. The lid portion **27** is a part of the housing **40** and also a part of the motor **20**. The fixing part **402a** is arranged on an upper side Z2 in the axial direction (one side in the axial direction) of the stator accommodating portion **25** described below, and has a disk shape expanding in the radial direction about the rotation axis J. A stator **23** described below of the motor **20** is fixed to the fixing part **402a**. That is, the fixing part **402a** is formed in a plate shape to which the stator **23** is fixed.

(18) The coupling parts **403a** and **403b** extend radially outward from the fixing part **402a** and couple the fixing part **402a** and a housing body portion **40c**. A plurality of the coupling parts **403a** are arranged in the circumferential direction and axially opposes an accommodating recess **252a** described below. The coupling part **403b** is disposed at one position in the circumferential direction and axially opposes a pullout piece **2522** described below. The air circulating through the blowing flow path **41** passes through between the adjacent coupling parts **403a** and **403b**.

(19) The coupling part **403a** is formed to be inclined to one side in the circumferential direction from the radially inner end toward the radially outside. Due to this, the airflow flowing into the housing **40** from the intake port **43** smoothly circulates along the coupling part **403a**. Therefore, the blowing efficiency of the blower **1** can be further improved. The coupling part **403a** may be formed to be inclined to the other side in the circumferential direction from the radially inner end toward the radially outside. The coupling part **403a** may be formed to extend linearly in the radial direction. The coupling part **403b** is formed to extend linearly in the radial direction.

(20) The coupling part **403a** has a coupling recess **405a** (see FIG. 4). The coupling recess **405a** is disposed to oppose the stator accommodating portion **25** in the axial direction, and is recessed to the one side in the axial direction from the lower end surface (end surface on the other side in the axial direction) of the coupling part **403a**. This can prevent the stator accommodating portion **25** from coming into contact with the coupling part **403** when swung in the axial direction.

(21) The lower housing part **40b** has a lower body portion **401b** that extends in the axial direction and is formed in a tubular shape. The lower body portion **401b** and the upper body portion **401a** are coupled in the axial direction to constitute the housing body portion **40c**. That is, the blower **1** includes the housing body portion **40c**, and the housing body portion **40c** is formed in a tubular shape extending along the rotation axis J, and internally has the blowing flow path **41** with both end surfaces in the axial direction opened. The motor **20** and the impeller **30** are accommodated inside the housing body portion **40c**.

(22) The impeller **30** includes an impeller cup **31** and a plurality of blades **32**. The impeller cup **31** is fixed to a radially outside of a rotor **24** described below of the motor **20**. The plurality of blades

32 are arrayed in the circumferential direction on a radially outer surface of the impeller cup **31**.

(23) FIG. **3** is a longitudinal cross-sectional perspective view of the blower **1**, and FIG. **4** is a longitudinal cross-sectional perspective view showing a part of the blower **1** in an enlarged manner. The motor **20** includes a shaft **21**, a bearing **22**, the stator **23**, the rotor **24**, the stator accommodating portion **25**, a seal **26**, the above-described lid portion **27**, and a circuit board **28**.

(24) The shaft **21** extends along the rotation axis J. The shaft **21** is a columnar member that is made of metal such as stainless steel and extends in the axial direction.

(25) The bearings **22** are arranged in a pair at least spaced apart in the axial direction. The bearing **22** is configured by, for example, a ball bearing, but may be configured by a sleeve bearing or the like. The pair of bearings **22** support the shaft **21** so as to be rotatable about the rotation axis J with respect to the stator **23**.

(26) The stator **23** opposes the rotor **24** with a gap interposed radially inward. The stator **23** includes a bearing holding portion **231**, a stator core **232**, an insulator **233**, and a coil **234**. The bearing holding portion **231** is formed in a cylindrical shape and internally holds the bearing **22**.

(27) An upper end portion (one end portion in the axial direction) of the bearing holding portion **231** is fitted via a connector **45** into a fitting hole **404a** of the fixing part **402a**. Due to this, the bearing holding portion **231** is fixed to the fixing part **402a**, and the stator **23** and the housing **40** are fixed. The fitting hole **404a** is formed to penetrate the fixing part **402a** in the axial direction. The connector **45** is formed in an annular shape and is disposed on the inner peripheral surface of the fitting hole **404a**. The bearing holding portion **231** is disposed on the inner peripheral surface of the connector **45**. A lower end portion (the other end portion in the axial direction) of the bearing holding portion **231** is fixed to the stator accommodating portion **25** described below. The upper end portion (one end portion in the axial direction) of the bearing holding portion **231** may be directly fitted into the fitting hole **404a** without the connector **45**.

(28) The stator core **232** is formed by vertically stacking electromagnetic steel plates such as silicon steel plates. The insulator **233** is made of an insulating resin. The stator core **232** includes an annular core back (not shown) and a plurality of teeth (not shown) protruding radially outward from the core back and arranged in the circumferential direction. The insulator **233** is provided on a part of the outer surface in the axial direction of the teeth and a part of the outer surface in the circumferential direction of the teeth. The coil **234** is formed of a conductive wire wound around the stator core **232** via the insulator **233**.

(29) The rotor **24** rotates about the rotation axis J with respect to the stator **23**. The rotor **24** includes a rotor yoke **241** and a magnet **242**.

(30) The rotor yoke **241** is a member in a substantially cylindrical shape made of a magnetic material and having a lid on portion (the other end portion in the axial direction) of the shaft **21**. The magnet **242** has a cylindrical shape and is fixed to an inner peripheral surface of the rotor yoke **241**. Due to this, the magnet **242** is disposed on the radially outside of the stator **23**.

(31) The circuit board **28** is in contact with the upper end (one end in the axial direction) of the insulator **233** and is disposed between the stator core **232** and the lid portion **27**. The circuit board **28** has a disk shape expanding in the radial direction about the rotation axis J, for example. The circuit board **28** has a board through hole **28a**. The board through hole **28a** is disposed on the rotation axis J and penetrates in the axial direction. The upper end portion (one end portion in the axial direction) of the bearing holding portion **231** is inserted into the board through hole **28a** and extends in the upper side Z2 in the axial direction (one side in the axial direction) relative to the circuit board **28**.

(32) A conductive wire (not shown) constituting the coil **234** is electrically connected to the circuit board **28**. An electronic circuit for supplying a drive current to the coil **234** is mounted on the circuit board **28**. The circuit board **28** is connected to a lead wire **50** (see FIGS. **6** and **7**), and the lead wire **50** is pulled out to the outside of the stator accommodating portion **25** and connected to an external power source. The lead wire **50** is electrically connected to the coil **234**, and the lead

wire **50** and the stator **23** are electrically connected. In the present example embodiment, three lead wires **50** are pulled out to the outside of the stator accommodating portion **25**.

(33) FIGS. **5** and **6** are a perspective view and a top view, respectively, of the motor **20**, and FIG. **7** is a longitudinal cross-sectional perspective view of the stator accommodating portion **25**. In FIGS. **5** and **6**, the rotor **24**, the seal **26**, and the lid portion **27** are not shown, and the elastic portion **29** is indicated by a broken line. In FIG. **5**, the lead wire **50** is not shown, and in FIGS. **6** and **7**, the lead wire **50** is indicated by an alternate long and short dash line.

(34) The stator accommodating portion **25** is formed in a tubular shape and has the opening **25a** on one end surface in the axial direction (end surface on one side in the axial direction). The stator accommodating portion **25** internally accommodates the shaft **21**, the bearing **22**, the stator **23**, and the circuit board **28**. The stator accommodating portion **25** is filled with the seal **26** (see FIG. **4**). Due to this, the shaft **21**, the bearing **22**, the stator **23**, and the circuit board **28** are integrated, and the assembly workability of the motor **20** is improved.

(35) The stator core **232** is press-fitted into the inner peripheral surface of the stator accommodating portion **25**. At this time, the radially outer surfaces of the teeth (not shown) come into contact with the inner peripheral surface of the stator accommodating portion **25**. The outer peripheral surface of the stator accommodating portion **25** opposes the magnet **242** in the radial direction with a gap interposed (see FIG. **3**).

(36) The seal **26** is formed of a curable insulating resin or the like, and for example, an epoxy resin, silicone rubber, a polyurethane resin, or the like is used. The liquid seal **26** is filled inside the stator accommodating portion **25** from the opening **25a** and is cured after a predetermined time elapses. Due to this, the stator **23** and the circuit board **28** are covered with the cured seal **26**, and waterproof property, oil proof property, and the like of the stator **23** and the circuit board **28** are improved.

(37) The stator accommodating portion **25** includes a stator tube portion **251**, a board tube portion **252**, an intermediate tube portion **253**, an accommodating lid portion **254**, and an accommodating inclined portion **255**.

(38) The stator tube portion **251** surrounds the stator **23** from circuit board **28** from radially outside. The intermediate tube portion **253** couples the stator tube portion **251** and the board tube portion **252**.

(39) The accommodating lid portion **254** covers the stator **23** from the lower side **Z1** in the axial direction (the other side in the axial direction) and expands in the radial direction. The accommodating lid portion **254** has an accommodating through hole **254a** and an accommodating holding portion **254b** penetrating in the axial direction. The lower end portion (the other end portion in the axial direction) of the bearing holding portion **231** is fitted into the accommodating through hole **254a** (see FIG. **3**). Due to this, the stator accommodating portion **25** is fixed to the bearing holding portion **231**. The accommodating holding portion **254b** protrudes in the upper side **Z2** in the axial direction (one side in the axial direction) from the peripheral edge of the accommodating through hole **254a**, and is formed in a tubular shape. The accommodating holding portion **254b** holds the lower end portion (the other end portion in the axial direction) of the bearing holding portion **231**.

(40) The board tube portion **252** has the accommodating recess **252a**. The accommodating recess **252a** is arranged in the upper end portion (one end portion in the axial direction) of the stator accommodating portion **25** and is recessed radially outward from the radially inner surface. In the radial direction, a gap **S** is formed between the radially outer edge of the circuit board **28** and the accommodating recess **252a**. In the present example embodiment, the accommodating recess **252a** has a part of the board tube portion **252** formed in a convex shape radially outside, and is provided at three places at equal intervals in the circumferential direction. The number of accommodating recesses **252a** is not limited to three. By providing the accommodating recess **252a**, the seal **26** can smoothly flow into the stator accommodating portion **25** from the gap **S**. This improves the

assembling workability of the blower **1**.

(41) As viewed from the axial direction, at least a part of the accommodating recess **252a** overlaps the coupling part **403a** of the lid portion **27** (see FIG. 4). In the present example embodiment, the circumferential width of the accommodating recess **252a** is equal to or less than the circumferential width of the coupling part **403a**, and the entire accommodating recess **252a** overlaps the coupling part **403a** as viewed from the axial direction. This can reduce the airflow that passes through between the adjacent coupling parts **403a** and flows into the housing **40** from being disturbed in the vicinity of the accommodating recess **252a**. Therefore, the blowing efficiency of the blower **1** can be improved.

(42) The radial protrusion amount of the accommodating recess **252a** is $\frac{1}{2}$ or less of the radial size of the coupling part **403a**. This can further reduce the airflow that passes through between the adjacent coupling parts **403a** and flows into the housing **40** from being disturbed in the vicinity of the accommodating recess **252a**. It is preferable that the radial protrusion amount of the accommodating recess **252a** is smaller as long as a predetermined size of the gap **S** is secured.

(43) The intermediate tube portion **253** is inclined radially inward toward the lower side **Z1** in the axial direction (the other side in the axial direction). This allows the seal **26** to smoothly flow into the stator tube portion **251** from the board tube portion **252** along the intermediate tube portion **253**.

(44) The accommodating inclined portion **255** couples the stator tube portion **251** and the accommodating lid portion **254** and is inclined radially inward toward the lower side **Z1** in the axial direction (the other side in the axial direction). This allows the seal **26** to smoothly flow into the radially inside of the along the accommodating inclined portion **255**. The resin amount of the seal **26** can be reduced, and the manufacturing cost can be reduced.

(45) The stator accommodating portion **25** has an accommodating projection **251a** that protrudes from the radially inner surface and extends in the axial direction (see FIG. 7). In the present example embodiment, the accommodating projection **251a** is disposed on the radially inner surface of the stator tube portion **251**. The accommodating projection **251a** is fitted into a groove (not shown) formed on the radially outer surface of the stator core **232** and extending in the axial direction. This enables easy positioning in the circumferential direction of the stator core **232** in the stator accommodating portion **25**. In a state where the stator core **232** is accommodated in the stator accommodating portion **25**, the accommodating projection **251a** is press-fitted between teeth (not shown) adjacent in the circumferential direction.

(46) The stator accommodating portion **25** further includes a cutout **2521** and the pullout piece **2522**.

(47) The cutout **2521** is recessed from the upper end (one end in the axial direction) of the stator accommodating portion **25** to the lower side **Z1** in the axial direction (the other side in the axial direction), and the lead wire **50** is pulled out radially outward (see FIG. 7).

(48) The pullout piece **2522** protrudes radially outward from the bottom of the cutout **2521**, and is formed in a plate shape. The elastic portion **29** in a rectangular parallelepiped shape is disposed on the upper surface (end surface on one side in the axial direction) of the pullout piece **2522**. The lead wire **50** is disposed on the upper surface (end surface on one side in the axial direction) of the elastic portion **29**. The upper end (one end in the axial direction) of the elastic portion **29** is disposed on the upper side **Z2** in the axial direction (one side in the axial direction) relative to the upper end (one end in the axial direction) of the board tube portion **252**.

(49) Due to this, even when flowing out to the outside of the cutout **2521**, the seal **26** before being cured is dammed by the elastic portion **29**. Therefore, the seal **26** before being cured can be prevented from flowing out of the stator accommodating portion **25** via the cutout **2521**. At this time, the upper end (one end in the axial direction) of the elastic portion **29** is disposed on the upper side **Z2** in the axial direction (one side in the axial direction) relative to the upper end (one end in the axial direction) of the cured seal **26**.

(50) The elastic portion **29** is fixed to the pullout piece **2522** via an adhesive layer **29a** (see FIG. 7).

This allows the elastic portion **29** to be easily fixed to the pullout piece **2522**, and improves the assembling workability of the motor **20**. The elastic portion **29** is made of, for example, a rubber portion.

(51) By providing the pullout piece **2522**, the lead wire **50** can be pulled out radially outward while being supported by the pullout piece **2522** without being largely bent in the axial direction.

Therefore, damage to the lead wire **50** can be prevented.

(52) The pullout piece **2522** includes a pullout inclined portion **2522a**, a pullout projection **2522b**, and a pair of pullout wall portions **2522c**. The pullout inclined portion **2522a** is inclined in the upper side **Z2** in the axial direction (one side in the axial direction) toward radially outward from the bottom of the cutout **2521**. By providing the pullout inclined portion **2522a**, the seal **26** before being cured can be further prevented from flowing out to the outside of the stator accommodating portion **25** via the cutout **2521**.

(53) The pullout projection **2522b** is disposed adjacent to the radially outside of the cutout **2521** and protrudes from the upper surface (end surface on one side in the axial direction) of the the elastic portion **29** can be easily positioned.

(54) The pullout wall portion **2522c** protrudes in the upper side **Z2** in the axial direction (one side in the axial direction) from both end portions in the radial direction of the pullout piece **2522** and extends in the radial direction. The radially inner end of the pullout wall portion **2522c** is coupled to the outer peripheral surface of the board tube portion **252**. The upper end (one end in the axial direction) of the pullout wall portion **2522c** is disposed in the upper side **Z2** in the axial direction (one side in the axial direction) relative to the upper end (one end in the axial direction) of the board tube portion **252**. Due to this, the seal **26** before being cured can be further prevented from flowing out to the outside of the stator accommodating portion **25** via the cutout **2521**.

(55) The pullout piece **2522** is arranged to oppose the coupling part **403b** (lid portion **27**) in the axial direction. At this time, the lead wire **50** is sandwiched between the coupling part **403b** (lid portion **27**) and the pullout piece **2522** via the elastic portion **29**. At this time, the elastic portion **29** deforms along the outer peripheral surface of the lead wire **50**, and a minute gap is hardly generated between the lead wire **50** and the elastic portion **29**. This can prevent the seal **26** before being cured from passing through between the lead wire **50** and the elastic portion **29** due to a capillary phenomenon along the lead wire **50**. Therefore, the seal **26** can be prevented from flowing out to the outside of the stator accommodating portion **25**. This can provide the motor **20** that can prevent the seal **26** from flowing out.

(56) FIG. **8** is a longitudinal cross-sectional view schematically showing a part of the motor **20**. The upper end (one end in the axial direction) of the stator accommodating portion **25** is positioned in the lower side **Z1** in the axial direction (the other side in the axial direction) relative to the lower end (the other end in the axial direction) of the lid portion **27** on the radially inside relative to the upper end (one end in the axial direction) of the stator accommodating portion **25**.

(57) There is a possibility that the seal **26** bulges and is cured in the upper side **Z2** in the axial direction (one side in the axial direction) along the radially inner surface of the stator accommodating portion **25**, and a fillet is formed at the radially outer end portion of the seal **26**. The fillet does not bulge in the upper side **Z2** of the axial direction (one side in the axial direction) beyond the upper end (one end in the axial direction) of the stator accommodating portion **25**. Due to this, even when a fillet is formed along the radially inner surface of the stator accommodating portion **25**, the upper end (one end in the axial direction) of the fillet is positioned in the lower side **Z1** in the axial direction (the other side in the axial direction) relative to the lower end (the other end in the axial direction) of the lid portion **27**. Therefore, the lid portion **27** covering the opening **25a** and the seal **26** can be prevented from coming into contact with each other. This can downsize the motor **20** in the axial direction.

(58) In the present example embodiment, the seal **26** is filled up to the upper end (one end in the axial direction) of the stator accommodating portion **25**, and the upper end (one end in the axial

direction) of the cured seal **26** is disposed at the same height in the axial direction as the upper side **Z2** in the axial direction (one side in the axial direction) relative to the upper end (one end in the axial direction) of the stator accommodating portion **25** or the one end in the axial direction of the stator accommodating portion **25**. At this time, at the radially outer end portion of the seal **26**, a fillet is not formed along the radially inner surface of the stator accommodating portion **25**. Therefore, it is possible to reduce variation, for each product, in the height of the upper end (end surface on one side in the axial direction) of the seal **26**. This allows the lid portion **27** to be disposed close to the upper end (one end in the axial direction) of the stator accommodating portion **25** while preventing the lid portion **27** and the seal **26** from coming into contact with each other. Therefore, it is possible to further downsize the motor **20** in the axial direction.

(59) The upper end surface (end surface on one side in the axial direction) of the seal **26** is formed orthogonal to the axial direction. This allows the lid portion **27** to be disposed closer to the upper end (one end in the axial direction) of the stator accommodating portion **25**.

(60) When the upper end (one end in the axial direction) of the cured seal **26** is disposed in the lower side **Z1** in the axial direction (the other side in the axial direction) relative to the upper end (one end in the axial direction) of the stator accommodating portion **25**, the upper end (one end in the axial direction) of the stator accommodating portion **25** can be disposed close to the lid portion **27**. At this time, the coupling recess **405a** is formed in the lower end surface (the end surface on the other side in the axial direction) of the coupling part **403a**, and it is possible to prevent the upper end (one end in the axial direction) of the stator accommodating portion **25** and the lid portion **27** from coming into contact with each other.

(61) The upper end (one end in the axial direction) of the bearing holding portion **231** extends to the upper side **Z2** in the axial direction (one side in the axial direction) relative to the upper end (one end in the axial direction) of the stator accommodating portion **25** and is fixed to the lid portion **27**. This allows the lid portion **27** and the stator accommodating portion **25** to be easily fixed with a small number of components via the bearing holding portion **231** in a state where the lid portion **27** and the upper end portion of the stator accommodating portion **25** filled with the seal **26** are not in contact with each other.

(62) The bearing holding portion **231** has a holding protrusion **2311**. The holding protrusion **2311** is disposed the upper side **Z2** in the axial direction (one side in the axial direction) relative to the upper end (one end in the axial direction) of the circuit board **28**. The holding protrusion **2311** protrudes radially outward from the radially outer surface and is formed in an annular shape. The lower end (the other end in the axial direction) of the holding protrusion **2311** is positioned at substantially the same height as the upper end (one end in the axial direction) of the stator accommodating portion **25** in the axial direction. The holding protrusion **2311** may be integrated with or separated from the bearing holding portion **231**. When the holding protrusion **2311** is separated from the bearing holding portion **231**, the holding protrusion **2311** is attached to the bearing holding portion **231** after the circuit board **28** is disposed on the upper end (one end in the axial direction) of the insulator **233**. This improves assembly workability of the circuit board **28**.

(63) When the seal **26** is about to be cured bulging to the upper side **Z2** in the axial direction (one side in the axial direction) along the radially outer surface of the bearing holding portion **231**, the holding protrusion **2311** can suppress rise of the seal **26**. This can prevent the lid portion **27** covering the opening **25a** and the seal **26** from coming into contact with each other. By arranging the lower end (the other end in the axial direction) of the holding protrusion **2311** at substantially the same height as the upper end (one end in the axial direction) of the stator accommodating portion **25** in the axial direction, the upper end surface (the end surface on one side in the axial direction) of the seal **26** orthogonal to the axial direction can be easily formed when the seal **26** is filled up to the upper end (one end in the axial direction) of the stator accommodating portion **25**.

(64) The radially outer end of the holding protrusion **2311** is positioned radially outside relative to the peripheral edge of the board through hole **28a**. Due to this, the holding protrusion **2311** further

protrudes radially outward, and the rise of the seal **26** can be more reliably suppressed.

(65) The holding protrusion **2311** has a curved surface **2312**. The curved surface **2312** is disposed at the other end portion in the axial direction of the holding protrusion **2311**, is inclined to the upper side **Z2** in the axial direction (one side in the axial direction) toward the radially outside, and is curved convexly toward the radially outside. This allows the holding protrusion **2311** to more reliably suppress the rise of the seal **26**.

(66) A plurality of grooves **2311a** are formed on the radially outer surface of the holding protrusion **2311**. Forming the groove **2311a** makes it difficult to form a fillet along the radially outer surface of the holding protrusion **2311** when the seal **26** is cured. Therefore, the holding protrusion **2311** can suppress rise of the seal **26** more reliably. The groove **2311a** is formed by knurling, for example.

(67) Next, the second example embodiment of the present disclosure will be described. FIG. **9** is a longitudinal cross-sectional view schematically showing a part of the motor **20**. For the sake of convenience in description, the same reference numerals are given to the same parts as those of the first example embodiment shown in FIGS. **1** to **8**. The second example embodiment is different from the first example embodiment in that an oil repellent layer **2313** is formed on a radially outer surface of the bearing holding portion **231** in place of the holding protrusion **2311**. Other parts are the same as those in the first example embodiment.

(68) The oil repellent layer **2313** is disposed in the upper side **Z2** in the axial direction (one side in the axial direction) relative to the upper end (one end in the axial direction) of the circuit board **28**. The oil repellent layer **2313** includes, for example, a fluoro resin, and repels the seal **26**.

(69) Due to this, the seal **26** is repelled by the oil repellent layer **2313** when the seal **26** is about to be cured bulging to the upper side in the axial direction (one side in the axial direction) along the radially outer surface of the bearing holding portion **231**. Therefore, the oil repellent layer **2313** can suppress rise of the seal **26**. This can prevent the lid portion **27** covering the opening **25a** and the seal **26** from coming into contact with each other.

(70) The lower end (the other end in the axial direction) of the oil repellent layer **2313** is positioned at substantially the same height as the upper end (one end in the axial direction) of the stator accommodating portion **25** in the axial direction. Due to this, the upper end surface (the end surface on one side in the axial direction) of the seal **26** orthogonal to the axial direction can be easily formed when the seal **26** is filled up to the upper end (one end in the axial direction) of the stator accommodating portion **25**. While the oil repellent layer **2313** is formed on the radially outer surface of the bearing holding portion **231** in the present example embodiment, the oil repellent layer **2313** may be formed on the radially outer surface of the holding protrusion **2311** of the first example embodiment.

(71) Next, the third example embodiment of the present disclosure will be described. FIG. **10** is a longitudinal cross-sectional view schematically showing a part of the motor **20**. For the sake of convenience in description, the same reference numerals are given to the same parts as those of the first example embodiment shown in FIGS. **1** to **8**. The third example embodiment is different from the first example embodiment in the position of the holding protrusion **2311**. Other parts are the same as those in the first example embodiment.

(72) The upper end (one end in the axial direction) of the holding protrusion **2311** is positioned at substantially the same height as one end in the axial direction of the stator accommodating portion **25** in the axial direction. When the seal **26** is filled up to the upper end (one end in the axial direction) of the stator accommodating portion **25**, the seal **26** is hardly cured bulging to the upper side **Z2** in the axial direction (one side in the axial direction) along the radially outer surface of the bearing holding portion **231** from the upper end of the holding protrusion **2311**. Therefore, at the radially inner end portion of the seal **26**, a fillet is not formed along the radially outer surface of the bearing holding portion **231** beyond the holding protrusion **2311**. Therefore, it is possible to reduce variation, for each product, in the height of the upper end (end surface on one side in the axial

direction) of the seal **26**.

(73) The holding protrusion **2311** may be integrated with or separated from the bearing holding portion **231**. When the holding protrusion **2311** is separated from the bearing holding portion **231**, the holding protrusion **2311** is attached to the bearing holding portion **231** after the circuit board **28** is disposed on the upper end (one end in the axial direction) of the insulator **233**. This improves assembly workability of the circuit board **28**.

(74) The example embodiments of the present disclosure have been described above. The scope of the present disclosure is not limited to the above-described example embodiments. The present disclosure can be implemented with various modifications within a scope not departing from the gist of the disclosure. The above-described example embodiments can be appropriately and optionally combined. For example, the oil repellent layer **2313** may be formed in which the groove **2311a** of the first example embodiment is formed.

(75) Hereinafter, exemplary example embodiments of a second aspect of the present disclosure will be described in detail with reference to the drawings.

(76) (1)

(77) A motor including: a rotor that rotates about a rotation axis; a stator that opposes the rotor with a gap interposed radially inward; a circuit board connected to the stator and disposed on one side in an axial direction of the stator; a stator accommodating portion in a tubular shape that accommodates the stator and the circuit board and has an opening on one end surface in the axial direction; a seal filled in the stator accommodating portion; and a lid portion that covers the opening, in which one end in the axial direction of the stator accommodating portion is positioned on another side in the axial direction relative to another end in the axial direction of the lid portion on a radially inside relative to the stator accommodating portion.

(2)

(78) A motor, in which one end in the axial direction of the seal is disposed at a same height in the axial direction as one side in the axial direction or the one end in the axial direction of the stator accommodating portion relative to the one end in the axial direction of the stator accommodating portion.

(79) (3)

(80) A motor, in which an end surface of the seal on one side in the axial direction is orthogonal to the axial direction.

(81) (4)

(82) A motor, in which the stator includes a bearing holding portion in a tubular shape that internally holds a bearing that rotatably supports a shaft extending along the rotation axis, the circuit board has a board through hole that is disposed on the rotation axis and penetrates the circuit board in the axial direction, and one end portion in the axial direction of the bearing holding portion is inserted into the board through hole, extends to one side in the axial direction relative to the circuit board, and is fixed to the lid portion.

(5)

(83) A motor, in which the bearing holding portion includes a holding protrusion in an annular shape disposed on one side in the axial direction relative to one end in the axial direction of the circuit board and protruding radially outward from a radially outer surface.

(6)

(84) A motor, in which another end in an axial direction of the holding protrusion is positioned at substantially a same height in the axial direction as the one end in the axial direction of the stator accommodating portion.

(85) (7)

(86) A motor, in which a radially outer end of the holding protrusion is positioned radially outside relative to a peripheral edge of the board through hole.

(87) (8)

(88) A motor, in which the holding protrusion includes: a curved surface that is disposed at another end portion in the axial direction, is inclined to one side in the axial direction toward a radially outside, and is curved convexly toward the radially outside.

(9)

(89) A motor, in which the holding protrusion has a plurality of grooves formed on a radially outer surface.

(90) (10)

(91) A blower including: a motor; an impeller that is fixed to the rotor and generates an airflow in an axial direction; and a housing body portion that extends along the rotation axis, is formed in a tubular shape, has both end surfaces in the axial direction opened, and internally has a blowing flow path, in which the motor and the impeller are accommodated inside the housing body portion.

(92) FIGS. 1 and 2 are a perspective view and an exploded perspective view, respectively, of an example of the blower 1 according to the first example embodiment of the present disclosure. The blower 1 includes a motor 20, an impeller 30, and a housing 40.

(93) The impeller 30 is fixed to the motor 20 and rotates about the rotation axis J to generate an airflow on the lower side Z1 in the axial direction (the other side in the axial direction) along the rotation axis J.

(94) The housing 40 is formed in a tubular shape extending along the rotation axis J, and has a blowing flow path 41 in which both end surfaces in the axial direction are opened and an airflow internally circulates. The motor 20 and the impeller 30 are accommodated inside the housing 40. The housing 40 has an exhaust port 42 on a lower end surface (the other end surface in the axial direction) (see FIG. 3) and an intake port 43 on an upper end side (one end surface in the axial direction).

(95) The housing 40 is configured by axially coupling an upper housing part 40a and a lower housing part 40b. The upper housing part 40a and the lower housing part 40b are resin molded articles. In the present example embodiment, the housing 40 can be divided into the upper housing part 40a and the lower housing part 40b, but the upper housing part 40a and the lower housing part 40b may be integrally formed. The upper housing part 40a includes an upper body portion 401a, a fixing part 402a, and coupling parts 403a and 403b. The upper body portion 401a extends in the axial direction and is formed in a tubular shape.

(96) The fixing part 402a and the coupling parts 403a and 403b constitute a lid portion 27 that covers an opening 25a (see FIG. 4) of a stator accommodating portion 25 described below. The lid portion 27 is a part of the housing 40 and also a part of the motor 20. The fixing part 402a is arranged on an upper side Z2 in the axial direction (one side in the axial direction) of the stator accommodating portion 25 described below, and has a disk shape expanding in the radial direction about the rotation axis J. A stator 23 described below of the motor 20 is fixed to the fixing part 402a. That is, the fixing part 402a is formed in a plate shape to which the stator 23 is fixed.

(97) The coupling parts 403a and 403b extend radially outward from the fixing part 402a and couple the fixing part 402a and a housing body portion 40c. A plurality of the coupling parts 403a are arranged in the circumferential direction and axially opposes an accommodating recess 252a described below. The coupling part 403b is disposed at one position in the circumferential direction and axially opposes a pullout piece 2522 described below. The air circulating through the blowing flow path 41 passes through between the adjacent coupling parts 403a and 403b.

(98) The coupling part 403a is formed to be inclined to one side in the circumferential direction from the radially inner end toward the radially outside. Due to this, the airflow flowing into the housing 40 from the intake port 43 smoothly circulates along the coupling part 403a. Therefore, the blowing efficiency of the blower 1 can be further improved. The coupling part 403a may be formed to be inclined to the other side in the circumferential direction from the radially inner end toward the radially outside. The coupling part 403a may be formed to extend linearly in the radial direction. The coupling part 403b is formed to extend linearly in the radial direction.

(99) The coupling part **403a** has a coupling recess **405a** (see FIG. 4). The coupling recess **405a** is disposed to oppose the stator accommodating portion **25** in the axial direction, and is recessed to the one side in the axial direction from the lower end surface (end surface on the other side in the axial direction) of the coupling part **403a**. This can prevent the stator accommodating portion **25** from coming into contact with the coupling part **403** when swung in the axial direction.

(100) The lower housing part **40b** has a lower body portion **401b** that extends in the axial direction and is formed in a tubular shape. The lower body portion **401b** and the upper body portion **401a** are coupled in the axial direction to constitute the housing body portion **40c**. That is, the blower **1** includes the housing body portion **40c**, and the housing body portion **40c** is formed in a tubular shape extending along the rotation axis J, and internally has the blowing flow path **41** with both end surfaces in the axial direction opened. The motor **20** and the impeller **30** are accommodated inside the housing body portion **40c**.

(101) The impeller **30** includes an impeller cup **31** and a plurality of blades **32**. The impeller cup **31** is fixed to a radially outside of a rotor **24** described below of the motor **20**. The plurality of blades **32** are arrayed in the circumferential direction on a radially outer surface of the impeller cup **31**.

(102) FIG. 3 is a longitudinal cross-sectional perspective view of the blower **1**, and FIG. 4 is a longitudinal cross-sectional perspective view showing a part of the blower **1** in an enlarged manner. The motor **20** includes a shaft **21**, a bearing **22**, the stator **23**, the rotor **24**, the stator accommodating portion **25**, a seal **26**, the above-described lid portion **27**, and a circuit board **28**.

(103) The shaft **21** extends along the rotation axis J. The shaft **21** is a columnar member that is made of metal such as stainless steel and extends in the axial direction.

(104) The bearings **22** are arranged in a pair at least spaced apart in the axial direction. The bearing **22** is configured by, for example, a ball bearing, but may be configured by a sleeve bearing or the like. The pair of bearings **22** support the shaft **21** so as to be rotatable about the rotation axis J with respect to the stator **23**.

(105) The stator **23** opposes the rotor **24** with a gap interposed radially inward. The stator **23** includes a bearing holding portion **231**, a stator core **232**, an insulator **233**, and a coil **234**. The bearing holding portion **231** is formed in a cylindrical shape and internally holds the bearing **22**.

(106) An upper end portion (one end portion in the axial direction) of the bearing holding portion **231** is fitted via a connector **45** into a fitting hole **404a** of the fixing part **402a**. Due to this, the bearing holding portion **231** is fixed to the fixing part **402a**, and the stator **23** and the housing **40** are fixed. The fitting hole **404a** is formed to penetrate the fixing part **402a** in the axial direction. The connector **45** is formed in an annular shape and is disposed on the inner peripheral surface of the fitting hole **404a**. The bearing holding portion **231** is disposed on the inner peripheral surface of the connector **45**. A lower end portion (the other end portion in the axial direction) of the bearing holding portion **231** is fixed to the stator accommodating portion **25** described below. The upper end portion (one end portion in the axial direction) of the bearing holding portion **231** may be directly fitted into the fitting hole **404a** without the connector **45**.

(107) The stator core **232** is formed by vertically stacking electromagnetic steel plates such as silicon steel plates. The insulator **233** is made of an insulating resin. The stator core **232** includes an annular core back (not shown) and a plurality of teeth (not shown) protruding radially outward from the core back and arranged in the circumferential direction. The insulator **233** is provided on a part of the outer surface in the axial direction of the teeth and a part of the outer surface in the circumferential direction of the teeth. The insulator **233** is provided surrounding an outer surface of the stator core **232**. The coil **234** is formed of a conductive wire wound around the stator core **232** via the insulator **233**.

(108) The rotor **24** rotates about the rotation axis J with respect to the stator **23**. The rotor **24** includes a rotor yoke **241** and a magnet **242**.

(109) The rotor yoke **241** is a member in a substantially cylindrical shape made of a magnetic material and having a lid on portion (the other end portion in the axial direction) of the shaft **21**.

The magnet **242** has a cylindrical shape and is fixed to an inner peripheral surface of the rotor yoke **241**. Due to this, the magnet **242** is disposed on the radially outside of the stator **23**.

(110) The circuit board **28** is in contact with the upper end (one end in the axial direction) of the insulator **233** and is disposed between the stator core **232** and the lid portion **27**. The circuit board **28** has a disk shape expanding in the radial direction about the rotation axis J, for example. The circuit board **28** has a board through hole **28a**. The board through hole **28a** is disposed on the rotation axis J and penetrates in the axial direction. The upper end portion (one end portion in the axial direction) of the bearing holding portion **231** is inserted into the board through hole **28a** and extends in the upper side Z2 in the axial direction (one side in the axial direction) relative to the circuit board **28**.

(111) A conductive wire (not shown) constituting the coil **234** is electrically connected to the circuit board **28**. An electronic circuit for supplying a drive current to the coil **234** is mounted on the circuit board **28**. The circuit board **28** is connected to a lead wire **50** (see FIGS. 6 and 7), and the lead wire **50** is pulled out to the outside of the stator accommodating portion **25** and connected to an external power source. The lead wire **50** is electrically connected to the coil **234**, and the lead wire **50** and the stator **23** are electrically connected. In the present example embodiment, three lead wires **50** are pulled out to the outside of the stator accommodating portion **25**.

(112) FIGS. 5 and 6 are a perspective view and a top view, respectively, of the motor **20**, and FIG. 7 is a longitudinal cross-sectional perspective view of the stator accommodating portion **25**. In FIGS. 5 and 6, the rotor **24**, the seal **26**, and the lid portion **27** are not shown, and the elastic portion **29** is indicated by a dotted line. In FIG. 5, the lead wire **50** is not shown, and in FIGS. 6 and 7, the lead wire **50** is indicated by an alternate long and short dash line.

(113) The stator accommodating portion **25** is formed in a tubular shape and has the opening **25a** on one end surface in the axial direction (end surface on one side in the axial direction). The stator accommodating portion **25** internally accommodates the shaft **21**, the bearing **22**, the stator **23**, and the circuit board **28**. The stator accommodating portion **25** is filled with the seal **26** (see FIG. 4). Due to this, the shaft **21**, the bearing **22**, the stator **23**, and the circuit board **28** are integrated, and the assembly workability of the motor **20** is improved.

(114) The stator core **232** is press-fitted into the inner peripheral surface of the stator accommodating portion **25**. At this time, the radially outer surfaces of the teeth (not shown) come into contact with the inner peripheral surface of the stator accommodating portion **25**. The outer peripheral surface of the stator accommodating portion **25** opposes the magnet **242** in the radial direction with a gap interposed (see FIG. 3).

(115) The seal **26** is formed of a curable insulating resin or the like, and for example, an epoxy resin, silicone rubber, a polyurethane resin, or the like is used. The liquid seal **26** is filled inside the stator accommodating portion **25** from the opening **25a** and is cured after a predetermined time elapses. Due to this, the stator **23** and the circuit board **28** are covered with the cured seal **26**, and waterproof property, oil proof property, and the like of the stator **23** and the circuit board **28** are improved.

(116) The stator accommodating portion **25** includes a stator tube portion **251**, a board tube portion **252**, an intermediate tube portion **253**, an accommodating lid portion **254**, and an accommodating inclined portion **255**.

(117) The stator tube portion **251** surrounds the stator **23** from circuit board **28** from radially outside. The intermediate tube portion **253** couples the stator tube portion **251** and the board tube portion **252**.

(118) The accommodating lid portion **254** covers the stator **23** from the lower side Z1 in the axial direction (the other side in the axial direction) and expands in the radial direction. The accommodating lid portion **254** has an accommodating through hole **254a** and an accommodating holding portion **254b** penetrating in the axial direction. The lower end portion (the other end portion in the axial direction) of the bearing holding portion **231** is fitted into the accommodating

through hole **254a** (see FIG. 3). Due to this, the stator accommodating portion **25** is fixed to the bearing holding portion **231**. The accommodating holding portion **254b** protrudes in the upper side **Z2** in the axial direction (one side in the axial direction) from the peripheral edge of the accommodating through hole **254a**, and is formed in a tubular shape. The accommodating holding portion **254b** holds the lower end portion (the other end portion in the axial direction) of the bearing holding portion **231**.

(119) The board tube portion **252** has the accommodating recess **252a**. The accommodating recess **252a** is arranged in the upper end portion (one end portion in the axial direction) of the stator accommodating portion **25** and is recessed radially outward from the radially inner surface. In the radial direction, a gap **S** is formed between the radially outer edge of the circuit board **28** and the accommodating recess **252a**. In the present example embodiment, the accommodating recess **252a** has a part of the board tube portion **252** formed in a convex shape radially outside, and is provided at three places at equal intervals in the circumferential direction. The number of accommodating recesses **252a** is not limited to three. By providing the accommodating recess **252a**, the seal **26** can smoothly flow into the stator accommodating portion **25** from the gap **S**. This improves the assembling workability of the blower **1**.

(120) As viewed from the axial direction, at least a part of the accommodating recess **252a** overlaps the coupling part **403a** of the lid portion **27** (see FIG. 4). In the present example embodiment, the circumferential width of the accommodating recess **252a** is equal to or less than the circumferential width of the coupling part **403a**, and the entire accommodating recess **252a** overlaps the coupling part **403a** as viewed from the axial direction. This can reduce the airflow that passes through between the adjacent coupling parts **403a** and flows into the housing **40** from being disturbed in the vicinity of the accommodating recess **252a**. Therefore, the blowing efficiency of the blower **1** can be improved.

(121) The radial protrusion amount of the accommodating recess **252a** is $\frac{1}{2}$ or less of the radial size of the coupling part **403a**. This can further reduce the airflow that passes through between the adjacent coupling parts **403a** and flows into the housing **40** from being disturbed in the vicinity of the accommodating recess **252a**. It is preferable that the radial protrusion amount of the accommodating recess **252a** is smaller as long as a predetermined size of the gap **S** is secured.

(122) The intermediate tube portion **253** is inclined radially inward toward the lower side **Z1** in the axial direction (the other side in the axial direction). This allows the seal **26** to smoothly flow into the stator tube portion **251** from the board tube portion **252** along the intermediate tube portion **253**.

(123) The accommodating inclined portion **255** couples the stator tube portion **251** and the accommodating lid portion **254** and is inclined radially inward toward the lower side **Z1** in the axial direction (the other side in the axial direction). This allows the seal **26** to smoothly flow into the radially inside of the along the accommodating inclined portion **255**. The resin amount of the seal **26** can be reduced, and the manufacturing cost can be reduced.

(124) The stator accommodating portion **25** has an accommodating projection **251a** that protrudes from the radially inner surface and extends in the axial direction (see FIG. 7). In the present example embodiment, the accommodating projection **251a** is disposed on the radially inner surface of the stator tube portion **251**. The accommodating projection **251a** is fitted into a groove (not shown) formed on the radially outer surface of the stator core **232** and extending in the axial direction. This enables easy positioning in the circumferential direction of the stator core **232** in the stator accommodating portion **25**. In a state where the stator core **232** is accommodated in the stator accommodating portion **25**, the accommodating projection **251a** is press-fitted between teeth (not shown) adjacent in the circumferential direction.

(125) The stator accommodating portion **25** further includes a cutout **2521** and the pullout piece **2522**.

(126) The cutout **2521** is recessed from the upper end (one end in the axial direction) of the stator accommodating portion **25** to the lower side **Z1** in the axial direction (the other side in the axial

direction), and the lead wire **50** is pulled out radially outward (see FIG. 7).

(127) The pullout piece **2522** protrudes radially outward from the bottom of the cutout **2521**, and is formed in a plate shape. The elastic portion **29** in a rectangular parallelepiped shape is disposed on the upper surface (end surface on one side in the axial direction) of the pullout piece **2522**. The lead wire **50** is disposed on the upper surface (end surface on one side in the axial direction) of the elastic portion **29**. The upper end (one end in the axial direction) of the elastic portion **29** is disposed on the upper side **Z2** in the axial direction (one side in the axial direction) relative to the upper end (one end in the axial direction) of the board tube portion **252**.

(128) Due to this, even when flowing out to the outside of the cutout **2521**, the seal **26** before being cured is dammed by the elastic portion **29**. Therefore, the seal **26** before being cured can be prevented from flowing out of the stator accommodating portion **25** via the cutout **2521**. At this time, the upper end (one end in the axial direction) of the elastic portion **29** is disposed on the upper side **Z2** in the axial direction (one side in the axial direction) relative to the upper end (one end in the axial direction) of the cured seal **26**.

(129) The elastic portion **29** is fixed to the pullout piece **2522** via an adhesive layer **29a** (see FIG. 7). This allows the elastic portion **29** to be easily fixed to the pullout piece **2522**, and improves the assembling workability of the motor **20**. The elastic portion **29** is made of, for example, a rubber portion.

(130) By providing the pullout piece **2522**, the lead wire **50** can be pulled out radially outward while being supported by the pullout piece **2522** without being largely bent in the axial direction. Therefore, damage to the lead wire **50** can be prevented.

(131) The pullout piece **2522** includes a pullout inclined portion **2522a**, a pullout projection **2522b**, and a pair of pullout wall portions **2522c**. The pullout inclined portion **2522a** is inclined in the upper side **Z2** in the axial direction (one side in the axial direction) toward radially outward from the bottom of the cutout **2521**. By providing the pullout inclined portion **2522a**, the seal **26** before being cured can be further prevented from flowing out to the outside of the stator accommodating portion **25** via the cutout **2521**.

(132) The pullout projection **2522b** is disposed adjacent to the radially outside of the cutout **2521** and protrudes from the upper surface (end surface on one side in the axial direction) of the the elastic portion **29** can be easily positioned.

(133) The pullout wall portion **2522c** protrudes in the upper side **Z2** in the axial direction (one side in the axial direction) from both end portions in the radial direction of the pullout piece **2522** and extends in the radial direction. The radially inner end of the pullout wall portion **2522c** is coupled to the outer peripheral surface of the board tube portion **252**. The upper end (one end in the axial direction) of the pullout wall portion **2522c** is disposed in the upper side **Z2** in the axial direction (one side in the axial direction) relative to the upper end (one end in the axial direction) of the board tube portion **252**. Due to this, the seal **26** before being cured can be further prevented from flowing out to the outside of the stator accommodating portion **25** via the cutout **2521**.

(134) The pullout piece **2522** is arranged to oppose the coupling part **403b** (lid portion **27**) in the axial direction. At this time, the lead wire **50** is sandwiched between the coupling part **403b** (lid portion **27**) and the pullout piece **2522** via the elastic portion **29**. At this time, the elastic portion **29** deforms along the outer peripheral surface of the lead wire **50**, and a minute gap is hardly generated between the lead wire **50** and the elastic portion **29**. This can prevent the seal **26** before being cured from passing through between the lead wire **50** and the elastic portion **29** due to a capillary phenomenon along the lead wire **50**. Therefore, the seal **26** can be prevented from flowing out to the outside of the stator accommodating portion **25**. This can provide the motor **20** that can prevent the seal **26** from flowing out.

(135) FIG. 8 is a longitudinal cross-sectional view schematically showing a part of the motor **20**. The upper end (one end in the axial direction) of the stator accommodating portion **25** is positioned in the lower side **Z1** in the axial direction (the other side in the axial direction) relative to the lower

end (the other end in the axial direction) of the lid portion **27** on the radially inside relative to the upper end (one end in the axial direction) of the stator accommodating portion **25**.

(136) There is a possibility that the seal **26** bulges and is cured in the upper side **Z2** in the axial direction (one side in the axial direction) along the radially inner surface of the stator accommodating portion **25**, and a fillet is formed at the radially outer end portion of the seal **26**. The fillet does not bulge in the upper side **Z2** of the axial direction (one side in the axial direction) beyond the upper end (one end in the axial direction) of the stator accommodating portion **25**. Due to this, even when a fillet is formed along the radially inner surface of the stator accommodating portion **25**, the upper end (one end in the axial direction) of the fillet is positioned in the lower side **Z1** in the axial direction (the other side in the axial direction) relative to the lower end (the other end in the axial direction) of the lid portion **27**. Therefore, the lid portion **27** covering the opening **25a** and the seal **26** can be prevented from coming into contact with each other. This can downsize the motor **20** in the axial direction.

(137) In the present example embodiment, the seal **26** is filled up to the upper end (one end in the axial direction) of the stator accommodating portion **25**, and the upper end (one end in the axial direction) of the cured seal **26** is disposed at the same height in the axial direction as the upper side **Z2** in the axial direction (one side in the axial direction) relative to the upper end (one end in the axial direction) of the stator accommodating portion **25** or the one end in the axial direction of the stator accommodating portion **25**. At this time, at the radially outer end portion of the seal **26**, a fillet is not formed along the radially inner surface of the stator accommodating portion **25**. Therefore, it is possible to reduce variation, for each product, in the height of the upper end (end surface on one side in the axial direction) of the seal **26**. This allows the lid portion **27** to be disposed close to the upper end (one end in the axial direction) of the stator accommodating portion **25** while preventing the lid portion **27** and the seal **26** from coming into contact with each other. Therefore, it is possible to further downsize the motor **20** in the axial direction.

(138) The upper end surface (end surface on one side in the axial direction) of the seal **26** is formed orthogonal to the axial direction. This allows the lid portion **27** to be disposed closer to the upper end (one end in the axial direction) of the stator accommodating portion **25**.

(139) When the upper end (one end in the axial direction) of the cured seal **26** is disposed in the lower side **Z1** in the axial direction (the other side in the axial direction) relative to the upper end (one end in the axial direction) of the stator accommodating portion **25**, the upper end (one end in the axial direction) of the stator accommodating portion **25** can be disposed close to the lid portion **27**. At this time, the coupling recess **405a** is formed in the lower end surface (the end surface on the other side in the axial direction) of the coupling part **403a**, and it is possible to prevent the upper end (one end in the axial direction) of the stator accommodating portion **25** and the lid portion **27** from coming into contact with each other.

(140) The upper end (one end in the axial direction) of the bearing holding portion **231** extends to the upper side **Z2** in the axial direction (one side in the axial direction) relative to the upper end (one end in the axial direction) of the stator accommodating portion **25** and is fixed to the lid portion **27**. This allows the lid portion **27** and the stator accommodating portion **25** to be easily fixed with a small number of components via the bearing holding portion **231** in a state where the lid portion **27** and the upper end portion of the stator accommodating portion **25** filled with the seal **26** are not in contact with each other.

(141) The bearing holding portion **231** has a holding protrusion **2311**. The holding protrusion **2311** is disposed the upper side **Z2** in the axial direction (one side in the axial direction) relative to the upper end (one end in the axial direction) of the circuit board **28**. The holding protrusion **2311** protrudes radially outward from the radially outer surface and is formed in an annular shape. The lower end (the other end in the axial direction) of the holding protrusion **2311** is positioned at substantially the same height as the upper end (one end in the axial direction) of the stator accommodating portion **25** in the axial direction. The holding protrusion **2311** may be integrated

with or separated from the bearing holding portion **231**. When the holding protrusion **2311** is separated from the bearing holding portion **231**, the holding protrusion **2311** is attached to the bearing holding portion **231** after the circuit board **28** is disposed on the upper end (one end in the axial direction) of the insulator **233**. This improves assembly workability of the circuit board **28**.

(142) When the seal **26** is about to be cured bulging to the upper side **Z2** in the axial direction (one side in the axial direction) along the radially outer surface of the bearing holding portion **231**, the holding protrusion **2311** can suppress rise of the seal **26**. This can prevent the lid portion **27** covering the opening **25a** and the seal **26** from coming into contact with each other. By arranging the lower end (the other end in the axial direction) of the holding protrusion **2311** at substantially the same height as the upper end (one end in the axial direction) of the stator accommodating portion **25** in the axial direction, the upper end surface (the end surface on one side in the axial direction) of the seal **26** orthogonal to the axial direction can be easily formed when the seal **26** is filled up to the upper end (one end in the axial direction) of the stator accommodating portion **25**.

(143) The radially outer end of the holding protrusion **2311** is positioned radially outside relative to the peripheral edge of the board through hole **28a**. Due to this, the holding protrusion **2311** further protrudes radially outward, and the rise of the seal **26** can be more reliably suppressed.

(144) The holding protrusion **2311** has a curved surface **2312**. The curved surface **2312** is disposed at the other end portion in the axial direction of the holding protrusion **2311**, is inclined to the upper side **Z2** in the axial direction (one side in the axial direction) toward the radially outside, and is curved convexly toward the radially outside. This allows the holding protrusion **2311** to more reliably suppress the rise of the seal **26**.

(145) A plurality of grooves **2311a** are formed on the radially outer surface of the holding protrusion **2311**. Forming the groove **2311a** makes it difficult to form a fillet along the radially outer surface of the holding protrusion **2311** when the seal **26** is cured. Therefore, the holding protrusion **2311** can suppress rise of the seal **26** more reliably. The groove **2311a** is formed by knurling, for example.

(146) Next, the second example embodiment of the present disclosure will be described. FIG. **9** is a longitudinal cross-sectional view schematically showing a part of the motor **20**. For the sake of convenience in description, the same reference numerals are given to the same parts as those of the first example embodiment shown in FIGS. **1** to **8**. The second example embodiment is different from the first example embodiment in that an oil repellent layer **2313** is formed on a radially outer surface of the bearing holding portion **231** in place of the holding protrusion **2311**. Other parts are the same as those in the first example embodiment.

(147) The oil repellent layer **2313** is disposed in the upper side **Z2** in the axial direction (one side in the axial direction) relative to the upper end (one end in the axial direction) of the circuit board **28**. The oil repellent layer **2313** includes, for example, a fluoro resin, and repels the seal **26**.

(148) Due to this, the seal **26** is repelled by the oil repellent layer **2313** when the seal **26** is about to be cured bulging to the upper side in the axial direction (one side in the axial direction) along the radially outer surface of the bearing holding portion **231**. Therefore, the oil repellent layer **2313** can suppress rise of the seal **26**. This can prevent the lid portion **27** covering the opening **25a** and the seal **26** from coming into contact with each other.

(149) The lower end (the other end in the axial direction) of the oil repellent layer **2313** is positioned at substantially the same height as the upper end (one end in the axial direction) of the stator accommodating portion **25** in the axial direction. Due to this, the upper end surface (the end surface on one side in the axial direction) of the seal **26** orthogonal to the axial direction can be easily formed when the seal **26** is filled up to the upper end (one end in the axial direction) of the stator accommodating portion **25**. While the oil repellent layer **2313** is formed on the radially outer surface of the bearing holding portion **231** in the present example embodiment, the oil repellent layer **2313** may be formed on the radially outer surface of the holding protrusion **2311** of the first example embodiment.

(150) Next, the third example embodiment of the present disclosure will be described. FIG. **10** is a longitudinal cross-sectional view schematically showing a part of the motor **20**. For the sake of convenience in description, the same reference numerals are given to the same parts as those of the first example embodiment shown in FIGS. **1** to **8**. The third example embodiment is different from the first example embodiment in the position of the holding protrusion **2311**. Other parts are the same as those in the first example embodiment.

(151) The upper end (one end in the axial direction) of the holding protrusion **2311** is positioned at substantially the same height as one end in the axial direction of the stator accommodating portion **25** in the axial direction. When the seal **26** is filled up to the upper end (one end in the axial direction) of the stator accommodating portion **25**, the seal **26** is hardly cured bulging to the upper side **Z2** in the axial direction (one side in the axial direction) along the radially outer surface of the bearing holding portion **231** from the upper end of the holding protrusion **2311**. Therefore, at the radially inner end portion of the seal **26**, a fillet is not formed along the radially outer surface of the bearing holding portion **231** beyond the holding protrusion **2311**. Therefore, it is possible to reduce variation, for each product, in the height of the upper end (end surface on one side in the axial direction) of the seal **26**.

(152) The holding protrusion **2311** may be integrated with or separated from the bearing holding portion **231**. When the holding protrusion **2311** is separated from the bearing holding portion **231**, the holding protrusion **2311** is attached to the bearing holding portion **231** after the circuit board **28** is disposed on the upper end (one end in the axial direction) of the insulator **233**. This improves assembly workability of the circuit board **28**.

(153) The example embodiments of the present disclosure have been described above. The scope of the present disclosure is not limited to the above-described example embodiments. The present disclosure can be implemented with various modifications within a scope not departing from the gist of the disclosure. The above-described example embodiments can be appropriately and optionally combined. For example, the oil repellent layer **2313** may be formed in which the groove **2311a** of the first example embodiment is formed.

(154) Hereinafter, exemplary example embodiments of a third aspect of the present disclosure will be described in detail with reference to the drawings.

(155) (1)

(156) A motor including: a rotor that rotates about a rotation axis; a stator that opposes the rotor with a gap interposed radially inward; a circuit board connected to the stator and disposed on one side in an axial direction of the stator; a stator accommodating portion in a tubular shape that accommodates the stator and the circuit board and has an opening on one end surface in the axial direction; a seal filled in the stator accommodating portion; and a lid portion that covers the opening, in which the stator includes a bearing holding portion in a tubular shape that internally holds a bearing that rotatably supports a shaft extending along the rotation axis, the circuit board has a board through hole that is disposed on the rotation axis and penetrates the circuit board in the axial direction, one end portion in the axial direction of the bearing holding portion is inserted into the board through hole and extends to one side in the axial direction relative to the circuit board, and the bearing holding portion includes an oil repellent layer formed on a radially outer surface on one side in the axial direction relative to one end in the axial direction of the circuit board.

(2)

(157) A motor, in which another end in the axial direction of the oil repellent layer is positioned at substantially a same height in the axial direction as the one end in the axial direction of the stator accommodating portion.

(158) (3)

(159) A motor, in which the oil repellent layer includes a fluororesin.

(160) (4)

(161) A motor including: a rotor that rotates about a rotation axis; a stator that opposes the rotor

with a gap interposed radially inward; a circuit board connected to the stator and disposed on one side in an axial direction of the stator; a stator accommodating portion in a tubular shape that accommodates the stator and the circuit board and has an opening on one end surface in the axial direction; a seal filled in the stator accommodating portion; and a lid portion that covers the opening, in which the stator includes a bearing holding portion in a tubular shape that internally holds a bearing that rotatably supports a shaft extending along the rotation axis, the circuit board has a board through hole that is disposed on the rotation axis and penetrates the circuit board in the axial direction, one end portion in the axial direction of the bearing holding portion is inserted into the board through hole and extends to one side in the axial direction relative to the circuit board, and the bearing holding portion includes a holding protrusion in an annular shape disposed on one side in the axial direction relative to one end in the axial direction of the circuit board and protruding radially outward from a radially outer surface.

(5)

(162) A motor, in which one end in the axial direction of the holding protrusion is positioned at substantially a same height in the axial direction as the one end in the axial direction of the stator accommodating portion.

(163) (6)

(164) A motor, in which a radially outer end of the holding protrusion is positioned radially outside relative to a peripheral edge of the board through hole.

(165) (7)

(166) A motor, in which the holding protrusion includes: a curved surface that is disposed at another end portion in the axial direction, is inclined to one side in the axial direction toward a radially outside, and is curved convexly toward the radially outside.

(8)

(167) A motor, in which the holding protrusion has a plurality of grooves formed on a radially outer surface.

(168) (9)

(169) A blower including: a motor; an impeller that is fixed to the rotor and generates an airflow in an axial direction; and a housing body portion that extends along the rotation axis, is formed in a tubular shape, has both end surfaces in the axial direction opened, and internally has a blowing flow path, in which the motor and the impeller are accommodated inside the housing body portion.

(170) FIGS. **1** and **2** are a perspective view and an exploded perspective view, respectively, of an example of the blower **1** according to the first example embodiment of the present disclosure. The blower **1** includes a motor **20**, an impeller **30**, and a housing **40**.

(171) The impeller **30** is fixed to the motor **20** and rotates about the rotation axis J to generate an airflow on the lower side X1 in the axial direction (the other side in the axial direction) along the rotation axis J.

(172) The housing **40** is formed in a tubular shape extending along the rotation axis J, and has a blowing flow path **41** in which both end surfaces in the axial direction are opened and an airflow internally circulates. The motor **20** and the impeller **30** are accommodated inside the housing **40**. The housing **40** has an exhaust port **42** on a lower end surface (the other end surface in the axial direction) (see FIG. **3**) and an intake port **43** on an upper end side (one end surface in the axial direction).

(173) The housing **40** is configured by axially coupling an upper housing part **40a** and a lower housing part **40b**. The upper housing part **40a** and the lower housing part **40b** are resin molded articles. In the present example embodiment, the housing **40** can be divided into the upper housing part **40a** and the lower housing part **40b**, but the upper housing part **40a** and the lower housing part **40b** may be integrally formed. The upper housing part **40a** includes an upper body portion **401a**, a fixing part **402a**, and coupling parts **403a** and **403b**. The upper body portion **401a** extends in the axial direction and is formed in a tubular shape.

(174) The fixing part **402a** and the coupling parts **403a** and **403b** constitute a lid portion **27** that covers an opening **25a** (see FIG. 4) of a stator accommodating portion **25** described below. The lid portion **27** is a part of the housing **40** and also a part of the motor **20**. The fixing part **402a** is arranged on an upper side X2 in the axial direction (one side in the axial direction) of the stator accommodating portion **25** described below, and has a disk shape expanding in the radial direction about the rotation axis J. A stator **23** described below of the motor **20** is fixed to the fixing part **402a**. That is, the fixing part **402a** is formed in a plate shape to which the stator **23** is fixed.

(175) The coupling parts **403a** and **403b** extend radially outward from the fixing part **402a** and couple the fixing part **402a** and a housing body portion **40c**. A plurality of the coupling parts **403a** are arranged in the circumferential direction and axially opposes an accommodating recess **252a** described below. The coupling part **403b** is disposed at one position in the circumferential direction and axially opposes a pullout piece **2522** described below. The air circulating through the blowing flow path **41** passes through between the adjacent coupling parts **403a** and **403b**.

(176) The coupling part **403a** is formed to be inclined to one side in the circumferential direction from the radially inner end toward the radially outside. Due to this, the airflow flowing into the housing **40** from the intake port **43** smoothly circulates along the coupling part **403a**. Therefore, the blowing efficiency of the blower **1** can be further improved. The coupling part **403a** may be formed to be inclined to the other side in the circumferential direction from the radially inner end toward the radially outside. The coupling part **403a** may be formed to extend linearly in the radial direction. The coupling part **403b** is formed to extend linearly in the radial direction.

(177) The coupling part **403a** has a coupling recess **405a** (see FIG. 4). The coupling recess **405a** is disposed to oppose the stator accommodating portion **25** in the axial direction, and is recessed to the one side in the axial direction from the lower end surface (end surface on the other side in the axial direction) of the coupling part **403a**. This can prevent the stator accommodating portion **25** from coming into contact with the coupling part **403** when swung in the axial direction.

(178) The lower housing part **40b** has a lower body portion **401b** that extends in the axial direction and is formed in a tubular shape. The lower body portion **401b** and the upper body portion **401a** are coupled in the axial direction to constitute the housing body portion **40c**. That is, the blower **1** includes the housing body portion **40c**, and the housing body portion **40c** is formed in a tubular shape extending along the rotation axis J, and internally has the blowing flow path **41** with both end surfaces in the axial direction opened. The motor **20** and the impeller **30** are accommodated inside the housing body portion **40c**.

(179) The impeller **30** includes an impeller cup **31** and a plurality of blades **32**. The impeller cup **31** is fixed to a radially outside of a rotor **24** described below of the motor **20**. The plurality of blades **32** are arrayed in the circumferential direction on a radially outer surface of the impeller cup **31**.

(180) FIG. 3 is a longitudinal cross-sectional perspective view of the blower **1**, and FIG. 4 is a longitudinal cross-sectional perspective view showing a part of the blower **1** in an enlarged manner. The motor **20** includes a shaft **21**, a bearing **22**, the stator **23**, the rotor **24**, the stator accommodating portion **25**, a seal **26**, the above-described lid portion **27**, and a circuit board **28**.

(181) The shaft **21** extends along the rotation axis J. The shaft **21** is a columnar member that is made of metal such as stainless steel and extends in the axial direction.

(182) The bearings **22** are arranged in a pair at least spaced apart in the axial direction. The bearing **22** is configured by, for example, a ball bearing, but may be configured by a sleeve bearing or the like. The pair of bearings **22** support the shaft **21** so as to be rotatable about the rotation axis J with respect to the stator **23**.

(183) The stator **23** opposes the rotor **24** with a gap interposed radially inward. The stator **23** includes a bearing holding portion **231**, a stator core **232**, an insulator **233**, and a coil **234**. The bearing holding portion **231** is formed in a cylindrical shape and internally holds the bearing **22**.

(184) An upper end portion (one end portion in the axial direction) of the bearing holding portion **231** is fitted via a connector **45** into a fitting hole **404a** of the fixing part **402a**. Due to this, the

bearing holding portion **231** is fixed to the fixing part **402a**, and the stator **23** and the housing **40** are fixed. The fitting hole **404a** is formed to penetrate the fixing part **402a** in the axial direction. The connector **45** is formed in an annular shape and is disposed on the inner peripheral surface of the fitting hole **404a**. The bearing holding portion **231** is disposed on the inner peripheral surface of the connector **45**. A lower end portion (the other end portion in the axial direction) of the bearing holding portion **231** is fixed to the stator accommodating portion **25** described below. The upper end portion (one end portion in the axial direction) of the bearing holding portion **231** may be directly fitted into the fitting hole **404a** without the connector **45**.

(185) The stator core **232** is formed by vertically stacking electromagnetic steel plates such as silicon steel plates. The insulator **233** is made of an insulating resin. The stator core **232** includes an annular core back (not shown) and a plurality of teeth (not shown) protruding radially outward from the core back and arranged in the circumferential direction. The insulator **233** is provided on a part of the outer surface in the axial direction of the teeth and a part of the outer surface in the circumferential direction of the teeth. The insulator **233** is provided surrounding an outer surface of the stator core **232**. The coil **234** is formed of a conductive wire wound around the stator core **232** via the insulator **233**.

(186) The rotor **24** rotates about the rotation axis J with respect to the stator **23**. The rotor **24** includes a rotor yoke **241** and a magnet **242**.

(187) The rotor yoke **241** is a member in a substantially cylindrical shape made of a magnetic material and having a lid on the axially inside. The rotor yoke **241** is fixed to the lower end portion (the other end portion in the axial direction) of the shaft **21**. The magnet **242** has a cylindrical shape and is fixed to an inner peripheral surface of the rotor yoke **241**. Due to this, the magnet **242** is disposed on the radially outside of the stator **23**.

(188) The circuit board **28** is in contact with the upper end (one end in the axial direction) of the insulator **233** and is disposed between the stator core **232** and the lid portion **27**. The circuit board **28** has a disk shape expanding in the radial direction about the rotation axis J, for example. The circuit board **28** has a board through hole **28a**. The board through hole **28a** is disposed on the rotation axis J and penetrates in the axial direction. The upper end portion (one end portion in the axial direction) of the bearing holding portion **231** is inserted into the board through hole **28a** and extends in the upper side X2 in the axial direction (one side in the axial direction) relative to the circuit board **28**.

(189) A conductive wire (not shown) constituting the coil **234** is electrically connected to the circuit board **28**. An electronic circuit for supplying a drive current to the coil **234** is mounted on the circuit board **28**. The circuit board **28** is connected to a lead wire **50** (see FIGS. **6** and **7**), and the lead wire **50** is pulled out to the outside of the stator accommodating portion **25** and connected to an external power source. The lead wire **50** is electrically connected to the coil **234**, and the lead wire **50** and the stator **23** are electrically connected. In the present example embodiment, three lead wires **50** are pulled out to the outside of the stator accommodating portion **25**.

(190) FIGS. **5** and **6** are a perspective view and a top view, respectively, of the motor **20**, and FIG. **7** is a longitudinal cross-sectional perspective view of the stator accommodating portion **25**. In FIGS. **5** and **6**, the rotor **24**, the seal **26**, and the lid portion **27** are not shown, and the elastic portion **29** is indicated by a dotted line. In FIG. **5**, the lead wire **50** is not shown, and in FIGS. **6** and **7**, the lead wire **50** is indicated by an alternate long and short dash line.

(191) The stator accommodating portion **25** is formed in a tubular shape and has the opening **25a** on one end surface in the axial direction (end surface on one side in the axial direction). The stator accommodating portion **25** internally accommodates the shaft **21**, the bearing **22**, the stator **23**, and the circuit board **28**. The stator accommodating portion **25** is filled with the seal **26** (see FIG. **4**). Due to this, the shaft **21**, the bearing **22**, the stator **23**, and the circuit board **28** are integrated, and the assembly workability of the motor **20** is improved.

(192) The stator core **232** is press-fitted into the inner peripheral surface of the stator

accommodating portion **25**. At this time, the radially outer surfaces of the teeth (not shown) come into contact with the inner peripheral surface of the stator accommodating portion **25**. The outer peripheral surface of the stator accommodating portion **25** opposes the magnet **242** in the radial direction with a gap interposed (see FIG. 3).

(193) The seal **26** is formed of a curable insulating resin or the like, and for example, an epoxy resin, silicone rubber, a polyurethane resin, or the like is used. The liquid seal **26** is filled inside the stator accommodating portion **25** from the opening **25a** and is cured after a predetermined time elapses. Due to this, the stator **23** and the circuit board **28** are covered with the cured seal **26**, and waterproof property, oil proof property, and the like of the stator **23** and the circuit board **28** are improved.

(194) The stator accommodating portion **25** includes a stator tube portion **251**, a board tube portion **252**, an intermediate tube portion **253**, an accommodating lid portion **254**, and an accommodating inclined portion **255**.

(195) The stator tube portion **251** surrounds the stator **23** from the radially outside. The board tube portion **252** surrounds the circuit board **28** from radially outside. The intermediate tube portion **253** couples the stator tube portion **251** and the board tube portion **252**.

(196) The accommodating lid portion **254** covers the stator **23** from the lower side **X1** in the axial direction (the other side in the axial direction) and expands in the radial direction. The accommodating lid portion **254** has an accommodating through hole **254a** and an accommodating holding portion **254b** penetrating in the axial direction. The lower end portion (the other end portion in the axial direction) of the bearing holding portion **231** is fitted into the accommodating through hole **254a** (see FIG. 3). Due to this, the stator accommodating portion **25** is fixed to the bearing holding portion **231**. The accommodating holding portion **254b** protrudes in the upper side **X2** in the axial direction (one side in the axial direction) from the peripheral edge of the accommodating through hole **254a**, and is formed in a tubular shape. The accommodating holding portion **254b** holds the lower end portion (the other end portion in the axial direction) of the bearing holding portion **231**.

(197) The board tube portion **252** has the accommodating recess **252a**. The accommodating recess **252a** is arranged in the upper end portion (one end portion in the axial direction) of the stator accommodating portion **25** and is recessed radially outward from the radially inner surface. In the radial direction, a gap **S** is formed between the radially outer edge of the circuit board **28** and the accommodating recess **252a**. In the present example embodiment, the accommodating recess **252a** has a part of the board tube portion **252** formed in a convex shape radially outside, and is provided at three places at equal intervals in the circumferential direction. The number of accommodating recesses **252a** is not limited to three. By providing the accommodating recess **252a**, the seal **26** can smoothly flow into the stator accommodating portion **25** from the gap **S**. This improves the assembling workability of the blower **1**.

(198) As viewed from the axial direction, at least a part of the accommodating recess **252a** overlaps the coupling part **403a** of the lid portion **27** (see FIG. 4). In the present example embodiment, the circumferential width of the accommodating recess **252a** is equal to or less than the circumferential width of the coupling part **403a**, and the entire accommodating recess **252a** overlaps the coupling part **403a** as viewed from the axial direction. This can reduce the airflow that passes through between the adjacent coupling parts **403a** and flows into the housing **40** from being disturbed in the vicinity of the accommodating recess **252a**. Therefore, the blowing efficiency of the blower **1** can be improved.

(199) The radial protrusion amount of the accommodating recess **252a** is $\frac{1}{2}$ or less of the radial size of the coupling part **403a**. This can further reduce the airflow that passes through between the adjacent coupling parts **403a** and flows into the housing **40** from being disturbed in the vicinity of the accommodating recess **252a**. It is preferable that the radial protrusion amount of the accommodating recess **252a** is smaller as long as a predetermined size of the gap **S** is secured.

(200) The intermediate tube portion **253** is inclined radially inward toward the lower side **X1** in the axial direction (the other side in the axial direction). This allows the seal **26** to smoothly flow into the stator tube portion **251** from the board tube portion **252** along the intermediate tube portion **253**. The resin amount of the seal **26** can be reduced, and the manufacturing cost can be reduced.

(201) The accommodating inclined portion **255** couples the stator tube portion **251** and the accommodating lid portion **254** and is inclined radially inward toward the lower side **X1** in the axial direction (the other side in the axial direction). This allows the seal **26** to smoothly flow into the radially inside of the accommodating lid portion **254** from the stator tube portion **251** along the accommodating inclined portion **255**.

(202) The stator accommodating portion **25** has an accommodating projection **251a** that protrudes from the radially inner surface and extends in the axial direction (see FIG. 7). In the present example embodiment, the accommodating projection **251a** is disposed on the radially inner surface of the stator tube portion **251**. The accommodating projection **251a** is fitted into a groove (not shown) formed on the radially outer surface of the stator core **232** and extending in the axial direction. This enables easy positioning in the circumferential direction of the stator core **232** in the stator accommodating portion **25**. In a state where the stator core **232** is accommodated in the stator accommodating portion **25**, the accommodating projection **251a** is press-fitted between teeth (not shown) adjacent in the circumferential direction.

(203) The stator accommodating portion **25** further includes a cutout **2521** and the pullout piece **2522**.

(204) The cutout **2521** is recessed from the upper end (one end in the axial direction) of the stator accommodating portion **25** to the lower side **X1** in the axial direction (the other side in the axial direction), and the lead wire **50** is pulled out radially outward (see FIG. 7).

(205) The pullout piece **2522** protrudes radially outward from the bottom of the cutout **2521**, and is formed in a plate shape. The elastic portion **29** in a rectangular parallelepiped shape is disposed on the upper surface (end surface on one side in the axial direction) of the pullout piece **2522**. The lead wire **50** is disposed on the upper surface (end surface on one side in the axial direction) of the elastic portion **29**. The upper end (one end in the axial direction) of the elastic portion **29** is disposed on the upper side **X2** in the axial direction (one side in the axial direction) relative to the upper end (one end in the axial direction) of the board tube portion **252**.

(206) Due to this, even when flowing out to the outside of the cutout **2521**, the seal **26** before being cured is dammed by the elastic portion **29**. Therefore, the seal **26** before being cured can be prevented from flowing out of the stator accommodating portion **25** via the cutout **2521**. At this time, the upper end (one end in the axial direction) of the elastic portion **29** is disposed on the upper side **X2** in the axial direction (one side in the axial direction) relative to the upper end (one end in the axial direction) of the cured seal **26**.

(207) The elastic portion **29** is fixed to the pullout piece **2522** via an adhesive layer **29a** (see FIG. 7). This allows the elastic portion **29** to be easily fixed to the pullout piece **2522**, and improves the assembling workability of the motor **20**. The elastic portion **29** is made of, for example, a rubber portion.

(208) By providing the pullout piece **2522**, the lead wire **50** can be pulled out radially outward while being supported by the pullout piece **2522** without being largely bent in the axial direction. Therefore, damage to the lead wire **50** can be prevented.

(209) The pullout piece **2522** includes a pullout inclined portion **2522a**, a pullout projection **2522b**, and a pair of pullout wall portions **2522c**. The pullout inclined portion **2522a** is inclined in the upper side **X2** in the axial direction (one side in the axial direction) toward radially outward from the bottom of the cutout **2521**. By providing the pullout inclined portion **2522a**, the seal **26** before being cured can be further prevented from flowing out to the outside of the stator accommodating portion **25** via the cutout **2521**.

(210) The pullout projection **2522b** is disposed adjacent to the radially outside of the cutout **2521**

and protrudes from the upper surface (end surface on one side in the axial direction) of the pullout piece **2522**. By providing the pullout projection **2522b**, the elastic portion **29** can be easily positioned.

(211) The pullout wall portion **2522c** protrudes in the upper side **X2** in the axial direction (one side in the axial direction) from both end portions in the radial direction of the pullout piece **2522** and extends in the radial direction. The radially inner end of the pullout wall portion **2522c** is coupled to the outer peripheral surface of the board tube portion **252**. The upper end (one end in the axial direction) of the pullout wall portion **2522c** is disposed in the upper side **X2** in the axial direction (one side in the axial direction) relative to the upper end (one end in the axial direction) of the board tube portion **252**. Due to this, the seal **26** before being cured can be further prevented from flowing out to the outside of the stator accommodating portion **25** via the cutout **2521**.

(212) The pullout piece **2522** is arranged to oppose the coupling part **403b** (lid portion **27**) in the axial direction. At this time, the lead wire **50** is sandwiched between the coupling part **403b** (lid portion **27**) and the pullout piece **2522** via the elastic portion **29**. At this time, the elastic portion **29** deforms along the outer peripheral surface of the lead wire **50**, and a minute gap is hardly generated between the lead wire **50** and the elastic portion **29**. This can prevent the seal **26** before being cured from passing through between the lead wire **50** and the elastic portion **29** due to a capillary phenomenon along the lead wire **50**. Therefore, the seal **26** can be prevented from flowing out to the outside of the stator accommodating portion **25**. This can provide the motor **20** that can prevent the seal **26** from flowing out.

(213) FIG. **8** is a longitudinal cross-sectional view schematically showing a part of the motor **20**. The upper end (one end in the axial direction) of the stator accommodating portion **25** is positioned in the lower side **X1** in the axial direction (the other side in the axial direction) relative to the lower end (the other end in the axial direction) of the lid portion **27** on the radially inside relative to the upper end (one end in the axial direction) of the stator accommodating portion **25**.

(214) There is a possibility that the seal **26** bulges and is cured in the upper side **X2** in the axial direction (one side in the axial direction) along the radially inner surface of the stator accommodating portion **25**, and a fillet is formed at the radially outer end portion of the seal **26**. The fillet does not bulge in the upper side **X2** of the axial direction (one side in the axial direction) beyond the upper end (one end in the axial direction) of the stator accommodating portion **25**. Due to this, even when a fillet is formed along the radially inner surface of the stator accommodating portion **25**, the upper end (one end in the axial direction) of the fillet is positioned in the lower side **X1** in the axial direction (the other side in the axial direction) relative to the lower end (the other end in the axial direction) of the lid portion **27**. Therefore, the lid portion **27** covering the opening **25a** and the seal **26** can be prevented from coming into contact with each other. This can downsize the motor **20** in the axial direction.

(215) In the present example embodiment, the seal **26** is filled up to the upper end (one end in the axial direction) of the stator accommodating portion **25**, and the upper end (one end in the axial direction) of the cured seal **26** is disposed at the same height in the axial direction as the upper side **X2** in the axial direction (one side in the axial direction) relative to the upper end (one end in the axial direction) of the stator accommodating portion **25** or the one end in the axial direction of the stator accommodating portion **25**. At this time, at the radially outer end portion of the seal **26**, a fillet is not formed along the radially inner surface of the stator accommodating portion **25**. Therefore, it is possible to reduce variation, for each product, in the height of the upper end (end surface on one side in the axial direction) of the seal **26**. This allows the lid portion **27** to be disposed close to the upper end (one end in the axial direction) of the stator accommodating portion **25** while preventing the lid portion **27** and the seal **26** from coming into contact with each other. Therefore, it is possible to further downsize the motor **20** in the axial direction.

(216) The upper end surface (end surface on one side in the axial direction) of the seal **26** is formed orthogonal to the axial direction. This allows the lid portion **27** to be disposed closer to the upper

end (one end in the axial direction) of the stator accommodating portion **25**.

(217) When the upper end (one end in the axial direction) of the cured seal **26** is disposed in the lower side **X1** in the axial direction (the other side in the axial direction) relative to the upper end (one end in the axial direction) of the stator accommodating portion **25**, the upper end (one end in the axial direction) of the stator accommodating portion **25** can be disposed close to the lid portion **27**. At this time, the coupling recess **405a** is formed in the lower end surface (the end surface on the other side in the axial direction) of the coupling part **403a**, and it is possible to prevent the upper end (one end in the axial direction) of the stator accommodating portion **25** and the lid portion **27** from coming into contact with each other.

(218) The upper end (one end in the axial direction) of the bearing holding portion **231** extends to the upper side **X2** in the axial direction (one side in the axial direction) relative to the upper end (one end in the axial direction) of the stator accommodating portion **25** and is fixed to the lid portion **27**. This allows the lid portion **27** and the stator accommodating portion **25** to be easily fixed with a small number of components via the bearing holding portion **231** in a state where the lid portion **27** and the upper end portion of the stator accommodating portion **25** filled with the seal **26** are not in contact with each other.

(219) The bearing holding portion **231** has a holding protrusion **2311**. The holding protrusion **2311** is disposed the upper side **X2** in the axial direction (one side in the axial direction) relative to the upper end (one end in the axial direction) of the circuit board **28**. The holding protrusion **2311** protrudes radially outward from the radially outer surface and is formed in an annular shape. The lower end (the other end in the axial direction) of the holding protrusion **2311** is positioned at substantially the same height as the upper end (one end in the axial direction) of the stator accommodating portion **25** in the axial direction. The holding protrusion **2311** may be integrated with or separated from the bearing holding portion **231**. When the holding protrusion **2311** is separated from the bearing holding portion **231**, the holding protrusion **2311** is attached to the bearing holding portion **231** after the circuit board **28** is disposed on the upper end (one end in the axial direction) of the insulator **233**. This improves assembly workability of the circuit board **28**.

(220) When the seal **26** is about to be cured bulging to the upper side **X2** in the axial direction (one side in the axial direction) along the radially outer surface of the bearing holding portion **231**, the holding protrusion **2311** can suppress rise of the seal **26**. This can prevent the lid portion **27** covering the opening **25a** and the seal **26** from coming into contact with each other. By arranging the lower end (the other end in the axial direction) of the holding protrusion **2311** at substantially the same height as the upper end (one end in the axial direction) of the stator accommodating portion **25** in the axial direction, the upper end surface (the end surface on one side in the axial direction) of the seal **26** orthogonal to the axial direction can be easily formed when the seal **26** is filled up to the upper end (one end in the axial direction) of the stator accommodating portion **25**.

(221) The radially outer end of the holding protrusion **2311** is positioned radially outside relative to the peripheral edge of the board through hole **28a**. Due to this, the holding protrusion **2311** further protrudes radially outward, and the rise of the seal **26** can be more reliably suppressed.

(222) The holding protrusion **2311** has a curved surface **2312**. The curved surface **2312** is disposed at the other end portion in the axial direction of the holding protrusion **2311**, is inclined to the upper side **X2** in the axial direction (one side in the axial direction) toward the radially outside, and is curved convexly toward the radially outside. This allows the holding protrusion **2311** to more reliably suppress the rise of the seal **26**.

(223) A plurality of grooves **2311a** are formed on the radially outer surface of the holding protrusion **2311**. Forming the groove **2311a** makes it difficult to form a fillet along the radially outer surface of the holding protrusion **2311** when the seal **26** is cured. Therefore, the holding protrusion **2311** can suppress rise of the seal **26** more reliably. The groove **2311a** is formed by knurling, for example.

(224) Next, the second example embodiment of the present disclosure will be described. FIG. **9** is a

longitudinal cross-sectional view schematically showing a part of the motor **20**. For the sake of convenience in description, the same reference numerals are given to the same parts as those of the first example embodiment shown in FIGS. **1** to **8**. The second example embodiment is different from the first example embodiment in that an oil repellent layer **2313** is formed on a radially outer surface of the bearing holding portion **231** in place of the holding protrusion **2311**. Other parts are the same as those in the first example embodiment.

(225) The oil repellent layer **2313** is disposed in the upper side X2 in the axial direction (one side in the axial direction) relative to the upper end (one end in the axial direction) of the circuit board **28**. The oil repellent layer **2313** includes, for example, a fluororesin, and repels the seal **26**.

(226) Due to this, the seal **26** is repelled by the oil repellent layer **2313** when the seal **26** is about to be cured bulging to the upper side in the axial direction (one side in the axial direction) along the radially outer surface of the bearing holding portion **231**. Therefore, the oil repellent layer **2313** can suppress rise of the seal **26**. This can prevent the lid portion **27** covering the opening **25a** and the seal **26** from coming into contact with each other.

(227) The lower end (the other end in the axial direction) of the oil repellent layer **2313** is positioned at substantially the same height as the upper end (one end in the axial direction) of the stator accommodating portion **25** in the axial direction. Due to this, the upper end surface (the end surface on one side in the axial direction) of the seal **26** orthogonal to the axial direction can be easily formed when the seal **26** is filled up to the upper end (one end in the axial direction) of the stator accommodating portion **25**. While the oil repellent layer **2313** is formed on the radially outer surface of the bearing holding portion **231** in the present example embodiment, the oil repellent layer **2313** may be formed on the radially outer surface of the holding protrusion **2311** of the first example embodiment.

(228) Next, the third example embodiment of the present disclosure will be described. FIG. **10** is a longitudinal cross-sectional view schematically showing a part of the motor **20**. For the sake of convenience in description, the same reference numerals are given to the same parts as those of the first example embodiment shown in FIGS. **1** to **8**. The third example embodiment is different from the first example embodiment in the position of the holding protrusion **2311**. Other parts are the same as those in the first example embodiment.

(229) The upper end (one end in the axial direction) of the holding protrusion **2311** is positioned at substantially the same height as one end in the axial direction of the stator accommodating portion **25** in the axial direction. When the seal **26** is filled up to the upper end (one end in the axial direction) of the stator accommodating portion **25**, the seal **26** is hardly cured bulging to the upper side X2 in the axial direction (one side in the axial direction) along the radially outer surface of the bearing holding portion **231** from the upper end of the holding protrusion **2311**. Therefore, at the radially inner end portion of the seal **26**, a fillet is not formed along the radially outer surface of the bearing holding portion **231** beyond the holding protrusion **2311**. Therefore, it is possible to reduce variation, for each product, in the height of the upper end (end surface on one side in the axial direction) of the seal **26**.

(230) The holding protrusion **2311** may be integrated with or separated from the bearing holding portion **231**. When the holding protrusion **2311** is separated from the bearing holding portion **231**, the holding protrusion **2311** is attached to the bearing holding portion **231** after the circuit board **28** is disposed on the upper end (one end in the axial direction) of the insulator **233**. This improves assembly workability of the circuit board **28**.

(231) The example embodiments of the present disclosure have been described above. The scope of the present disclosure is not limited to the above-described example embodiments. The present disclosure can be implemented with various modifications within a scope not departing from the gist of the disclosure. The above-described example embodiments can be appropriately and optionally combined. For example, the oil repellent layer **2313** may be formed on the radially outer surface of the bearing holding portion **231** in which the groove **2311a** of the first example

embodiment is formed.

(232) Hereinafter, exemplary example embodiments of a fourth aspect of the present disclosure will be described in detail with reference to the drawings.

(233) (1)

(234) A blower including: a rotor that rotates about a rotation axis; a stator that opposes the rotor with a gap interposed radially inward; a circuit board connected to the stator and disposed on one side in an axial direction of the stator; a stator accommodating portion in a tubular shape that accommodates the stator and the circuit board and has an opening on one end surface in the axial direction; a seal filled in the stator accommodating portion; a lid portion that covers the opening; an impeller that is fixed to the rotor and generates an airflow in the axial direction; and a housing body portion that is formed in a tubular shape extending along the rotation axis, has both end surfaces in the axial direction opened, and accommodates the stator accommodating portion and the impeller, the stator accommodating portion includes an accommodating recess disposed in one end portion in the axial direction and recessed radially outward from a radially inner surface, and

(235) a gap is formed between a radially outer edge of the circuit board and the accommodating recess in a radial direction.

(236) (2)

(237) The stator accommodating portion includes a stator tube portion that surrounds the stator from radially outside, a board tube portion that surrounds the circuit board from radially outside, and an intermediate tube portion that couples the stator tube portion and the board tube portion, the accommodating recess has a part of the board tube portion formed in a convex shape radially outside, the lid portion includes a fixing part in a plate shape that is disposed to oppose the opening in the axial direction and to which the stator is fixed, and a plurality of coupling parts extending radially outward from the fixing part, arranged in a circumferential direction, and coupling the fixing part and the housing body portion, and at least a part of the accommodating recess overlaps the coupling part as viewed from the axial direction.

(3)

(238) The intermediate tube portion is inclined radially inward toward another side in the axial direction.

(239) (4)

(240) The radial protrusion amount of the accommodating recess is $\frac{1}{2}$ or less of a radial size of the coupling part.

(241) (5)

(242) A circumferential width of the accommodating recess is equal to or less than a circumferential width of the coupling part.

(243) (6)

(244) The coupling part is formed to be inclined to one side in the circumferential direction from a radially inner end toward a radially outside.

(245) (7)

(246) The coupling part includes a coupling recess that is disposed to oppose the stator accommodating portion in the axial direction and is recessed on one side in the axial direction from an end surface on another side in the axial direction.

(8)

(247) The stator accommodating portion further includes an accommodating lid portion that covers the stator from another side in the axial direction and expands in a radial direction, and an accommodating inclined portion that couples the first tube portion and the accommodating lid portion and is inclined radially inward toward the other side in the axial direction.

(248) FIGS. 1 and 2 are a perspective view and an exploded perspective view, respectively, of an example of the blower 1 according to the first example embodiment of the present disclosure. The blower 1 includes a motor 20, an impeller 30, and a housing 40.

(249) The impeller **30** is fixed to the motor **20** and rotates about the rotation axis J to generate an airflow on the lower side Z1 in the axial direction (the other side in the axial direction) along the rotation axis J.

(250) The housing **40** is formed in a tubular shape extending along the rotation axis J, and has a blowing flow path **41** in which both end surfaces in the axial direction are opened and an airflow internally circulates. The motor **20** and the impeller **30** are accommodated inside the housing **40**. The housing **40** has an exhaust port **42** on a lower end surface (the other end surface in the axial direction) (see FIG. 3) and an intake port **43** on an upper end side (one end surface in the axial direction).

(251) The housing **40** is configured by axially coupling an upper housing part **40a** and a lower housing part **40b**. The upper housing part **40a** and the lower housing part **40b** are resin molded articles. In the present example embodiment, the housing **40** can be divided into the upper housing part **40a** and the lower housing part **40b**, but the upper housing part **40a** and the lower housing part **40b** may be integrally formed. The upper housing part **40a** includes an upper body portion **401a**, a fixing part **402a**, and coupling parts **403a** and **403b**. The upper body portion **401a** extends in the axial direction and is formed in a tubular shape.

(252) The fixing part **402a** and the coupling parts **403a** and **403b** constitute a lid portion **27** that covers an opening **25a** (see FIG. 4) of a stator accommodating portion **25** described below. The lid portion **27** is a part of the housing **40** and also a part of the motor **20**. The fixing part **402a** is arranged on an upper side Z2 in the axial direction (one side in the axial direction) of the stator accommodating portion **25** described below, and has a disk shape expanding in the radial direction about the rotation axis J. A stator **23** described below of the motor **20** is fixed to the fixing part **402a**. That is, the fixing part **402a** is formed in a plate shape to which the stator **23** is fixed.

(253) The coupling parts **403a** and **403b** extend radially outward from the fixing part **402a** and couple the fixing part **402a** and a housing body portion **40c**. A plurality of the coupling parts **403a** are arranged in the circumferential direction and axially opposes an accommodating recess **252a** described below. The coupling part **403b** is disposed at one position in the circumferential direction and axially opposes a pullout piece **2522** described below. The air circulating through the blowing flow path **41** passes through between the adjacent coupling parts **403a** and **403b**.

(254) The coupling part **403a** is formed to be inclined to one side in the circumferential direction from the radially inner end toward the radially outside. Due to this, the airflow flowing into the housing **40** from the intake port **43** smoothly circulates along the coupling part **403a**. Therefore, the blowing efficiency of the blower **1** can be further improved. The coupling part **403a** may be formed to be inclined to the other side in the circumferential direction from the radially inner end toward the radially outside. The coupling part **403a** may be formed to extend linearly in the radial direction. The coupling part **403b** is formed to extend linearly in the radial direction.

(255) The coupling part **403a** has a coupling recess **405a** (see FIG. 4). The coupling recess **405a** is disposed to oppose the stator accommodating portion **25** in the axial direction, and is recessed to the one side in the axial direction from the lower end surface (end surface on the other side in the axial direction) of the coupling part **403a**. This can prevent the stator accommodating portion **25** from coming into contact with the coupling part **403** when swung in the axial direction.

(256) The lower housing part **40b** has a lower body portion **401b** that extends in the axial direction and is formed in a tubular shape. The lower body portion **401b** and the upper body portion **401a** are coupled in the axial direction to constitute the housing body portion **40c**. That is, the blower **1** includes the housing body portion **40c**, and the housing body portion **40c** is formed in a tubular shape extending along the rotation axis J, and internally has the blowing flow path **41** with both end surfaces in the axial direction opened. The motor **20** and the impeller **30** are accommodated inside the housing body portion **40c**.

(257) The impeller **30** includes an impeller cup **31** and a plurality of blades **32**. The impeller cup **31** is fixed to a radially outside of a rotor **24** described below of the motor **20**. The plurality of blades

32 are arrayed in the circumferential direction on a radially outer surface of the impeller cup **31**. (258) FIG. 3 is a longitudinal cross-sectional perspective view of the blower **1**, and FIG. 4 is a longitudinal cross-sectional perspective view showing a part of the blower **1** in an enlarged manner. The motor **20** includes a shaft **21**, a bearing **22**, the stator **23**, the rotor **24**, the stator accommodating portion **25**, a seal **26**, the above-described lid portion **27**, and a circuit board **28**. (259) The shaft **21** extends along the rotation axis J. The shaft **21** is a columnar member that is made of metal such as stainless steel and extends in the axial direction. (260) The bearings **22** are arranged in a pair at least spaced apart in the axial direction. The bearing **22** is configured by, for example, a ball bearing, but may be configured by a sleeve bearing or the like. The pair of bearings **22** support the shaft **21** so as to be rotatable about the rotation axis J with respect to the stator **23**. (261) The stator **23** opposes the rotor **24** with a gap interposed radially inward. The stator **23** includes a bearing holding portion **231**, a stator core **232**, an insulator **233**, and a coil **234**. The bearing holding portion **231** is formed in a cylindrical shape and internally holds the bearing **22**. (262) An upper end portion (one end portion in the axial direction) of the bearing holding portion **231** is fitted via a connector **45** into a fitting hole **404a** of the fixing part **402a**. Due to this, the bearing holding portion **231** is fixed to the fixing part **402a**, and the stator **23** and the housing **40** are fixed. The fitting hole **404a** is formed to penetrate the fixing part **402a** in the axial direction. The connector **45** is formed in an annular shape and is disposed on the inner peripheral surface of the fitting hole **404a**. The bearing holding portion **231** is disposed on the inner peripheral surface of the connector **45**. A lower end portion (the other end portion in the axial direction) of the bearing holding portion **231** is fixed to the stator accommodating portion **25** described below. The upper end portion (one end portion in the axial direction) of the bearing holding portion **231** may be directly fitted into the fitting hole **404a** without the connector **45**. (263) The stator core **232** is formed by vertically stacking electromagnetic steel plates such as silicon steel plates. The insulator **233** is made of an insulating resin. The stator core **232** includes an annular core back (not shown) and a plurality of teeth (not shown) protruding radially outward from the core back and arranged in the circumferential direction. The insulator **233** is provided on a part of the outer surface in the axial direction of the teeth and a part of the outer surface in the circumferential direction of the teeth. The insulator **233** is provided surrounding an outer surface of the stator core **232**. The coil **234** is formed of a conductive wire wound around the stator core **232** via the insulator **233**. (264) The rotor **24** rotates about the rotation axis J with respect to the stator **23**. The rotor **24** includes a rotor yoke **241** and a magnet **242**. (265) The rotor yoke **241** is a member in a substantially cylindrical shape made of a magnetic material and having a lid on the axially inside. The rotor yoke **241** is fixed to the lower end portion (the other end portion in the axial direction) of the shaft **21**. The magnet **242** has a cylindrical shape and is fixed to an inner peripheral surface of the rotor yoke **241**. Due to this, the magnet **242** is disposed on the radially outside of the stator **23**. (266) The circuit board **28** is in contact with the upper end (one end in the axial direction) of the insulator **233** and is disposed between the stator core **232** and the lid portion **27**. The circuit board **28** has a disk shape expanding in the radial direction about the rotation axis J, for example. The circuit board **28** has a board through hole **28a**. The board through hole **28a** is disposed on the rotation axis J and penetrates in the axial direction. The upper end portion (one end portion in the axial direction) of the bearing holding portion **231** is inserted into the board through hole **28a** and extends in the upper side Z2 in the axial direction (one side in the axial direction) relative to the circuit board **28**. (267) A conductive wire (not shown) constituting the coil **234** is electrically connected to the circuit board **28**. An electronic circuit for supplying a drive current to the coil **234** is mounted on the circuit board **28**. The circuit board **28** is connected to a lead wire **50** (see FIGS. 6 and 7), and the

lead wire **50** is pulled out to the outside of the stator accommodating portion **25** and connected to an external power source. The lead wire **50** is electrically connected to the coil **234**, and the lead wire **50** and the stator **23** are electrically connected. In the present example embodiment, three lead wires **50** are pulled out to the outside of the stator accommodating portion **25**.

(268) FIGS. **5** and **6** are a perspective view and a top view, respectively, of the motor **20**, and FIG. **7** is a longitudinal cross-sectional perspective view of the stator accommodating portion **25**. In FIGS. **5** and **6**, the rotor **24**, the seal **26**, and the lid portion **27** are not shown, and the elastic portion **29** is indicated by a dotted line. In FIG. **5**, the lead wire **50** is not shown, and in FIGS. **6** and **7**, the lead wire **50** is indicated by an alternate long and short dash line.

(269) The stator accommodating portion **25** is formed in a tubular shape and has the opening **25a** on one end surface in the axial direction (end surface on one side in the axial direction). The stator accommodating portion **25** internally accommodates the shaft **21**, the bearing **22**, the stator **23**, and the circuit board **28**. The stator accommodating portion **25** is filled with the seal **26** (see FIG. **4**). Due to this, the shaft **21**, the bearing **22**, the stator **23**, and the circuit board **28** are integrated, and the assembly workability of the motor **20** is improved.

(270) The stator core **232** is press-fitted into the inner peripheral surface of the stator accommodating portion **25**. At this time, the radially outer surfaces of the teeth (not shown) come into contact with the inner peripheral surface of the stator accommodating portion **25**. The outer peripheral surface of the stator accommodating portion **25** opposes the magnet **242** in the radial direction with a gap interposed (see FIG. **3**).

(271) The seal **26** is formed of a curable insulating resin or the like, and for example, an epoxy resin, silicone rubber, a polyurethane resin, or the like is used. The liquid seal **26** is filled inside the stator accommodating portion **25** from the opening **25a** and is cured after a predetermined time elapses. Due to this, the stator **23** and the circuit board **28** are covered with the cured seal **26**, and waterproof property, oil proof property, and the like of the stator **23** and the circuit board **28** are improved.

(272) The stator accommodating portion **25** includes a stator tube portion **251**, a board tube portion **252**, an intermediate tube portion **253**, an accommodating lid portion **254**, and an accommodating inclined portion **255**.

(273) The stator tube portion **251** surrounds the stator **23** from the radially outside. The board tube portion **252** surrounds the circuit board **28** from radially outside. The intermediate tube portion **253** couples the stator tube portion **251** and the board tube portion **252**.

(274) The accommodating lid portion **254** covers the stator **23** from the lower side **Z1** in the axial direction (the other side in the axial direction) and expands in the radial direction. The accommodating lid portion **254** has an accommodating through hole **254a** and an accommodating holding portion **254b** penetrating in the axial direction. The lower end portion (the other end portion in the axial direction) of the bearing holding portion **231** is fitted into the accommodating through hole **254a** (see FIG. **3**). Due to this, the stator accommodating portion **25** is fixed to the bearing holding portion **231**. The accommodating holding portion **254b** protrudes in the upper side **Z2** in the axial direction (one side in the axial direction) from the peripheral edge of the accommodating through hole **254a**, and is formed in a tubular shape. The accommodating holding portion **254b** holds the lower end portion (the other end portion in the axial direction) of the bearing holding portion **231**.

(275) The board tube portion **252** has the accommodating recess **252a**. The accommodating recess **252a** is arranged in the upper end portion (one end portion in the axial direction) of the stator accommodating portion **25** and is recessed radially outward from the radially inner surface. In the radial direction, a gap **S** is formed between the radially outer edge of the circuit board **28** and the accommodating recess **252a**. In the present example embodiment, the accommodating recess **252a** has a part of the board tube portion **252** formed in a convex shape radially outside, and is provided at three places at equal intervals in the circumferential direction. The number of accommodating

recesses **252a** is not limited to three. By providing the accommodating recess **252a**, the seal **26** can smoothly flow into the stator accommodating portion **25** from the gap S. This improves the assembling workability of the blower **1**.

(276) As viewed from the axial direction, at least a part of the accommodating recess **252a** overlaps the coupling part **403a** of the lid portion **27** (see FIG. 4). In the present example embodiment, the circumferential width of the accommodating recess **252a** is equal to or less than the circumferential width of the coupling part **403a**, and the entire accommodating recess **252a** overlaps the coupling part **403a** as viewed from the axial direction. This can reduce the airflow that passes through between the adjacent coupling parts **403a** and flows into the housing **40** from being disturbed in the vicinity of the accommodating recess **252a**. Therefore, the blowing efficiency of the blower **1** can be improved.

(277) The radial protrusion amount of the accommodating recess **252a** is $\frac{1}{2}$ or less of the radial size of the coupling part **403a**. This can further reduce the airflow that passes through between the adjacent coupling parts **403a** and flows into the housing **40** from being disturbed in the vicinity of the accommodating recess **252a**. It is preferable that the radial protrusion amount of the accommodating recess **252a** is smaller as long as a predetermined size of the gap S is secured.

(278) The intermediate tube portion **253** is inclined radially inward toward the lower side **Z1** in the axial direction (the other side in the axial direction). This allows the seal **26** to smoothly flow into the stator tube portion **251** from the board tube portion **252** along the intermediate tube portion **253**. The resin amount of the seal **26** can be reduced, and the manufacturing cost can be reduced.

(279) The accommodating inclined portion **255** couples the stator tube portion **251** and the accommodating lid portion **254** and is inclined radially inward toward the lower side **Z1** in the axial direction (the other side in the axial direction). This allows the seal **26** to smoothly flow into the radially inside of the accommodating lid portion **254** from the stator tube portion **251** along the accommodating inclined portion **255**.

(280) The stator accommodating portion **25** has an accommodating projection **251a** that protrudes from the radially inner surface and extends in the axial direction (see FIG. 7). In the present example embodiment, the accommodating projection **251a** is disposed on the radially inner surface of the stator tube portion **251**. The accommodating projection **251a** is fitted into a groove (not shown) formed on the radially outer surface of the stator core **232** and extending in the axial direction. This enables easy positioning in the circumferential direction of the stator core **232** in the stator accommodating portion **25**. In a state where the stator core **232** is accommodated in the stator accommodating portion **25**, the accommodating projection **251a** is press-fitted between teeth (not shown) adjacent in the circumferential direction.

(281) The stator accommodating portion **25** further includes a cutout **2521** and the pullout piece **2522**.

(282) The cutout **2521** is recessed from the upper end (one end in the axial direction) of the stator accommodating portion **25** to the lower side **Z1** in the axial direction (the other side in the axial direction), and the lead wire **50** is pulled out radially outward (see FIG. 7).

(283) The pullout piece **2522** protrudes radially outward from the bottom of the cutout **2521**, and is formed in a plate shape. The elastic portion **29** in a rectangular parallelepiped shape is disposed on the upper surface (end surface on one side in the axial direction) of the pullout piece **2522**. The lead wire **50** is disposed on the upper surface (end surface on one side in the axial direction) of the elastic portion **29**. The upper end (one end in the axial direction) of the elastic portion **29** is disposed on the upper side **Z2** in the axial direction (one side in the axial direction) relative to the upper end (one end in the axial direction) of the board tube portion **252**.

(284) Due to this, even when flowing out to the outside of the cutout **2521**, the seal **26** before being cured is dammed by the elastic portion **29**. Therefore, the seal **26** before being cured can be prevented from flowing out of the stator accommodating portion **25** via the cutout **2521**. At this time, the upper end (one end in the axial direction) of the elastic portion **29** is disposed on the upper

side **Z2** in the axial direction (one side in the axial direction) relative to the upper end (one end in the axial direction) of the cured seal **26**.

(285) The elastic portion **29** is fixed to the pullout piece **2522** via an adhesive layer **29a** (see FIG. 7). This allows the elastic portion **29** to be easily fixed to the pullout piece **2522**, and improves the assembling workability of the motor **20**. The elastic portion **29** is made of, for example, a rubber portion.

(286) By providing the pullout piece **2522**, the lead wire **50** can be pulled out radially outward while being supported by the pullout piece **2522** without being largely bent in the axial direction. Therefore, damage to the lead wire **50** can be prevented.

(287) The pullout piece **2522** includes a pullout inclined portion **2522a**, a pullout projection **2522b**, and a pair of pullout wall portions **2522c**. The pullout inclined portion **2522a** is inclined in the upper side **Z2** in the axial direction (one side in the axial direction) toward radially outward from the bottom of the cutout **2521**. By providing the pullout inclined portion **2522a**, the seal **26** before being cured can be further prevented from flowing out to the outside of the stator accommodating portion **25** via the cutout **2521**.

(288) The pullout projection **2522b** is disposed adjacent to the radially outside of the cutout **2521** and protrudes from the upper surface (end surface on one side in the axial direction) of the pullout piece **2522**. By providing the pullout projection **2522b**, the elastic portion **29** can be easily positioned.

(289) The pullout wall portion **2522c** protrudes in the upper side **Z2** in the axial direction (one side in the axial direction) from both end portions in the radial direction of the pullout piece **2522** and extends in the radial direction. The radially inner end of the pullout wall portion **2522c** is coupled to the outer peripheral surface of the board tube portion **252**. The upper end (one end in the axial direction) of the pullout wall portion **2522c** is disposed in the upper side **Z2** in the axial direction (one side in the axial direction) relative to the upper end (one end in the axial direction) of the board tube portion **252**. Due to this, the seal **26** before being cured can be further prevented from flowing out to the outside of the stator accommodating portion **25** via the cutout **2521**.

(290) The pullout piece **2522** is arranged to oppose the coupling part **403b** (lid portion **27**) in the axial direction. At this time, the lead wire **50** is sandwiched between the coupling part **403b** (lid portion **27**) and the pullout piece **2522** via the elastic portion **29**. At this time, the elastic portion **29** deforms along the outer peripheral surface of the lead wire **50**, and a minute gap is hardly generated between the lead wire **50** and the elastic portion **29**. This can prevent the seal **26** before being cured from passing through between the lead wire **50** and the elastic portion **29** due to a capillary phenomenon along the lead wire **50**. Therefore, the seal **26** can be prevented from flowing out to the outside of the stator accommodating portion **25**. This can provide the motor **20** that can prevent the seal **26** from flowing out.

(291) FIG. **8** is a longitudinal cross-sectional view schematically showing a part of the motor **20**. The upper end (one end in the axial direction) of the stator accommodating portion **25** is positioned in the lower side **Z1** in the axial direction (the other side in the axial direction) relative to the lower end (the other end in the axial direction) of the lid portion **27** on the radially inside relative to the upper end (one end in the axial direction) of the stator accommodating portion **25**.

(292) There is a possibility that the seal **26** bulges and is cured in the upper side **Z2** in the axial direction (one side in the axial direction) along the radially inner surface of the stator accommodating portion **25**, and a fillet is formed at the radially outer end portion of the seal **26**. The fillet does not bulge in the upper side **Z2** of the axial direction (one side in the axial direction) beyond the upper end (one end in the axial direction) of the stator accommodating portion **25**. Due to this, even when a fillet is formed along the radially inner surface of the stator accommodating portion **25**, the upper end (one end in the axial direction) of the fillet is positioned in the lower side **Z1** in the axial direction (the other side in the axial direction) relative to the lower end (the other end in the axial direction) of the lid portion **27**. Therefore, the lid portion **27** covering the opening

25a and the seal **26** can be prevented from coming into contact with each other. This can downsize the motor **20** in the axial direction.

(293) In the present example embodiment, the seal **26** is filled up to the upper end (one end in the axial direction) of the stator accommodating portion **25**, and the upper end (one end in the axial direction) of the cured seal **26** is disposed at the same height in the axial direction as the upper side **Z2** in the axial direction (one side in the axial direction) relative to the upper end (one end in the axial direction) of the stator accommodating portion **25** or the one end in the axial direction of the stator accommodating portion **25**. At this time, at the radially outer end portion of the seal **26**, a fillet is not formed along the radially inner surface of the stator accommodating portion **25**.

Therefore, it is possible to reduce variation, for each product, in the height of the upper end (end surface on one side in the axial direction) of the seal **26**. This allows the lid portion **27** to be disposed close to the upper end (one end in the axial direction) of the stator accommodating portion **25** while preventing the lid portion **27** and the seal **26** from coming into contact with each other. Therefore, it is possible to further downsize the motor **20** in the axial direction.

(294) The upper end surface (end surface on one side in the axial direction) of the seal **26** is formed orthogonal to the axial direction. This allows the lid portion **27** to be disposed closer to the upper end (one end in the axial direction) of the stator accommodating portion **25**.

(295) When the upper end (one end in the axial direction) of the cured seal **26** is disposed in the lower side **Z1** in the axial direction (the other side in the axial direction) relative to the upper end (one end in the axial direction) of the stator accommodating portion **25**, the upper end (one end in the axial direction) of the stator accommodating portion **25** can be disposed close to the lid portion **27**. At this time, the coupling recess **405a** is formed in the lower end surface (the end surface on the other side in the axial direction) of the coupling part **403a**, and it is possible to prevent the upper end (one end in the axial direction) of the stator accommodating portion **25** and the lid portion **27** from coming into contact with each other.

(296) The upper end (one end in the axial direction) of the bearing holding portion **231** extends to the upper side **Z2** in the axial direction (one side in the axial direction) relative to the upper end (one end in the axial direction) of the stator accommodating portion **25** and is fixed to the lid portion **27**. This allows the lid portion **27** and the stator accommodating portion **25** to be easily fixed with a small number of components via the bearing holding portion **231** in a state where the lid portion **27** and the upper end portion of the stator accommodating portion **25** filled with the seal **26** are not in contact with each other.

(297) The bearing holding portion **231** has a holding protrusion **2311**. The holding protrusion **2311** is disposed the upper side **Z2** in the axial direction (one side in the axial direction) relative to the upper end (one end in the axial direction) of the circuit board **28**. The holding protrusion **2311** protrudes radially outward from the radially outer surface and is formed in an annular shape. The lower end (the other end in the axial direction) of the holding protrusion **2311** is positioned at substantially the same height as the upper end (one end in the axial direction) of the stator accommodating portion **25** in the axial direction. The holding protrusion **2311** may be integrated with or separated from the bearing holding portion **231**. When the holding protrusion **2311** is separated from the bearing holding portion **231**, the holding protrusion **2311** is attached to the bearing holding portion **231** after the circuit board **28** is disposed on the upper end (one end in the axial direction) of the insulator **233**. This improves assembly workability of the circuit board **28**.

(298) When the seal **26** is about to be cured bulging to the upper side **Z2** in the axial direction (one side in the axial direction) along the radially outer surface of the bearing holding portion **231**, the holding protrusion **2311** can suppress rise of the seal **26**. This can prevent the lid portion **27** covering the opening **25a** and the seal **26** from coming into contact with each other. By arranging the lower end (the other end in the axial direction) of the holding protrusion **2311** at substantially the same height as the upper end (one end in the axial direction) of the stator accommodating portion **25** in the axial direction, the upper end surface (the end surface on one side in the axial

direction) of the seal **26** orthogonal to the axial direction can be easily formed when the seal **26** is filled up to the upper end (one end in the axial direction) of the stator accommodating portion **25**.

(299) The radially outer end of the holding protrusion **2311** is positioned radially outside relative to the peripheral edge of the board through hole **28a**. Due to this, the holding protrusion **2311** further protrudes radially outward, and the rise of the seal **26** can be more reliably suppressed.

(300) The holding protrusion **2311** has a curved surface **2312**. The curved surface **2312** is disposed at the other end portion in the axial direction of the holding protrusion **2311**, is inclined to the upper side **Z2** in the axial direction (one side in the axial direction) toward the radially outside, and is curved convexly toward the radially outside. This allows the holding protrusion **2311** to more reliably suppress the rise of the seal **26**.

(301) A plurality of grooves **2311a** are formed on the radially outer surface of the holding protrusion **2311**. Forming the groove **2311a** makes it difficult to form a fillet along the radially outer surface of the holding protrusion **2311** when the seal **26** is cured. Therefore, the holding protrusion **2311** can suppress rise of the seal **26** more reliably. The groove **2311a** is formed by knurling, for example.

(302) Next, the second example embodiment of the present disclosure will be described. FIG. **9** is a longitudinal cross-sectional view schematically showing a part of the motor **20**. For the sake of convenience in description, the same reference numerals are given to the same parts as those of the first example embodiment shown in FIGS. **1** to **8**. The second example embodiment is different from the first example embodiment in that an oil repellent layer **2313** is formed on a radially outer surface of the bearing holding portion **231** in place of the holding protrusion **2311**. Other parts are the same as those in the first example embodiment.

(303) The oil repellent layer **2313** is disposed in the upper side **Z2** in the axial direction (one side in the axial direction) relative to the upper end (one end in the axial direction) of the circuit board **28**. The oil repellent layer **2313** includes, for example, a fluororesin, and repels the seal **26**.

(304) Due to this, the seal **26** is repelled by the oil repellent layer **2313** when the seal **26** is about to be cured bulging to the upper side in the axial direction (one side in the axial direction) along the radially outer surface of the bearing holding portion **231**. Therefore, the oil repellent layer **2313** can suppress rise of the seal **26**. This can prevent the lid portion **27** covering the opening **25a** and the seal **26** from coming into contact with each other.

(305) The lower end (the other end in the axial direction) of the oil repellent layer **2313** is positioned at substantially the same height as the upper end (one end in the axial direction) of the stator accommodating portion **25** in the axial direction. Due to this, the upper end surface (the end surface on one side in the axial direction) of the seal **26** orthogonal to the axial direction can be easily formed when the seal **26** is filled up to the upper end (one end in the axial direction) of the stator accommodating portion **25**. While the oil repellent layer **2313** is formed on the radially outer surface of the bearing holding portion **231** in the present example embodiment, the oil repellent layer **2313** may be formed on the radially outer surface of the holding protrusion **2311** of the first example embodiment.

(306) Next, the third example embodiment of the present disclosure will be described. FIG. **10** is a longitudinal cross-sectional view schematically showing a part of the motor **20**. For the sake of convenience in description, the same reference numerals are given to the same parts as those of the first example embodiment shown in FIGS. **1** to **8**. The third example embodiment is different from the first example embodiment in the position of the holding protrusion **2311**. Other parts are the same as those in the first example embodiment.

(307) The upper end (one end in the axial direction) of the holding protrusion **2311** is positioned at substantially the same height as one end in the axial direction of the stator accommodating portion **25** in the axial direction. When the seal **26** is filled up to the upper end (one end in the axial direction) of the stator accommodating portion **25**, the seal **26** is hardly cured bulging to the upper side **Z2** in the axial direction (one side in the axial direction) along the radially outer surface of the

bearing holding portion **231** from the upper end of the holding protrusion **2311**. Therefore, at the radially inner end portion of the seal **26**, a fillet is not formed along the radially outer surface of the bearing holding portion **231** beyond the holding protrusion **2311**. Therefore, it is possible to reduce variation, for each product, in the height of the upper end (end surface on one side in the axial direction) of the seal **26**.

(308) The holding protrusion **2311** may be integrated with or separated from the bearing holding portion **231**. When the holding protrusion **2311** is separated from the bearing holding portion **231**, the holding protrusion **2311** is attached to the bearing holding portion **231** after the circuit board **28** is disposed on the upper end (one end in the axial direction) of the insulator **233**. This improves assembly workability of the circuit board **28**.

(309) The example embodiments of the present disclosure have been described above. The scope of the present disclosure is not limited to the above-described example embodiments. The present disclosure can be implemented with various modifications within a scope not departing from the gist of the disclosure. The above-described example embodiments can be appropriately and optionally combined. For example, the oil repellent layer **2313** may be formed on the radially outer surface of the bearing holding portion **231** in which the groove **2311a** is formed.

(310) The present disclosure can be used in, for example, a cooling device including a blower.

(311) Features of the above-described example embodiments and the modifications thereof may be combined appropriately as long as no conflict arises.

(312) While example embodiments of the present disclosure have been described above, it is to be understood that variations and modifications will be apparent to those skilled in the art without departing from the scope and spirit of the present disclosure. The scope of the present disclosure, therefore, is to be determined solely by the following claims.

Claims

1. A motor comprising: a rotor that is rotatable about a rotation axis; a stator that opposes the rotor with a gap interposed radially inward; a stator accommodating portion in a tubular shape that accommodates the stator and includes an opening on one end surface in an axial direction; a seal filled in the stator accommodating portion; and a lid above the stator that covers the opening; wherein the stator accommodating portion includes: a cutout recessed from one end in the axial direction to another side in the axial direction and from which a lead wire electrically connected to the stator is pulled out to a radially outer position; and a pullout piece that protrudes radially outward from a bottom of the cutout and on which the lead wire is provided; the pullout piece includes a pullout inclined portion; the pullout inclined portion is inclined in the one end in the axial direction and extends radially outward from the bottom of the cutout; the lead wire is positioned between the lid and the pullout piece via an elastic portion located on an end surface on one side in the axial direction of the pullout piece; and an upper end of the elastic portion in the axial direction is located above an upper end of the seal in the axial direction, the lead wire is provided directly on the upper end of the elastic portion.

2. The motor according to claim 1, wherein the pullout piece includes a pullout projection protruding from the end surface on the one side in the axial direction.

3. The motor according to claim 1, wherein the pullout piece includes a pullout wall portion that protrudes in the one side in the axial direction from both end portions in a radial direction and extends in the radial direction.

4. The motor according to claim 1, wherein the stator accommodating portion includes: a stator tube that surrounds the stator from radially outside; an accommodating lid that covers the stator from another side in the axial direction and expands in the radial direction; and an accommodating inclined portion that couples the stator tube and the accommodating lid and is inclined radially inward toward the other side in the axial direction.

5. The motor according to claim 1, wherein the stator accommodating portion includes an accommodating projection protruding from a radially inner surface and extending in the axial direction.
 6. The motor according to claim 1, wherein the elastic portion is fixed to the pullout piece via an adhesive layer.
 7. The motor according to claim 1, wherein the elastic portion includes a rubber portion.
 8. A blower comprising: the motor according to claim 1; an impeller that is fixed to the rotor to generate an airflow in the axial direction; and a housing body that extends along the rotation axis, has a tubular shape, includes end surfaces in the axial direction opened, and internally includes a blowing flow path; wherein the motor and the impeller are accommodated inside the housing body.
 9. The motor according to claim 1, wherein at least a portion of the seal is provided directly on an axially upper surface of the pullout inclined portion.
-