

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12390030
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Edwards; Channé et al.

Pillow with cylindrical inserts

Abstract

A pillow with a plurality of cylinders snugly fit in a liner and the liner enclosed in a pillowcase wherein the cylinders are rotatable and interchangeable. The plurality of cylinders may be stacked or grouped to form a triangular formation when viewed from a side. The each of the plurality of cylinders may be selectively rotated while within the pillow for cooling purposes.

Inventors: Edwards; Channé (Beverly Hills, CA), Presley; Cayla (Beverly Hills, CA)
Applicant: Edwards; Channé (Beverly Hills, CA); Presley; Cayla (Beverly Hills, CA)
Family ID: 1000008766243
Appl. No.: 18/051641
Filed: November 01, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230135899 A1	May. 04, 2023

Related U.S. Application Data

us-provisional-application US 63263400 20211102

Publication Classification

Int. Cl.: A47G9/10 (20060101); A47G9/02 (20060101)

U.S. Cl.:

CPC A47G9/10 (20130101); A47G9/0253 (20130101); A47G2009/1018 (20130101);
A47G9/1036 (20130101)

Field of Classification Search

CPC: A47G (9/10); A47G (2009/1018); A47C (7/383); A47C (20/02); A47C (20/025)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
243228	12/1880	Doremus	428/6	A47G 9/10
2877472	12/1958	Wagner	5/636	A47G 9/10
5572757	12/1995	O'Sullivan	5/636	A47C 7/46
5732426	12/1997	Furuya et al.	N/A	N/A
5940913	12/1998	Horowitz	N/A	N/A
5987676	12/1998	Littleford et al.	N/A	N/A
6151733	12/1999	Takashima	N/A	N/A
6170103	12/2000	Wang et al.	N/A	N/A
6442778	12/2001	Shaharbarani	5/636	A47G 9/10
6795990	12/2003	Hutchinson	N/A	N/A
7120953	12/2005	Ferber et al.	N/A	N/A
7222379	12/2006	DiGirolamo	N/A	N/A
7874032	12/2010	North et al.	N/A	N/A
7904977	12/2010	Singh	5/497	A47G 9/0246
D655964	12/2011	Dror	D6/601	N/A
9101235	12/2014	Yu	N/A	N/A
9247836	12/2015	DuPre	N/A	N/A
10123638	12/2017	Thorn	N/A	N/A
10827843	12/2019	Miller	N/A	N/A
11064826	12/2020	Son et al.	N/A	N/A
11109698	12/2020	Ogden	N/A	N/A
11141009	12/2020	Rane	N/A	A47G 9/10
11446197	12/2021	Cortese	N/A	N/A
2005/0210590	12/2004	DiGirolamo	5/636	A47G 9/10
2006/0179573	12/2005	Nissen	128/845	A47G 9/1027
2007/0113347	12/2006	Lindell	5/636	A47G 9/10
2007/0226909	12/2006	Goldman	5/636	A47G 9/10
2009/0056024	12/2008	Paranjpe	5/643	A47C 27/146
2014/0283303	12/2013	Rochlin	5/636	A47G 9/10
2017/0055737	12/2016	Rochlin	N/A	A47G 9/10
2020/0154912	12/2019	Del Balso	N/A	A47G 9/10
2022/0079360	12/2021	Broadbelt	N/A	N/A
2022/0304411	12/2021	Maddock et al.	N/A	N/A
2022/0312977	12/2021	Riday	N/A	N/A
2022/0322852	12/2021	Sramek	N/A	N/A
2022/0395117	12/2021	Bair	N/A	A47C 31/11

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
204970611	12/2015	CN	N/A
108851855	12/2017	CN	N/A

Primary Examiner: Kurilla; Eric J

Attorney, Agent or Firm: Dunlap Bennett & Ludwig, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application claims the benefit of priority of U.S. provisional application No. 63/263,400, filed Nov. 2, 2021, the contents of which are herein incorporated by reference.

BACKGROUND OF THE INVENTION

(1) The present invention relates to pillows and, more particularly, to a pillow with cylindrical inserts.

(2) Standard pillows are limited in comfort. Traditional materials used to fill pillows, such as feathers, become flat and lose their fluff and shape over time. The standard shape of a pillow does not meet the needs of many users.

(3) As can be seen, there is a need for a pillow that does not lose its shape or its fluff with age and provides adequate support for all users.

SUMMARY OF THE INVENTION

(4) In one aspect of the present invention, a pillow comprises a plurality of cylinders snugly fit in a liner and the liner enclosed in a pillowcase wherein the cylinders are rotatable and interchangeable.

(5) These and other features, aspects and advantages of the present invention will become better understood with reference to the following drawings, description, and claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a top front perspective view of a pillow according to an embodiment of the present invention;

(2) FIG. 2 is a cross sectional view taken on line 2-2 of FIG. 1; and

(3) FIG. 3 is an exploded view thereof.

DETAILED DESCRIPTION OF THE INVENTION

(4) The following detailed description is of the best currently contemplated modes of carrying out exemplary embodiments of the invention. The description is not to be taken in a limiting sense but is made merely for the purpose of illustrating the general principles of the invention, since the scope of the invention is best defined by the appended claims.

(5) A general overview of the various features of the invention will be provided, with a detailed description following. Broadly, an embodiment of the present invention provides a pillow comprising three cylinders, a lining, and a pillowcase. The cylinders may be foam.

(6) The cylinders may be stacked or grouped to form a triangular formation when viewed from a side. The foam cylinders may have a density of approximately 2.25-2.5 lbs. per cubic inch with an approximate 1.00 pound per linear inch tear strength. A radius of the foam cylinders may range from 1.5 to 3 inches. A length of the foam cylinders may be approximately 18 inches. The radius and length of the foam cylinders are not particularly limited by the present invention and any length or radius may be used. The cylinders may be interchangeable, enabling a user to remove cylinders and replace them or customize the pillow with a predetermined amount of cylinders of various

sizes. The cylinders may also be rotatable while within the pillow for cooling purposes.

(7) The cylinders are housed in a lining. The lining may be mesh and may be breathable. The lining holds the foam cylinders in place, cools the cylinders, and prevents moisture from accumulating on the cylinders. The lining may be a triangular prism with round edges. The lining may have a zipper, buttons, or another mechanism for sealing the lining on an end. The lining may have a height of 5 inches and a length of 18 inches. The height and length of the lining are not particularly limited by the present invention and any height or length large enough to house or snugly fit the cylinders may be used. The liner may be a continuous piece of fabric forming with a triangular cross section. In some embodiments, when removed from the pillowcase and cylinders, the liner forms a cylinder. The liner may lack sidewalls for an additional cooling effect.

(8) A pillowcase surrounds the lining. The pillowcase may be a size slightly larger than the lining to encompass it. The pillowcase may have a zipper, buttons, or another mechanism for sealing the pillowcase on an end.

(9) The cylinders may rotate within the bounds of the pillowcase and interior liner to facilitate a cooling effect for a user.

(10) In some embodiments, three cylinders are utilized. The cylinders may vary in size. For example, two large cylinders may be utilized with one smaller cylinder. However, a plurality of smaller cylinders may be used. Any combination of sizes may be utilized.

(11) Referring now to FIGS. 1-3, a pillowcase **10** encloses a mesh liner **12**. Inside the mesh liner **12** are two large foam cylinders **16** and a small foam cylinder **14**. The two large foam cylinders **16** and the small foam cylinder **14** are stacked to form a triangle. The mesh liner **12** constrains the cylinders **14**, **16** and maintains the triangular shape.

(12) As used in this application, the term “about” or “approximately” refers to a range of values within plus or minus 10% of the specified number. And the term “substantially” refers to up to 80% or more of an entirety. Recitation of ranges of values herein are not intended to be limiting, referring instead individually to any and all values falling within the range, unless otherwise indicated, and each separate value within such a range is incorporated into the specification as if it were individually recited herein.

(13) For purposes of this disclosure, the term “aligned” means parallel, substantially parallel, or forming an angle of less than 35.0 degrees. For purposes of this disclosure, the term “transverse” means perpendicular, substantially perpendicular, or forming an angle between 55.0 and 125.0 degrees. Also, for purposes of this disclosure, the term “length” means the longest dimension of an object. Also, for purposes of this disclosure, the term “width” means the dimension of an object from side to side. For the purposes of this disclosure, the term “above” generally means superjacent, substantially superjacent, or higher than another object although not directly overlying the object. Further, for purposes of this disclosure, the term “snugly” generally refers to components being in direct physical contact with each other or being in indirect physical contact with each other where movement of one component affect the position of the other.

(14) The use of any and all examples, or exemplary language (“e.g.,” “such as,” or the like) provided herein, is intended merely to better illuminate the embodiments and does not pose a limitation on the scope of the embodiments or the claims. No language in the specification should be construed as indicating any unclaimed element as essential to the practice of the disclosed embodiments.

(15) In the following description, it is understood that terms such as “first,” “second,” “top,” “bottom,” “up,” “down,” and the like, are words of convenience and are not to be construed as limiting terms unless specifically stated to the contrary.

(16) It should be understood, of course, that the foregoing relates to exemplary embodiments of the invention and that modifications may be made without departing from the spirit and scope of the invention as set forth in the following claims.

Claims

1. A pillow comprising: a liner enclosed in a pillowcase; and the liner defines a triangular prism with rounded edges, wherein the liner is dimensioned and shaped to removably and snugly house a plurality of cylinders are rotatable relative to each other when so housed; wherein the plurality of cylinders comprises foam cylinders; and wherein the plurality of cylinders comprise two adjacent first cylinders and one second cylinder, wherein the second cylinder has a diameter less than the two first cylinders, and wherein the second cylinder is nestled in a space between the two adjacent first cylinders to define a triangular cross section, wherein said three cylinders are snugly constrained by the triangular prism of the liner to hold the triangular cross section while enabling said three cylinders to rotate relative to each other so that a user of the pillow is enabled to selectively facilitate a cooling effect by rotating each cylinder.
 2. The pillow of claim 1, wherein the liner is a mesh liner.
 3. The pillow of claim 1, wherein each of the two first cylinders has a radius of approximately 3 inches and the one second cylinder has a radius of approximately 1.5 inches.
 4. The pillow of claim 3, wherein each of the plurality of the cylinders has a length of approximately 18 inches.
 5. The pillow of claim 4, wherein said foam has a density of approximately 2.25-2.5 lbs. per cubic inch with an approximate 1.00 pound per linear inch tear strength.
 6. The pillow of claim 1, wherein the pillowcase defines a triangular prism with rounded edges, wherein the pillowcase is dimensioned and shaped to removably receive the liner.
 7. A pillow comprising: a pillowcase; and a liner dimensioned and shaped to move between an unenclosed condition and an enclosed condition relative to the pillowcase, wherein in the unenclosed condition the liner defines a triangular prism, wherein the liner is dimensioned and shaped to removably house a plurality of cylinders that are rotatable relative to each other when so housed; wherein the plurality of cylinders is snugly housed in the liner, and wherein the plurality of cylinders comprises two adjacent first cylinders and one second cylinder nestled in a space between the two adjacent first cylinders to define a triangular cross section; wherein said three cylinders are rotatable relative to each other so that a user of the pillow is enabled to selectively facilitate a cooling effect by rotating each cylinder.
 8. The pillow of claim 7, wherein the triangular prism has rounded edges in the unenclosed condition.
 9. The pillow of claim 2, wherein said three cylinders are foam cylinders.
 10. The pillow of claim 9, wherein the liner is a mesh liner.
 11. The pillow of claim 10, wherein each of the two first cylinders has a radius of approximately 3 inches and the one second cylinder has a radius of approximately 1.5 inches.
 12. The pillow of claim 11, wherein each of the plurality of the cylinders has a length of approximately 18 inches.
 13. The pillow of claim 12, wherein said foam has a density of approximately 2.25-2.5 lbs. per cubic inch with an approximate 1.00 pound per linear inch tear strength.
 14. The pillow of claim 7, wherein the pillowcase defines a triangular prism with rounded edges.
-