

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12394254
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Bohman; Mats et al.

Artificially intelligent provision of post-vehicular-collision evidence

Abstract

Systems/techniques that facilitate artificially intelligent provision of post-vehicular-collision evidence are provided. In various embodiments, a system can be onboard a vehicle. In various aspects, the system can capture, via one or more cameras or one or more microphones of the vehicle, vicinity data associated with a vicinity of the vehicle. In various instances, the system can determine, via execution of a deep learning neural network on the vicinity data, whether a vehicular collision not involving the vehicle has occurred in the vicinity of the vehicle. In various cases, the system can broadcast, in response to a determination that the vehicular collision has occurred, via the one or more cameras or the one or more microphones, and to an emergency service computing device, a post-collision live stream associated with the vicinity of the vehicle.

Inventors: Bohman; Mats (Gothenburg, SE), Carlsson; Anna Stina Ida (Västra Frölunda, SE), Ödblom; Carl Anders Eric (Öckerö, SE), Fei; Zhennan (Gothenburg, SE), Nilsson; Pär Bertil Gottfrid (Mölndal, SE)

Applicant: Volvo Car Corporation (Gothenburg, SE)

Family ID: 1000008764528

Assignee: Volvo Car Corporation (Gothenburg, SE)

Appl. No.: 18/050544

Filed: October 28, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240144736 A1	May. 02, 2024

Publication Classification

Int. Cl.: G07C5/00 (20060101); G06N5/04 (20230101); G07C5/08 (20060101)

U.S. Cl.:

CPC **G07C5/008** (20130101); **G06N5/04** (20130101); **G07C5/0841** (20130101);

Field of Classification Search

CPC: G07C (5/008); G07C (5/0841); G06N (5/04)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6700504	12/2003	Aslandogan et al.	N/A	N/A
6741168	12/2003	Webb	340/904	G07C 5/085
9402060	12/2015	Plante	N/A	H04N 23/62
9633318	12/2016	Plante	N/A	G07C 5/085
10800278	12/2019	Symanow et al.	N/A	N/A
11049186	12/2020	Medina, III	N/A	G06Q 40/08
11620906	12/2022	Hu	701/25	G05D 1/0212
11950316	12/2023	Nalevanko	N/A	H04W 4/40
12167164	12/2023	Jo	N/A	B60C 23/0408
2003/0112133	12/2002	Webb	340/436	G08G 1/162
2009/0027056	12/2008	Huang	320/132	G01R 31/392
2011/0288743	12/2010	Smith	701/102	B60L 50/61
2012/0113666	12/2011	Slipp	N/A	N/A
2013/0221741	12/2012	Stanek et al.	N/A	N/A
2014/0009275	12/2013	Bowers	340/436	G06Q 20/145
2015/0241880	12/2014	Kim	701/25	G05D 1/0055
2017/0026893	12/2016	Lagassey	N/A	N/A
2019/0236955	12/2018	Hu	N/A	G08G 1/096741
2020/0026289	12/2019	Alvarez et al.	N/A	N/A
2020/0027333	12/2019	Xu et al.	N/A	N/A
2020/0098200	12/2019	Pohlenz	N/A	N/A
2021/0039596	12/2020	Park	N/A	N/A
2021/0094438	12/2020	Ciccone	N/A	B60L 58/24
2021/0304592	12/2020	Lepp	N/A	H04W 4/40
2021/0342613	12/2020	Wang et al.	N/A	N/A
2021/0390858	12/2020	McFarland, Jr.	N/A	N/A
2022/0032977	12/2021	Gupta	N/A	N/A
2022/0277598	12/2021	Liu	N/A	H04W 4/44
2022/0281486	12/2021	Sakurada et al.	N/A	N/A
2022/0292974	12/2021	Qi	N/A	N/A
2022/0312086	12/2021	Schmidt	N/A	N/A
2023/0196489	12/2022	Khedekar	705/325	G06Q 50/265
2023/0343213	12/2022	Lauzière	N/A	G08G 1/095
2023/0386268	12/2022	Scarbrough	N/A	H04N 23/65
2024/0059323	12/2023	Gerrese	N/A	H04W 4/023

OTHER PUBLICATIONS

Non-Final Office Action for U.S. Appl. No. 18/050,540 dated Jul. 30, 2024, 16 pages. cited by applicant
European Search Report for European Patent Application No. EP23205601 dated Apr. 2, 2024, 7 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 18/050,540 dated Nov. 25, 2024, 18 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 18/050,548 dated Nov. 5, 2024, 22 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 18/050,550 dated Oct. 9, 2024, 175 pages. cited by applicant
Communication Pursuant to Rules 69 EPC received for EP Patent Application Serial No. 23205601.0 dated May 7, 2024, 2 pages. cited by applicant
Final Office Action received for U.S. Appl. No. 18/050,550 dated Mar. 21, 2025, 51 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 18/050,540 dated Jan. 29, 2025, 12 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 18/050,540 dated Mar. 7, 2025, 7 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 18/050,537 dated Feb. 18, 2025, 51 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 18/050,548 dated Apr. 2, 2025, 28 pages. cited by applicant

Primary Examiner: Refai; Ramsey

Attorney, Agent or Firm: Amin, Turocy & Watson, LLP

Background/Summary

TECHNICAL FIELD

(1) The subject disclosure relates generally to artificial intelligence, and more specifically to artificially intelligent provision of post-vehicular-collision evidence.

BACKGROUND

(2) A vehicular collision can involve one or more vehicles colliding with each other or with any suitable stationary or non-stationary objects. Unfortunately, existing techniques for addressing or responding to vehicular collisions can be unreliable.

(3) Accordingly, systems or techniques that can address one or more of these technical problems can be desirable.

SUMMARY

(4) The following presents a summary to provide a basic understanding of one or more embodiments of the invention. This summary is not intended to identify key or critical elements, or delineate any scope of the particular embodiments or any scope of the claims. Its sole purpose is to present concepts in a simplified form as a prelude to the more detailed description that is presented later. In one or more embodiments described herein, devices, systems, computer-implemented methods, apparatus or computer program products that facilitate artificially intelligent provision of post-vehicular-collision evidence are described.

(5) According to one or more embodiments, a system is provided. The system can be onboard a

first vehicle, and the system can comprise a non-transitory computer-readable memory that can store computer-executable components. The system can further comprise a processor that can be operably coupled to the non-transitory computer-readable memory and that can execute the computer-executable components stored in the non-transitory computer-readable memory. In various embodiments, the computer-executable components can comprise a sensor component that can capture, via one or more first cameras or one or more first microphones of the first vehicle, vicinity data associated with a first vicinity of the first vehicle. In various aspects, the computer-executable components can comprise an inference component that can determine, via execution of a deep learning neural network on the vicinity data, whether a vehicular collision not involving the first vehicle has occurred in the first vicinity of the first vehicle. In various instances, the computer-executable components can comprise an evidence component that can record, in response to a determination that the vehicular collision has occurred and via the one or more first cameras or the one or more first microphones, first post-collision evidence associated with the first vicinity of the first vehicle.

(6) According to one or more embodiments, a system is provided. The system can be onboard a vehicle, and the system can comprise a non-transitory computer-readable memory that can store computer-executable components. The system can further comprise a processor that can be operably coupled to the non-transitory computer-readable memory and that can execute the computer-executable components stored in the non-transitory computer-readable memory. In various embodiments, the computer-executable components can comprise a sensor component that can capture, via one or more cameras or one or more microphones of the vehicle, vicinity data associated with a vicinity of the vehicle. In various aspects, the computer-executable components can comprise an inference component that can generate, via execution of a deep learning neural network on the vicinity data, a classification label indicating whether a vehicular collision not involving the vehicle has occurred in the vicinity of the vehicle. In various instances, the computer-executable components can comprise an evidence component that can record, in response to the classification label indicating that the vehicular collision has occurred and via the one or more cameras or the one or more microphones, post-collision evidence associated with the vicinity of the vehicle. In various cases, the computer-executable components can comprise a broadcast component that can broadcast, in response to the classification label indicating that the vehicular collision has occurred, the classification label and the post-collision evidence to an emergency service computing device.

(7) According to one or more embodiments, a system is provided. The system can be onboard a vehicle, and the system can comprise a non-transitory computer-readable memory that can store computer-executable components. The system can further comprise a processor that can be operably coupled to the non-transitory computer-readable memory and that can execute the computer-executable components stored in the non-transitory computer-readable memory. In various embodiments, the computer-executable components can comprise a sensor component that can capture, via one or more cameras or one or more microphones of the vehicle, vicinity data associated with a vicinity of the vehicle. In various aspects, the computer-executable components can comprise an inference component that can determine, via execution of a deep learning neural network on the vicinity data, whether a vehicular collision not involving the vehicle has occurred in the vicinity of the vehicle. In various instances, the computer-executable components can comprise a broadcast component that can broadcast, in response to a determination that the vehicular collision has occurred, via the one or more cameras or the one or more microphones, and to an emergency service computing device, a post-collision live stream associated with the vicinity of the vehicle.

(8) According to one or more embodiments, a system is provided. The system can be onboard a vehicle, and the system can comprise a non-transitory computer-readable memory that can store computer-executable components. The system can further comprise a processor that can be

operably coupled to the non-transitory computer-readable memory and that can execute the computer-executable components stored in the non-transitory computer-readable memory. In various embodiments, the computer-executable components can comprise a sensor component that can capture, via one or more cameras or one or more microphones of the vehicle, vicinity data associated with a vicinity of the vehicle. In various aspects, the computer-executable components can comprise an inference component that can determine, via execution of a deep learning neural network on the vicinity data, whether a vehicular collision not involving the vehicle has occurred in the vicinity of the vehicle. In various instances, the computer-executable components can comprise a broadcast component that can broadcast, in response to a determination that the vehicular collision has occurred and via the one or more cameras or the one or more microphones, one or more electronic notifications.

(9) According to one or more embodiments, a system is provided. The system can comprise a non-transitory computer-readable memory that can store computer-executable components. The system can further comprise a processor that can be operably coupled to the non-transitory computer-readable memory and that can execute the computer-executable components stored in the non-transitory computer-readable memory. In various embodiments, the computer-executable components can comprise a receiver component that can receive one or more electronic notifications broadcasted by a vehicle. In various aspects, the computer-executable components can comprise a determination component that can determine, via parsing, whether the one or more electronic notifications indicate that a vehicular collision not involving the vehicle has occurred in a vicinity of the vehicle. In various instances, the computer-executable components can comprise an execution component that can initiate, in response to a determination that the one or more electronic notifications indicate that the vehicular collision has occurred, one or more electronic actions based on the vehicular collision.

(10) According to one or more embodiments, the above-described systems can be implemented as computer-implemented methods or computer program products.

Description

DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 illustrates an example, non-limiting block diagram showing a vehicular collision occurring within a vicinity of a vehicle, where such vehicle can facilitate artificially intelligent provision of post-vehicular-collision evidence in accordance with one or more embodiments described herein.

(2) FIG. 2 illustrates a block diagram of an example, non-limiting system that facilitates a broadcast-side of artificially intelligent provision of post-vehicular-collision evidence in accordance with one or more embodiments described herein.

(3) FIG. 3 illustrates a block diagram of an example, non-limiting system including various sensors that facilitates a broadcast-side of artificially intelligent provision of post-vehicular-collision evidence in accordance with one or more embodiments described herein.

(4) FIG. 4 illustrates a block diagram of an example, non-limiting system including a deep learning neural network and a vehicular collision classification label that facilitates a broadcast-side of artificially intelligent provision of post-vehicular-collision evidence in accordance with one or more embodiments described herein.

(5) FIG. 5 illustrates an example, non-limiting block diagram showing how a deep learning neural network can generate a vehicular collision classification label based on vicinity data in accordance with one or more embodiments described herein.

(6) FIG. 6 illustrates an example, non-limiting block diagram of a vehicular collision classification label in accordance with one or more embodiments described herein.

(7) FIG. 7 illustrates a block diagram of an example, non-limiting system including recorded post-collision evidence and an electronic alert that facilitates a broadcast-side of artificially intelligent provision of post-vehicular-collision evidence in accordance with one or more embodiments described herein.

(8) FIG. 8 illustrates an example, non-limiting block diagram showing recorded post-collision evidence and an electronic alert in accordance with one or more embodiments described herein.

(9) FIG. 9 illustrates a block diagram of an example, non-limiting system including a training component and a training dataset that facilitates a broadcast-side of artificially intelligent provision of post-vehicular-collision evidence in accordance with one or more embodiments described herein.

(10) FIG. 10 illustrates an example, non-limiting block diagram of a training dataset in accordance with one or more embodiments described herein.

(11) FIG. 11 illustrates an example, non-limiting block diagram showing how a deep learning neural network can be trained in accordance with one or more embodiments described herein.

(12) FIG. 12 illustrates a flow diagram of an example, non-limiting computer-implemented method that facilitates a broadcast-side of artificially intelligent provision of post-vehicular-collision evidence in accordance with one or more embodiments described herein.

(13) FIG. 13 illustrates a block diagram of an example, non-limiting system that facilitates a receipt-side of artificially intelligent provision of post-vehicular-collision evidence in accordance with one or more embodiments described herein.

(14) FIG. 14 illustrates a block diagram of an example, non-limiting system including a determination indicator that facilitates a receipt-side of artificially intelligent provision of post-vehicular-collision evidence in accordance with one or more embodiments described herein.

(15) FIG. 15 illustrates a block diagram of an example, non-limiting system including an electronic navigation display that facilitates a receipt-side of artificially intelligent provision of post-vehicular-collision evidence in accordance with one or more embodiments described herein.

(16) FIGS. 16-17 illustrate example, non-limiting block diagrams showing how an electronic navigation display can be adjusted in accordance with one or more embodiments described herein.

(17) FIG. 18 illustrates a flow diagram of an example, non-limiting computer-implemented method that facilitates adjusting an electronic navigation display in accordance with one or more embodiments described herein.

(18) FIG. 19 illustrates an example, non-limiting block diagram showing how an electronic navigation route can be computed and rendered in accordance with one or more embodiments described herein.

(19) FIG. 20 illustrates a flow diagram of an example, non-limiting computer-implemented method that facilitates generating an electronic navigation route in accordance with one or more embodiments described herein.

(20) FIG. 21 illustrates a block diagram of an example, non-limiting system including a deep learning neural network and a verification label that facilitates a receipt-side of artificially intelligent provision of post-vehicular-collision evidence in accordance with one or more embodiments described herein.

(21) FIG. 22 illustrates an example, non-limiting block diagram showing how a deep learning neural network can generate a verification label in accordance with one or more embodiments described herein.

(22) FIG. 23 illustrates a flow diagram of an example, non-limiting computer-implemented method that facilitates generation of a verification label in accordance with one or more embodiments described herein.

(23) FIG. 24 illustrates an example, non-limiting block diagram showing a neighboring vehicle within a vicinity of a vehicle that has detected a vehicular collision, where such neighboring vehicle can facilitate artificially intelligent provision of post-vehicular-collision evidence in

accordance with one or more embodiments described herein.

(24) FIG. 25 illustrates a flow diagram of an example, non-limiting computer-implemented method that facilitates a neighboring vehicle aspect of artificially intelligent provision of post-vehicular-collision evidence in accordance with one or more embodiments described herein.

(25) FIG. 26 illustrates a block diagram of an example, non-limiting system including a post-collision live stream that facilitates a broadcast-side of artificially intelligent provision of post-vehicular-collision evidence in accordance with one or more embodiments described herein.

(26) FIG. 27 illustrates an example, non-limiting block diagram of a post-collision live stream in accordance with one or more embodiments described herein.

(27) FIG. 28 illustrates a flow diagram of an example, non-limiting computer-implemented method that facilitates provision of a post-collision live stream in accordance with one or more embodiments described herein.

(28) FIG. 29 illustrates a block diagram of an example, non-limiting system including a battery component that facilitates provision of a post-collision live stream in accordance with one or more embodiments described herein.

(29) FIGS. 30-31 illustrate flow diagrams of example, non-limiting computer-implemented methods that facilitate provision of a post-collision live stream in accordance with one or more embodiments described herein.

(30) FIG. 32 illustrates a block diagram of an example, non-limiting system including a remote-control component that facilitates provision of a post-collision live stream in accordance with one or more embodiments described herein.

(31) FIG. 33 illustrates an example, non-limiting block diagram of a remote-control notification and remote-control commands in accordance with one or more embodiments described herein.

(32) FIG. 34 illustrates a flow diagram of an example, non-limiting computer-implemented method that facilitates provision of a post-collision live stream in accordance with one or more embodiments described herein.

(33) FIGS. 35-39 illustrate flow diagrams of example, non-limiting computer-implemented methods that facilitate artificially intelligent provision of post-vehicular-collision evidence in accordance with one or more embodiments described herein.

(34) FIG. 40 illustrates a block diagram of an example, non-limiting operating environment in which one or more embodiments described herein can be facilitated.

(35) FIG. 41 illustrates an example networking environment operable to execute various implementations described herein.

DETAILED DESCRIPTION

(36) The following detailed description is merely illustrative and is not intended to limit embodiments or application/uses of embodiments. Furthermore, there is no intention to be bound by any expressed or implied information presented in the preceding Background or Summary sections, or in the Detailed Description section.

(37) One or more embodiments are now described with reference to the drawings, wherein like referenced numerals are used to refer to like elements throughout. In the following description, for purposes of explanation, numerous specific details are set forth in order to provide a more thorough understanding of the one or more embodiments. It is evident, however, in various cases, that the one or more embodiments can be practiced without these specific details.

(38) A vehicular collision can involve one or more vehicles colliding (e.g., crashing) with each other or with any suitable stationary or non-stationary objects or entities (e.g., crashing into trees, power poles, buildings, furniture, animals, or pedestrians). A vehicular collision can cause or otherwise involve vehicle damage (e.g., crumpled bumpers, ruined fenders, broken headlights, bent frames) or bodily injury (e.g., broken bones, lacerations, whiplash). Remedying or addressing such vehicle damage or bodily injury (e.g., determining fault for insurance or legal liability purposes) can depend upon an aftermath of the vehicular collision (e.g., can depend upon who did what in the

moments after the vehicular collision occurred).

(39) Unfortunately, and as recognized by the inventors of various embodiments described herein, existing techniques for capturing such aftermath can be unreliable for various reasons.

(40) First, the present inventors realized that existing techniques usually rely upon eyewitness reports to reconstruct the aftermath of a vehicular collision. That is, after emergency services have responded to the vehicular collision (e.g., after emergency services have supplied appropriate medical care to all injured persons), the emergency services interview people who report what they witnessed regarding the vehicular collision, and the emergency services piece together the aftermath of the vehicular collision based on such eyewitness reports. Unfortunately, such eyewitness reports are intrinsically unreliable. Indeed, because emergency services can be preoccupied with supplying medical care when they first arrive at the scene of the vehicular collision, emergency services can acquire such eyewitness reports long periods of time (e.g., many hours) after the vehicular collision occurs. Such delay or lag between the occurrence of the vehicular collision and the recordation or taking of the eyewitness reports can increase a risk of the eyewitnesses misremembering the vehicular collision. Moreover, eyewitness reports are always vulnerable to lying by biased eyewitnesses. For example, an eyewitness might have a grudge against a person involved in the vehicular collision, and thus the eyewitness might lie so as to place blame on that person. Conversely, an eyewitness might have a special relationship (e.g., familial relationship) with a person involved in the vehicular collision, and thus the eyewitness might lie so as to protect that person. Indeed, in some cases, there might not be any eyewitnesses available to provide eyewitness reports (e.g., the vehicular collision might have occurred in a sparsely populated area or on an otherwise unbusy road; in such cases, emergency services might not even become aware of the vehicular collision until a long amount of time after the vehicular collision occurs).

(41) Second, the present inventors realized that, although some existing techniques utilize traffic cameras to capture the aftermath of a vehicular collision, such traffic cameras are not ubiquitous and are often stationary. In particular, traffic cameras are often installed at major or busy intersections. Accordingly, if a vehicular collision occurs in such a major or busy intersection, a traffic camera installed at that major or busy intersection can video-graphically record the vehicular collision or its aftermath. The video-graphic recording of such traffic camera can be considered as more reliable than an eyewitness report (e.g., the traffic camera cannot misremember or lie due to bias). However, traffic cameras are not omnipresent. Indeed, although traffic cameras are often installed at major or busy intersections, traffic cameras are often not installed at less-busy intersections or at non-intersection portions of road. Because such less-busy intersections or non-intersection portions of road can outnumber major or busy intersections, there can be many vehicular collisions that are not captured by traffic cameras. Furthermore, a traffic camera is often configured to swivel about a fixed point. Accordingly, although the traffic camera can adjust its orientation, the traffic camera cannot obtain a new vantage point for itself. Thus, when the traffic camera is recording a vehicular collision or its aftermath, some aspects or details of the vehicular collision or the aftermath can be hidden from the vantage point of the traffic camera, and the traffic camera cannot reposition itself so as to view such hidden aspects or details.

(42) Third, the present inventors realized that, although various existing techniques utilize personal computing devices of eyewitnesses to capture the aftermath of a vehicular collision, such personal computing devices rely upon manual activation. In particular, a person who witnesses a vehicular collision can utilize their personal computing device (e.g., their smart phone) to video-graphically capture the vehicular collision or its aftermath. The video-graphic recording of such personal computing device can be considered as more reliable than an eyewitness report (e.g., the personal computing device cannot misremember or lie due to bias). Moreover, the personal computing device can be not stationarily installed to a fixed location. In other words, the eyewitness can move to different locations while recording with their personal computing device, meaning that the

vantage point of the personal computing device can be changed. However, such techniques rely upon manual activation of the personal computing device. Regrettably, an eyewitness can (e.g., due to inattention or bias) forget or otherwise choose not to record the vehicular collision or its aftermath, notwithstanding having a personal computing device.

(43) Furthermore, an extent of bodily injury caused by a vehicular collision can depend upon how long it takes for emergency services to respond to the vehicular collision. For example, the longer it takes for emergency services to arrive at the scene of the vehicular collision, the more likely it can be for an injured pedestrian, injured driver, or injured passenger to experience exacerbated injuries (e.g., to bleed out). Existing techniques often allow emergency services to respond to a vehicular collision in about eight to ten minutes. Depending upon the severity of the vehicular collision, eight to ten minutes can be too long to wait for emergency services.

(44) Accordingly, systems or techniques that can address one or more of these technical problems can be desirable.

(45) Various embodiments described herein can address one or more of these technical problems. One or more embodiments described herein can include systems, computer-implemented methods, apparatus, or computer program products that can facilitate artificially intelligent provision of post-vehicular-collision evidence. That is, the present inventors realized that various disadvantages associated with existing techniques for capturing the aftermath of a vehicular collision can be ameliorated by artificially intelligent provision of post-vehicular-collision evidence. More specifically, a vehicle can be outfitted with various external sensors, such as road-facing cameras or road-facing microphones. In various aspects, the vehicle can utilize such external sensors to capture vicinity data of a vicinity of the vehicle (e.g., to capture pictures of roadways, sidewalks, pedestrians, or other vehicles that are in the vicinity of the vehicle, to capture noises that occur in the vicinity of the vehicle). Furthermore, the vehicle can be outfitted with a deep learning neural network that can be trained or otherwise configured to detect vehicular collisions based on data captured by the external sensors. Thus, in various instances, the vehicle can execute the deep learning neural network on the vicinity data, which can cause the deep learning neural network to produce an outputted classification label. In various aspects, the outputted classification label can exhibit any suitable format or dimensionality. For example, in some cases, the outputted classification label can be a dichotomous variable (e.g., binary variable) that binomially indicates a presence or absence of a vehicular collision. As another example, in other cases, the outputted classification label can be a set of dichotomous or multichotomous variables that binomially or multinomially indicate various characteristics of a detected vehicular collision (e.g., if the outputted classification label indicates that a vehicular collision has been detected, then the outputted classification label can further indicate how many vehicles are involved in the vehicular collision, whether one or more pedestrians were injured in the vehicular collision, or a severity level of the vehicular collision). In various cases, when the outputted classification label indicates that a vehicular collision has occurred in the vicinity of the vehicle, the vehicle can automatically begin recording, via its external sensors, whatever is transpiring in the vicinity after the vehicular collision (e.g., in some cases, pre-collision buffering can be implemented, such that data captured by the external sensors in the moments before a vehicular collision can also be recorded). The data that is recorded by the vehicle's external sensors in such fashion (e.g., recorded video clips, recorded audio clips) can be considered as post-collision evidence. In various aspects, the vehicle can electronically transmit the post-collision evidence to any suitable emergency service computing device (e.g., to a police vehicle, to a police depot, to an ambulance, to a hospital, to a public service access point (PSAP), to a third-party service (TSP) call center, or to any other suitable electronic service whatsoever).

(46) In various aspects, the external sensors and the deep learning neural network of the vehicle can be configured to constantly, continuously, or continually scan the vicinity of the vehicle for vehicular collisions. Whenever a vehicular collision is detected, its aftermath can be automatically

recorded by the external sensors (e.g., by the road-facing cameras or road-facing microphones) of the vehicle, and such recordings can be electronically broadcasted to an emergency service computing device. In this way, various disadvantages of existing techniques can be ameliorated. More specifically, the data recorded by the external sensors of the vehicle can be more reliable than eyewitness reports (e.g., video clips or audio clips do not misremember or lie due to bias). Moreover, the constant, continuous, or continual scanning of the external sensors or of the deep learning neural network can be more reliable than the manual activation required by some existing techniques (e.g., the external sensors or the deep learning neural network cannot forget or otherwise choose not to detect a vehicular collision that is manifested in the vicinity data). Furthermore, the vehicle can detect and record the aftermath of a vehicular collision, even if the vehicular collision occurs in a location where no traffic cameras are installed. Further still, the vehicle can be not stationarily fixed to any one point, meaning that the vehicle can, in some instances, move around a detected vehicular collision while recording with its external sensors, so as to capture the vehicular collision and its aftermath from more than one vantage point.

(47) In some cases, the emergency service computing device can even interact, vicariously through the vehicle, with the vehicular collision in real-time. In particular, when the outputted classification label indicates that a vehicular collision has occurred in the vicinity of the vehicle, the vehicle can, in various aspects, initiate a live stream to the emergency service computing device, via its external sensors. Such live stream can allow the emergency service computing device (e.g., can allow an operator or user of the emergency service computing device) to observe the vehicular collision in real-time, even before emergency services actually arrive at the scene of the vehicular collision. Moreover, the vehicle can, in some cases, be outfitted with any suitable autonomous driving capabilities (e.g., autonomously adjustable steering input, autonomously adjustable throttle input, autonomously adjustable camera angles). Accordingly, during such live stream, the vehicle can, in various instances, receive remote-control commands from the emergency service computing device (e.g., commands to adjust a camera orientation of the vehicle, to adjust a steering input of the vehicle, to adjust a throttle input of the vehicle, to play defined sound data via a speaker of the vehicle), and the vehicle can automatically obey such remote-control commands. This can allow the emergency service computing device (e.g., can allow an operator or user of the emergency service computing device) to interact with the vehicular collision in real-time, even before emergency services actually arrive at the scene of the vehicular collision. Thus, such embodiments can be considered as effectively reducing an emergency service response time.

(48) Various embodiments described herein can be considered as a computerized tool (e.g., any suitable combination of computer-executable hardware or computer-executable software) that can facilitate artificially intelligent provision of post-vehicular-collision evidence. In various aspects, there can be a vehicle and an emergency service computing device. In various instances, the vehicle can be outfitted with a first computerized tool, and the emergency service computing device can be outfitted with a second computerized tool. In various cases, the first computerized tool can comprise a sensor component, an inferencing component, an evidence component, or a broadcast component. In various aspects, the second computerized tool can comprise a receiver component, a determination component, or an execution component.

(49) In various embodiments, the sensor component of the first computerized tool can electronically record, measure, or otherwise capture vicinity data associated with a vicinity of the vehicle. More specifically, the sensor component can electronically access or otherwise control various sensors of the vehicle. Such sensors can include one or more cameras of the vehicle, one or more microphones of the vehicle, one or more thermometers of the vehicle, one or more hygrometers of the vehicle, or one or more proximity sensors (e.g., radar, sonar, lidar) of the vehicle. In various aspects, the sensor component can leverage such sensors to obtain the vicinity data. For example, the one or more cameras can capture one or more images of the vicinity of the vehicle (e.g., images of roadways, sidewalks, traffic lights, buildings, pedestrians, trees, or other

vehicles that are within any suitable distance in front of the vehicle, behind the vehicle, or beside the vehicle). As another example, the one or more microphones can record one or more noises that occur in the vicinity of the vehicle (e.g., noises that occur within any suitable distance in front of the vehicle, behind the vehicle, or beside the vehicle). As still another example, the one or more thermometers can measure one or more temperatures associated with the vicinity (e.g., air temperatures or surface temperatures within any suitable distance in front of the vehicle, behind the vehicle, or beside the vehicle). As yet another example, the one or more hygrometers can measure one or more humidities associated with the vicinity (e.g., air moisture levels or surface moisture levels within any suitable distance in front of the vehicle, behind the vehicle, or beside the vehicle). As even another example, the one or more proximity sensors can measure one or more proximity detections associated with the vicinity (e.g., can detect tangible objects that are within any suitable distance in front of the vehicle, behind the vehicle, or beside the vehicle). In various cases, such one or more images, such one or more noises, such one or more temperatures, such one or more humidities, or such one or more proximity detections can collectively be considered as the vicinity data.

(50) In various embodiments, the inference component of the first computerized tool can electronically store, maintain, control, or otherwise access a first deep learning neural network. In various instances, the first deep learning neural network can exhibit any suitable internal architecture. For example, the first deep learning neural network can include any suitable numbers of any suitable types of layers (e.g., input layer, one or more hidden layers, output layer, any of which can be convolutional layers, dense layers, non-linearity layers, pooling layers, batch normalization layers, or padding layers). As another example, the first deep learning neural network can include any suitable numbers of neurons in various layers (e.g., different layers can have the same or different numbers of neurons as each other). As yet another example, the first deep learning neural network can include any suitable activation functions (e.g., softmax, sigmoid, hyperbolic tangent, rectified linear unit) in various neurons (e.g., different neurons can have the same or different activation functions as each other). As still another example, the first deep learning neural network can include any suitable interneuron connections or interlayer connections (e.g., forward connections, skip connections, recurrent connections).

(51) In any case, the first deep learning neural network can be configured to receive, as input, data captured, measured, or recorded by the various sensors of the sensor component and to detect, as output, a vehicular collision in the vicinity based on such data. Accordingly, in various aspects, the inference component can electronically execute the first deep learning neural network on the vicinity data. In various instances, such execution can cause the first deep learning neural network to generate an outputted classification label. For example, the inference component can feed the vicinity data to an input layer of the first deep learning neural network, the vicinity data can complete a forward pass through one or more hidden layers of the first deep learning neural network, and an output layer of the first deep learning neural network can compute the outputted classification label based on activations from the one or more hidden layers. In any case, the outputted classification label can be one or more scalars, one or more vectors, one or more matrices, one or more tensors, or one or more character strings that indicate whether or not a vehicular collision has occurred within the vicinity of the vehicle. In some instances, if the outputted classification label indicates that a vehicular collision has occurred in the vicinity of the vehicle, then the outputted classification label can further indicate any suitable characteristics, properties, or attributes of the vehicular collision. As a non-limiting example, the outputted classification label can include any suitable scalars, vectors, matrices, tensors, or character strings indicating how many vehicles are involved in the vehicular collision. As another non-limiting example, the outputted classification label can include any suitable scalars, vectors, matrices, tensors, or character strings indicating whether or how many injured pedestrians are involved in the vehicular collision. As yet another non-limiting example, the outputted classification label can

include any suitable scalars, vectors, matrices, tensors, or character strings indicating an impact type of the vehicular collision (e.g., head-on, side-swipe, rear-end). As even another non-limiting example, the outputted classification label can include any suitable scalars, vectors, matrices, tensors, or character strings indicating whether the vehicular collision involves a rolled-over vehicle. As still another non-limiting example, the outputted classification label can include any suitable scalars, vectors, matrices, tensors, or character strings indicating whether the vehicular collision involves fire, flames, smoke, or a chance of explosion. As another non-limiting example, the outputted classification label can include any suitable scalars, vectors, matrices, tensors, or character strings indicating how severe the vehicular collision seems to be.

(52) In any case, the first deep learning neural network can be trained or otherwise configured, as described herein, to recognize, based on the vicinity data, a vehicular collision, and the outputted classification label can be any suitable electronic data indicating a presence or other characteristics of such vehicular collision. Note that, in some cases, the outputted classification label can indicate that no vehicular collision has occurred or was detected.

(53) To help cause the outputted classification label to be accurate, the first deep learning neural network can undergo any suitable type or paradigm of training (e.g., supervised training, unsupervised training, reinforcement learning). Accordingly, in various aspects, the first computerized tool can comprise a training component that can train the first deep learning neural network on a training dataset.

(54) In some instances, the training dataset can be an annotated training dataset. In such cases, the training dataset can include a set of training inputs and a set of ground-truth annotations that respectively correspond to the set of training inputs. In various aspects, any given training input can have the same format, size, or dimensionality as the vicinity data discussed above. In various instances, since it can be desired to train the deep learning neural network to detect vehicular collisions, each training input can correspond to a ground-truth annotation. In various cases, a ground-truth annotation, which can have the same format, size, or dimensionality as the outputted classification label discussed above, can be considered as a correct or accurate vehicular collision classification label that is known or deemed to correspond to a respective training input. Note that, in some cases, a training input can be associated with a vehicular collision (e.g., the training input can include sensor-data captured in a situation where a vehicular collision is occurring or is about to occur), and that, in other cases, a training input can be not associated with a vehicular collision (e.g., the training input can include sensor-data captured in a situation where no vehicular collision is occurring or is about to occur).

(55) If the training dataset is annotated, then the training component can, in various aspects, perform supervised training on the first deep learning neural network. Prior to the start of such supervised training, the internal parameters (e.g., weights, biases, convolutional kernels) of the first deep learning neural network can be randomly initialized.

(56) In various aspects, the training component can select from the training dataset any suitable training input and any suitable ground-truth annotation corresponding to such selected training input. In various instances, the training component can feed the selected training input to the first deep learning neural network, which can cause the first deep learning neural network to produce an output. For example, the training input can be received by an input layer of the first deep learning neural network, the training input can complete a forward pass through one or more hidden layers of the first deep learning neural network, and an output layer of the first deep learning neural network can compute the output based on activations generated by the one or more hidden layers.

(57) In various aspects, the output can be considered as a predicted or inferred vehicular collision classification label which the first deep learning neural network believes should correspond to the selected training input. In contrast, the selected ground-truth annotation can be considered as the correct or accurate vehicular collision classification label that is known or deemed to correspond to the selected training input. Note that, if the first deep learning neural network has so far undergone

no or little training, then the output can be highly inaccurate (e.g., the output can be very different from the selected ground-truth annotation).

(58) In any case, the training component can compute one or more errors or losses (e.g., mean absolute errors (MAE), mean squared errors (MSE), cross-entropies) between the output and the selected ground-truth annotation. In various aspects, the training component can update the internal parameters of the first deep learning neural network by performing backpropagation (e.g., stochastic gradient descent) driven by such computed errors or losses.

(59) In various instances, such supervised training procedure can be repeated for each training input in the training dataset, with the result being that the internal parameters of the first deep learning neural network can become iteratively optimized to accurately detect vehicular collisions based on inputted vicinity data. In various cases, the training component can implement any suitable training batch sizes, any suitable training termination criteria, or any suitable error, loss, or objective functions.

(60) In any case, the sensor component can obtain the vicinity data, and the inference component can execute (after training) the first deep learning neural network on the vicinity data, thereby yielding the outputted classification label.

(61) In various embodiments, the evidence component of the first computerized tool can, in response to the outputted classification label indicating that a vehicular collision has occurred in the vicinity of the vehicle, utilize the various sensors of the vehicle to electronically record post-collision evidence associated with the vicinity. In other words, the various sensors of the vehicle (e.g., the one or more cameras, microphones, thermometers, hygrometers, or proximity sensors) can capture, for any suitable temporal duration following detection of the vehicular collision, data representing whatever transpires in the vicinity of the vehicle, and the evidence component can record, store, maintain, or otherwise preserve such data.

(62) For example, suppose that the temporal duration is fifteen minutes. In such case, the one or more cameras of the vehicle can continually capture one or more images of the vicinity for fifteen minutes following the vehicular collision, where such images can be considered as forming a fifteen-minute video clip of the vicinity. Similarly, in such case, the one or more microphones of the vehicle can continually capture one or more noises occurring in the vicinity for fifteen minutes following the vehicular collision, where such noises can be considered as forming a fifteen-minute audio clip of the vicinity. Likewise, in such case, the one or more thermometers can continually capture one or more temperatures of the vicinity for fifteen minutes following the vehicular collision, where such temperatures can be considered as forming a fifteen-minute temperature measurement time-series of the vicinity. Moreover, in such case, the one or more hygrometers can continually capture one or more moisture levels of the vicinity for fifteen minutes following the vehicular collision, where such moisture levels can be considered as forming a fifteen-minute moisture measurement time-series of the vicinity. Furthermore, in such case, the one or more proximity sensors can continually capture one or more proximity detections of the vicinity for fifteen minutes following the vehicular collision, where such proximity detections can be considered as forming a fifteen-minute proximity measurement time-series of the vicinity. In various cases, such video clip, audio clip, temperature measurement time-series, moisture measurement time-series, or proximity measurement time-series can collectively be considered as the post-collision evidence.

(63) In various embodiments, the broadcast component of the first computerized tool can electronically broadcast, to the second computerized tool of the emergency service computing device, an electronic alert based on the post-collision evidence. In various aspects, the broadcast component can transmit the electronic alert to the second computerized tool via any suitable wireless electronic connection. For example, in some cases, such wireless electronic connection can be an Internet connection that makes use of one or more intermediary access points or intermediary routers. As another example, such wireless electronic connection can be a peer-to-peer

(P2P) communication link that can operate in the absence of an intermediary access point or intermediary router. For instance, such P2P communication link can be a BLUETOOTH® P2P connection (e.g., which can have an operable range of tens or dozens of meters) or a Wireless Fidelity (Wi-Fi) P2P connection (e.g., which can have an operable range of tens, dozens, or even hundreds of meters). In any case, the broadcast component can transmit the electronic alert to the second computerized tool of the emergency service computing device.

(64) In various aspects, the electronic alert can be any suitable electronic message that contains information pertaining to the vehicular collision detected by the first deep learning neural network. As an example, the electronic alert can, in some instances, include the post-collision evidence recorded by the evidence component. As another example, the electronic alert can, in some aspects, include the outputted classification label. As yet another example, the electronic alert can, in some cases, include the vicinity data.

(65) In some aspects, the sensor component can comprise a geolocation sensor, such as a global positioning sensor (“GPS”) or a Wi-Fi positioning sensor (“WPS”). In such cases, the geolocation sensor can capture or otherwise generate a geolocation stamp that indicates where (e.g., at which geographic location) the vicinity data was captured, measured, or recorded by the sensor component. Because the geolocation stamp can indicate where the vicinity data was captured, and because the vehicular collision can be detected based on the vicinity data, the geolocation stamp can be considered as indicating where the vehicular collision occurred. In any case, the electronic alert can, in various instances, include or otherwise specify such geolocation stamp.

(66) In some aspects, the sensor component can comprise a time sensor, such as a digital clock. In such cases, the time sensor can capture or otherwise generate a timestamp that indicates when (e.g., at what time or date) the vicinity data was captured, measured, or recorded by the sensor component. Because the timestamp can indicate when the vicinity data was captured, and because the vehicular collision can be detected based on the vicinity data, the timestamp can be considered as indicating when the vehicular collision occurred. In any case, the electronic alert can, in various instances, include or otherwise specify such timestamp.

(67) In various aspects, the electronic alert can further include an identifier associated with the vehicle. In various instances, the identifier can be any suitable piece of electronic data (e.g., an alphanumeric code) that indicates or otherwise represents an identity of the vehicle. For example, the identifier can be a make, model, or manufacturing year of the vehicle (e.g., such make, model, or manufacturing year can be hardcoded into the first computerized tool). As another example, the identifier can be a license plate number of the vehicle (e.g., such license plate number can be hardcoded into the first computerized tool). As yet another example, the identifier can be a vehicle identification number (VIN) of the vehicle (e.g., such VIN can be hardcoded into the first computerized tool). As still another example, the identifier can be a name or residential address of an owner of the vehicle (e.g., such name or address can be hardcoded into the first computerized tool; or the broadcast component can determine such name or address by searching any suitable database for the owner, where such database can be collated by license plate number or VIN). As even another example, the identifier can be a name or residential address of a current driver of the vehicle (e.g., the identity of the current driver can be determined via facial recognition, voice recognition, retina recognition, wearable beacon, or manual input).

(68) In various aspects, the electronic alert can further comprise an assistance request. In various instances, the assistance request can be any suitable electronic data that can indicate a specific type of emergency service assistance that should be dispatched to handle or otherwise address the vehicular collision. In various cases, the assistance request can be based on the outputted classification label. For example, if the outputted classification label indicates that the vehicular collision involves fire or flames, then the assistance request can ask that a firetruck be dispatched to address the vehicular collision. As another example, if the outputted classification label indicates that the vehicular collision is of a high severity level or involves injured pedestrians, then the

assistance request can ask that an ambulance be dispatched to address the vehicular collision. As even another example, if the outputted classification label indicates that the vehicular collision is of a low severity level, then the assistance request can indicate that dispatch of emergency services is not necessary.

(69) In any case, the first computerized tool (e.g., onboard the vehicle) can transmit the electronic alert to the second computerized tool (e.g., integrated into the emergency service computing device).

(70) In various embodiments, the receiver component of the second computerized tool can electronically receive or otherwise access the electronic alert. More specifically, any suitable wireless electronic connection (e.g., an Internet connection, a P2P communication link) can operatively couple the broadcast component of the first computerized tool to the receiver component of the second computerized tool. Accordingly, the broadcast component of the first computerized tool can transmit the electronic alert, and the receiver component of the second computerized tool can receive the electronic alert. In any case, the receiver component can electronically obtain or access the electronic alert, such that other components of the second computerized tool (e.g., the determination component, the execution component) can electronically interact with the electronic alert.

(71) In various aspects, the determination component of the second computerized tool can electronically parse, via any suitable parsing technique, the electronic alert. In other words, the determination component can read the contents of the electronic alert. In various instances, the determination component can generate a determination indicator based on such contents. In various cases, the determination indicator can be any suitable binomial or binary variable whose value represents whether or not the electronic alert indicates that a vehicular collision has been detected in the vicinity of the vehicle. For example, the electronic alert can include the outputted classification label, the geolocation stamp, and the timestamp, and the determination component can identify the outputted classification label, the geolocation stamp, and the timestamp by parsing the electronic alert. If the outputted classification label indicates a vehicular collision, then the determination component can conclude that the vehicular collision occurred at a location represented by the geolocation stamp at a time represented by the timestamp, and the determination indicator can accordingly be set to an active value or an active state. On the other hand, if the outputted classification label indicates no vehicular collision, then the determination component can conclude that no vehicular collision occurred at the location represented by the geolocation stamp at the time represented by the timestamp, and the determination indicator can accordingly be set to an inactive value or an inactive state.

(72) In various aspects, the execution component of the second computerized tool can facilitate, perform, conduct, or otherwise initiate any suitable electronic actions, in response to the determination indicator being set to the active value or the active state.

(73) As an example, such one or more electronic actions can include adjusting, updating, or otherwise modifying an electronic navigation display of an emergency service vehicle (e.g., a police car, an ambulance, a firetruck, a tow truck). In some cases, the electronic navigation display of the emergency service vehicle can be any suitable computer screen, monitor, or visual projection that is integrated into a dashboard of the emergency service vehicle. In other cases, the electronic navigation display of the emergency service vehicle can be any suitable computer screen, monitor, or visual projection that is integrated into a central console of the emergency service vehicle. In still other cases, the electronic navigation display of the emergency service vehicle can be any suitable computer screen, monitor, or visual projection that is integrated into a heads-up-display of the emergency service vehicle. In any case, in response to the determination indicator being set to the active value or the active state, the execution component can render any suitable graphical representation of the vehicular collision on the electronic navigation display. For instance, the electronic navigation display can illustrate a first symbol representing the emergency service

vehicle, can illustrate a second symbol representing a road on which the emergency service vehicle is traveling, and can illustrate a third symbol representing the presence of the vehicular collision.

(74) As another example, the one or more electronic actions can include calculating or otherwise generating an electronic navigation route for the emergency service vehicle, where such electronic navigation route can lead from a current position of the emergency service vehicle to the vehicular collision. In various aspects, the electronic navigation display of the emergency service vehicle can illustrate or otherwise render the electronic navigation route. That is, the electronic navigation display can depict one or more graphical representations of a route (e.g., of traffic directions) which, when followed, would lead the emergency service vehicle to the vehicular collision.

(75) As yet another example, the one or more electronic actions can include verifying whether or not the vehicular collision was properly detected by the vehicle. In particular, as mentioned above, the electronic alert can include the vicinity data captured by the various sensors of the vehicle, and the electronic alert can also include the outputted classification label generated by the first deep learning neural network of the vehicle. As explained above, the outputted classification label can indicate that the vehicular collision occurred in the vicinity of the vehicle. In other words, the first deep learning neural network can have inferred the presence of the vehicular collision, based on the vicinity data captured by the sensors of the vehicle.

(76) In various aspects, the execution component can electronically store, maintain, control, or otherwise access a second deep learning neural network that can be configured to detect vehicular collisions based on inputted sensor data. In various instances, the second deep learning neural network can exhibit any suitable artificial intelligence architecture and can be trained in any suitable fashion, as described above with respect to the first deep learning neural network.

(77) In any case, in response to the determination indicator being set to the active value or active state, the execution component can execute the second deep learning neural network on the vicinity data specified in the electronic alert, so as to double-check or otherwise verify the inference/conclusion of the first deep learning neural network.

(78) More specifically, an input layer of the second deep learning neural network can receive the vicinity data captured by the vehicle, the vicinity data captured by the vehicle can complete a forward pass through one or more hidden layers of the second deep learning neural network, and an output layer of the second deep learning neural network can compute a verification label based on activations provided by the one or more hidden layers. In various aspects, the verification label can have the same format, size, or dimensionality as the outputted classification label produced by the first deep learning neural network. In other words, the verification label can indicate whether a vehicular collision occurred in the vicinity of the vehicle, and if such a vehicular collision is determined to have occurred, the verification label can indicate various characteristics, attributes, or properties of such vehicular collision.

(79) In various aspects, the execution component can compare the verification label (produced by the second deep learning neural network) to the outputted classification label (produced by the first deep learning neural network). If the verification label matches the outputted classification label (e.g., if the verification label does not differ by more than any suitable threshold margin from the outputted classification label), then the execution component can verify the vehicular collision (e.g., can conclude that the first deep learning neural network correctly analyzed the vicinity data captured by the sensors of the vehicle). In contrast, if the verification label does not match the outputted classification label (e.g., if the verification label differs by more than any suitable threshold margin from the outputted classification label), then the execution component can fail to verify the vehicular collision (e.g., can conclude that the first deep learning neural network incorrectly analyzed the vicinity data captured by the sensors of the vehicle). In any of these cases, the second deep learning neural network of the emergency service computing device can be considered as double-checking the analytical work performed by the first deep learning neural network of the vehicle.

(80) In some embodiments, the first computerized tool can omit the evidence component. In such cases, rather than recording the post-collision evidence, the first computerized tool can instead initiate a live stream with the emergency service computing device. In particular, the broadcast component can, in response to the outputted classification label indicating that a vehicular collision has occurred in the vicinity, electronically broadcast a live stream of the vicinity to the emergency service computing device, using the various sensors of the vehicle. For example, the broadcast component can live-stream, to the emergency service computing device, images or video frames of the vicinity that are captured in real-time by the one or more cameras of the vehicle. As another example, the broadcast component can live-stream, to the emergency service computing device, noises occurring in the vicinity that are captured in real-time by the one or more microphones of the vehicle. As yet another example, the broadcast component can live-stream, to the emergency service computing device, air temperatures or surface temperatures of the vicinity that are captured in real-time by the one or more thermometers of the vehicle. As even another example, the broadcast component can live-stream, to the emergency service computing device, air moisture contents or surface moisture contents of the vicinity that are captured in real-time by the one or more hygrometers of the vehicle. As still another example, the broadcast component can live-stream, to the emergency service computing device, proximity detections between the vehicle and objects located in the vicinity that are captured in real-time by the one or more proximity sensors of the vehicle. In various aspects, the live stream provided by the broadcast component can be considered as allowing the emergency service computing device (e.g., as allowing a user or operator of the emergency service computing device) to observe the vehicular collision or its aftermath in real-time, notwithstanding that an emergency service vehicle might not yet have physically arrived at the scene of the vehicular collision.

(81) In various embodiments, the first computerized tool can comprise a battery component. In various aspects, the battery component can electronically monitor a remaining battery life of the vehicle, during the live stream. In particular, the battery component can continually or periodically compare the remaining battery life (e.g., remaining battery charge) of the vehicle to any suitable threshold. If the remaining battery life of the vehicle falls below the threshold, then the broadcast component can electronically transmit, during the live stream, a battery warning to the emergency service computing device. In various instances, the battery warning can be any suitable electronic message or notification that can indicate that the vehicle can no longer continue the live stream due to insufficient battery life.

(82) In some instances, if the remaining battery life of the vehicle falls below the threshold, then the battery component can implement any suitable electricity reroute actions, so as to attempt to prolong the remaining battery life of the vehicle. In other words, the battery component can shut-down or otherwise power-down any suitable electric loads of the vehicle that are unrelated to the live stream. For example, if an air conditioner of the vehicle is running during the live stream, then the battery component can power-down the air conditioner, in response to a determination that the remaining battery life of the vehicle is below the threshold (e.g., the battery component can cease expending battery power on the air conditioner, so that more battery power is available to sustain the live stream). As another example, if a seat heater or seat cooler of the vehicle is running during the live stream, then the battery component can power-down the seat heater or seat cooler, in response to a determination that the remaining battery life of the vehicle is below the threshold (e.g., the battery component can cease expending battery power on the seat heater or seat cooler, so that more battery power is available to sustain the live stream). As yet another example, if undercarriage lighting of the vehicle is running during the live stream, then the battery component can power-down the undercarriage lighting, in response to a determination that the remaining battery life of the vehicle is below the threshold (e.g., the battery component can cease expending battery power on the undercarriage lighting, so that more battery power is available to sustain the live stream).

(83) In various embodiments, the first computerized tool can comprise a remote-control component. In various aspects, the remote-control component can electronically control, adjust, or otherwise manipulate any suitable electronically-controllable features of the vehicle. In various instances, such electronically-controllable features can include electronically-controllable cameras of the vehicle (e.g., one or more cameras of the vehicle whose angles or zoom levels can be electronically adjusted). In various cases, such electronically-controllable features can include electronically-controllable speakers of the vehicle (e.g., one or more audio speakers of the vehicle whose volume levels or whose content-playbacks can be electronically adjusted). In various aspects, such electronically-controllable features can include electronically-controllable lighting of the vehicle (e.g., one or more lights of the vehicle whose brightness levels, colors, or angles can be electronically adjusted). In various instances, such electronically-controllable features can include electronically-controllable steering of the vehicle (e.g., one or more wheels of the vehicle whose steering angles can be electronically adjusted). In various cases, such electronically-controllable features can include electronically-controllable throttles of the vehicle (e.g., one or more wheels of the vehicle whose rotational speeds or torques can be electronically adjusted). In various aspects, such electronically-controllable features can include electronically-controllable braking of the vehicle (e.g., one or more brake pads of the vehicle whose application levels or compression levels can be electronically adjusted).

(84) In various instances, the broadcast component can electronically transmit, during the live stream, an indication of such electronically-controllable features of the vehicle to the receiver component of the second computerized tool (e.g., of the emergency service computing device). In response to the receiver component receiving, retrieving, or otherwise accessing the indication of such electronically-controllable features, the execution component of the second computerized tool (e.g., of the emergency service computing device) can transmit any suitable remote-control commands back to the first computerized tool (e.g., back to the vehicle). In various aspects, the remote-control commands can be any suitable electronic instructions to adjust, in any suitable specified fashions, any of the electronically-controllable features of the vehicle. For example, the remote-control commands can include an instruction to adjust an angle of an electronically-controllable camera of the vehicle by a specified angular displacement. As another example, the remote-control commands can include an instruction to adjust a zoom level of an electronically-controllable camera of the vehicle by a specified percentage. As yet another example, the remote-control commands can include an instruction to adjust a steering angle of an electronically-controllable wheel of the vehicle by a specified angular displacement. As even another example, the remote-control commands can include an instruction to adjust an amount of an electronically-controllable throttle of the vehicle by a specified percentage. As still another example, the remote-control commands can include an instruction to audibly reproduce or play specified sound data or voice data via an electronically-controllable speaker of the vehicle.

(85) In any case, the remote-control component of the first computerized tool can obey the remote-control commands transmitted by the second computerized tool. In other words, the remote-control component can adjust the electronically-controllable features of the vehicle, in accordance with or otherwise as specified by the remote-control commands. Accordingly, the emergency service computing device can be considered as controlling or otherwise acting vicariously through the vehicle. This can allow the emergency service computing device to effectively interact with the scene of the vehicular collision (e.g., to view the vehicular collision through the live-streaming cameras of the vehicle, to move the vehicle so as to view the vehicular collision from a different perspective or vantage point, to vocalize instructions or siren sounds through the speakers of the vehicle, to shine lights of the vehicle on the vehicular collision), notwithstanding that an emergency service vehicle might not yet actually be at the scene.

(86) Various embodiments described herein can be employed to use hardware or software to solve problems that are highly technical in nature (e.g., to facilitate artificially intelligent provision of

post-vehicular-collision evidence), that are not abstract and that cannot be performed as a set of mental acts by a human. Further, some of the processes performed can be performed by a specialized computer (e.g., a deep learning neural network having internal parameters such as convolutional kernels) for carrying out defined tasks related to peer-to-peer vehicular provision of artificially intelligent traffic analysis.

(87) For example, such defined tasks can include: capturing, by a device operatively coupled to a processor, onboard a first vehicle, and via one or more first cameras or one or more first microphones of the first vehicle, vicinity data associated with a first vicinity of the first vehicle; determining, by the device and via execution of a deep learning neural network on the vicinity data, whether a vehicular collision not involving the first vehicle has occurred in the first vicinity of the first vehicle; and recording, by the device, in response to a determination that the vehicular collision has occurred, and via the one or more first cameras or the one or more first microphones, first post-collision evidence associated with the first vicinity of the first vehicle.

(88) As another example, such defined tasks can include: capturing, by a device operatively coupled to a processor, onboard a vehicle, and via one or more cameras or one or more microphones of the vehicle, vicinity data associated with a vicinity of the vehicle; generating, by the device and via execution of a deep learning neural network on the vicinity data, a classification label indicating whether a vehicular collision not involving the vehicle has occurred in the vicinity of the vehicle; recording, by the device, in response to the classification label indicating that the vehicular collision has occurred, and via the one or more cameras or the one or more microphones, post-collision evidence associated with the vicinity of the vehicle; and broadcasting, by the device and in response to the classification label indicating that the vehicular collision has occurred, the classification label and the post-collision evidence to an emergency service computing device.

(89) As yet another example, such defined tasks can include: capturing, by a device operatively coupled to a processor, onboard a vehicle, and via one or more cameras or one or more microphones of the vehicle, vicinity data associated with a vicinity of the vehicle; determining, by the device and via execution of a deep learning neural network on the vicinity data, whether a vehicular collision not involving the vehicle has occurred in the vicinity of the vehicle; and broadcasting, by the device, in response to a determination that the vehicular collision has occurred, via the one or more cameras or the one or more microphones, and to an emergency service computing device, a post-collision live stream associated with the vicinity of the vehicle.

(90) As still another example, such defined tasks can include: capturing, by a device operatively coupled to a processor, onboard a vehicle, and via one or more cameras or one or more microphones of the vehicle, vicinity data associated with a vicinity of the vehicle; determining, by the device and via execution of a deep learning neural network on the vicinity data, whether a vehicular collision not involving the vehicle has occurred in the vicinity of the vehicle; and broadcasting, by the device, in response to a determination that the vehicular collision has occurred, and via the one or more cameras or the one or more microphones, one or more electronic notifications to an emergency service computing device.

(91) As even another example, such defined tasks can include: receiving, by a device operatively coupled to a processor, one or more electronic notifications broadcasted by a vehicle; determining, by the device and via parsing, whether the one or more electronic notifications indicate that a vehicular collision not involving the vehicle has occurred in a vicinity of the vehicle; and initiating, by the device and in response to a determination that the one or more electronic notifications indicate that the vehicular collision has occurred, one or more electronic actions based on the vehicular collision.

(92) Such defined tasks are not performed manually by humans. Indeed, neither the human mind nor a human with pen and paper can: electronically capture, measure, or otherwise record vicinity data using vehicle sensors (e.g., cameras, microphones, thermometers, hygrometers, or proximity sensors); electronically detect a vehicular collision by executing a deep learning neural network on

such vicinity data; and electronically transmit or receive information pertaining to such vehicular collision. Indeed, vehicle sensors and deep learning neural networks are inherently-computerized devices that simply cannot be implemented in any way by the human mind without computers. Accordingly, a computerized tool that can control vehicle sensors and that can train or execute a deep learning neural network on data captured by such vehicle sensors is likewise inherently-computerized and cannot be implemented in any sensible, practical, or reasonable way without computers.

(93) Moreover, various embodiments described herein can integrate into a practical application various teachings relating to artificially intelligent provision of post-vehicular-collision evidence. As explained above, some existing techniques rely upon eyewitness reports to capture the aftermath of a vehicular collision. However, such eyewitness reports can be vulnerable to misremembering or lying due to bias. As also explained above, other existing techniques rely upon traffic cameras to capture the aftermath of a vehicular collision. However, such traffic cameras are usually installed only at major intersections and cannot move to different vantage points. As also mentioned above, yet other existing techniques rely upon manual activation of personal computing devices to capture the aftermath of a vehicular collision. However, owners of such personal computing devices can forget or choose not to manually activate their personal computing devices when a vehicular collision occurs. These can be considered as various disadvantages of existing techniques.

(94) Various embodiments described herein can address various of these disadvantages. Specifically, various embodiments described herein can include outfitting a vehicle with a computerized tool, where such computerized tool can: automatically capture vicinity data via vehicle sensors (e.g., cameras, microphones, thermometers, hygrometers, proximity detectors); automatically execute a deep learning neural network on the vicinity data, thereby detecting a vehicular collision in the vicinity of the vehicle; and automatically recording or live-streaming, via the vehicular sensors, the aftermath of the detected vehicular collision to an emergency service computing device. In various aspects, the emergency service computing device can be outfitted with a computerized tool, wherein such computerized tool can: automatically receive an electronic alert pertaining to the detected vehicular collision; automatically parse the electronic alert to identify the vehicular collision; and automatically initiate any suitable electronic actions in response to the vehicular collision, such as updating an electronic navigation display of an emergency service vehicle, computing an electronic navigation route leading the vehicular collision, or double-checking the vehicular collision via its own deep learning neural network analysis. Such embodiments can more reliably capture the aftermath of a vehicular collision, as compared to various existing techniques (e.g., which rely on eyewitness reports, traffic cameras, or manual activation of personal computing devices). In some cases, the computerized tool of the emergency service computing device can even transmit any suitable remote-control instructions back to the computerized tool of the vehicle, so as to effectively or vicariously interact with the scene of the vehicular collision even before an emergency service vehicle actually arrives at the scene. In other words, an emergency service response time can be effectively reduced by various embodiments described herein. Accordingly, various embodiments can help to ameliorate various disadvantages of existing techniques. Thus, various embodiments described herein certainly constitute a concrete and tangible technical improvement. Therefore, various embodiments described herein clearly qualify as useful and practical applications of computers.

(95) Furthermore, various embodiments described herein can control real-world tangible devices based on the disclosed teachings. For example, various embodiments described herein can electronically control real-world vehicle sensors (e.g., real-world vehicle cameras, real-world vehicle microphones, real-world vehicle thermometers, real-world vehicle hygrometers, real-world vehicle proximity detectors), can electronically execute (or train) real-world deep learning neural networks on data captured by such real-world vehicle sensors, can electronically transmit or receive results outputted by such real-world deep learning neural networks, and can electronically render

such results on real-world computer screens or monitors.

(96) It should be appreciated that the herein figures and description provide non-limiting examples of various embodiments and are not necessarily drawn to scale.

(97) FIG. 1 illustrates an example, non-limiting block diagram **100** showing a vehicular collision occurring within a vicinity of a vehicle, where such vehicle can facilitate artificially intelligent provision of post-vehicular-collision evidence in accordance with one or more embodiments described herein.

(98) In various embodiments, there can be a vehicle **102**. In various aspects, the vehicle **102** can be any suitable vehicle or automobile (e.g., can be a car, a truck, a van, a motorcycle). In various instances, the vehicle **102** can have or otherwise exhibit any suitable type of propulsion system (e.g., can be an electric vehicle, can be a gasoline-powered or diesel-powered vehicle, can be a hybrid vehicle). In some cases, the vehicle **102** can be driving on any suitable road, street, lane, or highway at any suitable speed. In other cases, the vehicle **102** can, while driving, be stopped at an intersection, at a traffic light, at a stop sign, at a cross-walk, or at a traffic jam. In yet other cases, the vehicle **102** can be parked rather than driving (e.g., can be parked in a parking lot, by a curb, or in a driveway).

(99) In various aspects, there can be an emergency service system **110**. In various instances, the emergency service system **110** can be any suitable computing device that is associated with any suitable emergency service provider. In some cases, the emergency service system **110** can be integrated into any suitable emergency service vehicle (not shown), such as a police vehicle, an ambulance, a firetruck, a tow truck, or a helicopter. In other cases, the emergency service system **110** can be integrated into any suitable emergency service office or emergency service depot that is responsible for dispatching emergency service vehicles (e.g., a police station, a hospital, a fire station). In various instances, the emergency service system **110** can be any suitable distance away from the vehicle **102** (e.g., can be within mere feet of the vehicle **102**, or can be many miles away from the vehicle **102**).

(100) In any case, the vehicle **102** can comprise, have, or otherwise be outfitted or equipped with a collision evidence system **104**. In other words, the collision evidence system **104** can be onboard the vehicle **102**. In various aspects, the collision evidence system **104** can, as described herein, electronically monitor a vicinity **106** of the vehicle **102** for vehicular collisions.

(101) In various aspects, the vicinity **106** can be any suitable physical area that encompasses the immediate or nearby surroundings of the vehicle **102**. In other words, the vicinity **106** can be any suitable physical area or physical space that is within any suitable threshold distance in front of, beside, or behind the vehicle **102**. In some cases, as depicted in FIG. 1, the vicinity **106** can be considered as a circular space swept by any suitable radius extending from the vehicle **102** (e.g., the vehicle **102** can be at the center of such circular space, and such circular space can be considered as moving with the vehicle **102** as the vehicle **102** moves). Although FIG. 1 depicts the vicinity **106** as being circular, this is a mere non-limiting example for ease of illustration. In various aspects, the vicinity **106** can have any suitable shape (e.g., a regular shape or an irregular shape). In any case, the vicinity **106** can be considered as encompassing whatever surroundings happen to be near the vehicle **102** at any given instant in time. Accordingly, depending upon a current location of the vehicle **102**, the vicinity **106** can encompass one or more other vehicles (not shown), one or more buildings or portions of buildings (not shown), one or more street lanes (not shown), one or more street curbs (not shown), one or more highway medians (not shown), one or more sidewalks (not shown), one or more ditches or other off-road portions (not shown), one or more pedestrians (not shown), one or more animals (not shown), or any other suitable objects or fixtures (e.g., power poles, street lamps, street signs, fire hydrants, mailboxes, bus stops, benches).

(102) In various aspects, a vehicular collision **108** can occur within the vicinity **106** at any given time. In various instances, the vehicular collision **108** can be any suitable vehicular collision, crash, or accident not involving the vehicle **102**. In other words, the vehicular collision **108** can occur near

the vehicle **102**, such that the vehicle **102** can be considered as witnessing or spectating the vehicular collision **108**.

(103) In any case, as described herein, the collision evidence system **104** can continually or periodically scan, using vehicle sensors and deep learning, the vicinity **106** for vehicular collisions. When the vehicular collision **108** occurs in the vicinity **106**, the collision evidence system **104** can, as described herein, automatically detect the vehicular collision **108**. Upon such detection, the collision evidence system **104** can, as described herein, begin recording, via the vehicle sensors, an aftermath of the vehicular collision **108**. Furthermore, the collision evidence system **104** can, as described herein, electronically share such recorded evidence with the emergency service system **110**. In particular, the collision evidence system **104** can electronically share whatever recorded evidence it captures regarding the aftermath of the vehicular collision **108** with the emergency service system **110**, via a communication link **112**. In other words, the collision evidence system **104** and the emergency service system **110** can be communicatively coupled together by the communication link **112**. In various instances, the communication link **112** can be any suitable wireless electronic communication channel. In some cases, the communication link **112** can be any suitable Internet connection that utilizes one or more intermediate access points or intermediate routers. In other cases, the communication link **112** can be any suitable P2P connection that can operate or otherwise function in the absence of an intermediate access point or intermediate router. Non-limiting examples of such a P2P connection can include a BLUETOOTH® P2P connection or a Wi-Fi P2P connection (e.g., such as Wi-Fi DIRECT®).

(104) As described herein, the collision evidence system **104** can be considered as regularly monitoring the vicinity **106** for vehicular collisions. Whenever a vehicular collision (e.g., **108**) is detected, the collision evidence system **104** can automatically record an aftermath of such vehicular collision, and the collision evidence system **104** can transmit such recorded evidence to the emergency service system **110**. As also described herein, the emergency service system **110** can take any suitable electronic actions, based on such recorded evidence.

(105) In some cases, because the vehicle **102** can comprise the collision evidence system **104**, the vehicle **102** can be considered as a smart vehicle.

(106) FIG. 2 illustrates a block diagram of an example, non-limiting system **200** that can facilitate a broadcast-side of artificially intelligent provision of post-vehicular-collision evidence in accordance with one or more embodiments described herein. In other words, FIG. 2 depicts a non-limiting example embodiment of the collision evidence system **104**.

(107) In various embodiments, the collision evidence system **104** can comprise a processor **202** (e.g., computer processing unit, microprocessor) and a non-transitory computer-readable memory **204** that is operably or operatively or communicatively connected or coupled to the processor **202**. The non-transitory computer-readable memory **204** can store computer-executable instructions which, upon execution by the processor **202**, can cause the processor **202** or other components of the collision evidence system **104** (e.g., sensor component **206**, inference component **210**, evidence component **212**, broadcast component **214**) to perform one or more acts. In various embodiments, the non-transitory computer-readable memory **204** can store computer-executable components (e.g., sensor component **206**, inference component **210**, evidence component **212**, broadcast component **214**), and the processor **202** can execute the computer-executable components.

(108) In various embodiments, the collision evidence system **104** can comprise a sensor component **206**. In various aspects, as described herein, the sensor component **206** can obtain, via any suitable sensors of the vehicle **102**, vicinity data **208**. In various cases, the vicinity data **208** can exhibit any suitable format, size, or dimensionality. For example, the vicinity data **208** can comprise one or more scalars, one or more vectors, one or more matrices, one or more tensors, one or more character strings, or any suitable combination thereof.

(109) In various embodiments, the collision evidence system **104** can comprise an inference component **210**. In various instances, as described herein, the inference component **210** can detect a

vehicular collision (e.g., **108**) that occurs within the vicinity **106**, based on the vicinity data **208**.

(110) In various embodiments, the collision evidence system **104** can comprise an evidence component **212**. In various cases, as described herein, the evidence component **212** can record post-collision evidence, in response to the inference component **210** detecting a vehicular collision in the vicinity **106**.

(111) In various embodiments, the collision evidence system **104** can comprise a broadcast component **214**. In various cases, as described herein, the broadcast component **214** can inform, via the communication link **112**, the emergency service system **110** of the detected vehicular collision or of the recorded post-collision evidence.

(112) FIG. 3 illustrates a block diagram of an example, non-limiting system **300** including various sensors that can facilitate a broadcast-side of artificially intelligent provision of post-vehicular-collision evidence in accordance with one or more embodiments described herein.

(113) In various embodiments, the sensor component **206** can electronically control, electronically execute, electronically activate, or otherwise electronically access any suitable sensors of the vehicle **102**. In various aspects, such sensors can be external or road-facing. In other words, such sensors can be oriented or otherwise configured to monitor the vicinity **106** (e.g., the surroundings of the vehicle **102**) as the vehicle **102** drives around or is parked.

(114) As a non-limiting example, such sensors can include a set of vehicle cameras **302**. In various aspects, the set of vehicle cameras **302** can include any suitable number of any suitable types of cameras (e.g., of image-capture devices). In various instances, the set of vehicle cameras **302** can be integrated into or onto the vehicle **102**. In various cases, one or more of the set of vehicle cameras **302** can be forward-facing. For example, such one or more cameras can be integrated into or onto any suitable forward-facing surfaces, whether interior or exterior, of the vehicle **102** (e.g., can be built on a dash of the vehicle **102** so as to look through a front windshield of the vehicle **102**, can be built around the front windshield of the vehicle **102**, can be built into a front bumper of the vehicle **102**, can be built around headlights of the vehicle **102**, can be built into a hood of the vehicle **102**). Because such one or more cameras can be forward-facing, such one or more cameras can be configured to capture or otherwise record images or video frames of portions of the vicinity **106** that lie in front of the vehicle **102**. In various aspects, one or more of the set of vehicle cameras **302** can be rearward-facing. For example, such one or more cameras can be integrated into or onto any suitable rearward-facing surfaces, whether interior or exterior, of the vehicle **102** (e.g., can be built into or on a rearview mirror of the vehicle **102**, can be built into or onto sideview mirrors of the vehicle **102**, can be built around a rear windshield of the vehicle **102**, can be built into a rear bumper of the vehicle **102**, can be built around taillights of the vehicle **102**, can be built into a trunk-cover of the vehicle **102**). Because such one or more cameras can be rearward-facing, such one or more cameras can be configured to capture or otherwise record images or video frames of portions of the vicinity **106** that lie behind the vehicle **102**. In various instances, one or more of the set of vehicle cameras **302** can be laterally-facing. For example, such one or more cameras can be integrated into or onto any suitable lateral surfaces, whether interior or exterior, of the vehicle **102** (e.g., can be built into or around doors or door handles of the vehicle **102**, can be built into or around fenders of the vehicle **102**). Because such one or more cameras can be laterally-facing, such one or more cameras can be configured to capture or otherwise record images or video frames of portions of the vicinity **106** that lie beside the vehicle **102**.

(115) As another non-limiting example, such sensors can include a set of vehicle microphones **304**. In various aspects, the set of vehicle microphones **304** can include any suitable number of any suitable types of microphones (e.g., of sound-capture devices). In various instances, the set of vehicle microphones **304** can be integrated into or onto the vehicle **102**. In various cases, one or more of the set of vehicle microphones **304** can be forward-facing. For example, such one or more microphones can be integrated into or onto any suitable forward-facing surfaces, whether interior or exterior, of the vehicle **102**, so as to capture or otherwise record sounds or noises that occur in

portions of the vicinity **106** that lie in front of the vehicle **102**. In various aspects, one or more of the set of vehicle microphones **304** can be rearward-facing. For example, such one or more microphones can be integrated into or onto any suitable rearward-facing surfaces, whether interior or exterior, of the vehicle **102**, so as to capture or otherwise record sounds or noises that occur in portions of the vicinity **106** that lie behind the vehicle **102**. In various instances, one or more of the set of vehicle microphones **304** can be laterally-facing. For example, such one or more microphones can be integrated into or onto any suitable lateral surfaces, whether interior or exterior, of the vehicle **102**, so as to capture or otherwise record sounds or noises that occur in portions of the vicinity **106** that lie beside the vehicle **102**.

(116) As yet another non-limiting example, such sensors can include a set of vehicle thermometers **306**. In various aspects, the set of vehicle thermometers **306** can include any suitable number of any suitable types of thermometers (e.g., of temperature sensors). In various instances, the set of vehicle thermometers **306** can be integrated into or onto the vehicle **102**. In various cases, one or more of the set of vehicle thermometers **306** can be forward-facing. For example, such one or more thermometers can be integrated into or onto any suitable forward-facing surfaces, whether interior or exterior, of the vehicle **102**, so as to capture or otherwise record air temperatures or road surface temperatures associated with portions of the vicinity **106** that lie in front of the vehicle **102**. In various aspects, one or more of the set of vehicle thermometers **306** can be rearward-facing. For example, such one or more thermometers can be integrated into or onto any suitable rearward-facing surfaces, whether interior or exterior, of the vehicle **102**, so as to capture or otherwise record air temperatures or road surface temperatures associated with portions of the vicinity **106** that lie behind the vehicle **102**. In various instances, one or more of the set of vehicle thermometers **306** can be laterally-facing. For example, such one or more thermometers can be integrated into or onto any suitable lateral surfaces, whether interior or exterior, of the vehicle **102**, so as to capture or otherwise record air temperatures or road surface temperatures associated with portions of the vicinity **106** that lie beside the vehicle **102**.

(117) As even another non-limiting example, such sensors can include a set of vehicle hygrometers **308**. In various aspects, the set of vehicle hygrometers **308** can include any suitable number of any suitable types of hygrometers (e.g., of moisture or humidity sensors). In various instances, the set of vehicle hygrometers **308** can be integrated into or onto the vehicle **102**. In various cases, one or more of the set of vehicle hygrometers **308** can be forward-facing. For example, such one or more hygrometers can be integrated into or onto any suitable forward-facing surfaces, whether interior or exterior, of the vehicle **102**, so as to capture or otherwise record air humidities or road surface moisture levels associated with portions of the vicinity **106** that lie in front of the vehicle **102**. In various aspects, one or more of the set of vehicle hygrometers **308** can be rearward-facing. For example, such one or more hygrometers can be integrated into or onto any suitable rearward-facing surfaces, whether interior or exterior, of the vehicle **102**, so as to capture or otherwise record air humidities or road surface moisture levels associated with portions of the vicinity **106** that lie behind the vehicle **102**. In various instances, one or more of the set of vehicle hygrometers **308** can be laterally-facing. For example, such one or more hygrometers can be integrated into or onto any suitable lateral surfaces, whether interior or exterior, of the vehicle **102**, so as to capture or otherwise record air humidities or road surface moisture levels associated with portions of the vicinity **106** that lie beside the vehicle **102**.

(118) As still another non-limiting example, such sensors can include a set of vehicle proximity sensors **310**. In various aspects, the set of vehicle proximity sensors **310** can include any suitable number of any suitable types of proximity sensors (e.g., of radar, sonar, or lidar sensors). In various instances, the set of vehicle proximity sensors **310** can be integrated into or onto the vehicle **102**. In various cases, one or more of the set of vehicle proximity sensors **310** can be forward-facing. For example, such one or more proximity sensors can be integrated into or onto any suitable forward-facing surfaces, whether interior or exterior, of the vehicle **102**, so as to capture or otherwise record

proximities of tangible objects located in portions of the vicinity **106** that lie in front of the vehicle **102**. In various aspects, one or more of the set of vehicle proximity sensors **310** can be rearward-facing. For example, such one or more proximity sensors can be integrated into or onto any suitable rearward-facing surfaces, whether interior or exterior, of the vehicle **102**, so as to capture or otherwise record proximities of tangible objects located in portions of the vicinity **106** that lie behind the vehicle **102**. In various instances, one or more of the set of vehicle proximity sensors **310** can be laterally-facing. For example, such one or more proximity sensors can be integrated into or onto any suitable lateral surfaces, whether interior or exterior, of the vehicle **102**, so as to capture or otherwise record proximities of tangible objects located in portions of the vicinity **106** that lie beside the vehicle **102**.

(119) In any case, the sensor component **206** can utilize such sensors to capture, record, or otherwise measure the vicinity data **208**.

(120) For example, the set of vehicle cameras **302** can capture a set of vicinity images **312** while the vehicle **102** is driving or parked. In various aspects, the set of vicinity images **312** can include any suitable number of images or video frames (e.g., any suitable number of two-dimensional pixel arrays) that can depict portions of the vicinity **106** (e.g., portions of the vicinity **106** that lie in front of, behind, or beside the vehicle **102**).

(121) As another example, the set of vehicle microphones **304** can capture a set of vicinity noises **314** while the vehicle **102** is driving or parked. In various instances, the set of vicinity noises **314** can include any suitable number of audio clips that can represent noises occurring in portions of the vicinity **106** (e.g., in portions of the vicinity **106** that lie in front of, behind, or beside the vehicle **102**).

(122) As yet another example, the set of vehicle thermometers **306** can capture a set of vicinity temperatures **316** while the vehicle **102** is driving or parked. In various aspects, the set of vicinity temperatures **316** can include any suitable number of temperature measurements that can represent air temperatures or road surface temperatures associated with portions of the vicinity **106** (e.g., with portions of the vicinity **106** that lie in front of, behind, or beside the vehicle **102**).

(123) As still another example, the set of vehicle hygrometers **308** can capture a set of vicinity humidities **318** while the vehicle **102** is driving or parked. In various aspects, the set of vicinity humidities **318** can include any suitable number of humidity measurements or moisture measurements that can represent air humidity levels or road surface moisture levels associated with portions of the vicinity **106** (e.g., with portions of the vicinity **106** that lie in front of, behind, or beside the vehicle **102**).

(124) As even another example, the set of vehicle proximity sensors **310** can capture a set of vicinity proximity detections **320** while the vehicle **102** is driving or parked. In various aspects, the set of vicinity proximity detections **320** can include any suitable number of proximity detections (e.g., of radar, sonar, or lidar detections) that can represent distances between the vehicle **102** and nearby objects located in portions of the vicinity **106** (e.g., in portions of the vicinity **106** that lie in front of, behind, or beside the vehicle **102**).

(125) Although not explicitly shown in the figures, any of the set of vehicle cameras **302**, any of the set of vehicle microphones **304**, any of the set of vehicle thermometers **306**, any of the set of vehicle hygrometers **308**, or any of the set of vehicle proximity sensors **310** can be integrated into or onto a drone (e.g., an autonomous or remotely-operated drone) that can be launched by, controlled by, or otherwise associated with the vehicle **102**. For example, the vehicle **102** can launch an air-based or ground-based drone, and such drone can travel along with the vehicle **102** (e.g., can travel in front of the vehicle **102**, behind the vehicle **102**, or beside the vehicle **102**). As such drone travels along with the vehicle **102**, such drone can utilize any suitable sensors (e.g., cameras, microphones, thermometers, hygrometers, proximity sensors) integrated into or onto the drone to monitor the vicinity **106**. In various cases, such drone can electronically transmit (e.g., via a P2P communication link) any data captured by its sensors back to the vehicle **102**, and such

captured data can be considered as part of the vicinity data **208**.

(126) In any case, the set of vicinity images **312**, the set of vicinity noises **314**, the set of vicinity temperatures **316**, the set of vicinity humidities **318**, and the set of vicinity proximity detections **320** can collectively be considered as the vicinity data **208**.

(127) FIG. **4** illustrates a block diagram of an example, non-limiting system **400** including a deep learning neural network and a vehicular collision classification label that can facilitate a broadcast-side of artificially intelligent provision of post-vehicular-collision evidence in accordance with one or more embodiments described herein. As shown, the system **400** can, in some cases, comprise the same components as the system **300**, and can further comprise a deep learning neural network **402** or a vehicular collision classification label **404**.

(128) In various embodiments, the inference component **210** can electronically store, electronically maintain, electronically control, or otherwise electronically access the deep learning neural network **402**. In various aspects, the deep learning neural network **402** can have or otherwise exhibit any suitable internal architecture. For instance, the deep learning neural network **402** can have an input layer, one or more hidden layers, and an output layer. In various instances, any of such layers can be coupled together by any suitable interneuron connections or interlayer connections, such as forward connections, skip connections, or recurrent connections. Furthermore, in various cases, any of such layers can be any suitable types of neural network layers having any suitable learnable or trainable internal parameters. For example, any of such input layer, one or more hidden layers, or output layer can be convolutional layers, whose learnable or trainable parameters can be convolutional kernels. As another example, any of such input layer, one or more hidden layers, or output layer can be dense layers, whose learnable or trainable parameters can be weight matrices or bias values. As still another example, any of such input layer, one or more hidden layers, or output layer can be batch normalization layers, whose learnable or trainable parameters can be shift factors or scale factors. Further still, in various cases, any of such layers can be any suitable types of neural network layers having any suitable fixed or non-trainable internal parameters. For example, any of such input layer, one or more hidden layers, or output layer can be non-linearity layers, padding layers, pooling layers, or concatenation layers.

(129) No matter the internal architecture of the deep learning neural network **402**, the deep learning neural network **402** can be configured to detect vehicular collisions based on inputted vicinity data. Accordingly, the inference component **210** can electronically execute the deep learning neural network **402** on the vicinity data **208**, thereby yielding the vehicular collision classification label **404**. Various non-limiting aspects are described with respect to FIG. **5**.

(130) FIG. **5** illustrates an example, non-limiting block diagram **500** showing how the deep learning neural network **402** can generate the vehicular collision classification label **404** based on the vicinity data **208** in accordance with one or more embodiments described herein.

(131) As shown, the inference component **210** can, in various aspects, execute the deep learning neural network **402** on the vicinity data **208**, and such execution can cause the deep learning neural network **402** to produce the vehicular collision classification label **404**. More specifically, the inference component **210** can feed the vicinity data **208** (e.g., the set of vicinity images **312**, the set of vicinity noises **314**, the set of vicinity temperatures **316**, the set of vicinity humidities **318**, or the set of vicinity proximity detections **320**) to an input layer of the deep learning neural network **402**. In various instances, the vicinity data **208** (e.g., the set of vicinity images **312**, the set of vicinity noises **314**, the set of vicinity temperatures **316**, the set of vicinity humidities **318**, or the set of vicinity proximity detections **320**) can complete a forward pass through one or more hidden layers of the deep learning neural network **402**. In various cases, an output layer of the deep learning neural network **402** can compute the vehicular collision classification label **404**, based on activation maps or intermediate features produced by the one or more hidden layers.

(132) In various aspects, the vehicular collision classification label **404** can be any suitable electronic data exhibiting any suitable format, size, or dimensionality. That is, the vehicular

collision classification label **404** can be one or more scalars, one or more vectors, one or more matrices, one or more tensors, one or more character strings, or any suitable combination thereof. In various instances, the sensor component **206** can capture, measure, or otherwise record the vicinity data **208** when the vehicle **102** is at any given geolocation (e.g., when the vicinity **106** is at that given geolocation), and the vehicular collision classification label **404** can indicate, specify, convey, or otherwise represent whether a vehicular collision (e.g., **108**) has occurred or is occurring at such given geolocation. In some cases, if the vehicular collision classification label **404** indicates that a vehicular collision has occurred or is occurring at such given geolocation, then the vehicular collision classification label **404** can further indicate, specify, convey, or otherwise represent any suitable characteristics, attributes, or properties of such vehicular collision. Various non-limiting aspects are described with respect to FIG. 6.

(133) FIG. 6 illustrates an example, non-limiting block diagram **600** of a vehicular collision classification label in accordance with one or more embodiments described herein. That is, FIG. 6 depicts a non-limiting example embodiment of the vehicular collision classification label **404**.

(134) In various aspects, as shown, the vehicular collision classification label **404** can comprise a presence indicator **602**. In various instances, the presence indicator **602** can have any suitable format, size, or dimensionality. That is, the presence indicator **602** can be one or more scalars, one or more vectors, one or more matrices, one or more tensors, one or more character strings, or any suitable combination thereof. In any case, the presence indicator **602** can indicate, convey, or otherwise represent a presence or an absence of a vehicular collision in the vicinity **106**. For instance, the sensor component **206** can capture the vicinity data **208** when the vehicle **102** is at a given geolocation, and the deep learning neural network **402** can be trained or otherwise configured, as described herein, to determine, based on the vicinity data **208**, whether a vehicular collision (e.g., **108**) is occurring at that given geolocation. In other words, if a vehicular collision is occurring at that given geolocation, some manifestation of such vehicular collision can be conveyed in the vicinity data **208** (e.g., the vehicular collision can be depicted in the set of vicinity images **312**, distinctive sounds of the vehicular collision can be captured in the set of vicinity noises **314**, the vehicular collision can cause a distinctive anomaly in the set of vicinity proximity detections **320**), and the deep learning neural network **402** can recognize such manifestation of the vehicular collision. Conversely, if no vehicular collision is occurring at that given geolocation, no manifestation of such vehicular collision would be conveyed in the vicinity data **208** (e.g., no vehicular collision would be depicted in the set of vicinity images **312**, no distinctive sounds of a vehicular collision would be captured in the set of vicinity noises **314**, no distinctive anomalies of a vehicular collision would be in the set of vicinity proximity detections **320**), and the deep learning neural network **402** can recognize such lack of manifestation of a vehicular collision. In any of these cases, the presence indicator **602** can represent the determination, inference, or conclusion generated by the deep learning neural network **402** with respect to the presence or absence of the vehicular collision.

(135) As a non-limiting example, the presence indicator **602** can be a binary or binomial variable; that is, a variable that can take on one of two possible discrete states. In such case, one of the two possible discrete states can represent a “present” state, whereas the other of the two possible discrete states can represent an “absent” state. That is, the presence indicator **602** can take on the “present” state when the deep learning neural network **402** infers that a vehicular collision is occurring, and the presence indicator **602** can take on the “absent” state when the deep learning neural network **402** instead infers that no vehicular collision is occurring. As another non-limiting example, the presence indicator **602** can be a scalar whose magnitude (e.g., ranging continuously from 0 to 1) represents a likelihood or probability that a vehicular collision is occurring (or is not occurring).

(136) In various aspects, as shown, the vehicular collision classification label **404** can comprise a collision cardinality indicator **604**. In various instances, the collision cardinality indicator **604** can

have any suitable format, size, or dimensionality. That is, the collision cardinality indicator **604** can be one or more scalars, one or more vectors, one or more matrices, one or more tensors, one or more character strings, or any suitable combination thereof. In any case, the collision cardinality indicator **604** can indicate, convey, or otherwise represent how many vehicles are involved in a vehicular collision that is occurring in the vicinity **106**. For instance, the sensor component **206** can capture the vicinity data **208** when the vehicle **102** is at a given geolocation, and the deep learning neural network **402** can be trained or otherwise configured, as described herein, to determine, based on the vicinity data **208**, not just that a vehicular collision (e.g., **108**) is occurring at that given geolocation, but also how many vehicles are involved in such vehicular collision. In other words, if a vehicular collision is occurring at that given geolocation, some manifestation of how many vehicles are involved in such vehicular collision can be conveyed in the vicinity data **208** (e.g., the number of involved/damaged vehicles can be depicted in the set of vicinity images **312**, distinctive sounds associated with the number of involved/damaged vehicles can be captured in the set of vicinity noises **314**, distinctive anomalies caused by the number of involved/damaged vehicles can be in the set of vicinity proximity detections **320**), and the deep learning neural network **402** can recognize such manifestation of how many vehicles are involved in the vehicular collision. In any of these cases, the collision cardinality indicator **604** can represent the determination, inference, or conclusion generated by the deep learning neural network **402** with respect to how many vehicles are involved in a detected vehicular collision.

(137) As a non-limiting example, the collision cardinality indicator **604** can be a binary or binomial variable that can take on one of two possible discrete states. In such case, one of the two possible discrete states can represent a “single-vehicle” state, whereas the other of the two possible discrete values can represent a “multi-vehicle” state. That is, the collision cardinality indicator **604** can take on the “single-vehicle” state when the deep learning neural network **402** infers that a detected vehicular collision involves only a single vehicle, and the collision cardinality indicator **604** can take on the “multi-vehicle” state when the deep learning neural network **402** instead infers that the detected vehicular collision involves more than a single vehicle. As another non-limiting example, the collision cardinality indicator **604** can be a multinomial variable; that is, a variable that can take on one of three or more possible discrete states. In such case, the three or more possible discrete states can respectively represent any suitable vehicle cardinality labels or vehicle cardinality states (e.g., a “single-vehicle” state, a “two-vehicle” state, a “three-vehicle” state, a “four-or-more-vehicle” state). As yet another non-limiting example, the collision cardinality indicator **604** can be a scalar whose magnitude represents how many vehicles are involved in a detected vehicular collision.

(138) In various aspects, as shown, the vehicular collision classification label **404** can comprise an injured pedestrian indicator **606**. In various instances, the injured pedestrian indicator **606** can have any suitable format, size, or dimensionality. That is, the injured pedestrian indicator **606** can be one or more scalars, one or more vectors, one or more matrices, one or more tensors, one or more character strings, or any suitable combination thereof. In any case, the injured pedestrian indicator **606** can indicate, convey, or otherwise represent whether (or how many) pedestrians seem to have been injured in a vehicular collision that is occurring in the vicinity **106**. For instance, the sensor component **206** can capture the vicinity data **208** when the vehicle **102** is at a given geolocation, and the deep learning neural network **402** can be trained or otherwise configured, as described herein, to determine, based on the vicinity data **208**, not just that a vehicular collision (e.g., **108**) is occurring at that given geolocation, but also whether (or how many) pedestrians have been injured by the vehicular collision. In other words, if pedestrians have been injured in a vehicular collision that is occurring at that given geolocation, some manifestation of those injured pedestrians can be conveyed in the vicinity data **208** (e.g., the injured pedestrians can be depicted in the set of vicinity images **312**, distinctive sounds associated with the injured pedestrians can be captured in the set of vicinity noises **314**, distinctive anomalies caused by the injured pedestrians can be in the set of

vicinity proximity detections **320**), and the deep learning neural network **402** can recognize such manifestation of injured pedestrians. Conversely, if no pedestrians have been injured in the vehicular collision, no manifestation of such injured pedestrians would be conveyed in the vicinity data **208** (e.g., no injured pedestrians would be depicted in the set of vicinity images **312**, no distinctive sounds of injured pedestrians would be captured in the set of vicinity noises **314**, no distinctive anomalies associated with injured pedestrians would be in the set of vicinity proximity detections **320**), and the deep learning neural network **402** can recognize such lack of manifestation of injured pedestrians. In any of these cases, the injured pedestrian indicator **606** can represent the determination, inference, or conclusion generated by the deep learning neural network **402** with respect to whether (or how many) pedestrians have been injured by a detected vehicular collision. (139) As a non-limiting example, the injured pedestrian indicator **606** can be a binary or binomial variable that can take on one of two possible discrete states. In such case, one of the two possible discrete states can represent a “no-injured-pedestrians” state, whereas the other of the two possible discrete values can represent a “one-or-more-injured-pedestrians” state. That is, the injured pedestrian indicator **606** can take on the “no-injured-pedestrians” state when the deep learning neural network **402** infers that a detected vehicular collision involves no injured pedestrians, and the injured pedestrian indicator **606** can take on the “one-or-more-injured-pedestrians” state when the deep learning neural network **402** instead infers that the detected vehicular collision involves at least one injured pedestrian. As another non-limiting example, the injured pedestrian indicator **606** can be a multinomial variable that can take on one of three or more possible discrete states. In such case, the three or more possible discrete states can respectively represent any suitable injured pedestrian cardinality labels or injured pedestrian cardinality states (e.g., a “no-injured-pedestrians” state, a “one-injured pedestrian state” state, a “two-injured-pedestrians” state, a “three-or-more-injured-pedestrians” state). As yet another non-limiting example, the injured pedestrian indicator **606** can be a scalar whose magnitude represents how many injured pedestrians are involved in a detected vehicular collision.

(140) In various aspects, as shown, the vehicular collision classification label **404** can comprise an impact type indicator **608**. In various instances, the impact type indicator **608** can have any suitable format, size, or dimensionality. That is, the impact type indicator **608** can be one or more scalars, one or more vectors, one or more matrices, one or more tensors, one or more character strings, or any suitable combination thereof. In any case, the impact type indicator **608** can indicate, convey, or otherwise represent a type of vehicular impact involved in a vehicular collision that is occurring in the vicinity **106**. For instance, the sensor component **206** can capture the vicinity data **208** when the vehicle **102** is at a given geolocation, and the deep learning neural network **402** can be trained or otherwise configured, as described herein, to determine, based on the vicinity data **208**, not just that a vehicular collision (e.g., **108**) is occurring at that given geolocation, but also what type of vehicular impact (e.g., head-on impact (sub-types of which can include full-overlap, offset or partial-overlap, angled, glancing, or underdrive), rear-end impact (sub-types of which can include full-overlap, offset or partial-overlap, angled, glancing, or underdrive), side-impact (sub-types of which can include offzone or L-type, non-offzone or non-L-type, left, right, near, or far), or side-swipe) seems to be involved in the vehicular collision. In other words, if a vehicular collision that is occurring at that given geolocation involves a head-on impact, some manifestation of the head-on impact can be conveyed in the vicinity data **208** (e.g., damaged front-ends can be depicted in the set of vicinity images **312**, distinctive sounds associated with head-on impacts can be captured in the set of vicinity noises **314**, distinctive anomalies caused by a head-on impact can be in the set of vicinity proximity detections **320**), and the deep learning neural network **402** can recognize such manifestation of head-on impact. On the other hand, if the vehicular collision instead involves a side-swipe, some manifestation of the side-swipe can be conveyed in the vicinity data **208** (e.g., scraped vehicle doors can be depicted in the set of vicinity images **312**, distinctive sounds associated with side-swipes can be captured in the set of vicinity noises **314**, distinctive anomalies

caused by a side-swipe can be in the set of vicinity proximity detections **320**), and the deep learning neural network **402** can recognize such manifestation of side-swipe. In any of these cases, the impact type indicator **608** can represent the determination, inference, or conclusion generated by the deep learning neural network **402** with respect to what type of impact seems to be involved in a detected vehicular collision.

(141) As a non-limiting example, the impact type indicator **608** can be a multinomial variable that can take on one of three or more possible discrete states. In such case, the three or more possible discrete states can respectively represent any suitable impact type labels or impact type states. For instance, the impact type indicator **608** can have a “head-on-impact” state, a “rear-end-impact” state, a “side-impact” state, or a “side-swipe” state.

(142) In various aspects, as shown, the vehicular collision classification label **404** can comprise a roll-over indicator **610**. In various instances, the roll-over indicator **610** can have any suitable format, size, or dimensionality. That is, the roll-over indicator **610** can be one or more scalars, one or more vectors, one or more matrices, one or more tensors, one or more character strings, or any suitable combination thereof. In any case, the roll-over indicator **610** can indicate, convey, or otherwise represent whether a vehicular collision that is occurring in the vicinity **106** involves a rolled-over (e.g., upside-down or sideways-up) vehicle. For instance, the sensor component **206** can capture the vicinity data **208** when the vehicle **102** is at a given geolocation, and the deep learning neural network **402** can be trained or otherwise configured, as described herein, to determine, based on the vicinity data **208**, not just that a vehicular collision (e.g., **108**) is occurring at that given geolocation, but also whether that vehicular collision seems to involve a rolled-over vehicle. In other words, if a vehicular collision that is occurring at that given geolocation involves a rolled-over vehicle, some manifestation of the rolled-over vehicle can be conveyed in the vicinity data **208** (e.g., the rolled-over vehicle can be depicted in the set of vicinity images **312**, distinctive sounds associated with roll-over can be captured in the set of vicinity noises **314**, distinctive anomalies caused by a roll-over can be in the set of vicinity proximity detections **320**), and the deep learning neural network **402** can recognize such manifestation of the rolled-over vehicle.

Conversely, if the vehicular collision involves no rolled-over vehicle, no manifestation of a rolled-over vehicle would be conveyed in the vicinity data **208** (e.g., no rolled-over vehicle would be depicted in the set of vicinity images **312**, no distinctive sounds associated with roll-over would be captured in the set of vicinity noises **314**, no distinctive anomalies caused by a roll-over would be in the set of vicinity proximity detections **320**), and the deep learning neural network **402** can recognize such lack of manifestation of roll-over. In any of these cases, the roll-over indicator **610** can represent the determination, inference, or conclusion generated by the deep learning neural network **402** with respect to whether a detected vehicular collision involves a roll-over.

(143) As a non-limiting example, the roll-over indicator **610** can be a binary or binomial variable that can take on one of two possible discrete states. In such case, one of the two possible discrete states can represent a “roll-over” state, whereas the other of the two possible discrete states can represent an “no-roll-over” state. That is, the roll-over indicator **610** can take on the “roll-over” state when the deep learning neural network **402** infers that a detected vehicular collision involves a roll-over, and the roll-over indicator **610** can take on the “no-roll-over” state when the deep learning neural network **402** instead infers that the detected vehicular collision does not involve a roll-over. As another non-limiting example, the roll-over indicator **610** can be a scalar whose magnitude (e.g., ranging continuously from 0 to 1) represents a likelihood or probability that a detected vehicular collision involves a roll-over (or does not involve a roll-over).

(144) In various aspects, as shown, the vehicular collision classification label **404** can comprise a fire indicator **612**. In various instances, the fire indicator **612** can have any suitable format, size, or dimensionality. That is, the fire indicator **612** can be one or more scalars, one or more vectors, one or more matrices, one or more tensors, one or more character strings, or any suitable combination thereof. In any case, the fire indicator **612** can indicate, convey, or otherwise represent whether a

vehicular collision that is occurring in the vicinity **106** involves fire, flames, smoke, or other potentially explosive aspects. For instance, the sensor component **206** can capture the vicinity data **208** when the vehicle **102** is at a given geolocation, and the deep learning neural network **402** can be trained or otherwise configured, as described herein, to determine, based on the vicinity data **208**, not just that a vehicular collision (e.g., **108**) is occurring at that given geolocation, but also whether that vehicular collision seems to involve a vehicular fire. In other words, if a vehicular collision that is occurring at that given geolocation involves a vehicular fire, some manifestation of the vehicular fire can be conveyed in the vicinity data **208** (e.g., fire, flames, or smoke can be depicted in the set of vicinity images **312**, distinctive sounds associated with vehicular fires can be captured in the set of vicinity noises **314**, distinctive anomalies caused by vehicular fires can be in the set of vicinity temperatures **316** or the set of vicinity humidities **318**), and the deep learning neural network **402** can recognize such manifestation of the vehicular fire. Conversely, if the vehicular collision involves no vehicular fire, no manifestation of a vehicular fire would be conveyed in the vicinity data **208** (e.g., no fire, flames, or smoke would be depicted in the set of vicinity images **312**, no distinctive sounds associated with vehicular fires would be captured in the set of vicinity noises **314**, no distinctive anomalies caused by vehicular fires would be in the set of vicinity temperatures **316** or the set of vicinity humidities **318**), and the deep learning neural network **402** can recognize such lack of manifestation of vehicular fire. In any of these cases, the fire indicator **612** can represent the determination, inference, or conclusion generated by the deep learning neural network **402** with respect to whether a detected vehicular collision involves a vehicular fire.

(145) As a non-limiting example, the fire indicator **612** can be a binary or binomial variable that can take on one of two possible discrete states. In such case, one of the two possible discrete states can represent a “fire” state, whereas the other of the two possible discrete states can represent an “no-fire” state. That is, the fire indicator **612** can take on the “fire” state when the deep learning neural network **402** infers that a detected vehicular collision involves a vehicular fire, and the fire indicator **612** can take on the “no-fire” state when the deep learning neural network **402** instead infers that the detected vehicular collision does not involve a vehicular fire. As another non-limiting example, the fire indicator **612** can be a scalar whose magnitude (e.g., ranging continuously from 0 to 1) represents a likelihood or probability that a detected vehicular collision involves a vehicular fire (or does not involve a vehicular fire).

(146) In various aspects, as shown, the vehicular collision classification label **404** can comprise a severity indicator **614**. In various instances, the severity indicator **614** can have any suitable format, size, or dimensionality. That is, the severity indicator **614** can be one or more scalars, one or more vectors, one or more matrices, one or more tensors, one or more character strings, or any suitable combination thereof. In any case, the severity indicator **614** can indicate, convey, or otherwise represent how severe a vehicular collision that is occurring in the vicinity **106** seems to be. For instance, the sensor component **206** can capture the vicinity data **208** when the vehicle **102** is at a given geolocation, and the deep learning neural network **402** can be trained or otherwise configured, as described herein, to determine, based on the vicinity data **208**, not just that a vehicular collision (e.g., **108**) is occurring at that given geolocation, but also a severity level of such vehicular collision. In other words, if a highly-severe vehicular collision is occurring at that given geolocation, some manifestation of such high severity can be conveyed in the vicinity data **208** (e.g., highly crumpled or significantly destroyed vehicles can be depicted in the set of vicinity images **312**, very loud crashing sounds associated with highly-severe vehicular collisions can be captured in the set of vicinity noises **314**), and the deep learning neural network **402** can recognize such manifestation of high severity. Conversely, if a non-severe vehicular collision is occurring at that given geolocation, some manifestation of such low severity can be conveyed in the vicinity data **208** (e.g., very little vehicle damage can be depicted in the set of vicinity images **312**, relatively non-loud crashing sounds associated with non-severe vehicular collisions can be captured

in the set of vicinity noises **314**), and the deep learning neural network **402** can recognize such manifestation of low severity. In any of these cases, the severity indicator **614** can represent the determination, inference, or conclusion generated by the deep learning neural network **402** with respect to how severe a detected vehicular collision is.

(147) As a non-limiting example, the severity indicator **614** can be a binary or binomial variable that can take on one of two possible discrete states. In such case, one of the two possible discrete states can represent a “severe” state, whereas the other of the two possible discrete values can represent a “not-severe” state. As another non-limiting example, the severity indicator **614** can be a multinomial variable that can take on one of three or more possible discrete states. In such case, the three or more possible discrete states can respectively represent any suitable severity labels or severity states (e.g., a “not-severe” state, a “slightly-severe” state, a “moderately-severe” state, a “highly-severe” state). As yet another non-limiting example, the severity indicator **614** can be a scalar whose magnitude represents how severe a detected vehicular collision is.

(148) Although not explicitly shown in FIG. **6**, the vehicular collision classification label **404** can comprise any other suitable indicators. As a non-limiting example, the vehicular collision classification label **404** can comprise an airborne indicator (not shown), which can exhibit any suitable size, format, or dimensionality, and which can binomially, multinomially, discretely, or continuously indicate whether a vehicular collision that is occurring in the vicinity **106** involves a vehicle that has become airborne (e.g., that has lost physical contact with the ground for at least a moment). As another non-limiting example, the vehicular collision classification label **404** can comprise a terrain indicator (not shown), which can exhibit any suitable size, format, or dimensionality, and which can binomially, multinomially, discretely, or continuously indicate a type of terrain (e.g., pavement, dirt, mud, sand, rocks, grass, ditch) associated with a vehicular collision that is occurring in the vicinity **106**. As still another non-limiting example, the vehicular collision classification label **404** can comprise a final resting orientation indicator (not shown), which can exhibit any suitable size, format, or dimensionality, and which can binomially, multinomially, discretely, or continuously indicate a final resting orientation (e.g., on wheels, on left side, on right side, on roof) of a vehicle involved in a vehicular collision that is occurring in the vicinity **106**. As even another non-limiting example, the vehicular collision classification label **404** can comprise a pedestrian cardinality indicator (not shown), which can exhibit any suitable size, format, or dimensionality, and which can binomially, multinomially, discretely, or continuously indicate how many total pedestrians or other vulnerable road users there are (e.g., that are standing, walking, running, or lying down, whether injured or uninjured) at the scene of a vehicular collision that is occurring in the vicinity **106**.

(149) In any case, the inference component **210** can execute the deep learning neural network **402** on the vicinity data **208**, thereby yielding the vehicular collision classification label **404**.

(150) FIG. **7** illustrates a block diagram of an example, non-limiting system **700** including recorded post-collision evidence and an electronic alert that can facilitate a broadcast-side of artificially intelligent provision of post-vehicular-collision evidence in accordance with one or more embodiments described herein. As shown, the system **700** can, in some cases, comprise the same components as the system **400**, and can further comprise recorded post-collision evidence **702**, an electronic alert **704**, a set of vehicle geolocation sensors **706**, or a set of vehicle time sensors **708**.

(151) In various embodiments, the evidence component **212** can electronically generate the recorded post-collision evidence **702**, based on the vehicular collision classification label **404**. More specifically, in response to the vehicular collision classification label **404** indicating that a vehicular collision (e.g., **108**) is occurring in the vicinity **106**, the evidence component **212** can cause the various sensors of the vehicle **102** to record whatever transpires within the vicinity **106** for any suitable temporal duration that follows detection of the vehicular collision, and such data can be considered as the recorded post-collision evidence **702**. Accordingly, the broadcast component **214** can electronically generate the electronic alert **704**, based on the recorded post-

collision evidence **702** or based on the vehicular collision classification label **404**, and the broadcast component **214** can transmit, via the communication link **112**, the electronic alert **704** to the emergency service system **110**. In this way, the vehicle **102** can be considered as informing or notifying the emergency service system **110** of the vehicular collision detected by the deep learning neural network **402** and of the recorded/captured aftermath of such vehicular collision. Various non-limiting details are described with respect to FIG. **8**.

(152) FIG. **8** illustrates an example, non-limiting block diagram **800** showing recorded post-collision evidence and an electronic alert in accordance with one or more embodiments described herein. That is, FIG. **8** depicts a non-limiting example embodiment of the recorded post-collision evidence **702** and a non-limiting example embodiment of the electronic alert **704**.

(153) In various embodiments, as shown, the recorded post-collision evidence **702** can comprise a set of post-collision vicinity images **802**. In various aspects, the evidence component **212** can, in response to the vehicular collision classification label **404** indicating that a vehicular collision (e.g., **108**) is occurring or has occurred in the vicinity **106**, cause the set of vehicle cameras **302** to capture or otherwise record the set of post-collision vicinity images **802**. In various instances, the set of post-collision vicinity images **802** can include any suitable number of images or video frames (e.g., any suitable number of two-dimensional pixel arrays) that can depict portions of the vicinity **106** (e.g., portions of the vicinity **106** that lie in front of, behind, or beside the vehicle **102**) and that span any suitable temporal window or temporal duration following detection of the vehicular collision. For example, suppose that the temporal window or temporal duration is m seconds, for any suitable positive integer m. In such case, the evidence component **212** can cause the set of vehicle cameras **302** to begin recording the vicinity **106** whenever the deep learning neural network **402** detects the vehicular collision, and the evidence component **212** can cause the set of vehicle cameras **302** to cease recording the vicinity **106** after m seconds have elapsed. Accordingly, the set of post-collision vicinity images **802** can be considered as whatever data was recorded by the set of vehicle cameras **302** in the first m seconds after detection of the vehicular collision. In some cases, the set of post-collision vicinity images **802** can be considered as collectively forming an m-second-long video clip that depicts whatever transpired in the vicinity **106** during the first m seconds after the vehicular collision occurred or was detected.

(154) In various aspects, as shown, the recorded post-collision evidence **702** can comprise a set of post-collision vicinity noises **804**. In various instances, the evidence component **212** can, in response to the vehicular collision classification label **404** indicating that a vehicular collision (e.g., **108**) is occurring or has occurred in the vicinity **106**, cause the set of vehicle microphones **304** to capture or otherwise record the set of post-collision vicinity noises **804**. In various cases, the set of post-collision vicinity noises **804** can include any suitable number of sound bites that can represent noises occurring in portions of the vicinity **106** (e.g., portions of the vicinity **106** that lie in front of, behind, or beside the vehicle **102**) and that span any suitable temporal window or temporal duration following detection of the vehicular collision. For example, suppose again that the temporal window or temporal duration is m seconds, for any suitable positive integer m. In such case, the evidence component **212** can cause the set of vehicle microphones **304** to begin recording the vicinity **106** whenever the deep learning neural network **402** detects the vehicular collision, and the evidence component **212** can cause the set of vehicle microphones **304** to cease recording the vicinity **106** after m seconds have elapsed. Accordingly, the set of post-collision vicinity noises **804** can be considered as whatever data was recorded by the set of vehicle microphones **304** in the first m seconds after detection of the vehicular collision. In some cases, the set of post-collision vicinity noises **804** can be considered as collectively forming an m-second-long audio clip that contains whatever noises transpired in the vicinity **106** during the first m seconds after the vehicular collision occurred.

(155) In various aspects, as shown, the recorded post-collision evidence **702** can comprise a set of post-collision vicinity temperatures **806**. In various instances, the evidence component **212** can, in

response to the vehicular collision classification label **404** indicating that a vehicular collision (e.g., **108**) is occurring or has occurred in the vicinity **106**, cause the set of vehicle thermometers **306** to capture or otherwise record the set of post-collision vicinity temperatures **806**. In various cases, the set of post-collision vicinity temperatures **806** can include any suitable number of temperature measurements that can represent air temperatures or road surface temperatures associated with portions of the vicinity **106** (e.g., portions of the vicinity **106** that lie in front of, behind, or beside the vehicle **102**) and that span any suitable temporal window or temporal duration following detection of the vehicular collision. For example, suppose again that the temporal window or temporal duration is m seconds, for any suitable positive integer m. In such case, the evidence component **212** can cause the set of vehicle thermometers **306** to begin recording the vicinity **106** whenever the deep learning neural network **402** detects the vehicular collision, and the evidence component **212** can cause the set of vehicle thermometers **306** to cease recording the vicinity **106** after m seconds have elapsed. Accordingly, the set of post-collision vicinity temperatures **806** can be considered as whatever data was recorded by the set of vehicle thermometers **306** in the first m seconds after detection of the vehicular collision. In some cases, the set of post-collision vicinity temperatures **806** can be considered as collectively forming an m-second-long temperature measurement time-series that contains whatever temperatures were measured in the vicinity **106** during the first m seconds after the vehicular collision occurred.

(156) In various aspects, as shown, the recorded post-collision evidence **702** can comprise a set of post-collision vicinity humidities **808**. In various instances, the evidence component **212** can, in response to the vehicular collision classification label **404** indicating that a vehicular collision (e.g., **108**) is occurring or has occurred in the vicinity **106**, cause the set of vehicle hygrometers **308** to capture or otherwise record the set of post-collision vicinity humidities **808**. In various cases, the set of post-collision vicinity humidities **808** can include any suitable number of humidity measurements that can represent air moisture levels or road surface moisture levels associated with portions of the vicinity **106** (e.g., portions of the vicinity **106** that lie in front of, behind, or beside the vehicle **102**) and that span any suitable temporal window or temporal duration following detection of the vehicular collision. For example, suppose again that the temporal window or temporal duration is m seconds, for any suitable positive integer m. In such case, the evidence component **212** can cause the set of vehicle hygrometers **308** to begin recording the vicinity **106** whenever the deep learning neural network **402** detects the vehicular collision, and the evidence component **212** can cause the set of vehicle hygrometers **308** to cease recording the vicinity **106** after m seconds have elapsed. Accordingly, the set of post-collision vicinity humidities **808** can be considered as whatever data was recorded by the set of vehicle hygrometers **308** in the first m seconds after detection of the vehicular collision. In some cases, the set of post-collision vicinity humidities **808** can be considered as collectively forming an m-second-long humidity measurement time-series that contains whatever humidities were measured in the vicinity **106** during the first m seconds after the vehicular collision occurred.

(157) In various aspects, as shown, the recorded post-collision evidence **702** can comprise a set of post-collision vicinity proximity detections **810**. In various instances, the evidence component **212** can, in response to the vehicular collision classification label **404** indicating that a vehicular collision (e.g., **108**) is occurring or has occurred in the vicinity **106**, cause the set of vehicle proximity sensors **310** to capture or otherwise record the set of post-collision vicinity proximity detections **810**. In various cases, the set of post-collision vicinity proximity detections **810** can include any suitable number of radar, sonar, or lidar proximity measurements that can represent distances between the vehicle **102** and nearby objects located in portions of the vicinity **106** (e.g., portions of the vicinity **106** that lie in front of, behind, or beside the vehicle **102**) and that span any suitable temporal window or temporal duration following detection of the vehicular collision. For example, suppose again that the temporal window or temporal duration is m seconds, for any suitable positive integer m. In such case, the evidence component **212** can cause the set of vehicle

proximity sensors **310** to begin recording the vicinity **106** whenever the deep learning neural network **402** detects the vehicular collision, and the evidence component **212** can cause the set of vehicle proximity sensors **310** to cease recording the vicinity **106** after m seconds have elapsed. Accordingly, the set of post-collision vicinity proximity detections **810** can be considered as whatever data was recorded by the set of vehicle proximity sensors **310** in the first m seconds after detection of the vehicular collision. In some cases, the set of post-collision vicinity proximity detections **810** can be considered as collectively forming an m-second-long proximity measurement time-series that contains whatever proximity detections were measured in the vicinity **106** during the first m seconds after the vehicular collision occurred.

(158) In various embodiments, the electronic alert **704** can comprise any suitable electronic data pertaining to the vehicular collision (e.g., **108**) detected by the deep learning neural network **402**. As a non-limiting example, the electronic alert **704** can comprise the recorded post-collision evidence **702**. That is, the electronic alert **704** can include whatever data was recorded by the various sensors of the vehicle **102** in the moments after the vehicular collision was detected by the deep learning neural network **402**.

(159) As another non-limiting example, the electronic alert **704** can comprise the vehicular collision classification label **404**. That is, the electronic alert **704** can contain whatever data is outputted by the deep learning neural network **402**.

(160) As yet another non-limiting example, the electronic alert **704** can comprise the vicinity data **208** (or any suitable portion thereof). That is, the electronic alert **704** can contain whatever raw data was recorded, measured, or otherwise captured by the sensor component **206** and on the basis of which the deep learning neural network **402** detected a vehicular collision (e.g., the electronic alert **704** can contain the set of vicinity images **312**, the set of vicinity noises **314**, the set of vicinity temperatures **316**, the set of vicinity humidities **318**, or the set of vicinity proximity detections **320**).

(161) As even another non-limiting example, the electronic alert **704** can comprise a geolocation stamp **814**. In various aspects, as shown in FIG. 7, the sensor component **206** can comprise the set of vehicle geolocation sensors **706**. In various instances, the set of vehicle geolocation sensors **706** can include any suitable number of geolocation sensors that can be integrated into or onto the vehicle **102**. In various cases, a geolocation sensor can be any suitable sensor that can measure or determine a geographical position of the vehicle **102** at any given instant in time. As a non-limiting example, a geolocation sensor can be a global positioning sensor (GPS). As another non-limiting example, a geolocation sensor can be a Wi-Fi positioning sensor (WPS). In any case, the set of vehicle geolocation sensors **706** can electronically determine or otherwise generate the geolocation stamp **814**.

(162) In various aspects, the geolocation stamp **814** can be any suitable electronic data (e.g., can be one or more scalars, one or more vectors, one or more matrices, one or more tensors, one or more character strings, or any suitable combination thereof) that can indicate a geolocation at which the vicinity data **208** was captured, measured, or otherwise recorded. In various instances, the geolocation stamp **814** can recite such geolocation at any suitable level of granularity (e.g., can specify continent, country, state, province, city, address, latitude, longitude, or elevation at which the vicinity data **208** was captured). For example, the geolocation stamp **814** can specify a name or identifier of a road on which the vehicle **102** is traveling or is parked, and the geolocation stamp **814** can specify a mile-marker along that road, at which mile-marker the vicinity data **208** was captured by the sensor component **206**. In any case, because the geolocation stamp **814** can indicate the geolocation at which the vicinity data **208** was captured, and because the vehicular collision (e.g., **108**) can be detected based on the vicinity data **208**, the geolocation stamp **814** can be considered as indicating the geolocation at which the vehicular collision occurred or was detected (e.g., the geolocation at which the vehicular collision is present or is inferred to be present).

(163) As even another non-limiting example, the electronic alert **704** can comprise a timestamp

816. In various aspects, as shown in FIG. 7, the sensor component **206** can comprise the set of vehicle time sensors **708**. In various instances, the set of vehicle time sensors **708** can include any suitable number of time sensors that can be integrated into or onto the vehicle **102**. In various cases, a time sensor can be any suitable sensor that can measure or determine a time at which the vehicle **102** performs any given action. As a non-limiting example, a time sensor can be a digital clock. In any case, the set of vehicle time sensors **708** can electronically determine or otherwise generate the timestamp **816**.

(164) In various aspects, the timestamp **816** can be any suitable electronic data (e.g., can be one or more scalars, one or more vectors, one or more matrices, one or more tensors, one or more character strings, or any suitable combination thereof) that can indicate a time or date at which the vicinity data **208** was captured, measured, or otherwise recorded. In various instances, the timestamp **816** can recite such time or date at any suitable level of granularity (e.g., can specify year, season, month, week, day, hour, minute, second, or fraction of a second at which the vicinity data **208** was captured). In any case, because the timestamp **816** can indicate when the vicinity data **208** was captured, and because the vehicular collision (e.g., **108**) can be detected based on the vicinity data **208**, the timestamp **816** can be considered as indicating when the vehicular collision was detected (e.g., indicating a time at which the vehicular collision is present or is inferred to be present).

(165) As still another non-limiting example, the electronic alert **704** can comprise a vehicle identifier **818**. In various aspects, the vehicle identifier **818** can be any suitable electronic data (e.g., can be one or more scalars, one or more vectors, one or more matrices, one or more tensors, one or more character strings, or any suitable combination thereof) that can uniquely represent or otherwise uniquely correspond to the vehicle **102**. For example, the vehicle identifier **818** can comprise a VIN of the vehicle **102**. As another example, the vehicle identifier **818** can comprise a license plate number of the vehicle **102**. As yet another example, the vehicle identifier **818** can comprise make or model of the vehicle **102**. As even another example, the vehicle identifier **818** can comprise any suitable identification information of an owner of the vehicle **102**, such as name, age, gender, or residential address. In various cases, any of such information can be hard-coded into the collision evidence system **104**.

(166) In some aspects, the vehicle identifier **818** can comprise any suitable identification information (e.g., name, residential address, phone number, email address) pertaining to a driver of the vehicle **102**. In some cases, the driver of the vehicle **102** can be the owner of the vehicle **102**. However, in other cases, the driver of the vehicle **102** can be different from the owner of the vehicle **102**. In various aspects, although not explicitly shown in the figures, the sensor component **206** can comprise any suitable biometric sensors that can be integrated into or onto the vehicle **102**. In various instances, such biometric sensors can be implemented to identify the current driver of the vehicle **102**. For example, such biometric sensors can include: a facial recognition sensor (e.g., an interior camera of the vehicle **102** can capture an image of a face of whomever is driving the vehicle **102**); a fingerprint sensor (e.g., a steering wheel of the vehicle **102** can be embedded with fingerprint sensors that can scan fingerprints of whomever is driving the vehicle **102**); a voice recognition sensor (e.g., an interior microphone of the vehicle **102** can capture an audio clip of a voice of whomever is driving the vehicle **102**); or a weight sensor (e.g., a weight scale can be embedded into a driver seat of the vehicle **102**, so as to capture a body weight of whomever is driving the vehicle **102**). In other instances, although not explicitly shown in the figures, the sensor component **206** can comprise any suitable beacon-detector that can detect when a defined electronic beacon has entered a cabin of the vehicle. In such case, the beacon-detector can detect an electronic beacon emitted by any suitable electronic device of whomever is driving the vehicle **102** (e.g., emitted by a smart phone of the driver, emitted by a smart watch of the driver), where such electronic beacon can uniquely correspond to an identity of the current driver.

(167) Note that, because electronic alert **704** can comprise the vehicle identifier **818**, the electronic

alert **704** can be considered as a non-anonymous or deanonymized electronic alert.

(168) In various aspects, as shown, the vehicular collision classification label **404**, the vicinity data **208**, the geolocation stamp **814**, the timestamp **816**, and the vehicle identifier **818** can collectively be referred to as collision metadata **812**.

(169) In various embodiments, as shown, the electronic alert **704** can comprise an assistance request **820**. In various aspects, the assistance request **820** can be any suitable electronic data (e.g., can be one or more scalars, one or more vectors, one or more matrices, one or more tensors, or one or more character strings) that can indicate, represent, or otherwise convey that emergency service assistance should be dispatched to the geolocation indicated by the geolocation stamp **814**, so as to handle or otherwise address the vehicular collision (e.g., **108**) detected by the deep learning neural network **402**. In some cases, the assistance request **820** can identify a specific type of emergency service that should be dispatched, based on the vehicular collision classification label **404**.

(170) For example, if the injured pedestrian indicator **606** of the vehicular collision classification label **404** indicates that at least one pedestrian has been injured in the detected vehicular collision, then the assistance request **820** can indicate that an ambulance should be dispatched to the geolocation indicated by the geolocation stamp **814**. In some cases, if the injured pedestrian indicator **606** of the vehicular collision classification label **404** indicates that more than one pedestrian has been injured in the detected vehicular collision, then the assistance request **820** can indicate that more than one ambulance should be dispatched to the geolocation indicated by the geolocation stamp **814**. Conversely, if the injured pedestrian indicator **606** of the vehicular collision classification label **404** indicates that no pedestrian has been injured in the detected vehicular collision, then the assistance request **820** can indicate that no ambulance should be dispatched to the geolocation indicated by the geolocation stamp **814**.

(171) As another example, if the fire indicator **612** of the vehicular collision classification label **404** indicates that the detected vehicular collision involves fire, flames, or smoke, then the assistance request **820** can indicate that a firetruck should be dispatched to the geolocation indicated by the geolocation stamp **814**. On the other hand, if the fire indicator **612** of the vehicular collision classification label **404** indicates that the detected vehicular collision does not involve fire, flames, or smoke, then the assistance request **820** can indicate that no firetruck should be dispatched to the geolocation indicated by the geolocation stamp **814**.

(172) As even another example, if the roll-over indicator **610** of the vehicular collision classification label **404** indicates that the detected vehicular collision involves a rolled-over vehicle, then the assistance request **820** can indicate that heavy-equipment (e.g., a tow truck, a crane) should be dispatched to the geolocation indicated by the geolocation stamp **814**. On the other hand, if the roll-over indicator **610** of the vehicular collision classification label **404** indicates that the detected vehicular collision does not involve a rolled-over vehicle, then the assistance request **820** can indicate that no heavy-equipment should be dispatched to the geolocation indicated by the geolocation stamp **814**.

(173) Although not explicitly shown in the figures, the electronic alert **704** can be written or otherwise organized according to any suitable protocol or syntax (e.g., can have any suitable header, can have any suitable body).

(174) In any case, the broadcast component **214** can generate the electronic alert **704**, and the broadcast component **214** can transmit the electronic alert **704** to the emergency service system **110** via the communication link **112**.

(175) As explained above, the evidence component **212** and the broadcast component **214** can respectively generate the recorded post-collision evidence **702** and the electronic alert **704**, in response to the vehicular collision classification label **404** indicating that a vehicular collision (e.g., **108**) has occurred or is occurring in the vicinity **106**. In contrast, the evidence component **212** and the broadcast component **214** can respectively refrain from generating the recorded post-collision evidence **702** and the electronic alert **704**, in response to the vehicular collision classification label

404 indicating that no vehicular collision has occurred or is occurring in the vicinity **106**. Indeed, in such case, the vicinity data **208** can be deleted or discarded, the sensor component **206** can capture new vicinity data (e.g., a new instance of **208**), and the inference component **210**, the evidence component **212**, and the broadcast component **214** can perform their respective functionalities with respect to the new vicinity data. Accordingly, the collision evidence system **104** can be considered as repeatedly recording and discarding vicinity data, until a vehicular collision (e.g., **108**) is detected. Upon such detection, the recorded post-collision evidence **702** can be generated and the most recently captured vicinity data can be preserved, stored, or otherwise maintained for use in the electronic alert **704**.

(176) To help ensure that the vehicular collision classification label **404** is accurate, the deep learning neural network **402** can first undergo training. Various non-limiting aspects of such training are described with respect to FIGS. **9-11**.

(177) FIG. **9** illustrates a block diagram of an example, non-limiting system **900** including a training component and a training dataset that can facilitate a broadcast-side of artificially intelligent provision of post-vehicular-collision evidence in accordance with one or more embodiments described herein. As shown, the system **900** can, in some cases, comprise the same components as the system **700**, and can further comprise a training component **902** or a training dataset **904**.

(178) In various aspects, the training component **902** can electronically receive, retrieve, obtain, or otherwise access, from any suitable source, the training dataset **904**. In various aspects, the training component **902** can train the deep learning neural network **402** based on the training dataset **904**. Various non-limiting aspects are described with respect to FIGS. **10-11**.

(179) FIG. **10** illustrates an example, non-limiting block diagram **1000** of the training dataset **904** in accordance with one or more embodiments described herein. As shown, the training dataset **904** can, in various aspects, comprise a set of training inputs **1002** and a set of ground-truth annotations **1004**.

(180) In various aspects, the set of training inputs **1002** can include n inputs for any suitable positive integer n: a training input **1** to a training input n. In various instances, a training input can be any suitable electronic data having the same format, size, or dimensionality as the vicinity data **208**. In other words, each training input can be raw data captured by sensors of a vehicle that were monitoring a respective vehicle vicinity. For example, the training input **1** can include a first set of training vicinity images depicting portions of a first vehicle vicinity, a first set of training vicinity noises that occurred in those portions of the first vehicle vicinity, a first set of training vicinity temperatures associated with those portions of the first vehicle vicinity, a first set of training vicinity humidities associated with those portions of the first vehicle vicinity, or a first set of training vicinity proximity detections associated with those portions of the first vehicle vicinity. Likewise, as another example, the training input n can include an n-th set of training vicinity images depicting portions of an n-th vehicle vicinity, an n-th set of training vicinity noises that occurred in those portions of the n-th vehicle vicinity, an n-th set of training vicinity temperatures associated with those portions of the n-th vehicle vicinity, an n-th set of training vicinity humidities associated with those portions of the n-th vehicle vicinity, or an n-th set of training vicinity proximity detections associated with those portions of the n-th vehicle vicinity.

(181) In various aspects, the set of ground-truth annotations **1004** can respectively correspond (e.g., in one-to-one fashion) to the set of training inputs **1002**. Thus, since the set of training inputs **1002** can have n inputs, the set of ground-truth annotations **1004** can have n annotations: a ground-truth annotation **1** to a ground-truth annotation n. In various instances, each of the set of ground-truth annotations **1004** can have the same format, size, or dimensionality as the vehicular collision classification label **404**. That is, each ground-truth annotation can be any suitable electronic data that indicates or represents a presence or other attributes (e.g., collision cardinality, injured pedestrians, impact type, roll-over, fire, severity) of a vehicular collision that is known or deemed

to be manifested in a respect training input. For example, the ground-truth annotation **1** can correspond to the training input **1**. Accordingly, the ground-truth annotation **1** can be considered as the correct or accurate classification label that indicates the presence or other attributes of whatever vehicular collision is known or deemed to be manifested in the training input **1**. As another example, the ground-truth annotation **n** can correspond to the training input **n**. Accordingly, the ground-truth annotation **n** can be considered as the correct or accurate classification label that indicates the presence or other attributes of whatever vehicular collision is known or deemed to be manifested in the training input **n**.

(182) Now, consider FIG. **11**. FIG. **11** illustrates an example, non-limiting block diagram **1100** showing how the deep learning neural network **402** can be trained in accordance with one or more embodiments described herein.

(183) In various aspects, the training component **902** can, prior to beginning training, initialize in any suitable fashion (e.g., random initialization) the trainable internal parameters (e.g., convolutional kernels, weight matrices, bias values) of the deep learning neural network **402**.

(184) In various aspects, the training component **902** can select, from the training dataset **904**, a training input **1102** and a ground-truth annotation **1104** corresponding to the training input **1102**. In various instances, the training component **902** can execute the deep learning neural network **402** on the training input **1102**, thereby causing the deep learning neural network **402** to produce an output **1106**. More specifically, in some cases, an input layer of the deep learning neural network **402** can receive the training input **1102**, the training input **1102** can complete a forward pass through one or more hidden layers of the deep learning neural network **402**, and an output layer of the deep learning neural network **402** can compute the output **1106** based on activation maps or intermediate features provided by the one or more hidden layers.

(185) In various aspects, the output **1106** can be considered as the predicted or inferred vehicular collision classification label (e.g., as the predicted/inferred presence indicator, the predicted/inferred collision cardinality indicator, the predicted/inferred injured pedestrian indicator, the predicted/inferred impact type indicator, the predicted/inferred roll-over indicator, the predicted/inferred fire indicator, the predicted/inferred severity indicator) that the deep learning neural network **402** believes should correspond to the training input **1102**. In contrast, the ground-truth annotation **1104** can be considered as the correct/accurate vehicular collision classification label (e.g., as the correct/accurate presence indicator, the correct/accurate collision cardinality indicator, the correct/accurate injured pedestrian indicator, the correct/accurate impact type indicator, the correct/accurate roll-over indicator, the correct/accurate fire indicator, the correct/accurate severity indicator) that is known or deemed to correspond to the training input **1102**. Note that, if the deep learning neural network **402** has so far undergone no or little training, then the output **1106** can be highly inaccurate. In other words, the output **1106** can be very different from the ground-truth annotation **1104**.

(186) In various aspects, the training component **902** can compute one or more errors or losses (e.g., MAE, MSE, cross-entropy) between the output **1106** and the ground-truth annotation **1104**. In various instances, the training component **902** can incrementally update, via backpropagation, the trainable internal parameters of the deep learning neural network **402**, based on such one or more errors or losses.

(187) In various cases, the training component **902** can repeat such execution-and-update procedure for each training input in the training dataset **904**. This can ultimately cause the trainable internal parameters of the deep learning neural network **402** to become iteratively optimized for accurately detecting vehicular collisions in inputted vicinity data. In various aspects, the training component **902** can implement any suitable training batch sizes, any suitable error/loss functions, or any suitable training termination criteria.

(188) FIG. **12** illustrates a flow diagram of an example, non-limiting computer-implemented method **1200** that can facilitate a broadcast-side of artificially intelligent provision of post-

vehicular-collision evidence in accordance with one or more embodiments described herein. In various cases, the collision evidence system **104** can facilitate the computer-implemented method **1200**.

(189) In various embodiments, act **1202** can include recording, by a smart vehicle (e.g., **102**) having one or more road-facing sensors (e.g., **206**) vicinity data (e.g., **208**) associated with a vicinity (e.g., **106**) of the smart vehicle. In some cases, the one or more road-facing sensors can include cameras (e.g., **302**), microphones (e.g., **304**), thermometers (e.g., **306**), hygrometers (e.g., **308**), or proximity detectors (e.g., **310**).

(190) In various aspects, act **1204** can include recording, by the smart vehicle, a specific location (e.g., **814**) at which the vicinity data was recorded. In various cases, such recording can be facilitated by a GPS sensor or a WPS sensor (e.g., **706**) of the smart vehicle.

(191) In various instances, act **1206** can include recording, by the smart vehicle, a specific time (e.g., **816**) at which the vicinity data was recorded. In various cases, such recording can be facilitated by a clock (e.g., **708**) of the smart vehicle.

(192) In various aspects, act **1208** can include accessing, by the smart vehicle (e.g., via **210**), a deep learning neural network (e.g., **402**) that has been trained to detect vehicular collisions.

(193) In various instances, act **1210** can include executing, by the smart vehicle (e.g., via **210**), the deep learning neural network on the vicinity data. This can cause the deep learning neural network to produce an outputted classification label (e.g., **404**).

(194) In various cases, act **1212** can include determining, by the smart vehicle (e.g., via **210**), whether the outputted classification label indicates that there is vehicular collision (e.g. **108**) in the vicinity. If not (e.g., if the outputted classification label indicates that there is no vehicular collision), the computer-implemented method **1200** can proceed to act **1214**. If so (e.g., if the outputted classification label instead indicates that there is a vehicular collision), the computer-implemented method **1200** can proceed to act **1216**.

(195) In various aspects, act **1214** can include discarding, by the smart vehicle (e.g., via **212**) the vicinity data. In various cases, the computer-implemented method **1200** can proceed back to act **1202**.

(196) In various instances, act **1216** can include recording, by the smart vehicle (e.g., via **212**) and via the one or more road-facing sensors, post-collision evidence (e.g., **702**) concerning the vicinity.

(197) In various cases, act **1218** can include transmitting, by the smart vehicle (e.g., via **214**) and to an emergency service device (e.g., **110**), the post-collision evidence. In various aspects, the post-collision evidence can be tagged with the specific location and the specific time. In various instances, as shown, the computer-implemented method **1200** can proceed back to act **1202**.

(198) FIG. **13** illustrates a block diagram of an example, non-limiting system **1300** that can facilitate a receipt-side of artificially intelligent provision of post-vehicular-collision evidence in accordance with one or more embodiments described herein. In other words, FIG. **13** depicts a non-limiting example embodiment of the emergency service system **110**.

(199) In various embodiments, the emergency service system **110** can comprise a processor **1302** (e.g., computer processing unit, microprocessor) and a non-transitory computer-readable memory **1304** that is operably or operatively or communicatively connected or coupled to the processor **1302**. The non-transitory computer-readable memory **1304** can store computer-executable instructions which, upon execution by the processor **1302**, can cause the processor **1302** or other components of the emergency service system **110** (e.g., receiver component **1306**, determination component **1308**, execution component **1310**) to perform one or more acts. In various embodiments, the non-transitory computer-readable memory **1304** can store computer-executable components (e.g., receiver component **1306**, determination component **1308**, execution component **1310**), and the processor **1302** can execute the computer-executable components.

(200) In various embodiments, the emergency service system **110** can comprise a receiver component **1306**. In various aspects, the receiver component **1306** can electronically receive,

electronically retrieve, electronically obtain, or otherwise electronically access the electronic alert **704**. In particular, the receiver component **1306** can be operatively or operably coupled or connected to the broadcast component **214** via the communication link **112**. Accordingly, the receiver component **1306** can receive the electronic alert **704** from the broadcast component **214**. Thus, other components of the emergency service system **110** can electronically interact with (e.g., read, write, edit, copy, manipulate) the electronic alert **704**.

(201) In various embodiments, the emergency service system **110** can comprise a determination component **1308**. In various aspects, the determination component **1308** can, as described herein, determine whether or not the electronic alert **704** indicates that a vehicular collision has occurred or is occurring in the vicinity **106**.

(202) In various embodiments, the emergency service system **110** can comprise an execution component **1310**. In various instances, the execution component **1310** can, as described herein, initiate or otherwise perform any suitable electronic actions, in response to the determination component **1308** determining that the electronic alert **704** indicates that a vehicular collision (e.g., **108**) has occurred or is occurring in the vicinity **106**.

(203) FIG. **14** illustrates a block diagram of an example, non-limiting system **1400** including a determination indicator that can facilitate a receipt-side of artificially intelligent provision of post-vehicular-collision evidence in accordance with one or more embodiments described herein. As shown, the system **1400** can, in some cases, comprise the same components as the system **1300**, and can further comprise a determination indicator **1402**.

(204) In various embodiments, the determination component **1308** can electronically generate the determination indicator **1402**, based on the electronic alert **704**. More specifically, the determination component **1308** can, in various aspects, electronically read, via any suitable parsing techniques, the contents of the electronic alert **704**. Accordingly, the determination component **1308** can identify, via such parsing techniques, the recorded post-collision evidence **702**, the collision metadata **812**, or the assistance request **820**. In various cases, the determination component **1308** can generate the determination indicator **1402**, based on the vehicular collision classification label **404**, which can be specified in the collision metadata **812**. In particular, the determination indicator **1402** can be any suitable binary or binomial variable that can take on one of two discrete states. In various aspects, if the vehicular collision classification label **404** indicates that a vehicular collision (e.g., **108**) has been detected in the vicinity **106**, then the determination indicator **1402** can be set or otherwise configured to an active state. On the other hand, if the vehicular collision classification label **404** indicates that a vehicular collision has not (yet) been detected in the vicinity **106**, then the determination indicator **1402** can be set or otherwise configured to an inactive state.

(205) In various embodiments, the execution component **1310** can conduct, initiate, facilitate, or otherwise perform any suitable electronic actions, in response to the determination indicator **1402** being in the active state (e.g., in response to a determination that the electronic alert **704** indicates that a vehicular collision has been detected in the vicinity **106**). In contrast, the execution component **1310** can, in various instances, refrain from conducting, initiating, facilitating, or otherwise performing such electronic actions, in response to the determination indicator **1402** being in the inactive state (e.g., in response to a determination that the electronic alert **704** indicates that no vehicular collision has been detected yet in the vicinity **106**). Various non-limiting examples of such electronic actions are described with respect to FIGS. **15-23**.

(206) FIG. **15** illustrates a block diagram of an example, non-limiting system **1500** including an electronic navigation display that can facilitate a receipt-side of artificially intelligent provision of post-vehicular-collision evidence in accordance with one or more embodiments described herein. As shown, the system **1500** can, in some cases, comprise the same components as the system **1400**, and can further comprise an electronic navigation display **1502**.

(207) In various embodiments, the emergency service system **110** can be associated with any

suitable emergency service vehicle. For example, in some cases, the emergency service system **110** can be integrated or otherwise built into the emergency service vehicle. In other cases, the emergency service system **110** can be not integrated into the emergency service vehicle but can nevertheless have dispatch-authority over the emergency service vehicle.

(208) In any case, that emergency service vehicle can be outfitted with the electronic navigation display **1502**. In various aspects, the electronic navigation display **1502** can be any suitable computer monitor, computer screen, or visual projection that can visually render or otherwise illustrate navigation information (e.g., route data, traffic data) to a driver of the emergency service vehicle. In some cases, the electronic navigation display **1502** can be built into a dashboard of the emergency service vehicle. In other cases, the electronic navigation display **1502** can be built into a center console of the emergency service vehicle. In still other cases, the electronic navigation display **1502** can be a heads-up display that is projected onto a portion of a front windshield of the emergency service vehicle.

(209) In any case, in response to the determination indicator **1402** being in the active state (e.g., in response to the electronic alert **704** indicating that a vehicular collision has been detected in the vicinity **106**), the execution component **1310** can electronically render any suitable graphical representations of the vehicular collision on the electronic navigation display **1502**. Such graphical representations can be visible to a driver of the emergency service vehicle, so that the driver of the emergency service vehicle can be notified of the vehicular collision. Various non-limiting details are described with respect to FIGS. **16-17**.

(210) FIGS. **16-17** illustrate example, non-limiting block diagrams **1600** and **1700** showing how an electronic navigation display can be adjusted in accordance with one or more embodiments described herein.

(211) First, consider FIG. **16**. In various aspects, FIG. **16** depicts an example, non-limiting view that can be rendered on the electronic navigation display **1502** prior to receipt or parsing of the electronic alert **704** (e.g., prior to determining that the electronic alert **704** indicates that the vehicular collision **108** has been detected in the vicinity **106**).

(212) In various aspects, the emergency service vehicle corresponding to the emergency service system **110** can be traveling on any given road. Accordingly, as shown in FIG. **16**, the electronic navigation display **1502** can depict a graphical representation **1602** of the emergency service vehicle and a graphical representation **1604** of the road on which the emergency service vehicle is currently traveling. As shown, the graphical representation **1602** can be superimposed on top of the graphical representation **1604**, so as to indicate that the emergency service vehicle is traveling on the given road. Although FIG. **16** depicts the graphical representation **1602** as being a chevron shape (e.g., so as to indicate a direction of travel of the emergency service vehicle), this is a mere non-limiting example. Indeed, the graphical representation **1602** or the graphical representation **1604** can be rendered via any suitable colors, shapes, symbols, or artistic styles.

(213) Suppose that a second road perpendicularly intersects with the given road on which the emergency service vehicle is traveling, some distance ahead of the emergency service vehicle. In various aspects, as shown, the electronic navigation display **1502** can depict a graphical representation **1606** corresponding to that second road. Furthermore, suppose that a third road branches off perpendicularly from that second road, some distance to the left of the given road. In various instances, as shown, the electronic navigation display **1502** can depict a graphical representation **1608** of such third road.

(214) Now, suppose that the electronic alert **704** indicates that a vehicular collision (e.g., **108**) has been detected in the vicinity **106**. Accordingly, the determination indicator **1402** can be set to the active state. In response to the determination indicator **1402** being set to the active state, the execution component **1310** can render on the electronic navigation display **1502** a graphical representation of the vehicular collision. In various aspects, such graphical representation can be rendered at an intra-screen location on the electronic navigation display **1502** that corresponds to

whatever geolocation is indicated in the geolocation stamp **814**. A non-limiting example of this is shown in FIG. **17**.

(215) Suppose that the geolocation stamp **814** indicates that the vehicular collision was detected (e.g., by the deep learning neural network **402** of the vehicle **102**) at a geolocation that is on the third road (e.g., on the road represented by the graphical representation **1608**). In such case, the execution component **1310** can render, as shown in FIG. **17**, a graphical representation **1702** of the vehicular collision, such that the graphical representation **1702** is superimposed on top of the graphical representation **1608** (e.g., to indicate that the vehicular collision occurred on the third road). Although FIG. **17** depicts the graphical representation **1702** as being a triangular shape with an exclamation mark to indicate emphasis or importance, this is a mere non-limiting example. In various aspects, the graphical representation **1702** can be visually rendered via any suitable colors, shapes, symbols, or artistic styles.

(216) In some cases, the graphical representation **1702** can exhibit unique visual properties (e.g., unique colors, unique shapes, unique sizes, unique symbols) based on the vehicular collision classification label **404**. For example, if the vehicular collision (e.g., **108**) involves a first attribute (e.g., vehicular fire), then the graphical representation **1702** can have visual properties correlated with such first attribute (e.g., the graphical representation **1702** can be a flame symbol to represent the vehicular fire). As another example, if the vehicular collision (e.g., **108**) involves a second attribute (e.g., vehicular roll-over), then the graphical representation **1702** can have visual properties correlated with such second attribute (e.g., the graphical representation **1702** can be a circular arrow symbol to represent the vehicular roll-over). As yet another example, if the vehicular collision (e.g., **108**) involves a third attribute (e.g., injured pedestrians), then the graphical representation **1702** can have visual properties correlated with such third attribute (e.g., the graphical representation **1702** can be a red-cross symbol to represent the injured pedestrians).

(217) In various aspects, as shown, the execution component **1310** can also render on the electronic navigation display a textual description **1704** corresponding to the vehicular collision. In the non-limiting example shown in FIG. **17**, the vehicular collision classification label **404** can indicate that a highly severe head-on impact occurred at the geolocation indicated by the geolocation stamp **814**. Accordingly, the textual description **1704** can specify or otherwise convey such information (e.g., “vehicular collision detected”, “head-on impact”, “high severity”). In various instances, the textual description **1704** can include or otherwise be based on the assistance request **820**. Returning to the non-limiting example of FIG. **17**, the assistance request **820** can indicate that an ambulance should be dispatched to the geolocation indicated by the geolocation stamp **814**, due to the high severity of the detected vehicular collision. Accordingly, the textual description **1704** can, in various cases, specify or otherwise convey such information (e.g., “ambulance requested”).

(218) In any case, in response to the determination indicator **1402** being set to the active state, the execution component **1310** can visually render the graphical representation **1702**, can visually render the textual description **1704**, or can otherwise adjust the electronic navigation display **1502**, so as to notify a driver of whatever emergency service vehicle corresponds to the emergency service system **110** that the vehicular collision (e.g., **108**) has been detected in the vicinity **106**.

(219) FIG. **18** illustrates a flow diagram of an example, non-limiting computer-implemented method **1800** that can facilitate adjusting an electronic navigation display in accordance with one or more embodiments described herein. In various cases, the emergency service system **110** can facilitate the computer-implemented method **1800**.

(220) In various embodiments, act **1802** can include receiving (e.g., via **1306**), by an emergency service device (e.g., **110**) and from a smart vehicle (e.g., **102**), an electronic notification (e.g., **704**) pertaining to a vicinity (e.g., **106**) of the smart vehicle.

(221) In various aspects, act **1804** can include parsing, by the emergency service device (e.g., via **1308**), contents of the electronic notification.

(222) In various instances, act **1806** can include determining, by the emergency service device

(e.g., via **1308**), whether the electronic notification indicates that a vehicular collision (e.g., **108**) has occurred or is occurring in the vicinity. If not (e.g., if the electronic notification indicates that no vehicular collision has yet been detected in the vicinity), then the computer-implemented method **1800** can proceed back to act **1802**. If so (e.g., if the electronic notification indicates that a vehicular collision has been detected in the vicinity), then the computer-implemented method **1800** can proceed to act **1808**.

(223) In various cases, act **1808** can include rendering, by the emergency service device (e.g., via **1310**), a graphical representation (e.g., **1702** or **1704**) of the vehicular collision on an electronic navigation display (e.g., **1502**) of an emergency service vehicle. As shown, the computer-implemented method **1800** can proceed back to act **1802**.

(224) In various embodiments, in response to the determination indicator **1402** being in the active state, the execution component **1310** can compute an electronic navigation route for whatever emergency service vehicle corresponds to the emergency service system **110**. Various non-limiting examples are described with respect to FIG. **19**.

(225) FIG. **19** illustrates an example, non-limiting block diagram **1900** showing how an electronic navigation route can be computed and rendered in accordance with one or more embodiments described herein.

(226) As shown, FIG. **19** illustrates an example, non-limiting view of the electronic navigation display **1502**. As described above, the electronic navigation display **1502** can depict the graphical representation **1602** of the emergency service vehicle that corresponds to the emergency service system **110**, the graphical representation **1604** of the road on which the emergency service vehicle is currently driving, the graphical representation **1606** of a second road that perpendicularly intersects the road on which the emergency service vehicle is currently driving, the graphical representation **1608** of a third road that perpendicularly branches off from the second road, the graphical representation **1702** of the vehicular collision detected by the deep learning neural network **402**, or the textual description **1704** of the vehicular collision.

(227) In various aspects, the execution component **1310** can compute, calculate, or otherwise determine, via any suitable geographic mapping or routing techniques, an electronic navigation route for the emergency service vehicle to follow. In particular, like the vehicle **102**, the emergency service vehicle can be outfitted with any suitable geolocation sensors. Accordingly, the execution component **1310** can utilize such geolocation sensors to determine a current geolocation of the emergency service vehicle at any given instant in time. In various cases, as mentioned above, the electronic alert **704** can include the geolocation stamp **814**, which can indicate a geolocation of the vehicular collision (e.g., **108**) detected by the deep learning neural network **402**. That is, the execution component **1310** can, in various aspects, know both the current geolocation of the emergency service vehicle and the geolocation of the vehicular collision. Thus, the execution component **1310** can calculate or otherwise compute, via any suitable geographic mapping or routing techniques, an electronic navigation route (e.g., a sequence of traffic directions) that leads from the current geolocation of the emergency service vehicle to the geolocation of the vehicular collision. In various instances, the execution component **1310** can render a graphical representation **1902** of such electronic navigation route on the electronic navigation display **1502**. Therefore, the electronic navigation route can be visible to a driver of the emergency service vehicle, so that the driver can know how to get to the scene of the vehicular collision. In various aspects, rendition of the graphical representation **1902** can be considered as dispatching the emergency service vehicle to the scene of the vehicular collision (e.g., as ordering the emergency service vehicle to handle the vehicular collision).

(228) FIG. **20** illustrates a flow diagram of an example, non-limiting computer-implemented method **2000** that can facilitate generating an electronic navigation route in accordance with one or more embodiments described herein. In various cases, the emergency service system **110** can facilitate the computer-implemented method **2000**.

(229) In various embodiments, the computer-implemented method **2000** can include acts **1802**, **1804**, and **1806**, as described above. In various aspects, if it is determined at act **1806** that the electronic notification indicates that a vehicular collision (e.g., **108**) has occurred or is occurring in the vicinity (e.g., **106**) of the smart vehicle (e.g., **102**), then the computer-implemented method **2000** can proceed to act **2002**.

(230) In various embodiments, act **2002** can include calculating, by the emergency service device (e.g., via **1310**), an electronic navigation route that can lead from a current location of an emergency service vehicle to the vehicular collision.

(231) In various aspects, act **2004** can include rendering, by the emergency service device (e.g., via **1310**) and on an electronic navigation display (e.g., **1502**) of the emergency service vehicle, a graphical representation (e.g., **1902**) of the electronic navigation route. In various cases, the computer-implemented method **2000** can proceed back to act **1802**.

(232) FIG. **21** illustrates a block diagram of an example, non-limiting system **2100** including a deep learning neural network and a verification label that can facilitate a receipt-side of artificially intelligent provision of post-vehicular-collision evidence in accordance with one or more embodiments described herein. As shown, the system **2100** can, in some cases, comprise the same components as the system **1500**, and can further comprise a deep learning neural network **2102** or a verification label **2104**.

(233) In various embodiments, the execution component **1310** can electronically store, electronically maintain, electronically control, or otherwise electronically access the deep learning neural network **2102**. In various aspects, the deep learning neural network **2102** can have or otherwise exhibit any suitable internal architecture. For instance, the deep learning neural network **2102** can have an input layer, one or more hidden layers, and an output layer. In various instances, any of such layers can be coupled together by any suitable interneuron connections or interlayer connections, such as forward connections, skip connections, or recurrent connections. Furthermore, in various cases, any of such layers can be any suitable types of neural network layers having any suitable trainable or non-trainable internal parameters. For example, any of such input layer, one or more hidden layers, or output layer can be convolutional layers, dense layers, batch normalization layers, non-linearity layers, padding layers, pooling layers, or concatenation layers. In various cases, the deep learning neural network **2102** can have the same or different internal architecture as the deep learning neural network **402**.

(234) In any case, the deep learning neural network **2102** can be configured to detect vehicular collisions based on inputted vicinity data, just like the deep learning neural network **402**. Accordingly, the deep learning neural network **2102** can undergo any suitable type of training, just like the deep learning neural network **402** (e.g., as described with respect to FIGS. **9-11**). In some cases, the deep learning neural network **2102** can be trained on the same or different training dataset as the deep learning neural network **402**.

(235) In various aspects, the execution component **1310** can use the deep learning neural network **2102** to double-check the analysis outputted by the deep learning neural network **402**. In particular, as mentioned above, the electronic alert **704** can include the vicinity data **208**. As also mentioned above, the deep learning neural network **402** can have detected the vehicular collision (e.g., **108**) based on the vicinity data **208**. Accordingly, in various aspects, the execution component **1310** can double-check this detection of the deep learning neural network **402**, by executing the deep learning neural network **2102** on the vicinity data **208**, thereby yielding the verification label **2104**. Various non-limiting aspects are explained with respect to FIG. **22**.

(236) FIG. **22** illustrates an example, non-limiting block diagram **2200** showing how the deep learning neural network **2102** can generate the verification label **2104** in accordance with one or more embodiments described herein.

(237) As shown, in response to the determination indicator **1402** being set to the active state, the execution component **1310** can, in various aspects, execute the deep learning neural network **2102**

on the vicinity data **208**, and such execution can cause the deep learning neural network **2102** to produce the verification label **2104**. More specifically, the execution component **1310** can feed the vicinity data **208** (e.g., the set of vicinity images **312**, the set of vicinity noises **314**, the set of vicinity temperatures **316**, the set of vicinity humidities **318**, or the set of vicinity proximity detections **320**) to an input layer of the deep learning neural network **2102**. In various instances, the vicinity data **208** (e.g., the set of vicinity images **312**, the set of vicinity noises **314**, the set of vicinity temperatures **316**, the set of vicinity humidities **318**, or the set of vicinity proximity detections **320**) can complete a forward pass through one or more hidden layers of the deep learning neural network **2102**. In various instances, an output layer of the deep learning neural network **2102** can compute the verification label **2104**, based on activation maps or intermediate features produced by the one or more hidden layers.

(238) In various aspects, the verification label **2104** can have the same format, size, or dimensionality as the vehicular collision classification label **404**. That is, the vehicular collision classification label **404** can indicate, specify, convey, or otherwise represent a presence or attributes of a vehicular collision that the deep learning neural network **402** believes has occurred or is occurring in the vicinity **106**, whereas the verification label **2104** can indicate, specify, convey, or otherwise represent a presence or attributes of a vehicular collision that the deep learning neural network **2102** believes has occurred or is occurring in the vicinity **106**.

(239) In various aspects, the execution component **1310** can compare the verification label **2104** with the vehicular collision classification label **404**. If the verification label **2104** matches (e.g., differs by not more than any suitable threshold margin from) the vehicular collision classification label **404**, then the execution component **1310** can conclude that the deep learning neural network **402** correctly analyzed the vicinity data **208**. In such case, the execution component **1310** can transmit, via the communication link **112** and to the collision evidence system **104**, an electronic reply (not shown) indicating that the analysis results produced by the deep learning neural network **402** based on the vicinity data **208** have been successfully double-checked and that emergency services will thus be dispatched. In contrast, if the verification label **2104** does not match (e.g., differs by more than any suitable threshold margin from) the vehicular collision classification label **404**, then the execution component **1310** can conclude that the deep learning neural network **402** incorrectly analyzed the vicinity data **208**. In such case, the execution component **1310** can transmit, via the communication link **112** and to the collision evidence system **104**, an electronic reply (not shown) indicating that the analysis results produced by the deep learning neural network **402** based on the vicinity data **208** have not been successfully double-checked. In such case, the electronic reply can further indicate that emergency services will not be dispatched, in response to the verification label **2104** indicating that no vehicular collision is occurring or has occurred in the vicinity **106**. In contrast, the electronic reply can further indicate that emergency services will nevertheless be dispatched (e.g., notwithstanding the incorrect analysis of the deep learning neural network **402**), in response to the verification label **2104** indicating that a different vehicular collision (e.g., having attributes different from those specified in the vehicular collision classification label **404**) is occurring or has occurred in the vicinity **106**.

(240) Note that, in some cases where the verification label **2104** does not match the vehicular collision classification label **404**, it can be possible for the vehicular collision classification label **404** to be correct and for the verification label **2104** to be incorrect (e.g., it can be possible for the deep learning neural network **402** to have correctly analyzed the vicinity data **208** and for the deep learning neural network **2102** to have incorrectly analyzed the vicinity data **208**). To help deal with such situations, the execution component **1310** can, in some cases and in response to a determination that the verification label **2104** does not match the vehicular collision classification label **404**, electronically replay or reproduce any portions of the vicinity data **208** for viewing, listening, or other inspection by a user of the emergency service system **110**. For example, the execution component **1310** can electronically render the set of vicinity images **312** on any suitable

computer screen that is visible to the user. As another example, the execution component **1310** can electronically play the set of vicinity noises **314** on any suitable computer speakers that are audible to the user. Accordingly, the execution component **1310** can electronically receive from the user any suitable input (e.g., via keyboard, keypad, computer mouse, touchscreen, or voice command), where such input can indicate whether or not the user believes that the vicinity data **208** represents a vehicular collision. In this way, the user can provide manual confirmation regarding whether the vicinity data **208** represents a vehicular collision.

(241) FIG. **23** illustrates a flow diagram of an example, non-limiting computer-implemented method **2300** that can facilitate generation of a verification label in accordance with one or more embodiments described herein. In various cases, the emergency service system **110** can facilitate the computer-implemented method **2300**.

(242) In various embodiments, the computer-implemented method **2300** can include acts **1802**, **1804**, and **1806**, as described above. In various aspects, if it is determined at act **1806** that the electronic notification (e.g., **704**) indicates that a vehicular collision (e.g., **108**) has occurred or is occurring in the vicinity (e.g., **106**) of the smart vehicle (e.g., **102**), then the computer-implemented method **2300** can proceed to act **2302**.

(243) In various embodiments, act **2302** can include accessing, by the emergency service device (e.g., via **1310**), a deep learning neural network (e.g., **2102**) that has been trained to detect vehicular collisions.

(244) In various aspects, act **2304** can include executing, by the emergency service device (e.g., via **1310**), the deep learning neural network on vicinity data (e.g., **208**) specified in the electronic notification. In various cases, this can cause the deep learning neural network to produce an outputted classification label (e.g., **2104**).

(245) In various instances, act **2306** can include determining, by the emergency service device (e.g., via **1310**), whether the outputted classification label indicates the vehicular collision (e.g., determining whether **2104** matches **404**). If so, the computer-implemented method **2300** can proceed to act **2308**. If not, the computer-implemented method **2300** can instead proceed to act **2310**.

(246) In various cases, act **2308** can include informing, by the emergency service device (e.g., via **1310**), the smart vehicle (e.g., **102**) that the vehicular collision has been verified. In various aspects, this can further include informing, by the emergency service device (e.g., via **1310**), the smart vehicle that emergency assistance will accordingly be ordered or dispatched. As shown, the computer-implemented method **2300** can proceed back to act **1802**.

(247) In various instances, act **2310** can include informing, by the emergency service device (e.g., via **1310**), the smart vehicle (e.g., **102**) that the vehicular collision has not been verified. In various cases, this can further include informing, by the emergency service device (e.g., via **1310**), the smart vehicle that emergency assistance will accordingly not be ordered or dispatched. As shown, the computer-implemented method **2300** can proceed back to act **1802**.

(248) Thus far, various embodiments have been described in which the broadcast component **214** can transmit the electronic alert **704** to the emergency service system **110**. However, in various embodiments, there can be a neighboring vehicle within the vicinity **106**, and the broadcast component **214** can transmit a version of the electronic alert **704** to such neighboring vehicle. Various non-limiting aspects are described with respect to FIGS. **24-25**.

(249) FIG. **24** illustrates an example, non-limiting block diagram **2400** showing a neighboring vehicle within a vicinity of a vehicle that has detected a vehicular collision, where such neighboring vehicle can facilitate artificially intelligent provision of post-vehicular-collision evidence in accordance with one or more embodiments described herein.

(250) As shown, FIG. **24** depicts the vehicle **102**, the collision evidence system **104**, the vicinity **106**, the vehicular collision **108**, the emergency service system **110**, and the communication link **112**.

(251) As further shown, there can be a vehicle **2402**. In various aspects, the vehicle **2402** can be any suitable vehicle that is within the vicinity **106** and that is not involved in the vehicular collision **108**. In other words, the vehicle **2402** can be considered as a neighboring vehicle that is near the vehicle **102** and that, like the vehicle **102**, is spectating or witnessing the vehicular collision **108** or the aftermath of the vehicular collision **108**. Although not explicitly shown in FIG. **24** for purposes of visual clarity, the vehicle **2402** can be considered as having its own vicinity (e.g., like the vicinity **106**). Because the vehicular collision **108** and the vehicle **2402** can both be within the vicinity **106**, it can be presumed that the vehicular collision **108** is also within the vicinity of the vehicle **2402**.

(252) Furthermore, as shown, the vehicle **2402** can be communicatively coupled to the vehicle **102** via a communication link **2404**. In various aspects, the communication link **2404** can be like the communication link **112**. That is, the communication link **2404** can, in some cases, be any suitable wireless Internet connection that utilizes intermediate access points or intermediate routers, or the communication link **2404** can, in other cases, be any suitable P2P connection that can operate in the absence of intermediate access points or intermediate routers (e.g., BLUETOOTH® P2P or Wi-Fi P2P).

(253) In various aspects, in response to the vehicular collision classification label **404** indicating that a vehicular collision (e.g., **108**) is occurring or has occurred in the vicinity **106**, the broadcast component **214** of the collision evidence system **104** can electronically generate the electronic alert **704** as described above, and the broadcast component **214** can electronically transmit, via the communication link **2404**, an anonymized version of the electronic alert **704** to the vehicle **2402**. Like the electronic alert **704**, the anonymized version of the electronic alert **704** can, in various instances, comprise the recorded post-collision evidence **702**, the vehicular collision classification label **404**, the vicinity data **208**, the geolocation stamp **814**, or the timestamp **816**. However, unlike the electronic alert **704**, the anonymized version of the electronic alert **704** can, in various cases, lack the vehicle identifier **818**, hence the name “anonymized.” In other words, the vehicle **102** can inform the vehicle **2402** (can inform any suitable computing device of the vehicle **2402**) of the vehicular collision classification label **404**, of the vicinity data **208**, of the geolocation stamp **814**, or of the timestamp **816**, but the vehicle **102** can refrain from informing the vehicle **2402** of identifying information corresponding to the vehicle **102**. In this way, a privacy of the vehicle **102** can be preserved or maintained.

(254) Moreover, in various aspects, the anonymized version of the electronic alert **704** can lack the assistance request **820**. Instead, the anonymized version of the electronic alert **704** can, in various instances, comprise an evidence recordation request. Indeed, the vehicle **2402** can be considered as having its own vicinity, and the vehicular collision **108** can be considered as being within that vicinity of the vehicle **2402**. Furthermore, like the vehicle **102**, the vehicle **2402** can be outfitted or otherwise equipped with any suitable road-facing sensors that can monitor, scan, or otherwise capture what transpires in the vicinity of the vehicle **2402**. As some non-limiting examples, the vehicle **2402** can have any suitable vehicle cameras (e.g., like the set of vehicle cameras **302**), can have any suitable vehicle microphones (e.g., like the set of vehicle microphones **304**), can have any suitable vehicle thermometers (e.g., like the set of vehicle thermometers **306**), can have any suitable vehicle hygrometers (e.g., like the set of vehicle hygrometers **308**), or can have any suitable vehicle proximity sensors (e.g., like the set of vehicle proximity sensors **310**). Accordingly, in various cases, the evidence recordation request of the anonymized version of the electronic alert **704** can be any suitable electronic data that instructs, commands, prompts, or otherwise asks the vehicle **2402** to utilize its various sensors to begin recording the vehicular collision **108** (e.g., to begin recording the vicinity of the vehicle **2402**, which can encompass the vehicular collision **108**). In other words, the evidence recordation request of the anonymized version of the electronic alert **704** can instruct the vehicle **2402** to generate its own version of recorded post-collision evidence concerning the vehicular collision **108**. In various aspects, the vehicle **2402** can obey the evidence

recording request, thereby recording the vehicular collision **108** or its aftermath. In various instances, although not explicitly shown in the figures, the vehicle **2402** can transmit any of such recorded evidence to the emergency service system **110**, to the collision evidence system **104**, or to any other suitable computing device.

(255) FIG. **25** illustrates a flow diagram of an example, non-limiting computer-implemented method **2500** that can facilitate a neighboring vehicle aspect of artificially intelligent provision of post-vehicular-collision evidence in accordance with one or more embodiments described herein. In various cases, any suitable computing device of the vehicle **2402** can facilitate the computer-implemented method **2500**.

(256) In various embodiments, act **2502** can include receiving, by a first smart vehicle (e.g., **2402**) that is in a vicinity (e.g., **106**) of a second smart vehicle (e.g., **102**), an electronic notification (e.g., anonymized version of **704**) from the second smart vehicle.

(257) In various aspects, act **2504** can include parsing, by the first smart vehicle (e.g., **2402**), contents of the electronic notification.

(258) In various instances, act **2506** can include determining, by the first smart vehicle (e.g., **2402**), whether the electronic notification indicates that a vehicular collision (e.g., **108**) has occurred or is occurring in the vicinity. If not, the computer-implemented method **2500** can proceed back to act **2502**. If so, the computer-implemented method **2500** can proceed to act **2508**.

(259) In various cases, act **2508** can include recording, by the first smart vehicle (e.g., **2402**) and via one or more road-facing sensors of the first smart vehicle (e.g., cameras, microphones, thermometers, hygrometers, or proximity sensors of **2402**), post-collision evidence (e.g., like **702**) concerning the vicinity.

(260) In various aspects, act **2510** can include transmitting, by the first smart vehicle (e.g., **2402**), the post-collision evidence to an emergency service device (e.g., **110**). As shown, the computer-implemented method **2500** can proceed back to act **2502**.

(261) Thus far, various embodiments have been described in which the evidence component **212** can generate the recorded post-collision evidence **702** and the broadcast component **214** can transmit the electronic alert **704** (which can include the recorded post-collision evidence **702**) to the emergency service system **110**. However, in various aspects, the evidence component **212** can be omitted or can otherwise refrain from generating the recorded post-collision evidence **702**. In such cases, rather than transmitting the electronic alert **704**, the broadcast component **214** can instead broadcast a live stream of the vicinity **106** to the emergency service system **110**. Various non-limiting aspects are described with respect to FIGS. **26-34**.

(262) FIG. **26** illustrates a block diagram of an example, non-limiting system **2600** including a post-collision live stream that can facilitate a broadcast-side of artificially intelligent provision of post-vehicular-collision evidence in accordance with one or more embodiments described herein. As shown, the system **2600** can, in some cases, omit or otherwise deactivate the evidence component **212**, and can instead comprise a post-collision live stream **2602**.

(263) In various embodiments, in response to the vehicular collision classification label **404** indicating that a vehicular collision (e.g., **108**) is occurring or has occurred in the vicinity **106**, the broadcast component **214** can electronically transmit or otherwise electronically broadcast, via the communication link **112** and via the various sensors of the sensor component **206**, the post-collision live stream **2602** to the receiver component **1306** of the emergency service system **110**. In some cases, the broadcast component **214** can electronically transmit the collision metadata **812** (e.g., the vehicular collision classification label **404**, the vicinity data **208**, the geolocation stamp **814**, the timestamp **816**, or the vehicle identifier **818**) to the receiver component **1306** in parallel with the post-collision live stream **2602**. In otherwise, the post-collision live stream **2602** can be considered as being tagged with the collision metadata **812**.

(264) In any case, the post-collision live stream **2602** can be considered as any suitable electronic data that is captured by the various sensors of the sensor component **206** in the moments following

detection of the vehicular collision (e.g., **108**) by the deep learning neural network **402** and that is broadcasted/transmitted in real-time over the communication link **112**. In other words, the post-collision live stream **2602** can be considered as showing whatever is transpiring in real-time within the vicinity **106** after detection of the vehicular collision. Various non-limiting aspects are discussed with respect to FIG. **27**.

(265) FIG. **27** illustrates an example, non-limiting block diagram **2700** of a post-collision live stream in accordance with one or more embodiments described herein. In other words, FIG. **27** depicts a non-limiting example embodiment of the post-collision live stream **2602**.

(266) In various embodiments, as shown, the post-collision live stream **2602** can comprise a set of live-streamed post-collision vicinity images **2702**. In various aspects, the broadcast component **214** can, in response to the vehicular collision classification label **404** indicating that a vehicular collision (e.g., **108**) is occurring or has occurred in the vicinity **106**, cause the set of vehicle cameras **302** to capture or otherwise record any suitable number of images or video frames (e.g., any suitable number of two-dimensional pixel arrays) that can depict portions of the vicinity **106** (e.g., portions of the vicinity **106** that lie in front of, behind, or beside the vehicle **102**) in the moments after the vehicular collision. However, rather than being merely recorded or stored, such images or video frames can be transmitted or otherwise broadcasted, by the broadcast component **214** via the communication link **112**, immediately or substantially immediately upon being captured by the set of vehicle cameras **302**. In other words, such images or video frames can be captured and transmitted in real-time during the moments after the vehicular collision occurs or is detected. In still other words, such images or video frames can be live-streamed by the broadcast component **214** to the receiver component **1306**. Accordingly, such images or video frames can be considered as the set of live-streamed post-collision vicinity images **2702**.

(267) In various embodiments, as shown, the post-collision live stream **2602** can comprise a set of live-streamed post-collision vicinity noises **2704**. In various aspects, the broadcast component **214** can, in response to the vehicular collision classification label **404** indicating that a vehicular collision (e.g., **108**) is occurring or has occurred in the vicinity **106**, cause the set of vehicle microphones **304** to capture or otherwise record any suitable number of sound bites that can represent noises occurring in portions of the vicinity **106** (e.g., portions of the vicinity **106** that lie in front of, behind, or beside the vehicle **102**) in the moments after the vehicular collision. However, rather than being merely recorded or stored, such sound bites can be transmitted or otherwise broadcasted, by the broadcast component **214** via the communication link **112**, immediately or substantially immediately upon being captured by the set of vehicle microphones **304**. In other words, such sound bites can be captured and transmitted in real-time during the moments after the vehicular collision occurs or is detected. In still other words, such sound bites can be live-streamed by the broadcast component **214** to the receiver component **1306**. Accordingly, such sound bites can be considered as the set of live-streamed post-collision vicinity noises **2704**.

(268) In various embodiments, as shown, the post-collision live stream **2602** can comprise a set of live-streamed post-collision vicinity temperatures **2706**. In various aspects, the broadcast component **214** can, in response to the vehicular collision classification label **404** indicating that a vehicular collision (e.g., **108**) is occurring or has occurred in the vicinity **106**, cause the set of vehicle thermometers **306** to capture or otherwise record any suitable number of temperature measurements that can represent air temperatures or road surface temperatures associated with portions of the vicinity **106** (e.g., portions of the vicinity **106** that lie in front of, behind, or beside the vehicle **102**) in the moments after the vehicular collision. However, rather than being merely recorded or stored, such temperature measurements can be transmitted or otherwise broadcasted, by the broadcast component **214** via the communication link **112**, immediately or substantially immediately upon being captured by the set of vehicle thermometers **306**. In other words, such temperature measurements can be captured and transmitted in real-time during the moments after

the vehicular collision occurs or is detected. In still other words, such temperature measurements can be live-streamed by the broadcast component **214** to the receiver component **1306**.

Accordingly, such temperature measurements can be considered as the set of live-streamed post-collision vicinity temperatures **2706**.

(269) In various embodiments, as shown, the post-collision live stream **2602** can comprise a set of live-streamed post-collision vicinity humidities **2708**. In various aspects, the broadcast component **214** can, in response to the vehicular collision classification label **404** indicating that a vehicular collision (e.g., **108**) is occurring or has occurred in the vicinity **106**, cause the set of vehicle hygrometers **308** to capture or otherwise record any suitable number of humidity measurements that can represent air moisture contents or road surface moisture levels associated with portions of the vicinity **106** (e.g., portions of the vicinity **106** that lie in front of, behind, or beside the vehicle **102**) in the moments after the vehicular collision. However, rather than being merely recorded or stored, such humidity measurements can be transmitted or otherwise broadcasted, by the broadcast component **214** via the communication link **112**, immediately or substantially immediately upon being captured by the set of vehicle hygrometers **308**. In other words, such humidity measurements can be captured and transmitted in real-time during the moments after the vehicular collision occurs or is detected. In still other words, such humidity measurements can be live-streamed by the broadcast component **214** to the receiver component **1306**. Accordingly, such humidity measurements can be considered as the set of live-streamed post-collision vicinity humidities **2708**.

(270) In various embodiments, as shown, the post-collision live stream **2602** can comprise a set of live-streamed post-collision vicinity proximity detections **2710**. In various aspects, the broadcast component **214** can, in response to the vehicular collision classification label **404** indicating that a vehicular collision (e.g., **108**) is occurring or has occurred in the vicinity **106**, cause the set of vehicle proximity sensors **310** to capture or otherwise record any suitable number of radar, sonar, or lidar proximity measurements that can represent distances between the vehicle **102** and nearby objects located in portions of the vicinity **106** (e.g., portions of the vicinity **106** that lie in front of, behind, or beside the vehicle **102**) in the moments after the vehicular collision. However, rather than being merely recorded or stored, such radar, sonar, or lidar proximity measurements can be transmitted or otherwise broadcasted, by the broadcast component **214** via the communication link **112**, immediately or substantially immediately upon being captured by the set of vehicle proximity sensors **310**. In other words, such radar, sonar, or lidar proximity measurements can be captured and transmitted in real-time during the moments after the vehicular collision occurs or is detected. In still other words, such radar, sonar, or lidar proximity measurements can be live-streamed by the broadcast component **214** to the receiver component **1306**. Accordingly, such radar, sonar, or lidar proximity measurements can be considered as the set of live-streamed post-collision vicinity proximity detections **2710**.

(271) In any case, the post-collision live stream **2602** can be considered as allowing the emergency service system **110** (e.g., as allowing a user or operator of the emergency service system **110**) to observe in real-time the aftermath of a vehicular collision (e.g., **108**) that occurs in the vicinity **106**, even if no emergency service vehicle has physically arrived yet at the vehicular collision. For example, the live-streamed post-collision vicinity images **2702** can allow a user or operator of the emergency service system **110** to “see” the aftermath of the vehicular collision in real-time, notwithstanding that emergency services might not yet actually be at the scene of the vehicular collision. As another example, the live-streamed post-collision vicinity noises **2704** can allow a user or operator of the emergency service system **110** to “hear” the aftermath of the vehicular collision in real-time, notwithstanding that emergency services might not yet actually be at the scene of the vehicular collision.

(272) Because the collision metadata **812** can be transmitted in parallel with the post-collision live stream **2602**, the execution component **1310** of the emergency service system **110** can perform any suitable actions based on the collision metadata **812**, as described above (e.g., can render graphical

representations of the vehicular collision on the electronic navigation display **1502**, can compute an electronic navigation route leading to the vehicular collision, can double-check the vehicular collision classification label **404** via the deep learning neural network **2102**).

(273) FIG. **28** illustrates a flow diagram of an example, non-limiting computer-implemented method **2800** that can facilitate provision of a post-collision live stream in accordance with one or more embodiments described herein. In various cases, the collision evidence system **104** can facilitate the computer-implemented method **2800**.

(274) In various embodiments, the computer-implemented method **2800** can include acts **1202**, **1204**, **1206**, **1208**, **1210**, **1212**, and **1214**, as described above. In various aspects, if it is determined at act **1212** that the outputted classification label (e.g., **404**) indicates that a vehicular collision (e.g., **108**) has occurred or is occurring in the vicinity (e.g., **106**) of the smart vehicle (e.g., **102**), then the computer-implemented method **2800** can proceed to act **2802**.

(275) In various embodiments, act **2802** can include broadcasting, by the smart vehicle (e.g., via **214**), to an emergency service device (e.g., **110**), and via the one or more road-facing sensors (e.g., **302**, **304**, **306**, **308**, or **310**), a post-collision live stream (e.g., **2602**) of the vicinity. In various cases, the post-collision live stream can be tagged with the specific location (e.g., **814**, specified in **812**) and the specific time (e.g., **816**, specified in **812**).

(276) FIG. **29** illustrates a block diagram of an example, non-limiting system **2900** including a battery component that can facilitate provision of a post-collision live stream in accordance with one or more embodiments described herein. As shown, the system **2900** can, in some cases, comprise the same components as the system **2600**, and can further comprise a battery component **2902**, a battery warning **2904**, or a set of electricity reroute actions **2906**. Note that FIG. **29** does not depict the various sensors of the sensor component **206** for sake of visual clarity/space.

(277) In various embodiments, as shown, the collision evidence system **104** can comprise the battery component **2902**. In various aspects, the vehicle **102** can have any suitable electric battery (e.g., one or more lithium-ion car batteries, one or more solid-state car batteries) that can provide electric power to the various sensors of the sensor component **206** (e.g., to the set of vehicle cameras **302**, to the set of vehicle microphones **304**, to the set of vehicle thermometers **306**, to the set of vehicle hygrometers **308**, to the set of vehicle proximity sensors **310**). Accordingly, if the battery of the vehicle **102** loses its charge, the various sensors of the sensor component **206** can be unable to provide the post-collision live stream **2602**. In other words, if the battery of the vehicle **102** loses its charge during the post-collision live stream **2602**, the post-collision live stream **2602** can be terminated, meaning that the emergency service system **110** would no longer be able to observe the aftermath of the vehicular collision (e.g., **108**) in real-time (e.g., without having an actual emergency service presence at the scene of the vehicular collision).

(278) Therefore, in various aspects, the battery component **2902** can electronically monitor, during the post-collision live stream **2602** and via any suitable voltage-meters or amperage-meters, a remaining life of the battery of the vehicle **102**. Moreover, the battery component **2902** can compare such remaining life to any suitable threshold value. If the remaining battery life is above the threshold value, the battery component **2902** can re-measure the remaining battery life of the vehicle **102** and can compare that re-measurement to the threshold value. However, if the remaining battery life is below the threshold value, the broadcast component **214** can electronically generate the battery warning **2904**.

(279) In various aspects, the battery warning **2904** can be any suitable electronic message or notification that indicates that the post-collision live stream **2602** is nearing termination (e.g., is likely to be terminated within any suitable threshold amount of time) due to insufficient electric power. In various instances, the broadcast component **214** can electronically transmit the battery warning **2904** to the receiver component **1306** of the emergency service system **110**, via the communication link **112**.

(280) In various other aspects, if the remaining battery life is below the threshold value, the battery

component **2902** can implement, perform, or otherwise cause the set of electricity reroute actions **2906**. In various instances, as mentioned above, the various sensors of the vehicle **102** (e.g., the set of vehicle cameras **302**, the set of vehicle microphones **304**, the set of vehicle thermometers **306**, the set of vehicle hygrometers **308**, the set of vehicle proximity sensors **310**) can receive electric power from the battery of the vehicle **102**. However, there can be any other suitable features of the vehicle **102** that are unrelated from such sensors (e.g., that are not necessary to provide the post-collision live stream **2602**) but that consume electric power from the battery of the vehicle **102**. As some non-limiting examples, such features can include an air conditioner of the vehicle **102**, a seat heater of the vehicle **102**, a seat cooler of the vehicle **102**, a radio of the vehicle **102**, or cabin lighting or exterior lighting of the vehicle **102**.

(281) In various aspects, the set of electricity reroute actions **2906** can include any suitable number of electricity reroute actions, and an electricity reroute action can include powering-down or otherwise shutting-off an electricity-consuming feature of the vehicle **102** that is unrelated from the various sensors of the sensor component **206** (e.g., that does not contribute to the post-collision live stream **2602**). For example, if an air conditioner of the vehicle **102** is running during the post-collision live stream **2602**, then an electricity reroute action can include partially or fully shutting-off the air conditioner (e.g., battery life consumption by the air conditioner can be reduced, so as to increase an amount of battery life that is available to sustain the post-collision live stream **2602**). As another example, if a seat heater of the vehicle **102** is running during the post-collision live stream **2602**, then an electricity reroute action can include partially or fully shutting-off the seat heater (e.g., battery life consumption by the seat heater can be reduced, so as to increase an amount of battery life that is available to sustain the post-collision live stream **2602**). As yet another example, if undercarriage lighting of the vehicle **102** is running during the post-collision live stream **2602**, then an electricity reroute action can include partially or fully shutting-off the undercarriage lighting (e.g., battery life consumption by the undercarriage lighting can be reduced, so as to increase an amount of battery life that is available to sustain the post-collision live stream **2602**). In this way, the set of electricity reroute actions **2906** help to prolong the post-collision live stream **2602**, when the battery component **2902** determines that the remaining battery life of the vehicle **102** is below any suitable threshold.

(282) FIGS. **30-31** illustrate flow diagrams of example, non-limiting computer-implemented methods **3000** and **3100** that can facilitate provision of a post-collision live stream in accordance with one or more embodiments described herein. In various cases, the collision evidence system **104** can facilitate the computer-implemented methods **3000** or **3100**.

(283) First, consider FIG. **30**. In various embodiments, act **3002** can include initiating, by a smart vehicle (e.g., via **214** of **102**), in response to a determination that a vehicular collision (e.g., **108**) not involving the smart vehicle has occurred or is occurring in a vicinity (e.g., **106**) of the smart vehicle, and via one or more road-facing sensors (e.g., **302**, **304**, **306**, **308**, or **310**) of the smart vehicle, a post-collision live stream (e.g., **2602**) of the vicinity to an emergency service device (e.g., **110**).

(284) In various aspects, act **3004** can include measuring, by the smart vehicle (e.g., via **2902**) and during the live stream, a remaining battery life of the smart vehicle.

(285) In various instances, act **3006** can include determining, by the smart vehicle (e.g., via **2902**), whether the remaining battery life is below (or otherwise fails to satisfy) a threshold. If not (e.g., if the remaining battery life is not below or otherwise does not fail to satisfy the threshold), the computer-implemented method **3000** can proceed back to act **3004**. If so (e.g., if the remaining battery life is below or otherwise fails to satisfy the threshold), the computer-implemented method **3000** can proceed to act **3008**.

(286) In various cases, act **3008** can include transmitting, by the smart vehicle (e.g., via **214**) and to the emergency service device, an electronic warning (e.g., **2904**) indicating that the live stream will soon be terminated due to insufficient battery power.

(287) Now, consider FIG. 31. In various embodiments, the computer-implemented method **3100** can include acts **3002**, **3004**, and **3006**, as described above. However, in response to a determination at act **3006** that the remaining battery life of the smart vehicle (e.g., **102**) is below or otherwise fails to satisfy the threshold, the computer-implemented method **3100** can proceed to act **3102**.

(288) In various aspects, act **3102** can include rerouting, by the smart vehicle (e.g., via **2902**), electric power from one or more unnecessary electric loads of the smart vehicle. As some non-limiting examples, an unnecessary electric load can be any feature of the smart vehicle that consumes electricity but that does not contribute to the post-collision live stream, such as an air conditioner, a seat heater, or a light of the smart vehicle.

(289) FIG. 32 illustrates a block diagram of an example, non-limiting system **3200** including a remote-control component that can facilitate provision of a post-collision live stream in accordance with one or more embodiments described herein. As shown, the system **3200** can, in some cases, comprise the same components as the system **2900**, and can further comprise a remote-control component **3202**, a remote-control notification **3204**, or a set of remote-control commands **3206**.

(290) In various embodiments, as shown, the collision evidence system **104** can comprise a remote-control component **3202**. In various aspects, the vehicle **102** can be outfitted or otherwise equipped with any suitable autonomous or electronically-controllable features, such as autonomous or electronically-controllable cameras, autonomous or electronically-controllable speakers, autonomous or electronically-controllable lighting, autonomous or electronically-controllable steering, autonomous or electronically-controllable throttle, or autonomous or electronically-controllable braking. In various instances, such autonomous or electronically-controllable features can be governed or otherwise orchestrated by the remote-control component **3202**. In various aspects, during or in parallel with the post-collision live stream **2602**, the broadcast component **214** can transmit, to the receiver component **1306** via the communication link **112**, the remote-control notification **3204**, where the remote-control notification **3204** can be any suitable electronic message indicating or identifying the autonomous or electronically-controllable features of the vehicle **102**. In various cases, the execution component **1310** can, in response to the remote-control notification **3204** and via the communication link **112**, electronically transmit the set of remote-control commands **3206**, where the set of remote-control commands **3206** can be any suitable electronic instructions to controllably adjust or manipulate the autonomous or electronically-controllable features of the vehicle **102**. In various cases, the remote-control component **3202** can implement or otherwise obey the set of remote-control commands **3206**. Various non-limiting aspects are described with respect to FIG. 33.

(291) FIG. 33 illustrates an example, non-limiting block diagram **3300** of the remote-control notification **3204** and the set of remote-control commands **3206** in accordance with one or more embodiments described herein.

(292) In various embodiments, as shown, the remote-control notification **3204** can comprise a set of remote-control camera parameters **3302**. In various aspects, the set of remote-control camera parameters **3302** can include any suitable number of remote-control camera parameters. In various instances, a remote-control camera parameter can be any suitable electronic data (e.g., can be one or more scalars, one or more vectors, one or more matrices, one or more tensors, or one or more character strings) that can indicate an electronically-controllable or electronically-adjustable setting of a camera of the vehicle **102**. As a non-limiting example, a remote-control camera parameter can identify a particular camera of the vehicle **102**, the remote-control camera parameter can further identify a principal axis of the particular camera, and the remote-control parameter can even further identify a range of motion (e.g., an angular range) through which the particular camera can controllably swivel or rotate about the principal axis. As another non-limiting example, a remote-control camera parameter can identify a given camera of the vehicle **102**, and the remote-control camera parameter can further identify a zoom range (e.g., a minimum zoom level to a maximum

zoom level) that can be controllably swept by the given camera. As yet another non-limiting example, a remote-control camera parameter can identify a specific camera of the vehicle **102**, and the remote-control camera parameter can further identify visual settings (e.g., daylight setting, night-vision setting, thermal-vision setting) that can be controllably implemented by the specific camera.

(293) In various aspects, as shown, the remote-control notification **3204** can comprise a set of remote-control speaker parameters **3304**. In various aspects, the set of remote-control speaker parameters **3304** can include any suitable number of remote-control speaker parameters. In various instances, a remote-control speaker parameter can be any suitable electronic data (e.g., can be one or more scalars, one or more vectors, one or more matrices, one or more tensors, or one or more character strings) that can indicate an electronically-controllable or electronically-adjustable setting of an audio speaker of the vehicle **102**. As a non-limiting example, a remote-control speaker parameter can identify a particular speaker of the vehicle **102**, the remote-control speaker parameter can further identify a principal axis of the particular speaker, and the remote-control parameter can even further identify a range of motion (e.g., an angular range) through which the particular speaker can controllably swivel or rotate about the principal axis. As another non-limiting example, a remote-control speaker parameter can identify a given speaker of the vehicle **102**, and the remote-control speaker parameter can further identify a volume range (e.g., a minimum loudness level to a maximum loudness level) that can be controllably swept by the given speaker. As yet another non-limiting example, a remote-control speaker parameter can identify a specific speaker of the vehicle **102**, and the remote-control speaker parameter can further identify that the specific speaker can be instructed to playback or otherwise audibly reproduce any suitable sound data (e.g., voice data) that is provided to the specific speaker.

(294) In various embodiments, as shown, the remote-control notification **3204** can comprise a set of remote-control lighting parameters **3306**. In various aspects, the set of remote-control lighting parameters **3306** can include any suitable number of remote-control lighting parameters. In various instances, a remote-control lighting parameter can be any suitable electronic data (e.g., can be one or more scalars, one or more vectors, one or more matrices, one or more tensors, or one or more character strings) that can indicate an electronically-controllable or electronically-adjustable setting of a light of the vehicle **102**. As a non-limiting example, a remote-control lighting parameter can identify a particular headlight of the vehicle **102**, the remote-control lighting parameter can further identify a principal axis of the particular headlight, and the remote-control lighting parameter can even further identify a range of motion (e.g., an angular range) through which the particular headlight can controllably swivel or rotate about the principal axis. As another non-limiting example, a remote-control lighting parameter can identify a given taillight of the vehicle **102**, and the remote-control lighting parameter can further identify a set of colors that can be controllably implemented by the given taillight.

(295) In various embodiments, as shown, the remote-control notification **3204** can comprise a set of remote-control steering parameters **3308**. In various aspects, the set of remote-control steering parameters **3308** can include any suitable number of remote-control steering parameters. In various instances, a remote-control steering parameter can be any suitable electronic data (e.g., can be one or more scalars, one or more vectors, one or more matrices, one or more tensors, or one or more character strings) that can indicate an electronically-controllable or electronically-adjustable steering-related setting of the vehicle **102**. As a non-limiting example, a remote-control steering parameter can identify a particular wheel of the vehicle **102**, the remote-control steering parameter can further identify a principal axis of the particular wheel, and the remote-control parameter can even further identify a range of motion (e.g., an angular range) through which the particular wheel can controllably swivel or rotate about the principal axis for purposes of steering.

(296) In various embodiments, as shown, the remote-control notification **3204** can comprise a set of remote-control throttle parameters **3310**. In various aspects, the set of remote-control throttle

parameters **3310** can include any suitable number of remote-control throttle parameters. In various instances, a remote-control throttle parameter can be any suitable electronic data (e.g., can be one or more scalars, one or more vectors, one or more matrices, one or more tensors, or one or more character strings) that can indicate an electronically-controllable or electronically-adjustable throttle-related setting of the vehicle **102**. As a non-limiting example, a remote-control throttle parameter can identify a particular wheel of the vehicle **102**, and the remote-control throttle parameter can further identify a speed range (e.g., from a maximum speed in one direction to a maximum speed in an opposite direction) at which the particular wheel can be controllably driven or rotated.

(297) In various embodiments, as shown, the remote-control notification **3204** can comprise a set of remote-control braking parameters **3312**. In various aspects, the set of remote-control braking parameters **3312** can include any suitable number of remote-control braking parameters. In various instances, a remote-control braking parameter can be any suitable electronic data (e.g., can be one or more scalars, one or more vectors, one or more matrices, one or more tensors, or one or more character strings) that can indicate an electronically-controllable or electronically-adjustable braking-related setting of the vehicle **102**. As a non-limiting example, a remote-control braking parameter can identify a particular wheel of the vehicle **102**, and the remote-control braking parameter can further identify a braking intensity range (e.g., from a minimum amount of brake application or compression force to a maximum amount of brake application or compression) which can be controllably imparted to the particular wheel.

(298) In any case, the remote-control notification **3204** can thus be considered as informing the emergency service system **110** of what electronically-controllable, and thus remotely-controllable, features the vehicle **102** has at its disposal.

(299) In various embodiments, as mentioned above, the execution component **1310** of the emergency service system **110** can, in response to receiving the remote-control notification **3204** or otherwise at any point during the post-collision live stream **2602**, electronically transmit the set of remote-control commands **3206** to the collision evidence system **104**.

(300) In various aspects, as shown, the set of remote-control commands **3206** can comprise a set of remote-control camera commands **3314**. In various instances, the set of remote-control camera commands **3314** can include any suitable number of remote-control camera commands. In various cases, a remote-control camera command can be any suitable electronic data (e.g., can be one or more scalars, one or more vectors, one or more matrices, one or more tensors, or one or more character strings) that can serve as an instruction to controllably adjust a respective one of the set of remote-control camera parameters **3302**. As a non-limiting example, a remote-control camera command can be an electronic instruction to swivel or rotate a particular camera of the vehicle **102** to a particular angular orientation. As another non-limiting example, a remote-control camera command can be an electronic instruction to increase (or decrease) a zoom level of a specific camera of the vehicle **102** by a specified percentage or amount. As yet another non-limiting example, a remote-control camera command can be an electronic instruction for a given camera of the vehicle **102** to switch from a daylight setting to a night-vision setting.

(301) In various aspects, as shown, the set of remote-control commands **3206** can comprise a set of remote-control speaker commands **3316**. In various instances, the set of remote-control speaker commands **3316** can include any suitable number of remote-control speaker commands. In various cases, a remote-control speaker command can be any suitable electronic data (e.g., can be one or more scalars, one or more vectors, one or more matrices, one or more tensors, or one or more character strings) that can serve as an instruction to controllably adjust a respective one of the set of remote-control speaker parameters **3304**. As a non-limiting example, a remote-control speaker command can be an electronic instruction to swivel or rotate a particular speaker of the vehicle **102** to a particular angular orientation. As another non-limiting example, a remote-control speaker command can be an electronic instruction to increase (or decrease) a volume level of a specific

speaker of the vehicle **102** by a specified percentage or amount. As yet another non-limiting example, a remote-control speaker command can be an electronic instruction for a given speaker of the vehicle **102** to play or otherwise audibly reproduce specified sound data (e.g., to play or audibly reproduce vocal instructions provided by a user or operator of the emergency service system **110**).

(302) In various aspects, as shown, the set of remote-control commands **3206** can comprise a set of remote-control lighting commands **3318**. In various instances, the set of remote-control lighting commands **3318** can include any suitable number of remote-control lighting commands. In various cases, a remote-control lighting command can be any suitable electronic data (e.g., can be one or more scalars, one or more vectors, one or more matrices, one or more tensors, or one or more character strings) that can serve as an instruction to controllably adjust a respective one of the set of remote-control lighting parameters **3306**. As a non-limiting example, a remote-control lighting command can be an electronic instruction to swivel or rotate a particular light of the vehicle **102** to a particular angular orientation. As another non-limiting example, a remote-control lighting command can be an electronic instruction to increase (or decrease) a brightness level of a specific light of the vehicle **102** by a specified percentage or amount. As yet another non-limiting example, a remote-control lighting command can be an electronic instruction for a given light of the vehicle **102** to switch from one color to another.

(303) In various aspects, as shown, the set of remote-control commands **3206** can comprise a set of remote-control steering commands **3320**. In various instances, the set of remote-control steering commands **3320** can include any suitable number of remote-control steering commands. In various cases, a remote-control steering command can be any suitable electronic data (e.g., can be one or more scalars, one or more vectors, one or more matrices, one or more tensors, or one or more character strings) that can serve as an instruction to controllably adjust a respective one of the set of remote-control steering parameters **3308**. As a non-limiting example, a remote-control steering command can be an electronic instruction to swivel or rotate a particular wheel of the vehicle **102** to a particular steering position or angular orientation.

(304) In various aspects, as shown, the set of remote-control commands **3206** can comprise a set of remote-control throttle commands **3322**. In various instances, the set of remote-control throttle commands **3322** can include any suitable number of remote-control throttle commands. In various cases, a remote-control throttle command can be any suitable electronic data (e.g., can be one or more scalars, one or more vectors, one or more matrices, one or more tensors, or one or more character strings) that can serve as an instruction to controllably adjust a respective one of the set of remote-control throttle parameters **3310**. As a non-limiting example, a remote-control throttle command can be an electronic instruction to drive or otherwise rotate a particular wheel of the vehicle **102** at a particular speed.

(305) In various aspects, as shown, the set of remote-control commands **3206** can comprise a set of remote-control braking commands **3324**. In various instances, the set of remote-control braking commands **3324** can include any suitable number of remote-control braking commands. In various cases, a remote-control braking command can be any suitable electronic data (e.g., can be one or more scalars, one or more vectors, one or more matrices, one or more tensors, or one or more character strings) that can serve as an instruction to controllably adjust a respective one of the set of remote-control braking parameters **3312**. As a non-limiting example, a remote-control braking command can be an electronic instruction to apply a specified amount of braking force to a specified wheel of the vehicle **102**.

(306) In some cases, the execution component **1310** can generate the set of remote-control commands **3206** based on user-provided input from a user or operator of the emergency service system **110**.

(307) In some cases, the remote-control notification **3204** can be considered as a request or a prompt for the remote-control commands **3206**.

(308) In any case, upon receipt of the set of remote-control commands **3206**, the remote-control

component **3202** can implement, perform, or otherwise obey the set of remote-control commands **3206**. In other words, the remote-control component **3202** can controllably adjust any of the autonomous or electronically-controllable features of the vehicle **102** in accordance with or otherwise as specified by the set of remote-control commands **3206**. In this way, the emergency service system **110** (e.g., the user or operator of the emergency service system **110**) can be considered as vicariously interacting, through the vehicle **102**, with the scene of the vehicular collision (e.g., **108**), notwithstanding that emergency services might not yet actually be present at the scene of the vehicular collision. Thus, the remote-control component **3202** can, in some cases, be considered as effectively reducing an emergency service response time.

(309) As a non-limiting example, suppose that the vehicular collision (e.g., **108**) involves an injured pedestrian. Furthermore, suppose that emergency services have not yet physically arrived at the scene of the vehicular collision. In such case, a user or operator of the emergency service system **110** can nevertheless see the injured pedestrian in real-time via the post-collision live stream **2602**. Moreover, in such case, the user or operator of the emergency service system **110** can, by virtue of the remote-control commands **3206**, provide verbal medical advice for the injured pedestrian (or for by-standers near the injured pedestrian) through an audio speaker of the vehicle **102**. In other words, the user or operator of the emergency service system **110** can effectively provide some medical care at the scene of the vehicular collision, notwithstanding that emergency services have actually not yet arrived at the scene.

(310) As another non-limiting example, suppose that the vehicular collision (e.g., **108**) involves multiple vehicles. Furthermore, suppose that emergency services have not yet physically arrived at the scene of the vehicular collision. In such case, a user or operator of the emergency service system **110** might be able to see fewer than all of the involved vehicles via the post-collision live stream **2602**. To address this, the user or operator of the emergency service system **110** can, by virtue of the remote-control commands **3206**, remotely and controllably cause the vehicle **102** to move to a different location near the vehicular collision, so that the post-collision live stream **2602** now depicts the vehicular collision from a different vantage point. In this way, the user or operator of the emergency service system **110** can be able to survey or surveil in real-time the scene of the vehicular collision (e.g., to see in real-time other, previously hidden vehicles involved in the vehicular collision), notwithstanding that emergency services have actually not yet arrived at the scene.

(311) As still another non-limiting example, suppose that the vehicular collision (e.g., **108**) occurs at night. Furthermore, suppose that emergency services have not yet physically arrived at the scene of the vehicular collision. Because the vehicular collision has occurred at night, it is possible that the vehicular collision is not easily visually noticeable to oncoming traffic. In such case, a user or operator of the emergency service system **110** can, by virtue of the remote-control commands **3206**, remotely cause the vehicle **102** to shine lights on the vehicular collision, so as to draw attention from oncoming traffic (e.g., so as to reduce a likelihood that the vehicular collision will cause follow-on accidents in oncoming traffic). In other words, the user or operator of the emergency service system **110** can effectively engage or otherwise interact with the scene of the vehicular collision, notwithstanding that emergency services have actually not yet arrived at the scene.

(312) Note that, in various aspects, the remote-control notification **3204** can include any other suitable remote-control parameters of the vehicle **102**, such as a remote-control direction of travel parameter (e.g., the vehicle **102** can be able to move forward, backward, or sideways in some embodiments) or a remote-control suspension parameter (e.g., a suspension system of the vehicle **102** can be able to increase or decrease a ride height of the vehicle **102**). Accordingly, the set of remote-control commands **3206** can include any suitable remote-control commands corresponding to such other remote-control parameters (e.g., can include a set of direction of travel commands, or can include a set of suspension/ride-height commands).

(313) FIG. **34** illustrates a flow diagram of an example, non-limiting computer-implemented

method **3400** that can facilitate provision of a post-collision live stream in accordance with one or more embodiments described herein. In various cases, the collision evidence system **104** can facilitate the computer-implemented method **3400**.

(314) In various embodiments, the computer-implemented method **3400** can include act **3002**, as described above. After act **3002**, the computer-implemented method **3400** can proceed to act **3402**.

(315) In various aspects, act **3402** can include transmitting, by the smart vehicle (e.g., via **214** of **102**), in parallel with the post-collision live stream (e.g., **2602**), and to the emergency service device (e.g., **110**), an indication (e.g., **3204**) of one or more remotely-controllable features of the smart vehicle. In various cases, such features can include adjustable camera angles of the smart vehicle, adjustable camera zooms of the smart vehicle, adjustable speaker volumes of the smart vehicle, adjustable steering of the smart vehicle, adjustable throttle of the smart vehicle, adjustable braking of the smart vehicle, or adjustable lighting of the smart vehicle.

(316) In various instances, act **3404** can include receiving, by the smart vehicle (e.g., via **3202**) and from the emergency service device, one or more electronic instructions (e.g., **3206**) to adjust the one or more remotely-controllable features.

(317) In various cases, act **3406** can include adjusting, by the smart vehicle (e.g., via **3202**), the one or more remotely-controllable features according to the one or more electronic instructions. In various aspects, the post-collision live stream and the one or more electronic instructions can allow the emergency service device to effectively observe or interact with the vicinity (e.g., with the vehicular collision) in real-time, vicariously through the smart vehicle.

(318) FIGS. **35-39** illustrate flow diagrams of example, non-limiting computer-implemented methods **3500**, **3600**, **3700**, **3800**, and **3900** that can facilitate artificially intelligent provision of post-vehicular-collision evidence in accordance with one or more embodiments described herein. In various cases, the collision evidence system **104** or the emergency service system **110** can facilitate the computer-implemented methods **3500**, **3600**, **3700**, **3800**, or **3900**.

(319) First, consider FIG. **35**. In various embodiments, act **3502** can include capturing, by a device (e.g., via **206**) operatively coupled to a processor (e.g., **202**), onboard a first vehicle (e.g., **102**), and via one or more first cameras (e.g., **302**) or one or more first microphones (e.g., **304**) of the first vehicle, vicinity data (e.g., **208**) associated with a first vicinity (e.g., **106**) of the first vehicle.

(320) In various aspects, act **3504** can include determining, by the device (e.g., via **210**) and via execution of a deep learning neural network (e.g., **402**) on the vicinity data, whether a vehicular collision (e.g., **108**) not involving the first vehicle has occurred in the first vicinity of the first vehicle.

(321) In various instances, act **3506** can include recording, by the device (e.g., via **212**), in response to a determination that the vehicular collision has occurred, and via the one or more first cameras or the one or more first microphones, first post-collision evidence (e.g., **702**) associated with the first vicinity of the first vehicle.

(322) Although not explicitly shown in FIG. **35**, the recording the first post-collision evidence can comprise preserving, by the device (e.g., via **212**), the vicinity data.

(323) Although not explicitly shown in FIG. **35**, the computer-implemented method **3500** can further comprise: refraining, by the device (e.g., via **212**) and in response to a determination that the vehicular collision has not occurred, from recording the first post-collision evidence. In various cases, the refraining from recording the first post-collision evidence can comprise discarding, by the device (e.g., via **212**), the vicinity data.

(324) Although not explicitly shown in FIG. **35**, the computer-implemented method **3500** can further comprise: broadcasting, by the device (e.g., via **214**) and to an emergency service computing device (e.g., **110**), a deanonymized electronic alert (e.g., **704**) based on the vehicular collision. In various cases, the deanonymized electronic alert can comprise the first post-collision evidence.

(325) Although not explicitly shown in FIG. **35**, the computer-implemented method **3500** can

further comprise: broadcasting, by the device (e.g., via **214**) and to a second vehicle (e.g., **2402**) in the first vicinity of the first vehicle, an anonymized electronic alert (e.g., anonymized version of **704**) based on the vehicular collision. In various cases, the anonymized electronic alert can request that the second vehicle record, via one or more second cameras or one or more second microphones of the second vehicle, second post-collision evidence associated with a second vicinity of the second vehicle (e.g., as described with respect to FIG. **24**).

(326) Now, consider FIG. **36**. In various embodiments, act **3602** can include capturing, by a device (e.g., **206**) operatively coupled to a processor (e.g., **202**), onboard a vehicle (e.g., **102**), and via one or more cameras (e.g., **302**) or one or more microphones (e.g., **304**) of the vehicle, vicinity data (e.g., **208**) associated with a vicinity (e.g., **106**) of the vehicle.

(327) In various aspects, act **3604** can include generating, by the device (e.g., via **210**) and via execution of a deep learning neural network (e.g., **402**) on the vicinity data, a classification label (e.g., **404**) indicating whether a vehicular collision (e.g., **108**) not involving the vehicle has occurred in the vicinity of the vehicle.

(328) In various instances, act **3606** can include recording, by the device (e.g., via **212**), in response to the classification label indicating that the vehicular collision has occurred, and via the one or more cameras or the one or more microphones, post-collision evidence (e.g., **702**) associated with the vicinity of the vehicle.

(329) In various cases, act **3608** can include broadcasting, by the device (e.g., via **214**) and in response to the classification label indicating that the vehicular collision has occurred, the classification label and the post-collision evidence to an emergency service computing device (e.g., **110**).

(330) Although not explicitly shown in FIG. **36**, the deep learning neural network can receive the vicinity data as input and can produce the classification label as output, and the classification label can binomially indicate (e.g., via **602**) a presence or an absence of the vehicular collision. In various aspects, the deep learning neural network can receive the vicinity data as input and can produce the classification label as output, and the classification label can indicate (e.g., via **604**) how many vehicles are involved in the vehicular collision. In various instances, the deep learning neural network can receive the vicinity data as input and can produce the classification label as output, and the classification label can indicate (e.g., via **608**) an impact type of the vehicular collision, wherein the impact type of the vehicular collision can be one from the group consisting of a rear-end collision, a head-on collision, a side-impact collision, and a side-swipe collision. In various cases, the deep learning neural network can receive the vicinity data as input and can produce the classification label as output, and the classification label can indicate (e.g., via **610**) whether the vehicular collision involves a roll-over. In various aspects, the deep learning neural network can receive the vicinity data as input and can produce the classification label as output, and the classification label can indicate (e.g., via **612**) whether the vehicular collision involves flames. In various instances, the deep learning neural network can receive the vicinity data as input and can produce the classification label as output, and the classification label can indicate (e.g., via **614**) a severity of the vehicular collision.

(331) Now, consider FIG. **37**. In various embodiments, act **3702** can include capturing, by a device (e.g., via **206**) operatively coupled to a processor (e.g., **202**), onboard a vehicle (e.g., **102**), and via one or more cameras (e.g., **302**) or one or more microphones (e.g., **304**) of the vehicle, vicinity data (e.g., **208**) associated with a vicinity (e.g., **106**) of the vehicle.

(332) In various aspects, act **3704** can include determining, by the device (e.g., via **210**) and via execution of a deep learning neural network (e.g., **402**) on the vicinity data, whether a vehicular collision (e.g., **108**) not involving the vehicle has occurred in the vicinity of the vehicle.

(333) In various instances, act **3706** can include broadcasting, by the device (e.g., via **214**), in response to a determination that the vehicular collision has occurred, via the one or more cameras or the one or more microphones, and to an emergency service computing device (e.g., **110**), a post-

collision live stream (e.g., **2602**) associated with the vicinity of the vehicle.

(334) Although not explicitly shown in FIG. **37**, the computer-implemented method **3700** can comprise: refraining, by the device (e.g., via **214**) and in response to a determination that the vehicular collision has not occurred, from broadcasting the post-collision live stream.

(335) Although not explicitly shown in FIG. **37**, the computer-implemented method **3700** can comprise: monitoring, by the device (e.g., via **2902**), a remaining battery life of the vehicle during the post-collision live stream. In various aspects, the computer-implemented method **3700** can comprise: transmitting, by the device (e.g., via **214**), in response to a determination that the remaining battery life of the vehicle is below a threshold, an electronic warning (e.g., **2904**) to the emergency service computing device, wherein the electronic warning indicates that the post-collision live stream is nearing termination. In various instances, the computer-implemented method **3700** can comprise: shutting off, by the device (e.g., via **2902**) and in response to a determination that the remaining battery life of the vehicle is below a threshold, an electric load of the vehicle (e.g., **2906**), wherein the electric load is unrelated to the post-collision live stream. In various cases, the electric load can be one from the group consisting of a seat heater of the vehicle, a seat cooler of the vehicle, an air conditioner of the vehicle, a radio of the vehicle, and a light of the vehicle.

(336) Although not explicitly shown in FIG. **37**, the computer-implemented method **3700** can comprise: transmitting, by the device (e.g., via **214**), during the post-collision live stream, and to the emergency service computing device, an electronic request (e.g., **3204**) for remote-control input (e.g., **3206**) associated with the vehicle. In various cases, the remote-control input can be one from the group consisting of a camera angle input, a camera zoom input, a speaker volume input, a speaker content input, a lighting input, a steering input, a throttle input, and a braking input.

(337) Now, consider FIG. **38**. In various embodiments, act **3802** can include capturing, by a device (e.g., via **206**) operatively coupled to a processor (e.g., **202**), onboard a vehicle (e.g., **102**), and via one or more cameras (e.g., **302**) or one or more microphones (e.g., **304**) of the vehicle, vicinity data (e.g., **208**) associated with a vicinity (e.g., **106**) of the vehicle.

(338) In various aspects, act **3804** can include determining, by the device (e.g., via **210**) and via execution of a deep learning neural network (e.g., **402**) on the vicinity data, whether a vehicular collision (e.g., **108**) not involving the vehicle has occurred in the vicinity of the vehicle.

(339) In various instances, act **3806** can include broadcasting, by the device (e.g., via **214**), in response to a determination that the vehicular collision has occurred, and via the one or more cameras or the one or more microphones, one or more electronic notifications (e.g., **704**, **2602**, **812**, **2904**, **3204**) to an emergency service computing device (e.g., **110**).

(340) Although not explicitly shown in FIG. **38**, the deep learning neural network can receive as input the vicinity data and can produce as output a classification label (e.g., **404**) indicating the vehicular collision, and the one or more electronic notifications can comprise the vicinity data and the classification label (e.g., **704** can comprise **208** and **404**).

(341) Although not explicitly shown in FIG. **38**, the one or more electronic notifications can comprise a geolocation stamp (e.g., **814**) recorded by a global positioning sensor or a wi-fi positioning sensor (e.g., **706**) of the vehicle, and the geolocation stamp can indicate where the vehicular collision occurred.

(342) Although not explicitly shown in FIG. **38**, the one or more electronic notifications can comprise a timestamp (e.g., **816**) recorded by a clock (e.g., **708**) of the vehicle, and the timestamp can indicate when the vehicular collision occurred.

(343) Although not explicitly shown in FIG. **38**, the one or more electronic notifications can comprise an identifier (e.g., **818**) associated with the vehicle, wherein the identifier comprises at least one from the group consisting of a vehicle identification number (VIN) of the vehicle, a license plate of the vehicle, a first name of an owner of the vehicle, a first address of the owner of the vehicle, a second name of a current driver of the vehicle, and a second address of the current

driver of the vehicle.

(344) Although not explicitly shown in FIG. 38, the one or more electronic notifications can comprise post-collision recorded evidence (e.g., 702) or a post-collision live stream (e.g., 2602) captured by the one or more cameras or the one or more microphones of the vehicle.

(345) Although not explicitly shown in FIG. 38, the one or more electronic notifications can indicate what remote-control parameters (e.g., 3204) of the vehicle are available to the emergency service computing device. In various cases, the remote-control parameters include a camera angle parameter, a camera zoom parameter, a speaker content parameter, a speaker volume parameter, a lighting parameter, a steering parameter, a throttle parameter, or a braking parameter.

(346) Now, consider FIG. 39. In various embodiments, act 3902 can include receiving, by a device (e.g., via 1306) operatively coupled to a processor (e.g., 1302), one or more electronic notifications (e.g., 704, 2602, 812, 2904, 3204) broadcasted by a vehicle (e.g., 102).

(347) In various aspects, act 3904 can include determining, by the device (e.g., via 1308) and via parsing, whether the one or more electronic notifications indicate that a vehicular collision (e.g., 108) not involving the vehicle has occurred in a vicinity (e.g., 106) of the vehicle.

(348) In various instances, act 3906 can include initiating, by the device (e.g., via 1310) and in response to a determination that the one or more electronic notifications indicate that the vehicular collision has occurred, one or more electronic actions.

(349) Although not explicitly shown in FIG. 39, the one or more electronic notifications can include vicinity data (e.g., 208) captured by one or more cameras (e.g., 302) or one or more microphones (e.g., 304) of the vehicle, the one or more electronic notifications can indicate that the vehicle detected the vehicular collision by executing a first deep learning neural network (e.g., 402) on the vicinity data, and the computer-implemented method 3900 can further comprise: verifying, by the device (e.g., 1310), such detection by executing a second deep learning neural network (e.g., 2102) on the vicinity data. In various aspects, the computer-implemented method 3900 can further comprise: transmitting, by the device (e.g., via 1310) and in response to the second deep learning neural network detecting the vehicular collision based on the vicinity data, an electronic reply to the vehicle, wherein the electronic reply indicates that the vehicular collision has been successfully verified (e.g., as shown in FIG. 23). In various instances, the computer-implemented method 3900 can further comprise: transmitting, by the device (e.g., via 1310) and in response to the second deep learning neural network failing to detect the vehicular collision based on the vicinity data, an electronic reply to the vehicle, wherein the electronic reply indicates that the vehicular collision has not been successfully verified (e.g., as shown in FIG. 23).

(350) Although not explicitly shown in FIG. 39, the one or more electronic notifications can indicate where (e.g., via 814) the vehicular collision occurred, the device can be onboard an emergency service vehicle, and the computer-implemented method 3900 can further comprise: generating, by the device (e.g., via 1310), an electronic navigation route leading from a current location of the emergency service vehicle to the vehicular collision (e.g., as shown in FIGS. 19-20).

(351) Although not explicitly shown in FIG. 39, the one or more electronic notifications can indicate (e.g., via 3204) that the vehicle has a remotely-controllable camera (e.g., one of 3302), and the computer-implemented method 3900 can further comprise: transmitting, by the device (e.g., via 1310) and to the vehicle, an electronic instruction (e.g., one of 3314) to adjust an angle or a zoom level of the remotely-controllable camera.

(352) Although not explicitly shown in FIG. 39, the one or more electronic notifications can indicate (e.g., via 3204) that the vehicle has a remotely-controllable speaker (e.g., one of 3304), and the computer-implemented method 3900 can further comprise: transmitting, by the device (e.g., via 1310) and to the vehicle, an electronic instruction (e.g., one of 3316) to reproduce defined sound data via the remotely-controllable speaker or to adjust a volume level of the remotely-controllable speaker.

(353) Although not explicitly shown in FIG. 39, the one or more electronic notifications can

indicate (e.g., via **3204**) that the vehicle has remotely-controllable steering (e.g., **3308**), remotely-controllable throttle (e.g., **3310**), remotely-controllable braking (e.g., **3312**), or remotely-controllable lighting (e.g., **3306**), and the computer-implemented method **3900** can further comprise: transmitting, by the device (e.g., via **1310**) and to the vehicle, an electronic instruction (e.g., one of **3320**, **3322**, **3324**, or **3318**) to adjust the remotely-controllable steering, the remotely-controllable throttle, the remotely-controllable braking, or the remotely-controllable lighting. (354) Although the herein disclosure mainly describes various embodiments as generating a classification label (e.g., **404**, **2104**) indicating whether a vehicular collision has occurred or indicating characteristics, properties, or attributes of the vehicular collision, this is a mere non-limiting example. In various aspects, the herein-described deep learning neural networks (e.g., **402**, **2102**) can be configured to generate any suitable format or dimensionality of output (e.g., can be configured to produce bonding boxes or pixel-wise segmentation masks; are not limited only to producing classification labels).

(355) Although the herein disclosure mainly describes various embodiments as implementing deep learning neural networks (e.g., **402**, **2102**), this is a mere non-limiting example. In various aspects, the herein-described teachings can be implemented via any suitable machine learning models exhibiting any suitable artificial intelligence architectures (e.g., support vector machines, naïve Bayes, linear regression, logistic regression, decision trees, random forest).

(356) Although the herein disclosure mainly describes various embodiments as detecting whether or not a vehicular collision occurs within the vicinity of a smart vehicle, this is a mere non-limiting example. In various aspects, the herein-described teachings can be extrapolated to detecting whether or not any event of interest occurs within the vicinity of a smart vehicle (e.g., whether a vehicular collision occurs in the vicinity; whether a medical emergency, such as a heart attack, occurs within the vicinity; whether a crime, such as a burglary or an assault, occurs within the vicinity).

(357) In various instances, machine learning algorithms or models can be implemented in any suitable way to facilitate any suitable aspects described herein. To facilitate some of the above-described machine learning aspects of various embodiments, consider the following discussion of artificial intelligence (AI). Various embodiments described herein can employ artificial intelligence to facilitate automating one or more features or functionalities. The components can employ various AI-based schemes for carrying out various embodiments/examples disclosed herein. In order to provide for or aid in the numerous determinations (e.g., determine, ascertain, infer, calculate, predict, prognose, estimate, derive, forecast, detect, compute) described herein, components described herein can examine the entirety or a subset of the data to which it is granted access and can provide for reasoning about or determine states of the system or environment from a set of observations as captured via events or data. Determinations can be employed to identify a specific context or action, or can generate a probability distribution over states, for example. The determinations can be probabilistic; that is, the computation of a probability distribution over states of interest based on a consideration of data and events. Determinations can also refer to techniques employed for composing higher-level events from a set of events or data.

(358) Such determinations can result in the construction of new events or actions from a set of observed events or stored event data, whether or not the events are correlated in close temporal proximity, and whether the events and data come from one or several event and data sources. Components disclosed herein can employ various classification (explicitly trained (e.g., via training data) as well as implicitly trained (e.g., via observing behavior, preferences, historical information, receiving extrinsic information, and so on)) schemes or systems (e.g., support vector machines, neural networks, expert systems, Bayesian belief networks, fuzzy logic, data fusion engines, and so on) in connection with performing automatic or determined action in connection with the claimed subject matter. Thus, classification schemes or systems can be used to automatically learn and perform a number of functions, actions, or determinations.

(359) A classifier can map an input attribute vector, $z=(z_{\text{sub.1}}, z_{\text{sub.2}}, z_{\text{sub.3}}, z_{\text{sub.4}}, z_{\text{sub.n}})$, to a confidence that the input belongs to a class, as by $f(z)=\text{confidence}(\text{class})$. Such classification can employ a probabilistic or statistical-based analysis (e.g., factoring into the analysis utilities and costs) to determinate an action to be automatically performed. A support vector machine (SVM) can be an example of a classifier that can be employed. The SVM operates by finding a hyper-surface in the space of possible inputs, where the hyper-surface attempts to split the triggering criteria from the non-triggering events. Intuitively, this makes the classification correct for testing data that is near, but not identical to training data. Other directed and undirected model classification approaches include, e.g., naïve Bayes, Bayesian networks, decision trees, neural networks, fuzzy logic models, or probabilistic classification models providing different patterns of independence, any of which can be employed. Classification as used herein also is inclusive of statistical regression that is utilized to develop models of priority.

(360) The herein disclosure describes non-limiting examples. For ease of description or explanation, various portions of the herein disclosure utilize the term “each,” “every,” or “all” when discussing various examples. Such usages of the term “each,” “every,” or “all” are non-limiting. In other words, when the herein disclosure provides a description that is applied to “each,” “every,” or “all” of some particular object or component, it should be understood that this is a non-limiting example, and it should be further understood that, in various other examples, it can be the case that such description applies to fewer than “each,” “every,” or “all” of that particular object or component.

(361) In order to provide additional context for various embodiments described herein, FIG. 40 and the following discussion are intended to provide a brief, general description of a suitable computing environment 4000 in which the various embodiments of the embodiment described herein can be implemented. While the embodiments have been described above in the general context of computer-executable instructions that can run on one or more computers, those skilled in the art will recognize that the embodiments can be also implemented in combination with other program modules or as a combination of hardware and software.

(362) Generally, program modules include routines, programs, components, data structures, etc., that perform particular tasks or implement particular abstract data types. Moreover, those skilled in the art will appreciate that the inventive methods can be practiced with other computer system configurations, including single-processor or multi-processor computer systems, minicomputers, mainframe computers, Internet of Things (IoT) devices, distributed computing systems, as well as personal computers, hand-held computing devices, microprocessor-based or programmable consumer electronics, and the like, each of which can be operatively coupled to one or more associated devices.

(363) The illustrated embodiments of the embodiments herein can be also practiced in distributed computing environments where certain tasks are performed by remote processing devices that are linked through a communications network. In a distributed computing environment, program modules can be located in both local and remote memory storage devices.

(364) Computing devices typically include a variety of media, which can include computer-readable storage media, machine-readable storage media, or communications media, which two terms are used herein differently from one another as follows. Computer-readable storage media or machine-readable storage media can be any available storage media that can be accessed by the computer and includes both volatile and nonvolatile media, removable and non-removable media. By way of example, and not limitation, computer-readable storage media or machine-readable storage media can be implemented in connection with any method or technology for storage of information such as computer-readable or machine-readable instructions, program modules, structured data or unstructured data.

(365) Computer-readable storage media can include, but are not limited to, random access memory (RAM), read only memory (ROM), electrically erasable programmable read only memory

(EEPROM), flash memory or other memory technology, compact disk read only memory (CD-ROM), digital versatile disk (DVD), Blu-ray disc (BD) or other optical disk storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, solid state drives or other solid state storage devices, or other tangible or non-transitory media which can be used to store desired information. In this regard, the terms “tangible” or “non-transitory” herein as applied to storage, memory or computer-readable media, are to be understood to exclude only propagating transitory signals per se as modifiers and do not relinquish rights to all standard storage, memory or computer-readable media that are not only propagating transitory signals per se.

(366) Computer-readable storage media can be accessed by one or more local or remote computing devices, e.g., via access requests, queries or other data retrieval protocols, for a variety of operations with respect to the information stored by the medium.

(367) Communications media typically embody computer-readable instructions, data structures, program modules or other structured or unstructured data in a data signal such as a modulated data signal, e.g., a carrier wave or other transport mechanism, and includes any information delivery or transport media. The term “modulated data signal” or signals refers to a signal that has one or more of its characteristics set or changed in such a manner as to encode information in one or more signals. By way of example, and not limitation, communication media include wired media, such as a wired network or direct-wired connection, and wireless media such as acoustic, RF, infrared and other wireless media.

(368) With reference again to FIG. 40, the example environment **4000** for implementing various embodiments of the aspects described herein includes a computer **4002**, the computer **4002** including a processing unit **4004**, a system memory **4006** and a system bus **4008**. The system bus **4008** couples system components including, but not limited to, the system memory **4006** to the processing unit **4004**. The processing unit **4004** can be any of various commercially available processors. Dual microprocessors and other multi-processor architectures can also be employed as the processing unit **4004**.

(369) The system bus **4008** can be any of several types of bus structure that can further interconnect to a memory bus (with or without a memory controller), a peripheral bus, and a local bus using any of a variety of commercially available bus architectures. The system memory **4006** includes ROM **4010** and RAM **4012**. A basic input/output system (BIOS) can be stored in a non-volatile memory such as ROM, erasable programmable read only memory (EPROM), EEPROM, which BIOS contains the basic routines that help to transfer information between elements within the computer **4002**, such as during startup. The RAM **4012** can also include a high-speed RAM such as static RAM for caching data.

(370) The computer **4002** further includes an internal hard disk drive (HDD) **4014** (e.g., EIDE, SATA), one or more external storage devices **4016** (e.g., a magnetic floppy disk drive (FDD) **4016**, a memory stick or flash drive reader, a memory card reader, etc.) and a drive **4020**, e.g., such as a solid state drive, an optical disk drive, which can read or write from a disk **4022**, such as a CD-ROM disc, a DVD, a BD, etc. Alternatively, where a solid state drive is involved, disk **4022** would not be included, unless separate. While the internal HDD **4014** is illustrated as located within the computer **4002**, the internal HDD **4014** can also be configured for external use in a suitable chassis (not shown). Additionally, while not shown in environment **4000**, a solid state drive (SSD) could be used in addition to, or in place of, an HDD **4014**. The HDD **4014**, external storage device(s) **4016** and drive **4020** can be connected to the system bus **4008** by an HDD interface **4024**, an external storage interface **4026** and a drive interface **4028**, respectively. The interface **4024** for external drive implementations can include at least one or both of Universal Serial Bus (USB) and Institute of Electrical and Electronics Engineers (IEEE) 1394 interface technologies. Other external drive connection technologies are within contemplation of the embodiments described herein.

(371) The drives and their associated computer-readable storage media provide nonvolatile storage of data, data structures, computer-executable instructions, and so forth. For the computer **4002**, the

drives and storage media accommodate the storage of any data in a suitable digital format.

Although the description of computer-readable storage media above refers to respective types of storage devices, it should be appreciated by those skilled in the art that other types of storage media which are readable by a computer, whether presently existing or developed in the future, could also be used in the example operating environment, and further, that any such storage media can contain computer-executable instructions for performing the methods described herein.

(372) A number of program modules can be stored in the drives and RAM **4012**, including an operating system **4030**, one or more application programs **4032**, other program modules **4034** and program data **4036**. All or portions of the operating system, applications, modules, or data can also be cached in the RAM **4012**. The systems and methods described herein can be implemented utilizing various commercially available operating systems or combinations of operating systems.

(373) Computer **4002** can optionally comprise emulation technologies. For example, a hypervisor (not shown) or other intermediary can emulate a hardware environment for operating system **4030**, and the emulated hardware can optionally be different from the hardware illustrated in FIG. **40**. In such an embodiment, operating system **4030** can comprise one virtual machine (VM) of multiple VMs hosted at computer **4002**. Furthermore, operating system **4030** can provide runtime environments, such as the Java runtime environment or the .NET framework, for applications **4032**. Runtime environments are consistent execution environments that allow applications **4032** to run on any operating system that includes the runtime environment. Similarly, operating system **4030** can support containers, and applications **4032** can be in the form of containers, which are lightweight, standalone, executable packages of software that include, e.g., code, runtime, system tools, system libraries and settings for an application.

(374) Further, computer **4002** can be enable with a security module, such as a trusted processing module (TPM). For instance with a TPM, boot components hash next in time boot components, and wait for a match of results to secured values, before loading a next boot component. This process can take place at any layer in the code execution stack of computer **4002**, e.g., applied at the application execution level or at the operating system (OS) kernel level, thereby enabling security at any level of code execution.

(375) A user can enter commands and information into the computer **4002** through one or more wired/wireless input devices, e.g., a keyboard **4038**, a touch screen **4040**, and a pointing device, such as a mouse **4042**. Other input devices (not shown) can include a microphone, an infrared (IR) remote control, a radio frequency (RF) remote control, or other remote control, a joystick, a virtual reality controller or virtual reality headset, a game pad, a stylus pen, an image input device, e.g., camera(s), a gesture sensor input device, a vision movement sensor input device, an emotion or facial detection device, a biometric input device, e.g., fingerprint or iris scanner, or the like. These and other input devices are often connected to the processing unit **4004** through an input device interface **4044** that can be coupled to the system bus **4008**, but can be connected by other interfaces, such as a parallel port, an IEEE 1394 serial port, a game port, a USB port, an IR interface, a BLUETOOTH® interface, etc.

(376) A monitor **4046** or other type of display device can be also connected to the system bus **4008** via an interface, such as a video adapter **4048**. In addition to the monitor **4046**, a computer typically includes other peripheral output devices (not shown), such as speakers, printers, etc.

(377) The computer **4002** can operate in a networked environment using logical connections via wired or wireless communications to one or more remote computers, such as a remote computer(s) **4050**. The remote computer(s) **4050** can be a workstation, a server computer, a router, a personal computer, portable computer, microprocessor-based entertainment appliance, a peer device or other common network node, and typically includes many or all of the elements described relative to the computer **4002**, although, for purposes of brevity, only a memory/storage device **4052** is illustrated. The logical connections depicted include wired/wireless connectivity to a local area network (LAN) **4054** or larger networks, e.g., a wide area network (WAN) **4056**. Such LAN and WAN

networking environments are commonplace in offices and companies, and facilitate enterprise-wide computer networks, such as intranets, all of which can connect to a global communications network, e.g., the Internet.

(378) When used in a LAN networking environment, the computer **4002** can be connected to the local network **4054** through a wired or wireless communication network interface or adapter **4058**. The adapter **4058** can facilitate wired or wireless communication to the LAN **4054**, which can also include a wireless access point (AP) disposed thereon for communicating with the adapter **4058** in a wireless mode.

(379) When used in a WAN networking environment, the computer **4002** can include a modem **4060** or can be connected to a communications server on the WAN **4056** via other means for establishing communications over the WAN **4056**, such as by way of the Internet. The modem **4060**, which can be internal or external and a wired or wireless device, can be connected to the system bus **4008** via the input device interface **4044**. In a networked environment, program modules depicted relative to the computer **4002** or portions thereof, can be stored in the remote memory/storage device **4052**. It will be appreciated that the network connections shown are example and other means of establishing a communications link between the computers can be used.

(380) When used in either a LAN or WAN networking environment, the computer **4002** can access cloud storage systems or other network-based storage systems in addition to, or in place of, external storage devices **4016** as described above, such as but not limited to a network virtual machine providing one or more aspects of storage or processing of information. Generally, a connection between the computer **4002** and a cloud storage system can be established over a LAN **4054** or WAN **4056** e.g., by the adapter **4058** or modem **4060**, respectively. Upon connecting the computer **4002** to an associated cloud storage system, the external storage interface **4026** can, with the aid of the adapter **4058** or modem **4060**, manage storage provided by the cloud storage system as it would other types of external storage. For instance, the external storage interface **4026** can be configured to provide access to cloud storage sources as if those sources were physically connected to the computer **4002**.

(381) The computer **4002** can be operable to communicate with any wireless devices or entities operatively disposed in wireless communication, e.g., a printer, scanner, desktop or portable computer, portable data assistant, communications satellite, any piece of equipment or location associated with a wirelessly detectable tag (e.g., a kiosk, news stand, store shelf, etc.), and telephone. This can include Wireless Fidelity (Wi-Fi) and BLUETOOTH® wireless technologies. Thus, the communication can be a predefined structure as with a conventional network or simply an ad hoc communication between at least two devices.

(382) FIG. **41** is a schematic block diagram of a sample computing environment **4100** with which the disclosed subject matter can interact. The sample computing environment **4100** includes one or more client(s) **4110**. The client(s) **4110** can be hardware or software (e.g., threads, processes, computing devices). The sample computing environment **4100** also includes one or more server(s) **4130**. The server(s) **4130** can also be hardware or software (e.g., threads, processes, computing devices). The servers **4130** can house threads to perform transformations by employing one or more embodiments as described herein, for example. One possible communication between a client **4110** and a server **4130** can be in the form of a data packet adapted to be transmitted between two or more computer processes. The sample computing environment **4100** includes a communication framework **4150** that can be employed to facilitate communications between the client(s) **4110** and the server(s) **4130**. The client(s) **4110** are operably connected to one or more client data store(s) **4120** that can be employed to store information local to the client(s) **4110**. Similarly, the server(s) **4130** are operably connected to one or more server data store(s) **4140** that can be employed to store information local to the servers **4130**.

(383) The present invention may be a system, a method, an apparatus or a computer program

product at any possible technical detail level of integration. The computer program product can include a computer readable storage medium (or media) having computer readable program instructions thereon for causing a processor to carry out aspects of the present invention. The computer readable storage medium can be a tangible device that can retain and store instructions for use by an instruction execution device. The computer readable storage medium can be, for example, but is not limited to, an electronic storage device, a magnetic storage device, an optical storage device, an electromagnetic storage device, a semiconductor storage device, or any suitable combination of the foregoing. A non-exhaustive list of more specific examples of the computer readable storage medium can also include the following: a portable computer diskette, a hard disk, a random access memory (RAM), a read-only memory (ROM), an erasable programmable read-only memory (EPROM or Flash memory), a static random access memory (SRAM), a portable compact disc read-only memory (CD-ROM), a digital versatile disk (DVD), a memory stick, a floppy disk, a mechanically encoded device such as punch-cards or raised structures in a groove having instructions recorded thereon, and any suitable combination of the foregoing. A computer readable storage medium, as used herein, is not to be construed as being transitory signals per se, such as radio waves or other freely propagating electromagnetic waves, electromagnetic waves propagating through a waveguide or other transmission media (e.g., light pulses passing through a fiber-optic cable), or electrical signals transmitted through a wire.

(384) Computer readable program instructions described herein can be downloaded to respective computing/processing devices from a computer readable storage medium or to an external computer or external storage device via a network, for example, the Internet, a local area network, a wide area network or a wireless network. The network can comprise copper transmission cables, optical transmission fibers, wireless transmission, routers, firewalls, switches, gateway computers or edge servers. A network adapter card or network interface in each computing/processing device receives computer readable program instructions from the network and forwards the computer readable program instructions for storage in a computer readable storage medium within the respective computing/processing device. Computer readable program instructions for carrying out operations of the present invention can be assembler instructions, instruction-set-architecture (ISA) instructions, machine instructions, machine dependent instructions, microcode, firmware instructions, state-setting data, configuration data for integrated circuitry, or either source code or object code written in any combination of one or more programming languages, including an object oriented programming language such as Smalltalk, C++, or the like, and procedural programming languages, such as the “C” programming language or similar programming languages. The computer readable program instructions can execute entirely on the user's computer, partly on the user's computer, as a stand-alone software package, partly on the user's computer and partly on a remote computer or entirely on the remote computer or server. In the latter scenario, the remote computer can be connected to the user's computer through any type of network, including a local area network (LAN) or a wide area network (WAN), or the connection can be made to an external computer (for example, through the Internet using an Internet Service Provider). In some embodiments, electronic circuitry including, for example, programmable logic circuitry, field-programmable gate arrays (FPGA), or programmable logic arrays (PLA) can execute the computer readable program instructions by utilizing state information of the computer readable program instructions to personalize the electronic circuitry, in order to perform aspects of the present invention.

(385) Aspects of the present invention are described herein with reference to flowchart illustrations or block diagrams of methods, apparatus (systems), and computer program products according to embodiments of the invention. It will be understood that each block of the flowchart illustrations or block diagrams, and combinations of blocks in the flowchart illustrations or block diagrams, can be implemented by computer readable program instructions. These computer readable program instructions can be provided to a processor of a general purpose computer, special purpose

computer, or other programmable data processing apparatus to produce a machine, such that the instructions, which execute via the processor of the computer or other programmable data processing apparatus, create means for implementing the functions/acts specified in the flowchart or block diagram block or blocks. These computer readable program instructions can also be stored in a computer readable storage medium that can direct a computer, a programmable data processing apparatus, or other devices to function in a particular manner, such that the computer readable storage medium having instructions stored therein comprises an article of manufacture including instructions which implement aspects of the function/act specified in the flowchart or block diagram block or blocks. The computer readable program instructions can also be loaded onto a computer, other programmable data processing apparatus, or other device to cause a series of operational acts to be performed on the computer, other programmable apparatus or other device to produce a computer implemented process, such that the instructions which execute on the computer, other programmable apparatus, or other device implement the functions/acts specified in the flowchart or block diagram block or blocks.

(386) The flowcharts and block diagrams in the Figures illustrate the architecture, functionality, and operation of possible implementations of systems, methods, and computer program products according to various embodiments of the present invention. In this regard, each block in the flowchart or block diagrams can represent a module, segment, or portion of instructions, which comprises one or more executable instructions for implementing the specified logical function(s). In some alternative implementations, the functions noted in the blocks can occur out of the order noted in the Figures. For example, two blocks shown in succession can, in fact, be executed substantially concurrently, or the blocks can sometimes be executed in the reverse order, depending upon the functionality involved. It will also be noted that each block of the block diagrams or flowchart illustration, and combinations of blocks in the block diagrams or flowchart illustration, can be implemented by special purpose hardware-based systems that perform the specified functions or acts or carry out combinations of special purpose hardware and computer instructions.

(387) While the subject matter has been described above in the general context of computer-executable instructions of a computer program product that runs on a computer or computers, those skilled in the art will recognize that this disclosure also can or can be implemented in combination with other program modules. Generally, program modules include routines, programs, components, data structures, etc. that perform particular tasks or implement particular abstract data types.

Moreover, those skilled in the art will appreciate that the inventive computer-implemented methods can be practiced with other computer system configurations, including single-processor or multiprocessor computer systems, mini-computing devices, mainframe computers, as well as computers, hand-held computing devices (e.g., PDA, phone), microprocessor-based or programmable consumer or industrial electronics, and the like. The illustrated aspects can also be practiced in distributed computing environments in which tasks are performed by remote processing devices that are linked through a communications network. However, some, if not all aspects of this disclosure can be practiced on stand-alone computers. In a distributed computing environment, program modules can be located in both local and remote memory storage devices.

(388) As used in this application, the terms “component,” “system,” “platform,” “interface,” and the like, can refer to or can include a computer-related entity or an entity related to an operational machine with one or more specific functionalities. The entities disclosed herein can be either hardware, a combination of hardware and software, software, or software in execution. For example, a component can be, but is not limited to being, a process running on a processor, a processor, an object, an executable, a thread of execution, a program, or a computer. By way of illustration, both an application running on a server and the server can be a component. One or more components can reside within a process or thread of execution and a component can be localized on one computer or distributed between two or more computers. In another example, respective components can execute from various computer readable media having various data

structures stored thereon. The components can communicate via local or remote processes such as in accordance with a signal having one or more data packets (e.g., data from one component interacting with another component in a local system, distributed system, or across a network such as the Internet with other systems via the signal). As another example, a component can be an apparatus with specific functionality provided by mechanical parts operated by electric or electronic circuitry, which is operated by a software or firmware application executed by a processor. In such a case, the processor can be internal or external to the apparatus and can execute at least a part of the software or firmware application. As yet another example, a component can be an apparatus that provides specific functionality through electronic components without mechanical parts, wherein the electronic components can include a processor or other means to execute software or firmware that confers at least in part the functionality of the electronic components. In an aspect, a component can emulate an electronic component via a virtual machine, e.g., within a cloud computing system.

(389) In addition, the term “or” is intended to mean an inclusive “or” rather than an exclusive “or.” That is, unless specified otherwise, or clear from context, “X employs A or B” is intended to mean any of the natural inclusive permutations. That is, if X employs A; X employs B; or X employs both A and B, then “X employs A or B” is satisfied under any of the foregoing instances. As used herein, the term “and/or” is intended to have the same meaning as “or.” Moreover, articles “a” and “an” as used in the subject specification and annexed drawings should generally be construed to mean “one or more” unless specified otherwise or clear from context to be directed to a singular form. As used herein, the terms “example” or “exemplary” are utilized to mean serving as an example, instance, or illustration. For the avoidance of doubt, the subject matter disclosed herein is not limited by such examples. In addition, any aspect or design described herein as an “example” or “exemplary” is not necessarily to be construed as preferred or advantageous over other aspects or designs, nor is it meant to preclude equivalent exemplary structures and techniques known to those of ordinary skill in the art.

(390) As it is employed in the subject specification, the term “processor” can refer to substantially any computing processing unit or device comprising, but not limited to, single-core processors; single-processors with software multithread execution capability; multi-core processors; multi-core processors with software multithread execution capability; multi-core processors with hardware multithread technology; parallel platforms; and parallel platforms with distributed shared memory. Additionally, a processor can refer to an integrated circuit, an application specific integrated circuit (ASIC), a digital signal processor (DSP), a field programmable gate array (FPGA), a programmable logic controller (PLC), a complex programmable logic device (CPLD), a discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. Further, processors can exploit nano-scale architectures such as, but not limited to, molecular and quantum-dot based transistors, switches and gates, in order to optimize space usage or enhance performance of user equipment. A processor can also be implemented as a combination of computing processing units. In this disclosure, terms such as “store,” “storage,” “data store,” “data storage,” “database,” and substantially any other information storage component relevant to operation and functionality of a component are utilized to refer to “memory components,” entities embodied in a “memory,” or components comprising a memory. It is to be appreciated that memory or memory components described herein can be either volatile memory or nonvolatile memory, or can include both volatile and nonvolatile memory. By way of illustration, and not limitation, nonvolatile memory can include read only memory (ROM), programmable ROM (PROM), electrically programmable ROM (EPROM), electrically erasable ROM (EEPROM), flash memory, or nonvolatile random access memory (RAM) (e.g., ferroelectric RAM (FeRAM)). Volatile memory can include RAM, which can act as external cache memory, for example. By way of illustration and not limitation, RAM is available in many forms such as synchronous RAM (SRAM), dynamic RAM (DRAM), synchronous DRAM (SDRAM), double

data rate SDRAM (DDR SDRAM), enhanced SDRAM (ESDRAM), Synchlink DRAM (SLDRAM), direct Rambus RAM (DRRAM), direct Rambus dynamic RAM (DRDRAM), and Rambus dynamic RAM (RDRAM). Additionally, the disclosed memory components of systems or computer-implemented methods herein are intended to include, without being limited to including, these and any other suitable types of memory.

(391) What has been described above include mere examples of systems and computer-implemented methods. It is, of course, not possible to describe every conceivable combination of components or computer-implemented methods for purposes of describing this disclosure, but many further combinations and permutations of this disclosure are possible. Furthermore, to the extent that the terms “includes,” “has,” “possesses,” and the like are used in the detailed description, claims, appendices and drawings such terms are intended to be inclusive in a manner similar to the term “comprising” as “comprising” is interpreted when employed as a transitional word in a claim.

(392) The descriptions of the various embodiments have been presented for purposes of illustration, but are not intended to be exhaustive or limited to the embodiments disclosed. Many modifications and variations will be apparent without departing from the scope and spirit of the described embodiments. The terminology used herein was chosen to best explain the principles of the embodiments, the practical application or technical improvement over technologies found in the marketplace, or to enable others of ordinary skill in the art to understand the embodiments disclosed herein.

(393) Various non-limiting aspects of various embodiments described herein are presented in the following clauses.

(394) Clause 1: A system onboard a first vehicle, the system comprising: a processor that executes computer-executable components stored in a non-transitory computer-readable memory, the computer-executable components comprising: a sensor component that captures, via one or more first cameras or one or more first microphones of the first vehicle, vicinity data associated with a first vicinity of the first vehicle; an inference component that determines, via execution of a deep learning neural network on the vicinity data, whether a vehicular collision not involving the first vehicle has occurred in the first vicinity of the first vehicle; and an evidence component that, in response to a determination that the vehicular collision has occurred, records, via the one or more first cameras or the one or more first microphones, first post-collision evidence associated with the first vicinity of the first vehicle.

(395) Clause 2: The system of any preceding clause, wherein the recording the first post-collision evidence comprises preserving the vicinity data.

(396) Clause 3: The system of any preceding clause, wherein the evidence component, in response to a determination that the vehicular collision has not occurred, refrains from recording the first post-collision evidence.

(397) Clause 4: The system of any preceding clause, wherein the refraining from recording the first post-collision evidence comprises discarding the vicinity data.

(398) Clause 5: The system of any preceding clause, wherein the computer-executable components further comprise: a broadcast component that broadcasts, to an emergency service computing device, a deanonymized electronic alert based on the vehicular collision.

(399) Clause 6: The system of any preceding clause, wherein the deanonymized electronic alert comprises the first post-collision evidence.

(400) Clause 7: The system of any preceding clause, wherein the computer-executable components further comprise: a broadcast component that broadcasts, to a second vehicle in the first vicinity of the first vehicle, an anonymized electronic alert based on the vehicular collision.

(401) Clause 8: The system of any preceding clause, wherein the anonymized electronic alert requests that the second vehicle record, via one or more second cameras or one or more second microphones of the second vehicle, second post-collision evidence associated with a second

vicinity of the second vehicle.

(402) In various cases, any suitable combination or combinations of clauses 1-8 can be implemented.

(403) Clause 9: A computer-implemented method, comprising: capturing, by a device operatively coupled to a processor, onboard a first vehicle, and via one or more first cameras or one or more first microphones of the first vehicle, vicinity data associated with a first vicinity of the first vehicle; determining, by the device and via execution of a deep learning neural network on the vicinity data, whether a vehicular collision not involving the first vehicle has occurred in the first vicinity of the first vehicle; and recording, by the device, in response to a determination that the vehicular collision has occurred, and via the one or more first cameras or the one or more first microphones, first post-collision evidence associated with the first vicinity of the first vehicle.

(404) Clause 10: The computer-implemented method of any preceding clause, wherein the recording the first post-collision evidence comprises preserving, by the device, the vicinity data.

(405) Clause 11: The computer-implemented method of any preceding clause, further comprising: refraining, by the device and in response to a determination that the vehicular collision has not occurred, from recording the first post-collision evidence.

(406) Clause 12: The computer-implemented method of any preceding clause, wherein the refraining from recording the first post-collision evidence comprises discarding, by the device, the vicinity data.

(407) Clause 13: The computer-implemented method of any preceding clause, further comprising: broadcasting, by the device and to an emergency service computing device, a deanonymized electronic alert based on the vehicular collision.

(408) Clause 14: The computer-implemented method of any preceding clause, wherein the deanonymized electronic alert comprises the first post-collision evidence.

(409) Clause 15: The computer-implemented method of any preceding clause, further comprising: broadcasting, by the device and to a second vehicle in the first vicinity of the first vehicle, an anonymized electronic alert based on the vehicular collision.

(410) Clause 16: The computer-implemented method of any preceding clause, wherein the anonymized electronic alert requests that the second vehicle record, via one or more second cameras or one or more second microphones of the second vehicle, second post-collision evidence associated with a second vicinity of the second vehicle.

(411) In various cases, any suitable combination or combinations of clauses 9-16 can be implemented.

(412) Clause 17: A computer program product for facilitating artificially intelligent provision of post-vehicular-collision evidence, the computer program product comprising a non-transitory computer-readable memory having program instructions embodied therewith, the program instructions executable by a processor onboard a first vehicle to cause the processor to: capture, via one or more first cameras or one or more first microphones of the first vehicle, vicinity data associated with a first vicinity of the first vehicle; determine, via execution of a deep learning neural network on the vicinity data, whether a vehicular collision not involving the first vehicle has occurred in the first vicinity of the first vehicle; and record, in response to a determination that the vehicular collision has occurred and via the one or more first cameras or the one or more first microphones, first post-collision evidence associated with the first vicinity of the first vehicle.

(413) Clause 18: The computer program product of any preceding clause, wherein the recording the first post-collision evidence comprises preserving, by the processor, the vicinity data.

(414) Clause 19: The computer program product of any preceding clause, wherein the program instructions are further executable to cause the processor to: refrain, in response to a determination that the vehicular collision has not occurred, from recording the first post-collision evidence.

(415) Clause 20: The computer program product of any preceding clause, wherein the refraining from recording the first post-collision evidence comprises discarding, by the processor, the vicinity

data.

(416) In various cases, any suitable combination or combinations of clauses 17-20 can be implemented.

(417) Clause 21: A system onboard a vehicle, the system comprising: a processor that executes computer-executable components stored in a non-transitory computer-readable memory, the computer-executable components comprising: a sensor component that captures, via one or more cameras or one or more microphones of the vehicle, vicinity data associated with a vicinity of the vehicle; an inference component that generates, via execution of a deep learning neural network on the vicinity data, a classification label indicating whether a vehicular collision not involving the vehicle has occurred in the vicinity of the vehicle; an evidence component that records, in response to the classification label indicating that the vehicular collision has occurred and via the one or more cameras or the one or more microphones, post-collision evidence associated with the vicinity of the vehicle; and a broadcast component that broadcasts, in response to the classification label indicating that the vehicular collision has occurred, the classification label and the post-collision evidence to an emergency service computing device.

(418) Clause 22: The system of any preceding clause, wherein the deep learning neural network receives the vicinity data as input and produces the classification label as output, and wherein the classification label binomially indicates a presence or an absence of the vehicular collision.

(419) Clause 23: The system of any preceding clause, wherein the deep learning neural network receives the vicinity data as input and produces the classification label as output, and wherein the classification label indicates how many vehicles are involved in the vehicular collision.

(420) Clause 24: The system of any preceding clause, wherein the deep learning neural network receives the vicinity data as input and produces the classification label as output, and wherein the classification label indicates an impact type of the vehicular collision, wherein the impact type of the vehicular collision is one from the group consisting of a rear-end collision, a head-on collision, a side-impact collision, and a side-swipe collision.

(421) Clause 25: The system of any preceding clause, wherein the deep learning neural network receives the vicinity data as input and produces the classification label as output, and wherein the classification label indicates whether the vehicular collision involves a roll-over.

(422) Clause 26: The system of any preceding clause, wherein the deep learning neural network receives the vicinity data as input and produces the classification label as output, and wherein the classification label indicates whether the vehicular collision involves flames or smoke.

(423) Clause 27: The system of any preceding clause, wherein the deep learning neural network receives the vicinity data as input and produces the classification label as output, and wherein the classification label indicates a severity of the vehicular collision.

(424) In various cases, any suitable combination or combinations of clauses 21-27 can be implemented.

(425) Clause 28: A computer-implemented method, comprising: capturing, by a device operatively coupled to a processor, onboard a vehicle, and via one or more cameras or one or more microphones of the vehicle, vicinity data associated with a vicinity of the vehicle; generating, by the device and via execution of a deep learning neural network on the vicinity data, a classification label indicating whether a vehicular collision not involving the vehicle has occurred in the vicinity of the vehicle; recording, by the device, in response to the classification label indicating that the vehicular collision has occurred, and via the one or more cameras or the one or more microphones, post-collision evidence associated with the vicinity of the vehicle; and broadcasting, by the device and in response to the classification label indicating that the vehicular collision has occurred, the classification label and the post-collision evidence to an emergency service computing device.

(426) Clause 29: The computer-implemented method of any preceding clause, wherein the deep learning neural network receives the vicinity data as input and produces the classification label as output, and wherein the classification label binomially indicates a presence or an absence of the

vehicular collision.

(427) Clause 30: The computer-implemented method of any preceding clause, wherein the deep learning neural network receives the vicinity data as input and produces the classification label as output, and wherein the classification label indicates how many vehicles are involved in the vehicular collision.

(428) Clause 31: The computer-implemented method of any preceding clause, wherein the deep learning neural network receives the vicinity data as input and produces the classification label as output, and wherein the classification label indicates an impact type of the vehicular collision, wherein the impact type of the vehicular collision is one from the group consisting of a rear-end collision, a head-on collision, a side-impact collision, and a side-swipe collision.

(429) Clause 32: The computer-implemented method of any preceding clause, wherein the deep learning neural network receives the vicinity data as input and produces the classification label as output, and wherein the classification label indicates whether the vehicular collision involves a roll-over.

(430) Clause 33: The computer-implemented method of any preceding clause, wherein the deep learning neural network receives the vicinity data as input and produces the classification label as output, and wherein the classification label indicates whether the vehicular collision involves flames or smoke.

(431) Clause 34: The computer-implemented method of any preceding clause, wherein the deep learning neural network receives the vicinity data as input and produces the classification label as output, and wherein the classification label indicates a severity of the vehicular collision.

(432) In various cases, any suitable combination or combinations of clauses 28-34 can be implemented.

(433) Clause 35: A computer program product for facilitating artificially intelligent provision of post-vehicular-collision evidence, the computer program product comprising a non-transitory computer-readable memory having program instructions embodied therewith, the program instructions executable by a processor onboard a vehicle to cause the processor to: capture, via one or more cameras or one or more microphones of the vehicle, vicinity data associated with a vicinity of the vehicle; generate, via execution of a deep learning neural network on the vicinity data, a classification label indicating whether a vehicular collision not involving the vehicle has occurred in the vicinity of the vehicle; record, in response to the classification label indicating that the vehicular collision has occurred and via the one or more cameras or the one or more microphones, post-collision evidence associated with the vicinity of the vehicle; and broadcast, in response to the classification label indicating that the vehicular collision has occurred, the classification label and the post-collision evidence to an emergency service computing device.

(434) Clause 36: The computer program product of any preceding clause, wherein the deep learning neural network receives the vicinity data as input and produces the classification label as output, and wherein the classification label binomially indicates a presence or an absence of the vehicular collision.

(435) Clause 37: The computer program product of any preceding clause, wherein the deep learning neural network receives the vicinity data as input and produces the classification label as output, and wherein the classification label indicates how many vehicles are involved in the vehicular collision.

(436) Clause 38: The computer program product of any preceding clause, wherein the deep learning neural network receives the vicinity data as input and produces the classification label as output, and wherein the classification label indicates an impact type of the vehicular collision, wherein the impact type of the vehicular collision is one from the group consisting of a rear-end collision, a head-on collision, a side-impact collision, and a side-swipe collision.

(437) Clause 39: The computer program product of any preceding clause, wherein the deep learning neural network receives the vicinity data as input and produces the classification label as

output, and wherein the classification label indicates whether the vehicular collision involves a roll-over.

(438) Clause 40: The computer program product of any preceding clause, wherein the deep learning neural network receives the vicinity data as input and produces the classification label as output, and wherein the classification label indicates whether the vehicular collision involves flames or smoke.

(439) In various cases, any suitable combination or combinations of clauses 35-40 can be implemented.

(440) Clause 41: A system onboard a vehicle, the system comprising: a processor that executes computer-executable components stored in a non-transitory computer-readable memory, the computer-executable components comprising: a sensor component that captures, via one or more cameras or one or more microphones of the vehicle, vicinity data associated with a vicinity of the vehicle; an inference component that determines, via execution of a deep learning neural network on the vicinity data, whether a vehicular collision not involving the vehicle has occurred in the vicinity of the vehicle; and a broadcast component that broadcasts, in response to a determination that the vehicular collision has occurred, via the one or more cameras or the one or more microphones, and to an emergency service computing device, a post-collision live stream associated with the vicinity of the vehicle.

(441) Clause 42: The system of any preceding clause, wherein the broadcast component refrains, in response to a determination that the vehicular collision has not occurred, from broadcasting the post-collision live stream.

(442) Clause 43: The system of any preceding clause, wherein the computer-executable components further comprise: a battery component that monitors a remaining battery life of the vehicle during the post-collision live stream.

(443) Clause 44: The system of any preceding clause, wherein, in response to a determination that the remaining battery life of the vehicle is below a threshold, the broadcast component transmits to the emergency service computing device an electronic warning, wherein the electronic warning indicates that the post-collision live stream is nearing termination.

(444) Clause 45: The system of any preceding clause, wherein, in response to a determination that the remaining battery life of the vehicle is below a threshold, the battery component shuts off an electric load of the vehicle, wherein the electric load is unrelated to the post-collision live stream.

(445) Clause 46: The system of any preceding clause, wherein the electric load is one from the group consisting of a seat heater of the vehicle, a seat cooler of the vehicle, an air conditioner of the vehicle, a radio of the vehicle, and a light of the vehicle.

(446) Clause 47: The system of any preceding clause, wherein, during the post-collision live stream, the broadcast component transmits to the emergency service computing device an electronic request for remote-control input associated with the vehicle.

(447) Clause 48: The system of any preceding clause, wherein the remote-control input is one from the group consisting of a camera angle input, a camera zoom input, a speaker volume input, a speaker content input, a lighting input, a steering input, a throttle input, a braking input, and a direction of travel input.

(448) In various cases, any suitable combination or combinations of clauses 41-48 can be implemented.

(449) Clause 49: A computer-implemented method, comprising: capturing, by a device operatively coupled to a processor, onboard a vehicle, and via one or more cameras or one or more microphones of the vehicle, vicinity data associated with a vicinity of the vehicle; determining, by the device and via execution of a deep learning neural network on the vicinity data, whether a vehicular collision not involving the vehicle has occurred in the vicinity of the vehicle; and broadcasting, by the device, in response to a determination that the vehicular collision has occurred, via the one or more cameras or the one or more microphones, and to an emergency

service computing device, a post-collision live stream associated with the vicinity of the vehicle.

(450) Clause 50: The computer-implemented method of any preceding clause, further comprising: refraining, by the device and in response to a determination that the vehicular collision has not occurred, from broadcasting the post-collision live stream.

(451) Clause 51: The computer-implemented method of any preceding clause, further comprising: monitoring, by the device, a remaining battery life of the vehicle during the post-collision live stream.

(452) Clause 52: The computer-implemented method of any preceding clause, further comprising: transmitting, by the device, in response to a determination that the remaining battery life of the vehicle is below a threshold, an electronic warning to the emergency service computing device, wherein the electronic warning indicates that the post-collision live stream is nearing termination.

(453) Clause 53: The computer-implemented method of any preceding clause, further comprising: shutting off, by the device and in response to a determination that the remaining battery life of the vehicle is below a threshold, an electric load of the vehicle, wherein the electric load is unrelated to the post-collision live stream.

(454) Clause 54: The computer-implemented method of any preceding clause, wherein the electric load is one from the group consisting of a seat heater of the vehicle, a seat cooler of the vehicle, an air conditioner of the vehicle, a radio of the vehicle, and a light of the vehicle.

(455) Clause 55: The computer-implemented method of any preceding clause, further comprising: transmitting, by the device, during the post-collision live stream, and to the emergency service computing device, an electronic request for remote-control input associated with the vehicle.

(456) Clause 56: The computer-implemented method of any preceding clause, wherein the remote-control input is one from the group consisting of a camera angle input, a camera zoom input, a speaker volume input, a speaker content input, a lighting input, a steering input, a throttle input, a braking input, and a direction of travel input.

(457) In various cases, any suitable combination or combinations of clauses 49-56 can be implemented.

(458) Clause 57: A computer program product for facilitating artificially intelligent provision of post-vehicular-collision evidence, the computer program product comprising a non-transitory computer-readable memory having program instructions embodied therewith, the program instructions executable by a processor onboard a vehicle to cause the processor to: capture, via one or more cameras or one or more microphones of the vehicle, vicinity data associated with a vicinity of the vehicle; determine, via execution of a deep learning neural network on the vicinity data, whether a vehicular collision not involving the vehicle has occurred in the vicinity of the vehicle; and broadcast, in response to a determination that the vehicular collision has occurred, via the one or more cameras or the one or more microphones, and to an emergency service computing device, a post-collision live stream associated with the vicinity of the vehicle.

(459) Clause 58: The computer program product of any preceding clause, wherein the program instructions are further executable to cause the processor to: refrain, in response to a determination that the vehicular collision has not occurred, from broadcasting the post-collision live stream.

(460) Clause 59: The computer program product of any preceding clause, wherein the program instructions are further executable to cause the processor to: monitor a remaining battery life of the vehicle during the post-collision live stream.

(461) Clause 60: The computer program product of any preceding clause, wherein the program instructions are further executable to cause the processor to: transmit, in response to a determination that the remaining battery life of the vehicle is below a threshold, an electronic warning to the emergency service computing device, wherein the electronic warning indicates that the post-collision live stream is nearing termination.

(462) In various cases, any suitable combination or combinations of clauses 57-60 can be implemented.

(463) Clause 61: A system onboard a vehicle, the system comprising: a processor that executes computer-executable components stored in a non-transitory computer-readable memory, the computer-executable components comprising: a sensor component that captures, via one or more cameras or one or more microphones of the vehicle, vicinity data associated with a vicinity of the vehicle; an inference component that determines, via execution of a deep learning neural network on the vicinity data, whether a vehicular collision not involving the vehicle has occurred in the vicinity of the vehicle; and a broadcast component that broadcasts, in response to a determination that the vehicular collision has occurred and via the one or more cameras or the one or more microphones, one or more electronic notifications.

(464) Clause 62: The system of any preceding clause, wherein the deep learning neural network receives as input the vicinity data and produces as output a classification label indicating the vehicular collision, and wherein the one or more electronic notifications comprise the vicinity data and the classification label.

(465) Clause 63: The system of any preceding clause, wherein the one or more electronic notifications comprise a geolocation stamp recorded by a global positioning sensor or a wi-fi positioning sensor of the vehicle, and wherein the geolocation stamp indicates where the vehicular collision occurred.

(466) Clause 64: The system of any preceding clause, wherein the one or more electronic notifications comprise a timestamp recorded by a clock of the vehicle, and wherein the timestamp indicates when the vehicular collision occurred.

(467) Clause 65: The system of any preceding clause, wherein the one or more electronic notifications comprise an identifier associated with the vehicle, wherein the identifier comprises at least one from the group consisting of a vehicle identification number of the vehicle, a license plate of the vehicle, a first name of an owner of the vehicle, a first address of the owner of the vehicle, a second name of a current driver of the vehicle, and a second address of the current driver of the vehicle.

(468) Clause 66: The system of any preceding clause, wherein the one or more electronic notifications comprise post-collision recorded evidence or a post-collision live stream captured by the one or more cameras or the one or more microphones of the vehicle.

(469) Clause 67: The system of any preceding clause, wherein the one or more electronic notifications indicate what remote-control parameters of the vehicle are available.

(470) Clause 68: The system of any preceding clause, wherein the remote-control parameters include a camera angle parameter, a camera zoom parameter, a speaker content parameter, a speaker volume parameter, a lighting parameter, a steering parameter, a throttle parameter, a braking parameter, or a direction of travel parameter.

(471) In various cases, any suitable combination or combinations of clauses 61-68 can be implemented.

(472) Clause 69: A computer-implemented method, comprising: capturing, by a device operatively coupled to a processor, onboard a vehicle, and via one or more cameras or one or more microphones of the vehicle, vicinity data associated with a vicinity of the vehicle; determining, by the device and via execution of a deep learning neural network on the vicinity data, whether a vehicular collision not involving the vehicle has occurred in the vicinity of the vehicle; and broadcasting, by the device, in response to a determination that the vehicular collision has occurred, and via the one or more cameras or the one or more microphones, one or more electronic notifications.

(473) Clause 70: The computer-implemented method of any preceding clause, wherein the deep learning neural network receives as input the vicinity data and produces as output a classification label indicating the vehicular collision, and wherein the one or more electronic notifications comprise the vicinity data and the classification label.

(474) Clause 71: The computer-implemented method of any preceding clause, wherein the one or

more electronic notifications comprise a geolocation stamp recorded by a global positioning sensor or a wi-fi positioning sensor of the vehicle, and wherein the geolocation stamp indicates where the vehicular collision occurred.

(475) Clause 72: The computer-implemented method of any preceding clause, wherein the one or more electronic notifications comprise a timestamp recorded by a clock of the vehicle, and wherein the timestamp indicates when the vehicular collision occurred.

(476) Clause 73: The computer-implemented method of any preceding clause, wherein the one or more electronic notifications comprise an identifier associated with the vehicle, wherein the identifier comprises at least one from the group consisting of a vehicle identification number of the vehicle, a license plate of the vehicle, a first name of an owner of the vehicle, a first address of the owner of the vehicle, a second name of a current driver of the vehicle, and a second address of the current driver of the vehicle.

(477) Clause 74: The computer-implemented method of any preceding clause, wherein the one or more electronic notifications comprise post-collision recorded evidence or a post-collision live stream captured by the one or more cameras or the one or more microphones of the vehicle.

(478) Clause 75: The computer-implemented method of any preceding clause, wherein the one or more electronic notifications indicate what remote-control parameters of the vehicle are available.

(479) Clause 76: The computer-implemented method of any preceding clause, wherein the remote-control parameters include a camera angle parameter, a camera zoom parameter, a speaker content parameter, a speaker volume parameter, a lighting parameter, a steering parameter, a throttle parameter, a braking parameter, or a direction of travel parameter.

(480) In various cases, any suitable combination or combinations of clauses 69-76 can be implemented.

(481) Clause 77: A computer program product for facilitating artificially intelligent provision of post-vehicular-collision evidence, the computer program product comprising a non-transitory computer-readable memory having program instructions embodied therewith, the program instructions executable by a processor onboard a vehicle to cause the processor to: capture, via one or more cameras or one or more microphones of the vehicle, vicinity data associated with a vicinity of the vehicle; determine, via execution of a deep learning neural network on the vicinity data, whether a vehicular collision not involving the vehicle has occurred in the vicinity of the vehicle; and broadcast, in response to a determination that the vehicular collision has occurred and via the one or more cameras or the one or more microphones, one or more electronic notifications.

(482) Clause 78: The computer program product of any preceding clause, wherein the deep learning neural network receives as input the vicinity data and produces as output a classification label indicating the vehicular collision, and wherein the one or more electronic notifications comprise the vicinity data and the classification label.

(483) Clause 79: The computer program product of any preceding clause, wherein the one or more electronic notifications comprise a geolocation stamp recorded by a global positioning sensor or a wi-fi positioning sensor of the vehicle, and wherein the geolocation stamp indicates where the vehicular collision occurred.

(484) Clause 80: The computer program product of any preceding clause, wherein the one or more electronic notifications comprise a timestamp recorded by a clock of the vehicle, and wherein the timestamp indicates when the vehicular collision occurred.

(485) In various cases, any suitable combination or combinations of clauses 77-80 can be implemented.

(486) Clause 81: A system, comprising: a processor that executes computer-executable components stored in a non-transitory computer-readable memory, the computer-executable components comprising: a receiver component that receives one or more electronic notifications broadcasted by a vehicle; a determination component that determines, via parsing, whether the one or more electronic notifications indicate that a vehicular collision not involving the vehicle has occurred in

a vicinity of the vehicle; and an execution component that initiates, in response to a determination that the one or more electronic notifications indicate that the vehicular collision has occurred, one or more electronic actions based on the vehicular collision.

(487) Clause 82: The system of any preceding clause, wherein the one or more electronic notifications include vicinity data captured by one or more cameras or one or more microphones of the vehicle, wherein the one or more electronic notifications indicate that the vehicle detected the vehicular collision by executing a first deep learning neural network on the vicinity data, and wherein the execution component verifies such detection by executing a second deep learning neural network on the vicinity data.

(488) Clause 83: The system of any preceding clause, wherein the execution component transmits, in response to the second deep learning neural network detecting the vehicular collision based on the vicinity data, an electronic reply to the vehicle, wherein the electronic reply indicates that the vehicular collision has been successfully verified.

(489) Clause 84: The system of any preceding clause, wherein the execution component transmits, in response to the second deep learning neural network failing to detect the vehicular collision based on the vicinity data, an electronic reply to the vehicle, wherein the electronic reply indicates that the vehicular collision has not been successfully verified.

(490) Clause 85: The system of any preceding clause, wherein the one or more electronic notifications indicate where the vehicular collision occurred, wherein the system is onboard an emergency service vehicle, and wherein the execution component generates an electronic navigation route leading from a current location of the emergency service vehicle to the vehicular collision.

(491) Clause 86: The system of any preceding clause, wherein the one or more electronic notifications indicate that the vehicle has a remotely-controllable camera, and wherein the execution component transmits, to the vehicle, an electronic instruction to adjust an angle or a zoom level of the remotely-controllable camera.

(492) Clause 87: The system of any preceding clause, wherein the one or more electronic notifications indicate that the vehicle has a remotely-controllable speaker, and wherein the execution component transmits, to the vehicle, an electronic instruction to reproduce defined sound data via the remotely-controllable speaker or to adjust a volume level of the remotely-controllable speaker.

(493) Clause 88: The system of any preceding clause, wherein the one or more electronic notifications indicate that the vehicle has remotely-controllable steering, remotely-controllable throttle, remotely-controllable braking, or remotely-controllable lighting, and wherein the execution component transmits, to the vehicle, an electronic instruction to adjust the remotely-controllable steering, the remotely-controllable throttle, the remotely-controllable braking, or the remotely-controllable lighting.

(494) In various cases, any suitable combination or combinations of clauses 81-88 can be implemented.

(495) Clause 89: A computer-implemented method, comprising: receiving, by a device operatively coupled to a processor, one or more electronic notifications broadcasted by a vehicle; determining, by the device and via parsing, whether the one or more electronic notifications indicate that a vehicular collision not involving the vehicle has occurred in a vicinity of the vehicle; and initiating, by the device and in response to a determination that the one or more electronic notifications indicate that the vehicular collision has occurred, one or more electronic actions based on the vehicular collision.

(496) Clause 90: The computer-implemented method of any preceding clause, wherein the one or more electronic notifications include vicinity data captured by one or more cameras or one or more microphones of the vehicle, wherein the one or more electronic notifications indicate that the vehicle detected the vehicular collision by executing a first deep learning neural network on the

vicinity data, and further comprising: verifying, by the device, such detection by executing a second deep learning neural network on the vicinity data.

(497) Clause 91: The computer-implemented method of any preceding clause, further comprising: transmitting, by the device and in response to the second deep learning neural network detecting the vehicular collision based on the vicinity data, an electronic reply to the vehicle, wherein the electronic reply indicates that the vehicular collision has been successfully verified.

(498) Clause 92: The computer-implemented method of any preceding clause, further comprising: transmitting, by the device and in response to the second deep learning neural network failing to detect the vehicular collision based on the vicinity data, an electronic reply to the vehicle, wherein the electronic reply indicates that the vehicular collision has not been successfully verified.

(499) Clause 93: The computer-implemented method of any preceding clause, wherein the one or more electronic notifications indicate where the vehicular collision occurred, wherein the device is onboard an emergency service vehicle, and further comprising: generating, by the device, an electronic navigation route leading from a current location of the emergency service vehicle to the vehicular collision.

(500) Clause 94: The computer-implemented method of any preceding clause, wherein the one or more electronic notifications indicate that the vehicle has a remotely-controllable camera, and further comprising: transmitting, by the device and to the vehicle, an electronic instruction to adjust an angle or a zoom level of the remotely-controllable camera.

(501) Clause 95: The computer-implemented method of any preceding clause, wherein the one or more electronic notifications indicate that the vehicle has a remotely-controllable speaker, and further comprising: transmitting, by the device and to the vehicle, an electronic instruction to reproduce defined sound data via the remotely-controllable speaker or to adjust a volume level of the remotely-controllable speaker.

(502) Clause 96: The computer-implemented method of any preceding clause, wherein the one or more electronic notifications indicate that the vehicle has remotely-controllable steering, remotely-controllable throttle, remotely-controllable braking, or remotely-controllable lighting, and further comprising: transmitting, by the device and to the vehicle, an electronic instruction to adjust the remotely-controllable steering, the remotely-controllable throttle, the remotely-controllable braking, or the remotely-controllable lighting.

(503) In various cases, any suitable combination or combinations of clauses 89-96 can be implemented.

(504) Clause 97: A computer program product for facilitating artificially intelligent provision of post-vehicular-collision evidence, the computer program product comprising a non-transitory computer-readable memory having program instructions embodied therewith, the program instructions executable by a processor to cause the processor to: receive one or more electronic notifications broadcasted by a vehicle; determine, via parsing, whether the one or more electronic notifications indicate that a vehicular collision not involving the vehicle has occurred in a vicinity of the vehicle; and initiate, in response to a determination that the one or more electronic notifications indicate that the vehicular collision has occurred, one or more electronic actions based on the vehicular collision.

(505) Clause 98: The computer program product of any preceding clause, wherein the one or more electronic notifications include vicinity data captured by one or more cameras or one or more microphones of the vehicle, wherein the one or more electronic notifications indicate that the vehicle detected the vehicular collision by executing a first deep learning neural network on the vicinity data, and wherein the program instructions are further executable to cause the processor to: verify such detection by executing a second deep learning neural network on the vicinity data.

(506) Clause 99: The computer program product of any preceding clause, wherein the program instructions are further executable to cause the processor to: transmit, in response to the second deep learning neural network detecting the vehicular collision based on the vicinity data, an

electronic reply to the vehicle, wherein the electronic reply indicates that the vehicular collision has been successfully verified.

(507) Clause 100: The computer program product of any preceding clause, wherein the program instructions are further executable to cause the processor to: transmit, in response to the second deep learning neural network failing to detect the vehicular collision based on the vicinity data, an electronic reply to the vehicle, wherein the electronic reply indicates that the vehicular collision has not been successfully verified.

(508) In various cases, any suitable combination or combinations of clauses 97-100 can be implemented.

(509) In various cases, any suitable combination or combinations of clauses 1-100 can be implemented.

Claims

1. A system of a first passenger vehicle, the system comprising: a memory that stores computer-executable components; and a processor that executes at least one of the computer-executable components that: captures, via sensors of the first passenger vehicle, vicinity data associated with a vicinity comprising a defined physical area external to and adjacent to the first passenger vehicle and interior data of an interior of the first passenger vehicle, wherein the sensors comprises at least one interior sensor directed to an interior of the first passenger vehicle and at least one external sensor directed to the vicinity, wherein the at least one interior sensor comprises at least one of an interior image sensor or an interior sound sensor, wherein the at least one external sensor comprises at least one of an external image sensor or an external sound sensor, wherein the vicinity data comprises at least one of first external image data or first external audio data, and wherein the interior data comprises at least one of first interior image data or first interior audio data; a determines, via execution of a deep learning neural network on the vicinity data, whether a vehicular collision has occurred in the vicinity of the first passenger vehicle, wherein the vehicular collision involves at least one second passenger vehicle, and does not involve the first passenger vehicle; and in response to a determination that the vehicular collision has occurred, broadcasts, via at least one of the sensors, to an emergency service computing device, a post-collision live stream comprising additional vicinity associated with the vicinity of the first passenger vehicle.

2. The system of claim 1, wherein the post-collision live stream further comprises additional interior data of the interior of the first passenger vehicle.

3. The system of claim 1, wherein the at least one of the computer-executable components further: monitors a remaining battery life of the first passenger vehicle during the post-collision live stream.

4. The system of claim 3, wherein the at least one of the computer-executable components further: in response to determining that the remaining battery life of the first passenger vehicle is below a defined threshold, transmits to the emergency service computing device an electronic warning, wherein the electronic warning indicates that the post-collision live stream is nearing termination.

5. The system of claim 3, wherein the at least one of the computer-executable components further: in response to determining that the remaining battery life of the first passenger vehicle is below a defined threshold, shuts off at least one electric load of the first passenger vehicle, wherein the at least one electric load is unrelated to the post-collision live stream.

6. The system of claim 5, wherein the at least one electric load comprises at least one of a seat heater of the first passenger vehicle, a seat cooler of the first passenger vehicle, an air conditioner of the first passenger vehicle, a radio of the first passenger vehicle, or a light of the first passenger vehicle.

7. The system of claim 1, wherein the at least one of the computer-executable components further: during the post-collision live stream, transmits to the emergency service computing device an electronic request to provide remote-control input associated with the first passenger vehicle.

8. The system of claim 7, wherein the remote-control input comprises at least one of a camera angle input, a camera zoom input, a speaker volume input, a speaker content input, a lighting input, a steering input, a throttle input, a braking input, or a direction of travel input.
9. A computer-implemented method, comprising: capturing, by a system of a first passenger vehicle, via sensors of the first passenger vehicle, vicinity data associated with a vicinity comprising a defined physical area external to and adjacent to the first passenger vehicle and interior data of an interior of the first passenger vehicle, wherein the sensors comprises at least one interior sensor directed to an interior of the first passenger vehicle and at least one external sensor directed to the vicinity, wherein the at least one interior sensor comprises at least one of an interior image sensor or an interior sound sensor, wherein the at least one external sensor comprises at least one of an external image sensor or an external sound sensor, wherein the vicinity data comprises at least one of first external image data or first external audio data, and wherein the interior data comprises at least one of first interior image data or first interior audio data; determining, by the system, via execution of a deep learning neural network on the vicinity data, whether a vehicular collision has occurred in the vicinity of the first passenger vehicle, wherein the vehicular collision involves at least one second passenger vehicle, and does not involve the first passenger vehicle; and in response to determining that the vehicular collision has occurred, broadcasting, by the system, via at least one of the sensors, to an emergency service computing device, a post-collision live stream comprising additional vicinity associated with the vicinity of the first passenger vehicle.
10. The computer-implemented method of claim 9, wherein the post-collision live stream further comprises additional interior data of the interior of the first passenger vehicle.
11. The computer-implemented method of claim 9, further comprising: monitoring, by the system, a remaining battery life of the first passenger vehicle during the post-collision live stream.
12. The computer-implemented method of claim 11, further comprising: in response to determining that the remaining battery life of the first passenger vehicle is below a defined threshold, transmitting, by the system, an electronic warning to the emergency service computing device, wherein the electronic warning indicates that the post-collision live stream is nearing termination.
13. The computer-implemented method of claim 11, further comprising: in response to determining that the remaining battery life of the first passenger vehicle is below a threshold, shutting off, by the system, an at least one electric load of the first passenger vehicle, wherein the at least one electric load is unrelated to the post-collision live stream.
14. The computer-implemented method of claim 13, wherein the at least one electric load comprises at least one of a seat heater of the first passenger vehicle, a seat cooler of the first passenger vehicle, an air conditioner of the first passenger vehicle, a radio of the first passenger vehicle, or a light of the first passenger vehicle.
15. The computer-implemented method of claim 9, further comprising: during the post-collision live stream, transmitting, by the system, to the emergency service computing device, an electronic request to provide remote-control input associated with the first passenger vehicle.
16. The computer-implemented method of claim 15, wherein the remote-control input comprises at least one of a camera angle input, a camera zoom input, a speaker volume input, a speaker content input, a lighting input, a steering input, a throttle input, a braking input, or a direction of travel input.
17. A computer program product for facilitating artificially intelligent provision of post-vehicular-collision evidence, the computer program product comprising a non-transitory computer-readable memory having program instructions embodied therewith, the program instructions executable by a processor of a first passenger vehicle to cause the processor to: capture, via sensors of the first passenger vehicle, vicinity data associated with a vicinity comprising a defined physical area external to and adjacent to the first passenger vehicle and interior data of an interior of the first passenger vehicle, wherein the sensors comprises at least one interior sensor directed to an interior of the first passenger vehicle and at least one external sensor directed to the vicinity, wherein the at

least one interior sensor comprises at least one of an interior image sensor or an interior sound sensor, wherein the at least one external sensor comprises at least one of an external image sensor or an external sound sensor, wherein the vicinity data comprises at least one of first external image data or first external audio data, and wherein the interior data comprises at least one of first interior image data or first interior audio data; determine, via execution of a deep learning neural network on the vicinity data, whether a vehicular collision has occurred in the vicinity of the first passenger vehicle, wherein the vehicular collision involves at least one second passenger vehicle, and does not involve the first passenger vehicle; and in response to a determination that the vehicular collision has occurred, broadcast, via at least one of the sensors, to an emergency service computing device, a post-collision live stream comprising additional vicinity associated with the vicinity of the first passenger vehicle.

18. The computer program product of claim 17, wherein the post-collision live stream further comprises additional interior data of the interior of the first passenger vehicle.

19. The computer program product of claim 17, wherein the program instructions are further executable to cause the processor to: monitor a remaining battery life of the first passenger vehicle during the post-collision live stream.

20. The computer program product of claim 19, wherein the program instructions are further executable to cause the processor to: in response to determining that the remaining battery life of the first passenger vehicle is below a defined threshold, transmit an electronic warning to the emergency service computing device, wherein the electronic warning indicates that the post-collision live stream is nearing termination.
