

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250264653

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

WANG; Evan et al.

PRISMS FOR INDEPENDENT CONTROL OVER VIRTUAL IMAGE AND WORLD LEAKAGE ANGLES

Abstract

In some embodiments, an optical device includes a waveguide having a first surface and a second surface opposing the first surface. The waveguide further includes an input coupler and an output coupler disposed over the first surface or the second surface. The optical device further includes a first prism disposed over at least the output coupler and over the first surface. The first prism is operable to increase a first projection angle of an image relative to a horizontal plane of the waveguide. The optical device further includes a second prism disposed under at least the output coupler and under the second surface. The second prism is operable to increase the second projection angle of light leakage relative to the horizontal plane of the waveguide.

Inventors: WANG; Evan (Palo Alto, CA), MESSER; Kevin (Mountain View, CA), BHARGAVA; Samarth (Saratoga, CA), SELL; David Alexander (Santa Clara, CA)

Applicant: Applied Materials, Inc. (Santa Clara, CA)

Family ID: 1000008491269

Appl. No.: 19/054288

Filed: February 14, 2025

Related U.S. Application Data

us-provisional-application US 63565287 20240314

us-provisional-application US 63554618 20240216

Publication Classification

Int. Cl.: F21V8/00 (20060101)

U.S. Cl.:

CPC **G02B6/0036** (20130101); **G02B6/0016** (20130101); **G02B6/003** (20130101);
G02B6/0065 (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application claims benefit of U.S. Provisional Patent Application No. 63/554,618 filed Feb. 16, 2024 and U.S. Provisional Patent Application No. 63/565,287, filed Mar. 14, 2024, which are herein incorporated by reference in their entirety.

BACKGROUND

Field

[0002] Embodiments of the present disclosure relate to optical devices having a waveguide with eye-side and world-side prisms.

Description of the Related Art

[0003] Virtual reality is generally considered to be a computer generated simulated environment in which a user has an apparent physical presence. A virtual reality experience can be generated in 3D and viewed with a head-mounted display (HMD), such as glasses or other wearable display devices that have near-eye display panels as lenses to display a virtual reality environment that replaces an actual environment.

[0004] Augmented reality, however, enables an experience in which a user can still see through the display lenses of the glasses or other HMD device to view the surrounding environment, yet also see images of virtual objects that are generated for display and appear as part of the environment. Augmented reality can include any type of input, such as audio and haptic inputs, as well as virtual images, graphics, and video that enhances or augments the environment that the user experiences. As an emerging technology, there are many challenges and design constraints with augmented reality.

[0005] Accordingly, what is needed in the art are optical devices having a waveguide with eye-side and world-side prisms.

SUMMARY

[0006] In some embodiments, an optical device includes a waveguide having a first surface and a second surface opposing the first surface. The waveguide further includes an input coupler and an output coupler disposed over the first surface or the second surface. The optical device further includes a first prism disposed over at least the output coupler and over the first surface. The first prism is operable to increase a first projection angle of an image relative to a horizontal plane of the waveguide. The optical device further includes a second prism disposed under at least the output coupler and under the second surface. The second prism is operable to increase the second projection angle of light leakage relative to the horizontal plane of the waveguide.

[0007] In some embodiments, an optical device includes a waveguide having a first surface and a second surface opposing the first surface. The waveguide further includes an input coupler and an output coupler disposed over the first surface or the second surface. The optical device further includes an eye-side prism disposed over at least the output coupler and over the first surface. The eye-side prism is disposed on a first material disposed over the first surface. The first material has a refractive index of 1.1 or less. The optical device further includes a world-side prism disposed over at least the output coupler and over the second surface. The world-side prism is disposed on a second material disposed over the second surface. The second material has a refractive index of 1.1 or less.

[0008] In some embodiments, an optical device includes a waveguide having a first surface and a second surface opposing the first surface. The waveguide further includes an input coupler and an output coupler disposed over the first surface or the second surface. The optical device further includes a push lens disposed over the first surface. The push lens has a first prism disposed on or in the push lens. The first prism has a first thickness that decreases from a first end of the first prism to a second end of the first prism. The optical device further includes a pull lens disposed under the second surface. The pull lens has a second prism disposed on or in the pull lens. The second prism includes a second thickness that increases from a first end of the second prism to a second end of the second prism. The first end of the first prism is opposite the first end of the second prism. The second end of the first prism is opposite the second end of the second prism.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] So that the manner in which the above recited features of the present disclosure can be understood in detail, a more particular description of the disclosure, briefly summarized above, may be had by reference to embodiments, some of which are illustrated in the appendix. It is to be noted, however, that the appendix illustrates only typical embodiments of this disclosure and are therefore not to be considered limiting of its scope, for the disclosure may admit to other equally effective embodiments.

[0010] FIG. 1 is a perspective, frontal view of a waveguide, according to at least one embodiment.

[0011] FIG. 2A and 2B are schematic views of a portion of a waveguide, according to at least one embodiment.

[0012] FIG. 3 is a schematic cross-sectional view of an optical device, according to at least one embodiment.

[0013] FIG. 4 is a schematic cross-sectional view of an optical device, according to at least one embodiment.

[0014] FIG. 5 is a schematic cross-sectional view of an optical device, according to at least one embodiment.

[0015] FIG. 6 is a schematic cross-sectional view of an optical device, according to at least one embodiment.

[0016] FIG. 7 is a schematic cross-sectional view of an optical device, according to at least one embodiment.

[0017] FIG. 8 is a schematic cross-sectional view of an optical device, according to at least one embodiment.

[0018] FIG. 9A and 9B are schematic views of a lens integrated with a prism, according to one embodiment.

DETAILED DESCRIPTION

[0019] Embodiments of the present disclosure generally relate to augmented reality displays. More specifically, optical devices having a waveguide with eye-side and world-side prisms. The optical devices described herein have an eye-side prism and a world-side prism. The eye-side prism increases the angle of the image projected to the eye relative to a horizontal plane of the waveguide such that the FOV is lower relative to the user's eye. The world-side prism increases the angle of the light leakage relative to the horizontal plane of the waveguide such that the world leakage angle is lower relative to the user's eye. As used herein, the term "field of view location" (herein after referred to as "FOV") is a point at which a user perceives the virtual images of an augmented reality display to be located. As used herein, the term "world leakage angle" is the direction of light that is emitted on the world side of the waveguide.

[0020] FIG. 1 is a perspective, frontal view of a waveguide 100. It is to be understood that the

waveguide **100** described herein is an exemplary waveguide and that other waveguides may be used with or modified to accomplish aspects of the present disclosure. The waveguide **100** includes a plurality of structures **102**. The structures **102** may be disposed over, under, or on a surface **103** of a substrate **101**, or disposed in the substrate **101**. The structures **102** are nanostructures have a sub-micron critical dimension, e.g., a width less than 1 micrometer. Regions of the structures **102** correspond to one or more gratings **104**. In one embodiment, which can be combined with other embodiments described herein, the waveguide **100** includes at least an incoupler grating **104a** and an outcoupler grating **104c**. In another embodiment, which can be combined with other embodiments described herein, the waveguide **100** further includes an intermediate grating **104b**. The intermediate grating **104b** corresponds to a pupil expansion grating (“pupil expander”) or a fold grating.

[0021] FIGS. 2A and 2B are schematic views of a portion of a waveguide **100**. The waveguide **100** includes the outcoupler grating **104c** disposed on the eye-side of the waveguide **100**. I.e., the outcoupler grating **104c** is disposed on the side of the waveguide **100** closest to the user's eye **206**. A horizontal plane **208** is shown in both FIGS. 2A and 2B that is parallel to the to the user's eye **206**. As shown in FIG. 2A, the image **210a** projected to the user's eye **206**. The image **210a** has a first projection angle **212a** relative to the projection of the image **210a** and the horizontal plane **208**. The eye-side prism(s) **304**, **502**, and/or **802** (as show in FIGS. 3-8) of the optical device(s) **300**, **400**, **500**, **600**, **700**, and/or **800** described herein increases the first projection angle **212a** of the image projected to the user's eye **206** relative to a horizontal plane **208** of the waveguide **100** such that the FOV is lower relative to the user's eye **206**. The low FOV can provide user comfort during normal operation and use of the device. As shown in FIG. 2B, the leaked light **210b** is projected from the world-side of the waveguide **100**. The leaked light **210b** has a second projection angle **212b** relative to the horizontal plane **208**. The world-side prism(s) **308**, **504**, and **804** (as show in FIGS. 3-8) of the optical device(s) **300**, **400**, **500**, **600**, **700**, and/or **800** described herein increases the second projection angle **212b** of the light leakage relative to the horizontal plane **208** of the waveguide **100** such that the world leakage angle is lower relative to the user's eye **206**. A low world leakage angle reduces visibility from the world side and is desirable for to user privacy during use and operation of the optical device.

[0022] FIG. 3 is a schematic cross-sectional view of an optical device **300**. In at least one embodiment, which can be combined with other embodiments described herein, the optical device **300** includes a waveguide **100** with an outcoupler grating **104c** and an incoupler grating **104a** disposed on the eye-side surface of the waveguide **100**. A first prism **304** is disposed over the eye-side surface of the waveguide **100**. In one embodiment, the first prism **304** is coupled to the waveguide **100** by a first adhesive layer **306a**. In other embodiments, an air-gap is disposed between the first prism **304** and the waveguide **100**. The first adhesive layer **306a**, and the second adhesive layer **306b** have a refractive index of 1.1 or less. The air-gaps have a refractive index of 1.0. In at least one embodiment, the first prism **304** is disposed substantially over the eye-side surface of the waveguide **100**. Additionally, a second prism **308** is disposed over the world-side surface of the waveguide **100**. In one embodiment, the second prism **308** is coupled to the waveguide **100** with the second adhesive layer **306b**. In at least one embodiment, the second prism **308** is disposed substantially over the world-side surface of the waveguide **100**. Without being bound by theory, the first prism **304** on the eye-side surface of the waveguide **100** lowers the FOV location by raising the incident light **312a** to be projected to the eye, while the second prism **308** on the world-side surface of the waveguide **100** lowers the world-side leakage angle of the incident light **312b**. In addition, the first prism **304** and the second prism **308** are designed such that their effects cancel each other out for light coming in from outside the optical device **300**, causing no see through distortion. In some embodiments, the first prism **304** and the second prism **308** may independently be comprised of an optically transparent having a refractive index (RI) of greater than about 1.0, such as greater than about 1.2, such as greater than about 1.4. In at least one

embodiment, the prisms may individually be selected from the group including glass materials, aluminium oxide based materials, polycarbonate materials, acrylic materials, titanium oxide based materials, or combinations thereof. In some embodiments, which can be combined with other embodiments described herein, the first prism **304** and/or the second prism **308** can include a tapered thickness along the length of the waveguide **100**. In other words, the prisms have a continuously decreasing thickness along the length of at least one of the first prism **304** or the second prism **308**, such that one end of the first prism **304** and/or the second prism **308** has a thickness greater than the opposite end of the first prism **304** and/or the second prism **308**, respectively. In one or more embodiments, which can be combined with other embodiments described herein, the end of the first prism **304** and/or the second prism **308** having a greater thickness may include a thickness of up to about 10 mm, such as about 1 mm to about 10 mm, such as about 2.5 mm to about 10 mm, such as about 5 mm to about 10 mm. In one or more embodiments, which can be combined with other embodiments described herein, the end of the first prism **304** and/or the second prism **308** having a lesser thickness may include a thickness of greater than about 100 μm , such as about 100 μm to about 1,000 μm , such as about 100 μm to about 500 μm , such as about 100 μm to about 250 μm . In at least one embodiment, the first prism **304** and the second prism **308** are oriented such that there exists a balance in the optical effect on the opposite side. In other words, the end of the second prism **308** having a greater thickness is opposite the end of the first prism **304** having a greater thickness.

[0023] In some embodiments, which can be combined with other embodiments, described herein, prism structures of the present disclosure may be coupled to a waveguide **100** such that there exists a “gap” between the surface of the waveguide **100** and the first prism **304** (i.e., the gap **310a** as shown in FIG. **3**) and/or between the surface of the waveguide **202** and the second prism **308** (i.e., the gap **310b** as shown in FIG. **3**). In one or more embodiments, which can be combined with other embodiments described herein, a first adhesive layer **306a** and/or the second adhesive layer **306b** can include a low refractive index material, such as a silica containing material and/or a polymeric material. A silica-containing material can include a silica-containing aerogel material having a nanoscale porosity to provide air gaps in the space between the waveguide and the prism. The silica-containing aerogel material can include a porosity of greater than about 95%, wherein such porosity reduces the refractive index of silica.

[0024] In some embodiments, which can be combined with other embodiments described herein, a silica-containing aerogel material can be formed from a silica-containing aerogel material formation process. The formation process may include one or more of a precursor preparation process, deposition process, or supercritical drying process. The precursor preparation process includes preparing silica sol-gels. The sol (e.g., solution) is prepared by addition of a catalyst to a silica precursor solution in a solvent. Examples of the silica precursor include, but are not limited to, tetraethy lorthosilicate (TEOS), tetramethy lorthosilicate (TMOS), methyltrimethoxysilane (MTMS), methyltriethoxysilane (MTMS), methyltriethoxysilane (MTES), silbond H-5, or polyethoxydisiloxane (PEDS). Examples of the catalyst include, but are not limited to, hydrofluoric acid (HF), hydrogen chloride (HCl), nitric acid (HNO₃), sulfuric acid (H₂SO₄), oxalic acid (C₂H₂O₄), acetic acid (CH₃COOH), trifluoroacetic acid (TFA), or ammonium hydroxide (NH₄OH). Examples of the solvent precursor include, but are not limited to, methanol, ethanol, and isopropanol. The gel is prepared by ageing the solution, which strengthens the solution into a sol-gel by crosslinking. The ageing of the sol-gel keeps the shrinkage during drying to the supercritical drying process.

[0025] FIG. **4** is a schematic cross-sectional view of an optical device **400** according to one or more embodiments. In at least one embodiment, which can be combined with other embodiments described herein, the optical device **400** includes a waveguide **100** with an outcoupler grating **104c** and an incoupler grating **104a** disposed on the eye-side surface of the waveguide **100**. A first prism **304** is disposed over the eye-side surface of the waveguide **100**. In one embodiment, the first

prism **304** is coupled to the waveguide **100** with the first adhesive layer **306a**. In at least one embodiment, the first prism **304** is at least partially disposed over the eye-side surface of the waveguide **100**. In at least one embodiment, the first prism **304** is disposed substantially over the outcoupler grating **104c** and partially over the eye-side surface of the waveguide **100**. In at least one embodiment, the first adhesive layer **306a** is at least partially disposed over the eye-side surface of the waveguide **100**. In at least one embodiment, the first adhesive layer **306a** is disposed substantially over the outcoupler grating **104c** and partially over the eye-side surface of the waveguide **100**. A second prism **308** is disposed over the world-side surface of the waveguide **100**. In one embodiment, the second prism **308** is coupled to the waveguide with the second adhesive layer **306b**. In at least one embodiment, the second prism **308** is at least partially disposed over the world-side surface of the waveguide **100**. In at least one embodiment, the second prism **308** is disposed directly opposite the first prism **304**. In at least one embodiment, the second adhesive layer **306b** is at least partially disposed over the world-side surface of the waveguide **100**. In at least one embodiment, the second adhesive layer **306b** is disposed directly opposite the first adhesive layer **306a**.

[0026] FIG. 5 is a schematic cross-sectional view of an optical device **500** according to one or more embodiments. In at least one embodiment, which can be combined with other embodiments described herein, the optical device **500** includes a waveguide **100** with an outcoupler grating **104c** and an incoupler grating **104a** disposed on the eye-side surface of the waveguide **100**. A first micro-prism array **502** is disposed over the eye-side surface of the waveguide **100**. In one embodiment, the first micro-prism array **502** is coupled to the waveguide **100** with the first adhesive layer **306a**. In at least one embodiment, the first micro-prism array **502** is at least partially disposed over the eye-side surface of the waveguide **100**. In at least one embodiment, the first micro-prism array **502** is disposed substantially over the outcoupler grating **104c** and partially over the eye-side surface of the waveguide **100**. A second micro-prism array **504** is disposed over the world-side surface of the waveguide **100**. In one embodiment, the second micro-prism array **504** is coupled to the waveguide **100** with the second adhesive layer **306b**. In at least one embodiment, the second micro-prism array **504** is at least partially disposed over the world-side surface of the waveguide **100**. In at least one embodiment, the second micro-prism array **504** is disposed directly opposite the first micro-prism array **502**.

[0027] In at least one embodiment, which can be combined with other embodiments described herein, a micro-prism **506** of the first micro-prism array **502** and/or the second micro-prism array **504** can include a tapered thickness wherein the end with the greater thickness may include a thickness of up to about 10 mm, such as about 0.1 μm to about 10 mm, such as about 10 μm to about 10 mm, such as about 100 μm to about 10 mm, such as about 500 μm to about 10 mm, such as about 1 mm to about 10 mm such as about 5 mm to about 10 mm. In at least one alternative embodiment, which can be combined with other embodiments described herein, a micro-prism **506** of the first micro-prism array **502** and/or the second micro-prism array **504** can include a tapered thickness wherein the end with the greater thickness may include a thickness of up to about 0.1 μm to about 5 mm, alternatively about 10 μm to about 1 mm, alternatively about 100 μm to about 500 μm . In at least one embodiment, which can be combined with other embodiments described herein, a micro-prism **506** of the first micro-prism array **502** and/or the second micro-prism array **504** may also include an end with a lesser thickness of less than about 10 mm, such as about 0.1 μm to about 10 mm, such as about 0.1 μm to about 5 mm, such as about 0.1 μm to about 1 mm, such as about 0.1 μm to about 500 μm , such as about 0.1 μm to about 100 μm , such as about 0.1 μm to about 10. In at least one alternative embodiment, which can be combined with other embodiments a micro-prism **506** of the first micro-prism array **502** and/or the second micro-prism array **504** may also include an end with a lesser thickness of about 0.1 μm to about 1 mm, alternatively about 1 μm to about 500 μm , alternatively about 10 μm to about 100 μm . In at least one embodiment, the first micro-prism array **502** and the second micro-prism array **504** are oriented such that there exists a

balance in the optical effect on the opposite side.

[0028] In at least one embodiment, which can be combined with other embodiments described herein, the first micro-prism array **502** and/or the second micro-prism array **504** can independently include any suitable number of micro-prisms **506**, such as about 1 prism to about 10,000 prisms, such as about 1,000 prisms to about 10,000 prisms, such as about 5,000 prisms to about 10,000 prisms, alternatively about 1 prism to about 5,000 prisms, alternatively about 1 prism to about 1,000 prisms, alternatively about 1 prism to about 500 prisms. Such micro-prisms **506** may be configured such that there is a prism density (e.g., the number of prisms per unit area) of about 0.1 prisms/cm.² to about 1,000 prisms/cm.², such as about 1 prism/cm.² to about 1,000 prisms/cm.², such as about 10 prisms/cm.² to about 1,000 prisms/cm.², such as about 100 prisms/cm.², to about 1,000 prisms/cm.², such as about 500 prisms/cm.² to about 1,000 prisms/cm.², alternatively about 0.1 prisms/cm.² to about 500 prisms/cm.², alternatively about 0.1 prisms/cm.² to about 100 prisms/cm.², alternatively about 0.1 prisms/cm.² to about 10 prisms/cm.².

[0029] FIG. **6** is a schematic cross-sectional view of an optical device **600** according to one or more embodiments. In at least one embodiment, which can be combined with other embodiments described herein, the optical device **600** includes a waveguide **100** with an outcoupler grating **104c** and an incoupler grating **104a** disposed on the eye-side surface of the waveguide **100**. The first prism **304** is disposed over the eye-side surface of the waveguide **100**. In one embodiment, the first prism **304** is coupled to the waveguide **100** with the first adhesive layer **306a**. In at least one embodiment, the first prism **304** includes a first array of structures **602** coupled to the underside surface of the first prism **304**, such that the first array of structures **602** is in contact with the first adhesive layer **306a**. The second prism **308** is disposed over the world-side surface of the waveguide **100**. In one embodiment, the second prism **308** is coupled to the waveguide **100** with the second adhesive layer **306b**. In at least one embodiment, the second prism **308** includes a second array of structures **604** coupled to the underside surface of the second prism **308**, such that the second array of structures **604** is in contact with the second adhesive layer **306b**.

[0030] In some embodiments, which can be combined with other embodiments described herein, an array of structures (e.g., the first array of structures **602** and/or the second array of structures **604**) can include an array of grating structures. The array of grating structures (e.g., the first array of structures **602** and/or the second array of structures **604**) can include any suitable grating structure known to one of ordinary skill in the art, such as blazed grating structures, grating structures having an angle relative to the surface of the prism, grating structures perpendicular to the surface of the prism, and the like. In at least one embodiment, which can be combined with other embodiments described herein, the array of grating structures (e.g., the first array of structures **602** and/or the second array of structures **604**) can include grating structures which are perpendicularly oriented relative to the surface of the prism. In which case, a grating structure **606** of an array of grating structures (e.g., the first array of structures **602** and/or the second array of structures **604**) can include a grating depth (e.g., length extending from the prism) of about 1 nm to about 10 μm , such as about 500 nm to about 10 μm , such as about 1 μm to about 10 μm , such as about 5 μm to about 10 μm , alternatively about 1 nm to about 5 μm , alternatively about 1 nm to about 1 μm , alternatively about 1 nm to about 500 nm. Furthermore, an individual grating structure can include a grating pitch of about 100 nm to about 100 μm , such as about 500 nm to about 100 μm , such as about 1 μm to about 100 μm , such as about 10 μm to about 100 μm , such as about 50 μm to about 100 μm , alternatively about 100 nm to about 50 μm , alternatively about 100 nm to about 10 μm , alternatively about 100 nm to about 500 nm. Grating structures **606** of an array of grating structures (e.g., the first array of structures **602** and/or the second array of structures **604**) can include the same size parameters or different size parameters as the other grating structures **606** within the array.

[0031] In at least one embodiment, which can be combined with other embodiments described

herein, the array of grating structures (e.g., the first array of structures **602** and/or the second array of structures **604**) can independently include any suitable number of grating structures **606**, such as about 1,000 grating structures to about 1,000,000 grating structures, such as about 50,000 grating structures to about 1,000,000 grating structures, such as about 100,000 grating structures to about 1,000,000 grating structures, such as about 500,000 grating structures to about 1,000,000 grating structures, alternatively about 1,000 grating structures to about 500,000 grating structures, alternatively about 1,000 grating structures to about 100,000 grating structures, alternatively about 1,000 grating structures to about 50,000 grating structures. Such grating structure arrays (e.g., the first array of structures **602** and/or the second array of structures **604**) may be configured such that there is a grating structure density (e.g., the number of grating structures per unit area) on the surface of the prism of about 100 grating structures/cm.² to about 100,000 grating structures/cm.², such as about 500 grating structures/cm.² to about 100,000 grating structures/cm.², such as about 1,000 grating structures/cm.² to about 100,000 grating structures/cm.², such as about 50,000 grating structures/cm.² to about 100,000 grating structures/cm.², alternatively about 100 grating structures/cm.² to about 50,000 grating structures/cm.², alternatively about 100 grating structures/cm.² to about 1,000 grating structures/cm.², alternatively about 100 grating structures/cm.² to about 500 grating structures/cm.².

[0032] In some embodiments, which can be combined with other embodiments described herein, wherein the the first adhesive layer **306a** coupling the first prism **304** to the waveguide **100** substantially contacts at least one of the grating structures **606** of the first array of structures **602** coupled to the underside surface of the first prism **304**. In some embodiments, which can be combined with other embodiments described herein, wherein the first adhesive layer **306a** coupling the first prism **304** to the waveguide **100** substantially contacts a plurality of the grating structures **606** of the first array of structures **602** coupled to the underside surface of the first prism **304**.

[0033] In some embodiments, which can be combined with other embodiments described herein, wherein the second adhesive layer **306b** coupling the second prism **308** to the waveguide **100** substantially contacts at least one of the grating structures **606** of the second array of structures **604** coupled to the underside surface of the second prism **308**. In some embodiments, which can be combined with other embodiments described herein, wherein the second adhesive layer **306b** binding the second prism **308** to the waveguide **100** substantially contacts a plurality of the grating structures **606** of the second array of structures **604** coupled to the underside surface of the second prism **308**.

[0034] FIG. 7 is a schematic cross-sectional view of an optical device **700** according to one or more embodiments. The optical device **700** includes a waveguide **100** with an outcoupler grating **104c** and an incoupler grating **104a** disposed on the eye-side surface of the waveguide **100**. In at least one embodiment, which can be combined with other embodiments described herein, a push/pull lens is configured around the waveguide **100**. The push/pull lens includes a push lens (i.e., an eye-side lens **702**) and a pull lens (i.e., a world-side lens **704**). In at least one embodiment, the push lens is disposed over either the eye-side surface, and coupled to the waveguide **100** with the first adhesive layer **306a**. In at least one embodiment, the pull lens is disposed over the world-side surface of the waveguide **100**, and coupled to the waveguide **100** with the second adhesive layer **306b**. In at least one embodiment, the push/pull lens includes an eye-side lens **702** and a world-side lens **704**, wherein the eye-side lens **702** is disposed over the eye-side surface of the waveguide **100** and the world-side lens **704** is disposed over the world-side surface of the waveguide **100**. The eye-side lens **702** and a world-side lens **704** of the push/pull lens may be coupled to the waveguide **100** with the first adhesive layer **306a** or the second adhesive layer **306b**.

[0035] In some embodiments, which can be combined with other embodiments described herein, the eye-side lens **702** includes the first prism **304** disposed on the outer surface of the eye-side lens **702**. In other words, the first prism **304** is configured/disposed over the eye-side lens **702** such that

the first prism **304** is not coupled to the eye-side surface of the waveguide **100**. In some embodiments, the world-side lens **704** includes the second prism **308** disposed on the outer surface of the world-side lens **704**. In other words, the second prism **308** is configured/disposed over the world-side lens **704** such that the second prism **308** is not coupled to the world-side surface of the waveguide **100**. In one or more embodiments, the first prism **304** disposed on the outer surface of the eye-side lens **702** and/or the second prism **308** disposed on the outer surface of the world-side lens **704** are configured such that at least one of either the first prism **304** and/or the second prism **308** is at least partially disposed over the outcoupler grating **104c** of the waveguide **100**. In one or more embodiments, the first prism **304** disposed on the outer surface of the eye-side lens **702** and/or the second prism **308** disposed on the outer surface of the world-side lens **704** are configured such that at least one of either the first prism **304** and/or the second prism **308** is substantially disposed over the outcoupler grating **104c** of the waveguide **100**.

[0036] In some embodiments, which can be combined with other embodiments described herein, an eye-side lens **702** can include a thickness of about 0.1 mm to about 10 mm, such as about 1 mm to about 10 mm, such as about 5 mm to about 10 mm, alternatively about 0.1 mm to about 5 mm, alternatively about 0.1 mm to about 1 mm. In some embodiments, which can be combined with other embodiments described herein, a world-side lens **704** can include a thickness of about 0.1 mm to about 10 mm, such as about 1 mm to about 10 mm, such as about 5 mm to about 10 mm, alternatively about 0.1 mm to about 5 mm, alternatively about 0.1 mm to about 1 mm.

[0037] FIG. **8** is a schematic cross-sectional view of an optical device **800** according to one or more embodiments. The optical device **800** includes a waveguide **100** with an outcoupler grating **104c** and an incoupler grating **104a** disposed on the eye-side surface of the waveguide **100**. In at least one embodiment, which can be combined with other embodiments described herein, the push/pull includes an eye-side lens **702** and a world-side lens **708**, wherein the eye-side lens **702** is disposed over the eye-side surface of the waveguide **100** and the world-side lens **704** is disposed over the world-side surface of the waveguide **100**. The eye-side lens **702** and a world-side lens **704** of the push/pull lens may be coupled to the waveguide **100** with the first adhesive layer **306a** and/or the second adhesive layer **306b**. In some embodiments, the eye-side lens **702** includes a first tapered prism **802** disposed on the outer surface of the eye-side lens **702**, wherein the first tapered prism **802** is integrated with at least one taper(s). Such taper(s) may be integrated with the first tapered prism **802** to retain smoothness of the eye-side lens **702**. In some embodiments, the world-side lens **704** includes a second tapered prism **804** disposed on the outer surface of the world-side lens **704**, wherein the second tapered prism **804** is integrated with at least one taper(s). Such taper(s) may be integrated with the second tapered prism **804** to retain smoothness of the world-side lens **704**.

[0038] In some embodiments, which can be combined with other embodiments described herein, the first tapered prism **802** and/or the second tapered prism **804** can be integrated with one or more taper(s) such that position in which the first tapered prism **802** and/or the second tapered prism **804** is at its greatest thickness is located between a first end and a second end of thereof. In other words, the first tapered prism **802** and/or the second tapered prism **804** have a continuously decreasing thickness progressing outwards from the position of the greatest thickness. In one or more embodiments, which can be combined with other embodiments described herein, the position of the greatest thickness of the first tapered prism **802** and/or the second tapered prism **804** may include a thickness of up to about 10 mm, such as about 1 mm to about 10 mm, such as about 2.5 mm to about 10 mm, such as about 5 mm to about 10 mm. The first tapered prism **802** and/or the second tapered prism **804** may also include a position having a lowest thickness. In one or more embodiments, which can be combined with other embodiments described herein, the position of the lowest thickness may include a thickness of about 100 μm , such as about 100 μm to about 1,000 μm , such as about 100 μm to about 500 μm , such as about 100 μm to about 250 μm . In at least one embodiment, the first tapered prism **802** and the second tapered prism **804** are oriented such that

there exists a balance in the optical effect on the opposite side. In other words, the position of greatest thickness of the first tapered prism **802** is opposite the position of the lowest thickness of the second tapered prism **804**.

[0039] FIGS. **9A** and **9B** are schematic cross-sectional view of a lens (e.g., a push lens or a pull lens) integrated with a prism. FIG. **9a** shows a cross-sectional view of a lens **902** with a first prism **904a** disposed thereon. FIG. **9b** shows a cross-sectional view of a lens **902** including a second prism **904b**, wherein the second prism **904b** is a cavity imparted into the surface of the lens **902**. In an exemplary embodiment, which can be combined with other embodiments described herein, the first prism **904a** of FIG. **9a** and the second prism **904b** of FIG. **9b** are optically equivalent. In some embodiments, push/pull lenses of the present disclosure can be integrated with any one or more prisms of the present disclosure (e.g., either a prism disposed thereon as an external structure or disposed therein as a cavity in the lens), so long as the prism pair is in optical equivalence.

[0040] The present disclosure provides prism pair and waveguide configurations, which have both a low FOV location and a low world leakage angle. It has been found that employing an eye-side prism increases the angle of the image projected to the eye relative to a horizontal plane of the waveguide such that the FOV is lower relative to the user's eye. Furthermore, implementing a world-side prism increases the angle of the light leakage relative to the horizontal plane of the waveguide such that the world leakage angle is lower relative to the user's eye. Additionally, the disclosure provides push/pull lens configurations integrating prisms and arrays thereof while also maintaining the smoothness commonly associated with lens used augmented reality systems.

[0041] While the foregoing is directed to embodiments of the present disclosure, other and further embodiments of the disclosure may be devised without departing from the basic scope thereof, and the scope thereof is determined by the claims that follow.

Claims

1. An optical device comprising: a waveguide, the waveguide having a first surface and a second surface opposing the first surface, wherein an input coupler and an output coupler are disposed over the first surface or the second surface; and a first prism disposed over at least the output coupler and over the first surface, wherein the first prism is operable to increase a first projection angle of an image relative to a horizontal plane of the waveguide; and a second prism disposed under at least the output coupler and under the second surface, wherein the second prism is operable to increase a second projection angle of light leakage relative to the horizontal plane of the waveguide.
2. The optical device of claim 1, wherein the first prism comprises an optically transparent material having a refractive index of greater than about 1.4.
3. The optical device of claim 1, wherein the first prism comprises glass, aluminum oxide based materials, polycarbonate materials, acrylic materials, titanium dioxide based materials, or combinations thereof.
4. The optical device of claim 1, wherein the first prism comprises a tapered thickness along a length of the waveguide.
5. The optical device of claim 1, wherein the second prism comprises an optically transparent material having a refractive index of greater than about 1.4.
6. The optical device of claim 1, wherein the second prism comprises glass, aluminum oxide based materials, polycarbonate materials, acrylic materials, titanium dioxide based materials, or combinations thereof.
7. The optical device of claim 1, wherein the second prism comprises a tapered thickness along a length of the waveguide.
8. An optical device comprising: a waveguide, the waveguide having a first surface and a second surface opposing the first surface, wherein an input coupler and an output coupler are disposed over

the first surface or the second surface; and an eye-side prism disposed over at least the output coupler and over the first surface, the eye-side prism is disposed on a first material disposed over the first surface, wherein the first material has a refractive index of 1.1 or less; and a world-side prism disposed over at least the output coupler and over the second surface, the world-side prism is disposed on a second material disposed over the second surface, wherein the second material has a refractive index of 1.1 or less.

9. The optical device of claim 8, wherein the eye-side prism is disposed over the first surface and the world-side prism is disposed over the second surface.

10. The optical device of claim 9, wherein the first material and the second material both comprise a silica-containing aerogel material.

11. The optical device of claim 8, wherein the eye-side prism comprises a first micro-prism array and the world-side prism comprises second micro-prism array.

12. The optical device of claim 8, wherein the eye-side prism comprises a first array of structures coupled to an underside surface of the eye-side prism.

13. The optical device of claim 12, wherein the world-side prism comprises a second array of structures coupled to the underside surface of the world-side prism.

14. The optical device of claim 8, wherein the eye-side prism has a first thickness, wherein the first thickness increases from a first end of the output coupler to a center of the output coupler and decreases from the center to a second end of the output coupler.

15. The optical device of claim 14, wherein the world-side prism has a second thickness, wherein the second thickness increases from the first end of the output coupler to the center of the output coupler and decreases from the center to a second end of the output coupler.

16. An optical device comprising: a waveguide, the waveguide having a first surface and a second surface opposing the first surface, wherein an input coupler and an output coupler are disposed over the first surface or the second surface; a push lens disposed over the first surface, the push lens having a first prism disposed on or in the push lens, the first prism has a first thickness that decreases from a first end of the first prism to a second end of the first prism; and a pull lens disposed under the second surface, the pull lens having a second prism disposed on or in the pull lens, wherein: the second prism comprises a second thickness that increases from a first end of the second prism to a second end of the second prism, the first end of the first prism is opposite the first end of the second prism, and the second end of the first prism is opposite the second end of the second prism.

17. The optical device of claim 16, wherein the first prism and the second prism are disposed over the output coupler.

18. The optical device of claim 17, wherein the first prism is disposed in a cavity of the push lens.

19. The optical device of claim 17, wherein the second prism is disposed in a cavity of the pull lens.

20. The optical device of claim 17, wherein the first prism and the second prism are optically equivalent.
