

# US Patent & Trademark Office

## Patent Public Search | Text View

United States Patent Application Publication

20250263009

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Larson; Alec S. et al.

### VEHICLE FRONT RADAR INTEGRATION

#### Abstract

A main lighting assembly for a vehicle may comprise a headlight including a lens and a sensor assembly. The sensor assembly may be positioned adjacent the headlight lens and may include a forward-facing sensor unit positioned behind a sensor cover to sense objects in front of the vehicle. The headlight lens may include a recess and the sensor cover may include a portion that is substantially contiguous with the recess. The headlight lens and the sensor cover may be positioned within an opening of a front fairing of the vehicle and may define a substantially circular envelope.

**Inventors:** Larson; Alec S. (Wyoming, MN), Comana; Benjamin M. (Burgdorf, CH), Anderson; Tyson (Wyoming, MN), O'Halloran; Jeffrey M. (Wyoming, MN), Christoph; Richard J. (Medina, MN), Vorndran; Ronald A. (Wyoming, MN), Kujawa; Kyle R. (Medina, MN), Song; Michael M. (Medina, MN), Bébox; Olivier (Burgdorf, CH)

**Applicant:** Indian Motorcycle International, LLC (Medina, MN)

**Family ID:** 1000008588038

**Assignee:** Indian Motorcycle International, LLC (Medina, MN)

**Appl. No.:** 18/998732

**Filed (or PCT Filed):** March 27, 2024

**PCT No.:** PCT/US2024/021653

#### Related U.S. Application Data

us-provisional-application US 63456025 20230331

#### Publication Classification

**Int. Cl.: B60Q1/00** (20060101); **B60Q1/04** (20060101); **B62J6/026** (20200101); **B62J6/027** (20200101); **G01S13/931** (20200101)

**U.S. Cl.:**

**CPC B60Q1/0023** (20130101); **B60Q1/04** (20130101); **G01S13/931** (20130101); **B62J6/026** (20200201); **B62J6/027** (20200201); **G01S2013/93271** (20200101); **G01S2013/93277** (20200101)

---

## **Background/Summary**

CROSS-REFERENCE TO RELATED APPLICATION [0001] The present application claims the benefit of U.S. Provisional Application No. 63/456,025, entitled “VEHICLE FRONT RADAR INTEGRATION,” filed on Mar. 31, 2023, which is incorporated by reference herein for all purposes in its entirety.

### **TECHNICAL FIELD**

[0002] The present application relates generally to vehicle sensors and more particularly to mounting configurations for a forward facing radar sensor for a motorcycle.

### **BACKGROUND**

[0003] Various vehicles, including motorcycles, include radar sensors for detecting the presence of objects within the sensing cone of the sensor. Such sensors typically require a forward facing mounting location on the vehicle that is unobstructed, which results in reduced aesthetic appeal of the vehicle as the sensor is obviously positioned for functional purposes. Thus, it would be desirable to mount a radar sensor in a compact, concealed manner that does not degrade the performance of the sensor.

### **SUMMARY**

[0004] According to one embodiment, the disclosure provides a main lighting assembly for a vehicle, comprising: a headlight mounted to a frame of the vehicle, the headlight including a lens; a headlight bezel substantially surrounding the headlight and supported within an opening of a front fairing of the vehicle; and a sensor assembly positioned below the headlight lens and between the headlight bezel and the headlight to sense objects in front of the vehicle, the sensor assembly including a forward-facing sensor unit mounted to the vehicle and positioned behind a sensor cover; wherein the headlight lens includes an upper semi-circular edge and a lower recess and the sensor cover includes an upper protrusion that is substantially contiguous with the lower recess; and wherein the headlight lens and the sensor cover define a substantially circular envelope. In one aspect of this embodiment, the lower recess of the headlight lens includes a pair of lower edges extending from the upper semi-circular edge, a pair of lower angled edges extending from the pair of lower edges and a central lower edge. In a variant of this aspect, the upper protrusion of the sensor cover includes a pair of upper angled edges and a substantially flat upper edge extending between the upper angled edges, the upper angled edges being substantially contiguous with the lower angled edges of the headlight lens and the substantially flat upper edge being substantially contiguous with the central lower edge of the headlight lens. In another aspect, the main lighting assembly further comprises a pair of position lights positioned between an outer side wall of the headlight bezel and curved inner wall segments of the headlight bezel. In a further variant, the pair of position lights are positioned outside the substantially circular envelope. In another variant, each of the pair of position lights includes a lower portion that tapers along a curved defined by an outer wall of the headlight bezel and an upper portion that extends from the lower portion at a step between the lower portion and the upper portion. In another aspect, the headlight lens and the

sensor cover are symmetric about a centerline of the vehicle. In yet another aspect, the headlight bezel includes an outer wall that surrounds the headlight, the outer wall including tapering ends adjacent a curved lower edge of the sensor cover. In another aspect, the headlight bezel includes an outer wall that surrounds the headlight, an a pair of curved inner wall segments that are substantially contiguous with the upper semi-circular edge of the headlight lens. In still another aspect, the headlight bezel includes a pair of substantially triangular forward walls extending from the curved inner wall segments, the substantially triangular forward walls being positioned adjacent corresponding lower edges of the headlight lens and corresponding curved vertical edges of the sensor cover. In another aspect, the headlight lens includes a convex outer surface and the sensor cover includes a convex outer surface, the convex outer surface of the headlight lens has a curvature that is substantially continuous with a curvature of the convex outer surface of the sensor cover. In another aspect, the forward-facing sensor unit is a radar unit.

[0005] According to another embodiment of the present disclosure, a main lighting assembly for a vehicle is provided, comprising: a headlight including a lens; and a sensor assembly positioned below the headlight lens and including a forward-facing sensor unit positioned behind a sensor cover to sense objects in front of the vehicle; wherein the headlight lens includes a lower recess and the sensor cover includes an upper protrusion that is substantially contiguous with the lower recess; and wherein the headlight lens and the sensor cover are positioned within an opening of a front fairing of the vehicle and define a substantially circular envelope. In one aspect of this embodiment, the lower recess of the headlight lens includes a pair of lower edges extending from an upper semi-circular edge of the headlight lens, a pair of lower angled edges extending from the pair of lower edges and a central lower edge. In a variant of this aspect, the upper protrusion of the sensor cover includes a pair of upper angled edges and a substantially flat upper edge extending between the upper angled edges, the upper angled edges being substantially contiguous with the lower angled edges of the headlight lens and the substantially flat upper edge being substantially contiguous with the central lower edge of the headlight lens. In another aspect, the headlight lens and the sensor cover are symmetric about a centerline of the vehicle. Another aspect further comprises a headlight bezel including an outer wall that substantially surrounds the headlight, the outer wall including tapering ends adjacent a curved lower edge of the sensor cover. In another aspect, the headlight lens includes a convex outer surface and the sensor cover includes a convex outer surface, the convex outer surface of the headlight lens has a curvature that is substantially continuous with a curvature of the convex outer surface of the sensor cover. In another aspect, the forward-facing sensor unit is a radar unit.

[0006] Another embodiment of the present disclosure provides a main lighting assembly for a vehicle, comprising: a headlight including a lens; and a sensor assembly positioned above the headlight lens and including a forward-facing sensor unit positioned behind a sensor cover to sense objects in front of the vehicle; wherein the headlight lens includes an upper recess and the sensor cover includes a lower protrusion that is substantially contiguous with the upper recess; and wherein the headlight lens and the sensor cover are positioned within an opening of a front fairing of the vehicle and define a substantially circular envelope.

[0007] Still another embodiment of the present disclosure provides a main lighting assembly for a vehicle, comprising: a headlight including a lens; and a sensor assembly positioned adjacent the headlight lens and including a forward-facing sensor unit positioned behind a sensor cover to sense objects in front of the vehicle; wherein the headlight lens includes a recess and the sensor cover includes a portion that is substantially contiguous with the recess; and wherein the headlight lens and the sensor cover are positioned within an opening of a front fairing of the vehicle and define a substantially circular envelope.

---

## Description

## BRIEF DESCRIPTION OF THE DRAWINGS

[0008] The above mentioned and other features of this disclosure, and the manner of attaining them, will become more apparent and the disclosure itself will be better understood by reference to the following description of embodiments of the disclosure taken in conjunction with the accompanying drawings, wherein:

[0009] FIG. **1** is a perspective view of a vehicle that may incorporate the teachings of the present disclosure;

[0010] FIG. **2A** is a front view of a vehicle having a prior art main lighting assembly;

[0011] FIG. **2B** is a front view of a vehicle having one embodiment of a main lighting assembly according to the present disclosure; and

[0012] FIGS. **3** and **4** are front views of a vehicle having a main lighting assembly according to another embodiment of the present disclosure.

[0013] Corresponding reference characters may indicate corresponding parts throughout the several views.

## DETAILED DESCRIPTION OF THE DRAWINGS

[0014] It is to be understood that the phraseology and terminology used herein is for the purpose of description and should not be regarded as limiting. The use of “including,” “comprising,” or “having” and variations thereof herein is meant to encompass the items listed thereafter and equivalents thereof as well as additional items. Unless specified or limited otherwise, the terms “mounted,” “connected,” “supported,” and “coupled” and variations thereof are used broadly and encompass both direct and indirect mountings, connections, supports, and couplings. Further, “connected” and “coupled” are not restricted to physical or mechanical connections or couplings.

[0015] While the structures and components disclosed herein may be embodied in many different forms, several specific embodiments are discussed herein with the understanding that the embodiments described in the present disclosure are to be considered only exemplifications of the principles described herein, and the disclosure is not intended to be limited to the embodiments illustrated. While the present disclosure primarily involves a touring motorcycle, it should be understood, that the disclosure may have application to other types of vehicles such as all-terrain vehicles, motorcycles, watercraft, utility vehicles, scooters, golf carts, and mopeds.

[0016] With reference first to FIG. **1**, an illustrative embodiment of a two-wheeled vehicle **10** is shown. The vehicle **10** as illustrated is a touring style motorcycle although the majority of components may be used for a cruiser style motorcycle.

[0017] The vehicle **10** generally includes a frame **12** supported by ground engaging members, namely a front ground engaging member or wheel **14** and a rear ground engaging member or wheel **16**. The vehicle **10** travels relative to the ground on the front wheel **14** and the rear wheel **16**.

[0018] The rear wheel **16** is coupled to a power train assembly **18**, to propel the vehicle **10** through the rear wheel **16**. It will be appreciated that while the vehicle **10** is illustrated as a two-wheel vehicle, various embodiments of the present teachings are also operable with three, four, six, etc. wheeled vehicles.

[0019] The vehicle **10** also generally includes a steering assembly **20**, front suspension **22**, rear suspension (not shown), and seat **24**. The steering assembly **20** includes handlebars **26** which may be moved by an operator to rotate front the front wheel **14** either to the left or the right. The vehicle further includes safety systems such as a main lighting assembly **28**, front turn signals **30**, and rear turn signals **32**. Ergonomic systems may include a front fairing **34**, a windshield assembly **36** and a saddlebag assembly **38**.

[0020] Referring now to FIG. **2A**, a front view of a main lighting assembly **28** used in a conventional vehicle is shown along with the front fairing **34**. As shown, a typical main lighting assembly **28** may be centered along a centerline A of the vehicle **10** and positioned within the front fairing **34** above the front wheel **14** and below the windshield assembly **36**. The main lighting

assembly **28** includes a headlight **40** mounted to the frame **12** of the vehicle **10** and a headlight bezel **42** or trim piece that provides a stylized transition between the headlight **40** and the headlight bezel **42**. The headlight **40** generally includes a housing (not shown) and a lens **44** enclosing lighting elements that reflect off of the housing and illuminate a forward facing portion of the path of the vehicle **10**.

[0021] Referring now to FIG. 2B, a main lighting assembly **46** according to the teachings of the present disclosure is shown. In the example shown, the main lighting assembly **46** includes a headlight **48** mounted to the frame **12** of the vehicle, a headlight bezel **50** that substantially surrounds the headlight **48** and is supported within an opening **116** of the front fairing **34**, and a radar sensor assembly **52**. As shown, the main lighting assembly **46** (including the headlight **48** and the radar sensor assembly **52**) occupies the same envelope **54** as was occupied by the main lighting assembly **46** depicted in FIG. 2A. The radar sensor assembly **52**, in this example, includes a radar unit (not shown in FIG. 2B) and a radar mount as is described in further detail below.

[0022] The headlight bezel **42** of FIG. 2A includes side walls **56** that have tapering ends **58** which converge at the centerline A of the vehicle **10**. The headlight bezel **50** in FIG. 2B similarly includes side walls **60** with tapering ends **62** that substantially converge at the centerline A. The headlight bezel **50**, however, also includes a radar cover **64** that extends upwardly from the tapering ends **62** and covers the radar unit of the radar sensor assembly **52**. It should be understood that the radar cover **64** is made of material such as a molded polycarbonate with a hard coat applied for scratch resistance that does not interfere with the operation of the radar unit.

[0023] In the depicted example, the radar cover **64** includes a substantially flat lower edge **66**, a pair of angled lower edges **68** extending from the flat lower edge **66**, an upper protrusion **69** including a pair of substantially vertical edges **70** that extend upwardly from the angled lower edges **68**, a pair of upper angled edges **72** that extend from the vertical edges **70** and a substantially flat upper edge **74** extending between the angled upper edges **72**.

[0024] The headlight **48** is shaped to conform to the shape of the radar cover **64** while remaining within the envelope **54** to present, together with the radar cover **64**, an appearance of a typical headlight such as headlight **40** of FIG. 2A. As such, the headlight lens **76** (and housing behind it—not shown) includes an upper semi-arcuate edge, more specifically an upper semi-circular edge **78**, a pair of substantially vertical edges **80** extending from the upper semi-circular edge **78**, and a lower recess **81** including a pair of lower angled edges **82** extending upwardly and inwardly from the vertical edges **80**, and a lower edge **84** extending between the lower angled edges **82**. In this manner, the vertical edges **80** of the lens **76** are substantially contiguous with the vertical edges **70** of the radar cover **64**, the angled lower edges **82** of the lens **76** are substantially contiguous with the angled upper edges **72** of the radar cover **64**, and the lower edge **84** of the lens **76** is substantially contiguous with the upper edge **74** of the radar cover **64**.

[0025] Referring now to FIGS. 3 and 4, another embodiment of a main lighting assembly according to the present disclosure is shown. The main lighting assembly **100** is also centered along the centerline A of the vehicle **10** and positioned within the front fairing **34** above the front wheel **14** and below the windshield assembly **36**. The main lighting assembly **28** includes a headlight **102** mounted to the frame **12** of the vehicle **10** and a headlight bezel **104**. The headlight **40** generally includes a housing (not shown) and a lens **106** enclosing lighting elements that reflect off of the housing and illuminate a forward facing portion of the path of the vehicle **10**. The main lighting assembly **100** also includes a radar sensor assembly **106** and optional position lights **108**. As shown, the main lighting assembly **102** (including the headlight **102** and the radar sensor assembly **106**) again occupies the traditional envelope **54** of a standard headlight, such as that depicted in FIG. 2A. While the traditional headlight envelope **54** described herein is substantially circular in shape, it should be understood that other envelope shapes may be used including, and not limited to, generally rounded or arcuate (for example, oval-shaped or elliptical), semi-circular, triangular, square, rectangular or any other suitable shape. Moreover, it should be understood that while the

main lighting assemblies described herein are positioned on and substantially symmetrical about the centerline A of the vehicle **10**, the assemblies may, in certain embodiments, be positioned off-center and/or asymmetrical in shape.

[0026] As best shown in FIG. **4**, the radar assembly **106** includes a radar unit **110** and a radar mount **112** which is attached to a bracket (not shown) that connects the headlight **102** to the frame **12** of the vehicle **12**.

[0027] The headlight bezel **104** substantially surrounds the headlight **48** and is supported within the opening **116** of the front fairing **34**. The headlight bezel **104** includes outer side walls **114** that extend about the perimeter of an opening **116** formed in the front fairing **34**. The side walls **114** have tapering ends **118** which converge at the centerline A of the vehicle **10**. The headlight bezel **104** also includes a radar cover **120** that extends upwardly from the tapering ends **118** and covers the radar unit **110** of the radar sensor assembly **106**. It should be understood that the radar cover **120** is made of material that does not interfere with the operation of the radar unit **110**.

[0028] In the depicted example, the radar cover **120** includes a curved lower edge **122**, a pair of curved vertical edges **124** extending from the curved lower edge **122**, an upper protrusion **125** including a pair of upper angled edges **126** that extend from the vertical edges **124** and a substantially flat upper edge **128** extending between the upper angled edges **126**. In this example, the headlight bezel **104** also includes partially triangular forward walls **130** extending laterally outwardly relative to the centerline A from the curved vertical edges **124** of the radar cover **120**. A pair of curved inner wall segments **132** of the headlight bezel **104** extend upwardly from the forward walls **130** to the upper portion of the headlight bezel **104**.

[0029] The headlight **102** is shaped to conform to the shape of the radar cover **120** while remaining within the envelope **54** defined by the curved lower edge **122** of the headlight bezel **104**, the forward walls **130** of the headlight bezel **104**, portions of the radar cover **120** and the curved inner wall segments **132** of the headlight bezel **104** to present an appearance of a typical headlight such as headlight **40** of FIG. **2A**. As such, the headlight lens **134** (and housing behind it—not shown) includes an upper semi-circular edge **136**, a pair of lower edges **138** extending from the upper semi-circular edge **136**, a lower recess **137** including a pair of lower angled edges **140** extending upwardly and inwardly from the lower edges **138**, and a central lower edge **142** extending between the lower angled edges **140**. In this manner, the lower edges **138** of the lens **134** are substantially contiguous with the forward walls **130** of the headlight bezel **104**, the lower angled edges **140** of the lens **134** are substantially contiguous with the upper angled edges **126** of the radar cover **120**, and the central lower edge **142** of the lens **134** is substantially contiguous with the upper edge **128** of the radar cover **120**.

[0030] The main lighting assembly **100** of this embodiment further includes a pair of position lights **108** situated between the outer side walls **114**, the forward walls **130** and the curved inner wall segments **132** of the headlight bezel **104**. The position lights **108** may be required in certain jurisdictions as corner markers of the vehicle, but in other jurisdictions may be included as auxiliary or signature lights for styling. In certain embodiments, the position lights **108** are incorporated into the headlight **102**. The position lights **108** each include a lower portion **146** that tapers along the curve defined by the outer side wall **114**, the forward walls **130** and the inner wall segments **132** of the headlight bezel **104**. The position lights **108** further include an upper portion **148** that extend upwardly from the lower portion **146** along the inner wall segments **132** of the headlight bezel **104**. An outwardly projecting step **150** extends from the upper portion **148** toward the outer side wall **114** of the headlight bezel **104** at the transition between the lower portion **146** and the upper portion **148** of the position lights **108**.

[0031] It should be understood that while the embodiments described herein depict the radar sensing assembly situated below the headlight, the teachings of the present disclosure may readily be modified to position the radar sensing assembly within or above the headlight. The present disclosure is intended to encompass any such mounting location of the radar sensing assembly that

is within the envelope described herein.

[0032] Referring now to FIG. 3, the headlight lens **134** includes a convex outer surface **151** and the radar cover **120** includes a convex outer surface **153**. The curvature of the convex outer surface **151** of the headlight lens **134** is substantially contiguous with the curvature of the convex outer surface **153** of the radar cover **120**. In other words, when viewed from the side, the outer surface **151** of the lens **134** substantially conforms to the outer surface **153** of the radar cover **120** giving the appearance of one substantially continuous surface.

[0033] It should be understood that many headlights need to be aimed with changes in, for example, the weight of occupant(s) of the vehicle. Accordingly, the main lighting assembly including the radar sensor assemblies disclosed herein may also be readily configured for aiming. Moreover, the main lighting assembly and/or the radar sensor assembly may be modified to adapt to the orientation of the vehicle such as during cornering as disclosed in U.S. Pat. No. 11,465,705, the entire contents of which being expressly incorporated herein by reference. Finally, the teachings of the present disclosure are applicable to vehicles that use other types of visual or proximity sensors, such as a camera, LIDAR or other device, instead of a radar assembly.

[0034] Lighting assemblies according to the present disclosure may advantageously facilitate ease of aligning/positioning components and assemblies relative to each other, and/or integrating different types of lights and sensors based on the application of the vehicle. Relatedly, lighting assemblies according to the present disclosure may advantageously facilitate customization, for example use of lenses with varying degrees of transparency for use with different types of lights and sensors.

[0035] The following items are further variations and examples of the embodiments described with reference to the figures.

[0036] Example 1. A main lighting assembly for a vehicle may comprise a headlight mounted to a frame of the vehicle. The headlight may include a lens. The lighting assembly may further comprise a headlight bezel substantially surrounding the headlight and supported within an opening of a front fairing of the vehicle and a sensor assembly. The sensor assembly may be positioned in proximity to the headlight lens and between the headlight bezel and the headlight to sense objects in front of the vehicle. The sensor assembly may include a forward-facing sensor unit mounted to the vehicle and positioned behind a sensor cover. The headlight lens may include a semi-arcuate edge and a recess. The sensor cover may include a protrusion that is substantially contiguous with the recess. The headlight lens and the sensor cover may define an arcuate envelope.

[0037] Example 2. The main lighting assembly of Example 1, wherein the headlight lens may define a first portion within the envelope and the radar cover may define a second portion within the envelope. The radar cover may generally extend to a center point of the envelope.

[0038] Example 3. The main lighting assembly of Example 1, wherein the semi-arcuate edge may be an upper semi-arcuate edge, the recess may be a lower recess, and the protrusion may be an upper protrusion.

[0039] Example 4. The main lighting assembly of Example 1, may further comprise a pair of position lights positioned between an outer side wall of the headlight bezel and curved inner wall segments of the headlight bezel.

[0040] Example 5. The main lighting assembly of Example 4, wherein the pair of position lights may be positioned outside the substantially circular envelope.

[0041] Example 6. The main lighting assembly of Example 5, wherein each of the pair of position lights may include a lower portion that tapers along a curved defined by an outer wall of the headlight bezel and an upper portion that extends from the lower portion at a step between the lower portion and the upper portion.

[0042] Example 7. The main lighting assembly of Example 1, wherein the headlight lens and the sensor cover may be symmetric about a centerline of the vehicle.

[0043] Example 8. The main lighting assembly of Example 1, wherein the headlight bezel may

include an outer wall that surrounds the headlight. The outer wall may include tapering ends adjacent a curved lower edge of the sensor cover.

[0044] Example 9. The main lighting assembly of Example 1, wherein the headlight bezel may include an outer wall that surrounds the headlight. A pair of curved inner wall segments that may be substantially contiguous with the semi-arcuate edge of the headlight lens.

[0045] Example 10. The main lighting assembly of Example 1, wherein the headlight bezel may include a pair of substantially triangular forward walls extending from the curved inner wall segments. The substantially triangular forward walls may be positioned adjacent corresponding lower edges of the headlight lens and corresponding curved vertical edges of the sensor cover.

[0046] Example 11. The main lighting assembly of Example 1, wherein the headlight lens may include a convex outer surface and the sensor cover may include a convex outer surface. The convex outer surface of the headlight lens may have a curvature that is substantially continuous with a curvature of the convex outer surface of the sensor cover.

[0047] Example 12. The main lighting assembly of Example 1, wherein the forward-facing sensor unit may be a radar unit.

[0048] Example 13. A main lighting assembly for a vehicle may comprise a headlight including a lens and a sensor assembly. The sensor assembly may be positioned below the headlight lens and may include a forward-facing sensor unit positioned behind a sensor cover to sense objects in front of the vehicle. The headlight lens may include a lower recess and the sensor cover may include an upper protrusion that is substantially contiguous with the lower recess. The headlight lens and the sensor cover may be positioned within an opening of a front fairing of the vehicle and may define a substantially circular envelope.

[0049] Example 14. The main lighting assembly of Example 13, wherein the lower recess of the headlight lens may include a pair of lower edges extending from an upper semi-circular edge of the headlight lens, a pair of lower angled edges extending from the pair of lower edges and a central lower edge.

[0050] Example 15. The main lighting assembly of Example 14, wherein the upper protrusion of the sensor cover may include a pair of upper angled edges and a substantially flat upper edge extending between the upper angled edges. The upper angled edges may be substantially contiguous with the lower angled edges of the headlight lens and the substantially flat upper edge being substantially contiguous with the central lower edge of the headlight lens.

[0051] Example 16. The main lighting assembly of Example 15, wherein the headlight lens and the sensor cover may be symmetric about a centerline of the vehicle.

[0052] Example 17. The main lighting assembly of Example 13, may further comprise a headlight bezel including an outer wall that substantially surrounds the headlight. The outer wall may include tapering ends adjacent a curved lower edge of the sensor cover.

[0053] Example 18. The main lighting assembly of Example 13, wherein the headlight lens may include a convex outer surface and the sensor cover may include a convex outer surface. The convex outer surface of the headlight lens may have a curvature that is substantially continuous with a curvature of the convex outer surface of the sensor cover.

[0054] Example 19. The main lighting assembly of Example 13, wherein the forward-facing sensor unit may be a radar unit.

[0055] Example 20. A main lighting assembly for a vehicle may comprise a headlight including a lens and a sensor assembly. The sensor assembly may be positioned above the headlight lens and may include a forward-facing sensor unit positioned behind a sensor cover to sense objects in front of the vehicle. The headlight lens may include an upper recess and the sensor cover may include a lower protrusion that is substantially contiguous with the upper recess. The headlight lens and the sensor cover may be positioned within an opening of a front fairing of the vehicle and may define a substantially circular envelope.

[0056] Example 21. A lighting assembly for a vehicle may comprise a light including a lens and a



sensor assembly. The sensor assembly may be positioned adjacent the light lens and may include a forward-facing sensor unit positioned behind a sensor cover to sense objects the vehicle. The light lens may include a recess and the sensor cover may include a portion that is substantially contiguous with the recess. The light lens and the sensor cover may be positioned within an opening of a front fairing of the vehicle and may define a substantially circular envelope. [0057] While this disclosure has been described as having exemplary designs, the present disclosure may be further modified within the spirit and scope of this disclosure. This application is therefore intended to cover any variations, uses, or adaptations of the disclosure using its general principles. Further, this application is intended to cover such departures from the present disclosure as come within known or customary practice in the art to which this disclosure pertains.

## Claims

1. A main lighting assembly for a vehicle, comprising: a headlight mounted to a frame of the vehicle, the headlight including a lens; a headlight bezel substantially surrounding the headlight and supported within an opening of a front fairing of the vehicle; and a sensor assembly positioned in proximity to the headlight lens and between the headlight bezel and the headlight to sense objects in front of the vehicle, the sensor assembly including a forward-facing sensor unit mounted to the vehicle and positioned behind a sensor cover; wherein the headlight lens includes a semi-arcuate edge and a recess and the sensor cover includes a protrusion that is substantially contiguous with the recess; and wherein the headlight lens and the sensor cover define an arcuate envelope.
2. The main lighting assembly of claim 1, wherein the headlight lens defines a first portion within the envelope and the radar cover defines a second portion within the envelope, and the radar cover generally extends to a center point of the envelope.
3. The main lighting assembly of claim 1, wherein the semi-arcuate edge is an upper semi-arcuate edge, the recess is a lower recess, and the protrusion is an upper protrusion.
4. The main lighting assembly of claim 1, further comprising a pair of position lights positioned between an outer side wall of the headlight bezel and curved inner wall segments of the headlight bezel.
5. The main lighting assembly of claim 4, wherein the pair of position lights are positioned outside the substantially circular envelope.
6. The main lighting assembly of claim 5, wherein each of the pair of position lights includes a lower portion that tapers along a curved defined by an outer wall of the headlight bezel and an upper portion that extends from the lower portion at a step between the lower portion and the upper portion.
7. The main lighting assembly of claim 1, wherein the headlight lens and the sensor cover are symmetric about a centerline of the vehicle.
8. The main lighting assembly of claim 1, wherein the headlight bezel includes an outer wall that surrounds the headlight, the outer wall including tapering ends adjacent a curved lower edge of the sensor cover.
9. The main lighting assembly of claim 1, wherein the headlight bezel includes an outer wall that surrounds the headlight, an a pair of curved inner wall segments that are substantially contiguous with the semi-arcuate edge of the headlight lens.
10. The main lighting assembly of claim 1, wherein the headlight bezel includes a pair of substantially triangular forward walls extending from the curved inner wall segments, the substantially triangular forward walls being positioned adjacent corresponding lower edges of the headlight lens and corresponding curved vertical edges of the sensor cover.
11. The main lighting assembly of claim 1, wherein the headlight lens includes a convex outer surface and the sensor cover includes a convex outer surface, the convex outer surface of the headlight lens has a curvature that is substantially continuous with a curvature of the convex outer

surface of the sensor cover.

**12.** The main lighting assembly of claim 1, wherein the forward-facing sensor unit is a radar unit.

**13.** A main lighting assembly for a vehicle, comprising: a headlight including a lens; and a sensor assembly positioned below the headlight lens and including a forward-facing sensor unit positioned behind a sensor cover to sense objects in front of the vehicle; wherein the headlight lens includes a lower recess and the sensor cover includes an upper protrusion that is substantially contiguous with the lower recess; and wherein the headlight lens and the sensor cover are positioned within an opening of a front fairing of the vehicle and define a substantially circular envelope.

**14.** The main lighting assembly of claim 13, wherein the lower recess of the headlight lens includes a pair of lower edges extending from an upper semi-circular edge of the headlight lens, a pair of lower angled edges extending from the pair of lower edges and a central lower edge.

**15.** The main lighting assembly of claim 14, wherein the upper protrusion of the sensor cover includes a pair of upper angled edges and a substantially flat upper edge extending between the upper angled edges, the upper angled edges being substantially contiguous with the lower angled edges of the headlight lens and the substantially flat upper edge being substantially contiguous with the central lower edge of the headlight lens.

**16.** The main lighting assembly of claim 15, wherein the headlight lens and the sensor cover are symmetric about a centerline of the vehicle.

**17.** The main lighting assembly of claim 13, further comprising a headlight bezel including an outer wall that substantially surrounds the headlight, the outer wall including tapering ends adjacent a curved lower edge of the sensor cover.

**18.** The main lighting assembly of claim 13, wherein the headlight lens includes a convex outer surface and the sensor cover includes a convex outer surface, the convex outer surface of the headlight lens has a curvature that is substantially continuous with a curvature of the convex outer surface of the sensor cover.

**19.** The main lighting assembly of claim 13, wherein the forward-facing sensor unit is a radar unit.

**20.** A main lighting assembly for a vehicle, comprising: a headlight including a lens; and a sensor assembly positioned above the headlight lens and including a forward-facing sensor unit positioned behind a sensor cover to sense objects in front of the vehicle; wherein the headlight lens includes an upper recess and the sensor cover includes a lower protrusion that is substantially contiguous with the upper recess; and wherein the headlight lens and the sensor cover are positioned within an opening of a front fairing of the vehicle and define a substantially circular envelope.

**21.** A lighting assembly for a vehicle, comprising: a light including a lens; and a sensor assembly positioned adjacent the light lens and including a forward-facing sensor unit positioned behind a sensor cover to sense objects the vehicle; wherein the light lens includes a recess and the sensor cover includes a portion that is substantially contiguous with the recess; and wherein the light lens and the sensor cover are positioned within an opening of a front fairing of the vehicle and define a substantially circular envelope.

---