

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396090
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Harada; Tetsuro et al.

Radio-frequency module and communication device

Abstract

Detection accuracy is improved with a reduced size. A radio-frequency module includes an antenna terminal, a signal input terminal, a signal output terminal, a mounting substrate, a chip inductor, and a directional coupler. The mounting substrate has a first major surface and a second major surface opposite to each other. The chip inductor is mounted on the first major surface of the mounting substrate. The chip inductor is provided in at least one of a transmitting path between the antenna terminal and the signal input terminal and a receiving path between the antenna terminal and the signal output terminal. The directional coupler is mounted on the second major surface of the mounting substrate, and at least part of the directional coupler is provided in the transmitting path.

Inventors: Harada; Tetsuro (Kyoto, JP), Nakagawa; Dai (Kyoto, JP), Takematsu; Yuji (Kyoto, JP), Takaoka; Hiroaki (Kyoto, JP), Toyomura; Takahisa (Kyoto, JP)

Applicant: Murata Manufacturing Co., Ltd. (Kyoto, JP)

Family ID: 1000008765319

Assignee: MURATA MANUFACTURING CO., LTD. (Kyoto, JP)

Appl. No.: 18/332251

Filed: June 09, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230319984 A1	Oct. 05, 2023

Foreign Application Priority Data

JP	2020-217807	Dec. 25, 2020
----	-------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/JP2021/036218 20210930 PENDING child-doc US 18332251

Publication Classification

Int. Cl.: H05K1/02 (20060101)

U.S. Cl.:

CPC H05K1/0243 (20130101); H05K2201/1003 (20130101); H05K2201/10098 (20130101)

Field of Classification Search

CPC: H05K (1/0243); H05K (2201/1003); H05K (2201/10098)

USPC: 361/782

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2003/0143971	12/2002	Hongo et al.	N/A	N/A
2008/0212552	12/2007	Fukamachi et al.	N/A	N/A
2019/0014655	12/2018	Yazaki	N/A	H05K 1/181
2020/0051941	12/2019	Nakazawa et al.	N/A	N/A
2020/0091608	12/2019	Alpman	N/A	H03L 7/145
2021/0152202	12/2020	Uejima	N/A	N/A
2021/0234247	12/2020	Tokuda et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2002-076267	12/2001	JP	N/A
2009-124746	12/2008	JP	N/A
2020-027974	12/2019	JP	N/A
2019/240096	12/2018	WO	N/A
2020/129892	12/2019	WO	N/A

OTHER PUBLICATIONS

International Search Report for PCT/JP2021/036218 dated Dec. 28, 2021. cited by applicant

Primary Examiner: Tran; Binh B

Attorney, Agent or Firm: McDonald Hopkins LLC

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION (1) This is a continuation of International Application No. PCT/JP2021/036218 filed on Sep. 30, 2021 which claims priority from Japanese Patent Application No. 2020-217807 filed on Dec. 25, 2020. The contents of these applications are incorporated herein by reference in their entireties.

BACKGROUND ART

Technical Field

(1) The present disclosure generally relates to a radio-frequency module and a communication device and, more specifically, to a radio-frequency module that includes a mounting substrate, and a communication device that includes the radio-frequency module.

(2) Patent Document 1 describes a coupler module (radio-frequency module) that includes a module substrate (mounting substrate), a first component, and a second component. The first component has a directional coupler that includes a main line and an auxiliary line. The second component is, for example, an LC resonant filter that is made up of a capacitor and an inductor and that processes a signal passing through the main line or the auxiliary line. The first component and the second component are mounted adjacent to each other on the same major surface of the module substrate. Patent Document 1: International Publication No. 2020/129892

BRIEF SUMMARY

(3) In the coupler module described in Patent Document 1, the first component and the second component are adjacent to each other on the same major surface of the module substrate, so the detection accuracy may decrease due to interference of a signal or jump of a signal. In addition, in the coupler module described in Patent Document 1, there are a large number of components mounted on the same major surface of the module substrate, so the size may increase.

(4) The present disclosure provides a radio-frequency module and a communication device that can be reduced in size and that are capable of suppressing a decrease in detection accuracy.

(5) A radio-frequency module according to an aspect of the present disclosure includes an antenna terminal, a signal input terminal, a signal output terminal, a mounting substrate, a chip inductor, and a directional coupler. A transmitting signal is input to the signal input terminal. A receiving signal is output from the signal output terminal. The mounting substrate has a first major surface and a second major surface opposite to each other. The chip inductor is mounted on the first major surface of the mounting substrate and provided in at least one of a transmitting path between the antenna terminal and the signal input terminal and a receiving path between the antenna terminal and the signal output terminal. The directional coupler is mounted on the second major surface of the mounting substrate, and at least part of the directional coupler is provided in the transmitting path.

(6) A communication device according to an aspect of the present disclosure includes the radio-frequency module and a signal processing circuit. The signal processing circuit is connected to the radio-frequency module.

(7) With the radio-frequency module and the communication device according to the aspects of the present disclosure, it is possible to reduce the size and to suppress a decrease in detection accuracy.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a plan view that relates to a radio-frequency module according to a first embodiment and from which a shield layer and a resin layer are omitted.

(2) FIG. 2 is a plan view that relates to the radio-frequency module and that shows a second major surface of a mounting substrate and circuit components and a plurality of external connection terminals disposed on the second major surface of the mounting substrate when seen through from

the first major surface side of the mounting substrate.

(3) FIG. 3 is a cross-sectional view of the radio-frequency module.

(4) FIG. 4 is a circuit configuration diagram of a communication device that includes the radio-frequency module.

(5) FIG. 5 is a circuit configuration diagram of a relevant part of the radio-frequency module.

(6) FIG. 6 is a cross-sectional view of a radio-frequency module according to a modification of the first embodiment.

(7) FIG. 7 is a circuit configuration diagram of a relevant part of a radio-frequency module according to a second embodiment.

(8) FIG. 8 is a circuit configuration diagram of a relevant part of a radio-frequency module according to a first modification of the second embodiment.

(9) FIG. 9 is a circuit configuration diagram of a relevant part of a radio-frequency module according to a second modification of the second embodiment.

DETAILED DESCRIPTION

(10) FIGS. 1 to 3, and 6 that will be referenced in the following embodiments and the like all are schematic diagrams, and the ratios of the sizes and thicknesses of component elements in the drawings do not always reflect actual scale ratios.

First Embodiment

(11) A radio-frequency module **100** according to a first embodiment includes an antenna terminal **81**, signal input terminals **82**, **83**, signal output terminals **84**, **85**, a mounting substrate **9**, a chip inductor **601**, and a directional coupler **80**, as shown in FIGS. 1 to 4. The signal input terminals **82**, **83** are terminals to which a transmitting signal is input. The signal output terminals **84**, **85** are terminals from which a receiving signal is output. The mounting substrate **9** has a first major surface **91** and a second major surface **92** opposite to each other. The chip inductor **601** is disposed on the first major surface **91** of the mounting substrate **9**. The chip inductor **601** is provided in at least one of a transmitting path **T1** and a receiving path **R1**. The transmitting path **T1** is a path between the antenna terminal **81** and the signal input terminals **82**, **83**. The receiving path **R1** is a path between the antenna terminal **81** and the signal output terminals **84**, **85**. The directional coupler **80** is mounted on the second major surface **92** of the mounting substrate **9**, and at least part (main line **801**) of the directional coupler **80** is provided in the transmitting path **T1**.

(12) In the radio-frequency module **100** according to the first embodiment, as described above, the chip inductor **601** is mounted on the first major surface **91** of the mounting substrate **9**, and the directional coupler **80** is mounted on the second major surface **92** of the mounting substrate **9**. Thus, in comparison with the case where both a chip inductor and a directional coupler are mounted on a first major surface of a mounting substrate, it is possible to reduce the size in a direction that intersects with a thickness direction **D1** of the mounting substrate **9**. In the radio-frequency module **100** according to the first embodiment, it is possible to suppress jump of a signal between the chip inductor **601** and the directional coupler **80**, with the result that it is possible to suppress a decrease in detection accuracy. In other words, with the radio-frequency module **100** according to the first embodiment, it is possible to reduce the size and to suppress a decrease in detection accuracy.

(13) Hereinafter, the radio-frequency module **100** and a communication device **300** according to the first embodiment will be described in more detail with reference to FIGS. 1 to 5.

(1) Radio-Frequency Module and Communication Device

(1.1) Circuit Configuration of Radio-Frequency Module and Communication Device

(14) Initially, the circuit configuration of the radio-frequency module **100** and the communication device **300** according to the first embodiment will be described with reference to FIG. 4.

(15) The radio-frequency module **100** is used in, for example, the communication device **300**. The communication device **300** is, for example, a mobile phone (for example, a smartphone); however, the communication device **300** is not limited to a mobile phone. The communication device **300**

may be, for example, a wearable terminal (for example, a smart watch). The radio-frequency module **100** is, for example, a module that supports a fourth generation mobile communication (4G) standard, a fifth generation mobile communication (5G) standard, and the like. The 4G standard is, for example, a third generation partnership project (3GPP) long term evolution (LTE) standard. The 5G standard is, for example, a 5G new radio (NR). The radio-frequency module **100** is a module that supports, for example, carrier aggregation and dual connectivity.

(16) The radio-frequency module **100** supports simultaneous communication that uses a plurality of (two in the first embodiment) frequency bands (a first frequency band and a second frequency band) in uplink. The radio-frequency module **100** is configured to be capable of amplifying a transmitting signal in the first frequency band (radio-frequency signal) input from the signal processing circuit **301** with a first power amplifier **11** and outputting the transmitting signal to an antenna **310**. The radio-frequency module **100** is configured to be capable of amplifying a transmitting signal in the second frequency band (radio-frequency signal) input from the signal processing circuit **301** with a second power amplifier **12** and outputting the transmitting signal to the antenna **310**. The radio-frequency module **100** further includes a first low-noise amplifier **21**. The radio-frequency module **100** is configured to be capable of amplifying a receiving signal in the first frequency band (radio-frequency signal) input from the antenna **310** with the first low-noise amplifier **21** and outputting the receiving signal to the signal processing circuit **301**. The radio-frequency module **100** further includes a second low-noise amplifier **22**. The radio-frequency module **100** is configured to be capable of amplifying a receiving signal in the second frequency band (radio-frequency signal) input from the antenna **310** with the second low-noise amplifier **22** and outputting the receiving signal to the signal processing circuit **301**. The signal processing circuit **301** is not a component element of the radio-frequency module **100** but a component element of the communication device **300** that includes the radio-frequency module **100**. The radio-frequency module **100** is, for example, controlled by the signal processing circuit **301** of the communication device **300**. The communication device **300** includes the radio-frequency module **100** and the signal processing circuit **301**. The communication device **300** further includes the antenna **310**. The communication device **300** further includes a circuit board (not shown) on or in which the radio-frequency module **100** is mounted. The circuit board is, for example, a printed circuit board. The circuit board has a ground electrode to which a ground potential is applied.

(17) The signal processing circuit **301** includes, for example, an RF signal processing circuit **302** and a baseband signal processing circuit **303**. The RF signal processing circuit **302** is, for example, a radio frequency integrated circuit (RFIC). The RF signal processing circuit **302** performs signal processing on a radio-frequency signal. The RF signal processing circuit **302**, for example, performs signal processing on a radio-frequency signal (transmitting signal) output from the baseband signal processing circuit **303** by up conversion or the like and outputs the processed radio-frequency signal to the radio-frequency module **100**. The RF signal processing circuit **302**, for example, performs signal processing on a radio-frequency signal (receiving signal) output from the radio-frequency module **100** by down conversion or the like and outputs the processed radio-frequency signal to the baseband signal processing circuit **303**. The baseband signal processing circuit **303** is, for example, a baseband integrated circuit (BBIC). The baseband signal processing circuit **303** generates an I-phase signal and a Q-phase signal from a baseband signal. The baseband signal is, for example, an audio signal, an image signal, or the like input from the outside. The baseband signal processing circuit **303** performs IQ modulation process by synthesizing the I-phase signal with the Q-phase signal and outputs a transmitting signal. At this time, the transmitting signal is generated as a modulation signal (IQ signal) obtained by modulating the amplitude of a carrier wave signal with a predetermined frequency at a period longer than the period of the carrier wave signal. A receiving signal processed by the baseband signal processing circuit **303** is, for example, used to display an image as an image signal or to talk as a voice signal. The radio-frequency module **100** transmits a radio-frequency signal (a receiving signal or a transmitting

signal) between the antenna **310** and the RF signal processing circuit **302** of the signal processing circuit **301**.

(18) The radio-frequency module **100** includes the first power amplifier **11**, the second power amplifier **12**, a first switch **51**, a second switch **52**, and a plurality of (for example, four) filters **61** to **64**. The radio-frequency module **100** further includes a controller **20**. The radio-frequency module **100** further includes a first output matching circuit **31**, a second output matching circuit **32**, and a plurality of (for example, four) matching circuits **71** to **74**. The radio-frequency module **100** further includes the first low-noise amplifier **21**, the second low-noise amplifier **22**, a first input matching circuit **41**, and a second input matching circuit **42**. The radio-frequency module **100** further includes a third switch **53** and a fourth switch **54**. The radio-frequency module **100** further includes a low pass filter **60**. The radio-frequency module **100** further includes a fifth switch **55** and a sixth switch **56**. The radio-frequency module **100** further includes the directional coupler **80**. The radio-frequency module **100** further includes a filter **65** (see FIG. 1) and a matching circuit **75** (see FIG. 1). The filter **61** is a duplexer that includes a transmitting filter **611** and a receiving filter **612**. The filter **62** is a duplexer that includes a transmitting filter **621** and a receiving filter **622**. The filter **63** is a duplexer that includes a transmitting filter **631** and a receiving filter **632**. The filter **64** is a duplexer that includes a transmitting filter **641** and a receiving filter **642**. The filter **65** is a duplexer that includes a transmitting filter **651** and a receiving filter **652**.

(19) The radio-frequency module **100** includes a plurality of external connection terminals **8**. The plurality of external connection terminals **8** includes the antenna terminal **81**, the two signal input terminals **82**, **83**, the two signal output terminals **84**, **85**, and a plurality of (four) control terminals **86**. The plurality of external connection terminals **8** further includes an output terminal **87**, a plurality of (for example, three) input terminals **881**, **882**, **883**, and a plurality of ground terminals **89** (see FIG. 2). FIG. 4 shows only one control terminal **86** of the four control terminals **86**. The plurality of ground terminals **89** is terminals electrically connected to the ground electrode of the circuit board of the communication device **300** and applied with a ground potential. In the radio-frequency module **100** according to the first embodiment, the output terminal **87** and the plurality of input terminals **881**, **882**, **883** make up a plurality of signal terminals.

(20) Hereinafter, the circuit configuration of the radio-frequency module **100** will be described in more detail with reference to FIG. 4.

(21) The first power amplifier **11** has a first input terminal and a first output terminal. The first power amplifier **11** amplifies a transmitting signal in the first frequency band input to the first input terminal and outputs the amplified transmitting signal from the first output terminal. The first frequency band includes, for example, a transmitting band of a first communication band and a transmitting band of a second communication band. The first communication band is a communication band that corresponds to a transmitting signal that passes through the transmitting filter **611** of the filter **61**. The second communication band is a communication band that corresponds to a transmitting signal that passes through the transmitting filter **621** of the filter **62**.

(22) The first input terminal of the first power amplifier **11** is connected to the signal input terminal **82**. The first input terminal of the first power amplifier **11** is connected to the signal processing circuit **301** with the signal input terminal **82** interposed therebetween. The signal input terminal **82** is a terminal for inputting a radio-frequency signal (transmitting signal) from an external circuit (for example, the signal processing circuit **301**) to the radio-frequency module **100**. The first output terminal of the first power amplifier **11** is connected to a common terminal **510** of the first switch **51** with the first output matching circuit **31** interposed therebetween. Thus, the first output terminal of the first power amplifier **11** can be connected to any one of the filters **61**, **62** with the first switch **51** interposed therebetween. The first power amplifier **11** is, for example, a multistage amplifier, an in-phase synthesis amplifier, a differential synthesis amplifier, or a Doherty amplifier.

(23) The second power amplifier **12** has a second input terminal and a second output terminal. The second power amplifier **12** amplifies a transmitting signal in the second frequency band input to the

second input terminal and outputs the amplified transmitting signal from the second output terminal. The second frequency band is a frequency band different from the first frequency band. More specifically, the second frequency band is a frequency band lower in frequency than the first frequency band. The second frequency band includes, for example, a transmitting band of a third communication band, a transmitting band of a fourth communication band, and a transmitting band of a fifth communication band. The third communication band is a communication band that corresponds to a transmitting signal that passes through the transmitting filter **631** of the filter **63**. The fourth communication band is a communication band that corresponds to a transmitting signal that passes through the transmitting filter **641** of the filter **64**. The fifth communication band is a communication band that corresponds to a transmitting signal that passes through the transmitting filter **651** of the filter **65**.

(24) The second input terminal of the second power amplifier **12** is connected to the signal input terminal **83**. The second input terminal of the second power amplifier **12** is connected to the signal processing circuit **301** with the signal input terminal **83** interposed therebetween. The signal input terminal **83** is a terminal for inputting a radio-frequency signal (transmitting signal) from an external circuit (for example, the signal processing circuit **301**) to the radio-frequency module **100**. The second output terminal of the second power amplifier **12** is connected to a common terminal **520** of the second switch **52** with the second output matching circuit **32** interposed therebetween. Thus, the second output terminal of the second power amplifier **12** can be connected to any one of the filters **63**, **64** with the second switch **52** interposed therebetween. The second power amplifier **12** is, for example, a multistage amplifier, an in-phase synthesis amplifier, a differential synthesis amplifier, or a Doherty amplifier.

(25) The first switch **51** has a common terminal **510** and a plurality of (for example, two) selection terminals **511**, **512**. The common terminal **510** is connected to the first output terminal of the first power amplifier **11** with the first output matching circuit **31** interposed therebetween. In the first switch **51**, the selection terminal **511** is connected to the input terminal of the transmitting filter **611** of the filter **61**, and the selection terminal **512** is connected to the input terminal of the transmitting filter **621** of the filter **62**. The first switch **51** is, for example, a switch capable of connecting at least one of the plurality of selection terminals **511**, **512** to the common terminal **510**. Here, the first switch **51** is, for example, a switch capable of one-to-one connection and one-to-multiple connection.

(26) The first switch **51** is, for example, a switch integrated circuit (IC). The first switch **51** is controlled by, for example, the controller **20**. In this case, the first switch **51** is controlled by the controller **20** and switches the connection status between the common terminal **510** and the plurality of selection terminals **511**, **512**. The first switch **51** only has to be configured to, for example, switch the connection status between the common terminal **510** and the plurality of selection terminals **511**, **512** in accordance with a digital control signal input from the controller **20**. The first switch **51** may be controlled by the signal processing circuit **301**. In this case, the first switch **51** switches the connection status between the common terminal **510** and the plurality of selection terminals **511**, **512** in accordance with a control signal from the RF signal processing circuit **302** of the signal processing circuit **301**.

(27) The second switch **52** has a common terminal **520** and a plurality of (for example, two) selection terminals **521**, **522**. The common terminal **520** is connected to the second output terminal of the second power amplifier **12** with the second output matching circuit **32** interposed therebetween. In the second switch **52**, the selection terminal **521** is connected to the input terminal of the transmitting filter **631** of the filter **63**, and the selection terminal **522** is connected to the input terminal of the transmitting filter **641** of the filter **64**. The second switch **52** is, for example, a switch capable of connecting at least one of the plurality of selection terminals **521**, **522** to the common terminal **520**. Here, the second switch **52** is, for example, a switch capable of one-to-one connection and one-to-multiple connection.

(28) The second switch **52** is, for example, a switch IC. The second switch **52** is controlled by, for example, the controller **20**. In this case, the second switch **52** is controlled by the controller **20** and switches the connection status between the common terminal **520** and the plurality of selection terminals **521**, **522**. The second switch **52** only has to be configured to, for example, switch the connection status between the common terminal **520** and the plurality of selection terminals **521**, **522** in accordance with a digital control signal input from the controller **20**. The second switch **52** may be controlled by the signal processing circuit **301**. In this case, the second switch **52** switches the connection status between the common terminal **520** and the plurality of selection terminals **521**, **522** in accordance with a control signal from the RF signal processing circuit **302** of the signal processing circuit **301**.

(29) As described above, the filter **61** is a duplexer that includes the transmitting filter **611** and the receiving filter **612**. The transmitting filter **611** is, for example, a band pass filter that has a transmitting band of the first communication band as a pass band. The receiving filter **612** is, for example, a band pass filter that has a receiving band of the first communication band as a pass band.

(30) As described above, the filter **62** is a duplexer that includes the transmitting filter **621** and the receiving filter **622**. The transmitting filter **621** is, for example, a band pass filter that has a transmitting band of the second communication band as a pass band. The receiving filter **622** is, for example, a band pass filter that has a receiving band of the second communication band as a pass band.

(31) As described above, the filter **63** is a duplexer that includes the transmitting filter **631** and the receiving filter **632**. The transmitting filter **631** is, for example, a band pass filter that has a transmitting band of the third communication band as a pass band. The receiving filter **632** is, for example, a band pass filter that has a receiving band of the third communication band as a pass band.

(32) As described above, the filter **64** is a duplexer that includes the transmitting filter **641** and the receiving filter **642**. The transmitting filter **641** is, for example, a band pass filter that has a transmitting band of the fourth communication band as a pass band. The receiving filter **642** is, for example, a band pass filter that has a receiving band of the fourth communication band as a pass band.

(33) As described above, the filter **65** is a duplexer that includes the transmitting filter **651** and the receiving filter **652**. The transmitting filter **651** is, for example, a band pass filter that has a transmitting band of the fifth communication band as a pass band. The receiving filter **652** is, for example, a band pass filter that has a receiving band of the fifth communication band as a pass band.

(34) The controller **20** is connected to the first power amplifier **11** and the second power amplifier **12**. The controller **20** is connected to the signal processing circuit **301** with the plurality of (for example, four) control terminals **86** interposed therebetween. FIG. 4 shows only one of the four control terminals **86**. The plurality of control terminals **86** is terminals for inputting a control signal from an external circuit (for example, the signal processing circuit **301**) to the controller **20**. The controller **20** controls the first power amplifier **11** and the second power amplifier **12** in accordance with a control signal acquired from the plurality of control terminals **86**. The controller **20** controls the first power amplifier **11** and the second power amplifier **12** in accordance with a control signal from the RF signal processing circuit **302** of the signal processing circuit **301**. The controller **20** only has to be configured to, for example, control the first power amplifier **11** and the second power amplifier **12** in accordance with a digital control signal acquired from the signal processing circuit **301**.

(35) The first output matching circuit **31** is provided in a signal path between the first output terminal of the first power amplifier **11** and the common terminal **510** of the first switch **51**. The first output matching circuit **31** is a circuit for matching the impedance between the first power

amplifier **11** and the transmitting filters **611**, **621** of the two filters **61**, **62**. As shown in FIG. **1**, the first output matching circuit **31** is made up of, for example, two capacitors **311**, **312** and one inductor **313**. The first output matching circuit **31** is not limited to the above configuration and may be made up of, for example, only one inductor or only one capacitor. The first output matching circuit **31** may be configured to include, for example, a transformer.

(36) The second output matching circuit **32** is provided in a signal path between the second output terminal of the second power amplifier **12** and the common terminal **520** of the second switch **52**. The second output matching circuit **32** is a circuit for matching the impedance between the second power amplifier **12** and the transmitting filters **631**, **641** of the two filters **63**, **64**. The second output matching circuit **32**, as well as the first output matching circuit **31**, is made up of, for example, two capacitors and one inductor. The second output matching circuit **32** is not limited to the above configuration and may be made up of, for example, only one inductor or only one capacitor. The second output matching circuit **32** may be configured to include, for example, a transformer.

(37) The plurality of (for example, four) matching circuits **71** to **74** is in a one-to-one correspondence with the plurality of filters **61** to **64**. The matching circuit **71** is provided in a signal path between the filter **61** and the fifth switch **55**. The matching circuit **71** is a circuit for matching the impedance between the filter **61** and the fifth switch **55**. As shown in FIG. **1**, the matching circuit **71** is made up of, for example, one inductor **711** and one capacitor **712**. The matching circuit **71** is not limited to the above configuration. For example, the matching circuit **71** may be made up of a plurality of inductors and a plurality of capacitors or may be made up of only one inductor or only one capacitor.

(38) The matching circuit **72** is provided in a signal path between the filter **62** and the fifth switch **55**. The matching circuit **72** is a circuit for matching the impedance between the filter **62** and the fifth switch **55**. The matching circuit **72**, as well as the matching circuit **71**, is made up of, for example, one inductor and one capacitor. The matching circuit **72** is not limited to the above configuration. For example, the matching circuit **72** may be made up of a plurality of inductors and a plurality of capacitors or may be made up of only one inductor or only one capacitor.

(39) The matching circuit **73** is provided in a signal path between the filter **63** and the fifth switch **55**. The matching circuit **73** is a circuit for matching the impedance between the filter **63** and the fifth switch **55**. The matching circuit **73**, as well as the matching circuit **71**, is made up of, for example, one inductor and one capacitor. The matching circuit **73** is not limited to the above configuration. For example, the matching circuit **73** may be made up of a plurality of inductors and a plurality of capacitors or may be made up of only one inductor or only one capacitor.

(40) The matching circuit **74** is provided in a signal path between the filter **64** and the fifth switch **55**. The matching circuit **74** is a circuit for matching the impedance between the filter **64** and the fifth switch **55**. The matching circuit **74**, as well as the matching circuit **71**, is made up of, for example, one inductor and one capacitor. The matching circuit **74** is not limited to the above configuration. For example, the matching circuit **74** may be made up of a plurality of inductors and a plurality of capacitors or may be made up of only one inductor or only one capacitor.

(41) The first low-noise amplifier **21** has a first input terminal and a first output terminal. The first low-noise amplifier **21** amplifies a receiving signal in the first frequency band input to the first input terminal and outputs the amplified receiving signal from the first output terminal. The first input terminal of the first low-noise amplifier **21** is connected to a common terminal **530** of the third switch **53** with the first input matching circuit **41** interposed therebetween. The first output terminal of the first low-noise amplifier **21** is connected to the signal output terminal **84**. The first output terminal of the first low-noise amplifier **21** is, for example, connected to the signal processing circuit **301** with the signal output terminal **84** interposed therebetween. The signal output terminal **84** is a terminal for outputting a radio-frequency signal (receiving signal) from the first low-noise amplifier **21** to an external circuit (for example, the signal processing circuit **301**).

(42) The second low-noise amplifier **22** has a second input terminal and a second output terminal.

The second low-noise amplifier **22** amplifies a receiving signal in the second frequency band input to the second input terminal and outputs the amplified receiving signal from the second output terminal. The second input terminal of the second low-noise amplifier **22** is connected to a common terminal **540** of the fourth switch **54** with the second input matching circuit **42** interposed therebetween. The second output terminal of the second low-noise amplifier **22** is connected to the signal output terminal **85**. The second output terminal of the second low-noise amplifier **22** is, for example, connected to the signal processing circuit **301** with the signal output terminal **85** interposed therebetween. The signal output terminal **85** is a terminal for outputting a radio-frequency signal (receiving signal) from the second low-noise amplifier **22** to an external circuit (for example, the signal processing circuit **301**).

(43) The first input matching circuit **41** is provided in a signal path between the first input terminal of the first low-noise amplifier **21** and the common terminal **530** of the third switch **53**. The first input matching circuit **41** is a circuit for matching the impedance between the first low-noise amplifier **21** and the receiving filters **612**, **622** of the two filters **61**, **62**. As shown in FIG. **1**, the first input matching circuit **41** is made up of, for example, four inductors **411** to **414** and one capacitor **415**. The first input matching circuit **41** is not limited to the above configuration. For example, the first input matching circuit **41** may be made up of a plurality of inductors and a plurality of capacitors or may be made up of only one inductor or only one capacitor.

(44) The second input matching circuit **42** is provided in a signal path between the second input terminal of the second low-noise amplifier **22** and the common terminal **540** of the fourth switch **54**. The second input matching circuit **42** is a circuit for matching the impedance between the second low-noise amplifier **22** and the receiving filters **632**, **642** of the two filters **63**, **64**. The second input matching circuit **42**, as well as the first input matching circuit **41**, is made up of, for example, four inductors and one capacitor. The second input matching circuit **42** is not limited to the above configuration. For example, the second input matching circuit **42** may be made up of a plurality of inductors and a plurality of capacitors or may be made up of only one inductor or only one capacitor.

(45) The third switch **53** has the common terminal **530** and the plurality of (for example, two) selection terminals **531**, **532**. The common terminal **530** is connected to the first input terminal of the first low-noise amplifier **21** with the first input matching circuit **41** interposed therebetween. In the third switch **53**, the selection terminal **531** is connected to the output terminal of the receiving filter **612** of the filter **61**, and the selection terminal **532** is connected to the output terminal of the receiving filter **622** of the filter **62**. The third switch **53** is, for example, a switch capable of connecting at least one of the plurality of selection terminals **531**, **532** to the common terminal **530**. Here, the third switch **53** is, for example, a switch capable of one-to-one connection and one-to-multiple connection.

(46) The third switch **53** is, for example, a switch IC. The third switch **53** is controlled by, for example, the signal processing circuit **301**. In this case, the third switch **53** switches the connection status between the common terminal **530** and the plurality of selection terminals **531**, **532** in accordance with a control signal from the RF signal processing circuit **302** of the signal processing circuit **301**. The third switch **53** only has to be configured to, for example, switch the connection status between the common terminal **530** and the plurality of selection terminals **531**, **532** in accordance with a digital control signal input from the signal processing circuit **301**. The third switch **53** may be controlled by the controller **20** instead of being controlled by the signal processing circuit **301**.

(47) The fourth switch **54** has the common terminal **540** and a plurality of (for example, two) selection terminals **541**, **542**. The common terminal **540** is connected to the second input terminal of the second low-noise amplifier **22** with the second input matching circuit **42** interposed therebetween. In the fourth switch **54**, the selection terminal **541** is connected to the output terminal of the receiving filter **632** of the filter **63**, and the selection terminal **542** is connected to the output

terminal of the receiving filter **642** of the filter **64**. The fourth switch **54** is, for example, a switch capable of connecting at least one of the plurality of selection terminals **541**, **542** to the common terminal **540**. Here, the fourth switch **54** is, for example, a switch capable of one-to-one connection and one-to-multiple connection.

(48) The fourth switch **54** is, for example, a switch IC. The fourth switch **54** is controlled by, for example, the signal processing circuit **301**. In this case, the fourth switch **54** switches the connection status between the common terminal **540** and the plurality of selection terminals **541**, **542** in accordance with a control signal from the RF signal processing circuit **302** of the signal processing circuit **301**. The fourth switch **54** only has to be configured to, for example, switch the connection status between the common terminal **540** and the plurality of selection terminals **541**, **542** in accordance with a digital control signal input from the signal processing circuit **301**. The fourth switch **54** may be controlled by the controller **20** instead of being controlled by the signal processing circuit **301**.

(49) The fifth switch **55** has a common terminal **550** and a plurality of (for example, six) selection terminals **551** to **556**. The common terminal **550** is connected to the antenna terminal **81** with the low pass filter **60** and the directional coupler **80** interposed therebetween. The antenna **310** is connected to the antenna terminal **81**. The selection terminal **551** is connected to a junction point between the output terminal of the transmitting filter **611** and the input terminal of the receiving filter **612** in the filter **61** with the matching circuit **71** interposed therebetween. The selection terminal **552** is connected to a junction point between the output terminal of the transmitting filter **621** and the input terminal of the receiving filter **622** in the filter **62** with the matching circuit **72** interposed therebetween. The selection terminal **554** is connected to a junction point between the output terminal of the transmitting filter **631** and the input terminal of the receiving filter **632** in the filter **63** with the matching circuit **73** interposed therebetween. The selection terminal **555** is connected to a junction point between the output terminal of the transmitting filter **641** and the input terminal of the receiving filter **642** in the filter **64** with the matching circuit **74** interposed therebetween. The selection terminals **553**, **556** are not connected to any circuit. The fifth switch **55** is, for example, a switch capable of connecting at least one of the plurality of selection terminals **551** to **556** to the common terminal **550**. Here, the fifth switch **55** is, for example, a switch capable of one-to-one connection and one-to-multiple connection.

(50) The fifth switch **55** is, for example, a switch IC. The fifth switch **55** is controlled by, for example, the signal processing circuit **301**. In this case, the fifth switch **55** switches the connection status between the common terminal **550** and the plurality of selection terminals **551** to **556** in accordance with a control signal from the RF signal processing circuit **302** of the signal processing circuit **301**. The fifth switch **55** only has to be configured to, for example, switch the connection status between the common terminal **550** and the plurality of selection terminals **551** to **556** in accordance with a digital control signal input from the signal processing circuit **301**. The fifth switch **55** may be controlled by the controller **20** instead of being controlled by the signal processing circuit **301**.

(51) The sixth switch **56** has a common terminal **560** and a plurality of (for example, five) selection terminals **561** to **565**. The common terminal **560** is connected to the output terminal **87**. The selection terminal **561** is connected to an auxiliary line **802** (described later) of the directional coupler **80**. The selection terminal **562** is connected to an auxiliary line **803** (described later) of the directional coupler **80**. The selection terminal **563** is connected to the input terminal **883** of the plurality of input terminals **881** to **883**. The selection terminal **564** is connected to the input terminal **882** of the plurality of input terminals **881** to **883**. The selection terminal **565** is connected to the input terminal **881** of the plurality of input terminals **881** to **883**.

(52) The sixth switch **56** is, for example, a switch IC. The sixth switch **56** is controlled by, for example, the controller **20**. In this case, the sixth switch **56** is controlled by the controller **20** and switches the connection status between the common terminal **560** and the plurality of selection

terminals **561** to **565**. The sixth switch **56** only has to be configured to, for example, switch the connection status between the common terminal **560** and the plurality of selection terminals **561** to **565** in accordance with a digital control signal input from the controller **20**. The sixth switch **56** may be controlled by the signal processing circuit **301**. In this case, the sixth switch **56** switches the connection status between the common terminal **560** and the plurality of selection terminals **561** to **565** in accordance with a control signal from the RF signal processing circuit **302** of the signal processing circuit **301**.

(53) The low pass filter **60** is connected between the main line **801** (described later) of the directional coupler **80** and the common terminal **550** of the fifth switch **55**. As shown in FIG. **1**, the low pass filter **60** includes, for example, three inductors **601** to **603** and one capacitor **604**. The low pass filter **60** may be an integrated passive device (IPD) including a plurality of inductors and a capacitor.

(54) Although not shown in FIG. **4**, the matching circuit **75** is provided in a signal path between the input terminal of the first power amplifier **11** and the signal input terminal **82**. The matching circuit **75** is a circuit for matching the impedance between the RF signal processing circuit **302** of the signal processing circuit **301** and the first power amplifier **11**. As shown in FIG. **1**, the matching circuit **75** is made up of, for example, one inductor **751**. The matching circuit **75** is not limited to the above configuration and may be made up of, for example, a plurality of inductors and a plurality of capacitors.

(1.2) Structure of Radio-Frequency Module

(55) Next, the structure of the radio-frequency module **100** will be described with reference to FIGS. **1** to **3**.

(56) The radio-frequency module **100** further includes the mounting substrate **9**. The mounting substrate **9** has the first major surface **91** and the second major surface **92** opposite to each other in the thickness direction **D1** of the mounting substrate **9**. The mounting substrate **9** is, for example, a multilayer substrate that includes a plurality of dielectric layers and a plurality of electrically conductive layers. The plurality of dielectric layers and the plurality of electrically conductive layers are laminated in the thickness direction **D1** of the mounting substrate **9**. Each of the plurality of electrically conductive layers is formed in a predetermined pattern determined layer by layer. Each of the plurality of electrically conductive layers includes one or more conductor pattern portions in a plane orthogonal to the thickness direction **D1** of the mounting substrate **9**. The material of each electrically conductive layer is, for example, copper. The plurality of electrically conductive layers includes a ground layer. In the radio-frequency module **100**, the plurality of ground terminals **89** and the ground layer are electrically connected with a via conductor or the like of the mounting substrate **9**, interposed therebetween. The mounting substrate **9** is, for example, a low temperature co-fired ceramics (LTCC) substrate. The mounting substrate **9** is not limited to an LTCC substrate. The mounting substrate **4** may be, for example, a printed circuit board, a high temperature co-fired ceramics (HTCC) substrate, or a resin multilayer substrate.

(57) The mounting substrate **9** is not limited to an LTCC substrate and may be, for example, a wiring structure. The wiring structure is, for example, a multilayer structure. The multilayer structure includes at least one electrically insulating layer and at least one electrically conductive layer. The electrically insulating layer is formed in a predetermined pattern. When the number of the electrically insulating layers is multiple, each of the multiple electrically insulating layers is formed in a predetermined pattern determined layer by layer. The electrically conductive layer is formed in a predetermined pattern different from the predetermined pattern of the electrically insulating layer. When the number of the electrically conductive layers is multiple, each of the multiple electrically conductive layers is formed in a predetermined pattern determined layer by layer. The electrically conductive layer may include one or more rewiring portions. In the wiring structure, of two surfaces facing each other in the thickness direction of the multilayer structure, a first surface is the first major surface **91** of the mounting substrate **9**, and a second surface is the

second major surface **92** of the mounting substrate **9**. The wiring structure may be, for example, an interposer. The interposer may be an interposer using a silicon substrate or may be a substrate made up of multiple layers.

(58) The first major surface **91** and the second major surface **92** of the mounting substrate **9** are spaced apart in the thickness direction **D1** of the mounting substrate **9** and intersect with the thickness direction **D1** of the mounting substrate **9**. The first major surface **91** of the mounting substrate **9** is, for example, orthogonal to the thickness direction **D1** of the mounting substrate **9**. The first major surface **91** may include, for example, the side surface or the like of the conductor pattern portion as a surface not orthogonal to the thickness direction **D1**. The second major surface **92** of the mounting substrate **9** is, for example, orthogonal to the thickness direction **D1** of the mounting substrate **9**. The first major surface **91** may include, for example, the side surface or the like of the conductor pattern portion as a surface not orthogonal to the thickness direction **D1**. The first major surface **91** and the second major surface **92** of the mounting substrate **9** may have minute irregularities or a recessed portion or a protruding portion. When, for example, the first major surface **91** of the mounting substrate **9** has a recessed portion, the inner surface of the recessed portion is included in the first major surface **91**.

(59) In the radio-frequency module **100** according to the first embodiment, circuit components of a first group of the plurality of circuit components are mounted on the first major surface **91** of the mounting substrate **9**. The circuit components of the first group include the first power amplifier **11**, the second power amplifier **12**, the plurality of filters **61** to **65**, the first output matching circuit **31**, the second output matching circuit **32**, the first input matching circuit **41**, the second input matching circuit **42**, the plurality of matching circuits **71** to **75**, and the low pass filter **60**. The phrase “the circuit components are mounted on the first major surface **91** of the mounting substrate **9**” includes not only the structure that the circuit components are disposed on (mechanically connected to) the first major surface **91** of the mounting substrate **9** but also the structure that the circuit components are electrically connected to (appropriate conductor pattern portions of) the mounting substrate **9**.

(60) In the radio-frequency module **100**, circuit components of a second group of the plurality of circuit components are mounted on the second major surface **92** of the mounting substrate **9**. The circuit components of the second group include the first switch **51** to the sixth switch **56**, the first low-noise amplifier **21**, the second low-noise amplifier **22**, the controller **20**, and the directional coupler **80**. The phrase “the circuit components are mounted on the second major surface **92** of the mounting substrate **9**” includes not only the structure that the circuit components are disposed on (mechanically connected to) the second major surface **92** of the mounting substrate **9** but also the structure that the circuit components are electrically connected to (appropriate conductor pattern portions of) the mounting substrate **9**.

(61) FIG. 1 shows the first power amplifier **11**, the plurality of filters **61** to **65**, the first output matching circuit **31**, the first input matching circuit **41**, the plurality of matching circuits **71** to **75**, and the low pass filter **60**, of the circuit components of the first group mounted on the first major surface **91** of the mounting substrate **9**. FIG. 2 shows the first low-noise amplifier **21**, the first switch **51**, the fifth switch **55**, the sixth switch **56**, the controller **20**, and the directional coupler **80**, of the circuit components of the second group mounted on the second major surface **92** of the mounting substrate **9**. In FIG. 4, the filter **65** and the matching circuit **75** are not shown.

(62) The first power amplifier **11** is an IC chip that includes a circuit portion having a first amplifier transistor. As shown in FIG. 1, the first power amplifier **11** is flip-chip mounted on the first major surface **91** of the mounting substrate **9**. In a plan view in the thickness direction **D1** of the mounting substrate **9**, the outer edge of the first power amplifier **11** has a rectangular shape. The first amplifier transistor is, for example, a heterojunction bipolar transistor (HBT). In this case, the IC chip that is the first power amplifier **11** is, for example, a GaAs IC chip. The first amplifier transistor is not limited to a bipolar transistor, such as an HBT, and may be, for example, a field

effect transistor (FET). The FET is, for example, a metal-oxide-semiconductor field effect transistor (MOSFET). The IC chip that is the first power amplifier **11** is not limited to a GaAs IC chip and may be, for example, an Si IC chip, an SiGe IC chip, or a GaN IC chip.

(63) The second power amplifier **12** is an IC chip that includes a circuit portion having a second amplifier transistor. Although not shown in the drawing, the second power amplifier **12** is flip-chip mounted on the first major surface **91** of the mounting substrate **9**. In a plan view in the thickness direction **D1** of the mounting substrate **9**, the outer edge of the second power amplifier **12** has a rectangular shape. The second amplifier transistor is, for example, an HBT. In this case, the IC chip that is the second power amplifier **12** is, for example, a GaAs IC chip. The second amplifier transistor is not limited to a bipolar transistor, such as an HBT, and may be, for example, an FET. The IC chip that is the second power amplifier **12** is not limited to a GaAs IC chip and may be, for example, an Si IC chip, an SiGe IC chip, or a GaN IC chip.

(64) The first low-noise amplifier **21** is, for example, an IC chip that includes a substrate and a circuit portion (IC portion) formed on the substrate. As shown in FIG. 2, the first low-noise amplifier **21** is flip-chip mounted on the second major surface **92** of the mounting substrate **9**. In a plan view in the thickness direction **D1** of the mounting substrate **9**, the outer edge of the first low-noise amplifier **21** has a rectangular shape. The substrate is, for example, a silicon substrate. The circuit portion has a function of amplifying a receiving signal input to the input terminal of the first low-noise amplifier **21**.

(65) The second low-noise amplifier **22** is, for example, an IC chip that includes a substrate and a circuit portion (IC portion) formed on the substrate. Although not shown in the drawing, the second low-noise amplifier **22** is flip-chip mounted on the second major surface **92** of the mounting substrate **9**. In a plan view in the thickness direction **D1** of the mounting substrate **9**, the outer edge of the second low-noise amplifier **22** has a rectangular shape. The substrate is, for example, a silicon substrate. The circuit portion has a function of amplifying a receiving signal input to the input terminal of the second low-noise amplifier **22**.

(66) Each of the transmitting filter **611** and receiving filter **612** of the filter **61** is, for example, a ladder filter and has a plurality of (for example, four) series arm resonators and a plurality of (for example, three) parallel arm resonators. Each of the transmitting filter **611** and the receiving filter **612** is, for example, an acoustic wave filter. The acoustic wave filter is configured such that each of the plurality of series arm resonators and the plurality of parallel arm resonators is made up of an acoustic wave resonator. The acoustic wave filter is, for example, a surface acoustic wave filter that uses surface acoustic waves.

(67) Each of the transmitting filter **621** and receiving filter **622** of the filter **62** is, for example, a ladder filter and has a plurality of (for example, four) series arm resonators and a plurality of (for example, three) parallel arm resonators. Each of the transmitting filter **621** and the receiving filter **622** is, for example, an acoustic wave filter. The acoustic wave filter is configured such that each of the plurality of series arm resonators and the plurality of parallel arm resonators is made up of an acoustic wave resonator. The acoustic wave filter is, for example, a surface acoustic wave filter that uses surface acoustic waves.

(68) Each of the transmitting filter **631** and receiving filter **632** of the filter **63** is, for example, a ladder filter and has a plurality of (for example, four) series arm resonators and a plurality of (for example, three) parallel arm resonators. Each of the transmitting filter **631** and the receiving filter **632** is, for example, an acoustic wave filter. The acoustic wave filter is configured such that each of the plurality of series arm resonators and the plurality of parallel arm resonators is made up of an acoustic wave resonator. The acoustic wave filter is, for example, a surface acoustic wave filter that uses surface acoustic waves.

(69) Each of the transmitting filter **641** and receiving filter **642** of the filter **64** is, for example, a ladder filter and has a plurality of (for example, four) series arm resonators and a plurality of (for example, three) parallel arm resonators. Each of the transmitting filter **641** and the receiving filter

642 is, for example, an acoustic wave filter. The acoustic wave filter is configured such that each of the plurality of series arm resonators and the plurality of parallel arm resonators is made up of an acoustic wave resonator. The acoustic wave filter is, for example, a surface acoustic wave filter that uses surface acoustic waves.

(70) Each of the transmitting filter **651** and receiving filter **652** of the filter **65** is, for example, a ladder filter and has a plurality of (for example, four) series arm resonators and a plurality of (for example, three) parallel arm resonators. Each of the transmitting filter **651** and the receiving filter **652** is, for example, an acoustic wave filter. The acoustic wave filter is configured such that each of a plurality of series arm resonators and a plurality of parallel arm resonators is made up of an acoustic wave resonator. The acoustic wave filter is, for example, a surface acoustic wave filter that uses surface acoustic waves.

(71) In the surface acoustic wave filter, each of the plurality of series arm resonators and the plurality of parallel arm resonators is, for example, a surface acoustic wave (SAW) resonator.

(72) The surface acoustic wave filter includes, for example, a substrate and a circuit portion formed on the substrate. The substrate is, for example, a piezoelectric substrate. The piezoelectric substrate is, for example, a lithium niobate substrate, a lithium tantalate substrate, or a quartz crystal substrate. The circuit portion has a plurality of interdigital transducer electrodes in a one-to-one correspondence with a plurality of series arm resonators and a plurality of interdigital transducer electrodes in a one-to-one correspondence with a plurality of parallel arm resonators.

(73) As shown in FIG. 1, each of the transmitting filter **611** and receiving filter **612** of the filter **61** is mounted on the first major surface **91** of the mounting substrate **9**. In a plan view in the thickness direction **D1** of the mounting substrate **9**, the outer edge of each of the transmitting filter **611** and receiving filter **612** of the filter **61** has a rectangular shape.

(74) As shown in FIG. 1, each of the transmitting filter **621** and receiving filter **622** of the filter **62** is mounted on the first major surface **91** of the mounting substrate **9**. In a plan view in the thickness direction **D1** of the mounting substrate **9**, the outer edge of each of the transmitting filter **621** and receiving filter **622** of the filter **62** has a rectangular shape.

(75) As shown in FIG. 1, each of the transmitting filter **631** and receiving filter **632** of the filter **63** is mounted on the first major surface **91** of the mounting substrate **9**. In a plan view in the thickness direction **D1** of the mounting substrate **9**, the outer edge of each of the transmitting filter **631** and receiving filter **632** of the filter **63** has a rectangular shape.

(76) As shown in FIG. 1, each of the transmitting filter **641** and receiving filter **642** of the filter **64** is mounted on the first major surface **91** of the mounting substrate **9**. In a plan view in the thickness direction **D1** of the mounting substrate **9**, the outer edge of each of the transmitting filter **641** and receiving filter **642** of the filter **64** has a rectangular shape.

(77) As shown in FIG. 1, each of the transmitting filter **651** and receiving filter **652** of the filter **65** is mounted on the first major surface **91** of the mounting substrate **9**. In a plan view in the thickness direction **D1** of the mounting substrate **9**, the outer edge of each of the transmitting filter **651** and receiving filter **652** of the filter **65** has a rectangular shape.

(78) As described above, the first output matching circuit **31** includes two capacitors **311**, **312** and one inductor **313**. As shown in FIG. 1, each of the two capacitors **311**, **312** and one inductor **313** is mounted on the first major surface **91** of the mounting substrate **9**. In a plan view in the thickness direction **D1** of the mounting substrate **9**, the outer edge of each of the two capacitors **311**, **312** and one inductor **313** has a rectangular shape. The first output matching circuit **31** may include, for example, an internal layer inductor provided in the mounting substrate **9**.

(79) As described above, the second output matching circuit **32** includes two capacitors and one inductor. Although not shown in the drawing, each of the two capacitors and one inductor is mounted on the first major surface **91** of the mounting substrate **9**. In a plan view in the thickness direction **D1** of the mounting substrate **9**, the outer edge of each of the two capacitors and one inductor has a rectangular shape. The second output matching circuit **32** may include, for example,

an internal layer inductor provided in the mounting substrate **9**.

(80) As described above, the first input matching circuit **41** includes four inductors **411** to **414** and one capacitor **415**. As shown in FIG. **1**, each of the four inductors **411** to **414** and one capacitor **415** is mounted on the first major surface **91** of the mounting substrate **9**. In a plan view in the thickness direction **D1** of the mounting substrate **9**, the outer edge of each of the four inductors **411** to **414** and one capacitor **415** has a rectangular shape. The first input matching circuit **41** may include, for example, an internal layer inductor provided in the mounting substrate **9**.

(81) As described above, the second input matching circuit **42** includes four inductors and one capacitor. Although not shown in the drawing, each of the four inductors and one capacitor is mounted on the first major surface **91** of the mounting substrate **9**. In a plan view in the thickness direction **D1** of the mounting substrate **9**, the outer edge of each of the four inductors and one capacitor has a rectangular shape. The second input matching circuit **42** may include, for example, an internal layer inductor provided in the mounting substrate **9**.

(82) As described above, the matching circuit **71** includes one inductor **711** and one capacitor **712**. As shown in FIG. **1**, each of the one inductor **711** and the one capacitor **712** is mounted on the first major surface **91** of the mounting substrate **9**. In a plan view in the thickness direction **D1** of the mounting substrate **9**, the outer edge of each of the one inductor **711** and the one capacitor **712** has a rectangular shape. The matching circuit **71** may include, for example, an internal layer inductor provided in the mounting substrate **9**.

(83) As described above, the matching circuit **72** includes one inductor **721** and one capacitor **722**. As shown in FIG. **1**, each of the one inductor **721** and the one capacitor **722** is mounted on the first major surface **91** of the mounting substrate **9**. In a plan view in the thickness direction **D1** of the mounting substrate **9**, the outer edge of each of the one inductor **721** and the one capacitor **722** has a rectangular shape. The matching circuit **72** may include, for example, an internal layer inductor provided in the mounting substrate **9**.

(84) As described above, the matching circuit **73** includes one inductor **731** and one capacitor **732**. As shown in FIG. **1**, each of the one inductor **731** and the one capacitor **732** is mounted on the first major surface **91** of the mounting substrate **9**. In a plan view in the thickness direction **D1** of the mounting substrate **9**, the outer edge of each of the one inductor **731** and the one capacitor **732** has a rectangular shape. The matching circuit **73** may include, for example, an internal layer inductor provided in the mounting substrate **9**.

(85) As described above, the matching circuit **74** includes one inductor **741** and one capacitor **742**. As shown in FIG. **1**, each of the one inductor **741** and the one capacitor **742** is mounted on the first major surface **91** of the mounting substrate **9**. In a plan view in the thickness direction **D1** of the mounting substrate **9**, the outer edge of each of the one inductor **741** and the one capacitor **742** has a rectangular shape. The matching circuit **74** may include, for example, an internal layer inductor provided in the mounting substrate **9**.

(86) As described above, the matching circuit **75** includes one inductor **751**. As shown in FIG. **1**, the one inductor **751** is mounted on the first major surface **91** of the mounting substrate **9**. In a plan view in the thickness direction **D1** of the mounting substrate **9**, the outer edge of the one inductor **751** has a rectangular shape. The matching circuit **75** may include, for example, an internal layer inductor provided in the mounting substrate **9**.

(87) As described above, the low pass filter **60** includes three inductors **601** to **603** and one capacitor **604**. As shown in FIG. **1**, each of the three inductors **601** to **603** and the one capacitor **604** is mounted on the first major surface **91** of the mounting substrate **9**. The outer edge of each of the three inductors **601** to **603** and the one capacitor **604** has a rectangular shape. A cut-off frequency of the low pass filter **60** is, for example, higher than an upper limit of the first frequency band.

(88) As shown in FIG. **2**, the first switch **51** is mounted on the second major surface **92** of the mounting substrate **9**. In a plan view in the thickness direction **D1** of the mounting substrate **9**, the outer edge of the first switch **51** has a rectangular shape. The first switch **51** is, for example, an IC

chip that includes a substrate having a first major surface and a second major surface opposite to each other, and a circuit portion formed on the first major surface side of the substrate. The substrate is, for example, a silicon substrate. The circuit portion includes a plurality of FETs as a plurality of switching elements. Each of the plurality of switching elements is not limited to an FET and may be, for example, a bipolar transistor. The first switch **51** is flip-chip mounted on the second major surface **92** of the mounting substrate **9** such that, of the first major surface and the second major surface of the substrate, the first major surface is on the second major surface **92** side of the mounting substrate **9**.

(89) As shown in FIG. 2, the controller **20** is mounted on the second major surface **92** of the mounting substrate **9**. In a plan view in the thickness direction **D1** of the mounting substrate **9**, the outer edge of the controller **20** has a rectangular shape. The controller **20** is, for example, an IC chip that includes a substrate having a first major surface and a second major surface opposite to each other, and a circuit portion formed on the first major surface side of the substrate. The substrate is, for example, a silicon substrate. The circuit portion includes a control circuit that controls the first power amplifier **11** and the second power amplifier **12** in accordance with a control signal from the signal processing circuit **301**. The controller **20** is flip-chip mounted on the second major surface **92** of the mounting substrate **9** such that, of the first major surface and the second major surface of the substrate, the first major surface is on the second major surface **92** side of the mounting substrate **9**. The controller **20** may be, for example, included in one IC chip together with the first switch **51** and the second switch **52**.

(90) As shown in FIG. 2, in the radio-frequency module **100** according to the first embodiment, an IC chip **13** that includes a first circuit portion **141**, a second circuit portion **142**, and a third circuit portion **143** is mounted on the second major surface **92** of the mounting substrate **9**. The first circuit portion **141** includes the above-described directional coupler **80**. The second circuit portion **142** includes the above-described sixth switch **56**. The third circuit portion **143** includes the above-described fifth switch **55** and a control unit (not shown). The layout of the first circuit portion **141**, the second circuit portion **142**, and the third circuit portion **143** in the IC chip **13** will be described in detail in “(1.3) Layout of Radio-Frequency Module”.

(91) Although not shown in the drawing, the second switch **52**, the third switch **53**, and the fourth switch **54** are mounted on the second major surface **92** of the mounting substrate **9**. In a plan view in the thickness direction **D1** of the mounting substrate **9**, the outer edge of each of the second switch **52**, the third switch **53**, and the fourth switch **54** has a rectangular shape. Each of the second switch **52**, the third switch **53**, and the fourth switch **54** is, for example, an IC chip that includes a substrate having a first major surface and a second major surface opposite to each other, and a circuit portion formed on the first major surface side of the substrate. The substrate is, for example, a silicon substrate. The circuit portion includes a plurality of FETs as a plurality of switching elements. Each of the plurality of switching elements is not limited to an FET and may be, for example, a bipolar transistor. Each of the second switch **52**, the third switch **53**, and the fourth switch **54** is flip-chip mounted on the second major surface **92** of the mounting substrate **9** such that, of the first major surface and the second major surface of the substrate, the first major surface is on the second major surface **92** side of the mounting substrate **9**. The third switch **53** and the fourth switch **54** may be, for example, included in one IC chip together with the first low-noise amplifier **21** and the second low-noise amplifier **22**. The second switch **52** may be included in one IC chip together with the first switch **51**.

(92) As shown in FIG. 2, the plurality of external connection terminals **8** is disposed on the second major surface **92** of the mounting substrate **9**. The phrase “the external connection terminals **8** are disposed on the second major surface **92** of the mounting substrate **9**” includes not only the structure that the external connection terminals **8** are mechanically connected to the second major surface **92** of the mounting substrate **9** but also the structure that the external connection terminals **8** are electrically connected to (appropriate conductor pattern portions of) the mounting substrate **9**.

The material of the plurality of external connection terminals **8** is, for example, metal (for example, copper, copper alloy, or the like). Each of the plurality of external connection terminals **8** is a columnar electrode. The columnar electrode is, for example, a cylindrical electrode. The plurality of external connection terminals **8** is bonded to the conductor pattern portions of the mounting substrate **9** by, for example, solder; however, the configuration is not limited thereto. The plurality of external connection terminals **8** may be bonded by using, for example, electrically conductive adhesive (for example, electrically conductive paste) or may be directly bonded.

(93) As described above, the plurality of external connection terminals **8** includes the antenna terminal **81**, the plurality of signal input terminals **82**, **83**, the plurality of signal output terminals **84**, **85**, the plurality of control terminals **86**, the output terminal **87**, the plurality of input terminals **881**, **882**, **883**, and the plurality of ground terminals **89**. In the radio-frequency module **100** according to the first embodiment, the output terminal **87** and the plurality of input terminals **881**, **882**, **883** make up a plurality of signal terminals. Therefore, in the radio-frequency module **100** according to the first embodiment, the antenna terminal **81**, the plurality of signal input terminals **82**, **83**, the plurality of signal output terminals **84**, **85**, the plurality of control terminals **86**, and the plurality of ground terminals **89** are not included in the plurality of signal terminals. The plurality of ground terminals **89** is electrically connected to the ground layer of the mounting substrate **9**. The ground layer is a circuit ground of the radio-frequency module **100**. The plurality of circuit components of the radio-frequency module **100** includes circuit components electrically connected to the ground layer. Hereinafter, when the plurality of input terminals **881**, **882**, **883** is described separately, the plurality of input terminals **881**, **882**, **883** may be respectively referred to as the first input terminal **881**, the second input terminal **882**, and the third input terminal **883**.

(94) The radio-frequency module **100** further includes a first resin layer **105**. The first resin layer **105** covers each of the circuit components of the first group, mounted on the first major surface **91** of the mounting substrate **9**. More specifically, the first resin layer **105** covers the outer peripheral surface of each of the circuit components of the first group. The first resin layer **105** covers the major surface on the opposite side to the mounting substrate **9** side in each of the circuit components of the first group. Of the circuit components of the first group, in the first power amplifier **11**, the second power amplifier **12**, the first output matching circuit **31**, the second output matching circuit **32**, the first input matching circuit **41**, the second input matching circuit **42**, the plurality of matching circuits **71** to **75**, and the low pass filter **60**, the first resin layer **105** is also disposed between each circuit component and the first major surface **91** of the mounting substrate **9** in the thickness direction **D1** of the mounting substrate **9**. The first resin layer **105** includes resin (for example, epoxy resin). The first resin layer **105** may include a filler in addition to resin. In the specification, the phrase “the major surface of the circuit component” means a surface of the circuit component on the opposite side to the mounting substrate **9** side. In the specification, the phrase “the outer peripheral surface of the circuit component” means a surface of the circuit component along the thickness direction **D1** of the mounting substrate **9** from the outer edge of the major surface of the circuit component.

(95) The radio-frequency module **100** further includes a second resin layer **107** in addition to the first resin layer **105** disposed on the first major surface **91** of the mounting substrate **9**. The second resin layer **107** covers the circuit components of the second group, mounted on the second major surface **92** of the mounting substrate **9**, and the outer peripheral surface of each of the plurality of external connection terminals **8**. The second resin layer **107** includes resin (for example, epoxy resin). The second resin layer **107** may include a filler in addition to resin. The material of the second resin layer **107** may be the same material as the material of the first resin layer **105** or may be a different material.

(96) The second resin layer **107** may be formed so as to expose the major surface on the opposite side to the mounting substrate **9** side in each of the circuit components of the second group mounted on the second major surface **92** of the mounting substrate **9**.

(97) The radio-frequency module **100** further includes the electrically conductive layer **106**. The electrically conductive layer **106** has an electrical conductivity. The electrically conductive layer **106** is provided for the purpose of electromagnetic shielding between the inside and outside of the radio-frequency module **100**. The electrically conductive layer **106** has a multilayer structure such that a plurality of metal layers is laminated; however, the configuration is not limited to the multilayer structure. The electrically conductive layer **106** may have a single metal layer. The metal layer includes one or more types of metals. The electrically conductive layer **106** covers a major surface **151** of the first resin layer **105** on an opposite side to the mounting substrate **9** side, an outer peripheral surface **153** of the first resin layer **105**, and an outer peripheral surface **93** of the mounting substrate **9**. The electrically conductive layer **106** also covers an outer peripheral surface **173** of the second resin layer **107**. The electrically conductive layer **106** is in contact with at least part of the outer peripheral surface of the ground layer of the mounting substrate **9**. Thus, the potential of the electrically conductive layer **106** can be set to the same potential as the potential of the ground layer.

(1.3) Layout of Radio-Frequency Module

(98) Next, the layout of the radio-frequency module **100** according to the first embodiment will be described with reference to FIGS. **1** to **3**.

(99) As described above, in the radio-frequency module **100** according to the first embodiment, circuit components of the first group are mounted on the first major surface **91** of the mounting substrate **9**. In FIG. **1**, of the circuit components of the first group, the first power amplifier **11**, the first output matching circuit **31**, the first input matching circuit **41**, the low pass filter **60**, the plurality of filters **61** to **65**, and the plurality of matching circuits **71** to **75** are shown.

(100) In FIG. **1**, the first output matching circuit **31**, the first power amplifier **11**, and the matching circuit **75** are arranged along a width direction (short-side direction) **D2** of the mounting substrate **9**. In the first output matching circuit **31**, two capacitors **311**, **312** and one inductor **313** are arranged along the width direction **D2** of the mounting substrate **9**. In the radio-frequency module **100** according to the first embodiment, the width direction **D2** of the mounting substrate **9** is a first direction.

(101) In FIG. **1**, of the plurality of filters **61** to **65**, the four filters **61** to **64** are arranged along a longitudinal direction **D3** of the mounting substrate **9**. In FIG. **1**, of the plurality of filters **61** to **65**, the two filters **64**, **65** are arranged along the width direction **D2** of the mounting substrate **9**. In the filter **61**, the transmitting filter **611** and the receiving filter **612** are arranged along the width direction **D2** of the mounting substrate **9**. In the filter **62**, the transmitting filter **621** and the receiving filter **622** are arranged along the width direction **D2** of the mounting substrate **9**. In the filter **63**, the transmitting filter **631** and the receiving filter **632** are arranged along the width direction **D2** of the mounting substrate **9**. In the filter **64**, the transmitting filter **641** and the receiving filter **642** are arranged along the width direction **D2** of the mounting substrate **9**. In the filter **65**, the transmitting filter **651** and the receiving filter **652** are arranged along the width direction **D2** of the mounting substrate **9**. In the radio-frequency module **100** according to the first embodiment, the longitudinal direction **D3** of the mounting substrate **9** is a second direction.

(102) In FIG. **1**, the plurality of matching circuits **71** to **74** are arranged along the longitudinal direction **D3** of the mounting substrate **9**. In addition, in the matching circuit **71**, the inductor **711** and the capacitor **712** are arranged along the width direction **D2** of the mounting substrate **9**. In the matching circuit **72**, the inductor **721** and the capacitor **722** are arranged along the width direction **D2** of the mounting substrate **9**. In the matching circuit **73**, the inductor **731** and the capacitor **732** are arranged along the width direction **D2** of the mounting substrate **9**. In the matching circuit **74**, the inductor **741** and the capacitor **742** are arranged along the width direction **D2** of the mounting substrate **9**.

(103) In FIG. **1**, in the width direction **D2** of the mounting substrate **9**, the first input matching circuit **41** is disposed on an opposite side to the plurality of matching circuits **71** to **74** side with

respect to the plurality of filters **61** to **63**. In the first input matching circuit **41**, four inductors **411** to **414** and one capacitor **415** are arranged along the longitudinal direction **D3** of the mounting substrate **9**. In FIG. **1**, in the width direction **D2** of the mounting substrate **9**, the low pass filter **60** is disposed on an opposite side to the plurality of filters **61** to **63** side with respect to the plurality of matching circuits **71** to **74**. In the low pass filter **60**, three inductors **601** to **603** and one capacitor **604** are arranged along the longitudinal direction **D3** of the mounting substrate **9**.

(104) As described above, in the radio-frequency module **100** according to the first embodiment, circuit components of the second group are mounted on the second major surface **92** of the mounting substrate **9**. FIG. **2** shows the controller **20**, the first low-noise amplifier **21**, the first switch **51**, and the IC chip **13**, of the circuit components of the second group. As described above, the IC chip **13** includes the fifth switch **55**, the sixth switch **56**, the directional coupler **80**, and the control unit (not shown).

(105) As described above, in the radio-frequency module **100** according to the first embodiment, the plurality of external connection terminals **8** is disposed on the second major surface **92** of the mounting substrate **9**. As described above, the plurality of external connection terminals **8** includes the antenna terminal **81**, the two signal input terminals **82**, **83** (see FIG. **4**), the two signal output terminals **84**, **85** (see FIG. **4**), the four control terminals **86** (see FIG. **4**), the output terminal **87**, the three input terminals **881**, **882**, **883**, and the plurality of ground terminals **89**.

(106) In the radio-frequency module **100** according to the first embodiment, the mounting substrate **9** is formed in a rectangular shape in a plan view in the thickness direction **D1** of the mounting substrate **9**. More specifically, the mounting substrate **9** is formed in a rectangular shape of which the size in the longitudinal direction **D3** (the size in the right and left direction in FIG. **2**) is longer than the size in the width direction **D2** (the size in the up and down direction in FIG. **2**). As shown in FIGS. **1** and **2**, the mounting substrate **9** has a first side **94** and a second side **95** orthogonal to each other. As shown in FIG. **2**, the mounting substrate **9** has four regions (a first region **921**, a second region **922**, a third region **923**, and a fourth region **924**) divided by a first line **L1** and a second line **L2**. The first line **L1** is a straight line that passes through the center **C1** of the mounting substrate **9** and that extends along the first side **94** of the mounting substrate **9**. The second line **L2** is a straight line that passes through the center **C1** of the mounting substrate **9** and that extends along the second side **95** of the mounting substrate **9**. The phrase “the center **C1** of the mounting substrate **9**” means a point located right at the center of the mounting substrate **9** in a plan view in the thickness direction **D1** of the mounting substrate **9**. The word “orthogonal” includes not only a state where the angle between two is strictly 90 degrees but also a state where the angle between two falls within a range including an intersection with which effects are substantially obtained (for example, ± 5 degrees). The first switch **51** is disposed in the first region **921**. The IC chip **13** is disposed in the second region **922**. The first low-noise amplifier **21** is disposed in the third region **923**. The controller **20** is disposed in the fourth region **924**.

(107) At least one ground terminal **89** is disposed in each of the first region **921**, the third region **923**, and the fourth region **924**. The antenna terminal **81**, the output terminal **87**, the three input terminals **881**, **882**, **883**, and the plurality of ground terminals **89** are disposed in the second region **922**. In FIG. **2**, the antenna terminal **81**, the second input terminal **882**, and the output terminal **87** are disposed in a line (hereinafter, referred to as “first line”) along the width direction **D2** of the mounting substrate **9**. In the first line, the two ground terminals **89** are disposed between the antenna terminal **81** and the second input terminal **882**. In the first line, the one ground terminal **89** is disposed between the second input terminal **882** and the output terminal **87**. In other words, in the radio-frequency module **100** according to the first embodiment, the antenna terminal **81**, the second input terminal **882**, and the output terminal **87**, arranged in the first line, are not adjacent to each other in the width direction (first direction) **D2** of the mounting substrate **9**. The phrase “the antenna terminal **81** and the second input terminal **882** are not adjacent to each other in the width direction **D2** of the mounting substrate **9**” means that, in a plan view in the thickness direction **D1**

of the mounting substrate **9**, another terminal (ground terminal **89**) is present between the antenna terminal **81** and the second input terminal **882** in the width direction **D2** of the mounting substrate **9** and the antenna terminal **81** and the second input terminal **882** are not adjacent to each other. The phrase “the second input terminal **882** and the output terminal **87** are not adjacent to each other in the width direction **D2** of the mounting substrate **9**” means that, in a plan view in the thickness direction **D1** of the mounting substrate **9**, another terminal (ground terminal **89**) is present between the second input terminal **882** and the output terminal **87** in the width direction **D2** of the mounting substrate **9** and the second input terminal **882** and the output terminal **87** are not adjacent to each other. Each of the antenna terminal **81**, the second input terminal **882**, and the output terminal **87** is adjacent to the ground terminal **89** in the longitudinal direction **D3** of the mounting substrate **9**. In other words, each of the antenna terminal **81**, the second input terminal **882**, and the output terminal **87** is also not adjacent to each other in the longitudinal direction **D3** of the mounting substrate **9**.

(108) In FIG. 2, the first input terminal **881** and the third input terminal **883** are disposed in a line (hereinafter, referred to as “second line”) along the width direction **D2** of the mounting substrate **9**. In the second line, the one ground terminal **89** is disposed between the first input terminal **881** and the third input terminal **883**. In other words, in the radio-frequency module **100** according to the first embodiment, the first input terminal **881** and the third input terminal **883**, arranged in the second line, are not adjacent to each other in the width direction **D2** of the mounting substrate **9**. The phrase “the first input terminal **881** and the third input terminal **883** are not adjacent to each other in the width direction **D2** of the mounting substrate **9**” means that, in a plan view in the thickness direction **D1** of the mounting substrate **9**, another terminal (ground terminal **89**) is present between the first input terminal **881** and the third input terminal **883** in the width direction **D2** of the mounting substrate **9** and the first input terminal **881** and the third input terminal **883** are not adjacent to each other. In the second line, the two ground terminals **89** are disposed on an opposite side to the third input terminal **883** side with respect to the first input terminal **881**. In the second line, the one ground terminal **89** is disposed on an opposite side to the first input terminal **881** side with respect to the third input terminal **883**. Each of the first input terminal **881** and the third input terminal **883** is adjacent to the ground terminal **89** in the longitudinal direction **D3** of the mounting substrate **9**. In other words, each of the first input terminal **881** and the third input terminal **883** is also not adjacent to each other in the longitudinal direction **D3** of the mounting substrate **9**.

(109) As described above, in the radio-frequency module **100** according to the first embodiment, a terminal closest to each of the first input terminal **881**, the second input terminal **882**, the third input terminal **883**, and the output terminal **87** is the ground terminal **89**. In other words, the plurality of signal terminals (the input terminals **881** to **883** and the output terminal **87**) is disposed so as not to be adjacent to each other in each of the first direction (width direction **D2**) and the second direction (longitudinal direction **D3**) that intersect with the thickness direction **D1** of the mounting substrate **9**. Thus, it is possible to suppress jump of a signal between the terminals. As described above, in the radio-frequency module **100** according to the first embodiment, the output terminal **87** is disposed at a location farthest from the antenna terminal **81** as compared to any of the first input terminal **881**, the second input terminal **882**, and the third input terminal **883** in the width direction (first direction) **D2** of the mounting substrate **9**. Thus, it is possible to suppress jump of a signal to be received or transmitted via the antenna terminal **81**, to the output terminal **87**.

(110) As shown in FIG. 2, in the radio-frequency module **100** according to the first embodiment, the second circuit portion **142** and the third circuit portion **143**, included in the IC chip **13**, are arranged along the longitudinal direction **D3** of the mounting substrate **9**. More specifically, the third circuit portion **143** is disposed on an opposite side to the plurality of signal terminals (the input terminals **881** to **883** and the output terminal **87**) side with respect to the second circuit portion **142** in the longitudinal direction **D3** of the mounting substrate **9**. As shown in FIG. 2, in the radio-frequency module **100** according to the first embodiment, the first circuit portion **141** and the

second circuit portion **142**, included in the IC chip **13**, are disposed along the width direction **D2** of the mounting substrate **9**. In other words, in the radio-frequency module **100** according to the first embodiment, the third circuit portion **143** including the fifth switch **55** is disposed on an opposite side to the plurality of signal terminals side with respect to the first circuit portion **141** including the directional coupler **80** in the longitudinal direction **D3** of the mounting substrate **9**. Thus, it is possible to suppress jump of a signal between the plurality of signal terminals and the fifth switch **55**. As described above, in the radio-frequency module **100** according to the first embodiment, the plurality of signal terminals (the input terminals **881** to **883** and the output terminal **87**), the directional coupler **80** (first circuit portion **141**), and the fifth switch **55** (third circuit portion **143**) are disposed in the same region (second region **922**).

(111) As shown in FIG. 3, in the radio-frequency module **100** according to the first embodiment, the inductor **601** of the low pass filter **60** and the directional coupler **80** included in the IC chip **13** overlap each other in a plan view in the thickness direction **D1** of the mounting substrate **9**. More specifically, in a plan view in the thickness direction **D1** of the mounting substrate **9**, part of the inductor **601** and part of the directional coupler **80** overlap each other. In a plan view in the thickness direction **D1** of the mounting substrate **9**, part of the inductor **601** and the whole of the directional coupler **80** may overlap each other, the whole of the inductor **601** and part of the directional coupler **80** may overlap each other, or the whole of the inductor **601** and the whole of the directional coupler **80** may overlap each other. In short, the phrase “in a plan view in the thickness direction **D1** of the mounting substrate **9**, the inductor **601** and the directional coupler **80** overlap each other” means that, in a plan view in the thickness direction **D1** of the mounting substrate **9**, at least part of the inductor **601** and at least part of the directional coupler **80** overlap each other. Thus, it is possible to shorten the wiring length between the inductor **601** and the directional coupler **80**, with the result that it is possible to suppress the degradation of the characteristics of the radio-frequency module **100** due to the wiring length.

(112) As shown in FIG. 3, in the radio-frequency module **100** according to the first embodiment, the capacitor **604** of the low pass filter **60** and the fifth switch **55** included in the IC chip **13** overlap each other in a plan view in the thickness direction **D1** of the mounting substrate **9**. More specifically, in a plan view in the thickness direction **D1** of the mounting substrate **9**, part of the capacitor **604** and part of the fifth switch **55** overlap each other. In a plan view in the thickness direction **D1** of the mounting substrate **9**, part of the capacitor **604** and the whole of the fifth switch **55** may overlap each other, the whole of the capacitor **604** and part of the fifth switch **55** may overlap each other, or the whole of the capacitor **604** and the whole of the fifth switch **55** may overlap each other. In short, the phrase “in a plan view in the thickness direction **D1** of the mounting substrate **9**, the capacitor **604** and the fifth switch **55** overlap each other” means that, in a plan view in the thickness direction **D1** of the mounting substrate **9**, at least part of the capacitor **604** and at least part of the fifth switch **55** overlap each other. Thus, it is possible to shorten the wiring length between the capacitor **604** and the fifth switch **55**, with the result that it is possible to suppress the degradation of the characteristics of the radio-frequency module **100** due to the wiring length.

(113) As shown in FIG. 3, in the radio-frequency module **100** according to the first embodiment, the transmitting filter **611** of the filter **61** and the fifth switch **55** overlap each other in a plan view in the thickness direction **D1** of the mounting substrate **9**. More specifically, in a plan view in the thickness direction **D1** of the mounting substrate **9**, part of the transmitting filter **611** and part of the fifth switch **55** overlap each other. In a plan view in the thickness direction **D1** of the mounting substrate **9**, part of the transmitting filter **611** and the whole of the fifth switch **55** may overlap each other, the whole of the transmitting filter **611** and part of the fifth switch **55** may overlap each other, or the whole of the transmitting filter **611** and the whole of the fifth switch **55** may overlap each other. Thus, it is possible to shorten the wiring length between the transmitting filter **611** and the fifth switch **55**, with the result that it is possible to suppress the degradation of the characteristics of

the radio-frequency module **100** due to the wiring length.

(1.4) Circuit Configuration of Directional Coupler

(114) Next, the circuit configuration of the directional coupler **80** will be described with reference to FIGS. **4** and **5**.

(115) As shown in FIGS. **4** and **5**, the directional coupler (coupler) **80** has the main line **801** and the plurality of (for example, two) auxiliary lines **802**, **803**. The directional coupler **80** further has a plurality of (for example, six) terminals **806** to **811**. Hereinafter, when the plurality of auxiliary lines **802**, **803** is described separately, the plurality of auxiliary line **802**, **803** may be respectively referred to as the first auxiliary line **802** and the second auxiliary line **803**.

(116) As shown in FIG. **4**, the main line **801** is provided in the transmitting path T1 between the antenna terminal **81** and the signal input terminals **82**, **83**. More specifically, as shown in FIGS. **4** and **5**, the main line **801** is provided in the signal path between the antenna terminal **81** and the low pass filter **60** in the transmitting path T1. The “transmitting path T1” is a signal path for propagating a transmitting signal (radio-frequency signal) to be transmitted to the outside via the antenna **310**. The transmitting path T1 includes a first transmitting path T11, a second transmitting path T12, a third transmitting path T13, and a fourth transmitting path T14. The first transmitting path T11 is a path that passes through the signal input terminal **82**, the first power amplifier **11**, the first switch **51**, the transmitting filter **611** of the filter **61**, the matching circuit **71**, the fifth switch **55**, the low pass filter **60**, the main line **801** of the directional coupler **80**, and the antenna terminal **81**. The second transmitting path T12 is a path that passes through the signal input terminal **82**, the first power amplifier **11**, the first switch **51**, the transmitting filter **621** of the filter **62**, the matching circuit **72**, the fifth switch **55**, the low pass filter **60**, the main line **801** of the directional coupler **80**, and the antenna terminal **81**. The third transmitting path T13 is a path that passes through the signal input terminal **83**, the second power amplifier **12**, the second switch **52**, the transmitting filter **631** of the filter **63**, the matching circuit **73**, the fifth switch **55**, the low pass filter **60**, the main line **801** of the directional coupler **80**, and the antenna terminal **81**. The fourth transmitting path T14 is a path that passes through the signal input terminal **83**, the second power amplifier **12**, the second switch **52**, the transmitting filter **641** of the filter **64**, the matching circuit **74**, the fifth switch **55**, the low pass filter **60**, the main line **801** of the directional coupler **80**, and the antenna terminal **81**. The main line **801** is connected to the antenna terminal **81** with the terminal **806** interposed therebetween and is connected to the low pass filter **60** with the terminal **807** interposed therebetween.

(117) The first auxiliary line **802** is electromagnetically coupled to the main line **801**. The first end of the first auxiliary line **802** is connected to a first termination circuit **804** with the terminal **808** interposed therebetween. The first termination circuit **804** is a circuit for terminating the first auxiliary line **802**. The first termination circuit **804** includes, for example, a digital tunable capacitor (not shown). The second end of the first auxiliary line **802** is connected to the selection terminal **561** of the sixth switch **56** with the terminal **809** interposed therebetween.

(118) The second auxiliary line **803** is electromagnetically coupled to the main line **801**. The second auxiliary line **803** is disposed on an opposite side to the first auxiliary line **802** side with respect to the main line **801**. Thus, isolation between the first auxiliary line **802** and the second auxiliary line **803** is improved. The first end of the second auxiliary line **803** is connected to a second termination circuit **805** with the terminal **810** interposed therebetween. The second termination circuit **805** is a circuit for terminating the second auxiliary line **803**. The second termination circuit **805** includes, for example, a digital tunable capacitor (not shown). The second end of the second auxiliary line **803** is connected to the selection terminal **562** of the sixth switch **56** with the terminal **811** interposed therebetween. The directional coupler **80** includes not only the main line **801**, the first auxiliary line **802**, the second auxiliary line **803**, and the terminals **806** to **811** but also a first wiring portion connecting the main line **801** with the terminals **806**, **807**, a second wiring portion connecting the first auxiliary line **802** with the terminals **808**, **809**, and a

third wiring portion connecting the second auxiliary line **803** with the terminals **810**, **811**.

(119) The low pass filter **60** is provided in at least one of the transmitting path **T1** and the receiving path **R1** between the antenna terminal **81** and the signal output terminals **84**, **85**. In the radio-frequency module **100** according to the first embodiment, the low pass filter **60** is provided in each of the transmitting path **T1** and the receiving path **R1**. More specifically, as shown in FIGS. **4** and **5**, the low pass filter **60** is provided in the signal path between the directional coupler **80** and the fifth switch **55** in the transmitting path **T1** and the receiving path **R1**. The “receiving path **R1**” is a signal path for propagating a receiving signal (radio-frequency signal) to be received from the outside via the antenna **310**. The receiving path **R1** includes a first receiving path **R11**, a second receiving path **R12**, a third receiving path **R13**, and a fourth receiving path **R14**. The first receiving path **R11** is a path that passes through the antenna terminal **81**, the main line **801** of the directional coupler **80**, the low pass filter **60**, the fifth switch **55**, the matching circuit **71**, the receiving filter **612** of the filter **61**, the third switch **53**, the first input matching circuit **41**, the first low-noise amplifier **21**, and the signal output terminal **84**. The second receiving path **R12** is a path that passes through the antenna terminal **81**, the main line **801** of the directional coupler **80**, the low pass filter **60**, the fifth switch **55**, the matching circuit **72**, the receiving filter **622** of the filter **62**, the third switch **53**, the first input matching circuit **41**, the first low-noise amplifier **21**, and the signal output terminal **84**. The third receiving path **R13** is a path that passes through the antenna terminal **81**, the main line **801** of the directional coupler **80**, the low pass filter **60**, the fifth switch **55**, the matching circuit **73**, the receiving filter **632** of the filter **63**, the fourth switch **54**, the second input matching circuit **42**, the second low-noise amplifier **22**, and the signal output terminal **85**. The fourth receiving path **R14** is a path that passes through the antenna terminal **81**, the main line **801** of the directional coupler **80**, the low pass filter **60**, the fifth switch **55**, the matching circuit **74**, the receiving filter **642** of the filter **64**, the fourth switch **54**, the second input matching circuit **42**, the second low-noise amplifier **22**, and the signal output terminal **85**. As described above, the signal path between the antenna terminal **81** and the common terminal **550** of the fifth switch **55** is included in the transmitting path **T1** and is also included in the receiving path **R1**.

(120) As described above, the radio-frequency module **100** according to the first embodiment includes the plurality of input terminals **881**, **882**, **883**. The plurality of input terminals **881**, **882**, **883** is terminals for inputting detection signals from other radio-frequency modules **101** to **103** to the radio-frequency module **100**. More specifically, the first input terminal **881** is a terminal for inputting a detection signal from the radio-frequency module **101**. The second input terminal **882** is a terminal for inputting a detection signal from the radio-frequency module **102**. The third input terminal **883** is a terminal for inputting a detection signal from the radio-frequency module **103**.

(121) As shown in FIG. **5**, the radio-frequency module **101** includes a switch **57**, a directional coupler **66**, an antenna terminal **111**, and an output terminal **112**. The switch **57** has a common terminal **570** and a plurality of (for example, five) selection terminals **571** to **575**. The common terminal **570** is connected to the first end of a main line **661** of the directional coupler **66**. The second end of the main line **661** is connected to the antenna terminal **111**. The directional coupler **66** has the main line **661** and an auxiliary line **662**. The auxiliary line **662** is electromagnetically coupled to the main line **661**. The first end of the auxiliary line **662** is connected to a termination circuit **663**. The second end of the auxiliary line **662** is connected to the output terminal **112**. The auxiliary line **662** propagates (outputs) a detection signal corresponding to a radio-frequency signal that passes through the main line **661**. A detection signal that propagates through the auxiliary line **662** is input to the radio-frequency module **100** via the output terminal **112** and the first input terminal **881**.

(122) As shown in FIG. **5**, the radio-frequency module **102** includes a switch **58**, a directional coupler **67**, an antenna terminal **121**, and an output terminal **122**. The switch **58** has a common terminal **580** and a plurality of (for example, five) selection terminals **581** to **585**. The common terminal **580** is connected to the first end of a main line **671** of the directional coupler **67**. The

second end of the main line **671** is connected to the antenna terminal **121**. The directional coupler **67** has the main line **671** and an auxiliary line **672**. The auxiliary line **672** is electromagnetically coupled to the main line **671**. The first end of the auxiliary line **672** is connected to a termination circuit **673**. The second end of the auxiliary line **672** is connected to the output terminal **122**. The auxiliary line **672** propagates (outputs) a detection signal corresponding to a radio-frequency signal that passes through the main line **671**. A detection signal that propagates through the auxiliary line **672** is input to the radio-frequency module **100** via the output terminal **122** and the second input terminal **882**.

(123) As shown in FIG. 5, the radio-frequency module **103** includes a switch **59**, a directional coupler **68**, an antenna terminal **131**, and an output terminal **132**. The switch **59** has a common terminal **590** and a plurality of (for example, five) selection terminals **591** to **595**. The common terminal **590** is connected to the first end of a main line **681** of the directional coupler **68**. The second end of the main line **681** is connected to the antenna terminal **131**. The directional coupler **68** has the main line **681** and an auxiliary line **682**. The auxiliary line **682** is electromagnetically coupled to the main line **681**. The first end of the auxiliary line **682** is connected to a termination circuit **683**. The second end of the auxiliary line **682** is connected to the output terminal **132**. The auxiliary line **682** propagates (outputs) a detection signal corresponding to a radio-frequency signal that passes through the main line **681**. A detection signal that propagates through the auxiliary line **682** is input to the radio-frequency module **100** via the output terminal **132** and the third input terminal **883**.

(124) In the radio-frequency module **100** according to the first embodiment, when the common terminal **560** is connected to the selection terminal **561** in the sixth switch **56**, a detection signal (first detection signal) that propagates through the first auxiliary line **802** can be output to a detector (not shown) provided outside via the output terminal **87**. In the radio-frequency module **100** according to the first embodiment, when the common terminal **560** is connected to the selection terminal **562** in the sixth switch **56**, a detection signal (second detection signal) that propagates through the second auxiliary line **803** can be output to the detector via the output terminal **87**. In the radio-frequency module **100** according to the first embodiment, when the common terminal **560** is connected to the selection terminal **563** in the sixth switch **56**, a detection signal from the radio-frequency module **103** can be output to the detector via the output terminal **87**. In the radio-frequency module **100** according to the first embodiment, when the common terminal **560** is connected to the selection terminal **564** in the sixth switch **56**, a detection signal from the radio-frequency module **102** can be output to the detector via the output terminal **87**. In the radio-frequency module **100** according to the first embodiment, when the common terminal **560** is connected to the selection terminal **565** in the sixth switch **56**, a detection signal from the radio-frequency module **101** can be output to the detector via the output terminal **87**.

(2) Effects

(2.1) Radio-Frequency Module

(125) The radio-frequency module **100** according to the first embodiment includes the antenna terminal **81**, the signal input terminals **82**, **83**, the signal output terminals **84**, **85**, the mounting substrate **9**, the chip inductor **601**, and the directional coupler **80**. A transmitting signal is input to the signal input terminals **82**, **83**. A receiving signal is output from the signal output terminals **84**, **85**. The mounting substrate **9** has the first major surface **91** and the second major surface **92** opposite to each other. The chip inductor **601** is disposed on the first major surface **91** of the mounting substrate **9**. The chip inductor **601** is provided in at least one of the transmitting path **T1** and the receiving path **R1**. The transmitting path **T1** is a path between the antenna terminal **81** and the signal input terminals **82**, **83**. The receiving path **R1** is a path between the antenna terminal **81** and the signal output terminals **84**, **85**. The directional coupler **80** is mounted on the second major surface **92** of the mounting substrate **9**, and at least part (for example, the main line **801**) of the directional coupler **80** is provided in the transmitting path **T1**.

(126) In the radio-frequency module **100** according to the first embodiment, as described above, the chip inductor **601** is mounted on the first major surface **91** of the mounting substrate **9**, and the directional coupler **80** is mounted on the second major surface **92** of the mounting substrate **9**. Thus, in comparison with the case where both a chip inductor and a directional coupler are mounted on a first major surface of a mounting substrate, it is possible to reduce the size in a direction that intersects with the thickness direction **D1** of the mounting substrate **9**. In the radio-frequency module **100** according to the first embodiment, when a ground layer is provided in the mounting substrate **9**, isolation between the chip inductor **601** and the directional coupler **80** is further improved. Thus, it is possible to suppress jump of a signal between the chip inductor **601** and the directional coupler **80**, with the result that it is possible to suppress a decrease in detection accuracy. In other words, with the radio-frequency module **100** according to the first embodiment, it is possible to reduce the size and to suppress a decrease in detection accuracy.

(127) As described above, in the radio-frequency module **100** according to the first embodiment, the chip inductor **601** and the directional coupler **80** overlap each other in a plan view in the thickness direction **D1** of the mounting substrate **9**. Thus, it is possible to shorten the wiring length between the chip inductor **601** and the directional coupler **80**, with the result that it is possible to suppress the degradation of the characteristics of the radio-frequency module **100** due to the wiring length.

(128) As described above, in the radio-frequency module **100** according to the first embodiment, the first input terminal **881**, the second input terminal **882**, the third input terminal **883**, and the output terminal **87** are not adjacent to each other in each of the width direction **D2** and the longitudinal direction **D3** of the mounting substrate **9**. Thus, isolation between the signal terminals is improved, with the result that jump of a signal between the signal terminals is suppressed. In the radio-frequency module **100** according to the first embodiment, the ground terminal **89** is disposed between the signal terminals, so isolation between the signal terminals is further improved.

(129) As described above, in the radio-frequency module **100** according to the first embodiment, the output terminal **87** is disposed at a location farthest from the antenna terminal **81** in the width direction (first direction) **D2** of the mounting substrate **9**, of the plurality of signal terminals. Thus, isolation between the antenna terminal **81** and the output terminal **87** is improved, with the result that jump of a signal to be transmitted or received via the antenna terminal **81**, to the output terminal **87** is suppressed.

(130) As described above, in the radio-frequency module **100** according to the first embodiment, the plurality of input terminals **881** to **883** and the output terminal **87** are arranged in two lines. Thus, in comparison with the case where the plurality of input terminals and the output terminal are arranged in a line, the wiring length to the sixth switch **56** is shortened, with the result that the degradation of the characteristics of the radio-frequency module **100** is suppressed.

(2.2) Communication Device

(131) The communication device **300** according to the first embodiment includes the above-described radio-frequency module **100** and the signal processing circuit **301**. The signal processing circuit **301** is connected to the radio-frequency module **100**.

(132) Since the communication device **300** according to the first embodiment includes the radio-frequency module **100**, it is possible to reduce the size and to suppress a decrease in detection accuracy.

(133) A plurality of electronic components that make up the signal processing circuit **301** may be mounted on, for example, the above-described circuit board or may be mounted on a circuit board (second circuit board) different from the circuit board (first circuit board) on which the radio-frequency module **100** is mounted.

(3) Modification

(134) A radio-frequency module **100a** according to a modification of the first embodiment will be described with reference to FIG. **6**. For the radio-frequency module **100a** according to the

modification, like reference signs denote component elements similar to those of the radio-frequency module **100** according to the first embodiment, and the description is omitted.

(135) The radio-frequency module **100a** according to the modification differs from the radio-frequency module **100** according to the first embodiment in that the plurality of external connection terminals **8** is ball bumps. The radio-frequency module **100a** according to the modification differs from the radio-frequency module **100** according to the first embodiment in that the radio-frequency module **100a** according to the modification does not include the second resin layer **107** of the radio-frequency module **100** according to the first embodiment. The radio-frequency module **100a** according to the modification may include an underfill portion provided between the IC chip **13** mounted on the second major surface **92** of the mounting substrate **9** and the second major surface **92** of the mounting substrate **9**.

(136) The material of the ball bump that makes up each of the plurality of external connection terminals **8** is, for example, gold, copper, solder, or the like.

(137) The plurality of external connection terminals **8** may mixedly include the external connection terminals **8** each made up of a ball bump and the external connection terminals **8** each made up of a columnar electrode.

(138) With the radio-frequency module **100a** according to the modification, as well as the radio-frequency module **100** according to the first embodiment, it is possible to reduce the size and to suppress a decrease in detection accuracy.

Second Embodiment

(139) A radio-frequency module **100b** according to a second embodiment will be described with reference to FIG. 7. For the radio-frequency module **100b** according to the second embodiment, like reference signs denote component elements similar to those of the radio-frequency module **100** according to the first embodiment, and the description is omitted.

(140) The radio-frequency module **100b** according to the second embodiment differs from the radio-frequency module **100** according to the first embodiment in that only detection signals (the first detection signal and the second detection signal) from the directional coupler **80** of the radio-frequency module **100b** are output to the detector.

(1) Radio-Frequency Module

(141) The radio-frequency module **100b** according to the second embodiment will be described with reference to FIG. 7.

(142) In the radio-frequency module **100b** according to the second embodiment, the directional coupler **80** has the main line **801** and the plurality of (for example, two) auxiliary lines **802**, **803**. The directional coupler **80** further has the plurality of (for example, six) terminals **806** to **811**. The main line **801** is provided in the signal path between the antenna terminal **81** and the low pass filter **60** in the transmitting path T1 (see FIG. 4). In other words, the first end of the main line **801** is connected to the antenna terminal **81** with the terminal **806** interposed therebetween, and the second end of the main line **801** is connected to the low pass filter **60** with the terminal **807** interposed therebetween.

(143) The first auxiliary line **802** and the second auxiliary line **803** are electromagnetically coupled to the main line **801**. The first end of the first auxiliary line **802** is connected to the first termination circuit **804** with the terminal **808** interposed therebetween, and the second end of the first auxiliary line **802** is connected to the selection terminal **561** of a sixth switch **56b** with the terminal **809** interposed therebetween. The first end of the second auxiliary line **803** is connected to the second termination circuit **805** with the terminal **810** interposed therebetween, and the second end of the second auxiliary line **803** is connected to the selection terminal **562** of the sixth switch **56** with the terminal **811** interposed therebetween. The common terminal **560** of the sixth switch **56** is connected to the output terminal **87**.

(144) In the radio-frequency module **100b** according to the second embodiment, when the common terminal **560** is connected to the selection terminal **561** in the sixth switch **56b**, a first detection

signal that propagates through the first auxiliary line **802** can be output to a detector (not shown). In the radio-frequency module **100b** according to the second embodiment, when the common terminal **560** is connected to the selection terminal **562** in the sixth switch **56b**, a second detection signal that propagates through the second auxiliary line **803** can be output to the detector.

(2) Modifications

(145) Next, modifications of the second embodiment will be described with reference to FIGS. **8** and **9**.

(2.1) First Modification

(146) A radio-frequency module **100c** according to a first modification will be described with reference to FIG. **8**. For the radio-frequency module **100c** according to the first modification, like reference signs denote component elements similar to those of the radio-frequency module **100b** according to the second embodiment, and the description is omitted.

(147) The radio-frequency module **100c** according to the first modification differs from the radio-frequency module **100b** according to the second embodiment in that a first detection signal that propagates through the first auxiliary line **802** and a second detection signal that propagates through the second auxiliary line **803** are respectively output from different output terminals (the first output terminal **871** and the second output terminal **872**).

(148) The radio-frequency module **100c** according to the first modification includes the first output terminal **871** and the second output terminal **872** as the output terminals. The first output terminal **871** is a terminal for outputting a first detection signal that propagates through the first auxiliary line **802**. The second output terminal **872** is a terminal for outputting a second detection signal that propagates through the second auxiliary line **803**. In other words, the second end of the first auxiliary line **802** of which the first end is connected to the first termination circuit **804** with the terminal **808** interposed therebetween is connected to the first output terminal **871** with the terminal **809** interposed therebetween. The second end of the second auxiliary line **803** of which the first end is connected to the second termination circuit **805** with the terminal **810** interposed therebetween is connected to the second output terminal **872** with the terminal **811** interposed therebetween.

(149) In the radio-frequency module **100c** according to the first modification, a first detection signal that propagates through the first auxiliary line **802** can be output to a detector (not shown) via the first output terminal **871**. In the radio-frequency module **100c** according to the first modification, a second detection signal that propagates through the second auxiliary line **803** can be output to the detector via the second output terminal **872**.

(2.2) Second Modification

(150) A radio-frequency module **100d** according to a second modification will be described with reference to FIG. **9**. For the radio-frequency module **100d** according to the second modification, like reference signs denote component elements similar to those of the radio-frequency module **100b** according to the second embodiment, and the description is omitted.

(151) The radio-frequency module **100d** according to the second modification differs from the radio-frequency module **100c** according to the first modification in that a plurality of directional couplers **80A**, **80B** is provided.

(152) The radio-frequency module **100d** according to the second modification includes the plurality of (for example, two) directional couplers **80A**, **80B**, a plurality of (for example, two) low pass filters **60A**, **60B**, and a fifth switch **55d**. The radio-frequency module **100d** according to the second modification further includes a plurality of (for example, two) antenna terminals **81A**, **81B** and a plurality of (for example, four) output terminals **871A**, **871B**, **872A**, **872B**.

(153) The directional coupler **80A** has the main line **801** and the plurality of auxiliary lines **802**, **803**. The directional coupler **80A** further has the plurality of (for example, six) terminals **806** to **811**. The main line **801** is provided in the signal path between the antenna terminal **81A** and the low pass filter **60A** in the transmitting path T1 (see FIG. **4**). The first auxiliary line **802** and the second

auxiliary line **803** are electromagnetically coupled to the main line **801**. The first end of the first auxiliary line **802** is connected to the first termination circuit **804** with the terminal **808** interposed therebetween, and the second end of the first auxiliary line **802** is connected to the first output terminal **871A** with the terminal **809** interposed therebetween. The first end of the second auxiliary line **803** is connected to the second termination circuit **805** with the terminal **810** interposed therebetween, and the second end of the second auxiliary line **803** is connected to the second output terminal **872A** with the terminal **811** interposed therebetween.

(154) The directional coupler **80B** has the main line **801** and the plurality of auxiliary lines **802**, **803**. The directional coupler **80B** further has the plurality of (for example, six) terminals **806** to **811**. The main line **801** is provided in the signal path between the antenna terminal **81B** and the low pass filter **60B** in the transmitting path T1 (see FIG. 4). The first auxiliary line **802** and the second auxiliary line **803** are electromagnetically coupled to the main line **801**. The first end of the first auxiliary line **802** is connected to the first termination circuit **804** with the terminal **808** interposed therebetween, and the second end of the first auxiliary line **802** is connected to the first output terminal **871B** with the terminal **809** interposed therebetween. The first end of the second auxiliary line **803** is connected to the second termination circuit **805** with the terminal **810** interposed therebetween, and the second end of the second auxiliary line **803** is connected to the second output terminal **872B** with the terminal **811** interposed therebetween.

(155) The low pass filter **60A** is provided in the signal path between the directional coupler **80A** and the fifth switch **55d**. More specifically, the low pass filter **60A** is provided in the signal path between the main line **801** of the directional coupler **80A** and a common terminal **5501** of the fifth switch **55d**. The low pass filter **60B** is provided in the signal path between the directional coupler **80B** and the fifth switch **55d**. More specifically, the low pass filter **60B** is provided in the signal path between the main line **801** of the directional coupler **80B** and a common terminal **5502** of the fifth switch **55d**.

(156) The fifth switch **55d** has the plurality of (for example, two) common terminals **5501**, **5502**, the plurality of (for example, six) selection terminals **551** to **556** connectable with the common terminal **5501**, and the plurality of (for example, two) selection terminals **557**, **558** connectable with the common terminal **5502**.

(157) In the radio-frequency module **100d** according to the second modification, a first detection signal that propagates through the first auxiliary line **802** of the directional coupler **80A** can be output to a detector (not shown) via the first output terminal **871A**. In the radio-frequency module **100d** according to the second modification, a second detection signal that propagates through the second auxiliary line **803** of the directional coupler **80A** can be output to the detector via the second output terminal **872A**. In the radio-frequency module **100d** according to the second modification, a first detection signal that propagates through the first auxiliary line **802** of the directional coupler **80B** can be output to the detector via the first output terminal **871B**. In the radio-frequency module **100d** according to the second modification, a second detection signal that propagates through the second auxiliary line **803** of the directional coupler **80B** can be output to the detector via the second output terminal **872B**.

Other Modifications

(158) Each of the above-described first and second embodiments and the like is just one of various embodiments of the present disclosure. The above-described first and second embodiments and the like each may be modified into various forms according to design or the like as long as the object of the present disclosure is achieved. Mutually different component elements of the mutually different embodiments may be combined as needed.

(159) In the radio-frequency modules **100**, **100a**, **100b**, **100c**, **100d**, the electrically conductive layer **106** is not limited to the case where the electrically conductive layer **106** covers the entire part of the major surface **151** of the first resin layer **105** and may cover at least part of the major surface **151** of the first resin layer **105**.

- (160) Each of the plurality of transmitting filters **611, 621, 631, 641, 651** and the plurality of receiving filters **612, 622, 632, 642, 652** is not limited to a surface acoustic wave filter and may be, for example, a bulk acoustic wave (BAW) filter. A resonator in the BAW filter is, for example, a film bulk acoustic resonator (FBAR) or a solidly mounted resonator (SMR). The BAW filter has a substrate. The substrate is, for example, a silicon substrate.
- (161) Each of the plurality of transmitting filters **611, 621, 631, 641, 651** and the plurality of receiving filters **612, 622, 632, 642, 652** is not limited to a ladder filter and may be, for example, a longitudinally coupled resonator-type surface acoustic wave filter.
- (162) The above-described acoustic wave filter is an acoustic wave filter that uses surface acoustic waves or bulk acoustic waves; however, the configuration is not limited thereto. The above-described acoustic wave filter may be, for example, an acoustic wave filter that uses boundary acoustic waves, plate waves, or the like.
- (163) The communication device **300** according to the first embodiment may include any one of the radio-frequency modules **100a, 100b, 100c, 100d** instead of the radio-frequency module **100**.
- (164) In the radio-frequency modules **100, 100a, 100b, 100c, 100d**, each of the directional couplers **80, 80A, 80B** has two auxiliary lines **802, 803**; however, the configuration is not limited thereto. Each of the directional couplers **80, 80A, 80B**, for example, may have only the first auxiliary line **802** or may have only the second auxiliary line **803**.
- (165) In the radio-frequency module **100** according to the first embodiment, the plurality of input terminals **881** to **883** and the output terminal **87** are arranged in two lines; however, the configuration is not limited thereto. The plurality of input terminals **881** and the output terminal **87** may be, for example, arranged in three or more lines.
- (166) In the radio-frequency module **100** according to the first embodiment, one ground terminal **89** is disposed between the plurality of signal terminals (the input terminals **881** to **883** and the output terminal **87**). Alternatively, for example, two or more ground terminals **89** may be disposed between the plurality of signal terminals.
- (167) In the radio-frequency modules **100, 100a, 100b, 100c, 100d**, the low pass filter **60** is provided between the directional coupler **80** and the fifth switch **55**, the low pass filter **60A** is provided between the directional coupler **80A** and the fifth switch **55d**, and the low pass filter **60B** is provided between the directional coupler **80B** and the fifth switch **55d**; however, the configuration is not limited thereto. The low pass filter **60** may be provided between the antenna terminal **81** and the directional coupler **80**, the low pass filter **60A** may be provided between the antenna terminal **81A** and the directional coupler **80A**, and the low pass filter **60B** may be provided between the antenna terminal **81B** and the directional coupler **80B**.
- (168) In the radio-frequency module **100d**, two detection signals from the directional coupler **80A** and two detection signals from the directional coupler **80B** are configured to be respectively output from different output terminals. Alternatively, for example, one or some of the four detection signals may be configured to be output via a sixth switch. For example, two detection signals output from the directional coupler **80A** or the directional coupler **80B** may be configured to be output to an output terminal via the sixth switch. For example, one of the detection signals of the directional coupler **80A** and one of the detection signals of the directional coupler **80B** may be configured to be output to the output terminal via the sixth switch.
- (169) In the radio-frequency modules **100, 100a, 100b, 100c, 100d**, the chip inductor **601** is an inductor that is a component of each of the low pass filters **60, 60A, 60B**; however, the configuration is not limited thereto. The chip inductor **601** may be, for example, an inductor that is a component of a matching circuit provided in the signal path between the antenna terminal **81** and the fifth switch **55**, the signal path between the antenna terminal **81A** and the fifth switch **55d**, or the signal path between the antenna terminal **81B** and the fifth switch **55d**.

Aspects

- (170) The following aspects are disclosed in the specification.

(171) A radio-frequency module (**100; 100a to 100d**) according to a first aspect includes an antenna terminal (**81; 81A, 81B**), a signal input terminal (**82, 83**), a signal output terminal (**84, 85**), a mounting substrate (**9**), a chip inductor (**601**), and a directional coupler (**80; 80A, 80B**). A transmitting signal is input to the signal input terminal (**82, 83**). A receiving signal is output from the signal output terminal (**84, 85**). The mounting substrate (**9**) has a first major surface (**91**) and a second major surface (**92**) opposite to each other. The chip inductor (**601**) is disposed on the first major surface (**91**) of the mounting substrate (**9**). The chip inductor (**601**) is provided in at least one of a transmitting path (**T1**) between the antenna terminal (**81; 81A, 81B**) and the signal input terminal (**82, 83**) and a receiving path (**R1**) between the antenna terminal (**81; 81A, 81B**) and the signal output terminal (**84, 85**). The directional coupler (**80; 80A, 80B**) is mounted on the second major surface (**92**) of the mounting substrate (**9**), and at least part (main line **801**) of the directional coupler (**80; 80A, 80B**) is provided in the transmitting path (**T1**).

(172) According to this aspect, it is possible to reduce the size and improve detection accuracy.

(173) In a radio-frequency module (**100; 100a to 100d**) according to a second aspect, in the first aspect, the chip inductor (**601**) is a component of a low pass filter (**60; 60A, 60B**) or a matching circuit, provided in the transmitting path (**T1**). In a plan view in a thickness direction (**D1**) of the mounting substrate (**9**), the chip inductor (**601**) and the directional coupler (**80; 80A, 80B**) overlap each other.

(174) According to this aspect, it is possible to shorten the wiring length between the chip inductor (**601**) and the directional coupler (**80; 80A, 80B**), with the result that it is possible to suppress the degradation of the characteristics of the radio-frequency module (**100; 100a to 100d**) due to the wiring length.

(175) A radio-frequency module (**100; 100a to 100d**) according to a third aspect, in the first or second aspect, further includes an output terminal (**87; 871, 872; 871A, 871B, 872A, 872B**) that outputs a detection signal from the directional coupler (**80; 80A, 80B**). The directional coupler (**80; 80A, 80B**) has a main line (**801**) and at least one auxiliary line (**802, 803**). The main line (**801**) is provided in the transmitting path (**T1**). The auxiliary line (**802, 803**) is electromagnetically coupled to the main line (**801**). The output terminal (**87; 871, 872; 871A, 871B, 872A, 872B**) is connected to the auxiliary line (**802, 803**).

(176) According to this aspect, it is possible to output a detection signal from the directional coupler (**80; 80A, 80B**) to an outside.

(177) A radio-frequency module (**100**) according to a fourth aspect, in the third aspect, further includes a selecting switch (**56**). The selecting switch (**56**) selects at least one of a detection signal output from the directional coupler (**80**) and a detection signal output from another directional coupler (**66 to 68**) of another radio-frequency module (**101 to 103**) and outputs the selected detection signal to the output terminal (**87**).

(178) According to this aspect, it is possible to output a plurality of detection signals from one output terminal (**87**).

(179) In a radio-frequency module (**100; 100a to 100d**) according to a fifth aspect, in the third or fourth aspect, the directional coupler (**80; 80A, 80B**) has a first auxiliary line (**802**) and a second auxiliary line (**803**) as the auxiliary line (**802, 803**). The first auxiliary line (**802**) outputs a first detection signal corresponding to a transmitting signal. The second auxiliary line (**803**) outputs a second detection signal corresponding to a receiving signal.

(180) According to this aspect, it is possible to improve detection accuracy for both a transmitting signal and a receiving signal.

(181) A radio-frequency module (**100**) according to a sixth aspect, in any one of the third to fifth aspects, further includes a plurality of signal terminals (**87, 881 to 883**) and a switch (**55**). The plurality of signal terminals (**87, 881 to 883**) includes an output terminal (**87**) and is disposed on the second major surface (**92**) of the mounting substrate (**9**). The switch (**55**) is mounted on the second major surface (**92**) of the mounting substrate (**9**) and connected to the antenna terminal (**81**).

The mounting substrate (9) has a rectangular shape in a plan view in a thickness direction (D1) of the mounting substrate (9). The mounting substrate (9) has a first side (94) and a second side (95) orthogonal to each other. Where the mounting substrate (9) is divided into four regions (921 to 924) by a first line (L1) passing through a center (C1) of the mounting substrate (9) and extending along the first side (94) and a second line (L2) passing through the center (C1) of the mounting substrate (9) and extending along the second side (95), the plurality of signal terminals (87, 881 to 883), the directional coupler (80), and the switch (55) are disposed in the same region (922).

(182) According to this aspect, it is possible to shorten the wiring length between the plurality of signal terminals (87, 881 to 883) and the directional coupler (80) and the wiring length between the directional coupler (80) and the switch (55).

(183) In a radio-frequency module (100) according to a seventh aspect, in the sixth aspect, the plurality of signal terminals (87, 881 to 883) is disposed so as not to be adjacent to each other in each of a first direction (D2) and a second direction (D3) that are orthogonal to the thickness direction (D1) of the mounting substrate (9).

(184) According to this aspect, it is possible to improve isolation between the signal terminals, with the result that it is possible to suppress jump of a signal between the signal terminals.

(185) A radio-frequency module (100) according to an eighth aspect, in the seventh aspect, further includes at least one ground terminal (89). The ground terminal (89) is disposed on the second major surface (92) of the mounting substrate (9). The ground terminal (89) is disposed between two signal terminals in the first direction (D2) or the second direction (D3), of the plurality of signal terminals (87, 881 to 883).

(186) According to this aspect, it is possible to further improve isolation between the signal terminals.

(187) In a radio-frequency module (100) according to a ninth aspect, in the seventh or eighth aspect, the antenna terminal (81) is disposed on the second major surface (92) of the mounting substrate (9). The output terminal (87) is disposed at a location farthest from the antenna terminal (81) in the first direction (D2), of the plurality of signal terminals (87, 881 to 883).

(188) According to this aspect, it is possible to improve isolation between the antenna terminal (81) and the output terminal (87), with the result that it is possible to suppress jump of a signal between the antenna terminal (81) and the output terminal (87).

(189) In a radio-frequency module (100) according to a tenth aspect, in any one of the sixth to ninth aspects, the directional coupler (80) and the switch (55) are integrated into a single chip. The switch (55) is disposed on an opposite side to the plurality of signal terminals (87, 881 to 883) side with respect to the directional coupler (80) in a direction that intersects with the thickness direction (D1) of the mounting substrate (9) (for example, a longitudinal direction D3 of the mounting substrate 9).

(190) According to this aspect, it is possible to improve isolation between the plurality of signal terminals (87, 881 to 883) and the switch (55), with the result that it is possible to suppress jump of a signal between the plurality of signal terminals (87, 881 to 883) and the switch (55).

(191) A radio-frequency module (100; 100a to 100d) according to an eleventh aspect, in any one of the first to tenth aspects, further includes external connection terminals (8). The external connection terminals (8) include the antenna terminal (81), the signal input terminal (82, 83), and the signal output terminal (84, 85) and are disposed on the second major surface (92) of the mounting substrate (9).

(192) According to this aspect, the IC chip 13 is allowed to be disposed in a gap between the mounting substrate (9) and a mother substrate or the like to which the external connection terminals (8) are connected.

(193) A communication device (300) according to a twelfth aspect includes the radio-frequency module (100; 100a to 100d) according to any one of the first to eleventh aspects, and a signal processing circuit (301). The signal processing circuit (301) is connected to the radio-frequency

module (**100**; **100a** to **100d**).

(194) According to this aspect, it is possible to reduce the size and improve detection accuracy.

REFERENCE SIGNS LIST

(195) **8** external connection terminal **9** mounting substrate **11** first power amplifier **12** second power amplifier **13** IC chip **20** controller **31** first output matching circuit **32** second output matching circuit **41** first input matching circuit **42** second input matching circuit **51** first switch **52** second switch **53** third switch **54** fourth switch **55**, **55d** fifth switch **56**, **56b** sixth switch (selecting switch) **57**, **58**, **59** switch **60**, **60A**, **60B** low pass filter **61**, **62**, **63**, **64**, **65** filter **66**, **67**, **68** directional coupler **71**, **72**, **73**, **74**, **75** matching circuit **76** digital tunable capacitor **77** control power supply **80**, **80A**, **80B** directional coupler **81**, **81A**, **81B** antenna terminal **82**, **83** signal input terminal **84**, **85** signal output terminal **86** control terminal **87** output terminal **89** ground terminal **91** first major surface **92** second major surface **93** outer peripheral surface **94** first side **95** second side **100**, **100a**, **100b**, **100c**, **100d** radio-frequency module **101**, **102**, **103** another radio-frequency module **105** first resin layer **106** electrically conductive layer **107** second resin layer **111**, **121**, **131** antenna terminal **112**, **122**, **132** output terminal **151** major surface **153** outer peripheral surface **171** major surface **173** outer peripheral surface **300** communication device **301** signal processing circuit **302** RF signal processing circuit **303** baseband signal processing circuit **310** antenna **311**, **312** capacitor **313** inductor **411**, **412**, **413**, **414** inductor **415** capacitor **510** common terminal **511**, **512** selection terminal **520** common terminal **521**, **522** selection terminal **530** common terminal **531**, **532** selection terminal **540** common terminal **541**, **542** selection terminal **550** common terminal **551**, **552**, **553**, **554**, **555**, **556** selection terminal **560** common terminal **561**, **562**, **563**, **564**, **565** selection terminal **570** common terminal **571**, **572**, **573**, **574**, **575** selection terminal **580** common terminal **581**, **582**, **583**, **584**, **585** selection terminal **590** common terminal **591**, **592**, **593**, **594**, **595** selection terminal **601**, **602**, **603** inductor **604** capacitor **611**, **621**, **631**, **641**, **651** transmitting filter **612**, **622**, **632**, **642**, **652** receiving filter **661**, **671**, **681** main line **662**, **672**, **682** auxiliary line **663**, **673**, **683** termination circuit **711**, **721**, **731**, **741**, **751** inductor **712**, **722**, **732**, **742** capacitor **801** main line **802** first auxiliary line **803** second auxiliary line **804** first termination circuit **805** second termination circuit **871**, **871A**, **871B** first output terminal **872**, **872A**, **872B** second output terminal **881** first input terminal **882** second input terminal **883** third input terminal **921** first region **922** second region **923** third region **924** fourth region **C1** center **D1** thickness direction **D2** width direction (first direction) **D3** longitudinal direction (second direction) **L1**, **L2** straight line

Claims

1. A radio-frequency module comprising: an antenna terminal; a signal input terminal to which a transmitting signal is input; a signal output terminal from which a receiving signal is output; a mounting substrate having a first major surface and a second major surface opposite to each other in a thickness direction of the mounting substrate; a chip inductor mounted on the first major surface of the mounting substrate, and connected in a transmitting path between the antenna terminal and the signal input terminal or in a receiving path between the antenna terminal and the signal output terminal; and a directional coupler mounted on the second major surface of the mounting substrate, and at least partly connected in the transmitting path.
2. The radio-frequency module according to claim 1, wherein the chip inductor is a component of a low pass filter or a matching circuit, and is connected in the transmitting path, and wherein the chip inductor and the directional coupler overlap in a plan view of the mounting substrate.
3. The radio-frequency module according to claim 1, further comprising: an output terminal from which a detection signal from the directional coupler is output, wherein the directional coupler comprises: a main line in the transmitting path, and at least one auxiliary line electromagnetically coupled to the main line, and wherein the output terminal is connected to the auxiliary line.
4. The radio-frequency module according to claim 3, further comprising: a selecting switch

configured to select a detection signal output from the directional coupler or a detection signal output from another directional coupler of another radio-frequency module, and to output the selected detection signal to the output terminal.

5. The radio-frequency module according to claim 3, wherein the auxiliary line of the directional coupler comprises: a first auxiliary line through which a first detection signal corresponding to the transmitting signal is output, and a second auxiliary line through which a second detection signal corresponding to the receiving signal is output.

6. The radio-frequency module according to claim 3, further comprising: a plurality of signal terminals on the second major surface of the mounting substrate, the plurality of signal terminals comprising the output terminal; and a switch on the second major surface of the mounting substrate, and connected to the antenna terminal, wherein the mounting substrate is rectangular in a plan view of the mounting substrate, and wherein the plurality of signal terminals, the directional coupler, and the switch are in the same quadrant of the mounting substrate.

7. The radio-frequency module according to claim 6, wherein the plurality of signal terminals are not adjacent to each other in each of a first direction and a second direction that are orthogonal to the thickness direction of the mounting substrate.

8. The radio-frequency module according to claim 7, further comprising: at least one ground terminal on the second major surface of the mounting substrate, wherein the ground terminal is between two of the plurality of signal terminals in the first direction or the second direction.

9. The radio-frequency module according to claim 7, wherein the antenna terminal is on the second major surface of the mounting substrate, and wherein, among the plurality of signal terminals, the output terminal is farthest from the antenna terminal in the first direction.

10. The radio-frequency module according to claim 6, wherein the directional coupler and the switch are integrated into a single chip, and wherein the switch is on an opposite side to a side of the plurality of signal terminals, with respect to the directional coupler in a direction that intersects with a thickness direction of the mounting substrate.

11. The radio-frequency module according to claim 1, further comprising: external connection terminals comprising the antenna terminal, the signal input terminal, and the signal output terminal, the external connection terminals being on the second major surface of the mounting substrate.

12. A communication device comprising: the radio-frequency module according to claim 1; and a signal processing circuit connected to the radio-frequency module.
