

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250261835

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

MITSUHASHI; Keita et al.

---

### INSERTION APPARATUS AND ENDOSCOPE

---

#### Abstract

An insertion apparatus in the invention includes: a multi-lumen tube provided in an insertion portion and formed in a bendable manner, the insertion portion being inserted into a subject; a distal end member arranged so as to cover a distal end of the multi-lumen tube; a braided tube into which the multi-lumen tube is inserted, a distal end edge portion of the braided tube being disposed between the distal end member and the multi-lumen tube; and a wire configured to bend the multi-lumen tube by traction, in which the braided tube includes a gap through which the wire passes from an outside of the braided tube to an inside of the braided tube.

---

**Inventors:** MITSUHASHI; Keita (Tokyo, JP), OTA; Tsukasa (Tokyo, JP), YOSHINAGA; Takuto (Tokyo, JP), MATSUURA; Wataru (Tokyo, JP), SUZUKI; Motohiko (Sagamihara-shi, JP)

**Applicant:** OLYMPUS CORPORATION (Tokyo, JP)

**Family ID:** 1000008586689

**Assignee:** OLYMPUS CORPORATION (Tokyo, JP)

**Appl. No.:** 19/202522

**Filed:** May 08, 2025

#### Related U.S. Application Data

parent US continuation 17835237 20220608 parent-grant-document US 12318069 child US 19202522

parent WO continuation PCT/JP2019/048814 20191212 PENDING child US 17835237

---

#### Publication Classification

**Int. Cl.:** A61B1/005 (20060101); A61B1/00 (20060101)

## Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation application of U.S. patent application Ser. No. 17/835,237 filed Jun. 8, 2022, which is a continuation application of PCT/JP2019/048814 filed on Dec. 12, 2019, the entire contents of each of which are incorporated herein by reference.

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

[0002] The invention relates to an insertion apparatus and an endoscope, in which an insertion portion configured to be inserted into a subject is configured using a multi-lumen tube formed in a bendable manner.

#### 2. Description of the Related Art

[0003] In recent years, an endoscope that is a kind of insertion apparatus has been widely used, for example, in a medical field. The endoscope is an insertion apparatus configured such that a surface of an organ in a body cavity as a subject can be observed by inserting an elongated insertion portion into the body cavity. Moreover, the endoscope is an insertion apparatus configured such that various treatments can be performed to a desired site in the body cavity as an examination object or details of a desired site in the body cavity can be observed in more detail by inserting various treatment instruments or a miniature endoscope into the body cavity through a treatment instrument channel or the like provided on the endoscope as necessary.

[0004] In an endoscope that is this kind of insertion apparatus, in recent years, for example, various endoscopes configured using a multi-lumen tube have been proposed and put to practical use. By the multi-lumen tube, the insertion portion is formed in a bendable manner.

[0005] As insertion portions of conventional endoscopes, various insertion portions each of which is configured as a three-layer structure constituted by an insertion tube including a bending portion formed in a bendable manner, a braided tube externally provided so as to cover an outer surface of the insertion tube, and an outer sleeve sheathing an outer surface of the braided tube have been proposed and disclosed in U.S. Pat. No. 7,922,650 and Japanese Patent Application Laid-Open Publication No. 2001-112707 and the like. In the insertion portion having such a three-layer structure, the braided tube is provided for enhancing the strength and torsional rigidity of the insertion tube.

[0006] The insertion portion of the insertion apparatus disclosed in U.S. Pat. No. 7,922,650 is configured as a three-layer structure in which an outer surface of the multi-lumen tube formed in a bendable manner is sheathed with the braided tube and the outer surface of the braided tube is sheathed with the outer sleeve. A distal end edge portion of the braided tube is configured to be fixed at a distal end portion of the insertion portion while being sandwiched between the outer sleeve and the multi-lumen tube.

[0007] The bending portion of the insertion portion of the insertion apparatus disclosed in Japanese Patent Application Laid-Open Publication No. 2001-112707 is configured as a three-layer structure in which an outer surface of a bending tube constituted by a plurality of node rings is sheathed with the braided tube and the outer surface of the braided tube is sheathed with the outer sleeve. At the distal end portion of the insertion portion, the distal end edge portion of the braided tube is disposed on a distal end side of the bending portion, and a thread-winding binding fixation of the distal end edge portion is performed on an outer circumference surface of a metallic ring-shaped

member to which a distal end of a bending wire is fixed. The outer surface of the braided tube is configured so as to be sheathed with the outer sleeve.

## SUMMARY OF THE INVENTION

[0008] An insertion apparatus in an aspect of the present invention includes: a multi-lumen tube provided in an insertion portion and formed in a bendable manner, the insertion portion being inserted into a subject; a distal end member arranged so as to cover a distal end of the multi-lumen tube; a braided tube into which the multi-lumen tube is inserted, a distal end edge portion of the braided tube being disposed between the distal end member and the multi-lumen tube; and a wire configured to bend the multi-lumen tube by traction, in which the braided tube includes a gap through which the wire passes from an outside of the braided tube to an inside of the braided tube.

[0009] An endoscope in an aspect of the present invention includes: a multi-lumen tube provided in an insertion portion and formed in a bendable manner, the insertion portion being inserted into a subject; a distal end member arranged so as to cover a distal end of the multi-lumen tube; a braided tube into which the multi-lumen tube is inserted, a distal end edge portion of the braided tube being disposed between the distal end member and the multi-lumen tube; and a wire configured to bend the multi-lumen tube by traction. The braided tube includes a gap through which the wire passes from an outside of the braided tube to an inside of the braided tube.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0010] FIG. 1 is a plan view showing a schematic configuration of an endoscope that is an insertion apparatus in a first embodiment of the present invention;

[0011] FIG. 2 is an external perspective view showing a vicinity of a distal end portion of an insertion portion of an endoscope in FIG. 1;

[0012] FIG. 3 is a plan view showing a state where a distal end member and an outer sleeve that configures a flexible tube portion are removed in the endoscope in FIG. 1;

[0013] FIG. 4 is an external perspective view showing only a wire bonding ring of members that configure the distal end portion in the endoscope in FIG. 1;

[0014] FIG. 5 is an external perspective view showing a vicinity of a distal end portion of only a multi-lumen tube of members that configure the flexible tube portion in the endoscope in FIG. 1;

[0015] FIG. 6 is a half-sectional view of a vicinal part of the distal end portion of the insertion portion of the endoscope in FIG. 1;

[0016] FIG. 7 is a sectional view taken along line [7]-[7] in FIG. 6;

[0017] FIG. 8 is a sectional view showing a configuration of a vicinity of a proximal end of the flexible tube portion of the endoscope in FIG. 1;

[0018] FIG. 9 is a principal-portion enlarged sectional view showing a part shown by reference numeral in FIG. 8, as an enlarged view;

[0019] FIG. 10 is a plan view showing a state where a distal end member and an outer sleeve that configures a flexible tube portion are removed in an endoscope in a second embodiment of the present invention;

[0020] FIG. 11 is a half-sectional view of a vicinal part of a distal end portion of an insertion portion of the endoscope in FIG. 10; and

[0021] FIG. 12 is a sectional view taken along line [12]-[12] in FIG. 11.

### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0022] Generally, a configuration in which an outer surface side of an insertion tube is sheathed with a braided tube is well known. The braided tube that is used in a conventional insertion apparatus is formed by weaving an element wire member formed of metal, a carbon-based fiber or the like in a grid pattern. Therefore, a distal end edge portion of the braided tube is in a state where

a woven portion easily frays, where the shape is not stable and where a sharp end portion of the element wire member is exposed.

[0023] Therefore, in the case of employing the conventional well-known configuration disclosed in U.S. Pat. No. 7,922,650 and Japanese Patent Application Laid-Open Publication No. 2001-112707 and the like, there is fear that an element wire member end portion of the distal end edge portion of the braided tube cuts through the outer sleeve and protrudes toward the outer surface of the outer sleeve. This causes a problem that the watertight property of the distal end portion of the insertion portion cannot be maintained.

[0024] Further, in the case where the insertion portion of the endoscope is used in a state where the element wire member end portion of the distal end edge portion of the braided tube protrudes to the outer surface of the outer sleeve, there is fear that a mucous membrane in the body cavity is damaged or bleeding occurs, for example. Hence, for example, by increasing the thickness of the outer sleeve, it is possible to prevent the protrusion of the element wire member end portion of the distal end edge portion of the braided tube. However, in the case of such a configuration, a problem of increase in the diameter of the distal end portion of the insertion portion arises.

[0025] Meanwhile, as a contrivance for preventing fraying of the distal end edge portion of the braided tube, for example, it is possible to fix the distal end edge portion of the braided tube to the outer circumference surface of the metallic ring-shaped member provided at the distal end portion by thread-winding binding fixation, brazing fixation treatment or the like.

[0026] However, in the case where the fixation treatments are performed, there is a problem that an outer diameter of a thread-winding binding part or a brazing part becomes large. At the same time, there is a problem that production treatment equipment is separately needed, and in addition, there is a problem that a high-level treatment skill is required and therefore production cost rises.

[0027] Hence, as the insertion apparatus and the endoscope, each including the insertion portion using the multi-lumen tube, the present invention can provide an insertion apparatus and an endoscope, each of which makes it possible to surely prevent the distal end edge portion of the braided tube from protruding from the outer sleeve to the exterior, to restrain the increase in the diameter of the insertion portion, to secure the watertight property of the distal end portion, and to obtain a safe and suitable insertion property.

[0028] The present invention will be described below with illustrated embodiments.

[0029] Each drawing to be used in the following description is schematically shown, and for showing each component element in a size that allows each component element to be recognized on the drawing, the dimensional relation, scale and others of each member are sometimes shown so as to be different for each component element. Accordingly, in the present invention, the quantity of each component element described in each drawing, the shape of each component element, the size proportion of each component element, and the relative position relation of each component element are not limited to illustrated forms.

#### First Embodiment

[0030] FIG. 1 is a plan view showing a schematic configuration of an endoscope that is an insertion apparatus in a first embodiment of the present invention.

[0031] First, the endoscope that is the insertion apparatus in the present embodiment is an insertion apparatus for observing details of a desired site in a body cavity as an examination object by inserting an insertion portion into the body cavity through a treatment instrument channel (not illustrated) provided on a mother endoscope (not illustrated) having a conventionally general configuration, and is an example of a so-called baby endoscope. In this case, for example, the baby endoscope is a type of disposable insertion apparatus that is discarded after use.

[0032] Note that illustration of the mother endoscope and detailed descriptions of a configuration of the mother endoscope are omitted and only brief descriptions will be shown below assuming that an endoscope having a conventionally general configuration is applied to the mother endoscope.

[0033] The mother endoscope (not illustrated) to which an endoscope **20** (see FIG. 1) in the present

embodiment is applied is an endoscope having a general form and configured to include an insertion portion having an elongated shape and configured to be inserted into a subject and an operation portion joined to a proximal end of the insertion portion.

[0034] The insertion portion is formed such that a distal end portion, a bending portion and a flexible tube portion are continuously provided in order from a distal end side. In an interior of the distal end portion, for example, an image pickup unit constituted by an objective optical system and an image sensor such as a CCD or a CMOS, and an illumination optical system configured to forward emit illumination light transmitted using a light guide bundle are arranged.

[0035] At the distal end portion, a plurality of opening portions are provided. One of the opening portions communicates with a distal end of a treatment instrument channel configured to allow insertion of the insertion portion.

[0036] The bending portion is assembled such that a plurality of bending pieces are continuously provided, and is configured to be capable of being actively bent in all directions around an insertion axis. The flexible tube portion is configured by a tubular member formed in a passively bendable manner.

[0037] A treatment instrument insertion portion is provided on the operation portion, and the treatment instrument insertion portion communicates with a proximal end of the treatment instrument channel of the insertion portion. Further, a plurality of operation members such as a bending operation knob for performing a bending operation of the bending portion, and the like are provided in the operation portion.

[0038] A universal cable extends from the operation portion. A connector configured to allow attachment and detachment with an external apparatus (not illustrated) such as a light source device is provided at a distal end of the universal cable.

[0039] The endoscope **20** in the present embodiment is a baby endoscope that is applied to the mother endoscope (not illustrated) having the above-described configuration. As shown in FIG. **1**, the endoscope **20** in the present embodiment is configured to include an insertion portion **21** having an elongated shape and an operation portion **22** continuously provided at a proximal end of the insertion portion **21**.

[0040] In the insertion portion **21**, a distal end member **23** is provided on a distal end side, and a flexible tube portion **25** is formed on the distal end member **23** so as to be continuously provided.

[0041] In an interior of the distal end member **23**, for example, an observation optical system connected with an image guide bundle and an illumination optical system configured to forward emit illumination light transmitted using a light guide bundle are provided, although illustration is omitted. An observation opening **41a** (see FIG. **2**) on which front faces of the observation optical system and the illumination optical system are exposed is formed on a front face of the distal end member **23**. The observation opening **41a** communicates with an observation hole **41** (see FIG. **5** and the like) configured to allow insertion of the insertion portion **21**.

[0042] Note that the endoscope **20** in the present embodiment is a so-called front-viewing endoscope in which optical axes of an image pickup optical system and the illumination optical system are set in a long axis direction of the insertion portion **21**.

[0043] Further, a channel opening **42a** (see FIG. **2**) corresponding to a suction tube **28a** (described later; see FIG. **1**) inserted into the insertion portion **21** and a treatment instrument channel (described later; see reference numeral **42** in FIG. **5**), and a pair of water feeding openings **43a** (see FIG. **2**) corresponding to a water feeding tube **28b** (described later; see FIG. **1**) inserted into the insertion portion **21** are formed on the front face of the distal end member **23**.

[0044] The flexible tube portion **25** is formed by a tube **35** (see FIG. **3** and the like) formed in a passively bendable manner and having flexibility. The tube **35** extends from the distal end side to the proximal end side in the long axis direction.

[0045] An active bending portion is integrally formed at a predetermined region of the distal end side of the tube **35**. The active bending portion is inserted into the insertion portion **21**, and can

actively bend the tube **35** by an action of a bending wire **34** (described later; see FIG. **3** and the like) for bending the tube **35** when a traction operation is performed. In other words, a so-called multi-lumen tube in which the flexible tube portion **25** capable of being passively bent and the active bending portion capable of being actively bent are integrally formed is applied to the tube **35**.

[0046] Note that more detailed configurations of vicinities of distal ends of the distal end member **23** and flexible tube portion **25** in the insertion portion **21** of the endoscope **20** in the present embodiment will be described later.

[0047] The operation portion **22** is configured to include a pair of bending operation knobs **26** for performing a bending operation of the bending portion that forms a part of the distal end side of the flexible tube portion **25**, a treatment instrument insertion portion **27** and the like.

[0048] A tube group **28** including the image guide bundle, the light guide bundle, the suction tube **28a** and the water feeding tube **28b** that are inserted into the insertion portion **21** is inserted into the interior of the operation portion **22**, and extends from the operation portion **22**.

[0049] Note that the endoscope **20** in the present embodiment can be configured such that an image pickup unit (not illustrated) is arranged in the interior of the distal end member **23** or the interior of the operation portion **22**. In the case where such a configuration is employed, an image-pickup signal cable connected with the image pickup unit extends from the operation portion **22**, instead of the image guide bundle. In this case, the image-pickup signal cable is included in the above tube group.

[0050] The configuration of the vicinity of the distal end including the distal end member **23** of the insertion portion **21** of the endoscope **20** configured in this way will be described below. FIG. **2** is an external perspective view showing the vicinity of the distal end portion of the insertion portion of the endoscope in the present embodiment. FIG. **3** is a plan view showing a state where the distal end member and the outer sleeve that configures the flexible tube portion are removed in the endoscope in FIG. **1**. Note that the removed members are shown by two-dot chain lines in FIG. **3**. FIG. **4** is an external perspective view showing only a wire bonding ring of members that configure the distal end portion in the endoscope in FIG. **1**. FIG. **5** is an external perspective view showing the vicinity of the distal end portion of only the multi-lumen tube of members that configure the flexible tube portion in the endoscope in FIG. **1**. FIG. **6** is a half-sectional view of a vicinal part of the distal end portion of the insertion portion of the endoscope in FIG. **1**. Note that FIG. **6** shows only an upper half portion from a long axis directional center of a section taken along line [6]-[6] (long axis directional center) in FIG. **3**. FIG. **7** is a sectional view taken along line [7]-[7] in FIG. **6**. Note that FIG. **7** shows a whole section of a corresponding part in the insertion portion instead of showing only a section corresponding to the half section in FIG. **6**.

[0051] The vicinity of the distal end that includes the distal end member **23** of the insertion portion **21** of the endoscope **20** is configured by combining component members such as the distal end member **23**, the flexible tube portion **25** and a wire bonding ring **33** (not illustrated in FIG. **2**; see FIG. **3** and the like).

[0052] In the distal end member **23**, a distal end resin portion **31** and a distal end metal portion **32** are integrally formed by insert molding, for example. Here, the distal end resin portion **31** is composed of rigid resin, and includes the observation opening **41a**, the channel opening **42a**, the pair of water feeding openings **43a** and the like. The distal end metal portion **32** is a metallic formed component formed so as to include a buried part buried in a part near an outer circumference of the distal end resin portion **31** and integrated with the distal end resin portion **31** and a metallic annular portion extending from the buried part in a direction along a central axis of the distal end resin portion **31** and formed such that an outer circumference surface of the metallic annular portion is roughly flush with an outer circumference surface of the distal end resin portion **31**.

[0053] As shown in FIG. **3**, the flexible tube portion **25** is configured mainly by the tube **35**, a

braided tube **36** and an outer sleeve **37**.

[0054] As shown in FIG. 5, for example, the tube **35** is a multi-lumen tube including the observation hole **41** configured to allow insertion of a signal line and the like of the image guide bundle or the image pickup unit, the light guide bundle (not illustrated) and the like from the distal end of the insertion portion **21** to the proximal end of the insertion portion **21**, a channel hole **42** configured to function as a suction channel or a treatment instrument channel, a pair of water feeding holes **43** each of which is an insertion hole for the water feeding tube **28b**, and four wire insertion holes **44** configured to allow insertion of four wires **34** (described later; see FIG. 4, FIG. 6 and like) connected with the pair of the bending operation knobs **26** such that each of the four wires **34** can move in an axial direction. The tube **35** is formed by a deformable flexible member.

[0055] Note that the above distal end member **23** is continuously provided at the distal end of the flexible tube portion **25**. At this time, the observation hole **41** of the tube **35** is disposed so as to communicate with the observation opening **41a** of the distal end member **23**, the channel hole **42** of the tube **35** is disposed so as to communicate with the channel opening **42a** of the distal end member **23**, and the pair of the water feeding holes **43** of the tube **35** is disposed so as to communicate with the pair of the water feeding openings **43a** of the distal end member **23**.

[0056] The wire bonding ring **33** that is a circular member is fit to an outer circumference surface at a vicinity of a distal end part of the tube **35**. In other words, the tube **35** is inserted into the wire bonding ring **33**. For correspondence to the insertion, an insertion hole **45** configured to cause an outer surface and each wire insertion hole **44** to communicate with each other is formed at the vicinity of the distal end part of the tube **35**. Thereby, when the wire bonding ring **33** is disposed so as to be fit at the vicinity of the distal end part of the tube **35**, each of the plurality of bending wires **34** extending from the wire bonding ring **33** passes through the insertion hole **45**, and is inserted into the wire insertion hole **44**.

[0057] The braided tube **36** is a tubular member formed in a tubular shape as a whole by weaving an element wire formed of metal, a carbon-based fiber or the like in a resin layer in a grid pattern. The braided tube **36** is provided so as to cover the outer surface of the tube **35**.

[0058] The outer sleeve **37** is an elastic tube provided so as to cover an outer surface of the braided tube **36** and configuring an external facing member of the flexible tube portion **25**. An outer diameter of the outer sleeve **37** is formed so as to be roughly the same as diameters of the distal end resin portion **31** of the distal end member **23** and the metallic annular part of the distal end metal portion **32**. In an assembled state where the flexible tube portion **25** is joined to the distal end member **23**, the wire bonding ring **33** is internally provided in the distal end metal portion **32**. At this time, a gap between an inner surface of a metallic lead tube part of the distal end metal portion **32** and an outer surface of the wire bonding ring **33** is adhesively fixed in a watertight manner, using a member configured to maintain watertightness, for example, using an adhesive, with the braided tube **36** interposed. Furthermore, similarly, a gap between a distal end of the outer sleeve **37** and a proximal end surface of the distal end metal portion **32** is bonded in a watertight manner, using a member configured to maintain watertightness, for example, using an adhesive. In addition, similarly, a gap between the outer sleeve **37** and the wire bonding ring **33** is bonded in a watertight manner, using a member configured to maintain watertightness, for example, using an adhesive.

[0059] The wire bonding ring **33** is a circular member shown in FIG. 4, and is formed using a rigid material such as a metallic member including a stainless steel, for example. On an inner circumference surface of the wire bonding ring **33**, respective one ends of the four bending wires **34** are bonded at roughly equally spaced positions (for example, at intervals of a rotation angle of about 90 degrees) in a circumferential direction. Each bending wire **34** extends in one direction parallel to a central axis of the wire bonding ring **33**.

[0060] An outer diameter of the wire bonding ring **33** is formed so as to be roughly the same as an outer diameter of the tube **35** of the above flexible tube portion **25**. As described above, the wire bonding ring **33** is arranged so as to be fit at the vicinity of the distal end portion of the tube **35**. In

other words, the tube 35 is inserted into the wire bonding ring 33. At this time, the four bending wires 34 extending from the wire bonding ring 33 are disposed so as to be inserted into the wire insertion holes 44 through the insertion holes 45 of the tube 35, respectively (see FIG. 6).

[0061] Note that when the wire bonding ring 33 is disposed so as to be fit at the vicinity of the distal end portion of the tube 35, the wire bonding ring 33 is disposed such that the distal end part of the tube 35 protrudes by a slight quantity toward a distal end side in the axial direction of the tube 35 and is exposed (see FIG. 3).

[0062] On the tube 35 in this state (on the tube 35 in the state where the wire bonding ring 33 is disposed so as to be fit to the distal end), the braided tube 36 is disposed so as to cover the wire bonding ring 33. At this time, as shown in FIG. 3, the braided tube 36 covers a whole surface on an outer circumference side of the wire bonding ring 33, and a distal end edge portion 36a of the braided tube 36 is disposed so as to cover a part of the distal end protrusion part of the tube 35. In other words, the tube 35 is inserted into the braided tube 36.

[0063] When the flexible tube portion 25 is joined to the distal end member 23, the braided tube 36 and the tube 35 in the above-described state are fit into an inside of the distal end metal portion 32 of the distal end member 23. At this time, as shown in FIG. 6, the distal end edge portion 36a of the braided tube 36 is disposed so as to be fixed while being sandwiched between an inner surface of the distal end metal portion 32 and an outer surface of the distal end protrusion part of the tube 35.

[0064] An outer surface of the tube 35 and braided tube 36 in this state is sheathed with the outer sleeve 37. In other words, the outer sleeve 37 is fixed on the proximal end side of the distal end member 23, so as to cover the braided tube 36 and the wire bonding ring 33. While tightly contacting with the proximal end surface of the distal end metal portion 32, the distal end edge portion of the outer sleeve 37 is bonded in a watertight manner, using a member configured to maintain watertightness, for example, using an adhesive.

[0065] A configuration of a vicinity of a proximal end of the flexible tube portion 25 will be described below. FIG. 8 is a sectional view showing the configuration of the vicinity of the proximal end of the flexible tube portion of the endoscope in the present embodiment. FIG. 9 is a principal-portion enlarged sectional view showing a part shown by reference numeral [12] in FIG. 8, as an enlarged view.

[0066] A proximal end part of the flexible tube portion 25 is inserted into a bend preventing portion 51, and thereafter is inserted into an interior of an operation portion external face 52 of the operation portion 22. At the proximal end part of the flexible tube portion 25, as shown in FIG. 9, a proximal end portion of the outer sleeve 37 and a proximal end edge portion 36b of the braided tube 36 are provided so as to be fixed to an internal fixation member 53 of the operation portion 22, and is inserted into a silicone tube 55 provided for positioning fixation of an O-shaped ring 54. Note that the tube 35 passes through the silicone tube 55 and extends from the silicone tube 55 at this time. By this configuration, the proximal end edge portion 36b of the braided tube 36 is stably fixed while being sandwiched between an inner surface of the silicone tube 55 and an outer surface of the tube 35.

[0067] In this state, as shown in FIG. 9, an adhesive 56 is applied to outer surfaces of the internal fixation member 53, the silicone tube 55 and the outer sleeve 37, and by curing of the adhesive 56, the above respective component members (53, 55, 37) are fixed to each other. Accordingly, by such a configuration, at the proximal end edge portion 36b of the braided tube 36, a stable shape in a state where fraying of the woven portion is prevented is maintained.

[0068] As described above, according to the above first embodiment, in the endoscope 20 that is the insertion apparatus including the insertion portion 21 including the flexible tube portion 25 using the multi-lumen tube (35), the distal end edge portion 36a of the braided tube 36 in the flexible tube portion 25 is disposed on the inner circumference side of the distal end metal portion 32 that is the rigid member of the distal end member 23, and the distal end edge portion 36a is stably fixed while being sandwiched between the inner surface of the distal end metal portion 32



that is the rigid member and the distal end outer surface of the tube **35**. At this time, the outer circumference side of the wire bonding ring **33** is sheathed with the braided tube **36**.

[0069] By this configuration, in the endoscope **20** in the present embodiment, the distal end edge portion **36a** of the braided tube **36** is fixed in a stable state, on the inside of the distal end metal portion **32** that is the rigid member, and therefore, it is possible to surely prevent a state where the distal end edge portion **36a** of the braided tube **36** protrudes from the outer surface of the outer sleeve **37** or the like and is exposed, for example, by cutting through the member on the outer surface side. Further, thereby, it is possible to secure the watertight property of the distal end portion while restraining the increase in the diameter of the insertion portion **21**, and at the same time, it is possible to secure a safe and suitable insertion property.

[0070] Further, it is possible to avoid the distal end edge portion **36a** of the braided tube **36** from breaking the outer sleeve **37**, and since the distal end edge portion **36a** of the braided tube **36** is not disposed at the part on an inside of the outer sleeve **37**, it is possible to contribute to the decrease in the thickness of the outer sleeve **37** at that part. Accordingly, it is possible to reduce the diameter of the insertion portion **21** as a whole, and consequently, it is possible to secure the enhancement of the insertion property of the endoscope **20** as the insertion apparatus for the subject.

[0071] Furthermore, it is not necessary to perform, particularly, thread binding fixation, brazing processing, soldering treatment or the like, as stable fixation means for the distal end edge portion **36a** of the braided tube **36**, and therefore, it is possible to prevent a partial increase in diameter, and consequently, it is possible to contribute to the reduction in diameter of the insertion portion **21**.

[0072] Furthermore, since the above various fixation processing treatments and the like are unnecessary, it is possible to simplify assembly steps for the whole of the endoscope **20**, and to reduce production equipment and production steps.

## Second Embodiment

[0073] Next, a second embodiment of the present invention will be described below. Basically, a configuration of the present embodiment is roughly the same as the configuration of the above-described first embodiment. In the present embodiment, the configuration of the vicinity of the distal end portion of the insertion portion is different only in that the braided tube **36** is configured to be disposed on an inside of the wire bonding ring **33**. The other configuration is roughly the same as the configuration of the above-described first embodiment.

[0074] Accordingly, in the following description, only the point different from the above-described first embodiment will be described in detail, parts having the same configurations as the configurations of the above-described first embodiment are denoted by the same reference numerals, and detailed descriptions of the parts will be omitted.

[0075] FIG. **10** is a plan view showing a state where a distal end member and an outer sleeve that configures a flexible tube portion are removed in an endoscope in the second embodiment of the present invention. Note that the removed members are shown by two-dot chain lines in FIG. **10**. FIG. **11** is a half-sectional view of a vicinal part of a distal end portion of an insertion portion of the endoscope in FIG. **10**. Note that FIG. **11** shows only an upper half portion from a long axis directional center of a section taken along line [11]-[11] (long axis directional center) in FIG. **10**. FIG. **12** is a sectional view taken along line [12]-[12] in FIG. **11**. Note that FIG. **12** shows a whole section of a corresponding part in the insertion portion instead of showing only a section corresponding to the half section in FIG. **11**.

[0076] A vicinity of the distal end that includes the distal end member **23** of the insertion portion **21** of the endoscope **20** in the present embodiment is configured by combining component members such as the distal end member **23**, the flexible tube portion **25** and the wire bonding ring **33**, similarly to the above-described first embodiment.

[0077] In the above-described first embodiment, the wire bonding ring **33** is configured to be externally inserted to the tube **35**, such that the outer surface of the wire bonding ring **33** is disposed so as to be covered with the braided tube **36**, that is, such that the wire bonding ring **33** is

disposed on the inside of the braided tube **36**.

[0078] On the other hand, the present embodiment is different in that the wire bonding ring **33** is configured to be externally inserted to the tube **35**, such that the wire bonding ring **33** is disposed so as to cover a part of the outer surface of the braided tube **36**, that is, such that the wire bonding ring **33** is disposed on the outside of the braided tube **36**, in other words, such that a part of the braided tube **36** is internally provided in the wire bonding ring **33**. Note that in this case, the distal end edge portion **36a** of the braided tube **36** is disposed at a position on the distal end side of the wire bonding ring **33**. In a joined state where the distal end member **23** is attached to the distal end of the flexible tube portion **25**, the distal end edge portion **36a** of the braided tube **36** is disposed on the inner circumference side of the distal end metal portion **32**.

[0079] By this configuration, the distal end edge portion **36a** of the braided tube **36** is stably fixed at a part on the inside of the distal end metal portion **32**, and therefore the distal end edge portion **36a** does not protrude toward the outer surface.

[0080] In the configuration of the present embodiment, the wire bonding ring **33** is disposed on the outside of the braided tube **36**. In this case, each of the four bending wires **34** passes through the gap of the braided tube **36**, and is disposed on the inside of the braided tube **36**. Therefore, the gaps of the mesh of the braided tube **36** are relatively sparsely formed, and for example, the braided tube **36** is formed so as to have gaps through which the bending wires **34** can pass. Furthermore, the bending wires **34** pass through the insertion holes **45** of the tube **35**, and are inserted into the wire insertion holes **44**. By this configuration, each of the four bending wires **34** is configured to be capable of surely performing a prescribed action with no difficulty.

[0081] As described above, according to the above second embodiment, it is possible to obtain the same effect as the effect of the above-described first embodiment. Furthermore, according to the present embodiment, since the wire bonding ring **33** is configured to be disposed on the outside of the braided tube **36**, it is possible to contribute to a further decrease in the outer diameter of the insertion portion **21**.

[0082] The present invention is not limited to the above-described embodiments, and naturally, various modifications and applications can be performed without departing from the spirit of the invention. Furthermore, in the above embodiments, inventions in various stages are included, and various inventions can be extracted by appropriate combinations of a plurality of disclosed component requirements. For example, even when some component requirements are excluded from all component requirements shown in the above embodiments, the configuration in which the component requirements are excluded can be extracted as an invention as long as the problem to be solved by the invention can be solved and the effects of the invention can be obtained.

Furthermore, component elements in different embodiments may be appropriately combined. The invention is limited only by the attached claims, and is not restricted by particular embodiments.

## Claims

1. An insertion portion for use with an insertion apparatus comprising: a tube configured to be bendable, a distal end portion of the tube disposed radially inward of a part of a distal end body; and a braided tube, a distal end of the braided tube configured to be held between the part of the distal end body and the distal end portion of the tube.
2. The insertion portion according to claim 1, wherein the distal end body includes a distal end metal body, the distal end of the braided tube is held between the distal end metal body and the distal end portion of the tube.
3. The insertion portion according to claim 2, wherein the distal end of the braided tube is held between an inner surface of the distal end metal body and an outer surface of the distal end portion of the tube.
4. The insertion portion according to claim 1, wherein the tube is inserted into the braided tube.

5. The insertion portion according to claim 1, further comprising a ring disposed inside of the distal end body, the tube being inserted into the ring.
  6. The insertion portion according to claim 5, further comprising a wire configured to bend the tube, the wire is fixed to the ring.
  7. The insertion portion according to claim 5, wherein the distal end of the braided tube is disposed distally relative to a distal end of the ring.
  8. The insertion portion according to claim 1, wherein the tube is a multi-lumen tube.
  9. The insertion portion according to claim 1, wherein a hole is disposed in the tube proximally relative to the distal end portion of the tube, the wire is configured to pass through the hole.
  10. The insertion portion according to claim 1, wherein a part of the braided tube is disposed inside of the ring.
  11. The insertion portion according to claim 6, wherein the wire penetrates radially into an interior of the braided tube.
  12. An endoscope comprising: a distal end body; and an insertion portion disposed proximally relative to the distal end body, the insertion portion comprising: a tube configured to be bendable, a distal end portion of the tube disposed radially inward of a part of the distal end body; and a braided tube, a distal end of the braided tube being held between the part of the distal end body and the distal end portion of the tube.
  13. The endoscope according to claim 12, wherein the distal end body includes a distal end metal body, the distal end of the braided tube is held between an inner surface of the distal end metal body and an outer surface of the distal end portion of the tube.
  14. The endoscope according to claim 12, further comprising a ring disposed inside of the distal end body, wherein the tube is inserted into the braided tube, and the tube is inserted into the ring.
  15. The endoscope according to claim 14, further comprising: a wire configured to bend the tube, the wire is fixed to the ring, and an operation portion disposed proximally relative to the insertion portion.
  16. The endoscope according to claim 14, wherein the distal end of the braided tube is disposed distally relative to a distal end of the ring.
  17. The endoscope according to claim 12, wherein the tube is a multi-lumen tube.
  18. The endoscope according to claim 12, wherein a hole is disposed in the tube proximally relative to the distal end portion of the tube, the wire is configured to pass through the hole.
  19. The endoscope according to claim 12, wherein a part of the braided tube is disposed inside of the ring.
  20. The endoscope according to claim 15, wherein the wire penetrates radially into an interior of the braided tube.
-