

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12392218
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Boul; Peter J. et al.

Additive manufacture of wellbore tubulars

Abstract

Provided are systems and method for casing a wellbore of a hydrocarbon well. The casing including disposing a casing print head in a wellbore of a hydrocarbon well, and conducting a downhole casing operation including operating the casing print head to eject casing material to form a casing tubular in the wellbore, and operating the casing print head to eject casing liner material into an annular region located between the casing tubular and a wall of the wellbore to form a casing liner in the annular region, the casing tubular and the casing liner forming a casing of the wellbore.

Inventors:	Boul; Peter J. (Houston, TX), Thaemlitz; Carl J. (Cypress, TX)
Applicant:	Saudi Arabian Oil Company (Dhahran, SA)
Family ID:	1000008762744
Assignee:	Saudi Arabian Oil Company (Dhahran, SA)
Appl. No.:	18/499702
Filed:	November 01, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240060390 A1	Feb. 22, 2024

Related U.S. Application Data

division parent-doc US 17665773 20220207 US 11851979 child-doc US 18499702
division parent-doc US 16206222 20181130 US 11293259 20220405 child-doc US 17665773
us-provisional-application US 62594676 20171205

Publication Classification

Int. Cl.: **B29C64/00** (20170101); **B22F10/00** (20210101); **B22F10/85** (20210101); **B22F12/00** (20210101); **B22F12/82** (20210101); **B28B1/00** (20060101); **B28B13/02** (20060101); **B28B17/00** (20060101); **B29C64/10** (20170101); **B29C64/176** (20170101); **B29C64/182** (20170101); **B29C64/20** (20170101); **B29C64/205** (20170101); **B29C64/227** (20170101); **B29C64/245** (20170101); **B29C64/25** (20170101); **B29C64/255** (20170101); **B29C64/30** (20170101); **B29C64/307** (20170101); **B29C64/386** (20170101); **B29C64/393** (20170101); **B29C64/40** (20170101); **B33Y40/00** (20200101); **B33Y40/10** (20200101); **B33Y40/20** (20200101); **B33Y50/00** (20150101); **B33Y70/00** (20200101); **B33Y70/10** (20200101); **B33Y99/00** (20150101); **E21B33/14** (20060101); **E21B41/00** (20060101); **E21B43/10** (20060101); **B33Y10/00** (20150101); **B33Y30/00** (20150101); **B33Y50/02** (20150101); **B33Y80/00** (20150101)

U.S. Cl.:

CPC **E21B33/14** (20130101); **B22F10/00** (20210101); **B22F10/85** (20210101); **B22F12/00** (20210101); **B22F12/82** (20210101); **B28B1/001** (20130101); **B28B13/022** (20130101); **B28B13/0275** (20130101); **B28B17/0081** (20130101); **B29C64/00** (20170801); **B29C64/10** (20170801); **B29C64/176** (20170801); **B29C64/182** (20170801); **B29C64/20** (20170801); **B29C64/205** (20170801); **B29C64/227** (20170801); **B29C64/245** (20170801); **B29C64/25** (20170801); **B29C64/255** (20170801); **B29C64/30** (20170801); **B29C64/307** (20170801); **B29C64/386** (20170801); **B29C64/393** (20170801); **B29C64/40** (20170801); **B33Y40/00** (20141201); **B33Y40/10** (20200101); **B33Y40/20** (20200101); **B33Y50/00** (20141201); **B33Y70/00** (20141201); **B33Y70/10** (20200101); **B33Y99/00** (20141201); **E21B41/0078** (20130101); **E21B43/10** (20130101); **B33Y10/00** (20141201); **B33Y30/00** (20141201); **B33Y50/02** (20141201); **B33Y80/00** (20141201)

Field of Classification Search

CPC: E21B (33/14); B33Y (40/00)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2387002	12/1944	Bannister	N/A	N/A
3690378	12/1971	Land	N/A	N/A
5092265	12/1991	Hughes et al.	N/A	N/A
5255853	12/1992	Munoz	N/A	N/A
6613154	12/2002	Lester	N/A	N/A
7153454	12/2005	Khoshnevis	N/A	N/A
9388078	12/2015	Rael	N/A	N/A
10961813	12/2020	Boul et al.	N/A	N/A
11293257	12/2021	Boul et al.	N/A	N/A
11293258	12/2021	Boul et al.	N/A	N/A
11293259	12/2021	Boul et al.	N/A	N/A
2013/0062072	12/2012	Alvarez et al.	N/A	N/A
2013/0320598	12/2012	Atkins et al.	N/A	N/A

2014/0262668	12/2013	Austin et al.	N/A	N/A
2015/0034311	12/2014	Tunget	N/A	N/A
2015/0054195	12/2014	Greyf	N/A	N/A
2015/0083422	12/2014	Pritchard	N/A	N/A
2016/0107332	12/2015	Grivetti	N/A	N/A
2016/0326853	12/2015	Fredd et al.	N/A	N/A
2016/0341018	12/2015	Bell et al.	N/A	N/A
2016/0370499	12/2015	Berard et al.	N/A	N/A
2017/0173886	12/2016	Menchik et al.	N/A	N/A
2017/0175905	12/2016	Martino et al.	N/A	N/A
2017/0203468	12/2016	Sherman et al.	N/A	N/A
2017/0211331	12/2016	Vempati et al.	N/A	N/A
2017/0342797	12/2016	Murphree et al.	N/A	N/A
2018/0056544	12/2017	Kreiger et al.	N/A	N/A
2018/0093373	12/2017	Niederberger	N/A	N/A
2019/0078416	12/2018	Vick, Jr. et al.	N/A	N/A
2021/0353345	12/2020	Sahin et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
104297097	12/2014	CN	N/A
104891891	12/2014	CN	N/A
104961367	12/2014	CN	N/A
105731942	12/2015	CN	N/A
107313749	12/2016	CN	N/A
2503203	12/2012	GB	N/A
20170120762	12/2016	KR	N/A
2013043217	12/2012	WO	N/A
2013043908	12/2012	WO	N/A

OTHER PUBLICATIONS

Ali, Md. Hazrat et al.; “Development of a Robot for Boiler Tube Inspection” Proceedings of the 15th International Conference on Informatics in Control, Automation and Robotics (ICINCO)—vol. 2; pp. 534-541. cited by applicant

<https://www.designboom.com/technology/rise-v3-pole-climbing-robot/> (Year: 2009); pp. 1-6. cited by applicant

<https://www.instructables.com/Tree-Climbing-Robot/> (Year: 2014); pp. 1-40. cited by applicant

https://www.youtube.com/watch?v=TgPkXHf1_i6E&t=72s (Year: 2015). cited by applicant

International Search Report and Written Opinion for related PCT application PCT/US2018/063267 (SA5738) dated Feb. 21, 2019; pp. 1-12. cited by applicant

International Search Report and Written Opinion for related PCT application PCT/US2018/063270 (SA51038) dated Feb. 21, 2019; pp. 1-14. cited by applicant

International Search Report and Written Opinion for related PCT application PCT/US2018/063273 (SA51039) dated Feb. 21, 2019; pp. 1-12. cited by applicant

International Search Report and Written Opinion for related PCT application PCT/US2018/063278 (SA51040) dated Mar. 7, 2019; pp. 1-13. cited by applicant

Libonati, Flavia et al.; “Bone-Inspired Materials by Design: Toughness Application Observed Using 3D Printing and Testing**” Advanced Engineering Materials 2016, 18, No. 8; pp. 1354-1363. cited by applicant

Primary Examiner: Krasnow; Nicholas R

Attorney, Agent or Firm: Bracewell LLP

Background/Summary

RELATED APPLICATIONS (1) This application is a divisional of U.S. patent application Ser. No. 17/665,773 filed on Feb. 7, 2022, and titled "ADDITIVE MANUFACTURE OF WELLBORE TUBULARS," which is a divisional of U.S. patent application Ser. No. 16/206,222, now U.S. Pat. No. 11,293,259, filed on Nov. 30, 2018 and titled "ADDITIVE MANUFACTURE OF WELLBORE TUBULARS" which claims the benefit of U.S. Provisional Patent Application No. 62/594,676 filed on Dec. 5, 2017 and titled "ADDITIVE MANUFACTURE OF CEMENTITIOUS MATERIALS IN A WELLBORE," each of which are hereby incorporated by reference in their entireties.

FIELD

(1) Embodiments relate generally to developing wells, and more particularly to additive manufacture of cementitious materials in a wellbore of a well.

BACKGROUND

(2) A well includes a wellbore (or "borehole") that is drilled into the earth to provide access to a subsurface formation (a geographic formation below the earth's surface) to facilitate the extraction of natural resources, such as hydrocarbons and water from the subsurface formation, to facilitate the injection of fluids into the subsurface formation, or to facilitate the evaluation and monitoring of the subsurface formation. In the petroleum industry, wells are often drilled to extract (or "produce") hydrocarbons, such as oil and gas, from subsurface formations. The term "oil well" is used to refer to a well designed to produce oil. In the case of an oil well, some natural gas is typically produced along with oil. A well producing both oil and natural gas is sometimes referred to as an "oil and gas well" or "oil well."

(3) Creating an oil well typically involves several stages, including a drilling stage, a completion stage and a production stage. The drilling stage normally involves drilling a wellbore into a subsurface formation that is expected to contain a concentration of hydrocarbons that can be produced. The portion of the subsurface formation expected to contain hydrocarbons is often referred to as a "hydrocarbon reservoir" or "reservoir." The drilling process is usually facilitated by a drilling rig that sits at the earth's surface. The drilling rig provides for operating a drill bit to cut the wellbore, hoisting, lowering and turning drill pipe and tools, circulating drilling fluids in the wellbore, and generally controlling various operations in the wellbore (or "down-hole" operations). The completion stage involves making the well ready to produce hydrocarbons. In some instances, the completion stage includes installing casing pipe into the wellbore, cementing the casing in place, perforating the casing pipe and cement, installing production tubing, and pumping fluids into the well to fracture, clean or otherwise prepare the reservoir and well to produce hydrocarbons. The production stage involves producing hydrocarbons from the reservoir by way of the well. During the production stage, the drilling rig is normally removed and replaced with a collection of valves, often referred to as a "production tree", that regulates pressure in the wellbore, controls production flow from the wellbore and provides access to the wellbore in the event further completion work is needed. A pump jack or other mechanism is sometimes used to provide lift that assists in extracting hydrocarbons from the reservoir, especially in instances where the pressure in the well is so low

that the hydrocarbons do not flow freely to the surface. Flow from an outlet valve of the production tree is normally connected to a distribution network of midstream facilities, such as tanks, pipelines and transport vehicles that transport the production to downstream facilities, such as refineries and export terminals.

(4) A casing operation of a well completion can be particularly important for establishing the integrity of the well. The casing assembly usually includes a large diameter rigid casing pipe (for example, hollow-cylindrical steel pipe) that is inserted into the wellbore and is held in place by a hardened material, such as cement, disposed in an annular region formed between an exterior of the casing pipe and the wall of the wellbore. A casing operation typically includes lowering the casing pipe into the wellbore and pumping cement into the annular region to secure the casing pipe in place and effectively seal the annular region to prevent fluids and gasses from moving through the annular region. During completion operations the casing pipe and cement are often perforated to provide fluid communication with the surrounding portion of the reservoir. For example, in the case of a production oil well in which a given depth interval of the reservoir is expected to contain oil and gas, perforations can be made in the casing pipe and cement across the depth interval to facilitate the flow of oil and gas from the reservoir, into the interior of the casing pipe. During the production stage, the interior of casing pipe, or production tubing located inside the casing, can serve as a conduit to direct the oil and gas to the surface.

(5) In a traditional well the casing system often contains multiple intervals of casing successively placed within previous casing runs that extend deep into the wellbore. These can include, for example, a conductor pipe extending from the earth's surface into a first depth interval, surface casing extending from the conductor pipe into a second depth interval, intermediate casing extending from the surface casing into a third depth interval, and production casing extending from the intermediate casing into a fourth depth interval. The production casing may, for example, include perforations that provide fluid communication with a production zone of the surrounding reservoir within the fourth depth interval. The casing typically serves multiple functions that are critical to operating and maintaining integrity of the well. The casing can prevent the formation from caving into the wellbore (for example, by providing a rigid structure lining the wellbore), can provide for control of downhole pressure (for example, by sealing the annular region to direct pressurized formation fluids into the interior of the casing where it can be controlled by valves coupled to the casing), and can provide for selective isolation of different portions of the formation (for example, by sealing-off a first depth interval of the wellbore to inhibit water production across the first depth interval and providing a conduit for oil production from a second depth interval where perforations are present).

SUMMARY

(6) Applicant has recognized that existing techniques for casings wells have shortcomings. For example, traditional casing operations may not provide a suitable level of structural integrity. In many instances, a casing operation involves installing a casing pipe into a wellbore and a cementing operation to secure the casing pipe in the wellbore. The cementing operation normally involves determining a volume of an annular region formed between an exterior of the casing pipe and the wall of the wellbore to be filled with cement, pumping the determined volume of cement into the annular region, and allowing the cement to harden to fix the casing pipe in place. This can include, for example, pumping a volume of cement slurry down through an interior of the casing pipe, where it is expelled from a down-hole end of the casing and moves up-hole into the annular region, to fill the annular region. Unfortunately, the movement and placement of the cement can be difficult to predict and track, and is prone to forming inconsistencies that can compromise the integrity of the cement. For example, imprecise placement of the cement may create undesirable voids in the cement that can lead to unexpected fractures, and even catastrophic ruptures when the cement is exposed to high pressure fluids in the wellbore. Given the importance of cement integrity, well operators dedicate a significant amount of time and money to inspect and monitor

the cement, both at the time of installation and over the life of the well. For example, a well operator may regularly conduct logging operations to assess the condition of the cement over the life of a well. Thus, traditional casing operations may introduce inconsistencies that have to be identified and monitored, thereby adding to the complexity, risks and costs of developing and operating a well.

(7) As a further example of a shortcoming, traditional casing operations can be time consuming and costly. In many instances, a casing operation requires a significant amount of time to place the casing pipe and cement the casing pipe in place, and requires other operations to be suspended while the casing operation is completed. For example, after a first depth interval of a well is drilled, a drilling string (for example, including drill pipe and a drill bit) may be removed, a first interval of casing pipe may be positioned in the first depth interval of the wellbore, cement slurry may be pumped into the annular region, additional time may be taken to allow the cement to harden, and, once the cement has hardened, the drilling of the next depth interval may proceed. This can include, for example, drilling out the hardened cement at the bottom of the casing and proceeding to drill deeper into the formation. Thus, traditional casing operations can require a stop-start approach that requires additional runs and operations (for example, pulling a drill string, running the casing pipe, cementing the casing pipe in place, and re-running the drill string) that increase the time and costs for drilling and completing a well.

(8) Recognizing these and other shortcomings of existing well casing operations, Applicant has developed novel systems and methods for casing wells. In some embodiments, a casing operation for a wellbore employs an additive manufacturing (AM) technique, such as three-dimensional (3D) printing, to deposit a wellbore lining material, such as cement, in the wellbore. For example, an additive printing device, such as a 3D cement printing head, may be positioned in an annular region of the wellbore, located between an exterior of casing pipe positioned in the wellbore and the wall of the wellbore. The additive printing device may be operated to precisely deposit layers of cement in the annular region as it is advanced along a length of the annular region of the wellbore to create printed layers of a casing liner that, in combination, form a volume of a printed casing liner that fills a depth interval of the annular region. Advantageously, the precise incremental placement of the casing liner material can help to ensure that the casing liner material is deposited in specific locations and does not include inconsistencies, such as unwanted voids, that can negatively impact the mechanical properties of the casing liner and compromise the integrity of the casing. For example, the additive manufacture of the cement can enable the precise control and monitoring of the amount of cement deposited in each location within the annular region to form a printed cement casing liner.

(9) In some embodiments, the additive printing device includes a printing head having one or more nozzles that deliver the wellbore lining material to particular locations within the wellbore. For example, the additive printing device may include a 3D cement printing head having one or more nozzles that eject the casing liner material, such as cement, to particular locations within the annular region. In some embodiments, the one or more nozzles include nozzles for depositing different materials that form the printed casing liner. For example, the one or more nozzles may include a set of cement nozzles for depositing cement, and a set of additive nozzles for depositing additives, such as polymers, that can be deposited with the cement to form the printed cement casing. Such an arrangement may enable multiple materials to be deposited simultaneously during a cementing operation to form a printed casing liner that includes a cementitious matrix of cement and other materials.

(10) In some embodiments, the printed casing liner is formed to include integrated structures that modify mechanical properties of the casing liner. In some embodiments, the integrated structures include volumes within the printed casing liner that are void of the casing liner material. For example an integrated structure may include a void in the printed casing cement liner that includes a volume of a gas, liquid or solid (other than cement material) that is encapsulated in the cement

material. In some embodiments, the integrated structures are strategically positioned and shaped to effect particular modifications to the mechanical properties of the casing liner, such as ductility or impact resistance. For example, the printed cement casing liner may be printed to include a pattern of integrated structures extending in a radial or longitudinal direction of the wellbore. Such integrated structures may reduce the Young's Modulus of the printed casing cement (relative to that of a solid cement structure) in the radial or longitudinal direction, thereby enabling the cement to deform radially or longitudinally to absorb variations in radial or longitudinal stresses acting on the printed cement casing liner, without cracking or otherwise failing.

(11) In some embodiments, an integrated structure is formed in the wellbore independent of the depositing of the casing liner material. For example, an integrated structure, such as a honeycomb shaped polymer material, may be printed in the annular region of the wellbore to form an integrated structure having contiguous voids formed in the structure. Then, cement material may be injected into the contiguous voids of the integrated structure to form a printed casing liner formed of a cementitious matrix of the cement material and integrated structure material. In some embodiments, the casing liner material is formed in the wellbore independent of the integrated structures. For example, the cement material may be printed in the annular region of the wellbore with one or more contiguous integrated void structures formed in the cement material, such as a contiguous honeycomb shaped void structure. Then, an integrated structure material, such as a polymer, may be injected into the one or more contiguous integrated void structures of the printed cement material to form a printed casing liner formed of a cementitious matrix of the cement material and the additive material structure.

(12) Provided in some embodiments is a method that includes drilling a wellbore into a subsurface formation, positioning casing pipe in the wellbore, and conducting a cementing operation including additive manufacture of a casing liner in an annular region between an exterior of the casing pipe and a wall of the wellbore.

(13) In some embodiments, the casing liner includes a cementitious material and the cementing operation includes a print head depositing the cementitious material into position to form the casing liner as the print head is advanced within the annular region. In certain embodiments, the casing liner includes a casing liner material and one or more integrated structures formed in the casing liner material. In some embodiments, the casing liner material includes cement. In certain embodiments, at least one of the one or more integrated structures includes a void in the casing liner material containing a substance other than the cement. In some embodiments, the substance includes a gas, a fluid or a solid other than the cement. In some embodiments, the one or more integrated structures include elongated voids in the casing liner material extending in a radial direction in the annular region and containing a substance having a Young's Modulus that is less than a Young's Modulus of the casing liner material such that the casing liner has a Young's Modulus in the radial direction that is less than the Young's Modulus of the casing liner material. In certain embodiments, the integrated structures include elongated voids in the casing liner material extending in a longitudinal direction in the annular region and containing a substance having a Young's Modulus that is less than a Young's Modulus of the casing liner material such that the casing liner has a Young's Modulus in the longitudinal direction that is less than the Young's Modulus of the casing liner material. In some embodiments, the additive manufacture of the casing liner includes additive manufacture of an integrated structure in the annular region (the integrated structure having one or more voids formed therein) and the cementing operation further includes injecting a cementitious material into the one or more voids of the integrated structure.

(14) In certain embodiments, the additive manufacture of the casing liner includes additive manufacture of a cement structure in the annular region (the cement structure having one or more voids formed therein) and the cementing operation further includes injecting a substance into the one or more voids of the cement structure. In some embodiments, positioning the casing pipe in the wellbore includes conducting additive manufacture of the casing pipe in the wellbore. In some

embodiments, the additive manufacture of a casing liner in the annular region and the additive manufacturing of the casing pipe in the wellbore include forming one or more perforations in the casing liner and the casing pipe to facilitate flow of substances between the formation and a central passage of the casing pipe.

(15) Provided in some embodiments is a well system that includes an additive manufacture device including a print head including one or more nozzles adapted to deposit casing liner material in a wellbore of a well, and a well control system adapted to perform a cementing operation including controlling the additive manufacture device to perform an additive manufacture of a casing liner in the wellbore including depositing the casing liner material in an annular region of the wellbore located between an exterior of a casing pipe positioned in the wellbore and a wall of the wellbore to form a casing liner in the wellbore.

(16) In some embodiments, the casing liner material includes a cementitious material and the cementing operation includes controlling the print head to advance within the annular region and deposit the cementitious material into position to form the casing liner as the print head is advanced within the annular region. In certain embodiments, the casing liner includes a casing liner material and one or more integrated structures formed in the casing liner material. In some embodiments, the casing liner material includes cement. In certain embodiments, at least one of the one or more integrated structures includes a void in the casing liner material containing a substance other than the cement. In some embodiments, the substance includes a gas, a fluid or a solid other than the cement. In certain embodiments, the one or more integrated structures include elongated voids in the casing liner material extending in a radial direction in the annular region and containing a substance having a Young's Modulus that is less than a Young's Modulus of the casing liner material such that the casing liner has a Young's Modulus in the radial direction that is less than the Young's Modulus of the casing liner material. In some embodiments, the integrated structures include elongated voids in the casing liner material extending in a longitudinal direction in the annular region and containing a substance having a Young's Modulus that is less than a Young's Modulus of the casing liner material such that the casing liner has a Young's Modulus in the longitudinal direction that is less than the Young's Modulus of the casing liner material.

(17) In certain embodiments, the additive manufacture of the casing liner includes additive manufacture of an integrated structure in the annular region (the integrated structure having one or more voids formed therein) and the cementing operation further includes controlling injection of a cementitious material into the one or more voids of the integrated structure. In some embodiments, the additive manufacture of the casing liner includes additive manufacture of a cement structure in the annular region (the cement structure having one or more voids formed therein) and the cementing operation further includes controlling injection of a substance into the one or more voids of the cement structure. In some embodiments, the well control system is further adapted to perform a casing pipe operation including controlling the additive manufacture device to perform an additive manufacture of the casing pipe in the wellbore. In some embodiments, the additive manufacture of a casing liner in the annular region and the additive manufacturing of the casing pipe in the wellbore include forming one or more perforations in the casing liner and the casing pipe to facilitate flow of substances between the formation and a central passage of the casing pipe.

(18) Provided in some embodiments, is a non-transitory computer readable medium including program instructions stored thereon that are executable by a processor to cause the operations of drilling a wellbore into a subsurface formation, positioning casing pipe in the wellbore, and conducting a cementing operation including additive manufacture of a casing liner in an annular region between an exterior of the casing pipe and a wall of the wellbore.

(19) In some embodiments, the casing liner includes a cementitious material and the cementing operation includes a print head depositing the cementitious material into position to form the casing liner as the print head is advanced within the annular region. In certain embodiments, the casing liner includes a casing liner material and one or more integrated structures formed in the casing

liner material. In some embodiments, the casing liner material includes cement. In certain embodiments, at least one of the one or more integrated structures includes a void in the casing liner material containing a substance other than the cement. In some embodiments, the substance includes a gas, a fluid or a solid other than the cement. In certain embodiments, the one or more integrated structures include elongated voids in the casing liner material extending in a radial direction in the annular region and containing a substance having a Young's Modulus that is less than a Young's Modulus of the casing liner material such that the casing liner has a Young's Modulus in the radial direction that is less than the Young's Modulus of the casing liner material. In some embodiments, the integrated structures include elongated voids in the casing liner material extending in a longitudinal direction in the annular region and containing a substance having a Young's Modulus that is less than a Young's Modulus of the casing liner material such that the casing liner has a Young's Modulus in the longitudinal direction that is less than the Young's Modulus of the casing liner material.

(20) In certain embodiments, the additive manufacture of the casing liner includes additive manufacture of an integrated structure in the annular region (the integrated structure having one or more voids formed therein) and the cementing operation further includes injecting a cementitious material into the one or more voids of the integrated structure. In some embodiments, the additive manufacture of the casing liner includes additive manufacture of a cement structure in the annular region (the cement structure having one or more voids formed therein) and the cementing operation further includes injecting a substance into the one or more voids of the cement structure. In certain embodiments, positioning the casing pipe in the wellbore includes conducting additive manufacture of the casing pipe in the wellbore. In some embodiments, the additive manufacture of a casing liner in the annular region and the additive manufacturing of the casing pipe in the wellbore include forming one or more perforations in the casing liner and the casing pipe to facilitate flow of substances between the formation and a central passage of the casing pipe.

(21) Provided in some embodiments is a method of casing a wellbore of a hydrocarbon well. The method including disposing a casing print head in a wellbore of a hydrocarbon well, and conducting a downhole casing operation including operating the casing print head to eject casing material to form a casing tubular in the wellbore, and operating the casing print head to eject casing liner material into an annular region located between the casing tubular and a wall of the wellbore to form a casing liner in the annular region, the casing tubular and the casing liner forming a casing of the wellbore.

(22) In some embodiments, the downhole casing operation includes advancing the casing print head along a length of the wellbore and ejecting the casing material and the casing liner material along the length of the wellbore to form the casing along the length of the wellbore. In certain embodiments, the downhole casing operation includes forming a perforation in the casing. In some embodiments, forming a perforation in the casing includes operating the casing print head to form a contiguous void extending across the casing tubular and the casing liner. In certain embodiments, operating the casing print head to form a contiguous void extending across the casing tubular and the casing liner includes operating the casing print head to deposit a disposable material to define the contiguous void extending across the casing tubular and the casing liner, and the method further including performing a perforation operation including removing the disposable material. In some embodiments, the disposable material includes a dissolvable material, and where the perforation operation includes exposing the dissolvable material to a substance adapted to dissolve the dissolvable material. In certain embodiments, the casing material includes a metal material. In some embodiments, the casing material includes steel. In certain embodiments, the casing liner material includes a cementitious material. In some embodiments, the casing liner material includes casing cement.

(23) Provided in some embodiments is a wellbore casing system that includes a casing print head adapted to be disposed in a wellbore of a hydrocarbon well, and adapted to eject casing material to

form a casing tubular in the wellbore, and eject casing liner material into an annular region located between the casing tubular and a wall of the wellbore to form a casing liner in the annular region, the casing tubular and the casing liner forming a casing of the wellbore.

(24) In some embodiments, the casing print head is adapted to be advanced along a length of the wellbore and eject the casing material and the liner casing material along a length of the wellbore to form the casing along the length of the wellbore. In certain embodiments, the downhole casing operation includes forming a perforation in the casing. In some embodiments, forming a perforation in the casing includes forming a contiguous void extending across the casing tubular and the casing liner. In some embodiments, forming a contiguous void extending across the casing tubular and the casing liner includes depositing a disposable material to define the contiguous void extending across the casing tubular and the casing liner, where the disposable material is removable. In certain embodiments, the disposable material includes a dissolvable material. In some embodiments, the casing material includes a metal material. In certain embodiments, the casing material includes steel. In some embodiments, the casing liner material includes a cementitious material. In certain embodiments, the casing liner material includes casing cement.

(25) Provided in some embodiments is a method of lining a wellbore of a hydrocarbon well. The method including disposing a liner print head in a wellbore of a hydrocarbon well and conducting a downhole lining operation including operating the lining print head to eject tubular material to form a tubular in the wellbore, and operating the lining print head to eject liner material into an annular region located between the tubular and a wall of the wellbore to form, in the annular region, a casing liner in the wellbore, the tubular and the casing liner forming a lined tubular in the wellbore. In some embodiments, the downhole lining operation includes advancing the lining print head along a length of the wellbore and ejecting the tubular material and the lining material along the length of the wellbore to form the casing along the length of the wellbore. In certain embodiments, the tubular material includes metal and the lining material includes a cementitious material.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is diagram that illustrates a well environment in accordance with one or more embodiments.
- (2) FIGS. 2A and 2B are diagrams that illustrate an example casing liner formed by way of an additive manufacturing process in accordance with one or more embodiments.
- (3) FIG. 3 is a diagram that illustrates an example of casing liner including integrated structures in accordance with one or more embodiments.
- (4) FIGS. 4A and 4B are diagrams that illustrate an example casing liner including integrated structures formed by way of an additive manufacturing process in accordance with one or more embodiments.
- (5) FIGS. 5A and 5B are diagrams that illustrate an example casing liner containing radially oriented integrated structures in accordance with one or more embodiments.
- (6) FIGS. 6A and 6B are diagrams that illustrate an example casing liner containing longitudinally oriented integrated structures in accordance with one or more embodiments.
- (7) FIG. 7A-7N are diagrams that illustrate an example structures in accordance with one or more embodiments.
- (8) FIG. 8 is a flowchart that illustrates a method of printing a casing liner in accordance with one or more embodiments.
- (9) FIGS. 9A and 9B are diagrams that illustrate an example casing formed by way of an additive manufacturing process in accordance with one or more embodiments.
- (10) FIG. 10 is a diagram that illustrates printing casing having integrated structures, including

perforations in accordance with one or more embodiments.

(11) FIG. 11 is a flowchart that illustrates a method of printing a casing in accordance with one or more embodiments.

(12) FIG. 12 is a diagram that illustrates an example computer system in accordance with one or more embodiments.

(13) While this disclosure is susceptible to various modifications and alternative forms, specific embodiments are shown by way of example in the drawings and will be described in detail. The drawings may not be to scale. It should be understood that the drawings and the detailed descriptions are not intended to limit the disclosure to the particular form disclosed, but are intended to disclose modifications, equivalents, and alternatives falling within the spirit and scope of the present disclosure as defined by the claims.

DETAILED DESCRIPTION

(14) Described are embodiments of systems and methods for casing wells. In some embodiments, a casing operation for a wellbore employs an additive manufacturing (AM) technique, such as three-dimensional (3D) printing, to deposit a wellbore lining material, such as cement, in the wellbore. For example, an additive printing device, such as a 3D cement printing head, may be positioned in an annular region of the wellbore, located between an exterior of casing pipe positioned in the wellbore and the wall of the wellbore. The additive printing device may be operated to precisely deposit layers of cement in the annular region as it is advanced along a length of the annular region of the wellbore to create printed layers of a casing liner that, in combination, form a volume of a printed casing liner that fills a depth interval of the annular region. Advantageously, the precise incremental placement of the casing liner material can help to ensure that the casing liner material is deposited in specific locations and does not include inconsistencies, such as unwanted voids, that can negatively impact the mechanical properties of the casing liner and compromise the integrity of the casing. For example, the additive manufacture of the cement can enable the precise control and monitoring of the amount of cement deposited in each location within the annular region to form a printed cement casing liner.

(15) In some embodiments, the additive printing device includes a printing head having one or more nozzles that deliver the wellbore lining material to particular locations within the wellbore. For example, the additive printing device may include a 3D cement printing head having one or more nozzles that eject the casing liner material, such as cement, to particular locations within the annular region. In some embodiments, the one or more nozzles include nozzles for depositing different materials that form the printed casing liner. For example, the one or more nozzles may include a set of cement nozzles for depositing cement, and a set of additive nozzles for depositing additives, such as polymers, that can be deposited with the cement to form the printed cement casing. Such an arrangement may enable multiple materials to be deposited simultaneously during a cementing operation to form a printed casing liner that includes a cementitious matrix of cement and other materials.

(16) In some embodiments, the printed casing liner is formed to include integrated structures that modify mechanical properties of the casing liner. In some embodiments, the integrated structures include volumes within the printed casing liner that are void of the casing liner material. For example an integrated structure may include a void in the printed casing cement liner that includes a volume of a gas, liquid or solid (other than cement material) that is encapsulated in the cement material. In some embodiments, the integrated structures are strategically positioned and shaped to effect particular modifications to the mechanical properties of the casing liner, such as ductility or impact resistance. For example, the printed cement casing liner may be printed to include a pattern of integrated structures extending in a radial or longitudinal direction of the wellbore. Such integrated structures may reduce the Young's Modulus of the printed casing cement (relative to that of a solid cement structure) in the radial or longitudinal direction, thereby enabling the cement to deform radially or longitudinally to absorb variations in radial or longitudinal stresses acting on the

printed cement casing liner, without cracking or otherwise failing.

(17) In some embodiments, an integrated structure is formed in the wellbore independent of the depositing of the casing liner material. For example, an integrated structure, such as a honeycomb shaped polymer material, may be printed in the annular region of the wellbore to form an integrated structure having contiguous voids formed in the structure. Then, cement material may be injected into the contiguous voids of the integrated structure to form a printed casing liner formed of a cementitious matrix of the cement material and integrated structure material. In some embodiments, the casing liner material is formed in the wellbore independent of the integrated structures. For example, the cement material may be printed in the annular region of the wellbore with one or more contiguous integrated void structures formed in the cement material, such as a contiguous honeycomb shaped void structure. Then, an integrated structure material, such as a polymer, may be injected into the one or more contiguous integrated void structures of the printed cement material to form a printed casing liner formed of a cementitious matrix of the cement material and the additive material structure.

(18) FIG. 1 is diagram that illustrates a well environment **100** in accordance with one or more embodiments. In the illustrated embodiment, the well environment **100** includes a hydrocarbon reservoir (“reservoir”) **102** located in a subsurface formation (“formation”) **104** and a well system (“well”) **106**.

(19) The formation **104** may include a porous or fractured rock formation that resides underground, beneath the earth's surface (“surface”) **108**. In the case of the well **106** being a hydrocarbon well, the reservoir **102** may include a portion of the formation **104** that contains (or is at least determined to or expected to contain) a subsurface pool of hydrocarbons, such as oil and gas. The formation **104** and the reservoir **102** may each include different layers of rock having varying characteristics, such as varying degrees of permeability, porosity, and resistivity. In the case of the well **106** being operated as a production well, the well **106** may facilitate the extraction (or “production”) of hydrocarbons from the reservoir **102**. In the case of the well **106** being operated as an injection well, the well **106** may facilitate the injection of fluids, such as water, into the reservoir **102**. In the case of the well **106** being operated as a monitoring well, the well **106** may facilitate the monitoring of characteristics of the reservoir **102**, such as reservoir pressure or water encroachment.

(20) The well **106** may include a wellbore **120**, a well control system (“control system”) **122** and a well casing system **124**. The well control system **122** may control various operations of the well **106**, such as well drilling operations, well completion operations, well injection operations, and well and formation monitoring operations. In some embodiments, the well control system **122** includes a computer system that is the same as or similar to that of computer system **2000** described with regard to at least FIG. 12.

(21) The wellbore **120** may include a bored hole that extends from the surface **108** into a target zone of the formation **104**, such as the reservoir **102**. An upper end of the wellbore **120** at or near the surface **108** may be referred to as the “up-hole” end of the wellbore **120**, and a lower end of the wellbore **120** terminating in the formation **104** may be referred to as the “down-hole” end of the wellbore **120**. The wellbore **120** may be created, for example, by a drill bit boring through the formation **104** and the reservoir **102**. The wellbore **120** can provide for the circulation of drilling fluids during drilling operations, the flow of hydrocarbons (for example, oil and gas) from the reservoir **102** to the surface **108** during production operations, the injection of substances (for example, water) into one or both of the formation **104** and the reservoir **102** during injection operations, or the communication of monitoring devices (for example, logging tools) into one or both of the formation **104** and the reservoir **102** during monitoring operations (for example, during in situ logging operations).

(22) In some embodiments, the wellbore **120** includes cased or uncased portions. For example the wellbore **120** may have a cased portion **132** and an uncased (or “open-hole”) portion **134**. The cased portion **132** may include a portion of the wellbore **120** having casing **140** of the well casing

system **124** disposed in that portion. The uncased portion **134** may include a portion of the wellbore **120** not having casing **140** disposed in that portion.

(23) In some embodiments, the casing **140** includes an annular casing that lines the wall of the wellbore **120** to define a central passage **142** that provides a conduit for the transport of tools and substances through the wellbore **120**. For example, the central passage **142** may provide a conduit for lowering logging tools into the wellbore **120**, a conduit for the flow of production substances, such as oil and gas, from the reservoir **102** to the surface **108**, or a conduit for the flow of injection substances, such as water, from the surface **108** into the formation **104**. In some embodiments, the casing **140** includes perforations **144**. The perforations **144** may include openings that extend between an exterior surface of the casing **140** and the central passage **142** of the casing **140** to facilitate the flow of production substances, such as oil and gas, from the reservoir **102** into the central passage **142**, or to facilitate the flow of injection substances, such as water, from the central passage **142** into the formation **104**. Although certain embodiments describe a perforation **144** as one or more elongated holes in the casing **140** for the purpose of illustration, embodiments can include any suitable form of perforations **144**. For example, perforations **144** may include in a mesh structure defined by a plurality of relatively small holes that enable the flow of substances across the holes, while also filtering out larger debris from the flowing substance.

(24) In some embodiments, the casing **140** includes a casing pipe **150** and a casing liner **152**, as illustrated at least in the detail section of FIG. 1. The casing pipe **150** may include a hollow pipe that defines the central passage **142**. The casing pipe **150** may include, for example, a hollow-cylindrical steel pipe. The casing liner **152** may include a rigid material, such as cement, disposed in an annular region **154** located between an exterior surface **156** of the casing pipe **150** and the interior wall **158** of the wellbore **120**. The casing liner **152** may fill the annular region **154** to secure the casing pipe **150** in place and seal the annular region **154**. This can help to inhibit substances, such as high pressure gases and liquids, from bypassing the central passage **142** and flowing through the annular region **154**.

(25) In some embodiments, the casing liner **152** is installed in the annular region **154** by way of an additive manufacturing process. For example, the casing liner **152** may be formed of cement that is deposited into place by way of a 3D cement printing process. FIGS. 2A and 2B are diagrams that illustrate top and side section views of an example casing liner **152** formed by way of an additive manufacturing process in accordance with one or more embodiments. In the illustrated embodiment, a casing liner printing system **200** includes a print head **202** positioned in the annular region **154** of the wellbore **120**. The print head **202** may include one or more nozzles **204** (for example, nozzles **204a-204e**) coupled to a cylindrical collar **206** disposed about the exterior surface **156** of the casing pipe **150**. During a casing liner printing operation of a casing operation, the casing liner printing system **200** may be operated to eject casing liner material **210** from the nozzles **204** to form (or “print”) the casing liner **152**. For example, during a casing liner printing operation, the print head **202** may be rotated about the casing pipe **150** and a longitudinal axis **208** of the wellbore **120** (as illustrated by the arrow **212**) as casing liner material **210**, such as cement, is ejected from the nozzles **204** to deposit the casing liner material **210** in particular locations to form at least a first layer **214a** of the casing liner **152** in the annular region **154**.

(26) In some embodiments, multiple rotational passes of the print head **202** are made in coordination with the print head **202** being advanced along a length of the wellbore **120** (for example, parallel to the longitudinal axis **208** of the wellbore **120**) to deposit multiple casing liner layers **214** of the casing liner material **210** (for example, layers **214a-214e**) to form the casing liner **152**. Continuing with the prior example, during a casing liner printing operation, after the first layer **214a** is formed by way of a first rotational pass of the print head **202** about the casing pipe **150**, the print head **202** may be advanced longitudinally along the length of the wellbore **120** (as illustrated by the arrow **216**) (for example, parallel to a longitudinal axis **208** of the wellbore **120**) by a distance equal to a thickness of a second layer **214b** of the casing liner **152** to be formed, and again

be rotated about the casing pipe **150** (as illustrated by the arrow **212**) while ejecting casing liner material **210** from the nozzles **204** to deposit the casing liner material **210** in particular locations to form the second layer **214b** of the casing liner **152** in the annular region **154**. A similar iterative layering approach can be conducted to form additional layers of the casing liner **152**, such as layers **214c-214e**. The layers **214a-214e** may together form the casing liner **152** across a depth interval **218**. The resulting casing liner layers **214** and casing liner **152** may be referred to as “printed” casing liner layers **214** and a “printed” casing liner **152**, respectively. Although only five layers (layers **214a-214e**) of the casing liner **152** are discussed for the purpose of illustration, embodiments can include any suitable number of layers to form the printed casing liner **152** across a given depth interval. Although embodiments describe advancing the print head **202** vertically in an incremental manner after completing a rotational pass about the wellbore **120**, embodiments can include any suitable path of advancement of the print head **202** to form the casing liner **152**. For example, the print head **202** may be advanced vertically as it is rotated about the wellbore **120** to, for example, form a contiguous helical layer of casing liner material **210** across a depth interval. (27) In some embodiments, the operation of the print head **202**, including the positioning and movement of the print head **202**, the alignment and direction of the nozzles **204**, and the rate of the ejection of the casing liner material **210** from the nozzles **204** is controlled by the well control system **122**, to provide for the deposition of the casing liner material **210** in specific locations. In some embodiments, each of the nozzles **204** includes a flow sensor and deposition sensor that can detect and report a flow rate of the casing liner material **210** from the nozzle and a location of the deposition of the casing liner material **210**, and the flow rate information and deposition information can be used by the well control system **122** to determine whether the casing liner material **210** has been appropriately placed.

(28) In some embodiments, the casing liner **152** contains integrated structures formed within the casing liner material **210**. For example, the casing liner **152** may include a cementitious matrix formed of a cement casing liner material **210** and one or more elements forming integrated structures within the cement casing liner material **210**. FIG. 3 is a diagram that illustrates a section view of an example of the casing liner **152** having integrated structures **162** formed within the casing liner material **210** in accordance with one or more embodiments. In some embodiments, an integrated structure **162** includes a void in the deposited casing liner material **210** that is filled with a volume of a substance other than the casing liner material **210**, such as a gas, liquid or solid. For example, the casing liner **152** may be formed of a cement casing liner material **210** and integrated structures **162** that include pockets of a polymer formed in the cement casing liner material **210**. In some embodiments, an integrated structure **162** may simply include a formed pocket of air, void of the casing liner material **210**.

(29) FIGS. 4A and 4B are diagrams that illustrate top and side section views of an example of the casing liner **152** including integrated structures **162** formed by way of an additive manufacturing process, in accordance with one or more embodiments. In some embodiments, the print head **202** may include a first subset of the nozzles **204** (for example, nozzles **204a-204e**) for depositing a first material, such as a cement casing liner material **210**, and a second subset of the nozzles **204** (for example, nozzles **204f-204j**) for depositing an integrated structure material **400**, such as a polymer, for forming integrated structures **162**. The first subset of the nozzles **204** may include a first row of nozzles extending radially from the cylindrical collar **206** and the second subset of the nozzles **204** may include a second row of nozzles offset from the first row of nozzles. For example, the first subset of the nozzles **204** may include nozzles **204a-204e** forming a first row of the nozzles **204** distributed along a first axis **211a** extending radially from the cylindrical collar **206** and the second subset of the nozzles **204** may include nozzles **204f-204j** forming a second row of the nozzles **204** distributed along a second axis **211b** offset from the first axis **211a**. In such an embodiment, one row of nozzles may “lead” with the second row of nozzles “following” or “trailing”. For example during clockwise rotation of the print head **202**, the second row of nozzles **204** may lead with the

first row of nozzles **204** following, such that the first and second rows of nozzles pass over an area in sequence, one after the other. In some embodiments, the nozzles **204** of each of the rows of nozzles have the same radial distribution such that the two sets of nozzles **204** pass over the same radial locations. For example, the nozzles **204a-204e** may be arranged to follow the same circular path in the annular region **154** as nozzles **204f-204j**, respectively. This may enable different materials to be deposited in a given area in a single rotational pass of the print head **202**. For example, where the nozzles **204a-204e** are employed to deposit a first material (for example, cement) and the nozzles **204f-204j** are employed to deposit a second material (for example, a polymer), either of the first or second material may be deposited in each area of the annular region **154** by controlling each set of the nozzles **204** to eject either the first or second material in each area. Although two rows are described for the purpose of illustration, any suitable arrangement of nozzles **204** may be employed. For example, three offset rows of nozzles **204** may be employed, with each of the three rows being operated to eject first, second and third materials respectively.

(30) During a casing liner printing operation, the casing liner printing system **200** may be operated to eject casing liner material **210** from the first subset of the nozzles **204** (for example, from nozzles **204a-204e**) and to eject integrated structure material **400** from the second set of the nozzles **204** (for example, nozzles **204f-204j**) to form the casing liner **152**. For example, referring to FIGS. **4A** and **4B**, during a casing liner printing operation, in a first pass, the print head **202** may be rotated about the casing pipe (as illustrated by the arrow **212**) as casing liner material **210**, such as cement, is ejected from the nozzles **204a-204e** to deposit the casing liner material **210** in particular locations to form the first layer **214a'** of the casing liner **152** in the annular region **154**. In second, third and fourth passes, the print head **202** may be rotated about the casing pipe **150** and the longitudinal axis **208** of the wellbore **120** (as illustrated by the arrow **212**) as the casing liner material **210** is ejected from the nozzles **204a-204e** to deposit the casing liner material **210** in the shaded portions of the second, third, and fourth layers **214a'**, **214b'** and **214c'**, respectively, and as integrated structure material **400**, such as a polymer, is ejected from the nozzles **204f-204j** to deposit the integrated structure material **400** in the unshaded portions of the second, third, and fourth layers **214b'**, **214c'** and **214d'**, respectively, to form the second, third, and fourth layers **214b'**, **214c'** and **214d'** respectively of the casing liner **152** in the annular region **154**. In a fifth pass the print head **202** may be rotated about the casing pipe **150** and the longitudinal axis **208** of the wellbore **120** (as illustrated by the arrow **212**) as the casing liner material **210** is ejected from the nozzles **204a-204e** to deposit the casing liner material **210** in particular locations to form a fifth layer **214e'** of the casing liner **152** in the annular region **154**. Although a certain shape of integrated structure is described for the purpose of illustration, various shapes and arrangements of integrated structures can be formed using the additive manufacturing processes described, or similar processes.

(31) In some embodiments, the integrated structures **162** are provided to modify mechanical properties of the casing liner **152**. For example, the integrated structures **162** can be strategically positioned, shaped and filled with particular types of substances to effect particular modifications to the mechanical properties of the casing liner **152**, such as ductility or impact resistance. For example, the integrated structures **162** may include pockets filled with a substance, such as a polymer, having a Young's Modulus that is less than a Young's Modulus of the casing liner material **210** to effectively reduce the Young's Modulus of the resulting casing liner **152** to a level below that of the casing liner material **210**. As a further example, the integrated structures **162** may be oriented to extend in a radial direction (for example, perpendicular to the casing pipe **150** or the longitudinal axis **208** of the wellbore **120**) or longitudinal direction (for example, parallel to the casing pipe **150** or the longitudinal axis **208** of the wellbore **120**) in the annular region **154**. Such integrated structures **162** may reduce the Young's Modulus of the casing liner **152** in the radial or longitudinal direction relative to that of a casing liner **152** formed of a solid cement casing liner material **210**. This can, for example, facilitate the casing liner **152** deforming radially or longitudinally to absorb

variations in radial or longitudinal stresses acting on the casing liner **152**, without cracking or otherwise failing.

(32) FIGS. **5A** and **5B** are diagrams that illustrate top and section views of an example of the casing liner **152** containing radially oriented integrated structures **162** formed within casing liner material **210** in accordance with one or more embodiments. In the illustrated embodiment, each of the oriented integrated structures **162** includes an elongated void formed in the casing liner material **210** that extends in a radial direction (for example, perpendicular to the casing pipe **150** and the longitudinal axis **208** of the wellbore **120**) in the annular region **154**. For example, each the oriented integrated structures **162** of FIG. **5A** includes an elongated elliptical shaped void extending radially along a width of the annular region **154** in a lateral direction, generally transverse to the longitudinal axis **208** of the wellbore **120** and the casing pipe **150**. Each of the oriented integrated structures **162** may be encapsulated within the casing liner material **210**. The void of the integrated structures **162** may be filled with a substance, such as a polymer, having a Young's Modulus that is less than a Young's Modulus of the casing liner material **210** and thus may reduce the Young's Modulus of the casing liner **152** in the radial direction, relative to that of a solid casing liner formed of only the casing liner material **210**. As described, each of the oriented integrated structures **162** may be formed by not depositing the casing liner material **210** in the region of the oriented integrated structure **162**, or by depositing integrated structure material **400** into the region of the oriented integrated structure **162** in place of the casing liner material **210**, for example.

(33) FIGS. **6A** and **6B** are diagrams that illustrate top and side section views of an example of the casing liner **152** containing longitudinally oriented integrated structures **162** formed within casing liner material **210** in accordance with one or more embodiments. In the illustrated embodiment, each of the longitudinally oriented integrated structures **162** includes an elongated void formed in the casing liner material **210** that extends in a longitudinally direction (for example, parallel to the casing pipe **150** and the longitudinal axis **208** of the wellbore **120**) in the annular region **154**. For example, each the oriented integrated structures **162** of FIG. **5B** includes an elongated elliptical shaped void extending longitudinally along a length of the annular region **154** in a direction generally parallel to the longitudinal axis **208** of the wellbore **120** and the casing pipe **150**. Each of the oriented integrated structures **162** may be encapsulated within the casing liner material **210**. The void of the integrated structures **162** may be filled with a substance, such as a polymer, having a Young's Modulus that is less than a Young's Modulus of the casing liner material **210** and thus may reduce the Young's Modulus of the casing liner **152** in the longitudinal direction, relative to that of a solid casing liner **152** formed of only the casing liner material **210**. As described, each of the oriented integrated structures **162** may be formed by not depositing the casing liner material **210** in the region of the oriented integrated structure **162**, or by depositing integrated structure material **400** into the region of the oriented integrated structure **162** in place of the casing liner material **210**, for example. Although elliptically shaped integrated structures **162** are described for the purpose of illustration, embodiments may include other suitably shaped integrated structures, as described here.

(34) The integrated structure material **400** that forms the integrated structures **162** may be any of a variety of substances, including gases, liquids or solids. Examples gases include air, nitrogen and helium. Examples of liquids include water, brine (for example, calcium chloride and calcium bromide potassium chloride), organic liquids (for example, N-butyl-pyrrolidone, N-ethyl pyrrolidone, and N-methyl pyrrolidone), organic ionic liquids (for example, imidazolium salts such as butyl-imidazolium tetrafluoroborate), and silicon containing liquids (for example, siloxanes and colloidal silicas). Further examples of liquids can include monomeric liquids, which when activated, cross-polymerize to make liquids with modified rheological properties. Examples of solids include metals (for example, steel, aluminum, and nickel-aluminum alloys), polymers (for example, polyesters, polycarbonates, polyanhydrides, polyamides, polyaramids and polyurethanes),

and cementitious composites (for example, Portland cement, aluminate cements, and pozzolan/lime cements). Although the casing liner material **210** is often described as cement for the purpose of illustration, the casing liner material **210** may include any suitable material, such as an epoxy, phenolic resin, monomeric species such as acrylamide, which when activated, polymerize to render solid materials. In some embodiments, these materials can be either hard-set materials which are solvent-free or materials containing solvent which cure as gels. Further examples include layered composites. These can include combinations of solids, gases or liquids, such as those described above, arranged into layers. Such layered composites may provide advantageous mechanical or chemical properties for conditions within the well-bore.

(35) In some embodiments, an integrated structure **162** is formed in the wellbore independent of the depositing of the casing liner material **210**. For example, an integrated structure **162** formed of the integrated structure material **400**, such as a honeycomb shaped structure formed of a polymer, may be printed in the annular region **154** of the wellbore **120** to form an integrated structure **162** having one or more contiguous voids formed in the structure material. The casing liner material **210**, such as cement, may then be injected into the one or more contiguous voids of the integrated structure **162** to form the casing liner **152** including a matrix of the casing liner material **210** and the material of the integrated structure **162**. In some embodiments, the casing liner material **210** is deposited in the wellbore independent of the deposition of the integrated structure material **400**. For example, the casing liner material **210**, such as cement, may be printed in the annular region **154** of the wellbore **120** with one or more contiguous integrated void structures formed in the casing liner material, such as a contiguous honeycomb shaped void structure. An integrated structure material **400**, such as a polymer, may then be injected into the one or more contiguous integrated void structures of the printed casing liner material **210** to form the casing liner **152** including a matrix of the casing liner material **210** and the material of the integrated structure **162**.

(36) FIGS. 7A-7N illustrate example integrated structures **162** (including integrated structures **700a-700n**) in accordance with one or more embodiments. The arrangement of the integrated structures **162** may be adapted to provide characteristics that are suitable in the wellbore environment in which they are disposed. For example, the integrated structures can include various patterns and can be formed of certain materials or combinations of different materials. In some embodiments, the integrated structures **700a-700n** include structural elements **702** and corresponding void regions **704**. The void regions **704** may include one or more contiguous channels or regions within the structural elements **702** of the respective structure. FIG. 7A illustrates a honeycomb shaped integrated structure **700a** deposited in a wellbore and having longitudinally oriented hexagonal structural elements **702** and corresponding longitudinally oriented hexagonal void regions **704**. FIG. 7B illustrates a honeycomb shaped integrated structure **700b** having radially oriented hexagonal structural elements **702** and corresponding radially oriented hexagonal void regions **704**. FIG. 7C illustrates a mesh shaped integrated structure **700c** having radially oriented structural elements **702** and corresponding radially oriented cylindrical void regions **704**. FIG. 7D illustrates a mesh shaped integrated structure **700d** having radially oriented rectangular structural elements **702** and corresponding radially oriented rectangular void regions **704**. FIG. 7E illustrates a mesh shaped integrated structure **700e** having radially oriented angular structural elements **702** and corresponding radially oriented angular void regions **704**. FIG. 7F illustrates a mesh shaped integrated structure **700f** having radially oriented polygonal structural elements **702** and corresponding radially oriented polygonal void regions **704**. FIG. 7G illustrates a mesh shaped integrated structure **700g** having longitudinal and radially oriented patterned rectangular structural elements **702** and corresponding longitudinal and radially oriented patterned rectangular void regions **704**. FIG. 7H illustrates a mesh shaped integrated structure **700h** having radially oriented wave structural elements **702** and corresponding radially oriented wave void regions **704**. FIG. 7I illustrates a mesh shaped integrated structure **700i** having radially oriented spiral structural elements **702** and corresponding radially oriented spiral void regions **704**. FIG. 7J

illustrates a mesh shaped integrated structure **700j** having radially oriented circular structural elements **702** of varying radial lengths and corresponding radially oriented circular void regions **704**. FIG. 7K illustrates a mesh shaped integrated structure **700k** having radially oriented rectangular block structural elements **702** of varying radially lengths and corresponding radially oriented void regions **704**. FIG. 7L illustrates a mesh shaped integrated structure **700l** having radially oriented prismic block structural elements **702** of varying radially lengths and corresponding radially oriented void regions **704**. FIG. 7M illustrates a mesh shaped integrated structure **700m** having a pattern of radially oriented rectangular block structural elements **702** and corresponding radially oriented void regions **704**. FIG. 7N illustrates a mesh shaped integrated structure **700n** having a pattern of radially oriented rectangular block structural elements **702** (for example, different subsets of the block structural elements **702** being formed of different materials, as indicated by the varied shading of subsets of the blocks) and corresponding radially oriented void regions **704**. Although certain arrangements of integrated structures **162** are described for the purpose of illustration, the arrangements can have any suitable shape, and be formed of any suitable material. For example, the arrangements of integrated structures **162** can include spiral structures, brick layered structures, circular structures, prismic structures, or other geometric shapes, and can include brick patterns, mosaic patterns, parquet patterns, patterns with triangles, circles, squares, or other geometric patterns. The arrangements of integrated structures **162** can be formed of one of or a combination of liquids, solids, and gases.

(37) As described, in some embodiments, the integrated structures **700a-700n** may be formed by way of an additive manufacturing technique, such as three-dimensional 3D printing. For example, an integrated structure **162** formed of the integrated structure material **400**, such as a honeycomb shaped integrated structure **700a** or **700b** formed of a polymer, is printed in the annular region **154** of the wellbore **120** using an additive manufacturing technique. A casing liner material **210**, such as cement, may be injected into the annular region **154** and the void regions **704** to form the casing liner **152** including a matrix of the casing liner material **210** and the integrated structure material **400** of the integrated structure **162**. In some embodiments, the casing liner material **210** is placed to define a structure having voids, and the integrated structure material **400** is deposited in the resulting void regions. For example, a casing liner material **210**, such as cement, having a structure consistent with the structural elements **702** of the integrated structure **162**, such as the honeycomb shaped integrated structure **700a** or **700b**, may be printed in the annular region **154** of the wellbore **120** using an additive manufacturing technique, such as 3D printing, to form printed casing liner material **210** having one or more voids formed in the casing liner material that corresponds to the void regions **704** of the integrated structure **162**, such as the honeycomb shaped voids **704** of integrated structure **700a** or **700b**. An integrated structure material **400**, such as a polymer, may be injected into the void regions **704** formed in the printed casing liner material **210** to form the casing liner **152** including a matrix of the casing liner material **210** and the integrated structure material **400** of the integrated structure **162**. Although a honeycomb shape is discussed for the purpose of illustration, embodiments can employ any suitable structural arrangement, such as those of any of the integrated structures **700a-700n**.

(38) FIG. 8 is a flowchart that illustrates a method **800** of printing a casing liner in accordance with one or more embodiments. The method **800** may generally include drilling a wellbore into a subsurface formation (block **802**), positioning casing pipe in the wellbore (block **804**), and conducting a cementing operation including additive manufacture of a casing liner (block **806**). In some embodiments, drilling a wellbore into a subsurface formation (block **802**) includes drilling the wellbore **120** into the formation **104** and the reservoir **102** as described here. For example, the well control system **122** may control a drilling rig to drill the wellbore **120** into the formation **104** and the reservoir **102** along a given wellbore trajectory. In some embodiments, positioning casing pipe in the wellbore (block **804**) includes positioning the casing pipe **150** into the wellbore **120**. For example, the well control system **122** may control a drilling rig to lower the casing pipe **150** into a

given depth interval of the wellbore **120**. In some embodiments, conducting a cementing operation including additive manufacture of a casing liner (block **806**) includes forming the casing liner **152** in the annular region **154** by way of an additive manufacturing process, such as 3D printing of the casing liner material **210**, or the casing liner material **210** and the integrated structure material **400**, as described here, to form the casing liner **152** without or with integrated structures **162**. For example, the well control system **122** may control the casing liner printing system **200** to deposit the casing liner material **210**, or the casing liner material **210** and the integrated structure material **400**, as described here, to form the casing liner **152** without integrated structures **162** (for example, as described with regard to at least FIGS. 2A and 2B) or with integrated structures **162** (for example, as described with regard to at least FIGS. 3-7).

(39) In some embodiments, additive manufacturing can be employed to manufacture a tubular, such as casing pipe or production tubing in place. For example, the casing liner printing system **200** may be operated to print both the casing liner **152** and the casing pipe **150** downhole, as a print head of the casing liner printing system **200** is advanced through the wellbore **120**. This can, for example, enable a single casing printing operation to replace the running of the casing pipe **150**, such as steel pipe, into the wellbore **120** and the separate installation of the casing liner, such as cement, into the annular region **154**. FIGS. 9A and 9B are diagrams that illustrate top and side section views of an example casing **140** formed by way of an additive manufacturing process in accordance with one or more embodiments. In the illustrated embodiment, a casing printing system **900** includes a casing print head **902** positioned in the wellbore **120**. The casing print head **902** may include multiple nozzles **904** (for example, nozzles **904a-904g**). During a casing printing operation, the casing printing system **900** may be operated to eject casing liner material **210** from a first subset of the nozzles **904** (for example, from nozzles **904a-904e**) and to eject casing pipe material **910** from a second subset of the nozzles **904** (for example, nozzles **904f** and **904g**) to form the casing pipe **150**. For example, during a casing printing operation, the print head **902** may be rotated about the longitudinal axis **208** of the wellbore **120** (as illustrated by the arrow **912**) as casing liner material **210**, such as cement, is ejected from a first subset of the nozzles **904** (for example, nozzles **904a-904e**) and casing pipe material **910**, such as steel, is ejected from a second subset of the nozzles **204** (for example, nozzles **904f** and **904g**) to simultaneously deposit the casing liner material **210** and the casing pipe material **910** in particular locations to form at least a first layer **914a** of the casing **140** in the wellbore **120**.

(40) In some embodiments, multiple rotational passes of the print head **902** are made in coordination with the print head **902** being advanced along the length of the wellbore **120** to deposit multiple layers of casing liner material **210** and casing pipe material **910** to form the casing liner **152** and the casing pipe **150** in the wellbore **120**. Continuing with the prior example, during a casing printing operation, after the first layer **914a** is formed by way of a first rotational pass of the print head **902** about the wellbore **120**, the print head **902** may be advanced longitudinally along the length of the wellbore **120** (for example, parallel to the longitudinal axis **208** of the wellbore **120**) (as illustrated by the arrow **916**) by a distance equal to a thickness of a second layer **914b** of the casing **140** to be formed, and again be rotated about the longitudinal axis **208** of the wellbore **120** (as illustrated by the arrow **912**) as casing liner material **210**, such as cement, is ejected from a first subset of the nozzles **204** (for example, nozzles **904a-904e**) and casing pipe material **910**, such as steel, is ejected from a second subset of the nozzles **204** (for example, nozzles **904f** and **904g**) to simultaneously deposit the casing liner material **210** and the casing pipe material **910** in particular locations to form at least a second layer **914b** of the casing **140** in the wellbore **120**. A similar iterative layering approach can be conducted to form additional layers **914** of the casing liner **152**. For example, additional layers **914c-914e** of the casing **140** may be formed to form the casing **140** across a depth interval **918**. The resulting casing **140** may be referred to as “printed” casing. Although only five layers (**914a-914e**) of the casing **140** are discussed for the purpose of illustration, embodiments can include any suitable number of layers to form the printed casing **140**.

across a given depth interval. Although embodiments describe advancing the print head **902** vertically in an incrementally manner, after completing a rotational pass about the wellbore **120**, embodiments can any suitable path of advancement of the print head **902** to form the casing **140**. For example, the print head **902** may be advanced vertically as it is rotated about the wellbore **120** to, for example, form a contiguous helical layer that forms the printed casing **140** across a depth interval. Although a casing operation is described for the purpose of illustration, embodiments can include forming other types of tubular members in a similar manner. For example, a production tubing may be formed downhole alone, or in conjunction with forming of casing (for example, a production tubing with a casing pipe and a casing liner surrounding the production tubing). In such an embodiment, nozzles may be provided at radial locations corresponding to the walls of the production tubing, and may eject production tubing material, such as steel, to form the production tubing in a manner similar to that described with regard to the casing **140**.

(41) In some embodiments, a casing printing operation can include printing integrated structures into the casing **140**. For example, a casing printing operation can include printing integrated structures similar to those discussed with regard to at least FIGS. 3-7 into the casing liner **152** of the printed casing **140**. In some embodiments, the integrated structures can include perforations. Perforations may include contiguous voids that extend radially through the casing **140** (for example, from an interior wall of the printed casing pipe **150** to an exterior surface of the printed casing liner **152**) to define openings that extend between an exterior of the casing **140** and the central passage **142** of the casing **140**. A perforation may facilitate the flow of production substances, such as oil and gas, from the reservoir **102** into the central passage **142** or to facilitate the flow of injection substances, such as water, from the central passage **142** into the formation **104**. FIG. **10** is a diagram that illustrates printed casing **140** having integrated structures **162**, including perforations **144**, in accordance with one or more embodiments. In some embodiments, the perforations **144** may be formed of a solid substance that initially inhibits flow through the perforation, but that can be dissolved or otherwise removed to enable the flow of fluids there through. For example, a perforation **144** may be formed by printing a polymer into a void region that defines the perforation **144**, and the polymer may later be exposed to a chemical that dissolves the polymer, or an elevated temperature that melts the polymer, leaving a passage defined by the void. Although individual elongated perforations are described for the purpose of illustration, embodiments can include any suitable form of perforation. For example, a perforation **144** may be defined by an integrated mesh (or “screen”) printed into the casing pipe **150** and an adjacent opening(s) formed in the casing liner **152**. The mesh may inhibit debris from traveling between the surrounding portion of the formation and the central passage **142** of the casing **150**.

(42) FIG. **11** is a flowchart that illustrates a method **1100** of printing a casing in accordance with one or more embodiments. The method **1100** may generally include drilling a wellbore into a subsurface formation (block **1102**) and conducting a casing operation including additive manufacture of a casing (block **1104**). In some embodiments, drilling a wellbore into a subsurface formation (block **1102**) includes drilling the wellbore **120** into the formation **104** and the reservoir **102** as described here. For example, the well control system **122** may control a drilling rig to drill the wellbore **120** into the formation **104** and the reservoir **102** along a given wellbore trajectory. In some embodiments, conducting a casing operation including additive manufacture of a casing (block **1104**) includes forming the casing **140** in the wellbore **120** by way of an additive manufacturing process, such as 3D printing of the casing pipe material **910**, the casing pipe material **910** and the casing liner material **210**, or the casing pipe material **910**, the casing liner material **210** and the integrated structure material **400**, as described here, to form the casing **140**, including the casing pipe **150** and the casing liner **152** without or with integrated structures **162**. For example, the well control system **122** may control the print head **902** to deposit the casing pipe material **910**, the casing pipe material **910** and the casing liner material **210**, or the casing pipe material **910**, the casing liner material **210** and the integrated structure material **400**, as described

here, to form the casing **140**, including the casing pipe **150** and the casing liner **152** without or with integrated structures **162**. Although a casing operation is described for the purpose of illustration, embodiments can include forming other types of tubular members in a similar manner. For example, a production tubing may be formed downhole alone, or in conjunction with forming of casing (for example, a production tubing with a casing pipe and a casing liner surrounding the production tubing). In such an embodiment, nozzles may be provided at radial locations corresponding to the walls of the production tubing, and may eject production tubing material, such as steel, to form the production tubing in a manner similar to that described with regard to the casing **140**.

(43) Although certain embodiments describe additive manufacturing including layering in a bottom-up approach (for example, forming a subsequent layer on top of (or on an up-hole side of) a previous layer) to form a printed casing liner **152** or printed casing **140**, embodiments can employ any suitable technique to form a printed casing liner **152** or a printed casing **140**. For example, embodiments can include layering in a top-down approach (for example, forming a subsequent layer underneath (or on a down-hole side of) a previous layer) to form a printed casing liner **152** or a printed casing **140**.

(44) FIG. **12** is a diagram that illustrates an example computer system (or “system”) **2000** in accordance with one or more embodiments. In some embodiments, the system **2000** is a programmable logic controller (PLC). The system **2000** may include a memory **2004**, a processor **2006** and an input/output (I/O) interface **2008**. The memory **2004** may include one or more of non-volatile memory (for example, flash memory, read-only memory (ROM), programmable read-only memory (PROM), erasable programmable read-only memory (EPROM), electrically erasable programmable read-only memory (EEPROM)), volatile memory (for example, random access memory (RAM), static random access memory (SRAM), synchronous dynamic RAM (SDRAM)), and bulk storage memory (for example, CD-ROM or DVD-ROM, hard drives). The memory **2004** may include a non-transitory computer-readable storage medium having program instructions **2010** stored thereon. The program instructions **2010** may include program modules **2012** that are executable by a computer processor (for example, the processor **2006**) to cause the functional operations described, such as those described with regard to the well control system **122**, the method **800** or the method **1100**.

(45) The processor **2006** may be any suitable processor capable of executing program instructions. The processor **2006** may include a central processing unit (CPU) that carries out program instructions (for example, the program instructions of the program module(s) **2012**) to perform the arithmetical, logical, and input/output operations described. The processor **2006** may include one or more processors. The I/O interface **2008** may provide an interface for communication with one or more I/O devices **2014**, such as a joystick, a computer mouse, a keyboard, and a display screen (for example, an electronic display for displaying a graphical user interface (GUI)). The I/O devices **2014** may include one or more of the user input devices. The I/O devices **2014** may be connected to the I/O interface **2008** via a wired connection (for example, Industrial Ethernet connection) or a wireless connection (for example, Wi-Fi connection). The I/O interface **2008** may provide an interface for communication with one or more external devices **2016**, such as sensors, valves, motors, other computers and networks. In some embodiments, the I/O interface **2008** includes one or both of an antenna and a transceiver. In some embodiments, the external devices **2016** include the casing liner printing system **200** or the casing printing system **900**.

(46) Further modifications and alternative embodiments of various aspects of the disclosure will be apparent to those skilled in the art in view of this description. Accordingly, this description is to be construed as illustrative only and is for the purpose of teaching those skilled in the art the general manner of carrying out the embodiments. It is to be understood that the forms of the embodiments shown and described here are to be taken as examples of embodiments. Elements and materials may be substituted for those illustrated and described here, parts and processes may be reversed or

omitted, and certain features of the embodiments may be utilized independently, all as would be apparent to one skilled in the art after having the benefit of this description of the embodiments. Changes may be made in the elements described here without departing from the spirit and scope of the embodiments as described in the following claims. Headings used here are for organizational purposes only and are not meant to be used to limit the scope of the description.

(47) It will be appreciated that the processes and methods described here are example embodiments of processes and methods that may be employed in accordance with the techniques described here. The processes and methods may be modified to facilitate variations of their implementation and use. The order of the processes and methods and the operations provided may be changed, and various elements may be added, reordered, combined, omitted, modified, etc. Portions of the processes and methods may be implemented in software, hardware, or a combination thereof. Some or all of the portions of the processes and methods may be implemented by one or more of the processors/modules/applications described here.

(48) As used throughout this application, the word “may” is used in a permissive sense (that is, meaning having the potential to), rather than the mandatory sense (that is, meaning must). The words “include,” “including,” and “includes” mean including, but not limited to. As used throughout this application, the singular forms “a,” “an,” and “the” include plural referents unless the content clearly indicates otherwise. Thus, for example, reference to “an element” may include a combination of two or more elements. As used throughout this application, the term “or” is used in an inclusive sense, unless indicated otherwise. That is, a description of an element including A or B may refer to the element including one or both of A and B. As used throughout this application, the phrase “based on” does not limit the associated operation to being solely based on a particular item. Thus, for example, processing “based on” data A may include processing based at least in part on data A and based at least in part on data B, unless the content clearly indicates otherwise. As used throughout this application, the term “from” does not limit the associated operation to being directly from. Thus, for example, receiving an item “from” an entity may include receiving an item directly from the entity or indirectly from the entity (for example, via an intermediary entity). Unless specifically stated otherwise, as apparent from the discussion, it is appreciated that throughout this specification discussions utilizing terms such as “processing,” “computing,” “calculating,” “determining,” or the like refer to actions or processes of a specific apparatus, such as a special purpose computer or a similar special purpose electronic processing/computing device. In the context of this specification, a special purpose computer or a similar special purpose electronic processing/computing device is capable of manipulating or transforming signals, typically represented as physical, electronic or magnetic quantities within memories, registers, or other information storage devices, transmission devices, or display devices of the special purpose computer or similar special purpose electronic processing/computing device.

Claims

1. Non-transitory computer readable storage medium comprising program instructions stored thereon that are executable by a processor to cause the following for casing a wellbore of a hydrocarbon well: conducting a downhole casing operation comprising: operating a casing print head disposed in a wellbore of a hydrocarbon well to eject casing material to form a casing tubular in the wellbore, the casing print head comprising a row of nozzles, the row of nozzles comprising a first subset of nozzles configured to eject casing liner material, a second subset of nozzles configured to eject casing material, and a third subset of nozzles configured to eject disposable material; operating the casing print head such that the casing print head rotates about a longitudinal axis of the wellbore and advances along the length of the wellbore, and the second subset of nozzles ejects the casing liner material into an annular region located between the casing tubular and a wall of the wellbore to form a casing liner in the annular region formed of the casing liner

material, such that the casing tubular and the casing liner are simultaneously deposited to form a casing of the wellbore; forming a perforation in the casing, forming the perforation in the casing comprising operating the casing print head to form a contiguous void extending radially across the casing tubular and the casing liner, wherein operating the casing print head to form a contiguous void extending radially across the casing tubular and the casing liner comprises operating the casing print head such that the third subset of nozzles ejects the disposable material to define the contiguous void extending radially across the casing tubular and the casing liner; and performing a perforation operation comprising removing the disposable material.

2. The medium of claim 1, wherein the downhole casing operation comprises advancing the casing print head along a length of the wellbore and ejecting the casing material and the casing liner material along the length of the wellbore to form the casing along the length of the wellbore.

3. The medium of claim 1, wherein the disposable material comprises a dissolvable material, and wherein the perforation operation comprises exposing the dissolvable material to a substance configured to dissolve the dissolvable material.

4. The medium of claim 1, wherein the casing liner material comprises casing cement.
