

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12393062
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Lv; Gaofeng et al.

Automatic righting system and method, and glasses

Abstract

An automatic righting system includes a discrimination calibration module, a righting module, and a controller. The discrimination calibration module includes a distance sensing unit. The distance sensing unit is located at the front end of the glasses and configured to acquire the distance between the distance sensing unit and a first feature position. The righting module includes a push-up air cushion. The push-up air cushion is mounted at the front end of the glasses. The push-up air cushion is configured to be inflated to push the glasses to move upward. The controller is electrically connected to the distance sensing unit and the push-up air cushion. The controller is configured to control the push-up air cushion to start or stop to right the glasses according to a distance signal of the distance sensing unit.

Inventors: Lv; Gaofeng (Nanjing, CN), Wang; Cheng (Nanjing, CN), Li; Chunguang (Nanjing, CN), Wu; Zhongyu (Nanjing, CN), Gao; Yajuan (Nanjing, CN), Jiang; Birong (Nanjing, CN), You; Ran (Nanjing, CN), Xu; Guojun (Nanjing, CN)

Applicant: Luxshare Precision Technology (Nanjing) Co., LTD (Nanjing, CN)

Family ID: 1000008762620

Assignee: LUXSHARE PRECISION TECHNOLOGY (NANJING) CO., LTD (Nanjing, CN)

Appl. No.: 18/091744

Filed: December 30, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240094563 A1	Mar. 21, 2024

Foreign Application Priority Data

CN	202211144165.7	Sep. 20, 2022
----	----------------	---------------

Publication Classification

Int. Cl.: G02C11/00 (20060101); G02C5/14 (20060101); G06F3/0354 (20130101)

U.S. Cl.:

CPC G02C11/10 (20130101); G02C5/14 (20130101); G06F3/03547 (20130101);

Field of Classification Search

CPC: G02C (11/10); G02C (11/00); G02C (5/14); G02C (5/001); G06F (3/03547); G06F (1/163); G02B (27/0176); G02B (2027/0178)

USPC: 351/158

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9880441	12/2017	Osterhout	N/A	G02B 27/0172
11726337	12/2022	Huang	345/80	G02B 27/0149
2011/0240383	12/2010	Gettings	180/9.1	B62D 55/08
2015/0351965	12/2014	Umentum	2/427	A47F 1/08
2018/0190011	12/2017	Platt	N/A	G02B 27/017
2018/0292679	12/2017	Mou et al.	N/A	N/A
2020/0310376	12/2019	Hyde	N/A	G05B 19/0428
2022/0252887	12/2021	Nortrup	N/A	G02B 27/0093
2023/0314819	12/2022	Huang	345/80	G02B 27/0176

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
201965335	12/2010	CN	N/A
105223908	12/2015	CN	N/A
207516663	12/2017	CN	N/A
209075218	12/2018	CN	N/A
111025685	12/2019	CN	N/A
210401874	12/2019	CN	N/A
112782869	12/2020	CN	N/A
113160520	12/2020	CN	N/A
215006110	12/2020	CN	N/A
114991800	12/2021	CN	N/A
115308905	12/2021	CN	N/A
115629489	12/2022	CN	N/A
2018-180532	12/2017	JP	N/A

OTHER PUBLICATIONS

Chinese Office Action and Search Report for Chinese Application No. 202211144165.7, dated Mar. 28, 2025, with English translation. cited by applicant

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S)

(1) This application claims priority to Chinese Patent Application No. 202211144165.7 filed Sep. 20, 2022, the disclosure of which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

(2) The present disclosure relates to the field of wearable technology and, in particular, to an automatic righting system and method, and glasses.

BACKGROUND

(3) With the advancement of science and technology, VR glasses, AR glasses, and XR glasses become commonly used electronic products.

(4) VR glasses, AR glasses, and XR glasses are overweight due to components such as lenses, circuit boards, and fans at front ends of the glasses, while there are fewer components at back ends of the glasses, so that the back ends are lighter. Thus, there is a problem that the glasses are top-heavy and easily skew and slide during the wearing process, and the user has to manually right the glasses frequently. However, when the user is inconvenient in both hands, the user cannot right the glasses. As a result, the use effect is poor.

SUMMARY

(5) The present disclosure provides an automatic righting system and method, and glasses, which can automatically right glasses and have high automaticity and convenience.

(6) The present disclosure provides the solutions below.

(7) The automatic righting system includes a discrimination calibration module, a righting module, and a controller.

(8) The discrimination calibration module includes a distance sensing unit. The distance sensing unit is located at the front end of the glasses and configured to acquire the distance between the distance sensing unit and a first feature position.

(9) The righting module includes a push-up air cushion. The push-up air cushion is mounted at the front end of the glasses. The push-up air cushion is configured to be inflated to push the glasses to move upward.

(10) The controller is electrically connected the distance sensing unit and the push-up air cushion. The controller is configured to control the push-up air cushion to start or stop to right the glasses according to a distance signal of the distance sensing unit.

(11) Optionally, the discrimination calibration module also includes a touch sensing unit located at the back end of the glasses. The touch sensing unit is configured to be triggered by sliding and capable of monitoring the sliding distance of the touch sensing unit relative to a second feature position. The controller is electrically connected to the touch sensing unit and is configured to acquire the sliding distance of the touch sensing unit.

(12) Optionally, a plurality of distance sensing units are provided, and the plurality of distance sensing units are disposed at intervals on the outer surface of a frame.

(13) Optionally, the righting module also includes a plurality of clamping air cushions. A part of the plurality of clamping air cushions is mounted on the inside of one temple of the glasses, and the other part of the plurality of clamping air cushions is mounted on the inside of the other temple of the glasses. The controller is electrically connected to the plurality of clamping air cushions and is configured to control the clamping air cushions to start or stop.

- (14) Optionally, the push-up air cushion is mounted at the nose pad groove of the frame.
- (15) An automatic righting method is applicable to the preceding automatic righting system and includes the steps below.
- (16) In step S1, an initial distance is acquired. The initial distance is the distance which is between the distance sensing unit and the first feature position and recorded by the distance sensing unit when the glasses are in a comfortable position.
- (17) In step S2, a first distance is acquired. The first distance is the distance which is between the distance sensing unit and the first feature position and recorded by the distance sensing unit at the current moment.
- (18) In step S3, it is determined whether the first distance is greater than or equal to a to-be-righted distance. If so, step S4 is executed. If not, step S5 is executed.
- (19) In step S4, the push-up air cushion is controlled to start or stop according to the first distance and the initial distance so that the push-up air cushion is inflated to right the glasses.
- (20) In step S5, step S3 is executed after a preset duration.
- (21) Optionally, step S4 includes the steps below.
- (22) In step S41, the push-up air cushion is controlled to start, and the real-time distance between the distance sensing unit and the first feature position is recorded in real time through the distance sensing unit.
- (23) In step S42, when the real-time distance is equal to or less than the initial distance, the push-up air cushion is controlled to stop.
- (24) Optionally, the discrimination calibration module also includes a touch sensing unit. The automatic righting method includes the steps below.
- (25) A sliding distance is acquired. The sliding distance is a distance which is monitored by the touch sensing unit, and the sliding distance is the distance for which the touch sensing unit slides relative to the second feature position when the glasses slide from the comfortable position to a to-be-righted position.
- (26) In step S4, when the distance for which the touch sensing unit moves reversely is 60% of the sliding distance, the inflation rate of the push-up air cushion is controlled to decrease.
- (27) Optionally, the righting module also includes a plurality of clamping air cushions. After the glasses are righted, the automatic righting method also includes the steps below.
- (28) The plurality of clamping air cushions are controlled to start. The plurality of clamping air cushions are inflated to increase the distance between two temples.
- (29) The glasses include a frame, temples, and the preceding automatic righting system.
- (30) The distance sensing unit and the push-up air cushion are each mounted on the frame. The controller is disposed in the frame or the temples.
- (31) The automatic righting system and method, and glasses provided by the present disclosure have at least the beneficial effects below.
- (32) The distance sensing unit acquires the distance between the distance sensing unit and the first feature position and transmits the distance to the controller. The controller determines whether to control the push-up air cushion to start or not according to the distance, and controls the push-up air cushion to start when the glasses need to be righted. The push-up air cushion can be inflated to push the frame of the glasses to move upward. The controller controls the push-up air cushion to stop after the frame moves to a proper position. In this manner, the automatic righting the glasses is implemented, and a user does not need to manually push the glasses, thereby improving the convenience of righting glasses.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a view of glasses from an angle according to an embodiment of the present disclosure.
- (2) FIG. 2 is a view of the glasses from another angle according to an embodiment of the present disclosure.
- (3) FIG. 3 is a view of the glasses from another angle according to an embodiment of the present disclosure.
- (4) FIG. 4 is a flowchart of an automatic righting method according to an embodiment of the present disclosure.

REFERENCE LIST

- (5) **11** distance sensing unit **12** touch sensing unit **2** righting module **21** push-up air cushion **22** clamping air cushion **10** frame **20** temple

DETAILED DESCRIPTION

(6) To make problems to be solved, adopted solutions and achieved effects of the present disclosure clearer, solutions of the present disclosure are further described below through embodiments in conjunction with drawings. It is to be understood that the embodiments described herein are merely intended to explain the present disclosure and not to limit the present disclosure. In addition, it should be noted that for ease of description, only the part, instead of all, related to the present disclosure is illustrated in the drawings.

(7) In the description of the present disclosure, unless otherwise expressly specified and limited, the term “connected to each other”, “connected” or “secured” is to be construed in a broad sense, for example, as securely connected, detachably connected or integrated; mechanically connected or electrically connected; directly connected to each other or indirectly connected to each other via an intermediary; or internally connected between two components or interaction relations between two components. For those of ordinary skill in the art, specific meanings of the preceding terms in the present disclosure may be construed based on specific situations.

(8) In the present disclosure, unless otherwise expressly specified and limited, when a first feature is described as “above” or “below” a second feature, the first feature and the second feature may be in direct contact or be in contact via another feature between the two features. Moreover, when the first feature is described as “on”, “above” or “over” the second feature, the first feature is right on, above or over the second feature or the first feature is obliquely on, above or over the second feature, or the first feature is simply at a higher level than the second feature. When the first feature is described as “under”, “below”, or “underneath” the second feature, the first feature is right under, below, or underneath the second feature or the first feature is obliquely under, below, or underneath the second feature, or the first feature is simply at a lower level than the second feature.

(9) In the description of this embodiment, the orientation or position relationships indicated by terms “above”, “below”, “right” and the like are based on the orientation or position relationships shown in the drawings, merely for ease of description and simplifying an operation, and these relationships do not indicate or imply that the referred device or element has a specific orientation and is constructed and operated in a specific orientation, and thus it is not to be construed as limiting the present disclosure. In addition, the terms “first” and “second” are used only to distinguish between descriptions and have no special meaning.

Embodiment One

(10) This embodiment provides an automatic righting system. The system is applicable to glasses and can push the glasses to move when the glasses skew or slide. In this manner, a user does not need to manually push the glasses, and the automatic righting of the glasses can be implemented. It is to be noted that the glasses in this embodiment are smart glasses such as VR glasses, AR glasses, and XR glasses.

(11) As shown in FIGS. 1 to 3, the automatic righting system includes a discrimination calibration module, a righting module 2, and a controller.

(12) The discrimination calibration module includes a distance sensing unit **11**. The distance sensing unit **11** is located at the front end of the glasses. As shown in FIG. 1, the distance sensing unit **11** is specifically located on the front surface of a frame. The distance sensing unit **11** is configured to acquire the distance between the distance sensing unit **11** and a first feature position. The first feature position may be a point on the user's face that is easy to acquire, such as the user's nose tip, nose bone, and eyebrows. Preferably, it is better to select an unchanged point on the user's face and use the point as the first feature position. In this embodiment, the distance sensing unit **11** may be a distance sensor or a camera.

(13) The preceding righting module **2** is configured to push the slid glasses upward so that the glasses are in a proper position. Specifically, the righting module **2** includes a push-up air cushion **21**. The push-up air cushion **21** may automatically be inflated after being powered on. The push-up air cushion **21** is mounted at the front end of the glasses and specifically between the frame and the user's nose. Thus, when the push-up air cushion **21** is inflated, the frame of the glasses can be pushed upward with the user's nose as a supporting point. In this embodiment, the push-up air cushion **21** is powered by a battery in the glasses. In some embodiments, the push-up air cushion **21** is mounted at the nose pad groove of the frame. The lower surface of the frame has a nose pad groove with the same shape as a nose, and the nose pad groove is used for clamping the nose. The push-up air cushion **21** is mounted at the nose pad groove to better push the frame to move.

(14) The controller is electrically connected to the distance sensing unit **11** and the push-up air cushion **21**. The controller is configured to control the push-up air cushion **21** to start or stop to right the glasses according to a distance signal of the distance sensing unit **11**. Specifically, when the controller determines that the distance, which is acquired by the distance sensing unit **11** and is between the distance sensing unit **11** and the first feature position, is not an initial distance and is greater than or equal to a to-be-righted distance, it indicates that the glasses need to be righted. At this time, the push-up air cushion **21** is controlled to start, so that the push-up air cushion is inflated to push the frame of the glasses to move upward. During the upward movement, the controller acquires the distance which is acquired by the distance sensing unit **11** and is between the distance sensing unit **11** and the first feature position in real time. When the distance is equal to the initial distance, it indicates that the glasses are righted in place. At this time, the controller controls the push-up air cushion **21** to stop. In this manner, the automatic righting of the glasses is implemented. It is to be noted that the initial distance is the distance which is acquired by the distance sensing unit **11** and is between the distance sensing unit **11** and the first feature position when the glasses are at the proper position on the user's face. The to-be-righted distance is the distance which is acquired by the distance sensing unit **11** and is between the distance sensing unit **11** and the first feature position when the frame of the glasses slides to a position where the glasses need to be righted. In this embodiment, the user may set the initial distance and the to-be-righted distance, that is, the user may set the comfortable position of the glasses (namely, the position of the glasses where the glasses are located to make the users feel comfortable) and the to-be-righted position of the glasses (namely, the position of the glasses where the glasses are needed to be righted). There may be different settings for different users.

(15) In the automatic righting system provided by this embodiment, the distance sensing unit **11** acquires the distance between the distance sensing unit **11** and the first feature position and transmits the distance to the controller. The controller determines whether to control the push-up air cushion **21** to start or not according to the distance, and controls the push-up air cushion **21** to start when the glasses need to be righted. The push-up air cushion **21** is configured to be inflated to push the frame of the glasses to move upward. The controller controls the push-up air cushion **21** to stop after the frame moves to the proper position. In this manner, the automatic righting of the glasses is implemented, and the user does not need to manually push the glasses, thereby improving the convenience of glasses righting.

(16) Optionally, referring to FIG. 1, the discrimination calibration module also includes a touch

sensing unit **12**. The touch sensing unit **12** is located at the back end of the glasses, specifically mounted on the temple of the glasses, and in contact with the user's face. The touch sensing unit **12** is configured to be triggered by sliding, that is, the touch sensing unit **12** can be automatically triggered when the touch sensing unit **12** senses that the touch sensing unit **12** moves relative to the user's face. The touch sensing unit **12** can monitor the sliding distance of the touch sensing unit **12** relative to a second feature position, that is, the touch sensing unit **12** can monitor the sliding distance when the touch sensing unit **12** slides on the user's face. The controller is electrically connected to the touch sensing unit **12** and is configured to acquire the sliding distance of the touch sensing unit **12**, and control the push-up air cushion **21** according to the sliding distance and the distance signal. In this embodiment, the touch sensing unit **12** may be a touch sensor.

(17) It is to be noted that the second feature position is the position of the user's face. In some embodiments, when the glasses are in a comfortable position, the position of the user's face in contact with the touch sensing unit **12** is the second feature position. It is to be noted that the method for the touch sensing unit **12** to acquire sliding may be referred to the method for a touch display panel to acquire the sliding length of the user's finger. The touch sensing unit **12** is similar to the touch display panel, and the skin at the second feature position is similar to the finger. Details are not repeated in this embodiment.

(18) In some embodiments, the controller may control when to decrease the inflation rate of the push-up air cushion **21** according to the sliding distance. For example, during the upward movement of the glasses, when the distance for which the glasses move reversely is 60% of the sliding distance, the controller controls the inflation rate of the push-up air cushion **21** to decrease to prevent over-righting due to an excessive inflation rate.

(19) Optionally, as shown in FIG. **1**, a plurality of distance sensing units **11** are provided, and the plurality of distance sensing units **11** are disposed to ensure the accuracy of the distance signal. The plurality of distance sensing units **11** are disposed at intervals on the outer surface of the frame. The outer surface of the frame is specifically the surface of the frame that is not in contact with the user's face. The controller may determine whether the glasses has reached a to-be-righted position or not according to a plurality of distance signals of the plurality of distance sensing units **11**, thereby preventing misjudgment. In FIG. **1**, three distance sensing units **11** are disposed. Two distance sensing units **11** are disposed on the lower parts of the two lenses near a nose. One distance sensing unit **11** is located on the upper surface of the frame.

(20) In this embodiment, as shown in FIGS. **2** and **3**, the righting module **2** also includes a plurality of clamping air cushions **22**. A part of the plurality of clamping air cushions **22** is mounted on the inside of one temple of the glasses, that is, between the temple and the user's face. The other part of the plurality of clamping air cushions **22** is mounted on the inside of the other temple of the glasses. The controller is electrically connected to the plurality of clamping air cushions **22** and is configured to control the clamping air cushions **22** to start or stop. When the clamping air cushions **22** are inflated, the distance between the temple and the user's face increases, and the distance between two temples increases. Under the action of the deformation forces of the temples, the two temples clamps the face, so that the entire glasses can be firmly fixed on the user's face. The clamping air cushions **22** may be used in conjunction with the push-up air cushion **21**. After the push-up air cushion **21** rights the glasses to the comfortable position, the clamping air cushions **22** are started to better fix the glasses in the comfortable position. In this embodiment, as shown in FIGS. **2** and **3**, two clamping air cushions **22** are disposed on each temple.

(21) In the automatic righting system provided in this embodiment, the automatic righting of the glasses can be implemented, the structure is simple, and the reliability is high. The clamping air cushions **22** are disposed, so that the firmness of the glasses when the user wears glasses can be improved.

Embodiment Two

(22) This embodiment provides a type of glasses. As shown in FIGS. **1** to **3**, the glasses include a

frame **10**, temples **20**, and the automatic righting system described in embodiment one. In this embodiment, the glasses may be AR glasses, VR glasses, or XR glasses. This is not limited in this embodiment.

(23) The distance sensing unit **11** and the push-up air cushion **21** are each mounted on the frame **10**. The controller is disposed in the frame **10** or the temples **20**. The glasses also include a battery and a control button. The battery is configured to provide electrical energy for the distance sensing unit **11**, the push-up air cushion **21**, and the controller. The control button may be used for inputting a set command.

(24) The glasses provided by this embodiment include an automatic righting system. In the automatic righting system, the distance sensing unit **11** acquires the distance between the distance sensing unit **11** and the first feature position and transmits the distance to the controller. The controller determines whether to control the push-up air cushion **21** to start or not according to the distance, and controls the push-up air cushion **21** to start when the glasses need to be righted. The push-up air cushion **21** is configured to be inflated to push the frame of the glasses to move upward. The controller controls the push-up air cushion **21** to stop after the frame moves to the proper position. In this manner, the automatic righting of the glasses is implemented, and the user does not need to manually push the glasses, thereby improving the convenience of glasses righting.

Embodiment Three

(25) This embodiment provides an automatic righting method. The method is applicable to the automatic righting system in embodiment one. As shown in FIG. **4**, the automatic righting method includes the steps below.

(26) In step **S1**, the initial distance is acquired. The initial distance is the distance which is between the distance sensing unit **11** and the first feature position and recorded by the distance sensing unit **11** when the glasses are in the comfortable position.

(27) The comfortable position of the glasses refers to a position where the glasses are located when the user feels comfortable and after the user wears the glasses on the user's face. The position may be configured by the user. The first feature position may be a point on the user's face that is easy to acquire, such as the user's nose tip, nose bone, and eyebrows. Preferably, it is better to select an unchanged point on the user's face and use the point as the first feature position. It is to be noted that the initial distance is acquired or set by the controller.

(28) Optionally, in this embodiment, after the initial distance is acquired, in order to improve a processing speed, the controller may convert the initial distance to an ADC value and define this value as threshold value **A**.

(29) In step **S2**, the first distance is acquired. The first distance is the distance which is between the distance sensing unit **11** and the first feature position and recorded by the distance sensing unit **11** at the current moment.

(30) In this embodiment, the first distance may be equal to the initial distance, that is, the distance recorded by the distance sensing unit **11** when the glasses do not slide. It is to be noted that the first distance is acquired by the controller.

(31) In step **S3**, it is determined whether the first distance is greater than or equal to the to-be-righted distance. If so, step **S4** is executed. If not, step **S5** is executed.

(32) The to-be-righted distance is a distance which is recorded by the distance sensing unit **11** and is between the distance sensing unit **11** and the first feature position when the frame of the glasses slides to the to-be-righted position. The distance may be preset by the user. When the first distance is greater than or equal to the to-be-righted distance, it indicates that the frame of the glasses have slid to the to-be-righted position. At this time, the controller may control the push-up air cushion **21** to start. It is to be noted that the to-be-righted distance is acquired or set by the controller.

(33) In this embodiment, after a processor obtains the to-be-righted distance, in order to improve a processing speed, the controller may convert the to-be-righted distance to an ADC value and define this value as threshold value **B**. When the ADC value corresponding to the first distance triggers

threshold value B, the controller controls the push-up air cushion **21** to start.

(34) In step **S4**, the push-up air cushion **21** is controlled to start or stop according to the first distance and the initial distance so that the push-up air cushion **21** is inflated to right the glasses.

(35) The preceding righting module **2** is configured to push the slid glasses upward so that the glasses are in the proper position. Specifically, the righting module **2** includes a push-up air cushion **21**. The push-up air cushion **21** may automatically be inflated after being powered on. The push-up air cushion **21** is mounted at the front end of the glasses and specifically between the frame and the user's nose. Thus, when the push-up air cushion **21** is inflated, the frame of the glasses can be pushed upward with the user's nose as the supporting point. In this embodiment, the push-up air cushion **21** is powered by the battery in the glasses. In some embodiments, the push-up air cushion **21** is mounted at the nose pad groove of the frame. The lower surface of the frame has the nose pad groove with the same shape as the nose, and the nose pad groove is used for clamping the nose. The push-up air cushion **21** is mounted at the nose pad groove to better push the frame to move.

(36) In step **S5**, step **S3** is executed after the preset duration.

(37) In step **S5**, the controller controls the cyclic execution of steps **S3** and **S4** to periodically detect whether the frame needs to be righted. The preset duration may be set according to actual requirements, such as 0.1 second, 0.5 second, and 1 second. This is not limited in this embodiment.

(38) In the automatic righting method of the automatic righting system provided in this embodiment, the distance sensing unit **11** acquires the distance between the distance sensing unit **11** and the first feature position and transmits the distance to the controller. The controller determines whether to control the push-up air cushion **21** to start or not according to the distance, and controls the push-up air cushion **21** to start when the glasses need to be righted. The push-up air cushion **21** is configured to be inflated to push the frame of the glasses to move upward. The controller controls the push-up air cushion **21** to stop after the frame moves to the proper position. In this manner, the automatic righting of the glasses is implemented, and the user does not need to manually push the glasses, thereby improving the convenience of glasses righting.

(39) Optionally, step **S4** includes the steps below.

(40) In step **S41**, the push-up air cushion **21** is controlled to start, and the real-time distance between the distance sensing unit **11** and the first feature position is recorded in real time through the distance sensing unit **11**.

(41) During the righting process, it is necessary for the distance sensing unit **11** to record the real-time distance between the distance sensing unit **11** and the first feature position in real time to determine whether the frame is righted in place. In this embodiment, the acquisition interval or the record interval of the distance sensing unit **11** may be set according to actual requirements, such as 0.1 second, 0.5 second, and 1 second. This is not limited in this embodiment. To prevent the problem of over-righting, the acquisition interval or the record interval should not be too large.

(42) In step **S42**, when the real-time distance is equal to or less than the initial distance, the push-up air cushion **21** is controlled to stop.

(43) In step **S42**, when the real-time distance is less than or equal to the initial distance, it indicates that the frame is righted in place and is already in the comfortable position. At this time, the controller may control the push-up air cushion **21** to stop to complete the righting of the glasses.

(44) Optionally, when the discrimination calibration module includes a touch sensing unit **12**. The automatic righting method includes the steps below.

(45) The sliding distance is acquired. The sliding distance is a distance which is monitored by the touch sensing unit **12**, and the sliding distance is the distance for which the touch sensing unit **12** slides relative to the second feature position when the glasses slide from the comfortable position to the to-be-righted position.

(46) It is to be noted that when the glasses start to slide, the touch sensing unit **12** monitors the distance between the touch sensing unit **12** and the second feature position in real time until the controller controls the push-up air cushion **21** to start. The distance recorded before the push-up air

cushion **21** is opened is used as the sliding distance. When the push-up air cushion **21** is opened, the controller immediately acquires the sliding distance. The second feature position is the position of the user's face. In some embodiments, when the glasses are in the comfortable position, the position of the user's face in contact with the touch sensing unit **12** is the second feature position. (47) In step **S4**, when the distance for which the touch sensing unit **12** moves reversely is 60% of the sliding distance, the inflation rate of the push-up air cushion **21** is controlled to decrease. (48) The reverse movement of the touch sensing unit **12** may be considered that the moving direction of the touch sensing unit **12** is opposite to the sliding direction when the glasses slide. During the righting process, when the distance for which the touch sensing unit **12** moves reversely is 60% of the sliding distance, it indicates that the glasses are about to reach the comfortable position. At this time, if the inflation rate of the push-up air cushion **21** is still large, it is easy to cause over-righting. For this reason, the controller may control the inflation rate of the push-up air cushion **21** to decrease, so that the glasses slowly move to the comfortable position. (49) Optionally, in the case where the righting module **2** includes a plurality of clamping air cushions **22**, and after the glasses are righted, the automatic righting method also includes the steps below. (50) The clamping air cushions **22** are controlled to start. The clamping air cushions **22** are inflated to increase the distance between two temples, thereby improving the firmness of the glasses when the glasses are worn on the user's face. In this manner, the glasses do not slide again in a short time.

Claims

1. An automatic righting system, comprising: a discrimination calibration module comprising a distance sensing unit, wherein the distance sensing unit is configured to be located at a front end of glasses and configured to acquire a distance between the distance sensing unit and a first feature position; a righting module comprising a push-up air cushion, wherein the push-up air cushion is configured to be mounted at the front end of the glasses, and the push-up air cushion is configured to be inflated to push the glasses to move upward; and a controller electrically connected to the distance sensing unit and the push-up air cushion, wherein the controller is configured to control the push-up air cushion to start or stop to right the glasses according to a distance signal of the distance sensing unit.
2. The automatic righting system according to claim 1, wherein the discrimination calibration module further comprises a touch sensing unit configured to be located at a back end of the glasses, wherein the touch sensing unit is configured to be triggered by sliding, and capable of monitoring a sliding distance of the touch sensing unit relative to a second feature position, and the controller is electrically connected to the touch sensing unit and is configured to acquire the sliding distance of the touch sensing unit.
3. The automatic righting system according to claim 1, wherein a plurality of distance sensing units are provided, wherein the plurality of distance sensing units are configured to be disposed at intervals on an outer surface of a frame.
4. The automatic righting system according to claim 1, wherein the righting module further comprises a plurality of clamping air cushions, wherein a part of the plurality of clamping air cushions is configured to be mounted on an inside of one temple of the glasses, and another part of the plurality of clamping air cushions is configured to be mounted on an inside of another temple of the glasses; and the controller is electrically connected to the plurality of clamping air cushions and is configured to control the plurality of clamping air cushions to start or stop.
5. The automatic righting system according to claim 1, wherein the push-up air cushion is configured to be mounted at a nose pad groove of a frame.
6. Glasses, comprising a frame, temples, and the automatic righting system according to claim 1, wherein the distance sensing unit and the push-up air cushion are each mounted on the frame, and

the controller is disposed in the frame or the temples.

7. The glasses according to claim 6, wherein the discrimination calibration module further comprises a touch sensing unit configured to be located at a back end of the glasses, wherein the touch sensing unit is configured to be triggered by sliding, and capable of monitoring a sliding distance of the touch sensing unit relative to a second feature position, and the controller is electrically connected to the touch sensing unit and is configured to acquire the sliding distance of the touch sensing unit.

8. The glasses according to claim 6, wherein a plurality of distance sensing units are provided, wherein the plurality of distance sensing units are configured to be disposed at intervals on an outer surface of a frame.

9. The glasses according to claim 6, wherein the righting module further comprises a plurality of clamping air cushions, wherein a part of the plurality of clamping air cushions is configured to be mounted on an inside of one temple of the glasses, and another part of the plurality of clamping air cushions is configured to be mounted on an inside of another temple of the glasses; and the controller is electrically connected to the plurality of clamping air cushions and is configured to control the plurality of clamping air cushions to start or stop.

10. The glasses according to claim 6, wherein the push-up air cushion is configured to be mounted at a nose pad groove of a frame.

11. An automatic righting method, applicable to an automatic righting system, wherein the automatic righting system comprises: a discrimination calibration module comprising a distance sensing unit, wherein the distance sensing unit is configured to be located at a front end of glasses and configured to acquire a distance between the distance sensing unit and a first feature position; a righting module comprising a push-up air cushion, wherein the push-up air cushion is configured to be mounted at the front end of the glasses, and the push-up air cushion is configured to be inflated to push the glasses to move upward; and a controller electrically connected to the distance sensing unit and the push-up air cushion, wherein the controller is configured to control the push-up air cushion to start or stop to right the glasses according to a distance signal of the distance sensing unit, and the automatic righting method comprises following steps: in step S1, acquiring an initial distance, wherein the initial distance is a distance which is between the distance sensing unit and the first feature position and recorded by the distance sensing unit when the glasses are in a comfortable position; in step S2, acquiring a first distance, wherein the first distance is a distance which is between the distance sensing unit and the first feature position and recorded by the distance sensing unit at a current moment; in step S3, determining whether the first distance is greater than or equal to a to-be-righted distance, if so, executing step S4, and if not, executing step S5; in the step S4, controlling the push-up air cushion to start or stop according to the first distance and the initial distance so that the push-up air cushion is inflated to right the glasses; and in the step S5, executing the step S3 after a preset duration.

12. The automatic righting method according to claim 11, wherein the discrimination calibration module further comprises a touch sensing unit configured to be located at a back end of the glasses, wherein the touch sensing unit is configured to be triggered by sliding, and capable of monitoring a sliding distance of the touch sensing unit relative to a second feature position, and the controller is electrically connected to the touch sensing unit and is configured to acquire the sliding distance of the touch sensing unit.

13. The automatic righting method according to claim 11, wherein a plurality of distance sensing units are provided, wherein the plurality of distance sensing units are configured to be disposed at intervals on an outer surface of a frame.

14. The automatic righting method according to claim 11, wherein the righting module further comprises a plurality of clamping air cushions, wherein a part of the plurality of clamping air cushions is configured to be mounted on an inside of one temple of the glasses, and another part of the plurality of clamping air cushions is configured to be mounted on an inside of another temple of

- the glasses; and the controller is electrically connected to the plurality of clamping air cushions and is configured to control the plurality of clamping air cushions to start or stop.
15. The automatic righting method according to claim 11, wherein the push-up air cushion is configured to be mounted at a nose pad groove of a frame.
16. The automatic righting method according to claim 11, wherein the step S4 comprises: in step S41, controlling the push-up air cushion to start and recording a real-time distance between the distance sensing unit and the first feature position in real time through the distance sensing unit; and in step S42, when the real-time distance is equal to or less than the initial distance, controlling the push-up air cushion to stop.
17. The automatic righting method according to claim 11, wherein the discrimination calibration module further comprises a touch sensing unit, and the automatic righting method comprises following steps: acquiring a sliding distance, wherein the sliding distance is a distance which is monitored by the touch sensing unit, and the sliding distance is the distance for which the touch sensing unit slides relative to a second feature position when the glasses slide from the comfortable position to a to-be-righted position; in the step S4, when a distance for which the touch sensing unit moves reversely is 60% of the sliding distance, controlling an inflation rate of the push-up air cushion to decrease.
18. The automatic righting method according to claim 11, wherein the righting module further comprises a plurality of clamping air cushions; after the glasses are righted, the automatic righting method further comprises: controlling the plurality of clamping air cushions to start, wherein the plurality of clamping air cushions are inflated to increase a distance between two temples.
-