

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250265169

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Saini; Manesh et al.

AUTOMATIC GENERATION OF PROCESS INSTRUCTIONS FROM LOG FILES

Abstract

A computing system may access log files that log data associated with prior performances of a process by users. Such data may be recorded by one or more computing systems based on tracking user interactions with the one or more computing systems to perform the process. The computing system may generate, using an instructions generation model that is trained using machine learning, the process instructions for performing the process based on the data associated with the prior performances of the process. The process instructions may be human-readable written instructions.

Inventors: Saini; Manesh (New York, NY), Lindgren, JR.; Carleton Jay (Denver, CO), Hubbard; James (Charlotte, NC), Sobey; Ronald (Porter, TX), Smith; Winthrop Treynor (Littleton, CO)

Applicant: Wells Fargo Bank, N.A. (San Francisco, CA)

Family ID: 1000007694172

Appl. No.: 18/443069

Filed: February 15, 2024

Publication Classification

Int. Cl.: G06F11/34 (20060101)

U.S. Cl.:

CPC G06F11/3476 (20130101);

Background/Summary

TECHNICAL FIELD

[0001] This disclosure relates to computing systems, and more specifically, to techniques for generating process documents using machine learning.

BACKGROUND

[0002] In recent years, organizations have increasingly integrated machine learning into their operations. Organizations have recognized the potential of machine learning to drive innovation, efficiency, and competitiveness, and are using machine learning algorithms to analyze vast datasets, uncovering insights and patterns that inform decision-making for those organizations. Recently, organizations have begun to use large language models for purposes of data analysis to summarize large volumes of text and to extract actionable insights.

SUMMARY

[0003] This disclosure describes techniques for using machine learning within an organization to analyze the performance of a process within the organization. A computing system may access log files that log data from prior performances of a process by users within the organization. To perform the process, users may interact with a variety of computing systems, and the log files may log data based on tracking user interactions with the computing systems. The computing system may use data from prior performances of the process into a machine trained model to generate written process instructions, which are instructions for performing the process that a human can read and follow to re-perform the process and/or that can be stored as formal documentation of the process for security and regulatory compliance.

[0004] The computing system may train a neural network using machine learning to generate process instructions for a process based on prior performances of the process. For example, the computing system may train and/or fine-tune a foundational large language model (LLM) to generate process instructions in a human-readable format for a process based on prior performances of the process.

[0005] Training and/or fine-tuning a foundational LLM to generate process instructions for a process based on prior performances of the process may enable the computing system to train a neural network for the specific task of generating process instructions for a process based on prior performances of the process without having to perform the initial, resource-intensive pre-training of the neural network. Not having to perform pre-training of the neural network may reduce the amount of data that is used and the amount of computational resources that are required to train a neural network to generate process instructions for a process based on prior performances of the process. Furthermore, because a foundational LLM has already been pre-trained and therefore exposed to a wide variety of language use cases and scenarios, a neural network that is based on a foundational LLM may be able to quickly adapt to the specific requirements of generating process instructions with only a small amount of additional training data. As such, the techniques of this disclosure may reduce the use of memory and processing resources that may be required to train a neural network to generate process instructions, thereby providing a technical improvement over prior techniques for training and using a neural network using machine learning to generate process instructions for a process based on prior performances of the process.

[0006] In some aspects, the techniques described herein relate to a method including: accessing, by one or more processors, log files that log data associated with prior performances of a process by users, wherein the data are recorded by one or more computing systems based on tracking user interactions with the one or more computing systems to perform the process; and generating, by the one or more processors and using an instructions generation model that is trained using machine learning, process instructions for performing the process based on the data associated with the prior performances of the process, wherein the process instructions are human-readable written instructions.

[0007] In some aspects, the techniques described herein relate to a computing system including:

memory configured to store log files that log data associated with prior performances of a process by users, wherein the data are recorded by one or more computing systems based on tracking user interactions with the one or more computing systems to perform the process; and one or more processors configured to: access the log files; and generate, using an instructions generation model that is trained using machine learning, process instructions for performing the process based on the data associated with the prior performances of the process, wherein the process instructions are human-readable written instructions.

[0008] In some aspects, the techniques described herein relate to a non-transitory computer-readable medium including instructions that, when executed, cause one or more processors of a computing system to: access log files that log data associated with prior performances of a process by users, wherein the data are recorded by one or more computing systems based on tracking user interactions with the one or more computing systems to perform the process; and generate, using an instructions generation model that is trained using machine learning, the process instructions for performing the process based on the data associated with the prior performances of the process, wherein the process instructions are human-readable written instructions.

[0009] The details of one or more examples of the disclosure are set forth in the accompanying drawings and the description herein. Other features, objects, and advantages of the disclosure will be apparent from the description and drawings, and from the claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] FIG. 1 is a conceptual diagram illustrating an example system for procedure analysis using category-specific models, in accordance with one or more aspects of the present disclosure.

[0011] FIG. 2 is a block diagram illustrating an example computing system, in accordance with one or more aspects of the present disclosure.

[0012] FIG. 3 is a flow diagram illustrating operations performed by an example computing system, in accordance with one or more aspects of the present disclosure.

DETAILED DESCRIPTION

[0013] In general, aspects of this disclosure are directed to using machine learning within an organization to analyze the performance of a process within the organization and to generate process instructions for performing the process based on the data from prior performances of the process. In various industries and domains, processes are performed by users to achieve specific tasks or objectives. These processes may involve a series of steps or actions that are performed to achieve the desired outcome.

[0014] Different users within an organization may perform the same process in different ways. For example, different users may take different actions in different orders, omit performance of one or more actions, perform one or more extraneous actions, perform the same action in different ways, and the like. While an organization may manually generate a single set of process instructions for performing a process, such manually created process instructions may not fully capture the nuances and variations that can arise during performance of the process by different users within the organization.

[0015] In accordance with aspects of this disclosure, a computing system may train a neural network to be an instructions generation model that generates process instructions for performing a given process based on the data from prior performances of the process by users within an organization. The computing system may track actions performed by users during prior performances of the process to log data from prior performances of the process by the users. The logged data may contain valuable information about the steps taken, decisions made, and outcomes achieved during performances of the process.

[0016] The instructions generation model may synthesize the different actions and workflows taken by different users to perform the process, as captured in the logged data, to generate a single set of process instructions for performing the process. Using a neural network to generate process instructions for performing a process from data from prior performances of the process by users within an organization may enable the instructions generation model to generate process instructions that capture variations in the prior performances of a process, as indicated by the logged data. That is, if different users perform the same process in different ways (e.g., by performing different numbers of steps, by performing steps of the process in different orders, etc.), the instructions generation model may generate process instructions that captures the different ways the process is performed.

[0017] Although manually-created written process instructions may already exist for instructing users to perform a particular process, the sequence of actions indicated in such manually-created written process instructions may deviate significantly from the sequence of actions users are taking to perform the process. For example, laws and regulations may have changed since the manually-created written process instructions were last updated, which may require users to deviate from the manually-created written process instructions. In another example, some users may have found ways to more efficiently perform the process compared to the manually-created written process instructions. By synthesizing the different actions and workflows taken by different users to perform the process to generate a single set of process instructions for performing the process, the techniques of this disclosure may enable the instructions generation model to generate process instructions for performing a process that may be more efficient than manually-created written process instructions while complying with the latest rules and regulations.

[0018] The instructions generation model may therefore leverage logged data from prior performances of the process by users to generate process instructions for the process that may provide insights into the patterns, trends, and variations that exist in the process. For example, computing system may be able to derive, from the process instructions, operational intelligence regarding how users within the organization perform the process, and may be able to determine how efficient users are at performing the process, how much do users conform to procedural requirements of the process, and the like.

[0019] The computing system may train a neural network using machine learning to generate process instructions for a process based on prior performances of the process. For example, the computing system may train and/or fine-tune a foundational large language model (LLM) to generate process instructions for a process based on prior performances of the process.

[0020] Training and/or fine-tuning a foundational LLM to generate process instructions for a process based on prior performances of the process may enable the computing system to train a neural network for the specific task of generating process instructions for a process based on prior performances of the process without having to perform the initial, resource-intensive pre training of the neural network. Not having to perform pre-training of the neural network may reduce the amount of data that is used and the amount of computational resources that is required to train a neural network to generate process instructions for a process based on prior performances of the process. Furthermore, because a foundational LLM has already been pre-trained and therefore exposed to a wide variety of language use cases and scenarios, a neural network that is based on a foundational LLM may be able to more quickly adapt to the specific requirements of generating process instructions with only a small amount of additional training data. As such, the techniques of this disclosure may reduce the use of memory and processing resources, thereby providing a technical improvement over prior techniques for training and using a neural network using machine learning to generate process instructions for a process based on prior performances of the process.

[0021] FIG. 1 is a conceptual diagram illustrating an example system for automatic generation of process instructions, in accordance with one or more aspects of the present disclosure. As shown in FIG. 1, computing system 100 represent any suitable computing system, such as one or more

desktop computers, laptop computers, mainframes, servers, and the like. In some examples, computing system **100** may represent cloud computing systems that provide access to their respective services via a cloud.

[0022] Computing system **100** includes data parsing module **106**, process tracking module **108**, instructions generation model **110**, process refinement model **114**, operational intelligence module **116**, instructions comparison model **120**, and process analysis module **124**. Data parsing module **106**, process tracking module **108**, instructions generation model **110**, process refinement model **114**, operational intelligence module **116**, instructions comparison model **120**, and process analysis module **124** may be implemented as software that computing system **100** may execute, or may in some examples include any combination of hardware, firmware, and software.

[0023] Computing system **100** may be associated with an organization, such as a company, a school, a charitable organization, and the like. Computing system **100** may be operable to execute data parsing module **106**, instructions generation model **110**, process refinement model **114**, operational intelligence module **116**, instructions comparison model **120**, and process analysis module **124** to generate process instructions.

[0024] A process may be a series of actions that are performed for the purposes of completing a task. In the context of a financial organization (e.g., a bank), examples of processes may include a process for approving a mortgage or other types of loans, a process for opening a bank account, a process for repossessing a vehicle or a home, a process for trading stocks, a process for assessing the value of a home, and the like.

[0025] Users within an organization may perform a series of actions to perform a process. For example, to perform a process for approving the mortgage, a computing system in a financial organization may receive the loan application and may assign it to an employee (i.e., a user). The user may perform a series of actions such as conducting a credit check for the applicant, verifying the income of the applicant, perform a debt-to-income ratio calculation, conduct a property appraisal, conduct a title search, conduct underwriting, and/or any other actions in order to approve or deny the loan.

[0026] While performing the process for approving the mortgage, the user may perform a series of actions, such as placing and receiving calls to and from other parties (e.g., to and from the appraiser and/or underwriter), sending and receiving e-mails, and the like. The user may perform some of the actions of the process in a particular sequence. For example, the user may perform income verification and a credit check of the applicant before performing other actions of the process. Further, The user may conduct a property appraisal if and only if the applicant passes the debt-to-income ratio calculation.

[0027] The users may interact with various computing systems **130A-130N** (“computing systems **130**”) to perform the actions of processes. Each of computing systems **130** may represent any suitable computing system, such as one or more desktop computers, laptop computers, mainframes, servers, and the like. In some examples, each of computing systems **130** may represent cloud computing systems that provide access to their respective services via a cloud. For example, a user may conduct a credit check on a customer by inputting personal information of the customer into a credit check system (e.g., computing system **130A**), and the credit check system may, in response, return a credit score for the person. In another example, a user may place and receive calls using a Voice over Internet Protocol (VOIP) system (e.g., computing system **130N**).

[0028] As users of the organization performs actions of processes by interacting with computing systems **130**, computing systems **130** and/or computing system **100** may track and/or log data regarding the actions performed by the users and computing systems **130**. For example, computing system **130** and/or computing system **100** (e.g., process tracking module **108** of computing system **100**) may track and/or log use of different applications by the users, the computing systems accessed by the users, the interactions of users with computing systems **130** (e.g., keystrokes and/or text entered by the users, cursor movements of the users, options and/or links selected by the

users), actions taken by computing systems **130** in response to user interactions, details of messages (e.g., e-mails, text messages, direct messages, instant messages, etc.) sent and received by the users (e.g., the identities of senders and/or recipients of the messages, the contents of the messages, the timestamps of when the messages were sent and received), the details of calls (e.g., video calls, phone calls, teleconference calls, etc.) placed and received by users (e.g., the identities of parties of the call, the contents of the call, text transcriptions of the calls, timestamps of when the calls were placed or received, etc.). Computing systems **130** and/or computing system **100** may also track and log additional data related to the performed actions such as timestamps of each of the actions.

[0029] In some examples, computing systems **130** may log data regarding the tracked actions into log files **102** and may send log files **102** to computing system **100**. In some examples, computing system **130** may send the data regarding the tracked actions to computing system **100**, and computing system **100** may generate log files **102** that includes data regarding the tracked actions. Log files **102** may be stored in a variety of different data stores in computing system **100**.

[0030] Data parsing module **106** is configured to access and parse log files **102** to extract, from log files **102**, data associated with prior performance of a particular process by users within the organization and to store, in process logs **104**, data from prior performance of the process by users within the organization. Data parsing module **106** may extract, for each performance of a given process, data such as the user that performed the process, all of the actions taken by the user in performing the process, data regarding each action taken by the user in performing the process (e.g., the action taken, timestamps of the start and end of the action, the contents of messages and/or calls send and/or received to perform the action, etc.), the ordering of the actions taken to perform the process, and the like. Data parsing module **106** may therefore generate process log **104** that contains data regarding each performance of a given process by each user of an organization.

[0031] Data parsing module **106** may be able to parse log files **102** to extract all of the logged data regarding a specific performance of a process based on a unique identifier associated with the performance of the process. For example, in the example of a process for processing loan applications, each application may be associated with a unique loan number, which may be an alphanumeric string, such as a string of numbers and/or characters, that is included in all forms of communication regarding the application. Each loan number may also be associated in log files **102** with a particular user that took the actions to process the loan. To extract the actions taken to process the particular application from log files **102**, data parsing module **106** may parse log files **102** to search for log entries that contain the loan number associated with the application. Data parsing module **106** may extract all log entries that contain the loan number associated with the application and may include the extracted data associated with the loan number in process logs **104** as the actions taken for a single performance of the loan application process. Process logs **104** may therefore, for a particular loan, include data regarding the user that processed the loan and data regarding all of the actions taken by the user to process the loan.

[0032] Process logs **104** may be log files that log, for a given process (e.g., loan approval), data from prior performances of the process by users within the organization. By including log data from prior performance of a process by users within the organization, process logs **104** may capture the general process workflow of the process and all the variances in performing the process, as performed by users within the organization.

[0033] Instructions generation model **110** may be configured to receive process log **104** that contains data associated with prior performances of a process, and to generate, based on the data associated with prior performances of a process, process instructions **112** for performing the process. Instructions generation model **110** may synthesize the different actions and workflows taken by different users to perform a given process, as captured in process log **104**, to generate a single set of process instructions **112** for performing the process. Process instructions **112** may be human readable process instructions. That is, instructions generation model **110** may generate

process instructions **112** that are designed to be read and understood by a human, as opposed to machine-readable instructions, such as computer code, that are designed to be automatically read and processed by a computer.

[0034] In some examples, computing system **100** may, in response to instructions generation model **110** generating process instructions **112**, send process instructions **112** to process administration system **132**. Process administration system **132** may represent any suitable computing system, such as one or more desktop computers, laptop computers, mainframes, servers, and the like. In some examples, process administration system **132** may represent cloud computing systems that provide access to their respective services via a cloud. Process administration system **132** may receive and store process instructions **112** so that other computing systems may be able to retrieve process instructions **112** from process administration system **132**. For example, a user that wishes to perform the process may use a computing device to communicate with process administration system **132** in order to access and view process instructions **112** for performing the process.

[0035] Instructions generation model **110** may generate process instructions **112** that capture variations in the prior performances of a process, as indicated by the data contained in process log **104**. That is, if different users perform the same process in different ways (e.g., by performing different numbers of steps, by performing steps of the process in different orders, etc.), instructions generation model **110** may generate process instructions **112** that captures the different ways the process is performed.

[0036] In some examples, instructions generation model **110** may be one or more neural networks trained using machine learning to receive data associated with prior performance of a process and to generate, based on the data, process instructions **112** for performing the process. For example, instructions generation model **110** may be a large language model (LLM). In the example where instructions generation model **110** is a LLM, instructions generation model **110** may be a foundational LLM that is further trained and fine-tuned to generate process instructions for processes within an organization. Examples of foundational models may include Generative Pre-trained Transformer (GPT), Claude, BigScience Large Open-science Open-access Multilingual Language Model (BLOOM), Large Language Model Meta AI (LLaMA), and the like.

[0037] In some examples, instructions generation model **110** is configured to generate process instructions **112** in the form of written instructions for performing a process. The written instructions may be verbose textual instructions, such as in the form of a written narrative, that describes how to perform the process, including describing breaks or jumps in the process workflow. In some examples, instructions generation model **110** is trained to generate process instructions **112** that are written instructions formatted for use as training data or for inclusion in a corpus for another machine-trained model configured to operate as a chatbot or a virtual assistant for users of the processes.

[0038] In some examples, instructions generation model **110** is configured to generate process instructions **112** in the form of a process map for performing a process. A process map may be a visual representation, such as in the form of a process flowchart, of the steps involved in completing a specific process. A process map may include a series of symbols and arrows that depict a flow of tasks and/or actions from the start of the process to the completion of the process. For example, a process map may include start and end points, that indicate the beginning and the end of the process, steps or tasks that represent the actions that are performed in the process, decision points that indicate decisions that affect the next steps in the process, arrows illustrating the direction of the process flow, inputs and outputs that identify what is needed to perform steps or tasks and what is produced by performing steps or tasks, and/or swim lanes that indicate different roles and/or departments responsible for each step of the process.

[0039] In some examples, instructions generation model **110** is configured to map data associated with prior performances of a process given process onto procedural template **118**. Procedural template **118** may be a pre-defined framework or structure used to standardize the way processes

are captured and presented within an organization, and may be designed to capture the variances in the workflow of a process in an appropriate format. Procedural template **118** may serve as a guideline for documenting processes to ensure consistency, clarity, and comprehensiveness across process maps. Mapping a process onto a selected procedural template may including mapping process owners and/or people (e.g., human resources), technology (systems, geographic area, applicable regulation), and/or other operational data of the process onto the procedural template.

[0040] Instructions generation model **110** may select, based on the process type of the process, procedural template **118** onto which instructions generation model **110** may map data to generate a process map for the process. An organization may have different processing types that correspond to different types of procedural templates. In the example of a financial organization, the types of procedural templates may define a standard format or sequence for certain process types, which may include accounting, financial reporting, regulatory reporting, board report, external audit report, Federal Deposit Insurance Corporation (FDIC) reporting, or the like.

[0041] Because instructions generation model **110** may be a neural network that is the result of training a foundational LLM, computing system **100** may prompt instructions generation model **110** to analyze prior performances of the process. For example, computing system **100** may prompt instructions generation model **110** with “given this log file and then the contents of the log file, please develop a process instruction” to cause instructions generation model **110** to generate process instructions **112**. In another example, computing system **100** may prompt instructions generation model **110** with “please find the average time it takes to complete a process” to cause instructions generation model **110** to analyze the data regarding prior performance of the process to generate an answer to the average time it takes to complete the process. Such prompts may be automatically generated by computing system **100** and inputted into instructions generation model **110** and/or may be inputted by a user.

[0042] Process refinement model **114** may be configured to receive process instructions **112** for performing a process and to generate, based on process instructions **112**, an ideal process workflow **128** for the process. Process refinement model **114** may generate such an ideal process workflow **128** through identification of redundant and/or unnecessary steps in the process instructions **112**. In some examples, process refinement model **114** may receive feedback from a human reviewer labeling the generated ideal process workflow **128** as appropriate or as needing further review and refinement. Such feedback from a human reviewer may be used to train process refinement model **114** to improve the ideal process workflows generated by process refinement model **114**.

[0043] In some examples, process refinement model **114** may provide a platform through which a human reviewer is able to review and/or refine the process instructions **112** generated by instructions generation model **110** and to compare the process instructions **112** against a procedure for the process as it should be performed (which may be written down as text, represented as a flowchart, or retained mentally by the human reviewer). Process refinement model **114** may provide a graphical user interface (GUI) for such a platform, and the human reviewer may interact with the platform, such as by providing user input, via the GUI to modify process instructions **112** to represent an ideal workflow for the process and document modifications made to the process instructions. The platform may further enable comparison and verification of the newly drafted, ideal process workflow **128** against existing policies, regulations, and testing requirements.

[0044] Operational intelligence module **116** is configured to analyze data regarding prior performances by users of a process and to generate operational intelligence regarding the performance of the process by users. For example, operational intelligence module **116** may be configured to receive process logs **104** and to generate, based on the data in process logs **104**, operational intelligence regarding the performance of the process by users.

[0045] Operational intelligence module **116** may generate such operational intelligence by using the data regarding prior performances by users of the process to systematically track and document how users perform the process. The operational intelligence may therefore provide insight into how

a process is performed by users. In some examples, operational intelligence module **116** may be included in instructions generation model **110** and may operate by prompting instructions generation model **110** to generate such operational intelligence regarding the performance of the process by users.

[0046] In some examples, operational intelligence module **116** may generate operational intelligence regarding the performance of a process by users in the form of a singular process flow or process map. Such a process flow or process map may be navigable to provide insights into the performance of the process, such as when the process was started, when the process was completed, the steps of the process that were performed and the sequencing of such steps, when each of the step of the process was performed, the systems used to perform the steps, responsible and/or accountable parties for each step of the process, evidence documenting performance of each of the steps of the process, and the like.

[0047] Operational intelligence module **116** may generate operational intelligence that compares the process as performed by users against process instructions **112** and/or ideal process workflow **128**. For example, operational intelligence module **116** may generate operational intelligence that includes conformance information, which may indicate how often users conformed to and/or deviated from process instructions **112** and/or ideal process workflow **128**. The conformance information may include, for each performance of the process that does not conform to process instructions **112** and/or ideal process workflow **128**, detailed information regarding such divergence of the performance from process instructions **112** and/or ideal process workflow **128**, such as information regarding specific steps of the process as performed that do not conform to process instructions **112** and/or ideal process workflow **128**, information regarding actions taken in those steps, information regarding the person(s) who took those steps, the systems used in taking those steps, and the like. Such detailed information may enable a human review to be able to determine, based on the conformance information, reasons for such deviations, such as whether these deviations are a failure in control or a sign of fraud, whether the process instructions need to be updated, and the like.

[0048] In some examples, such conformance information may be in the form of operational control scorecards. The operational control scorecards may rank and/or score users' performances of the process based on how well each user's performance conformed with process instructions **112** and/or ideal process workflow **128**. For example, the operational control scorecards may rank each user with a score, such as from one to ten, where a higher score for a user may correspond to a higher level of conformance to process instructions **112** and/or ideal process workflow **128**.

[0049] Operational intelligence module **116** may also generate operational intelligence that includes efficiency information. Operational efficiency information may include per-user efficiency information that indicates each user's efficiency in performing the process. Such per-user efficiency information may enable the efficiency of different users to be compared, in order to gain insights as to differences in efficiency between users performing the process. For example, operational efficiency information may include, for each user, information such as the total time taken by each user to perform the process, as the number of steps taken by each user to perform the process, the time spent by each user on each of the steps, the actions taken by each to perform each of the steps of the process, and the like, which may enable a human reviewer to determine, based on the efficiency information, answers to questions such as why certain users are taking longer to perform the process than others, why certain users are taking much longer to perform certain steps of the process, and the like.

[0050] In some examples, operational intelligence module **116** may perform techniques such as sample-based testing of a process, simulations of the process, and the like to generate operational intelligence regarding the process. For example, operational intelligence module **116** may simulate adding and/or removing steps of a process to generate operational intelligence regarding those simulated processes, such as time saved by removing one or more steps of the process, the money

saved by removing one or more steps of the process, and the like.

[0051] Operational intelligence module **116** may use data regarding prior performances by users of a process to perform simulations of the process. For example, operational intelligence module **116** may determine how much time a new step would add to the process based on data regarding the average amount of time taken to perform a step of the process, as specified by the data regarding prior performances by users of the process.

[0052] Instructions comparison model **120** is configured to identify inconsistencies between official process documents **122** for a process and process instructions **112** for the process that are generated, such as by instructions generation model **110**, based on analyzing the performance of the process by users. Such inconsistencies between the official process documents **122** and the process instructions **112** generated by instructions comparison model **120** may be indicative of deviation by users performing a process from the official or ideal written process documents for the process.

[0053] Instructions comparison model **120** may be configured to receive, as input, official process documents **122** for a process and process instructions **112** for the process, and to generate a procedural report **126** that indicates inconsistencies between process instructions **112** and official process documents **122** for the process. That is, instructions comparison model **120** may identify differences, also referred to as deltas, between process instructions **112** and official process documents **122** for the process and may generate procedural report **126** that details such differences.

[0054] The official process documents **122** for a process may be an official set of instructions for performing the process within an organization. The official process documents **122** may be in any suitable form, such as in the form of written process instructions, process maps, flowcharts, narratives, and the like. The official process documents **122** for performing a process in an organization may be a set of instructions that have been officially approved within the organization as the standardized approach within the organization for performing the process. For example, the official process documents **122** for a process may have been approved by various departments within the organization, such as by the legal department, the finance department, the human resources department, and the like to meet legal, regulatory, financial, and/or compliance needs of the organization.

[0055] Instructions comparison model **120** may be configured to categorize the deltas between process instructions **112** and the official process documents **122** to identify where users are deviating from officially prescribed processes indicated in the official process documents **122**. For example, instructions comparison model **120** may define or categorize the identified inconsistencies as process step “add,” “modify,” “counter,” or “no change” compared to the official process documents **122**, and may tag such inconsistent steps of the process with the appropriate category in procedural report **126**.

[0056] A process step tagged as “add” may indicate that the particular step has been added to the process indicated in process instructions **112** compared to official process documents **122**. A process step tagged as “modify” may indicate that the particular step has been subtracted or modified in process instructions **112** compared to official process documents **122**. A process step tagged as “counter” may indicate that the particular step is determined to be more efficient in process instructions **112** compared to official process documents **122**. A process step tagged as “no change” may indicate that the particular step in process instructions **112** is consistent with official process documents **122**.

[0057] In some examples, instructions comparison model **120** is configured to determine whether the actions taken by users to perform a process, as captured in process instructions **112**, comply with applicable regulations. Instructions comparison model **120** may receive, as input, process instructions **112**, official process documents **122**, as well as documents associated with applicable procedures, and may output an analysis of whether actions taken by users to perform a process comply with the applicable regulations. Instructions comparison model **120** may also be able to

perform attribution analysis to determine reasons as to why the actions taken by users to perform a process does or does not comply with the applicable regulations.

[0058] In some examples, instructions comparison model **120** is configured to determine whether the actions taken by users to perform a process, as captured in process instructions **112**, meet efficiency goals for the process. For example, a process may have a goal of being completed in 30 days, and instructions comparison model **120** may be configured to determine whether the actions taken by users to perform a process, as captured in process instructions **112**, would meet efficiency goal of completing the process in 30 days.

[0059] Instructions comparison model **120** may receive, as input, process instructions **112** and official process documents **122**, and may output an analysis of whether actions taken by users to perform a process would meet an efficiency goal. Instructions comparison model **120** may also be able to perform attribution analysis to determine reasons as to why the actions taken by users to perform a process would or would not enable the process to meet the efficiency goal.

[0060] In some examples, instructions comparison model **120** is a LLM that is trained using machine learning to receive official process documents **122** and process instructions **112** and to generate, based on the inputs, procedural report **126** that indicates inconsistencies between process instructions **112** and official process documents **122** for the process. Instructions comparison model **120** may be a foundational model that is further trained and fine-tuned to generate process instructions for processes within an organization.

[0061] In an example, where computing system **100** is used in an automotive loan division of an organization, instructions generation model **110** may generate process instructions **112** that describe the process, as performed by employees in the automotive loan division, for approving or denying automotive loans. Instructions comparison model **120** may compare the process instructions **112** generated by instructions generation model **110** against official process documents **122** written by the organization that enumerate an approval process for automotive loans. Instructions comparison model **120** may analyze the differences or deltas identified between process instructions **112** and the official process documents **122** to generate procedural report **126** that may indicate how users are deviating from approved processes when approving automotive loans. The organization may use such analysis in procedural report **126** to recommend and/or generate new official process documents **122** to either include the deviation (e.g., if it improves efficiency or compliance) or correct/avoid the deviation (e.g., if it is less efficient, increases errors, violates policies/preferences, etc.).

[0062] In some examples, process analysis module **124** is configured to conduct root cause analysis of problems or inconsistencies that emerge in a process workflow based on an identified pattern of deviation from official process documents **122**. Process analysis module **124** may be configured to capture unique characteristics associated with the deviation and to determine whether the official process documents **122** of the process may require modification to prevent future inconsistencies. Computing system **100** may communicate with process administration system **132** to send notifications or other indications of the results of the root cause analysis to process administration system **132**.

[0063] In some scenarios, instructions generation model **110** may be configured to track, in real-time, changes to users' performances of a process and to generate process instructions **112** for the process that are based on tracking the changes to users' performances of the process. For example, as users perform a particular process, computing systems **130** and/or computing system **100** may log the user's actions in real-time into log files **102**, and data parsing module **106** may parse log files **102** to update, in real time, process logs **104** to include log entries of actions taken by users to perform the process. Instructions generation model **110** may therefore generate new versions of process instructions **112** for a process that are based on real-time tracking of changes to users' performances of the process, and instructions comparison model **120** may determine, based on the new versions of process instructions **112**, patterns of deviations of users' performances of the

process from the official process documents **122**. Computing system **100** may send the newly generated versions of process instructions **112** and notifications of the patterns of deviations from the official process documents **122** to process administration system **132**.

[0064] In some examples, changes to users' performance of a process may reflect user adaptations to various circumstances. For example, users may begin deviating from a formal procedure for a given process in order to comply with a recent regulation change that has not been reflected in the formal procedure. Computing system **100** may send indications of the identified patterns of deviations from the official process documents **122** to process administration system **132**, which may update official process documents **122** based on the identified patterns of deviations. In some examples, computing system **100** may also use the identified patterns of deviation to automatically and/or manually update the official process documents **122** to reflect compliance with the recent regulation change. In this way, computing system **100** may enable fast adaptation of written process documentation.

[0065] In some examples, changes to users' performance of a process may reflect user error, misunderstanding, or potential fraud or other malicious activity. For example, users may begin deviating from a formal procedure for a given process based on incorrect verbal instructions or a misunderstanding, or based on malicious intent. Computing system **100** may therefore use the identified patterns of deviation to identify training issues with a particular user or across users. Alternatively, computing system **100** may use the identified patterns of deviation to alert management or security personnel to potentially malicious behavior performed by a particular user. In this way, computing system **100** may generate notifications or alerts of anomalies with respect to the formal procedure for further investigation. For example, computing system **100** may send, to process administration system **132**, notifications that indicate training issues with a particular user or across users, and/or may send, to process administration system **132**, notifications that indicate potentially malicious behavior performed by a particular user.

[0066] FIG. 2 is a block diagram illustrating an example computing system, in accordance with one or more aspects of the present disclosure. Computing system **200** of FIG. 2 is described below as an example of computing system **100** of FIG. 1. FIG. 2 illustrates only one particular example of computing system **200**, and many other examples of computing system **200** may be used in other instances and may include a subset of the components included in example computing system **200** or may include additional components not shown in FIG. 2. For example, computing system **200** may comprise a cluster of servers, and each of the servers comprising the cluster of servers making up computing system **200** may include all, or some, of the components described herein in FIG. 2, to perform the techniques disclosed herein.

[0067] For ease of illustration, computing system **200** is depicted in FIG. 2 as a single computing system. However, in other examples, computing system **200** may be implemented through multiple devices or computing systems distributed across a data center or multiple data centers. For example, computing system **200** (or various modules illustrated in FIG. 2 as included within computing system **200**) may be implemented through distributed virtualized compute instances (e.g., virtual machines, containers) of a data center, cloud computing system, server farm, and/or server cluster.

[0068] As shown in the example of FIG. 2, computing system **200** includes one or more processors **240**, one or more communication units **242**, and one or more storage devices **248**. One or more storage devices **248** include training module **260**, foundational large language model **264**, data parsing module **206**, instructions generation model **210**, process refinement model **214**, operational intelligence module **216**, instructions comparison model **220**, and process analysis module **224**. One or more storage devices **248** may also include log files **202**, process logs **204**, process instructions **212**, official process documents **222**, procedural report **226**, ideal process workflow **228**, and training data **238**.

[0069] Data parsing module **206** is an example of data parsing module of **106** of FIG. 1.

Instructions generation model **210** is an example of instructions generation model **210** of FIG. **1**. Process refinement model **214** is an example of process refinement model **114** of FIG. **1**. Operational intelligence module **216** is an example of operational intelligence module **116** of FIG. **1**. Instructions comparison model **220** is an example of instructions comparison model **120** of FIG. **1**. Process analysis module **224** is an example of process analysis module **124** of FIG. **1**. Log files **202** are an example of log files **102** of FIG. **1**. Process logs **204** are examples of process logs **104** of FIG. **1**. Process instructions **212** are examples of process instructions **112** of FIG. **1**. Official process documents **222** are examples of official process documents **122** of FIG. **1**. Procedural reports **226** are examples of procedural reports **126** of FIG. **1**. Ideal process workflow **228** is an example of ideal process workflow **128** of FIG. **1**.

[0070] One or more processors **240** may implement functionality and/or execute instructions associated with computing system **200**. Examples of one or more processors **240** include application processors, display controllers, auxiliary processors, one or more sensor hubs, and any other hardware configured to function as a processor, a processing unit, or a processing device. Training module **260**, foundational large language model **264**, data parsing module **206**, instructions generation model **210**, process refinement model **214**, operational intelligence module **216**, instructions comparison model **220**, and process analysis module **224** may be operable by one or more processors **240** to perform various actions, operations, or functions of computing system **200**. For example, one or more processors **240** of computing system **200** may retrieve and execute instructions stored by one or more storage devices **248** that cause one or more processors **240** to perform the operations of training module **260**, foundational large language model **264**, data parsing module **206**, instructions generation model **210**, process refinement model **214**, operational intelligence module **216**, instructions comparison model **220**, and process analysis module **224**. The instructions, when executed by one or more processors **240**, may cause computing system **200** to store information within one or more storage devices **248**.

[0071] One or more communication units **242** of computing system **200** may communicate with external devices (e.g., computing systems **130** and process administration system **132**) via one or more wired and/or wireless networks by transmitting and/or receiving network signals on the one or more networks. Examples of one or more communication units **242** include a network interface card (e.g., such as an Ethernet card), an optical transceiver, a radio frequency transceiver, a global positioning satellite (GPS) receiver, or any other type of device that can send and/or receive information. Other examples of one or more communication units **242** may include short wave radios, cellular data radios, wireless network radios, as well as universal serial bus (USB) controllers.

[0072] Communication channels **250** may interconnect each of the components **240**, **242**, and **248** for inter-component communications (physically, communicatively, and/or operatively). In some examples, communication channels **250** may include a system bus, a network connection, an inter-process communication data structure, or any other method for communicating data.

[0073] One or more storage devices **248** within computing system **200** may store information for processing during operation of computing system **200** (e.g., computing system **200** may store data accessed by training module **260**, foundational large language model **264**, data parsing module **206**, instructions generation model **210**, process refinement model **214**, operational intelligence module **216**, instructions comparison model **220**, and process analysis module **224** during execution at computing system **200**). In some examples, one or more storage devices **248** is a temporary memory, meaning that a primary purpose of one or more storage devices **248** is not long-term storage. In this example, one or more storage devices **248** may be configured for short-term storage of information as volatile memory and therefore not retain stored contents if powered off. Examples of volatile memories include random access memories (RAM), dynamic random access memories (DRAM), static random access memories (SRAM), and other forms of volatile memories known in the art.

[0074] In some examples, one or more storage devices **248** may also include one or more computer-readable storage media. One or more storage devices **248**, in some examples, include one or more non-transitory computer-readable storage mediums. One or more storage devices **248** may be configured to store larger amounts of information than typically stored by volatile memory. One or more storage devices **248** may further be configured for long-term storage of information as non-volatile memory space and retain information after power on/off cycles. Examples of non-volatile memories include magnetic hard discs, optical discs, floppy discs, flash memories, or forms of electrically programmable memories (EPROM) or electrically erasable and programmable (EEPROM) memories. One or more storage devices **248** may store program instructions and/or information (e.g., data) associated with training module **260**, foundational large language model **264**, data parsing module **206**, instructions generation model **210**, process refinement model **214**, operational intelligence module **216**, instructions comparison model **220**, and process analysis module **224**. One or more storage devices **248** may include a memory configured to store data or other information associated with training module **260**, foundational large language model **264**, data parsing module **206**, instructions generation model **210**, process refinement model **214**, operational intelligence module **216**, instructions comparison model **220**, and process analysis module **224**.

[0075] One or more processors **240** are configured to execute training module **260** to train instructions generation model **210** to generate, based on data associated with prior performances of a process, process instructions **212** for performing the process. Instructions generation model **210** may be one or more neural networks, such as a large language model (LLM), and training module **260** may perform training and/or fine tuning of foundational LLM **264** to generate instructions generation model **210**.

[0076] In some examples, training module **260** may train instructions generation model **210** to generate process instructions for a process based on prior performances of the process using training data **238** that includes a large number (e.g., tens of thousands) of example process logs detailing prior performances of a process and corresponding process instructions for the process. The example process logs may include process logs having data regarding prior performances of a process that are performed in different ways, and the corresponding process instructions may capture the various ways the process was performed, thereby training instructions generation model **210** to be able to generate process instructions that capture variations in the prior performances of a process. In this way, training module **260** may train instructions generation model **210** to learn how to generate process instructions of a process based on prior performances of the process.

[0077] In some examples, training module **260** may train instructions generation model **210** to generate process instructions in the form of human-readable written instructions by using process instructions in the form of human-readable written data to train instructions generation model **210**. The written instructions used to train instructions generation model **210** may be verbose textual instructions, such as in the form of a written narrative in natural language, that describes how to perform the process, including describing breaks or jumps in the process workflow. In some examples, to train instructions generation model **210** to generate process instructions that are written instructions formatted for use as training data **238** or for inclusion in a corpus for another machine-trained model configured to operate as a chatbot or a virtual assistant for users of the process, the written instructions used to train instructions generation model **210** may be formatted for use as training data or for inclusion in a corpus for use as training data **238** or for inclusion in a corpus for another machine-trained model configured to operate as a chatbot or a virtual assistant.

[0078] In some examples, training module **260** may train instructions generation model **210** to generate process instructions in the form of process maps. For example, training module **260** may train instructions generation model **210** to map data regarding prior performances of a process onto procedural template **218** to generate a process map of the process by training instructions generation model **210** using training data **238** that includes example process logs detailing prior

performances of processes, corresponding procedural templates, and corresponding process maps. In this way, training module **260** may train instructions generation model **210** to, for prior performances of a process, select an appropriate procedural template and to map data regarding the prior performances of the process onto the appropriate procedural template to generate a process map of the process.

[0079] One or more processors **240** are configured to execute training module **260** to train process refinement model **214** to receive process instructions **212** for performing a process and to identify redundant and/or unnecessary steps in process instructions **212** to generate an ideal process workflow **228** for the process. Process refinement model **214** may be one or more neural networks, such as a large language model (LLM), and training module **260** may perform training and/or fine tuning of foundational LLM **264** to generate process refinement model **214**.

[0080] In some examples, training module **260** may train process refinement model **214** to generate an ideal workflow for a process and to identify redundant and/or unnecessary steps in the process instructions based on the process instructions. The training data **238** used to train process refinement model **214** includes a large number (e.g., tens of thousands) of example process instructions for processes, corresponding ideal workflows for the process, and corresponding tags for the processes indicating redundant and/or unnecessary steps in the corresponding processes. In this way, training module **260** may train process refinement model **214** to learn how to generate an ideal workflow for a process based on process instructions for the process and to identify redundant and/or unnecessary steps in the process instructions.

[0081] One or more processors **240** are configured to execute training module **260** to train instructions comparison model **220** to identify inconsistencies between official process documents **222** for a process and process instructions **212** for the process that are generated, such as by instructions generation model **210**. Instructions comparison model **220** may be one or more neural networks, such as a large language model (LLM), and training module **260** may perform training and/or fine tuning of foundational LLM **264** to generate instructions comparison model **220**.

[0082] In some examples, training module **260** may train instructions comparison model **220** to generate procedural report **226** that indicates inconsistencies between official process documents **222** for a process and process instructions **212** for the process using training data **238** that includes a large number (e.g., tens of thousands) of example process instructions, corresponding official process documents, and corresponding procedural reports that indicate inconsistencies between a corresponding official process documents and a corresponding process instructions. In this way, training module **260** may train instructions comparison model **220** to learn how to generate procedural report **226** that indicates inconsistencies between official process documents **222** for a process and process instructions **212** for the process.

[0083] In some examples, training module **260** may train instructions comparison model **220** to generate procedural report **226** that categorizes inconsistencies between official process documents **222** for a process and process instructions **212** for the process. For example, training module **260** may train instructions comparison model **220** using training data **238** that includes a large number (e.g., tens of thousands) of example process instructions, corresponding official process documents, and corresponding procedural reports that indicate and categorize the inconsistencies between a corresponding official process documents and a corresponding process instructions.

[0084] In some examples, training module **260** may train instructions comparison model **220** to generate procedural report **226** that indicate whether process instructions **212** for a process comply with applicable regulations. For example, training module **260** may train instructions comparison model **220** using training data **238** that includes a large number (e.g., tens of thousands) of example process instructions, corresponding applicable regulations, and corresponding procedural reports that indicate whether a corresponding process instructions comply with corresponding applicable regulations.

[0085] In some examples, training module **260** may train instructions comparison model **220** to

generate procedural report **226** that indicate whether process instructions **212** for a process meet efficiency goals. For example, training module **260** may train instructions comparison model **220** using training data **238** that includes a large number (e.g., tens of thousands) of example process instructions and corresponding procedural reports that indicate whether a corresponding process instructions meet efficiency goals.

[0086] Training module **260** may train and/or fine-tune instructions comparison model **220** to perform attribution analysis to determine reasons as to why the actions taken by users to perform a process, as indicated in process instructions **212** would or would not enable the process to meet an efficiency goal and/or to comply with applicable regulations. For example, training module **260** may fine-tune instructions comparison model **220** using training data **238** that include a large number (e.g., tens of thousands) of example stimulus and response pairs. Each example stimulus and response pair may include an example process instruction, one or more applicable regulations, one or more efficiency goals, and one or more example questions regarding whether actions indicated in the process instruction would or would not cause the process to meet an efficiency goal and/or to comply with applicable regulations, and a preferred response to the question that is a reasoned answer of whether actions indicated in the process instruction would or would not cause the process to meet an efficiency goal and/or to comply with applicable regulations. In this way, training module **260** may be able to train and fine-tune instructions comparison model **220** to perform attribution analysis to determine reasons as to why the actions taken by users to perform a process, as indicated in process instructions **212** would or would not enable the process to meet an efficiency goal and/or to comply with applicable regulations.

[0087] In some examples, instructions comparison model **220** is implemented using the LangChain framework on top of a LLM to create reasoning engines that are able to determine whether process instructions **212** are in compliance with official process documents **222** and/or regulations associated with the process and to determine whether process instructions **212** are able to meet an efficiency goal. Such reasoning engines may be linked together as a chain of thoughts to perform logical reasoning, such as in order to perform attribution analysis to determine reasons as to why a process performed according to process instructions **212** is or is not in compliance with official process documents **222** and/or to determine reasons as to why a process performed according to process instructions **212** is or is not meeting efficiency goals.

[0088] For example, the reasoning engines may be able to perform chain of thought prompting of the underlying LLM to instruct the LLM to explicitly reason, step-by-step, the determination made by the LLM of whether process instructions **212** are in compliance with official process documents **222** and/or regulations associated with the process, or the determination made by the LLM of whether process instructions **212** are able to meet an efficiency goal. Instructions comparison model **220** may therefore capture the reasoning outputted by the LLM as reasons as to why the actions taken by users to perform a process, as indicated in process instructions **212** would or would not enable the process to meet an efficiency goal and/or to comply with applicable regulations.

[0089] In some examples, instead of training a single instructions comparison model **220** that performs attribution analysis to determine reasons as to why actions taken by users to perform a process, as indicated in process instructions **212** would or would not meet an efficiency goal as well as the reasons as to why the actions would or would not comply with applicable regulations, training module **260** may train and/or fine-tune separate instructions comparison models for performing attribution analysis. Training module **260** may train a first instructions comparison model to performs attribution analysis to determine both the reasons as to why the actions taken by users to perform a process, as indicated in process instructions **212** would or would not enable the process to meet an efficiency goal. Similarly, training module **260** may train a separate, second instructions comparison model to performs attribution analysis to determine both the reasons as to why the actions taken by users to perform a process, as indicated in process instructions **212** would

or would not enable the process to comply with applicable regulations.

[0090] The two different models may therefore be trained to produce different recommendations based on the attribution analysis. For example, the first instructions comparison model may be able to output, in the procedure report, a recommendation to re-train users that are performing the process within the organization if the first model determines that the actions taken by users to perform a process, as indicated in process instructions **212** would not enable current performance of the process to meet an efficiency goal. Similarly, the second instructions comparison model may be able to output, in the procedure report, a recommendation to shut down performance of the process within the organization if the second model determines that the actions taken by users to perform a process, as indicated in process instructions **212** would not enable current performance the process to comply with applicable regulations.

[0091] In some examples, training module **260** may train instructions comparison model **220** to generate procedural report **226** to detect whether patterns of deviations between official process documents **222** for a process and process instructions **212** for the process indicate that the actions taken by users to perform the process, as indicated in process instructions **212**, are indicative of user adaptations to comply with a recent regulation change that has not been reflected in official process documents **222**. For example, training module **260** may train instructions comparison model **220** using training data **238** that includes a large number (e.g., tens of thousands) of example process instructions, corresponding official process documents, corresponding regulation changes, and corresponding procedural reports that indicate that the inconsistencies between a corresponding official process documents and a corresponding process instructions are the result of user adaptations to comply with a recent regulation change that has not been reflected in the corresponding official process documents.

[0092] In some examples, training module **260** may train instructions comparison model **220** to generate procedural report **226** to detect whether patterns of deviations between official process documents **222** for a process and process instructions **212** for the process indicate that the actions taken by users to perform the process, as indicated in process instructions **212**, are indicative of user error, misunderstanding, or potential fraud or other malicious activity. For example, training module **260** may train instructions comparison model **220** using training data **238** that includes a large number (e.g., tens of thousands) of example process instructions, corresponding official process documents, and corresponding procedural reports that indicate that the inconsistencies between a corresponding official process documents and a corresponding process instructions are the result of user error, misunderstanding, or potential fraud or other malicious behaviors.

[0093] One or more processors **240** are configured to execute process tracking module **208** to track performances of processes by users within an organization and to log data associated with such performances of processes into log files **202**. For example, process tracking module **208** may receive, from computing systems **130**, data associated with actions performed by users interacting with computing systems **130** to perform actions, and process tracking module **208** may use the data to log actions performed by users to perform the processes into log files **202**.

[0094] For example, process tracking module **208** may receive, from computing systems **130**, data regarding computing systems and websites accessed by users, the interactions of users with the computing systems and websites (e.g., keystrokes and/or text entered by the users, cursor movements of the users, options and/or links selected by the users), details of messages (e.g., e-mails, text messages, direct messages, instant messages, etc.) sent and received by the users (e.g., the identities of senders and/or recipients of the messages, the contents of the messages, the timestamps of when the messages were sent and received), the details of calls (e.g., video calls, phone calls, teleconference calls, etc.) placed and received by users (e.g., the identities of parties of the call, the contents of the call, text transcriptions of the calls, timestamps of when the calls were placed or received, etc.). Process tracking module **208** may therefore log such data into log files **202**.

[0095] One or more processors **240** are configured to execute data parsing module **206** to access and parse log files **202** to extract, from log files **202**, data associated with prior performance of a particular process by users within the organization and to store, in process logs **204**, data from prior performance of the process by users within the organization. Data parsing module **206** may extract, for each performance of a given process, data such as the user that performed the process, all of the actions taken by the user in performing the process, data regarding each action taken by the user in performing the process (e.g., the action taken, timestamps of the start and end of the action, the contents of messages and/or calls send and/or received to perform the action, etc.), the ordering of the actions taken to perform the process, and the like. Data parsing module **206** may therefore generate process log **204** that contains data regarding each performance of a given process by each user of an organization.

[0096] Data parsing module **206** may be able to parse log files **202** to extract all of the logged data regarding a specific performance of a process based on a unique identifier associated with the performance of the process. For example, each entry in log files **202** associated with the performance of a process may include a unique identifier associated with the performance of the process. For example, in the process for approving a loan application, the loan application may be assigned with a unique loan number. While performing actions to approve the loan application, the unique loan number may be used to perform queries in various systems to gather information for approving the loan, be included in messages (e.g., in e-mail messages) about the loan application, be mentioned in phone calls regarding the loan application, and the like.

[0097] Data parsing module **206** may therefore be able to extract, from log files **202**, log entries for a particular performance of a process by extracting all log entries in log files **202** having a particular unique identifier associated with the particular performance of the process. In this way, data parsing module **206** may generate process logs **204** that include, for each performance of a process, a sequence of timestamped log entries. Process logs **204** may therefore capture the general process workflow of a process and all the variances in performing the process, as performed by users within the organization.

[0098] One or more processors **240** are configured to execute instructions generation model **110** to receive, from data parsing module **206**, process log **204** that contains data associated with prior performances of a process, and to generate, based on the data associated with prior performances of a process, process instructions **212** for performing the process. Instructions generation model **210** may synthesize the different actions and workflows taken by different users to perform a given process, as captured in process log **204**, to generate a single set of process instructions **212** for performing the process.

[0099] Instructions generation model **210** may generate process instructions **212** that capture variations in the prior performances of a process, as indicated by the data contained in process log **204**. That is, if different users perform the same process in different ways (e.g., by performing different numbers of steps, by performing steps of the process in different orders, etc.), instructions generation model **210** may generate process instructions **212** that captures the different ways the process is performed.

[0100] In some examples, instructions generation model **210** is configured to generate process instructions **212** in the form of written instructions for performing a process. The written instructions may be verbose textual instructions, such as in the form of a written narrative, that describes how to perform the process, including describing breaks or jumps in the process workflow. In some examples, instructions generation model **210** is trained to generate process instructions **212** that are written instructions formatted for use as training data **238** or for inclusion in a corpus for another machine-trained model configured to operate as a chatbot or a virtual assistant for users of the processes.

[0101] In some examples, instructions generation model **210** is configured to generate process instructions **212** in the form of a process map for performing a process. A process map may be a

visual representation, such as in the form of a process flowchart, of the steps involved in completing a specific process. A process map may include a series of symbols and arrows that depict a flow of tasks and/or actions from the start of the process to the completion of the process. For example, a process map may include start and end points, that indicate the beginning and the end of the process, steps or tasks that represent the actions that are performed in the process, decision points that indicate decisions that affect the next steps in the process, arrows illustrating the direction of the process flow, inputs and outputs that identify what is needed to perform steps or tasks and what is produced by performing steps or tasks, and/or swim lanes that indicate different roles and/or departments responsible for each step of the process.

[0102] In some examples, instructions generation model **210** is configured to map data associated with prior performances of a process given process onto procedural template **218**. Procedural template **218** may be a pre-defined framework or structure used to standardize the way processes are captured and presented within an organization, and may be designed to capture the variances in the workflow of a process in in an appropriate format. Procedural template **218** may serve as a guideline for documenting processes to ensure consistency, clarity, and comprehensiveness across process maps. Mapping a process onto a selected procedural template may including mapping process owners and/or people (e.g., human resources), technology (systems, geographic area, applicable regulation), and/or other operational data of the process onto the procedural template.

[0103] Instructions generation model **210** may select, based on the process type of the process, procedural template **218** onto which instructions generation model **210** may map data to generate a process map for the process. An organization may have different processing types that correspond to different types of procedural templates. In the example of a financial organization, the types of procedural templates may define a standard format or sequence for certain process types, which may include accounting, financial reporting, regulatory reporting, board report, external audit report, Federal Deposit Insurance Corporation (FDIC) reporting, or the like.

[0104] Computing system **200** may include or otherwise provide a platform through which a human reviewer is able to review and/or refine the process instructions **212** generated by instructions generation model **210** and to compare the process instructions **212** against a procedure for the process as it should be performed (which may be written down as text, represented as a flowchart, or retained mentally by the human reviewer). The human reviewer may interact with the platform, such as by providing user input, to modify process instructions **212** to represent an ideal workflow for the process and document modifications made to the process instructions. The platform may further enable comparison and verification of the newly drafted, ideal process workflow **228** against existing policies, regulations, and testing requirements.

[0105] One or more processors **240** are configured to execute process refinement model **214** may to receive process instructions **212** for performing a process and to generate, based on process instructions **212**, an ideal process workflow **228** for the process. Process refinement model **214** may generate such an ideal process workflow **228** through identification of redundant and/or unnecessary steps in the process instructions **212**. In some examples, process refinement model **214** may receive feedback from a human reviewer labeling the generated ideal process workflow **228** as appropriate or as needing further review and refinement. Such feedback from a human reviewer may be used to train process refinement model **214** to improve the ideal process workflows generated by process refinement model **214**.

[0106] One or more processors **240** are configured to execute operational intelligence module **216** to analyze data regarding prior performances by users of a process and to generate operational intelligence regarding the performance of the process by users. For example, operational intelligence module **216** may be configured to receive process logs **204** and to generate, based on the data in process logs **204**, operational intelligence regarding the performance of the process by users.

[0107] Operational intelligence module **216** may generate such operational intelligence by using

the data regarding prior performances by users of the process to systematically track and document how users perform the process. The operational intelligence may therefore provide insight into how a process is performed by users. In some examples, operational intelligence module **216** may be included in instructions generation model **210** and may operate by prompting instructions generation model **210** to generate such operational intelligence regarding the performance of the process by users.

[0108] In some examples, operational intelligence module **216** may generate operational intelligence regarding the performance of a process by users in the form of a singular process flow or process map. Such a process flow or process map may be navigable to provide insights into the performance of the process, such as when the process was started, when the process was completed, the steps of the process that were performed and the sequencing of such steps, when each of the step of the process was performed, the systems used to perform the steps, responsible and/or accountable parties for each step of the process, evidence documenting performance of each of the steps of the process, and the like.

[0109] Operational intelligence module **216** may generate operational intelligence that compares the process as performed by users against process instructions **212**. For example, operational intelligence module **216** may generate operational intelligence that includes conformance information, which may indicate how often users conformed to and/or deviated from process instructions **212**. The conformance information may include, for each performance of the process that does not conform to process instructions **212**, detailed information regarding such divergence of the performance from process instructions **212**, such as information regarding specific steps of the process as performed that do not conform to process instructions **212**, information regarding actions taken in those steps, information regarding the person(s) who took those steps, the systems used in taking those steps, and the like. Such detailed information may enable a human review to be able to determine, based on the conformance information, reasons for such deviations, such as whether these deviations are a failure in control or a sign of fraud, whether the process instructions need to be updated, and the like.

[0110] In some examples, such conformance information may be in the form of operational control scorecards. The operational control scorecards may rank and/or score users' performances of the process based on how well each user's performance conformed with process instructions **212**. For example, the operational control scorecards may rank each user with a score, such as from one to ten, where a higher score for a user may correspond to a higher level of conformance to process instructions **212**.

[0111] Operational intelligence module **216** may also generate operational intelligence that includes efficiency information. Operational efficiency information may include per-user efficiency information that indicates each user's efficiency in performing the process. Such per-user efficiency information may enable the efficiency of different users to be compared, in order to gain insights as to differences in efficiency between users performing the process. For example, operational efficiency information may include, for each user, information such as the total time taken by each user to perform the process, as the number of steps taken by each user to perform the process, the time spent by each user on each of the steps, the actions taken by each to perform each of the steps of the process, and the like, which may enable a human reviewer to determine, based on the efficiency information, answers to questions such as why certain users are taking longer to perform the process than others, why certain users are taking much longer to perform certain steps of the process, and the like.

[0112] In some examples, operational intelligence module **216** may perform techniques such as sample-based testing of a process, simulations of the process, and the like to generate operational intelligence regarding the process. For example, operational intelligence module **216** may simulate adding and/or removing steps of a process to generate operational intelligence regarding those simulated processes, such as time saved by removing one or more steps of the process, the money

saved by removing one or more steps of the process, and the like.

[0113] Operational intelligence module **216** may use data regarding prior performances by users of a process to perform simulations of the process. For example, operational intelligence module **216** may determine how much time a new step would add to the process based on data regarding the average amount of time taken to perform a step of the process, as specified by the data regarding prior performances by users of the process.

[0114] One or more processors are configured to execute instructions comparison model **220** to identify inconsistencies between official process documents **222** for a process and process instructions **212** for the process that are generated, such as by instructions generation model **210**, based on analyzing the performance of the process by users. Such inconsistencies between the official process documents **222** and the process instructions **212** generated by instructions comparison model **220** may be indicative of deviation by users performing a process from the official or ideal written process documents for the process.

[0115] Instructions comparison model **220** may receive, as input, official process documents **222** for a process and process instructions **212** for the process, and to generate a procedural report **226** that indicates inconsistencies between process instructions **212** and official process documents **222** for the process. That is, instructions comparison model **220** may identify differences, also referred to as deltas, between process instructions **212** and official process documents **222** for the process and may generate procedural report **226** that details such differences.

[0116] The official process documents **222** for a process may be an official set of instructions for performing the process within an organization. The official process documents **222** may be in any suitable form, such as in the form of written process instructions, process maps, flowcharts, narratives, and the like. The official process documents **222** for performing a process in an organization may be a set of instructions that have been officially approved within the organization as the standardized approach within the organization for performing the process. For example, the official process documents **222** for a process may have been approved by various departments within the organization, such as by the legal department, the finance department, the human resources department, and the like to meet legal, regulatory, financial, and/or compliance needs of the organization.

[0117] Instructions comparison model **220** may be configured to categorize the deltas between process instructions **212** and the official process documents **222** to identify where users are deviating from officially prescribed processes indicated in the official process documents **222**. For example, instructions comparison model **220** may define or categorize the identified inconsistencies as process step “add,” “modify,” “counter,” or “no change” compared to the official process documents **222**, and may tag such inconsistent steps of the process with the appropriate category in procedural report **226**.

[0118] A process step tagged as “add” may indicate that the particular step has been added to the process indicated in process instructions **212** compared to official process documents **222**. A process step tagged as “modify” may indicate that the particular step has been subtracted or modified in process instructions **212** compared to official process documents **222**. A process step tagged as “counter” may indicate that the particular step is determined to be more efficient in process instructions **212** compared to official process documents **222**. A process step tagged as “no change” may indicate that the particular step in process instructions **212** is consistent with official process documents **222**.

[0119] In some examples, instructions comparison model **220** is configured to determine whether the actions taken by users to perform a process, as captured in process instructions **212**, comply with applicable regulations. Instructions comparison model **220** may receive, as input, process instructions **212**, official process documents **222**, as well as documents associated with applicable procedures, and may output an analysis of whether actions taken by users to perform a process comply with the applicable regulations. Instructions comparison model **220** may also be able to

perform attribution analysis to determine reasons as to why the actions taken by users to perform a process does or does not comply with the applicable regulations.

[0120] In some examples, one or more processors are configured to execute instructions comparison model **220** to determine whether the actions taken by users to perform a process, as captured in process instructions **212**, meet efficiency goals for the process. For example, a process may have a goal of being completed in 30 days, and instructions comparison model **220** may be configured to determine whether the actions taken by users to perform a process, as captured in process instructions **212**, would meet efficiency goal of completing the process in 30 days.

[0121] Instructions comparison model **220** may receive, as input, process instructions **212** and official process documents **222**, and may output an analysis of whether actions taken by users to perform a process would meet an efficiency goal. Instructions comparison model **220** may also be able to perform attribution analysis to determine reasons as to why the actions taken by users to perform a process would or would not enable the process to meet the efficiency goal.

[0122] In some examples, process analysis module **224** is configured to conduct root cause analysis of problems or inconsistencies that emerge in a process workflow based on an identified pattern of deviation from official process documents **222**. Process analysis module **224** may be configured to capture unique characteristics associated with the deviation and to determine whether the official process documents **222** of the process may require modification to prevent future inconsistencies.

[0123] In some scenarios, instructions generation model **210** may be configured to track, in real-time, changes to users' performances of a process and to generate process instructions **212** for the process that are based on tracking the changes to users' performances of the process. For example, as users perform a particular process, computing system **200** may log the user's actions in real-time into log files **202**, and data parsing module **206** may parse log files **202** in real time to update process logs **204**, in real-time, to include log entries of actions taken by users to perform the process. Instructions generation model **210** may therefore generate process instructions **212** for a process that are based on real-time tracking of changes to users' performances of the process, and instructions comparison model **220** may determine, based on process instructions **212**, patterns of deviations of users' performances of the process from the official process documents **222**.

[0124] In some examples, changes to users' performance of a process may reflect user adaptations to various circumstances. For example, users may begin deviating from a formal procedure for a given process in order to comply with a recent regulation change that has not been reflected in the formal procedure. Computing system **200** may therefore use the identified patterns of deviation to automatically and/or manually update the official process documents **222** to reflect compliance with the recent regulation change. In this way, computing system **200** may enable fast adaptation of written process documentation.

[0125] In some examples, changes to users' performance of a process may reflect user error, misunderstanding, or potential fraud or other malicious activity. For example, users may begin deviating from a formal procedure for a given process based on incorrect verbal instructions or a misunderstanding, or based on malicious intent. Computing system **200** may therefore use the identified patterns of deviation to identify training issues with a particular user or across users. Alternatively, computing system **200** may use the identified patterns of deviation to alert management or security personnel to potentially malicious behavior performed by a particular user. In this way, computing system **200** may generate notifications or alerts of anomalies with respect to the formal procedure for further investigation.

[0126] FIG. **3** is a flow diagram illustrating operations performed by an example computing system, in accordance with one or more aspects of the present disclosure. FIG. **3** is described below within the context of computing system **200** of FIG. **1**. In other examples, operations described in FIG. **2** may be performed by one or more other components, modules, systems, or devices. Further, in other examples, operations described in connection with FIG. **2** may be merged, performed in a difference sequence, omitted, or may encompass additional operations not specifically illustrated or

described.

[0127] In the process illustrated in FIG. 3, and in accordance with one or more aspects of the present disclosure, one or more processors **240** may access log files **202** that log data associated with prior performances of a process by users, wherein the data are recorded by one or more computing systems based on tracking user interactions with the one or more computing systems to perform the process (**302**). One or more processors **240** may generate, using an instructions generation model **210** that is trained using machine learning to generate process instructions **212**, the process instructions **212** for performing the process based on the data associated with the prior performances of the process, wherein the process instructions **212** are human-readable written instructions (**304**).

[0128] In some examples, to generate the process instructions **212**, the one or more processors **240** may select a procedural template **218** for the process. One or more processors **240** may map, using the instructions generation model **210**, the data associated with the prior performances of the process by the users onto the procedural template **218** to generate a process map for performing the process.

[0129] In some examples, the one or more processors **240** may train a foundational large language model **264** to be the instructions generation model **210** that generates, from the data associated with the prior performances of the process by the users, the process instructions **212** for performing the process.

[0130] In some examples, to access the log files **202** that log the data associated with the prior performances of the process by the users, one or more processors **240** may parse the log files **202** to determine log entries associated with the same unique identifier as data associated with an instance of a prior performance of the process by a user and may include the data associated with the instance of the prior performance of the process by the user in the data associated with the prior performances of the process by the users.

[0131] In some examples, one or more processors **240** may generate, using a process refinement model **214** trained using machine learning to refine the process instructions **212**, an ideal process workflow **228** for the process. In some examples, one or more processors **240** may generate operational intelligence associated with the prior performances of the process that includes at least one of conformance information associated with the prior performances of the process or efficiency information associated with the prior performance of the process.

[0132] In some examples, one or more processors **240** may train a foundational large language model **264** to be the instructions comparison model **220** that compares the process instructions **212** and official process documents **222** for the process to generate a procedural report **226** that indicates inconsistencies between the process instructions **212** and the official process documents **222** for the process.

[0133] In some examples, the instructions comparison model **220** includes one or more reasoning engines implemented using a LangChain framework to perform attribution analysis of why the actions taken by the users to perform the process would enable the process to meet an efficiency goal, and wherein the procedural report **226** includes the attribution analysis.

[0134] In some examples, the procedural report **226** may categorize differences between the process instructions **212** and the official process documents **222** as add, modify, counter, or no change. In some examples, the procedural report **226** may indicate that the inconsistencies between the process instructions **212** and the official process documents **222** for the process are due to malicious behavior by one or more of the users. In some examples, the procedural report **226** may indicate that the inconsistencies between the process instructions and the official process documents **222** for the process are due to compliance with recent regulation changes.

[0135] For processes, apparatuses, and other examples or illustrations described herein, including in any flowcharts or flow diagrams, certain operations, acts, steps, or events included in any of the techniques described herein can be performed in a different sequence, may be added, merged, or

left out altogether (e.g., not all described acts or events are necessary for the practice of the techniques). Moreover, in certain examples, operations, acts, steps, or events may be performed concurrently, e.g., through multi-threaded processing, interrupt processing, or multiple processors, rather than sequentially. Further certain operations, acts, steps, or events may be performed automatically even if not specifically identified as being performed automatically. Also, certain operations, acts, steps, or events described as being performed automatically may be alternatively not performed automatically, but rather, such operations, acts, steps, or events may be, in some examples, performed in response to input or another event.

[0136] The disclosures of all publications, patents, and patent applications referred to herein are hereby incorporated by reference. To the extent that any such disclosure material that is incorporated by reference conflicts with the present disclosure, the present disclosure shall control.

[0137] For ease of illustration, only a limited number of devices (e.g., computing system **100**, computing system **200**, as well as others) are shown within the Figures and/or in other illustrations referenced herein. However, techniques in accordance with one or more aspects of the present disclosure may be performed with many more of such systems, components, devices, modules, and/or other items, and collective references to such systems, components, devices, modules, and/or other items may represent any number of such systems, components, devices, modules, and/or other items.

[0138] The Figures included herein each illustrate at least one example implementation of an aspect of this disclosure. The scope of this disclosure is not, however, limited to such implementations. Accordingly, other example or alternative implementations of systems, methods or techniques described herein, beyond those illustrated in the Figures, may be appropriate in other instances. Such implementations may include a subset of the devices and/or components included in the Figures and/or may include additional devices and/or components not shown in the Figures.

[0139] The detailed description set forth above is intended as a description of various configurations and is not intended to represent the only configurations in which the concepts described herein may be practiced. The detailed description includes specific details for the purpose of providing a sufficient understanding of the various concepts. However, these concepts may be practiced without these specific details. In some instances, well-known structures and components are shown in block diagram form in the referenced figures in order to avoid obscuring such concepts.

[0140] Accordingly, although one or more implementations of various systems, devices, and/or components may be described with reference to specific Figures, such systems, devices, and/or components may be implemented in a number of different ways. For instance, one or more devices illustrated herein as separate devices may alternatively be implemented as a single device; one or more components illustrated as separate components may alternatively be implemented as a single component. Also, in some examples, one or more devices illustrated in the Figures herein as a single device may alternatively be implemented as multiple devices; one or more components illustrated as a single component may alternatively be implemented as multiple components. Each of such multiple devices and/or components may be directly coupled via wired or wireless communication and/or remotely coupled via one or more networks. Also, one or more devices or components that may be illustrated in various Figures herein may alternatively be implemented as part of another device or component not shown in such Figures. In this and other ways, some of the functions described herein may be performed via distributed processing by two or more devices or components.

[0141] Further, certain operations, techniques, features, and/or functions may be described herein as being performed by specific components, devices, and/or modules. In other examples, such operations, techniques, features, and/or functions may be performed by different components, devices, or modules. Accordingly, some operations, techniques, features, and/or functions that may be described herein as being attributed to one or more components, devices, or modules may, in

other examples, be attributed to other components, devices, and/or modules, even if not specifically described herein in such a manner.

[0142] Although specific advantages have been identified in connection with descriptions of some examples, various other examples may include some, none, or all of the enumerated advantages. Other advantages, technical or otherwise, may become apparent to one of ordinary skill in the art from the present disclosure. Further, although specific examples have been disclosed herein, aspects of this disclosure may be implemented using any number of techniques, whether currently known or not, and accordingly, the present disclosure is not limited to the examples specifically described and/or illustrated in this disclosure.

[0143] In one or more examples, the functions described may be implemented in hardware, software, firmware, or any combination thereof. If implemented in software, the functions may be stored, as one or more instructions or code, on and/or transmitted over a computer-readable medium and executed by a hardware-based processing unit. Computer-readable media may include computer-readable storage media, which corresponds to a tangible medium such as data storage media, or communication media including any medium that facilitates transfer of a computer program from one place to another (e.g., pursuant to a communication protocol). In this manner, computer-readable media generally may correspond to (1) tangible computer-readable storage media, which is non-transitory or (2) a communication medium such as a signal or carrier wave. Data storage media may be any available media that can be accessed by one or more computers or one or more processors to retrieve instructions, code and/or data structures for implementation of the techniques described in this disclosure. A computer program product may include a computer-readable medium.

[0144] By way of example, and not limitation, such computer-readable storage media can include RAM, ROM, EEPROM, or optical disk storage, magnetic disk storage, or other magnetic storage devices, flash memory, or any other medium that can be used to store desired program code in the form of instructions or data structures and that can be accessed by a computer. Also, any connection may properly be termed a computer-readable medium. For example, if instructions are transmitted from a website, server, or other remote source using a wired (e.g., coaxial cable, fiber optic cable, twisted pair) or wireless (e.g., infrared, radio, and microwave) connection, then the wired or wireless connection is included in the definition of medium. It should be understood, however, that computer-readable storage media and data storage media do not include connections, carrier waves, signals, or other transient media, but are instead directed to non-transient, tangible storage media.

[0145] Instructions may be executed by one or more processors, such as one or more digital signal processors (DSPs), general purpose microprocessors, application specific integrated circuits (ASICs), field programmable logic arrays (FPGAs), or other equivalent integrated or discrete logic circuitry. Accordingly, the terms “processor” or “processing circuitry” as used herein may each refer to any of the foregoing structure or any other structure suitable for implementation of the techniques described. In addition, in some examples, the functionality described may be provided within dedicated hardware and/or software modules. Also, the techniques could be fully implemented in one or more circuits or logic elements.

[0146] The techniques of this disclosure may be implemented in a wide variety of devices or apparatuses, including a wireless handset, a mobile or non-mobile computing device, a wearable or non-wearable computing device, an integrated circuit (IC) or a set of ICs (e.g., a chip set). Various components, modules, or units are described in this disclosure to emphasize functional aspects of devices configured to perform the disclosed techniques, but do not necessarily require realization by different hardware units. Rather, as described above, various units may be combined in a hardware unit or provided by a collection of interoperating hardware units, including one or more processors as described above, in conjunction with suitable software and/or firmware.

Claims

1. A method comprising: accessing, by one or more processors, log files that log data associated with prior performances of a process by users, wherein the data are recorded by one or more computing systems based on tracking user interactions with the one or more computing systems to perform the process; and generating, by the one or more processors and using an instructions generation model that is trained using machine learning, process instructions for performing the process based on the data associated with the prior performances of the process, wherein the process instructions are human-readable written instructions.
2. The method of claim 1, wherein generating the process instructions further comprises: selecting, by the one or more processors, a procedural template for the process; and mapping, by the one or more processors and using the instructions generation model, the data associated with the prior performances of the process by the users onto the procedural template to generate a process map for performing the process.
3. The method of claim 1, further comprising: training, by the one or more processors, a foundational large language model to be the instructions generation model that generates, from the data associated with the prior performances of the process by the users, the process instructions for performing the process.
4. The method of claim 1, wherein accessing the log files that log the data associated with the prior performances of the process by the users further comprises: parsing, by the one or more processors, the log files to determine log entries associated with the same unique identifier as data associated with an instance of a prior performance of the process by a user; and including, by the one or more processors, the data associated with the instance of the prior performance of the process by the user in the data associated with the prior performances of the process by the users.
5. The method of claim 1, further comprising: generating, by the one or more processors and using a process refinement model trained using machine learning to refine the process instructions, an ideal process workflow for the process.
6. The method of claim 1, further comprising: generating, by the one or more processors, operational intelligence associated with the prior performances of the process that includes at least one of conformance information associated with the prior performances of the process or efficiency information associated with the prior performance of the process.
7. The method of claim 1, further comprising: generating, by the one or more processors and using an instructions comparison model that is trained using machine learning to compare the process instructions and official process documents for the process, a procedural report that indicates inconsistencies between the process instructions and the official process documents for the process.
8. The method of claim 7, further comprising: training, by the one or more processors, a foundational large language model to be the instructions comparison model that compares the process instructions and official process documents for the process to generate a procedural report that indicates inconsistencies between the process instructions and the official process documents for the process.
9. The method of claim 8, wherein the instructions comparison model includes one or more reasoning engines implemented using a LangChain framework to perform attribution analysis of why actions taken by the users to perform the process would enable the process to meet an efficiency goal, and wherein the procedural report includes the attribution analysis.
10. The method of claim 7, wherein the procedural report categorizes differences between the process instructions and the official process documents as add, modify, counter, or no change.
11. The method of claim 7, wherein the procedural report indicates that the inconsistencies between the process instructions and the official process documents for the process are due to malicious behavior by at least one of the users.

- 12.** The method of claim 7, wherein the procedural report indicates that the inconsistencies between the process instructions and the official process documents for the process are due to compliance with recent regulation changes.
- 13.** A computing system comprising: memory configured to store log files that log data associated with prior performances of a process by users, wherein the data are recorded by one or more computing systems based on tracking user interactions with the one or more computing systems to perform the process; and one or more processors configured to: access the log files; and generate, using an instructions generation model that is trained using machine learning, process instructions for performing the process based on the data associated with the prior performances of the process, wherein the process instructions are human-readable written instructions.
- 14.** The computing system of claim 13, wherein to generate the process instructions, the one or more processors are further configured to: select a procedural template for the process; and map, using the instructions generation model, the data associated with the prior performances of the process by the users onto the procedural template to generate a process map for performing the process.
- 15.** The computing system of claim 13, the one or more processors are further configured to: train a foundational large language model to be the instructions generation model that generates, from the data associated with the prior performances of the process by the users, the process instructions for performing the process.
- 16.** The computing system of claim 13, wherein to access the log files that log the data associated with the prior performances of the process by the users, the one or more processors are further configured to: parse the log files to determine log entries associated with the same unique identifier as data associated with an instance of a prior performance of the process by a user; and include the data associated with the instance of the prior performance of the process by the user in the data associated with the prior performances of the process by the users.
- 17.** The computing system of claim 13, wherein the one or more processors are further configured to: generate, using a process refinement model trained using machine learning to refine the process instructions, an ideal process workflow for the process.
- 18.** The computing system of claim 13, wherein the one or more processors are further configured to: generate operational intelligence associated with the prior performances of the process that includes at least one of conformance information associated with the prior performances of the process or efficiency information associated with the prior performance of the process.
- 19.** The computing system of claim 13, wherein the one or more processors are further configured to: generate, using an instructions comparison model that is trained using machine learning to compare the process instructions and official process documents for the process, a procedural report that indicates inconsistencies between the process instructions and the official process documents for the process.
- 20.** A non-transitory computer-readable medium comprising instructions that, when executed, cause one or more processors of a computing system to: access log files that log data associated with prior performances of a process by users, wherein the data are recorded by one or more computing systems based on tracking user interactions with the one or more computing systems to perform the process; and generate, using an instructions generation model that is trained using machine learning, the process instructions for performing the process based on the data associated with the prior performances of the process, wherein the process instructions are human-readable written instructions.
-