

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250261330

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

LV; Heng

FAN MOUNTING MECHANISM AND SERVER

Abstract

A fan installing mechanism and a server are provided. The fan installing mechanism includes a base (10), a flipping member (20) and a locking component (30). The base (10) has a first limiting component (11) for limiting the movement of a fan. The flipping member (20) is rotatably connected to the base (10), and the flipping member (20) has a second limiting component (21) for limiting the movement of the fan, and has an avoiding state and a locking state. When the flipping member (20) is in the avoiding state, the flipping member (20) avoids the movement path of the installation of the fan to the base (10), and the fan is capable of being limiting-fitted to the first limiting component (11). When the flipping member (20) is in the locking state, the flipping member (20) is flipped relative to the base (10) and the second limiting component (21) is limiting-fitted to the fan, to hinder the fan from disengaging from the base (10). The locking component (30) is provided between the base (10) and the flipping member (20), and when the flipping member (20) is in the locking state, the locking component (30) locks the position of the flipping member (20) to the locking state. The present application solves the problem of time costing and labor costing in the installation of fan modules in the related art.

Inventors: LV; Heng (Suzhou, Jiangsu, CN)

Applicant: SUZHOU METABRAIN INTELLIGENT TECHNOLOGY CO., LTD
(Suzhou, CN)

Family ID: 87870110

Appl. No.: 19/116286

**Filed (or PCT
Filed):** August 09, 2024

PCT No.: PCT/CN2024/111146

Foreign Application Priority Data

CN 202310997626.3

Aug. 09, 2023

Publication Classification

Int. Cl.: H05K7/20 (20060101)

U.S. Cl.:

CPC H05K7/20172 (20130101); H05K7/20718 (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

[0001] The present application claims the priority of the Chinese patent application filed on Aug. 9, 2023 before the Chinese Patent Office with the application number of 202310997626.3 and the title of “FAN MOUNTING MECHANISM AND SERVER”, which is incorporated herein in its entirety by reference.

FIELD

[0002] The embodiments of the present application relate to the field of servers, and particularly relate to a fan installing mechanism and a server.

BACKGROUND

[0003] In the installation of the fan modules of conventional servers, usually a fan support is provided. The fan support is mounted to a bottom plate by using bolts, the fan module is provided with mounting holes, and the fan support is provided with via holes matching with the positions of the mounting holes. In the installation of the fan module, usually the fan module is placed onto the fan support, and subsequently the bolts penetrate the via holes and the mounting holes, so as to install and fix the fan module to the bottom plate.

[0004] Although the above-described mode can realize the installation and the fixing of the fan, it entirely has a high component quantity and a complicated structure. Furthermore, in the installation it is required to tighten up the bolts one by one, and the installation and the detaching are time-costing and labor-costing, which affects the efficiency, and increases the cost of labor and components. Furthermore, the conventional fan supports block part of the gas flow, which affects the efficiency of the heat dissipation by the fan modules.

SUMMARY

[0005] The embodiments of the present application provide a fan installing mechanism and a server, to at least solve the problem of time costing and labor costing in the installation of fan modules in the related art.

[0006] According to the first aspect of the present application, there is provided a fan installing mechanism, wherein the fan installing mechanism comprises a base, a flipping member and a locking component. The base has a first limiting component for limiting movement of a fan; the flipping member is rotatably connected to the base, and the flipping member has a second limiting component for limiting the movement of the fan, and has an avoiding state and a locking state; when the flipping member is in the avoiding state, the flipping member avoids a movement path of installation of the fan to the base, and the fan is capable of being limiting-fitted to the first limiting component; and when the flipping member is in the locking state, the flipping member is flipped relative to the base and the second limiting component is limiting-fitted to the fan, to hinder the fan from disengaging from the base; and [0007] the locking component is provided between the base and the flipping member, and when the flipping member is in the locking state, the locking component locks a position of the flipping member to the locking state.

[0008] In an embodiment, when the flipping member is in the locking state, the first limiting

component and the second limiting component are located on two opposite sides of the fan.

[0009] In an embodiment, the flipping member and the base are rotatable and translatable relative to each other, and the flipping member further has an intermediate state between the avoiding state and the locking state; [0010] while the flipping member is being switched from the avoiding state to the intermediate state, the flipping member is flipped relative to the base; and [0011] while the flipping member is being switched from the intermediate state to the locking state, the flipping member is translated relative to the base.

[0012] In an embodiment, a flipping axis of the flipping member and a trajectory line of the translation of the fan to the base are not parallel to each other, and a translation trajectory line of the switching of the flipping member from the intermediate state to the locking state and the trajectory line of the translation of the fan to the base are not perpendicular to each other.

[0013] In an embodiment, a connecting line between the first limiting component and the second limiting component and a translation trajectory line of the switching of the flipping member from the intermediate state to the locking state are parallel to each other.

[0014] In an embodiment, the flipping member comprises a first section and a second section that are sequentially connected, the first section is rotatably and translatable connected to the base, and the second limiting component and/or the locking component are located at the second section.

[0015] In an embodiment, one of the first section and the base is provided with a chute, the other of the first section and the base is provided with a connecting pin, the connecting pin is located inside the chute, and the connecting pin and the chute are translatable relative to each other and rotatable relative to each other.

[0016] In an embodiment, the connecting pin and the first limiting component are located on neighboring sides of the base.

[0017] In an embodiment, the first section is a plurality of first sections, and each of two ends of the second section is connected to one instance of the first sections, whereby the flipping member is of a structure of a shape of a rectangle without one side.

[0018] In an embodiment, the base has a limiting directing component, and the limiting directing component forms a directing channel; [0019] when the flipping member is in the avoiding state, the first section is located inside the directing channel, and the flipping member is merely capable of translating along a direction of extension of the directing channel; and [0020] when the first section has exited from the directing channel, the flipping member is capable of being flipped to switch the states.

[0021] In an embodiment, the base has a flipping limiting component, and the flipping limiting component is located in a rotation path of the flipping of the flipping member; and [0022] when the flipping member has been flipped and switched to the locking state, the flipping member and the flipping limiting component stop each other, to control a flipping angle of the flipping member.

[0023] In an embodiment, the flipping limiting component is a plurality of flipping limiting components, and on each of two opposite sides in a circumferential direction of a rotation axis of the flipping member is provided one instance of the flipping limiting components; and [0024] when the flipping member is in the locking state, the flipping member is stopping-fitted to both of the flipping limiting components on the two sides.

[0025] In an embodiment, the second limiting component and the locking component are located on a same one side of the base.

[0026] In an embodiment, the locking component comprises a lockout slot and a lockout member, wherein the lockout slot is located on the base; [0027] the lockout member is movably connected to the flipping member; and [0028] when the flipping member is in the locking state, the lockout member butts the lockout slot, and the lockout member is located inside the lockout slot and locks a relative position between the flipping member and the base.

[0029] In an embodiment, the lockout member and the lockout slot are of a shape-matching non-circular structure; and [0030] when the flipping member is in the locking state, shapes of the

lockout member and the lockout slot are aligned, the lockout member is protruded into the lockout slot, and the lockout member is rotated to be limiting-fitted to the lockout slot.

[0031] In an embodiment, the locking component further comprises a rotary knob, the rotary knob and the lockout member are connected and synchronously rotated, and the lockout member and the rotary knob are located at an inner face and an outer face of a side wall of the flipping member respectively.

[0032] In an embodiment, a connecting hole is provided at a bottom of the base, and the base is connected to an external installation frame by the connecting hole.

[0033] In an embodiment, the first limiting component and/or the second limiting component is plural, and the first limiting components or the second limiting components are arranged separately along a surface where the first limiting components or the second limiting components are located.

[0034] In an embodiment, the flipping member is of a structure of a shape of a rectangle without one side, two ends of the structure of a shape of a rectangle without one side are rotatably and translatably connected to two sides of the base; when the flipping member is in the avoiding state, a plane where the structure of a shape of a rectangle without one side is located is perpendicular to an installation surface of the base; and when the flipping member is in the locking state, the plane where the structure of a shape of a rectangle without one side is located is parallel to the installation surface of the base; [0035] the base has a limiting directing component, and the limiting directing component forms a directing channel; when the flipping member is in the avoiding state, part of the flipping member is located inside the directing channel, and the flipping member is merely capable of translating along a direction of extension of the directing channel; and when the flipping member has exited from the directing channel, the flipping member is capable of being flipped to switch the states; [0036] the flipping member further has an intermediate state between the avoiding state and the locking state; while the flipping member is being switched from the avoiding state to the intermediate state, the flipping member is flipped relative to the base; and while the flipping member is being switched from the intermediate state to the locking state, the flipping member is translated relative to the base; and [0037] the base has a flipping limiting component, and the flipping limiting component is located in a rotation path of the flipping of the flipping member; and when the flipping member has been flipped and switched to the intermediate state and the locking state, the flipping member and the flipping limiting component stop each other, to control a flipping angle of the flipping member.

[0038] According to the second aspect of the present application, there is provided a server, wherein the server comprises a fan and the fan installing mechanism stated above, and the fan is installed to the fan installing mechanism.

[0039] In the technical solutions of the present application, by providing the rotatable flipping member and the fitting between the locking component and the base, a fan installing mechanism that can lock and unlock a fan is formed. The flipping member has the locking state and the avoiding state, and the flipping member can complete the switching between the avoiding state and the locking state by actions such as rotation. While the fan is being mounted to the fan installing mechanism, the flipping member is in the avoiding state, at which point, because of the avoiding of the flipping member, the fan can smoothly enter the installation region of the base. Moreover, after the fan has entered the installation region of the base, the fan is fitted to the first limiting component of the base, to preliminarily limit the fan to the base, at which point the fan is not completely limited, and can still be removed from the base. Moreover, after the fan has been fitted to the first limiting component, i.e., after the preliminary placement of the fan has been completed, the flipping member is rotated to be switched from the original avoiding state to the locking state, and the second limiting component of the flipping member is limiting-fitted to the fan, at which point the movement path of the reverse movement of the fan to exit from the base is blocked by the flipping member, and is also blocked by the second limiting component. Accordingly, by the cooperation between the first limiting component and the second limiting component, the fan can

be locked to the base, to realize the installation of the fan to the base. After the flipping member has been flipped to the locking state, the locking component acts. The locking component causes that the flipping member cannot switch back to the avoiding state, so as to lock the position of the flipping member, thereby fixedly installing the fan to the fan installing mechanism. When inspection and repairing are required, it is merely required to unlock the locking component, and reversely rotate the flipping member, whereby the limiting to the fan can be released, and the fan can be taken out. By using the above-described configuring mode, in the installation, it is merely required to place the fan onto the base, subsequently flip the flipping member, and operate the locking component to lock the flipping member, and it is not required to tighten up the screws one by one. The whole process is convenient and quick, greatly increases the efficiency of the installation, facilitates the maintenance, and reduces the labor cost. Furthermore, the above-described mechanism has a simple structure and a low processing cost, which facilitates to reduce the processing cost. Moreover, the blocking by the flipping member to the fan is very small, and does not affect the blowing by the fan, which facilitates to improve the effect of the heat dissipation.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0040] FIG. 1 is a schematic structural diagram of a fan installing mechanism according to the first embodiment of the present application;

[0041] FIG. 2 is a schematic structural diagram of the base in FIG. 1;

[0042] FIG. 3 is a schematic structural diagram of the base in FIG. 1 in another perspective;

[0043] FIG. 4 is a schematic structural diagram of the flipping member in FIG. 1;

[0044] FIG. 5 is a schematic structural diagram of the flipping member in FIG. 1 in another perspective;

[0045] FIG. 6 is a schematic structural diagram when the fan installing mechanism in FIG. 1 and a fan are aligned for installation;

[0046] FIG. 7 is a schematic structural diagram when the fan in FIG. 1 has been placed to the base and the flipping member is in the avoiding state;

[0047] FIG. 8 is a schematic structural diagram when the flipping member in FIG. 1 has been flipped to the intermediate state; and

[0048] FIG. 9 is a schematic structural diagram when the flipping member in FIG. 1 has been translated to the locking state.

[0049] The drawings contain the following reference numbers:

[0050] **10**: base; **11**: first limiting component; **12**: connecting pin; **13**: limiting directing component; **131**: directing channel; **14**: flipping limiting component; **15**: connecting hole; **20**: flipping member; **21**: second limiting component; **22**: first section; **221**: chute; **23**: second section; **30**: locking component; **31**: lockout slot; **32**: lockout member; and **33**: rotary knob.

DETAILED DESCRIPTION

[0051] It should be noted that, subject to the avoiding of any conflict, the embodiments and the features of the embodiments of the present application may be combined. The present application will be described in detail below with reference to the drawings and the embodiments.

[0052] It should be noted that, unless otherwise indicated, all of the technical and scientific terminologies used herein have the same meanings as those usually comprehended by a person skilled in the art that the present application pertains to.

[0053] In the present application, unless stated otherwise, the used words of orientation, such as “upper”, “lower”, “top” and “bottom”, generally refer to the orientations shown in the drawings, or refer to the case in which the components themselves are in the vertical, perpendicular or gravity

direction. Likewise, in order to facilitate the comprehension and the description, “inner” and “outer” refer to the interior and the exterior with respect to the contours of the components themselves. However, those words of orientation are not intended to limit the present application. [0054] In order to solve the problem of time costing and labor costing in the installation of fan modules in the related art, the present application provides a fan installing mechanism and a server. The server has a fan and the fan installing mechanism described below, and the fan is installed to the fan installing mechanism.

The First Embodiment

[0055] The fan installing mechanism shown in FIGS. 1 to 9 comprises a base 10, a flipping member 20 and a locking component 30. The base 10 has a first limiting component 11 for limiting the movement of a fan. The flipping member 20 is rotatably connected to the base 10, and the flipping member 20 has a second limiting component 21 for limiting the movement of the fan, and has an avoiding state and a locking state. When the flipping member 20 is in the avoiding state, the flipping member 20 avoids the movement path of the installation of the fan to the base 10, and the fan is capable of being limiting-fitted to the first limiting component 11. When the flipping member 20 is in the locking state, the flipping member 20 is flipped relative to the base 10 and the second limiting component 21 is limiting-fitted to the fan, to hinder the fan from disengaging from the base 10. The locking component 30 is provided between the base 10 and the flipping member 20, and when the flipping member 20 is in the locking state, the locking component 30 locks the position of the flipping member 20 to the locking state.

[0056] In the present embodiment, by providing the rotatable flipping member 20 and the fitting between the locking component 30 and the base 10, a fan installing mechanism that can lock and unlock a fan is formed. The flipping member 20 has the locking state and the avoiding state, and the flipping member 20 can complete the switching between the avoiding state and the locking state by actions such as rotation. While the fan is being mounted to the fan installing mechanism, the flipping member 20 is in the avoiding state, at which point, because of the avoiding of the flipping member 20, the fan can smoothly enter the installation region of the base 10. Moreover, after the fan has entered the installation region of the base 10, the fan is fitted to the first limiting component 11 of the base 10, to preliminarily limit the fan to the base 10, at which point the fan is not completely limited, and can still be removed from the base 10. Moreover, after the fan has been fitted to the first limiting component 11, i.e., after the preliminary placement of the fan has been completed, the flipping member 20 is rotated to be switched from the original avoiding state to the locking state, and the second limiting component 21 of the flipping member 20 is limiting-fitted to the fan, at which point the movement path of the reverse movement of the fan to exit from the base 10 is blocked by the flipping member 20, and is also blocked by the second limiting component 21. Accordingly, by the cooperation between the first limiting component 11 and the second limiting component 21, the fan can be locked to the base 10, to realize the installation of the fan to the base 10. After the flipping member 20 has been flipped to the locking state, the locking component 30 acts. The locking component 30 causes that the flipping member 20 cannot switch back to the avoiding state, so as to lock the position of the flipping member 20, thereby fixedly installing the fan to the fan installing mechanism. When inspection and repairing are required, it is merely required to unlock the locking component 30, and reversely rotate the flipping member 20, whereby the limiting to the fan can be released, and the fan can be taken out. By using the above-described configuring mode, in the installation, it is merely required to place the fan onto the base 10, subsequently flip the flipping member 20, and operate the locking component 30 to lock the flipping member 20, and it is not required to tighten up the screws one by one. The whole process is convenient and quick, greatly increases the efficiency of the installation, facilitates the maintenance, and reduces the labor cost. Furthermore, the above-described mechanism has a simple structure and a low processing cost, which facilitates to reduce the processing cost. Moreover, the blocking by the flipping member 20 to the fan is very small, and does not affect the

blowing by the fan, which facilitates to improve the effect of the heat dissipation.

[0057] In the present embodiment, as shown in FIG. 6, the fan that is required to be installed and fixed has an overall structure that is similar to a regular tetragonal prism, and the axis of the regular tetragonal prism is horizontal, and is substantially parallel to the surface of the base **10**. Mounting holes are provided at the four corners of the end face of the regular tetragonal prism. The axes of the mounting holes are parallel to the axis of the regular tetragonal prism, and the mounting holes are blind holes. The positions of the four openings are symmetrical and the sizes are substantially equal. The mounting holes are components of the fan itself, and cooperate with the via holes in the support in the conventional installation mode, and the present embodiment still utilizes the mounting holes, and employs the mode in which the first limiting component **11** and the second limiting component **21** cooperate with the mounting holes. Accordingly, it is not required to change the structure of the fan, and the support may be directly replaced, which facilitates the reconstruction.

[0058] As shown in FIGS. 2 and 5, based on the above-described structure of the mounting hole of the fan, both of the second limiting component **21** located on the flipping member **20** and the first limiting component **11** located on the base **10** according to the present embodiment may use a protruding-column structure, and the axes of the protruding-column structures are parallel to the surface of the base **10**. Furthermore, the present embodiment employs the configuration in which, when the flipping member **20** is in the locking state, the first limiting component **11** and the second limiting component **21** are located on the two opposite sides of the fan. Accordingly, when the fan is being, along the surface of the base **10**, placed into the installation region over the base **10**, the first limiting component **11** can be protruded into the mounting hole of one end face, so as to limit all of the movements in the other directions than the exiting out of the installation region in the reverse direction of the fan. Moreover, when the flipping member **20** is in the locking state, the second limiting component **21** is protruded into the mounting hole of the other end face, so as to also limit the movement of the exiting out of the installation region in the reverse direction of the fan. Accordingly, the locking of the movement of the fan is realized, to ensure the effect that the fan is stably fixed to the base **10**.

[0059] It should be noted that the above-described two sides refer to the two sides of the base **10** along the translation trajectory line of the mounting into the base **10** of the fan, i.e., the two sides of the two end faces of the fan. Accordingly, the first limiting component **11** and the second limiting component **21** may be fitted to the mounting holes in the two end faces of the fan, to realize the limiting on the two sides, to ensure the effect of the fixing.

[0060] Certainly, the first limiting component **11** and the second limiting component **21**, besides being provided on the two opposite sides, may also be provided on neighboring sides. Accordingly, the mode of the fitting between the fan and the first limiting component **11** maintains unchanged, and, because the second limiting component **21** is on the neighboring side of the first limiting component **11**, in this case, the stopping of the movement of the exiting out of the installation region in the reverse direction of the fan is realized by stopping fitting between the side face of the second limiting component **21** and the circumferential side face of the mounting hole. Certainly, the second limiting component **21** may also be provided on both of the neighboring side and the opposite side of the first limiting component **11**.

[0061] As shown in FIGS. 2 and 3, in the present embodiment, the base **10** is of a flat-shaped structure having a certain thickness, and is of the structure of a cuboid. Its upper surface is the surface for the placement of the fan, and the surface is the surface for forming the installation region. Because usually the fan has a high length, in the present embodiment a mounting plate that protrudes upwardly is provided at the shorter side of the base **10**, and the first limiting component **11** is located on the mounting plate. Accordingly, the fan, when has slid in the direction parallel to the surface of the base **10** into the installation region, can be fitted to the first limiting component **11**. Because the base **10** according to the present embodiment is merely required to serve to support

the fan, and has very small blocking to the side face of the fan, the affection on the gas flow of the fan may be reduced, to ensure the effect of the heat dissipation by the fan.

[0062] Certainly, the base **10** may employ the structure of a hollow cube, and is opened at one of the side faces and the top face, to realize the avoiding of the flipping member **20** and the mounting of the fan.

[0063] As shown in FIGS. **6** to **9**, in the present embodiment, not only the flipping member **20** and the base **10** are rotatable, they have a relation of relative translation therebetween. Taking into consideration that, when the flipping member **20** is directly flipped to the locking state from the avoiding state, it is inconvenient for the second limiting component **21** to be limiting-fitted to the mounting hole in the fan, the flipping member **20** according to the present embodiment further has an intermediate state between the avoiding state and the locking state, wherein the intermediate state, as a transition state between the avoiding state and the locking state, serves to transit.

Particularly, when it is required to lock the fan, the flipping member **20** is flipped from the avoiding state. In the flipping, the second limiting component **21** cannot be directly protruded into the mounting hole. Therefore, the flipping member **20** cannot be directly flipped to the locking state, and the flipping member **20** is firstly flipped relative to the base **10** to the intermediate state. At this point, the second limiting component **21** is switched from a position not aligned with the mounting hole to a position aligned with the mounting hole; however, at this point, they are merely aligned, and the second limiting component **21** has not protruded into the mounting hole. Subsequently, the flipping member **20** is horizontally translated relative to the base **10**, the flipping member **20** is switched from the intermediate state to the locking state, the second limiting component **21** gradually approaches and protrudes into the mounting hole, till the flipping member **20** has translated to the locking state, and the second limiting component **21** has protruded in the mounting hole to complete the limiting. Accordingly, by using the intermediate state, a convenient butting between the mounting hole and the second limiting component **21** may be realized. Certainly, if the second limiting component **21**, in the flipping of the flipping member **20**, can directly butt with the mounting hole, then the intermediate state may not be provided.

[0064] Optionally, the flipping axis of the flipping member **20** and the trajectory line of the translation of the fan to the base **10** are not parallel to each other. In the present embodiment they are perpendicular. Accordingly, although both of them are parallel to the surface of the base **10**, the directions of them are not the same, and no matter when the fan is being placed or the flipping member **20** is being flipped, the flipping member **20** and the fan do not interference. The translation trajectory line of the switching of the flipping member **20** from the intermediate state to the locking state and the trajectory line of the translation of the fan to the base **10** are not perpendicular to each other. In the present embodiment they are parallel. Accordingly, while the flipping member **20** is being switched from the intermediate state to the locking state, the second limiting component **21** can gradually approach and protrude into the mounting hole, to realize the fitting to the mounting hole. The connecting line between the first limiting component **11** and the second limiting component **21** and the translation trajectory line of the switching of the flipping member **20** from the intermediate state to the locking state are parallel to each other. In other words, the upper surface of the base **10**, the trajectory line of the sliding of the fan to the base **10**, the connecting line between the first limiting component **11** and the second limiting component **21**, and the trajectory line of the switching of the flipping member **20** from the intermediate state to the locking state are parallel to each other, and the latter three are perpendicular to the flipping axis of the flipping member **20**. More particularly, all of the trajectory line of the sliding of the fan to the base **10**, the connecting line between the first limiting component **11** and the second limiting component **21**, and the trajectory line of the switching of the flipping member **20** from the intermediate state to the locking state are horizontal and extend along the longer sides of the base **10**, and the flipping axis of the flipping member **20** is also horizontal but extends along the shorter sides of the base **10**. Certainly, the particular configuration is not limited to the above mode according to the present

embodiment, and may be adjusted correspondingly according to demands.

[0065] As shown in FIGS. 4 and 5, in the present embodiment, the flipping member **20** comprises a first section **22** and a second section **23** that are sequentially connected, the first section **22** is rotatably and translatably connected to the base **10**, and the second limiting component **21** and/or the locking component **30** are located at the second section **23**.

[0066] Particularly, the first section **22** and the second section **23** according to the present embodiment form an L-shaped structure. Accordingly, the first section **22** is located at the longer side of the base **10**, and the second section **23** can be fitted to the shorter side of the base **10**. Because the flipping member **20** according to the present embodiment is required to rotate, in the present embodiment a protruding section that extends upwardly by a small distance is provided at the side face of the longer side of the base **10**, and the end of the first section **22** that is farther from the second section **23** is rotatably and translatably connected to the protruding section. In the present embodiment, the rotatable and translatable connection between them is realized in the mode of the fitting between a chute **221** and a pin roll. In other words, the first section **22** is provided with a chute **221**, and the chute **221** extends in the length direction of the first section **22**.

Moreover, the protruding section is provided with a penetrating connecting pin **12**, C-shaped buckle and so on, the connecting pin **12** is fixed to the protruding section, and at the same time the connecting pin **12** penetrates the chute **221**. Therefore, the first section **22** and the protruding section cannot only be translated along the chute **221**, but also can be rotated around the connecting pin **12**. Moreover, the second section **23** serves to mount the components, and both of the second limiting component **21** and the locking component **30** are provided at the second section **23**.

[0067] Because the protruding section is located on the side of the longer side of the base **10**, the connecting pin **12** is naturally also located on the side of the longer side of the base **10**.

Accordingly, the connecting pin **12** and the first limiting component **11** are located on the neighboring sides of the base **10**; in other words, the first limiting component **11** and the second limiting component **21** are located on the sides of the two shorter sides of the base **10**, and the connecting pin **12** and the chute **221** are located on the side of the longer side of the base **10**.

Accordingly, when the flipping member **20** is in the avoiding state, the first section **22** is perpendicular to the upper surface of the base **10**, and the second section **23** is located above the base **10** at a large distance, whereby the flipping member **20** can avoid the path of the sliding of the fan to the base **10**. Moreover, when the flipping member **20** is in the locking state, the first section **22** is flipped to be parallel to the longer side, and the second section **23** is located at the shorter side, which can realize the locking of the fan.

[0068] In order to ensure the stability of the flipping of the flipping member **20**, a plurality of first sections **22** may be provided according to demands. In the present embodiment two first sections **22** are provided, and the two first sections are located at the two ends of the second section **23**.

Accordingly, the flipping member **20** forms an overall structure of a shape of a rectangle without one side. The two ends of the structure of a shape of a rectangle without one side are connected to the two shorter sides of the base **10**, and the middle space of the structure of a shape of a rectangle without one side forms the installation region with the base **10**.

[0069] As shown in FIGS. 1 and 2, in the present embodiment, because the flipping member **20** has the two movement modes of rotation and vertical translation in the avoiding state, the base **10** according to the present embodiment is further provided with a limiting directing component **13**, and the limiting directing component **13** forms a directing channel **131**. When the flipping member **20** is in the avoiding state, the first section **22** is located inside the directing channel **131**.

Accordingly, the flipping member **20** is merely capable of translating along the direction of extension of the directing channel **131**; in other words, it can merely be vertically translated but cannot be rotated. Merely when the first section **22** has exited from the directing channel **131**, the flipping member **20** is capable of being flipped to switch the states. Accordingly, by the cooperation by the limiting directing component **13** with the movement of the flipping member **20**

in the avoiding state, the flipping member **20** can automatically maintain in the avoiding state. In other words, when having no action, the flipping member **20** hangs by the effect of the gravity of itself, and the connecting pin **12** is located at the topmost end of the chute **221**. At this point, part of the first section **22** is definitely located inside the directing channel **131**, and the limiting by the limiting directing component **13** causes that the flipping member **20** cannot be rotated, thereby maintaining in the avoiding state, which may facilitate the personnel to place the fan in place. Moreover, when it is required to flip, the operator manually lifts the flipping member **20**, to cause the flipping member **20** to translate upwardly, till the first section **22** has completely exited from the directing channel **131**. At this point, the limiting directing component **13** no longer serves to limit the rotation of the flipping member **20**, and the flipping member **20** can be flipped and switched to the intermediate state and the locking state.

[0070] The limiting directing component **13** according to the present embodiment is provided under the connecting pin **12**, and is in the form of bumps. In other words, two bumps are provided at the middle part of the side face of the longer side of the base **10**, and the two bumps are arranged separately in the direction of the longer side. Accordingly, the two bumps form the directing channel **131** therebetween, and the size of the directing channel **131** is substantially equal to the width of the first section **22**, whereby the directing channel **131** can be for the first section **22** to protrude into and serve to limit the first section **22**. Moreover, because two first sections **22** are provided, in the present embodiment the sides of both of the two longer sides of the base **10** are provided with the limiting directing component **13**. Certainly, the particular structural form of the limiting directing component is not limited to the above-described mode according to the present embodiment, and may also employ other modes. For example, a vertically extending guide rail is provided on the side of the longer side, and the first section **22** is provided inside the guide rail so as to replace the function of the directing channel **131**.

[0071] In the present embodiment, the base **10** further has a flipping limiting component **14**, and the flipping limiting component **14** is located in the rotation path of the flipping of the flipping member **20**. When the flipping member **20** has been flipped and switched to the locking state, the flipping member **20** and the flipping limiting component **14** stop each other. The flipping limiting component **14** mainly serves to control the flipping angle of the flipping member **20**, thereby preventing the flipping member **20** from flipping excessively, and can have the effect of assisting locking the flipping member **20** after the fan has been locked. In other words, while the locking component **30** is locking the flipping member **20**, the flipping limiting component **14** also serves to limit the flipping of the flipping member **20**, thereby ensuring the reliability of the locking.

[0072] The flipping limiting component **14** according to the present embodiment employs a protruding boss, and the boss is located on the side of the longer side of the base **10** and outwardly protrudes. When the flipping member **20** has been flipped to the intermediate state, one end of the flipping member **20** can abut the boss, thereby preventing the flipping member **20** from continuously rotating, to realize the functions of limiting and positioning. Furthermore, the flipping limiting component **14** according to the present embodiment is plural, and on each of the two opposite sides in the circumferential direction of the rotation axis of the flipping member **20** is provided one flipping limiting component **14**. In other words, on the side of one longer side at least two bosses are provided, and the present embodiment takes two as an example. The two bosses are located on the two sides of the connecting pin **12**, and the heights are substantially equal, to form the form of boss-connecting pin **12**-boss. Accordingly, when the flipping member **20** is in the locking state, because the flipping member **20** is required to be translated by a certain distance from the intermediate state to the locking state, the first section **22** of the flipping member **20** is simultaneously supported by the two bosses on the side of the longer side, as shown in FIG. 9. Accordingly, by using the relation between the two bosses and the first section **22**, the limiting of the flipping is realized to a certain extent. Likewise, because two first sections **22** are provided, the sides of both of the two longer sides are provided with two bosses, thereby serving to limit both of

the two first sections **22**.

[0073] In the present embodiment, the locking component **30** comprises a lockout slot **31** and a lockout member **32**. The lockout slot **31** is located on the side of the shorter side opposite to the first limiting component **11** of the base **10**. The lockout member **32** is movably connected to the second section **23** of the flipping member **20**. When the flipping member **20** is in the locking state, the lockout member **32** butts the lockout slot **31**, and the lockout member **32** is located inside the lockout slot **31** and locks the relative position between the flipping member **20** and the base **10**, to realize a quick lockout.

[0074] The lockout member **32** and the lockout slot **31** according to the present embodiment are of a shape-matching non-circular structure. When the flipping member **20** is in the locking state, the shapes of the lockout member **32** and the lockout slot **31** are aligned, the lockout member **32** is protruded into the lockout slot **31**, and the lockout member **32** is rotated to be limiting-fitted to the lockout slot **31**. Particularly, the lockout slot **31** in the lockout face is configured to be a rectangular hole. The lockout member **32** on the second section **23** of the flipping member **20** is provided with a rotation shaft and a blocking member nested to the rotation shaft, and the blocking member and the rotation shaft are synchronously rotated. The blocking member has a longer wing having a length greater than the width of the rectangular hole of the lockout slot **31** and a shorter wing having a width less than the width of the rectangular hole, and, with the above precondition, the length of the longer wing of the blocking member is less than the length of the rectangular hole. When the rotation shaft has been rotated by a suitable angle to cause the direction of the longer wing of the blocking member and the length direction of the rectangular hole to be aligned, while the flipping member **20** is being horizontally moved to be switched from the intermediate state to the locking state, the blocking member enters the lockout slot **31**. The rotation shaft is subsequently rotated by a suitable angle, so that the direction of the longer wing of the blocking member is perpendicular to the length direction of the rectangular hole. On that basis, the flipping member **20** cannot complete the horizontal movement relative to the base **10**; in other words, the flipping member **20** is locked in the locking state.

[0075] In the present embodiment, the locking component **30** of the fan installing mechanism further comprises a rotary knob **33**. The rotary knob **33**, via the rotation shaft of the lockout member **32**, is synchronously rotatably connected to the blocking member of the lockout member **32**, and the lockout member **32** and the rotary knob **33** are located at the inner face and the outer face of the side wall of the flipping member **20** respectively. Particularly, the rotary knob **33** is connected to the blocking member by the rotation shaft, and, by rotation of the rotary knob **33**, the pose of the blocking member is adjusted, to finally reach the purpose of locking and unlocking the fan installing mechanism.

[0076] As shown in FIG. **3**, in the present embodiment, a connecting hole **15** is provided at the bottom of the base **10**, and the base **10** is connected to an external installation frame by the connecting hole **15**. Moreover, as shown in FIGS. **2** and **5**, the quantities of the first limiting component **11** and/or the second limiting component **21** may also be configured correspondingly according to demands, and may be one or more. When they are plural, the first limiting components **11** or the second limiting components **21** are arranged separately along the surface where the first limiting components **11** or the second limiting components **21** are located. In the present embodiment, two first limiting components **11** and two second limiting components **21** are provided, and the first limiting components **11** and the second limiting components **21** correspond one to one, and correspond to the mounting holes in the fan.

[0077] In the present embodiment, in the sequence of FIGS. **6** to **9**, the process of installing the fan to the fan installing mechanism is as follows. In the installation of the fan, firstly it is required to ensure that the flipping member **20** is in the avoiding state. In the avoiding state, the length direction of the first sections **22** of the flipping member **20** is perpendicular to the upper surface of the base **10**, and the first sections **22** of the flipping member **20** are located inside the limiting

directing components **13** on the sides of the two longer sides. When it is ensured that the flipping member **20** is in the avoiding state, the pose of the fan is adjusted, whereby the direction of extension of the mounting holes of the fan is parallel to the direction of extension of the protruding-column structures of the first limiting components **11**, and one of the rectangular side faces of the fan is parallel to the upper surface of the base **10**. After the pose of the fan has been adjusted, the position of the fan is adjusted, whereby two openings of the fan that are closer to the upper surface are aligned with the protruding-column structures of the first limiting components **11** on the base **10**. Subsequently, the fan is horizontally moved, whereby the protruding-column structures of the first limiting components **11** are inserted into the mounting holes of the fan, and the end face of the fan where the mounting holes are located and the fixing face where the first limiting components **11** are located completely abut. In the above-described process, the end face of the fan that abuts the fixing face passes through between the flipping member **20** and the base **10**, and the fan is finally located within the installation region between the flipping member **20** and the base **10**. After the fan has been in place, the flipping member **20** is lifted, whereby the first sections **22** of the flipping member **20** move along the directing channels **131**, till they have exited from the directing channels **131**. Subsequently, the flipping member **20** is downwardly rotated, and, by the effect of the flipping limiting components **14**, the flipping member **20** is finally rotated by 90 degrees as compared with the original avoiding state and reaches the intermediate state. When the flipping member **20** is in the intermediate state, its first sections **22** are parallel to the upper surface of the base **10**, and the protruding-column structures of the second limiting components **21** on the second section **23** are aligned with two mounting holes of the end face of the fan. After the intermediate state has been reached, firstly the pose of the blocking member of the lockout member **32** is determined, and, by rotating the rotary knob **33** to drive the blocking member to rotate via the rotation shaft, the pose of the blocking member is adjusted, whereby the direction of extension of the longer wing of the blocking member is parallel to the length direction of the lockout slot **31**. After the pose of the blocking member has been adjusted, the flipping member **20** is pushed to horizontally move to approach the base **10**, the blocking member on the second section **23** of the flipping member **20** enters the space behind the lockout slot **31**, and finally the second section **23** of the flipping member **20** abuts the side of the shorter side of the base **10**. Subsequently, the rotary knob **33** is rotated, to drive the blocking member to rotate to adjust the pose of itself, whereby the direction of extension of the longer wing of the blocking member is parallel to the width direction of the lockout slot **31**. After such a pose adjustment, the blocking member cannot exit from the lockout slot **31**, the flipping member **20** is fixed to the base **10**, and the locking of the fan by the locking component **30** is finally completed. In the above-described movement of the flipping member **20** approaching the base **10**, the protruding-column structures of the second limiting components **21** on the flipping member **20** are aligned with and inserted into the mounting holes in the corresponding end face of the fan.

[0078] In the present embodiment, the process of detaching the fan from the fan installing mechanism is as follows. Firstly, the rotary knob **33** is rotated to drive the blocking member of the lockout member **32** to rotate to adjust the pose of itself, whereby the direction of extension of the longer wing of the blocking member is parallel to the length direction of the rectangular hole. After the pose of the blocking member has been adjusted, the flipping member **20** is pulled to horizontally move in the direction away from the base **10**. In the process of the flipping member **20** horizontally leaving the base **10**, the blocking member exits from the lockout slot **31**, the protruding-column structures of the second limiting components **21** on the flipping member **20** exit from the corresponding mounting holes in the fan, and finally the flipping member **20** is switched from the original locking state to the intermediate state. After the flipping member **20** has completed the switching from the locking state to the intermediate state, the flipping member **20** is upwardly rotated by 90°, whereby the length direction of the first sections **22** of the flipping member **20** is the vertical direction, to finally cause the flipping member **20** to be switched from the

intermediate state to the avoiding state. When the flipping member **20** is in the avoiding state, the fan may horizontally move relative to the base **10**. During such movement, the protruding-column structures of the first limiting components **11** exit from the corresponding mounting holes of the fan, the fan is finally disengaged from the fan installing mechanism, and the detachment is completed.

The Second Embodiment

[0079] The difference from the first embodiment is that the mode of the fitting between the first section **22** and the base **10** is different.

[0080] In the present embodiment, the first section **22** and the protruding section still employ the mode of the fitting between a chute **221** and a pin roll. However, in the present embodiment, the chute **221** is provided on the base **10**, and the connecting pin **12** is provided on the first section **22** of the flipping member **20**. The connecting pin **12** is still provided inside the chute **221** and can be rotated and translated relative to the chute **221**. Taking into consideration that, in this case, the I-shaped chute **221** cannot realize the rotation, the chute **221** according to the present embodiment may, according to demands, be a cross-shaped or X-shaped slot and so on. Taking a cross-shaped chute **221** as an example, the cross-shaped chute **221** may be considered as two chutes **221** that are perpendicular and intersect, wherein one of the two chutes **221** is horizontal, and the other is vertical. Accordingly, when the flipping member **20** is moving in the vertical direction and the horizontal direction, essentially the connecting pin **12** is translating in the two chutes **221** that are perpendicular and intersect.

[0081] Certainly, the particular structure of the fitting between the flipping member **20** and the base **10** is not limited to the modes according to the above embodiments of the present application, and other structural forms may also be employed according to demands, provided that the translation and the relative rotation can be realized.

The Third Embodiment

[0082] The difference from the first embodiment is that the flipping member **20**, the limiting directing component **13** and the flipping directing component are different.

[0083] In the present embodiment, merely one first section **22** of the flipping member **20** is provided, whereby the flipping member **20** forms an overall structure of an L shape. In this case, the flipping member **20** can still realize the relevant function in the first embodiment. Moreover, because merely a single side of the base **10** is provided with the first section **22**, the limiting directing component **13** and the flipping directing component also may be provided on the single side; in other words, merely the side of the longer side of the base **10** that is provided with the first section **22** is provided with the limiting directing component **13** and the flipping directing component. That may also realize the limitation on the mode of the rotation and the translation of the flipping member **20**, and at the same time reduces the used components, which reduces the structural complexity, and reduces the cost on manufacturing and repairing.

[0084] It should be noted that the plurality in the above embodiments refers to “at least two”.

[0085] It can be seen from the above description that the above embodiments of the present application realize the following technical effects:

[0086] The structure is simple, has a low cost of manufacturing and installation, and is convenient to repair.

[0087] The mechanism has a good versatility and a wide application scope, and the components are conveniently produced and replaced.

[0088] No large-scale metal framework is used, which saves the cost.

[0089] The fan installing mechanism realizes an open installation mode of the fan, and does not block the fan, which improves the performance of the heat dissipation of the server.

[0090] Apparently, the above-described embodiments are merely certain embodiments of the present application, rather than all of the embodiments. All of the other embodiments that a person skilled in the art obtains on the basis of the embodiments of the present application without paying

creative work should fall within the protection scope of the present application.

[0091] It should be noted that the terms used herein are merely for the description on the particular embodiments, and are not intended to limit the exemplary embodiments of the present application. As used herein, unless explicitly stated otherwise in the context, the terms in the singular forms are intended to encompass the plural forms. Furthermore, it should also be understood that, when the term “comprise” and/or “include” is used in the description, it indicates the existence of a feature, a step, a process, a device, a component and/or a combination thereof.

[0092] It should be noted that the terms “first”, “second” and so on in the description, the claims and the drawings of the present application are intended to distinguish similar objects, and are not necessarily used to describe a particular order or sequence. It should be understood that the data so used may be interchanged in suitable cases, whereby the embodiments of the present application described herein can be implemented in other sequences than those illustrated or described herein.

[0093] The above are merely preferable embodiments of the present application, and are not intended to limit the present application. For a person skilled in the art, the present application may have various modifications and variations. Any modifications, equivalent substitutions and improvements that are made within the spirit and the principle of the present application should fall within the protection scope of the present application.

Claims

1. A fan installing mechanism, wherein the fan installing mechanism comprises: a base, wherein the base has a first limiting component for limiting movement of a fan; a flipping member, wherein the flipping member is rotatably connected to the base, and the flipping member has a second limiting component for limiting the movement of the fan, and has an avoiding state and a locking state; when the flipping member is in the avoiding state, the flipping member avoids a movement path of installation of the fan to the base, and the fan is capable of being limiting-fitted to the first limiting component; and when the flipping member is in the locking state, the flipping member is flipped relative to the base and the second limiting component is limiting-fitted to the fan, to hinder the fan from disengaging from the base; and a locking component, wherein the locking component is provided between the base and the flipping member, and when the flipping member is in the locking state, the locking component locks a position of the flipping member to the locking state; wherein the flipping member comprises a first section and a second section that are sequentially connected, the first section is rotatably and translatably connected to the base, and the second limiting component and/or the locking component are located at the second section; wherein the base has a limiting directing component, and the limiting directing component forms a directing channel; when the flipping member is in the avoiding state, the first section is located inside the directing channel, and the flipping member is merely capable of translating along a direction of extension of the directing channel; and when the first section has exited from the directing channel, the flipping member is capable of being flipped to switch the states.

2. The fan installing mechanism according to claim 1, wherein when the flipping member is in the locking state, the first limiting component and the second limiting component are located on two opposite sides and/or neighboring sides of the fan.

3. The fan installing mechanism according to claim 1, wherein the flipping member and the base are rotatable and translatable relative to each other, and the flipping member further has an intermediate state between the avoiding state and the locking state; while the flipping member is being switched from the avoiding state to the intermediate state, the flipping member is flipped relative to the base; and while the flipping member is being switched from the intermediate state to the locking state, the flipping member is translated relative to the base.

4. The fan installing mechanism according to claim 3, wherein a flipping axis of the flipping member and a trajectory line of the translation of the fan to the base are not parallel to each other,

and a translation trajectory line of the switching of the flipping member from the intermediate state to the locking state and the trajectory line of the translation of the fan to the base are not perpendicular to each other.

5. The fan installing mechanism according to claim 4, wherein the flipping axis of the flipping member and the trajectory line of the translation of the fan to the base are perpendicular to each other, and the translation trajectory line of the switching of the flipping member from the intermediate state to the locking state and the trajectory line of the translation of the fan to the base are parallel to each other.

6. The fan installing mechanism according to claim 3, wherein a connecting line between the first limiting component and the second limiting component and a translation trajectory line of the switching of the flipping member from the intermediate state to the locking state are parallel to each other.

7. The fan installing mechanism according to claim 1, wherein each of the first limiting component and the second limiting component is of a protruding-column structure, and axes of the protruding-column structures are parallel to a surface of the base.

8. (canceled)

9. The fan installing mechanism according to claim 8, wherein one of the first section and the base is provided with a chute, the other of the first section and the base is provided with a connecting pin, the connecting pin is located inside the chute, and the connecting pin and the chute are translatable relative to each other and rotatable relative to each other.

10. The fan installing mechanism according to claim 9, wherein the connecting pin and the first limiting component are located on neighboring sides of the base.

11. The fan installing mechanism according to claim 8, wherein the first section is a plurality of first sections, and each of two ends of the second section is connected to one instance of the first sections, whereby the flipping member is of a structure of a shape of a rectangle without one side.

12. (canceled)

13. The fan installing mechanism according to claim 1, wherein the base has a flipping limiting component, and the flipping limiting component is located in a rotation path of the flipping of the flipping member; and when the flipping member has been flipped and switched to the locking state, the flipping member and the flipping limiting component stop each other, to control a flipping angle of the flipping member.

14. The fan installing mechanism according to claim 13, wherein the flipping limiting component is a plurality of flipping limiting components, and on each of two opposite sides in a circumferential direction of a rotation axis of the flipping member is provided one instance of the flipping limiting components; and when the flipping member is in the locking state, the flipping member is stopping-fitted to both of the flipping limiting components on the two sides.

15. The fan installing mechanism according to claim 1, wherein the second limiting component and the locking component are located on a same one side of the base.

16. The fan installing mechanism according to claim 1, wherein the locking component comprises: a lockout slot, wherein the lockout slot is located on the base; and a lockout member, wherein the lockout member is movably connected to the flipping member; and when the flipping member is in the locking state, the lockout member butts the lockout slot, and the lockout member is located inside the lockout slot and locks a relative position between the flipping member and the base.

17. The fan installing mechanism according to claim 16, wherein the lockout member and the lockout slot are of a shape-matching non-circular structure; and when the flipping member is in the locking state, shapes of the lockout member and the lockout slot are aligned, the lockout member is protruded into the lockout slot, and the lockout member is rotated to be limiting-fitted to the lockout slot.

18. The fan installing mechanism according to claim 16, wherein the locking component further comprises a rotary knob, the rotary knob and the lockout member are connected and synchronously

rotated, and the lockout member and the rotary knob are located at an inner face and an outer face of a side wall of the flipping member respectively.

19. (canceled)

20. (canceled)

21. The fan installing mechanism according to claim 1, wherein the flipping member is of a structure of a shape of a rectangle without one side, two ends of the structure of a shape of a rectangle without one side are rotatably and translatably connected to two sides of the base; when the flipping member is in the avoiding state, a plane where the structure of a shape of a rectangle without one side is located is perpendicular to an installation surface of the base; and when the flipping member is in the locking state, the plane where the structure of a shape of a rectangle without one side is located is parallel to the installation surface of the base; the base has a limiting directing component, and the limiting directing component forms a directing channel; when the flipping member is in the avoiding state, part of the flipping member is located inside the directing channel, and the flipping member is merely capable of translating along a direction of extension of the directing channel; and when the flipping member has exited from the directing channel, the flipping member is capable of being flipped to switch the states; the flipping member further has an intermediate state between the avoiding state and the locking state; while the flipping member is being switched from the avoiding state to the intermediate state, the flipping member is flipped relative to the base; and while the flipping member is being switched from the intermediate state to the locking state, the flipping member is translated relative to the base; and the base has a flipping limiting component, and the flipping limiting component is located in a rotation path of the flipping of the flipping member; and when the flipping member has been flipped and switched to the intermediate state and the locking state, the flipping member and the flipping limiting component stop each other, to control a flipping angle of the flipping member.

22. A server, wherein the server comprises a fan and the fan installing mechanism according to claim 1, and the fan is installed to the fan installing mechanism.
