

# US Patent & Trademark Office

## Patent Public Search | Text View

United States Patent	12387080
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Nyalamadugu; Sheshi et al.

### Radio frequency identification enabled mirrors

#### Abstract

A radio frequency identification (RFID) enabled mirror includes a mirror comprising a reflective layer. The reflective layer comprises at least one layer of a metallic material. At least one portion of the reflective layer is removed to form a booster antenna from a remaining portion of the reflective layer. A dielectric coating is applied to the mirror where the reflective layer was removed. The RFID-enabled mirror further includes an RFID chip coupled to the booster antenna.

Inventors:	Nyalamadugu; Sheshi (San Diego, CA), Mullis; Joe (Escondido, CA)
Applicant:	NEOLOGY, INC. (Carlsbad, CA)
Family ID:	55853017
Assignee:	Neology, Inc. (Carlsbad, CA)
Appl. No.:	18/738514
Filed:	June 10, 2024

#### Prior Publication Data

Document Identifier	Publication Date
US 20240330641 A1	Oct. 03, 2024

#### Related U.S. Application Data

continuation parent-doc US 18231001 20230807 US 12008427 child-doc US 18738514  
continuation parent-doc US 17850729 20220627 US 11720780 20230719 child-doc US 18231001  
continuation parent-doc US 17235128 20210420 US 11373082 20220628 child-doc US 17850729  
continuation parent-doc US 17188876 20210301 US 11301745 20220412 child-doc US 17235128  
continuation parent-doc US 16852889 20200420 US 10963771 20210330 child-doc US 17188876  
continuation parent-doc US 16545945 20190820 US 10628728 20200421 child-doc US 16852889  
continuation parent-doc US 15979232 20180514 US 10402717 20190903 child-doc US 16545945  
continuation parent-doc US 15633400 20170626 US 9996791 20180612 child-doc US 15979232

## Publication Classification

**Int. Cl.:** **G06K19/077** (20060101); **B60R1/12** (20060101); **G02B5/08** (20060101); **H01Q1/22** (20060101); **H01Q1/32** (20060101); **H01Q1/38** (20060101); **H01Q5/378** (20150101); **H01Q7/00** (20060101); **H01Q13/10** (20060101); **H01Q15/14** (20060101)

**U.S. Cl.:**

**CPC** **G06K19/07794** (20130101); **B60R1/12** (20130101); **G02B5/0875** (20130101); **H01Q1/2225** (20130101); **H01Q1/3266** (20130101); **H01Q1/38** (20130101); **H01Q5/378** (20150115); **H01Q7/00** (20130101); **H01Q13/106** (20130101); **H01Q15/14** (20130101); **B60R2001/1261** (20130101); **B60R2001/1276** (20130101); **G02B5/085** (20130101)

## Field of Classification Search

**CPC:** G06K (19/07794); H01Q (5/378)

**USPC:** 235/492

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4989964	12/1990	Meise	N/A	N/A
8844831	12/2013	Mullis et al.	N/A	N/A
9688202	12/2016	Nyalamadugu et al.	N/A	N/A
2002/0126054	12/2001	Fuerst et al.	N/A	N/A
2004/0164865	12/2003	de Velasco Cortina	N/A	N/A
2006/0028344	12/2005	Forster	N/A	N/A
2007/0285256	12/2006	Batra	N/A	N/A
2009/0079568	12/2008	Forster et al.	N/A	N/A
2010/0090833	12/2009	Mullis et al.	N/A	N/A
2011/0169701	12/2010	Bergsmann et al.	N/A	N/A
2012/0056791	12/2011	Cisneros Gonzalez et al.	N/A	N/A
2012/0162430	12/2011	Heslin et al.	N/A	N/A
2012/0267434	12/2011	Kohla et al.	N/A	N/A
2013/0222156	12/2012	Colburn	N/A	N/A
2014/0191043	12/2013	Forster	N/A	N/A
2015/0002262	12/2014	Geerlings et al.	N/A	N/A

### FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2008/079902	12/2007	WO	N/A

### OTHER PUBLICATIONS

International Search Report and Written Opinion received in PCT/US2015/058163 mailed Jan. 29, 2016, 9 pages. cited by applicant

Extended European Search Report received in EP 15855994.8 dated Jun. 13, 2018 (7 pages). cited by applicant

Extended European Search Report received in EP 19208887.0 dated Apr. 3, 2020 (13 pages). cited by applicant

Serra CC et al: "Mirror-Integrated Transparent Antenna for RFID Application", IEEE Antennas and Wireless Propagation Letters, vol. 10, Jan. 1, 2011 (Jan. 1, 2011 ), pp. 776-779, (4 pages). cited by applicant

Examination Report dated Feb. 3, 2021 for related EP Patent Application No. 19208887.0 in 11 pages. cited by applicant

---

*Primary Examiner:* Trail; Allyson N

*Attorney, Agent or Firm:* Procopio, Cory, Hargreaves & Savitch, LLP

---

## **Background/Summary**

RELATED APPLICATIONS (1) This patent application is a continuation of U.S. patent application Ser. No. 18/231,001, filed Aug. 7, 2023, entitled, "RADIO FREQUENCY IDENTIFICATION ENABLED MIRROR", which is a continuation of U.S. patent application Ser. No. 17/850,729 entitled "RADIO FREQUENCY IDENTIFICATION ENABLED MIRRORS" filed on Jun. 27, 2022, now issued as U.S. Pat. No. 11,720,780, with an issue date of Jul. 19, 2023, which is a continuation of U.S. patent application Ser. No. 17/235,128 entitled "RADIO FREQUENCY IDENTIFICATION ENABLED MIRRORS" and filed on Apr. 20, 2021, now issued as U.S. Pat. No. 11,373,082 with an issue date of Jun. 28, 2022, which is a continuation of U.S. patent application Ser. No. 17/188,876 entitled "RADIO FREQUENCY IDENTIFICATION ENABLED MIRRORS" and filed on Mar. 1, 2021, now issued as U.S. Pat. No. 11,301,745 with an issue date of Apr. 12, 2022, which is a continuation of U.S. patent application Ser. No. 16/852,889 entitled "RADIO FREQUENCY IDENTIFICATION ENABLED MIRRORS" and filed on Apr. 20, 2020, now issued as U.S. Pat. No. 10,963,771 with an issue date of Mar. 30, 2021, which is a continuation of U.S. patent application Ser. No. 16/545,945 entitled "RADIO FREQUENCY IDENTIFICATION ENABLED MIRRORS" and filed on Aug. 20, 2019, now issued as U.S. Pat. No. 10,628,728 with an issue date of Apr. 21, 2020, which is a continuation of U.S. patent application Ser. No. 15/979,232 entitled "RADIO FREQUENCY IDENTIFICATION ENABLED MIRRORS" and filed on May 14, 2018, now issued as U.S. Pat. No. 10,402,717 with an issue date of Sep. 3, 2019, which is a continuation of U.S. patent application Ser. No. 15/633,400 entitled "RADIO FREQUENCY IDENTIFICATION ENABLED MIRRORS" and filed on Jun. 26, 2017, now issued as U.S. Pat. No. 9,996,791 with an issue date of Jun. 12, 2018, which is a continuation of U.S. patent application Ser. No. 14/927,426 entitled "RADIO FREQUENCY IDENTIFICATION ENABLED MIRRORS" and filed on Oct. 29, 2015, now issued as U.S. Pat. No. 9,688,202 with an issue date of Jun. 27, 2017, which claims the benefit under 35 U.S.C. § 119 (c) to U.S. Provisional Patent Application No. 62/072,416, entitled "RADIO FREQUENCY IDENTIFICATION ENABLED MIRRORS" filed on Oct. 29, 2014, the disclosures of which are incorporated herein by reference in their entirety as a part of this document.

## **BACKGROUND**

### **1. Technical Field**

(1) The various embodiments described herein are related to wireless devices, and more particularly to radio frequency identification (RFID) enabled mirrors.

## 2. Related Art

(2) Radio frequency identification (RFID) technology plays a significant role in the regulation of motor vehicles and the provision of related services. For example, modern electronic toll systems (ETTs) and parking garages both rely heavily on RFID transponders. Thus, vehicles nowadays commonly carry an RFID transponder. The RFID transponder can communicate with RFID readers to provide data (e.g., one or more identifiers) that allows the ETT or parking authority to identify and/or debit an appropriate account.

(3) The placement of conventional RFID transponders tends to be obtrusive. For example, a conventional RFID transponder may be mounted on the vehicle's windshield or dashboard. As such, the RFID transponder can obstruct the driver's line-of-sight and interfere with the aesthetic of the vehicle. Therefore, what is needed is an RFID transponder that can be integrated as a component of the vehicle.

## SUMMARY

(4) Radio frequency identification enabled mirrors are provided.

(5) According to various embodiments, there is provided an RFID-enabled mirror. The RFID-enabled mirror includes a mirror comprising a reflective layer, wherein: the reflective layer comprises at least one layer of a metallic material; at least one portion of the reflective layer is removed to form a booster antenna from a remaining portion of the reflective layer; and a dielectric coating is applied to the mirror where the reflective layer was removed. The RFID-enabled mirror further includes an RFID chip coupled to the booster antenna.

(6) According to various embodiments, there is provided an RFID-enabled mirror. The RFID-enabled mirror includes a mirror comprising a reflective layer, wherein: the reflective layer comprises a dielectric coating; at least one portion of the reflective layer is removed; and a metallic material is applied to the mirror where the reflective layer was removed to form a booster antenna. The RFID-enabled mirror further includes an RFID chip coupled to the booster antenna.

(7) Other features and advantages of the present inventive concept should be apparent from the following description which illustrates by way of example aspects of the present inventive concept.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) The above and other aspects and features of the present inventive concept will be more apparent by describing example embodiments with reference to the accompanying drawings, in which:

(2) FIG. 1A illustrates a mirror according to various embodiments;

(3) FIG. 1B illustrates a lateral cross-sectional view of a mirror according to various embodiments;

(4) FIG. 2A illustrates an RFID-enabled mirror according to various embodiments;

(5) FIG. 2B illustrates a lateral cross-sectional view of the RFID-enabled mirror according to various embodiments;

(6) FIG. 3 illustrates an RFID-enabled mirror according to various embodiments;

(7) FIG. 4 illustrates a multi-frequency RFID-enabled mirror according to various embodiments; and

(8) FIG. 5 illustrates a self-declaring system according to various embodiments.

### DETAILED DESCRIPTION

(9) While certain embodiments are described, these embodiments are presented by way of example only, and are not intended to limit the scope of protection. The methods and systems described herein may be embodied in a variety of other forms. Furthermore, various omissions, substitutions, and changes in the form of the example methods and systems described herein may be made

without departing from the scope of protection.

(10) FIG. 1A illustrates a mirror **100** according to various embodiments. FIG. 1B illustrates a lateral cross-sectional view of the mirror **100** according to various embodiments. Referring to FIGS. 1A-B, the mirror **100** includes a substrate layer **110**. In various embodiments, the substrate **100** can be any suitable transparent or substantially transparent material including, for example, but not limited to, glass, acrylic (i.e., polymethyl methacrylate (PMMA)), and polycarbonate (PC).

(11) The mirror **100** further includes a reflective layer **120** that is deposited on top of the substrate layer **110**. In some embodiments, the reflective layer **120** can include at least one layer of a suitable metal or metal alloy including, for example, but not limited to, aluminum (Al), silver (Ag), and speculum metal (i.e., copper (Cu) and tin (Sn) alloy).

(12) In some embodiments, the reflective layer **120** can include multiple layers of the same or different metals. For example, in some embodiments, the reflective layer **120** can include a layer of one metal (e.g., silver (Ag) or aluminum (Al)) deposited on top of the substrate layer **110** followed by a layer of a different metal (e.g., copper (Cu)).

(13) Alternately or in addition, in some embodiments, the reflective layer **120** can include a dielectric coating. The dielectric coating can include stacked layers of transparent dielectric material adapted to modify the reflective properties of the substrate layer **110**.

(14) The mirror **100** further includes a protective layer **130** that is deposited on top of the reflective layer **120**. For example, in some embodiments, the protective layer **130** can include a backing (e.g., paint) that is adapted to prevent exposure of the reflective layer **120** to corrosive substances (e.g., moisture, chemicals).

(15) A person having ordinary skill in the art can appreciate that the mirror **100** can include additional and/or different components without departing from the scope of the present disclosure.

(16) FIG. 2A illustrates an RFID-enabled mirror **200** according to various embodiments. Referring to FIGS. 1A-B and 2A, the RFID-enabled mirror **200** includes the mirror **100**. As shown in FIG. 2, in some embodiments, the RFID-enabled mirror **200** can be implemented as a rearview mirror. A person having ordinary skill in the art can appreciate that the RFID-enabled mirror **300** can be implemented as any suitable vehicle component (e.g., side view mirror) without departing from the scope of the present disclosure.

(17) In various embodiments, a portion of the reflective layer **120** of the mirror **100** is selectively removed in order to form a booster antenna **210**. For example, in some embodiments, the reflective layer **120** can include at least one metal or metal alloy layer (e.g., aluminum (Al), silver (Ag), and speculum metal). As such, the reflective layer **120** can be subject to a selective demetallization procedure adapted to remove a portion of the metal or metal alloy layer. A portion of the metal or metal alloy layer that remains after the selective demetallization procedure corresponds to a silhouette of the booster antenna **210**.

(18) One embodiment of a selective demetallization procedure is described in detail in co-owned U.S. Pat. No. 7,034,688 as well as U.S. Pat. No. 7,463,154, the disclosures of which are incorporated herein by reference in their entirety. For example, a demetallizing solution (e.g., sodium hydroxide (NaOH)) can be applied to the reflective layer **120** in order to remove a portion of the metal or metal alloy layer while preserving a portion of the metal or metal alloy layer that corresponds to the booster antenna **210**.

(19) Selectively demetallizing the reflective layer **120** to remove a portion of the metal or metal alloy layer can impair the reflective properties of the mirror **100**. Thus, in various embodiments, a dielectric coating can be applied to substrate layer **110** of the mirror **100** to replace the removed portion of the metal or metal alloy layer in the reflective layer **120**. As such, the mirror **100** can further include a dielectric section **220** providing the same or substantially the same reflective properties as the metal or metal alloy layer that has been removed.

(20) Alternately, in some embodiments, the reflective layer **120** includes a dielectric coating that can be subject to a selective metallization procedure. For example, a portion of the reflective layer

**120** that corresponds to a silhouette of the booster antenna **120** can be removed and a suitable metal or metal alloy (e.g., aluminum (Al), silver (Ag), and speculum metal) can be deposited to form the booster antenna **210**. As such, the mirror **100** includes the metal or metal alloy booster antenna **210** and the dielectric section **220** that both provide the same or substantially the same reflective properties.

(21) The booster antenna **210** is coupled to the RFID chip **230**. For example, as shown in FIG. 2, the booster antenna **210** can be capacitively coupled to the RFID chip **230** via a first contact **212** and a second contact **214**. However, a person having ordinary skill in the art can appreciate that the booster antenna **210** can be coupled to the RFID chip **230** in a different manner (e.g., inductively) without departing from the scope of the present disclosure.

(22) In various embodiments, the booster antenna **310** can be configured to resonate at a suitable frequency band. For example, the booster antenna **310** can be adapted to resonate at an ultra-high frequency (UHF) band (e.g., 915 megahertz (MHz)), which enables the RFID-enabled mirror **200** to communicate with UHF systems and/or devices including, for example, but not limited to, RFID toll booth readers. Alternately, the booster antenna **310** can be adapted to resonate at a high frequency (HF) band (e.g., 13.5 MHz), which enables the RFID-enabled mirror **200** to communicate with an HF systems and/or device including, for example, but not limited to, a near field communication (NFC) enabled smartphone.

(23) In some embodiments, the RFID-enabled mirror **200** can be coupled with a power source (not shown). For example, the RFID-enabled mirror **200** can include a battery or can be connected to an external power source (e.g., provided by a vehicle). As such, the RFID-enabled mirror **200** can be configured to provide one or more notifications (e.g., visual, audio). According to one exemplary embodiment, the RFID-enabled mirror **200** can be adapted to provide an audio notification (e.g., beep) and/or visual notification (e.g., light emitting diode (LED)) when a vehicle passes a toll booth and/or accesses a high occupancy toll (HOT) lane.

(24) In various embodiments, the RFID-enabled mirror **200** can further include a switch **240**. The switch **240** can be adapted to control one or more operational states of the RFID-enabled mirror **200** including, for example, but not limited to, activating and deactivating the RFID-enabled mirror **200**. For example, in some embodiments, the RFID-enabled mirror **200** can be activated via the switch **240** when a single occupancy vehicle (SOV) enters HOT lane.

(25) Additional details with respect to the switching mechanism are described in U.S. Pat. Nos. 8,844,831 and 8,944,337, and U.S. patent application Ser. Nos. 14/480,458 and 14/578,196, the disclosures of which are incorporated herein by reference in their entirety. For example, in some embodiments, the switch **240** can be adapted to control the operational states of the RFID-enabled mirror **200** by changing a position of the RFID chip **230** relative to the booster antenna **210**.

(26) In some embodiments, access to data stored by the RFID-enabled mirror **200** may be granted based on one or more security keys. Additional details with respect to security key based access control are described in U.S. Pat. No. 8,933,807, the disclosure of which is incorporated herein by reference in its entirety.

(27) Although the booster antenna **210** is shown as a loop antenna, a person having ordinary skill in the art can appreciate that the booster antenna **210** can have any suitable configuration (e.g., slot antenna) without departing from the scope of the present disclosure.

(28) FIG. 2B illustrates a lateral cross-sectional view of the RFID-enabled mirror **200** according to various embodiments. Referring to FIGS. 1A-B and 2A-B, the reflective layer **120** of the mirror **100** included in the RFID-enabled mirror **200** can be subject to selective demetallization or selective metallization to form the booster antenna **210**. A dielectric coating is applied to the substrate **110** of the mirror **100** where metal or metal alloy was removed (i.e., selective demetallization) or was not deposited (i.e., selective metallization) to form the dielectric section **220**. In various embodiments, the mirror **100** can further include the protective layer **130**, which prevents exposure of the booster antenna **210** and the dielectric section **220** to corrosive substances

(e.g., moisture, chemicals)

(29) The RFID-enabled mirror **200** further includes the RFID chip **230** coupled with the booster antenna **210**. For example, in some embodiments, the RFID chip **230** can be coupled (e.g., capacitively) with the booster antenna **210** via the first contact **212** and the second contact **214**, which penetrate through a portion of the protective layer **130**. Alternately, the RFID chip **230** can be coupled with the booster antenna **210** in a different manner (e.g., inductively) without departing from the scope of the present disclosure.

(30) FIG. 3 illustrates an RFID-enabled mirror **300** according to various embodiments. Referring to FIGS. 1A-B and 3, in some embodiments, the RFID-enabled mirror **300** may be implemented as a side view mirror. A person having ordinary skill in the art can appreciate that the RFID-enabled mirror **300** can be implemented as any suitable vehicle component (e.g., a rearview mirror) without departing from the scope of the present disclosure.

(31) In various embodiments, the RFID-enabled mirror **300** includes the mirror **100**. According to one exemplary embodiment, a booster antenna **310** is formed by subjecting the reflective layer **120** of the mirror **100** to a selective demetallization or a selective metallization procedure.

(32) For example, in one embodiment, the booster antenna **310** is formed from a portion of a metal or metal alloy layer of the reflective layer **120** that remains after the reflective layer **120** is subject to a selective demetallization procedure. A dielectric coating is deposited to replace the removed metal or metal alloy layer. A resulting dielectric section **320** provides the same or substantially the same reflective properties as the metal or metal alloy layer that has been removed.

(33) Alternately, in some embodiments, the booster antenna **310** is formed by removing a portion of a dielectric coating corresponding to a silhouette of the booster antenna **310** while preserving the dielectric section **330**. Metal or metal alloy is deposited where the dielectric coating has been removed to form the booster antenna **310**.

(34) In various embodiments, the booster antenna **310** can be configured to resonate at a suitable frequency band (e.g., HF or UHF). The booster antenna **310** can be coupled (e.g., capacitively) to an RFID chip **330** via a first contact **312** and a second contact **314**. However, the booster antenna **310** can be coupled to the RFID chip **330** in a different manner (e.g., inductively) without departing from the scope of the present disclosure.

(35) In some embodiments, the RFID-enabled mirror **300** can be coupled with a power source (not shown). For example, the RFID-enabled mirror **300** can include a battery or can be connected to an external power source provided by a vehicle. As such, the RFID-enabled mirror **300** can be configured to provide one or more notifications (e.g., visual, audio). According to one exemplary embodiment, the RFID-enabled mirror **300** can be adapted to provide an audio notification (e.g., beep) and/or visual notification (e.g., LED) when a vehicle passes a toll booth and/or accesses an HOT lane.

(36) Although the booster antenna **310** is shown as a loop antenna, a person having ordinary skill in the art can appreciate that the booster antenna **210** can have any suitable configuration (e.g., slot antenna) without departing from the scope of the present disclosure.

(37) FIG. 4 illustrates a multi-frequency RFID-enabled mirror **400** according to various embodiments. Referring to FIGS. 1A-B and 4, the multi-frequency RFID-enabled mirror **400** can be implemented as a rearview mirror. A person having ordinary skill in the art can appreciate that the RFID-enabled mirror **300** can be implemented as any suitable vehicle component (e.g., side view mirror) without departing from the scope of the present disclosure.

(38) In various embodiments, the multi-frequency RFID-enabled mirror **400** can include the mirror **100**. The mirror **100** can be subject to a selective demetallization procedure or a selective metallization procedure to form a booster antenna **420**. In some embodiments, the booster antenna **420** can be a slot antenna having a plurality of slots including, for example, but not limited to, a first slot **412** and a second slot **414**.

(39) For example, in some embodiments, the reflective layer **120** of the mirror **100** can include a

metal or a metal alloy layer (e.g., silver (Au), aluminum (Al), or speculum metal). To form the first slot **412** and the second slot **414**, silhouettes corresponding to the first slot **412** and the second slot **414** can be selectively removed from the reflective layer **120**. To preserve the reflective qualities of the mirror **100**, a dielectric coating can be applied on the substrate layer **110** in the first slot **412** and the second slot **414** where the reflective layer **120** of the mirror **100** was removed. As such, the mirror **100** can include the booster antenna **420**, which has a plurality of dielectric slots (e.g., the first slot **412** and the second slot **414**).

(40) Alternately, in some embodiments, the reflective layer **120** of the mirror **100** can include a dielectric coating. As such, a portion of the reflective layer **120** can be removed while preserving the first slot **412** and the second slot **414**. A metal or a metal alloy layer can be deposited where the dielectric coating was removed to form the booster antenna **420**.

(41) An RFID strap **430** can be positioned across one of the plurality of slots (e.g., the second slot **414**) and coupled with the booster antenna **420**. For example, in some embodiments, the RFID strap **430** can be coupled (e.g., capacitively) with the booster antenna **420** via a first contact **432** and a second contact **434**. However, the RFID strap **430** can also be coupled with booster antenna **420** in a different manner (e.g., inductively) without departing from the scope of the present disclosure.

(42) According to one exemplary embodiment, the multi-frequency RFID-enabled mirror **400** is adapted to support a plurality of frequency bands. Thus, in various embodiments, the relative and respective dimensions, spacing, and location of each of the plurality of slots (e.g., the first slot **412** and the second slot **414**) are configured such that the booster antenna **420** resonates at multiple frequency bands. For example, the booster antenna **420** can be adapted to resonate at a UHF band (e.g., 915 MHz) and at an HF band (e.g., 13.5 MHz). As such, the multi-frequency RFID-enabled mirror **400** is able to communicate with multiple RFID systems and/or devices including, for example, but not limited to, UHF systems or devices (e.g., RFID toll booth readers) and/or HF systems or devices (e.g., an NFC-enabled smartphone).

(43) For example, in some embodiments, the multi-frequency RFID-enabled mirror **400** is able to communicate with UHF RFID readers installed at toll booths and parking garages. The multi-frequency RFID-enabled mirror **400** is further able to communicate with an NFC-enabled device (e.g., smartphone). As such, the multi-frequency RFID-enabled mirror **400** can provide data (e.g., one or more identifiers) to the UHF RFID readers that allow the ETS system or parking authority to identify and debit an appropriate account. The multi-frequency RFID-enabled mirror **400** can further provide data (e.g., one or more identifiers) to the NFC-enabled device allowing the NFC-enabled device to recharge the account (e.g., via an electronic wallet application). Additional details with respect to account management are described in U.S. patent application Ser. No. 14/459,299, the disclosure of which is incorporated herein by reference in its entirety.

(44) In some embodiments, the multi-frequency RFID-enabled mirror **400** can be coupled with a power source (not shown). For example, the multi-frequency RFID-enabled mirror **400** can include a battery or can be connected to an external power source provided by a vehicle. As such, the multi-frequency RFID-enabled mirror **400** can be configured to provide one or more notifications (e.g., visual, audio). According to one exemplary embodiment, the multi-frequency RFID-enabled mirror **400** can be adapted to provide an audio notification (e.g., beep) and/or visual notification (e.g., LED) when a vehicle passes a toll booth and/or accesses an HOT lane.

(45) In various embodiments, the multi-frequency RFID-enabled mirror **400** can further include a switch **440**. The switch **440** can be adapted to control one or more operational states of the multi-frequency RFID-enabled mirror **400** including, for example, but not limited to, activating and deactivating the multi-frequency RFID-enabled mirror **400** with respect to at least one of the plurality of frequency bands (e.g., UHF, HF) supported by the multi-frequency RFID-enabled mirror **400**.

(46) Although the multi-frequency RFID-enabled mirror **400** is shown with the first slot **412** and



the second slot **414**, a person having ordinary skill in the art can appreciate that the multi-frequency RFID-enabled mirror **400** can include a different number of slots without departing from the scope of the present disclosure. Moreover, the multi-frequency RFID-enabled mirror **400** can include a plurality of slots (e.g., the first slot **412** and the second slot **414**) having a different relative and respective dimension, spacing, and/or location than shown without departing from the scope of the present disclosure.

(47) Additional details with respect to multi-frequency RFID devices are described in Reissued U.S. Patent Nos. RE 43,335 and RE 44,691, the disclosures of which are incorporated by reference herein in their entirety.

(48) FIG. 5 illustrates a self-declaring system **500** according to various embodiments. Referring to FIGS. 1A-B, 2A, 3, and 4, the self-declaring system **500** can include a sensor module **510**, a microcontroller **520**, and an RFID-enabled mirror **530**. In various embodiments, the RFID-enabled mirror **530** can be implemented by the RFID enabled mirror **200**, the RFID-enabled mirror **300**, or the multi-frequency RFID-enabled mirror **400**.

(49) In various embodiments, the sensor module **510** can collect data that may be used to determine a number of occupants in a vehicle. For example, in some embodiments, the sensor module **510** can include one or more sensors including, for example, but not limited to, a motion sensor, an infrared (IR) sensor, and an image recognition sensor.

(50) In various embodiments, the sensor module **510** can transmit at least some of the collected data to the microcontroller **520**. According to one exemplary embodiment, the micro controller **520** can be configured to determine a number of occupants in the vehicle based on the sensor data. In some embodiments, the microcontroller **520** can further determine whether the number of occupants in the vehicle exceeds a minimum number of occupants required for high occupancy vehicle (HOV) lane access in a given jurisdiction. For example, the micro controller **520** can determine, based on the sensor data, whether the vehicle is an SOV or an HOV.

(51) In various embodiments, the microcontroller **520** is configured to control an operational state of the RFID-enabled mirror **530**. For example, in some embodiments, the microcontroller **520** can change the operational state (e.g., activate and deactivate) of the RFID-enabled mirror **530** based on occupancy data. If the number of occupants in the vehicle does not exceed a certain number (e.g., one), the microcontroller **520** can be configured to activate the RFID-enabled mirror **530**. Activating the RFID-enabled mirror **530** allows the RFID-enabled mirror **530** to communicate relevant data to an HOT lane reader (e.g., one or more identifiers allowing the ETS to identify and debit an appropriate toll account).

(52) A person having ordinary skill in the art can appreciate that the sensor module **510**, the micro controller **520**, and the RFID-enabled mirror **530** can be coupled via one or more wired and/or wireless connections without departing from the scope of the present inventive concept. As such, in some embodiments, the sensor module **510**, the micro controller **520**, and the RFID-enabled mirror **530** may be installed in separate locations on a vehicle.

(53) The accompanying claims and their equivalents are intended to cover such forms or modifications as would fall within the scope and spirit of the protection. For example, the example apparatuses, methods, and systems disclosed herein can be applied wireless communication devices incorporating HF and/or UHF RFID reader capabilities. The various components illustrated in the figures may be implemented as, for example, but not limited to, software and/or firmware on a processor, ASIC/FPGA/DSP, or dedicated hardware. Also, the features and attributes of the specific example embodiments disclosed above may be combined in different ways to form additional embodiments, all of which fall within the scope of the present disclosure.

(54) The foregoing method descriptions and the process flow diagrams are provided merely as illustrative examples and are not intended to require or imply that the steps of the various embodiments must be performed in the order presented. As will be appreciated by one of skill in the art the order of steps in the foregoing embodiments may be performed in any order. Words such

as “thereafter,” “then,” “next,” etc. are not intended to limit the order of the steps; these words are simply used to guide the reader through the description of the methods. Further, any reference to claim elements in the singular, for example, using the articles “a,” “an” or “the” is not to be construed as limiting the element to the singular.

(55) The various illustrative logical blocks, modules, circuits, and algorithm steps described in connection with the embodiments disclosed herein may be implemented as electronic hardware, computer software, or combinations of both. To clearly illustrate this interchangeability of hardware and software, various illustrative components, blocks, modules, circuits, and steps have been described above generally in terms of their functionality. Whether such functionality is implemented as hardware or software depends upon the particular application and design constraints imposed on the overall system. Skilled artisans may implement the described functionality in varying ways for each particular application, but such implementation decisions should not be interpreted as causing a departure from the scope of the present invention.

(56) The hardware used to implement the various illustrative logics, logical blocks, modules, and circuits described in connection with the aspects disclosed herein may be implemented or performed with a general purpose processor, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general-purpose processor may be a microprocessor, but, in the alternative, the processor may be any conventional processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of receiver devices, e.g., a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration. Alternatively, some steps or methods may be performed by circuitry that is specific to a given function.

(57) In one or more exemplary aspects, the functions described may be implemented in hardware, software, firmware, or any combination thereof. If implemented in software, the functions may be stored as one or more instructions or code on a non-transitory computer-readable storage medium or non-transitory processor-readable storage medium. The steps of a method or algorithm disclosed herein may be embodied in processor-executable instructions that may reside on a non-transitory computer-readable or processor-readable storage medium. Non-transitory computer-readable or processor-readable storage media may be any storage media that may be accessed by a computer or a processor. By way of example but not limitation, such non-transitory computer-readable or processor-readable storage media may include RAM, ROM, EEPROM, FLASH memory, CD-ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium that may be used to store desired program code in the form of instructions or data structures and that may be accessed by a computer. Disk and disc, as used herein, includes compact disc (CD), laser disc, optical disc, digital versatile disc (DVD), floppy disk, and Blu-ray disc where disks usually reproduce data magnetically, while discs reproduce data optically with lasers. Combinations of the above are also included within the scope of non-transitory computer-readable and processor-readable media. Additionally, the operations of a method or algorithm may reside as one or any combination or set of codes and/or instructions on a non-transitory processor-readable storage medium and/or computer-readable storage medium, which may be incorporated into a computer program product.

(58) Although the present disclosure provides certain example embodiments and applications, other embodiments that are apparent to those of ordinary skill in the art, including embodiments which do not provide all of the features and advantages set forth herein, are also within the scope of this disclosure. Accordingly, the scope of the present disclosure is intended to be defined only by reference to the appended claims.

## Claims

1. A method for self-declaring a vehicle, comprising: receiving data from one or more inputs, wherein the data is indicative of a service corresponding to the vehicle; controlling an operation state of a radio frequency identified (RFID) enabled mirror from a plurality of operation states based on at least the received data; and communicating, by the RFID enabled mirror, with at least one reader via the determined operation state of the mirror.
  2. The method of claim 1, wherein the RFID-enabled mirror comprises a reflective layer and an RFID chip, wherein at least a portion of the reflective layer is removed to form an antenna.
  3. The method of claim 2, wherein the antenna is formed via one of selective demetallization and selective metallization.
  4. The method of claim 3, wherein the reflective layer comprises at least one layer of metallic material, wherein at least one portion of the reflective layer is removed to form the antenna from a remaining portion of the reflective layer and a dielectric coating is applied to the mirror where the reflective layer was removed.
  5. The method of claim 3, wherein the reflective layer comprises a dielectric coating, wherein at least one portion of the reflective layer is removed and a metallic material is applied to the mirror where the reflective layer was removed to form a booster antenna.
  6. The method of claim 2, wherein the RFID chip is coupled to the antenna via one of inductive coupling and capacitive coupling.
  7. The method of claim 2, wherein the RFID chip is configured to operate at multiple frequencies.
  8. The method of claim 7, wherein the antenna is configured to resonate at a first frequency band.
  9. The method of claim 8, wherein the antenna is configured to resonate at a second frequency band.
  10. The method of claim 9, wherein the first frequency band is a high-frequency band and the second frequency band is an ultra-high frequency band.
  11. The method of claim 1, wherein the RFID-enabled mirror comprises: a plurality of dielectric sections disposed on a plane, and an antenna disposed on the plane and between the plurality of dielectric sections.
  12. The method of claim 1, wherein the data includes data collected by one or more of the following: a motion sensor, infrared (IR) sensor, and image sensor.
  13. The method of claim 1, wherein the operation state is controlled by a switch adapted to control the operational state of the RFID enabled mirror.
  14. The method of claim 1, wherein the operation state of the mirror includes an activated state and a deactivated state.
  15. The method of claim 1, further comprising determining occupancy data based in part on the received data, wherein determining the occupancy data includes determining a number of occupants in the vehicle and whether the number of occupants in the vehicle exceeds a predetermined threshold number of occupants.
  16. The method of claim 15, wherein the operational state of the mirror corresponds to the number of occupants in a vehicle.
  17. The method of claim 1, wherein the mirror comprises one of a rearview mirror and a side view mirror.
  18. The method of claim 1, wherein the data is related to different accounts associated with the vehicle or a user thereof.
-