

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250261776

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Bernstein; Steven J. et al.

---

### **COLLAPSIBLE ARMS HANGER WITH PINCH AND PULL LOCK WITH OR WITHOUT FOLDING HOOK**

---

#### **Abstract**

A garment hanger with a hook either metal or plastic that moves between a substantially vertical position and a substantially horizontal position or also remains in a stationary upright position. The body of the hanger has arms that collapse and move between a substantially vertical position and a substantially horizontal position. Secondary “locking” system on arms and bodies to ensure the arms remain in a horizontal position without folding unintentionally by being interlocked with each other in a manner that requires a user to manually release the interlocking through use of a lock releasing lever. This allows easier insertion or removal of hanger in closed neck garment. When both arms and hook are folded or collapsed this creates footprint reduction of hanger, creating space savings in packaging and transport. A size tab can be fitted to the hanger.

---

**Inventors:** Bernstein; Steven J. (Hewlett, NY), Blitz; Leslie S. (New Hyde Park, NY)

**Applicant:** SJBEE LLC (Hewlett, NY)

**Family ID:** 1000008561086

**Appl. No.:** 19/057995

**Filed:** February 20, 2025

#### **Related U.S. Application Data**

us-provisional-application US 63556317 20240221

us-provisional-application US 63634823 20240416

---

#### **Publication Classification**

**Int. Cl.:** A47G25/40 (20060101); A47G25/32 (20060101)

**U.S. Cl.:**

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] The present patent application claims the benefit of and priority to U.S. Provisional Patent Application Nos. 63/556,317, filed Feb. 21, 2024, by Steven J. Bernstein and Leslie S. Blitz, entitled “COLLAPSIBLE ARMS HANGER WITH OR WITHOUT FOLDING HOOK” and 63/634,823, filed Apr. 16, 2024, entitled “COLLAPSIBLE ARMS HANGER WITH PINCH AND PULL LOCK WITH OR WITHOUT FOLDING HOOK”. The entire contents of each of the patent applications listed above are incorporated herein by reference.

### BACKGROUND OF THE INVENTION

[0002] Garment hangers have been around for hundreds of years. Modern day retail use garment hangers have many packaging and travel requirements and specifications intended to increase efficiency in the supplier to retailer pipeline by minimizing order to sales floor or ecommerce shipment time. Many garments are manufactured all over the world and then shipped to United States (or other countries) pre-hung as a “garment on hanger” from the originating garment manufacturing location. To save time and expense at the retail level the garment is placed on the hanger at the point of garment manufacturing and placed into a shipping box or container. Upon delivery to the retailer location, the retailer must remove the “garment on hanger” from the box or container and hang appropriately in distribution center for e commerce shipment or further shipment to an individual store.

[0003] Present day Omni Channel process dictates if the garment goes directly to the sales floor, the hanger will stay on the garment, if to be shipped in ecommerce packaging there is a need for the hanger to be easily removed without harming the hanger or unbuttoning the garment to remove the hanger. Since the retailer or the garment manufacturer does not always know, which apparel will go to the greater need either brick and mortar store or ecommerce, the need for a garment hanger that can be used in both channels without being changed is required.

[0004] This invention relates to the need for an individual hanger to be able to be used both at retail level and ecommerce shipments due to the nature of the folding hook and collapsible arms. There have been many examples of collapsible hangers over the years but never one that appears to meet all the current retail or GS1 specifications for weight of garment and silhouette. This invention improves upon the hangers of U.S. Pat. No. 10,959,558 Hanger with Folding hook that folds and arms that collapse when needed or remain solid when used as a commercial hanger holding garments up to two- and one-half pounds without folding unintentionally.

[0005] Today's dimensional packaging shipping costs have made for the appreciation of smaller shipping boxes saving cost based on the dimension of the box. A smaller footprint of hanger when collapsed will allow for smaller shipping cartons.

### SUMMARY OF THE INVENTION

[0006] The foregoing and other objects of the invention are realized in accordance with the disclosure herein with a garment hanger, comprising: a hanger body having a central neck to which a hanger hook is connected, and hanger arms removably connectible to said hanger body such that said hanger arms are collapsible to a substantially vertical position permitting the hanger to be removed from or inserted into a garment through a neck opening of the garment, without having to unbutton said garment for such removal; said hanger body comprising openings at opposite ends of said central neck, and adjacent each said opening, an arm-motion arrester comprising a projection located outside the opening and projecting outwardly; said hanger arms including a first hanger arm and a second hanger arm, each hanger arm being connectible to and pivotably movable in a

respective one of said openings, in configurations that enable said hanger arms to be held and fixed in a standard horizontal position and selectively collapsed by pivoting said hanger arms with respect to said central neck to assume said substantially vertical position relative to said neck portion, said first and second hanger arms being interchangeable such that said hanger arms can be attached to said hanger body at opposite ends thereof, and said hanger arms being removable from said openings; and each hanger arm being molded to include a flexible lock including a pinchable or pullable handle and a locking region that is so located on the hanger arm that rotation of the hanger arm from its extended to said collapsed position is prevented when the locking region on the arm meets and engages with the projection located on the arm-motion arrester of the hanger body, and such that pinching or pulling of the handle of the flexible lock is required to release the engagement between the flexible lock and said projection to allow the hanger arm to be moved to its collapsed position.

[0007] Preferably, the described hanger is such that also includes one or more of the following: each of the hanger body, the first hanger arm and the second hanger arm is formed as and of a molded plastic material; said hanger arms are identical in structure whether used on either side of said hanger body; the pullable handle extends below a lower edge of the hanger arm so as to be easily locatable by a user's fingers even when concealed from view by the garment; the arm-motion arrester and the flexible lock have mutual surfaces that abut each other in the locked, extended orientation of the hanger arms; the arm-motion arrester defines a nestling space that is shaped to receive therein a corresponding pointed end of the flexible lock in the locked, extended orientation of the hanger arms; the hanger arms are configured to remain in their extended orientations even when supporting garment weights of two pounds; and/or said hanger hook is pivotably connected to said hanger neck and moveable to either substantially vertical or horizontal positions.

---

## **Description**

### **BRIEF DESCRIPTION OF THE DRAWINGS**

[0008] FIG. 1A is a perspective view of the hanger of the present invention with collapsible arms and folding metal hook boss.

[0009] FIG. 1B is a perspective view similar to FIG. 1A with the collapsible arms and a plastic hook.

[0010] FIG. 1C is a perspective view similar to FIG. 1A and FIG. 1B with non-folding hook with collapsible arms and SOHS sizer mount.

[0011] FIG. 2A is a front perspective view of collapsible arm.

[0012] FIG. 2B is a rear perspective view of the collapsible arm.

[0013] FIG. 3 is a front perspective view of the central neck portion of the hanger of this invention.

[0014] FIG. 4 is a perspective view of the hanger arms in the closed position.

[0015] FIG. 5 is a perspective view of the pull in lock hanger of the present invention with collapsible arms and metal hook boss.

[0016] FIG. 6 is a perspective view of hanger body and neck.

[0017] FIG. 7 is a front and back perspective view of the collapsible arms.

[0018] FIG. 8 is a perspective view of the hanger arms in the closed position.

[0019] FIG. 9 is a perspective view of the pinch lock hanger of the present invention with collapsible arms and metal hook boss.

[0020] FIG. 10 is a perspective view of hanger body and neck.

[0021] FIG. 11 is a perspective view of the collapsible arms.

[0022] FIG. 12 is a perspective view of the hanger arms in the closed position.

[0023] FIGS. 13, 13A and 13B include a perspective view of another pinch lock hanger of the present invention with collapsible arms and metal hook boss and enlarged views pertaining thereto,

substantially similar to the hanger described relative to FIGS. 9 through 12, with modified stop and lock components.

## DETAILED DESCRIPTION OF DRAWINGS

[0024] Referring to FIG. 1A, a hanger **8** is shown having central neck **10** with metal hook and SOHS (secure over the hook sizer) sizer receiver mount **12** on top thereof. The hanger is preferably of an "I" beam construction. Hanger **8** is shown as a full hanger with the hanger arms **14** in the upright open standard horizontal position. This design is not limited to an "I" beam construction. In one preferred embodiment (FIG. 1C and FIG. 3) central neck **10** includes a coordinate loop **11** for receiving a second similar hanger or it could be for an entirely different hanger silhouette.

[0025] In accordance with this invention, arms **14** are pivotably connected to the central neck **10** at pivots **16** (FIG. 1B) located on either side at the bottom of central neck **10**.

[0026] FIG. 1B shows hanger **8** similar to FIG. 1A except that folding plastic hook **18** is pivotably connected to mount **12** and is added to central neck **10** with plastic hook sizer mount **13** formed as an I beam construction.

[0027] FIG. 1C shows hanger **8** similar to FIG. 1A except with metal hook boss **19** in place for non-foldable hook and 9 steps for SOHS (secure over the hook sizer) size identity tab and coordinate loop **11** is shown.

[0028] FIGS. 2A and 2B are front and rear perspective views of arm **14** which can be used as right or left arms for the hangers. Hanger arm **14** has a substantially circular cantilevered projection **21** at an inner end **22** with three tabs **24** to hold arms to the central neck and hanger body formed on the radial surface **26** of the circular projection **21** and cantilevered positions nub **28** projecting from radial surface **26**.

[0029] The cantilevered nub **28** and its circular position are also shown in U.S. Pat. Nos. 9,655,466 and 10,959,558 ('466 and '558 having the same inventors as for the present invention). FIG. 2A shows the addition of 15 flexible stabilization mechanism which interacts with stabilizing nub **17** shown in FIG. 3. The contents of U.S. Pat. Nos. 9,655,466 and 10,959,558 are incorporated herein by reference. Additionally, the attachment between circular projection **21** and nub **28** of this invention are substantially similar to the mechanism of FIGS. 3A and 3B of the '466 patent. The '466 patent describes a cantilevered projection system as well as a closed projection system with respective nubs to achieve pivot and removal functions as are achieved in this invention. Either closed or cantilevered system can be used with the present invention.

[0030] FIG. 2A shows the introduction of a closed cantilever **26** and open flexible stabilization mechanism **15** which provides more stability to the hanger when in the open arm position. Nub **17** (FIG. 3) serves as an additional protrusion to hold the arm in open position when flexible stabilization mechanism **15** passes over it.

[0031] Projection **21** and retainer tab **24** locks into hole **30**. Retainer tabs **24** align with recesses **32** for easy assembly and friction holding of the arm in hole **30**. Back bearing surface **34** presses against perimeter **36** around hole **30** for stability for the complete assembly. Positioning nub **28** is attached to the cantilevered flexible member **29** and allows positioning nub **28** to align with recess **38** (FIG. 3) to position and hold the arms to be in the standard horizontal position. Upper arm stop **40** prevents the arm **14** from being positioned above the horizontal plane. Lower arm stop **42** prevents the arm **14** from being positioned beyond the vertical plane when butting up against central head arm stop **44** (FIG. 1B).

[0032] FIG. 1A, which is a complete assembled hanger with no hook shown, shows the pivotable arms **14** pivoted into the upright horizontal position and functions as a conventional garment hanger for supporting and displaying a garment. However when the arms **14** need to be collapsed to remove or insert into a buttoned or closed neck garment as shown in FIG. 4 the cantilevered hangers arms can be collapsed by pressing down on the arms which forces nub **28** of the cantilever member **29** and flexible stabilization mechanism **15** to be free to rotate on projection **21**.

Collapsible arms **14** employ a locking mechanism that allows for the arms to remain upright

(horizontal) and “locked” into position for display but may be easily folded or collapsed when they need to remove them from a closed neck garment or buttoned neck garment is required. The simplicity of the pivotable movement of the arms using nub **28** and **17** releasing it from the locking position will be cost effective to manufacturers, easy to assemble and simple for pivoting the locking arm **14** in the upright or folded position.

[0033] As discussed above the collapsed state of the hanger provides a reduced footprint for the hanger creating space savings in packaging and transport and the inclusion of the flexible stabilization mechanism **15** and stabilizing nub **17** allow for heavier weight garments. In order to save time and expense at the retail distribution center level, the hanger can either remain as a conventional hanger or the arm **14** can be collapsed for easy removal when hanger is not wanted in e-commerce use or when looking to save space in the dimensional packaging reducing the footprint of box and space required in shipping.

[0034] Referring to FIG. 5, hanger **8** is shown having central neck **10** with metal hook boss **19** and SOHS (secure over the hook sizer) sizer receiver mount **9** on side thereof. The hanger is preferably of an I-beam construction. Hanger is shown as a full hanger with hanger body **8** and the hanger arms **14** in the upright open standard horizontal position. This design is not limited to an I-beam construction. In one preferred embodiment central neck **10** includes a coordinate loop **11** for receiving a second similar hanger or it could be for an entirely different hanger silhouette.

[0035] In accordance with this invention, arms **14** are pivotably connected to the central neck **10** at pivots **16** (FIG. 5) located on either side at the bottom of central neck **10**. Here can be seen flexible pull in lock **15A** which when pulled in releases lock against arm stop **18A** to collapse. FIG. 5, which is a complete assembled hanger, shows the pivotable arms **14** pivoted into the upright horizontal position and functions as a conventional garment hanger for supporting and displaying a garment. However, when the arms **14** need to be collapsed to remove or insert into a buttoned or closed neck garment as shown in FIG. 8 the cantilevered hangers arms can be collapsed by pulling inwards on flexible pull in lock **15A** which forces flexible pull in lock **15A** to be free from arm stop **18A** and to rotate on pivot **16**. Collapsible arms **14** employ a locking mechanism that allows for the arms to remain upright (horizontal) and “locked” into position for display but may be easily folded or collapsed when they need to remove them from a closed neck garment or buttoned neck garment is required. The simplicity of the pivotable movement of the arms using flexible pull in lock **15A** and releasing it from the locking position will be cost effective to manufacturers, easy to assemble and simple for pivoting the locking arm **14** in the upright or folded position. Also shown in FIG. 5 is flexible pull in lock **15A** when pulled away from body releases the hold on arm stops **18A**.

[0036] FIG. 6 is a front perspective of hanger body **8**.

[0037] FIG. 7 are front and back perspective views of arm **14** which can be used as right or left arms for the hangers. Hanger arm **14** has a substantially circular inner end of arm **22** with three retainer tabs **24** to hold arms to the central neck and hanger body formed on the back bearing surface **34**.

[0038] FIG. 8 shows the “collapsed” version of the arms.

[0039] As discussed above the collapsed state of the hanger provides a reduced footprint for the hanger creating space savings in packaging and transport and the inclusion of the flexible pull in lock **15A** and arm stop **18A** allow for heavier weight garments. In order to save time and expense at the retail distribution center level, the hanger can either remain as a conventional hanger or the arm **14** can be collapsed for easy removal when hanger is not wanted in e-commerce use or when looking to save space in the dimensional packaging reducing the footprint of box and space required in shipping.

[0040] Referring to FIG. 9, hanger **8** is shown having central neck **10** with metal hook boss **19** and SOHS (secure over the hook sizer) sizer receiver mount **9** on side thereof. The hanger is preferably of an “I” beam construction. Hanger is shown as a full hanger with hanger body **8** and the hanger arms **14** in the upright open standard horizontal position. This design is not limited to an I-beam

construction. In one preferred embodiment central neck **10** includes a coordinate loop **11** for receiving a second similar hanger or it could be for an entirely different hanger silhouette.

[0041] In accordance with this invention, arms **14** are pivotably connected to the central neck **10** at pivots **16** (FIG. **9**) located on either side at the bottom of central neck **10**. Here can be seen flexible pinchable lock **15B** which when pinched releases lock on arm stop **18B** to collapse. FIG. **9**, which is a complete assembled hanger, shows the pivotable arms **14** pivoted into the upright horizontal position and functions as a conventional garment hanger for supporting and displaying a garment. However, when the arms **14** need to be collapsed to remove or insert into a buttoned or closed neck garment as shown in FIG. **12** the cantilevered hangers arms can be collapsed by pinching flexible pinchable lock **15B** which forces flexible pinchable lock **15B** to be free to rotate on pivot **16**. Collapsible arms **14** employ a locking mechanism that allows for the arms to remain upright (horizontal) and “locked” into position for display but may be easily folded or collapsed when they need to remove them from a closed neck garment or buttoned neck garment is required. The simplicity of the pivotable movement of the arms using flexible pinchable lock **15B** and releasing it from the locking position will be cost effective to manufacturers, easy to assemble and simple for pivoting the locking arm **14** in the upright or folded position. FIG. **10** is a front perspective of hanger body **8**.

[0042] FIG. **11** are front and back perspective views of arm **14** which can be used as right or left arms for the hangers. Hanger arm **14** has a substantially circular inner end of arm **22** with three retainer tabs **24** to hold arms to the central neck and hanger body formed on the back bearing surface **34**. Also shown in FIG. **11** is flexible pinchable lock **15B** when pinched releases the hold on arm stop **18B**.

[0043] FIG. **12** shows the “collapsed” version of the arms.

[0044] As discussed above the collapsed state of the hanger provides a reduced footprint for the hanger creating space savings in packaging and transport and the inclusion of the flexible pinchable lock **15B** and arm stop **18B** allow for heavier weight garments. In order to save time and expense at the retail distribution center level, the hanger can either remain as a conventional hanger or the arm **14** can be collapsed for easy removal when hanger is not wanted in e-commerce use or when looking to save space in the dimensional packaging reducing the footprint of box and space required in shipping.

[0045] Referring to FIGS. **13**, **13A** and **13b**, FIG. **13** shares virtually all of the elements of the embodiment of FIG. **9**, including hanger **8** having central neck **10** and SOHS (secure over the hook sizer) sizer receiver mount **9** on side thereof. The hanger is preferably of an “I” beam construction. Hanger **8** is shown with only one of the two hanger arms **14** in the upright open standard horizontal position.

[0046] In accordance with this invention, arms **14** are pivotably connected to the central neck **10** at pivots **16** located on either side at the bottom of central neck **10**. Here can be seen flexible pinchable lock **1315B**, located at the distal end of an elongate, arcuate and flexible lock finger connected at its opposite end to and extending from the underside of the arm **14**. When the handle **1315C** of pinchable lock is pinched or pulled the lock **1315B** is released from the arm stop **1318B**, thereby enabling the arm to be moved to its collapsed, vertical orientation. The arm stop **1318B** functions as a hanger arm arrester by arresting or blocking the ability of the extended hanger arm from returning to the collapsed position owing to excessive force exerted on the arm by a super heavy garment or due to an unintended jerking force applied to the arms. FIG. **13**, which depicts the assembled hanger, shows one of the two pivotable arms **14** pivoted into the upright horizontal position to enable it to function as a conventional garment hanger for supporting and displaying a garment.

[0047] However, when the arms **14** need to be collapsed to enable the hanger to be removed from or inserted into a buttoned or closed neck garment, the cantilevered hangers arms **14** can be collapsed by pinching flexible pinchable lock **1315B** which forces flexible pinchable lock **1315B** to

be free to rotate on pivot **16**. Collapsible arms **14** employ a locking mechanism that allows for the arms to remain upright (horizontal) and “locked” into position for display but may be easily folded or collapsed when they need to remove them from a closed neck garment or buttoned neck garment is required. The simplicity of the pivotable movement of the arms using flexible pinchable lock **1315B** and releasing it from the locking position will be cost effective to manufacturers, easy to assemble and simple for pivoting the locking arm **14** in the upright or folded position.

[0048] The improved operation of the arm stop **1318B** working together with the pinchable lock **1315B** over the prior embodiment can be more easily appreciated from FIG. **13A**, as it provides an enlarged view of the encircled section of FIG. **13**. As shown, the hook **18** has a distal end that forms the “pointed” arm stop **1318B**, which in turn defines a complementary shaped “nestling” space **1318C** in which the similarly shaped distal end **1315D** of the pinchable lock **1315B** is tightly and snugly received and locked, in the arms fully extended state of the hanger **8**. When the arm **14** is being moved from the collapsed to the fully extended position, the tip of the stop **1318B** slides on the interior surface **1315E** of the lock. Even after extended and repeated use, the possibility of the plastic material of the tip of the “stop” wearing off is entirely negated. As in the prior embodiment, one can easily locate the extending arm **1315C** of the lock **1315B** and press on it inwardly to release it from the nestling space **1318C**. Note that the arm **1315C** protrudes and extends below the bottom surface or edge of the arm **14**, whereby one can collapse the arm **14** even when it supports and rendered invisible by a garment hanging thereon. FIG. **13B** is provided to illustrate the positions of the stop and lock in the intermediate position, when the hanger arm **14** is located about midway between being fully extended and collapsed.

[0049] As discussed above, as with the embodiment of FIG. **9**, the FIG. **13** embodiment provides a reduced footprint for the hanger creating space savings in packaging and transport and the inclusion of the flexible pinchable lock **1315B** and arm stop **1318B** allow for heavier weight garments. In order to save time and expense at the retail distribution center level, the hanger can either remain as a conventional hanger or the arm **14** can be collapsed for easy removal when hanger is not wanted in e-commerce use or when looking to save space in the dimensional packaging reducing the footprint of box and space required in shipping.

[0050] In general, the collapsible hangers described in the present inventors' issued patents relied on frictional forces between lock and nub components, and use of snap into detents, to hold the arms of the hangers in their extended positions. The arms could be forced down, into their collapsed positions by applying a torque force that caused the plastic lock and nub components to plastically deform and thereby be forced to the down positions. In marked contrast, in the embodiments of the present inventions employ different locking components located outside the interior of the pivot to positively inter-engage and interlock the various stop and lock components in a manner that does not rely on the frictional forces and plastic deformation to effect the locking of the in their extended orientations. Rather, the flexible lock components include a “pinchable” or “pull-able” extension, that preferably extends below the lower edge of the arms, and which can and must be pinched or squeezed or pulled to release the lock component from being firmly grasped and held by the stop. Without this pinching action, the arms remain firmly lock, unable to being bent down to the collapsed position.

[0051] In addition, the present inventions realize the objective of positive locking and holding of the arms through the use of only three injection molded piece, namely the center piece and the two arms. The center piece is formed with the above-described pivot cavity in which is received and supported a respective one of the arm, with the arm and center piece having molded therein all the features that form the lock and stop components described above without resorting to any additional pins, or levers or the locking to realize the improved hanger construction described above. Also, all the hanger embodiments described above meet the requirements of GS1: Guideline Hanger Specifications for Floor-Ready Merchandise for hangers including for parameters such as weight, distortion, materials and the like. Regardless, preferably, the hangers herein are suited to

support garments weighing at least two pounds.

[0052] It should be understood that the preferred embodiment was described to provide the best illustration of the principles of the invention and its practical application to thereby enable one of ordinary skill in the art to utilize the invention in various embodiments and with various modifications which are within the suited to the particular use contemplated. All such modifications and variations are within the scope of the invention are deemed by the appended claims when interpreted in accordance with the breadth to which they are fairly legally and equitably entitled.

#### LIST OF PARTS

[0053] **6** metal hook [0054] **8** Hanger [0055] **9** Steps for SOHS size identity tab [0056] **10** Central neck [0057] **11** Coordinate loop for metal hook [0058] **12** Hook and Sizer mount for folding metal hook [0059] **13** Plastic hook sizer mount [0060] **14** Hanger Arms [0061] **15** Flexible stabilization mechanism [0062] **15A** flexible pull in lock [0063] **15B** flexible pinch lock [0064] **16** Pivots [0065] **17** Stabilizing nub for **15** [0066] **18** Plastic Hook [0067] **18A** Arm stop [0068] **18B** Arm Step stop [0069] **19** Metal Hook Boss [0070] **20** Circular projection [0071] **21** Cantilevered Projection [0072] **22** inner end of hanger arm [0073] **24** Retainer tab [0074] **26** Radial surface of circular cantilevered projection [0075] **28** Cantilevered positioning nub [0076] **29** Cantilevered Flexible member [0077] **30** Hole [0078] **32** Recess [0079] **34** Back bearing surface [0080] **36** Perimeter around hole **30** [0081] **38** Recess for nub **28** [0082] **40** Upper arm stop [0083] **42** Lower arm stop [0084] **44** Central head arm stop [0085] **46** Projection nub [0086] **48** Cylindrical projection [0087] **1315** Flexibly extending lock support finger [0088] **1315B** Modified flexible pinch lock [0089] **1315C** Extended arm [0090] **1315D** Distal end [0091] **1315E** Interior surface of lock [0092] **1318B** Modified arm stop [0093] **1318C** Lock nestling space

[0094] Although the present invention has been described in relation to particular embodiments thereof, many other variations and modifications and other uses will become apparent to those skilled in the art. It is preferred, therefore, that the present invention be limited not by the specific disclosure herein, but only by the appended claim.

## Claims

**1.** A garment hanger, comprising: a hanger body having a central neck with a configuration to receive a hanger hook, and hanger arms removably connectible to said hanger body such that said hanger arms are collapsible to a substantially vertical position permitting the hanger to be removed from or inserted into a garment through a neck opening of the garment, without having to unbutton said garment for such removal; said hanger body comprising openings at opposite ends of said central neck, and adjacent each said opening, an arm-motion arrester comprising a projection located outside the opening and projecting outwardly; said hanger arms including a first hanger arm and a second hanger arm, each hanger arm being connectible to and pivotably movable in a respective one of said openings, in configurations that enable said hanger arms to be held and fixed in a standard horizontal position and selectively collapsed by pivoting said hanger arms with respect to said central neck to assume said substantially vertical position relative to said neck portion, said first and second hanger arms being interchangeable such that said hanger arms can be attached to said hanger body at opposite ends thereof, and said hanger arms being removable from said openings; and each hanger arm being molded to include a flexible lock including a pinchable or pullable handle and a locking region that is so located on the hanger arm that rotation of the hanger arm from its extended to said collapsed position is prevented when the locking region on the arm meets and engages with the projection located on the arm-motion arrester of the hanger body, and such that pinching or pulling of the handle of the flexible lock is required to release the engagement between the flexible lock and said projection to allow the hanger arm to be moved to its collapsed position.

**2.** A garment hanger as described in claim 1, wherein each of the hanger body, the first hanger arm



and the second hanger arm is formed as and of a molded plastic material.

3. A garment hanger as described in claim 1, wherein said hanger arms are identical in structure whether used on either side of said hanger body.
  4. A garment hanger as described in claim 1, wherein the pullable handle extends below a lower edge of the hanger arm so as to be easily locatable by a user's fingers even when concealed from view by the garment.
  5. A garment hanger as described in claim 1, wherein the arm-motion arrester and the flexible lock have mutual surfaces that abut each other in the locked, extended orientation of the hanger arms.
  6. A garment hanger as described in claim 1, wherein the arm-motion arrester defines a nestling space that is shaped to receive therein a corresponding pointed end of the flexible lock in the locked, extended orientation of the hanger arms.
  7. A garment hanger as described in claim 1, wherein the hanger arms are configured to remain in their extended orientations even when supporting garment weights of two pounds.
  8. A garment hanger as described in claim 1, including a hanger hook pivotably connected to said hanger neck and moveable to either substantially vertical or horizontal positions.
  9. A garment hanger as described in claim 8, wherein said central neck comprises a pivot for said hanger hook.
  10. A garment hanger as described in claim 2, including a hanger hook that is pivotably moveable to either substantially vertical or horizontal positions.
  11. A garment hanger as described in claim 10, wherein said central neck comprises a pivot for said hanger hook.
  12. A garment hanger as described in claim 1, wherein said hanger arms are held in said substantially horizontal position by an interlock.
  13. A garment hanger as described in claim 12, wherein said interlock comprises a rotatable cylindrical member having a nub captured in a recess to lock said hanger arms in position.
  14. A garment hanger as described in claim 2, wherein said hanger arms are held in said substantially horizontal position by an interlock.
  15. A garment hanger as described in claim 14, wherein said interlock comprises a rotatable cylindrical member having a nub captured in a recess to lock said hanger arms in position.
  16. A garment hanger as described in claim 1, wherein said hanger is molded.
  17. A garment hanger as described in claim 16, wherein said hanger is molded plastic.
-