United States Patent	12392999
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Shabtay; Gal et al.

Folded camera lens designs including eight lenses of +-+-+++-refractive powers

Abstract

Folded cameras with a total track length (TTL), f numbers smaller than 1.2 and large fields of view, e.g. of at least 60 degrees. Such folded cameras may comprise a lens with N≥7 lens elements, an image sensor and an optical path folding element for providing a folded optical path between an object and the lens, wherein an aperture stop of the lens is located closer to a first surface of the first lens element facing the object than a distance d that fulfills d/TTL=0.2.

Inventors:	**Shabtay; Gal** (Tel Aviv, IL), **Goldenberg; Ephraim** (Tel Aviv, IL), **Rudnick; Roy** (Tel Aviv, IL), **Goulinski; Nadav** (Tel Aviv, IL)
Applicant:	**Corephotonics Ltd.** (Tel Aviv, IL)
Family ID:	**1000008765626**
Assignee:	**Corephotonics Ltd. (Tel Aviv, IL)**
Appl. No.:	**18/755732**
Filed:	**June 27, 2024**

Prior Publication Data

Document Identifier	Publication Date
US 20240345372 A1	Oct. 17, 2024

Related U.S. Application Data

continuation parent-doc US 17607400 US 12050308 WO PCT/IB2021/056357 20210714 child-doc US 18755732
us-provisional-application US 63054862 20200722

Publication Classification

Int. Cl.:   **G02B13/00** (20060101); **G02B9/64** (20060101)

U.S. Cl.:

CPC   **G02B13/0065** (20130101); **G02B9/64** (20130101); **G02B13/0045** (20130101);

Field of Classification Search

CPC: G02B (13/0065); G02B (9/64); G02B (13/0045)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2106752	12/1937	Land	N/A	N/A
2354503	12/1943	Arthur	N/A	N/A
2378170	12/1944	Aklin	N/A	N/A
2441093	12/1947	Aklin	N/A	N/A
3388956	12/1967	Eggert et al.	N/A	N/A
3524700	12/1969	Eggert et al.	N/A	N/A
3558218	12/1970	Grey	N/A	N/A
3864027	12/1974	Harada	N/A	N/A
3942876	12/1975	Betensky	N/A	N/A
4134645	12/1978	Sugiyama et al.	N/A	N/A
4338001	12/1981	Matsui	N/A	N/A
4465345	12/1983	Yazawa	N/A	N/A
4792822	12/1987	Akiyama et al.	N/A	N/A

5000551	12/1990	Shibayama	N/A	N/A
5327291	12/1993	Baker et al.	N/A	N/A
5331465	12/1993	Miyano	N/A	N/A
5969869	12/1998	Hirai et al.	N/A	N/A
6014266	12/1999	Obama et al.	N/A	N/A
6035136	12/1999	Hayashi et al.	N/A	N/A
6147702	12/1999	Smith	N/A	N/A
6169636	12/2000	Kreitzer	N/A	N/A
6654180	12/2002	Ori	N/A	N/A
7187504	12/2006	Horiuchi	N/A	N/A
7206136	12/2006	Labaziewicz et al.	N/A	N/A
7515351	12/2008	Chen et al.	N/A	N/A
7564635	12/2008	Tang	N/A	N/A
7643225	12/2009	Tsai	N/A	N/A
7660049	12/2009	Tang	N/A	N/A
7684128	12/2009	Tang	N/A	N/A
7688523	12/2009	Sano	N/A	N/A
7692877	12/2009	Tang et al.	N/A	N/A
7697220	12/2009	Iyama	N/A	N/A
7738186	12/2009	Chen et al.	N/A	N/A
7777972	12/2009	Chen et al.	N/A	N/A
7813057	12/2009	Lin	N/A	N/A
7821724	12/2009	Tang et al.	N/A	N/A
7826149	12/2009	Tang et al.	N/A	N/A
7826151	12/2009	Tsai	N/A	N/A
7869142	12/2010	Chen et al.	N/A	N/A
7898747	12/2010	Tang	N/A	N/A
7916401	12/2010	Chen et al.	N/A	N/A
7918398	12/2010	Li et al.	N/A	N/A
7957075	12/2010	Tang	N/A	N/A
7957076	12/2010	Tang	N/A	N/A
7957079	12/2010	Tang	N/A	N/A
7961406	12/2010	Tang et al.	N/A	N/A
8000031	12/2010	Tsai	N/A	N/A
8004777	12/2010	Sano et al.	N/A	N/A
8077400	12/2010	Tang	N/A	N/A
8149523	12/2011	Ozaki	N/A	N/A
8218253	12/2011	Tang	N/A	N/A
8228622	12/2011	Tang	N/A	N/A
8233224	12/2011	Chen	N/A	N/A
8253843	12/2011	Lin	N/A	N/A
8279537	12/2011	Sato	N/A	N/A
8363337	12/2012	Tang et al.	N/A	N/A
8395851	12/2012	Tang et al.	N/A	N/A
8400717	12/2012	Chen et al.	N/A	N/A
8451549	12/2012	Yamanaka et al.	N/A	N/A
8503107	12/2012	Chen et al.	N/A	N/A
8514502	12/2012	Chen	N/A	N/A
8570668	12/2012	Takakubo et al.	N/A	N/A
8718458	12/2013	Okuda	N/A	N/A
8780465	12/2013	Chae	N/A	N/A
8810923	12/2013	Shinohara	N/A	N/A
8854745	12/2013	Chen	N/A	N/A
8958164	12/2014	Kwon et al.	N/A	N/A
9185291	12/2014	Shabtay	N/A	N/A
9229194	12/2015	Yoneyama et al.	N/A	N/A
9235036	12/2015	Kato et al.	N/A	N/A
9279957	12/2015	Kanda et al.	N/A	N/A
9438792	12/2015	Nakada et al.	N/A	N/A
9488802	12/2015	Chen et al.	N/A	N/A
9568712	12/2016	Dror et al.	N/A	N/A
9678310	12/2016	Iwasaki et al.	N/A	N/A
9817213	12/2016	Mercado	N/A	N/A
9869846	12/2017	Bone et al.	N/A	N/A
10330892	12/2018	Hashimoto	N/A	N/A
11347016	12/2021	Shabtay et al.	N/A	N/A
12066605	12/2023	Shim	N/A	N/A
2002/0118471	12/2001	Imoto	N/A	N/A
2003/0048542	12/2002	Enomoto	N/A	N/A
2005/0041300	12/2004	Oshima et al.	N/A	N/A
2005/0062346	12/2004	Sasaki	N/A	N/A
2005/0128604	12/2004	Kuba	N/A	N/A
2005/0141103	12/2004	Nishina	N/A	N/A
2005/0168840	12/2004	Kobayashi et al.	N/A	N/A
2005/0270667	12/2004	Gurevich et al.	N/A	N/A

2006/0092524	12/2005	Konno	N/A	N/A
2006/0238902	12/2005	Nakashima et al.	N/A	N/A
2006/0275025	12/2005	Labaziewicz et al.	N/A	N/A
2007/0114990	12/2006	Godkin	N/A	N/A
2007/0229983	12/2006	Saori	N/A	N/A
2007/0247726	12/2006	Sudoh	N/A	N/A
2007/0253689	12/2006	Nagai et al.	N/A	N/A
2008/0056698	12/2007	Lee et al.	N/A	N/A
2008/0094730	12/2007	Toma et al.	N/A	N/A
2008/0094738	12/2007	Lee	N/A	N/A
2008/0273250	12/2007	Nishio	N/A	N/A
2008/0291531	12/2007	Heimer	N/A	N/A
2008/0304161	12/2007	Souma	N/A	N/A
2009/0002839	12/2008	Sato	N/A	N/A
2009/0067063	12/2008	Asami et al.	N/A	N/A
2009/0122423	12/2008	Park et al.	N/A	N/A
2009/0135245	12/2008	Luo et al.	N/A	N/A
2009/0141365	12/2008	Jannard et al.	N/A	N/A
2009/0147368	12/2008	Oh et al.	N/A	N/A
2009/0225438	12/2008	Kubota	N/A	N/A
2009/0279191	12/2008	Yu	N/A	N/A
2009/0303620	12/2008	Abe et al.	N/A	N/A
2010/0026878	12/2009	Seo	N/A	N/A
2010/0033844	12/2009	Katano	N/A	N/A
2010/0060995	12/2009	Yumiki et al.	N/A	N/A
2010/0165476	12/2009	Eguchi	N/A	N/A
2010/0214664	12/2009	Chia	N/A	N/A
2010/0277813	12/2009	Ito	N/A	N/A
2011/0001838	12/2010	Lee	N/A	N/A
2011/0032409	12/2010	Rossi et al.	N/A	N/A
2011/0080655	12/2010	Mori	N/A	N/A
2011/0102667	12/2010	Chua et al.	N/A	N/A
2011/0102911	12/2010	Iwasaki	N/A	N/A
2011/0115965	12/2010	Engelhardt et al.	N/A	N/A
2011/0149119	12/2010	Matsui	N/A	N/A
2011/0157430	12/2010	Hosoya et al.	N/A	N/A
2011/0188121	12/2010	Goring et al.	N/A	N/A
2011/0249347	12/2010	Kubota	N/A	N/A
2012/0062783	12/2011	Tang et al.	N/A	N/A
2012/0069455	12/2011	Lin et al.	N/A	N/A
2012/0092777	12/2011	Tochigi et al.	N/A	N/A
2012/0105708	12/2011	Hagiwara	N/A	N/A
2012/0147489	12/2011	Matsuoka	N/A	N/A
2012/0154929	12/2011	Tsai et al.	N/A	N/A
2012/0194923	12/2011	Um	N/A	N/A
2012/0229920	12/2011	Otsu et al.	N/A	N/A
2012/0262806	12/2011	Lin et al.	N/A	N/A
2013/0002933	12/2012	Topliss et al.	N/A	N/A
2013/0057971	12/2012	Zhao et al.	N/A	N/A
2013/0088788	12/2012	You	N/A	N/A
2013/0176479	12/2012	Wada	N/A	N/A
2013/0208178	12/2012	Park	N/A	N/A
2013/0271852	12/2012	Schuster	N/A	N/A
2013/0279032	12/2012	Suigetsu et al.	N/A	N/A
2013/0286488	12/2012	Chae	N/A	N/A
2014/0022436	12/2013	Kim et al.	N/A	N/A
2014/0063616	12/2013	Okano et al.	N/A	N/A
2014/0092487	12/2013	Chen et al.	N/A	N/A
2014/0139719	12/2013	Fukaya et al.	N/A	N/A
2014/0146216	12/2013	Okumura	N/A	N/A
2014/0160581	12/2013	Cho et al.	N/A	N/A
2014/0204480	12/2013	Jo et al.	N/A	N/A
2014/0240853	12/2013	Kubota et al.	N/A	N/A
2014/0285907	12/2013	Tang et al.	N/A	N/A
2014/0293453	12/2013	Ogino et al.	N/A	N/A
2014/0362274	12/2013	Christie et al.	N/A	N/A
2015/0022896	12/2014	Cho et al.	N/A	N/A
2015/0029601	12/2014	Dror et al.	N/A	N/A
2015/0116569	12/2014	Mercado	N/A	N/A
2015/0138431	12/2014	Shin et al.	N/A	N/A
2015/0153548	12/2014	Kim et al.	N/A	N/A
2015/0160438	12/2014	Okuda	N/A	N/A
2015/0168667	12/2014	Kudoh	N/A	N/A
2015/0177496	12/2014	Marks et al.	N/A	N/A
2015/0205068	12/2014	Sasaki	N/A	N/A

2015/0244942	12/2014	Shabtay et al.	N/A	N/A
2015/0253532	12/2014	Lin	N/A	N/A
2015/0253543	12/2014	Mercado	N/A	N/A
2015/0253647	12/2014	Mercado	N/A	N/A
2015/0323757	12/2014	Bone	N/A	N/A
2015/0373252	12/2014	Georgiev	N/A	N/A
2015/0373263	12/2014	Georgiev et al.	N/A	N/A
2016/0007008	12/2015	Molgaard et al.	N/A	N/A
2016/0033742	12/2015	Huang	N/A	N/A
2016/0044250	12/2015	Shabtay et al.	N/A	N/A
2016/0062084	12/2015	Chen et al.	N/A	N/A
2016/0062136	12/2015	Nomura et al.	N/A	N/A
2016/0070088	12/2015	Koguchi	N/A	N/A
2016/0085089	12/2015	Mercado	N/A	N/A
2016/0105616	12/2015	Shabtay et al.	N/A	N/A
2016/0187631	12/2015	Choi et al.	N/A	N/A
2016/0202455	12/2015	Aschwanden et al.	N/A	N/A
2016/0212333	12/2015	Liege et al.	N/A	N/A
2016/0241756	12/2015	Chen	N/A	N/A
2016/0291295	12/2015	Shabtay	N/A	N/A
2016/0306161	12/2015	Harada et al.	N/A	N/A
2016/0313537	12/2015	Mercado	N/A	N/A
2016/0341931	12/2015	Liu et al.	N/A	N/A
2016/0349504	12/2015	Kim et al.	N/A	N/A
2016/0353008	12/2015	Osborne	N/A	N/A
2017/0023778	12/2016	Inoue	N/A	N/A
2017/0094187	12/2016	Sharma et al.	N/A	N/A
2017/0102522	12/2016	Jo	N/A	N/A
2017/0115471	12/2016	Shinohara	N/A	N/A
2017/0153422	12/2016	Tang et al.	N/A	N/A
2017/0160511	12/2016	Kim et al.	N/A	N/A
2017/0199360	12/2016	Chang	N/A	N/A
2017/0276911	12/2016	Huang	N/A	N/A
2017/0310952	12/2016	Adomat et al.	N/A	N/A
2017/0329108	12/2016	Hashimoto et al.	N/A	N/A
2017/0337703	12/2016	Wu et al.	N/A	N/A
2018/0024319	12/2017	Lai et al.	N/A	N/A
2018/0048825	12/2017	Wang	N/A	N/A
2018/0059365	12/2017	Bone et al.	N/A	N/A
2018/0059376	12/2017	Lin et al.	N/A	N/A
2018/0081149	12/2017	Bae et al.	N/A	N/A
2018/0120674	12/2017	Avivi et al.	N/A	N/A
2018/0149835	12/2017	Park	N/A	N/A
2018/0196236	12/2017	Ohashi et al.	N/A	N/A
2018/0196238	12/2017	Goldenberg et al.	N/A	N/A
2018/0217475	12/2017	Goldenberg et al.	N/A	N/A
2018/0218224	12/2017	Olmstead et al.	N/A	N/A
2018/0224630	12/2017	Lee et al.	N/A	N/A
2018/0268226	12/2017	Shashua et al.	N/A	N/A
2019/0025549	12/2018	Hsueh et al.	N/A	N/A
2019/0025554	12/2018	Son	N/A	N/A
2019/0049687	12/2018	Bachar et al.	N/A	N/A
2019/0075284	12/2018	Ono	N/A	N/A
2019/0086638	12/2018	Lee	N/A	N/A
2019/0094500	12/2018	Tseng et al.	N/A	N/A
2019/0107651	12/2018	Sade	N/A	N/A
2019/0121216	12/2018	Shabtay et al.	N/A	N/A
2019/0155002	12/2018	Shabtay et al.	N/A	N/A
2019/0170965	12/2018	Shabtay	N/A	N/A
2019/0187443	12/2018	Jia et al.	N/A	N/A
2019/0187486	12/2018	Goldenberg et al.	N/A	N/A
2019/0196148	12/2018	Yao et al.	N/A	N/A
2019/0215440	12/2018	Rivard et al.	N/A	N/A
2019/0222758	12/2018	Goldenberg et al.	N/A	N/A
2019/0235202	12/2018	Smyth et al.	N/A	N/A
2019/0353874	12/2018	Yeh et al.	N/A	N/A
2020/0084358	12/2019	Nadamoto	N/A	N/A
2020/0192069	12/2019	Makeev et al.	N/A	N/A
2020/0221026	12/2019	Fridman et al.	N/A	N/A
2020/0241233	12/2019	Shabtay et al.	N/A	N/A
2020/0333691	12/2019	Shabtay et al.	N/A	N/A
2020/0400926	12/2019	Bachar	N/A	N/A
2021/0048628	12/2020	Shabtay et al.	N/A	N/A
2021/0048649	12/2020	Goldenberg et al.	N/A	N/A
2021/0165192	12/2020	Goldenberg et al.	N/A	N/A

2021/0231914	12/2020	Chang	N/A	G02B 3/04
2021/0263276	12/2020	Huang et al.	N/A	N/A
2021/0364746	12/2020	Chen	N/A	N/A
2021/0396974	12/2020	Kuo	N/A	N/A
2022/0046151	12/2021	Shabtay et al.	N/A	N/A
2022/0066168	12/2021	Shi	N/A	N/A
2022/0113511	12/2021	Chen	N/A	N/A
2022/0206264	12/2021	Rudnick et al.	N/A	N/A
2022/0232167	12/2021	Shabtay et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101634738	12/2009	CN	N/A
102147519	12/2010	CN	N/A
102193162	12/2010	CN	N/A
102466865	12/2011	CN	N/A
102466867	12/2011	CN	N/A
102147519	12/2012	CN	N/A
103576290	12/2013	CN	N/A
103698876	12/2013	CN	N/A
104297906	12/2014	CN	N/A
104407432	12/2014	CN	N/A
105467563	12/2015	CN	N/A
105657290	12/2015	CN	N/A
106680974	12/2016	CN	N/A
104570280	12/2016	CN	N/A
S54157620	12/1978	JP	N/A
S59121015	12/1983	JP	N/A
6165212	12/1985	JP	N/A
S6370211	12/1987	JP	N/A
H0233117	12/1989	JP	N/A
406059195	12/1993	JP	N/A
H07325246	12/1994	JP	N/A
H07333505	12/1994	JP	N/A
H09211326	12/1996	JP	N/A
H11223771	12/1998	JP	N/A
2000131610	12/1999	JP	N/A
2000292848	12/1999	JP	N/A
3210242	12/2000	JP	N/A
2004334185	12/2003	JP	N/A
2006195139	12/2005	JP	N/A
2007133096	12/2006	JP	N/A
2007164065	12/2006	JP	N/A
2007219199	12/2006	JP	N/A
2007306282	12/2006	JP	N/A
2008111876	12/2007	JP	N/A
2008191423	12/2007	JP	N/A
2010032936	12/2009	JP	N/A
2010164841	12/2009	JP	N/A
2011145315	12/2010	JP	N/A
2011151448	12/2010	JP	N/A
2012203234	12/2011	JP	N/A
2012230323	12/2011	JP	N/A
2013003317	12/2012	JP	N/A
2013003754	12/2012	JP	N/A
2013101213	12/2012	JP	N/A
2013105049	12/2012	JP	N/A
2013106289	12/2012	JP	N/A
2013148823	12/2012	JP	N/A
2014142542	12/2013	JP	N/A
2017116679	12/2016	JP	N/A
2018059969	12/2017	JP	N/A
2019113878	12/2018	JP	N/A
20080088477	12/2007	KR	N/A
20090019525	12/2008	KR	N/A
20090131805	12/2008	KR	N/A
20110058094	12/2010	KR	N/A
20110115391	12/2010	KR	N/A
20120068177	12/2011	KR	N/A
20140135909	12/2012	KR	N/A
20140023552	12/2013	KR	N/A
20160000759	12/2015	KR	N/A
101632168	12/2015	KR	N/A
20160115359	12/2015	KR	N/A
M602642	12/2019	TW	N/A

2013058111	12/2012	WO	N/A
2013063097	12/2012	WO	N/A
2018130898	12/2017	WO	N/A

OTHER PUBLICATIONS

A compact and cost effective design for cell phone zoom lens, Chang et al., Sep. 2007, 8 pages. cited by applicant
Consumer Electronic Optics: How small a lens can be? The case of panomorph lenses, Thibault et al., Sep. 2014, 7 pages. cited by applicant
Optical design of camera optics for mobile phones, Steinich et al., 2012, pp. 51-58 (8 pages). cited by applicant
The Optics of Miniature Digital Camera Modules, Bareau et al., 2006, 11 pages. cited by applicant
Modeling and measuring liquid crystal tunable lenses, Peter P. Clark, 2014, 7 pages. cited by applicant
Mobile Platform Optical Design, Peter P. Clark, 2014, 7 pages. cited by applicant
Boye et al., "Ultrathin Optics for Low-Profile Innocuous Imager", Sandia Report, 2009, pp. 56-56. cited by applicant
"Cheat sheet: how to understand f-stops", Internet article, Digital Camera World, 2017. cited by applicant
Husain Sumra: "Security Camera Field Of View Tips—How ToPosition Your Camera I Ooma", Aug. 2, 2019 (Aug. 2, 2019), XP093206028,
Retrieved from the Internet: URL:https://www.ooma.com/blog/home-security/how-to-positionyour-. cited by applicant
Office Action in related EP patent application 21847019.3, dated Sep. 24, 2024. cited by applicant
Office Action in related CN patent application 202180004577.8, dated Nov. 13, 2024. cited by applicant

---

Background/Summary

CROSS REFERENCE TO EXISTING APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/607,400 filed Oct. 29, 2021 (now allowed), which was a 371 application from international patent application No. PCT/IB2021/056357 filed Jul. 14, 2021, and is related to and claims the benefit of U.S. Provisional patent application 63/054,862 filed Jul. 22, 2020, which is incorporated herein by reference in its entirety.

FIELD
(1) The presently disclosed subject matter is related generally to the field of digital cameras and in particular to folded optical designs in such cameras.
Definitions
(2) In this application and for optical and other properties mentioned throughout the description and figures, the following symbols and abbreviations are used, all of which are known in the art: Total track length (TTL): the maximal distance, measured along a direction parallel to the optical axis, between a point of the front surface S_1 of a first lens element L_1 of a lens (or "lens assembly") and an image sensor, when a camera system including the lens is focused to an infinity object distance. Back focal length (BFL): the minimal distance, measured along a direction parallel to the first optical axis, between a point of the rear surface S_{2N} of a last lens element L_N of a lens (or "lens assembly") and the image sensor, when a camera system including the lens is focused to an infinity object distance. Effective focal length (EFL): the distance between a rear principal point P′ and a rear focal point F′ of a lens assembly of lens elements L_1 to L_N. f-number, (f/#): the ratio of the EFL to an entrance pupil diameter.
BACKGROUND
(3) Dual-cameras or triple-cameras (or multi-cameras in general) for mobile devices such as smartphones are known. In a typical triple-camera, one camera has an Ultra-Wide (UV) field of view (FOV) FOV_{UW}, another camera has a Wide field of view FOV_W narrower than FOV_{UW} and yet another camera has Tele field of view FOV_T narrower than FOV_W. These cameras are also referred to herein as, respectively, an Ultra-Wide (or UW) camera, a Wide (or W) camera and a Tele (or T) camera. In general, the Wide camera is considered to be a smartphone's main camera.
(4) The f-number ("f/#") of a camera lens is the ratio of the effective focal length (EFL) to the diameter D of the camera's entrance pupil: $f/\# = EFL/D$. The entrance pupil is the optical image of the aperture stop, as 'seen' through the front aperture of the lens system. The front aperture is the object-sided aperture of the lens. A low f/# is desired for a smartphone's main camera as it has 3 major advantages: good low light sensitivity, strong "natural" Bokeh effect and high image resolution, discussed next:
(5) 1. Low light sensitivity is a major performance drawback of today's mobile device compatible cameras when compared to e.g. digital single-lens reflex (DSLR) cameras. As an example, halving a camera's f/#(for same EFL) increases the aperture area by a factor of 4, meaning that 4 times more light enters the camera. This difference is especially relevant when capturing low light scenes.
(6) 2. Bokeh is the aesthetic quality of the blur produced in the out-of-focus segments of an image, and it is a highly demanded feature for today's smartphones. The Bokeh effect correlates inversely with the depth of field (DOF) of an image, wherein $DOF \sim f/\#$. A low f/# is beneficial for supporting strong "natural" Bokeh effects. As the f/#s present in today's smartphone cameras do not provide sufficient "natural" Bokeh, the demand for strong Bokeh is answered by "artificial" Bokeh, i.e. artificially applying blur to out-of-focus image segments.
(7) 3. Image sensors with continuously increasing pixel resolution are entering mobile devices, exceeding 100 megapixel in 2019 for the first time. This (amongst other factors) is achieved by shrinking the size of single pixels, i.e. increasing the spatial pixel frequency. For translating pixel resolution to image resolution, a camera's lens must support the spatial pixel frequency k_{Pixel} of the sensor. For a well-designed (diffraction-limited) camera lens, the resolvable spatial frequency of the lens k_{Lens} depends inversely on the f/#: $k_{Lens} \sim 1/f/\#$, i.e. a lower f/# corresponds to a higher image resolution (assuming an image sensor with sufficient spatial pixel frequency).
(8) The latest premium smartphones are equipped with main Wide cameras that have f/# of about f/1.9 (Huawei P40 Pro) and f/1.8 (Apple iphone 11 Pro Max). A major challenge in low f/# cameras is the design of lenses that correct for the strong aberration imposed by the large front apertures required, e.g. for correction of chromatic aberration. This is usually tackled by a more complex lens design that includes a larger number of lens elements. However, this generally leads to larger total track length (TTL) and larger camera module heights, what is detrimental to the goal of slim smartphone design.
(9) A recent development in mobile Tele cameras involves using a prism to "fold" the Tele camera: a reflecting or optical path folding element ("OPFE") is added to the optical path in order to "fold" (tilt) the light propagation direction from perpendicular to the back surface of a host device to parallel to the host device's back surface. Folded cameras allow large TTLs in a slim camera design.
(10) For improving a smartphone's main camera it would be beneficial to have a folded Wide camera designs with low f/#.
SUMMARY
(11) In various embodiments there are provided folded cameras, comprising: a lens with N 7 lens elements L_i, having an effective focal length

(EFL), each L.sub.i having a respective focal length f.sub.i wherein a first lens element L.sub.1 faces an object side; an image sensor; and an OPFE for providing a folded optical path between an object and the lens, to the lens optical axis, wherein a folded camera has a total track length (TTL), wherein an aperture stop of the lens is located closer to a first surface of the first lens element facing the object than a distance d that fulfills d/TTL=0.2, and wherein an f number f/# of the camera is smaller than 1.2.

(12) In various embodiments there are provided folded cameras, comprising: a lens having an effective focal length (EFL) and including N≥7 lens elements L.sub.i having a first optical axis, each lens element having a respective focal length f.sub.i and comprising a respective front surface S.sub.2i-1 and a respective rear surface S.sub.2i, the lens element surfaces marked S.sub.k where 1≤k≤2N, wherein each lens element surface S.sub.k has a clear height value CH(S.sub.k), wherein clear height value CH(S.sub.17) of surface S.sub.17 is greater than or equal to a clear height value of each of surfaces S.sub.2 to S.sub.2N-1; an image sensor; and an OPFE for providing a folded optical path between an object and the lens elements, and wherein an f number f/# of the camera is smaller than 1.2.

(13) In some embodiments, f/#<1.1.

(14) In some embodiments, f/#≤1.0.

(15) In some embodiments, 0.8<f/#≤1.0.

(16) In some embodiments, a folded camera as above or below has a diagonal FOV that is larger than 60 degrees.

(17) In some embodiments, |f.sub.i|>4.Math.EFL for 1≤i≤3.

(18) In some embodiments, |f.sub.i|>5.Math.EFL for 1≤i≤3.

(19) In some embodiments, L.sub.5 is the lens element with the strongest optical power, i.e. |f.sub.5|<|f.sub.i| for i≠5.

(20) In some embodiments, f.sub.5<EFL.

(21) In some embodiments, a lens sub-system including lens elements L.sub.4 and L.sub.5 has positive refractive power.

(22) In some embodiments, focal lengths f.sub.4 of L.sub.4 and f.sub.5 of L.sub.5 satisfy |f.sub.4|<4.Math.f.sub.5.

(23) In some embodiments, focal lengths f.sub.4 of L.sub.4 and f.sub.5 of L.sub.5 satisfy |f.sub.4|<3.Math.f.sub.5.

(24) In some embodiments, the lens includes at least one air gap between lens elements that comply with the condition STD<0.020, where STD is a normalized gap standard deviation.

(25) In some embodiments, the lens includes at least one air gap between lens elements that comply with the condition STD<0.010, where STD is a normalized gap standard deviation.

(26) In some embodiments, an air gap between lens elements L.sub.4 and L.sub.5 satisfies STD<0.020, where STD is a normalized gap standard deviation.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Non-limiting examples of embodiments disclosed herein are described below with reference to figures attached hereto that are listed following this paragraph. The drawings and descriptions are meant to illuminate and clarify embodiments disclosed herein, and should not be considered limiting in any way. Like elements in different drawings may be indicated by like numerals. Elements in the drawings are not necessarily drawn to scale. In the drawings:

(2) FIG. **1**A illustrates a known digital folded camera that may operate as a Wide camera in a perspective view;

(3) FIG. **1**B shows the camera of FIG. **1**A in a side view;

(4) FIG. **1**C illustrates a known dual camera that includes a folded camera as in FIGS. **1**A and **1**B together with an "upright" (non-folded) camera;

(5) FIG. **2**A shows a schematic view of a folded optical lens system according to some examples of the presently disclosed subject matter;

(6) FIG. **2**B shows a schematic view of another folded optical lens system according to some examples of the presently disclosed subject matter;

(7) FIG. **2**C shows a schematic view of yet another folded optical lens system according to some examples of the presently disclosed subject matter;

(8) FIG. **2**D shows a schematic view of yet another folded optical lens system according to some examples of the presently disclosed subject matter;

(9) FIG. **2**E depicts schematically yet another folded optical lens system disclosed herein;

(10) FIG. **3**A illustrates the orthogonal projections IP.sub.orth,1, IP.sub.orth,2 of two impact points IP.sub.1 and IP.sub.2 on a plane P that is orthogonal to the optical axis of the lens of the system in FIGS. **2**A-**2**D;

(11) FIG. **3**B illustrates the orthogonal projections IP.sub.orth,3, IP.sub.orth,4 of two impact points IP.sub.3 and IP.sub.4 on a plane P that is orthogonal to the optical axis of the lens of the system in FIGS. **2**A-**2**D;

(12) FIG. **4** provides graphically a definition of clear height;

(13) FIG. **5** provides graphically a definition of clear aperture;

(14) FIG. **6** provides a graphical illustration of diameter H.sub.Li of lens element L.sub.i;

(15) FIG. **7** shows an exploded view of lens elements illustrating lens element width W.sub.Li and height H.sub.Li.

DETAILED DESCRIPTION

(16) In the following detailed description, numerous specific details are set forth in order to provide a thorough understanding. However, it will be understood by those skilled in the art that the presently disclosed subject matter may be practiced without these specific details. In other instances, well-known methods have not been described in detail so as not to obscure the presently disclosed subject matter.

(17) It is appreciated that certain features of the presently disclosed subject matter, which are, for clarity, described in the context of separate embodiments, may also be provided in combination in a single embodiment. Conversely, various features of the presently disclosed subject matter, which are, for brevity, described in the context of a single embodiment, may also be provided separately or in any suitable sub-combination.

(18) Furthermore, for the sake of clarity the term "substantially" is used herein to imply the possibility of variations in values within an acceptable range. According to one example, the term "substantially" used herein should be interpreted to imply possible variation of up to 10% over or under any specified value. According to another example, the term "substantially" used herein should be interpreted to imply possible variation of up to 5% over or under any specified value. According to a further example, the term "substantially" used herein should be interpreted to imply possible variation of up to 2.5% over or under any specified value.

(19) FIGS. **1**A and **1**B illustrate a known digital folded camera **100**, which may operate for example as a Wide camera. Camera **100** comprises an optical path folding element (OPFE) **102** e.g. a prism, a lens **104** with a plurality of lens elements (not visible in this representation, but visible e.g. in FIGS. **2**A-D) and an image sensor **106**. In some embodiments (as in FIGS. **2**A-**2**D), the lens elements are axial symmetric along a first optical axis **108**. In other embodiments the lens elements may not be axial symmetric. For example, lens elements may be cut (or diced or sliced) to a non-circular shape, as e.g. demonstrated in FIG. **2**B.

(20) At least some of the lens elements can be held by a structure called a "barrel" **110**. The barrel may have a longitudinal symmetry along optical axis **108**. In FIGS. **1**A to **1**C, the cross-section of this barrel is circular. This is however not mandatory and other shapes can be used, e.g. for hosting cut lens elements.

(21) The path of the optical rays from an object (not shown) to image sensor **106** defines an optical path (see optical paths **112** and **114**, which represent portions of the optical path).

(22) OPFE folds the optical path from a first optical path **112** to a second optical path **114**. Optical path **114** is substantially parallel to the optical axis **108**. The optical path is thus referred to as "folded optical path" (indicated by optical paths **112** and **114**) and camera **100** is referred to as "folded

camera".

(23) In particular, in some examples, OPFE **102** is inclined at substantially 45° with respect to optical axis **108**. In FIG. **1**A, OPFE **102** is also inclined at substantially 45° with respect to optical path **112**.

(24) In some known examples, image sensor **106** lies in a X-Y plane substantially perpendicular to optical axis **108**. This is however not limiting and the image sensor **106** can have a different orientation. For example, and as described in WO 2016/024192, image sensor **106** can be in the XZ plane. In this case, an additional OPFE can be used to reflect the optical rays towards image sensor **106**.

(25) Two cameras, for example a Wide camera **100** and a regular UW camera **130** may be included in a digital camera **150** (also referred to as dual-camera). A possible configuration is shown in FIG. **1**C.

(26) UW camera **130** may include an aperture **132** (indicating object side of the camera) and an optical lens system **134** (or "Wide lens module") with a symmetry (and optical) axis **136** in the Y direction, as well as a UW image sensor **138**. The UW camera comprises a UW lens system configured to provide a UW image. As already indicated above, the UW camera has a field of view FOV.sub.UW larger than the field of view of the Wide camera FOV.sub.W. For example, FOV.sub.UW may be 80-130 degrees and FOV.sub.W may be 60-90 deg. Notably, in other examples, a plurality of Wide cameras and/or a plurality of Tele cameras can be incorporated and operative in a single digital camera. The FOV.sub.T of a Tele camera may be for example 20-50 degrees.

(27) Attention is now drawn to FIG. **2**A which depicts schematically an optical lens system disclosed herein and numbered **200**. Lens system **200** comprises an OPFE **202**, a lens (or "lens assembly") **204**, an optical element **206** and an image sensor **208**. System **200** is shown with ray tracing. Optical element **206** may be for example infra-red (IR) filter, and/or a glass image sensor dust cover. Optical rays (after their reflection by prism **202**) pass through lens **204** and form an image on image sensor **208**. FIG. **2**A shows 3 fields with 3 rays for each: the upper marginal-ray, the lower marginal-ray and the chief-ray. In the example of FIG. **2**A, the optical rays pass through optical element **206** before impinging on image sensor **208**. This is however not limiting, and in some examples, optical element **206** is not present, i.e. in some lens systems, the optical element is optional.

(28) Lens **204** includes a plurality of N lens elements L.sub.i **220** (wherein "i" is an integer between 1 and N). L.sub.1 is the lens element closest to the object (prism) side and L.sub.N is the lens element closest to the image side, i.e. the side where the image sensor is located. This order holds for all lenses and lens elements disclosed herein. Lens elements L.sub.i can be used e.g. as lens elements of camera **100** above. The N lens elements are axial symmetric along an optical axis **210**. Each lens element L.sub.i comprises a respective front surface S.sub.2i-1 (the index "2i−1" being the number of the front surface) and a respective rear surface S.sub.2i (the index "2i" being the number of the rear surface), where "i" is an integer between 1 and N. This numbering convention is used throughout the description. Alternatively, as done throughout this description, lens surfaces are marked as "S.sub.k", with k running from 1 to 2N. The front surface and the rear surface can be in some cases aspherical. This is however not limiting.

(29) As used herein the term "front surface" of each lens element refers to the surface of a lens element located closer to the entrance of the camera (camera object side) and the term "rear surface" refers to the surface of a lens element located closer to the image sensor (camera image side).

(30) In lens system **200**, a first horizontal surface of the prism (oriented along Z direction), marked as T**1**, is 10.93 mm. A second horizontal surface of the prism (oriented along the X direction, not shown) and marked T**2** is 12.6 mm. The vertical surface of the prism (along Y) marked V is 8.68 mm. The angle of the prism is 45 deg. The relatively large prism size allows for a high amount of light entering the camera, which allows the camera to have in this example a low f/# of 1.0. In other embodiments, f/# may be 0.8-1.2. The aperture stop of lens **204** is located at a distance d=−0.042 mm from S.sub.2, i.e. from the first surface of the first lens element. For the non-zero fields shown in lens system **200**, about 80% of light reaches image sensor **208**.

(31) As explained below, a clear height value CH(S.sub.k) can be defined for each surface S.sub.k for 1≤k≤2N), and a clear aperture value CA(S.sub.k) can be defined for each surface S.sub.k for 1≤k≤2N). CA(S.sub.k) and CH(S.sub.k) define optical properties of each surface S.sub.k of each lens element. The CH term is defined with reference to FIG. **4** and the CA term is defined with reference to FIG. **5**, below.

(32) In addition a height ("H.sub.Li", for 1≤i≤N) is defined for each lens element L.sub.i. H.sub.Li corresponds, for each lens element L.sub.i, to the maximal height of lens element L.sub.i measured along a direction perpendicular to the optical axis of the lens elements. For a given lens element, the height is greater than, or equal to the clear height value CH and the clear aperture value CA of the front and rear surfaces of this given lens element. Typically, for an axial symmetric lens element, H.sub.Li is the diameter of lens element L.sub.i as seen in FIG. **6**. Typically, for an axial symmetric lens element, H.sub.Li=max{CA(S.sub.2i-1), CA(S.sub.2i)}+mechanical part size.

(33) In general, in lens design the mechanical part size is defined as not contributing to the optical properties of the lens. Because of this, one defines two heights of a lens: an optical height H.sub.opt (corresponding to the CA value) of an optically active area (dotted) and a geometrical (or mechanical) height of the lens H.sub.L which covers an optically active and an optically inactive area. The mechanical part size contribution to H.sub.Li is typically 200-1000 μm.

(34) In lens **204**, the clear aperture of the last surface S.sub.17 of the last lens element L.sub.8, CA.sub.17, is larger than the CA of all other surfaces S.sub.i of the lens elements, i.e. CA.sub.17>CA.sub.i for i<17. The CA of the first surface S.sub.16 of last lens element L.sub.8, CA.sub.16, is larger than the CA of all preceding surfaces S.sub.i of the lens elements, i.e. CA.sub.16>CA.sub.i for i<16.

(35) In lens system **200**, N is equal to eight. This is however not limiting and a different number of lens elements can be used. According to some examples, N is equal to or greater than 7. For example, N can be equal to 7, 8, 9 or 10.

(36) In lens system **200**, some of the surfaces of the lens elements are represented as convex, and some are represented as concave. The representation of FIG. **2**A is however not limiting and a different combination of convex and/or concave surfaces can be used, depending on various factors such as the application, the desired optical power, etc.

(37) A lens barrel such as lens barrel **110** may carry lens **204**. In some embodiments the lens barrel may be circular such as lens barrel **110**. In other embodiments the lens barrel may be not be circular but may have a shape such as the lens elements in FIG. **7**. Referring to FIG. **7**, a non-circular lens barrel may have a X axis or a Y axis as symmetry axis. A non-circular lens barrel may e.g. be shaped according to the cut lens elements of a lens such as lens **204**′. The height of a lens barrel may be only slightly higher than the lens element having the largest height in the lens. E.g. a lens barrel may be 0-0.5 mm higher than the highest lens element. A lens barrel having an identical height as the highest lens element is described for example in co-owned international patent application PCT/IB2018/050988, which is incorporated herein by reference in its entirety.

(38) As shown in FIGS. **3**A, **3**B and **4**, each optical ray that passes through a surface S.sub.k (for 1≤k≤2N) impinges this surface on an impact point IP. Optical rays enter optical lens system **200** from surface S.sub.1 and pass through surfaces S.sub.2 to S.sub.2N. Some optical rays can impinge on any surface S.sub.k but cannot/will not reach image sensor **208**. For a given surface S.sub.k, only optical rays that can form an image on image sensor **208** are considered. CH(S.sub.k) is defined as the distance between two closest possible parallel lines, see lines **400** and **402** in FIG. **4** located on a plane P orthogonal to the optical axis of the lens elements. In the representation of FIGS. **3**A and **3**B, plane P is parallel to plane X-Y and is orthogonal to optical axis **103** such that the orthogonal projection IP.sub.orth of all impact points IP on plane P is located between the two parallel lines. CH(S.sub.k) can be defined for each surface S.sub.k (front and rear surfaces, with 1≤k≤2N).

(39) The definition of CH(S.sub.k) does not depend on the object currently imaged, since it refers to the optical rays that "can" form an image on the image sensor. Thus, even if the currently imaged object is located in a black background that does not produce light, the definition does not refer to this black background since it refers to any optical rays that "can" reach the image sensor to form an image (for example optical rays emitted by a background which would emit light, contrary to a black background).

(40) For example, FIG. **3**A illustrates the orthogonal projections IP.sub.orth,1, IP.sub.orth,2 of two impact points IP.sub.1 and IP.sub.2 on plane P which is orthogonal to optical axis **103**. By way of example, in the representation of FIG. **3**A, surface S.sub.k is convex.

(41) FIG. **3**B illustrates the orthogonal projections IP.sub.orth,3, IP.sub.orth,4 of two impact points IP.sub.3 and IP.sub.4 on plane P. By way of example, in the representation of FIG. **3**B, surface S.sub.k is concave.

(42) In FIG. **4**, the orthogonal projection IP.sub.orth of all impact points IP of a surface S.sub.k on plane P is located between parallel lines **400** and **402**. CH(S.sub.k) is thus the distance between lines **400** and **402**.

(43) Attention is drawn to FIG. **5**. According to the presently disclosed subject matter, a clear aperture CA(S.sub.k) is defined for each given surface S.sub.k(for 1≤k≤2N) as the diameter of a circle, wherein the circle is the smallest possible circle located in a plane P orthogonal to the optical axis **108** and encircling all orthogonal projections IP.sub.orth of all impact points on plane P. As mentioned above with respect to CH(S.sub.k), it is noted that the definition of CA(S.sub.k) also does not depend on the object which is currently imaged.

(44) As shown in FIG. **5**, the circumscribed orthogonal projection IP.sub.orth of all impact points IP on plane P is a circle **500**. The diameter of circle **500** defines CA(S.sub.k).

(45) Detailed optical data and surface data are given in Tables 1-3 for the example of the lens elements in FIG. **2**A. The values provided for these examples are purely illustrative and according to other examples, other values can be used.

(46) Surface types are defined in Table 1 and the coefficients for the surfaces are defined in Table 2:

(47) Surface types are: a) Plano: flat surfaces, no curvature b) Q type 1 (QT1) surface sag formula:

(48)

$$z(r) = \frac{cr^2}{1 + \sqrt{1 - (1+k)c^2 r^2}} + D_{con}(u) \quad D_{con}(u) = u^4 \cdot \text{Math.}_{n=0}^{N} A_n Q_n^{con}(u^2) \quad u = \frac{r}{r_{norm}}, x = u^2 \quad Q_0^{con}(x) = 1 \quad Q_1^{con} = \text{-}(5 - 6x) \quad Q_2^{con} = 15 - 14x(3 - 2x) \quad Q_3^{con} = \text{-}\{35 - 12$$

where {z, r} are the standard cylindrical polar coordinates, c is the paraxial curvature of the surface, k is the conic parameter, r.sub.norm is generally one half of the surface's clear aperture, and A.sub.n are the polynomial coefficients shown in lens data tables. The Z axis is positive

(49) TABLE-US-00001 TABLE 1 Lens system 200 EFL = 4.14 mm, F/# = 1.00, Diagonal FOV = 80.4 deg. Aperture Surface Curvature Radius Abbe Focal # Comment Type Radius Thickness (D/2) Material Index # Length 1 A.S Plano Infinity −0.042 2.078 2 Lens 1 QT1 −3.314 0.354 2.078 Plastic 1.54 55.9 26.78 3 −2.804 0.058 2.018 4 Lens 2 QT1 11.125 0.294 2.002 Plastic 1.66 20.4 −55.77 5 8.474 0.040 2.010 6 Lens 3 QT1 2.122 0.359 1.967 Plastic 1.65 21.5 34.22 7 2.186 0.355 2.050 8 Lens 4 QT1 9.582 0.256 2.065 Plastic 1.67 19.4 −7.46 9 3.266 0.061 2.305 10 Lens 5 QT1 4.164 1.565 2.357 Plastic 1.54 55.9 3.38 11 −2.887 0.219 2.481 12 Lens 6 QT1 −3.676 1.591 2.579 Plastic 1.54 55.9 99.93 13 −3.971 0.040 2.583 14 Lens 7 QT1 2.537 0.912 2.436 Plastic 1.67 19.4 13.54 15 3.002 0.801 2.852 16 Lens 8 QT1 8.867 0.354 2.974 Plastic 1.66 20.4 −8.81 17 3.479 0.259 3.285 18 Filter Plano Infinity 0.210 — Glass 1.52 64.2 19 Infinity 0.610 — 20 Image Plano Infinity — —

towards image. Values for CA are given as a clear aperture radius, i.e. CA/2. The reference wavelength is 555.0 nm. Units are in mm except for refraction index ("Index") and Abbe #. Each lens element L.sub.i has a respective focal length f.sub.i, given in Table 1.

(50) TABLE-US-00002 TABLE 2 Aspheric Coefficients Surface # R.sub.norm A0 A1 A2 A3 2 1.96E+00 7.01E−01 −4.57E−02 1.03E−02 −9.49E−04 3 1.98E+00 8.98E−01 −9.70E−02 1.92E−02 −5.01E−03 4 1.96E+00 −7.58E−02 −8.16E−02 1.72E−02 1.98E−03 5 1.90E+00 −2.09E−01 −2.62E−02 7.39E−03 2.93E−03 6 1.76E+00 −6.48E−01 −4.85E−02 −2.11E−03 −1.95E−03 7 1.79E+00 −7.12E−01 −5.06E−02 4.56E−03 −4.47E−04 8 1.80E+00 −2.24E−01 −7.75E−03 7.30E−03 −1.86E−03 9 1.84E+00 −2.52E−01 1.46E−02 2.39E−03 −3.73E−03 10 1.98E+00 −1.56E−01 −3.39E−04 1.13E−03 −7.45E−04 11 2.04E+00 5.32E−01 −7.05E−02 6.97E−03 3.13E−04 12 2.14E+00 8.97E−01 −1.12E−01 1.97E−02 −2.85E−03 13 2.09E+00 1.58E−02 2.61E−02 −4.19E−03 7.93E−04 14 2.13E+00 −7.72E−01 −5.12E−02 −1.16E−02 −6.42E−04 15 2.63E+00 −1.11E+00 −1.05E−01 4.11E−02 −2.53E−05 16 2.73E+00 −9.92E−01 1.86E−01 2.37E−02 −1.12E−02 17 3.20E+00 −2.04E+00 1.88E−01 −6.16E−02 −2.74E−02 Surface # A4 A5 A6 A7 A8 2 1.37E−04 3.42E−05 1.55E−06 0.00E+00 0.00E+00 3 8.19E−04 −1.08E−04 5.14E−06 0.00E+00 0.00E+00 4 −8.58E−04 5.69E−05 −2.90E−04 0.00E+00 0.00E+00 5 −1.76E−03 5.55E−04 −2.96E−04 0.00E+00 0.00E+00 6 −7.14E−04 1.16E−04 3.39E−05 0.00E+00 0.00E+00 7 −2.33E−04 −4.64E−05 2.51E−05 0.00E+00 0.00E+00 8 8.01E−04 −2.83E−04 1.97E−05 0.00E+00 0.00E+00 9 1.36E−03 −2.35E−04 1.55E−05 0.00E+00 0.00E+00 10 6.24E−04 −1.91E−04 1.83E−05 0.00E+00 0.00E+00 11 −2.57E−04 6.98E−05 −5.72E−06 0.00E+00 0.00E+00 12 3.28E−04 −1.68E−05 −7.24E−07 0.00E+00 0.00E+00 13 −1.38E−04 2.67E−05 −2.84E−06 0.00E+00 0.00E+00 14 −4.12E−04 3.26E−04 −2.63E−04 1.47E−04 −3.10E−05 15 4.72E−03 −3.18E−03 7.16E−05 −2.80E−04 1.03E−04 16 7.44E−03 −5.47E−03 4.68E−04 3.29E−04 −3.43E−05 17 1.30E−02 −4.97E−03 2.36E−03 −2.23E−03 4.96E−04

(51) In the example of FIG. **2**A, the following optical properties are achieved: TTL=8.34 mm BFL=1.08 mm EFL=4.14 mm

(52) CA(S_{17}) > CA(S_k), 1 < k ≤ 2N CA(S_{16}) > CA(S_k), 1 < k ≤ 2N - 1 CA(S_{15}) > CA(S_k), 1 < k < 2N - 2 f/#=1.0 Sensor diagonal (SD) is 7 mm, sensor width/height ratio is 4:3 Minimum CA/SD ratio: CA(S.sub.4)/SD=0.57 Maximum CA/SD ratio: CA(S.sub.17)/SD=0.94 Diagonal FOV=80.44 deg, Horizontal FOV=68.32 deg, Vertical FOV=53.48 deg, Distance d from aperture stop to S.sub.2: d=−0.042 mm L.sub.1, L.sub.2 and L.sub.3 have relatively low power (magnitude), so |f.sub.i|>5.Math.EFL for 1≤i≤3 L.sub.4 and L.sub.5 together have positive power, so for the lens sub-system including L.sub.4 and L.sub.5 at a thickness d apart from each other and as given in Table 1 which has focal length 1/(f.sub.4+f.sub.5)= [1/f.sub.4+1/f.sub.5−d/(f.sub.4f.sub.5)]>0 For L.sub.5 yields: f.sub.5<EFL L.sub.4 and L.sub.5 satisfy: |f.sub.4|<3×f.sub.5 Minimal gap between L.sub.4 and L.sub.5: Gap.sub.Min=0.04 mm Maximal gap between L.sub.4 and L.sub.5: Gap.sub.Max=0.0745 mm Average gap AVG.sub.4 between L.sub.4 and L.sub.5: AVG.sub.4=0.048 mm STD.sub.4 from average gap AVG.sub.4(r) between L.sub.4 and L.sub.5: STD.sub.4=3.42.Math.10.sup. −3 mm.

Lens **204** may be carried by a lens barrel having a lens barrel height of e.g. 6.57 mm-7.2 mm.

(53) In this specification, a "gap" or an "air gap" refers to the space between consecutive lens elements. In the case of lens elements **4** and **5**, "gap" refers to the air space between the last surface of L.sub.4 and the first surface of L.sub.5.

(54) A number of functions and constants per gap are defined:

(55) 1. A "Gap.sub.i(r)" function, (where i is the lens element number and r is the same variable used in Eq. 1) is: a) for i=1: Gap.sub.1(r)=z(r) of L.sub.2S.sub.1+(the distance along the second optical axis between the prism exit surface and L.sub.2S.sub.1); b) for i>1: Gap.sub.i(r)=z(r) of L.sub.i+1S.sub.1+(the distance along the second optical axis between L.sub.iS.sub.2 and L.sub.i+1S.sub.1)−z(r) of L.sub.iS.sub.2; c) for r=0, an "on-axis gap" (OA_Gap.sub.i) is defined as Gap.sub.i(r=0);

(56) 2. A "gap average" (AVG.sub.i) constant is given by:

(57) $\quad AVG_i = \frac{1}{N+1/2} \cdot \text{Math.}_{j=0}^{N} Gap_i\left(\frac{j.\text{Math.}\, r_{norm}}{N}\right)$ (Eq. 2)

where j is a discrete variable that runs from 0 to N, where N is an integer >10, and where r.sub.norm is the minimum value D/2 of surfaces {L.sub.iS.sub.2, L.sub.i+1S.sub.1}.

(58) 3. A normalized gap standard deviation (STD.sub.i) constant is given by:

(59) $\quad STD_i = \frac{1}{r_{norm}} \sqrt{\frac{1}{N-1/2} \cdot \underset{j=0}{\overset{N}{\text{Math.}}} \left(Gap_i\left(\frac{j.\text{Math.}\, r_{norm}}{N}\right) - AVG_i\right)^2}$ (Eq. 3)

where r.sub.norm is the minimum value D/2 of surfaces {L.sub.iS.sub.2, L.sub.i+1S.sub.1}, N is an integer >10, and AVG.sub.i is defined as in (Eq.2).

(60) Attention is now drawn to FIG. **2**B, which depicts schematically another optical lens system disclosed herein and numbered **200′**. Lens system **200′** comprises an OPFE **202**, a lens **204′** with a plurality of lens elements, an optical element **206** and an image sensor **208**. Ray tracing is provided as in FIG. **2**A. Detailed optical data and surface data are given in Tables 1 and 2. However, data on aperture radius for all surfaces of L.sub.6 and L.sub.8 as well as surface S.sub.15 of L.sub.7 is to be replaced by 2.5 mm in the y-direction (no change in x-direction).

(61) For achieving a folded lens system with low f/# and low lens height at the same time, lens elements are cut to a non-circular shape (often called "cut lens" or "D cut lens"). The lens elements are obtained by cutting the large lens elements of lens **204′** to a height of 5 mm (in the Y direction). That is, the lens elements L.sub.i of lens **204′** that have height H.sub.Li>5 mm (i.e. L.sub.6, L.sub.7 and L.sub.8) are cut to 5 mm. The cut lens elements have no circular symmetry like that of lens elements **204**, but their width is larger than their height, i.e. W.sub.Li>H.sub.Li (see example in FIG. **7**). The lens elements Li of lens **204** that have height H.sub.Li≤5 mm are not changed. As of the cut, lens elements L.sub.6, L.sub.7 and L.sub.8 have a large CA but still low CH. This is beneficial as in a folded lens design a lens height H.sub.L may determine the camera's height, wherein the camera height is generally limited by a height of the host device. A lens having large CA and low CH is beneficial for a low f/# folded lens that is compatible with e.g. a smartphone's height constraints. Lens elements of lens **204′** are cut in direction Y, meaning that the height of a lens element H.sub.Li is smaller than its width W.sub.Li. The CA of lens elements L.sub.1-L.sub.5 may be oriented in any direction, e.g. in Y direction. As of the cut design, the CA of lens element L.sub.6, L.sub.7 and L.sub.8 is oriented in X direction (not shown here). In other embodiments, only one or only two lens elements L.sub.i may be cut, i.e. may have W.sub.Li>H.sub.Li. In yet other embodiments, more than 3 lens elements L.sub.i may be cut, i.e. may have W.sub.Li>H.sub.Li. In yet other embodiments, all lens elements L.sub.i may be cut, i.e. may have W.sub.Li>H.sub.Li. In other embodiments, lens **204′** may be achieved by cutting the large lens elements of lens **204** to a height of e.g. 4.5 mm or 4 mm (in the Y direction), i.e. the lens elements L.sub.i that have height H.sub.Li>4.5 mm (i.e. L.sub.4, L.sub.5, L.sub.6, L.sub.7 and L.sub.8) or 4 mm (i.e. L.sub.1-L.sub.8) may be cut to 4.5 mm or 4 mm respectively. In yet other embodiments, lens **204′** may formed by cutting the large lens elements of lens **204** to a height of e.g. 3.5 mm or 3 mm (in Y direction).

(62) In lens system **200′**, the prism dimensions are identical with those in lens system **200**: T**1**=10.93 mm, T**2**=12.6 mm and V=8.68 mm.

(63) Besides the properties described in FIG. **2**A, in the example of FIG. **2**B, the following optical properties are achieved:

(64) $CA(S_{12}) = 1.03 \times CH(S_{12}) = 2.58mm$ $CA(S_{13}) = 1.03 \times CH(S_{13}) = 2.58mm$
$CA(S_{15}) = 1.14 \times CH(S_{15}) = 2.85mm$ $CA(S_{16}) = 1.19 \times CH(S_{16}) = 2.97mm$. $CA(S_{17}) = 1.32 \times CH(S_{12}) = 3.29mm$
$CA(S_{17}) > CA(S_k), 1 < k \leq 2N$. $CA(S_{16}) > CA(S_k), 1 < k \leq 2N - 1$ $CA(S_{15}) > CA(S_k), 1 < k < 2N - 2$ For all lens surfaces CH(S.sub.k)≤5 mm f/#=1.0 Minimum CA/SD ratio: CA(S.sub.4)/SD=0.57 Maximum CA/SD ratio: CA(S.sub.17)/SD=0.71

Lens **204′** may be carried by a lens barrel having a lens barrel height of e.g. 5.0 mm-5.5 mm.

(65) FIG. **2**C depicts schematically another optical lens system disclosed herein and numbered **200″**. Lens system **200″** comprises an OPFE **202′**, lens **204**, an optical element **206** and image sensor **208**. Ray tracing is provided as in FIG. **2**A. Detailed optical data and surface data are given in Tables 1 and 2. In comparison with the OPFEs shown in FIG. **2**A and FIG. **2**B, OPFE **202′** has a smaller prism height ("V") of 7.82 mm. The smaller prism height may be beneficial for achieving a slim folded camera.

(66) Here T**1**=9.815 mm, T**2**=12.6 mm and V=7.82 mm. For the non-zero fields of lens system **200″**, the reduction of light compared to optical lens systems **200** and **200′** is 8% or less. For the zero fields there is no change in the amount of light entering the camera. The high amount of light entering the camera allows for the camera's low f/# of 1.0. In other embodiments a f/# may be 0.8-1.2.

(67) FIG. **2**D depicts schematically yet another optical lens system disclosed herein and numbered **200‴**. Lens system **200‴** comprises an OPFE **202″**, lens **204**, optical element **206** and image sensor **208**. Ray tracing is provided as in FIG. **2**A. Detailed optical data and surface data are given in Tables 1, 2. In comparison with OPFE **202′** shown in FIG. **2**C, OPFE **202″** has a smaller prism height ("V") of 7.02 mm.

(68) Here T**1**=8.75 mm, T**2**=12.6 mm and V=7.02 mm. For the non-zero fields of lens system **200‴** the reduction of light compared to lens systems **200** and **200′** is 19% or less. For the zero fields there is no change in the amount of light entering the camera. The high amount of light entering the camera allows for the camera's low f/# of 1.0. In other embodiments, f/# may be 0.8-1.2.

(69) FIG. **2**E depicts schematically yet another optical lens system disclosed herein and numbered **200″″**. Lens system **200″″** comprises an OPFE **202‴**, lens **204″**, optical element **206** and image sensor **208**. Ray tracing is provided as in FIG. **2**A. Detailed optical data and surface data are given in Tables 1, 2. However, data on aperture radius for all surfaces of L.sub.6, and L.sub.5 as well as of surfaces S.sub.11 of L.sub.5 and S.sub.15 of L.sub.7 is to be replaced by 2.45 mm in y-direction (no change in x-direction). The prism height (measured along the Y-axis) is larger than the height of lens **204″**. The height of the entire lens system **200″″** (measured along the Y-axis) is determined solely by the prism height, i.e. there is no additional "height penalty" introduced by lens **204″**.

(70) In comparison with OPFE **202″** shown in FIG. 2D, OPFE **202‴** has a smaller prism height of 6.00 mm.

(71) The lens elements of lens **204″** are obtained by cutting the large lens elements of lens **204″** to a height of 4.9 mm (in Y direction). That is, the lens elements L.sub.i of lens **204″** that have height H.sub.Li>4.9 mm (i.e. L.sub.6, L.sub.7 and L.sub.8) are cut to 4.9 mm. The cut lens elements have no circular symmetry like that of lens elements **204**, but their width is larger than their height, i.e. W.sub.Li>H.sub.Li (see example in FIG. **7**). In other embodiments, lens **204″** may be achieved by cutting the large lens elements of lens **204** to a height of e.g. 4.5 mm or 4 mm (in the Y direction), i.e. the lens elements L.sub.i that have height H.sub.Li>4.5 mm (i.e. L.sub.4, L.sub.5, L.sub.6, L.sub.7 and L.sub.8) or 4 mm (i.e. L.sub.1-L.sub.8) may be cut to 4.5 mm or 4 mm respectively.

(72) Further explanation on cut lenses is provided in description of FIG. **2**B. Here T**1**=6.95 mm, T**2**=12.6 mm and V=6.00 mm. For the non-zero fields shown in lens system **200″″**, about 55%-60% of light reaches image sensor **208**. For the non-zero fields of lens system **200″″** the reduction of light compared to the respective non-zero fields of lens systems **200** and **200′** is about 30%. The light reduction is primarily caused by the smaller prism dimensions, not by the D cut of the larger lens elements. The light reduction occurs symmetrically for the upper marginal-ray and the lower marginal-ray. The difference in the amount of light that reaches image sensor **208** for the D cut lens in lens system **200″″** and a non D cut lens amounts to <5%. For the zero fields there is no change in the amount of light entering the camera. The high amount of light entering the camera allows for the camera's low f/# of 1.0. In other embodiments, f/# may be 0.8-1.2. Lens **204″** may be carried by a lens barrel having a lens barrel height of e.g. 4.9 mm-5.5 mm.

(73) According to some examples, at least part of the lens elements can have a shape (profile) in cross-section (in plane X-Y, which is orthogonal to the optical lens system and which generally coincides with the optical axis) which is not circular. In particular, as shown e.g. in FIG. **7**, at least some of the lens elements which are integrated in lens barrel **710** can have a width W.sub.Li (measured along axis X) which is greater than their height H.sub.Li (measured along axis Y). The height H.sub.Li can correspond to the total height of the lens element (including the mechanical part). In some embodiments, a lens element in lens system **700** may have a symmetry about axis Y and/or about axis X.

(74) According to some examples, W.sub.Li is substantially greater than H.sub.Li (for example, by at least a percentage that is equal or greater than 20%, these values being not limiting). In some examples, W.sub.Li may be greater than H.sub.Li by a percentage of 20-70%. Consider lens element L.sub.8 of folded lens **204′** as an example: W.sub.L8 is greater than H.sub.L8 by a percentage of 32%. Another example is lens element L.sub.8 of folded lens **204″**: W.sub.L8 is greater than H.sub.L8 by a percentage of 44%.

(75) Unless otherwise stated, the use of the expression "and/or" between the last two members of a list of options for selection indicates that a selection of one or more of the listed options is appropriate and may be made.

(76) It should be understood that where the claims or specification refer to "a" or "an" element, such reference is not to be construed as there being only one of that element.

(77) All patents and patent applications mentioned in this specification are herein incorporated in their entirety by reference into the specification, to the same extent as if each individual patent or patent application was specifically and individually indicated to be incorporated herein by reference. In addition, citation or identification of any reference in this application shall not be construed as an admission that such reference is available as prior art to the present disclosure.

Claims

1. A folded camera, comprising: a lens having an effective focal length (EFL) and including $N \geq 7$ lens elements L_i along a lens optical axis wherein a first lens element L_1 faces an object side, wherein each lens element Li has a respective front surface S_{2i-1} and a respective rear surface S_{2i}, the lens element surfaces marked S_k where $1 \leq k \leq 2N$, wherein each lens element surface S_k has a clear height value $CH(S_k)$ and a clear aperture value $CA(S_k)$, and wherein a clear aperture value $CA(S_{2N})$ in lens element L_N is greater than a clear aperture value $CA(S_1)$ in lens element L_1; an image sensor; and an optical path folding element (OPFE) for folding a first optical path to a second optical path that is perpendicular to the first optical path and parallel to the lens optical axis, wherein one or more of the lens elements are cut lens elements that have a respective width W_{Li} measured along an axis perpendicular to both the first optical path and the second optical path, and a respective height H_{Li} measured along an axis parallel to the first optical path, wherein $W_{Li} > H_{Li}$, wherein the camera has an f number $f/\# < 1.1$, and wherein the folded camera is a wide camera with a field of view (FOV) ranging from 60 degrees to 90 degrees.
2. The folded camera of claim 1, wherein $f/\# \leq 1.0$.
3. The folded camera of claim 1, wherein in at least one of the cut lens elements $W_{Li}/H_{Li} > 1.1$.
4. The folded camera of claim 1, wherein in at least one of the cut lens elements $W_{Li}/H_{Li} > 1.2$.
5. The folded camera of claim 1, wherein a clear height value of all lens elements is smaller than or equal to 5 mm.
6. The folded camera of claim 5, wherein the lens is included in a lens barrel, wherein the lens barrel has a lens barrel height measured along the first optical path, and wherein the lens barrel height is smaller than or equal to 5.5 mm.
7. The folded camera of claim 1, wherein the camera has a diagonal field of view (FOV) larger than 60 degrees.
8. The folded camera of claim 1, wherein the image sensor lies in a plane that is parallel to the first optical path.
9. The folded camera of claim 1, wherein the folded camera has a total track length (TTL), and wherein an aperture stop of the lens is located closer to a first surface S_1 of lens L_1 than a distance d that fulfills $d/TTL = 0.2$.
10. The folded camera of claim 1, wherein the image sensor has a sensor diagonal $SD > 6$ mm.
11. The folded camera of claim 1, wherein the OPFE has a height H_O, wherein the lens has a height H_L, wherein H_O and H_L are measured along a direction parallel to the first optical path, and wherein $H_O > H_L$.
12. The folded camera of claim 6, wherein the OPFE has a height H_O, wherein the lens barrel has a height H_{LB}, wherein H_O and H_{LB} are measured along a direction parallel to the first optical path, and wherein $H_O > H_{LB}$.
13. The folded camera of claim 1, wherein the camera has a height H_C and the OPFE has a height H_O, wherein H_O and H_C are measured along a direction parallel to the first optical path, and wherein H_C is determined by H_O.
14. The folded camera of claim 1, wherein an absolute value of an optical power of element $L_i |f_i| > 5 \times EFL$ for $1 \leq i \leq 3$.
15. The folded camera of claim 1, wherein lens element L_5 has a strongest optical power of all lens elements $|f_5| < |f_i|$ for $i \neq 5$.
16. The folded camera of claim 1, wherein STD is a normalized air gap standard deviation of an air gap between two consecutive lens elements, and wherein the lens includes at least one air gap between lens elements that complies with the condition $STD < 0.020$.
17. The folded camera of claim 1, wherein the folded camera is included in a mobile device.
18. The folded camera of claim 17, wherein the mobile device is a smartphone.