US012394353B2

(12) **United States Patent**
**Yoshiga**

(10) **Patent No.: US 12,394,353 B2**
(45) **Date of Patent: Aug. 19, 2025**

(54) **ELECTRONIC DEVICE**

(71) Applicant: **Innolux Corporation**, Miaoli County (TW)

(72) Inventor: **Masahiro Yoshiga**, Miaoli County (TW)

(73) Assignee: **Innolux Corporation**, Miaoli County (TW)

( * ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **18/634,979**

(22) Filed: **Apr. 14, 2024**

(65) **Prior Publication Data**

US 2024/0257695 A1 Aug. 1, 2024

**Related U.S. Application Data**

(63) Continuation of application No. 17/979,001, filed on Nov. 2, 2022, now Pat. No. 11,990,078.

(51) **Int. Cl.**
***G09G 5/10*** (2006.01)
***G09G 3/20*** (2006.01)
***G09G 3/3233*** (2016.01)

(52) **U.S. Cl.**
CPC ..... ***G09G 3/2074*** (2013.01); ***G09G 3/3233*** (2013.01); *G09G 2300/0452* (2013.01); *G09G 2300/0842* (2013.01); *G09G 2320/0242* (2013.01); *G09G 2360/16* (2013.01)

(58) **Field of Classification Search**
CPC ..... G09G 3/2074; G09G 3/3233; G09G 2300/0452; G09G 2300/0842; G09G 2320/0242; G09G 2360/16
USPC ..... 345/690
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

| | | | | |
|---|---|---|---|---|
| 11,990,078 | B1 * | 5/2024 | Yoshiga | G09G 3/2003 |
| 2016/0133176 | A1 * | 5/2016 | Oh | G09G 3/3648 345/694 |
| 2016/0307490 | A1 * | 10/2016 | Lee | G09G 3/3225 |
| 2017/0278446 | A1 * | 9/2017 | Ishiyama | G02F 1/134309 |
| 2021/0043153 | A1 | 2/2021 | Yang et al. | |

OTHER PUBLICATIONS

"Office Action of Taiwan Counterpart Application", issued on Jun. 4, 2025, p. 1-p. 6.

* cited by examiner

*Primary Examiner* — Jennifer T Nguyen
(74) *Attorney, Agent, or Firm* — JCIPRNET

(57) **ABSTRACT**

An electronic device includes a color module and a control module. The color module includes a first sub-pixel and a second sub-pixel. The first sub-pixel and the second sub-pixel are adjacent and have different colors. The control module is configured to convert an input data to an output data. The input data includes a first grayscale value of a first color. The output data includes the first grayscale value of the first color and a second grayscale value of a second color, and the first color and the second color are different. The first grayscale value of the output data is provided to the first sub-pixel, and the second grayscale value of the output data is provided to the second sub-pixel.

**6 Claims, 8 Drawing Sheets**




100
Electronic device
110
120
Din
Control module
Dout
Color module

FIG. 1


200
P2
P1
P3
Second sub-pixel
First sub-pixel
Third sub-pixel

FIG. 2A


200
VDD
P3
C3
TS3
TD3
L3
DL3
D3
VDD
P1
C1
TS1
TD1
L1
DL1
Din
D1
VDD
P2
C2
TS2
TD2
L2
DL2
D2
SL
SS

FIG. 2B


y
301
(Green, GL255)
(Green, GL255
+ Red GL36)
301'(x_N,y_N)
302 (x_T,y_T)
(Green, GL16)
Sd
x

FIG. 3


Compensation value
32
16
0
32
128
255
First grayscale value
(first color)

FIG. 4


Din
D2
Second grayscale value GV2
D1
First grayscale value GV1
D3
Third grayscale value GV3
510
512
CD
Calculator
511
Dout
D2'
Second grayscale value GV2'
D1
First grayscale value GV1
D3
Third grayscale value GV3

FIG. 5


Din
D2
Second grayscale value GV2
D1
First grayscale value GV1
D3
Third grayscale value GV3
610
612
CD
611
Grayscale lookup table
601
Dout
D2'
Second grayscale value GV2'
D1
First grayscale value GV1
D3
Third grayscale value GV3

FIG. 6


Din
D2
Second grayscale value GV2
D1
First grayscale value GV1
D3
Third grayscale value GV3
710
701
711
Grayscale lookup table
Dout
D2'
Second grayscale value GV2'
D1
First grayscale value GV1
D3
Third grayscale value GV3

FIG. 7


Din
D2
Second grayscale value GV2
D1
First grayscale value GV1
D3
Third grayscale value GV3
810
801
812
Grayscale lookup table
811
Grayscale lookup table
813
Grayscale lookup table
Dout
D2'
Second grayscale value GV2'
D1'
First grayscale value GV1'
D3'
Third grayscale value GV3'

FIG. 8


901(Din)
902(Dout)
CD=−36
255
254
253
...
37
36
35
...
1
0
219
218
217
...
1
0
0
...
0
0

FIG. 9


1001(Din)
1002(Dout)
255
254
253
...
37
36
35
...
1
0
876
873
869
...
127
124
130
...
3
0

FIG. 10

# ELECTRONIC DEVICE

## CROSS-REFERENCE TO RELATED APPLICATION

This application is a continuation application of and claims the priority benefit of U.S. application Ser. No. 17/979,001, filed on Nov. 2, 2022. The entirety of the above-mentioned patent application is hereby incorporated by reference herein and made a part of this specification.

## BACKGROUND

### Technical Field

The disclosure relates an electronic device, particularly, the disclosure relates to an electronic device including a control module which modifies the grayscale value.

### Description of Related Art

A light-emitting device (LED) display apparatus includes a pixel array, and the pixel array includes a plurality of sub-pixels, such as three sub-pixels of red LED, green LED and blue LED. In the LED display apparatus, the red LED, the green LED and the blue LED are respectively driven by different driving currents to determine the grayscales of the light emitted from the LEDs. However, LED with different grayscales may result in different color chromaticities (or color purities), which can be called color shift problem. Taking the green LED for example, when the driving current of the green LED increases, the color of the green light provided by the pixel may occur the color shift problem, such that the color of the green light provided by the pixel becomes higher purity green. On the contrary, as the driving current of the green LED decreases, the color of the green light provided by the pixel may also be shifted, such that the color of the green light becomes reddish.

## SUMMARY

An electronic device of the disclosure includes a color module and a control module.

The color module includes a first sub-pixel and a second sub-pixel. The first sub-pixel and the second sub-pixel are adjacent and have different colors. The control module is configured to convert an input data to an output data. The input data includes a first grayscale value of a first color. The output data comprises the first grayscale value of the first color and a second grayscale value of a second color, and the first color and the second color are different. The first grayscale value of the output data is provided to the first sub-pixel, and the second grayscale value of the output data is provided to the second sub-pixel.

Based on the above, according to the electronic device of the disclosure, the electronic device can effectively reduce or eliminate the color shift problem of the color module.

To make the aforementioned more comprehensible, several embodiments accompanied with drawings are described in detail as follows.

## BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings are included to provide a further understanding of the disclosure, and are incorporated in and constitute a part of this specification. The drawings illustrate exemplary embodiments of the disclosure and, together with the description, serve to explain the principles of the disclosure.



FIG. **1** is a circuit schematic diagram of an electronic device according to an embodiment of the disclosure.

FIG. **2**A and FIG. **2**B are schematic diagrams of a pixel according to an embodiment of the disclosure.

FIG. **3** is a schematic diagram of a chromaticity coordinate system according to an embodiment of the disclosure.

FIG. **4** is a relationship schematic diagram of a first grayscale value and a compensation value according to an embodiment of the disclosure.

FIG. **5** is a schematic diagram of a control module according to an embodiment of the disclosure.

FIG. **6** is a schematic diagram of a control module according to another embodiment of the disclosure.

FIG. **7** is a schematic diagram of a control module according to another embodiment of the disclosure.

FIG. **8** is a schematic diagram of a control module according to another embodiment of the disclosure.

FIG. **9** is a schematic diagram of an input data and an output data according to an embodiment of the disclosure.

FIG. **10** is a schematic diagram of an input data and an output data according to another embodiment of the disclosure.

## DESCRIPTION OF THE EMBODIMENTS

The accompanying drawings are included to provide a further understanding of the disclosure, and are incorporated in and constitute a part of this specification. The drawings illustrate exemplary embodiments of the disclosure and, together with the description, serve to explain the principles of the disclosure.

Certain terms are used throughout the specification and appended claims of the disclosure to refer to specific components. Those skilled in the art should understand that electronic device manufacturers may refer to the same components by different names. This article does not intend to distinguish those components with the same function but different names. In the following description and rights request, the words such as "comprise" and "include" are open-ended terms, and should be explained as "including but not limited to . . . ".

The term "couple (or electrically connect)" used throughout the whole specification of the present application (including the appended claims) may refer to any direct or indirect connection means. For example, if the text describes that a first device is coupled (or connected) to a second device, it should be interpreted that the first device may be directly connected to the second device, or the first device may be indirectly connected through other devices or certain connection means to be connected to the second device. The terms "first", "second", and similar terms mentioned throughout the whole specification of the present application (including the appended claims) are merely used to name discrete elements or to differentiate among different embodiments or ranges. Therefore, the terms should not be regarded as limiting an upper limit or a lower limit of the quantity of the elements and should not be used to limit the arrangement sequence of elements. In addition, wherever possible, elements/components/steps using the same reference numerals in the drawings and the embodiments represent the same or similar parts. Reference may be mutually made to related descriptions of elements/components/steps using the same reference numerals or using the same terms in different embodiments.

It should be noted that in the following embodiments, the technical features of several different embodiments may be replaced, recombined, and mixed without departing from the spirit of the disclosure to complete other embodiments. As long as the features of each embodiment do not violate the spirit of the disclosure or conflict with each other, they may be mixed and used together arbitrarily.

The electronic device of the disclosure may include a display device, an antenna device (such as liquid crystal antenna), a sensing device, a lighting device, a touch device, a curved device, a free shape device, a bendable device, flexible device, tiled device or a combination thereof, but is not limited thereto. The electronic device may include light-emitting diode (LED), liquid crystal, fluorescence, phosphor, other suitable materials or a combination thereof, but is not limited thereto. The light emitting diode may include organic light emitting diode (OLED), inorganic light emitting diode such as mini LED, micro LED or quantum dot (QD) light emitting diode (QLED or QDLED), other suitable type of LED or any combination of the above, but is not limited thereto.

FIG. **1** is a circuit schematic diagram of an electronic device according to an embodiment of the disclosure. FIG. **2**A and FIG. **2**B are schematics diagram of a pixel according to an embodiment of the disclosure. Referring to FIG. **1**, the electronic device **100** includes a control module **110** and a color module **120**. The control module **110** is coupled to the color module **120**. In the embodiment of the disclosure, the color module **120** may include a plurality of pixels. Referring to FIG. **2**A, each pixel **200** may include a first sub-pixel P**1** and a second sub-pixel P**2**. The first sub-pixel P**1** and the second sub-pixel P**2** are adjacent and have different colors. The control module **110** may receive an input data Din from an image data source, and convert the input data Din to an output data Dout for driving the first sub-pixel P**1** and the second sub-pixel P**2**. The input data Din may include a first grayscale value of a first color and a second grayscale value of a second color, and the first color and the second color are different. The first sub-pixel P**1** may be configured to display the first color, and the second sub-pixel may be configured to display the second color. The first grayscale value of the output data Dout is provided to the first sub-pixel P**1**. The second grayscale value of the output data Dout is provided to the second sub-pixel.

In the embodiment of the disclosure, the electronic device **100** may be a display device. In some embodiments, the color module **120** may be a display panel, such as a liquid crystal display (LCD) panel, an organic light emitting diode display panel, or an inorganic light emitting diode display panel, but the disclosure is not limited thereto. In some embodiments, the color module **120** can be a backlight module. In this case, the electronic device **100** can include an LCD panel, and the backlight module can provide light source to the LCD panel. The backlight module can be a white light backlight module or a RGB backlight module. The RGB backlight module can include red color light emitting elements, green color light emitting elements, and blue color light emitting elements, thus providing white light. In the embodiment of the disclosure, the first color may be green, and the second color may be red, but the disclosure is not limited thereto.

Referring to FIG. **1**, FIG. **2**A and FIG. **2**B, the color module **120** may include a pixel array including a plurality of pixels, and each of the plurality of pixels may be implemented as the pixel **200** of the FIG. **2**A and FIG. **2**B. In the embodiment of the disclosure, the pixel **200** includes the first sub-pixel P**1**, the second sub-pixel P**2** and a third sub-pixel P**3**. The first sub-pixel P**1** may display the first color. The second sub-pixel P**2** may display the second color. The third sub-pixel P**3** may display a third color. For example, the first color may be green, the second color may be red, and the third color may be blue, but the disclosure is not limited thereto. As shown in FIG. **2**A, the first sub-pixel P**1** may be arranged between the second sub-pixel P**2** and the third sub-pixel P**3**, but the disclosure is not limited thereto.

As shown in FIG. **2**B, the first sub-pixel P**1** includes a transistor TS**1**, a transistor TD**1**, a capacitor C**1** and a first light emitting element L**1**. A first terminal of the transistor TS**1** is coupled to a data line DL**1** to receive a display data D**1** (or referred to as data voltage). A second terminal of the transistor TS**1** is coupled to a control terminal of the transistor TD**1** and the capacitor C**1**. The control terminal of the transistor TS**1** is coupled to the scan line SL to receive the scan signal SS. A first terminal of the transistor TD**1** is coupled to a first operation voltage VDD. A second terminal of the transistor TD**1** is coupled to the first light emitting element L**1**. The capacitor C**1** is coupled between the first operation voltage VDD and the control terminal of the transistor TD**1**. The light emitting element L**1** is coupled between the second terminal of the transistor TD**1** and a second operation voltage VSS.

As shown in FIG. **2**B, the second sub-pixel P**2** includes a transistor TS**2**, a transistor TD**2**, a capacitor C**2** and a second light emitting element L**2**. A first terminal of the transistor TS**2** is coupled to a data line DL**2** to receive a display data D**2** (or referred to as data voltage). A second terminal of the transistor TS**2** is coupled to a control terminal of the transistor TD**2** and the capacitor C**2**. The control terminal of the transistor TS**2** is coupled to a scan line SL to receive the scan signal SS. A first terminal of the transistor TD**2** is coupled to the first operation voltage VDD. A second terminal of the transistor TD**2** is coupled to the first light emitting element L**2**. The capacitor C**2** is coupled between the first operation voltage VDD and the control terminal of the transistor TD**2**. The light emitting element L**2** is coupled between the second terminal of the transistor TD**2** and a second operation voltage VSS.

As shown in FIG. **2**B, the third sub-pixel P**3** includes a transistor TS**3**, a transistor TD**3**, a capacitor C**3** and a third light emitting element L**3**. A first terminal of the transistor TS**3** is coupled to a data line DL**3** to receive a display data D**3** (or referred to as data voltage). A second terminal of the transistor TS**3** is coupled to a control terminal of the transistor TD**3** and the capacitor C**3**. The control terminal of the transistor TS**3** is coupled to the scan line SL to receive the scan signal SS. A first terminal of the transistor TD**3** is coupled to the first operation voltage VDD. A second terminal of the transistor TD**3** is coupled to the first light emitting element L**3**. The capacitor C**3** is coupled between the first operation voltage VDD and the control terminal of the transistor TD**3**. The light emitting element L**3** is coupled between the second terminal of the transistor TD**3** and the second operation voltage VSS.

In the embodiment of the disclosure, the control module **110** of FIG. **1** may receive the input data Din, and convert the input data Din to the output data Dout for driving the second sub-pixel P**2**, the first sub-pixel P**1** and the third sub-pixel P**3**. The output data Dout may include the display data D**2**, the display data D**1** and the display data D**3**. The display data D**2** may include a second grayscale value of the second color. The display data D**1** may include a first grayscale value of the first color. The display data D**3** may include a third grayscale value of the third color. In the embodiment of the disclosure, the sub-pixel P**2**, the sub-

pixel P1 and the sub-pixel P3 may receive the display data D2, the display data D1 and the display data D3 to drive the light emitting element L2, the light emitting element L1 and the light emitting element L3, respectively.

In the embodiment of the disclosure, the light emitting elements L1, L2 and L3 may be a light emitting diode (LED), a mini-LED or a micro-LED, respectively, but the disclosure is not limited thereto.

In some embodiments of the disclosure, the control module can convert an input data to an output data, and the output data includes a modified grayscale value of a second color, which can compensate the color shift problem of a first color. Thus, the color shift problem can be solved without modifying the design of the pixel circuit. The pixel **200** of the disclosure does not need to additionally design the pixel circuit, and especially does not need to additionally increase the transistors in the pixel circuit. Referring to FIG. **2**B, in some embodiments, in one pixel **200**, the circuit design in the first sub-pixel P1 and the circuit design in the second sub-pixel P2 can be the same. In some embodiments, in one pixel **200**, the circuit design in the first sub-pixel P1, the circuit design in the second sub-pixel P2, and the circuit design in the third sub-pixel P3 can be the same.

FIG. **3** is a schematic diagram of a chromaticity coordinate system (chromaticity diagram) according to an embodiment of the disclosure. Referring to FIG. **1** to FIG. **3**, the first sub-pixel P1 may display the first color, and may have a color shift problem. In this embodiment, the first color is green. Referring to a chromaticity coordinate system of FIG. **3**, the chromaticity coordinate system of FIG. **3** may correspond to a CIE (International Commission on Illumination) color space (e.g. xy color space). In the embodiment of the disclosure, the first color displayed by the first sub-pixel P1 without the color shift problem (having a normal color tone) may correspond to the color coordinate point **302** on the chromaticity coordinate system of FIG. **3**. Thus, the color coordinate point **302** can be regarded as a target coordinate point. However, when the first sub-pixel P1 is driven by the display data D1 including the first grayscale value (specific grayscale value) of the first color, the first color with the color shift problem displayed by the first sub-pixel P1 may correspond to a color coordinate point **301** on the chromaticity coordinate system of FIG. **3**. Due to the influence of the color shift problem, the color coordinate of the first color displayed by the first sub-pixel P1 on the chromaticity coordinate system may be shifted from the color coordinate point **302** (the target coordinate point) to the color coordinate point **301**. In some embodiments, the color coordinate point **301** may correspond to a higher grayscale (for example, 255), and the color coordinate point **302** may correspond to a lower grayscale (for example, 16).

In the embodiment of the disclosure, in order to overcome the color shift problem of the first color, the control module **110** may adjust the display data D2 of the input data Din used for driving the second sub-pixel P2 adjacent to the first sub-pixel P1, so as to adjust (for example, increase) the second grayscale value of the second color displayed by the sub-pixel P2 to compensate color display result of the first color displayed by the pixel **200**. The control module **110** may convert the input data Din to an output data Dout. Specifically, the control module **110** may convert the display data D2 of the input data Din to a modified display data D2' (see FIG. **5**) of the output data Dout. For example, the control module **110** may increase the second grayscale value of the second color (e.g. the second grayscale value of the second color plus a compensation value). Thus, the compensated first color displayed by the pixel **200** may correspond to a modified color coordinate point **301'**, and the modified color coordinate point **301'** may be close to or the same as the target color coordinate point **302**. That is, the control module **110** may dynamically adjust the second grayscale value of the second color for compensating the first color having different grayscale values to adaptively compensate the first color.

In the embodiment of the disclosure, referring to FIG. **3**, the compensation value CD can be determined according to a modified first color coordinate ($x_N$, $y_N$) corresponding to the first color and a target coordinate ($x_T$, $y_T$) corresponding to a target grayscale value of the first color on a chromaticity diagram. Specifically, a first color coordinate of the color coordinate point **301** corresponds to the first grayscale value of the first color (i.e. green grayscale value of 255) and a target coordinate of the target color coordinate point **302** corresponds to a target grayscale value of the first color (i.e. green grayscale value of 16) on the chromaticity diagram. The compensation value is also a grayscale value. Moreover, there is a shortest distance (i.e. a distance Sd as shown in FIG. **3**) between a modified first color coordinate corresponding to the compensated first color (i.e. the display result of green grayscale value of 255 plus red grayscale value of 36) and the target coordinate on the chromaticity diagram.

Specifically, the modified first color coordinate ($x_N$, $y_N$) of the color coordinate point **301'** may be determined by a following equation (1), wherein the target coordinate ($x_T$, $y_T$) corresponds to the target color coordinate point **302**, and the parameter Δxy may represent the distance Sd between the color coordinate point **301'** and the target color coordinate point **302**. The control module **110** may calculate the modified first color coordinate ($x_N$, $y_N$) of the compensated first color based on the minimum value of the parameter Δxy (e.g. Δxy=0) and the target coordinate ($x_T$, $y_T$). Then, the control module **110** may determine the compensation value according to the modified first color coordinate ($x_N$, $y_N$) of the color coordinate point **301'**, and the compensation value can be the additional value for the second grayscale value of the second color.

$$\Delta xy = \sqrt{(x_N - x_T)^2 + (y_N - y_T)^2} \quad \text{equation (1)}$$

For example, the first color may be green, and the second color may be red. When the first sub-pixel P1 is driven by the display data D_G corresponding to the grayscale value of 255 of green (i.e. Green, GL255)(e.g. the grayscale value (R, G, B) of the pixel **200** may be (0,255,0)), the first color with the color shift problem displayed by the first sub-pixel P1 may correspond to the color coordinate point **301** on the chromaticity coordinate system of FIG. **3**. Therefore, the control module **110** may adjust (increase) the grayscale value of red displayed by the second sub-pixel P2 to compensate color display result of green of the pixel **200** by the compensation value. The control module **110** may increase the grayscale value of red (e.g. the original grayscale value of red (0) plus the compensation value of 36), thus obtaining the grayscale value of Red, GL36. Thus, the color coordinate point **301'** of the compensated green corresponding to the grayscale value of 255 of green and the grayscale value of the grayscale value of red plus the compensation value of 36 displayed by the pixel **200** (i.e. Green, GL255+Red, GL36) (e.g. the grayscale value (R, G, B) of the pixel **200** may be changed to (36,255,0)) may be close to or the same as the target color coordinate point **302**

of green corresponding to the grayscale value of 16 of green (i.e. Green, GL16) (e.g. the grayscale value (R, G, B) corresponding to the target color coordinate point **302** may be (0,16,0)).

FIG. **4** is a relationship schematic diagram of a first grayscale value and a compensation value according to an embodiment of the disclosure. Referring to FIG. **4**, in the embodiment of the disclosure, the compensation value for the second color may be proportional to the first grayscale value of the first color, and the compensation value may be smaller than the first grayscale value. As show in FIG. **4**, when the first grayscale value of the first color is less than or equal to 16, the compensation value may be 0. When the first grayscale value of the first color is 128, the compensation value may be, for example, 16. When the first grayscale value of the first color is 255, the compensation value may be, for example, 32. The relationship of the first grayscale value and the compensation value may be linear, but the disclosure is not limited thereto. In one embodiment of the disclosure, the relationship of the first grayscale value and the compensation value may be non-linear.

For example, the first color may be green, and the second color may be red. The control module of FIG. **1** may dynamically adjust the grayscale value of red for compensating green having different gray values to adaptively compensate green, so that, as shown as FIG. **3**, the color coordinate point corresponding to any compensated green corresponding to any grayscale value showed by the pixel may be close to or the same as the target color coordinate point of green. Thus, for all pixels of the pixel array, the green displayed by the all pixels may be compensated as the above-mentioned manner, so that the green displayed by the whole pixel array can be presented as a consistent chromaticity, and the color shift problem of the green displayed by the whole pixel array can be effectively improved or eliminated. In one embodiment of the disclosure, the color difference of any grayscale of green displayed by the pixel array may be lower than 0.01.

FIG. **5** is a schematic diagram of a control module according to an embodiment of the disclosure. Referring to FIG. **2**A and FIG. **5**, the control module **510** may include a calculator **511** and an arithmetic unit **512**. The arithmetic unit **512** may include an adder and/or a subtractor, but the disclosure is not limited thereto. In the embodiment of the disclosure, the control module **510** may receive an input data Din form an image data source. The input data Din can include display data D**1** to D**3**. The display data D**1** corresponds to the first sub-pixel P**1**, and the display data D**1** includes a (original) first grayscale value GV**1**. The display data D**2** corresponds to the second sub-pixel P**2**, and the display data D**2** includes a (original) second grayscale value GV**2**. The display data D**3** corresponds to the third sub-pixel P**3**, and the display data D**3** includes a (original) third grayscale value GV**3**. The control module **510** may generate an output data Dout for driving the pixel **200** according to the input data Din. The output data Dout can include display data D**1**, display data D**2'** and display data D**3**. The display data D**1** is used for driving the first sub-pixel P**1**, and the display data D**1** includes the (original) first grayscale value GV**1**. In the output data Dout, the display data D**2'** is used for driving the second sub-pixel P**2**, and the display data D**2'** includes a modified second grayscale value GV**2'**. The display data D**3** is used for driving the third sub-pixel P**3**, and the display data D**3** includes the (original) third grayscale value GV**3**.

Referring to FIG. **5**, in the embodiment of the disclosure, the calculator **511** may calculate a compensation value CD according to the first grayscale value GV**1** of the display data D**1** by the manner of the embodiment of FIG. **3**, and then the arithmetic unit **512** may add the compensation value CD to the original second grayscale value GV**2** of the display data D**2** to generate the modified second grayscale value GV**2'** of the display data D**2'**. The modified second grayscale value GV**2'** may be equal to the original second grayscale value GV**2** plus the compensation value CD.

Referring to FIG. **5**, for example, the first color may be green, the second color may be red, and the third color may be blue. The input data Din may include the display data D**1** to D**3**. The display data D**1** has the first grayscale value GV**1** of 255, the display data D**2** has the second grayscale value GV**2** of 0, and the display data D**3** has the third grayscale value GV**3** of 0 (i.e. grayscale value (R, G, B)=(0,255,0)). The calculator **511** may calculate the compensation value CD of 36 according to the first grayscale value GV**1** of 255 of the display data D**1**. Then, the arithmetic unit **512** may add the compensation value CD of 36 to the original second grayscale value GV**2** of 0 of the display data D**2** to generate the modified second grayscale value GV**2'** of 36 of the display data D**2'**. Thus, the first sub-pixel P**1** may display the first grayscale value GV**1** of 255, the second sub-pixel P**2** may display the modified second grayscale value GV**2'** of 36, and the third sub-pixel P**3** may display the third grayscale value GV**3** of 0 (i.e. grayscale value (R, G, B)=(36, 255,0)). Therefore, compared to the color shift problem of the original green displayed by the pixel **200** driven by the input data Din, the green displayed by the pixel **200** driven by the output data Dout may effectively reduce or eliminate the color shift problem by adjusting the grayscale value of the adjacent sub-pixel corresponding to red based on the color compensation mechanism.

In this example, referring to FIG. **5**, when a calculated sum of the original second grayscale value GV**2** plus the compensation value CD exceeds a maximum grayscale value, the control module **510** or the arithmetic unit **512** may output or generate the modified second grayscale value GV**2'** to be equal to or smaller than the maximum grayscale value. For example, the display data D**1** has the first grayscale value GV**1** of 255, the display data D**2** has the second grayscale value GV**2** of 255, and the display data D**3** has the third grayscale value GV**3** of 0 (i.e. grayscale value (R, G, B)=(255,255,0)). The calculator **511** may calculate the compensation value CD of 36 according to the first grayscale value GV**1** of 255 of the display data D**1**. Then, the arithmetic unit **512** may add the compensation value CD of 36 to the second grayscale value GV**2** of 255 of to get a value of 291 (=36+255), but the value exceeds the maximum grayscale value of 255. So, the arithmetic unit **512** may generate the modified second grayscale value GV**2'** of 255 of the display data D**2'**. Thus, the first sub-pixel P**1** may display the first grayscale value GV**1** of 255, the second sub-pixel P**2** may display the modified second grayscale value GV**2'** of 255, and the third sub-pixel P**3** may display the third grayscale value GV**3** of 0 (i.e. grayscale value (R, G, B)=(255,255,0)).

For another example, referring to FIG. **5**, the display data D**1** has the first grayscale value GV**1** of 255, the display data D**2** has the second grayscale value GV**2** of 255, and the display data D**3** has the third grayscale value GV**3** of 0 (i.e. grayscale value (R, G, B)=(255,255,0)). The calculator **511** may calculate the compensation value CD of 36 according to the first grayscale value GV**1** of 255 of the display data D**1**. The arithmetic unit **512** may pre-store a default operation value of −36 (or other values). Then, the arithmetic unit **512** may add the compensation value CD of 36 and the

default operation value of −36 to the second grayscale value GV2 of 255 of the display data D2 to generate the modified second grayscale value GV2' of 255 (=255+36−36) of the display data D2'. Thus, the first sub-pixel P1 may display the first grayscale value GV1 of 255, the second sub-pixel P2 may display the modified second grayscale value GV2' of 255, and the third sub-pixel P3 may display the third grayscale value GV3 of 0 (i.e. grayscale value (R, G, B)=(255,255,0)).

For yet another example, referring to FIG. **5**, the display data D1 has the first grayscale value GV1 of 0, the display data D2 has the second grayscale value GV2 of 255, and the display data D3 has the third grayscale value GV3 of 0 (i.e. grayscale value (R, G, B)=(255, 0,0)). The calculator **511** may calculate the compensation value CD of 0 according to the first grayscale value GV1 of 0 of the display data D1. Then, the arithmetic unit **512** may add the compensation value CD of 0 and a default operation value of −36 to the second grayscale value GV2 of 255 of the display data D2 to generate the modified second grayscale value GV2' of 219 (=255+0−36) of the display data D2'. Thus, the first sub-pixel P1 may display the first grayscale value GV1 of 0, the second sub-pixel P2 may display the modified second grayscale value GV2' of 219, and the third sub-pixel P3 may display the third grayscale value GV3 of 0 (i.e. grayscale value (R, G, B)=(219,0,0)).

In some embodiments of the disclosure, the second grayscale value GV2 of the input data Din may be "0", but the modified second grayscale value GV2' of the output data Dout may not be "0" because adding the compensation value. Therefore, as long as it is determined whether the some color pixels of the pixel circuit of the disputed product with the function of compensating for color shift are turned-on, but the corresponding grayscale values in the input data are "0", it can be known whether the disputed product uses the technical means of the present disclosure to cause infringement.

FIG. **6** is a schematic diagram of a control module according to another embodiment of the disclosure. In the embodiment of disclosure, the electronic device of FIG. **1** may further include a storage unit **601** as shown in FIG. **6**, and the storage unit **601** is coupled to the control module **110**. The storage unit **601** may store a grayscale lookup table, and the control module **110** may read the grayscale lookup table to obtain the compensation value from the grayscale lookup table. Referring to FIG. **2**A and FIG. **6**, the control module **610** may include an arithmetic unit **612**. The arithmetic unit **612** may include an adder and/or a subtractor, but the disclosure is not limited thereto. In the embodiment of the disclosure, the control module **610** may receive an input data Din form an image data source. The input data Din includes display data D1 to D3. The display data D1 corresponds to the first sub-pixel P1, and the display data D1 includes a (original) first grayscale value GV1. The display data D2 corresponds to the second sub-pixel P2, and the display data D2 includes a (original) second grayscale value GV2. The display data D3 corresponds to the third sub-pixel P3, and the display data D3 includes a (original) third grayscale value GV3. The control module **610** may generate an output data Dout for driving the pixel **200** according to the input data Din. The output data Dout includes display data D1, display data D2' and display data D3. The display data D1 is used for driving the first sub-pixel P1, and the display data D1 includes the (original) first grayscale value GV1. The display data D2' is used for driving the second sub-pixel P2, and the display data D2' includes a modified second grayscale value GV2'. The display data D3 is used for driving the third sub-pixel P3, and the display data D3 includes the (original) third grayscale value GV3.

In the embodiment of the disclosure, referring to FIG. **6**, the control module **610** may obtain a compensation value CD from the grayscale lookup table **611** according to the first grayscale value GV1 of the display data D1, and then the arithmetic unit **612** may add the compensation value CD to the second grayscale value GV2 of the display data D2 to generate the modified second grayscale value GV2' of the display data D2'. The modified second grayscale value GV2' may equal to the original second grayscale value GV2 plus the compensation value CD.

For example, referring to FIG. **6**, the first color may be green, the second color may be red and the third color may be blue. The input data Din may include the display data D1 to D3. The display data D1 has the first grayscale value GV1 of 255, the display data D2 has the second grayscale value GV2 of 0, and the display data D3 has the third grayscale value GV3 of 0 (i.e. grayscale value (R, G, B)=(0,255,0)). The control module **610** may obtain the compensation value CD of 36 from the grayscale lookup table **611** according to the first grayscale value GV1 of 255 of the display data D1. Then, the arithmetic unit **612** may add the compensation value CD of 36 to the second grayscale value GV2 of 0 of the display data D2 to generate the modified second grayscale value GV2' of 36 of the display data D2'. Thus, the first sub-pixel P1 may display the first grayscale value GV1 of 255, the second sub-pixel P2 may display the modified second grayscale value GV2' of 36, and the third sub-pixel P3 may display the third grayscale value GV3 of 0 (i.e. grayscale value (R, G, B)=(36,255,0)). Therefore, compared to the color shift problem of the original green displayed by the pixel **200** driven by the input data Din, the green displayed by the pixel **200** driven by the output data Dout may effectively reduce or eliminate the color shift problem by adjusting the grayscale value of the adjacent sub-pixel corresponding to red based on the color compensation mechanism. In addition, the control module **610** may also implement the above-mentioned examples of FIG. **5**.

FIG. **7** is a schematic diagram of a control module according to another embodiment of the disclosure. In the embodiment of disclosure, the electronic device of FIG. **1** may further include a storage unit **701** as shown in FIG. **7**, and the storage unit **701** is coupled to the control module **110**. The storage unit **701** may store a grayscale lookup table, and the control module **110** may read the grayscale lookup table to convert an input data to an output data. Referring to FIG. **2**A and FIG. **7**, the control module **710** may directly read the grayscale lookup table. In the embodiment of the disclosure, the control module **710** may receive an input data Din form an image data source. The input data Din includes display data D1 to D3. The display data D1 corresponds to the first sub-pixel P1, and the display data D1 includes a (original) first grayscale value GV1. The display data D2 corresponds to the second sub-pixel P2, and the display data D2 includes a (original) second grayscale value GV2. The display data D3 corresponds to the third sub-pixel P3, and the display data D3 includes a (original) third grayscale value GV3. The control module **710** may generate an output data Dout for driving the pixel **200** according to the input data Din. The output data Dout includes the display data D1, the display data D2' and the display data D3. The display data D1 is used for driving the first sub-pixel P1, and the display data D1 includes the (original) first grayscale value GV1. The display data D2' is used for driving the second sub-pixel P2, and the display data D2' includes a modified second grayscale value GV2'. The display data D3

is used for driving the third sub-pixel P3, and the display data D3 includes the (original) third grayscale value GV3.

In the embodiment of the disclosure, referring to FIG. 7, the control module 710 may directly read the grayscale lookup table 711 according to the first grayscale value GV1 of the display data D1, so as to obtain the modified second grayscale value GV2' of the display data D2'.

For example, the first color may be green, the second color may be red and the third color may be blue. The input data Din may include the display data D1 to D3. The display data D1 has the first grayscale value GV1 of 255, the display data D2 has the second grayscale value GV2 of 0, and the display data D3 has the third grayscale value GV3 of 0 (i.e. grayscale value (R, G, B)=(0,255,0)). The control module 710 may obtain the modified second grayscale value GV2' of 36 of the display data D2' from the grayscale lookup table 711 according to the first grayscale value GV1 of 255 of the display data D1. Thus, the first sub-pixel P1 may display the first grayscale value GV1 of 255, the second sub-pixel P2 may display the modified second grayscale value GV2' of 36, and the third sub-pixel P3 may display the third grayscale value GV3 of 0 (i.e. grayscale value (R, G, B)=(36, 255,0)). Therefore, compared to the color shift problem of the original green displayed by the pixel 200 driven by the input data Din, the green displayed by the pixel 200 driven by the output data Dout may effectively reduce or eliminate the color shift problem by adjusting the grayscale value of the adjacent sub-pixel corresponding to red based on the color compensation mechanism.

FIG. 8 is a schematic diagram of a control module according to another embodiment of the disclosure. In the embodiment of disclosure, the electronic device of FIG. 1 may further include a storage unit 801 as shown in FIG. 8, and the storage unit 801 is coupled to the control module 110. The storage unit 801 may store a grayscale lookup table, and the control module 110 may read the grayscale lookup table to convert an input data to an output data. Referring to FIG. 2A and FIG. 8, the control module 810 may directly read the grayscale lookup table. In the embodiment of the disclosure, the control module 810 may receive an input data Din form an image data source. The input data Din includes display data D1 to D3. The display data D1 corresponds to the first sub-pixel P1, and the display data D1 includes a (original) first grayscale value GV1. The display data D2 corresponds to the second sub-pixel P2, and the display data D2 includes a (original) second grayscale value GV2. The display data D3 corresponds to the third sub-pixel P3, and the display data D3 includes a (original) third grayscale value GV3. The control module 810 may generate an output data Dout for driving the pixel 200 according to the input data Din. The output data Dout includes the display data D1', the display data D2' and the display data D3'. The display data D1' is used for driving the first sub-pixel P1, and the display data D1' includes a modified first grayscale value GV1'. The display data D2' is used for driving the second sub-pixel P2, and the display data D2' includes a modified second grayscale value GV2'. The display data D3' is used for driving the third sub-pixel P3, and the display data D3' includes a modified third grayscale value GV3'.

In the embodiment of the disclosure, referring to FIG. 8, the control module 810 may directly read the grayscale lookup tables 811 to 813 according to the first grayscale value GV1 of the display data D1, the second grayscale value GV2 of the display data D2 and the third grayscale value GV3 of the display data D3, so as to obtain the modified first grayscale value GV1' of the display data D1', the modified second grayscale value GV2' of the display data D2' and the modified third grayscale value GV3' of the display data D3'. Therefore, compared to the color shift problem of the original colors displayed by the pixel 200 driven by the input data Din, the colors displayed by the pixel 200 driven by the output data Dout may effectively reduce or eliminate the color shift problem.

FIG. 9 is a schematic diagram of an input data and an output data according to an embodiment of the disclosure. Referring to FIG. 9, in the embodiment of the disclosure, a bit number of an input data 901 may be the same as a bit number of an output data 902. Thus, a number of the grayscale values of the output data 902 may less than a number of the grayscale values of the input data 901. As the above-mentioned examples, if the first grayscale value GV1 of the input data 901 is "255", and the compensation value is "−36", the second grayscale value GV2 of the output data 902 is "219". Analogously, if the first grayscale value GV1 of the input data 901 is any one of "0" to "36", and the compensation value is "−36", the second grayscale value GV2 of the output data 902 is "0". That is, the value range of the first grayscale value GV1 of the input data 901 may be "0" to "255", and the value range of the second grayscale value GV2 of the output data 902 may be "0" to "219". Therefore, the value range of the second grayscale value GV2 of the output data 902 may less than the value range of the first grayscale value GV1 of the input data 901.

FIG. 10 is a schematic diagram of an input data and an output data according to another embodiment of the disclosure. Referring to FIG. 10, in the embodiment of the disclosure, a bit number of an input data 1001 may be smaller than a bit number of an output data 1002. The input data 1001 may be an 8-bit data, and the output data 1002 may be a 10-bit data. The bit number of the output data Dout is larger than a bit number of the input data Din. Thus, a max grayscale value of the output data 1002 may be larger than a max grayscale value of the input data 1001. Moreover, a number of the grayscale values of the output data 1002 may be larger than a number of the grayscale values of the input data 1001. As the above-mentioned examples, if the first grayscale value of the input data 1001 is "255", and the compensation value is "−143 (converted from −35 (8-bit) to −143 (10-bit))", the second grayscale value of the output data 1002 is "876 (=1019−143)". Analogously, if the first grayscale value of the input data 901 is "143" (lowest grayscale value), and the compensation value is "−143", the second grayscale value of the output data 1002 is "0". That is, the value range of the first grayscale value of the input data 1001 may be "0" to "255", and the value range of the second grayscale value of the output data 1002 may be "0" to "876". Therefore, the value range of the second grayscale value of the output data 1002 may be larger than the value range of the first grayscale value of the input data 1001.

In summary, according to some embodiments, the electronic device includes a color module and a control module. The color module can include a first sub-pixel of a first color and a second sub-pixel of a second color, and the first sub-pixel and the second sub-pixel are adjacent. The control module can convert an input data to an output data, and the output data can include a modified grayscale value of the second color, which can compensate the color shift problem of the first color. According to some embodiments, the specific color displayed by the whole pixel array can be presented as a consistent chromaticity. Moreover, the electronic device of the disclosure does not need to additionally design the pixel circuit, especially does not need to additionally increase the transistors in the pixel circuit, and thus has the advantage of high applicability.

It will be apparent to those skilled in the art that various modifications and variations can be made to the disclosed embodiments without departing from the scope or spirit of the disclosure. In view of the foregoing, it is intended that the disclosure covers modifications and variations provided that they fall within the scope of the following claims and their equivalents.

What is claimed is:

**1**. An electronic device, comprising:

a color module, comprising a first sub-pixel;

a control module, disposed outside the color module, and configured to convert a first input grayscale value of the first sub-pixel to a first output grayscale value of the first sub-pixel; and

a first data line, wherein the control module is coupled to the first sub-pixel through the first data line,

wherein the first input grayscale value is different from the first output grayscale value,

wherein the first sub-pixel is configured to receive the first output grayscale value through the first data line,

wherein when the first input grayscale value of the first sub-pixel is received by the control module, the control module converts the first input grayscale value to the first output grayscale value, and the first output grayscale value is provided to the first sub-pixel of the color module, and

wherein the first input grayscale value of the first sub-pixel is 0, and the first output grayscale value provided to the first sub-pixel is greater than 0.

**2**. The electronic device according to claim **1**, wherein the color module is a display panel.

**3**. The electronic device according to claim **2**, wherein the color module is a liquid crystal display panel.

**4**. The electronic device according to claim **2**, wherein the color module is a light emitting diode display panel.

**5**. The electronic device according to claim **1**, wherein the color module comprises a second sub-pixel disposed adjacent to the first sub-pixel, and the first sub-pixel and the second sub-pixel have different colors,

wherein the control module is configured to convert a second input grayscale value of the second sub-pixel to a second output grayscale value of the second sub-pixel.

**6**. The electronic device according to claim **5**, wherein when the first input grayscale value of the first sub-pixel is received by the control module, the second input grayscale value of the second sub-pixel is received by the control module, the control module converts the second input grayscale value to the second output grayscale value, and the second output grayscale value is provided to the second sub-pixel of the color module,

wherein the second input grayscale value of the second sub-pixel is greater than 0.

* * * * *