

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12394889
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Igarashi; Eri et al.

Wave control medium, wave control element, wave control member, wave control device, and manufacturing method of wave control medium

Abstract

To provide a wave control medium that can absorb and control wave motion while achieving downsizing and wider bandwidth of a metamaterial and the like. A wave control medium 5 includes a three-dimensional microstructure having a base 2, a spiral part 3, and a matching element 6 disposed between the base 2 and the spiral part 3, in which the three-dimensional microstructure includes a material selected from any one of a metal, a dielectric, a magnetic body, a semiconductor, and a superconductor, or a combination of a plurality of these materials. The wave control medium 5 can absorb the wave motion by having the matching element 6 disposed between the base 2 and the spiral part 3 to moderate a change in the entire impedance value.

Inventors:	Igarashi; Eri (Tokyo, JP), Kawamura; Takashi (Tokyo, JP)
Applicant:	Sony Group Corporation (Tokyo, JP)
Family ID:	1000008762347
Assignee:	Sony Group Corporation (Tokyo, JP)
Appl. No.:	18/038148
Filed (or PCT Filed):	October 13, 2021
PCT No.:	PCT/JP2021/037892
PCT Pub. No.:	WO2022/113551
PCT Pub. Date:	June 02, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240006749 A1	Jan. 04, 2024

Foreign Application Priority Data

JP 2020-196694 Nov. 27, 2020

Publication Classification

Int. Cl.: H01Q15/00 (20060101); H01P7/00 (20060101); H01Q1/36 (20060101); H01Q1/38 (20060101); H01Q15/14 (20060101)

U.S. Cl.:

CPC H01Q1/38 (20130101); H01P7/005 (20130101); H01Q1/362 (20130101); H01Q15/141 (20130101);

Field of Classification Search

CPC: H01Q (1/38); H01Q (1/362); H01Q (15/141); H01Q (1/364); H01Q (15/10); H01Q (17/002); H01Q (15/0086); H01P (7/005); G02B (1/002)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2005/0008308	12/2004	Bit	385/123	B82Y 20/00
2011/0175795	12/2010	Toujo	343/909	G02B 1/007

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
105137520	12/2014	CN	N/A
106163247	12/2015	CN	N/A
2011097334	12/2010	JP	N/A
20180054105	12/2017	KR	N/A
2010026907	12/2009	WO	N/A

OTHER PUBLICATIONS

International Search Report from corresponding PCT application PCT/JP2021/037892, dated Dec. 7, 2021. cited by applicant

He Zidong et al., "Ultrawide bandwidth and large-angle electromagnetic wave absorption based on triple-nested helix metamaterial absorbers", Journal of Applied Physics, American Institute of Physics, 2 Huntington Quadrangle, Melville, NY 11747, vol. 127, No. 17, May 6, 2020. cited by applicant

Soumitra Mokashi-Punekar et al., "Construction of Chiral, Helical Nanoparticle Superstructures: Progress Prospects", Advanced Materials, VCH Publishers, DE, vol. 32, No. 41, Dec. 9, 2019. cited by applicant

Zhenyu Yang et al, "A novel helical metamaterial absorber: Simulation study with the FDTD method", Metamaterials (META), 2012 International Workshop On, IEEE, Oct. 8, 2012, pp. 1-3. cited by applicant

Background/Summary

TECHNICAL FIELD

(1) The present technology relates to a technique using a wave control medium and the like, and more specifically, to a technique of controlling wave motion using an artificial structure.

BACKGROUND ART

(2) Conventionally, it has been proposed to use a metamaterial having characteristics such as a negative refractive index for reflection, shielding, absorption, phase modulation, and the like of various waves including radio waves, light waves, and sound waves. Here, the metamaterial refers to an artificial structure that generates a function that cannot be exhibited by a substance that exists in nature. The metamaterial is produced by, for example, aligning unit microstructures such as metals, dielectrics, magnetic bodies, semiconductors, and superconductors at sufficiently short intervals with respect to a wavelength to exhibit properties that do not exist in nature. The metamaterial thus produced can control wave motion of electromagnetic waves or the like by controlling the permittivity and the permeability.

(3) A wave control medium, which is a unit structure of the metamaterial, usually has a size of about 1/10 of a wavelength, and exerts the function by being formed into an array structure of about several units. When a wave having a long wavelength such as a microwave or a sound wave in an audible range is used, a metamaterial structure is also enlarged according to the wavelength, and a large footprint is required. This causes a problem when such wave motion is used in a small electronic device.

(4) As a solution of downsizing, for example, Patent Document 1 proposes a metamaterial including: a plurality of first resonators each of which generates a negative permittivity with respect to a predetermined wavelength, each of the plurality of first resonators including an internal space; a plurality of second resonators each of which generates a negative permeability with respect to the predetermined wavelength; and a support member that fixes positions of the first resonators and the second resonators, in which the support member fixes each of the second resonators inside the plurality of first resonators and fixes the plurality of first resonators such that the plurality of first resonators is spatially continuous.

(5) Here, because the operation principle of the metamaterial is based on a resonance phenomenon due to interaction between a wave motion and a structure, a response intensity of the metamaterial sharply decreases at frequencies other than the resonance frequency, and a response is obtained in a narrowband frequency range. This causes a problem in a case where a broadband frequency is used at the same time. However, the technique of Patent Document 1 does not propose a solution for the metamaterial to achieve downsizing and widening of the bandwidth at the same time and putting the metamaterial into practical use.

(6) Meanwhile, as a solution to downsizing and widening of the bandwidth, for example, Non-Patent Document 1 discloses a metamaterial having a structure in which a three-dimensional spiral part is disposed on a base of a two-dimensional square lattice.

CITATION LIST

Patent Document

(7) Patent Document 1: International Publication No. WO 2010/026907

Non-Patent Document

(8) Non-Patent Document 1: SCIENCE 18 Sep. 2009: Vol. 325, Issue 5947, pp. 1513-1515, "Gold

SUMMARY OF THE INVENTION

Problems to be Solved by the Invention

(9) However, in the technique of Non-Patent Document 1, because impedance values of the base and the spiral part are greatly different from each other, due to impedance mismatch between the base and the spiral part, a wave of an incident electromagnetic wave or the like is reflected at a matching portion between the base and the spiral part, and the wave motion cannot be absorbed. Therefore, the technique of Non-Patent Document 1 cannot be used for a member or the like that absorbs and controls the wave motion.

(10) Accordingly, a main object of the present technology is to provide a wave control medium that can absorb and control wave motion while achieving downsizing and wider bandwidth of a metamaterial and the like.

Solution to Problems

(11) In the present technology, there is provided a wave control medium including a three-dimensional microstructure having a base, a spiral part, and a matching element disposed between the base and the spiral part, in which the three-dimensional microstructure includes a material selected from any one of a metal, a dielectric, a magnetic body, a semiconductor, and a superconductor, or a combination of a plurality of these materials.

(12) Furthermore, the spiral part may have a multilayer structure. The spiral part may have a cone shape. At least two of the three-dimensional microstructures may be provided. The at least two of the three-dimensional microstructures may have a continuous structure in which the structures are intertwined while facing each other without being in contact with each other. At least one of the three-dimensional microstructures may have any one of a wire shape, a plate shape, and a sphere shape.

(13) Furthermore, the present technology provides a wave control element in which a plurality of the above wave control media is integrated in an array structure or dispersedly disposed. Furthermore, it is also possible to provide a wave control element including the above wave control medium, the wave control element having a specific bandwidth of a response of 30% or more, and an absorption intensity in the specific bandwidth of 50% or more. In addition, the present technology provides a wave control member including the above wave control medium.

(14) Furthermore, the present technology provides a metamaterial including the above wave control medium and a wave control device including the metamaterial. Furthermore, the present technology provides a wave control device including an electromagnetic wave absorbing and/or blocking member having the above wave control medium and the above metamaterial.

Furthermore, the present technology provides a wave control device including a sensor having the above wave control medium or the above electromagnetic wave absorbing and/or blocking member. In addition, the present technology provides a wave control device that performs signal transmission/reception or light reception/emission using the above wave control medium.

(15) Moreover, the present technology provides a manufacturing method of a wave control medium, the manufacturing method including forming a microstructure into a three-dimensional structure using a molecular template that utilizes self-assembly of an organic substance, the microstructure including a material selected from any one of a metal, a dielectric, a magnetic body, a semiconductor, and a superconductor, or a combination of a plurality of these materials.

Effects of the Invention

(16) According to the present technology, it is possible to provide a wave control medium that can absorb and control wave motion while achieving downsizing and wider bandwidth of a metamaterial and the like. Note that the above effects are not necessarily limited, and any of the

effects described in the present description or other effects that can be grasped from the present description may be exhibited together with the above effects or instead of the above effects.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a perspective view showing a configuration example of a wave control medium according to a first embodiment of the present technology.
- (2) FIG. 2 is a cross-sectional view showing a configuration example of a wave control medium according to a second embodiment of the present technology.
- (3) FIG. 3 is a perspective view showing a configuration example of a wave control medium according to a third embodiment of the present technology.
- (4) FIG. 4 is a perspective view showing a configuration example of a wave control medium according to a fourth embodiment of the present technology.
- (5) FIG. 5 is a cross-sectional view showing a configuration example of a wave control medium according to a fifth embodiment of the present technology.
- (6) FIG. 6 is a perspective view showing a configuration example of a wave control medium according to a sixth embodiment of the present technology.
- (7) FIG. 7 is a perspective view showing a configuration example of a wave control medium according to a seventh embodiment of the present technology.
- (8) FIG. 8 is a perspective view showing a configuration example of a wave control medium according to an eighth embodiment of the present technology.
- (9) FIG. 9 is a perspective view showing a modified example of the wave control medium according to the eighth embodiment of the present technology.
- (10) FIG. 10 is a perspective view showing another modified example of the wave control medium according to the eighth embodiment of the present technology.
- (11) FIG. 11 is a perspective view showing a configuration example of a wave control medium according to a ninth embodiment of the present technology.
- (12) FIG. 12 is a perspective view showing a modified example of the wave control medium according to the ninth embodiment of the present technology.
- (13) FIG. 13 is a perspective view showing a configuration example of a wave control medium according to a tenth embodiment of the present technology.
- (14) FIG. 14 is a cross-sectional view showing a configuration example of an electromagnetic wave absorbing sheet according to an eleventh embodiment of the present technology.
- (15) FIG. 15 is a cross-sectional view showing a configuration example of a waveguide according to a twelfth embodiment of the present technology.
- (16) FIG. 16 is a cross-sectional view showing a modified example of the waveguide according to the twelfth embodiment of the present technology.
- (17) FIG. 17 is a graph for explaining a specific bandwidth of a metamaterial having a wave control medium according to the present technology.

MODE FOR CARRYING OUT THE INVENTION

- (18) Hereinafter, preferred embodiments for carrying out the present technology are described with reference to the drawings. The embodiments described below each show an example of the representative embodiment of the present technology, and any of the embodiments can be combined with each other. Furthermore, the scope of the present technology is not narrowly interpreted by these. Note that the description is given in the following order.
1. First embodiment (Single-turn coil type 1) (1) Overview of metamaterial (2) Configuration example of wave control medium 1
 2. Second embodiment (Single-turn coil type 2) 3. Third embodiment (Multiple coil type 1) 4. Fourth embodiment (Multiple coil type 2) (1) Configuration example of wave control medium

10 (2) Example of manufacturing method of wave control medium **10** Fifth embodiment (Coaxial cable type) 6. Sixth embodiment (Double gyroid type) 7. Seventh embodiment (Cone type) 8. Eighth embodiment (Combination with wire structure) (1) Combination of a plurality of structures (2) Configuration example of wave control medium **50** (3) Modified example 1 of wave control medium **50** (4) Modified example 2 of wave control medium **50** 9. Ninth embodiment (Combination with plate structure) (1) Configuration example of wave control medium **80** (2) Modified example of wave control medium **80** 10. Tenth embodiment (Combination with sphere structure) 11. Eleventh embodiment (Electromagnetic wave absorbing member) 12. Twelfth embodiment (Electromagnetic waveguide) (1) Configuration example of electromagnetic waveguide **120** (2) Modified example of electromagnetic waveguide **120** 13. Specific bandwidth 14. Other applications

1. First Embodiment (Single-Turn Coil Type **1**)

(19) (1) Overview of Metamaterial

(20) First, an outline of a metamaterial having a wave control medium which is a unit structure of a medium that controls wave motion of an electromagnetic wave, a sound wave, and the like is described.

(21) The metamaterial is configured, for example, by aligning a unit structure in a dielectric, the unit structure having a size sufficiently smaller than a wavelength of an electromagnetic wave and having a resonator inside. Note that the interval between the unit structures (resonators) of the metamaterial is set to about 1/10 or less, or about 1/5 or less of the wavelength of the electromagnetic wave to be used.

(22) By setting such a configuration, a permittivity ϵ and/or a permeability μ of the metamaterial can be artificially controlled, and a refractive index $n (= \pm[\epsilon \cdot \mu]^{1/2})$ of the metamaterial can be artificially controlled. In particular, in the metamaterial, the refractive index can be set to a negative value with respect to an electromagnetic wave having a desired wavelength by appropriately adjusting, for example, a shape, a dimension, and the like of the unit structure to simultaneously realize the negative permittivity and the negative permeability.

(23) Incidentally, a resonance (operation) frequency ω_0 of the metamaterial is determined by an inductance L and a capacitance C in a case where the metamaterial is described as a circuit according to the LC circuit theory, and the larger the inductance L and the capacitance C , the lower the resonance frequency. That is, a high-density structure having a large inductance L and a large capacitance C can function for a wave having a long wavelength (=a low frequency) even with a small metamaterial.

(24) Therefore, in the present embodiment, in order to put the metamaterial as described above into practical use, an example of a configuration of a wave control medium is described, the wave control medium being a unit structure of the metamaterial that can absorb and control the wave motion while simultaneously realizing downsizing and wider bandwidth of the metamaterial.

(25) (2) Configuration Example of Wave Control Medium **1**

(26) A configuration example of a wave control medium **1** according to the first embodiment of the present technology is described with reference to FIGS. **1A** and **1B**. FIG. **1A** is a perspective view showing a configuration example of the wave control medium **1** of a single-turn coil type **1** according to the present embodiment. FIG. **1B** is a diagram for explaining impedance matching of the wave control medium **1**. The wave control medium **1** according to the present embodiment is a unit structure of the metamaterial and can control the wave motion of an electromagnetic wave, a sound wave, and the like.

(27) As shown in FIG. **1A**, the wave control medium **1** includes, as an example, a three-dimensional microstructure having a base **2** formed in a substrate or a rectangular parallelepiped, a spiral part **3** having a spiral structure, and a matching element **4** disposed between the base **2** and the spiral part **3**. Such a three-dimensional microstructure includes a material selected from any one of a metal, a dielectric, a magnetic body, a semiconductor, and a superconductor, or a combination

of a plurality of these materials.

(28) As an example, a loss type element including a resistor, a circuit type element including a capacitor and an inductor, or the like can be applied as the matching element 4.

(29) The wave control medium 1 according to the present embodiment provides a solution for simultaneously achieving downsizing and wider bandwidth using a single-turn coil having a three-dimensional spiral structure as a unit microstructure of the metamaterial.

(30) A metamaterial having a three-dimensional coil structure is known to resonate with a wave having a wavelength of about the same length to a coil length of the metamaterial and a shorter wave having a wavelength being a fraction of the wavelength by a constant value, and to exhibit broadband characteristics in which a plurality of resonance peaks is broad-coupled. Therefore, according to the wave control medium 1, it is possible to realize a metamaterial having the broadband characteristics by being downsized with a fine structure and including the spiral part 3 having a three-dimensional coil structure.

(31) Moreover, an impedance value $Z1$ of the spiral part 3 and an impedance value $Z2$ of the base 2 are greatly different from each other due to a difference in materials. Therefore, when the base 2 and the spiral part 3 are directly joined to each other, due to impedance mismatch between the base 2 and the spiral part 3, an incident wave IW such as an electromagnetic wave is reflected at a matching portion between the base 2 and the spiral part 3, and the wave motion cannot be absorbed. That is, energy cannot be dissipated in the substrate in the base 2.

(32) As shown in FIGS. 1A and 1B, in the wave control medium 1, the matching element 4 having an impedance value $Z3$ for filling a difference between the impedance values of the base 2 and the spiral part 3 is disposed between the base 2 and the spiral part 3 to make the entire impedance value to change gently, which enables a reflected wave RW to be absorbed in the base 2.

(33) Therefore, according to the wave control medium 1, it is possible to absorb and control the wave motion while achieving downsizing and wider bandwidth of the metamaterial and the like having the wave control medium 1. Moreover, according to the wave control medium 1, it is possible to provide a three-dimensional metamaterial exhibiting an electromagnetic wave absorbing function with high efficiency over a wide frequency band.

(34) Furthermore, according to the wave control medium 1, the wave control element (an antenna, a lens, a speaker and the like) using the wave control medium 1 can be significantly downsized. In addition, according to the wave control medium 1, new shielding functions such as complete shielding, absorption, rectification, and filtering that cannot be realized by a natural material can be performed. Moreover, the wave control medium 1 can exhibit the above effects not only in an electromagnetic wave but also in a wide range such as a light wave or a sound wave. In particular, the wave control medium 1 can exert an effect in a region having a long wavelength and a wide band.

(35) In addition, the wave control medium 1 can provide a wave control member including the wave control medium 1. As the wave control member, for example, an antireflection film, an antireflection coating material, a filter, an energy conversion member, a photoelectric conversion member, and the like can be applied.

(36) In addition, the wave control medium 1 can provide a wave control device including the wave control medium 1. As the wave control device, for example, an antenna, an infrared sensor, a visible light sensor, an electromagnetic wave measurement device, or the like can be applied.

2. Second Embodiment (Single-Turn Coil Type 2)

(37) Next, a configuration example of a wave control medium 5 according to a second embodiment of the present technology is described with reference to FIG. 2. FIG. 2A is a perspective view showing a configuration example of the wave control medium 5 of a single-turn coil type 2 according to the present embodiment. FIG. 2B is a side view showing a configuration example of the wave control medium 5, and FIG. 2C is a plan view showing a configuration example of the wave control medium 5. The wave control medium 5 is a unit structure of the metamaterial

similarly to the first embodiment.

(38) As shown in FIG. 2A, the wave control medium 5 includes, as an example, a three-dimensional microstructure having a base 2 formed in a substrate or a rectangular parallelepiped, a spiral part 3 having a spiral structure, and a matching element 6 disposed between the base 2 and the spiral part 3. The matching element 6 is disposed on the base 2 over the entire surface facing the spiral part 3.

(39) The base 2 of the wave control medium 5 includes a resin or a dielectric. The spiral part 3 of the wave control medium 5 includes a thin copper wire. The matching element 6 includes a copper plate, a resin, or a resistance element.

(40) As shown in FIG. 2B, a height L1 of the spiral part 3 is preferably $1/100$ to $1/2$ of the wavelength of the incident wave motion, and a width S1 of one turn of the spiral part 3 in the direction perpendicular to the surface of the base 2 is preferably $1/1000$ to $1/10$ of the wavelength of the incident wave motion. The wave control medium 5 has a structure that exerts a role equivalent to that of a capacitor by an interval of the width S1.

(41) Furthermore, as shown in FIG. 2C, a diameter D1 of the spiral part 3 is preferably $1/100$ to $1/2$ of the wavelength of the incident wave motion, and a width d1 of the copper thin wire of the spiral part 3 is preferably $1/1000$ to $1/100$ of the wavelength of the incident wave motion.

(42) Therefore, with the above configuration, according to the wave control medium 5, it is possible to absorb and control the wave motion while achieving downsizing and wider bandwidth of a metamaterial and the like having the wave control medium 1, similarly to the first embodiment.

3. Third Embodiment (Multiple Coil Type 1)

(43) Next, a configuration example of a wave control medium 7 according to a third embodiment of the present technology is described with reference to FIG. 3. FIG. 3A is a perspective view showing a configuration example of the wave control medium 7 of a multiple coil type 1 according to the present embodiment. FIG. 3B is a side view showing a configuration example of the wave control medium 7, and FIG. 3C is a plan view showing a configuration example of the wave control medium 7. The wave control medium 7 is a unit structure of the metamaterial similarly to the first embodiment.

(44) As shown in FIG. 3A, the wave control medium 7 includes, as an example, a three-dimensional microstructure having a base 2 formed in a substrate or a rectangular parallelepiped, spiral parts 8 and 9 having a double spiral structure in which spirals vertically overlap with each other, and a matching element 6 disposed between the base 2 and the spiral parts 8 and 9. The matching element 6 is disposed on the base 2 over the entire surface facing the spiral parts 8 and 9.

(45) As shown in FIG. 3B, a height L2 of the spiral parts 8 and 9 is preferably $1/100$ to $1/2$ of the wavelength of the incident wave motion, and a width S2 of the spiral parts 8 and 9 with respect to the direction perpendicular to the surface of the base 2 is preferably $1/1000$ to $1/10$ of the wavelength of the incident wave motion. The wave control medium 7 has a structure in which each of the spiral parts 8 and 9 has a role equivalent to that of reactance, and has a role equivalent to a capacitor by an interval of the width S2.

(46) Furthermore, as shown in FIG. 3C, a diameter D2 of the spiral parts 8 and 9 is preferably $1/100$ to $1/2$ of the wavelength of the incident wave motion, and a width d2 of the copper thin wire of the spiral parts 8 and 9 is preferably $1/1000$ to $1/100$ of the wavelength of the incident wave motion. Moreover, a deviation in the spiral direction (circumferential direction) between an end of the spiral part 8 and an end of the spiral part 9 is preferably 1° to 90° expressed by a center angle θ of one turn.

(47) The materials of the spiral part 8 and the spiral part 9 are not necessarily the same, and may be different materials. In addition, the spiral part 8 and the spiral part 9 form a capacitor between the lower surface of the spiral part 8 and the upper surface of the spiral part 9 facing each other, and form an inductor by forming a three-dimensional multiple resonance structure by the spiral

structure of the spiral part **8** and the spiral part **9**.

(48) The wave control medium **7** multiplexes the three-dimensional coil structure to increase inductance, and meanwhile, increases capacitance by acting as a capacitor between the thin wires. Therefore, according to the wave control medium **7**, it is possible to realize a metamaterial having the broadband characteristics by being downsized with a fine structure and having the three-dimensional multiple resonance structure. In addition, the wave control medium **7** can absorb and control the wave motion by including the matching element **6**, similarly to the first embodiment.

4. Fourth Embodiment (Multiple Coil Type 2)

(49) (1) Configuration Example of Wave Control Medium **10**

(50) Next, a configuration example of a wave control medium **10** according to a fourth embodiment of the present technology is described with reference to FIG. **4**. FIG. **4** is a perspective view showing a configuration example of a wave control medium **10** according to the present embodiment. The wave control medium **10** according to the present embodiment is a unit structure of the metamaterial and can control the wave motion of an electromagnetic wave, a sound wave, and the like.

(51) As shown in FIG. **4**, the wave control medium **10** includes a coil **11** and a coil **12** which constitute a three-dimensional microstructure having a spiral structure. The wave control medium **10** forms a double spiral structure of thin wires in which the coils are wound in parallel to each other while the coil **12** faces the outer side of the coil **11**. The wave control medium **10** is not limited to a double coil, and may have a multiple coil structure of three or more. In the case of multiple coils of three or more, the facing directions of the coils are not limited to be in the parallel positional relationship to each other, and it is sufficient that the coils are arranged so as not to be in direct contact with each other.

(52) Each of the coil **11** and the coil **12** has a shape of a thin wire, the wire including a material selected from any one of a metal, a dielectric, a magnetic body, a semiconductor, and a superconductor, or a combination of a plurality of these materials. The materials of the coil **11** and the coil **12** are not necessarily the same, and may be different materials. In addition, the coil **11** and the coil **12** form a capacitor between the side surface of the coil **11** and the side surface of the coil **12** facing each other, and form an inductor by forming a three-dimensional multiple resonance structure by the spiral structure of the coil **11** and the coil **12**.

(53) The wave control medium **10** according to the present embodiment provides a solution for simultaneously achieving downsizing and wider bandwidth using a multiple coil as a unit microstructure of the metamaterial, the multiple coil having a three-dimensional spiral structure including the plurality of conductor thin wires facing each other.

(54) A metamaterial having a three-dimensional coil structure is known to resonate with a wave having a wavelength of about the same length to a coil length of the metamaterial and a shorter wave having a wavelength being a fraction of the wavelength by a constant value, and to exhibit broadband characteristics in which a plurality of resonance peaks is broad-coupled. Furthermore, the relationship between the size and the wavelength of a metamaterial structure depends on inductance and capacitance when the metamaterial structure is regarded as an equivalent circuit, and a metamaterial having a larger inductance and a larger capacitance can be made smaller.

(55) The wave control medium **10** multiplexes the three-dimensional coil structure to increase inductance, and meanwhile, increases capacitance by acting as a capacitor between the thin wires. Therefore, according to the wave control medium **10**, it is possible to realize a metamaterial having the broadband characteristics by being downsized with a fine structure and having the three-dimensional multiple resonance structure.

(56) Furthermore, according to the wave control medium the wave control element (an antenna, a lens, a speaker and the like) using the wave control medium **10** can be significantly downsized. In addition, according to the wave control medium **10**, new shielding functions such as complete shielding, absorption, rectification, and filtering that cannot be realized by a natural material can be

performed. Moreover, the wave control medium **10** can exhibit the above effect not only in an electromagnetic wave but also in a wide range such as a light wave or a sound wave. In particular, the wave control medium **10** can exert an effect in a region having a long wavelength and a wide band.

(57) (2) Example of Manufacturing Method of Wave Control Medium **10**

(58) Next, an example of a manufacturing method of the wave control medium **10** according to the present embodiment is described.

(59) The wave control medium **10** can be manufactured by a molecular template method as an example. Here, the molecular template method refers to a method in which a microscopic and complicated structure obtained from an organic substance (such as artificial/biopolymer, nanoparticle, and liquid crystal molecule) is used as a template to form a microstructure including a material selected from any one of a metal, a dielectric, a magnetic body, a semiconductor, a superconductor, and the like, or a combination of a plurality of these materials. As the molecular template method, two methods described later are mainly known.

(60) The first method is a method of coating an organic structure with plating or the like. The second method is a method of using a structure formed by using an organic substance into which a precursor such as a metal or an oxide is previously introduced, and the structure is fired, oxidized and reduced, and like to convert the precursor into a metal, an oxide, or the like.

(61) In the present embodiment, the wave control medium **10** including the coil **11** and the coil **12** having a metal spiral structure is manufactured by using a three-dimensional spiral structure including an organic substance as a template and applying electrolysis or electroless plating to the structure. In the manufacturing process of the wave control medium **10**, the coil **11** and the coil **12** can be formed in a three-dimensional fine structure by utilizing self-assembly of the organic substance. According to the manufacturing method of the present embodiment, it is possible to easily manufacture the wave control medium **10** having a complicated and microscopic three-dimensional microstructure that is difficult to manufacture by a normal method.

(62) Note that the wave control medium **10** may be manufactured by a method of forming a three-dimensional spiral structure using the fact that a metal pattern is deflected due to stress after etching of a metal film manufactured on a substrate such as a dielectric.

5. Fifth Embodiment (Coaxial Cable Type)

(63) Next, a configuration example of a wave control medium **20** according to a fifth embodiment of the present technology is described with reference to FIG. 5. FIG. 5 is a cross-sectional view showing a configuration example of the wave control medium **20** of a coaxial cable type according to the present embodiment. The wave control medium **20** according to the present embodiment is a unit structure of the metamaterial similarly to the first embodiment.

(64) As shown in FIG. 5, the wave control medium **20** has a shape of a coaxial cable type. The wave control medium **20** is formed in, for example, a two-layer structure having a shape in which an outer surface of a coil **21**, which constitutes a three-dimensional microstructure having a spiral structure similarly to the wave control medium **10** according to the first embodiment, is covered with the inner surface of a coil **22** with a minute space interposed therebetween. The wave control medium **20** forms a single coil structure as a whole, but has two three-dimensional microstructures including the coil **22** and the coil **21** incorporated in the coil **22**. Note that the wave control medium **20** is not limited to a two-layer structure and may have three or more layers, and is not limited to a single coil as a whole and may have a double or more multi-coil structure.

(65) The coil **21** and the coil **22** each have a shape of a thin wire. The coil **21** and the coil **22** form a capacitor between the outer side surface of the coil **21** and the inner side surface of the coil **22** facing each other, and form an inductor by forming a three-dimensional multiple resonance structure by the spiral structure of the coil **21** and the coil **22**.

(66) The wave control medium **20** multiplexes the three-dimensional coil structure to increase inductance, and meanwhile, increases capacitance by acting as a capacitor in a space between the

outer side surface of the coil **21** and the inner side surface of the coil **22**, both of which are the thin wires. Therefore, according to the wave control medium **20**, it is possible to realize a metamaterial having the broadband characteristics by being downsized with a fine structure and having the three-dimensional multiple resonance structure similarly to the first embodiment.

6. Sixth Embodiment (Double Gyroid Type)

(67) Next, a configuration example of a wave control medium **30** according to a sixth embodiment of the present technology is described with reference to FIG. 6. FIG. 6 is a perspective view showing a configuration example of a wave control medium **30** of a double gyroid type according to the present embodiment. The wave control medium **30** according to the present embodiment is also a unit structure of the metamaterial similarly to the first embodiment.

(68) As shown in FIG. 6, the wave control medium **30** has a shape of a double gyroid type. Here, the double gyroid refers to a continuous structure in which two coils face each other and are entangled without being in contact with each other. The wave control medium **30** includes a coil **31** and a coil **32** of a three-dimensional microstructure, and forms a continuous three-dimensional structure in which the coil **31** and the coil **32** face each other and are entangled without being in contact with each other. Note that the wave control medium **30** is not limited to a double gyroid having a double coil structure, and may be a gyroid having a multiple coil structure of three or more.

(69) The coil **31** and the coil **32** each have a shape of a thin wire. The coil **31** and the coil **32** form a capacitor between the side surface of the coil **31** and the side surface of the coil **32** facing each other, and form an inductor by forming a three-dimensional multiple resonance structure by the continuous three-dimensional structure of the coil **31** and the coil **32**.

(70) The wave control medium **30** multiplexes the three-dimensional coil structure to increase inductance, and meanwhile, increases capacitance by acting as a capacitor in a space between the side surface of the coil **31** and the side surface of the coil **22**, both of which are the thin wires. Therefore, according to the wave control medium **30**, it is possible to realize a metamaterial having the broadband characteristics by being downsized with a fine structure and having the three-dimensional multiple resonance structure similarly to the first embodiment.

7. Seventh Embodiment (Cone Type)

(71) Next, a configuration example of a wave control medium **40** according to a seventh embodiment of the present technology is described with reference to FIG. 7. FIG. 7 is a perspective view showing a configuration example of a wave control medium **40** of a cone type according to the present embodiment. The wave control medium **40** according to the present embodiment is also a unit structure of the metamaterial similarly to the first embodiment.

(72) As shown in FIG. 7, the wave control medium **40** as a whole has a shape of a cone type extending downward in the paper surface of FIG. 7. The wave control medium **40** includes a coil **41** and a coil **42** of a three-dimensional microstructure, and forms a double spiral structure of thin wires in which the coils are wound in parallel to each other while the coil **42** faces the outer side of the coil **41**. Note that the wave control medium **40** is not limited to a double coil, and may have a multiple coil structure of three or more. Furthermore, the wave control medium **40** as a whole has a shape of a cone type narrowing downward in the paper surface of FIG. 7.

(73) The coil **41** and the coil **42** each have a shape of a thin wire. The coil **41** and the coil **42** form a capacitor between the side surface of the coil **41** and the side surface of the coil **42** facing each other, and form an inductor by forming a three-dimensional multiple resonance structure by the cone spiral structure of the coil **41** and the coil **42**.

(74) The wave control medium **40** multiplexes the three-dimensional coil structure to increase inductance, and meanwhile, increases capacitance by acting as a capacitor in a space between the side surface of the coil **41** and the side surface of the coil **42**, both of which are the thin wires. Therefore, according to the wave control medium **40**, it is possible to realize a metamaterial having the broadband characteristics by being downsized with a fine structure and having the three-

dimensional multiple resonance structure similarly to the first embodiment.

8. Eighth Embodiment (Combination with Wire Structure)

(75) (1) Combination of a Plurality of Structures

(76) In an eighth embodiment of the present technology, an example in which a wave control medium is designed by a combination of a plurality of structures is described. The purpose of combining the plurality of structures is, for example, to provide a structure in which each structure functions with respect to an electric field and a magnetic field constituting an electromagnetic wave. That is, it is an object to share functions by each of the structures.

(77) Here, functioning with respect to the electric field will control a relative permittivity $\epsilon_{\text{sub.r}}$, and functioning with respect to the magnetic field will control the relative permeability $\mu_{\text{sub.r}}$. Therefore, the wave control medium according to the present embodiment can control the relative permittivity and the relative permeability to desired values with a high degree of freedom by combining a plurality of structures.

(78) (2) Configuration Example of Wave Control Medium 50

(79) Next, a configuration example of a wave control medium 50 according to the eighth embodiment of the present technology is described with reference to FIG. 8. FIG. 8 is a perspective view showing a configuration example of the wave control medium 50 according to the present embodiment. The wave control medium 50 is different from the wave control medium 10 according to the first embodiment in that a wire structure is combined with a double coil structure. Other configurations of the wave control medium 50 are similar to those of the wave control medium 10.

(80) As shown in FIG. 8, the wave control medium 50 includes a coil 11 and a coil 12 which constitute a three-dimensional microstructure having a spiral structure. The wave control medium 50 forms a double spiral structure of thin wires in which the coils are wound in parallel to each other while the coil 12 faces the outer side of the coil 11. Moreover, the wave control medium 50 is provided with a rod-like thin wire 51 extending in a direction in which the central axis extends at a central axis position of the spiral structure on the inner side of the coil 11. The wire 51 is disposed separated from the coil 11 by a minute interval.

(81) The coil of the wave control medium 50 is not limited to a double coil, and may be a single coil or have a multiple coil structure of three or more. In the case of multiple coils of three or more, the facing directions of the coils are not limited to be in the parallel positional relationship to each other, and it is sufficient that the coils are arranged so as not to be in direct contact with each other.

(82) Similarly to the coil 11 and the coil 12, the wire 51 has a shape of a thin wire, the wire including a material selected from any one of a metal, a dielectric, a magnetic body, a semiconductor, and a superconductor, or a combination of a plurality of these materials. In addition, the material of the wire 51 is not necessarily the same as that of the coil 11 and the coil 12, and the materials may be different from each other. Moreover, the number of wires 51 is not limited to one, and may be two or more. Note that the wire 51 is not limited to a state of being contained in the coil 11 and the coil 12, and may be in a state of being adjacent to or near the coil 11 and the coil 12.

(83) In the wave control medium 50, it is assumed that an electric field direction of the radio wave to be applied coincides with a vibration direction of electrons in which the wire 51 extends, and a magnetic field direction of the radio wave to be applied is orthogonal to a magnetic force direction electromagnetically induced by the annular current flowing in the coil 11 and the coil 12. At this time, the wire 51 functions to the magnetic field, and the coil 11 and the coil 12 function to the electric field. That is, the electrons vibrating along the wire 51 function with respect to the magnetic field. In addition, the coil 11 and the coil 12 function with respect to the electric field.

(84) Here, functioning with respect to the magnetic field will control the relative permeability $\mu_{\text{sub.r}}$, and functioning with respect to the electric field will control the relative permittivity $\epsilon_{\text{sub.r}}$. Therefore, the wave control medium 50 can control the relative permeability and the relative permittivity to desired values with a high degree of freedom by combining a plurality of

structures.

(85) According to the wave control medium **50** according to the present embodiment, in addition to the similar effects as those of the wave control medium **10** according to the first embodiment, in a case where desired physical properties are difficult to be obtained only by the spiral structure of the coil **11** and the coil **12**, the relative permeability and/or the relative permittivity can be finely adjusted by performing function role-sharing by combining the structure of the wire **51** to the spiral structure. Moreover, because the wave control medium **50** also serves as a capacitor between the wire **51** and the coil **11**, the capacitance can be increased more than that of the wave control medium **10**.

(86) (3) Modified Example 1 of Wave Control Medium **50**

(87) Next, a modified example 1 of the wave control medium **50** is described with reference to FIG. **9**. FIG. **9** is a perspective view showing a configuration example of a wave control medium **60** as the modified example 1 of the wave control medium **50**. The wave control medium **60** is different from the wave control medium **50** in that the wire is located outside the coil and extends in a direction orthogonal to the central axis of the coil. Other configurations of the wave control medium **60** are similar to those of the wave control medium **50**.

(88) As shown in FIG. **9**, the wave control medium **60** is provided with a rod-like thin wire **61** extending in a direction orthogonal to the central axis of the spiral structure of the coil **11** and the coil **12**, on the outer side of the coil **11** and the coil **12**. The wire **61** is disposed separated from the coil **12** by a minute interval.

(89) In the wave control medium **60**, it is assumed that the electric field direction of the radio wave to be applied coincides with the vibration direction of electrons in which the wire **61** extends, and the magnetic field direction of the radio wave to be applied coincides with the magnetic force direction electromagnetically induced by the annular current flowing in the coil **11** and the coil **12**. At this time, the wire **61** functions to the electric field, and the coil **11** and the coil **12** function to the magnetic field. That is, the electrons vibrating along the wire **61** function with respect to the electric field. In addition, when the annular current is generated by vibration of electrons along the coil **11** and the coil **12**, the magnetic force is induced at a central axis position in the center of the coil **11** and the coil **12** on the principle of electromagnetic induction, and as a result, the coil **11** and the coil **12** function with respect to the magnetic field.

(90) Here, functioning with respect to the electric field will control the relative permittivity $\epsilon_{\text{sub.r}}$, and functioning with respect to the magnetic field will control the relative permeability $\mu_{\text{sub.r}}$. Therefore, the wave control medium **60** can control the relative permittivity and the relative permeability to desired values with a high degree of freedom by combining a plurality of structures.

(91) According to the wave control medium **60** according to the present modified example, similarly to the wave control medium **50**, in a case where desired physical properties are difficult to be obtained only by the spiral structure of the coil **11** and the coil **12**, the relative permittivity and/or the relative permeability can be finely adjusted by performing function role-sharing by combining the structure of the wire **61** to the spiral structure.

(92) (4) Modified Example 2 of Wave Control Medium **50**

(93) Next, a modified example 2 of the wave control medium **50** is described with reference to FIG. **10**. FIG. **10** is a perspective view showing a configuration example of a wave control medium **70** as the modified example 2 of the wave control medium **50**. The wave control medium **70** is different from the wave control medium **50** in that the wire is located outside the coil. Other configurations of the wave control medium **70** are similar to those of the wave control medium **50**.

(94) As shown in FIG. **10**, the wave control medium **70** is provided with a rod-like thin wire **71** extending in a direction parallel to the central axis of the spiral structure of the coil **11** and the coil **12**, on the outer side of the coil **11** and the coil **12**. The wire **71** is disposed separated from the coil **12** by a minute interval.

(95) In the wave control medium **70**, it is assumed that the electric field direction of the radio wave

to be applied coincides with the vibration direction of electrons in which the wire **71** extends, and the magnetic field direction of the radio wave to be applied is orthogonal to the magnetic force direction electromagnetically induced by the annular current flowing in the coil **11** and the coil **12**. At this time, the wire **71** functions to the magnetic field, and the coil **11** and the coil **12** function to the electric field. That is, the electrons vibrating along the wire **71** function with respect to the magnetic field. In addition, the coil **11** and the coil **12** function with respect to the electric field. (96) The wave control medium **70** according to the present modified example can have the similar effect as the wave control medium **50**.

9. Ninth Embodiment (Combination with Plate Structure)

(97) (1) Configuration Example of Wave Control Medium **80**

(98) Next, a configuration example of a wave control medium **80** according to a ninth embodiment of the present technology is described with reference to FIG. **11**. FIG. **11** is a perspective view showing a configuration example of the wave control medium **80** according to the present embodiment. The wave control medium **80** is different from the wave control medium **10** according to the first embodiment in that a plate structure is combined with a double coil structure. Other configurations of the wave control medium **80** are similar to those of the wave control medium **10**. (99) As shown in FIG. **11**, the wave control medium **80** includes a coil **11** and a coil **12** similarly to the wave control medium **10**. Moreover, the wave control medium **80** is provided with a thin tabular plate **81** extending in a direction parallel to the central axis of the spiral structure of the coil **11** and the coil **12**, on the outer side of the coil **11** and the coil **12**. The plate **81** is disposed separated from the coil **12** by a minute interval.

(100) Similarly to the coil **11** and the coil **12**, the plate **81** has a shape of a thin wire, the wire including a material selected from any one of a metal, a dielectric, a magnetic body, a semiconductor, and a superconductor, or a combination of a plurality of these materials. In addition, the material of the plate **81** is not necessarily the same as that of the coil **11** and the coil **12**, and the materials may be different from each other. Moreover, the number of plates **81** is not limited to one, and may be two or more. Note that the plate **81** can also be provided at a central axis position of the spiral structure on the inner side of the coil **11** so as to be separated from the coil **11** in a direction in which the central axis extends. In this case, because the wave control medium **80** also serves as a capacitor between the plate **81** and the coil **11**, the capacitance can be increased more than that of the wave control medium **10**.

(101) In the wave control medium **80**, it is assumed that the electric field direction of the radio wave to be applied coincides with the vibration direction of electrons in which the plate **81** extends, and the magnetic field direction of the radio wave to be applied is orthogonal to the magnetic force direction electromagnetically induced by the annular current flowing in the coil **11** and the coil **12**. At this time, the plate **81** functions to the magnetic field, and the coil **11** and the coil **12** function to the electric field. That is, the electrons vibrating along the plate **81** function with respect to the magnetic field. In addition, the coil **11** and the coil **12** function with respect to the electric field.

(102) Here, functioning with respect to the magnetic field will control the relative permeability μ_r , and functioning with respect to the electric field will control the relative permittivity ϵ_r . Therefore, the wave control medium **80** can control the relative permeability and the relative permittivity to desired values with a high degree of freedom by combining a plurality of structures.

(103) According to the wave control medium **80** according to the present embodiment, in addition to the similar effects as those of the wave control medium **10** according to the first embodiment, in a case where desired physical properties are difficult to be obtained only by the spiral structure of the coil **11** and the coil **12**, the relative permeability and/or the relative permittivity can be finely adjusted by performing function role-sharing by combining the structure of the plate **81** to the spiral structure.

(104) (2) Modified Example of Wave Control Medium **80**

(105) Next, a modified example of the wave control medium **80** is described with reference to FIG.

12. FIG. 12 is a perspective view showing a configuration example of a wave control medium **90** as the modified example of the wave control medium **80**. The wave control medium **90** is different from the wave control medium **80** in that the plate extends in a direction orthogonal to the central axis of the coil. Other configurations of the wave control medium **90** are similar to those of the wave control medium **90**.

(106) As shown in FIG. 12, the wave control medium **90** is provided with a tabular thin plate **91** extending in a direction orthogonal to the central axis of the spiral structure of the coil **11** and the coil **12**, on the outer side of the coil **11** and the coil **12**. The plate **91** is disposed separated from the coil **12** by a minute interval.

(107) In the wave control medium **90**, it is assumed that the electric field direction of the radio wave to be applied coincides with the vibration direction of electrons in which the plate **91** extends, and the magnetic field direction of the radio wave to be applied coincides with the magnetic force direction electromagnetically induced by the annular current flowing in the coil **11** and the coil **12**. At this time, the plate **91** functions to the electric field, and the coil **11** and the coil **12** function to the magnetic field. That is, the electrons vibrating along the plate **91** function with respect to the electric field. In addition, when the annular current is generated by vibration of electrons along the coil **11** and the coil **12**, the magnetic force is induced at a central axis position in the center of the coil **11** and the coil **12** on the principle of electromagnetic induction, and as a result, the coil **11** and the coil **12** function with respect to the magnetic field.

(108) Here, functioning with respect to the electric field will control the relative permittivity $\epsilon_{\text{sub.r}}$, and functioning with respect to the magnetic field will control the relative permeability $\mu_{\text{sub.r}}$. Therefore, the wave control medium **90** can control the relative permittivity and the relative permeability to desired values with a high degree of freedom by combining a plurality of structures.

(109) According to the wave control medium **90** according to the present modified example, similarly to the wave control medium **80**, in a case where desired physical properties are difficult to be obtained only by the spiral structure of the coil **11** and the coil **12**, the relative permittivity and/or the relative permeability can be finely adjusted by performing function role-sharing by combining the structure of the plate **81** to the spiral structure.

10. Tenth Embodiment (Combination with Sphere Structure)

(110) Next, a configuration example of a wave control medium **100** according to a tenth embodiment of the present technology is described with reference to FIG. 13. FIG. 13 is a perspective view showing a configuration example of the wave control medium **100** according to the present embodiment. The wave control medium **100** is different from the wave control medium **10** according to the first embodiment in that a sphere structure is combined with a double coil structure. Other configurations of the wave control medium **100** are similar to those of the wave control medium **10**.

(111) As shown in FIG. 13, the wave control medium **100** includes a coil **11** and a coil **12** which constitute a three-dimensional microstructure similarly to the wave control medium **10**. Moreover, the wave control medium **100** is provided with a plurality of spheres **101** aligned in a direction in which the central axis extends at a central axis position of the spiral structure on the inner side of the coil **11**. Each of the spheres **101** is disposed separated from the coil **11** by a minute interval.

(112) Similarly to the coil **11** and the coil **12**, the sphere **101** includes a material selected from any one of a metal, a dielectric, a magnetic body, a semiconductor, and a superconductor, or a combination of a plurality of these materials. In addition, the material of the sphere **101** is not necessarily the same as that of the coil **11** and the coil **12**, and the materials may be different from each other. Moreover, the number of the spheres **101** is not limited, and may be any number. Note that the spheres **101** can also be disposed on the outer side of the coil **11** and the coil **12**.

(113) In the wave control medium **100**, it is assumed that the electric field direction of the radio wave to be applied coincides with the vibration direction of electrons in which the spheres **101** are aligned, and the magnetic field direction of the radio wave to be applied is orthogonal to the

magnetic force direction electromagnetically induced by the annular current flowing in the coil **11** and the coil **12**. At this time, the sphere **101** functions to the magnetic field, and the coil **11** and the coil **12** function to the electric field. That is, the electrons vibrating along the sphere **101** function with respect to the magnetic field. In addition, the coil **11** and the coil **12** function with respect to the electric field.

(114) According to the wave control medium **100** according to the present embodiment, in addition to the similar effects as those of the wave control medium **10** according to the first embodiment, in a case where desired physical properties are difficult to be obtained only by the spiral structure of the coil **11** and the coil **12**, the relative permeability and/or the relative permittivity can be finely adjusted by performing function role-sharing by combining the structure of the sphere **101** to the spiral structure. Moreover, because the wave control medium **100** also serves as a capacitor between the sphere **101** and the coil **11**, the capacitance can be increased more than that of the wave control medium **10**.

11. Eleventh Embodiment (Electromagnetic Wave Absorbing Member)

(115) Next, a configuration example of an electromagnetic wave absorbing member **110** according to an eleventh embodiment of the present technology is described with reference to FIG. **14**. FIG. **14** is a cross-sectional view showing a configuration example of an electromagnetic wave absorbing member **110** according to the present embodiment perpendicular to the extending direction.

(116) As shown in FIG. **14**, the electromagnetic wave absorbing member (electromagnetic wave absorbing sheet) **110** has a rectangular shape in which a cross section perpendicular to the extending direction is widened in the horizontal direction. The electromagnetic wave absorbing member **110** includes a support **111** in a lower part and a wave control medium **112** above the support **111**. The support **111** includes a metal, a dielectric, or a resin.

(117) The wave control medium **112** is a metamaterial having a resin of a wave control element in which any of the wave control media **10** to **100** described above is integrated in an array structure or a plurality of the wave control media is dispersedly disposed.

(118) The electromagnetic wave absorbing member **110** can absorb the irradiated electromagnetic wave by controlling a refractive index in a direction in which the electromagnetic wave is absorbed by the wave control medium **112**. Furthermore, the electromagnetic wave absorbing member **110** can also be used as an electromagnetic wave shielding member for shielding the irradiated electromagnetic wave by controlling a refractive index in a direction in which the electromagnetic wave is shielded by the wave control medium **112**. Moreover, the electromagnetic wave absorbing member **110** can be applied to a sensor such as an electronic toll collection system (ETC) or a radar.

12. Twelfth Embodiment (Electromagnetic Waveguide)

(119) (1) Configuration Example of Electromagnetic Waveguide **120**

(120) Next, a configuration example of an electromagnetic waveguide **120** according to a twelfth embodiment of the present technology is described with reference to FIG. **15**. FIG. **15** is a cross-sectional view showing a configuration example of an electromagnetic waveguide **120** according to the present embodiment perpendicular to the extending direction.

(121) As shown in FIG. **15**, the electromagnetic waveguide **120** has a rectangular shape in which a cross section perpendicular to the extending direction is widened in the horizontal direction. The electromagnetic waveguide **120** includes a support **121** at a lower part, and includes a medium **122** of silicon dioxide (SiO_2) or a dielectric at above the support **121**. The support **121** includes silicon (Si), a metal, a dielectric, or a resin.

(122) A waveguide tube **123** having a rectangular shape with a horizontally widened cross section is provided in the central part of the medium **122** at a contact position with the support **121**. The waveguide tube **123** includes a metamaterial having a resin of a wave control element in which any of the wave control media **10** to **100** described above is integrated in an array structure or a

plurality of the wave control media is dispersedly disposed. Note that the shapes of the electromagnetic waveguide **120** and the waveguide tube **123** are not limited to the present embodiment, and may be a cylindrical shape or the like.

(123) With the above configuration, the electromagnetic waveguide **120** can control the refractive index of the electromagnetic wave guided to the waveguide tube **123**. Furthermore, the electromagnetic waveguide **120** can be included in the arithmetic element.

(124) (2) Modified Example of Electromagnetic Waveguide **120**

(125) Next, a configuration example of the electromagnetic waveguide **120** is described with reference to FIG. **16**. FIG. **16** is a cross-sectional view showing a configuration example of an electromagnetic waveguide **130**, which is a modified example of the electromagnetic waveguide **120**, perpendicular to the extending direction. The electromagnetic waveguide **130** is different from the electromagnetic waveguide **120** in that a layer of a material other than the wave control medium is formed in the waveguide tube. The overall shape of the electromagnetic waveguide **130** is similar to that of the electromagnetic waveguide **120**.

(126) As shown in FIG. **16**, the electromagnetic waveguide **130** has a rectangular shape in which a cross section perpendicular to the extending direction is widened in the horizontal direction. The electromagnetic waveguide **130** includes a support **131** at a lower part, and includes a medium **132** of silicon dioxide (SiO_2) or a dielectric at above the support **131**. The support **131** includes a metal, a dielectric, or a resin.

(127) A waveguide tube **133** having a rectangular shape with a horizontally widened cross section is provided in the central part of the medium **132** at a contact position with the support **131**. The waveguide tube **133** includes a metamaterial having a resin of a wave control element in which any of the wave control media **10** to **100** described above is integrated in an array structure or a plurality of the wave control media is dispersedly disposed. Moreover, a medium layer **134** including silicon (Si) or resin and having the same shape as the waveguide tube **133** is formed in the central part of the waveguide tube **133** at the contact position with the support **131**.

(128) With the above configuration, the electromagnetic waveguide **130** can control the refractive index of the electromagnetic wave guided to the waveguide tube **133**.

13. Specific Bandwidth

(129) Next, a specific bandwidth of the metamaterial having the wave control medium according to each of the above embodiments of the present technology is described with reference to FIG. **17**. FIG. **17** is a graph for explaining an example of the specific bandwidth of the metamaterial having the wave control medium according to each of the above embodiments.

(130) In the graph in FIG. **17**, the vertical axis represents a frequency f , and the horizontal axis represents a frequency band B . A curve K in FIG. **17** shows a relationship between the bandwidth B and the frequency f of the metamaterial having the wave control medium according to each of the above embodiments.

(131) The above specific bandwidth of the metamaterial is obtained from the curve K . Here, the bandwidth refers to an inter-band distance of a frequency of $2 \times \frac{1}{2}$ of the peak frequency, and the specific bandwidth refers to a value obtained by dividing the bandwidth by the peak frequency that is the center frequency.

(132) In the curve K , the frequency is a peak frequency f_c in a band B_c , and is a frequency $f_{sub.1}$ which is $2 \times \frac{1}{2}$ of the peak frequency in the bands $B_{sub.1}$ and $B_{sub.2}$. Therefore, in the curve K , the bandwidth is $B_{sub.1} - B_{sub.2}$, and the fractional bandwidth is $(B_{sub.1} - B_{sub.2})/f_c$.

(133) As described above, the wave control medium according to each of the above embodiments is optimum in a case where the specific bandwidth of a response is 30% or more, and the absorption intensity in the specific bandwidth is 50% or more. Therefore, according to the above embodiments, it is possible to provide a wave control element including the wave control medium according to each of the above embodiments and having a specific bandwidth of a response of 30% or more, and an absorption intensity in the specific bandwidth of 50% or more. Note that, in the

wave control element, the above wave control medium may be integrated in an array structure, or a plurality of the wave control media may be dispersedly disposed.

14. Other Applications

(134) Next, applications of the metamaterial having the wave control medium according to each of the above embodiments of the present technology is described.

(135) In addition to the applications described above, the metamaterial having the wave control medium according to each of the above embodiments can be applied to a wave control device that performs signal transmission/reception or light reception/emission, a small antenna, a low-profile antenna, a frequency selection filter, an artificial magnetic conductor, an electro band gap member, a noise suppression member, an isolator, a radio wave lens, a radar member, an optical lens, an optical film, an optical element for terahertz, a radio wave and optical camouflage/invisibility member, a heat dissipation member, a heat shielding member, a heat storage member, a non-linear device for electromagnetic wave modulation/demodulation, wavelength conversion, and the like, a speaker, and the like.

(136) Note that the present technology can have the following configurations. (1)

(137) A wave control medium including a three-dimensional microstructure having a base, a spiral part, and a matching element disposed between the base and the spiral part, in which the three-dimensional microstructure includes a material selected from any one of a metal, a dielectric, a magnetic body, a semiconductor, and a superconductor, or a combination of a plurality of these materials. (2)

(138) The wave control medium according to (1), in which the spiral part has a multilayer structure. (3)

(139) The wave control medium according to any one of (1) to (3), further including at least two of the three-dimensional microstructures. (4)

(140) The wave control medium according to (4), in which the at least two of the three-dimensional microstructures have a continuous structure in which the structures are intertwined while facing each other without being in contact with each other. (5)

(141) The wave control medium according to (4) or (5), in which at least one of the three-dimensional microstructures has any one of a wire shape, a plate shape, and a sphere shape. (6)

(142) A wave control element in which the wave control medium according to any one of (1) to (6) is integrated in an array structure. (7)

(143) A wave control element in which the wave control medium according to any one of (1) to (6) is dispersedly disposed in plural numbers. (8)

(144) A wave control element including the wave control medium according to any one of (1) to (6), in which the wave control element has a specific bandwidth of a response of 30% or more, and an absorption intensity in the specific bandwidth of 50% or more. (9)

(145) A wave control member including the wave control medium according to any one of (1) to (6). (10)

(146) A wave control device including a metamaterial having the wave control medium according to any one of (1) to (6). (11)

(147) A wave control device including an electromagnetic absorbing and/or shielding member having the wave control medium according to any one of (1) to (6). (12)

(148) A wave control device including a sensor having an electromagnetic absorbing and/or shielding member having the wave control medium according to any one of (1) to (6). (13)

(149) A wave control device that performs signal transmission/reception or light reception/emission using the wave control medium according to any one of (1) to (6). (14)

(150) A manufacturing method of a wave control medium, the manufacturing method including forming a microstructure into a three-dimensional structure using a molecular template that utilizes self-assembly of an organic substance, the microstructure including a material selected from any one of a metal, a dielectric, a magnetic body, a semiconductor, and a superconductor, or a

combination of a plurality of these materials.

REFERENCE SIGNS LIST

(151) **1, 5, 7** Wave control medium **2** Base **3, 8, 9** Spiral part **4, 6** Matching element **20, 30, 40, 50, 60, 70, 80, 90, 100** Three-dimensional structure **11, 12, 21, 22, 31, 32, 41, 42** Coil **51, 61, 71** Wire **81, 91** Plate **101** Sphere **110** Electromagnetic wave absorbing sheet **111, 121, 131** Support **112** Wave control medium **120, 130** Electromagnetic waveguide **122, 132** Medium **123, 133** Waveguide tube **134** Medium layer

Claims

1. A wave control medium comprising a three-dimensional microstructure having a base, a spiral part, and a matching element disposed between the base and the spiral part, wherein the three-dimensional microstructure includes a material selected from any one of a metal, a dielectric, a magnetic body, a semiconductor, and a superconductor, or a combination of a plurality of the metal, the dielectric, the magnetic body, the semiconductor, and the superconductor.
 2. The wave control medium according to claim 1, wherein the spiral part has a multilayer structure.
 3. The wave control medium according to claim 1, wherein the spiral part has a cone shape.
 4. The wave control medium according to claim 1, further comprising at least two of the three-dimensional microstructures.
 5. The wave control medium according to claim 4, wherein the at least two of the three-dimensional microstructures have a continuous structure in which the structures are intertwined while facing each other without being in contact with each other.
 6. The wave control medium according to claim 4, wherein at least one of the three-dimensional microstructures has any one of a wire shape, a plate shape, and a sphere shape.
 7. A wave control element wherein the wave control medium according to claim 1 is integrated in an array structure.
 8. A wave control element wherein the wave control medium according to claim 1 is dispersedly disposed in plural numbers.
 9. A wave control element comprising the wave control medium according to claim 1, wherein the wave control element has a specific bandwidth of a response of 30% or more, and an absorption intensity in the specific bandwidth of 50% or more.
 10. A wave control member comprising the wave control medium according to claim 1.
 11. A wave control device comprising a metamaterial having the wave control medium according to claim 1.
 12. A wave control device comprising an electromagnetic absorbing and/or shielding member having the wave control medium according to claim 1.
 13. A wave control device comprising a sensor having an electromagnetic absorbing and/or shielding member having the wave control medium according to claim 1.
 14. A wave control device that performs signal transmission/reception or light reception/emission using the wave control medium according to claim 1.
 15. A manufacturing method of a wave control medium, the manufacturing method comprising forming a microstructure into a three-dimensional structure using a molecular template that utilizes self-assembly of an organic substance, the microstructure including a material selected from any one of a metal, a dielectric, a magnetic body, a semiconductor, and a superconductor, or a combination of a plurality of the metal, the dielectric, the magnetic body, the semiconductor, and the superconductor, wherein the three-dimensional microstructure having a base, a spiral part, and a matching element disposed between the base and the spiral part.
-