

### (12) United States Patent McAuley et al.

### (54) BREATHING ASSISTANCE APPARATUS

Applicant: Fisher & Paykel Healthcare Limited,

Auckland (NZ)

Inventors: Alastair Edwin McAuley, Dallas, TX

(US); Gregory James Olsen, Auckland

(NZ); Roheet Patel, Auckland (NZ)

Assignee: Fisher & Paykel Healthcare Limited,

Auckland (NZ)

(\*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 26 days.

This patent is subject to a terminal dis-

claimer.

Appl. No.: 18/468,663

(22)Filed: Sep. 15, 2023

(65)**Prior Publication Data** 

> US 2024/0115827 A1 Apr. 11, 2024

#### Related U.S. Application Data

- (60) Continuation of application No. 17/816,275, filed on Jul. 29, 2022, now Pat. No. 11,766,535, which is a (Continued)
- (51) Int. Cl. A61M 16/06 (2006.01)A61M 16/00 (2006.01)(Continued)

(52) U.S. Cl.

CPC .... A61M 16/0622 (2014.02); A61M 16/0066 (2013.01); A61M 16/0616 (2014.02);

(Continued)

(58) Field of Classification Search

CPC ...... A61M 16/06; A61M 16/0605; A61M 16/0611; A61M 16/0616; A61M 16/0622;

(Continued)

#### US 12.390.610 B2 (10) Patent No.:

(45) Date of Patent: \*Aug. 19, 2025

#### (56)References Cited

#### U.S. PATENT DOCUMENTS

301,111 A 7/1884 Genese 4/1892 Van Orden 472,238 A (Continued)

#### FOREIGN PATENT DOCUMENTS

2009321054 AU12/1992 CA1311662 (Continued)

#### OTHER PUBLICATIONS

Opponent's outline of submissions in the matter of Australian patent applications Nos. 20223628, 2021201838, 2021201840, 2021201841, 2021201842 and 2021201843, dated Mar. 13, 2024, 51 pp.


(Continued)

Primary Examiner - Joseph D. Boecker (74) Attorney, Agent, or Firm — VIA LLP

#### ABSTRACT

A mask assembly for use as part of an apparatus for supplying a flow of respiratory gases to a user is disclosed. The mask assembly includes a mask body having an inlet through which said flow of respiratory gases are provided to the interior of said mask body. A mask seal assembly comprising a seal of flexible material and a clip of rigid material is attached to the body. The seal has a first side and a second side. The first side of the seal is shaped to approximately match the contours of a user's face and in use substantially seal against a user's face. The second side is attached to the clip. The clip provides an interface extending substantially the full perimeter or periphery of the mask seal assembly for releasably attaching the mask seal assembly to the mask body. The clip comprises a bridging portion spanning outwards from the perimeter or periphery of the mask body to space at least a portion of the second side of the seal outwards from the perimeter or periphery of the mask body.

#### 25 Claims, 15 Drawing Sheets



#### Related U.S. Application Data

continuation of application No. 17/568,186, filed on Jan. 4, 2022, now Pat. No. 11,559,650, which is a continuation of application No. 16/384,218, filed on Apr. 15, 2019, now Pat. No. 11,247,013, which is a continuation of application No. 15/425,937, filed on Feb. 6, 2017, now Pat. No. 10,835,702, and a continuation of application No. 14/977,083, filed on Dec. 21, 2015, now Pat. No. 10,272,218, said application No. 15/425,937 is a division of application No. 13/877,903, filed as application No. PCT/NZ2011/000211 on Oct. 7, 2011, now Pat. No. 9,561,338, said application No. 13/877,903, filed as application No. PCT/NZ2011/000211 on Oct. 7, 2011, now Pat. No. 9,561, 338.

- (60) Provisional application No. 61/391,527, filed on Oct. 8, 2010.
- (51) **Int. Cl.**A61M 16/10 (2006.01)

  A61M 16/16 (2006.01)
- (52) U.S. Cl.

CPC .... A61M 16/0633 (2014.02); A61M 16/0683 (2013.01); A61M 2016/0039 (2013.01); A61M 16/0069 (2014.02); A61M 16/024 (2017.08); A61M 16/109 (2014.02); A61M 16/16 (2013.01); A61M 2205/3368 (2013.01); A61M 2205/50 (2013.01)

(58) Field of Classification Search

CPC .. A61M 16/0627; A62B 18/02; A62B 18/025; A62B 18/04; A62B 18/06

See application file for complete search history.

#### (56) References Cited

### U.S. PATENT DOCUMENTS

577,926 A 3/1897 Miller 718,470 A 1/1903 Jones 751,091 A 2/1904 Moran 770,013 A 9/1904 Linn 1,635,545 A 2,126,755 A 7/1927 Drager 8/1938 Dreyfus 2,228,218 A 1/1941 Schwartz 2,241,535 A 5/1941 Boothby et al. 2,296,150 A 9/1942 Dockson et al. 2,353,643 A 7/1944 Bulbulian 2,359,506 A 10/1944 Battley et al. 11/1945 2.388.604 A Eisenbud 2,415,846 A 2/1947 Francis 2,452,845 A 11/1948 Fisher 2,508,050 A 5/1950 Valente 2,684,066 A 7/1954 Glidden 2,693,800 A 11/1954 Caldwell 2,738,788 A 3/1956 Matheson et al. 2,749,910 A 6/1956 Faulconer 2.837.090 A 6/1958 Bloom 2,843,121 A 7/1958 Hudson 11/1958 2,859,748 A Hudson 2,875,759 A 3/1959 Galleher 2,894,506 A 7/1959 Rose 2,939,458 A 6/1960 Lundquist 3,234,940 A 2/1966 Morton 3,330,273 A 7/1967 Ray 1/1969 3.424.633 A Corrigall et al. 1/1970 3,490,452 A Greenfield 3,545,437 A 12/1970 Ouackenbush 3,599,635 A 8/1971 Kenneth 3,682,171 A 8/1972 Dali et al.

9/1974 McPhee 3,834,682 A 3,850,171 A 11/1974 Ball et al. 3,894,562 A 7/1975 Mosley et al. 8/1976 Proctor 3,972,321 A 3,977,432 A 8/1976 Vidal 3.982,532 A 9/1976 Halldin et al. 3,992,720 A 11/1976 Nicolinas 5/1978 4.090.510 A Segersten D250.047 10/1978 Lewis et al. D250,131 S 10/1978 Lewis et al. 4,127,130 A 11/1978 Naysmith 4,150,464 A 4/1979 Tracy D252,322 7/1979 Johnson 4,201,205 A 5/1980 Bartholomew 4,258,710 A 3/1981 Reber 4,266,540 A 5/1981 Panzik et al. 4.278.082 A 7/1981 Blackmer 4,354,488 A 10/1982 Bartos 4,367,735 1/1983 Dali 4,378,011 3/1983 Warncke et al. 3/1984 4,437,462 A Piljay 4,454,880 A 6/1984 Muto et al. 4,574,799 3/1986 Warncke et al. 4.603.602 A 8/1986 Montesi 11/1986 4,621,632 A Bartels et al. 4,644,974 A 2/1987 Zingg 4,676,241 A Webb et al. 6/1987 4,677,977 7/1987 Wilcox D293,613 S 1/1988 Wingler 4,753,233 A 6/1988 Grimes 4,773,411 A 9/1988 Downs 4.782.832 11/1988 Trimble et al. 4.803.981 A 2/1989 Vickery 2/1989 Harbeke 4,804,160 A 6/1989 4,836,200 A Clark et al. 4,856,508 A 8/1989 Tayebi 4,907,584 A 3/1990 McGinnis 4,915,104 A 4/1990 Marcy 4,915,105 A 4/1990 Lee 4/1990 Kopala et al. 4.919.128 A 7/1990 Fry 4.938.209 A 7/1990 4.941.467 A Takata 4,944,310 A 7/1990 Sullivan D310,431 S 9/1990 Bellm 4,958,658 A 9/1990 Zajac 4,971,051 A 11/1990 Toffolon 4,986,269 A 1/1991 Hakkinen 5.010.925 A 4/1991 Atkinson et al. 5,016,625 A 5/1991 Hsu et al. 5,031,261 A 7/1991 Fenner 8/1991 5,042,478 A Kopala et al. 5,046,491 A 9/1991 Derrick D320,677 10/1991 Kumagai et al. D321,419 S 11/1991 Wallace 5,062,421 A 11/1991 Burns et al. 5,065,756 11/1991 Rapoport D322,318 S 12/1991 Sullivan et al. 5,074,297 A 12/1991 Venegas 5,094,236 A 3/1992 Tayebi 5,113,857 A 5/1992 Dickerman et al. 5,121,745 A 6/1992 Israel et al. 5,148,802 A 9/1992 Sanders et al. 5,164,652 A 11/1992 Johnson et al. 5,231,979 A 8/1993 Rose 5,243,971 9/1993 Sullivan et al. 5,245,995 9/1993 Sullivan et al. D340.317 10/1993 Cole 5,259,377 A 11/1993 Schroeder 5,267,556 A 12/1993 Feng 5.269,296 A 12/1993 Landis et al. 5,315,859 A 5/1994 Schommer 5.349.949 A 9/1994 Schegerin 5,353,789 A 10/1994 Schobohm 5,366,805 A 11/1994 Fujiki et al. 1/1995 Rinehart D354,128 S D355,484 S 2/1995 Rinehart 5,400,776 A 3/1995 Bartholomew

5,429,683 A

5,438,979 A

7/1995

Le Mitouard

8/1995 Johnson et al.

(56)		Referen	ces Cited	6,439,234			Curti et al.
	Ţ	IS DATENT	DOCUMENTS	6,457,473 6,467,483			Brostrom et al. Kopacko et al.
	C	J.B. TAILINI	DOCOMENTS	6,470,886			Jestrabek-Hart
	5,441,046		Starr et al.	6,478,026		11/2002	
	5,449,206 A		Lockwood	6,484,725 6,488,664			Chi et al. Solomon et al.
	5,449,234 A 5,458,202 A		Gipp et al. Fellows et al.	6,491,034			Gunaratnam et al.
	5,460,174 A			6,497,232		12/2002	
	5,461,932			6,513,526 6,526,978	B2		Kwok et al. Dominguez
	5,477,852 A 5,513,634 A		Landis et al. Jackson	6,530,373			Patron et al.
	5,518,802		Colvin et al.	6,561,188		5/2003	
	5,533,506			6,561,190 6,561,191		5/2003 5/2003	
	5,540,223 A 5,542,128 A		Starr et al. Lomas	6,571,798			Thornton
	5,551,419 A		Froehlich et al.	6,581,594	B1		Drew et al.
	5,558,090			6,581,601 6,581,602		6/2003	Ziaee Kwok et al.
	5,560,354 A		Berthon-Jones et al. Starr et al.	6,584,977			Serowski
	5,588,423			6,588,424	B2	7/2003	
	5,595,174	<b>A</b> 1/1997	Gwaltney	6,615,832		9/2003	
	5,601,078 A		Schaller et al.	6,629,531 6,631,718		10/2003	Gleason et al.
	D378,610 S 5,649,532		Reischel et al. Griffiths	6,634,358	B2	10/2003	Kwok et al.
	5,657,752		Landis et al.	6,637,434		10/2003	
	5,662,101		Ogden et al.	6,644,315 6,651,658		11/2003	Hill et al.
	5,664,566 A 5,687,715 A		Mcdonald et al.	6,651,663			Barnett et al.
	5,690,097		Howard et al.	6,659,102		12/2003	
	5,724,677		Bryant et al.	6,662,803 6,668,828			Gradon et al. Figley et al.
	5,724,965 A 5,746,201 A		Handke et al.	D485,905		1/2004	
	5,752,510		Goldstein	6,679,257			Robertson et al.
	5,755,578		Contant et al.	6,679,265 6,691,707			Strickland et al. Gunaratnam et al.
	5,789,660 A 5,806,727 A		Kofoed et al. Joseph	6,712,072		3/2004	
	5,800,727		Hutcheon et al.	6,736,139	B1	5/2004	Wix
	5,857,460		Popitz	6,769,432 6,772,760		8/2004	Keifer Frater et al.
	5,884,624 A 5,904,278 A		Barnett et al. Barlow et al.	6,772,761			Rucker, Jr.
	5,918,598			6,796,308	B2		Gunaratnam et al.
	5,921,239	<b>A</b> 7/1999	McCall et al.	6,817,362 6,823,869			Gelinas et al. Raje et al.
	5,924,420 A 5,941,245 A		Reischel Hannah et al.	6,851,425			Jaffre et al.
	5,943,473		Levine	6,851,428	B2	2/2005	
	5,953,763	<b>A</b> 9/1999	Gouget	6,883,177 6,892,729	Bl		Ouellette et al. Smith et al.
	5,966,745 A		Schwartz et al. Gleason et al.	6,895,965	B2		Scarberry et al.
	6,017,315		Starr et al.	6,907,882	B2	6/2005	Ging et al.
	6,019,101			6,918,390 6,951,218			Lithgow et al. Gradon et al.
	6,021,528 A 6,039,044 A		Jurga Sullivan	6,953,354			Edirisuriya et al.
	6,050,260 A		Daniell et al.	6,997,187	B2	2/2006	Wood et al.
	6,112,746 A	<b>A</b> 9/2000	Kwok et al.	7,004,165 7,007,696			Salcido Palkon et al.
	6,116,235 A		Walters et al. Kwok et al.	7,007,090			Gunaratnam et al.
	6,119,694	<b>A</b> 9/2000	Correa et al.	D520,140	$\mathbf{S}$		Chaggares
	6,127,071			7,051,765 7,066,179			Kelley et al. Eaton et al.
	6,135,109 A		Blasdell et al. Hebblewhite et al.	7,000,179			Kummer et al.
	6,192,886 I		Rudolph	D526,094	$\mathbf{S}$	8/2006	Chen
	D440,302 S	S 4/2001	Wolfe	7,096,864 D533,269			Mayer et al. McAuley et al.
	6,272,933 H 6,298,850 H		Gradon et al. Argraves	7,178,525		2/2007	Matula, Jr. et al.
	6,302,105 I		Wickham et al.	7,178,528		2/2007	Lau
	6,341,606 I	31 1/2002	Bordewick et al.	7,201,169 7,207,333		4/2007 4/2007	Wilkie et al.
	6,347,631 I 6,354,293 I		Hansen et al. Madison	7,207,333			Lovell et al.
	D455,891 S		Biedrzycki	7,219,669	B1	5/2007	Lovell et al.
	6,398,197 I	31 6/2002	Dickinson et al.	7,225,811			Ruiz et al.
	6,412,487 I 6,412,488 I		Gunaratnam et al. Barnett	7,255,106 7,261,104		8/2007 8/2007	Gallem et al. Keifer
	6,418,928 I		Bordewick et al.	7,287,528			Ho et al.
	6,418,929 I	31 7/2002	Norfleet	7,290,546	B2	11/2007	Sprinkle et al.
	6,422,238 I		Lithgow	7,296,575		11/2007	
	6,427,694 I 6,431,172 I		Hecker et al. Bordewick	7,318,437 7,353,827		1/2008 4/2008	Gunaratnam et al.
	6,435,181 I		Jones, Jr. et al.	7,357,136			Ho et al.
	, ,		,				

(56)			Referen	ces Cited	9,292,799			McAuley et al.	
		U.S.	PATENT	DOCUMENTS	9,295,799 9,302,065	B2	4/2016	McAuley et al. Smith et al.	
	7 100 000	D.a	0/2000	337 11 4 1	9,320,566 9,320,866			Alston, Jr. McAuley et al.	
	7,406,966 7,448,386			Wondka et al. Ho et al.	9,333,315			McAuley et al.	
	7,487,772			Ging et al.	9,339,622			McAuley et al.	
	7,493,902			White et al.	9,339,624			McAuley	
	D589,139		3/2009	Guney	9,375,545			Darkin et al.	
	7,523,754			Lithgow et al.	9,381,316 9,439,405			Ng et al. Brüggemann	
	7,549,420			Martinez et al.	9,457,162			Ging et al.	
	D595,841 7,562,658			McAuley et al. Madaus et al.	9,486,601			Stallard et al.	
	7,597,100		10/2009	Ging	9,517,317			McAuley et al.	
	7,640,934	B2	1/2010	Zollinger et al.	9,522,246			Frater et al.	
	7,647,926			Gerder et al.	9,539,405 9,550,038			McAuley et al. McAuley et al.	
	7,658,189 7,665,464			Davidson et al. Kopacko et al.	9,561,338			McAuley	A61M 16/0633
	D612,933			Prentice	9,561,339	B2		McAuley et al.	
	7,681,575			Wixey et al.	9,744,385			Henry et al.	
	7,694,677		4/2010		9,884,160 9,901,699			McAuley et al. Veliss et al.	
	7,703,457			Barnett et al. Davidson	9,901,700			McAuley et al.	
	7,708,017 7,753,051			Burrow et al.	9,907,925			McAuley et al.	
	D623,288		9/2010		9,974,914			McAuley	
	7,814,911	B2		Bordewick et al.	10,080,856			McLaren et al.	
	7,827,990			Melidis et al.	10,137,271 10,201,678			McAuley et al. Guney et al.	
	7,828,990 7,856,982		11/2010	Matula et al.	10,252,015			McAuley et al.	
	7,850,982			Jones et al.	10,258,756			Mainusch et al.	
	7,877,817		2/2011		10,258,757			Allan et al.	
	7,896,003			Matula et al.	10,272,218			McAuley et al.	
	7,931,024			Ho et al.	10,328,226 10,363,387			Allan et al. Allan et al.	
	7,934,501 7,942,150		5/2011	Guney et al.	10,384,029			McAuley et al.	
	7,992,560			Burton et al.	10,413,694			Allan et al.	
	8,042,539	B2		Chandran et al.	10,463,825			McAuley et al.	
	8,042,541	B2		Amarasinghe et al.	10,742,451		8/2020		
	8,109,271			Vandine et al.	10,792,451 10,821,251			Allan et al. McAuley et al.	
	8,136,524 8,136,525			Ging et al. Lubke et al.	10,835,702			McAuley et al.	
	8,171,933			Xue et al.	10,842,964			McAuley et al.	
	D661,796	$\mathbf{S}$		Andrews et al.	10,980,962			McAuley et al.	
	8,245,711			Matula et al.	11,179,535 11,247,013			McAuley et al. McAuley et al.	
	8,272,382 8,371,302			Howard et al. Ging et al.	11,260,194	B2		McAuley et al.	
	8,397,727			Ng et al.	11,291,790	B2	4/2022	McAuley et al.	
	8,443,807	B2	5/2013	McAuley et al.	11,357,944			McAuley et al.	
	D686,313			Matula et al.	11,395,894 11,471,635			McAuley et al. McAuley et al.	
	8,479,726 8,479,741			McAuley McAuley et al.	11,541,197			McAuley et al.	
	8,567,404			Davidson et al.	11,554,234	B2		McAuley et al.	
	8,631,793	B2		Omura et al.	11,559,650			McAuley	A61M 16/0633
	8,631,799			Davenport	11,660,413 11,712,532			McAuley et al.	
	8,636,005			Gradon et al.	11,766,535			McAuley et al. McAuley et al.	
	8,701,667 8,714,157			Ho et al. McAuley et al.	2001/0017134		8/2001		
	8,720,444		5/2014	Chang	2001/0020474			Hecker et al.	
	8,757,157			Price et al.	2001/0029952		1/2001		
	8,783,257			McAuley et al.	2002/0005198 2002/0014241			Kwok et al. Gradon et al.	
	8,869,797 8,869,798			Davidson et al. Wells et al.	2002/0020416		2/2002		
	8,875,709			Davidson et al.	2002/0026934			Lithgow et al.	
	8,944,061			D'Souza et al.	2002/0029780			Frater et al.	
	8,950,404			Formica et al.	2002/0039867 2002/0046755		4/2002	Curro et al.	
	8,960,196 8,969,196		2/2015 3/2015		2002/0053347		5/2002		
	9,010,331	B2		Lang et al.	2002/0059935		5/2002	Wood	
	9,027,556	B2	5/2015	Ng et al.	2002/0069467			Immediato et al.	
	9,032,955		5/2015	Lubke et al.	2002/0092527		7/2002		
	9,032,956 9,072,852			Scheiner et al.	2002/0096173 2002/0096176			Berthon-Jones Gunaratnam et al	
	9,072,852 9,095,673			McAuley et al. Barlow et al.	2002/0096178		7/2002		•
	9,119,929			McAuley et al.	2002/0100474			Kellner et al.	
	9,119,931			D'Souza et al.	2002/0100479			Scarberry et al.	
	9,138,555			McAuley et al.	2002/0108613			Gunaratnam et al	
	9,149,596			Valcic et al.	2002/0117177		8/2002		
	9,186,474 9,242,062		11/2015	Melidis et al.	2003/0000533 2003/0005509		1/2003	Olsen et al.	
	J,472,002	L∠	1/2010	mondia et al.	2005/0005509	7.8.1	1/2003	1201201	

(56)	Referer	ices Cited	2006/0027237			Sleeper
211	PATENT	DOCUMENTS	2006/0032504 2006/0042629		3/2006	Burton et al. Geist
0.5	. 17111111	DOCOMENTS	2006/0042632			Bishop et al.
2003/0005931 A1	1/2003	Jaffre et al.	2006/0054169			Han et al.
2003/0005933 A1		Izuchukwu	2006/0060200 2006/0076019		3/2006 4/2006	Ho et al.
2003/0019495 A1		Palkon et al.	2006/0076019			Bordewick et al.
2003/0019496 A1 2003/0029454 A1		Kopacko et al. Gelinas et al.	2006/0081256			Palmer
2003/0047185 A1		Olsen et al.	2006/0096598	A1	5/2006	Ho et al.
2003/0051732 A1	3/2003		2006/0102185			Drew et al.
2003/0075180 A1	4/2003	Raje	2006/0107958 2006/0118117			Sleeper Berthon-Jones et al.
2003/0075182 A1		Heidmann et al.	2006/011811/			Chandran
2003/0079749 A1 2003/0084996 A1		Strickland et al. Alberg et al.	2006/0130844			Ho et al.
2003/0084330 A1 2003/0089373 A1		Gradon et al.	2006/0137690			Gunaratnam et al.
2003/0094177 A1		Smith et al.	2006/0169286			Eifler et al.
2003/0121519 A1		Estes et al.	2006/0174887			Chandran et al.
2003/0145857 A1		Sullivan et al.	2006/0178645 2006/0196511		8/2006 9/2006	Lau et al.
2003/0149384 A1 2003/0164170 A1		Davis et al. Drew et al.	2006/0201514			Jones et al.
2003/0172936 A1		Wilkie et al.	2006/0207599		9/2006	
2003/0196655 A1		Ging et al.	2006/0213516			Hoffman
2003/0196656 A1	10/2003		2006/0225740			Eaton et al.
2003/0196658 A1		Ging et al.	2006/0231103 2006/0237017			Matula et al. Davidson et al.
2003/0196659 A1 2003/0196664 A1		Gradon et al. Jacobson	2006/0237017			McAuley et al.
2003/0190004 A1 2003/0200970 A1	10/2003		2006/0249159		11/2006	
2003/0217746 A1		Gradon et al.	2006/0254593		11/2006	
2003/0221691 A1	12/2003		2006/0266361			Hernandez
2004/0011087 A1		Rebouillat et al.	2006/0283456 2006/0283458			Geiselhart et al. Woodard
2004/0025882 A1		Madaus et al.	2006/0283438			Geiselhart et al.
2004/0035427 A1 2004/0065328 A1		Bordewick et al. Amarasinghe et al.	2006/0283461			Lubke et al.
2004/0067333 A1		Amarasinghe et al.	2007/0000492			Hansel et al.
2004/0092999 A1		Lojewski	2007/0010786			Casey et al.
2004/0094157 A1		Dantanarayana et al.	2007/0044804 2007/0062536			Matula et al. McAuley
2004/0107968 A1		Griffiths	2007/0002330			Ho et al.
2004/0112377 A1 2004/0112384 A1		Amarasinghe et al. Lithgow et al.	2007/0107733		5/2007	
2004/0112385 A1	6/2004		2007/0125384	A1		Zollinger et al.
2004/0118212 A1		Orr et al.	2007/0125385			Ho et al.
2004/0118406 A1		Lithgow	2007/0125387			Zollinger et al.
2004/0118412 A1		Piletti-Reyes	2007/0137653 2007/0142785		6/2007 6/2007	Lundgaard et al.
2004/0133604 A1 2004/0139973 A1	7/2004 7/2004	Wright	2007/0157353			Guney et al.
2004/0149280 A1	8/2004		2007/0163594	A1		Ho et al.
2004/0182398 A1	9/2004		2007/0163600			Hoffman
2004/0211427 A1	10/2004		2007/0174952 2007/0175480		8/2007	Jacob Gradon et al.
2004/0221850 A1		Ging et al.	2007/0173480 2007/0209663			Marque et al.
2004/0226566 A1 2004/0255949 A1		Gunaratnam et al. Lang et al.	2007/0215158			Kroupa et al.
2004/0261797 A1		White et al.	2007/0215161		9/2007	Frater et al.
2005/0011521 A1	1/2005	Sprinkle et al.	2007/0221227		9/2007	
2005/0011524 A1	1/2005	Thomlinson et al.	2007/0227541 2007/0267022		10/2007	Van Den
2005/0016532 A1		Farrell	2007/027022		11/2007	
2005/0016544 A1 2005/0028822 A1		Thornton Sleeper et al.	2007/0272249			Chandran
2005/0028833 A1		Vena et al.	2007/0295335		12/2007	
2005/0033247 A1		Thompson	2008/0035152			Ho et al.
2005/0045182 A1		Wood et al.	2008/0041388 2008/0041393			McAuley et al. Bracken
2005/0051171 A1 2005/0051177 A1		Booth Wood	2008/0041393			Veliss et al.
2005/0066976 A1		Wondka	2008/0053446			Sleeper et al.
2005/0076913 A1		Ho et al.	2008/0053450			Van Kerkwyk et al.
2005/0092327 A1	5/2005	Fini et al.	2008/0060648			Thornton et al.
2005/0098183 A1		Nash et al.	2008/0060653 2008/0060657			Hallett et al. McAuley et al.
2005/0121030 A1		Bateman et al.	2008/0000037			Janbakhsh
2005/0121037 A1 2005/0133038 A1		Wood Rutter	2008/0066755			Janbakhsh
2005/0150497 A1		Eifler et al.	2008/0078387			Vandine
2005/0155604 A1		Ging et al.	2008/0078396		4/2008	Janbakhsh
2005/0172969 A1	8/2005	_	2008/0083412			Henry et al.
2005/0199239 A1		Lang et al.	2008/0092905			Gunaratnam
2005/0199241 A1		Ging et al.	2008/0099024			Gunaratnam et al.
2005/0199242 A1 2005/0205096 A1		Matula et al. Matula	2008/0105257 2008/0110464			Klasek et al. Davidson et al.
2005/0205090 AT 2005/0235999 AT		Wood et al.	2008/0110404			Rubin et al.
2005/0241644 A1		Guney et al.	2008/0135050			Hitchcock et al.
				_		

(56)	Referen	ices Cited	2011	/0259337 A1	10/2011	Hitchcock et al.
U.S.	PATENT	DOCUMENTS	2011	/0265796 A1 /0290253 A1	11/2011 12/2011	
				/0125339 A1 /0132208 A1		Ho et al. Judson et al.
2008/0142019 A1 2008/0149104 A1	6/2008 6/2008			/0132208 A1 /0132209 A1		Rummery
2008/0171737 A1		Fensome		/0138061 A1		Dravitzki et al.
2008/0178875 A1		Henry		/0204879 A1		Cariola et al.
2008/0178886 A1	7/2008	Lieberman et al.		/0285457 A1		Mansour et al.
2008/0190432 A1		Blochlinger et al.		/0304999 A1 /0318265 A1	12/2012	Swift et al. Amirav et al.
2008/0190436 A1 2008/0196728 A1	8/2008 8/2008	Jaffe et al.		/0133659 A1		Ng et al.
2008/0190728 A1 2008/0210241 A1		Schulz et al.		/0133664 A1		Startare
2008/0223370 A1	9/2008			/0152918 A1		Rummery et al.
2008/0230068 A1		Rudolph		/0160769 A1 /0026888 A1		Ng et al. Matula
2008/0236586 A1 2008/0245369 A1		Mcdonald et al. Matula et al.		/0020888 A1 /0083428 A1		Rothermel et al.
2008/0243369 A1 2008/0257354 A1		Davidson		/0083430 A1		Matula, Jr. et al.
2008/0264422 A1		Fishman		/0137870 A1		Barlow et al.
2008/0271739 A1		Facer et al.		/0261432 A1		Eves et al.
2008/0276937 A1		Davidson et al.		/0290669 A1 /0311492 A1	10/2014 10/2014	Stuebiger et al.
2008/0302366 A1 2008/0314388 A1		McGinnis et al. Brambilla et al.		/0338672 A1		D'Souza et al.
2008/0314390 A1		Kwok et al.		/0373834 A1		Gunaratnam et al.
2008/0319334 A1		Yamamori		/0033457 A1		Tryner et al.
2009/0014007 A1		Brambilla et al.		/0090266 A1 /0246198 A1		Melidis et al. Bearne et al.
2009/0032024 A1 2009/0044808 A1		Burz et al. Guney et al.		/0335846 A1		Romagnoli et al.
2009/0078267 A1		Burz et al.		/0352308 A1		Cullen et al.
2009/0090364 A1		Daugaard et al.		/0374944 A1		Edwards et al.
2009/0107504 A1		McAuley et al.		/0001028 A1 /0008558 A1		McAuley et al. Huddart et al.
2009/0114227 A1 2009/0120442 A1	5/2009	Gunaratnam et al.		0008338 A1		Chodkowski et al.
2009/0120442 A1 2009/0126739 A1		Ng et al.		/0038707 A1	2/2016	Allan et al.
2009/0133697 A1		Kwok et al.		/0051786 A1	2/2016	McAuley et al.
2009/0139527 A1		Ng et al.		/0213873 A1		McAuley et al.
2009/0145429 A1		Ging et al.		/0213874 A1 /0296720 A1		Davidson et al. Henry et al.
2009/0151729 A1 2009/0173349 A1		Judson et al. Hernandez et al.		/0246411 A1	8/2017	
2009/0173313 AT 2009/0183734 A1		Kwok et al.		/0296770 A1		Gunaratnam et al.
2009/0183739 A1		Wondka		/0368288 A1	12/2017	
2009/0188507 A1		Lacava		/0221615 A1 /0250483 A1	8/2018 9/2018	Sevincli Olsen et al.
2009/0211583 A1 2009/0223519 A1		Carroll et al. Eifler et al.		0256844 A1		Galgali et al.
2009/0223513 A1 2009/0223521 A1		Howard	2019	/0001095 A1	1/2019	Rose et al.
2009/0320842 A1	12/2009	Doherty		/0046928 A1	2/2020	Allan et al.
2009/0320851 A1		Selvarajan et al.		/0171260 A1 /0197644 A1	6/2020	McAuley et al.
2010/0000538 A1 2010/0000539 A1		Edwards et al. Woodard		0228829 A1		McAuley et al.
2010/0000533 A1		Berthon-Jones et al.		/0105294 A1	4/2022	McAuley et al.
2010/0006101 A1*		McAuley A61M 16/0633		/0249794 A1		McAuley et al.
2010/0025005	2/2010	128/206.24		/0331539 A1 /0084024 A1		McAuley et al. McAuley et al.
2010/0037897 A1	2/2010	Wood Lustenberger et al.		/0086085 A1		McAuley et al.
2010/0051031 A1 2010/0051034 A1		Howard		/0256188 A1		McAuley et al.
2010/0083969 A1		Crumblin	2023	/0381440 A1	11/2023	Allan et al.
2010/0108072 A1		D'Souza				
2010/0132717 A1 2010/0154798 A1		Davidson et al. Henry et al.		FOREIC	JN PATE	NT DOCUMENTS
2010/0134738 A1 2010/0170516 A1		Grane	CA	264	8690	11/2007
2010/0199992 A1	8/2010	Но	CD	000966064-		9/2008
2010/0229868 A1		Rummery et al.	CD	000966064-		9/2008
2010/0229872 A1 2010/0258132 A1	9/2010 10/2010		$^{\rm CD}$	000966064-		9/2008
2010/0258132 A1 2010/0258136 A1		Doherty et al.	CD	000966064		9/2008
2010/0294281 A1	11/2010		CD CN	000966064- 217	2538	9/2008 7/1994
2010/0307502 A1		Rummery et al.	CN		0265	12/2005
2010/0313891 A1		Veliss et al.	CN		0854	3/2006
2010/0319700 A1 2010/0326445 A1		Ng et al. Veliss et al.	CN		4250	6/2006
2011/0067704 A1	3/2011		CN CN		1961 1897 A	1/2007 3/2011
2011/0072553 A1	3/2011	Но	DE		5692	11/1953
2011/0088699 A1*	4/2011	Skipper A61M 16/06	DE	2972	3101 U1	7/1998
2011/0126838 A1	6/2011	128/206.26 Alberici	DE		3949	11/1998
2011/0126838 A1 2011/0146675 A1	6/2011		DE DE	10200504 10200601		4/2006 9/2007
2011/0162654 A1		Carroll et al.	EP		1 275	9/1988
2011/0232649 A1		Collazo et al.	$\mathbf{EP}$	0 350	322	1/1990
2011/0253156 A1	10/2011	Sweeney	EP	0 423	7 474	5/1991

(56)	Refe	rences Cited	WO	WO 02/011804	2/2002
			WO	WO 02/047749	6/2002
	FOREIGN PA	TENT DOCUMENTS	WO WO	WO 02/074372 WO 03/035156	9/2002 5/2003
ED	0.462.701	13/1001	wo	WO 03/035130 WO 03/076020	9/2003
EP EP	0 462 701 0 747 078	12/1991 12/1996	wo	WO 03/082406	10/2003
EP	1 099 452	5/2001	WO	WO 03/092755	11/2003
EP	0 830 180	3/2002	WO	WO 04/007010	1/2004
EP	1 258 266	11/2002	WO	WO 04/096332	1/2004
EP	1 306 098	5/2003	WO	WO 04/012803	2/2004
EP	1 488 820	12/2004	WO WO	WO 04/022146 WO 04/022147	3/2004 3/2004
EP EP	1 582 231 2 042 209	10/2005 4/2009	WO	WO 04/030510	4/2004
EP EP	2 130 563	12/2009	WO	WO 04/030736	4/2004
EP	2 145 645	1/2010	WO	WO 04/041341	5/2004
EP	1 753 495	9/2010	WO	WO 04/041342	5/2004
EP	1 481 702	9/2012	WO	WO 04/052438	6/2004
EP	2 749 176	7/2014	WO WO	WO 04/071565 WO 04/073777	8/2004 9/2004
EP EP	1 646 910 2 022 528	8/2015 3/2016	wo	WO 04/073778	9/2004
EP	1 841 482	7/2016	WO	WO 04/079066	9/2004
EP	2 451 518	10/2017	WO	WO 05/010608	2/2005
FR	2658725	8/1991	WO	WO 05/016403	2/2005
FR	2749176	12/1997	WO WO	WO 05/018523 WO 05/021075	3/2005
FR	2823122	10/2002	WO	WO 05/051468	3/2005 6/2005
GB GB	190224431 880824	12/1902 10/1961	wo	WO 05/063326	7/2005
GB	979357	1/1965	WO	WO 05/063328	7/2005
GB	1467828	3/1977	WO	WO 05/076874	8/2005
GB	2133275	7/1984	WO	WO 05/079726	9/2005
GB	2173274	10/1986	WO	WO 05/086943	9/2005 9/2005
GB	2186801	8/1987	WO WO	WO 05/086946 WO 05/097247	10/2005
GB GB	2385533 2408459 A	8/2003 A 1/2005	wo	WO 05/03/24/ WO 05/123166	12/2005
GB	2406439 A		WO	WO 06/000046	1/2006
JР	62-024721	2/1987	WO	WO 06/050559	5/2006
JР	H09-010311	1/1997	WO	WO 06/069415	7/2006
JP	2000-325481	11/2000	WO	WO 06/074513	7/2006
JР	2004-016488	1/2004	WO WO	WO 06/074514 WO 06/074515	7/2006 7/2006
JP JP	2005-529687 2005-537906	10/2005 12/2005	WO	WO 06/096924	9/2006
JP	2003-337900	6/2007	WO	WO 06/130903	12/2006
NZ	531332	2/2004	WO	WO 06/138346	12/2006
NZ	534606	8/2004	WO	WO 06/138416	12/2006
NZ	528029	3/2005	WO WO	WO 07/006089 WO 07/009182	1/2007 1/2007
NZ	548575	7/2006	wo	WO 07/003182 WO 07/021777	2/2007
NZ NZ	551103 567740	11/2006 12/2009	WO	WO 07/022562	3/2007
wo	WO 82/003548	10/1982	WO	WO 07/041751	4/2007
WO	WO 97/00092	1/1997	WO	WO 07/041786	4/2007
WO	WO 97/32494	9/1997	WO WO	WO 07/045008 WO 07/048174	4/2007 5/2007
WO	WO 97/45154	12/1997	WO	WO 07/048174 WO 07/053878	5/2007
WO WO	WO 98/04310 WO 98/04311	2/1998 2/1998	WO	WO 07/114492	10/2007
WO	WO 98/018514	5/1998	WO	WO 07/147088	12/2007
WO	WO 98/024499	6/1998	WO	WO 08/007985	1/2008
WO	WO 98/048878	11/1998	WO	WO 08/011682	1/2008
WO	WO 98/57691	12/1998	WO WO	WO 08/014543 WO 08/030831	2/2008 3/2008
WO WO	WO 99/04842 WO 99/43375	2/1999 9/1999	wo	WO 08/036625	3/2008
WO	WO 99/43373 WO 99/058181	11/1999	WO	WO 08/043134	4/2008
wo	WO 99/058198	11/1999	WO	WO 08/060295	5/2008
WO	WO 00/050122	8/2000	WO	WO 08/068966	6/2008
WO	WO 00/057942	10/2000	WO WO	WO 08/070929 WO 08/106716	6/2008 9/2008
WO	WO 00/069497	11/2000	WO	WO 08/106/16 WO 08/148086	12/2008
WO WO	WO 00/74509 WO 00/074758	12/2000 12/2000	wo	WO 09/026627	3/2009
WO	WO 00/074738 WO 00/078384	12/2000	WO	WO 09/022248	4/2009
wo	WO 01/00266	1/2001	WO	WO 09/052560	4/2009
WO	WO 01/32250	5/2001	WO	WO 09/059353	5/2009
WO	WO 01/041854	6/2001	WO	WO 09/092057	7/2009
WO	WO 01/058293	8/2001	WO	WO 09/109005	9/2009
WO WO	WO 01/062326 WO 01/89381	8/2001 11/2001	WO WO	WO 09/133561 WO 09/139647	11/2009 11/2009
WO	WO 01/89381 WO 01/94721	12/2001	WO	WO 10/066004	6/2010
wo	WO 01/94721 WO 01/097892	12/2001	wo	WO 10/000004 WO 10/073142	7/2010
wo	WO 01/097892	12/2001	wo	WO 10/131189	11/2010
WO	WO 01/097893	12/2001	WO	WO 10/135785	12/2010
WO	WO 02/005883	1/2002	WO	WO 10/148453	12/2010

(56)	References Cited			
	FOREIGN PAT	ENT DOCUMENTS		
WO	WO 11/014931	2/2011		
WO	WO 11/059346	5/2011		
WO	WO 11/060479	5/2011		
WO	WO 11/077254	6/2011		
WO	WO 12/040791	4/2012		
WO	WO 12/045127	4/2012		
WO	WO 12/052902	4/2012		
WO	WO 12/143822	10/2012		
WO	WO 14/015382	1/2014		
WO	WO 14/020469	2/2014		
WO	WO 14/109749	7/2014		
WO	WO 14/175752	10/2014		
WO	WO 14/175753	10/2014		
WO	WO 15/033287	3/2015		
WO	WO 16/000040	1/2016		
WO	WO 17/049356	3/2017		
WO	WO 17/049357	3/2017		
WO	WO 18/007966	1/2018		
WO	WO 18/064712	4/2018		

#### OTHER PUBLICATIONS

Applicant's Outline of Submissions in the matter of Australian Patent Application Nos. 2020223628, 2021201838, 2021201840, 2021201841, 2021201842, 2021201843 dated Mar. 20, 2024, 72 pp. Australian Examination Report for Patent Application No. 2012265597 dated Dec. 19, 2013, in 5 pages.

Australian Examination Report in patent application No. 2010241390, dated Jan. 9, 2015, 4 pages.

Australian Examination Report in patent application No. 2015201920, dated Jul. 20, 2015, 3 pages.

Australian examination report in patent application No. 2016202801, dated Jun. 20, 2016, 2 pages.

Australian Examination Report in patent application No. 2010241390, dated Sep. 28, 2016, 4 pages.

Australian Examination Report in patent application No. 2010246985, dated Mar. 4, 2014, 5 pages.

Australian Examination Report in patent application No. 2015202814, dated Aug. 14, 2015, 8 pages.

Australian Examination Report in patent application No. 2016202799, dated May 31, 2016, 2 pages.

Australian Examination Report No. 1, in patent application No. AU 2013300237, dated Jun. 8, 2017, in 4 pages.

Australian Examination Report No. 2 for patent application No. 2018217307, dated Mar. 3, 2020, 4 pp.

Australian Examination Report; Application No. 2007273324; dated

May 22, 2012; 4 pages. Brazilian office action dated Jul. 11, 2019 in patent application No.

BR11201211420-4.

Canadian Examination Report for Application No. 2655839 dated Oct. 4, 2013, in 2 pages.

Canadian Examination Report for patent application No. 2880749, dated Feb. 28, 2020, 4 pp.

Canadian Examination Report in patent application No. 2998247, dated Jan. 8, 2019, 4 pages.

Canadian Examination Report in patent application No. 2780310, dated Jul. 26, 2016, 4 pages.

Canadian Examination Report in patent application No. 2918167, dated Oct. 3, 2016, 4 pages.

Canadian Examination Report in patent application No. 2780310,

dated Jan. 25, 2018 4 pages. Canadian Examination Report in patent application No. 2780310,

dated Oct. 9, 2018, 3 pp. Canadian Examination Report in patent application No. 2880749,

dated May 16, 2019, 5 pages. Canadian Examination Report in patent application No. 2890556, dated Nov. 28, 2016, 4 pages.

Canadian Examination Report in patent application No. 3010066, dated Dec. 19, 2019, 4 pages.

Canadian Examination Report in patent application No. 3010066, dated May 3, 2019, 4 pages.

Canadian Examination Report in patent application No. 3017161, dated Apr. 22, 2020. 4 pp.

Canadian Examination Report in patent application No. 3017161, dated Aug. 21, 2019, 3 pp.

Chinese Examination Report in patent application No. 201080028029. 0, dated Mar. 27, 2014, 16 pages.

Chinese Examination Report in patent application No. 2007800266164, dated Feb. 17, 2011, 18 pages.

Chinese Examination Report in patent application No. 201080061122. 1, dated Jul. 17, 2015, 10 pages.

Chinese examination report in patent application No. 201210080441,8, dated Dec. 1, 2014, 1 pp. (English translation).

Chinese examination report in patent application No. 201210080441. 8, dated Mar. 4, 2014, 11 pp. (English translation).

Chinese Examination Report in patent application No. 201610114706. X, dated Jul. 30, 2018, 9 pp., with translation.

Chinese Examination Report; dated Sep. 14, 2015; Application No. 201080028029.0; 3 pages.

Chinese Examination Report; dated Sep. 3, 2014; Application No. 201080061122.1; 7 pages.

Chinese First Office Action in patent application No. 201710824612. 6, dated Sep. 30, 2019, 25 pp.

Chinese Fourth Office Action in patent application No. 201610116121. 1. dated Sep. 30, 2019, 12 pages.

Chinese Office Action in patent application No. 201610116121.1, dated Sep. 28, 2017, 5 pages.

Chinese Second Examination Report in patent application No. 201610114706.X, dated Apr. 24, 2019 8 pp., with translation.

Chinese Second Office Action in patent application No. 201710824612. 6, dated May 25, 2020. 19 pages.

Chinese Second Office Action; dated Jan. 19, 2015; Application No. 201080028029.0; 30 pages.

Chinese Third Examination Report in patent application No. 201610114706.X, dated Jan. 16, 2020, with translation. 32 pages. Chinese Third Office Action in patent application No. 201810116121. 1, dated Apr. 28, 2019, 16 pages.

Decision Denying Institute of Inter Partes Review dated Jul. 16, 2019 in IRP2019-00179, 32 pp.

Decision to Institute dated Jul. 16, 2019 in IPR2019-00180, 34 pp. English Translation of JP Examination Report; dated Feb. 10, 2014; Application No. 2012-510418; 8 pages.

European examination report dated Jun. 16, 2020 in patent application No. 18163847.9, 5 pp.

European Examination Report dated Mar. 16, 2020 in patent application No. 18195537.8. 7 pages.

European examination report dated Sep. 5, 2019 in patent application No. 18163847.9, 5 pp.

European Examination Report in patent application No. 09746823. 5, dated Apr. 3, 2017, 2 pages.

European Examination Report in patent application No. 07808683. 2, dated May 9, 2018, 5 pages.

European Examination Report, European Application 13828380.9, dated Apr. 7, 2017, 8 pp.

U.S. Appl. No. 60/493,515, filed Aug. 8, 2002, Sleeper et al.

U.S. Appl. No. 60/496,059, filed Aug. 18, 2003, Ho et al.

U.S. Appl. No. 60/529,696, filed Dec. 16, 2003, Lithgow et al.

U.S. Appl. No. 61/064,406, filed Mar. 4, 2008, Wehbeh.

U.S. Appl. No. 61/071,893, filed May 22, 2008, Wehbeh et al.

U.S. Appl. No. 61/136,617, filed Sep. 19, 2008, Wehbeh et al. Resmed Mirage Swift™ II Nasal Pillows System product page (http://www.resmed.com/en-us/products/masks/mirage\_swift\_II\_nasal\_pillows.\_system/Mirage-Swift-II-Nasal-Pillows-System.html?

menu=products); archived Jul. 21, 2008, 2 pp.
Resmed Mirage Swift<sup>TM</sup> II user brochure (http://www.resmed.com/en\_us/products/masks/mirage-swift\_II\_nasal\_pillows\_system/documents/mirage-swift-ii-np-brochure-patient-english-usa.pdf) copy-

right 2007, 4 pp.
ResMed Mirage Swift II Fitting guide (http://www;resmed.com/en-us/products/masks/mirage\_swift\_II\_nasal\_pillows\_system/documents/mirage-swift\_ii\_np-fitting\_English.pdf) copyright 2006, 2 pp.

#### OTHER PUBLICATIONS

ResMed Mirage Swift II comparison to older Swift patient interface (http://www.resmed.com/en-us/products/masks/mirage\_swift\_II\_nasal\_pillows\_system/documents/mirage-swift-ii-np-comparison-guide.pdf, 2007, 6 pp.

ResMed Mirage Swift II user guide (http://www.resmed.com/en-us/products/service\_and\_support/documents/60893rl\_mirage\_swiftll\_nasal\_userglide\_us\_multi.pdf) copyright 2006, 1 p.

ResMed Mirage Swift II component card (http://www.resmed.com/en-us/products/masks/mirage\_swift\_II\_nasal\_pillows\_system/documents/mirage-swift-ii-np-cc-USA.pdf); copyright 2006, 2 pp. Resmed Swift<sup>TM</sup> LT Nasal Pillows System, product page, (http://www.resmed.com/en-us/products/masks/mirage\_swift\_II\_nasal\_pillows\_system/Mirage-Swift-II-Nasal\_Pillows-System.html?menu=products), Jul. 3, 2008, 2 pp.

Resmed Swift LT user brochure, (http://www.resmed.com/en-us/products/masks/mirage\_swift\_II\_nasal\_pillows\_system/documents/mirage-swift-ii-np-brochure-patient-english-usa.pdf), copyright 2008, 4 pp.

Resmed Swift<sup>TM</sup> LT component card (http://www.resmed.com/en-us/assets/documents/product/swift\_tt/components\_card/1012463\_swift-It\_components-card\_usa\_eng.pdf) copyright 2008, 46 pp.

Resmed Swift<sup>TM</sup> LT fitting guide, (http://www.resmed.com/en-us/assets/documents/product/swift-II/clinical\_fact\_sheet/1012406 swift-ii fact-sheet usa eng.pdf), 2008, 2 pp.

Resmed Swift<sup>TM</sup> LT fact sheet (http://www.resmcd.com/en-us/assets/documents/product/swift-It/clinical\_fact\_sheet/1012406 swiftIt\_fact-sheet\_usa\_eng.pdf, copyright 2008, 4 pp.

Resmed Swift<sup>TM</sup> LT image gallery (http://www.resmed.com/en-us/products/masks/swift\_It\_nasal\_pillows\_system/imagegallery.html? menu=products, Apr. 25, 2008, 2 pp.

Resmed Swift<sup>TM</sup> LT interactive fitting guide—screenshot from troubleshooting part (http://www.resmed.com/enus/assets/multimedia/product/swift-It/flash/swift-It-fitting-eng.swf), Jul. 3, 2008, 2 pp. Puritan Bennett Breeze® SleepGear® CPAP Interface, product page

(http://puritanbennett.com/prod/product.aspx?id=233); archived Oct. 19, 2007, 2 pp.

Bennett Breeze® SleepGear® User's Guide (http://puritanbennett.com/\_catalog/pdf/dfu/107598a00[I].pdf); copyright 2007, 18 pp. Bennett Breeze® SleepGear® sales sheet (http://www.puritanbennett.com/\_Catalog/PDF/Product/BreezeSleepGear.pdf) copyright 2016, 7 PP.

Bennett mask coding matrix (http://www.puritanbennett.com/\_Catalog/PDF/Product/BreezeSlpGear(ST03700).pdf) copyright 2006, 3 pp.

Puritan Bennett Breeze fitting guide (http://www.puritanbennett.com/\_Catalog/PDF/Product/BreezeFittingPoster.pdf, Oct. 19, 2007, 1 p.

Respironics Optilife Pillows mask product page (http://optilife.respironics.com:80/); archived Nov. 21, 2007, 2 pp.

Respironics Optilife Pillows mask part numbers page (http://optilife.respironics.com:80/Parts.aspx); archived Nov. 23, 2007, 4 pp.

Respironics Optilife Pillows mask FAQ (http://optilife.respironics.com:80/fags.aspx); archived Nov. 23, 2007, 6 pp.

Respironics Optilife Pillows mask feature page (http://optilife.respironics.com:80/features.aspx); archived Nov. 23, 2007, 4 pp. Respironics Optilife Pillows mask fitting guide screen shot (http://optilife.respironics.com:80/fittingGuide.aspx); archived Aug. 7, 2008, 1 p.

Respironics Optilife Pillows mask adjustment video screenshots, https://www.youtube.com/watch?v=shjcNmvvcBA); uploaded Aug. 3, 2008, 2 pp.

Puritan Bennett Breeze description; copyright 2000 by Mallinckrodt Inc., 4 pp.

Fisher & Paykel Opus product page, archived Sep. 3, 2009, 2 pp. Fisher & Paykel Opus patient interface product photographs, Jul. 2007, 6 pp.

Photographs of Opus 360 nasal pillows mask patient instructions RevB, Jul. 2007, 4 pp.

Respironics Optilife brochure detailing updates; copyright 2008; dated Mar. 26, 2008, 3 pp.

Fisher & Paykel Opus product page, archived Sep. 7, 2009, 2 pp. Fisher & Paykel Opus "Off-the-lips" pillows explanation page, archived Aug. 23, 2009, 2 pp.

Fisher & Paykel Opus "Off-the-lips" patient interface brochure, archived Oct. 14, 2009, 6 pp.

Fisher & Paykel Opus user-guide, archived Nov. 17, 2009, 2 pp. Fisher & Paykel HC200 Series Nasal CPAP Blower & Heated Humidifier User Manual, 17 pp., May 1998.

Fisher & Paykel Healthcare, FlexiFit® 431 Full Face Mask instructions, 2010, 4 pp.

Fisher & Paykel Healthcare, FlexiFit™ 431 Full Face Mask, specification sheet, 2004, 2 pp.

Fisher & Paykel Healthcare, Interface Solutions Product Profile, 2006, 12 pp.

Fisher & Paykel MR810 Manual, Rev. C, 2004, 43 pp.

HomeDepot.com—Ring Nut Sales Page (Retrieved Oct. 16, 2015 from http://www.homedepot.com/p/Everbilt-1-2-in-Galvanized-HexNut-804076/20464- 7893), 4 pp.

Malloy, 1994, Plastic Part Design for Injection Molding, Hanser Gardner Publications, Inc, Cincinnati, OH, 14 pp.

Merriam-Webster's Collegiate Dictionary, Eleventh Edition, 2004, pp. 703, 905, 1074, 1184.

Philips Respironics 'System One Heated Humidifier—User Manual', 2011, pp. 1-16, [retrieved on Nov. 25, 2013] from the internet: URL: http://www.cpapxchange.com/cpap-machines-biap-machines/systemone-60-seri- es-cpap-humidifier-manual.pdf front cover, pp. 3-4 and 6

ResMed FlexiFit brochure.

ResMed Exhibit, FlexiFit<sup>TM</sup> 431, product brochure, web pages (Wayback Machine), 2006, 23 pp.

ResMed Origins Brochure (Retrieved Apr. 17, 2016 from http://www.resmed.com/us/dam/documents/articles/resmedorigins.pdf), 64 pp.

ResMed Ultra Mirage™ Full Face Mask, product brochure, 2004, 2 pp.

ResMed Ultra Mirage™ Full Face Mask, product brochure, web pages (Wayback Machine), 2006, 9 pp.

ResMed, Jun. 29, 1997, Mask Frames (Source: Wayback Machine Internet Archive); http://web.archive.org/web/19970629053430/http://www.resmed.com-/maskframes/mask.htm, 2 pp/.

ResMed, Mirage Swift  $^{\text{TM}}$  Nasal Pillows System from ResMed, product brochure, 2004, 6 pp.

ResMed, Mirage Swift™ Nasal Pillows System: User's Guide, product brochure, 2004, 11 pp.

ResMed, Mirage Vista<sup>TM</sup> Nasal Mask: Components Card, product brochure, 2005, 1 p.

The American Heritage Dictionary of the English Language, Fourth Edition, 2006, pp. 1501, 1502, 1650.

WeddingBands.com—Men's Wedding Ring Shopping Page (Retrieved Oct. 16, 2015 from http://www.weddingbands.com/ProductPop. sub.--wedding.sub.--band- s.sub.--metal/48214W.html), 3 pp.

ResMed, Oct. 1999, Mirage® Full Face Mask Update, Product Bulletin No. 161, 3 pp.

ResMed, Dec. 6, 1998, Mirage Full Face Cushion—Medium, drawing, 1 p.

ResMed, Jun. 20, 2000, Brochure, Mirage Full Face Mask, 5 pp. ResMed, Oct. 4, 2000, Mirage® Full Face Mask, User's Guide, 3

U.S. Appl. No. 61/064,406, 34 pages, provided by USPTO on Feb. 23, 2009.

U.S. Appl. No. 61/071,893, 43 pages, provided by USPTO on Feb. 23, 2009.

U.S. Appl. No. 61/136,617, 82 pages, provided by USPTO on Feb. 23, 2009.

Petition for Inter Partes Review of U.S. Pat. No. 8,479,741 Pursuant to 35 U.S.C. §§ 311-19, 37 C.F.R. § 42, IPR2016-01714, dated Sep. 7, 2016.

Patent Owner Preliminary Response to Petition for Inter Partes Review of U.S. Pat. No. 8,479,741, IPR2016-01714, filed Dec. 14, 2016

#### OTHER PUBLICATIONS

Decision Denying Institution of Inter Partes Review of U.S. Pat. No. 8,479,741 Pursuant to 37 C.F.R. § 42.108, IPR2016-01714, entered Mar. 10, 2017.

Declaration of Dr. John Izuchukwu, Ph.D., P.E., U.S. Pat. No. 8,443,807, IPR Nos. 2016-1726 & 2016-1734, dated Sep. 7, 2016. Declaration of Dr. John Izuchukwu, Ph.D., P.E., U.S. Pat. No. 8,479,741, IPR Nos. 2016-1714 & 2016-1718, dated Sep. 7, 2016. Patent Owner Preliminary Response to Petition for Inter Partes Review of U.S. Pat. No. 8,479,741, IPR2016-01718, filed Dec. 16, 2016.

Decision Denying Institution of Inter Partes Review of U.S. Pat. No. 8,479,741 Pursuant to 37 C.F.R. § 42.108, IPR2016-01718, entered Mar. 13, 2017.

Petition for Inter Partes Review of U.S. Pat. No. 8,479,741 Pursuant to 35 U.S.C. §§ 311-19, 37 C.F.R. § 42, IPR2016-01718, dated Sep. 7, 2016.

Petition for Inter Partes Review of U.S. Pat. No. 8,443,807 Pursuant to 35 U.S.C. §§ 311-19, 37 C.F.R. § 42, IPR2016-01726, dated Sep. 7, 2016.

Patent Owner Preliminary Response to Petition for Inter Partes Review of U.S. Pat. No. 8,443,807, IPR2016-01726, filed Dec. 13, 2016.

Decision Denying Institution of Inter Partes Review of U.S. Pat. No. 8,443,807 Pursuant to 37 C.F.R. § 42.108, IPR2016-01726, entered Mar. 6, 2017.

Petition for Inter Partes Review of U.S. Pat. No. 8,443,807 Pursuant to 35 U.S.C. §§ 311-19, 37 C.F.R. § 42, IPR2016-01734, dated Sep. 7, 2016.

Patent Owner Preliminary Response to Petition for Inter Partes Review of U.S. Pat. No. 8,443,807, IPR2016-01734, filed Dec. 22, 2016.

Decision Denying Institution of Inter Partes Review of U.S. Pat. No. 8,443,807 Pursuant to 37 C.F.R. § 42.108, IPR2016-01734, entered Mar. 13, 2017.

File History of U.S. Pat. No. 8,479,741 to McAuley et al, published Oct. 1, 2009.

File History of U.S. Pat. No. 8,443,807 to McAuley et al, published Jan. 7, 2010.

Patent Owner's Complaint for Fisher & Paykel Healthcare Ltd. v. ResMed Corp., Case No. 2:16-cv- 06099-R-AJW (C.D. Cal.), dated Aug. 15, 2016.

Patent Owner's Notice of Voluntary Dismissal Without Prejudice for *Fisher & Paykel Healthcare Ltd.* v. *ResMed Corp.*, Case No. 2:16-cv-06099-R-AJW (C.D. Cal.), dated Aug. 16, 2016.

Patent Owner's Complaint for Fisher & Paykel Healthcare Ltd. v. ResMed Corp., Case No. 3:16-cv-02068-GPC-WVG (S.D. Cal.), dated Aug. 16, 2016.

Petitioners' Complaint for ResMed Inc., et al. v. Fisher & Paykel Healthcare Corp. Ltd., et al., Case No. 3:16-cv-02072-JAH-MDD (S.D. Cal.), dated Aug. 16, 2016.

Petitioners' Notice of Voluntary Dismissal Without Prejudice for *ResMed Inc., et al.* v. *Fisher & Paykel Healthcare Corp. Ltd., et al.*, Case No. 3:16-cv-02072-JAH-MDD (S.D. Cal.) , dated Aug. 18, 2016.

Statutory Declaration made by Alistair Edwin McAuley, Apr. 9, 2015, in the matter of an Opposition by Fisher & Paykel Healthcare Limited of Australian patent application 2009221630 in the name of ResMed Limited.

Statutory Declaration made by Alistair Edwin McAuley, Apr. 14, 2015, in the matter of an Opposition by Fisher & Paykel Healthcare Limited of Australian patent application 2009221630 in the name of ResMed Limited.

Statutory Declaration made by Alistair Edwin McAuley, Apr. 17, 2015, in the matter of an Opposition by Fisher & Paykel Healthcare Limited of Australian patent application 2009221630 in the name of ResMed Limited.

Statutory Declaration made by Alistair Edwin McAuley, Sep. 16, 2015, in the matter of an Opposition by Fisher & Paykel Healthcare Limited of Australian patent application 2009221630 in the name of ResMed Limited.

First Affidavit of Alistair Edwin McAuley, Dec. 5, 2016, in the matter of *Fisher and Paykel Healthcare Limited* v. *ResMed Limited* filed in the Federal Court of Australia.

Second Affidavit of Alistair Edwin McAuley, Dec. 21, 2016, in the matter of *Fisher and Paykel Healthcare Limited* v. *ResMed Limited* filed in the Federal Court of Australia.

Third Affidavit of Alistair Edwin McAuley, Jan. 31, 2017, in the matter of *Fisher and Paykel Healthcare Limited* v. *ResMed Limited* filed in the Federal Court of Australia, 284 pp.

Declaration of Anthony Michael Ging in IPR 2019-000172, IPR 2019-000173, IPR 2019-000177, IPR 2019-000178, dated Nov. 8, 2018, 329 pp.

McGraw-Hill Dictionary of Scientific and Technical Terms, Sixth Edition, 2003, Tube, p. 2200.

Claim Chart for Air Fit P10, U.S. Pat. No. 9,333,315, dated Nov. 7, 2018, 3 pp.

Affidavit of Martina Elise Muellers regarding the purchase of a sample of the "Respironics ComfortClassic nasal mask".

An extract of parallel infringement proceedings on the basis of the opposed patent that a reinforcing member necessarily limits the lateral expansion of the cushion, dated Sep. 16, 2016, 3 pp.

Cleaning Instruction for the "Respironics ComfortClassic nasal mask" dated 2002, 4 pp.

A submission of Jan. 2, 2018 in parallel proceedings in New Zealand.

Declaration of Greg Olsen regarding the "Respironics ComfortClassic nasal mask".

Excerpt from a notice of Sep. 6, 2017 in parallel proceedings pending in Germany.

Excerpt from a notice of Sep. 8, 2018 in parallel proceedings pending in Australia, 3 pp.

Excerpt from a submission of Jan. 31, 2017 in parallel proceedings pending in New Zealand, 2 pp.

Expert opinion of Mr. Herbert T. Bauer, dated Sep. 4, 2017, 18 pp. Extract of patentee's submission of Oct. 24, 2016 made in preliminary injunction proceedings based on the opposed patent.

FDA Home Medical Devised Databases, 510(k) Premarket Notification, 3 pp., Decision Date Jan. 31, 1996.

Feature analysis of claim 1 of EP 1 841 482 B1.

ResMed, Instruction manual of the "MAP Papillon mask", 2005. Instructions for Use for the "Respironics ComfortClassic Nasal Mask" (English and German version), 7 pp.

Invoice for a Respironics ComfortClassic nasal mask, dated Jun. 13, 2003.

Letter of May 16, 2018 from the procedure of European patent No. EP 1 841 482 B1 with enclosures.

Opposition Division preliminary opinion in EP 1 841 482 B1 (with enclosures), filed Aug. 22, 2019.

Overview table regarding the auxiliary requests filed by the patentee, submitted May 16, 2018, 1 p.

Respironics Inc, Securities and Exchange Commission Form 10-K Annual Report, Jun. 30, 1998, 79 pp.

Respironics Monarch Mini, 1 p. with 7 pp. of photos dated Jul. 20, 2005.

Respironics, Inc, Sep. 30, 1997, Solo<sup>TM</sup> CPAP System, User Instructions, 33 pp.

Respironics ComfortCurve, 1 p. with 7 pp. of photos dated Nov. 4, 2005

Affidavit of Christopher Bryn Sparks regarding European patent No. EP1841482B1, dated Nov. 12, 2018, 5 pp.

Affidavit of Christopher Earl Nightingale regarding European patent No. EP1841482B1, dated May 15, 2018, 16 pp.

Affidavit of Christopher Earl Nightingale regarding European patent No. EP1841482B1, dated May 9, 2018, 22 pp.

Affidavit of Richard Joseph Lordo regarding European patent No. EP1841482B1, dated Nov. 26, 2019, 3 pp.

Affidavit of Richard Joseph Lordo regarding European patent No. EP1841482B1, dated Nov. 29, 2018, 5 pp.

#### OTHER PUBLICATIONS

Department of Health and Human Services, May 7, 1997, Premarket Notification [501(k)] review, Appendix 2, ResMed Operating Manual, Autoset Home System, 7 pp.

Resmed, Aug. 26, 1997, Mask frames, nasal cushions and headgear, web page, http://web/archive/org/web/199806111424/http:/www.resmed.com:80/maskframes/standar.htm., 3 pp.

Resmed, Feb. 12, 2001, Modular mask components and part numbers, https://web.archive.org/web/20010212075443/http:www.resmed.com:80/products/modular\_components.htm, 1 p.

Photos of the Fisher and Paykel Healthcare Aclaim Mask, photos taken Oct. 6, 2023, 133 pp. (uploaded in 4 parts) The Fisher & Paykel Aclaim Mask has been publicly displayed, offered for sale and sold by the Applicant since at least 200.

Photos of the Healthdyne Soft Series Mask, photos taken Oct. 6, 2023, 45 pp. The Healthdyne Soft Series Mask has been publicly displayed, offered for sale and sold since at least 1993.

Letter to IP Australia dated Jun. 14, 2023 in Australian patent application No. 2021240146, 1 pp.

Opposition—Statement of Grounds and Particulars dated Jul. 18, 2023 in Australian patent application No. 2021240146, 20 pp.

Photos of the ResMed Activa Mask and Associated Packaging, photos taken Feb. 3, 2023, 120 pp.

The ResMed Mirage Activa Nasal Mask has been publicly displayed, offered for sale and sold by ResMed Pty Ltd since at least 2003 (Uploaded in 2 parts).

Photos of the ResMed Activa LT Mask and Associated Packaging, photos taken Feb. 3, 2023, 75pp. (uploaded in 5 parts) The ResMed Mirage Activa LT Nasal Mask has been publicly displayed, offered for sale and sold by ResMed Pty Ltd since at least 2008 (Uploaded in 5 parts).

Photos of the Respironics Comfort Curve and Associated Packaging, photos taken Feb. 3, 2023,143 pp. The Respironics Comfort Curve has been publicly displayed, offered for sale and sold by Respironics since at least 2005.

Photos of the Respironics Monarch Mini and Associated Packaging, photos taken Feb. 3, 2023, 152 pp. The Respironics Monarch Mini has been publicly displayed, offered for sale and sold by Respironics since at least 2000.

Statement of Grounds and Particulars dated Jun. 9, 2023 in Australian patent application No. 2021240146, 16 pp.

Statement of Grounds and Particulars dated Jul. 12, 2023 in Australian patent application No. 202173595, 19 pp.

Statutory Declaration for David John Palkon dated Sep. 7, 2023 in Australian patent application Nos. 2021240146 and 2021273595, 1879 pp. (uploaded in 4 parts).

Statutory Declaration for Melody Crinion dated Sep. 7, 2023 in Australian patent application Nos. 2021240146 and 2021273595, 98 pp.

Statutory Declaration of Robynne Lyndsay Sanders dated Sep. 7, 2023 in Australian patent application Nos. 2021240146 and 2021273595, 6566 pp (uploaded in 54 parts).

Photos of the Sullivan Bubble Mask, photos taken Feb. 3, 2023, 49 pp. (uploaded in 2 parts) TheSullivan Bubble Mask has been publicly displayed, offered for sale and sold by ResMed Pty Ltd (or its predecessor in title) since at least 1996.

Declaration of Jason Eaton dated Dec. 11, 2023 in the matter of Australian Patent ApplicationsNo. 2021240146 and 2021273595 in the name of Fisher & Paykel Healthcare Limited and Opposition by ResMed Pty Ltd, 227 pp.

European Examination Report, European Application 13828380.9, dated Jul. 27, 2018, 8 pp.

European Examination Report, European Application 13828380.9, dated Mar. 3, 2020, 8 pp.

European Extended Search Report dated Feb. 14, 2019 in patent application No. 18195537.8.

European extended search report dated Oct. 31, 2018 in patent application No. 18171619.2, 9 pp.

European Extended Search Report in patent application No. 10830251. 4, dated Sep. 4, 2015, 7 pages.

European Extended Search Report in patent application No. 17179765. 7, dated Dec. 11, 2017, 8 pages.

European Extended Search Report; dated Apr. 2, 2014; Application No. 09819444.2; 8 pages.

European Patent Office, Extended European Search Report, Application No. 18163847.9-1122, dated Jul. 23, 2018, in 7 pages.

European Search Report and Written Opinion in patent application No. 09746823.5, dated May 12, 2016, 12 pages.

European Search Report in patent application No. 11830981.4, dated Aug. 24, 2015; 6 pages.

European Search Report in patent application No. 191976761.1, dated Mar. 3, 2020, 10 pages.

European Summons to Attend Oral Proceedings and Written Opinion in patent application No. 09746823.5, dated Dec. 13, 2017, 7 pages.

Extended European Search Report in EP patent application No. 18178220.2, dated Sep. 21, 2018, 8 pp.

Extended Search Report; European Application No. 10774623.2; dated Sep. 8, 2015; 7 pages.

Great Britain combined search and examination report dated May 11, 2018 in patent application No. GB1805606.9. 3 pp.

Great Britain Combined Search and Examination Report in patent application No. GB1406401.8, dated May 7, 2014, 4 pages.

Great Britain Combined Search and Examination Report in patent application No. GB1406402.6, dated May 7, 2014, 6 pages.

Great Britain Combined Search and Examination Report in patent application No. GB1719334.3, dated Nov. 30, 2017, in 9 pages. Great Britain examination report dated Jul. 20, 2018 in patent application No. GB1719334.3, 3 pp.

Great Britain examination report dated Jul. 5, 2018 in patent application No. GB1805606.9, 3 pp.

Great Britain examination report dated May 11, 2018 in patent application No. GB1805605, 1, 7 pp.

Great Britain examination report dated May 30, 2018 in patent application No. GB1719334.3, 4 pp.

Great Britain Examination Report in patent application No. GB1119385. 1, dated May 9, 2013, 4 pages.

Great Britain examination report in patent application No. GB1501499. 6, dated Jun. 1, 2017, in 8 pages.

Indian Examination Report dated Mar. 14, 2019 in patent application No. 8767/CHENP/2011. 6 pages.

Indian Examination Report in patent application No. 1431/KOLNP/2012. 7 pages.

Intention to Grant dated Nov. 22, 2021, in EP Application No. 18171619.2; in 55 pages.

International Preliminary Report on Patentability (IPRP), International application No. PCT/NZ2009/000219, dated Apr. 12, 2011,9 pages.

International Preliminary Report on Patentability and Written Opinion of the ISA; International Application No. PCT/ NZ2010/000229; dated May 22, 2012; 14 pages.

International Search Report and Written Opinion received for PCT Patent Application No. PCT/NZ2009/000072, mailed on Jul. 28, 2009, 12 pages.

International Search Report for application No. PCT/NZ2005/000062 dated May 27, 2005. 3 pages.

International Search Report for International Application No. PCT/NZ2007/000185, dated Oct. 31, 2007 in 3 pages.

International Search Report for International application No. PCT/NZ2014/000021, filed Feb. 21, 2014, 10 pages.

International Search Report, International Application No. PCT/NZ2009/000219, mailed Feb. 2, 2010, 3 pages.

International Search Report, PCT/NZ2010/000229, dated Mar. 18, 2011.8 pages.

International Search Report, PCT/NZ2011/000211, dated Feb. 17, 2012, 4 pages.

International Search Report; Application No. PCT/NZ2013/000138; dated Nov. 1, 2013; 7 pp.

Japanese Decision for Final Rejection dated Jul. 1, 2019 in patent application No. 2017-238259, 2 pp.

Japanese Examination Report in patent application No. 2012-510418, dated Feb. 10, 2014, 4 pages.

#### OTHER PUBLICATIONS

Japanese Examination Report in patent application No. 2012-538784, dated Aug. 25, 2014, 7 pages.

Japanese Examination Report in patent application No. 2015-098324, dated Jul. 22, 2015, 8 pages.

Japanese examination report in patent application No. 2015-526496, dated Apr. 17, 2017, in 13 pages.

Japanese Examination Report in patent application No. 2015-526496, dated Feb. 28, 2018, 2 pp.

Japanese Examination Report in patent application No. 2017-040092, dated Feb. 5, 2018. 4 pages.

Japanese Examination Report; dated Jul. 22, 2015; Application No. 2015-098324; 8 pages.

Japanese notification of reason for rejection in patent application No. 2012-538784, dated Aug. 5, 2015, 10 pp.

Japanese office action dated Sep. 1, 2019 in patent application No. 2018-188040. 10 pages.

Japanese Office Action; Application No. 2012-538784; dated Jul. 25, 2016; 4 pages.

Japanese Official Action dated Sep. 3, 2018 in patent application No. 2017-238259. 8 pages.

Japanese Pretrial Examination Report dated Jan. 7, 2020 in patent application No. 2017-238259. 4 pages.

Office Action in corresponding Indian Patent Application No. 5250/KOLNP/2008, dated May 23, 2017, in 8 pages.

Office Action, Canadian Application No. 2890556; dated Jan. 27, 2016; 3 pages.

Office Action; European Application No. 07808683.2; dated Jul. 8, 2015; 8 pages.

Scheduling Order dated Jul. 16, 2019 in IPR2019-00180, 12 pp. Third Office Action; Chinese Application No. 201080061122.1; dated Apr. 1, 2016; 5 pages.

UK Search and Examination Report; Mar. 14, 2013; Application No. GB1210075.6; 2 pages.

Written Opinion of the international Searching Authority, PCT/NZ2013/000139, dated Nov. 1, 2013. 5 pages.

Written Opinion, PCT/NZ2011/00021, dated Feb. 17, 2012, 7 pages.

Written Opinion; PCT/NZ2011/000211; dated Feb. 172012; 7 pages.

\* cited by examiner




FIGURE 1 (Prior Art)





FIGURE 2 (Prior Art)






FIGURE 4A (Prior Art)





FIGURE 4B (Prior Art)







FIGURE 6 (Prior Art)











FIGURE 8























FIGURE 13

FIGURE 14A

Aug. 19, 2025




FIGURE 14B




FIGURE 14C







FIGURE 14D







#### **BREATHING ASSISTANCE APPARATUS**

#### PRIORITY, INCORPORATION BY REFERENCE

This application is a continuation of U.S. patent application Ser. No. 17/816,275, filed Jul. 29, 2022 and issuing as U.S. Pat. No. 11,766,535, which is a continuation of U.S. patent application Ser. No. 17/568,186, filed Jan. 4, 2022, now U.S. Pat. No. 11,559,650, which is a continuation of U.S. patent application Ser. No. 16/384,218, filed Apr. 15, 2019, now U.S. Pat. No. 11,247,013, which is a continuation of both U.S. patent application Ser. No. 14/977,083, filed Dec. 21, 2015, now U.S. Pat. No. 10,272,218, and of U.S. patent application Ser. No. 15/425,937, filed Feb. 6, 2017,  $_{15}$ now U.S. Pat. No. 10,835,702. Both U.S. patent application Ser. Nos. 14/977,083 and 15/425,937 claim priority to U.S. patent application Ser. No. 13/877,903, filed May 30, 2013, now U.S. Pat. No. 9,561,338, which claims priority to international Patent App. No. PCT/NZ2011/000211, filed 20 Oct. 7, 2011, which claims benefit of U.S. Provisional Patent App. No. 61/391,527, filed Oct. 8, 2010. All of the above, and any and all applications for which a foreign or domestic priority claim is identified in the Application Data Sheet as filed with the present application, are hereby incorporated by 25 reference under 37 CFR § 1.57, for all that each contains, for all purposes.

#### **BACKGROUND**

#### Field

The present invention generally relates to patient interfaces. More particularly, the present invention relates to such interfaces particularly though not solely for use in delivering <sup>35</sup> CPAP therapy to patients suffering from obstructive sleep apnoea (OSA).

#### Related Art

In the art of respiration devices, there are a variety of respiratory masks that cover the nose and/or mouth of a human user in order to provide a continuous seal around the nasal and/or oral areas of the face such that gas may be provided at positive pressure within the mask for consumption by the user. The uses for such masks range from high altitude breathing (i.e., aviation applications) to mining and firefighting applications, to various medical diagnostic and therapeutic applications.

Such respiratory masks should provide an effective seal 50 against the user's face to reduce the likelihood of leakage of the gas being supplied. Commonly, in prior mask configurations, a good mask-to-face seal has been attained in many instances only with considerable discomfort for the user. This problem is prevalent in those applications, especially 55 medical applications, in which the user wears a mask or patient interface continuously for hours or perhaps even days. In such situations, the user may not tolerate the mask for long durations and optimum therapeutic or diagnostic objectives thus will not be achieved, or will be achieved with 60 great difficulty and considerable user discomfort.

To aid with user comfort, masks can be provided in a range of different sizes. A user will find one particular size in the available range of sizes most suitable for providing an effective seal and a comfortable fit. A single mask frame can 65 be provided to which a range of different sized seals may be fitted. A user chooses the most suitably sized seal from the

2

available range (e.g., the user chooses one size from small, medium, large and extra large) and attaches that seal to the mask frame for use.

A further example of a way in which differently sized users are accommodated is the nasal mask range disclosed in US2010/0006101, the entire contents of which are hereby incorporated by reference herein. As shown in FIG. 1 of this application, three different sized mask bodies 430 and correspondingly sized seal assemblies 440 are provided. A user may select the most suitably sized frame and corresponding seal assembly for use. Various components of the nasal mask disclosed in US2010/0006101 are described below with reference to FIGS. 2 to 6.

The mask assembly 402 comprises a mask body 430 and a mask seal assembly 440. The mask body 430 provides the overall structural support for the mask assembly, and provides a clip type fitting 433 for attaching the mask assembly 402 to headgear 421. The mask body includes a forehead support 431 to which the headgear is also attached.

A rear side of the mask body 430 interfaces to the seal assembly 440. The seal assembly 440 provides a sealing interface against a user's face in use.

The mask body 430 has an inlet for receiving a flow of respiratory gases and exhaust holes 425 to allow exhaled breath to be vented from the mask assembly. The mask body forms an internal cavity to which respiratory gases are supplied via the inlet. The inlet comprises a tubular projection 422 extending from a front side 471 of the mask body 430. A connector 423 connects to the inlet and swivels with respect to the mask body 430, for connecting a supply conduit to the mask body.

The seal assembly 440 comprises a flexible seal 443 attached to a relatively rigid plastic clip 442. The flexible seal 443 is over-moulded to the plastic clip 442 so that the seal assembly 440 forms a single item of the mask assembly 402. The plastic clip has a series of holes 446 around its perimeter. During manufacture, overmoulding of the seal to the clip causes the seal material to flow through the series of holes 446. During manufacture, the seal material is cured. Once cured, the seal 443 is mechanically linked to the plastic clip 442 via holes 446, providing a mechanical joint between the clip and the seal. The holes 446 are located through a raised ridge 445 running around the inside perimeter of the clip.

The clip 442 releasably attaches to the mask body in a 'clip' or 'snap' type engagement. A series of bumps 448, or raised portions, on the mask body 430 interact with corresponding recesses 447 on the clip 442, to hold the clip 442 in place on the body 430. As the clip 442 attaches to the mask body, interference between the clip and each mask body bump 448 causes the clip or the mask body, or both, to deflect to a deflected condition until each bump 448 reaches a corresponding recess 447. Once the clip has been fully engaged with the body, each bump 448 locates within a corresponding recess 447, and the clip or body, or both un-deflect from the deflected condition to an un-deflected or partially deflected condition, the parts being clipped or snapped together in a fully engaged position.

The clip 442 preferably has a relatively long lead in, or ramped profile 449, leading to the clip recess 447. This lead in section extends the full inside perimeter length of the clip 442. The lead-in section assists with the attachment of the clip to the mask body. The clip 442 or mask body 430, or both, are gradually deflected over the length of the lead-in section until the apex of the lead-in section and each mask body bump 448 pass each other. Once the bumps 448 have passed over the lead-in section, the bumps 448 locate within

each corresponding recess 447, such that there is little or no interference between the two parts 430 and 442. The two parts un-deflect in a relatively sudden snap action compared to the gradual deflection caused by the lead in section 449 during engagement.

The face seal assembly 440 includes at least one wing portion 444 to assist a user to disengage the face seal assembly from the mask body. The wing portions 444 provide a gripping flange to pull the clip 442 away from the mask body 430.

The nasal mask includes a cushion 441. Cushion 441 is provided around the periphery of the mask, and is surrounded by the seal assembly 440. The cushion 441 provides support to the seal 443 to achieve an effective seal onto the 15 face of the user to reduce the likelihood of leakage.

One end 462 of the mask cushion is shaped to match the shape of the seal in contact with the user's face, and an opposite end 463 is shaped to match the mask body. The cushion includes a raised bridge 465 in the nasal bridge 20 region. The raised bridge 465 can also be described as a cut out section made in the cushion, the cut out being on the mask body end 463 of the cushion. As the raised bridge 465 is unsupported by the mask body 430, it is much more flexible and results in less pressure on the nasal bridge of the  $\,^{25}$ patient.

The cushion 441 is located around the outer periphery of the mask body, contacting the mask body except for in the raised bridge portion 465 of the cushion. The cushion is located in a generally triangular cavity 466, the cavity 30 continuing around the periphery of the body, terminating at each side of the nose bridge region 467 of the mask, where the raised bridge portion 465 of the cushion does not contact the mask body 430. The cavity 466 is generally formed by two spaced apart walls 476 and 477. The cushion 441 is a 35 separate item, the seal assembly 440 fitting in place over the cushion to hold it in place within the mask assembly 402.

In this specification where reference has been made to patent specifications, other external documents, or other sources of information, this is generally for the purpose of 40 providing a context for discussing the features of the invention. Unless specifically stated otherwise, reference to such external documents is not to be construed as an admission that such documents, or such sources of information, in any jurisdiction, are prior art, or form part of the common 45 general knowledge in the art.

#### **SUMMARY**

An object of the present invention is to provide a patient 50 interface which goes some way to overcoming disadvantages in the prior art or which will at least provide the users with a useful choice.

In one aspect, the present invention broadly consists in a mask assembly for use as part of an apparatus for supplying 55 is larger at a bottom portion of the seal assembly and smaller a flow of respiratory gases to a user, comprising:

- a mask body having an inlet through which said flow of respiratory gases are provided to the interior of said mask body, the inlet adapted to be connected to a gases conduit.
- a mask seal assembly comprising a seal of flexible material and a clip of rigid material,
- the seal having a first side and a second side, the first side of the seal being shaped to approximately match the contours of a user's face and in use substantially seal 65 against a user's face, the second side attached to said

the clip providing an interface extending substantially the full perimeter or periphery of the mask seal assembly for releasably attaching the mask seal assembly to the mask body, and

wherein the clip comprises a bridging portion spanning outwards from the perimeter or periphery of the mask body to space at least a portion of the second side of the seal outwards from the perimeter or periphery of the mask body.

Preferably the mask assembly comprises an inner cushion located between the clip and the first side of the seal.

Preferably the inner cushion is located between the bridging portion of the clip and the first side of the seal.

Preferably the clip comprises a channel in the bridging portion, a first side of the inner cushion in use supporting the first side of the seal, and a second side of the inner cushion being received in the channel.

Preferably the seal is attached to a first side of the clip and a second side of the clip releasably attaches to the mask body, and the bridging portion spans between the first and second sides of the clip.

Preferably the seal assembly comprises a second seal of flexible material attached to the second side of the clip for forming a seal between the mask seal assembly and the mask body.

Preferably the bridging portion and the seal are sized according to one of a series of sizes, each one of the series of sizes suitable for sealing against a differently sized user's face.

Preferably the mask body is adapted for use with a plurality of the seal assemblies, at least one said seal assembly having a said bridging portion, each said seal assembly having a said seal sized according to one of a series of sizes, each one of the series of sizes suitable for sealing against a differently sized user's face, and the second side of the clip of each said seal assembly being the same or similar to be releasably attached to the mask body.

Preferably the seal and the second seal are integrally formed and joined together across the bridging portion.

Preferably the seal and the second seal are integrally formed and joined together across the bridging portion via a runner across or through the bridging portion.

Preferably the mask assembly comprises an inner cushion located between the mask body and the first side of the seal.

Preferably the mask assembly comprises a channel in the mask body, a first side of the inner cushion in use supporting the first side of the seal, and a second side of the inner cushion being received in the channel in the mask body.

Preferably the bridging portion has an outward dimension that is the same or similar around the perimeter or periphery of the mask body.

Preferably the bridging portion has an outward dimension that varies around the perimeter or periphery of the clip.

Preferably the outward dimension of the bridging portion at an upper portion or nasal bridge region of the seal

Preferably the bridging portion tapers from a first outward dimension in the bottom portion of the mask assembly to a 60 second outward dimension in the upper portion or nasal bridge region of the mask assembly.

Preferably each said seal assembly in the said plurality of seal assemblies has a bridging portion with a first outward dimension in the bottom of the mask assembly and a second outward dimension in the upper portion of the mask assembly and the first outward dimension is greater than the second outward dimension, and the second outward dimen-

sion of each said seal assembly is the same or similar, and the first outward dimension of each said seal assembly is different to the first outward dimension of the other said seal assemblies in said plurality of seal assemblies, the first outward dimension of each said seal assembly sized to be suitable for sealing against a differently sized user's face.

Preferably the bridging portion extends rearward away from a front of the mask body towards a user's face in use.

Preferably the mask body is adapted for use with a plurality of the seal assemblies, at least one said seal assembly having a said bridging portion, each said seal assembly having a seal of a different type comprising one of a cannula seal, a nasal seal, a mouth seal and a full face seal, and the second side of the clip of each said seal assembly being the same or similar to be releasably attached to the mask body

Preferably the mask seal assembly releasably attaches to a rear perimeter of the mask body.

Preferably the rear perimeter of the mask body defines an 20 area being more than ten times the area of the mask body inlet.

Preferably the bridging portion spaces the second side of the seal outwards from the perimeter or periphery of the mask body by at least 10 mm.

Preferably the mask body defines a hollow space for receiving or covering a user's nose or mouth or both.

In another aspect, the present invention broadly consists in a mask package comprising:

- a mask body having an inlet through which a flow of 30 respiratory gases are provided to the interior of the mask body, the inlet adapted to be connected to a gases conduit.
- a first seal assembly comprising:
- a first seal of a flexible material and a first clip of a rigid 35 material, the first seal having a first side and a second side, the first side of the first seal being shaped to approximately match the contours of a user's face and in use substantially seal against a user's face, said second side of said first seal attached to said first clip, 40
- the first clip providing an interface extending substantially the full perimeter or periphery of the first seal assembly, the second side of the first seal attached to a first side of the first clip and a second side of the first clip for releasably attaching the first seal assembly to the mask 45 body,
- a second seal assembly comprising:
- a second seal of a flexible material and a second clip of a rigid material, the second seal having a first side and a second side, the first side of the second seal being 50 shaped to approximately match the contours of a user's face and in use substantially seal against a user's face, said second side of said second seal attached to said second clip.
- the second clip providing an interface extending substantially the full perimeter or periphery of the second seal assembly, the second side of the second seal attached to a first side of the second clip and a second side of the second clip for releasably attaching the second seal assembly to the mask body,

  60
- wherein the first clip or the second clip or both comprises a bridging portion spanning outwards from the perimeter or periphery of the mask body to space at least a portion of the second side of the first or second seal outwards from the perimeter or periphery of the mask body when the first or second seal assembly is attached to the mask body, and the first side of the first clip being

6

comparatively different to the first side of the second clip, and the first seal being comparatively different to the second seal.

Preferably the mask package comprises a first inner cushion for use with the first seal assembly and a second inner cushion for use with the second seal assembly.

Preferably the first seal assembly attached to the mask body, the first inner cushion is located between the first clip and the first side of the first seal, or with the second seal assembly attached to the mask body, the second inner cushion is located between the second clip and the first side of the second seal.

Preferably the first seal assembly attached to the mask body, the first inner cushion is located between the bridging portion of the first clip and the first side of the first seal, or with the second seal assembly attached to the mask body, the second inner cushion is located between the bridging portion of the second clip and the first side of the second seal.

Preferably the bridging portion of the first clip of the first seal assembly has a channel for receiving the first inner cushion, or/and the bridging portion of the second clip of the second seal assembly has a channel for receiving the second inner cushion.

Preferably the bridging portion of the first clip of the first seal assembly has an outward dimension that varies around the perimeter of the first clip, or the bridging portion of the second clip of the second seal assembly has an outward dimension that varies around the perimeter of the first clip.

Preferably the bridging portion of the first clip of the first seal assembly has a larger outward dimension at the bottom of the first seal assembly compared to the outward dimension at the top or nasal bridge region of the first seal assembly, and/or the bridging portion of the second clip of the second seal assembly has a larger outward dimension at the bottom of the second seal assembly compared to the outward dimension at the top or nasal bridge region of the second seal assembly.

Preferably the bridging portion of the second clip of the second seal assembly has a larger outward dimension at the bottom of the second seal assembly compared to the bridging portion of the first clip of the first seal assembly, the second seal of the second seal assembly being larger than the first seal of the first seal assembly.

Preferably the bridging portion of the first clip of the first seal assembly and the bridging portion of the second clip of the second seal assembly have the same or a similar outward dimension in the nasal bridge region of the clip.

Preferably the first side of the second seal has a longer perimeter length than the first side of the first seal.

Preferably a mask assembly comprising the mask body and the first seal assembly has an internal cavity having a first depth, and a mask assembly comprising the mask body and the second seal assembly has an internal cavity having a second depth, the second depth being greater than the first depth.

Preferably the bridging portion of the second clip of the second seal assembly extends rearward away from the general plane of the mask body when the second seal assembly is attached to the mask body.

Preferably the first seal assembly comprises a seal of flexible material attached to the second side of the first clip for forming a seal between the first mask seal assembly and the mask body, and/or

the second seal assembly comprises a seal of flexible material attached to the second side of the second clip for forming a seal between the second mask seal assembly and the mask body.

Preferably the first seal of the first seal assembly and the seal on the second side of the first clip of the first seal assembly are integrally formed and joined together across the bridging portion of the first clip, and/or

the second seal of the second seal assembly and the seal 5 on the second side of the second clip of the second seal assembly are integrally formed and joined together across the bridging portion of the second clip.

Preferably a mask assembly comprising the mask body and the first seal assembly or the second seal assembly is a 10 nasal mask or a full face mask.

Preferably the first side of the second clip has a longer perimeter length than the first side of the first clip, the second seal being larger than the first seal.

Preferably the first side of the second seal has a longer 15 perimeter length than the first side of the first seal.

Preferably the first and second seals are different types of seals, the first and second seals being one of a cannula seal, a nasal seal, a mouth seal and a full face seal.

Preferably the first mask seal assembly and the second 20 mask seal assembly releasably attach to a rear perimeter of the mask body.

Preferably the rear perimeter of the mask body defines an area being more than ten times the area of the mask body inlet.

Preferably the bridging portion of the first clip spaces the second side of the first seal outwards from the perimeter or periphery of the mask body by at least 10 mm, or the bridging portion of the second clip spaces the second side of the second seal outwards from the perimeter or periphery of 30 the mask body by at least 10 mm.

Preferably the mask body defines a hollow space for receiving or covering a user's nose or mouth or both.

In another aspect, the present invention broadly consists in a mask assembly for use as part of an apparatus for 35 supplying a flow of respiratory gases to a user, comprising:

- a mask body having an inlet through which said flow of respiratory gases are provided to the interior of said mask body, the inlet adapted to be connected to a gases conduit
- a mask seal assembly comprising a seal of a flexible material and a clip of a rigid material,
- said seal having a first side and a second side, the first side of said seal being shaped to approximately match the contours of a user's face and in use substantially seal 45 against a user's face, said second side attached to said clip.
- said clip providing an interface extending substantially the full perimeter or periphery of the mask seal assembly for releasably attaching the mask seal assembly to 50 the mask body, and

an inner cushion located between the clip and said first side of the seal.

Preferably the clip comprises a bridging portion spanning outwards from the perimeter or periphery of the mask body 55 to space at least the second side of the seal outwards from the perimeter or periphery of the mask body.

Preferably the inner cushion is located between the bridging portion and the first side of the seal.

Preferably the clip comprises a channel in the bridging 60 portion, a first side of the inner cushion in use supporting the first side of the seal, and a second side of the inner cushion being received in the channel.

Preferably the seal is attached to a first side of the clip and a second side of the clip releasably attaches to the mask 65 body, and the bridging portion spans between the first and second sides of the clip.

8

Preferably the seal assembly comprises a second seal of flexible material attached to the second side of the clip for forming a seal between the mask seal assembly and the mask body.

Preferably the bridging portion and said seal are sized according to one of a series of sizes, each one of the series of sizes suitable for sealing against a differently sized user's face.

Preferably the mask body is adapted for use with a plurality of said seal assemblies, at least one said seal assembly having a said bridging portion, each said seal assembly having a said seal sized according to one of a series of sizes, each one of the series of sizes suitable for sealing against a differently sized user's face, and said second side of the clip of each said seal assembly being the same or similar to be releasably attached to the mask body.

Preferably the seal and the second seal are integrally formed and joined together across the bridging portion.

Preferably the seal and the second seal are integrally formed and joined together across the bridging portion via a runner across or through the bridging portion.

Preferably the mask assembly comprises an inner cushion located between the mask body and said first side of the seal.

Preferably the mask assembly comprises a channel in the mask body, a first side of the inner cushion in use supporting the first side of the seal, and a second side of the inner cushion being received in the channel in the mask body.

Preferably the bridging portion has an outward dimension that is the same or similar around the perimeter or periphery of the mask body.

Preferably the bridging portion has an outward dimension that varies around the perimeter or periphery of the clip.

Preferably the outward dimension of the bridging portion is larger at a bottom portion of the seal assembly and smaller at an upper portion or nasal bridge region of the seal assembly.

Preferably the bridging portion tapers from a first outward dimension in the bottom portion of the mask assembly to a second outward dimension in the upper portion or nasal bridge region of the mask assembly.

Preferably each said seal assembly in the said plurality of seal assemblies has a bridging portion with a first outward dimension in the bottom of the mask assembly and a second outward dimension in the upper portion of the mask assembly and the first outward dimension is greater than the second outward dimension, and the second outward dimension of each said seal assembly is the same or similar, and the first outward dimension of each said seal assembly is different to the first outward dimension of the other said seal assemblies in said plurality of seal assemblies, the first outward dimension of each said seal assembly sized to be suitable for sealing against a differently sized user's face.

Preferably the bridging portion extends rearward away from a front of the mask body towards a user's face in use.

Preferably the mask body is adapted for use with a plurality of the seal assemblies, at least one said seal assembly having a said bridging portion, each said seal assembly having a seal of a different type comprising one of a cannula seal, a nasal seal, a mouth seal and a full face seal, and the second side of the clip of each said seal assembly being the same or similar to be releasably attached to the mask body.

Preferably the mask seal assembly releasably attaches to a rear perimeter of the mask body.

Preferably the rear perimeter of the mask body defines an area being more than ten times the area of the mask body inlet.

Preferably the bridging portion spaces the second side of the seal outwards from the perimeter or periphery of the mask body by at least 10 mm.

Preferably the mask body defines a hollow space for receiving or covering a user's nose or mouth or both.

In another aspect, the present invention broadly consists in a mask seal assembly for use as part of an apparatus for supplying a flow of respiratory gases to a user, comprising: a seal of flexible material and a clip of rigid material,

the seal having a first side and a second side, the first side of the seal being shaped to approximately match the contours of a user's face and in use substantially seal against a user's face, the second side attached to said clip.

the clip providing an interface extending substantially the full perimeter or periphery of the seal assembly, the clip having a first side and a second side, the second side of the seal being attached to the first side of the clip, and the second side of the clip for releasably attaching the 20 mask seal assembly to a mask body,

wherein the clip comprises a bridging portion spanning between the first and second sides of the clip to space at least a portion of the second side of the seal outwards from the perimeter or periphery of the second side of <sup>25</sup> the clip.

Preferably the clip comprises a channel in the bridging portion for receiving an inner cushion for supporting the first side of the seal in use.

Preferably the seal assembly comprises a second seal of flexible material attached to the second side of the clip for forming a seal between the mask seal assembly and a mask body.

Preferably the bridging portion and the seal are sized according to one of a series of sizes, each one of the series of sizes suitable for sealing against a differently sized user's face.

Preferably the seal and the second seal are integrally formed and joined together across the bridging portion.

Preferably the seal and the second seal are integrally formed and joined together across the bridging portion via a runner across or through the bridging portion.

Preferably the bridging portion has an outward dimension that is the same or similar around the perimeter or periphery 45 of the mask seal assembly.

Preferably the bridging portion has an outward dimension that varies around the perimeter or periphery of the clip.

Preferably the outward dimension of the bridging portion is larger at a bottom portion of the seal assembly and smaller 50 at an upper portion or nasal bridge region of the seal assembly.

Preferably the bridging portion tapers from a first outward dimension in the bottom portion of the mask assembly to a second outward dimension in the upper portion or nasal 55 bridge region of the mask assembly.

Preferably the bridging portion extends rearward away from a front of a mask body to which the mask assembly is attached in use and towards a user's face in use.

Preferably the mask seal assembly is adapted to releasably 60 attach to a rear perimeter of a mask body defining a hollow space for receiving or covering a user's nose or mouth or both and having an inlet through which the flow of gases are provided to the interior of the mask body.

Preferably the rear perimeter of the mask body defines an 65 area being more than ten times the area of the mask body inlet.

10

Preferably the bridging portion spaces the second side of the seal outwards from the perimeter or periphery of the second side of the clip by at least 10 mm.

The term "comprising" is used in the specification and claims, means "consisting at least in part of." When interpreting a statement in this specification and claims that includes "comprising", features other than that or those prefaced by the term may also be present. Related terms such as "comprise" and "comprises" are to be interpreted in the same manner. The invention consists in the foregoing and also envisages constructions of which the following gives examples.

For purposes of summarizing the invention and the advantages achieved over the prior art, certain objects and advantages of the invention have been described above and as further described below. Of course, it is to be understood that not necessarily all such objects or advantages may be achieved in accordance with any particular embodiment of the invention. Thus, for example, those skilled in the art will recognize that the invention may be embodied or carried out in a manner that achieves or optimizes one advantage or group of advantages as taught herein without necessarily achieving other objects or advantages as may be taught or suggested herein.

All of these embodiments are intended to be within the scope of the invention herein disclosed. These and other embodiments of the present invention will become readily apparent to those skilled in the art from the following detailed description of the preferred embodiments having reference to the attached figures, the invention not being limited to any particular preferred embodiment(s) disclosed.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Preferred forms of the present invention will now be described with reference to the accompanying drawings. The appended drawings are schematic, not necessarily drawn to scale, unless otherwise indicated, and are meant to illustrate and not to limit embodiments of the invention.

FIG. 1 illustrates three differently sized prior art mask frames and corresponding seal assemblies.

FIG. 2 is a perspective view of the nasal mask of FIG. 1.

FIG. 3 is an exploded view of the nasal mask of FIG. 1. FIG. 4a is a perspective view of the mask seal assembly

of the nasal mask of FIG. 1.

FIG. 4b is a perspective view of the seal clip of the mask seal assembly of the nasal mask of FIG. 1.

FIG. 5 is a perspective view showing the mask body and the mask seal assembly of the nasal mask of FIG. 1, with the mask seal assembly removed from the mask body.

FIG. 6 is a sectional view on line X-X of the nasal mask of FIG. 2.

FIG. 7 is a block diagram of a humidified continuous positive airway pressure system as might be used in conjunction with the mask assembly of the present invention.

FIG. 8 is a cross sectional view of a mask assembly according to one embodiment of the present invention.

FIGS. 9A to 9C are part sectional views of a lower portion of a series of three differently sized mask assemblies.

FIGS. **10**A to **10**C are part sectional views of a lower portion of three alternative mask assemblies each having a 'large' sized seal assembly.

FIGS. 11A to 11C are part sectional views of a lower portion of three alternative mask assemblies each having a 'medium' sized seal assembly.

FIG. 12 is a diagram showing part sectional views of a common mask body and a range of mask seal assemblies for attachment to the common mask base.

FIG. 13 is a perspective view of a mask assembly comprising the present invention with section cut away to show 5 a lower portion of the mask assembly in cross section.

FIGS. 14A to 14D show cross sections of alternative seal arrangements for forming a seal between a seal assembly and a mask body of a mask assembly comprising the present invention.

FIGS. **15**A and **15**B are part sectional views of a lower portion of two alternative mask assemblies each with a first seal and a second seal joined together across a bridging portion of a seal clip.

#### DETAILED DESCRIPTION

It will be appreciated that the mask assembly as described in the preferred embodiment of the present invention can be used in respiratory care generally or with a ventilator, but 20 will now be described below with reference to use in a humidified Continuous Positive Airway Pressure (CPAP) system. It will also be appreciated that the present invention can be applied to various forms of mask assembly including, but not limited to, nasal masks and full face masks that cover 25 both the user's nose and mouth.

With reference to FIG. 7 a humidified CPAP system is shown in which a patient 1 is receiving humidified and pressurised gases through a patient interface 2 connected to a supply conduit 3. It should be understood that CPAP is 30 used generically and includes a range of variants including VPAP (Variable Positive Airway Pressure) and BiPAP (Bilevel Positive Airway Pressure) and numerous other forms of respiratory therapy.

Supply conduit 3 is connected to the outlet 4 of a 35 humidification chamber 5 that contains a volume of water 6. Supply conduit 3 may contain a heater or heater wires (not shown) which heat the walls of the conduit or the gases in the conduit to reduce condensation of humidified gases within the conduit. Humidification chamber 6 is preferably 40 formed from a plastics material. The contents of the chamber are heated by a heater. For example the chamber may have a highly heat conductive base (for example an aluminium base) which is in direct contact with a heater plate 7 of humidifier 8. Humidifier 8 is provided with control means or 45 electronic controller 9 which may comprise a microprocessor based controller executing computer software commands stored in associated memory.

Controller 9 receives input from sources such as a user interface or dial 10 through which a user of the device may, 50 for example, set a value (e.g., a preset or predetermined value) of humidity or temperature of the gases to be supplied. The controller may also receive input from other sources; for example temperature and/or flow velocity sensors 11 and 12 through connector 13 and heater plate 55 temperature sensor 14. In response to the user set humidity or temperature value input via dial 10 and the other inputs, controller 9 determines when (or to what level) to energise heater plate 7 to heat the water 6 within humidification chamber 5. As the volume of water 6 within humidification 60 chamber 5 is heated, water vapour begins to fill the volume of the chamber above the water's surface and is passed out of the humidification chamber 5 outlet 4 with the flow of gases (for example air) provided from a gases supply means or blower 15 which enters the chamber through inlet 16. 65 Exhaled gases from the patient's mouth are passed directly to ambient surroundings in FIG. 1.

12

Blower **15** is provided with variable pressure regulator or a variable speed fan **21**. The fan draws air or other gases through blower inlet **17**. The speed of the variable speed fan **21** is controlled by electronic controller **18** (or alternatively the function of controller **18** could carried out by controller **9**) in response to inputs from controller **9**. Mask Assembly

A mask assembly 2 according to the present invention is described with reference to FIGS. 8 to 13. FIG. 8 shows a mask comprising a mask body 30. The mask body includes an inlet 22 for receiving a flow of gases into the mask assembly. The mask body preferably includes features for securing the mask assembly in position on the user's face. For example, the embodiment of FIG. 8 includes a forehead rest 31 to assist with correct placement of the mask assembly against the user's face, and a clip 33 for attachment to headgear. Headgear may also be attached to features of the forehead rest. The mask body may include other known features, for example vent holes 25 for venting expired gases and air, and a channel 66 for receiving an inner cushion (not shown) for supporting the seal 43.

A seal assembly 40 comprising a seal 43 of a flexible material and clip 42 of a rigid material is attached to a rear side of the mask body. A first side of the flexible seal contacts a user's facial features in use. A second side of the flexible seal is attached to the clip. The seal assembly is releasably attached to the mask body 30 by the clip. Preferably the clip extends substantially the full perimeter of the mask seal assembly. The clip is rigid compared to the seal material and provides a convenient interface for releasably attaching the flexible seal to the mask body. For example, the clip is manufactured from polycarbonate, ABS, nylon, acetyl or other similar rigid plastic. Alternatively the clip may be made from a high Shore A hardness silicone. For example, a silicone with a Shore A hardness of 90 may provide sufficient rigidity. The clip and mask body may be manufactured from the same material type. The seal is formed from rubber or other suitable flexible, resilient material. Preferable the seal is formed from silicone with a Shore-A hardness of less than 60. Preferably the seal is made from silicone with a Shore A hardness of 20-40.

From the above mentioned materials, the difference in rigidity of the clip material (rigid) and the seal material (flexible) will be appreciated. For example, polycarbonate has a Young's modulus of approximately 2 GPa, whereas the Young's modulus of a rubber or other suitable material for use as the flexible seal is in the order of 1 to 5 MPa.

The seal generally provides a flexible perimeter about the perimeter or periphery of the mask body. The seal surrounds an opening to the inside of the mask assembly. A nasal mask assembly seals against a user's face around the user's nose, the seal opening covering the user's nose. A full face mask seals against a user's face around the users nose and mouth, the seal opening covering both the user's nose and mouth.

The clip has a bridging portion 50 that spans outwards from the perimeter or periphery of the mask body 30. The bridging portion spaces at least a portion of the second side of the flexible seal 43 outwards from the perimeter or periphery of the mask body to which the clip is attached.

The mask body 30 may be used with a conventional seal assembly as disclosed in the prior art, for example as illustrated in FIG. 4A. Where a larger mask may be used by a larger user, the same mask body 30 useable with the conventional seal assembly may be used together with a seal assembly comprising a clip with a bridging portion 50. The bridging portion 50 allows a larger flexible seal 43 to be attached to the mask body 30, as illustrated in FIG. 8.

The present invention allows a single mask body 30 to be used for a range of differently sized users. For example, a range of differently sized seal assemblies may be provided. Each seal assembly may have a clip including a bridging portion 50. The bridging portion of each seal assembly may 5 be a different size and each clip may be attached to a different size flexible seal. A smallest seal assembly in a range of differently sized seal assemblies may not include a bridging portion, the smallest seal assembly being a standard or conventional type seal assembly, for example as illustrated in FIG. 4A.

For supply to a user, a packaged interface product may include a single mask body, and a plurality of these seal assemblies, each of a different size with at least one of the seal assemblies having a bridging portion. The package may 15 include instructions for selection and assembly of the seal assemblies to the mask body 30. The plurality of different size seal assemblies may be varied according to their size, by the size and arrangement of the bridging portion, the placement of an inner cushion and other aspects of variation 20 described in this specification.

The range of seal assemblies for use with a single mask body preferably each have an identical or at least similar connection portion or side for attaching to the single mask body.

The clip with bridging portion expands a mask body to a larger size for use with a larger flexible seal. The mask body may be used with a first seal assembly comprising a flexible seal and clip without a bridging portion, for example as shown in FIG. 9C. The same mask body may be used with 30 one or more seal assemblies each comprising a flexible seal and clip with a bridging portion to expand the mask body for use with a larger seal. A series of seal assemblies may be provided, each seal assembly in the series having a clip with a progressively larger bridging portion and corresponding 35 larger flexible seal. A plurality of seal assemblies with clips each having differently sized bridging portions may be provided to achieve a range of mask assemblies, for appropriate selection by a user, as illustrated in FIGS. 9A and 9B.

As shown in FIG. 8, preferably the bridging portion of the 40 clip has an outward dimension D that varies around the perimeter or periphery of the mask body. As shown in FIG. 8, preferably the outward dimension of the bridging portion is larger at a bottom portion of the clip and smaller at an upper portion of the clip. Alternatively, the bridging portion 45 may have an outward dimension the same or similar around the periphery of the mask body.

The outward dimension of the bridging portion of a number of different seal assemblies may be the same in a particular portion of the mask body perimeter or periphery 50 to which the clips are attached. For example, a range of different seal assemblies each may comprise a clip with bridging portion having a similar or the same outward dimension in the nasal bridge region, and each clip having a different outward dimension outside the nasal bridge 55 region.

A mask according to the present invention may include a mask body having a forehead rest, for example as shown in FIG. 8. It can be advantageous for a mask having a forehead rest to have a range of different seal assemblies each 60 comprising a clip with bridging portion having a similar or the same outward dimension in the nasal bridge region. With each clip in the range of seal assemblies having a similar outward dimension in the nasal bridge region, the distance between the top of the seal assembly and the forehead rest 65 remains the same across the range of different sized seal assemblies. This is preferred as the distance the forehead rest

14

is above the top of the mask body can be sized to be suitable for use with a range of different sized seal assemblies. By comparison, in a less preferred embodiment of the present invention, each seal assembly has a clip with bridging portion having a substantially constant outward dimension around the full parameter of the seal assembly. For larger seals, the distance between the top of the seal and the forehead rest therefore decreases.

The distance between the top of the seal and the forehead rest ideally should increase for increasing sized users. With each seal in a range of seals having the same bridging portion outward dimension in the nasal bridge region, the distance between the forehead rest and the top of each seal is the same, which is preferred to the previously described less preferred embodiment.

Preferably the clip has a bridging portion that tapers from a first outward dimension in a lower section of the seal to a second outward dimension in the nasal bridge region, the first dimension being greater than the second dimension.

The embodiment of FIG. 8 is illustrated without an inner cushion between the mask body 30 and the flexible seal 43. Preferably the mask assembly comprises an inner cushion between the mask body 30 and the flexible seal 43, or an inner cushion between the clip and the flexible seal.

FIGS. 10A to 10C illustrate alternative clips with a bridging portion in the lower portion of the seal assembly for providing a 'large' sized seal 43 compared to other sealing assemblies. In each embodiment of FIGS. 10A to 10C, an inner cushion is located between the clip and the first side of the flexible seal 43. Preferably the inner cushion is located between the clip bridging portion and the first side of the flexible seal.

Preferably the bridging portion comprises a channel 67 for receiving and locating a side of the inner cushion at the clip. The channel may extend around a full circumference of the clip, or the channel may extend around a portion of a circumference of the clip. For example, the channel may extend around the clip outside the nasal bridge region only for use with a cushion having a raised nasal bridge region similar to the configuration of the inner cushion described in US2010/0006101.

In the embodiment of FIG. 10B, the bridging portion extends outwardly from the mask body 30 and also rearward, away from the general plane of the mask body, towards the user in use. The mask body and seal assembly combine to provide a cavity for surrounding the user's nose. or mouth or both. The rearward extension of the clip bridging portion increases the depth of the cavity provided by the mask assembly. For example, the depth  $D_B$  of the cavity provided by the assembly of FIG. 10B with a rearward extension of the clip bridging portion is deeper than the depth  $D_4$  of the cavity of the assembly of FIG. 10A with a clip bridging portion that does not extend rearward. The rearward extension of the bridging portion 50 of the embodiment of FIG. 10B spaces the second side of the seal 43 rearward from the perimeter or periphery of the mask body. For larger sized users, for example a user with a larger nose, a deeper internal cavity provided by the mask body and seal clip may reduce the likelihood of the user's nose touching an inside surface of the mask body compared to a mask assembly comprising a smaller seal 43. Extending the second side of the flexible seal 43 rearwards by providing a clip with a rearward extending bridging portion provides a deeper cavity to receive the user's nose compared to a mask assembly having a clip without a rearward extending bridging portion.

In the alternative embodiment of FIG. 10C, a deeper mask cavity is created compared to the embodiment of FIG. 10A by providing a deeper inner cushion and flexible seal for sealing against the user's face. The embodiments of FIGS. 10A and 10C each have the same shaped clip with bridging 5 portion.

FIGS. 11A to 11C illustrate alternative clips with a bridging portion in the lower portion of the seal assembly for providing a 'medium' sized seal compared to other sealing assemblies. For example, the bridging portions 50 of the 10 embodiments of FIGS. 11A to 11C have a smaller outward dimension compared to the bridging portions 50 of the embodiments of FIGS. 10A to 10C so that the seal 43 of the embodiments of FIGS. 11A to 11C are smaller than the seals of the embodiments of FIGS. 10A to 10C. And the bridging 15 portions 50 of the embodiments of FIGS. 11A to 11C each provide a seal 43 that is larger than the seal of the illustrative embodiment comprising a clip with a bridging portion having a smaller outward dimension, or an embodiment comprising a clip without a bridging portion, for example 20 the illustrative embodiment of FIG. 9C.

In the embodiment of FIG. 11A, an inner cushion 41 is located between the mask body 30 and the first side of the flexible seal 43, similar in concept to the aforementioned nasal mask illustrated in FIGS. 1-6. A channel 66 is formed 25 in the mask body by two spaced apart members 76 and 77. A side of the inner cushion 41 in contact with the mask body is received in the channel 66.

FIGS. 11B and 11C illustrate embodiments similar to the embodiment of FIG. 10A described above, with the inner 30 cushion located between the clip 42 and the flexible seal 43. However the outward dimension of the clip bridging portion of the 'medium' seal assemblies of FIGS. 11B and 11C is smaller than the outward dimension of the 'large' clip of the embodiment of FIG. 10A.

Due to the smaller bridging portion of the clip of the medium seal assembly of FIG. 11B, the side of the inner cushion in contact with the clip may be reduced in cross section compared to the inner cushion of the large seal assemblies of FIGS. 10A to 10C. In the alternative embodiment of FIG. 11C, a channel for receiving the cushion in the seal assembly is formed by material of the flexible seal that contacts a user's face in use, and material of a second flexible seal 44 on the other side of the bridging portion 50.

The second flexible seal 44 is discussed below.

One embodiment of the present invention comprises a packaged mask assembly product including a single mask body and a plurality of seal assemblies of different sizes for use with the single mask body. For example, a mask package may include a single mask body 30 and a first seal assembly 50 540, a second seal assembly 640, and a third seal assembly 740, as shown in FIG. 12. The first seal assembly has a clip 542 and seal 543. The clip 542 does not have a bridging portion, the second side 5432 of the seal attached to the clip is not spaced outwards of the mask body when the seal 55 assembly is attached to the mask body. For example, a portion of the material forming the seal 543 also forms a seal against the mask body. The mask assembly comprising the mask body 30 and the first seal assembly 540 may also include an inner cushion 541 located between the first side 60 5431 of the seal 542 and the mask body 30. The inner cushion is received in the channel 66 of the mask body 30. The mask assembly comprising the first seal assembly 540 is most suited to users with smaller facial features compared to other users.

Where the first seal assembly is not large enough for a particular user, that user may chose to use the second seal 16

assembly 640. The second seal assembly has a clip 642 and seal 643. The clip 642 has a bridging portion 650 to space the second side 6432 of the seal attached to the clip outwards of the mask body when the seal assembly is attached to the mask body. The bridging portion has an outward dimension  $D_m$  to space the second side of the seal outwards from the mask body by a distance. The bridging portion 650 of clip 642 allows a larger seal to be used with the body 30 by comparison with the seal of the first seal assembly 540. For example, the seal 643 attached to clip 642 of the second seal assembly 640 may be taller and wider in places compared to the seal 543 of the first seal assembly 540.

The mask assembly comprising the mask body 30 and the second seal assembly 640 may also include an inner cushion 641. In the illustrated example, the inner cushion 641 is located between the first side 6431 of the seal 643 and clip 642. The inner cushion 641 is received in the channel 667 of the clip 642.

Where the second seal assembly is not large enough for a particular user, that user may chose to use the third seal assembly 740. The third seal assembly has a clip 742 and seal 743. The clip 742 has a bridging portion 750 to space the second side 7432 of the seal attached to the clip outwards of the mask body when the seal assembly is attached to the mask body. The bridging portion has an outward dimension D<sub>L</sub> to space the second side of the seal outwards from the mask body by a distance. By comparison, the outward dimension of the bridging portion 750 of the third seal assembly 740 is larger than the outward dimension of the bridging portion 650 of the second seal assembly 640. The bridging portion 750 of clip 742 allows a larger seal to be used with the body 30 by comparison with the seal of the second seal assembly 640. For example, the seal 743 attached to clip 742 of the third seal assembly 740 may be 35 taller and wider in places compared to the seal 743 of the second seal assembly.

The mask assembly comprising the mask body 30 and the third seal assembly 740 may also include an inner cushion 741. In the illustrated example, the inner cushion 741 is located between the first side 7431 of the seal 743 and clip 742. The inner cushion 741 is received in the channel 767 of the clip 742.

It can be seen from FIG. 12 that incorporating a bridging portion into the clip of a plurality of seal assemblies, each one with a different sized bridging portion, provides for a series of differently sized seal assemblies for use with a common mask body. A series of seal assemblies, each with a bridging portion with an increased outward dimension provides a series of increasing sized seal assemblies for use 50 with a common mask body.

The seal of a seal assembly generally provides a flexible perimeter about the perimeter or periphery of the mask assembly. The seal surrounds an opening to the inside of the mask assembly. A second seal described as being larger than a first seal has a larger perimeter and opening than the first smaller seal. For example, the present invention may comprise a nasal mask package comprising a common mask body and a series of differently sized seal assemblies, each having a perimeter adapted to seal about a user's nose, the user's nose being received in an opening of the seal. Alternatively, the present invention may comprise a full face mask package comprising a common mask body and a series of differently sized seal assemblies, each having a perimeter adapted to seal about a user's nose and mouth, the user's nose and mouth being received in an opening of the seal.

Furthermore, a second seal described as being larger than a first seal not only has a larger perimeter and opening than

the first smaller seal, but preferably also has a deeper seal assembly depth. The depth of a seal assembly is indicated in FIG. 12 by dimensions  $D_1$ ,  $D_2$  and  $D_3$  for the three different sized seals illustrated. As shown, the depth of the seal assemblies increases for increasing seal sizes.

A large range of users can be accommodated by providing three different size mask seals for use with a common body. The three different size seals may conveniently be labeled as small, medium and large. A nasal mask suitable for a range of smaller users may have a seal height from the bridge of the nose to the philtrum area of around 45 mm. A nasal mask suitable for a range of medium sized users may have a seal height from the bridge of the nose to the philtrum area of around 54 mm. According to the present invention, the difference in height between the small seal and the medium seal is accommodated by the outward dimension of the bridging portion of the clip of the medium seal assembly. A nasal mask suitable for a range of larger sized users may have a seal height from the bridge of the nose to the philtrum 20 area of around 58 mm. Similarly, according to the present invention, the difference in height between the small seal and the large seal is accommodated by the outward dimension of the bridging portion of the clip of the large seal assembly, the outward dimension of the bridging portion of 25 the clip of the large seal assembly being greater than the outward dimension of the bridging portion of the clip of the medium seal assembly.

A series of differently sized seal assemblies may comprise a feature or features that are common to more than one seal 30 assembly in the series. For example, a plurality of seal assemblies in a series of seal assemblies may each have the same or a similarly shaped nasal bridge region.

The present invention allows for a range of different types of seals to be used with a common mask body. For example, 35 a common mask body may be used with a nasal seal assembly comprising a clip and seal for sealing around the nose of a user. The same mask body may also be used with a full face seal assembly comprising a clip and a seal for sealing around the nose and mouth of a user.

The seal of each seal assembly is attached to a first side of the seal assembly clip. A second side of the clip attaches to the common mask body. Each seal assembly clip has an identical or at least similar connection portion or second side for attaching to the common mask body. The clip of each 45 seal assembly has a different first side to allow different types of seals to be used with the common mask body. The portion of the clip spanning between the first and second sides of the clip allows a different size or type of seal to be used with the common mask body. For example, the seal and 50 first side of the clip of a full face seal assembly has a longer perimeter length than the seal and first side of the clip of a nasal seal assembly. The difference in perimeter lengths of the first sides of the clips of the full face and nasal seal assemblies is achieved by the clip of the full face seal 55 assembly having bridging portion spanning between the first and second sides of the clip with a larger outward dimension than the clip of the nasal seal assembly. For example, the clip of the nasal seal assembly may have a bridging portion with a smaller outward dimension than the clip of the full face 60 seal assembly, or the clip of the nasal seal assembly may not have a bridging portion, the second side of the seal of the nasal seal assembly not being spaced outwardly from the perimeter of the common mask body.

A range of different types of seals, each with a clip having 65 a different first side allows many different types of seals to be used with a common mask body. For example the

common mask body may be used with a cannula seal assembly, a nasal seal assembly, a mouth seal assembly and a full face assembly.

18

As described above, a sealing assembly according to one embodiment of the present invention comprises a rigid clip having a bridging portion for spacing the second side of the flexible seal in contact with a user's face outwards from the perimeter of the mask body. The flexible seal is attached to a first side of the clip. A second side of the clip attaches to the mask body. The bridging portion of the clip spans between the first and second sides of the clip.

Preferably the seal assembly further comprises a second flexible seal 44 attached to the second side of the clip for forming a seal between the seal assembly 40 and the mask body 30, as shown in FIGS. 10A to 14B. The bridging portion 50 spans between a first seal 43 for forming a seal against a user's face, and a second seal 44 for forming a seal between the seal assembly and the mask body 30.

The first and second seals may be integrally formed, for example in an injection moulding process, the first and second seals integrally formed and joined together via a runner across or through the bridging portion. Alternatively, the first and second seals may be joined by overmoulding the seal material from the first flexible seal to the second flexible seal across the bridging portion as illustrated in FIGS. 15A and 15B. Alternatively, the first and second seals may be separately formed, for example by providing multiple insertion points, a multiple stage moulding process, or by a runner subsequently removed.

Various second seal configurations for sealing between the seal assembly and the mask body are illustrated in FIGS. 14A to 14D. As illustrated in FIG. 14A, the second seal 44 has a bearing surface 51 extending around the perimeter of the clip. The second seal bearing surface 51 faces a corresponding bearing surface 52 on the mask body. The seal bearing surface and the mask bearing surface are in contact when the seal assembly is attached to the mask body in a butting engagement. When the seal assembly 40 is attached to the mask body 30, the second seal 44 at the bearing interface is compressed so that a sealing interface is formed between the seal assembly and the mask body.

Preferably, the clip has a raised ridge 45 running around the inside perimeter of the clip. The second seal 44 is compressed when the clip is attached to the mask body by being squashed between the raised ridge 45 and the mask body bearing surface 52 when the seal assembly 40 is attached to the mask body 30.

To assist with creating a good seal between the seal assembly and the mask body, a continuous rim 53 may be provided on the seal bearing surface 51. The rim provides a small contact area in contact with the mask body bearing surface 52. The small contact area allows a relatively high compression of the rim, and therefore effective seal, for a relatively small seal assembly to mask body engagement force.

The alternative sealing arrangement illustrated in FIG. 14B comprises a seal that slides against a corresponding lateral member of the mask body during engagement of the seal assembly to the mask body. For example, a wall 77 forming a side of a channel 66 in the mask body for receiving the inner cushion as shown in FIG. 11A extends rearward to contact the second seal 44 when the seal assembly 40 is attached to the mask body 30. Preferably the second seal 44 comprises a raised rim 53 on the surface 51 that contacts the lateral member 77. The rim provides a small contact area in contact with the mask body bearing surface 52 in contact with the seal. The small contact area allows a

relatively high compression of the rim, and therefore effective seal, for a relatively small seal assembly to mask body engagement force.

The alternative sealing arrangement illustrated in FIG. 14C comprises a lip 54 that bears against an end of a lateral 5 member of the mask body 30. For example, a wall 77 forming a side of a channel 66 in the mask body for receiving the inner cushion as shown in FIG. 11A extends rearward to contact the lip 54 of the second seal 44 when the seal assembly 40 is attached to the mask body 30.

The alternative sealing arrangement illustrated in FIG. 14D is similar to the arrangement of FIG. 14B but includes two sealing rims 53 in sealing contact with a surface of the mask body.

The present invention has been described with reference 15 to a nasal mask assembly. However, the present invention may equally be applied to other mask assemblies, for example full face masks that cover a user's nose and mouth.

Although certain preferred embodiments and examples have been discussed herein, it will be understood by those 20 skilled in the art that the present invention extends beyond the specifically disclosed embodiments to other alternative embodiments and/or uses of the invention and obvious modifications and equivalents thereof. In addition, while a number of variations of the invention have been shown and 25 described in detail, other modifications, which are within the scope of this invention, will be readily apparent to those of skill in the art based upon this disclosure. It is also contemplated that various combinations or sub-combinations of the specific features and aspects of the embodiments may be 30 made and still fall within the scope of the invention. Accordingly, it should be understood that various features and aspects of the disclosed embodiments can be combined with or substituted for one another in order to form varying modes of the disclosed invention. Thus, it is intended that 35 the scope of the present invention herein disclosed should not be limited by the particular disclosed embodiments described above, but should be determined only by a fair reading of the present disclosure, including the appended claims.

We claim:

- 1. A mask seal assembly for use as part of an apparatus for supplying a flow of respiratory gases to a user, the mask seal assembly comprising:
  - a first seal and a second seal, each of flexible material, and a clip of rigid material,
  - the first seal having a first side and a second side, the first side of the first seal being shaped to approximately match contours of a face of the user and in use 50 substantially seal against the face of the user, the second side attached to said clip.
  - the clip providing an interface extending substantially a full perimeter or periphery of the mask seal assembly, the clip having a first side and a second side, the second 55 side of the first seal being attached to the first side of the clip, and the second side of the clip for releasably attaching the mask seal assembly to a mask body by way of direct engagement with the mask body,
  - the second seal attached to the second side of the clip for 60 forming a seal between the mask seal assembly and the mask body,
  - wherein the clip comprises a bridging portion spanning between the first side and the second side of the clip to space at least a portion of the second side of the first 65 seal outwards from a perimeter or periphery of the second side of the clip,

20

- wherein the first seal and the second seal are integrally formed and joined together across the bridging portion via a runner across or through the bridging portion.
- 2. The mask seal assembly of claim 1, wherein the first seal and the second seal are joined by overmoulding the flexible material of the first seal to the second seal across the bridging portion.
- 3. The mask seal assembly of claim 1, wherein the first seal and the second seal are separately formed by:
  - providing multiple insertion points,
  - a multiple stage moulding process, or
  - a second runner which is subsequently removed.
- **4**. The mask seal assembly of claim **1**, wherein the second seal comprises a lip.
- 5. The mask seal assembly of claim 4, wherein the lip is configured to bear against an end of a lateral member of the mask body.
- **6**. The mask seal assembly of claim **1**, wherein the bridging portion has an outward dimension (D) that is approximately the same around the perimeter or periphery of the mask seal assembly.
- 7. The mask seal assembly of claim 1, wherein the bridging portion has an outward dimension (D) that varies around the perimeter or periphery of the second side of the clip.
- **8**. The mask seal assembly of claim **1**, wherein the bridging portion extends rearward away from a front of the mask body to which the mask seal assembly is configured to be attached to in use and towards the face of the user in use.
- **9**. The mask seal assembly of claim **1**, wherein the mask seal assembly is adapted to releasably attach to a rear perimeter of the mask body defining a hollow space for receiving or covering a nose or a mouth of the user, or both, and having an inlet through which the flow of respiratory gases is provided to an interior of the mask body.
- 10. The mask seal assembly of claim 1, wherein the clip is manufactured from polycarbonate, ABS, nylon, acetyl or other similar rigid plastic, and the first seal is formed from silicone with a Shore-A hardness of less than 60.
- 11. A mask assembly for supplying a flow of respiratory gases to a user, the mask assembly comprising:
- a mask seal assembly according to claim 1, and the mask body.
- 12. The mask assembly of claim 11, wherein the mask body includes an inlet for receiving a flow of gases into the mask assembly.
  - 13. A packaged interface product comprising:
  - a single mask body, and
  - a plurality of mask seal assemblies each of a different size and comprising a connection portion or side configured to attach to the single mask body,
  - wherein at least one of the plurality of mask seal assemblies is as claimed in claim 1.
  - 14. The packaged interface product of claim 13, wherein: two or more of the plurality of mask seal assemblies are as claimed in claim 1, and
  - an outward dimension (D) of the bridging portion of each of the two or more of the plurality of mask seal assemblies are the same in a particular portion of the mask body perimeter or periphery to which the clips are attached.
- **15**. A mask seal assembly for use as part of an apparatus for supplying a flow of respiratory gases to a user, the mask seal assembly comprising:
  - a first seal and a second seal, each of flexible material, and a clip of rigid material,

the first seal having a first side and a second side, the first side of the first seal being shaped to approximately match contours of a face of the user and in use substantially seal against the face of the user, the second side attached to said clip,

21

the clip providing an interface extending substantially a full perimeter or periphery of the mask seal assembly, the clip having a first side and a second side, the second side of the first seal being attached to the first side of the clip, and the second side of the clip for releasably attaching the mask seal assembly to a mask body,

the second seal attached to the second side of the clip for forming a seal between the mask seal assembly and the mask body,

wherein the clip comprises a bridging portion spanning between the first side and the second side of the clip to space at least a portion of the second side of the first seal outwards from a perimeter or periphery of the second side of the clip,

wherein the first seal and the second seal are integrally formed and joined together across the bridging portion via a runner across or through the bridging portion,

wherein the bridging portion spaces the second side of the first seal outwards from the perimeter or periphery of <sup>25</sup> the second side of the clip by at least 10 mm.

16. A packaged interface product comprising:

a single mask body, and

a plurality of mask seal assemblies each of a different size and comprising a connection portion or side configured to attach to the single mask body, wherein at least one of the plurality of mask seal assemblies comprises:

a first seal and a second seal, each of flexible material, and a clip of rigid material,

the first seal having a first side and a second side, the first side of the first seal being shaped to approximately match contours of a face of the user and in use substantially seal against the face of the user, the second side attached to said clip,

the clip providing an interface extending substantially a full perimeter or periphery of the mask seal assembly, the clip having a first side and a second side, the second side of the first seal being attached to the first side of the clip, and the second side of the clip for releasably attaching the mask seal assembly to a mask body, 45

the second seal attached to the second side of the clip for forming a seal between the mask seal assembly and the mask body,

wherein the clip comprises a bridging portion spanning between the first side and the second side of the clip to 50 space at least a portion of the second side of the first seal outwards from a perimeter or periphery of the second side of the clip,

wherein the first seal and the second seal are integrally formed and joined together across the bridging portion 55 via a runner across or through the bridging portion,

wherein the bridging portion and the first seal is one of a series of sizes, each one of the series of sizes suitable for sealing against a differently sized user's face.

22

17. A mask seal assembly for use as part of an apparatus for supplying a flow of respiratory gases to a user, the mask seal assembly comprising:

a clip of rigid material providing an interface extending substantially a full perimeter or periphery of the mask seal assembly, the clip comprising:

a first side:

a second side including a connection portion configured to releasably engage the mask seal assembly to a mask body assembly; and

a bridging portion spanning between the first side and the second side of the clip;

a first seal of flexible material, the first seal having a first side and a second side, the first side of the first seal being shaped to approximately match contours of a face of the user and in use substantially seal against the face of the user, the second side of the first seal being attached to the first side of the clip;

a second seal of flexible material, the second seal attached to the second side of the clip, wherein the first seal and the second seal are integrally formed and joined together across the bridging portion via a runner across or through the bridging portion;

wherein the bridging portion spaces at least a portion of the second side of the first seal outwards from a perimeter or periphery of the second side of the clip.

18. The mask seal assembly of claim 17, wherein the first seal and the second seal are joined by overmoulding the flexible material of the first seal to the second seal across the bridging portion.

19. The mask seal assembly of claim 17, wherein the second seal comprises a lip.

20. The mask seal assembly of claim 19, wherein the lip is configured to bear against an end of a lateral member of the mask body assembly.

21. The mask seal assembly of claim 17, wherein the bridging portion has an outward dimension (D) that varies around the perimeter or periphery of the second side of the clip.

22. The mask seal assembly of claim 17, wherein the bridging portion extends rearward away from a front of the mask body assembly to which the mask seal assembly is configured to be attached to in use and towards the face of the user, in use.

23. The mask seal assembly of claim 17, wherein the mask seal assembly is adapted to releasably attach to a rear perimeter of the mask body assembly defining a hollow space for receiving or covering a nose or a mouth of the user, or both, and having an inlet through which the flow of respiratory gases is provided to an interior of the mask body assembly.

24. The mask seal assembly of claim 17, in combination with the mask body assembly, the mask body assembly comprising an inlet configured to connect with a respiratory gas supply.

**25**. A mask assembly for supplying a flow of respiratory gases to a user, the mask assembly comprising:

the mask seal assembly according to claim 17, and the mask body assembly.

\* \* \* \* \*