

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250265981

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Ting; Chin-Lung et al.

ELECTRONIC DEVICE

Abstract

A display panel and a spliced display are provided. The display panel includes a substrate, a plurality of light-emitting elements, a driving circuit, and an optical sensor. The substrate includes a through hole, and the through hole includes a hole. The plurality of the light-emitting elements are disposed on the substrate. The through hole is located in a region between two of the plurality of the light-emitting elements. The driving circuit is disposed on the substrate and electrically connected to the plurality of the light-emitting elements. The optical sensor is disposed corresponding to the through hole and receives sensing light through the hole. The width W of the hole meets the equation of $H \leq W < D$. H is the depth of the hole, and D is the distance between the two of the plurality of the light-emitting elements.

Inventors: Ting; Chin-Lung (Miaoli County, TW), Chen; Chien-Chih (Miaoli County, TW), Chang; Ti Chung (Miaoli County, TW), Wang; Chih-Chieh (Miaoli County, TW), Li; Jenhung (Miaoli County, TW)

Applicant: Innolux Corporation (Miaoli County, TW)

Family ID: 1000008586673

Assignee: Innolux Corporation (Miaoli County, TW)

Appl. No.: 19/200629

Filed: May 06, 2025

Foreign Application Priority Data

CN

202011504933.6

Dec. 18, 2020

Related U.S. Application Data

parent US continuation 18481250 20231005 parent-grant-document US 12322329 child US 19200629

parent US continuation 17961578 20221007 parent-grant-document US 11817049 child US

18481250

parent US continuation 17308041 20210504 parent-grant-document US 11501701 child US 17961578

us-provisional-application US 63031581 20200529

Publication Classification

Int. Cl.: **G09G3/3208** (20160101); **H10K59/65** (20230101)

U.S. Cl.:

CPC **G09G3/3208** (20130101); G09G2354/00 (20130101); G09G2360/14 (20130101); H10K59/65 (20230201)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION [0001] This application is a continuation application of and claims the priority benefit of U.S. application Ser. No. 18/481,250, filed on Oct. 5, 2023. The prior application Ser. No. 18/481,250 is a continuation application of and claims the priority benefit of U.S. application Ser. No. 17/961,578, filed on Oct. 7, 2022. The prior application Ser. No. 17/961,578 is a continuation application of and claims the priority benefit of U.S. application Ser. No. 17/308,041, filed on May 4, 2021, which claims the priority benefit of U.S. provisional application Ser. No. 63/031,581, filed on May 29, 2020, and China application serial no. 202011504933.6, filed on Dec. 18, 2020. The entirety of each of the above-mentioned patent applications is hereby incorporated by reference herein and made a part of this specification.

BACKGROUND

Technical Field

[0002] The disclosure relates to an electronic device, and particularly, to a display panel and a spliced display.

Description of Related Art

[0003] With the advancement of technology, electronic devices (e.g., display devices) are evolving toward more functions and getting thinner and lighter. Technologies to connect an external camera lens to a display screen are proposed. However, the circuit configuration of the peripheral area of a panel and the user experience of a display device still need to be optimized. Moreover, in large-scale display devices, the external camera lens may not meet the usage requirements. Therefore, the current display device still has room for improvement.

SUMMARY

[0004] The disclosure provides a display panel and a spliced display contributing to improving at least one of shortcomings of an external camera lens.

[0005] According to an embodiment of the disclosure, a display panel includes a substrate, a plurality of light-emitting elements, a driving circuit, and an optical sensor. The substrate includes a through hole, and the through hole includes a hole. The plurality of the light-emitting elements are disposed on the substrate. The through hole is located in a region between two of the plurality of the light-emitting elements. The driving circuit is disposed on the substrate and electrically connected to the plurality of the light-emitting elements. The optical sensor is disposed corresponding to the through hole and receives sensing light through the hole. A width W of the hole meets the equation of $H \leq W < D$. H is a depth of the hole, and D is a distance between the two of the plurality of the light-emitting elements.

[0006] According to an embodiment of the disclosure, a spliced display includes at least one display panel described.

[0007] In order to make the features and advantages of the disclosure comprehensible, embodiments accompanied with drawings are described in detail below.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] The accompanying drawings are included to provide a further understanding of the invention, and are incorporated in and constitute a part of this specification. The drawings illustrate embodiments of the disclosure and, together with the description, serve to explain the principles of the disclosure.

[0009] FIG. 1 is a schematic cross-sectional view of part of a display panel according to some embodiments of the disclosure.

[0010] FIG. 2 to FIG. 5 are various enlarged schematic views of part of the region X in FIG. 1.

[0011] FIG. 6 to FIG. 8 are various schematic top views of the display panel in FIG. 1.

[0012] FIG. 9 is a schematic view of a spliced display according to some embodiments of the disclosure.

[0013] FIG. 10 is a schematic view of another spliced display according to some embodiments of the disclosure.

DESCRIPTION OF THE EMBODIMENTS

[0014] The disclosure will be described in detail with reference to the accompanying drawings. It is noted that for comprehension of the reader and simplicity of the drawings, in the drawings of the disclosure, only a part of the electronic device/the display device is shown, and specific components in the drawings are not necessarily drawn to scale. Moreover, the quantity and the size of each component in the drawings are only schematic and are not intended to limit the scope of the disclosure. For example, for clarity, a relative size, a thickness, and a location of each film layer, region, and/or structure may be reduced or enlarged.

[0015] Throughout the specification and the appended claims of the disclosure, certain terms are used to refer to specific components. Those skilled in the art should understand that electronic device manufacturers may probably use different names to refer to the same components. This specification is not intended to distinguish between components that have the same function but different names. In the following specification and claims, the terms “including” and “having”, etc., are open-ended terms, so they should be interpreted to mean “including but not limited to . . .”.

[0016] Directional terminology mentioned in the specification, such as “top”, “bottom”, “front”, “back”, “left”, “right”, etc., is used with reference to the orientation of the drawings being described. Therefore, the used directional terminology is only intended to illustrate, rather than limit, the disclosure. It should be understood that when an element or layer is referred to as being “on” or “connected to” another element or layer, it can be directly set on said other element or layer or directly connected to said other element or layer, or there is an intervening element or layer between the two (indirect connection). In contrast, when an element is referred to as being “directly on” or “directly connected to” another element or layer, there are no intervening elements or layers between the two.

[0017] The terms such as “about”, “equal”, “same”, “substantially”, or “approximately” are generally interpreted as being within a range of plus or minus 10% of a given value or range, or as being within a range of plus or minus 5%, plus or minus 3%, plus or minus 2%, plus or minus 1%, or plus or minus 0.5% of the given value or range. In addition, the term “a given range is between the first value and the second value” or the term “a given value falls in the range between the first value and the second value”, both mean the given range includes the first value, the second value,

and values between the two values.

[0018] In some embodiments of the disclosure, terms such as “connect” and “interconnect” with respect to bonding and connection, unless specifically defined, may refer to two structures that are in direct contact with each other, or may refer to two structures that are indirectly in contact with each other, wherein there are other structures set between these two structures. In addition, the terms that describe joining and connecting may apply to the case where both structures are movable or both structures are fixed. In addition, the term “electrically connected” or “coupling” involves any direct and indirect electrical connection means.

[0019] In the exemplary embodiments provided herein, the same or similar elements will be given the same or similar reference numerals and their description will be omitted. In addition, the features in the different exemplary embodiments may be combined with each other as long as there is no conflict, and equivalent changes and modifications made according to the specification or claims are still within the scope of this disclosure. Moreover, “first”, “second”, and similar terms mentioned in the specification or the claims are merely used to name the discrete elements or to differentiate among different embodiments or ranges. Therefore, the terms should not be regarded as limiting the upper or lower bound of the number of the components/devices and should not be used to limit the manufacturing sequence or arrangement sequence of components.

[0020] The electronic device in the disclosure may include a display device, an antenna device, a sensing device, a light-emitting device, or a splicing device, but the disclosure is not limited thereto. The electronic device may be a bendable or flexible electronic device. The electronic device may, for example, include light-emitting diodes (LEDs). The light-emitting diodes may include, for example, organic light-emitting diodes (OLEDs), mini LEDs, micro LEDs, or quantum dot light-emitting diodes (including QLEDs and QDLEDs), fluorescence, phosphors, other suitable materials, or a combination thereof, but the disclosure is not limited thereto. A display device is configured as an electronic device to illustrate the content of the disclosure in the following, but the disclosure is not limited thereto.

[0021] The display device of the disclosure may be a self-luminous display device, for example. The self-luminous display device may include a light-emitting diode, a light conversion layer or other suitable materials, or a combination thereof, but the disclosure is not limited thereto. The light-emitting diode may, for example, include organic light-emitting diodes (OLEDs), mini light-emitting diode (mini LEDs), micro LEDs or quantum dot LEDs (including QLEDs and QDLEDs), but the disclosure is not limited thereto. The light conversion layer may include a wavelength conversion material and/or a light filtering material. The light conversion layer may include, for example, fluorescence, phosphors, quantum dots, other suitable materials, or a combination thereof, but the disclosure is not limited thereto. The display panel in the display device will be described with accompanying drawings, and the spliced display will be adapted as the display device to illustrate the content of the disclosure. However, the display device in the disclosure may also be a non-spliced display.

[0022] FIG. 1 is a schematic cross-sectional view of part of a display panel according to some embodiments of the disclosure. FIG. 2 to FIG. 5 are various enlarged schematic views of part of the region X in FIG. 1.

[0023] Referring to FIG. 1 and FIG. 2 first, a display panel **100** is a self-luminous display panel. The self-luminous display panel may include a light-emitting diode display panel, but the disclosure is not limited thereto. The display panel **100** may be a display panel embedded with an image capturing device. For example, one or more image capturing devices may be embedded in the display panel **100**. According to different requirements, while obtaining an image of the subject, the display panel **100** displays the obtained image, but the disclosure is not limited thereto.

[0024] In detail, the display panel **100** includes a substrate **110**, the plurality of the light-emitting elements **120**, a driving circuit **130**, and an optical sensor **140**. The substrate **110** includes a rigid substrate or a flexible substrate and may also include a film-like substrate with flexibility, but the

disclosure is not limited thereto. For example, the substrate **110** may include a printed circuit board, a plastic substrate, a glass substrate, or a composite substrate. For example, composite boards include polyimide (PI) and printed circuit boards, composite boards include polyimide and polyethylene terephthalate (PET), or the like, but the disclosure is not limited thereto. The plurality of the light-emitting elements **120** may include light-emitting diodes. The light-emitting diode, for example, may include organic light-emitting diodes (OLEDs), mini light-emitting diodes (mini LEDs), micro light-emitting diodes (micro LEDs), or quantum dot light-emitting diodes (quantum dot LEDs, including QLEDs and QDLEDs), fluorescence, phosphor, other suitable materials, or a combination thereof, but the disclosure is not limited thereto. The driving circuit **130** may include one or more integrated circuits, but the disclosure is not limited thereto. The optical sensor **140** includes a camera module or a fingerprint recognition module and may also include an infrared camera, a thermal imager, or other image capturing devices providing functions of ranging, position recognition, or identification, but the disclosure is not limited thereto. In some embodiments, the optical sensor **140** may include a charge-coupled device (CCD) or a CMOS image sensor (CIS), such as front side illuminated (FSI) CIS, back side illuminated (BSI) CIS, etc., to receive sensing light, but the disclosure is not limited thereto.

[0025] The substrate **110** has a surface **S1** and another surface **S2** opposite to the surface **S1**. In addition, the substrate **110** includes a through hole **T1**. The through hole **T1** penetrates the surface **S1** and the surface **S2** of the substrate **110**. In other words, the through hole **T1** extends from the surface **S1** to the surface **S2**.

[0026] The plurality of the light-emitting elements **120** are disposed on the substrate **110**, and the plurality of the light-emitting elements **120**, for example, are disposed on the surface **S1** of the substrate **110**. The through hole **T1**, for example, is located in a region **A** between two (e.g., the light-emitting element **120a** and the light-emitting element **120b**) of the plurality of the light-emitting elements.

[0027] The driving circuit **130** is disposed on the substrate **110** and electrically connected to the plurality of the light-emitting elements **120**. The driving circuit **130** controls the plurality of the light-emitting elements **120** to display images. The driving circuit **130** is disposed on the surface **S1** of the substrate **110** or disposed on the surface **S2** of the substrate **110** to reduce its influence on the visual effect, but the disclosure is not limited thereto. In some embodiments, the driving circuit **130** may be disposed on the surface **S1** of the substrate **110**.

[0028] The optical sensor **140** is disposed corresponding to the through hole **T1** and receives sensing light through the through hole **T1**. As shown in FIG. 1 and FIG. 2, for example, the through hole **T1** penetrates the part of the substrate **110** located in the region **A**, and for example the optical sensor **140** is embedded in the through hole **T1** of the substrate **110** to obtain image data of the object to be photographed by receiving sensing light.

[0029] With the optical sensor **140** disposed in the display region (e.g., the region between the light-emitting element **120a** and the light-emitting element **120b**) of the display panel **100**, the space waste and the affected appearance caused by the external camera lens are improved, or technical problems, such as failing to directly look at the screen and the image capturing device at the same time while the users use the image capturing device, are solved.

[0030] Referring to FIG. 2, in the display panel **100**, the through hole **T1** is a composite through hole, but the disclosure is not limited thereto. For example, the through hole **T1** includes a part **T1b** where the optical sensor is disposed and a hole part (a hole **T1a**) of the optical sensor **140** is exposed. The hole **T1a** is connected to the surface **S1** of the substrate **110** and is located between the surface **S1** and the part **T1b** where the optical sensor is disposed. The part **T1b** where the optical sensor is disposed is connected to the surface **S2** of the substrate **110** and is located between the surface **S2** and the hole **T1a**. The optical sensor **140** is disposed in the part **T1b** where the optical sensor is disposed, the hole **T1a** exposes the optical sensor **140**, and the sensing light is transmitted to the optical sensor **140** through the hole **T1a** so that the optical sensor **140** obtains image data of

the object to be photographed. In some embodiments, the part **T1b** where the optical sensor is disposed may be designed according to the size of the optical sensor **140** and may have an aperture greater than that of the hole **T1a**, but the disclosure is not limited thereto.

[0031] In the embodiment of the disclosure, when taking the image capturing effect into consideration, a width W of the hole **T1a** meets the following equation: $H \leq W < D$. For example, the width W of the hole **T1a** refers to the maximum width of the through hole **T1** in a direction parallel to the substrate **110** on the surface (e.g., the surface **S1**) of the substrate **110** where the plurality of the light-emitting elements **120** are disposed. In FIG. 2, for example, the width W of the hole **T1a** is the maximum width in the direction parallel to the substrate **110** on the surface **S1**. H is the depth of the hole **T1a**, for example, the distance from the surface (e.g., surface **S1**) of the substrate **110** where the plurality of the light-emitting elements **120** are disposed to the surface (e.g., an upper surface **S3**) of the optical sensor **140** in a direction perpendicular to the substrate **110**. D is the distance between the light-emitting element **120a** and the light-emitting element **120b**, for example, the minimum distance between the light-emitting element **120a** and the light-emitting element **120b** in the direction parallel to the substrate **110**.

[0032] In some embodiments of the disclosure, the optical sensor **140** may be a camera module. For example, the optical sensor **140** may include a lens **1401** and a housing **1402** to carry the lens **1401**. In some embodiments, if a width B of the housing **1402** of the optical sensor **140** is greater than a distance D between the light-emitting element **120a** and the light-emitting element **120b**, with the design of the composite through hole, at least part of the housing **1402** is embedded in the part **T1b** where the optical sensor is disposed in the substrate **110**. Accordingly, the optical sensor **140** is fixed in the substrate **110** without increasing the distance D . In other embodiments, the optical sensor **140** may also adopt other structural configurations, which is not limited in the disclosure.

[0033] Referring to FIG. 3, in a display panel **100A**, the substrate **110** includes a through hole **T2**. The through hole **T2** includes a part **T2b** where the optical sensor is disposed and a hole part (a hole **T2a**) where the optical sensor **140** is exposed. The through hole **T2** is a single through hole, and the hole **T2a** in the through hole **T2** and the part **T2b** where the optical sensor is disposed have a single aperture. A width B' of part of the housing **1402** of the optical sensor **140** is less than the distance D between the light-emitting element **120a** and the light-emitting element **120b**. Therefore, with the design of a single through hole, the housing **1402** is embedded in the through hole **T2** of the substrate **110**, but the disclosure is not limited thereto. In FIG. 3, the depth of the hole is the distance from the surface **S1** to the upper surface **S3** of the optical sensor **140** (the defined H), and for example, the depth is 0.

[0034] Referring to FIG. 4, in a display panel **100B**, the substrate **110** includes a through hole **T3**. The through hole **T3** includes a part **T3b** where the optical sensor is disposed and a hole part (a hole **T3a**) where the optical sensor **140** is exposed. The through hole **T3** is a single through hole, and the hole **T3a** in the through hole **T3** and the part **T3b** where the optical sensor is disposed have a single aperture. In some embodiments, a larger distance D' exists between the light-emitting element **120a** and the light-emitting element **120b** (e.g., the display panel **100B** has a larger pixel pitch or a lower resolution than that of the display panel **100**), and the distance D' is greater than the width B of the housing **1402** of the optical sensor **140**. Therefore, in the display panel **100B**, the through hole **T3** with a larger aperture is disposed between the light-emitting element **120a** and the light-emitting element **120b**, and with the housing **1402** disposed in the through hole **T3**, the optical sensor **140** is disposed corresponding to the through hole **T3**, but the disclosure is not limited thereto. In FIG. 4, the depth of the hole is the distance from the surface **S1** to the upper surface **S3** of the optical sensor **140** (the defined H), and for example, the depth is 0.

[0035] Referring to FIG. 5, in a display panel **100C**, the optical sensor **140** has a viewing angle θ , where the viewing angle θ may fall within a range of $\pm 10\%$ of $180 - [2 \times \tan.\text{sup.} - 1 (H/D)]$, for example. In other words, a distance H from the surface **S1** to the upper surface **S3** of the optical

sensor **140** and the distance **D** between the light-emitting element **120a** and the light-emitting element **120b** may be designed according to the light collection capability (the viewing angle θ) of the optical sensor **140**.

[0036] FIG. **6** to FIG. **8** are various schematic top views of the display panel in FIG. **1**. Referring to FIG. **6** first, the display panel **100** includes the plurality of the light-emitting elements **120** disposed on the surface **S1** of the substrate **110**. The plurality of the light-emitting elements **120** are disposed in an array in a direction parallel to the substrate **110** (e.g., a first direction **D1** and a second direction **D2**). The second direction **D2** intersects the first direction **D1**, and for example, the second direction **D2** may be perpendicular to the first direction **D1**, but the disclosure is not limited thereto. The first direction **D1** may be a horizontal direction when the users face the display panel **100**. The second direction **D2** may be a vertical direction when the users face the display panel **100**.

[0037] As shown in FIG. **6**, in the display panel **100**, the through hole **T1** is located in a region between two (e.g., the light-emitting element **120a** and the light-emitting element **120b**) of the plurality of the light-emitting elements **120**. For example, the light-emitting element **120a** and the light-emitting element **120b** are adjacent light-emitting elements **120** in a diagonal direction **D3**. The diagonal direction **D3** is a diagonal direction between the first direction **D1** and the second direction **D2**. For example, the through hole **T1** may be located in the region among the four light-emitting elements **120**. Alternatively, the through hole **T1** may be located in the region among six, eight, or more light-emitting elements **120**.

[0038] Referring to FIG. **7**, in a display panel **100D**, a through hole **T4** is located in a region between two (e.g., the light-emitting element **120a** and the light-emitting element **120b**) of the plurality of the light-emitting elements **120**. For example, the light-emitting element **120a** and the light-emitting element **120b** are adjacent light-emitting elements **120** in the horizontal direction (e.g., the first direction **D1**).

[0039] Referring to FIG. **8**, in a display panel **100E**, a through hole **T5** is located in a region between two (e.g., the light-emitting element **120a** and the light-emitting element **120b**) of the plurality of the light-emitting elements **120**. For example, the light-emitting element **120a** and the light-emitting element **120b** are adjacent light-emitting elements **120** in the vertical direction (e.g., the second direction **D2**).

[0040] FIG. **9** is a schematic view of a spliced display according to some embodiments of the disclosure. Referring to FIG. **9**, a spliced display **10A** includes a plurality of display panels **DP**. In some embodiments, some of the plurality of the display panels **DP** in the spliced display **10A** may have driving circuits electrically coupled to one another, so that some of the plurality of the display panels **DP** in the spliced display **10A** cooperatively display the entire or the corresponding images. [0041] As shown in FIG. **9**, the spliced display **10A** may include at least two display panels **100** as shown in FIG. **1**, FIG. **2**, and FIG. **6**. Through the optical sensor **140**, the spliced display **10A** obtains image data of the object to be photographed. The spliced display **10A** may also include the display panel **100A** of FIG. **3**, the display panel **100B** of FIG. **4**, the display panel **100C** of FIG. **5**, the display panel **100D** of FIG. **7**, the display panel **100E** of FIG. **8**, or a combination thereof. The disclosure is not limited thereto.

[0042] The spliced display **10A** may include one optical sensor **140** or multiple optical sensors **140**. The spliced display **10A** may include a plurality of display panels including optical sensors **140**, and may also include a display panel including a plurality of optical sensors **140**. The plurality of the optical sensors **140** may be respectively disposed in different display panels **DP**, or the plurality of the optical sensors **140** may be disposed on one display panel **DP**. The spliced display **10A** may also include a display panel without the optical sensor **140**, which is not limited in the disclosure. The plurality of the optical sensors **140** provides multiple shooting angles and a wider shooting range. For example, the spliced display **10A** may include an optical sensor **140a**, an optical sensor **140b**, and an optical sensor **140c**; and the optical sensor **140a**, the optical sensor **140b**, and the optical sensor **140c** obtain image data in a range **Va**, a range **Vb**, and a range **Vc**, respectively.

Therefore, the optical sensor **140a**, the optical sensor **140b**, and the optical sensor **140c** respectively track and photograph objects to be photographed in different regions.

[0043] FIG. **10** is a schematic view of another spliced display according to some embodiments of the disclosure. Referring to FIG. **10**, a spliced display **10B** is ring-shaped and includes a plurality of display panels DP. The plurality of the display panels DP may include one or more curved display panels, but the disclosure is not limited thereto. FIG. **10** shows the spliced display **10B** disposed inside the ring. However, in other embodiments, the spliced display may also be disposed outside the ring or disposed in other shapes, and this disclosure is not limited thereto. In some embodiments, some of the plurality of the display panels DP in the spliced display **10B** may have driving circuits electrically coupled to one another, so that some of the plurality of the display panels DP of the spliced display **10B** cooperatively display the entire or the corresponding images. [0044] As shown in FIG. **10**, the spliced display **10B** includes at least one display panel **100** as shown in FIG. **1**, FIG. **2**, and FIG. **6**. Through the optical sensor **140**, the spliced display **10B** obtains image data of an object O to be photographed. The spliced display **10B** may also include the display panel **100A** of FIG. **3**, the display panel **100B** of FIG. **4**, the display panel **100C** of FIG. **5**, the display panel **100D** of FIG. **7**, the display panel **100E** of FIG. **8**, or a combination thereof, but the disclosure is not limited thereto.

[0045] The spliced display **10B** may include one optical sensor **140** or a plurality of optical sensors **140**. The spliced display **10B** may include a plurality of display panels including optical sensors **140** or may also include a display panel including a plurality of optical sensors **140**. The plurality of the optical sensors **140** may be respectively disposed in different display panels, or the plurality of the optical sensors **140** may be disposed on one display panel. The spliced display **10B** may also include a display panel without the optical sensor **140**, which is not limited in the disclosure. The plurality of the optical sensors **140** provide multiple shooting angles and a wider shooting range. For example, the plurality of the optical sensors **140** of the spliced display **10B** obtain a three-dimensional image of the object O to be photographed, and it is possible to further combine the obtained three-dimensional image with the display image of the spliced display **10B** to present real time virtual reality images. In some embodiments, a spliced display including an optical sensor may also integrate a signage system with a monitoring system.

[0046] Based on the above, in the embodiments of the disclosure, with an optical sensor disposed in the display region (e.g., the region between two light-emitting elements) of a display panel or that of a spliced display, the space waste and the affected appearance caused by the external camera lens are improved, or technical problems, such as failing to directly look at the screen and the image capturing device at the same time while the users use the image capturing device, are solved, thereby further contributing to optimizing the circuit configuration of the peripheral area of the panel and the user experience.

[0047] It will be apparent to those skilled in the art that various modifications and variations can be made to the structure of the present invention without departing from the scope or spirit of the invention. In view of the foregoing, it is intended that the present invention cover modifications and variations of this invention provided they fall within the scope of the following claims and their equivalents.

[0048] Although the disclosure has been described with reference to the above embodiments and the features, it will be apparent to one of ordinary skill in the art that modifications and changes to the described embodiments may be made without departing from the spirit and the scope of the disclosure. In addition, the protection scope of the disclosure is not limited to the manufacturing processes, machines, manufacturing, material composition, devices, methods, and steps in the specific embodiments of the specification. Any skilled in the art can understand the current or future development processes, machines, manufacturing, material composition, devices, methods, and steps from the content of the disclosure, and as long as the substantially same functions can be implemented in the embodiments described herein or the substantially same results can be

obtained, they can be used according to the disclosure. Therefore, the protection scope of the disclosure includes the above manufacturing processes, machines, manufacturing, material composition, devices, methods, and steps. In addition, each claim constitutes an individual embodiment, and the protection scope of the disclosure also includes the combination of each claim and embodiment. The protection scope of the disclosure shall be defined by the appended claims.

Claims

1. An electronic device, comprising: a layer comprising a first surface, a second surface opposite to the first surface and an opening penetrating from the first surface to the second surface; a first light-emitting element and a second light-emitting element disposed corresponding to the first surface of the layer; and an optical sensor disposed corresponding to the second surface of the layer, wherein in a top view of the electronic device, the opening is overlapped with the optical sensor, and the first light-emitting element, the opening of the layer and the second light-emitting element are arranged in sequence along a first direction, wherein in a cross-sectional view of the electronic device along the first direction, a width of the opening is greater than or equal to a first distance between the first surface and the second surface along a second direction perpendicular to the first direction and less than a second distance between the first light-emitting element and the second light-emitting element.
 2. The electronic device according to claim 1, wherein the first direction is perpendicular to a normal direction of the electronic device.
 3. The electronic device according to claim 2, wherein the second direction is parallel to the normal direction of the electronic device.
 4. The electronic device according to claim 1, wherein the layer comprises plastic materials.
 5. The electronic device according to claim 1, wherein the layer is rigid.
 6. The electronic device according to claim 1, wherein the optical sensor is a camera module.
 7. The electronic device according to claim 1, further comprising: a driving circuit electrically connected to the first light-emitting element.
 8. The electronic device according to claim 7, wherein the driving circuit is disposed between the first surface of the layer and the first light-emitting element.
 9. The electronic device according to claim 1, wherein the optical sensor comprises a housing, and a width of the housing is greater than the second distance between the first light-emitting element and the second light-emitting element.
 10. The electronic device according to claim 1, wherein the first light-emitting element and the second light-emitting element are light-emitting diodes.
 11. The electronic device according to claim 10, wherein the first light-emitting element and the second light-emitting element are organic light-emitting diodes.
 12. The electronic device according to claim 10, further comprising: a light conversion layer disposed on the light-emitting diodes.
 13. The electronic device according to claim 12, wherein the light conversion layer comprises quantum dots.
 14. The electronic device according to claim 1, wherein the optical sensor comprises a lens, and in the cross-sectional view of the electronic device, a width of the lens is greater than the width of the opening.
 15. The electronic device according to claim 1, wherein the optical sensor comprises a lens, and in the cross-sectional view of the electronic device, the width of the opening is greater than a width of the lens.
-