

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication	20250261186
Kind Code	A1
Publication Date	August 14, 2025
Inventor(s)	ROTH-MANDUTZ; Elke et al.

MOBILE DEVICE AND METHOD

Abstract

A mobile device being a member of a communication group and configured to communicate with one or more other members of the communication group and to exchange control information with the one or more other members, wherein the mobile device is configured to create an identification information and to transmit the identification information on a physical layer of the control information, wherein the identification information assigns the communication group.

Inventors: ROTH-MANDUTZ; Elke (Erlangen, DE), SHAWKY HASSAN HUSSEIN; Khaled (Erlangen, DE), BHADAURIA; Shubhangi (Erlangen, DE), LEYH; Martin (Erlangen, DE)

Applicant: Koninklijke Philips N.V. (Eindhoven, NL)

Family ID: 63914776

Appl. No.: 19/097995

Filed: April 02, 2025

Foreign Application Priority Data

EP	18197357.9	Sep. 27, 2018
----	------------	---------------

Related U.S. Application Data

parent US continuation 18531773 20231207 parent-grant-document US 12284642 child US 19097995

parent US continuation 17212725 20210325 parent-grant-document US 11882555 child US 18531773

parent WO continuation PCT/EP2019/075872 20190925 PENDING child US 17212725

Publication Classification

Int. Cl.: H04W72/121 (20230101); H04W4/08 (20090101); H04W72/20 (20230101); H04W72/30 (20230101); H04W76/11 (20180101); H04W92/18 (20090101)

U.S. Cl.:

CPC H04W72/121 (20130101); H04W4/08 (20130101); H04W72/20 (20230101); H04W72/30 (20230101); H04W76/11 (20180201); H04W92/18 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION [0001] This application is a continuation of U.S. patent application Ser. No. 18/531,773, filed on Dec. 7, 2023 which is a continuation of U.S. Pat. No. 11,882,555 filed on Mar. 25, 2021 which is a continuation of International Application No. PCT/EP2019/075872, filed on Sep. 25, 2019, which claims the benefit of EP Patent Application No. EP 18197357.9, filed on Sep. 27, 2018. These applications are hereby incorporated by reference herein.

BACKGROUND OF THE INVENTION

[0002] Embodiments of the present invention refer to a mobile device using an identification information on the physical layer. Further embodiments refer to a method using an identification information on a physical layer and to a computer program. In general, the invention lies on the technical field of mobile communication having focus on groupcast/group ID management.

[0003] Including Rel-15, the LTE based V2X sidelink communication is using broadcast only. Only with Rel-16 (using NR for the sidelink) the advanced use cases in NR such as the vehicle platooning and advanced driving need groupcast based sidelink communication is available [1].

[0004] Current solutions are mostly solved at the application layer in the IEEE 802.11p, which may be neither applicable nor fulfill the latency requirements for 5G V2X use cases in Rel 16 [1].

[0005] The decision of who is the group or platoon head is usually been tackled in DSRC within the application layer by defining Group ID's in the CAM messages. This is one possibility that can be adapted by the NR-V2X that in the application layer a "Group ID" is defined within the CAM and DENM messages. Only the vehicles that can decode this Group ID become a member of the platoon. This solution however, will lead to a higher delay in decoding the messages and may not fit the stringent latency requirements as these are broadcasted every 100 ms [2]. This will also create issues when the platoon member wants to leave the platoon. Then the information will reach only after 100 ms the remaining platoon members until when the platoon dynamics will have changed. Therefore there is a need for an improved approach.

SUMMARY

[0006] An embodiment may have a mobile device being a member of a communication group and configured to communicate with one or more other members of the communication group and to exchange control information with the one or more other members, wherein the mobile device is configured to create an identification information and to transmit the identification information on a physical layer of the control information, wherein the identification information assigns the communication group.

[0007] According to another embodiment, a method for identifying a communication group, the method being performed within a communication group within which a member communicates with one or more other members of the communication group and exchanges control information with one or more other members, may have the step of: creating an identification information and transmitting the identification information on a physical layer of the control information so as to assign the identification information to the communication group.

[0008] According to yet another embodiment, a non-transitory digital storage medium may have a computer program stored thereon to perform the inventive method, when said computer program is run by a computer.

[0009] Embodiments of the present invention provide a mobile device being a member of a communication group. The mobile device is configured to communicate with one or more other members of the communication group (e.g., using a sidelink) and to exchange control information with the one or more other members. The mobile device is configured to create (or to compile) an identification information as well as to transmit (distribute) the identification information on a physical layer of the control information (e.g., on the physical layer in the control channel). The identification information assigns the communication group (e.g., enabling to identify the communication group and/or the individual member within the communication group. Note that the identification information may be adaptive to the application/scenario.

[0010] Embodiments of the present invention are based on the principle that the usage of lower layers for the group ID management, e.g., a physical layer, enables to fulfill the latency constraints. Based on this general idea, low latency variants on how to assign group IDs/group internal IDs, which may be used especially for low latency demanding use cases, are based. This principle can be used for groupcast management, e.g., Rel-16 for V2X using NR.

[0011] According to embodiments of the present invention, the mobile device is a group head of the communication group. The communication group can be a platoon communicating to each other using V2X, wherein the other members of the group are so-called group members. According to a further embodiment, the mobile device may also be a group member, e.g., a group member of a platoon. Here, a so-called decentralized groupcast (all members are equal) approach can be used.

[0012] According to embodiments, the control information uses the SCI format. For example, the identification is inserted into one or more reserved information bits, of the SCI format. According to further embodiments, the identification information is inserted into the control information by scrambling or multiplexing the control information with the identification information (e.g., SCI information with the group ID).

[0013] According to embodiments, the identification information is out of a group comprising a group destination ID, a group source ID, a group destination and a group source ID in combination and a common group ID. According to further embodiments, the identification information is composed of a cell/zone/geographical reference of the group and/or a unique ID of the group within the geographical area.

[0014] According to further embodiments, a so-called radio temporary identification information or network temporary identification information is used as identification information. The radio/network temporary identification information may be dependent on a certain area or geographical reference. According to embodiments, the mobile device may be configured to define the radio/network temporary identification information. According to a further embodiment, a so-called sidelink identification information may be used as identification information. Here, the mobile device may be configured to define the sidelink identification information during a setup phase. According to embodiments, the radio/network temporary identification information or the sidelink identification information may be generated by the mobile device which acts as group head, if the communication group or at least a member of the communication group is out of coverage or in idle mode. This enables—even if network or the base station of the network could not serve the identification information—to have a clearly defined identification. The generation may be based on an application group ID or a PN sequence number. Note that, according to further embodiments, the radio/network temporary identification information or the sidelink communication information may be updated, if the network and/or the tracking area changes.

[0015] According to embodiments, the mobile device or each member of the group may be configured to generate an additional group member identification, e.g., according to the order of the platoon. In this case, the global group member identification may be—according to embodiments—

composed of a network reference, a cell/zone/geographical reference and/or a unique identification of the group within the geographical area and/or a unique identification of each group member within the group.

[0016] Another embodiment provides a method for identifying a communication group. The method can be performed within a communication group within which a member communicates with one or more other members of the communication group (e.g., via sidelink) and exchanges control information with one or more other members. The method comprises the step of creating an identification information and transmitting (distributing) the identification information on a physical layer of the control information (on the physical layer in the control channel) so as to assign the identification information to the communication group (enabling to identify the communication group and/or the individual member within the communication group). Another embodiment provides a computer program for performing this method.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0017] Embodiments of the present invention will be detailed subsequently referring to the appended drawings, in which:

[0018] FIG. **1a** shows a communication device of a communication group to be identified according to a basic embodiment;

[0019] FIG. **1b** shows a method for identifying a communication group according to a basic embodiment;

[0020] FIG. **2a** schematically illustrates the principle of centralized groupcast according to an embodiment; and

[0021] FIG. **2b** schematically illustrates the principle of decentralized groupcast according to another embodiment.

DETAILED DESCRIPTION OF THE INVENTION

[0022] Below, embodiments of the present invention will be subsequently discussed referring to the enclosed figures, wherein identical reference numerals are provided to objects having identical or similar function, so that the description thereof is interchangeable and mutually applicable.

[0023] FIG. **1a** shows a communication device **10g**, which could be, for example, part of a communication group 1 comprising the communication device **10g** as well as one or more further communication devices **10m1** and **10m2**. The communication device **10g** may be the group head of the communication group 1, while the other communication devices **10m1** and **10m2** are group members of the communication group 1.

[0024] In this embodiment, it is assumed that the communication devices **10g**, **10m1** and **10m2** communicate to each other using sidelink communication (cf. **12sl**).

[0025] In the surrounding of the group one base station **5** is illustrated. Since a plurality of groups may be in the surrounding of the base station **5** or since a plurality of groups may be present, it would be beneficial to identify clearly the group. This especially helps the user equipments **10g** to **10m2** to communicate with each other. Therefore, according to an embodiment, the sidelink communication **12sl** includes an ID, e.g., a group ID **11D**. According to advantageous embodiments, the sidelink communication **12sl** comprises at least two parts, namely a control portion **12cp** and a data portion **12dp**. The control information **12cp** and the data portion **12dp** may be arranged within different sub-resource pools (BWP, bandwidth portions) as it is illustrated by the enlarged view of the sidelink **12sl**. It should be noted that the resources used for the sidelink are, for example, assigned by the base station **5** or preconfigured/preassigned resources. A part of the resources can be used for the control information (cf. part **12cp**). It should be noted that it is not required for all embodiments that separate bandwidth portions are available for the control portion

12cp and the data portion **12dp**. Within this sidelink **12sl**, another information is exchanged, namely the ID, one ID of group 1. As it is illustrated within the enlarged view of the sidelink **12sl**, the ID can be part of the control portion **12cp** or can have its own portion. Therefore, the additional portion **12id** carrying the group ID **1ID** is marked within the large view of the sidelink communication. According to embodiments, the ID **1ID** is exchanged between the mobile devices **10g**, **10m1** and **10m2** using a physical layer, advantageously a physical layer of the control channel (cf. **12cp**). Often, but not necessarily, the control information uses the so-called SCI format so that the identification information **1ID** can be inserted into reserved bits. Another variant is to scramble or multiplex the control information **12cp** with the identification information **12ID**. It is beneficial within some embodiments that the identification information is available within a physical layer which reduces the latency.

[0026] As it is illustrated by FIG. **1b**, the mobile device, e.g., the mobile device **10g** as group head, uses the following method for generating and exchanging the identification information **1ID/12ID**. The method **100** comprises the two basic steps **110** and **120**. Within the first step **110**, the identification information **1ID** is created/compiled. After that the identification information **1ID** is transmitted or in general distributed as it is illustrated by the step **120**.

[0027] According to embodiments, there are different approaches for generating **110** the ID **1ID**. For example, the identification information **1ID** may be based application group ID or PN sequence ID. Another variant is that the network reference, a cell/zone/geographical reference or a unique identification of the group within the geographical area or unique identification of each group member within the group may be used for the compilation. Background thereof is that the ID **1ID** may, according to embodiments, not necessarily be the group ID. It can also be (alternatively or additionally) group member identification (additional group member identification which depends on the order of the mobile device/platoon member within the group 1/platoon). Note, advantageously both IDs/communication group ID and individual member ID are included in order to enable identify the communication group and the individual member within the communication group.

[0028] Regarding the step **120**, it should be noted that same is performed, such that the identification information **1ID** is transmitted on a physical layer **12ID** as it has been discussed in context of FIG. **1a**. It should be additionally noted that there are different types of exchanging the control information **12cp** and identification information **12ID**, e.g., unicast, groupcast/multicast or broadcast.

[0029] With regard to above embodiments, it should be noted that although the embodiment of FIG. **1a** has been illustrated as a group 1 being in coverage or being partially in coverage of the base station 5, the discussed principle, especially the method as it has been discussed in context of FIG. **1b** can also be applied to communication scenarios, wherein the group 1 or at least part of the group is out of coverage of the base station 5.

[0030] Below, additional embodiments will be discussed with respect to FIGS. **2a** and **2b**.

[0031] FIG. **2a** shows a centralized group 1' having a group head **10g'** and a plurality of group members **10m1'** to **10mx'**. As it is illustrated, a platoon 1' may consist of platoon head **10g'** and platoon members **10m1'** to **10mx'**. The platoon members **10m1'** to **10mx'** follow the platoon head **10g1'** at a (pre)defined or fixed or adapted distance and with a (pre)defined or fixed or adapted speed. For the following description of the solution, a few groupcast related terms are initially defined:

[0032] The group ID **1ID'** identifies the group 1'. Each group member **10m1'** to **10mx'** as well as the group head **10g'** should advantageously know the group ID **1ID'** of the group(s) 1' it belongs to. One example of the group ID **1ID'** is the platoon ID. Typically, each group consists of one (or usually) multiple group members: group head **10g'/gh**: per group there might be one group head **10g'** taking over some controlling function within the group 1', i.e., using a centralized group management.

[0033] According to other embodiments, a group without group head can also be used as it is illustrated by FIG. 2b. FIG. 2b shows a platoon comprising the group members **10m1'** to **10mx''** which all belong to the same group 1''. Here, within this decentralized group approach, all members **10m1''** to **10mx''** are equal.

[0034] Below, for these platoons, two ideas having three variants of how to improve and accelerate the group ID assignment by using lower layers will be discussed.

[0035] The group ID refers to either of the below: [0036] Group Destination ID [0037] Group Source ID [0038] Group Destination and Source ID (combination of both) [0039] Common Group ID (unique identification)

[0040] Note that sidelink (SL) refers to D2D sidelink, M2M sidelink or V2X sidelink.

[0041] According to embodiments, the ID, e.g., the group ID can be transferred using the sidelink control channel PSCCH, e.g., within the SCI format. Here, changes in the sidelink control channel PSCCH and the SCI format are made to satisfy the latency requirements. According to embodiments, a group ID or, in general, an ID is added in the SCI format 1. There are reserved 32 information bits set to 0 out of which all or some (e.g., 8) bits can be used to define a group ID or in general an ID which could be configured (set by the application layer (first variant)).

[0042] According to another variant (2) providing another/enhanced embodiment it is possible to scramble the SCI information or part of the SCI information with the respective ID, e.g., the group ID.

[0043] Another embodiment provides a third variant: for the group ID/ID a new RNTI is introduced, e.g., called. The “group sidelink (GSL)”-RNTI can be defined during the group setup and is typically unique for a certain area (e.g. within a certain network, cell, or zone, if in coverage).

[0044] According to embodiments, the, e.g., group RNTI or GSL-RNTI, is selected for a network connected group head or group-head and multiple members

[0045] According to embodiments, in an incoverage scenario the RNTI, e.g., group RNTI or GSL-RNTI, and further invited RNTI, e.g., group RNTI or GSL-RNTI, in this document may be mapped to the network identifiers

[0046] According to embodiments, once the GH is out of coverage, a temporary local RNTI, e.g., group RNTI or GSL-RNTI, can be considered until the next in coverage.

[0047] According to embodiments, once the UEs are in coverage again, either this local RNTI, e.g., group RNTI or GSL-RNTI, can be mapped to the network new RNTI or update the group RNTI, e.g., group RNTI or GSL-RNTI, once the RRC is connected.

[0048] Below, an out of coverage (idle mode scenario will be discussed). If the UE is out of coverage or in idle mode (NR2-like) a GSL-RNTI may be generated by the group head (GH) and distributed to the other group members (GMS). For example, this can be a PN sequence number. Alternatively/additionally, the (known) application layer group ID (e.g., as used in CAM or DENM message (is used as a source for the generation of the, e.g., GSL-RNTI.

[0049] According to embodiments, the method may be adapted for the network/tracking area change scenario as it follows:

[0050] If the network and/or the tracking area changes, the GSL-RNTI may be updated by the current group head. The updating may be performed by the group head, the (resent) network controller or by a combination of both (e.g. by the head, while the network controller assists).

[0051] Below, embodiments for the global group (member) ID will be discussed: a unique global group ID within one network uniquely identifies each group and each group member within a network. It may—according to embodiments—be composed of at least of the following information: [0052] 1. Cell/zone/etc. ID: geographical reference of the group [0053] 2. Group ID: unique ID of the group within the geographical area [0054] 3. Group internal ID: unique identification of each GM within the group

[0055] According to embodiments, within each group (same Group ID), each group member is

identified by a group internal ID [0056] For platoons (or any other group, where the position of the GM within the group is important), the group internal ID can represent the the sequence of the vehicle in the platoon. This improves the fast and easy tracking of the vehicles within the platoon, e.g. first, middle, last position of the vehicle within the platoon. [0057] Whenever the position of the vehicle within the platoon changes, the group internal ID may be updated accordingly.

[0058] According to a further embodiment, the group member ID can be composed of one of the following elements: [0059] The group ID and the member unique ID (C-RNTI, V-RNTI, V2X RNTI). [0060] If the network RNTI is not available (especially for out of coverage cases) the group member ID is composed of the group ID (e.g. selected from a PN-sequence generator) plus a unique identifier for each GM.

[0061] Below, some examples will be given:

[0062] One platoon groupcast (group ID x) with 3 group members (3 vehicles following each other) could have the following group member IDs: [0063] GH: group ID (XYZ)+group member internal ID (01)=XYZ01 [0064] 1.sup.st GM: groupcast ID; x, group member internal ID (02)=XYZ02 [0065] 2.sup.nd GM: groupcast ID; x, group member internal ID (03)=XYZ03 [0066] Note: The group member internal IDs could represent the vehicle order in the platoon [0067] The solution is partly described for the platooning use case, which is seen as the most prominent use case for groupcast in V2X. However, the solution is neither limited to platooning nor to V2X, but is applicable to groupcast in 5G groupcast management in general.

[0068] If included in the TS, this invention has to be used to allow V2X groupcast to work in 5G NR.

[0069] Further technical areas are: V2X groupcast to allow efficient low-latency assignment and modification of the group ID and the GM group internal ID.

[0070] Although some aspects have been described in the context of an apparatus, it is clear that these aspects also represent a description of the corresponding method, where a block or device corresponds to a method step or a feature of a method step. Analogously, aspects described in the context of a method step also represent a description of a corresponding block or item or feature of a corresponding apparatus. Some or all of the method steps may be executed by (or using) a hardware apparatus, like for example, a microprocessor, a programmable computer or an electronic circuit. In some embodiments, some one or more of the most important method steps may be executed by such an apparatus.

[0071] Depending on certain implementation requirements, embodiments of the invention can be implemented in hardware or in software. The implementation can be performed using a digital storage medium, for example a floppy disk, a DVD, a Blu-Ray, a CD, a ROM, a PROM, an EPROM, an EEPROM or a FLASH memory, having electronically readable control signals stored thereon, which cooperate (or are capable of cooperating) with a programmable computer system such that the respective method is performed. Therefore, the digital storage medium may be computer readable.

[0072] Some embodiments according to the invention comprise a data carrier having electronically readable control signals, which are capable of cooperating with a programmable computer system, such that one of the methods described herein is performed.

[0073] Generally, embodiments of the present invention can be implemented as a computer program product with a program code, the program code being operative for performing one of the methods when the computer program product runs on a computer. The program code may for example be stored on a machine readable carrier.

[0074] Other embodiments comprise the computer program for performing one of the methods described herein, stored on a machine readable carrier.

[0075] In other words, an embodiment of the inventive method is, therefore, a computer program having a program code for performing one of the methods described herein, when the computer program runs on a computer.

[0076] A further embodiment of the inventive methods is, therefore, a data carrier (or a digital storage medium, or a computer-readable medium) comprising, recorded thereon, the computer program for performing one of the methods described herein. The data carrier, the digital storage medium or the recorded medium are typically tangible and/or non-transitory.

[0077] A further embodiment of the inventive method is, therefore, a data stream or a sequence of signals representing the computer program for performing one of the methods described herein. The data stream or the sequence of signals may for example be configured to be transferred via a data communication connection, for example via the Internet.

[0078] A further embodiment comprises a processing means, for example a computer, or a programmable logic device, configured to or adapted to perform one of the methods described herein.

[0079] A further embodiment comprises a computer having installed thereon the computer program for performing one of the methods described herein.

[0080] A further embodiment according to the invention comprises an apparatus or a system configured to transfer (for example, electronically or optically) a computer program for performing one of the methods described herein to a receiver. The receiver may, for example, be a computer, a mobile device, a memory device or the like. The apparatus or system may, for example, comprise a file server for transferring the computer program to the receiver.

[0081] In some embodiments, a programmable logic device (for example a field programmable gate array) may be used to perform some or all of the functionalities of the methods described herein. In some embodiments, a field programmable gate array may cooperate with a microprocessor in order to perform one of the methods described herein. Generally, the methods are advantageously performed by any hardware apparatus.

[0082] While this invention has been described in terms of several embodiments, there are alterations, permutations, and equivalents which fall within the scope of this invention. It should also be noted that there are many alternative ways of implementing the methods and compositions of the present invention. It is therefore intended that the following appended claims be interpreted as including all such alterations, permutations and equivalents as fall within the true spirit and scope of the present invention.

ABBREVIATIONS

[0083] Abbreviation Meaning [0084] NR New Radio [0085] DSRC Dedicated Short Range Communication [0086] SLR Service Level Requirements [0087] CAM Cooperative Awareness messages [0088] DENM Decentralized Environmental Notification [0089] PSCCH Physical Sidelink Control Channel [0090] SCI Sidelink Control Information [0091] PN Pseudo random Number [0092] ACK/NACK Acknowledgement/Negative Acknowledgement [0093] DMRS Demodulation Reference Signals [0094] S-RSRP Sidelink—Received Signal Strength [0095] GSL Group Sidelink [0096] GH Group head [0097] GM Group member [0098] RNTI Radio Network Temporary ID. Note that dependent on the use case [0099] gNB assisted communication [0100] Network pre-configurations [0101] out of coverage [0102] the Radio Network Temporary ID may have a different name, e.g., group RNTI or GSL-RNTI

REFERENCE LABELS

[0103] Number Details [0104] [1] TR 22.886 [0105] [2] TR 36.885 [0106] [3] TS36.212

Claims

1. A device comprising: a communication circuit, wherein the communication unit circuit comprises at least one receiver and at least one transmitter; a controller circuit; and a data storage circuit, wherein the data storage unit circuit comprises is arranged to store instructions for the processor circuit, wherein the controller circuit is arranged to join the device to a communication group, wherein the controller circuit is arranged to communicate with at least one other members of

- the communication group; wherein the device is has application identifier, wherein the application identifier is associated with a geographical area; wherein the controller circuit is arranged to create an identification information using the application identifier or pseudo number sequence, wherein the identification information is a destination address, wherein the controller circuit is arranged to transmit the identification information on a physical layer of control information.
2. The device according to claim 1, wherein the device is a group head of the communication group.
 3. The device according to claim 1, wherein the control information uses the SCI format.
 4. The device according to claim 1, wherein the control information uses the SCI format, wherein the identification is inserted into at least one of a plurality of reserved information bits.
 5. The device according to claim 1, wherein the identification information is inserted into the control information by scrambling or multiplexing the control information with the identification information.
 6. The device according to claim 1, wherein the identification information is selected from the group consisting of a group destination ID, a group source ID, a group destination, a group source ID in combination and a common group ID.
 7. The device according to claim 1, wherein the identification information comprises a cell/zone/geographical reference of the group and/or a unique ID of the group within the geographical area.
 8. The device according to claim 1, wherein a radio/network temporary identification information is used as identification information.
 9. The device according to claim 1, wherein a radio/network temporary identification information is used as identification information, wherein the radio/network temporary identification information is dependent on a certain area or geographical reference.
 10. The device according to claim 1, wherein a sidelink identification information is used as identification information.
 11. The mobile device according to claim 8, wherein the controller circuit is arranged to define the radio/network temporary identification information or the sidelink identification information during a setup phase.
 12. The device according to claim 8, wherein the controller circuit is arranged to generate the radio/network temporary identification information or sidelink identification if the communication group or at least a member of the communication group is out of coverage or in idle mode.
 13. The device according to claim 8, wherein the controller circuit is arranged to generate the radio/network temporary identification information or the sidelink identification information based on an application group ID or a PN sequence number.
 14. The device according to claim 8, wherein the radio/network temporary identification information or the sidelink communication information is updated, if the network and/or the tracking area changes.
 15. The device according to claim 1, wherein each member if the communication group is arranged to generate an additional group member identification.
 16. The device according to claim 15, wherein the global group member identification comprises a network reference, a cell/zone/geographical reference and/or a unique identification of the group within the geographical area and/or a unique identification of each group member within the group.
 17. A method comprising: joining a communication group; communicating with at least one other members of the communication group; storing an application identifier, wherein the application identifier is associated to a geographical area; creating an identification information using the application identifier or pseudo number sequence, wherein the identification information is a destination address; and transmitting the identification information on a physical layer of control information.
 18. A non-transitory computer-readable medium storing a computer program, wherein the computer

program when executed on a processor performs the method as claimed in claim 17.

19. The method according to claim 17, wherein the control information uses the SCI format.

20. The method according to claim 17, wherein the control information uses the SCI format, wherein the identification is inserted into at least one of a plurality of reserved information bits.

21. The method according to claim 17, wherein the identification information is inserted into the control information by scrambling or multiplexing the control information with the identification information.

22. The method according to claim 17, wherein the identification information is selected from the group consisting of a group destination ID, a group source ID, a group destination, a group source ID in combination and a common group ID.

23. The method according to claim 17, wherein the identification information comprises a cell/zone/geographical reference of the group and/or a unique ID of the group within the geographical area.

24. The method according to claim 17, wherein a radio/network temporary identification information is used as identification information.

25. The method according to claim 17, wherein a radio/network temporary identification information is used as identification information, wherein the radio/network temporary identification information is dependent on a certain area or geographical reference.

26. The method according to claim 17, wherein a sidelink identification information is used as identification information.

27. The method according to claim 24, further comprising defining the radio/network temporary identification information or the sidelink identification information during a setup phase.

28. The method according to claim 24, further comprising generating the radio/network temporary identification information or sidelink identification if the communication group or at least a member of the communication group is out of coverage or in idle mode.

29. The method according to claim 24, further comprising generating the radio/network temporary identification information or the sidelink identification information based on an application group ID or a PN sequence number.

30. The method according to claim 24, wherein the radio/network temporary identification information or the sidelink communication information is updated, if the network and/or the tracking area changes.

31. The method according to claim 17, wherein each member of the communication group is arranged to generate an additional group member identification.

32. The method according to claim 12, wherein the global group member identification comprises a network reference, a cell/zone/geographical reference and/or a unique identification of the group within the geographical area and/or a unique identification of each group member within the group.
