

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250262621

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

BUSE; David et al.

FLUID CONTAINER

Abstract

A container comprises a top wall and a fluid vessel depending from a top wall aperture formed in the top wall to a bottom end of the fluid vessel. A first wall segment depends from a first perimeter segment of the top wall and extends from the first perimeter segment to a bottom edge of the first wall segment and at least partially surrounds the fluid vessel. At least a portion of the bottom edge of the first wall segment is disposed below the bottom end of the fluid vessel and includes an alignment notch extending upwardly from the bottom edge of the first wall segment. A top wall fluid retainer barrier projects above a top surface of the top wall and extends continuously around the top wall aperture and is spaced from a perimeter of the top wall aperture.

Inventors: BUSE; David (San Diego, CA), KNIGHT; Byron J. (San Diego, CA)

Applicant: GEN-PROBE INCORPORATED (San Diego, CA)

Family ID: 1000008574964

Assignee: GEN-PROBE INCORPORATED (San Diego, CA)

Appl. No.: 19/068286

Filed: March 03, 2025

Related U.S. Application Data

parent US continuation 18470927 20230920 parent-grant-document US 12239989 child US 19068286

parent US continuation 17210040 20210323 parent-grant-document US 11794189 child US 18470927

us-provisional-application US 62994552 20200325

Publication Classification

Int. Cl.: B01L3/00 (20060101); **B65D51/00** (20060101)

U.S. Cl.:

CPC B01L3/523 (20130101); **B65D51/002** (20130101); B01L2200/16 (20130101);
B01L2300/044 (20130101); B01L2300/0858 (20130101); B01L2300/123 (20130101)

Background/Summary

CROSS-REFERENCE OF RELATED APPLICATION [0001] This application is a continuation of U.S. application Ser. No. 18/470,927, filed Sep. 20, 2023, which is continuation of U.S. application Ser. No. 17/210,040, filed Mar. 23, 2021, now U.S. Pat. No. 11,794,189, which claims the benefit under 35 U.S.C. § 119(e) of the filing date of U.S. Provisional Patent Application No. 62/994,552 filed Mar. 25, 2020, the disclosure of which is incorporated herein by reference.

FIELD OF THE DISCLOSURE

[0002] This disclosure relates to a fluid container for use in automated processing instruments.

BACKGROUND

[0003] Automated processing instruments, such as analyzers for performing chemical and/or biological tests or assays, employ fluid containers that are automatically manipulated—e.g., grasped and/or moved from one location in the instrument to another by a robotic transfer device. To ensure secure and precise manipulation of the fluid container by the robotic transfer device, the container should be securely and repeatably graspable by the robotic transfer device.

[0004] In addition, fluids may be removed from and/or dispensed into the fluid container by a robotic fluid transfer device, such as a robotic pipettor that inserts a hollow probe into an opening of the container to dispense and/or remove fluid. Minimizing fluid spillage within the instrument is important for maintaining instrument cleanliness and to avoid cross-contamination. Robotic fluid transfer mechanisms, such as pipettors, maybe a source of fluid dripping within the instrument as fluid adhere to the outer surface of a pipettor probe may drip from the probe and onto an unintended surface within the instrument.

[0005] Thus, features of a container that help reduce the amount of fluid adhered to the exterior of the fluid probe may help reduce spills within the instrument.

SUMMARY

[0006] The following presents a simplified summary in order to provide a basic understanding of some aspects described herein. This summary is not an extensive overview of the claimed subject matter. It is intended to neither identify key or critical elements of the claimed subject matter nor delineate the scope thereof. Its sole purpose is to present some concepts in a simplified form as a prelude to the more detailed description that is presented later.

[0007] Aspects of the disclosure are embodied in a container that includes a base and a lid disposed on a top end of the base. The base includes a top wall and a fluid vessel depending from the top wall and extending from a top wall aperture formed in the top wall to a bottom end of the fluid vessel. A first wall segment is oriented transversely to the top wall and depends from a first perimeter segment of the top wall, and a second wall segment is oriented transversely to the top wall and depends from a second perimeter segment of the top wall. The first wall segment extends from the first perimeter segment of the top wall to a bottom edge of the first wall segment and at least partially surrounds the fluid vessel, and at least a portion of the bottom edge of the first wall segment is disposed below the bottom end of the fluid vessel. The second wall segment extends from the second perimeter segment of the top wall to a bottom edge of the second wall segment.

[0008] The base may further include an alignment notch formed in the first wall segment and

extending upwardly from the bottom edge of the first wall segment.

[0009] The base may further include grooves formed on opposed sides of the base, and each groove is defined by opposed, exteriorly-convex surfaces converging towards a root of the groove. One of the opposed, exteriorly-convex surfaces of each groove includes part of the first wall segment, and the other of the opposed, exteriorly-convex surfaces of each groove includes part of the second wall segment. The root of each groove separates the first wall segment and the second wall segment.

[0010] The base may further include a first fluid retainer barrier projecting above a top surface of the top wall. The fluid retainer barrier extends continuously around the top wall aperture and is spaced from the perimeter of the top wall aperture.

[0011] The base may further include a plurality of alternating merlons and crenels disposed on the top surface of the top wall and surrounding the top wall aperture within the space between the first fluid retainer barrier and a perimeter of the top wall aperture.

[0012] The base may further include connecting posts projecting above the top surface of the top wall. Each connecting posts is disposed on an opposed side of the top wall aperture. Each post may be disposed on one of the plurality of merlons within the space between the first fluid retainer barrier and the perimeter of the top wall aperture.

[0013] The lid includes a cover wall disposed at a spaced-apart position above the top wall of the base. The cover wall has formed therein a lid aperture generally aligned with the top wall aperture of the base. The lid further includes a perimeter wall that is oriented transversely to the cover wall and depends from a perimeter of the cover wall. The perimeter wall surrounds the first fluid retainer barrier of the base, and at least a portion of the perimeter wall is coplanar with a first portion of the first wall segment of the base, and a second portion of the perimeter wall is coplanar with at least a portion of the second wall segment of the base.

[0014] The lid may further include a second fluid retainer barrier projecting above a top surface of the cover wall. The second fluid retainer barrier extends continuously around the lid aperture and is spaced from a perimeter of the lid aperture.

[0015] The lid may further include a lid wall projecting below a bottom surface of the cover wall. The lid wall is oriented transversely to the bottom surface of the cover wall and extends continuously around the lid aperture and is spaced from the perimeter of the lid aperture. The lid wall may be configured to have a conforming fit within an interior surface of the first fluid retainer barrier of the base.

[0016] The lid may further include a plurality of alternating merlons and crenels forming a free edge of the lid wall. Each of the plurality of alternating merlons and crenels of the lid wall of the lid may be disposed in opposed alignment with an associated one of the alternating merlons and crenels of the top wall of the base.

[0017] A merlon of the lid wall on each of two opposed sides of the lid aperture may define a post capture pocket, where the post capture pocket includes a curved first segment, a second segment connected to a first end of the first segment and extending transversely from a concave side of the first segment, and a third segment connected to a second end of the first segment and extending transversely from the concave side of the first segment. The second and third segments are arranged with converging orientations, and each post capture pocket is configured to receive one of the connecting posts between the respective first, second, and third segments thereof.

[0018] The lid may further include an annular relief formed on the bottom surface of the cover wall. The annular relief has an inner edge that is coextensive with the perimeter of the lid aperture.

[0019] The container may further include an elastomeric septum disposed within the first fluid retainer barrier of the base and overlying the top wall aperture and the plurality of alternating merlons and crenels of the top wall. The septum is at least partially retained by means of the connecting posts extending through holes formed through the septum and aligned with the posts. A perimeter of the septum is sandwiched between merlons of the base and opposed, associated merlons of the lid wall. The septum may include a plurality of slits formed through a portion of the

septum between the lid aperture and the top wall aperture and configured to permit a pipette tip to pass through the septum and into the fluid vessel of the base.

[0020] Further aspects of the disclosure are embodied in a container that includes a top wall of a fluid vessel depending from the top wall and extending from a top wall aperture formed in the top wall to a bottom end of the fluid vessel, a first wall segment depending from a first perimeter segment of the top wall, a second wall segment depending from a second perimeter segment of the top wall, and grooves formed on opposed sides of the container. The first wall segment extends from the first perimeter segment of the top wall to a bottom edge of the first wall segment and at least partially surrounds the fluid vessel, and at least a portion of the bottom edge of the first wall segment is disposed below the bottom end of the fluid vessel. The second wall segment extends from the second perimeter segment of the top wall to a bottom edge of the second wall segment. Each groove is defined by opposed, exteriorly-convex surfaces converging towards a root of the groove. One of the opposed, exteriorly-convex surfaces of each groove includes part of the first wall segment and the other of the opposed, exteriorly-convex surfaces of each groove includes part of the second wall segment, and the root of each groove separates the first wall segment and the second wall segment.

[0021] According to other aspects of the disclosure, the first wall segment is oriented transversely to the top wall, and the second wall segment is oriented transversely to the top wall.

[0022] According to other aspects of the disclosure, the first wall segment includes an alignment notch formed in the first wall segment and extending upwardly from the bottom edge of the first wall segment.

[0023] According to other aspects of the disclosure, the base further includes a machine-readable label disposed on the second wall segment.

[0024] According to other aspects of the disclosure, the first wall segment has a uniform height from the first perimeter segment of the top wall to the bottom edge of the first wall segment.

[0025] According to other aspects of the disclosure, the second wall segment has a uniform height from the second perimeter segment of the top wall to the bottom edge of the second wall segment, and the height of the second wall segment is equal to the height of the first wall segment.

[0026] According to other aspects of the disclosure, the grooves extend from the top wall to the bottom edges of the first wall segment and the second wall segment.

[0027] According to other aspects of the disclosure, the base further includes a top wall fluid retainer barrier projecting above a top surface of the top wall, and the top wall fluid retainer barrier extends continuously around the top wall aperture and is spaced from a perimeter of the top wall aperture.

[0028] According to other aspects of the disclosure, the base further includes a plurality of alternating merlons and crenels disposed on the top surface of the top wall and surrounding the top wall aperture within the space between the top wall fluid retainer barrier and the perimeter of the top wall aperture.

[0029] According to other aspects of the disclosure, the base further includes connecting posts projecting above the top surface of the top wall, and each of the connecting posts is disposed on an opposed side of the top wall aperture and is disposed within the space between the top wall fluid retainer barrier and the perimeter of the top wall aperture.

[0030] According to other aspects of the disclosure, the container further includes a lid, and the lid includes a cover wall disposed at a spaced-apart position above the top wall of the base and having formed therein a lid aperture generally aligned with the top wall aperture and a perimeter wall depending from a perimeter of the cover wall.

[0031] According to other aspects of the disclosure, the perimeter wall is oriented transversely to the cover wall.

[0032] According to other aspects of the disclosure, at least a portion of the perimeter wall is coplanar with at a first portion of the first wall segment and a second portion of the perimeter wall

is coplanar with at least a portion of the second wall segment.

[0033] According to other aspects of the disclosure, the lid further includes a cover wall fluid retainer barrier projecting above a top surface of the cover wall, where the cover wall fluid retainer barrier extends continuously around the lid aperture and is spaced from the perimeter of the lid aperture.

[0034] According to other aspects of the disclosure, the lid further includes a lid wall projecting below a bottom surface of the cover wall, and the lid wall extends continuously around the lid aperture and is spaced from a perimeter of the lid aperture.

[0035] According to other aspects of the disclosure, the lid wall is oriented transversely to the bottom surface of the cover wall.

[0036] According to other aspects of the disclosure, the lid wall includes a plurality of alternating merlons and crenels forming a free edge of the lid wall.

[0037] According to other aspects of the disclosure, the lid further includes an annular relief formed on the bottom surface of the cover wall and having an inner edge that is coextensive with the perimeter of the lid aperture.

[0038] According to other aspects of the disclosure, the container further includes an elastomeric septum disposed within the top wall fluid retainer barrier and overlying the top wall aperture. The septum is at least partially retained by the connecting posts extending through holes formed through the septum and aligned with the posts, and the septum may include a plurality of slits formed through a portion of the septum overlying the top wall aperture and configured to permit a pipette tip to pass through the septum and into the fluid vessel.

[0039] According to other aspects of the disclosure, the perimeter wall surrounds the top wall fluid retainer barrier.

[0040] According to other aspects of the disclosure, the lid wall is configured to have a conforming fit within an interior surface of the top wall fluid retainer barrier.

[0041] According to other aspects of the disclosure, the container is made of plastic.

[0042] According to other aspects of the disclosure, the container is at least partially translucent.

[0043] According to other aspects of the disclosure, the fluid vessel contains a reagent for performing a molecular assay.

[0044] Further aspects of the disclosure are embodied in a container that includes a top wall, a fluid vessel depending from the top wall and extending from a top wall aperture formed in the top wall to a bottom end of the fluid vessel, a first wall segment depending from a first perimeter segment of the top wall, and a top wall fluid retainer barrier projecting above a top surface of the top wall. The first wall segment extends from the first perimeter segment of the top wall to a bottom edge of the first wall segment and at least partially surrounds the fluid vessel, and at least a portion of the bottom edge of the first wall segment is disposed below the bottom end of the fluid vessel. The container may further include an alignment notch formed in the first wall segment and extending upwardly from the bottom edge of the first wall segment. The top wall fluid retainer barrier extends continuously around the top wall aperture and is spaced from a perimeter of the top wall aperture.

[0045] According to other aspects of the disclosure, the container further includes a second wall segment depending from a second perimeter segment of the top wall, and the second wall segment extends from the second perimeter segment of the top wall to a bottom edge of the second wall segment.

[0046] According to other aspects of the disclosure, each of the first and second wall segments is oriented transversely to the top wall.

[0047] According to other aspects of the disclosure, the container further includes grooves formed on opposed sides of the container. Each groove defined by opposed, exteriorly-convex surfaces converging towards a root of the groove. One of the opposed, exteriorly-convex surfaces of each groove includes part of the first wall segment and the other of the opposed, exteriorly-convex surfaces of each groove includes part of the second wall segment, and the root of each groove

separates the first wall segment and the second wall segment.

[0048] According to other aspects of the disclosure, the container further includes a lid, and the lid includes a cover wall disposed at a spaced-apart position above the top wall and having formed therein a lid aperture generally aligned with the top wall aperture, and a perimeter wall depending from a perimeter of the cover wall. At least a first portion of the perimeter wall is coplanar with at least a portion of the first wall segment.

[0049] According to other aspects of the disclosure, the container further includes connecting posts projecting above the top surface of the top wall. Each of the connecting posts is disposed on an opposed side of the top wall aperture and is disposed within the space between the top wall fluid retainer barrier and the perimeter of the top wall aperture, and the septum is at least partially retained by the connecting posts extending through holes formed through the septum and aligned with the posts.

[0050] According to other aspects of the disclosure, the container further includes a lid that includes a cover wall disposed at a spaced-apart position above the top wall and having formed therein an aperture generally aligned with the top wall aperture and a perimeter wall depending from a perimeter of the cover wall. The perimeter wall surrounds the top wall fluid retainer barrier.

[0051] According to other aspects of the disclosure, the container further includes a lid wall projecting below a bottom surface of the cover wall. The lid wall extends continuously around the lid aperture and is spaced from the perimeter of the lid aperture and is configured to have a conforming fit within an interior surface of the top wall fluid retainer barrier.

[0052] Further aspects of the disclosure are embodied in a container that includes a base and a lid disposed on a top end of the base. The base includes a top wall, a fluid vessel depending from the top wall and extending from a top wall aperture formed in the top wall to a bottom end of the fluid vessel, and a first fluid retainer barrier projecting above a top surface of the top wall. The first fluid retainer barrier extends continuously around the top wall aperture and is spaced from a perimeter of the top wall aperture. The lid includes a cover wall disposed at a spaced-apart position above the top wall of the base and having formed therein a lid aperture generally aligned with the top wall aperture of the base and a lid wall projecting below a bottom surface of the cover wall. The lid wall extends continuously around the lid aperture and is spaced from a perimeter of the lid aperture, and where the lid wall is configured to have a conforming fit within an interior surface of the first fluid retainer barrier of the base.

[0053] Further aspects of the disclosure are embodied in a container that includes a top wall, a fluid vessel depending from the top wall and extending from a top wall aperture formed in the top wall to a bottom end of the fluid vessel, a first wall segment depending from a first perimeter segment of the top wall, and a second wall segment depending from a second perimeter segment of the top wall. The first wall segment extends from the first perimeter segment of the top wall to a bottom edge of the first wall segment and at least partially surrounds the fluid vessel, and at least a portion of the bottom edge of the first wall segment is disposed below the bottom end of the fluid vessel. The second wall segment extends from the second perimeter segment of the top wall to a bottom edge of the second wall segment. Grooves are formed on opposed sides of the base, and each groove is defined by opposed, exteriorly-convex surfaces converging towards a root of the groove. One of the opposed, exteriorly-convex surfaces of each groove includes part of the first wall segment, and the other of the opposed, exteriorly-convex surfaces of each groove includes part of the second wall segment, and the root of each groove separates the first wall segment and the second wall segment. A first fluid retainer barrier projects above a top surface of the top wall. The first fluid retainer barrier extends continuously around the top wall aperture and is spaced from the perimeter of the top wall aperture. A plurality of alternating merlons and crenels are disposed on the top surface of the top wall and surround the top wall aperture within the space between the first fluid retainer barrier and a perimeter of the top wall aperture. Connecting posts project above the top surface of the top wall, and each of the connecting posts is disposed on an opposed side of the

top wall aperture and is disposed on one of the plurality of merlons within the space between the first fluid retainer barrier and the perimeter of the top wall aperture. An elastomeric septum is disposed within the first fluid retainer barrier and overlies the top wall aperture and the plurality of alternating merlons and crenels of the top wall. The septum is at least partially retained by the connecting posts extending through holes formed through the septum and aligned with the posts, and a perimeter of the septum is sandwiched between merlons of the base and opposed, associated merlons of the lid wall. The septum includes a plurality of slits formed through a portion of the septum overlying the top wall aperture and configured to permit a pipette tip to pass through the septum and into the fluid vessel.

[0054] Further aspects of the disclosure are embodied in a container that includes a base and a lid disposed on a top end of the base. The base includes a top wall, a fluid vessel depending from the top wall and extending from a top wall aperture formed in the top wall to a bottom end of the fluid vessel, a first fluid retainer barrier projecting above a top surface of the top wall, and connecting posts projecting above the top surface of the top wall. The first fluid retainer barrier extends continuously around the top wall aperture and is spaced from a perimeter of the top wall aperture. Each of the connecting posts is disposed on an opposed side of the top wall aperture and is disposed within the space between the first fluid retainer barrier and the perimeter of the top wall aperture. The lid includes a cover wall disposed at a spaced-apart position above the top wall of the base and having formed therein a lid aperture generally aligned with the top wall aperture of the base. The lid further includes perimeter wall depending from the perimeter of the cover wall, where the perimeter wall surrounds the first fluid retainer barrier of the base, a lid wall projecting below a bottom surface of the cover wall, where the lid wall extends continuously around the lid aperture, and post capture pockets secured to the bottom surface of the cover wall, where each connecting post of the base is inserted into one of the post capture pockets. An elastomeric septum is disposed within the first fluid retainer barrier and overlies the top wall aperture. The septum is at least partially retained by the connecting posts extending through holes formed through the septum and into the post capture pockets.

[0055] Further aspects of the disclosure are embodied in a container that includes a base and a lid disposed on a top end of the base. The base includes a top wall and a fluid vessel depending from the top wall and extending from a top wall aperture formed in the top wall to a bottom end of the fluid vessel. The lid includes a cover wall disposed at a spaced-apart position above the top wall of the base and having formed therein a lid aperture generally aligned with the top wall aperture of the base and a lid wall projecting below a bottom surface of the cover wall. The lid wall extends continuously around the lid aperture and is spaced from a perimeter of the lid aperture. A septum overlies the top wall with a portion of the septum disposed between the lid aperture and the top wall aperture and is configured to permit a pipette tip to pass through the septum and into the fluid vessel. A fluid retainer/return structure is configured to prevent fluid deposited on the septum from dripping off the container and to allow at least a portion of the fluid deposited on the septum to run off the septum and into the fluid vessel.

[0056] According to other aspects of the disclosure, lid further includes a perimeter wall depending from a perimeter of the cover wall.

[0057] According to other aspects of the disclosure, the perimeter wall of the lid is oriented transversely to the cover wall.

[0058] According to other aspects of the disclosure, the fluid retainer/return structure includes a top wall fluid retainer barrier projecting above a top surface of the top wall, extending continuously around the top wall aperture, and spaced from a perimeter of the top wall aperture.

[0059] A plurality of alternating merlons and crenels are disposed on the top surface of the top wall and surround the top wall aperture within the space between the top wall fluid retainer barrier and the perimeter of the top wall aperture. A cover wall fluid retainer barrier projects above a top surface of the cover wall, extending continuously around the lid aperture and spaced from the

perimeter of the lid aperture. A lid wall projects below a bottom surface of the cover wall, extending continuously around the lid aperture and spaced from the perimeter of the lid aperture. A plurality of alternating merlons and crenels form a free edge of the lid wall. Each of the plurality of alternating merlons and crenels of the lid wall is disposed in opposed alignment with an associated one of the alternating merlons and crenels of the top wall.

[0060] Further aspects of the disclosure are embodied in a container that includes a top wall, a fluid vessel depending from the top wall and extending from a top wall aperture formed in the top wall to a bottom end of the fluid vessel, and gripping structures. The gripping structures are configured to enable an automated gripping mechanism to securely grip the container in a repeatable position and orientation with respect to container-gripping components of the gripping mechanism.

[0061] According to other aspects of the disclosure, the container further includes a first wall segment depending from a first perimeter segment of the top wall and a second wall segment depending from a second perimeter segment of the top wall. The first wall segment extends from the first perimeter segment of the top wall to a bottom edge of the first wall segment and at least partially surrounds the fluid vessel, and at least a portion of the bottom edge of the first wall segment is disposed below the bottom end of the fluid vessel. The second wall segment extends from the second perimeter segment of the top wall to a bottom edge of the second wall segment. The gripping structures include grooves formed on opposed sides of the container. Each groove is defined by opposed, exteriorly-convex surfaces converging towards a root of the groove. One of the opposed, exteriorly-convex surfaces of each groove includes part of the first wall segment, and the other of the opposed, exteriorly-convex surfaces of each groove includes part of the second wall segment. The root of each groove separates the first wall segment and the second wall segment.

[0062] Other features and characteristics of the subject matter of this disclosure, as well as the methods of operation, functions of related elements of structure and the combination of parts, and economies of manufacture, will become more apparent upon consideration of the following description and the appended claims with reference to the accompanying drawings, all of which form a part of this specification, where like reference numerals designate corresponding parts in the various figures.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0063] The accompanying drawings, which are incorporated herein and form part of the specification, illustrate various embodiments of the subject matter of this disclosure. In the drawings, like reference numbers indicate identical or functionally similar elements.

[0064] FIG. 1 is a top, front perspective view of a container as described herein.

[0065] FIG. 2 is a top, rear perspective view of the container.

[0066] FIG. 3 is an inverted, perspective view of the container.

[0067] FIG. 4 is an exploded, top, front perspective view of the container.

[0068] FIG. 5 is a top plan view of the container with a lid omitted.

[0069] FIG. 6 is a top plan view of the container, including the lid.

[0070] FIG. 7 is an inverted, perspective view of the lid of the container.

[0071] FIG. 8 is a transverse cross-section of the container along the line 8-8 in FIG. 2.

[0072] FIG. 9 is a transverse cross-section of the container along the line 9-9 in FIG. 1.

[0073] FIG. 10 is an enlarged, partial view of the cross-section shown in FIG. 8.

[0074] FIG. 11 is an enlarged, partial view of the cross-section shown in FIG. 9.

[0075] FIG. 12 is a perspective view of a container held within the tongs of a container-gripping mechanism.

DETAILED DESCRIPTION

[0076] While aspects of the subject matter of the present disclosure may be embodied in a variety of forms, the following description and accompanying drawings are merely intended to disclose some of these forms as specific examples of the subject matter. Accordingly, the subject matter of this disclosure is not intended to be limited to the forms or embodiments so described and illustrated.

[0077] Unless defined otherwise, all terms of art, notations and other technical terms or terminology used herein have the same meaning as is commonly understood by one of ordinary skill in the art to which this disclosure belongs. All patents, applications, published applications and other publications referred to herein are incorporated by reference in their entirety. If a definition set forth in this section is contrary to or otherwise inconsistent with a definition set forth in the patents, applications, published applications, and other publications that are herein incorporated by reference, the definition set forth in this section prevails over the definition that is incorporated herein by reference.

[0078] Unless otherwise indicated or the context suggests otherwise, as used herein, “a” or “an” means “at least one” or “one or more.”

[0079] This description may use relative spatial and/or orientation terms in describing the position and/or orientation of a component, apparatus, location, feature, or a portion thereof. Unless specifically stated, or otherwise dictated by the context of the description, such terms, including, without limitation, top, bottom, above, below, under, on top of, upper, lower, left of, right of, in front of, behind, next to, adjacent, between, horizontal, vertical, diagonal, longitudinal, transverse, radial, axial, etc., are used for convenience in referring to such component, apparatus, location, feature, or a portion thereof in the drawings and are not intended to be limiting.

[0080] Furthermore, unless otherwise stated, any specific dimensions mentioned in this description are merely representative of an exemplary implementation of a device embodying aspects of the disclosure and are not intended to be limiting.

[0081] As used herein, the term “adjacent” refers to being near or adjoining. Adjacent objects can be spaced apart from one another or can be in actual or direct contact with one another. In some instances, adjacent objects can be coupled to one another or can be formed integrally with one another.

[0082] As used herein, the terms “substantially” and “substantial” refer to a considerable degree or extent. When used in conjunction with, for example, an event, circumstance, characteristic, or property, the terms can refer to instances in which the event, circumstance, characteristic, or property occurs precisely as well as instances in which the event, circumstance, characteristic, or property occurs to a close approximation, such as accounting for typical tolerance levels or variability of the embodiments described herein.

[0083] A “molecular assay” as used herein refers to a procedure for specifically detecting and/or quantifying a target molecule, such as a target nucleic acid. A sample containing or suspected of containing the target molecule is contacted with one or more reagents, including at least one reagent specific for the target molecule, and subjected to conditions permissive for generating a detectable signal informative of whether the target molecule is present. For example, where the molecular assay is Polymerase Chain Reaction (PCR), the reagents include primers specific for the target and the generation of a detectable signal can be accomplished at least in part by providing a labeled probe that hybridizes to the amplicon produced by the primers in the presence of the target. Alternatively, the reagents can include an intercalating dye for detecting the formation of double-stranded nucleic acids.

[0084] A “reagent” as used herein refers to any substance or combination thereof that participates in a molecular assay, other than sample material and products of the assay. Exemplary reagents include nucleotides, enzymes, amplification oligomers, probes, and salts.

[0085] An “assay” as used herein refers to a procedure for detecting and/or quantifying a target molecule in a sample. A sample containing or suspected of containing the target molecule is

contacted with one or more reagents and subjected to conditions permissive for generating a detectable signal informative of whether the target molecule is present in the sample or the amount of the target molecule in the sample.

[0086] Referring to FIGS. **1-3**, a container **100** includes a base **102** and a lid **200** disposed on a top end of the base **102**. A septum **250** may be disposed between the lid **200** and the base **102** over a top wall aperture **106** formed in the base and below a lid aperture **204** formed in the lid **200**.

[0087] In various embodiments, base **102** and lid **200** are made from suitable moldable materials, including various plastics, such as polypropylene or cyclic olefin copolymer, polyethylene, polycarbonate, acrylic, or polyvinyl chloride (PVC), and the base **102** and lid **200** may be injection molded. Characteristics of the material used to form the base **102** and lid **200** include chemical compatibility a fluid intended for use with the container **100**. In some applications, the material must be inert so that chemicals are not leached into the fluid (e.g., a fluid reagent for performing a molecular assay) and so that the material is not degraded by the fluid. Other characteristics that may be important include manufacturability (i.e., how easily is the material injection molded?), bondability (i.e., how well can the lid **200** be bonded to the base **102**?), and ergonomics (e.g., the look and feel in a user's hand).

[0088] The septum **250** may be made from an elastomeric material, such as silicone, Viton®, polyurethane, nitrile, butyl, ethylene propylene diene monomer (EPDM), Neoprene, polyethylene, or Santoprene® (dynamically vulcanized EPDM rubber in a thermoplastic matrix of polypropylene).

[0089] Referring to FIGS. **4, 5, 8, and 9**, the base **102** includes a top wall **104** and a vessel **110** configured to hold a fluid depending from the top wall **104** and extending longitudinally below the top wall **104**. The vessel **110** extends from the top wall aperture **106** and includes side walls **114** and a bottom wall **116** at a bottom end **118** of the vessel **110**. In the illustrated embodiment, the vessel **110** has a tubular or cylindrical side wall **114** (i.e., a circular transverse profile) with a rounded, interiorly concave bottom wall **116**. The vessel **110** may have different shapes and configurations, such as a square or rectangular transverse profile and/or a flat bottom wall.

[0090] Referring to FIGS. **1-4, 8, and 9**, container **100** further includes a skirt **130** extending from a perimeter **108** (labeled in FIGS. **4 and 5**, see also FIGS. **10 and 11**) of the top wall **104**. In various embodiments, the skirt **130** has a flat bottom edge that extends below the bottom end **118** of the vessel **110**. Accordingly, the container **100** may be self-balancing in an upright position when placed with the bottom edge of the skirt **130** supported on a flat surface. Skirt **130** may include a first wall segment **132** oriented transversely to the top wall **104** and depending from a first segment of the perimeter **108** of the top wall **104** and extending longitudinally from the perimeter segment of the top wall to a bottom edge **134** of the first wall segment. First wall segment **132** partially surrounds the vessel **110**, and at least a portion of the bottom edge **134** extends below the bottom end **118** of the vessel **110**. In the illustrated embodiment, the bottom edge **134** of the first wall segment is substantially straight and parallel to the top wall **104** of the base **102**, and thus, the entire bottom edge **134** of the first wall segment **132** extends below the bottom end **118** of the vessel **110**.

[0091] As best seen in FIGS. **2 and 3**, in an embodiment, first wall segment **132** includes an alignment notch **136** formed therein and extending upwardly from the bottom edge **134** of the first wall segment **132**. The container **100** may be carried within a recessed pocket of a rack, shelf, conveyor, carousel, etc., (not shown), and a prong or other inward extension (not shown) may be provided within the recessed pocket to extend into and engage the alignment notch **136** of the container **100** placed within the pocket to thereby force a particular, desired orientation of the container **100** within the pocket and prevent the container **100** from rotating within the pocket.

[0092] Skirt **130** may further include a second wall segment **138**, also oriented transversely to the top wall **104** of the base **102** and depending from a second segment of the perimeter **108** of the top wall **104** and extending longitudinally from the perimeter segment to the bottom edge **142** of the

second wall segment **138**. In the illustrated embodiment, the bottom edge **142** of the second wall segment **138** is coplanar with the bottom edge **134** of the first wall segment **132**.

[0093] Second wall segment may include a label panel **140** on which is secured a label **141** (see FIG. **4**). Label **141** may be imprinted with identification or other informational indicia related to the container and/or its contents and may include machine-readable indicia such as bar codes or radio frequency ID tags (“RFID”). Label panel **140** may include a single, flat surface as shown in FIG. **5**, or it may include a curved surface or two or more discrete flat and/or curved surfaces.

[0094] Referring to FIGS. **1-3** and **5**, the skirt further includes longitudinally oriented grooves **144**, **146** formed on opposed sides of the base **102**. Referring more particularly to FIG. **5**, groove **144** is defined by exteriorly convex surfaces **148** and **150** (i.e., sides, or walls of the groove) converging towards a root **156** of the groove **144**. The root **156** of the groove **144** is the transition between one wall **148** of the groove **144** and an opposite wall **150** of the groove **144**. Convergent surface **148** may include part of the first wall segment **132**, and converging surface **150** may include part of the second wall segment **138**. The root **156** thereby separates the first wall segment **132** and the second wall segment **138**. Similarly, groove **146** is defined by exteriorly convex surfaces **152**, and **154** (i.e., sides, or walls of the groove) converging towards a root **158** of the groove **146**. Converging surface **152** may include part of the first wall segment **132**, and converging surface **154** may include part of the second wall segment **138**. The root **158** thereby separates the first wall segment **132** and the second wall segment **138**.

[0095] Referring to FIGS. **4** and **5**, a first, or top wall, fluid retainer barrier **170** projects above a top surface **120** of the top wall **104**. Top wall fluid barrier **170** may include an upstanding wall oriented transversely to the plane of the top wall **104** and may be substantially perpendicular to the top wall **104**. Top wall fluid retainer barrier **170** extends continuously around the top wall aperture **106** and is spaced apart from the outer perimeter of the top wall aperture **106**. In the illustrated embodiment, top wall fluid retainer barrier **170** has a generally diamond shape with rounded corners.

[0096] A plurality of alternating merlons **172** and crenels **174** are disposed on the top wall **104** and surround the top wall aperture **106** within the space between the top wall fluid retainer barrier **170** and the perimeter of the top wall aperture **106**. Connecting posts **176**, **178** project above the top surface **120** of the top wall **104**. The connecting posts **176**, **178** may be located at diametrically opposed positions with respect to the top wall aperture **106** and may each be disposed on a respective one of the merlons **172** surrounding the aperture **106**.

[0097] Referring to FIGS. **4**, **6**, **7**, **10**, and **11**, the lid **200** includes a cover wall **202** disposed at spaced-apart position above the top wall **104** of the base and has formed therein a lid aperture **204** that is generally aligned with the top wall aperture **106** of the base **102**. A perimeter wall, or skirt, **212** is oriented transversely to the cover wall **202** and depends from the perimeter **206** of the cover wall **202**. The perimeter wall **212** generally surrounds the top wall fluid retainer barrier **170** of the base **102**. As can be appreciated from FIGS. **8** and **9**, in an embodiment, at least a portion of the perimeter wall **212** is coplanar with at least a portion of the first wall segment **132** of the skirt **130** of base **102**, and a different portion of the perimeter wall **212** is coplanar with at least a portion of the second wall segment **138** of the skirt **130** of the base **102**.

[0098] Referring to FIGS. **1**, **2**, **6**, **10**, and **11**, a second fluid retainer barrier, or cover wall fluid retainer barrier, **214** projects above a top surface **208** of the cover wall **202**. The cover wall retainer barrier **214** extends continuously around the lid aperture **204** and is spaced from the perimeter of the lid aperture **204**.

[0099] Referring to FIGS. **7**, **10**, and **11**, a lid wall **216** projects below a bottom surface **210** of the cover wall **202**. The lid wall **216** is oriented transversely to the bottom surface of the cover wall **202** and extends continuously around the lid aperture **204** and is spaced from the perimeter of the lid aperture **204**. In an embodiment, the lid wall **216** has a similar shape as the top wall fluid retainer barrier **170**, which, in the illustrated embodiments, is generally diamond shaped with rounded corners. In some embodiments, the lid wall **216** is configured to have a conforming fit

inside the top wall fluid retainer barrier **170**, as shown in FIGS. **10** and **11**, so that the lid wall has a conforming fit within an interior surface of the top wall fluid retainer barrier **170**.

[0100] As shown in FIGS. **7**, **10**, and **11**, in an embodiment, a plurality of alternating merlons **218** and crenels **220** form a free edge of the lid wall **216**. Each of the plurality of alternating merlons **218** and crenels **220** of the lid wall **216** is disposed in opposed alignment with an associated one of the alternating merlons **172** and crenels **174** of the top wall **104** of the base **102**.

[0101] In an embodiment, a merlon of the lid wall **216** on each of two opposed sides of the lid aperture **204** defines a post capture pocket **222**, **223**. Each post capture pocket **222**, **223** includes a curved first segment **224**, a second segment **232** connected to a first end **226** of the first segment **224** and extending transversely from a concave side of the first segment **224**, and a third segment **234** connected to a second end **228** of the first segment **224** and extending transversely from the concave side of the first segment **224**. The second segment **232** and the third segment **234** converge toward each other at their free ends, but do not contact each other in the illustrated embodiment. Each post capture pocket **222**, **223** is configured to receive a respective one of the connecting posts **176**, **178** inserted into a pocket defined between the respective first segment **224**, second segment **232**, and third segment **234** of thereof.

[0102] Friction between the connecting posts **176**, **178**, the first segment **224**, second segment **232**, and third segment **234** of each respective post capture pocket **222**, **223** at least partially retains the lid **200** on the top end of the base **102**. In various embodiments, the lid **200** may be secured to the base **102** by any suitable adhesive. What constitutes a suitable adhesive will depend on the specific polymer material used to form the lid **200** and the base **102**. For example, solvent bonding may be possible for PVC or acrylic but not for polypropylene. Various UV cure adhesives could also be considered. Ultrasonic welding or heat stake methods are also possible.

[0103] As shown in FIG. **7**, in various embodiments, an annular relief **236** is formed on the bottom surface **210** of the cover wall **202**. Relief **236** represents an area, or region, of reduced thickness of the cover wall **202**. In various embodiments, and as shown in FIG. **7**, annular relief surrounds lid aperture **204**, such that a radially inner edge of the annular relief **236** is coextensive with the perimeter of the lid aperture **204**. In addition, portions of a radially outer edge of the annular relief **236** are coextensive with inner surfaces of parts of the lid wall **216**. One purpose of the relief **236** is to create as big of a gap as possible between the surface of the septum **250** and the underside of the lid **200** to minimize or prevent oil or another fluid from wicking between the lid **200** and the septum **250**.

[0104] As shown in FIGS. **4**, **10**, and **11**, septum **250** is disposed within the top wall fluid retainer barrier **170** and overlies the top wall aperture **106** and the plurality of alternating merlons **172** and crenels **174** of the top wall **104**. In this regard, and as shown in FIG. **4**, the septum may have a perimeter shape **256** corresponding to the interior shape of the top wall fluid retainer barrier **170**. Septum **250** may be at least partially retained within the top wall fluid retainer barrier **170** by means of the connecting posts **176**, **178** extending through holes **252**, **254** formed through the septum and aligned with the posts. When the lid **200** is installed on the top end of the base **102**, a perimeter **256** of the septum **250** is sandwiched between merlons **172** of the base **102** and opposed, associated merlons **218** of the lid wall **216**. Septum **250** may include a plurality of slits **258** formed through a portion of the septum **250** disposed between lid aperture **204** and top wall aperture **106**, whereby the slits intersect at a common, central point and or oriented radially with respect to the lid aperture and the top wall aperture. Slits **258** are configured to permit a rigid instrument, such as the probe of a pipettor, (not shown) to pass through the septum **250** and into the vessel **110**.

[0105] Due to the resiliency of the septum material, the pie-shaped sections of the septum **250** between the slits **258** will deflect downwardly as the rigid instrument is lowered through the slits **258** and into the vessel **110**, but will retain at least some contact with the outer surface of the instrument as the instrument is lowered into and then withdrawn from the vessel. In addition, the pie-shaped portions will elastically return toward their undeflected positions after the instrument is

removed, thereby providing an at least partial closure for the vessel **110**.

[0106] The resilient, pie-shaped sections of the septum **250** in contact with the outer surface of the instrument inserted into and removed from the vessel **110** function as wipers to remove at least some excess fluid from the outer surface of the instrument, and at least some of that wiped fluid may be deposited on top of the septum **250**. Accordingly, the container **100** may include fluid retainer/return structure that prevents the fluid deposited on the septum **250** from dripping off the container **100** and allows at least a portion of the fluid deposited on the septum **250** to run off the septum and into the vessel **110**.

[0107] The fluid retainer/return structure may include retainer walls or barriers that prevent fluid deposited on the septum **250** from falling off the container **100** and openings or gaps that permit fluid retained on top of the septum **250** to fall into the vessel **110**. In the illustrated embodiment, that fluid retainer/return structure may be provided by the top wall fluid retainer barrier **170**, the merlons **172**, and the crenels **174** of the base **102** and the lid wall **216**, the merlons **218**, and the crenels **220** of the lid **200**. The fluid retainer/return structure may also include fluid retainer barrier **214** on the cover wall **202** and surrounding the lid aperture **204** to prevent fluid deposited on the cover wall **202** adjacent the cover wall aperture **204** from falling off the container **100**.

[0108] At least some fluid that is deposited on top of the septum **250** is able to flow to the outer perimeter **256** of the septum **250**, where there are gaps between the lid wall **216** and the septum **250** at the crenels **220** formed in the lid wall **216**. Fluid flowing to the perimeter **256** can flow around the perimeter, where it is retained by the top wall fluid retainer barrier **170**, and then flow through the gaps between the septum **250** and the top wall **104** of the base **102** through the crenels **174** formed in the base **102** and aligned with the crenels **220** formed in the lid wall **216**.

[0109] FIG. **12** shows a gripping mechanism holding a container **100**. The gripping mechanism includes opposed arms **260**, **262** that are movable in a clamping fashion toward and away from each other to selectively grip, or grasp, the container **100** or release the container **100**, respectively. Each of the opposed arms **260**, **262** includes longitudinally spaced fingers, or extensions, **264**, **266** (only visible for arm **260**). Each of the fingers **264**, **266** includes an enlarged tip **268**, **270** that extends into the grooves **144**, **146** of the container **100**.

[0110] In an embodiment, the container **100** may include gripping structures, such as grooves **144**, **146**, configured to enable the gripping mechanism to securely grip the container **100** in a repeatable position and orientation with respect to the opposed arms **260**, **262**. That is, the gripping structures engaged by container-contacting components of the gripping mechanism result in a securing grasping engagement between the container and the container-contacting components and where the position and orientation of the container with respect to the gripping mechanism is substantially the same each time a container is grasped by the gripping mechanism.

[0111] Because each of the grooves **144**, **146** includes opposed, exteriorly-convex surfaces **148**, **150**, **152**, **154** (see FIG. **5**), the enlarged tips **268**, **270** of the fingers **264**, **266**, of the opposed arms **260**, **262** are wedged toward the roots **156**, **158** of each of the grooves **144**, **146**, thereby providing a secure gripping engagement between the enlarged tips **268**, **270** and the grooves **144**, **146**. In addition, the opposed, exteriorly-convex surfaces **148**, **150**, **152**, **154**, combined with the longitudinal spacing between the enlarged tips **268**, **270** of the fingers **264**, **266**, provide a self-centering functionality of the fingers **264**, **266** and the enlarged tips **268**, **270** with respect to the grooves **144**, **146**. Therefore, for example, if the container **100** is tilted so that one or both grooves **144**, **146** is not aligned with an imaginary, longitudinal line extending through the enlarged tips **268**, **270**, the container **100** will be reoriented in an upright orientation as the opposed arms **260**, **262** close on the container **100** and the enlarged tips **268**, **270** wedge into the groove toward the roots **156**, **158** at longitudinally-spaced positions. Similarly, if the container is twisted about its longitudinal axis so that one or both of the opposed arms **260**, **262** (and its associated enlarged tips, such as enlarged tips **268**, **270** for arm **260**) is not aligned with the associated groove **144** or **146**, the container **100** will be rotated about its longitudinal axis as the opposed arms **260**,

262 close on the container **100** and the enlarged tips **268, 270** wedge into each groove toward the roots **156, 158** to align the enlarged tips **268, 270** of both arms **260, 262** with its associated groove **144, 146**.

[0112] Accordingly, the container **100** can be gripped more securely and with more repeatable positioning than if the container were simply gripped on opposite sides of the skirt **130**.

[0113] While the subject matter of this disclosure has been described and shown in considerable detail with reference to certain illustrative embodiments, including various combinations and sub-combinations of features, those skilled in the art will readily appreciate other embodiments and variations and modifications thereof as encompassed within the scope of the present disclosure. Moreover, the descriptions of such embodiments, combinations, and sub-combinations is not intended to convey that the claimed subject matter requires features or combinations of features other than those expressly recited in the claims. Accordingly, the scope of this disclosure is intended to include all modifications and variations encompassed within the scope of the following appended claims.

Claims

1. A container comprising: a top wall; a fluid vessel depending from the top wall and extending from a top wall aperture formed in the top wall to a bottom end of the fluid vessel; a first wall segment depending from a first perimeter segment of the top wall, wherein the first wall segment extends from the first perimeter segment of the top wall to a bottom edge of the first wall segment and at least partially surrounds the fluid vessel, and wherein at least a portion of the bottom edge of the first wall segment is disposed below the bottom end of the fluid vessel, and further comprising an alignment notch formed in the first wall segment and extending upwardly from the bottom edge of the first wall segment; and a top wall fluid retainer barrier projecting above a top surface of the top wall, wherein the top wall fluid retainer barrier extends continuously around the top wall aperture and is spaced from a perimeter of the top wall aperture.
2. The container of claim 1, further comprising a second wall segment depending from a second perimeter segment of the top wall, wherein the second wall segment extends from the second perimeter segment of the top wall to a bottom edge of the second wall segment.
3. The container of claim 2, further comprising grooves formed on opposed sides of the container, each groove defined by opposed, exteriorly-convex surfaces converging towards a root of the groove, wherein one of the opposed, exteriorly-convex surfaces of each groove comprises part of the first wall segment and the other of the opposed, exteriorly-convex surfaces of each groove comprises part of the second wall segment, and wherein the root of each groove separates the first wall segment and the second wall segment.
4. The container of claim 1, further comprising a plurality of alternating merlons and crenels disposed on the top surface of the top wall and surrounding the top wall aperture within the space between the top wall fluid retainer barrier and the perimeter of the top wall aperture.
5. The container of claim 1, further comprising a lid, wherein the lid comprises: a cover wall disposed at a spaced-apart position above the top wall and having formed therein a lid aperture generally aligned with the top wall aperture; and a perimeter wall depending from a perimeter of the cover wall, wherein at least a first portion of the perimeter wall is coplanar with at least a portion of the first wall segment.
6. The container of claim 5, wherein the perimeter wall is oriented transversely to the cover wall.
7. The container of claim 5, further comprising a cover wall fluid retainer barrier projecting above a top surface of the cover wall, wherein the cover wall fluid retainer barrier extends continuously around the lid aperture and is spaced from a perimeter of the lid aperture.
8. The container of claim 7, further comprising a lid wall projecting below a bottom surface of the cover wall, wherein the lid wall extends continuously around the lid aperture and is spaced from

the perimeter of the lid aperture.

9. The container of claim 8, wherein the lid wall comprises a plurality of alternating merlons and crenels forming a free edge of the lid wall.

10. The container of claim 7, further comprising an annular relief formed on the bottom surface of the cover wall and having an inner edge that is coextensive with the perimeter of the lid aperture.

11. The container of claim 1, further comprising an elastomeric septum disposed within the top wall fluid retainer barrier and overlying the top wall aperture, wherein the septum includes a plurality of slits formed through a portion of the septum overlying the top wall aperture and configured to permit a pipette tip to pass through the septum and into the fluid vessel.

12. The container of claim 11, further comprising connecting posts projecting above the top surface of the top wall, wherein each of the connecting posts is disposed on an opposed side of the top wall aperture and is disposed within the space between the top wall fluid retainer barrier and the perimeter of the top wall aperture, and wherein the septum is at least partially retained by the connecting posts extending through holes formed through the septum and aligned with the posts.

13. The container of claim 1, further comprising a lid, wherein the lid comprises: a cover wall disposed at a spaced-apart position above the top wall and having formed therein an aperture generally aligned with the top wall aperture; and a perimeter wall depending from a perimeter of the cover wall, wherein the perimeter wall surrounds the top wall fluid retainer barrier.

14. The container of claim 13, further comprising a lid wall projecting below a bottom surface of the cover wall, wherein the lid wall extends continuously around the lid aperture and is spaced from the perimeter of the lid aperture, and wherein the lid wall is configured to have a conforming fit within an interior surface of the top wall fluid retainer barrier.

15. The container of claim 14, further comprising an annular relief formed on the bottom surface of the cover wall and having an inner edge that is coextensive with the perimeter of the lid aperture.

16. The container of claim 4, further comprising a lid, wherein the lid comprises: a cover wall disposed at a spaced-apart position above the top wall and having formed therein a lid aperture generally aligned with the top wall aperture; a perimeter wall depending from a perimeter of the cover wall, wherein the perimeter wall surrounds the top wall fluid retainer barrier; a lid wall projecting below a bottom surface of the cover wall, wherein the lid wall extends continuously around the lid aperture and is spaced from a perimeter of the lid aperture; and a plurality of alternating merlons and crenels forming a free edge of the lid wall, wherein each of the plurality of alternating merlons and crenels of the lid wall of the lid is disposed in opposed alignment with an associated one of the alternating merlons and crenels of the top wall.

17. The container of claim 16, wherein the lid wall is configured to have a conforming fit within an interior surface of the fluid retainer.

18. The container of claim 16, further comprising an annular relief formed on the bottom surface of the cover wall and having an inner edge that is coextensive with the perimeter of the lid aperture.

19. The container of claim 16, further comprising an elastomeric septum disposed within the top wall fluid retainer barrier and overlying the top wall aperture and the plurality of alternating merlons and crenels of the top wall, wherein a perimeter of the septum is sandwiched between merlons of the top wall and opposed, associated merlons of the lid wall, and wherein the septum includes a plurality of slits formed through a portion of the septum between the lid aperture and the top wall aperture and configured to permit a pipette tip to pass through the septum and into the fluid vessel.

20. The container of claim 1, wherein the container is made of plastic, and wherein the container is at least partially translucent.
