

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12395575
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Maurio; Joseph M. et al.

---

### Out of band network and passive interface device

---

#### Abstract

A communications system includes a primary network communicating in accordance with a first communications protocol an out-of-band (OOB) network communicating in accordance with a second communications protocol. The primary network includes first and second primary network nodes, which are connected via a twisted-pair cable. The first primary network node is configured to transmit first communications protocol signals on the twisted-pair cable to the second primary network node. The OOB network includes first and second OOB network nodes, which are connected to the twisted-pair cable via a first OOB passive interface device connected between the first primary network node and the second primary network node. The second OOB network node is connected to the twisted-pair cable via a second OOB passive interface device connected between the first and second primary network nodes.

---

**Inventors:** Maurio; Joseph M. (Westminster, MD), Rogers; James M. (Columbia, MD), Beall; Alexander W. (Rockville, MD)

**Applicant:** The Johns Hopkins University (Baltimore, MD)

**Family ID:** 1000008765778

**Assignee:** The Johns Hopkins University (Baltimore, MD)

**Appl. No.:** 17/590106

**Filed:** February 01, 2022

#### Prior Publication Data

Document Identifier	Publication Date
US 20220247842 A1	Aug. 04, 2022

#### Related U.S. Application Data

us-provisional-application US 63144506 20210202

---

## Publication Classification

**Int. Cl.:** H04L69/40 (20220101); H04L9/40 (20220101); H04L69/18 (20220101)

**U.S. Cl.:**

**CPC** H04L69/40 (20130101); H04L63/18 (20130101); H04L69/18 (20130101)

## Field of Classification Search

**CPC:** H04L (69/40); H04L (63/18)

**USPC:** 370/252

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8331792	12/2011	Jovanovich	398/135	H04B 10/40
2011/0013705	12/2010	Lin	375/258	H04B 3/00
2012/0134428	12/2011	Bobrek	375/257	H04B 3/00
2017/0230204	12/2016	Sivertsen	N/A	H04L 25/0292

### FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
110995467	12/2019	CN	H04L 49/10
WO-2017032163	12/2016	WO	H04L 12/28

---

*Primary Examiner:* Crutchfield; Christopher M

*Assistant Examiner:* Voltaire; Jean F

---

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application claims priority to and the benefit of prior-filed, U.S. Provisional Application No. 63/144,506 filed on Feb. 2, 2021, the entire contents of which are hereby incorporated herein by reference.

### TECHNICAL FIELD

(1) Exemplary embodiments generally relate to communications systems, and more specifically relate to out of band communications systems.

### BACKGROUND

(2) With the vast connectivity of communications networks, network security has become an increasingly difficult issue to address. The risk that malware or a network intruder can gain access to a communications network to inhibit or alter the network's behavior continues to increase as the sophistication of the attacks increase. While network monitoring may provide a means for detecting and thwarting such attacks, such approaches are only effective until the attackers identify a weakness in such monitoring and exploit it.

(3) Another option for thwarting such attacks is to implement network redundancy. In this regard,

some network operators maintain completely separate networks that are ready to be activated in the event that a primary network is lost due to, for example, an attack or an unrelated device or system failure. Such redundancy can be effective, but is costly to construct and maintain because duplicate equipment and connectivity is needed and ultimately under-utilized. In many instances, such costs can be so significant that implementation of a redundant network is unrealistic. As such, techniques for implementing redundant and alternative networks in a manner that saves cost are desired and would be beneficial.

#### BRIEF SUMMARY

(4) According to some example embodiments, a communications system is provided. The communications system includes a primary network communicating in accordance with a first communications protocol. The primary network includes a first primary network node and a second primary network node. The first primary network node and the second primary network node may be connected via a twisted-pair cable. The first primary network node may be configured to transmit first communications protocol signals on the twisted-pair cable to the second primary network node. The communications system may also include an out-of-band (OOB) network communicating in accordance with a second communications protocol. The OOB network may include a first OOB network node and a second OOB network node. The first OOB network node may be connected to the twisted-pair cable via a first OOB passive interface device that is connected between the first primary network node and the second primary network node. The second OOB network node may be connected to the twisted-pair cable via a second OOB passive interface device that is connected between the first primary network node and the second primary network node. The first OOB passive interface device may be configured to receive second communications protocol signals from the first OOB network node and inject the second communications protocol signals onto the twisted-pair cable with the first communications protocol signals. The second OOB network node may be configured to receive and extract the injected second communications protocol signals from the twisted pair cable for provision to the second OOB network node. Extraction of the injected second communications protocol signals may be performed such that the first communications protocol signals are received by the second primary network node unaffected by the injection of the second communications protocol signals.

(5) According to some example embodiments, an out-of-band (OOB) passive interface device is provided. The OOB passive interface device may include a first Ethernet port, a second Ethernet port, and an OOB communications protocol port. The OOB passive interface device may also include a first transformer and a second transformer. A first pair of conductors from the first Ethernet port may be connected to first terminals of the first transformer and a second pair of conductors from the second Ethernet port may be connected to second terminals of the first transformer. A third pair of conductors from the first Ethernet port may be connected to first terminals of the second transformer and a fourth pair of conductors from the second Ethernet port may be connected to second terminals of the second transformer. A first OOB interface conductor may be connected from a centertap of the first transformer to the OOB communication protocol port. A second OOB interface conductor may be connected from a centertap of the second transformer to the OOB communication protocol port.

(6) According to some example embodiments, a method for implementing an out-of-band (OOB) network is provided. The method may include receiving first communications protocol signals via a receiving twisted-pair cable, and receiving second communications protocol signals at an OOB communications protocol port. The method may further include injecting the second communications protocol signal, as a differential signal, between a first twisted-pair and a second twisted-pair, with the first communications protocol signals, and transmitting the first communications protocol signals with the second communications protocol signals via the first twisted-pair and the second twisted-pair on a transmitting twisted-pair cable.

---

## Description

### BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING(S)

- (1) Having thus described some example embodiments in general terms, reference will now be made to the accompanying drawings, which are not necessarily drawn to scale, and wherein:
- (2) FIG. 1 illustrates an example primary network according to some example embodiments;
- (3) FIG. 2 illustrates an example primary network operating with an out-of-band network according to some example embodiments;
- (4) FIG. 3 illustrates an example primary network operating with an out-of-band network including an out-of-band bridge according to some example embodiments;
- (5) FIG. 4 illustrates an example out-of-band passive interface device according to some example embodiments;
- (6) FIG. 5 illustrates another example primary network operating with an out-of-band network showing signaling examples according to some example embodiments;
- (7) FIG. 6A illustrates components of an example out-of-band network that operates with two-wire out-of-band passive interface devices according to some example embodiments;
- (8) FIG. 6B illustrates components of an example out-of-band network that operates that operates with four-wire out-of-band passive interface devices according to some example embodiments;
- (9) FIG. 7 shows a signaling graph illustrating a lack of interference between signaling for the primary network and the out-of-band network according to some example embodiments;
- (10) FIG. 8 illustrates an example dual network device that may be configured to leverage communications on both the primary and the out-of-band networks according to some example embodiments; and
- (11) FIG. 9 illustrates a flow chart of an example method for implementing an out-of-band network according to some example embodiments.

### DETAILED DESCRIPTION

- (12) Some example embodiments now will be described more fully hereinafter with reference to the accompanying drawings, in which some, but not all example embodiments are shown. Indeed, the examples described and pictured herein should not be construed as being limiting as to the scope, applicability or configuration of the present disclosure. Rather, these example embodiments are provided so that this disclosure will satisfy applicable legal requirements. Like reference numerals refer to like elements throughout.
- (13) According to some example embodiments, a network solution is provided that allows for the implementation of an out-of-band (OOB) network on the same twisted-pair cabling as a primary network. The OOB network may be implemented in a manner that the OOB devices, and the OOB network itself, operates separate from the primary network. While the primary network and the OOB network may share some portion of a physical layer in the form of shared twisted-pair cabling, the existence and operation of the OOB network may be invisible and undetectable by primary network devices. As such, the OOB network may be operated as a redundant network that resides in a separate security domain from the primary network such that a security threat to the primary network need not be a security threat to the OOB network. Further in the event that the threat is a non-physical layer threat that affects the primary network, the affects may be not be realized on the OOB network which may continue to operate unaffected by the impact to the primary network.
- (14) While the OOB network may be leveraged for use in a network security context, the OOB network, according to some example embodiments, may be utilized as an isolated communications channel. For example, according to some example embodiments, the OOB network may be used for command and control, while, for example, the primary network is being used for data transfer. Further, according to some example embodiments, the OOB network may be utilized for situational

awareness in isolation from the primary network.

(15) To implement the OOB network, according to some example embodiments, OOB passive interface devices may be utilized as bump-in-the wire components. As such, the OOB passive interface devices may be added to already existing Ethernet infrastructure thereby realizing a significant cost savings for implementing a separate network. An OOB passive interface device may be an electronic device configured to inject or extract OOB network signaling from the shared twisted-pair cabling. Due to the positioning of the OOB passive interface devices, the signaling for the OOB network may be injected and extracted between nodes of the primary network. Therefore, the primary network devices, according to some example embodiments, cannot see the OOB network signaling because it is injected behind a primary network device (or node) and extracted before a next connected primary network device.

(16) As such, an OOB network device (or node) connected to an OOB passive interface device may cause the OOB passive interface device to inject signaling onto the twisted-pair cabling for transmission within the OOB network. Alternatively, the OOB network device may cause the OOB passive interface device to extract signaling for receipt by the OOB network device from the twisted-pair cabling. To do so, according to some example embodiments, the OOB passive interface device may include a centertap transformer for each twisted-pair in the twisted-pair cabling. The OOB network signaling may be injected as a differential signal applied between two centertap connections on transformers, for example, connected to respective twisted-pairs. Because the centertap connections are used, the injection of the OOB network signaling on each individual twisted-pair has no relative effect, since only the differential between the signals on the conductors of the twisted-pair is of significance to the primary network. Since the OOB network signaling is applied between twisted-pairs via the centertap transformers, no differential on a single twisted-pair is introduced. Further, because the injected OOB network signaling is extracted, also via centertap transformers at the receive end, the primary network is not aware that any modification to the signaling on the twisted-pair cabling occurred. The primary network signaling is therefore received at a primary network destination device without any indication that the OOB network signaling had been injected.

(17) As such, the twisted-pair cabling may be utilized for the separate networks, thereby reducing the cost of realizing such redundancy and/or the additional communications channel, while also supporting high data rates. Additionally, the OOB passive interface devices may be passive devices that leverage a transformer to perform the injection and extraction of signaling. Due to the lack of active components such as processing devices on the OOB passive interface devices, the cost of the devices can be quite low. Additionally, such a passive approach can also improve reliability and availability of the devices and the network. As such, the overhead needed to implement the OOB network may be relatively small allowing for, for example, increased security at a low cost.

(18) As such, the OOB network may be operated as a diverse communication channel and network from the primary network that, for example, uses different types of components and signaling, without requiring substantial additional infrastructure. According to some example embodiments, the OOB network described herein may have a wide variety of applications that are related to network security and/or independent network operation. The primary network and the OOB network may be operated as cyber-physical system architecture. For example, the OOB network may be leveraged in the context of utility systems for security and control. Because the OOB network may not be visible to the primary network, the OOB may be more difficult to attack and therefore sensitive control signals may be transmitted on the OOB network. In this regard, for example, relay control signaling for electric substation breakers may be provided via the OOB network. Similarly, valve controls for water systems may be transmitted via the OOB network. As such, the operation of the OOB network with the primary network may be leveraged in a variety of ways that can be implemented on separate networks without the cost of entirely separate infrastructure. Further, in the event that the primary network is lost, the OOB network may be

leveraged to perform a primary network restart or primary network node restart where real-time controls may be necessary during the restart and can be provided via the OOB network. Additionally, the OOB network may be leveraged for independent data or instruction verification and secure data exchange.

(19) Having described some aspects of example embodiments, reference will now be made to FIG. 1, which illustrates a primary network **100**, in complete isolation. The primary network **100** may be a simplified representation of a network having a first primary network node **110**, a second primary network node **120**, and a twisted-pair cable **130**. The first primary network node **110** may be connected to the second primary network node **120** via twisted-pairs of the twisted-pair cable **130**. The primary network **100** may be a local area network, a metropolitan area network, a wide area network, or the like.

(20) A network node may be any type of device that resides as a networked entity on the network. As such, a network node may be edge device (e.g., a server, a terminal, etc.) or a midstream device (e.g., a router, a switch, or the like). The first primary network node **110** and the second primary network node **120** may be edge devices as shown in FIG. 1. However, in another example embodiment, the nodes may be embodied as midstream devices. In any event, as further described below, communications and associated signaling may be generated by one of the first primary network node **110** or the second primary network node **120** for receipt by the other of the first primary network node **110** or the second primary network node **120**.

(21) The twisted-pair cable **130** may include a plurality of twisted-pairs. According to some example embodiments, the twisted-pair cable **130** may include two or four twisted-pairs. The twisted-pair cable **130** may be, for example, shielded or unshielded, and copper-based. Such twisted-pair cabling may be used for Ethernet implementations in the context of, for example, a local area network. In this regard, in accordance with Ethernet protocols, a twisted-pair may be utilized to deliver a signal as a differential signal between the two conductors of a given pair. Because of the twisted relationship of the conductors, common mode noise that exists on both conductors may be ignored, since the differential signal is the signal of interest. However, according to some example embodiments, because the introduction of common mode signals on both of the conductors can be injected without a loss of signal characteristics for the differential signal on the twisted-pair, additional signaling may be injected to support the operation of an alternative network, i.e., an OOB network.

(22) As such, in operation, the primary network **100** may leverage the twisted-pair cable **130** to transmit communications between the first primary network node **110** and the second primary network node **120**. Such communications may involve use of one or more of the twisted-pairs of the twisted-pair cable **130**. According to some example embodiments, the primary network **100** may communicate via first communications protocol. The first communications protocol may be any type of communications protocol that may be implemented on the twisted-pair cable **130**, such as transmission control protocol (TCP), Internet protocol (IP), user datagram protocol (UDP), orthogonal frequency multiplexing (OFDM), or the like.

(23) Now referring to FIG. 2, the primary network **100** is shown in combination with an OOB network **200**, according to some example embodiments. The primary network **100** including the first primary network node **110**, the second primary network node **120**, and the twisted-pair cable **130** are shown within the primary network cloud (solid line).

(24) An OOB network **200** is also shown within an OOB network cloud (dashed line). The OOB network **200** may include a first OOB network node **210**, a second OOB network node **220**, a first OOB passive interface device **230**, and a second OOB passive interface device **240**. Following from the description above, the first OOB network node **210** and the second OOB network node **220** may be nodes on the OOB network **200**. As such, the first OOB network node **210** and the second OOB network node **220** may be any type of device that resides as a networked entity on the OOB network **200**. The first OOB network node **210** and the second OOB network node **220** may

be edge devices (e.g., a server, a terminal, etc.) or midstream devices (e.g., a router, a switch, or the like). In any event, as further described below, communications and associated signaling may be generated by one of the first OOB network node **210** or the second OOB network node **220** for receipt by the other of the first OOB network node **210** or the second OOB network node **220**.

(25) The first OOB network node **210** may be connected to the OOB network **200** via a connection **250** to the first OOB passive interface device **230**. Similarly, the second OOB passive interface device **240** may be connected to the OOB network **200** via a connection **251** to the second OOB passive interface device **240**. As OOB passive interface devices, the first OOB passive interface device **230** and the second OOB passive interface device **240** may operate as a passive interface for OOB network nodes to gain access to the OOB network **200**. The OOB passive interface devices may be connected to the twisted-pair cable **130** such that the primary network signals on the twisted-pair cable **130** pass through the OOB passive interface devices. Since the OOB passive interface devices are in-line devices, the twisted-pair cable **130** may be separated or cut to allow for the OOB passive interface devices to be installed in an in-line configuration. As a result of the first OOB passive interface device **230** being installed in this manner, the first primary network node **110** may be connected to the first OOB passive interface device **230** via a connection **132**, which may include twisted-pair cabling. Similarly, as a result of the second OOB passive interface device **240** being installed in this manner, the second primary network node **120** may be connected to the second OOB passive interface device **240** via a connection **131**, which may include twisted-pair cabling.

(26) The twisted-pair cable **130**, on the other hand, may be shared resource between the primary network **100** and the OOB network **200** on the physical layer. As such, signaling for both networks (i.e., the primary network **100** and the OOB network **200**) may be present on the twisted-pair cable **130**. As further described below, the OOB passive interface devices may be configured to operate in a manner that couples or bundles the primary network signaling with the OOB network signaling on the twisted-pair cable **130**. Additionally, the OOB passive interface devices may operate as pass-through devices for signaling for the primary network **100**.

(27) In operation, the OOB network **200** may leverage the twisted-pair cable **130** to transmit communications between the first OOB network node **210** and the second OOB network node **220**. Such communications may involve the use of one or more of the twisted-pairs of the twisted-pair cable **130**. According to some example embodiments, the OOB network **200** may communicate via second communications protocol, which may be same or different from the first communications protocol used by the primary network **100**. The second communications protocol may be any type of communications protocol that may be implemented on the twisted-pair cable **130**, such as transmission control protocol (TCP), Internet protocol (IP), user datagram protocol (UDP), orthogonal frequency division multiplexing (OFDM), or the like. Further, according to some example embodiments, a serial communications protocol or any other two-wire protocol may be implemented by the OOB network **200**, which may be limited, for example, only by the quality of the cabling that supports the signaling.

(28) According to some example embodiments, while the primary network **100** and the OOB network **200** may share resources (e.g., the twisted-pair cable **130**), the primary network **100** and the OOB network **200** may operate using different communications protocols. For example, while the primary network **100** may operate using TCP, the OOB network **200** may implement a serial communications protocol. Due to the operation of the OOB passive interface devices, communication signaling for the two different protocols may reside on the shared resources without creating interference. Further, due to the placement of the OOB passive interface devices, signaling for the OOB network **200** may be injected and extracted between nodes of the primary network **100**. Therefore, the signaling for the OOB network **200** may not be accessible (or even visible) to a node on the primary network **100**.

(29) Accordingly, the operation of the primary network **100** and the OOB network **200** may

involve, for example, first communications signaling according to a first communications protocol for the primary network **100** being transmitted by the first primary network node **110** to the second primary network node **120**. Additionally, second communications signaling according to a second communications protocol for the OOB network **200** may be transmitted by the first OOB network node **210** to the second OOB network node **220**. As such, the first communications signaling may be received at the first OOB passive interface device **230** via connection **132**. Additionally, the second communications signaling transmitted by the first OOB network node **210** may also be received at the first OOB passive interface device **230** via the connection **250**. The first OOB passive interface device **230** may be configured to inject the second communications signaling onto twisted-pairs of the twisted-pair cable **130** with the first communications signaling. As such, the aggregate or combined signaling on the twisted-pair cable **130** may include both the first communications signaling and the second communications signaling, with the first communications signaling essentially passing through the first OOB passive interface device **230** and the second communications signaling being injected onto the twisted-pair cable **130** with the first communications signaling.

(30) When the combined signaling is received at the second OOB passive interface device **240**, the second OOB passive interface device **240** may be configured to extract the second communications signaling from the combined signaling. The extracted second communications signaling may be then be provided to the second OOB network node **220** for receipt, without inference from the first communications signaling. Additionally, the second OOB passive interface device **240** may transmit the first communications signaling, without interference from the second communications signaling, to the second primary network node **120** for receipt.

(31) As such, while the primary network **100** and the OOB network **200** utilize the twisted-pair cable **130**, the primary network **100** and the OOB network **200** operate separately and are not susceptible to a common network attack (unless, for example, the twisted-pair cable **130** is physically attacked). Further, if the primary network **100** is offline, the OOB network **200** may still continue to operate, and if the OOB network **200** is offline the primary network **100** may still continue to operate. Additionally, while the OOB passive interface devices see communications signaling and associated traffic from both networks, the network nodes (e.g., the first primary network node **110**, the second primary network node **120**, the first OOB network node **210**, and the second OOB network node **220**) need not be aware of the signaling or traffic associated with the other network. In other words, operation of the first primary network node **110** and the second primary network node **120** may unaffected by the existence and operation of the first OOB network node **210** and the second OOB network node **220**. Similarly, the first OOB network node **210** and the second OOB network node **220** may unaffected by the existence and operation of the first primary network node **110** and the second primary network node **120**. Additionally, because the OOB passive interface devices are, according to some example embodiments, passive devices that do not include a processor or other active hardware, the OOB passive interface devices are generally insusceptible to direct network attacks, making the OOB passive interface devices reliable and hardy, and able support operations of one network when the other network is down.

(32) Turning now to FIG. 3, a modified primary network **101** and a modified OOB network **201** are shown. The primary network **101** is similar to the primary network **100** with the exception that a midstream third primary network node **140** (e.g., a router, switch, etc.) is connected between the first primary network node **110** and the second primary network node **120**. As such, the twisted-pair cable **130** is separated in networks of FIG. 3 into a twisted-pair cable portion **134** and a twisted-pair cable portion **135**.

(33) Because of the placement of the third primary network node **140**, additional OOB passive interface devices **260** and **270**, and an OOB bridge **252** may be included in the OOB network **201**, relative to the OOB network **200** of FIG. 2. In this regard, following from the signaling scenario described above with respect FIG. 2, the first communications signaling from the first primary



network node **110** may essentially pass through the first OOB passive interface device **230**, the third OOB passive interface device **260**, the third primary network node **140**, the fourth OOB passive interface device **270**, and the second OOB passive interface device **240** to arrive at the second primary network node **120**.

(34) The second communications signaling from the first OOB network node **210** may travel through the OOB bridge **252** to arrive at the second OOB network node **220**. In this regard, the second communications signaling from the first OOB network node **210** may be injected onto the portion of the twisted-pair cable portion **134** with the first communications signaling. The third OOB passive interface device **260** may receive the combined signaling, extract the second communications signaling, and pass the first communications signaling to the third primary network node **140**. The extracted second communications signaling may be routed through the OOB bridge **252** (e.g., a wired connection which may be a twisted-pair cable) to the fourth OOB passive interface device **270**. In doing so, the third primary network node **140** does not have access or visibility to the second communications signaling. The fourth OOB passive interface device **270** may then re-inject the second communications signaling onto the portion of the twisted-pair cable portion **135**, again with the first communications signaling. Upon receipt by the second OOB passive interface device **240**, the second OOB passive interface device **240** may be configured to extract the second communications signaling for provision to the second OOB network node **220** and pass the first communications signaling to the second OOB network node **220**.

(35) As such, through the implementation of the OOB passive interface devices signaling for the OOB network **200** need not be accessible to a primary network node, even when a primary network node is disposed in-line with a travel path for signaling of the OOB network **200**. Accordingly, each primary network node may be bracketed by OOB passive interface devices to avoid signaling for the OOB network **200** passing to a node of the primary network.

(36) Having generally described the network level operation for implementing an OOB network, FIG. **4** will now be described which illustrates the components of an example OOB passive interface device **400**. In this regard, the OOB passive interface device **400** may include a circuit board **402** with a first connector **404**, a second connector **408**, and an OOB connector **406** affixed thereto. According to some example embodiments, the first connector **404** and the second connector **408** may be connection points to twisted-pair cables that may or may not be shared resource cables between a primary network and an OOB network. As such, the first connector **404** and the second connector **408** may be, for example, RJ45 connectors configured to connect with an RJ45 plug coupled to a twisted-pair cable having two or four twisted pairs. As such, the first connector **404** and the second connector **408** may be configured to operate as a first Ethernet port and a second Ethernet port. In example embodiment of OOB passive interface device **400**, the first connector **404** and the second connector **408** may be configured to support connections to a twisted-pair cable with two active twisted-pairs. In this regard, conductor pair **423** may be connected to a first twisted-pair of a cable connected to the first connector **404** and conductor pair **422** may be connected to a second twisted-pair of the cable connected to the first connector **404**. Similarly, conductor pair **416** may be connected to a first twisted-pair of a cable connected to the second connector **408** and conductor pair **418** may be connected to a second twisted-pair of the cable connected to the second connector **408**. The OOB connector **406**, which may be configured to operate as an OOB communications protocol port, may be connected to an OOB network node to receive signals from or transmit signals to the OOB network node. The signals may be OOB communications protocol signals for transmission or reception on the OOB network. According to some example embodiments, the OOB connector **406** may be serial port connector, such as a DB9 connector.

(37) The OOB passive interface device **400** may also include transformers **412** and **414**, which may be part of a transformer bank **410**. The transformers **412** and **414** may be rated for Ethernet voltages and may have a 1:1 turns ratio. Because the transformers **412** and **414** may have a 1:1 (or

unity) turns ratio, signals that are received at terminals on one side of the transformer may be output as the same (or substantially similar) signals at the terminals on the other side of the transformer (because no step up or step down in voltage occurs through the transformer). As such, signals received by second connector **408** and provided to conductor pair **416** may be received at transformer terminals **430** of transformer **414**, and the same signals may be output on the terminals **428** of the transformer **414** and conductor pair **423** for provision to first connector **404**. Similarly, signals received by second connector **408** and provided to conductor pair **418** may be received at transformer terminals **434** of transformer **412**, and the same signals may be output on the terminals **432** of the transformer **412** and conductor pair **422** for provision to first connector **404**. Again, because the transformers **412** and **414** have a 1:1 turns ratio, signals that are received at the first connector **404** that travel through the transformers **412** and **414** may be as the same signals at the second connector **408**.

(38) However, according to some example embodiments, the transformers **412** and **414** may include a centertap on one or both sides of the transformer and signals applied to the centertap may cause changes to an output signal of the transformers **412** and **414** relative to the input signal. The centertap may be a connection to a transformer coil at a midpoint of the coil. As such, the transformer **414** may have a centertap **438** and the transformer **412** may have a centertap **436**. As shown in FIG. 4, conductor **424** is connected between the OOB connector **406** and the centertap **436**, and conductor **426** is connected between the OOB connector **406** and the centertap **438**.

(39) The centertap connections to the transformers **412** and **414** may be used to inject OOB network signals received via the OOB connector **406** onto the conductor pairs or extract OOB network signals from the conductor pairs for provision to the OOB connector **406**. In this regard, because the signal on, for example, conductor **424** is applied to the centertap **436**, the effect of the signal on the conductor pairs **418** or **422** (and the connected twisted-pairs) results in no additional differential voltage between the conductors of the conductor pairs. As such, the injection of the signal and the associated voltage at the centertap **436** results in no loss of information in the signals that were already present on the conductor pairs **422** and **418**. However, information from conductor **424** (and an OOB network node connected to OOB connector **406**) has still been added to the conductor pairs **418** and **422** as a non-differential dynamic offset. Similarly, a signal on the conductor **426** may be applied to the centertap **438**. Again, the effect of the signal on the conductor pairs **416** or **423** (and the connected twisted-pairs) results in no additional differential voltage between the conductors of the conductor pairs. As such, the injection of the signal and the associated voltage at the centertap **438** results in no loss of information in the signals that were already present on the conductor pairs **416** and **423**. However, information from conductor **426** (and an OOB network node connected to OOB connector **406**) has still been added to the conductor pairs **416** and **423** as a non-differential dynamic offset.

(40) However, a differential signal between the conductors **424** and **426** may be applied to the centertaps **436** and **438**, respectively. Such a differential signal would generate a non-differential offset on each individual set of conductor pairs (i.e., conductor pairs **418** and **422**, and conductor pairs **416** and **423**), but a differential may exist between the signals on the conductor pairs (i.e., between conductor pairs **418** and **422**, and conductor pairs **416** and **423**) and may be implemented without generating interference or loss of information. In other words, a differential signal for the OOB network may be applied between the conductor pairs without impacting the information in the signals on each of the conductor pairs (and the associated twisted-pairs of a cable). In this way, OOB network signals can be injected as a differential signal on two twisted-pairs to realize the OOB network.

(41) In a similar manner, OOB network signals may be extracted from the conductor pairs (i.e., conductor pairs **418** and **422**, and conductor pairs **416** and **423**) to remove a previously injected non-differential offset on each set of conductor pairs and evaluate the signals as a differential signal for the OOB network. The extraction of the injected non-differential offset from the centertaps of

the transformers **412** and **414** removes the energy from the signal on the conductor pairs to return the signals on the conductor pairs to the signals that existed on the conductor pairs prior to the injection. As such, via a coupled set of OOB passive interface devices **400**, OOB network signals can be injected and extracted, without interfering with or otherwise impacting the primary network signals that reside on the twisted-pair cabling connecting the coupled set of OOB passive interface devices **400**.

(42) It is noteworthy that the use of centertap transformers, according to some example embodiments, provides for injection and extraction of OOB network signals, without the use of active components such as signal processors and the like. Due to the passive characteristics of the OOB passive interface device **400**, the device itself is not susceptible to malware and other network attacks that may be lodged against active components. Accordingly, a successful attack on, for example, the primary network would not affect the operation of the OOB passive interface devices **400**, and therefore, the OOB network may continue to operate. The passive characteristics of the OOB passive interface devices **400** may allow the networks to operate in different security domains, even though the OOB passive interface devices **400** have an operational role in both the primary and the OOB networks.

(43) Additionally, according to some example embodiments, the OOB passive interface device **400** may be configured to operate within a power-over-Ethernet (PoE) context. In this regard, a number of different PoE standards have been defined for use in powering devices directly from the Ethernet or twisted-pair cabling. PoE introduces power onto the twisted-pairs in a manner that does not create a differential between the conductors of the twisted-pairs. However, according to some example embodiments, the OOB passive interface device **400** may be configured to inject the OOB signaling between the twisted-pairs as described herein, regardless of whether a non-differential offset for PoE is present on the twisted-pair cabling. Accordingly, the OOB network may be implemented as described herein in the context of a PoE system that uses, for example, PoE Mode A or Mode B.

(44) Now referring to FIG. 5, a system **500** is shown that includes a primary network and an OOB network similar to the configuration shown in FIG. 2. However, FIG. 5 illustrates example signaling that may be present within the system **500**. The system **500** includes a two twisted-pair cabling configuration. A first twisted-pair includes twisted-pair segments **502**, **506**, and **508**. A second twisted-pair includes twisted-pair segments **504**, **505**, and **507**. These twisted-pairs are connected from the primary signal transmitter **510** to the OOB passive interface device **535**, to the OOB passive interface device **545**, to the primary signal receiver **520**. An OOB signal transmitter **530** is connected to the OOB passive interface device **535**, and an OOB signal receiver **540** is connected to the OOB passive interface device **545**. The OOB passive interface devices **535** and **545** may be constructed and configured to operate in the same or similar manner as the OOB passive interface device **400**.

(45) With respect to the example operational scenario shown in FIG. 5, it can be seen that a first primary network signal (e.g., a data signal) is being transmitted by the primary signal transmitter **510** onto the twisted-pair segment **504** of the second twisted-pair. A differential measurement of the primary network signal between the conductors of the twisted-pair segment **504** is shown at graph **551**. Although not shown, a second primary network signal is also applied by the primary signal transmitter **510** to the twisted-pair segment **502** of the first twisted-pair.

(46) The first primary network signal on the twisted-pair segment **504** and the second primary network signal on the twisted-pair segment **502** may be received by the OOB passive interface device **535**. The OOB passive interface device **535** may also receive an OOB signal from the OOB signal transmitter **530**. A differential measurement of the OOB signal between the conductors from the OOB signal transmitter **530** is shown at graph **552**. The OOB passive interface device **535** may be configured to inject the OOB signal as a differential signal between the first twisted-pair and the second twisted-pair (e.g., on centertap transformers of the OOB passive interface device).

Accordingly, a measurement of the centertap differential between the first twisted-pair at segment **505** and second twisted-pair at segment **506** is shown at graph **553**. As can be seen, the measurement of the OOB signal in graph **552** is the same as the signal shown in graph **553** indicating that the OOB signal has been injected as a differential signal between the first twisted-pair and the second twisted-pair. Additionally, as shown in the graph **554**, a differential measurement of the signal between the conductors of the first twisted-pair at segment **505** is shown. As can be seen, despite the injection of the OOB signal, the signal shown at graph **554** is the same as the first primary network signal shown at graph **551**. Additionally, a single ended measurement may have been taken on the segment **506** and is shown at graph **555**. Because the graph **555** shows a single ended measurement, as opposed to a differential measurement, characteristics of the second primary signal and the OOB signal can be seen.

(47) The OOB passive interface device **545** may receive the signals on the segments **505** and **506** and extract the OOB signal (e.g., via centertap transformers) for provision to the OOB signal receiver **540**. A differential measurement of the signal received between the conductors of the OOB signal receiver **540** shown in graph **556** reveals that the signal is the same as the OOB signal in graph **552** and the centertap differential signal shown in graph **556**. Additionally, a differential measurement between the conductors of the first twisted-pair at **507** shown in graph **557** reveals that the signal on the segment **507** and provided to the primary signal receiver **520** is the same as the first primary signal shown in graph **551**. As such, the first primary (and the second primary signal) and the OOB signal have been transmitted through the system without interference.

(48) FIG. **6A** will now be described, which depicts an example embodiment of an OOB network **600**. The OOB network **600** includes a first OOB passive interface device **610**, a twisted-pair cable **630**, and a second OOB passive interface device **640**. The first OOB passive interface device **610** and the second OOB passive interface device **640** may be configured to operate as two-wire devices that support two-wire communications protocols (e.g., RS-485) on the OOB network **600**. The first OOB passive interface device **610** may include an Ethernet connector **611**, which in turn, may include a transformer bank. The transformer bank of the first OOB passive interface device **610** may include four transformers (i.e., one for each twisted-pair of a connected cable).

Transformers **616**, **617**, **618**, and **619** may be configured to connect to data pairs (or twisted-pairs) **612**, **613**, **614**, and **615**, respectively. The transformers **616**, **617**, **618**, and **619** may also be connected to twisted-pairs **631**, **632**, **633**, and **634** of the cable **630**, respectively. Transformers **617** and **618** may have centertaps **620** and **621**, respectively, that may be connected as a transmit or receive OOB data interface **622**. Accordingly, signals provided to the OOB data interface **622** may be injected onto the twisted-pairs **632** and **633** as a differential signal in combination with the primary signals provided via the data pairs **613** and **614** for provision to the second OOB passive interface device **640**. Alternatively, signals may be extracted via the centertap **620** and **621** from the twisted-pairs **632** and **633** as a differential signal and provided as an output via the OOB data interface **622**.

(49) The second OOB passive interface device **640** may include an Ethernet connector **641**, which in turn, may include a transformer bank. The transformer bank of the second OOB passive interface device **640** may include four transformers (i.e., one for each twisted-pair of a connected cable). Transformers **646**, **647**, **648**, and **649** may be configured to connect to data pairs (or twisted-pairs) **642**, **643**, **644**, and **645**, respectively. The transformers **646**, **647**, **648**, and **649** may also be connected to twisted-pairs **631**, **632**, **633**, and **634** of the cable **630**, respectively. Transformers **647** and **648** may have centertaps **650** and **651**, respectively, that may be connected as a transmit or receive OOB data interface **652**. Accordingly, signals provided to the OOB data interface **652** may be injected onto the twisted-pairs **632** and **633** as a differential signal in combination with the primary signals provided via the data pairs **643** and **644** for provision to the first OOB passive interface device **610**. Alternatively, signals may be extracted via the centertap **650** and **651** from the twisted-pairs **632** and **633** as a differential signal and provided as an output via the OOB data

interface **652**.

(50) While the example embodiment shown in FIG. **6A** indicates that the twisted-pairs **632** and **633** are used to support operation of the OOB network **600**, it is understood that the centertaps of any two transformers, connected to any two corresponding twisted-pairs, may be used to support the operation of the OOB network **600** to support a two-wire communications protocol. For example, a centertap of transformer **616** may be used in conjunction with a centertap of transformer **619**. Additionally, when the cabling of the system includes four twisted-pairs, two OOB networks or channels may be implemented on respective sets of twisted-pairs (i.e., with two twisted-pairs in each set) where each set operates in according with a two-wire communications protocol. In this regard, the configuration as shown in FIG. **6A** may be implemented to operate a first OOB network on twisted-pairs **632** and **633**. However, a second OOB network may also be implemented using, for example, a centertap of transformer **616** and a centertap of transformer **619** to operate the second OOB network on twisted-pairs **631** and **634**. In such a configuration, for example, two separate serial signaling channels may be implemented that use a two-wire protocol (e.g., RS-485).

(51) Referring now to FIG. **6B**, another example embodiment of an OOB network **601** is shown. The OOB network **601** includes a first OOB passive interface device **660**, the twisted-pair cable **630**, and a second OOB passive interface device **661**. The first OOB passive interface device **660** and the second OOB passive interface device **661** may be configured to operate as four-wire devices that support four-wire communications protocols (e.g., RS-232) on the OOB network **601**. In this regard, the first OOB passive interface device **660** and the second OOB passive interface device **661** may be constructed and connected in a similar manner as the first OOB passive interface device **610** and the second OOB passive interface device **640** shown in FIG. **6A**. However, the OOB data interface **662** of the first OOB passive interface device **660** may have four connections with one to each of the centertaps of the transformers **616**, **617**, **618**, and **619**. Similarly, the OOB data interface **663** of the second OOB passive interface device **661** may have four connections with one to each of the centertaps of the transformers **646**, **647**, **648**, and **649**. Since the transformers **616**, **617**, **618**, and **619**, and the transformers **646**, **647**, **648**, and **649** are connected to twisted-pairs **631**, **632**, **633**, and **634**, respectively, four-wire communications protocols can be implemented using all four of the twisted-pairs of the cable **630**. Accordingly, signals provided to the OOB data interface **662** may be injected onto the twisted-pairs **631**, **632**, **633**, and **634** in combination with the primary signals provided via the data pairs **612**, **613**, **614**, and **615** for provision to the second OOB passive interface device **661**. Alternatively, signals may be extracted via the centertaps of the transformers **646**, **647**, **648**, and **649** and provided as an output via the OOB data interface **663** as a four-wire protocol signal.

(52) FIG. **7** includes a graph **700** illustrating an OOB network signal **710** and a twisted-pair differential signal **720**. The twisted-pair differential signal **720** includes the injected OOB network signal **710**, but because the signal is applied via a centertap transformer, the OOB signal injects no differential on the twisted-pair differential signal **720**. As can be seen in region **730**, despite the changes in the voltage of the OOB network signal **710**, no effect can be seen on the twisted-pair differential signal **720**. Accordingly, this again shows that the injection of the OOB network signal does not create interference with a primary network signal.

(53) Now referring to FIG. **8**, an assembly **800** is shown that includes a dual network device **810**. According to some example embodiments, the dual network device may include processing circuitry **820**, a primary network interface **830** and an OOB network interface **840**. The dual network device **810** may be connected to an OOB passive interface device **860** via a twisted-pair cable **870** and an OOB connection **880**. The OOB passive interface device **860** may be connected to a twisted-pair cable **850**.

(54) The twisted-pair cable **850** may include signaling in the form of a combined signal with a primary network signal and an OOB network signal. The OOB network signal may have been injected onto the twisted-pair cable **850** as a differential signal between the centertaps of the two

sets of twisted-pairs with the primary network signal. As described above, the OOB passive interface device **860** may extract the OOB signal and provide the OOB signal to the processing circuitry **820** via the OOB network interface **840**. The OOB passive interface device **860** may also pass the primary network signal, after extraction of the OOB network signal, to the processing circuitry **820** via the primary network interface **830**.

(55) According to some example embodiments, the processing circuitry **820** may include a software-configured processing device that executes instructions stored in a memory or a hardware configured processing device, such as an application specific integrated circuit (ASIC) or a field programmable gate array (FPGA). In either case, the processing circuitry **820** may be configured to perform a signal integrity check between the received OOB network signal and the primary network signal. In this regard, another dual network device may have sent redundant operational instructions to the dual network device **810** via both the primary network and the OOB network. Since the networks operate separately, the same instructions should be received by the dual network device **810** via each of the primary network and the OOB network. If the instructions are different, then an assumption can be made that one of the networks has been attacked, and further communications are unreliable. As such, the processing circuitry **820** may be configured to compare the instructions received in the primary network signal and the instructions received in the OOB network signal to make a security assessment.

(56) Alternatively, such a dual network device **810** may be configured to operate by leveraging both the primary network and the OOB network. In this regard, for example, the primary network may be used as a data channel (e.g., for video data). The OOB network may be used as a command and control channel for transmitting operational instructions.

(57) With reference now to FIG. **9**, an example embodiment in the form of a method for implementing an out-of-band (OOB) network is provided in association with a flowchart. According to some example embodiments, elements of the example method may be implemented by a OOB passive interface device, as described herein. In this regard, the example method may include, at **900**, receiving first communications protocol signals via a receiving twisted-pair cable. At **910**, the example method may include receiving second communications protocol signals at an OOB communications protocol port. Further, at **920**, the example method may include injecting the second communications protocol signal, as a differential signal, between a first twisted-pair and a second twisted-pair, with the first communications protocol signals. Finally, at **930**, the example method may include transmitting the first communications protocol signals with the second communications protocol signals via the first twisted-pair and the second twisted-pair on a transmitting twisted-pair cable.

(58) According to some example embodiments, injecting the second communications protocol signals may include injecting the second communications protocol signals onto centertaps of a first transformer and a second transformer. In this regard, the first transformer and second transformer may be connected to the receiving twisted-pair cable and the transmitting twisted-pair cable. Further, according to some example embodiments, the example method may include additional operations. In this regard, the example method may further include receiving the first communications protocol signals with the second communications protocol signals (e.g., at a second OOB passive interface device), removing the second communications protocol signals for provision of the second communications protocol signals to an OOB network node, and passing the first communications protocol signals, unaffected by the injection of the second communications protocol signals, to a primary network node.

(59) Additional example embodiments will now be described. According to some example embodiments, a communications system is provided. The communications system may include a primary network communicating in accordance with a first communications protocol. The primary network may include a first primary network node and a second primary network node. The first primary network node and the second primary network node may be connected via a twisted-pair

cable. The first primary network node may be configured to transmit first communications protocol signals on the twisted-pair cable to the second primary network node. The communications system may also include an out-of-band (OOB) network communicating in accordance with a second communications protocol. The OOB network may include a first OOB network node and a second OOB network node. The first OOB network node may be connected to the twisted-pair cable via a first OOB passive interface device that is connected between the first primary network node and the second primary network node. The second OOB network node may be connected to the twisted-pair cable via a second OOB passive interface device that is connected between the first primary network node and the second primary network node. The first OOB passive interface device may be configured to receive second communications protocol signals from the first OOB network node and inject the second communications protocol signals onto the twisted-pair cable with the first communications protocol signals. The second OOB network node may be configured to receive and extract the injected second communications protocol signals from the twisted pair cable for provision to the second OOB network node. Extraction of the injected second communications protocol signals may be performed such that the first communications protocol signals are received by the second primary network node unaffected by the injection of the second communications protocol signals.

(60) According to some example embodiments, the twisted-pair cable may include a plurality of twisted pairs. The plurality of twisted pairs may include a first twisted pair and a second twisted pair. The first OOB passive interface device may be configured to inject the second communications protocol signals as a differential signal between the first twisted pair and the second twisted pair. According to some example embodiments, the first OOB passive interface device may be configured to inject the second communications protocol signals as a differential signal between the first twisted pair and the second twisted pair. The differential signal may be applied to the first twisted pair such that no differential voltage is introduced between signals on each of the wires of the first twisted pair. The differential signal may be applied to the second twisted pair such that no differential voltage is introduced between signals on each of the wires of the second twisted pair. According to some example embodiments, the first OOB passive interface device may include a first transformer coupled to the first twisted pair and a second transformer coupled to the second twisted pair. The first OOB passive interface device may be configured to inject the second communications protocol signals as a differential signal on a centertap of first transformer and a centertap of the second transformer. According to some example embodiments, the second OOB passive interface device may include a third transformer coupled to the first twisted pair and a fourth transformer coupled to the second twisted pair. The second OOB passive interface device may be configured to receive and extract the second communications protocol signals as a differential signal from a centertap of third transformer and a centertap of the fourth transformer. According to some example embodiments, the twisted-pair cable may include a first portion and a second portion. A third primary network node may be connected between the first portion and the second portion of the twisted-pair cable. The first OOB passive interface device and a third OOB passive interface device may be connected to the first portion of the twisted-pair cable. The second OOB passive interface device and a fourth OOB passive interface device may be connected to the second portion of the twisted-pair cable. The OOB network may further include an OOB bridge connection that bridges over the third primary network node from the third OOB passive interface device to the fourth OOB passive interface device. According to some example embodiments, the second communications protocol may be a serial communications protocol. According to some example embodiments, the second primary network node and the second OOB network node may be housed within a dual protocol device. The dual protocol device may be configured to compare a first communication received via the first communications protocol signals with a second communication received via the second communications protocol signals. According to some example embodiments, the primary network may be disposed within a first

security domain and the OOB network may be disposed with a second security domain. According to some example embodiments, wherein the OOB network is configured to continue to operate when a non-physical layer failure of the primary network occurs.

(61) According to some example embodiments, an out-of-band (OOB) passive interface device is provided. The OOB passive interface device may include a first Ethernet port, a second Ethernet port, and an OOB communications protocol port. The OOB passive interface device may also include a first transformer and a second transformer. A first pair of conductors from the first Ethernet port may be connected to first terminals of the first transformer and a second pair of conductors from the second Ethernet port may be connected to second terminals of the first transformer. A third pair of conductors from the first Ethernet port may be connected to first terminals of the second transformer and a fourth pair of conductors from the second Ethernet port may be connected to second terminals of the second transformer. A first OOB interface conductor may be connected from a centertap of the first transformer to the OOB communication protocol port. A second OOB interface conductor may be connected from a centertap of the second transformer to the OOB communication protocol port.

(62) According to some example embodiments, the OOB communications protocol port may be configured to receive OOB communications protocol signals to be injected as a differential signal onto the centertap of the first transformer and the centertap of the second transformer. According to some example embodiments, the OOB communications protocol port may be configured to receive OOB communications protocol signals from the centertap of the first transformer and the centertap of the second transformer for provision to an external OOB network node via a connection to the OOB communications protocol port. According to some example embodiments, the OOB communications protocol port may be configured to receive OOB communications protocol signals as serial communications signals to be injected as a differential signal onto the centertap of the first transformer and the centertap of the second transformer. The OOB communications protocol port may be configured to receive OOB communications protocol signals as serial communications signals for provision to an external OOB network node via a connection to the OOB communications protocol port. According to some example embodiments, the first transformer and the second transformer are 1:1 transformers and have a 1:1 turns ratio. According to some example embodiments, the first Ethernet port and the second Ethernet port may be configured to couple with twisted-pair cables. According to some example embodiments, the OOB passive interface device does not include a processing device.

(63) Many modifications and other embodiments of the inventions set forth herein will come to mind to one skilled in the art to which these inventions pertain having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is to be understood that the inventions are not to be limited to the specific embodiments disclosed and that modifications and other embodiments are intended to be included within the scope of the appended claims. Moreover, although the foregoing descriptions and the associated drawings describe exemplary embodiments in the context of certain exemplary combinations of elements and/or functions, it should be appreciated that different combinations of elements and/or functions may be provided by alternative embodiments without departing from the scope of the appended claims. In this regard, for example, different combinations of elements and/or functions than those explicitly described above are also contemplated as may be set forth in some of the appended claims. In cases where advantages, benefits or solutions to problems are described herein, it should be appreciated that such advantages, benefits and/or solutions may be applicable to some example embodiments, but not necessarily all example embodiments. Thus, any advantages, benefits or solutions described herein should not be thought of as being critical, required or essential to all embodiments or to that which is claimed herein. Although specific terms are employed herein, they are used in a generic and descriptive sense only and not for purposes of limitation.



## Claims

1. A communications system comprising: a primary network communicating in accordance with a first communications protocol, the primary network comprising a first primary network node and a second primary network node, the first primary network node and the second primary network node being connected via a twisted-pair cable, the first primary network node being configured to transmit first communications protocol signals on the twisted-pair cable to the second primary network node; and an out-of-band (OOB) network communicating in accordance with a second communications protocol, the OOB network comprising a first OOB network node and a second OOB network node, the first OOB network node being connected to the twisted-pair cable via a first OOB passive interface device that is connected between the first primary network node and the second primary network node, the second OOB network node being connected to the twisted-pair cable via a second OOB passive interface device that is connected between the first primary network node and the second primary network node, wherein the first OOB passive interface device is configured to receive second communications protocol signals from the first OOB network node and inject the second communications protocol signals onto the twisted-pair cable with the first communications protocol signals, and wherein the second OOB network node is configured to receive and extract the injected second communications protocol signals from the twisted pair cable for provision to the second OOB network node, wherein extraction of the injected second communications protocol signals is performed such that the first communications protocol signals are received by the second primary network node unaffected by the injection of the second communications protocol signals.
2. The communications system of claim 1, wherein the twisted-pair cable comprises a plurality of twisted pairs, the plurality of twisted pairs comprising a first twisted pair and a second twisted pair, and the first OOB passive interface device is configured to inject the second communications protocol signals as a differential signal between the first twisted pair and the second twisted pair.
3. The communications system of claim 1, wherein the twisted-pair cable comprises a plurality of twisted pairs, the plurality of twisted pairs comprising a first twisted pair and a second twisted pair, the first OOB passive interface device is configured to inject the second communications protocol signals as a differential signal between the first twisted pair and the second twisted pair, the differential signal is applied to the first twisted pair such that no differential voltage is introduced between signals on each wire of the first twisted pair, and the differential signal is applied to the second twisted pair such that no differential voltage is introduced between signals on each wire of the second twisted pair.
4. The communications system of claim 1, wherein the twisted-pair cable comprises a plurality of twisted pairs, the plurality of twisted pairs comprising a first twisted pair and a second twisted pair, the first OOB passive interface device comprises a first transformer coupled to the first twisted pair and a second transformer coupled to the second twisted pair, and the first OOB passive interface device is configured to inject the second communications protocol signals as a differential signal on a centertap of first transformer and a centertap of the second transformer.
5. The communications system of claim 4, wherein the second OOB passive interface device comprises a third transformer coupled to the first twisted pair and a fourth transformer coupled to the second twisted pair, and the second OOB passive interface device is configured to receive and extract the second communications protocol signals as a differential signal from a centertap of third transformer and a centertap of the fourth transformer.
6. The communications system of claim 1, wherein the twisted pair cable comprises a first portion and a second portion, a third primary network node is connected between the first portion and the second portion of the twisted-pair cable, the first OOB passive interface device and a third OOB passive interface device are connected to the first portion of the twisted-pair cable, the second OOB

passive interface device and a fourth OOB passive interface device are connected to the second portion of the twisted-pair cable, and the OOB network further comprises an OOB bridge connection that bridges over the third primary network node from the third OOB passive interface device to the fourth OOB passive interface device.

7. The communications system of claim 1, wherein the second communications protocol is a serial communications protocol.

8. The communications system of claim 1, wherein the second primary network node and the second OOB network node are housed within a dual protocol device, and the dual protocol device is configured to compare a first communication received via the first communications protocol signals with a second communication received via the second communications protocol signals.

9. The communications system of claim 1, wherein the primary network is disposed within a first security domain and the OOB network is disposed with a second security domain.

10. The communications system of claim 1, wherein the OOB network is configured to continue to operate when a non-physical layer failure of the primary network occurs.

11. An out-of-band (OOB) passive interface device comprising: a first Ethernet port; a second Ethernet port; an OOB communications protocol port; a first transformer; and a second transformer, wherein a first pair of conductors from the first Ethernet port are connected to first terminals of the first transformer and a second pair of conductors from the second Ethernet port are connected to second terminals of the first transformer, wherein a third pair of conductors from the first Ethernet port are connected to first terminals of the second transformer and a fourth pair of conductors from the second Ethernet port are connected to second terminals of the second transformer, wherein a first OOB interface conductor is connected from a centertap of the first transformer to the OOB communications protocol port, and wherein a second OOB interface conductor is connected from a centertap of the second transformer to the OOB communications protocol port; wherein the connection to the centertap of the first transformer and the connection to the centertap of the second transformer are configured to inject OOB communications protocol signals received at OOB communications protocol port, as differential signals, between the first pair of conductors from the first Ethernet port and the third pair of conductors from the first Ethernet port, with first communications protocol signals received at the first Ethernet, the first communications protocol signals with the injected OOB communications protocol signals being provided to the second Ethernet port for transmitting; and wherein the connection to the centertap of the first transformer and the connection to the centertap of the second transformer are also configured to extract, from first communications protocol signals with injected OOB communications protocol signals received at the second Ethernet port, OOB communications protocol signals for provision to the OOB communications protocol port and provide first communications protocol signals, unaffected by the injection of the OOB communications protocol signals, to the first Ethernet port.

12. The out-of-band (OOB) passive interface device of claim 11, wherein the OOB communications protocol port is configured to receive OOB communications protocol signals to be injected as the differential signals onto the centertap of the first transformer and the centertap of the second transformer.

13. The out-of-band (OOB) passive interface device of claim 11, wherein the OOB communications protocol port is configured to receive OOB communications protocol signals from the centertap of the first transformer and the centertap of the second transformer for provision to an external OOB network node via a connection to the OOB communications protocol port.

14. The out-of-band (OOB) passive interface device of claim 11, wherein the OOB communications protocol port is configured to receive OOB communications protocol signals as serial communications signals to be injected as the differential signals onto the centertap of the first transformer and the centertap of the second transformer, and the OOB communications protocol port is configured to receive OOB communications protocol signals as serial communications

signals for provision to an external OOB network node via the connections to the centertap of the first transformer and the centertap of the second transformer.

15. The out-of-band (OOB) passive interface device of claim 11, wherein the first transformer and the second transformer have a 1:1 turns ratio.

16. The out-of-band (OOB) passive interface device of claim 11, wherein the first Ethernet port and the second Ethernet port may be configured to couple with twisted-pair cables.

17. The out-of-band (OOB) passive interface device of claim 11, wherein the OOB passive interface device does not comprise a processing device.

18. A method for implementing an out-of-band (OOB) network, the method comprising: receiving first communications protocol signals via a receiving twisted-pair cable; receiving a second communications protocol signals at an OOB communications protocol port; injecting the second communications protocol signals, as differential signals, between a first twisted-pair and a second twisted-pair, with the first communications protocol signals; transmitting the first communications protocol signals with the second communications protocol signals via the first twisted-pair and the second twisted-pair on a transmitting twisted-pair cable; receiving the first communications protocol signals with the second communications protocol signals; removing the second communications protocol signals for provision of the second communications protocol signals to an OOB network node; and passing the first communications protocol signals, unaffected by the injection of the second communications protocol signals, to a primary network node.

19. The method of claim 18, wherein the injecting the second communications protocol signals comprises injecting the second communications protocol signals onto centertaps of a first transformer and a second transformer, the first transformer and second transformer being connected to the receiving twisted-pair cable and the transmitting twisted-pair cable.

---