

US012388492B2

## (12) United States Patent

## Adest et al.

## (54) SAFETY MECHANISMS, WAKE UP AND SHUTDOWN METHODS IN DISTRIBUTED POWER INSTALLATIONS

(71) Applicant: Solaredge Technologies Ltd., Herzeliya (IL)

(72) Inventors: Meir Adest, Modiin (IL); Guy Sella,
Bitan Aharon (IL); Lior Handelsman,
Givatayim (IL); Yoav Galin, Raanana
(IL); Amir Fishelov, Tel Aviv (IL);
Meir Gazit, Ashkelon (IL); Yaron

Binder, Shoham (IL)

(73) Assignee: Solaredge Technologies Ltd., Herzeliya

(IL)

(\*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-

claimer.

(21) Appl. No.: 18/538,061

(22) Filed: **Dec. 13, 2023** 

(65) Prior Publication Data

US 2024/0250716 A1 Jul. 25, 2024

## Related U.S. Application Data

- (63) Continuation of application No. 15/369,881, filed on Dec. 5, 2016, now Pat. No. 11,888,387, which is a (Continued)
- (51) Int. Cl. H04B 3/00 (2006.01) G01S 3/786 (2006.01) (Continued)

(Continued)

## (10) Patent No.: US 12.388.492 B2

(45) **Date of Patent:** \*Aug. 12, 2025

#### (58) Field of Classification Search

CPC ..... H02J 1/10; H02J 3/38; H02M 1/32; G01S

See application file for complete search history.

## (56) References Cited

### U.S. PATENT DOCUMENTS

2,367,925 A 1/1945 Brown 2,586,804 A 2/1952 Fluke (Continued)

### FOREIGN PATENT DOCUMENTS

AU 2073800 A 9/2000 AU 2005262278 A1 1/2006 (Continued)

#### OTHER PUBLICATIONS

Mar. 4-8, 2001—Andersen Gert, et al.,—Aalborg University, Institute of Energy Technology, Denmark—"Currect Programmed Control of a Single Phase Two-Switch Buck-Boost Power Factor Correction Circut"—Applied Power Electronics Conference and Exposition, 2001. APEC 2001. Sixteenth Annual IEEE.


(Continued)

Primary Examiner — Adi Amrany (74) Attorney, Agent, or Firm — Banner & Witcoff, Ltd.

## (57) ABSTRACT

A distributed power system including multiple DC power sources and multiple power modules. The power modules include inputs coupled respectively to the DC power sources and outputs coupled in series to form a serial string. An inverter is coupled to the serial string. The inverter converts power input from the serial string to output power. A signaling mechanism between the inverter and the power module is adapted for controlling operation of the power modules. Also, for a protection method in the distributed power system, when the inverter stops production of the output power, each of the power modules is shut down and thereby the power input to the inverter is ceased.

## 24 Claims, 15 Drawing Sheets



## Related U.S. Application Data

continuation-in-part of application No. 13/372,009, filed on Feb. 13, 2012, now Pat. No. 9,590,526, which is a continuation of application No. 12/329,525, filed on Dec. 5, 2008, now Pat. No. 8,531,055, which is a continuation-in-part of application No. 11/950,271, filed on Dec. 4, 2007, now Pat. No. 9,088,178, said application No. 15/369,881 is a continuation-in-part of application No. 14/323,531, filed on Jul. 3, 2014, now Pat. No. 9,960,667, which is a continuation of application No. 12/328,742, filed on Dec. 4, 2008, now Pat. No. 8,816,535, which is a continuation-in-part of application No. 11/950,271, filed on Dec. 4, 2007, now Pat. No. 9,088,178.

(60) Provisional application No. 60/992,589, filed on Dec. 5, 2007, provisional application No. 60/916,815, filed on May 9, 2007, provisional application No. 60/908,095, filed on Mar. 26, 2007, provisional application No. 60/868,962, filed on Dec. 7, 2006, provisional application No. 60/868,851, filed on Dec. 6, 2006, provisional application No. 60/868,893, filed on Dec. 6, 2006.

```
(51) Int. Cl.
     H02H 3/20
                          (2006.01)
     H02J 1/10
                          (2006.01)
     H02J 3/38
                          (2006.01)
     H02J 3/46
                          (2006.01)
     H02M 1/32
                          (2007.01)
     H02M 3/158
                          (2006.01)
     H02M 7/493
                          (2007.01)
     H04B 3/54
                          (2006.01)
     H10F 77/00
                          (2025.01)
                          (2006.01)
     H02J 7/35
     H02M 1/00
                          (2006.01)
(52)
```

## (56) References Cited

## U.S. PATENT DOCUMENTS

2,758,219 A	8/1956	Miller
2,852,721 A	9/1958	Harders et al.
2.958.171 A	11/1960	Deckers
3.369.210 A	2/1968	Manickella
3.380.035 A	4/1968	Hecker
3,392,326 A	7/1968	Lamberton
3,496,029 A	2/1970	King et al.
3,566,143 A	2/1971	Paine et al.
3,569,784 A	3/1971	Carroll et al.
3,643,564 A	2/1972	Uchiyama
3,696,286 A	10/1972	Ule
3,740,652 A	6/1973	Burgener
3,958,136 A	5/1976	Schroeder
3,982,105 A	9/1976	Eberle
4.060.757 A	11/1977	McMurray
4,101,816 A	7/1978	Shepter
4,104,687 A	8/1978	Zulaski
4,127,797 A	11/1978	Perper
4,129,788 A	12/1978	Chavannes

4,129,823 A	12/1978	van der Pool et al.
4,146,785 A	3/1979	Neale
		Bates
	7/1979	
4,171,861 A	10/1979	Hohorst
4,183,079 A	1/1980	Wachi
4,253,764 A	3/1981	Morrill
4,257,087 A	3/1981	Cuk
/ /		
4,296,461 A	10/1981	Mallory et al.
4,321,581 A	3/1982	Tappeiner et al.
4,324,225 A	4/1982	Trihey
4,327,318 A	4/1982	Kwon et al.
4.246.241 A		
4,346,341 A	8/1982	Blackburn et al.
4,363,040 A	12/1982	Inose
4,367,557 A	1/1983	Stern et al.
4,375,662 A	3/1983	Baker
	5/1983	
· · · · · · · · · · · · · · · · · · ·		Rippel
4,404,472 A	9/1983	Steigerwald
4,412,142 A	10/1983	Ragonese et al.
4,452,867 A	6/1984	Conforti
4,453,207 A	6/1984	Paul
4,460,232 A	7/1984	Sotolongo
4,470,213 A	9/1984	Thompson
4,479,175 A	10/1984	Gille et al.
4,481,654 A	11/1984	Daniels et al.
4,488,136 A	12/1984	Hansen et al.
4,526,553 A	7/1985	Guerrero
4,533,986 A	8/1985	Jones
4,545,997 A	10/1985	Wong et al.
, ,	10/1985	Kissel
4,554,502 A	11/1985	Rohatyn
4,554,515 A	11/1985	Burson et al.
4,580,090 A	4/1986	Bailey et al.
, ,	5/1986	Dickerson
4,598,330 A	7/1986	Woodworth
4,602,322 A	7/1986	Merrick
4,604,567 A	8/1986	Chetty
4,611,090 A	9/1986	Catella et al.
4,623,753 A	11/1986	Feldman et al
4,626,983 A	12/1986	Harada et al.
4,631,565 A	12/1986	Tihanyi
4,637,677 A	1/1987	Barkus
	1/1987	Gallios et al.
4,641,042 A	2/1987	Miyazawa
4,641,079 A	2/1987	Kato et al.
4,644,458 A	2/1987	Harafuji et al.
4,649,334 A	3/1987	Nakajima
4,652,770 A	3/1987	Kumano
4,683,529 A	7/1987	Bucher, II
4,685,040 A	8/1987	Steigerwald et al.
4,686,617 A	8/1987	Colton
, ,		
4,706,181 A	11/1987	Mercer
4,719,553 A	1/1988	Hinckley
4,720,667 A	1/1988	Lee et al.
4,720,668 A	1/1988	Lee et al.
4,736,151 A	4/1988	Dishner
		Ma et al.
4,746,879 A	5/1988	
4,772,994 A	9/1988	Harada et al.
4,783,728 A	11/1988	Hoffman
4,797,803 A	1/1989	Carroll
4,819,121 A	4/1989	Saito et al.
RE33,057 E	9/1989	Clegg et al.
4,864,213 A	9/1989	Kido
4,868,379 A	9/1989	West
4,873,480 A	10/1989	Lafferty
4,888,063 A	12/1989	Powell
4,888,702 A	12/1989	Gerken et al.
4,899,246 A	2/1990	Tripodi
4,899,269 A	2/1990	Rouzies
4,903,851 A	2/1990	Slough
4,906,859 A	3/1990	Kobayashi et al.
4,910,518 A	3/1990	Kim et al.
4,951,117 A	8/1990	Kasai
4,978,870 A	12/1990	Chen et al.
4,987,360 A	1/1991	Thompson
5,001,415 A	3/1991	Watkinson
5,027,051 A	6/1991	Lafferty
5,027,059 A	6/1991	de Montgolfier et al.
5,041,739 A	8/1991	Goto
5,045,988 A	9/1991	Gritter et al.
2,072,200 A	ン/エププエ	ornior of ar.

(56)		1	Referen	ces Cited	5,734,565			Mueller et al.
	Ţ	IQ D	ATENIT	DOCUMENTS	5,747,967 5,751,120			Muljadi et al. Zeitler et al.
	,	J.G. 12	ALLINI	DOCUMENTS	5,773,963			Blanc et al.
5.	054,023	<b>A</b> 1	10/1991	Kronberg	5,777,515	A		Kimura
	081,558		1/1992		5,777,858			Rodulfo
	097,196			Schoneman	5,780,092 5,793,184			Agbo et al. O'Connor
	138,422		8/1992 9/1992	Fujii et al.	5,798,631			Spee et al.
	143,556 144,222		9/1992		5,801,519			Midya et al.
	155,670		10/1992		5,804,894		9/1998	Leeson et al.
	191,519			Kawakami	5,812,045			Ishikawa et al.
	196,781			Jamieson et al.	5,814,970 5,821,734		10/1998	Schmidt Faulk
	210,519 235,266		5/1993 8/1993	Moore Schaffrin	5,822,186			Bull et al.
	237,194			Takahashi	5,838,148			Kurokami et al.
	268,832		12/1993	Kandatsu	5,847,549			Dodson, III
	280,133		1/1994		5,859,772 5,869,956		1/1999	Nagao et al.
	280,232 287,261		1/1994 2/1994	Kohl et al.	5,873,738		2/1999	
	289,361			Vinciarelli	5,886,882			Rodulfo
	289,998			Bingley et al.	5,886,890			Ishida et al.
	327,071			Frederick et al.	5,892,354		4/1999 4/1999	Nagao et al.
	329,222			Gyugyi et al.	5,898,585 5,903,138			Sirichote et al. Hwang et al.
	345,375 379,209		9/1994 1/1995		5,905,645		5/1999	
	381,327		1/1995		5,917,722	A	6/1999	
5,	391,235	A	2/1995	Inoue	5,919,314		7/1999	
	402,060			Erisman	5,923,100 5,923,158			Lukens et al. Kurokami et al.
	404,059 412,558		4/1995 5/1995	Loffler Sakurai et al.	5,929,614			Copple
	412,336			Mutterlein et al.	5,930,128		7/1999	
	428,286		6/1995		5,930,131		7/1999	Feng
	446,645	A		Shirahama et al.	5,932,994			Jo et al.
	460,546			Kunishi et al.	5,933,327 5,945,806		8/1999 8/1999	Leighton et al.
	472,614 475,296		12/1995	Vinsant et al.	5,946,206		8/1999	Shimizu et al.
	477,091			Fiorina et al.	5,949,668		9/1999	Schweighofer
	493,154			Smith et al.	5,955,885		9/1999	
	497,289			Sugishima et al.	5,959,438		9/1999 10/1999	Jovanovic et al. Osborne
	501,083		3/1996		5,961,739 5,963,010			Hayashi et al.
	,504,415 ,504,418		4/1996	Podrazhansky et al.	5,963,078		10/1999	
	504,449			Prentice	5,982,253			
	513,075			Capper et al.	5,986,909		11/1999	Hammond et al.
	517,378			Asplund et al.	5,990,659 6,002,290		11/1999	Frannhagen Avery et al.
	530,335 539,238		6/1996 7/1996	Decker et al.	6,002,603			
	548,504			Takehara	6,008,971		12/1999	Duba et al.
	563,780		10/1996		6,021,052			Unger et al.
	565,855		10/1996		6,031,736		2/2000 3/2000	Takehara et al.
	566,022 576,941			Segev Nguyen et al.	6,037,720 6,038,148		3/2000	Wong et al. Farrington et al.
	580,395			Yoshioka et al.	6,046,470		4/2000	Williams et al.
5,	585,749	A I		Pace et al.	6,046,919	A	4/2000	Madenokouji et al.
	604,430			Decker et al.	6,050,779			Nagao et al.
	616,913		4/1997		6,058,035 6,064,086			Madenokouji et al. Nakagawa et al.
	625,539 631,534		4/1997 5/1997	Nakata et al.	6,078,511			Fasullo et al.
	636,107			Lu et al.	6,081,104	A	6/2000	
5,	644,212	A		Takahashi	6,082,122			Madenokouji et al.
	644,219			Kurokawa	6,087,738 6,091,329			Hammond Newman
	646,501 648,731			Fishman et al. Decker et al.	6,093,885			Takehara et al.
	654,740			Schulha	6,094,129		7/2000	
5,	659,465	A		Flack et al.	6,101,073			Takehara
	677,833		10/1997		6,105,317			Tomiuchi et al.
	684,385 686.766			Guyonneau et al.	6,111,188 6,111,391		8/2000	Kurokami et al. Cullen
	686,766 696,439			Tamechika Presti et al.	6,111,767			Handleman
5.	703,390	A	12/1997		6,127,801		10/2000	
5,	708,576	A	1/1998	Jones et al.	6,130,458			Takagi et al.
	719,758			Nakata et al.	6,150,739			Baumgartl et al.
	722,057 726,505		2/1998		6,151,234 6,163,086		11/2000 12/2000	Oldenkamp
	726,505 726,615		3/1998	Yamada et al.	6,165,086		12/2000	
	731,603			Nakagawa et al.	6,166,527			Dwelley et al.
	734,258		3/1998	Esser	6,169,678	B1		Kondo et al.
5,	734,259	A	3/1998	Sisson et al.	6,175,219	B1	1/2001	Imamura et al.

(56)		Refere	nces Cited	6,603,672			Deng et al.
	TI	I C. DATENII	C DOCUMENTS	6,608,468 6,611,130		8/2003 8/2003	Nagase
	U	.s. Patent	DOCUMENTS	6,611,441			Kurokami et al.
	6,175,512 E	31 1/2001	Hagihara et al.	6,628,011	B2	9/2003	Droppo et al.
	6,191,456 E		Stoisiek et al.	6,633,824			Dollar, II
	6,191,498 E		Chang	6,636,431			Seki et al.
	6,215,286 E		Scoones et al.	6,650,031 6,650,560			Goldack MacDonald et al.
	6,219,623 E 6,222,351 E		Wills Fontanella et al.	6,653,549			Matsushita et al.
	6,225,793 E		Dickmann	6,655,987			Higashikozono et al.
	6,255,360 E	31 7/2001	Domschke et al.	6,657,419			Renyolds
	6,255,804 E		Herniter et al.	6,664,762 6,672,018		1/2003	Shingleton
	6,256,234 E 6,259,234 E		Keeth et al. Perol	6,678,174			Suzui et al.
	6,262,558 E		Weinberg	6,690,590	B2	2/2004	Stamenic et al.
	6,268,559 E		Yamawaki	6,693,327			Priefert et al.
	6,274,804 E		Psyk et al.	6,693,781 6,708,507			Kroker Sem et al.
	6,275,016 E 6,281,485 E		Ivanov	6,709,291			Wallace et al.
	6,285,572 E		Onizuka et al.	6,724,593	В1	4/2004	Smith
	6,291,764 E		Ishida et al.	6,731,136		5/2004	
	6,292,379 E		Edevold et al.	6,738,692 6,744,643			Schienbein et al. Luo et al.
	6,297,621 E		Hui et al.	6,750,391			Bower et al.
	6,301,128 E 6,304,065 E		Jang et al. Wittenbreder	6,765,315			Hammerstrom et al.
	6,307,749 E		Daanen et al.	6,768,047		7/2004	Chang et al.
	6,311,137 E	31 10/2001	Kurokami et al.	6,768,180			Salama et al.
	6,316,716 E		Hilgrath	6,788,033 6,788,146			Vinciarelli Forejt et al.
	6,320,769 E 6,329,808 E		Kurokami et al. Enguent	6,795,318			Haas et al.
	6,331,670 E		Takehara et al.	6,800,964		10/2004	
	6,339,538 E		Handleman	6,801,442			Suzui et al.
	6,344,612 E		Kuwahara et al.	6,807,069			Nieminen et al. Madenokouji et al.
	6,346,451 E		Simpson et al.	6,809,942 6,810,339		10/2004	
	6,348,781 E 6,350,944 E		Midya et al. Sherif et al.	6,812,396			Makita et al.
	6,351,130 E		Preiser et al.	6,828,503			Yoshikawa et al.
	6,369,461 E	31 4/2002	Jungreis et al.	6,828,901	B2		Birchfield et al.
	6,369,462 E			6,835,491 6,837,739	B2 B2		Gartstein et al. Gorringe et al.
	6,380,719 E 6,396,170 E		Underwood et al. Laufenberg et al.	6,838,611			Kondo et al.
	6,396,239 E		Benn et al.	6,838,856		1/2005	Raichle
	6,400,579 E	32 6/2002	Cuk	6,842,354			Tallam et al.
	6,425,248 E		Tonomura et al.	6,844,739 6,850,074			Kasai et al. Adams et al.
	6,429,546 E 6,429,621 E		Ropp et al.	6,856,102			Lin et al.
	6,433,522 E			6,882,131	B1	4/2005	Takada et al.
	6,433,978 E	31 8/2002	Neiger et al.	6,888,728		5/2005	Takagi et al.
	6,441,597 E	8/2002	Lethellier	6,894,911 6,897,370			Telefus et al. Kondo et al.
	6,445,599 E		Nguyen Kimura et al.	6,914,418		7/2005	Sung
	6,448,489 E 6,452,362 E		Choo	6,919,714			Delepaut
	6,452,814 E		Wittenbreder	6,927,955	B2	8/2005	Suzui et al.
	6,465,910 E	32 10/2002	Young et al.	6,933,627 6,933,714			Wilhelm Fasshauer et al.
	6,465,931 E		Knowles et al.	6,936,995			Kapsokavathis et al.
	6,469,919 E 6,472,254 E		Bennett Cantarini et al.	6,940,735			Deng et al.
	6,479,963 E		Manor et al.	6,949,843			Dubovsky
	6,483,203 E		McCormack	6,950,323			Achleitner et al.
	6,493,246 E		Suzui et al.	6,963,147 6,966,184			Kurokami et al. Toyomura et al.
	6,501,362 E 6,507,176 E		Hoffman et al. Wittenbreder, Jr.	6,970,365		11/2005	
	6,509,712 E		Landis	6,980,783	B2	12/2005	Liu et al.
	6,512,444 E	31 1/2003	Morris, Jr. et al.	6,984,967			Notman
	6,515,215 E		Mimura	6,984,970 6,985,967		1/2006 1/2006	
	6,515,217 E 6,519,165 E		Aylaian Koike	6,987,444			Bub et al.
	6,528,977 E		Arakawa	6,996,741	B1	2/2006	Pittelkow et al.
	6,531,848 E	3/2003	Chitsazan et al.	7,030,597			Bruno et al.
	6,545,211 E		Mimura	7,031,176			Kotsopoulos et al.
	6,548,205 E		Leung et al. vonBrethorst	7,038,430 7,039,941			Itabashi et al. Caporizzo et al.
	6,560,131 E 6,587,051 E		Takehara et al.	7,039,941			Tsunetsugu et al.
	6,590,793 E	31 7/2003	Nagao et al.	7,045,991			Nakamura et al.
	6,590,794 E	31 7/2003	Carter	7,046,531	B2	5/2006	Zocchi et al.
	6,593,520 E		Kondo et al.	7,053,506			Alonso et al.
	6,593,521 E		Kobayashi	7,061,211			Satoh et al.
	6,600,100 E	oz //2003	Ho et al.	7,061,214	DΖ	0/2006	Mayega et al.

(56)	Referen	nces Cited	7,485,987 7,495,419		2/2009 2/2009	Mori et al.
U.S.	PATENT	DOCUMENTS	7,504,811			Watanabe et al.
			7,518,346			Prexl et al.
7,064,967 B2		Ichinose et al.	7,538,451 7,560,915			Nomoto Ito et al.
7,068,017 B2 7,072,194 B2		Willner et al. Nayar et al.	7,589,437			Henne et al.
7,072,194 B2 7,078,883 B2		Chapman et al.	7,595,616			Prexl et al.
7,079,406 B2		Kurokami et al.	7,596,008		9/2009	Iwata et al.
7,087,332 B2	8/2006		7,599,200			Tomonaga
7,088,595 B2	8/2006		7,600,349 7,602,080			Liebendorfer Hadar et al.
7,089,780 B2 7,090,509 B1		Sunshine et al. Gilliland et al.	7,602,626			Iwata et al.
7,091,707 B2	8/2006		7,605,498			Ledenev et al.
7,097,516 B2		Werner et al.	7,612,283			Toyomura et al.
7,099,169 B2		West et al.	7,615,981 7,626,834			Wong et al. Chisenga et al.
7,126,053 B2 7,126,294 B2		Kurokami et al. Minami et al.	7,634,667			Weaver et al.
7,138,786 B2		Ishigaki et al.	7,646,116			Batarseh et al.
7,142,997 B1	11/2006		7,649,434			Xu et al.
7,148,669 B2		Maksimovic et al.	7,659,701 7,701,083		4/2010	Metsker et al.
7,150,938 B2 7,157,888 B2		Munshi et al. Chen et al.	7,709,727		5/2010	Roehrig et al.
7,158,359 B2		Bertele et al.	7,719,140	B2	5/2010	Ledenev et al.
7,158,395 B2		Deng et al.	7,723,865			Kitanaka
7,161,082 B2		Matsushita et al.	7,733,069 7,748,175			Toyomura et al. Liebendorfer
7,174,973 B1 7,176,667 B2		Lysaght Chen et al.	7,759,575			Jones et al.
7,170,007 B2 7,183,667 B2	2/2007	Colby et al.	7,763,807	B2	7/2010	Richter
7,193,872 B2	3/2007		7,772,716			Shaver, II et al.
7,202,653 B2	4/2007		7,777,570		8/2010	
7,208,674 B2		Aylaian	7,780,472 7,782,031		8/2010 8/2010	Qiu et al.
7,218,541 B2 7,248,946 B2		Price et al. Bashaw et al.	7,783,389			Yamada et al.
7,256,566 B2		Bhavaraju et al.	7,787,273			Lu et al.
7,259,474 B2	8/2007		7,804,282			Bertele Powell et al
7,262,979 B2		Wai et al.	7,807,919 7,808,125			Powell et al. Sachdeva et al.
7,276,886 B2 7,277,304 B2		Kinder et al. Stancu et al.	7,812,592			Prior et al.
7,281,141 B2		Elkayam et al.	7,812,701			Lee et al.
7,282,814 B2	10/2007	Jacobs	7,821,225			Chou et al.
7,282,924 B1	10/2007		7,824,189 7,839,022		11/2010	Lauermann et al.
7,291,036 B1 7,298,113 B2		Daily et al. Orikasa	7,843,085			Ledenev et al.
RE39,976 E		Schiff et al.	7,864,497			Quardt et al.
7,315,052 B2	1/2008		7,868,599	B2		Rahman et al.
7,319,313 B2		Dickerson et al.	7,880,334 7,883,808	B2 B2		Evans et al. Norimatsu et al.
7,324,361 B2 7,336,004 B2	1/2008 2/2008		7,884,278			Powell et al.
7,336,056 B1		Dening	7,893,346			Nachamkin et al.
7,339,287 B2	3/2008	Jepsen et al.	7,898,112			Powell et al.
7,348,802 B2		Kasanyal et al.	7,900,361 7,906,007			Adest et al. Gibson et al.
7,352,154 B2 7,361,952 B2	4/2008 4/2008	Miura et al.	7,906,870		3/2011	
7,371,963 B2	5/2008	Suenaga et al.	7,919,952	B1		Fahrenbruch
7,372,712 B2		Stancu et al.	7,919,953 7,925,552			Porter et al. Tarbell et al.
7,385,380 B2 7,385,833 B2		Ishigaki et al. Keung	7,944,191		5/2011	
7,388,348 B2		Mattichak	7,945,413	B2	5/2011	Krein
7,391,190 B1		Rajagopalan	7,948,221			Watanabe et al.
7,394,237 B2		Chou et al.	7,952,897 7,960,650			Nocentini et al. Richter et al.
7,405,117 B2 7,414,870 B2		Zuniga et al. Rottger et al.	7,960,950			Glovinsky
7,414,870 B2 7,420,354 B2	9/2008		7,962,249			Zhang H02J 3/381
7,420,815 B2	9/2008	Love				700/297
7,432,691 B2	10/2008		7,969,043			Caraghiorghiopol et al.
7,435,134 B2 7,435,897 B2	10/2008 10/2008		7,969,133 7,977,810			Zhang et al. Choi et al.
7,443,052 B2		Wendt et al.	8,003,885			Richter et al.
7,443,152 B2	10/2008	Utsunomiya	8,004,113			Sander et al.
7,450,401 B2	11/2008	Iida	8,004,116			Ledenev et al.
7,456,510 B2		Ito et al. Kobayashi	8,004,117 8,004,237			Adest et al. Manor et al.
7,456,523 B2 7,463,500 B2	12/2008		8,004,237			Bucella et al.
7,466,566 B2		Fukumoto	8,013,472			Adest et al.
7,471,014 B2	12/2008	Lum et al.	8,018,748	B2		Leonard
7,471,524 B1		Batarseh et al.	8,035,249			Shaver, II et al.
7,479,774 B2		Wai et al.	8,039,730			Hadar et al.
7,482,238 B2	1/2009	Sung	8,049,363	DΖ	11/2011	McLean et al.

(56)		Referen	ces Cited		,017 B2		Perichon et al.
	HS	PATENT	DOCUMENTS		,441 B2 ,151 B2		Rotzoll et al. Adest et al.
	0.5.	TAILINI	DOCOMENTS		,692 B2		Adest et al.
	8,050,804 B2	11/2011	Kernahan		,443 B2		Mumtaz
	8,058,747 B2		Avrutsky et al.		,689 B2 ,675 B2		Rozenboim Capp et al.
	8,058,752 B2 8,067,855 B2		Erickson, Jr. et al. Mumtaz et al.		0,255 B2		Gong et al.
	8,077,437 B2		Mumtaz et al.	8,674	,548 B2	3/2014	Mumtaz
	8,080,986 B2		Lai et al.		,668 B2		Chisenga et al.
	8,089,780 B2		Mochikawa et al.		5,333 B2 5,351 B2		Arditi et al. Robbins
	8,089,785 B2 8,090,548 B2	1/2012	Rodriguez Abdennadher et al.		,053 B2		Hadar et al.
	8,093,756 B2		Porter et al.	8,773	,236 B2		Makhota et al.
	8,093,757 B2	1/2012	Wolfs		,598 B2	7/2014	
	8,097,818 B2		Gerull et al.		5,884 B2 5,699 B2	8/2014 8/2014	Naiknaware et al.
	8,098,055 B2 8,102,074 B2		Avrutsky et al. Hadar et al.		,047 B2		Rodriguez
	8,102,144 B2		Capp et al.		,535 B2		Adest et al.
	8,111,052 B2		Glovinsky		,212 B2		Garrity et al. Hadar et al.
	8,116,103 B2		Zacharias et al.		,218 B2 ,342 B2		Williams
	8,138,631 B2 8,138,914 B2		Allen et al. Wong et al.		,748 B2		Frolov et al.
	8,139,335 B2	3/2012	Quardt et al.		,916 B2		Avrutsky
	8,139,382 B2		Zhang et al.		,397 B2 ,886 B2		Fahrenbruch et al. Avrutsky et al.
	8,148,849 B2 8,158,877 B2		Zanarini et al. Klein et al.		,193 B2		Makhota et al.
	8,169,252 B2		Fahrenbruch et al.	8,859	,884 B2	10/2014	Dunton et al.
	8,179,147 B2	5/2012	Dargatz et al.		,241 B2		Hadar et al.
	8,184,460 B2		O'Brien et al.		,246 B2 ,439 B2	10/2014	Hadar et al.
	8,188,610 B2 8,204,709 B2		Scholte-Wassink Presher, Jr. et al.		5,563 B2	11/2014	
	8,212,408 B2		Fishman	8,917	,156 B2		Garrity et al.
	8,212,409 B2		Bettenwort et al.		,061 B2	1/2014	Ardıtı Hadar et al.
	8,232,790 B2	7/2012 7/2012	Leong et al.		,321 B2 ,269 B2	1/2015	
	8,233,301 B1 8,248,804 B2		Han et al.		,194 B2		Sella et al.
	8,271,599 B2		Eizips et al.		,375 B2		DeGraaff
	8,274,172 B2		Hadar et al.		,378 B1 ,501 B2		Fornage et al. Shigemizu et al.
	8,279,644 B2 8,284,574 B2		Zhang et al. Chapman et al.		,518 B2	2/2015	
	8,289,183 B1	10/2012			,765 B1		Krolak et al.
	8,289,742 B2		Adest et al.		,645 B2 ,339 B2		Arnouse Adest et al.
	8,294,451 B2 8,299,757 B2		Hasenfus Yamauchi et al.		,178 B2		Adest et al.
	8,299,773 B2 8,299,773 B2		Jang et al.	9,130	,401 B2	9/2015	Adest et al.
	8,304,932 B2	11/2012	Ledenev et al.		2,965 B2	9/2015	
	8,310,101 B2		Amaratunga et al.		,848 B2 ,696 B2		Coccia et al. Adest et al.
	8,310,102 B2 8,314,375 B2	11/2012	Arditi et al.		,743 B2		Gazit et al.
	8,319,471 B2		Adest et al.		,497 B2		Ledenev
	8,324,921 B2		Adest et al.		,664 B2 ,161 B2		Perreault et al. Adest et al.
	8,325,059 B2 8,344,548 B2	1/2012	Rozenboim		5,737 B2		Ledenev
	8,355,563 B2		Kasahara et al.	9,577	,454 B2	2/2017	Seymour et al.
	8,369,113 B2		Rodriguez		,442 B2 ,527 B2		Yoscovich et al. Glovinski
	8,378,656 B2	2/2013 2/2013	de Rooij et al.		,630 B2		Ledenev et al.
	8,379,418 B2 8,391,031 B2	3/2013			,178 B2	11/2017	Gazit et al.
	8,391,032 B2		Garrity et al.		,916 B2		Behrends
	8,395,366 B2	3/2013			,193 B2 ,490 B2	12/2017	Getsla Adest et al.
	8,405,248 B2 8,405,349 B2		Mumtaz et al. Kikinis et al.		5,411 B2		Friebe et al.
	8,405,367 B2		Chisenga et al.	9,869	,701 B2		Sella et al.
	8,410,359 B2	4/2013			,516 B2 ,717 B1		Har-Shai et al. Rowe et al.
	8,410,889 B2 8,410,950 B2		Garrity et al. Takehara et al.		,717 B1		Johnson
	8,415,552 B2		Hadar et al.	10,032	,939 B2		Ledenev et al.
	8,415,937 B2	4/2013	Hester	10,256	5,770 B2		Hadar et al.
	8,427,009 B2		Shaver, II et al.		,139 B2 ,159 B1		Chaintreuil et al. Castelaz et al.
	8,436,592 B2 8,461,809 B2	5/2013 6/2013	Saitoh Rodriguez		,139 B1 5,045 B2		Gemin et al.
	8,466,789 B2	6/2013	Muhlberger et al.		,253 B2		Adest et al.
	8,472,220 B2	6/2013	Garrity et al.		,119 B2		Har-Shai et al.
	8,473,250 B2		Adest et al.		,412 B2		Sella et al.
	8,509,032 B2 8,526,205 B2	8/2013 9/2013		· · · · · · · · · · · · · · · · · · ·	5,623 B2 5,946 B2		Loewenstern et al. Yoscovich et al.
	8,531,055 B2		Adest et al.		5,786 B2		Hopf et al.
	8,542,512 B2	9/2013			,799 B2		Sella et al.

(56)		Referen	ces Cited	2004/0027112			Kondo et al.
	U.S.	PATENT	DOCUMENTS	2004/0041548 2004/0056642		3/2004 3/2004	Nebrigic et al.
				2004/0056768			Matsushita et al.
11,682,918			Adest et al.	2004/0061527 2004/0076028		4/2004	Knee Achleitner et al.
11,728,724 2001/0000957			Braginsky et al. Birchfield et al.	2004/00/0028			Kobayashi et al.
2001/0000937			Emori et al.	2004/0118446	A1	6/2004	Toyomura
2001/0013767	A1	8/2001	Takemoto	2004/0123894		7/2004	
2001/0023703			Kondo et al.	2004/0124816 2004/0125618			DeLepaut De Rooij et al.
2001/0032664 2001/0034982			Takehara et al. Nagao et al.	2004/0140719			Vulih et al.
2001/0035180		11/2001	Kimura et al.	2004/0141345			Cheng et al.
2001/0048605		12/2001	Kurokami et al.	2004/0144043 2004/0150410		7/2004 8/2004	
2001/0050102 2001/0054881			Matsumi et al. Watanabe	2004/0130410		8/2004	1
2002/0002040			Kline et al.	2004/0165408		8/2004	West et al.
2002/0014262			Matsushita et al.	2004/0167676			Mizumaki
2002/0017900			Takeda et al.	2004/0169499 2004/0170038			Huang et al. Ichinose et al.
2002/0034083 2002/0038667			Ayyanar et al. Kondo et al.	2004/0189090			Yanagida et al.
2002/0041505			Suzui et al.	2004/0189432			Yan et al.
2002/0044473		4/2002	Toyomura et al.	2004/0201279 2004/0201933		10/2004 10/2004	Templeton Blanc
2002/0047309 2002/0047693		4/2002 4/2002	Droppo et al.	2004/0201933		10/2004	
2002/004/093			Houston	2004/0211456			Brown et al.
2002/0059035			Yagi et al.	2004/0211458			Gui et al.
2002/0063552			Arakawa	2004/0211459 2004/0213169		10/2004 10/2004	Suenaga et al. Allard et al.
2002/0063625 2002/0078991			Takehara et al. Nagao et al.	2004/0213109			Kurokami et al.
2002/00/8991			Conley	2004/0230343	A1	11/2004	Zalesski
2002/0085397		7/2002	Suzui et al.	2004/0233685		11/2004	
2002/0105765			Kondo et al.	2004/0246226 2004/0255999		12/2004 12/2004	
2002/0113689 2002/0118559			Gehlot et al. Kurokami et al.	2004/0258141			Tustison et al.
2002/0127980			Amanullah et al.	2004/0262998			Kunow et al.
2002/0134567			Rasmussen et al.	2004/0263119 2004/0263183			Meyer et al. Naidu et al.
2002/0148497			Sasaoka et al.	2004/0263183			Bhavaraju et al.
2002/0149950 2002/0162585			Takebayashi Sugawara et al.	2005/0002214			Deng et al.
2002/0165458			Carter et al.	2005/0005785			Poss et al.
2002/0177401			Judd et al.	2005/0006958 2005/0017697		1/2005	Dubovsky
2002/0179140 2002/0180408			Toyomura McDaniel et al.	2005/0017701		1/2005	
2002/0180408			Darshan	2005/0030772	A1	2/2005	Phadke
2003/0001709		1/2003		2005/0040800		2/2005	
2003/0002303			Riggio et al.	2005/0041442 2005/0057214		3/2005	Balakrishnan Matan
2003/0025594 2003/0038615			Akiyama et al. Elbanhawy	2005/0057215		3/2005	
2003/0043597			Betts-Lacroix	2005/0068012		3/2005	
2003/0047207			Aylaian	2005/0068820 2005/0077879		3/2005 4/2005	Radosevich et al.
2003/0058593 2003/0058662			Bertele et al. Baudelot et al.	2005/0077879			Wilhelm
2003/0058002			Mimura	2005/0103376		5/2005	Matsushita et al.
2003/0066076			Minahan	2005/0105224		5/2005	
2003/0066555			Hui et al. Makita et al.	2005/0105306 2005/0109386			Deng et al. Marshall
2003/0075211 2003/0080741			LeRow et al.	2005/0110454			Tsai et al.
2003/0085621		5/2003		2005/0121067			Toyomura et al.
2003/0090233		5/2003		2005/0122747 2005/0135031			Gaksch Colby et al.
2003/0090246 2003/0094931			Shenai et al. Renyolds	2005/0139051			Liu et al.
2003/0094931			Fronek et al.	2005/0140335	A1	6/2005	Lee et al.
2003/0107352			Downer et al.	2005/0162018			Realmuto et al.
2003/0111103			Bower et al.	2005/0163063 2005/0172995			Kuchler et al. Rohrig et al.
2003/0116154 2003/0121514			Butler et al. Davenport et al.	2005/0179420		8/2005	Satoh et al.
2003/0127126		7/2003		2005/0191528			Cortes et al.
2003/0140960			Baum et al.	2005/0194937		9/2005	
2003/0156439 2003/0164695			Ohmichi et al. Fasshauer et al.	2005/0201397 2005/0213272		9/2005 9/2005	Kobayashi
2003/0185026			Matsuda et al.	2005/0213272		10/2005	
2003/0193821			Krieger et al.	2005/0225090		10/2005	Wobben
2003/0201674			Droppo et al.	2005/0226017			Kotsopoulos et al.
2003/0206424			Jungreis et al.	2005/0231183		10/2005	
2003/0214274 2003/0223257		11/2003	Lethellier Once	2005/0242795 2005/0248428			Al-Kuran et al. Coleman et al.
2004/0004402			Kippley	2005/0252545			Nowlan et al.
2004/0027101			Vinciarelli et al.	2005/0257827			Gaudiana et al.

(56)	Refere	ences Cited	2007/0089778			Horne et al.
11	I C. DATENI	T DOCUMENTS	2007/0103108 2007/0103297			Capp et al. Armstrong et al.
U	.S. PATEN	T DOCUMENTS	2007/0103297			Hayden et al.
2005/0269988 A	12/200	5 Thrap	2007/0115635			Low et al.
2005/0275386 A		5 Jepsen et al.	2007/0119718			Gibson et al.
2005/0275527 A		5 Kates	2007/0121648		5/2007	
2005/0275979 A			2007/0133241 2007/0133421			Mumtaz et al.
2005/0281064 A		5 Olsen et al.	2007/0133421		6/2007 6/2007	
2005/0286510 A 2005/0287402 A		5 Nakajima et al. 5 Maly et al.	2007/0158185			Andelman et al.
2005/0287402 F		6 Matan	2007/0159866		7/2007	Siri
2006/0017327 A		Siri et al.	2007/0164612			Wendt et al.
2006/0034106 A		5 Johnson	2007/0164750			Chen et al.
2006/0038692 A		5 Schnetker	2007/0165347 2007/0205778			Wendt et al. Fabbro et al.
2006/0043792 A 2006/0043942 A		5 Hjort et al. 5 Cohen	2007/0203778		9/2007	
2006/0043942 F		Krzyzanowski et al.	2007/0211888		9/2007	Corcoran et al.
2006/0055384 A		5 Jordan et al.	2007/0217178			Johnson et al.
2006/0066349 A	A1 3/200	5 Murakami	2007/0223165			Itri et al.
2006/0068239 A		Norimatsu et al.	2007/0227574 2007/0235071		10/2007	Work et al.
2006/0077046 A		5 Endo	2007/0235071			Wai et al.
2006/0085167 A 2006/0091958 A		5 Warfield et al. 5 Bhatti et al.	2007/0241720		10/2007	Sakamoto et al.
2006/0091938 F		5 Cutler	2007/0246546	A1	10/2007	Yoshida
2006/0108979 A		5 Daniel et al.	2007/0247135		10/2007	
2006/0109009 A		5 Banke et al.	2007/0247877			Kwon et al.
2006/0113843 A		6 Beveridge	2007/0262802 2007/0271006			Huard et al. Golden et al.
2006/0113979 A		5 Ishigaki et al. 5 Arisawa	2007/0271000			Steele et al.
2006/0116968 A 2006/0118162 A		5 Arisawa 5 Saelzer et al.	2007/0273339		11/2007	
2006/0125449 A		5 Unger	2007/0273342	A1	11/2007	Kataoka et al.
2006/0132102 A		6 Harvey	2007/0273351		11/2007	
2006/0149396 A		5 Templeton	2007/0284451 2007/0290636			Uramoto Beck et al.
2006/0152085 A		Flett et al. Presher et al.	2007/0290656			Lee Tai Keung
2006/0162772 A 2006/0163946 A		Henne et al.	2008/0021707			Bou-Ghazale et al.
2006/0164065 A		6 Hoouk et al.	2008/0023061			Clemens et al.
2006/0167762 A	<b>A</b> 1 7/200	5 Hahn-Carlson	2008/0024098		1/2008	
2006/0171182 A		5 Siri et al.	2008/0030198 2008/0036440			Kawata et al. Garmer
2006/0174939 A 2006/0176029 A		6 Matan 6 McCintry et al	2008/0030440			Chen et al.
2006/0176029 F		6 McGinty et al. 6 Forman et al.	2008/0055941			Victor et al.
2006/0176036 A		Flatness et al.	2008/0072091			Hanson et al.
2006/0176716 A		5 Balakrishnan et al.	2008/0080177		4/2008	
2006/0185727 A	<b>A1*</b> 8/200	5 Matan H02S 40	2008/0088820		4/2008	Tung et al.
2006/0192540 A	N 1 8/200	136/ 5 Balakrishnan et al.	2008/0089277			Alexander et al.
2006/0192540 A		5 Shinmura et al.	2008/0097655			Hadar et al.
2006/0222912 A		5 Smith	2008/0106250			Prior et al.
2006/0222916 A		Norimatsu et al.	2008/0111529 2008/0115823		5/2008	Shah et al.
2006/0225781 A		5 Locher	2008/0113823			Besser et al.
2006/0227577 A 2006/0227578 A		6 Horiuchi et al. 6 Datta et al.	2008/0122449	A1		Besser et al.
2006/0231132 A		Neussner	2008/0122518			Besser et al.
2006/0232220 A	10/200	5 Melis	2008/0136367			Adest et al.
2006/0235717 A		Sharma et al.	2008/0142071 2008/0143188			Dorn et al. Adest et al.
2006/0237058 A		McClintock et al. Shimotomai	2008/0143462			Belisle et al.
2006/0238750 A 2006/0243318 A		5 Feldmeier et al.	2008/0144294			Adest et al.
2006/0243318 P		6 Okabe et al.	2008/0147335			Adest et al.
2006/0266408 A		6 Horne et al.	2008/0149167		6/2008	
2006/0267515 A		5 Burke et al.	2008/0150366 2008/0150484			Adest et al. Kimball et al.
2006/0290317 A		McNulty et al.	2008/0156551			Kawahara et al.
2007/0001653 A 2007/0013349 A		7 Xu 7 Bassett	2008/0164766			Adest et al.
2007/0019543 A		7 Frezzolini	2008/0179949			Besser et al.
2007/0024257 A		7 Boldo	2008/0186004			Williams
2007/0027644 A		7 Bettenwort et al.	2008/0191560 2008/0191675			Besser et al. Besser et al.
2007/0029468 A		7 Sinton et al. 7 Kanemaru et al.	2008/0191073		8/2008	
2007/0029636 A 2007/0030068 A		7 Kanemaru et al. 7 Motonobu et al.	2008/0192519			Iwata et al.
2007/0035975 A		7 Dickerson et al.	2008/0198523		8/2008	Schmidt et al.
2007/0040540 A	1 2/200	7 Cutler	2008/0205096			Lai et al.
2007/0044837 A		7 Simburger et al.	2008/0218152		9/2008	
2007/0075689 A 2007/0075711 A		7 Kinder et al. 7 Blanc et al.	2008/0224652 2008/0236647			Zhu et al. Gibson et al.
2007/00/3/11 A 2007/0081364 A		7 Bianc et al. 7 Andreycak	2008/0236648			Klein et al.
2007/0081504 P		7 Scoones et al.	2008/0238195			Shaver et al.
		**				

(56)	Referen	nces Cited		2009/0283130			Gilmore et al.	C057-1/67
IIS	PATENT	DOCUMENTS		2009/0284078	A1*	11/2009	Zhang	. G05F 1/67 307/82
0.5.	IAILI	DOCOMENTS		2009/0284232	<b>A</b> 1	11/2009	Zhang et al.	307702
2008/0238372 A1		Cintra et al.		2009/0284240		11/2009	Zhang et al.	
2008/0246460 A1	10/2008			2009/0284998 2009/0295225		12/2009	Zhang et al. Asplund et al.	
2008/0246463 A1 2008/0252273 A1		Sinton et al. Woo et al.		2009/0296434			De Rooij et al.	
2008/0264470 A1		Masuda et al.		2009/0322494	A1	12/2009	Lee	
2008/0266913 A1		Brotto et al.		2009/0325003			Aberle et al.	
2008/0266919 A1		Mallwitz		2010/0001587 2010/0002349			Casey et al. La Scala et al.	
2008/0283118 A1 2008/0291707 A1	11/2008	Rotzoll et al.		2010/0002343			Tang et al.	
2008/0294472 A1		Yamada		2010/0020576	A1	1/2010	Falk	
2008/0297963 A1		Lee et al.		2010/0026097			Avrutsky et al.	
2008/0298608 A1	12/2008 12/2008			2010/0026736 2010/0038907		2/2010	Hunt et al.	
2008/0303503 A1 2008/0304296 A1		NadimpalliRaju et al.		2010/0043781			Jones et al.	
2008/0304298 A1		Toba et al.		2010/0052735			Burkland et al.	
2009/0010035 A1		Williams		2010/0057267			Liu et al. Scholte-Wassink	
2009/0012917 A1 2009/0014050 A1	1/2009	Thompson et al.		2010/0060000 2010/0071742			de Rooij et al.	
2009/0014057 A1		Croft et al.		2010/0085670			Palaniswami et al.	
2009/0014058 A1	1/2009	Croft et al.		2010/0103579			Carkner et al.	
2009/0015071 A1		Iwata et al.		2010/0115093 2010/0124027		5/2010	Rice Handelsman et al.	
2009/0020151 A1 2009/0021877 A1		Fornage et al.		2010/0124027		5/2010		
2009/0039833 A1		Kitagawa		2010/0126550	A1	5/2010		
2009/0039852 A1	2/2009	Fishelov et al.		2010/0127570			Hadar et al.	
2009/0064252 A1		Howarter et al.		2010/0127571 2010/0131108		5/2010	Hadar et al.	
2009/0066357 A1 2009/0066382 A1		Fornage Yousefzadeh et al.		2010/0131100			He et al.	
2009/0066399 A1		Chen et al.		2010/0132758			Gilmore	
2009/0069950 A1		Kurokami et al.		2010/0132761			Echizenya et al. Williams et al.	
2009/0073726 A1 2009/0078300 A1		Babcock Ang et al.		2010/0133911 2010/0139734			Hadar et al.	
2009/0076300 A1 2009/0080226 A1		Fornage		2010/0139743			Hadar et al.	
2009/0084570 A1		Gherardini et al.		2010/0141041			Bose et al.	
2009/0097172 A1		Bremicker et al.		2010/0141153 2010/0147362			Recker et al. King et al.	
2009/0097283 A1 2009/0101191 A1		Krein et al. Beck et al.		2010/0154858		6/2010		
2009/0102440 A1	4/2009	Coles		2010/0176773		7/2010		
2009/0114263 A1		Powell et al.		2010/0181957 2010/0191383		7/2010	Goeltner	
2009/0120485 A1 2009/0121549 A1*		Kikinis Leonard	H02J 3/381	2010/0191363			Fornage et al.	
	0.200		307/51	2010/0195361		8/2010	Stem	
2009/0127448 A1		Fuyuki		2010/0206378 2010/0207764			Erickson, Jr. et al. Muhlberger et al.	
2009/0133736 A1 2009/0140715 A1		Powell et al. Adest et al.		2010/0207704			Thiemann	
2009/0141522 A1		Adest et al.		2010/0208501	A1		Matan et al.	
2009/0145480 A1		Adest et al.		2010/0213897		8/2010		
2009/0146667 A1		Adest et al.		2010/0214808 2010/0217551			Rodriguez Goff et al.	
2009/0146671 A1 2009/0147554 A1	6/2009 6/2009	Adest et al.		2010/0229915			Ledenev et al.	
2009/0150005 A1		Hadar et al.		2010/0241375			Kumar et al.	
2009/0160258 A1		Allen et al.		2010/0244575 2010/0246223		9/2010	Coccia et al.	
2009/0179500 A1 2009/0179662 A1		Ragonese et al. Moulton et al.		2010/0264736			Mumtaz et al.	
2009/0182532 A1		Stoeber et al.		2010/0269430			Haddock	
2009/0183763 A1		Meyer		2010/0277001 2010/0282290			Wagoner Schwarze et al.	
2009/0184746 A1 2009/0189456 A1	7/2009 7/2009	Fahrenbruch		2010/0282290			Shaver, II et al.	
2009/0189436 A1 2009/0190275 A1		Gilmore et al.		2010/0288327	A1	11/2010	Lisi et al.	
2009/0195081 A1	8/2009	Quardt et al.		2010/0289337			Stauth et al. Sella et al.	
2009/0206666 A1 2009/0207543 A1	8/2009	Sella et al. Boniface et al.		2010/0294528 2010/0294903			Shmukler et al.	
2009/0207343 A1 2009/0217965 A1		Dougal et al.		2010/0295680	A1	11/2010	Dumps	
2009/0224817 A1	9/2009	Nakamura et al.		2010/0297860			Shmukler et al.	
2009/0234692 A1		Powell et al.		2010/0301677 2010/0301991		12/2010	Tomita Sella et al.	
2009/0237042 A1 2009/0237043 A1		Glovinski Glovinsky		2010/0301991			Schatz et al.	
2009/0237043 A1 2009/0238444 A1		Su et al.		2010/0309692	A1	12/2010	Chisenga et al.	
2009/0242011 A1	10/2009	Proisy et al.		2010/0315043		12/2010		
2009/0243385 A1 2009/0243547 A1		Ichikawa Andelfinger		2010/0321148 2010/0326809			Gevorkian Lang et al.	
2009/0243347 A1 2009/0273241 A1		Gazit et al.		2010/0326809		12/2010		
2009/0278496 A1		Nakao et al.		2010/0327659			Lisi et al.	
2009/0282755 A1		Abbott et al.		2010/0332047			Arditi et al.	
2009/0283129 A1	11/2009	ross		2011/0006743	Al	1/2011	Fabbro	

(56)	Referer	ices Cited	2011/0304204			Avrutsky et al.
11.6	DATENT	DOCUMENTS	2011/0304213 2011/0304215		12/2011	Avrutsky et al. Avrutsky et al.
0.5	o. PATENT	DOCUMENTS	2011/0316346			Porter et al.
2011/0012430 A1	1/2011	Cheng et al.	2012/0007434			Perreault et al.
2011/0019444 A1		Dargatz et al.	2012/0007558		1/2012	
2011/0025130 A1		Hadar et al.	2012/0007613		1/2012	
2011/0026282 A1		Chapman et al.	2012/0019966 2012/0026763			DeBoer Humphrey et al.
2011/0027626 A1 2011/0031816 A1		Lattin Buthker et al.	2012/0026769		2/2012	
2011/0031816 A1 2011/0031946 A1		Egan et al.	2012/0032515		2/2012	Ledenev et al.
2011/0037600 A1			2012/0033392			Golubovic et al.
2011/0043172 A1		Dearn	2012/0033463 2012/0039099			Rodriguez Rodriguez
2011/0045802 A1		Bland et al.	2012/0039099			Erickson, Jr.
2011/0049990 A1 2011/0050002 A1		Amaratunga et al. De Luca	2012/0043818			Stratakos et al.
2011/0050190 A1		Avrutsky	2012/0043823	A1		Stratakos et al.
2011/0056533 A1	3/2011	Kuan	2012/0044014			Stratakos et al.
2011/0061705 A1		Croft et al.	2012/0044717 2012/0048325			Suntio et al. Matsuo et al.
2011/0061713 A1 2011/0062784 A1	3/2011	Powell et al. Wolfs	2012/0049627			Matsuo et al.
2011/0002/84 A1 2011/0068633 A1		Quardt et al.	2012/0049801		3/2012	Chang
2011/0079263 A1		Avrutsky	2012/0049819			Mao et al.
2011/0080147 A1		Schoenlinner et al.	2012/0056483			Capp et al. Abe et al.
2011/0083733 A1		Marroquin et al.	2012/0056591 2012/0063177			Garrity
2011/0084553 A1 2011/0088741 A1		Adest et al. Dunton et al.	2012/0080943			Phadke
2011/0008741 A1 2011/0101949 A1		Lopata et al.	2012/0081009	A1	4/2012	Shteynberg et al.
2011/0108087 A1		Croft et al.	2012/0081933			Garrity
2011/0109158 A1			2012/0081934 2012/0081937			Garrity et al.
2011/0114154 A1		Lichy et al.	2012/0081937			Phadke Chapman et al.
2011/0115295 A1 2011/0115393 A1		Moon et al.	2012/0091810		4/2012	Aiello et al.
2011/0116294 A1			2012/0091817	A1	4/2012	Seymour et al.
2011/0121441 A1		Halstead et al.	2012/0098344			Bergveld et al.
2011/0121652 A1		Sella et al.	2012/0104861 2012/0104863		5/2012	Kojori et al.
2011/0125431 A1		Adest et al.	2012/0104803			Paoletti et al.
2011/0132424 A1 2011/0133552 A1		Rakib Binder et al.	2012/0119584			Hadar et al.
2011/0133556 A1			2012/0126624			Hester et al.
2011/0139213 A1	6/2011		2012/0127764			Phadke et al.
2011/0140535 A1		Choi et al.	2012/0133372 2012/0134058			Tsai et al. Pamer et al.
2011/0140536 A1 2011/0141644 A1		Adest et al. Hastings et al.	2012/0134030			Newdoll et al.
2011/0141044 A1 2011/0144822 A1			2012/0139343			Adest et al.
2011/0161722 A1		Makhota et al.	2012/0146420		6/2012	
2011/0172842 A1		Makhota et al.	2012/0146583 2012/0161526			Gaul et al. Huang et al.
2011/0173276 A1		Eizips et al.	2012/0161528			Mumtaz et al.
2011/0179726 A1 2011/0181251 A1		Pao et al. Porter et al.	2012/0169124			Nakashima et al.
2011/0181340 A1			2012/0169291			Abe et al.
2011/0183537 A1		Fornage et al.	2012/0174961			Larson et al.
2011/0198935 A1		Hinman et al.	2012/0175961 2012/0175963			Har-Shai et al. Adest et al.
2011/0210610 A1 2011/0210611 A1		Mitsuoka et al. Ledenev et al.	2012/0187769		7/2012	Spannhake et al.
2011/0210611 A1 2011/0210612 A1		Leutwein	2012/0194003			Schmidt et al.
2011/0218687 A1		Hadar et al.	2012/0199172			Avrutsky
2011/0227411 A1		Arditi	2012/0200311			Chaintreuil Adest et al.
2011/0232714 A1		Bhavaraju et al.	2012/0212066 2012/0215367			Eizips et al.
2011/0240100 A1 2011/0245989 A1		Lu et al. Makhota et al.	2012/0217797			Butzmann
2011/0246338 A1			2012/0217973			Avrutsky
2011/0254372 A1		Haines et al.	2012/0228931			Butzmann
2011/0260866 A1		Avrutsky et al.	2012/0240490 2012/0242156		9/2012	Gangemi Butzmann et al.
2011/0267721 A1 2011/0267859 A1		Chaintreuil et al. Chapman	2012/0253533			Eizips et al.
2011/0207839 A1 2011/0271611 A1		Maracci et al.	2012/0253541		10/2012	Arditi et al.
2011/0273015 A1		Adest et al.	2012/0255591			Arditi et al.
2011/0273016 A1		Adest et al.	2012/0268969		10/2012	Cuk Kamel et al.
2011/0273017 A1		Borup et al.	2012/0271576 2012/0274145		10/2012	
2011/0273024 A1 2011/0273302 A1		Butzmann Fornage et al.	2012/0274143			Mun et al.
2011/0273302 A1 2011/0278955 A1		Signorelli et al.	2012/0280571		11/2012	
2011/0285205 A1		Ledenev et al.	2012/0299380	A1	11/2012	Haupt
2011/0285375 A1			2012/0318320			Robbins
2011/0290317 A1		Naumovitz et al.	2013/0002335			DeGraaff
2011/0291486 A1		Adest et al.	2013/0026839 2013/0026840		1/2013	Grana Arditi et al.
2011/0298288 A1 2011/0301772 A1		Cho et al. Zuercher et al.	2013/0026840			Arditi et al.
2011/0301/72 AI	12/2011	Zuerener et al.	2010/0020072	4 3 1	1/2013	. mana et al.

(56)	Referen	ices Cited	2015/0188415			Abido et al.
U.S.	PATENT	DOCUMENTS	2015/0214889 2015/0236589 2015/0263609	A1	8/2015	Nam et al. Baba Weida et al.
2012/0026042	1/2012	A 1121 4 1	2015/0318410		11/2015	
2013/0026843 A1 2013/0038124 A1		Arditi et al. Newdoll et al.	2015/0310410			Linderman
2013/0039028 A1		Korman et al.	2015/0364918			Singh et al.
2013/0049710 A1		Kraft et al.	2015/0372490			Bakas et al.
2013/0057223 A1	3/2013		2015/0381108			Hoft et al.
2013/0062956 A1		Meyer et al.	2015/0381111 2016/0006392		1/2015	Nicolescu et al.
2013/0062958 A1		Erickson, Jr. et al.	2016/0036235		2/2016	
2013/0063119 A1 2013/0069438 A1		Lubomirsky Liu et al.	2016/0126367			Dunton et al.
2013/0082724 A1		Noda et al.	2016/0172900	A1		Welch, Jr.
2013/0094112 A1	4/2013	Burghardt et al.	2016/0181802			Jacobson et al.
2013/0094262 A1		Avrutsky	2016/0190931 2016/0211841		6/2016	Zhang Harrison
2013/0134790 A1		Amaratunga et al.	2016/0211841			Kravtiz et al.
2013/0175971 A1 2013/0181533 A1		Har-Shai et al. Capp et al.	2016/0226257			Porter et al.
2013/0192657 A1		Hadar et al.	2016/0241039			Cheng et al.
2013/0193765 A1		Yoscovich	2016/0268809			Ledenev et al.
2013/0194706 A1		Har-Shai et al.	2016/0270245 2016/0276820			Linderman Olivas et al.
2013/0200709 A1		Kirchner et al.	2016/02/0820			Yamashita et al.
2013/0200710 A1 2013/0214607 A1		Robbins Harrison	2016/0329715			Orr et al.
2013/02214007 A1 2013/0222144 A1		Hadar et al.	2016/0336899			Ledenev et al.
2013/0229834 A1		Garrity et al.	2016/0380436			Porter et al.
2013/0229842 A1		Garrity	2017/0104413			Busch et al.
2013/0234518 A1		Mumtaz et al.	2017/0138804 2017/0179876			Lebental et al. Freeman et al.
2013/0235637 A1 2013/0269181 A1		Rodriguez McBride et al.	2017/0179876			Oishi et al.
2013/0209181 A1 2013/0271096 A1		Inagaki	2017/0184343			Freer et al.
2013/0279210 A1		Chisenga et al.	2017/0207746			Yoscovich et al.
2013/0285459 A1		Jaoui et al.	2017/0211190			Glasscock et al.
2013/0294126 A1		Garrity et al.	2017/0222542 2017/0271879			Adest et al. Ledenev et al.
2013/0307556 A1 2013/0313909 A1		Ledenev et al. Storbeck et al.	2017/0278375			Galin et al.
2013/0313303 A1 2013/0320778 A1		Hopf et al.	2017/0288384	A1		Loewenstern et al.
2013/0321013 A1		Pisklak et al.	2017/0331325		11/2017	
2013/0328541 A1		Euler et al.	2018/0034411 2018/0145593			Charles et al. Xi et al.
2013/0332093 A1 2013/0335861 A1		Adest et al. Laschinski et al.	2018/0191292			Ehlmann
2013/0353801 A1 2014/0062206 A1		Bryson	2018/0248513		8/2018	Höft
2014/0062209 A1		Liu et al.	2018/0351401			Binder et al.
2014/0062396 A1		Reddy	2019/0379279 2019/0393834			Adest et al. Har-Shai et al.
2014/0077756 A1 2014/0097808 A1		Kataoka et al. Clark et al.	2020/0176937		6/2020	
2014/0097808 A1 2014/0119072 A1		Behrends et al.	2020/0279963			Yoscovich et al.
2014/0119076 A1		Chang et al.	2020/0373841	A1	11/2020	Xie et al.
2014/0167715 A1		Wu et al.	2021/0036557	A1	2/2021	Haug et al.
2014/0169053 A1		Ilic et al.				
2014/0191583 A1 2014/0210485 A1	7/2014	Chisenga et al. Lang et al.	FO	REIC	in patel	NT DOCUMENTS
2014/0233136 A1		Heerdt	AU 20	വരാവ	2125 A1	12/2009
2014/0246915 A1		Mumtaz			5199 A1	10/2013
2014/0246927 A1		Mumtaz	CA	118	3574 A	3/1985
2014/0252859 A1 2014/0265551 A1	9/2014	Chisenga et al. Willis	CA		3243 A1	12/1991
2014/0265579 A1		Mumtaz	CA CA		1657 A1 4761 A1	3/1999 6/2001
2014/0265629 A1		Gazit et al.	CA		8087 A1	6/2001
2014/0265638 A1		Orr et al.	CA		3450 A1	3/2005
2014/0268913 A1 2014/0277796 A1		Zheng et al. Peskin et al.	CA		2452 A1	1/2006
2014/0293491 A1		Robbins	CA		3038 A1	1/2007
2014/0306543 A1		Garrity et al.	CA CA		4605 A1 2392 C	5/2009 9/2015
2014/0327313 A1		Arditi et al.	CN		1396 U	2/1991
2014/0327995 A1 2014/0354245 A1		Panjwani et al. Batikoff et al.	CN		6523 A	8/1995
2015/0022006 A1		Garrity et al.	CN		4479 Y	6/1998
2015/0028683 A1		Hadar et al.	CN CN		8453 A 5016 Y	7/1998 1/1999
2015/0028692 A1		Makhota et al.	CN		6213 A	11/1999
2015/0061409 A1		Dunton et al.	CN	124	4745 A	2/2000
2015/0069844 A1 2015/0100265 A1		Wu et al. Duchemin	CN		2552 A	8/2000
2015/0100203 A1 2015/0103572 A1	4/2015		CN CN		4487 C 9451 A	4/2001 8/2001
2015/0131187 A1	5/2015	Krein et al.	CN		2655 A	8/2002
2015/0161872 A1		Beaulieu et al.	CN	251	4538 Y	10/2002
2015/0171789 A1		Har-Shai et al.	CN		2905 C	10/2003
2015/0183328 A1	//2015	Kusch et al.	CN	257	9063 Y	10/2003

(56)	References Ci				2013
	FOREIGN PATENT DO	CUMENTS	CN 1032	299501 A 9/2	2013
CN	1474492 A 2/20	04	CN 1035	548226 A 1/2	2013 2014
CN	1523726 A 8/20	· · · · · · · · · · · · · · · · · · ·			2014 2014
CN CN	1551377 A 12/20 1185782 C 1/20	05	CN 1041	143916 A 11/2	2014
CN CN	2672668 Y 1/20 2672938 Y 1/20	,			2014 2014
CN	1588773 A 3/20	05	CN 1044		2015
CN CN	1201157 C 5/20 1614854 A 5/20	0.5			2015 2015
CN	2706955 Y 6/20	05			2015 2015
CN CN	1245795 C 3/20 1787717 A 6/20	06	CN 1054	190298 A 4/2	2016
CN	1794537 A 6/20	06			2016 2016
CN CN	1838191 A 9/20 1841254 A 10/20	06	CN 1060	093721 A 11/2	2016
CN CN	1841823 A 10/20 1848588 A 10/20	JU -			2018 1964
CN	1892239 A 1/20	07 <u>I</u>	DE 32	236071 A1 1/.	1984
CN CN	1902809 A 1/20 1929276 A 3/20	J1			1987 1989
CN	1930925 A 3/20	07 <u> </u>			1992 1992
CN CN	1933315 A 3/20 2891438 Y 4/20	J /			1992
CN	101030752 A 9/20	07			1993 1994
CN CN	101050770 A 10/20 101107712 A 1/20	08 I	DE 43	325436 A1 2/	1995
CN	100371843 C 2/20	JO			1995 1995
CN CN	101128974 A 2/20 101136129 A 3/20	08 I	DE 195	502762 A1 8/	1996
CN CN	101180781 A 5/20 101257221 A 9/20	JO			1997 1997
CN	100426175 C 10/20	08 I	DE 196	518882 A1 11/	1997
CN CN	201167381 Y 12/20 201203438 Y 3/20	JO			1998 1998
CN	100487970 C 5/20	09 <u>I</u>			1999 1999
CN CN	101488271 A 7/20 101521459 A 9/20	09 I	DE 198	338230 A1 2/2	2000
CN	101523230 A 9/20	09 <u> </u>			2000 2000
CN CN	101647172 A 2/20 101672252 A 3/20	10 10	DE 199	904561 C1 8/2	2000
CN CN	101697462 A 4/20 101779291 A 7/20	10			2001 2001
CN	101847939 A 9/20	10 I			2001
CN CN	201601477 U 10/20 201623478 U 11/20	10			2001
CN	201623651 U 11/20	10 I			2002
CN CN	101902051 A 12/20 101902171 A 12/20	10 I	DE 102	219956 A1 4/2	2003
CN	101904015 A 12/20	TO T			2003 2004
CN CN	201663167 U 12/20 101939660 A 1/20	11 <u>I</u>	DE 103	345302 A1 4/2	2005
CN CN	101951011 A 1/20 101951190 A 1/20	· · · · · · · · · · · · · · · · · · ·			2005 2006
CN	101953051 A 1/20	11 <sup>I</sup>			2006 2006
CN CN	101953060 A 1/20 101976855 A 2/20	11 I	DE 697	735169 T2 8/2	2006
CN	101976952 A 2/20	11 <sup>Ţ</sup>			2006 2006
CN CN	101980409 A 2/20 102084584 A 6/20	11 I	DE 20 2005 (	020161 U1 11/2	2006
CN CN	102089883 A 6/20 102117815 A 7/20	11 -			2006 2007
CN	102148584 A 8/20	11 11	DE 1020050	)32864 A1 1/2	2007
CN CN	201926948 U 8/20 201956938 U 8/20	11 I	DE 1020060		2007 2007
CN	202034903 U 11/20	ii Į	DE 2020070	002077 U1 4/2	2008
CN CN	102273039 A 12/20 202103601 U 1/20				2008 2008
CN	102362550 A 2/20	12 I	DE 1020070		2009
CN CN	102386259 A 3/20 202178274 U 3/20				2009 2009
CN	102474112 A 5/20	12 I	DE 1020070	050031 B3 4/2	2009
CN CN	102565635 A 7/20 102771017 A 11/20				2009 2010
CN	102845136 A 12/20	12 I	DE 1020080	)57874 A1 5/2	2010
CN	202871823 U 4/20	Ι3 Ι	DE 1020090	051186 A1 5/2	2010

(56)	Referenc	es Cited	EP EP	1532727 A2 1552563 A2	5/2005 7/2005
	FOREIGN PATEN	IT DOCUMENTS	EP EP	1562281 A1 1580862 A1	8/2005 9/2005
DE DE DE	102009022569 A1 102010023549 A1 202011109688 U1	12/2010 12/2011 3/2012	EP EP EP	1603212 A2 1610571 A2 1623495 A1	12/2005 12/2005 12/2006
DE DE	102013101314 A1 102013106255 A1	8/2014 12/2014	EP EP	1642355 A2 0964457 A3	4/2006 5/2006
DE	102013106808 A1	12/2014	EP EP	1657557 A1 1657797 A1	5/2006 5/2006
DE EP	102016117229 A1 0027405 A1	3/2018 4/1981	EP	1684397 A2	7/2006
EP EP	169673 A1 0178757 A2	1/1986 4/1986	EP EP	1691246 A2 1706937 A1	8/2006 10/2006
EP EP	0206253 A1 0231211 A1	12/1986 8/1987	EP EP	1708070 A1 1716272 A1	10/2006 11/2006
EP	0293219 A2	11/1988	EP EP	1728413 A1 1734373 A2	12/2006 12/2006
EP EP	0340006 A2 0418612 A1	11/1989 3/1991	EP	1750193 A1	2/2007
EP EP	419093 A2 420295 A1	3/1991 4/1991	EP EP	1766490 A1 1782146 A2	3/2007 5/2007
EP	0521467 A2	1/1993	EP EP	1785800 A1 1837985 A2	5/2007 9/2007
EP EP	0576271 A2 0577334 A2	12/1993 1/1994	EP	1842121 A2	10/2007
EP EP	604777 A1 0628901 A2	7/1994 12/1994	EP EP	1609250 B1 1887675 A2	1/2008 2/2008
EP	0642199 A1	3/1995	EP EP	1901419 A2 1902349 A2	3/2008 3/2008
EP EP	653692 A2 0670915 A1	5/1995 9/1995	EP	1911101 A1	4/2008
EP EP	677749 A2 756178 A2	10/1995 1/1997	EP EP	1914857 A1 2048679 A1	4/2008 4/2009
EP	0756372 A1	1/1997	EP EP	2054944 A2 2061088 A2	5/2009 5/2009
EP EP	0780750 A2 0809293 A1	6/1997 11/1997	EP	2092625 A2	8/2009
EP EP	824273 A2 827254 A2	2/1998 3/1998	EP EP	2092631 A2 2130286 A1	8/2009 12/2009
EP	0895146 A1	2/1999	EP EP	2135296 A2 2135348 A2	12/2009 12/2009
EP EP	0906660 A1 0947904 A2	4/1999 10/1999	EP	2144133 A1	1/2010
EP EP	0947905 A2 964415 A1	10/1999 12/1999	EP EP	2179451 A1 2206159 A2	4/2010 7/2010
EP EP	0978884 A3 1012886 A1	3/2000 6/2000	EP EP	2232690 A1 2234237 A1	9/2010 9/2010
EP	1024575 A2	8/2000	EP EP	2249457 A1 2256819 A1	11/2010 12/2010
EP EP	1034465 A1 1035640 A1	9/2000 9/2000	EP	2315328 A2	4/2011
EP EP	1039361 A1 1039620 A2	9/2000 9/2000	EP EP	2355268 A1 2374190 A1	8/2011 10/2011
EP	1039621 A2	9/2000 10/2000	EP EP	2386122 A2 2393178 A2	11/2011 12/2011
EP EP	1047179 A1 1130770 A2	9/2001	EP EP	2395648 A2 2495766 A1	12/2011
EP EP	1143594 A2 1187291 A2	10/2001 3/2002	EP	2515424 A2	9/2012 10/2012
EP EP	1235339 A2 1239573 A1	8/2002 9/2002	EP EP	2533299 A1 2549635 A1	12/2012 1/2013
EP	1239576 A2	9/2002	EP EP	2561596 A2 2581941 A2	2/2013 4/2013
EP EP	1254505 A2 1271742 A2	11/2002 1/2003	EP	2615644 A2	7/2013
EP EP	1291997 A2 1330009 A2	3/2003 7/2003	EP EP	2621045 A2 2666222 A1	7/2013 11/2013
EP	1339153 A2	8/2003	EP EP	2722979 A1 2779251 A1	4/2014 9/2014
EP EP	1369983 A1 1376706 A2	12/2003 1/2004	$\mathbf{EP}$	3176933 A1	6/2017
EP EP	1388774 A1 1400988 A2	2/2004 3/2004	EP EP	2139104 B1 3252909 A1	10/2017 12/2017
EP EP	1407534 A2 1120895 A3	4/2004 5/2004	EP ES	3382871 A1 2249147 A1	10/2018 3/2006
EP	1418482 A1	5/2004	ES FR	2249149 A1	3/2006 1/2001
EP EP	1429393 A2 1442473 A2	6/2004 8/2004	FR	2796216 A1 2819653 A1	7/2001
EP EP	1447561 A1 1457857 A2	8/2004 9/2004	FR GB	2894401 A1 310362 A	6/2007 9/1929
EP	1463188 A2	9/2004	GB	612859 A	11/1948
EP EP	1475882 A2 1503490 A1	11/2004 2/2005	GB GB	1211885 A 1231961 A	11/1970 5/1971
EP	1521345 A1	4/2005	GB	1261838 A	1/1972
EP EP	1526633 A2 1531542 A2	4/2005 5/2005	GB GB	1571681 A 1597508 A	7/1980 9/1981
EP	1531545 A2	5/2005	GB	2128017 A	4/1984

(56)	Reference	ces Cited	JP JP	2000160789 A 2000166097 A	6/2000 6/2000
	FOREIGN PATEN	T DOCUMENTS	JP	2000174307 A	6/2000
GB	2327208 A	1/1999	JР	2000232791 A 2000232793 A	8/2000 8/2000
GB	2339465 A	1/2000	ЈР ЈР	2000316282 A 2000324852 A	11/2000 11/2000
GB GB	2376801 A 2399463 A	12/2002 9/2004	JP	2000339044 A	12/2000
GB	2399465 A	9/2004	JP JP	2000341974 A 2000347753 A	12/2000 12/2000
GB GB	2415841 A 2419968 A	1/2006 5/2006	JP	2000358330 A	12/2000
GB	2421847 A	7/2006 7/2007	JP JP	200185716 A 2001060120 A	3/2001 3/2001
GB GB	2434490 A 2476508 A	6/2011	JP	2001075662 A	3/2001
GB GB	2480015 B 2482653 A	12/2011 2/2012	JP JP	2001086765 A 2001178145 A	3/2001 6/2001
GB	2483317 A	3/2012	JP	2001189476 A	7/2001
GB GB	2485527 A 2486408 A	5/2012 6/2012	JP JP	2001224142 A 2001238466 A	8/2001 8/2001
GB	2487368 A	7/2012	JP JP	2001250964 A 2001255949 A	9/2001 9/2001
GB GB	2497275 A 2498365 A	6/2013 7/2013	JP	2001-320827 A	11/2001
GB	2498790 A	7/2013	JP JP	2002073184 A 2002231578 A	3/2002 8/2002
GB GB	2498791 A 2499991 A	7/2013 9/2013	JP	2002238246 A	8/2002
JP JP	S56042365 A	4/1981	JP JP	2002-262461 A 2002270876 A	9/2002 9/2002
JP JP	S60027964 A S60148172 A	2/1985 8/1985	JP	2002300735 A	10/2002
JP JP	61065320 A S62154121 A	4/1986 7/1987	ЈР ЈР	2002339591 A 2002354677 A	11/2002 12/2002
JP	S62154122 A	7/1987	JP	2003068312 A	3/2003
JP JP	H01311874 A H04219982 A	12/1989 8/1992	JP JP	2003102134 A 2003124492 A	4/2003 4/2003
JР	H04364378 A	12/1992	JP JP	2003132959 A 2003132960 A	5/2003
JP JP	H05003678 A H06035555 A	1/1993 2/1994	JP	2003132900 A 2003134661 A	5/2003 5/2003
JР	H06141261 A	5/1994	ЈР ЈР	2003134667 A 2003168487 A	5/2003 6/2003
JP JP	H07026849 A H07058843 A	1/1995 3/1995	JP	2003282916 A	10/2003
JР	H07-222436 A	8/1995	JP JP	2003289674 A 3499941 B2	10/2003 2/2004
JP JP	H07322529 A 8009557 A	12/1995 1/1996	JP	2004047279 A	2/2004
JP JP	H08033347 A H08066050 A	2/1996 3/1996	JP JP	2004055603 A 2004-096090 A	2/2004 3/2004
JР	H0897460 A	4/1996	JP	2004111754 A	4/2004
JP JP	08138754 A H08116628 A	5/1996 5/1996	ЈР ЈР	2004-147465 A 2004194500 A	5/2004 7/2004
JР	H08181343 A	7/1996	JP JP	2004260944 A 2004-334704 A	9/2004 11/2004
JP JP	H08185235 A H08204220 A	7/1996 8/1996	JP	2004312994 A	11/2004
JP	H08227324 A	9/1996	JP JP	2005-151662 A 3656531 B2	6/2005 6/2005
JP JP	H08316517 A H08317664 A	11/1996 11/1996	JP	2005192314 A	7/2005
JP JP	097644 A H094692 A	1/1997 1/1997	JP JP	2005-235082 A 2005251039 A	9/2005 9/2005
JР	H09097918 A	4/1997	JP	2005-276942 A	10/2005
JP JP	H09148611 A H09148613 A	6/1997 6/1997	JP JP	2005283516 A 2005-312287 A	10/2005 11/2005
JР	H09275644 A	10/1997	JP JP	2006041440 A	2/2006
JP JP	2676789 B2 H1017445 A	11/1997 1/1998	JР	2006262619 A 2006271083 A	9/2006 10/2006
JР	H1075580 A	3/1998	JP JP	2006278755 A 2007058845 A	10/2006 3/2007
JP JP	H10201086 A H10201105 A	7/1998 7/1998	JP	2007104872 A	4/2007
JP	H10308523 A	11/1998	JP JP	2007225625 A 4174227 B2	9/2007 10/2008
JP JP	11041832 A H1146457 A	2/1999 2/1999	JP	2010-146047 A	7/2010
JP JP	11103538 A	4/1999 5/1999	JP JP	2010245532 A 2011-055634 A	10/2010 3/2011
JР	2892183 B2 11206038 A	5/1999 7/1999	JP	2011-249790 A	12/2011
JP JP	H11266545 A 11289891 A	9/1999 10/1999	ЈР ЈР	2012-60714 A 2012511299 A	3/2012 5/2012
JP	11318042 A	11/1999	JP	2012178535 A	9/2012
JP JP	H11332088 A 2000020150 A	11/1999 1/2000	JP KR	2015-233386 A 20010044490 A	12/2015 6/2001
JР	2000051074 A	2/2000	KR	20030050390 A	6/2003
JP JP	3015512 B2 2000-112545 A	3/2000 4/2000	KR KR	20040086088 A 100468127 B1	10/2004 1/2005
JP	2000-112343 A 2000-116010 A	4/2000	KR	200402282 Y1	11/2005

(56)	References Cite		2006078685 A2	7/2006
	PODELCNI DATENIT DOG	WO CLIMENTS WO	2006079503 A2 2006089778 A2	8/2006 8/2006
	FOREIGN PATENT DO	COMENTS WO WO	2006089778 A2 2006110613 A2	10/2006
KR	20060060825 A 6/200	WO	2006/125664 A1	11/2006
KR	20070036528 A 4/200	7 WO	2006117551 A2	11/2006
KR	100725755 B1 5/200		2006130520 A2	12/2006
KR	20080092747 A 10/200	WO	2006137948 A2 2007006564 A2	12/2006 1/2007
KR	100912892 B1 8/200 101073143 B1 10/201	, wo	2007000304 A2 2007007360 A2	1/2007
KR NL	101073143 B1 10/201 1011483 C2 9/200	1 11/0	2007010326 A1	1/2007
TW	497326 B 8/200	2 WO	2007/020419 A1	2/2007
TW	200913291 A 3/200		2007048421 A2 2007072517 A1	5/2007 6/2007
WO WO	8202134 A1 6/198	L 11/0	2007072317 A1 2007073951 A1	7/2007
WO	1984003402 A1 8/198 1988004801 A1 6/198	T 17/0	2007080429 A2	7/2007
WO	9003680 A1 4/199	0 WO	2007084196 A2	7/2007
WO	1992007418 A1 4/199		2007090476 A2	8/2007
WO	1993013587 A1 7/199	11/0	2006124130 A9 2007113358 A1	10/2007 10/2007
WO WO	95/25374 A1 9/199 95/34121 A1 12/199	J 11/0	2007113536 A1	11/2007
wo	1996007130 A1 3/199	6 WO	2007129808 A1	11/2007
WO	1996013093 A1 5/199	WO	2007142693 A2 2008008528 A2	12/2007
WO	1998023021 A2 5/199		2008008528 A2 2008026207 A2	1/2008 3/2008
WO WO	1999028801 A1 6/199 00/00839 A1 1/200	7	2008/046370 A1	4/2008
WO	00/00839 A1 1/200 00/21178 A1 4/200	$_{0}$ WO	2008/077473 A2	7/2008
WO	0042689 A1 7/200	0 WO	2008069926 A3	8/2008
WO	0075947 A1 12/200	WO	2008097591 A2 2008119034 A1	8/2008 10/2008
WO WO	0077522 A1 12/200 01/13502 A1 2/200	V	2008121266 A2	10/2008
WO	01/13302 A1 2/200 01047095 A2 6/200	1 WO	2008125915 A2	10/2008
WO	02/17469 A1 2/200	2 WO	2008132551 A2	11/2008
WO	0231517 4/200		2008132553 A2 2008142480 A2	11/2008
WO	02056126 A1 7/200	L 11/0	2008142480 A2 2009003680 A1	11/2008 1/2009
WO WO	2002073785 A1 9/200 02078164 A1 10/200		2009006879 A2	1/2009
WO	02093655 A1 11/200	2 WO	2009007782 A2	1/2009
WO	03012569 A1 2/200	WO	2009011780 A2	1/2009
WO	03/026114 A2 3/200	J 11/0	2009020917 A2 2009/026602 A1	2/2009 3/2009
WO WO	2003036688 A2 5/200 2003050938 A2 6/200	J 11/0	2009046533 A1	4/2009
WO	2003071655 A1 8/200	3 WO	2009051221 A1	4/2009
WO	03084041 A1 10/200		2009051222 A1	4/2009
WO	2003098703 11/200		2009051853 A1 2009051854 A1	4/2009 4/2009
WO WO	2004001942 A1 12/200 2004006342 A1 1/200	J WO	2009051870 A1	4/2009
wo	2004008619 A2 1/200	4 WO	2009055474 A1	4/2009
WO	2004023278 A2 3/200		2009/059877 A1 2009056957 A2	5/2009 5/2009
WO	2004053993 A1 6/200 2004090993 A2 10/200	7 77.0	2009059937 A2 2009059028 A2	5/2009
WO WO	2004090993 A2 10/200 2004098261 A2 11/200	TWO.	2009064683 A2	5/2009
wo	2004100344 A2 11/200	4 WO	2009/072075 A2	6/2009
WO	2004100348 A1 11/200		2009/073867 A1	6/2009
WO	2004107543 A2 12/200		2009072076 A2 2009072077 A1	6/2009 6/2009
WO WO	2005015584 A2 2/200 2005027300 A1 3/200	J 11/0	2009073868 A1	6/2009
wo	2005036725 A1 4/200	5 WO	2009073995 A1	6/2009
WO	2005053189 A1 6/200		2009075985 A2	6/2009
WO	2005069096 A1 7/200	1170	2009098729 A1 2009114341 A2	8/2009 9/2009
WO WO	2005076444 A1 8/200 2005076445 A1 8/200	7 7770	2009114541 A2 2009118682 A2	10/2009
wo	2005089030 A1 9/200	5 WO	2009118683 A2	10/2009
WO	2005112551 A2 12/200	5 WO	2009136358 A1	11/2009
WO	2005119278 A1 12/200		2009140539 A2 2009140543 A2	11/2009 11/2009
WO WO	2005119609 A2 12/200 2005124498 A1 12/200	J WO	2009155392 A1	12/2009
WO	2006002380 A2 1/200	WO WO	2010/002960 A1	1/2010
WO	2006005125 A1 1/200	6 WO	2010/003941 A2	1/2010
WO	2006007198 A1 1/200		2009/140536 A3	2/2010
WO WO	2006011071 A2 2/200 2006011359 A1 2/200		2009/140551 A3 2010014116 A1	2/2010 2/2010
WO	2006011339 A1 2/200 2006013600 A2 2/200		2010020385 A2	2/2010
WO	2006033143 A1 3/200		2010/042124 A1	4/2010
WO	2006045016 A2 4/200		2010037393 A1	4/2010
WO	2006048688 A1 5/200		2010056777 A1	5/2010
WO	2006048689 A2 5/200		2010/071855 A2	6/2010
WO WO	2006/074561 A1 7/200 2006071436 A2 7/200		2010062410 A1 2010062662 A2	6/2010 6/2010
.,,	2000071130 AZ 7/200	WO	2010002002 A2	5/2010

(56)	References Cited
	FOREIGN PATENT DOCUMENTS
WO W	POREIGN PATENT DOCUMENTS  2010065043 A1 6/2010 2010065388 A1 6/2010 2010078303 A2 7/2010 2010080672 A2 7/2010 20100991025 A2 8/2010 2010094012 A1 8/2010 2010118503 A1 10/2010 2010120315 A1 10/2010 2010/132369 A1 11/2010 20101034057 A1 11/2010 2011005339 A1 1/2011 2011017711 A2 1/2011 2011017721 A1 2/2011 2011017936 A1 2/2011 2011019936 A1 2/2011 2011019936 A1 2/2011 201101933732 A2 3/2011
WO W	2011028456 A2 3/2011 2011028457 A2 3/2011 2011044641 A1 4/2011 2011049985 A1 4/2011 2011059067 A1 5/2011 2011076707 A2 6/2011 2011085259 A2 7/2011 2011085259 A2 7/2011 2011089607 A1 7/2011 2011109746 A2 9/2011 2011119587 A2 9/2011 2011133843 A2 10/2011 2011133928 A2 10/2011 2011151672 A1 12/2011 2012024538 A3 5/2012 2012100263 A2 7/2012 2013015921 A1 1/2013 2013019899 A2 2/2013 2013019899 A2 2/2013 2013019899 A2 2/2013 2013019899 A2 7/2012 2013015921 A1 1/2013 2013019899 A2 10/2013 2013019899 A2 10/2013 2013130563 A1 9/2013 2014143021 A1 9/2014 2017/125375 A1 7/2017 2018122835 A1 7/2018

## OTHER PUBLICATIONS

Feb. 22-26, 2004—Andersen, Gert et al.,—"Utilizing the free running Current Programmed Control as a Power Factor Correction Technique for the two switch Buck-Boost converter"—Applied Power Electronic Conference and Exposition, 2004. APEC '04. Nineteenth Annual IEEE.

Mar. 3-7, 1996—Caricchi F et al.,—"Prototype of Innovative Wheel Direct Drive With Water-Cooled Exial-Flux Motor for Electric Vehicle Applications"—Applied Power Electronics Conference and Expositions, 1996. APEC '96. Conference Proceedings 1996., Eleventh Annual IEEE.

Feb. 15-19, 1998—Caricchi, F. et al.,—"Study of Bi-Directional Buck-Boost Converter Topologies for Application in Electrical Vehicle Motor Drives"—Applied Power Electronics Conference and Exposition, 1998, APEC '98. Conference Proceedings 1998., Thirteenth Annual IEEE.

Nov. 27-30, 1990—Ensling, JHR—"Maximum Power Point Tracking: A Cost Saving Necessity in Solar Energy Systems"—Industrial Electornics Society, 1990. IECON '90., 16th Annual Conference of IEEE.

Feb. 22-26, 2004—Gaboriault, Mark et al.,—"A High Efficiency, Non-Inverting, Buck-Boost DC-DC Converter"—Applied Power Electronics Conference and Exposition, 2004. APEC '04. Nineteenth Annual IEEE.

Feb. 15-19, 1998—Hua, et al.,—"Comparative Study of Peak Power Tracking Techniques for Solar Storage System"—Applied Power Electronics Conference and Exposition, 1998. APEC'98. Conferenced Proceedings 1998., Thirteenth Annual IEEE.

Jun. 20-24, 1993—Sullivan, et al., "A High-Efficiency Maximum Power Point Tracker for Photovoltaic Arrays in a Solar-Powered Race Vehicle"—University of California, Berkeley, Department of Electrical Engineering and OCmputer Sciences—Power Electronics Specialists Conference, 1993. PESC '93 Record., 24th Annual IEEE.

May 19-24, 2002—Bower et at.,—"Certification of Photovoltaic Inverters: The Initial Step Toward PV System Certification"—Photovoltaic Specialists Conferences, 2002. Conference Record of the Twenty-Ninth IEEE.

Jun. 17-21, 2001—Tse et al., "A Novel Maximum Power Point Tracking Technique for PV Panels"—Power Electronics Specialists Conferences, 2001. PESC. 2001 IEEE 32nd Annual.

May 12-18, 2008—Cuadras et al., "Smart Interfaces for Low Power Energy Harvesting Systems"—Instrumentation and Measurement Technology Conferences Proceedings, 2008. IMTC 2008. IEEE.

Dec. 5-9, 1994—Haan, et al., "Test Results of a 130 W AC Module; a modular solar as power station"—Photovoltaic Energy Conversion 1994. Conference Record of the Twenty Fourth. IEEE Phtovoltaic Specialists Conference—1994.

Sep. 1-3, 2008—Jung, et al., "Soft Switching Boost Converter for Photovoltaic Power Generation System"—Power Electronics and Motion Control Conference, 2008. EPE-PEMC 2008.

Jun. 3-5, 2008—Duan, et al., "A Novel High-Efficiency Inverter for Stand Alone and Grid-Connected Systems"—Industrial Electronics and Applications, 2008. ICIEA 2008.

Nov. 7, 2002—Ertl, et al., "A Novel Multicell DC-AC Converter for Application in Renewable Energy Systems"—IEEE Transactions on Industrial Electronics (vol. 49, Issue 5, Oct. 2002).

Oct. 8-12, 2000—Hashimoto, et al., "A Novel High Peforamance Utility Interactive Photovoltain Inverter System"—Industry Applications Conference, 2000. Conference Record of the 2000 IEEE. Feb. 22-26, 2004—Ho, et al., "An Integrated Inverter with Maximum Power Tracking for Grid-Connected PV Systems"—Applied Power Electronics Conference and Exposition, 2004. APEC '04. Nineteenth Annual IEEE.

Nov. 14, 1997 Hua et al., "Control of DC/DC Converters for Solar Energy System with Maximum Power Tracking"—Industrial Electronics, Control and Instrumentation, 1997. IECON 97. 23rd International Conference on Industrial Electronics, Control and Instrumentation vol. 4 of 4.

Sep. 1-3, 2008 Lee et al., "Soft Switching Mutli-Phase Boost Converter for Photovoltaic System"—Power Electronics and Motion Control Conference, 2008. EPE-PEMC 2008.

Jul. 5, 2005, Yao et al., "Tapped-Inductor Buck Converter for High-Step-Down DC-DC Conversion" IEEE Transactions on Power Electronics (vol. 20, Issue 4, Jul. 2005).

Sep. 21-23, 1998 Kretschmar, et al., "An AC Converter with a Small DC Link Capacitor for a 15KW Permanent Magnet Synchronous Integral Motor"—Power Electronics and Variable Speed Drives, 1998. Sevent International Converterest (Conf. Publ. No. 456).

May 25, 2000—Hong Lim, et al., "Simple Maximum Power Point Tracker for Photovoltaic Arrays"—Electronics Letters (vol. 36, Issue 11, May 25, 2000).

Aug. 14-16, 2004 Nishida et al., "A Novel Type of Utility-Interactive Inverter for Phtovoltaic System"—Power Electronics and Mtion Control Conference, 2004. IPEMC 2004.

May 30-Jun. 3, 2011—, Jung, et al., "DC-Link Ripple Reduction of Series-connected Module Integrated Converter for Photovoltaic Systems."—Power Electronics and ECCE Asia (ICPE & ECCE). Jan. 8, 2007, Li et al., "An Analysis of ZVS Two-Inductor Boost Converter under Variable Frequency Operation"—IEEE Transactions on Power Electronics (vol. 22, Issue 1, Jan. 2007).

Sep. 17, 2007 Rodriguez et al., "Analytic Solution to the Photovoltaic Maximum Power Point Problem"—IEEE Transactions on Circuits and Systems I: Regular Papers (vol. 54, Issue 9, Sep. 2007).

Jun. 27, 1997, Reimann et al., "A Novel Control Principle of Bi-Directional DC-DC Power Conversion"—Powre Electronics Specialists Conference 1997. PESC '97 Record.

Sep. 15-22, 2000 Russell et al., "The Massachusetts Electric Solar Project: A Pilot Project to Commercialize Residential PV Systems"—Photovoltaic Specialists Conference, 2000, Conference Record of the Twenty-Eighth IEEE Photovoltaic Specialists Conference—2000.

### OTHER PUBLICATIONS

May 2001, Shimizu et al., "Generation Control Circuit for Photvoltaic Modules"—IEEE Transactions of Power Electronics (vol. 16, Issue 3, May 2001).

Feb. 6-10, 2000, Siri, Kasemsan "Study of System Instability in Current-Mode Converter Power Systems Operating in Solar Array Voltage Regulation Mode"—Applied Power Electronics Conference and Exposition, 2000. APEC 2000. Fiftheenth Annual IEEE. Aug. 13-16, 1990—Rajan, Anita "A Maximum Power Point Tracker Optimized for Solar Powered Cars"—Future Transportation Technology Conference and Expostion.

Jul. 10, 1995—"Battery I.D. chip from Dallas Semiconductor monitors and reports battery pack temperature"—Business Wire. Nov. 3, 1999—Takahashi et al., "Development of a Long-Life Three-Phase Flywheel UPS Using an Electrolytic Capacitorless Converter/Inverter"—Electrical Engineering in Japan, vol. 127.

Jan. 2001—Walker, Geoffrey "Evaluating MPPT Converter Topologies Using a Matlab PV Model"—"Journal of Electrical and Electronics Engineering, Australia".

Feb. 13, 2007—Roman et al., "Experimental Results of Controlled PV Module for Building Integrated PV Systems"—Solar Energy 82 (2008) 471-480.

2006—Bower et al., "Innovative PV Micro-Inverter Topology Eliminates Electrolytic Capacitors for Longer Lifetime"—IEEE 1-4244-0016-3/06/ pp. 2038-2041.

Aug. 23-27, 1993—Case et al., "A Minimum Component Photovoltaic Array Maximum Power Point Tracker"—European Space Power Conference vol. 1. Power Systems, Power Electronics.

Jun. 4, 1997—Maranda et al., "Optimization of the Master-Slave Inverter System for Grid-Connected Photovoltaic Plants"—Energy Convers. Mgmt. vol. 39, No. 12 pp. 1239-1246.

2005—Kang et al., "Photovoltaic Power Interface Circuit Incorporated with a Buck-Boost Converter and a Full-Bridge Inverter"—Applied Energy 82, pp. 266-283.

Nov. 21, 1997—Feuermann et al., "Reversable Low Soalr Heat Gain Windows for Energy Savings"—Solar Energy vol. 62, No. 3 pp. 169-175.

May 16, 2005—Enrique et al., "Theoretical assessment of the maximum power point tracking efficiency of photovoltaic facilities with different converter topologies"—Solar Energy 81 (2007) p. 31-38.

Dehbonei, Hooman "Power Conditioning for Distributed Renewable Energy Generation"—Curtin University of Technology, School of Electrical and Computer Engineering, 2003 568 pages Dissertation: Thesis. Abstract, 1 page—retrieved on Nov. 13, 2017 on https://books.google.com/books/about/Power\_Conditioning\_for\_Distributed\_Renew.html?id=3wVXuAAACAAJ.

Korean Patent Application No. 102005-7008700, filed May 13, 2015. Applicant: Exar Corporation.

Jan. 23, 2018—EP Search Report, EP App No. 17187230.2.

Apr. 16, 2018—EP Examination Report 12707899.6.

Aug. 9, 2010 Hong, Wei, et al., "Charge Equalization of Battery POwer Modules in Series" The 2010 International Power Electronics Conference, IEEE, p. 1568-1572.

Jun. 6, 2018—EP Search Report EP App No. 18151594.1.

Jun. 29, 2018—EP Search Report—EP App No. 18175980.4.

Jun. 23, 2000; Bascope, G.V.T. Barbi, I; "Generation of Family of Non-isolated DC-DC PWM Converters Using New Three-state Switching Cells"; 2000 IEEE 31st Annual Power Electronics Specialists Conference in Galway, Ireland; vol. 2.

Oct. 3-7, 2004; Nobuyoshi, M. et al., "A Controlling Method for Charging Photovoltaic Generation Power Obtained by a MPPT Control Method to Series Connected Ultra-Electric Double Layer Capacitors"—Industry Application Conference, 2004. 39th IAS Annual Meeting. Conference Record of the 2004 IEEE.

Chinese Office Action—CN Appl. 201310035221.8—dated Aug. 11, 2016.

Zhou, Wilson and Theo Phillips—"Industry's First 4-Switch Buck-Boost Controller Achieves Highest Efficiency Using a Single Inducutor—Design Note 369"—Linear Technology Corporation—www. linear.com—2005.

"Micropower Synchronous Buck-Boost DC/DC Converter"— Linear Technology Corporation—www.linear.com/LTC3440— 2001.

Mar. 5-9, 1995—Caricchi, F. et al—20 kW Water-Cooled Prototype of a Buck-Boost Bidirectional DC-DC Converter Topology for Electrical Vehicle Motor Drives—University of Rome—IEEE 1995—pp. 887-892.

Roy, Arunanshu et al—"Battery Charger using Bicycle"—EE318 Electronic Design Lab Project Report, EE Dept, IIT Bombay, Apr. 2006.

Jun. 20-25, 2004—Viswanathan, K. et al—Dual-Mode Control of Cascade Buck-Boost PFC Converter—35th Annual IEEE Power Electronics Specialists Conference—Aachen, Germany, 2004.

Zhang, Pei et al.—"Hardware Design Experiences in ZebraNet"—Department of Electrical Engineering, Princeton University—SenSys '04, Nov. 3-5, 2004.

"High Efficiency, Synchronous, 4-Switch Buck-Boost Controller"— Linear Technology Corporation—www.linear.com/LTC3780— 2005.

May 19-24, 2002—Chomsuwan, Komkrit et al. "Photovoltaic Grid-Connected Inverter Using Two-Switch Buck-Boost Converter"—Department of Electrical Engineering, King Mongkut's Institute of Technology Ladkrabang, Thailand, National Science and Technology Development Agency, Thailand—IEEE—2002.

Midya, Pallab et al.—"Buck or Boost Tracking Power Converter"—IEEE Power Electronics Letters, vol. 2, No. 4—Dec. 2004.

Chinese Office Action—CN Appl. 201510111948.9—dated Sep. 14, 2016.

Chinese Office Action—CN Appl. 201310066888.4—dated Nov. 2, 2016.

"Power-Switching Converters—the Principle, Simulation and Design of the Switching Power (the Second Edition)", Ang, Oliva, et al., translated by Xu Dehong, et al., China Machine Press, Aug. 2010, earlier publication 2005.

European Notice of Opposition—EP Patent 2092625—mailed Nov. 29, 2016.

Mar. 8, 2003—Vishay Siliconix "Si 7884DP—n-Channel 40-V (D-S) MOSFET" (2003).

Chinese Office Action—CN 201510423458.2—mailed Jan. 3, 2017 (english translation provided).

Chinese Office Action—CN 201410098154.9—mailed Mar. 3, 2017 (english translation provided).

European Search Report—EP Appl. 13150911.9—Apr. 7, 2017. Howard et al, "Relaxation on a Mesh: a Formalism for Generalized Localization." Proceedings of the IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS 2001). Wailea, Hawaii, Oct. 2001.

Chinese Office Action and Search Report—CN 201510578586.4—mailed Apr. 19, 2017.

Jul. 13, 2017—Chinese Office Action—CN201210007491.3.

Jul. 31, 2014—Huimin Zhou et al.—"PV Balancers: Concept, Architectures, and Realization"—IEEE Transactions on Power Electronics, vol. 30, No. 7, pp. 3479-3487.

Sep. 15, 2012—Huimin Zhou et. al—"PV balancers: Concept, architectures, and realization"—Energy Conversion Congress and Exposition (ECCE), 2012 IEEE, IEEE pp. 3749-3755.

Jul. 17, 2017—International Search Report—PCT/US2017/031571. Aug. 4, 2017—European Search Report—EP 17165027.

Jul. 19, 2016—Notice of Opposition—EP 2374190—EP App No. 08878650.4

Sep. 28, 2017—European Office Action—EP 08857835.6.

Nov. 2, 2017—EP Search Report App No. 13157876.7.

Nov. 11, 2017—EP Search Report—App No. 17171489.2.

Dec. 14, 2017—EP Search Report App No. 17188362.2.

Dec. 15, 2017—EP Search Report App No. 17188365.5.

2000; Bascope, G.V.T. Barbi, I; "Generation of Family of Non-isolated DC-DC PWM Converters Using New Three-state Switching Cells"; 2000 IEEE 31st Annual Power Electronics Specialists Conference in Galway, Ireland; vol. 2.

### OTHER PUBLICATIONS

Jan. 20, 2005; Duncan, Joseph, A Global Maximum Power Point Tracking DC-DC Converter, Massachussetts Institute of Technology, Dept. of Electrical Engineering and Computer Science Dissertation; 8 pages.

2005; Edelmoser, K.H. et al.; High Efficiency DC-to-AC Power Inverter with Special DC Interface; Professional Paper, ISSN 0005-1144, Automatika 46 (2005) 3-4, 143-148, 6 pages.

2006; Esmaili, Gholamreza; "Application of Advanced Power Electornics in Renewable Energy Sources and Hygrid Generating Systems" Ohio State Univerty, Graduate Program in Electrical and Computer Engineering, Dissertation. 169 pages.

Nov. 13, 2007; Gomez, M; "Consulting in the Solar Power Age," IEEE-CNSV: Consultants' Network of Scilion Valley; 30 pages. Jul. 25, 1995-Jun. 30, 1998; Kern, G; "SunSine (TM)300: Manufacture of an AC Photovoltaic Module," Final Report, Phases I & II; National Renewable Energy Laboratory, Mar. 1999; NREL-SR-520-26085; 33 pages.

May 1, 2000; Kroposki, H. Thomas and Witt, B & C; "Progress in Photovoltaic Components and Systems," National Renewable Energy Laboratory; NREL-CP-520-27460; 7 pages.

Jan. 22-23, 1998 Oldenkamp, H. et al; "AC Modules: Past, Present and Future" Workshop Installing the Solar Solution; Hatfield, UK; 6 pages.

Linear Technology Specification Sheet, LTC3443—"High Current Micropower 600kHz Synchronous Buck-Boost DC/DC Converter"—2004

Linear Technology Specification Sheet, LTC3780—"High Efficiency Synchronous, 4-Switch Buck-Boost Controller"—2005.

Apr. 22, 2004—MICREL—MIC2182 High Efficiency Synchronous Buck Controller.

Apr. 1972—Methods for Utilizing Maximum Power From a Solar Array—Decker, DK.

2000—Evaluating MPPT converter topologies using a MATLAB PV model—Walker, Geoffrey.

Jun. 30, 2008—Wang, Ucilia; Greentechmedia; "National Semi Casts Solarmagic"; www.greentechmedia.com; 3 pages; accessed Oct. 24, 2017.

Sep. 2004; Yuvarajan, S; Dchuan Yu; Shanguang, Xu; "A Novel Power Converter for PHotovoltaic Applications," Journal of Power Sources; vol. 135, No. 1-2, pp. 327-331.

Jun. 1998—Stern M., et al., "Development of a Low-Cost Integrated 20-KW-AC Solar Tracking Subarray for Grid-Connected PV Power System Applications—Final Technical Report"—National Renewable Energy Laboratory; 41 pages.

1997; Verhoeve, C.W.G., et al., "Recent Test Results of AC\_Module inverters," Netherlands Energy Research Foundation ECN, 1997; 3 pages.

2004—Nobuyoshi, M. et al., "A Controlling Method for Charging Photovoltaic Generation Power Obtained by a MPPT Control Method to Series Connected Ultra-Electric Double Layer Capacitors"—Industry Application Conference, 2004. 39th IAS Annual Meeting. Conference Record of the 2004 IEEE.

Feb. 23-27, 1992—Miwa, Brett et al., "High Efficiency Power Factor Correction Using Interleaving Techniques"—Applied Power Electronics Conference and Exposition, 1992. APEC '92. Conference Proceedings 1992., Seventh Annual.

Storfer, Lior, "Enhancing Cable Modem TCP Performance," Texas Instruments Inc. white paper, Jul. 2003.

Philips Semiconductors, Data Sheet PSMN005-55B; PSMN005-55P N-channel logic trenchMOS transistor, Oct. 1999, Product specification, pp. 1-11.

International Preliminary Report on Patentability Issued in corresponding international application No. PCT/US04/16668, filed May 27, 2004.

International Application No. PCT/US13/27965, International Preliminary Examination Report, Sep. 2, 2014.

International Patent Application PCT/US13/027965, International Search Report and Written Opinion, Jun. 2, 2013.

International Application No. PCT/US12/44045, International Preliminary Examination Report, Jan. 28, 2014.

International Patent Application No. PCT/US2012/044045, International Search Report and Written Opinion, Jan. 2, 2013.

International Patent Application No. PCT/US2009/047734, International Search Report and Written Opinion, May 4, 2010.

Linares, Leonor et al., "Improved Energy Capture in Series String Photovoltaics via Smart Distributed Power Electronics," 24th Annual IEEE Applied Power Electronics Conference and Exposition, pp. 904-910, Feb. 15, 2009.

International Patent Application No. PCT/US2010/029929, International Search Report and Written Opinion, Oct. 27, 2010.

Lowe, Electronics Basis: What is a Latch Circuit, http://www.dummies.com/how-to/content/electronics-basics-what-is-a-latch-circuit.html, from Electronics All-in-One for Dummies, Feb. 2012, downloaded Jul. 13, 2014.

International Patent Application No. PCT/US2011/020591, International Search Report and Written Opinion, Aug. 8, 2011.

International Patent Application No. PCT/US2011/033544, International Search Report and Written Opinion, Nov. 24, 2011.

J. Keller and B. Kroposki, titled, "Understanding Fault Characteristics of Inverter-Based Distributed Energy Resources", in a Technical Report NREL/TP-550-46698, published Jan. 2010, pp. 1 through 48.

International Patent Application No. PCT/US2008/081827, International Search Report and Written Opinion, Jun. 24, 2009.

International Patent Application No. PCT/US2010/046274 International Search Report and Written Opinion, Apr. 22, 2011.

International Patent Application No. PCT/US2011/033658, International Search Report and Written Opinion, Jan. 13, 2012.

International Patent Application No. PCT/US2011/029392, International Search Report and Written Opinion, Oct. 24, 2011.

European Patent Application No. 09829487.9, Extended Search Report, Apr. 21, 2011.

International Patent Application No. PCT/US2009/062536, International Search Report and Written Opinion, Jun. 17, 2010.

International Patent Application No. PCT/US2010/022915, International Search Report and Written Opinion, Aug. 23, 2010.

International Patent Application No. PCT/US2010/046272, International Search Report and Written Opinion, Mar. 31, 2011.

Exell et al., "The Design and Development of a Solar Powered Refrigerator", [retrieved on Feb. 13, 2013], Retrieved from the Internet <URL: http://www.appropedia.org/The\_Design\_and\_Development of a Solar Powered Refrigerator>, pp. 1-64.

"Development of Water-Lithium Bromide Low-Temperature Absorption Refridgerating Machine", 2002 Energy & Environment on Database on Noteworthy contributions for Science and Technology (Japan), Research Data (No. 1748) [online], [retrieved on Aug. 29, 2012]. Retrieved from the Internet: <URL: http://dbnstl.nii.ac.jp/english/detail/1748>, pp. 1-4.

Dictionary.com, "air conditioning" [online], [retrieved on Aug. 28, 2012]. Retrieved from the Internet: <URL: http://dictionary.reference.com/browse/air+conditioning?s=t>, pp. 1-3.

International Patent Application No. PCT/US2010/029936, International Search Report and Written Opinion, Nov. 12, 2010.

International Patent Application No. PCT/US08/75127, International Search Report and Written Opinion, Apr. 28, 2009.

International Patent Application No. PCT/US09/35890, International Search Report and Written Opinion, Oct. 1, 2009.

European Patent Application No. 08845104.2, Extended Search Report, Jul. 31, 2014.

European Patent Application No. 11772811.3, Extended Search Report, Dec. 15, 2014.

International Patent Application No. PCT/US2008/082935, International Search Report and Written Opinion, Jun. 25, 2009.

Bhatnagar et al., Silicon Carbide High Voltage (400 V) Shottky Barrier Diodes, IEEE Electron Device Letters, vol. 13 (10) p. 501-503 Oct. 10, 1992.

Jun. 6-10, 2004—Rodriguez, C., and G. A. J. Amaratunga. "Dynamic stability of grid-connected photovoltaic systems." Power Engineering Society General Meeting, 2004. IEEE, pp. 2194-2200.

Nov. 3-Dec. 29, 1999—Kikuchi, Naoto, et al. "Single phase amplitude modulation inverter for utility interaction photovoltaic sys-

### OTHER PUBLICATIONS

tem." Industrial Electronics Society, 1999. IECON'99 Proceedings. The 25th Annual Conference of the IEEE. vol. 1. IEEE, 1999.

Oct. 7-12, 1990—Nonaka, Sakutaro, et al. "Interconnection system with single phase IGBT PWM CSI between photovoltaic arrays and the utility line." Industry Applications Society Annual Meeting, 1990., Conference Record of the 1990 IEEE.

Jun. 23-27, 2002—Calais, Martina, et al. "Inverters for single-phase grid connected photovoltaic systems—an overview." Power Electronics Specialists Conference, 2002. pesc 02. 2002 IEEE 33rd Annual. vol. 4. IEEE, 2002.

Jul. 1999—Marra, Enes Goncalves, and José Antenor Pomilio. "Self-excited induction generator controlled by a VS-PWM bidirectional converter for rural applications." Industry Applications, IEEE Transactions on 35.4 (1999): 877-883.

Apr. 2-5, 2002—Xiaofeng Sun, Weiyang Wu, Xin Li, Qinglin Zhao: A Research on Photovoltaic Energy Controlling System with Maximum Power Point Tracking:; Proceedings of the Power Conversion Conference—Osaka 2002 (Cat. No. 02TH8579) IEEE-Piscataway, NJ, USA, ISBN 0-7803-7156-9, vol. 2, p. 822-826, XP010590259: the whole document.

International Search Report for corresponding PCT/GB2005/050198 completed Jun. 28, 2006 by C. Wirner of the EPO.

Brunello, Gustavo, et al., "Shunt Capacitor Bank Fundamentals and Protection," 2003 Conference for Protective Relay Engineers, Apr. 8-10, 2003, pp. 1-17, Texas A&M University, College Station, TX, USA

Cordonnier, Charles-Edouard, et al., "Application Considerations for Sensefet Power Devices," PCI Proceedings, May 11, 1987, pp. 47-65.

Jun. 9-11, 2003—Kotsopoulos, Andrew, et al., "Predictive DC Voltage Control of Single-Phase PV Inverters with Small DC Link Capacitance," IEEE International Symposium, Month Unknown, 2003, pp. 793-797.

Meinhardt, Mike, et al., "Multi-String-Converter with Reduced Specific Costs and Enhanced Functionality," Solar Energy, May 21, 2001, pp. 217-227, vol. 69, Elsevier Science Ltd.

Mar. 6-10, 2005—Kimball, et al.: "Analysis and Design of Switched Capacitor Converters"; Grainger Center for Electric Machinery and Electromechanics, University of Illinois at Urbana-Champaign, 1406 W. Green St, Urbana, IL 61801 USA, © 2005 IEEE; pp. 1473-1477.

Martins, et al.: "Interconnection of a Photovoltaic Panels Array to a Single-Phase Utility Line From a Static Conversion System"; Power Electronics Specialists Conference, 2000. PESC 00. 2000 IEEE 31st Annual; Jun. 18, 2000-Jun. 23, 2000; ISSN: 0275-9306; pp. 1207-1211, vol. 3.

International Search Report for corresponding PCT/GB2005/050197, completed Dec. 20, 2005 by K-R Zettler of the EPO.

Kjaer, Soeren Baekhoej, et al., "Design Optimization of a Single Phase Inverter for Photovoltaic Applications," IEEE 34th Annual Power Electronics Specialist Conference, Jun. 15-19, 2003, pp. 1183-1190, vol. 3, IEEE.

Jun. 23-27, 2002—Shimizu, Toshihisa, et al., "A Flyback-type Single Phase Utility Interactive Inverter with Low-frequency Ripple Current Reduction on the DC Input for an AC Photovoltaic Module System," IEEE 33rd Annual Power Electronics Specialist Conference 2002, pp. 1483-1488, vol. 3, IEEE.

Written Opinion of PCT/GB2005/050197, Feb. 14, 2006 (mailing date), Enecsys Limited.

Jun. 17-21, 2001—Yatsuki, Satoshi, et al., "A Novel AC Photovoltaic Module System based on the Impedance-Admittance Conversion Theory," IEEE 32nd Annual Power Electronics Specialists Conference, Month Unknown, 2001, pp. 2191-2196, vol. 4, IEEE.

Ciobotaru, et al., Control of single-stage single-phase PV inverter, Aug. 7, 2006.

International Search Report and Written Opinion for PCT/IB2007/004591 dated Jul. 5, 2010.

European Communication for EP07873361.5 dated Jul. 12, 2010. European Communication for EP07874022.2 dated Oct. 18, 2010.

European Communication for EP07875148.4 dated Oct. 18, 2010. Chen, et al., "A New Low-Stress Buck-Boost Converter for Universal-Input PFC Applications", IEEE Applied Power Electronics Conference, Feb. 2001, Colorado Power Electronics Center Publications. Chen, et al., "Buck-Boost PWM Converters Having Two Independently Controlled Switches", IEEE Power Electronics Specialists Conference, Jun. 2001, Colorado Power Electronics Center Publications.

Esram, et al., "Comparison of Photovoltaic Array Maximum Power Point Tracking Techniques", IEEE Transactions on Energy Conversion, vol. 22, No. 2, Jun. 2007, pp. 439-449.

Walker, et al., "Photovoltaic DC-DC Module Integrated Converter for Novel Cascaded and Bypass Grid Connection Topologies—Design and Optimisation", 37th IEEE Power Electronics Specialists Conference, Jun. 18-22, 2006, Jeju, Korea.

Geoffrey R. Walker Affidavit re: U.S. Appl. No. 11/950,271, submitted in an IDS for U.S. Appl. No. 11/950,271 on Mar. 9, 2010. International Search Report for PCT/IB2007/004610 dated Feb. 23, 2009.

International Search Report for PCT/IB2007/004584 dated Jan. 28, 2009.

International Search Report for PCT/IB2007/004586 dated Mar. 5, 2009.

International Search Report for PCT/IB2007/004643 dated Jan. 30, 2009.

International Search Report for PCT/US2008/085736 dated Jan. 28, 2009.

International Search Report for PCT/US2008/085754 dated Feb. 9, 2009.

International Search Report for PCT/US2008/085755 dated Feb. 3, 2009.

Kajihara, et al., "Model of Photovoltaic Cell Circuits Under Partial Shading", 2005 IEEE, pp. 866-870.

Knaupp, et al., "Operation of a 10 KW PV Façade with 100 W AC Photovoltaic Modules", 1996 IEEE, 25th PVSC, May 13-17, 1996, pp. 1235-1238, Washington, DC.

Alonso, et al., "Cascaded H-Bridge Multilevel Converter for Grid Connected Photovoltaic Generators with Independent Maximum Power Point Tracking of Each Solar Array", 2003 IEEE 34th, Annual Power Electronics Specialists Conference, Acapulco, Mexico, Jun. 15-19, 2003, pp. 731-735, vol. 2.

Myrzik, et al., "String and Module Integrated Inverters for Single-Phase Grid Connected Photovoltaic Systems—A Review", Power Tech Conference Proceedings, 2003 IEEE Bologna, Jun. 23-26, 2003, p. 8, vol. 2.

Chen, et al., "Predictive Digital Current Programmed Control", IEEE Transactions on Power Electronics, vol. 18, Issue 1, Jan. 2003. Wallace, et al., "DSP Controlled Buck/Boost Power Factor Correction for Telephony Rectifiers", Telecommunications Energy Conference 2001, INTELEC 2001, Twenty-Third International, Oct. 18, 2001, pp. 132-138.

Alonso, "A New Distributed Converter Interface for PV Panels", 20th European Photovoltaic Solar Energy Conference, Jun. 6-10, 2005, Barcelona, Spain, pp. 2288-2291.

Alonso, "Experimental Results of Intelligent PV Module for Grid-Connected PV Systems", 21st European Photovoltaic Solar Energy Conference, Sep. 4-8, 2006, Dresden, Germany, pp. 2297-2300. Enslin, "Integrated Photovoltaic Maximum Power Point Tracking

Converter", IEEE Transactions on Industrial Electronics, vol. 44, No. 6, Dec. 1997, pp. 769-773.

Sep. 7-9, 1999—Lindgren, "Topology for Decentralised Solar Energy Inverters with a Low Voltage AC-Bus", Chalmers University of Technology, Department of Electrical Power Engineering, EPE '99—Lausanne.

Jun. 20-25, 2004—Nikraz, "Digital Control of a Voltage Source Inverter in a Photovoltaic Applications", 2004 35th Annual IEEE Power Electronics Specialists Conference, Aachen, Germany, 2004, pp. 3266-3271.

Orduz, "Evaluation Test Results of a New Distributed MPPT Converter", 22nd European Photovoltaic Solar Energy Conference, Sep. 3-7, 2007, Milan, Italy.

### OTHER PUBLICATIONS

Jun. 17-21, 2007—Palma, "A Modular Fuel Cell, Modular DC-DC Converter Concept for High Performance and Enhanced Reliability", IEEE 2007, pp. 2633-2638.

Sep. 16-19, 1996—Quaschning, "Cost Effectiveness of Shadow Tolerant Photovoltaic Systems", Berlin University of Technology, Institute of Electrical Energy Technology, Renewable Energy Section. EuroSun '96, pp. 819-824.

Roman, "Intelligent PV Module for Grid-Connected PV Systems", IEEE Transactions on Industrial Electronics, vol. 52, No. 4, Aug. 2006, pp. 1066-1073.

Roman, "Power Line Communications in Modular PV Systems", 20th European Photovoltaic Solar Energy Conference, Jun. 6-10, 2005, Barcelona, Spain, pp. 2249-2252.

Uriarte, "Energy Integrated Management System for PV Applications", 20th European Photovoltaic Solar Energy Conference, Jun. 6-10, 2005, Barcelona, Spain, pp. 2292-2295.

Walker, "Cascaded DC-DC Converter Connection of Photovoltaic Modules", IEEE Transactions on Power Electronics, vol. 19, No. 4, Jul. 2004, pp. 1130-1139.

Oct. 3-7, 1999—Matsui, et al., "A New Maximum Photovoltaic Power Tracking Control Scheme Based on Power Equilibrium at DC Link", IEEE, 1999, pp. 804-809.

Hou, et al., Application of Adaptive Algorithm of Solar Cell Battery Charger, Apr. 2004.

Sep. 15-22, 2000—Stamenic, et al., "Maximum Power Point Tracking for Building Integrated Photovoltaic Ventilation Systems". International Preliminary Report on Patentability for PCT/IB2008/055092 dated Jun. 8, 2010.

International Search Report for PCT/IB2008/055092 dated Sep. 8, 2009

International Search Report and Opinion of International Patent Application WO2009136358 (PCT/IB2009/051831), dated Sep. 16, 2009

Informal Comments to the International Search Report dated Dec. 3, 2009.

PCT/IB2010/052287 International Search Report and Written Opinion dated Sep. 2, 2010.

UK Intellectual Property office, Combined Search and Examination Report for GB1100450.4 under Sections 17 and 18 (3), Jul. 14, 2011.

Jain, et al., "A Single-Stage Grid Connected Inverter Topology for Solar PV Systems with Maximum Power Point Tracking", IEEE Transactions on Power Electronics, vol. 22, No. 5, Sep. 2007, pp. 1928-1940.

Lynch, et al., "Flexible DER Utility Interface System: Final Report", Sep. 2004-May 2006, Northern Power Systems, Inc., Waitsfield, Vermont B. Kroposki, et al., National Renewable Energy Laboratory Golden, Colorado Technical Report NREL/TP-560-39876, Aug. 2006.

Schimpf, et al., "Grid Connected Converters for Photovoltaic, State of the Art, Ideas for improvement of Transformerless Inverters", NORPIE/2008, Nordic Workshop on Power and Industrial Electronics, Jun. 9-11, 2008.

Sandia Report SAND96-2797 I UC-1290 Unlimited Release, Printed Dec. 1996, "Photovoltaic Power Systems and The National Electrical Code: Suggested Practices", by John Wiles, Southwest Technology Development Institute New Mexico State University Las Cruces NM

United Kingdom Intellectual Property Office, Combined Search and Examination Report Under Sections 17 and 18(3), GB1020862.7, dated Jun. 16, 2011.

Jan. 1, 2005; Linear Technology Specification Sheet, LTC3780—"High Efficiency Synchronous, 4-Switch Buck-Boost Controller". Dec. 19, 2005; Edelmoser, K.H. et al.; High Efficiency DC-to-AC Power Inverter with Special DC Interface; Professional Paper, ISSN 0005-1144, Automatika 46 (2005) 3-4, 143-148, 6 pages.

Jan. 29, 2019—European Search Report for EP App No. 18199117. 5.

Jul. 12, 2019—European Search Report—EP 19170538.3.

Sep. 4, 2019—Extended European Search Report—EP 19181247.8. Aug. 6, 2019—Notice of Opposition of European Patent 2232663—Fronius International GmbH.

Sep. 5, 2019—Notice of Opposition of European Patent 2549635—Huawei Technologies Co.

Sep. 5, 2019—Notice of Opposition of European Patent 2549635—Fronius International GmbH.

Solide Arbeit, Heinz Neuenstein, Dec. 2007.

Spitzenwirkungsgrad mit drei Spitzen, Heinz Neuenstien and Andreas Schlumberger, Jan. 2007.

Technical Information, Temperature Derating for Sunny Boy, Sunny Mini Central, Sunny Tripower, Aug. 9, 2019.

Prinout from Energy Matters online Forum, Jul. 2011.

Wayback Machine Query for Energy Matters Online Forum Jul. 2011.

Nov. 27, 2019—European Search Report—3567562.

Baocheng, DC to AC Inverter with Improved One Cycle Control, 2003

Brekken, Utility-Connected Power Converter for Maximizing Power Transfer From a Photovoltaic Source While Drawing Ripple-Free Current, 2002.

Cramer, Modulorientierter Stromrichter Geht In Serienfertigung , SPVSE, 1994.

Cramer, Modulorientierter Stromrichter, Juelich, Dec. 31, 1995. Cramer, String-Wechselrichter Machen Solarstrom Billiger, Elektronik, Sep. 1996.

Dehbonei, A Combined Voltage Controlled and Current Controlled "Dual Converter" for a Weak Grid Connected Photovoltaic System with Battery Energy Storage, 2002.

Engler, Begleitende Untersuchungen zur Entwicklung eines Multi-String-Wechselrichters, SPVSE, Mar. 2002.

Geipel, Untersuchungen zur Entwicklung modulorientierter Stromrichter Modulorientierter Stromrichter für netzgekoppelte Photovoltaik-Anlagen, SPVSE, 1995.

Hoor, DSP-Based Stable Control Loops Design for a Single Stage Inverter, 2006.

Isoda, Battery Charging Characteristics in Small Scaled Photovoltaic System Using Resonant DC-DC Converter With Electric Isolation, 1990.

Jones, Communication Over Aircraft Power lines, Dec. 2006/ Jan. 2007.

Kalaivani, A Novel Control Strategy for the Boost DC-AC Inverter, 2006.

Lee, Powering The Dream, IET Computing & Control Engineering, Dec. 2006/ Jan. 2007.

Lee, A Novel Topology for Photovoltaic Series Connected DC/DC Converter with High Efficiency Under Wide Load Range, Jun. 2007. Lin, LLC DC/DC Resonant Converter with PLL Control Scheme, 2007.

Niebauer, Solarenergie Optimal Nutzen, Stromversorgung, Elektronik, 1996.

Rodrigues, Experimental Study of Switched Modular Series Connected DC-DC Converters, 2001.

Sanchis, Buck-Boost DC-AC Inverter: Proposal for a New Control Strategy, 2004.

Sen, A New DC-to-AC Inverter With Dynamic Robust Performance, 1998.

Shaojun, Research on a Novel Inverter Based on DC/DC Converter Topology, 2003.

Siri, Sequentially Controlled Distributed Solar-Array Power System with Maximum Power Tracking, 2004.

Walko, Poised For Power, IEE Power Engineer, Feb./ Mar. 2005. White, Electrical Isolation Requirements In Power-Over-Ethernet (POE) Power Sourcing Equipment (PSE), 2006.

Yu, Power Conversion and Control Methods for Renewable Energy Sources, May 2005.

Zacharias, Modularisierung in der PV-Systemtechnik—Schnittstellen zur Standardisierung der Komponenten, Institut für Solare Energieversorgungstechnik (ISET), 1996.

Dec. 24, 2019—CN Office Action—CN Application 201610946835.

Jan. 30, 2020-EP Office Action-EP 18204177.2.

Feb. 3, 2020—Chinese Office Action—201710749388.9.

### OTHER PUBLICATIONS

Mar. 24, 2020—Non-Final Rejection—U.S. Appl. No. 15/593,761.

Apr. 20, 2020—European Search Report—EP 20151729.9.

Apr. 23, 2020—European Search Report—EP 19217486.0.

May 12, 2020—Extended European Search Report—EP 20161381.

Jul. 8, 2020—CN Office Action—CN 201710362679.2.

Sep. 17, 2020—Extended European Search Report—EP Application 20176744.9.

Oct. 12, 2020—CN Office Action—CN 201610946835.5.

Nov. 12, 2020—Preliminary Opinion by EPO-EP 12188944.8.

Dec. 31, 2020—CN Invalidation Decision—CN 200780045351.2.

Dec. 31, 2020—CN Invalidation Decision—CN 201210253614.1.

Mar. 3, 2021—EP Office Action—EP 17188365.5.

May 7, 2021—Chinese Office Action—CN 20181025083.8.

Jun. 21, 2021—Japanese Office Action—JP 2017-158887.

Zhao Junjian & al.: "Analysis of high efficiency DC/DC converter processing partial input/output power", 14th Workshop on Control and Modeling for Power Electronics, Jun. 23, 2013 (Jun. 23, 2013), DOI: 10.1109/COMPEL.2013.6626440.

Apr. 14, 2021—European Summons to Oral Proceedings—EP 17724234.4

PV Balancers: Concept, Architectures, and Realization—Huimmin Zhou—IEEE Transactions on Power Electronics vol. 30 No. 7—Jul. 7, 2015

Petition for Inter Partes Review of U.S. Pat. No. 10,256,770; IPR 2021-00540; Petitioner *Altenergy Power Systems Inc* vs. Patent Owner *Tigo Energy Inc*.

Declaration in Support of Petition for Inter Partes Review of U.S. Pat. No. 10,256,770; IPR 2021-00540; Petitioner *Altenergy Power Systems Inc* vs. Patent Owner *Tigo Energy Inc*.

Petition for Inter Partes Review of U.S. Pat. No. 8,988,321; IPR 2021-00541; Petitioner Altenergy Power Systems Inc vs. Patent Owner Tigo Energy Inc.

Declaration in Support of Petition for Inter Partes Review of U.S. Pat. No. 8,933,321; IPR 2021-00541; Petitioner *Altenergy Power Systems Inc* vs. Patent Owner *Tigo Energy Inc*.

Petition for Inter Partes Review of U.S. Pat. No. 8,933,321; IPR 2021-01286; Petitioner *SunSpec Alliance* vs. Patent Owner *Tigo Energy Inc.* 

Declaration in Support of Petition for Inter Partes Review of U.S. Pat. No. 8,933,321; IPR 2021-01286; Petitioner SunSpec Alliance vs. Patent Owner Tigo Energy Inc.

Petition for Inter Partes Review of U.S. Pat. No. 10,256,770; IPR 2021-01287; Petitioner *SunSpec Alliance* vs. Patent Owner *Tigo Energy Inc.* 

Declaration in Support of Petition for Inter Partes Review of U.S. Pat. No. 10,256,770; IPR 2021-01287; Petitioner SunSpec Alliance vs. Patent Owner Tigo Energy Inc.

Maxouris, et al. "United States sets record for most Covid-19 deaths reported in one day," Jan. 13, 2021, CNN, https://www.cnn.com/2021/01/12/health/us-coronavirus-tuesday/index.html.

Texas Instruments, CMOS Ripple-Carry Binary Counter/Dividers, acquired from Harris Semiconductor SCHS030D—Revised Dec. 2003.

Excerpts from IEEE 100—The Authoritative Dictionary of IEEE Standards Terms (7th Ed. 2000).

Excerpts from Paul Horowitz & Winfield Hill—The Art of Electronics (2d. Ed. 1989).

Webeck, Evan, "Coronavirus: California sets another daily case record in possible first sign of 'surge on top of a surge," Jan. 5, 2021, The Mercury News (California).

Declaration of Randy R. Dunton in Support of Petition for Inter Partes Review of U.S. Pat. No. 8,933,321, Petitioner Altenergy Power Systems, Inc. v. Tigo Energy Inc., IPR2021-00541.

Declaration of Randy R. Dunton in Support of Petition for Inter Partes Review of U.S. Pat. No. 10,256,770, Petitioner Altenergy Power Systems, Inc. v. Tigo Energy Inc., IPR2021-00540. Declaration of Randy R. Dunton in Support of Petition for Inter Partes Review of U.S. Pat. No. 8,933,321, Petitioner SunSpec Alliance v. Patent Owner Tigo Energy Inc., IPR2021-01286.

Declaration of Randy R. Dunton in Support of Petition for Inter Partes Review of U.S. Pat. No. 10,256,770, Petitioner SunSpec Alliance v. Patent Owner Tigo Energy Inc., IPR2021-01287.

Nov. 17, 2021—CN Office Action—CN App No. 201810025083.8. Dec. 16, 2021—EP Office Action—EP App. No. 19178054.3.

Noguchi, Short-Current Pulse-Based Maximum-Power-Point Tracking Method for Multiple Photovoltaic-and-Converter Module System, IECON, Feb. 2002.

Siri, Maximum Power Tracking in Parallel Connected Converters, IEEE, Jul. 1993.

Solero, Performance of A 10 kW Power Electronic Interface For Combined Wind/PV Isolated Generating Systems, PESC, 1996. Wu, An Improved Dynamic Power Distribution Control Scheme for Pwm Controlled Converter Modules, IEEE, 1992.

Jun. 30, 2022—Extended EP Search Report—EP App. No. 22150308.

Jul. 7, 2023—European Search Report—EP App. No. 22191698.4. Oct. 5, 2023—European Search Report—EP App. No. 23180721.5. QT Technical Application Papers, "ABB Circuit-Breakers for Direct current Applications", ABB SACE S.p.A., An ABB Group Company, L.V. Breakers, Via Baioni, 35, 24123 Bergamo-Italy, Tel.: +39 035.395.111—Telefax: +39 035.395.306-433, Sep. 2007.

Woyte, et al., "Mains Monitoring and Protection in a European Context", 17th European Photovoltaic Solar Energy Conference and Exhibition, Munich, Germany, Oct. 22-26, 2001, Achim, Woyte, et al., pp. 1-4.

"Implementation and testing of Anti-Islanding Algorithms for IEEE 929-2000 Compliance of Single Phase Photovoltaic Inverters", Raymond M. Hudson, Photovoltaic Specialists Conference, 2002. Conference Record of the Twenty-Ninth IEEE, May 19-24, 2002. Fairchild Semiconductor, Application Note 9016, IGBT Basics 1, by K.S. Oh Feb. 1, 2001.

"Disconnect Switches in Photovoltaic Applications", ABB, Inc., Low Voltage Control Products & Systems, 1206 Hatton Road, Wichita Falls, TX 86302, Phone 888-385-1221, 940-397-7000, Fax: 940-397-7085, 1SXU301197B0201, Nov. 2009.

Walker, "A DC Circuit Breaker for an Electric Vehicle Battery Pack", Australasian Universities Power Engineering Conference and IEAust Electric Energy Conference, Sep. 26-29, 1999.

Combined Search and Examination Report for GB1018872.0 dated Apr. 15, 2011, 2 pages.

International Search Report and Opinion of International Patent Application PCT/2009/051221, dated Oct. 19, 2009.

International Search Report and Opinion of International Patent Application PCT/2009/051222, dated Oct. 7, 2009.

Communication in EP07874025.5 dated Aug. 17, 2011.

IPRP for PCT/IB2008/055095 dated Jun. 8, 2010, with Written Opinion.

ISR for PCT/IB2008/055095 dated Apr. 30, 2009.

ISR for PCT/IL07/01064 dated Mar. 25, 2008.

IPRP for PCT/IB2007/004584 dated Jun. 10, 2009, with Written Opinion.

IPRP for PCT/IB2007/004591 dated Jul. 13, 2010, with Written Opinion.

IPRP for PCT/IB2007/004643 dated Jun. 10, 2009, with Written Opinion.

Written Opinion for PCT/IB2008/055092 submitted with IPRP dated Jun.  $8,\,2010.$ 

IPRP for PCT/US2008/085754 dated Jun. 8, 2010, with Written Opinion dated Jan. 21, 2009.

IPRP for PCT/US2008/085755 dated Jun. 8, 2010, with Written Opinion dated Jan. 20, 2009.

IPRP for PCT/IB2009/051221 dated Sep. 28, 2010, with Written Opinion.

IPRP for PCT/IB2009/051222 dated Sep. 28, 2010, with Written Opinion.

IPRP for PCT/IB2009/051831 dated Nov. 9, 2010, with Written Opinion.

IPRP for PCT/US2008/085736 dated Jun. 7, 2011, with Written Opinion.

### OTHER PUBLICATIONS

IPRP for PCT/IB2010/052287 dated Nov. 22, 2011, with Written Opinion.

ISR for PCT/IB2010/052413 dated Sep. 7, 2010.

UK Intellectual Property Office, Application No. GB1109618.7, Patents Act 1977, Examination Report Under Section 18(3), Sep. 16, 2011

UK Intellectual Property Office, Patents Act 1977: Patents Rules Notification of Grant: Patent Serial No. GB2480015, Nov. 29, 2011. Walker, et al. "PV String Per-Module Maximum Power Point Enabling Converters", School of Information Technology and Electrical Engineering The University of Queensland, Sep. 28, 2003.

Walker, "Cascaded DC-DC Converter Connection of Photovoltaic Modules", 33rd Annual IEEE Power Electronics Specialists Conference. PESC 2002. Conference Proceedings. CAIRNS, Queensland, Australia, Jun. 23-27, 2002; [Annual Power Electronics Specialists Conference], New York, NY: IEEE US, vol. 1, Jun. 23, 2002, pp. 24-29, XP010596060 ISBN: 978-0-7803-7262-7, figure 1.

Baggio, "Quasi-ZVS Activity Auxiliary Commutation Circuit for Two Switches Forward Converter", 32nd Annual IEEE Power Electronics Specialists Conference. PESC 2001. Conference Proceedings. Vancouver, Canada, Jun. 17-21, 2001; [Annual Power Electronics Specialists Conference] New York, NY: IEEE, US.

Ilic, "Interleaved Zero-Current-Transition Buck Converter", IEEE Transactions on Industry Applications, IEEE Service Center, Piscataway, NJ, US, vol. 43, No. 6, Nov. 1, 2007, pp. 1619-1627, XP011197477 ISSN: 0093-9994, pp. 1619-1922.

Lee: "Novel Zero-Voltage-Transition and Zero-Current-Transition Pulse-Width-Modulation Converters", Power Electronics Specialists Conference, 1997, PESC '97, Record, 28th Annual IEEE St. Louis, MO, USA, Jun. 22-27, 1997, New York, NY, USA IEEE, US, vol. 1, Jun. 22, 1997, pp. 233-239, XP010241553, ISBN: 978-07803-3840-1, pp. 233-236.

Sakamoto, "Switched Snubber for High-Frequency Switching Converters", Electronics & Communications in Japan, Part 1—Communications, Wiley, Hoboken, NJ, US, vol. 76, No. 2, Feb. 1, 1993, pp. 30-38, XP000403018 ISSN: 8756-6621, pp. 30-35.

Duarte, "A Family of ZVX-PWM Active-Clamping DC-to-DC Converters: Synthesis, Analysis and Experimentation", Telecommunications Energy Conference, 1995, INTELEC '95, 17th International The Hague, Netherlands, Oct. 29-Nov. 1, 1995, New York, NY, US, IEEE, US, Oct. 29, 1995, pp. 502-509, XP010161283 ISBN: 978-0-7803-2750-4 p. 503-504.

IPRP for PCT/IL2007/001064 dated Mar. 17, 2009, with Written Opinion dated Mar. 25, 2008.

IPRP for PCT/IB2007/004586 dated Jun. 10, 2009, with Written Opinion.

Gao, et al., "Parallel-Connected Solar PV System to Address Partial and Rapidly Fluctuating Shadow Conditions", IEEE Transactions on Industrial Electronics, vol. 56, No. 5, May 2009, pp. 1548-1556. IPRP PCT/IB2007/004610—date of issue Jun. 10, 2009.

Extended European Search Report—EP12176089.6—Mailing date: Nov. 8, 2012.

Gwon-Jong Yu et al: "Maximum power point tracking with temperature compensation of photovoltaic for air conditioning system with fuzzy controller", May 13, 1996; May 13, 1996-May 17, 1996, May 13, 1996 (May 13, 1996), pp. 1429-1432, XP010208423.

Extended European Search Report—EP12177067.1—Mailing Date: Dec. 7, 2012.

GB Combined Search and Examination Report—GB1200423.0—Mailing date: Apr. 30, 2012.

GB Combined Search and Examination Report—GB1201499.9—Mailing date: May 28, 2012.

GB Combined Search and Examination Report—GB1201506.1—Mailing date: May 22, 2012.

"Study of Energy Storage Capacitor Reduction for Single Phase PWM Rectifier", Ruxi Wang et al., Virginia Polytechnic Institute and State University, Feb. 2009. "Multilevel Inverters: A Survey of Topologies, Controls, and Applications", Jose Rodriguez et al., IEEE Transactions on Industrial Electronics, vol. 49, No. 4, Aug. 2002.

Extended European Search Report—EP 08878650.4—Mailing date: Mar. 28, 2013.

Satcon Solstice—Satcon Solstice 100 kW System Solution Sheet—2010.

John Xue, "PV Module Series String Balancing Converters", University of Queensland—School of Information Technology & Electrical Engineering, Nov. 6, 2002.

Robert W. Erickson, "Future of Power Electronics for Photovoltaics", IEEE Applied Power Electronics Conference, Feb. 2009.

International Search Report for corresponding PCT/GB2004/001965, completed Aug. 16, 2004 by A. Roider.

Mar. 5-9, 1995—Naik et al., A Novel Grid Interface for Photovoltaic, Wind-Electric, and Fuel-Cell Systems With a Controllable Power Factor or Operation, IEEE, 1995, pp. 995-998.

Petkanchin, Processes following changes of phase angle between current and voltage in electric circuits, Aug. 1999, Power Engineering Review, IEEE vol. 19, Issue 8, pp. 59-60.

Mumtaz, Asim, et al., "Grid Connected PV Inverter Using a Commercially Available Power IC," PV in Europe Conference, Oct. 2002, 3 pages, Rome, Italy.

Koutroulis, Effichios, et al., "Development of a Microcontroller-Based, Photovoltaic Maximum Power Point Tracking Control System," IEEE Transactions on Power Electronics, Jan. 2001, pp. 46-54, vol. 16, No. 1, IEEE.

European Search Report—EP App. 14159457.2—mailed Jun. 12, 2015.

European Search Report and Written Opinion—EP Appl. 12150819. 6—dated Jul. 6, 2015.

Alonso, O. et al. "Cascaded H-Bridge Multilevel Converter for Grid Connected Photovoltaic Generators With Independent Maximum Power Point Tracking of Each Solar Array." IEEE 34th Annual Power Electronics Specialists Conference. vol. 2, Jun. 15, 2003.

Chinese Office Action—CN Appl. 201280006369.2—dated Aug. 4, 2015.

Chinese Office Action—CN Appl. 201210253614.1—dated Aug. 18, 2015.

Extended European Search Report—EP Appl. 04753488.8—mailed Apr. 29, 2015.

International Search Report—PCT/US2004/016668, form PCT/ISA/220—filing date May 27, 2004—mailed Jan. 19, 2005.

US Office Action—U.S. Appl. No. 13/785,857—mailed Jun. 6, 2013

Supplementary Partial European Search Report—EP Appl. 04753488. 8—mailed Feb. 2, 2015.

Written Opinion of the International Searching Authority—PCT/US2004/016668, form PCT/ISA/220—filing date May 27, 2004—mailed Jan. 19, 2005.

International Search Report from PCT/US04/16668, form PCT/ISA/220, filing date May 27, 2004.

The International Search Report (Form PCT /ISA/220) Issued in corresponding international application No. PCT/ US04/16668, filed May 27, 2004.

Extended European Search Report, EP Application 04753488.8, mailed Apr. 29, 2015.

Partial Extended European Search Report, EP Application 04753488. 8, mailed Feb. 2, 2015.

Office Action U.S. Appl. No. 13/785,857, dated Jun. 6, 2013.

European Office Action—EP Appl. 09725443.7—dated Aug. 18, 2015.

Definition of Isomorphism by Merriam-Webster, <a href="http://www.merriaum-webster.com/dictionary/isomorphism">http://www.merriaum-webster.com/dictionary/isomorphism</a>, dated Oct. 20, 2015. Definition of Isomorphic by Merriam-Webster, <a href="http://www.merriam-webster.com/dictionary/isomorphic">http://www.merriam-webster.com/dictionary/isomorphic</a>, dated Oct. 20, 2015.

Chinese Office Action—CN Appl. 201110349734.7—dated Oct. 13, 2015.

Chinese Office Action—CN Appl. 201210007491.3—dated Nov. 23, 2015.

European Office Action—EP Appl. 12176089.6—dated Dec. 16, 2015

### OTHER PUBLICATIONS

Chinese Office Action—CN Appl. 201310035223.7—dated Dec. 29, 2015.

Chinese Office Action—CN Application 201210334311.2—dated Jan. 20, 2016.

European Search Report—EP Appl. 13800859.4—mailed Feb. 15, 2016.

Chinese Office Action—CN App. 201310035221.8—mailed Mar. 1, 2016.

PCT/2008/058473 International Preliminary Report, 6 pages, Nov. 2, 2009.

International Search Report and Written Opinion, WO 2010080672, dated Aug. 19, 2010.

PCT/US2010/045352 International Search Report and Written Opinion; 12 pages; Oct. 26, 2010.

International Search Report and Written Opinion mailed Feb. 6, 2009,. In counterpart PCT/US2008/008451, 13 pages.

European Search Report: dated Jan. 10, 2013 in corresponding EP application No. 09838022.3, 7 pages.

D. Ton and W. Bower; Summary Report of the DOE High-Tech Inverter Workshop; Jan. 2005.

First Action Interview Pre-Interview Communication from U.S. Appl. No. 13/174,495 mailed Jun. 18, 2014, 7 pgs.

Johnson et al., "Arc-fault detector algorithm evaluation method utilizing prerecorded arcing signatures", Photovoltaic Specialists Conference (PVSC), Jun. 2012.

Aug. 6, 2007—Philippe Welter, et al. "Electricity at 32 kHz," Photon International, The Photovoltaic Magazine, Http://www.photon-magazine.com/archiv/articles.aspx?criteria=4&HeftNr=0807 &Title=Elec . . . printed May 27, 2011).

PCT/US2009/069582 Int. Search Report—dated Aug. 19, 2010. Chinese Office Action—CN Appl. 201210007491.3—mailed Apr.

25, 2016. CN Office Action—CN Appl. 201310004123.8—dated May 5,

Law et al, "Design and Analysis of Switched-Capacitor-Based Step-Up Resonant Converters," IEEE Transactions on Circuits and Systems, vol. 52, No. 5, published May 2005.

CN Office Action—CN Appl. 201310066888.4—dated May 30, 2016.

European Search Report—EP Appl. 13152966.1—dated Jul. 21, 2016

European Search Report—EP Appl. 12183811.4—dated Aug. 4, 2016

European Notice of Opposition—EP Patent 2374190—dated Jul. 19, 2016.

"Es werde Dunkelheit. Freischaltung von Solarmodulen im Brandfall"—"Let there be Darkness: Quality control of Solar Modules in Case of Fire"; Photon, May 2005, 75-77, ISSN 1430-5348, English translation provided.

Chinese Office Action—CN Appl. 201380029450.7—dated Jul. 28, 2016

Jun. 1, 2024—Chinese Office Action—CN App. No. 202110496807.

Dec. 12, 2023—Japanese Office Action—JP App. No. 2020-004452.

Jan. 18, 2023—Chinese Notice of Allowance—CN App. No. 202010044554.7.

Jan. 30, 2024—CN Office Action—CN 202110858752.1

Summons to Oral Proceedings Pursuant to Rule 115(1) EPC, dated Feb. 26, 2024 regarding EP Patent No. 2557650.

GB Combined Search and Examination Report—GB1203763.6—Mailing date: Jun. 25, 2012.

Mohammad Reza Amini et al., "Quasi Resonant DC Link Inverter with a Simple Auxiliary Circuit", Journal of Power Electronics, vol. 11, No. 1, Jan. 2011.

Khairy Fathy et al., "A Novel Quasi-Resonant Snubber-Assisted ZCS-PWM DC-DC Converter with High Frequency Link", Journal of Power Electronics, vol. 7, No. 2, Apr. 2007.

May 22, 1998—Cheng K.W.E., "New Generation of Switched Capacitor Converters", Department of Electrical Engineering, The Hong Kong Polytechnic University, Hung Hom, Hong Kong, Power Electronics Conference, PESC 98.

1999—Per Karlsson, "Quasi Resonant DC Link Converters—Analysis and Design for a Battery Charger Application", Universitetstryckeriet, Lund University, 1999, ISBN 91-88934-14-4; Added to Lund University Publications on Jun. 4, 2012.

Hsiao Sung-Hsin et al., "ZCS Switched-Capacitor Bidirectional Converters with Secondary Output Power Amplifier for Biomedical Applications", Power Electronics Conference (IPEC) Jun. 21, 2010. Nov. 27-30, 2007—Yuang-Shung Lee et al., "A Novel QR ZCS Switched-Capacitor Bidirectional Converter", IEEE, 2007.

Antti Tolvanen et al., "Seminar on Solar Simulation Standards and Measurement Principles", May 9, 2006 Hawaii.

J.A. Eikelboom and M.J. Jansen, "Characterisation of PV Modules of New Generations—Results of tests and simulations", Jun. 2000. Yeong-Chau Kuo et al., "Novel Maximum-Power-Point-Tracking Controller for Photovoltaic Energy Conversion System", IEEE Transactions on Industrial Electronics, vol. 48, No. 3, Jun. 2001. C. Liu et al., "Advanced Algorithm for MPPT Control of Photovoltaic Systems", Canadian Solar Buildings Conference, Montreal, Aug. 20-24, 2004.

May 22, 1998—Chihchiang Hua and Chihming Shen, "Study of Maximum Power Tracking Techniques and Control of DC/DC Converters for Photovoltaic Power System", IEEE.

Tore Skjellnes et al., "Load sharing for parallel inverters without communication", Nordic Workshop in Power and Industrial Electronics, Aug. 12-14, 2002.

Jun. 23, 2000—Giorgio Spiazzi at el., "A New Family of Zero-Current-Switching Variable Frequency dc-dc Converters", IEEE. Nayar, C.V., M. Ashari and W.W.L Keerthiphala, "A Grid Interactive Photovoltaic Uninterruptible Power Supply System Using Battery Storage and a Back up Diesel Generator", IEEE Transactions on Energy Conversion, vol. 15, No. 3, Sep. 2000, pp. 348?353. Ph. Strauss et al., "AC coupled PV Hybrid systems and Micro Grids-state of the art and future trends", 3rd World Conference on Photovoltaic Energy Conversion, Osaka, Japan May 11-18, 2003. Jul. 16-20, 2000—Nayar, C.V., abstract, Power Engineering Society Summer Meeting, 2000. IEEE, 2000, pp. 1280-1282 vol. 2.

Mar. 15, 2004—D. C. Martins et al., "Analysis of Utility Interactive Photovoltaic Generation System using a Single Power Static Inverter", Asian J. Energy Environ., vol. 5, Issue 2, (2004), pp. 115-137.

Rafael C. Beltrame et al., "Decentralized Multi String PV System With Integrated ZVT Cell", Congresso Brasileiro de Automática / Sep. 12-16, 2010, Bonito-MS.

Sergio Busquets-Monge et al., "Multilevel Diode-clamped Converter for Photovoltaic Generators With Independent Voltage Control of Each Solar Array", IEEE Transactions on Industrial Electronics, vol. 55, No. 7, Jul. 2008.

Soeren Baekhoej Kjaer et al., "A Review of Single-Phase Grid-Connected Inverters for Photovoltaic Modules", IEEE Transactions on Industry Applications, vol. 41, No. 5, Sep./Oct. 2005.

Office Action—JP 2011-539491—Mailing date: Mar. 26, 2013

Supplementary European Search Report—EP08857456—Mailing Date Dec. 6, 2013.

Extended European Search Report—EP14151651.8—Mailing date: Feb. 25, 2014.

Iyomori H et al: "Three-phase bridge power block module type auxiliary resonant AC link snubber-assisted soft switching inverter for distributed AC power supply", INTELEC 2003. 25th. International Telecommunications Energy Conference. Yokohama, Japan, Oct. 19-23, 2003; Tokyo, IEICE, JP, Oct. 23, 2003 (Oct. 23, 2003), pp. 650-656, XP031895550, ISBN: 978-4-88552-196-6.

Yuqing Tang: "High Power Inverter EMI characterization and Improvement Using Auxiliary Resonant Snubber Inverter", Dec. 17, 1998 (Dec. 17, 1998), XP055055241, Blacksburg, Virginia Retrieved from the Internet: URL:http:jjscholar.lib.vt.edu/theses/available/etd-012299-165108/unrestricted/THESIS. PDF, [retrieved on Mar. 5, 2013].

Yoshida M et al: "Actual efficiency and electromagnetic noises evaluations of a single inductor resonant AC link snubber-assisted three-phase soft-switching inverter", INTELEC 2003. 25th. Inter-

### OTHER PUBLICATIONS

national Telecommunications Energy Conference. Yokohama, Japan, Oct. 19-23, 2003; Tokyo, IEICE, JP, Oct. 23, 2003 (Oct. 23, 2003), pp. 721-726, XP031895560, ISBN: 978-4-88552-196-6.

Third party observation—EP07874025.5—Mailing date: Aug. 6, 2011

Extended European Search Report—EP 13152967.9—Mailing date: Aug. 28, 2014.

Extended European Search Report—EP 14159696—Mailing Date: Jun. 20, 2014.

Gow Ja A et al: "A Modular DC-DC Converter and Maximum Power Tracking Controller For Medium to Large Scale Photovoltaic Generating Plant'8<SUP>th </SUP> European Conference on Power Electronics and Applications. Lausaane, CH, Sep. 7-9, 1999, EPE. European Conference on Power Electronics and Applications, Brussls: EPE Association, BE, vol. Conf. 8, Sep. 7, 1999, pp. 1-8, XP000883026.

Chihchiang Hua et al: "Comparative Study of Peak Power Tracking Techniques for Solar Storage System" Applied Power Electronics Conference and Exposition, 1998. APEC '98. Conference Proceedings 1998, Thirteenth Annual Anaheim, CA USA Feb. 15-19, 1998, New York, NY, USA, IEEE, US, Feb. 15, 1998, pp. 679-685, XP010263666.

Matsuo H et al: "Novel Solar Cell Power Supply System Using the Multiple-input DC-DC Converter" 20<SUP>th</SUP> International telecommunications Energy Conference. Intelec '98 San Francisco, CA, Oct. 4-8, 1998, Intelec International Telecommunications Energy Conference, New York, NY: IEEE, US, Oct. 4, 1998, pp. 797-802, XP000896384.

Chihchiang Hua et al: "DSP-based controller application in battery storage of photovoltaic system" Industrial Electronics, Control, and Instrumentation, 1996, Proceedings of the 1996 IEEE IECON 22<SUP>nd</SUP> International Conference on Taipei, Taiwan Aug. 5-10, 1996, New York, NY, USA, IEEE, US, Aug. 5, 1996, pp. 1705-1710, XP010203239.

Hua C et al: "Implementation of a DSP-Controlled Photovoltaic System with Peak Power Tracking" IEEE Transactions on industrial Electronics, IEEE, Inc. New York, US, vol. 45, No. 1, Feb. 1, 1998, pp. 99-107, XP000735209.

I. Weiss et al.: "A new PV system technology-the development of a magnetic power transmission from the PV module to the power bus" 16th European Photovoltaic Solar Energy Conference, vol. III, May 1-5, 2000, pp. 2096-2099, XP002193468 Glasgow, UK cited in the application.

Basso, Tim, "IEEE Standard for Interconnecting Distributed Resources With the Electric Power System," IEEE PES Meeting, Jun. 9, 2004. Feb. 11, 2003—Boostbuck.com, "The Four Boostbuck Topologies," located at http://www.boostbuck.com/TheFourTopologies.html.

Apr. 2002—Gautam, Nalin K. et al., "An Efficient Algorithm to Simulate the Electrical Performance of Solar Photovoltaic Arrays," Energy, vol. 27, No. 4, pp. 347-361, 2002.

Nordmann, T. et al., "Performance of PV Systems Under Real

Nordmann, T. et al., "Performance of PV Systems Under Real Conditions," European Workshop on Life Cycle Analysis and Recycling of Solar Modules, The "Waste" Challenge, Brussels, Belgium, Mar. 18-19, 2004.

Wiles, John, "Photovoltaic Power Systems and the National Electrical Code: Suggested Practices," Sandia National Laboratories, document No. SAND2001-0674, Mar. 2001.

Hewes, J. "Relays," located at http://web.archive.org/web/20030816010159/www.kpsec.freeuk.com/components/relay.htm, Aug. 16, 2003.

Jan. 1, 1993—Definition of "remove" from Webster's Third New International Dictionary, Unabridged, 1993.

Jan. 1, 1993—Definition of "removable" from Webster's Third New International Dictionary, Unabridged, 1993.

Advanced Energy Group, "The Basics of Solar Power Systems," located at http://web.archive.org/web/20010331044156/http://www.solar4power.com/solar-power-basics.html, Mar. 31, 2001.

International Patent Application No. PCT/AU2005/001017, International Search Report and Written Opinion, Aug. 18, 2005.


Baek, Ju-Won et al., "High Boost Converter using Voltage Multiplier," 2005 IEEE Conference, IECON 05, pp. 567-572, Nov. 2005. Wikimedia Foundation, Inc., "Electric Power Transmission," located at http://web.archive.org/web/20041210095723/en.wikipedia.org/wiki/Electric-power-transmission, Nov. 17, 2004.


Jacobsen, K.S., "Synchronized Discrete Multi-Tone (SDMT) Modulation for Cable Modems: Making the Most of the Scarce Reverse Channel Bandwidth," Conference Proceedings of Wescon/97, pp. 374-380, Nov. 4, 1997.

Loyola, L. et al., "A Multi-Channel Infrastructure based on DCF Access Mechanism for Wireless LAN Mesh Networks Compliant with IEEE 802.11," 2005 Asia-Pacific Conference on Communications, pp. 497-501, Oct. 5, 2005.

Subudhi et al., "A Comparative Study on Maximum Power Point Tracking Techniques for Photovoltaic Power Systems," IEEE Transactions on Sustainable Energy, vol. 4, No. 1, Jan. 2013.

\* cited by examiner













Fig. 3
















Pigure 70











Figure 8B







# SAFETY MECHANISMS, WAKE UP AND SHUTDOWN METHODS IN DISTRIBUTED POWER INSTALLATIONS

# CROSS REFERENCE TO RELATED APPLICATIONS

The present application is a continuation of U.S. application Ser. No. 15/369,881, filed Dec. 5, 2016, which is a continuation-in-part of U.S. application Ser. No. 13/372, 10 009, filed Feb. 13, 2012 (now U.S. Pat. No. 9,590,526), which is a continuation of U.S. application Ser. No. 12/329, 525, filed Dec. 5, 2008 (now U.S. Pat. No. 8,531,055), which claims the benefit of U.S. Provisional Application Ser. No. 60/992,589, filed Dec. 5, 2007. U.S. application Ser. No. 15 12/329,525, filed Dec. 5, 2008 is a continuation-in-part of U.S. application Ser. No. 11/950,271, filed Dec. 4, 2007 (now U.S. Pat. No. 9,088,178), which claims the benefit of each of U.S. Provisional Application Ser. No. 60/916,815, filed May 9, 2007, U.S. Provisional Application Ser. No. 20 60/908,095, filed Mar. 26, 2007, U.S. Provisional Application No. 60/868,962, filed Dec. 7, 2006, U.S. Provisional Application No. 60/868,851, filed Dec. 6, 2006, and U.S. Provisional Application No. 60/868,893, filed Dec. 6, 2006. U.S. application Ser. No. 15/369,881 also is a continuation- 25 in-part of U.S. application Ser. No. 14/323,531, filed Jul. 3, 2014 (now U.S. Pat. No. 9,960,667), which is a continuation of U.S. application Ser. No. 12/328,742, filed Dec. 4, 2008 (now U.S. Pat. No. 8,816,535), which is a continuation-inpart of U.S. application Ser. No. 11/950,271, filed Dec. 4, 30 2007. Each of the above-mentioned disclosures are incorporated herein by reference in their entireties and for all purposes.

### FIELD AND BACKGROUND

The present invention relates to distributed power systems and, more particularly, wake-up and shutdown algorithms for the photovoltaic distributed power systems. The present invention also relates to anti-islanding in a distributed power 40 system and, more particularly, system and method for protection of photovoltaic distributed power equipment and personnel during anti-islanding.

Utility networks provide an electrical power system to utility customers. The distribution of electric power from 45 utility companies to customers utilizes a network of utility lines connected in a grid-like fashion, referred to as an electrical grid. The electrical grid may consist of many independent energy sources energizing the grid in addition to utility companies energizing the grid, with each indepen- 50 dent energy source being referred to as a distributed power (DP) generation system. The modern utility network includes the utility power source, consumer loads, and the distributed power generation systems which also supply electrical power to the network. The number and types of 55 distributed power generation systems is growing rapidly and can include photovoltaics, wind, hydro, fuel cells, storage systems such as battery, super-conducting flywheel, and capacitor types, and mechanical devices including conventional and variable speed diesel engines, Stirling engines, 60 gas turbines, and micro-turbines. These distributed power generation systems are connected to the utility network such that they operate in parallel with the utility power sources.

One common problem faced by modern utility networks is the occurrence of islanding. Islanding is the condition 65 where a distributed power generation system is severed from the utility network, but continues to supply power to por-

2

tions of the utility network after the utility power supply is disconnected from those portions of the network. All photovoltaic systems must have anti islanding detection in order to comply with safety regulations. Otherwise the photovoltaic installation may shock or electrocute repairmen after the grid is shut down from the photovoltaic installation generating power as an island downstream. The island condition complicates the orderly reconnection of the utility network and poses a hazard also to equipment. Thus, it is important for an island condition to be detected and eliminated.

Several techniques have been proposed to guard against islanding. For example, one method involves the monitoring of auxiliary contacts on all circuit breakers of the utility system between its main source of generation and DP systems. The auxiliary contacts are monitored for a change of state which represents an open circuit breaker on the utility source. The utility circuit breaker is typically monitored and tripped by external protective relays. When a loss of utility is detected by the change in state of the auxiliary contact of a circuit breaker, a transferred trip scheme is employed to open the interconnection between the utility and the distributed power system. A transferred trip scheme uses the auxiliary contacts of the utility source being monitored. The auxiliary contacts are connected in parallel with other devices which can trigger the trip of the local interconnection breaker. When the auxiliary contacts change state, a trip is induced on the local interconnection breaker. This prevents an island condition from occurring. The drawback of such a method is that often the point of utility isolation (the point at which the utility circuit breaker opens) is of such a distance from the local distributed power system that running a contact status signal back to the local distributed power system control system is not practical.

Anti-islanding schemes presently used or proposed include passive schemes and active schemes. Passive schemes are based on local monitoring of the grid signals, such as under or over voltage, under or over frequency, rate of change of frequency, phase jump, or system harmonics, for example. Active schemes are based on active signal injection with monitoring of the resulting grid signals, such as impedance measurement for example, or active signal injection with active controls, such as active frequency shifting or active voltage shifting for example. With active schemes, some distortion may occur in the output current waveform, thereby resulting in a tradeoff between islanding detection time and waveform distortion, with faster detection typically resulting in higher total harmonic distortion.

A conventional installation of a solar distributed power system 10, including multiple solar panels 101, is illustrated in FIG. 1. Since the voltage provided by each individual solar panel 101 is low, several panels 101 are connected in series to form a string 103 of panels 101. For a large installation, when higher current is required, several strings 103 may be connected in parallel to form overall system 10. The interconnected solar panels 101 are mounted outdoors, and connected to a maximum power point tracking (MPPT) module 107 and then to an inverter 104. MPPT 107 is typically implemented as part of inverter 104 as shown in FIG. 1. The harvested power from DC sources 101 is delivered to inverter 104, which converts the direct-current (DC) into alternating-current (AC) having a desired voltage and frequency, which is usually 110V or 220V at 60 Hz, or 220V at 50 Hz. The AC current from inverter 104 may then be used for operating electric appliances or fed to the power

As noted above, each solar panel 101 supplies relatively very low voltage and current. A problem facing the solar

array designer is to produce a standard AC current at 120V or 220V root-mean-square (RMS) from a combination of the low voltages of the solar panels. The delivery of high power from a low voltage requires very high currents, which cause large conduction losses on the order of the second power of 5 the current i<sup>2</sup>. Furthermore, a power inverter, such as inverter 104, which is used to convert DC current to AC current, is most efficient when its input voltage is slightly higher than its output RMS voltage multiplied by the square root of 2 (which is the peak voltage). Hence, in many applications, the power sources, such as solar panels 101, are combined in order to reach the correct voltage or current. A large number of panels 101 are connected into a string 103 and strings 103 are connected in parallel to power inverter 15 104. Panels 101 are connected in series in order to reach the minimal voltage required for inverter 104. Multiple strings 103 are connected in parallel into an array to supply higher current, so as to enable higher power output.

FIG. 1B illustrates one serial string 103 of DC sources, 20 e.g., solar panels 101a-101d, connected to MPPT circuit 107 and inverter 104. The current versus voltage (IV) characteristics is plotted (110a-110d) to the left of each DC source 101. For each DC power source 101, the current decreases as the output voltage increases. At some voltage value, the 25 current goes to zero, and in some applications the voltage value may assume a negative value, meaning that the source becomes a sink. Bypass diodes (not shown) are used to prevent the source from becoming a sink. The power output of each source 101, which is equal to the product of current 30 and voltage (P=i\*V), varies depending on the voltage drawn from the source. At a certain current and voltage, close to the falling off point of the current, the power reaches its maximum. It is desirable to operate a power generating cell at this maximum power point (MPP). The purpose of the MPPT is 35 to find this point and operate the system at this point so as to draw the maximum power from the sources.

In a typical, conventional solar panel array, different algorithms and techniques are used to optimize the integrated power output of system 10 using MPPT module 107. 40 MPPT module 107 receives the current extracted from all of solar panels 101 together and tracks the maximum power point for this current to provide the maximum average power such that if more current is extracted, the average voltage from the panels starts to drop, thus lowering the 45 harvested power. MPPT module 107 maintains a current that yields the maximum average power from system 10.

However, since power sources 101a-101d are connected in series to single MPPT 107, MPPT 107 selects a maximum power point which is some average of the maximum power 50 points of the individual serially connected sources 101. In practice, it is very likely that MPPT 107 would operate at an I-V point that is optimum for only a few or none of sources 101. In the example of FIG. 1B, the selected point is the maximum power point for source 101b, but is off the 55 maximum power point for sources 101a, 101c and 101d. Consequently, the arrangement is not operated at best achievable efficiency.

The present applicant has disclosed in co-pending U.S. application Ser. No. 11/950,271 entitled "Distributed Power 60 Harvesting System Using DC Power Sources", the use of an electrical power converter, e.g., DC-to-DC converter, attached to the output of each power source, e.g., photovoltaic panel. The electrical power converter converts input power to output power by monitoring and controlling the 65 input power at a maximum power level. This system may be used also to address the anti-islanding issue.

4

The term "signaling" or "signaling mechanism" as used herein refers to either a signal modulated on an electromagnetic carrier signal or a simple unmodulated signal such as an on/off signal "keep alive" signal or "dry contact" signal. For a modulated signal, the modulation method may be by any such method known in the art by way of example, frequency modulation (FM) transmission, amplitude modulation (AM), FSK (frequency shift keying) modulation, PSK (phase shift keying) modulation, various QAM (Quadrature amplitude modulation) constellations, or any other method of modulation.

The term "leakage" as used herein refers to electrical power which is radiated or conducted into an electrical signal line typically at low levels and typically because of insufficient isolation.

The term "power module" as used herein includes power converters such as a DC-DC power converter but also includes modules adapted to control the power passing through the module or a portion of the power, whether by switching or other means.

#### **SUMMARY**

The following summary of the invention is included in order to provide a basic understanding of some aspects and features of the invention. This summary is not an extensive overview of the invention and as such it is not intended to particularly identify key or critical elements of the invention or to delineate the scope of the invention. Its sole purpose is to present some concepts of the invention in a simplified form as a prelude to the more detailed description that is presented below.

According to an aspect of the present invention, there is provided a distributed power system including a DC power source and a power module. The power module includes an input coupled respectively to the DC power source and an output. An inverter is coupled to the output. The inverter converts power input from the output of the power module to output power. A signaling mechanism between the inverter and the power module is adapted for controlling operation of the power module. During operation of the distributed power system, in some embodiments, the signaling mechanism may superimpose a signal on the output of the power module. The signaling mechanism may include a switch integrated with the inverter, the switch modulating the signal onto the output of the power module. A receiver integrated with the power modules receives the signal from the inverter. Alternatively a detection mechanism in the power module detects a signal at the frequency of the electrical grid. Alternatively, a signal from the electrical grid is detected in the output of the power module at a higher frequency up-converted from the frequency of the electrical grid. Alternatively, a detection mechanism in the power module detects a switching frequency of the inverter. The power modules are may be configured for operation in a safety mode, and during the safety mode, the power at the output of the power module, the voltage across the output of the power module, and/or the current flowing through it, are limited so as not to endanger personnel. The power module may include a detection mechanism wherein during operation of the distributed power system, the detection mechanism detects a signal from the inverter. Based on the signal, the operation of the power module is varied from the safety mode of operation to a normal mode of operation for converting power of the DC power source from the input to the output of the power module.

According to another aspect of the present invention there is provided a method for operating a distributed power system. The system includes a DC power source and a power module. The power module includes an input coupled to the DC power source. The power module includes an output. An inverter is coupled to the output of the power module. The inverter converts a power output from the power module to an output power. The method includes operating the power modules in a safety mode by limiting the power output from the power module. The safety mode is characterized by 10 having less than a predetermined amount (e.g. ten milliamperes) of current flow and/or less than a predetermined amount (e.g. 2 Volts) through the output of the power module. A signal from the inverter is preferably monitored and upon detecting the signal from the inverter, the power 15 input to the inverter is increased by operating the power module in a normal mode of operation for converting power of the DC power source from the input to the output of the power module. Upon detecting the signal and prior to the operation of the power module in the normal mode of 20 operation, the voltage of the output of the power module is preferably ramped up slowly. The normal mode of operation of the power module may include controlling a maximum peak power at the input coupled to the DC power sources.

According to an aspect of the present invention, there is 25 provided in a distributed power system multiple DC power sources and multiple power modules which include inputs coupled respectively to the DC power sources. The power modules each include outputs coupled in series to form a serial string. An inverter is coupled to the serial string. The 30 inverter converts power input from the string and produces output power. A protection mechanism in the power modules shuts down the power modules and ceases the power input to the inverter when the inverter stops producing the output power. Typically, the inverter is connected to the electrical 35 grid. A monitoring mechanism is attached to the electrical grid which monitors one or more electrical parameters of the electrical grid. A shutdown mechanism is attached to the monitoring mechanism which when one or more of the electrical parameters is out of predetermined specification, 40 the inverter stops the production of the output power or disconnects from the grid. A switch is preferably disposed between the serial string and the inverter. The switch is activated by the shutdown mechanism and the protection mechanism senses a change in current flowing through the 45 serial string when the switch is activated. When the switch is connected serially with the serial string, the protection mechanism senses that current less than a previously specified minimal threshold current in the serial string; or when the switch is connected in parallel with the serial string the 50 protection mechanism senses a current greater than a previously specified maximal threshold current in the string. Alternatively a signal-providing mechanism is attached to the inverter which provides a signal based on the shutdown mechanism. Multiple receivers are attached respectively to 55 the power modules. The receivers receive the signal and multiple enabling mechanisms, which are attached respectively to the receivers, enable the respective power modules to supply the input power to the inverter based on the a keep-alive signal, the enabling mechanisms enable the respective power modules to supply the input power to the inverter based on the presence of the keep-alive signal. When the signal is a shut-down signal, the enabling mechanism disables the respective power modules and stops 65 supply of the input power to the inverter based on the presence of the shut-down signal. The signal in the serial

string is optionally from the electrical grid and detected at the frequency of the electrical grid or detected at a higher frequency up converted from the frequency of the electrical grid. The signal in the serial string is optionally from the inverter or the output power therefrom, and detected at a switching frequency of the inverter. The signal is optionally superimposed on the power input to the inverter from the serial string. The signal may be wirelessly transmitted by the signal-providing mechanism, and the receiver in each of the power modules, receives the wirelessly transmitted signal.

According to another aspect of the present invention, there is provided a protection method in a distributed power system including DC power sources and multiple power modules each of which include inputs coupled to the DC power sources. The power modules each include outputs coupled in series to form a serial string. An inverter is coupled to the serial string. The inverter converts power input from the string and produces output power. When the inverter stops production of the output power, each of the power modules is shut down and thereby the power input to the inverter is ceased. When the inverter is connected to and supplies the output power to the electrical grid, one or more electrical parameters of the grid are monitored. When the one or more electrical parameters of the grid are out of a predetermined specification, the inverter is shut down and thereby production of the output power is stopped or the inverter is disconnected from the grid. When the inverter is shut down, a switch disposed between the serial string and the inverter is activated. When the switch is activated a change in current flowing through the serial string is sensed. Alternatively a signal is provided based on the shutdown mechanism. Multiple receivers are attached respectively to the power modules. The receivers receive the signals which enable the respective power modules to supply the input power to the inverter based on the presence of the signal or absence thereof. When the signal is a keep-alive signal, the respective power modules supply the input power to the inverter based on the presence of the keep-alive signal. When the signal is a shut-down signal, the respective power modules stop supply of the input power to the inverter based on the presence of the shut-down signal. The signal may be based on current in the serial string from the electrical grid and detected at the frequency of the electrical grid or detected at a higher frequency up converted from the frequency of the electrical grid. The signal in the serial string is optionally from the inverter or the output power therefrom, and detected at a switching frequency of the inverter. The signal is optionally actively superimposed on the power input to the inverter from the serial string. The signal may be wirelessly transmitted, and the receiver in each of the power modules, receives the wirelessly transmitted signal.

The foregoing and/or other aspects will become apparent from the following detailed description when considered in conjunction with the accompanying drawing figures.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in presence of the signal or absence thereof When the signal is 60 and constitute a part of this specification, exemplify embodiments of the present invention and, together with the description, serve to explain and illustrate principles of the invention. The drawings are intended to illustrate various features of the illustrated embodiments in a diagrammatic manner. The drawings are not intended to depict every feature of actual embodiments nor relative dimensions of the depicted elements, and are not necessarily drawn to scale.

The invention is herein described, by way of example only, with reference to the accompanying drawings, wherein:

FIG. 1 is a block diagram of a conventional power harvesting system using photovoltaic panels as DC power 5 sources:

FIG. 1B illustrates current versus voltage characteristic curves for one serial string the DC power sources of FIG. 1;

FIG. **2** is a simplified block diagram illustrating a distributed power harvesting circuit, based on the disclosure in <sup>10</sup> U.S. application Ser. No. 11/950,271, according to an aspect of the present invention;

FIG. 2A is a simplified block diagram of a DC-to-DC converter, including a feature of the present invention;

FIG. 3 illustrates an exemplary DC-to-DC converter, is a 15 simplified block diagram illustrating in more detail;

FIG. 4 is a simplified block diagram of another exemplary system, according to an embodiment of the present invention:

FIG. **4A** is a simplified block diagram illustrating in more 20 detail, a power module according to the embodiment of FIG. **4**.

FIG. 4B is a simplified block diagram illustrating in more detail, a signaling mechanism attached to a conventional inverter, according to embodiments of the present invention; <sup>25</sup>

FIG. 5 is a simplified flow diagram illustrating a method for wake-up and shutdown of a power harvesting system with a safety mode, according to a feature of the present invention;

FIG. **5**A is a flow diagram illustrating methods for wakeup and shutdown of a power harvesting system, according to embodiments of the present invention, the flow diagram including method steps performed by the power converters/modules;

FIG. **6** is another flow diagram illustrating methods for <sup>35</sup> wake-up and shutdown of a power harvesting system, according to embodiments of the present invention, the flow diagram including method steps performed by the inverter of FIG. **2** or signaling block of FIG. **4**B;

FIGS. 7 and 7A illustrate a system for protection during 40 an islanding condition, in accordance with aspects of the present invention;

FIGS. 7B and 7C illustrate in more detail the system of FIGS. 7 and 7A;

FIG. 7D illustrates a method, according to an aspect of the 45 present invention using the system of FIGS. 7 and 7A;

FIGS. **8** and **8**A, illustrate a system for protection during an islanding condition in accordance with other aspects of the present invention;

FIG. **8**B illustrates an example wherein a system according to an embodiment of the invention is applied as a retrofit to a prior art system, such as the system of FIG. **1**;

FIGS. 9, 9A and 9B illustrate a system for protection during an islanding condition, according to still other aspects of the present invention; and

FIGS. 10 and 10A, illustrate a system for protection during an islanding condition, according to yet other aspects of the present invention.

## DETAILED DESCRIPTION

Reference will now be made in detail to embodiments of the present invention, examples of which are illustrated in the accompanying drawings, wherein like reference numerals refer to the like elements throughout. The embodiments 65 are described below to explain the present invention by referring to the figures. 8

It should be noted, that although the discussion herein relates primarily to wake-up and shutdown methods in photovoltaic systems and more particularly to those systems previously disclosed in U.S. application Ser. No. 11/950, 271, the present invention may, by non-limiting example, alternatively be configured as well using conventional photovoltaic distributed power systems and other distributed power systems including (but not limited to) wind turbines, hydroturbines, fuel cells, storage systems such as battery, super-conducting flywheel, and capacitors, and mechanical devices including conventional and variable speed diesel engines, Stirling engines, gas turbines, and micro-turbines.

By way of introduction, it is important to note that aspects of the present invention have important safety benefits. While installing or performing maintenance on photovoltaic systems according to certain aspects of the present invention, installers are protected from danger of shock or electrocution since systems according to embodiments of the present invention do not output potentially dangerous high voltage and/or currents such as when solar panels are exposed to sunlight when an operational inverter is not connected during installation and maintenance procedures. Similarly, firefighters, even after they shut down the main electrical switch to a burning building can safely break into the burning building or hose the roof of the building with water without fear of high voltage DC conduction through the water, since high voltage direct current feeding the inverter is safely turned off.

Before explaining embodiments of the invention in detail, it is to be understood that the invention is not limited in its application to the details of design and the arrangement of the components set forth in the following description or illustrated in the drawings. The invention is capable of other embodiments or of being practiced or carried out in various ways. Also, it is to be understood that the phraseology and terminology employed herein is for the purpose of description and should not be regarded as limiting.

Reference is now made to FIG. 2 which illustrates a distributed power harvesting circuit 20, based on the disclosure in U.S. application Ser. No. 11/950,271. Circuit 20 enables connection of multiple distributed power sources, for example solar panels 101a-101d, to a single power supply. Series string 203 of solar panels 101 may be coupled to an inverter 204 or multiple connected strings 203 of solar panels 101 may be connected to a single inverter 204. In configuration 20, each solar panel 101a-101d is connected individually to a separate power converter circuit or a module 205a-205d. Each solar panel 101 together with its associated power converter circuit 205 forms a power generating element 222. (Only one such power generating element 222 is marked in FIG. 2.) Each converter 205a-205d adapts optimally to the power characteristics of the connected solar panel 101a-101d and transfers the power efficiently from input to output of converter 205. Converters 205a-205d are typically microprocessor controlled switching converters, e.g. buck converters, boost converters, buck/ boost converters, flyback or forward converters, etc. The converters 205a-205d may also contain a number of component converters, for example a serial connection of a buck and a boost converter. Each converter 205a-205d includes a control loop 221, e.g. MPPT loop that receives a feedback signal, not from the converter's output current or voltage, but rather from the converter's input coming from solar panel 101. The MPPT loop of converter 205 locks the input voltage and current from each solar panel 101a-101d at its optimal power point, by varying one or more duty cycles of the switching conversion typically by pulse width modula-

tion (PWM) in such a way that maximum power is extracted from each attached panel 101a-101d. The controller of converter 205 dynamically tracks the maximum power point at the converter input. Feedback loop 221 is closed on the input power in order to track maximum input power rather 5 than closing a feedback loop on the output voltage as performed by conventional DC-to-DC voltage converters.

As a result of having a separate MPPT circuit in each converter 205a-205d, and consequently for each solar panel 101a-101d, each string 203 may have a different number or 10 different specification, size and/or model of panels 101a-101d connected in series. System 20 of FIG. 2 continuously performs MPPT on the output of each solar panel 101a-101d to react to changes in temperature, solar radiance, shading or other performance factors that effect one or more of solar 15 panels 101a-101d. As a result, the MPPT circuit within the converters 205a-205d harvests the maximum possible power from each panel 101a-101d and transfers this power as output regardless of the parameters effecting other solar panels 101a-101d.

The outputs of converters 205a-205d are series connected into a single DC output that forms the input to inverter 204. Inverter 204 converts the series connected DC output of converters 205a-205d into an AC power supply. Inverter 204, regulates the voltage at the input of inverter 204. In this 25 example, an independent control loop 220 holds the voltage input to inverter 204 at a set value, say 400 volts. The current at the input of inverter 204 is typically fixed by the power available and generated by photovoltaic panels 101.

In order to legally be allowed to connect to the grid in an each country, inverter 104,204 is preferably designed to comply with local electrical regulations. Electrical regulations typically dictate, among other things, the minimal and maximal voltages of the grid e.g. 220-260 root mean squares voltage V, and a range of permitted frequency, e.g. 45-55 Hz. 35 Whenever the grid deviates from allowed values inverter 104,204 is required to disconnect from the grid. Disconnection from the grid is typically performed using software controlling inverter 104, 204 and control circuitry which constantly monitors grid parameters, e.g. voltage, frequency. 40

In system 10, solar panels 101 are directly connected (e.g. in series-parallel) to inverter 104. When an islanding condition is detected, inverter 104 is disconnected from the grid. Hence, inverter 104 stops drawing current and therefore panels 101 output a relatively high open circuit voltage 45 typically 25% higher than the normal operating voltage. An open circuit voltage 25% higher than nominal working voltage is typically safe, (less than the allowed 600 VDC in the USA and 1000 VDC in Europe) which are typical ratings for inverters 104 designed to be able to handle the higher 50 open circuit voltage.

In system 20, there are power converters 205 which "push" power to the output of converters 205. Under an islanding condition which has been detected by inverter 204, inverter 204 is shut down and current is not flowing between 55 converters 205 and inverter 204. Consequently, in system 20, the open circuit voltage at the input to inverter 204, reaches dangerous voltages, higher than the open circuit maximum voltage ratings of inverters 104, 204.

According to a feature of the present invention, information regarding wakeup or shut-down may be conveyed from inverter 204 to converters 205. The information may be transmitted using any of the methods well known to those experienced in the art. According to certain embodiments, a modulation method may be used, by way of example, 65 frequency modulation (FM) transmission, amplitude modulation (AM), FSK (frequency shift keying) modulation, PSK

10

(phase shift keying) modulation, various QAM (Quadrature amplitude modulation) constellations, or any other method of modulation. Alternatively, inverter 204, while converting power from its input to its output, actively creates a frequency ripple in serial string 203. During normal operation, the 100 Hz (or 120 Hz in USA) ripple is detectable in serial string 203 since the capacitors of inverter 204 do not entirely block the alternating current (AC), and an additional signaling mechanism is not required to produce the 100/120 Hz signal in serial string 203. Alternatively or in addition, one or more switching frequencies of inverter 204, typically 16 Khz or 32 KHz may be detectable as leakage or provided intentionally to serial string 203.

Reference is now made to FIG. 2A which illustrates a feature of the present invention. In FIG. 2A, converter 205 is shown in more detail. Integrated with power converter 205 is a detector/receiver 207, according to a feature of the present invention which is configured to receive, optionally amplify and detect the signal, e.g. at 100/120 Hz originating 20 in inverter 204.

Controller 306 preferably either polls a signal input 209 from receiver/detector 207 or uses signal input 209 as an interrupt so that only when detector/receiver 207 detects the 100/120 Hz signal, is module 205 in a normal operating mode converting power from its input to its output. Receiver 207 is alternatively configured to detect the 16/32 KHz inverter switching frequency and provides an enabling signal to controller on signal input 209 while inverter 204 is operating.

Reference is now made to FIG. 3 which illustrates an exemplary DC-to-DC converter 205, according to a feature of the present invention. DC-to-DC converters are used to either step down or step up a DC voltage input to a higher or a lower DC voltage output, depending on the requirements of the output circuit. However, in the embodiment of FIG. 3 the DC-DC converter 205 is used as a power converter, i.e., transferring the input power to output power, the input voltage varying according to the MPPT at the input, while the output current is dictated by the constant input voltage to inverter 104, 204. That is, the input voltage and current may vary at any time and the output voltage and current may vary at any time, depending on the operating condition of DC power sources 101.

Converter 205 is connected to a corresponding DC power source 101 at input terminals 314 and 316. The converted power of the DC power source 101 is output to the circuit through output terminals 310, 312. Between the input terminals 314, 316 and the output terminals 310, 312, the converter circuit includes input and output capacitors 320, 340, backflow prevention diodes 322, 342 and a power conversion circuit including a controller 306 and an inductor 308.

Diode 342 is in series with output 312 with a polarity such that current does not backflow into the converter 205. Diode 322 is coupled between the positive output lead 312 through inductor 308 which acts a short for DC current and the negative input lead 314 with such polarity to prevent a current from the output 312 to backflow into solar panel 101.

A potential difference exists between wires 314 and 316 due to the electron-hole pairs produced in the solar cells of panel 101. Converter 205 maintains maximum power output by extracting current from the solar panel 101 at its peak power point by continuously monitoring the current and voltage provided by panel 101 and using a maximum power point tracking algorithm. Controller 306 includes an MPPT circuit or algorithm for performing the peak power tracking. Peak power tracking and pulse width modulation (PWM) are

12 205 show

performed together to achieve the desired input voltage and current. The MPPT in controller 306 may be any conventional MPPT, such as, e.g., perturb and observe (P&O), incremental conductance, etc. However, notably the MPPT is performed on panel 101 directly, i.e., at the input to converter 205, rather than at the output of converter 205. The generated power is then transferred to the output terminals 310 and 312. The outputs of multiple converters 205 may be connected in series, such that the positive lead 312 of one converter 205 is connected to the negative lead 310 of the next converter 205.

In FIG. 3, converter 205 is shown as a buck plus boost converter. The term "buck plus boost" as used herein is a buck converter directly followed by a boost converter as 15 shown in FIG. 3, which may also appear in the literature as "cascaded buck-boost converter". If the voltage is to be lowered, the boost portion is substantially shorted. If the voltage is to be raised, the buck portion is substantially shorted. The term "buck plus boost" differs from buck/boost 20 topology which is a classic topology that may be used when voltage is to be raised or lowered, and sometimes appears in the literature as "cascaded buck-boost". The efficiency of "buck/boost" topology is inherently lower than a buck or a boost. Additionally, for given requirements, a buck-boost 25 converter will need bigger passive components then a buck plus boost converter in order to function. Therefore, the buck plus boost topology of FIG. 3 has a higher efficiency than the buck/boost topology. However, the circuit of FIG. 3 continuously decides whether it is bucking or boosting. In some 30 situations when the desired output voltage is similar to the input voltage, then both the buck and boost portions may be operational.

The controller 306 may include a pulse width modulator, PWM, or a digital pulse width modulator, DPWM, to be 35 used with the buck and boost converter circuits. Controller 306 controls both the buck converter and the boost converter and determines whether a buck or a boost operation is to be performed. In some circumstances both the buck and boost portions may operate together. That is, the input voltage and current are selected independently of the selection of output current and voltage. Moreover, the selection of either input or output values may change at any given moment depending on the operation of the DC power sources. Therefore, in the embodiment of FIG. 3, converter 205 is constructed so 45 that at any given time a selected value of input voltage and current may be up converted or down converted depending on the output requirement.

In one implementation, an integrated circuit (IC) 304 may be used that incorporates some of the functionality of 50 converter 205. IC 304 is optionally a single ASIC able to withstand harsh temperature extremes present in outdoor solar installations. ASIC 304 may be designed for a high mean time between failures (MTBF) of more than 25 years. However, a discrete solution using multiple integrated cir- 55 cuits may also be used in a similar manner. In the exemplary embodiment shown in FIG. 3, the buck plus boost portion of the converter 305 is implemented as the IC 304. Practical considerations may lead to other segmentations of the system. For example, in one aspect of the invention, the IC 304 60 may include two ICs, one analog IC which handles the high currents and voltages in the system, and one simple lowvoltage digital IC which includes the control logic. The analog IC may be implemented using power FETs which may alternatively be implemented in discrete components, 65 FET drivers, A/Ds, and the like. The digital IC may form controller 306.

In the exemplary circuit 205 shown, the buck converter includes input capacitor 320, transistors 328 and 330, diode 322 positioned in parallel to transistor 328, and inductor 308. Transistors 328, 330 each have a parasitic body diode 324, 326. The boost converter includes inductor 308, which is shared with the buck converter, transistors 348 and 350 a diode 342 positioned in parallel to transistor 350, and output capacitor 340. Transistors 348, 350 each have a parasitic body diode 344, 346.

System 20 includes converters 205 which are connected in series and carry the current from string 203. If a failure in one of the serially connected converters 205 causes an open circuit in failed converter 205, current ceases to flow through the entire string 203 of converters 205, thereby causing system 20 to stop functioning. Aspects of the present invention provide a converter circuit 205 in which electrical components have one or more bypass routes associated with them that carry the current in case of an electrical component failing within one of converters 205. For example, each switching transistor of either the buck or the boost portion of the converter has its own diode bypass. Also, upon failure of inductor 308, the current bypasses the failed inductor 308 through parasitic diodes 344,346.

In FIG. 3, detector/receiver block 207 is shown which is configured to provide an enable signal 209 to microcontroller 306 when the communications signal originating in inverter 104,204 is detected.

Reference in now made to FIGS. 4, which illustrate system 40, according to an embodiment of the present invention. For simplicity, a single string 423 is shown of distributed power sources, e.g. solar panels 101a-101d connected to respective power modules 405a-d. Serial string 423 is input to conventional inverter 104 through wires 412 and 410. The output of inverter 104 is connected to and supplies electrical power to the electrical grid. At the input of inverter 104, is connected a signaling mechanism 420 which superimposes a signal on serial string 423 through wires 412 and 410 when inverter 104 is converting power to the grid.

Reference is now also made to FIG. 4B which illustrates in more detail signaling mechanism 420. Signaling mechanism 420 includes a relay 428 which is normally open and controlled by a microcontroller 422. Relay 428 is switched at a given rate, e.g. 100 Hz, and the signal is superimposed by action of relay 428 onto serial string 423 over wires 410 and 412. Microcontroller 422 typically provides the control of the signal, e.g. 100 Hz, during normal operation of distributed power system 40. Microcontroller 422 is typically connected to one or more sensors in order to monitor the operation of inverter 104. In the example of FIG. 4B, microcontroller 422 monitors over-voltage of the input DC voltage to inverter 104. The example shown in FIG. 4B includes an input DC voltage tap 432 connected to an analog to digital converter (A/D) 430, the output of which is provided to microcontroller 422. The tap 432 may be, e.g., a Hall-effect sensors, series connected resistor across which the voltage drop is measured, etc. In one embodiment, an over-voltage condition as measured by microcontroller 422, results in microcontroller 422 stopping the signaling through relay 428 and/or opening one or more protective relays 424, 426 in series with the input DC voltage to inverter 104. Note that one switch 424 or 426 may be enough for performing the required action, and two switches in series are shown solely for the purpose of illustration that double protection might be required by some regulatory bodies. A power

management block 434 taps voltage for powering microcontroller 422 and any other active electronics components (not shown) in block 420.

Reference is now made to FIG. 4A which illustrates in more detail certain aspects of power module 405. Integrated 5 with power module 405 is detector/receiver 207 which is configured to receive, optionally amplify and detect the signal, e.g. at 100 Hz, produced by signal mechanism 420. Controller 306 preferably either polls signal input 209 or uses signal input 209 as an interrupt so that only when 10 detector/receiver 207 detects the 100 Hz signal, is module 405 operating in a normal operating mode. Power module 405 is shown to include a bypass diode 414. Optionally, power module 405 may include a conventional DC/DC switching converter with a control loop based on output 15 power. Power module 405 includes at least one switch 416 controlled by controller 306 which functions to stop normal operation of power from the input of module 405 to the output of 405 when signal input 209 is absent indicating that inverter 104 is not transferring power to the electrical grid. 20

Reference is now made to FIG. 5 which illustrates a simplified method for safe operation of system 40, according to an aspect of the present invention. In step 501, active control circuits, e.g. microcontroller 306, are turned on. Module 205, 405 begins operation (step 53) in a safety 25 mode. In safety mode, output current and/or voltage from module 405 is limited, for instance output voltage is limited to 2 volts and output current is limited to 10 mA so that a person can touch the wires of serial string 203, 423 without any danger of electrocution.

Controller 306 maintains safety mode operation (step 53) until a communications signal, e.g. 100 Hz, is received (decision box 505) by receiver/detector 207 from inverter 204 or signaling block 420. When the communications signal is received (decision block 505) indicating inverter 35 104 or 204 is connected and converting power, safety mode (step 53) of operation ends. When the communications signal is received (decision block 505), module 405 preferably enters a normal operation mode (step 57), typically with maximum power point tracking. The normal operation of 40 transferring power is maintained as long as the communications signal, e.g. 100 Hz is received from inverter 204 or signal mechanism 420, and no other warning condition is present. If the communications signal is not detected, or another warning condition is present, the normal mode (step 45 57) is typically ended and power conversion of modules 405 is typically turned off. If in decision box 509, the communications signal is not detected, or another warning condition is present, the normal mode (step 57) is typically ended and power conversion of modules 405 is typically turned off. 50

Reference is now made to FIG. 5A, which illustrates a method 50 for wake-up and shutdown of module 405, according to embodiments of the present invention. Method 50 is applicable to both systems 20 and 40. In step 501, active control circuits, e.g. microcontroller 306, are turned 55 on. Active control circuits are typically turned on (step 501) in the early morning when there is sufficient light to power the active control circuits typically with voltage of DC voltage source 101 reaching three volts. In decision block 503, when voltage output—or power output—from DC 60 voltage source 101 is sufficiently high and stable (e.g. voltage input to module 405 is ten volts for a period of 30 seconds), then module 205,405 begins operation (step 53) in a safety mode. In safety mode, output current and/or voltage from module 405 is limited, for instance output voltage is 65 limited to 2 volts and output current is limited to 10 mA so that a person can touch the wires of serial string 203,423

14

without any danger of electrocution. Note also, that in this case even if 25 modules are connected in series, the maximum output voltage of the string doesn't exceed 50V—which means the string voltage is still safe. Referring back to FIG. 3, safety mode may be achieved by controller 306 in module 405 by turning on FET 330 and turning off FETS 328, 348, and 350. Output wire 412 is held close to zero volts. Alternatively, the controller 306 may alternate the switches (e.g. switches 324 & 326 of buck converter) at a low duty-cycle in order to maintain a low output voltage.

Referring back to FIG. 5A, controller 306 maintains safety mode operation (step 53) until a communications signal, e.g. 100 Hz, is received by receiver/detector 207 from inverter 204 or signaling block 420. When the communications signal is received (decision block 505) indicating inverter 104 or 204 is connected and converting power, safety mode (step 53) of operation ends. When the communications signal is received (decision block 505), module 405 preferably enters a voltage control mode (step 55) and voltage output between wires 412,410 is slowly ramped up. Voltage continues to ramp up, typically as high as +60V until module 205,405 detects that current is being drawn by the inverter 104, 204 (step 507). When sufficient current is drawn (step 507), module 205, 405 begins normal operation, (step 57) e.g. for module 205, the normal mode is the maximum power point (MPP) tracking mode of converting DC power from its input to its output by maintaining maximum power at its input. The normal operation of transferring power is maintained as long as the communications signal, e.g. 100 Hz is received from inverter 204 or signal mechanism 420, and no other warning condition is present. If the communications signal is not detected, or another warning condition is present, the normal mode (step 57) is typically ended and power conversion of modules 405 is typically turned off. Exemplary warning conditions in decision box 509, which cause module 205,405 to end normal mode (step 57) and to stop transferring power to its output include: (i) input voltage less than predetermined value, e.g. about 10 volts for 5 seconds, (ii) rapid change in output voltage, for instance greater than 20% in 100 milliseconds, (iii) reception of signal requesting to stop producing power, (iv) not receiving a signal to produce power (in the case where recurring "allow production" signals are required for the converter to function), or (v) output exceeds over voltage threshold caused for instance when multiple modules 205 in string 203 are converting power (step 57) and one of modules 205 of string 203 shuts down, then the other modules 205 of string 203 have a raise of output voltage.

Reference is now made to FIG. 6, which illustrates a method 60 performed by inverter 204 or signaling block 420 attached at the input of inverter 104. In step 601, inverter 104 is off or inverter 204 is on standby, and not converting power to its output. In decision box 603, start conditions for turning on inverter 104,204 are determined. Typically, as a safety requirement, inverter 104 delays operation (converting power to its output) until after at least 5 minutes of connection to a functioning AC-grid at its output. This safety requirement may be achieved using microcontroller 422 and at least one of relays 424 and 426 in signaling block 420. In inverter 204, a minimum voltage is required at the input to inverter 204 (e.g. if the safety output voltage of each module is 2V, and the minimal-length string allowed contains 5 modules, the inverter will wait until at least 10V are present at its DC input) and only thereafter does inverter 204 begin to charge its input, typically to a specified standard input of 400V.

In step 605, communications signal, e.g. 100 Hz, is superimposed on serial string 203,423 either from signaling mechanism 420 or from inverter 204 for instance when at least a 50 Watt load is attached to the output of inverter 204. In decision box 607, when the specified input voltage is 5 reached, e.g. 400V for inverter 204, inverter 204 is turned on or inverter 104 is attached to serial string 423 by mechanism 420. In decision box 609, if a time out occurs before the minimum specified input voltage is reached of inverter 204,404 then inverter is returned to the off or standby state 10 (step 601). Otherwise inverter 204,404 is connected or turned on in step 611. Inverter 204, 404 remains on and connected unless a warning condition (decision box 613) occurs. Possible warning conditions include, (i) disconnection from the electrical grid, (ii) electrical grid stops pro- 15 ducing power (islanding), (iii) less than 50 Watts transferred in the last minute, (iv) input voltage to inverter 204,404 is over the maximum limit, and (v) input power is over the maximum limit. If a warning condition occurs (decision box 613) communications signal is turned off (step 615) for 20 inverter 404 or inverter 204 is turned off or put into standby.

Reference is now made to FIG. 7 which illustrates a system 70 for protection during an islanding condition, in accordance with embodiments of the present invention. For simplicity, a single string 723 is shown of distributed power 25 sources, e.g. solar panels 201 a-201 d connected to respective power converters 705 a-d. Serial string 723 is input to inverter 704 through wires 412 and 410. The output of inverter 704 is connected to and supplies electrical power to the electrical grid. Inverter 704, typically includes a monitoring, and detection mechanism 701 which monitors one or more parameters of the electrical grid such as voltage and/or frequency. If one or more of the grid parameters is out of specification indicating an islanding condition, monitoring and detection mechanism 701 typically causes inverter 704 35 to be shut down or inverter 704 is disconnected from the grid so that output power is no longer supplied by inverter 704 to the grid. At the same time, a signal 714 is transmitted to a switch mechanism 703 which may be located at the input of inverter 704 before input capacitor 708. Switch mechanism 40 703 is optionally packaged with inverter 704 or may be integrated with inverter 704 and packaged separately. In this example, signal 714 activates switch mechanism 703 so that when switch 703 is activated, the current flowing through serial string 723 and wires 410, 412 varies abruptly.

Reference is now also made to FIG. 7A which illustrates in more detail converter 705. Converter 705 is equipped with a current sensing mechanism 707 which upon sensing a variation in current through serial string 723 signals controller 306 to shut down and stop converting power. Typically, current sensing mechanism 707 includes an analog/digital converter which continuously feeds data to controller 306. Controller 306 detects a shutdown in current and decides to shut down the converters 705 accordingly.

Reference is now also made to FIGS. B and C which 55 illustrate schematically switch mechanism 703 in more detail. FIG. 7B illustrates switch mechanism 703 in a serial configuration in which switch 703 is connected in series with the serial string 723 and FIG. 7C illustrates a parallel configuration in which switch 703 is connected in parallel 60 with serial string 723. In the serial configuration (FIG. 7B) switch 703 is closed during normal operation of inverter 704. When an island condition is detected, serial switch 703 opens during shut down of inverter 704. Current sensing mechanism 707 upon sensing zero current signals controller 306 that output current is less than a previously specified minimum value and controller 306 shuts down power con-

16

version in converter 705. In the parallel configuration (FIG. 7C), switch 703 is open during normal operation of inverter 704. When an island condition is detected, parallel switch 703 closes during shut down of inverter 704. With all the current of serial string 723 flowing through the switch 703 at minimal load, the current increases to above a previously specified maximum current. Current sensing mechanism 707 upon sensing a current maximum signals controller 306 that output current is above maximal previously specified value and controller 306 shuts down power conversion. Switch mechanism 703 in different embodiments may be embodied by a mechanical switch or a solid state switch with current and voltage ratings appropriate to the present application. Switch mechanism 703 is preferably selected by one skilled in the art of power electronics so that arcing across its open terminals is avoided while practicing some embodiments of the present invention.

Reference is now made FIG. 7D which illustrates a method, according to an embodiment of the present invention. In decision block 750, output power from inverter 104, 204 is constantly monitored. If output power is stopped, power converters 705 are shut down.

Reference is now made to FIG. 8, illustrating a system 80 according to other embodiments of the present invention for protection during an islanding condition. For simplicity, a single string 823 is shown of distributed power sources, e.g. solar panels 201 a-201 d connected to respective power converters 805 a-d. Serial string 823 is input to inverter 804 through wires 412 and 410. The output of inverter 804 is connected to and supplies electrical power to the electrical grid. Inverter 804, typically includes a monitoring and detection mechanism 701 which monitors one or more parameters of the electrical grid such as voltage and/or frequency. If one or more of the grid parameters is out of specification indicating an islanding condition, monitoring/ detection mechanism 701 typically shuts down inverter 804 or disconnects from the grid, so that output power is no longer supplied by inverter 804 to the grid. During normal operation, a line communications transmitter 803 superimposes a keep-alive signal, for instance between 1 kilohertz to 100 Megahertz on direct current (DC) input lines 410 and 412 attached to serial string 823.

Reference is now also made to FIG. 8A which illustrates converter 805 in more detail. The keep-alive signal is constantly monitored and detected by a line communications receiver 807. Only while receiver 807 senses the keep-alive signal does receiver 807 provide an enable signal to controller 306. When controller 306 doesn't receive an enabling signal from receiver 807, controller 306 shuts down power conversion of converter 805.

Alternatively, instead of a "keep-alive" signal, a stop signal 814 which is first generated by monitoring and detection mechanism 701 when an islanding condition is detected, is transmitted to receiver 807. The stop signal is transmitted over line communications by superimposing a varying (e.g. 10 Khz to 100 Mhz) signal over the power lines of serial string 823. Receiver 807 receives the stop signal and relays the stop signal to controller 306 using, e.g., a single disable bit. Controller 306 on receiving a disable signal, stops converting power to the output of converter 805. Typically, when converters 805 are disabled they go into a bypass mode which allows current from other converters 805 to pass through. Hence, the stop signal may be continued until all power stops being supplied on string 823 by all of converters 805.

It should be noted that one skilled in the art would realize that although in system 80, converters 805 are shown to have

feedback loop 221, as in controller 205 of system 20, embodiments of the present invention as illustrated in system 70 using switch mechanism 703 and/or in system 80 using line communications, to the serial string may be applied to and find benefit in other distributed power sys- 5 tems using converters without feedback loops 221 as applied to prior art system 10. Similarly, conventional inverters 104 may be used instead of inverter 804 with communications transmitter 803 added to inverter 104 either by the inverter manufacturer or as a retrofit. For example, FIG. 8B illus- 10 trates a system according to an embodiment of the invention applied as a retrofit to a prior art system, such as the system of FIG. 1. In this example, detection mechanism 701 and switch mechanism 703 are installed between the grid and the conventional inverter 104. Of course, detection mechanism 701 and switch mechanism 703 may be incorporated into the inverter, e.g., for original installation, rather than a retrofit. Also, other implementations described herein may be used instead of detection mechanism 701 and switch mechanism 703. Advantages of incorporation of monitoring and detec- 20 tion mechanism 701 and one of switch mechanism 703 or communications transmitter 803 into system 10 is beneficial during installation, maintenance, and firefighting.

Reference in now made to FIG. 9 which illustrates system 90, according to another embodiment of the present inven- 25 tion for protection during an islanding condition. For simplicity, a single string 923 is shown of distributed power sources, e.g. solar panels 201 a-201 d connected to respective power converters 905a-d. Serial string 923 is input to conventional inverter 104 through wires 412 and 410. The 30 output of inverter 104 is connected to and supplies electrical power to the electrical grid. Inverter 104, typically includes a monitoring and detection mechanism 701 which monitors one or more parameters of the electrical grid such as voltage and/or frequency. If one or more of the grid parameters is out 35 of specification indicating an islanding condition, monitoring and detection mechanism 701 typically shuts down inverter 104 so that output power is no longer supplied by inverter 104 to the grid. During normal operation, a 100 Hz (or 120 Hz. in USA) ripple current is detectable between 40 lines 410, 412 and in serial string 923 since capacitors of inverter 104 do not block entirely the alternating current (AC), or the 100/120 Hz is intentionally leaked into serial string 923 through lines 410, 412.

Reference is now also made to FIG. 9A which illustrates 45 converter 905 in more detail. The 100/120 Hz leakage is constantly monitored and detected by a receiver 907. Only while receiver 907 senses the leakage from the grid does receiver 907 provide an enable signal to controller 306. When controller 306 doesn't receive an enabling signal from 50 receiver 907, controller 306 shuts down power conversion of converters 905.

Alternatively or in addition, one or more switching frequencies of inverter 104, typically 16 Khz or 32 KHz. may be detected as leakage or provided intentionally to serial 55 string 923 along lines 412,410. Receiver 907 is configured to detect the 16/32 KHz inverter switching frequency and provides an enabling signal to controller while inverter 104 is operating.

Reference is now made to FIG. 9B, showing a simplified 60 block diagram according to an embodiment of the present invention for up conversion of 100/120 Hz. into a higher frequency in order to enable faster detection in receiver 907 of leakage from the grid. The 100 Hertz or 120 Hertz signal is AC coupled by capacitor 931 to remove the direct current 65 component in serial string 923 and lines 410 and 412. The 100/120 Hz. signal is optionally amplified and rectified by a

full wave rectifier 935 so that a 100 Hz or 120 Hz unipolar DC ripple is achieved. The 100/120 Hz unipolar signal is split. One portion of the 100/120 Hz unipolar ripple is converted to a square wave, such as in a comparator/digitize circuit 939. A second portion of the 100/120 Hz unipolar ripple undergoes a known phase shift, e.g. of 400 Hz. in a phase shifter 933 and output to a second comparator/digitizing circuit 931. The two outputs of two digitizing circuits 939,931 undergo an exclusive OR in a XOR circuit 933 which outputs a signal at a much higher frequency, e.g. 800 Hz

18

Reference is now made to FIG. 10, illustrating a system 1000 according to other embodiments of the present invention for protection during an islanding condition. For simplicity, a single string 1023 is shown of distributed power sources, e.g. solar panels 201 a-201 d connected to respective power converters 1005 a-d. Serial string 1023 is input to inverter 1004 through wires 412 and 410. The output of inverter 1004 is connected to and supplies electrical power to the electrical grid. Inverter 1004, typically includes a monitoring and detection mechanism 701 which monitors one or more parameters of the electrical grid such as voltage and/or frequency. If one or more of the grid parameters is out of specification indicating an islanding condition, monitoring, and detection mechanism 701 typically shuts down inverter 1004 or disconnects inverter 704 from the grid so that output power is no longer supplied by inverter 1004 to the grid. During normal operation, a wireless transmitter 1003 transmits wirelessly a signal, for instance between 100 Megahertz-10 Gigahertz.

Reference is now also made to FIG. 10A which illustrates converter 1005 in more detail. The wireless signal is received and constantly monitored by a wireless receiver 1007 Only while receiver 1007 senses the wireless signal does receiver 1007 provide an enable signal to controller 306. When controller 306 doesn't receive an enabling signal from receiver 1007, controller 306 shuts down power conversion of converter 1005.

The present invention has been described in relation to particular examples, which are intended in all respects to be illustrative rather than restrictive. Those skilled in the art will appreciate that many different combinations of hardware, software, and firmware will be suitable for practicing the present invention. Moreover, other implementations of the invention will be apparent to those skilled in the art from consideration of the specification and practice of the invention disclosed herein. Various aspects and/or components of the described embodiments may be used singly or in any combination in the server arts. It is intended that the specification and examples be considered as exemplary only, with a true scope and spirit of the invention being indicated by the following claims.

While the invention has been described with respect to a limited number of embodiments, it will be appreciated that many variations, modifications and other applications of the invention may be made.

The invention claimed is:

1. A method comprising:

receiving power from a direct current (DC) power source at an input of a power converter;

performing, with a controller, the following steps:

operating one or more switches of the power converter in a safety mode by limiting output voltage at an output of the power converter below a predetermined voltage;

detecting, while limiting the output voltage in the safety mode, receipt of a communication signal;

- responsive to the detecting receipt of the communication signal, transitioning from the safety mode to a voltage control process including:
  - operating the one or more switches of the power converter to cause increases of the output voltage, 5 and
  - detecting, for each of the increases of the output voltage, an amount of current being drawn from the output of the power converter;
  - after detecting that the amount of current being 10 drawn exceeds a preexisting level, the controller transitioning the power converter from the voltage control process to a maximum power point tracking mode;
- maintaining, by the controller and after the transitioning from the voltage control process, the output
  voltage to be below a maximum output voltage of the
  power converter while simultaneously remaining in
  the maximum power point tracking mode; and
- responsive to an interruption in receipt of the communication signal, transitioning from the maximum power point tracking mode to the safety mode.
- 2. The method of claim 1, further comprising:
- responsive to a different interruption in receipt of the communication signal, transitioning from the voltage 25 control process to the safety mode.
- 3. The method of claim 1, wherein the DC power source comprises one or more solar cells.
- **4.** The method of claim **1**, wherein the detecting receipt of the communication signal comprises detecting receipt of the 30 communication signal from a signaling mechanism integrated in an inverter.
- **5**. The method of claim **1**, wherein the power converter comprises a direct current to direct current (DC/DC) converter.
- **6**. The method of claim **1**, wherein the detecting receipt of the communication signal comprises one of:
  - detecting the communication signal at a frequency of an electrical grid;
  - detecting the communication signal at a second fre- 40 quency, wherein the second frequency is up-converted from the frequency of the electrical grid; and
  - detecting the communication signal at a frequency of an inverter.
- 7. The method of claim 1, wherein the detecting receipt of 45 the communication signal comprises one of:
  - detecting the communication signal delivered over an electrical conductor; and
  - detecting the communication signal delivered over a wireless medium.
- 8. The method of claim 1, wherein the detecting receipt of the communication signal is based on a change in voltage, current, or power corresponding to an inverter or a power grid.
  - 9. An apparatus comprising:
  - a power converter comprising:
    - an input configured to receive power from a direct current (DC) power source,
    - an output terminal, and
    - a controller, wherein the controller is further configured 60 to:
      - operate one or more switches of the power converter in a safety mode by limiting output voltage at the output terminal of the power converter below a predetermined voltage;
      - detect, while limiting the output voltage in the safety mode, receipt of a communication signal;

20

- responsive to the detecting receipt of the communication signal, transition from the safety mode to a voltage control process including:
  - operating the one or more switches of the power converter to cause increases of the output voltage, and
  - detecting, for each of the increases of the output voltage, an amount of current being drawn from the output terminal of the power converter;
- after detecting the amount of current being drawn exceeds a preexisting level, the controller transitioning the power converter from the voltage control process to a maximum power point tracking mode;
- maintain, by the controller and after the transitioning from the voltage control process, the output voltage to be below a maximum output voltage of the power converter while simultaneously remaining in the maximum power point tracking mode; and
- responsive to an interruption in receipt of the communication signal, transition from the maximum power point tracking mode to the safety mode.
- 10. The apparatus of claim 9, wherein the voltage control process further includes:
  - responsive to a different interruption in receipt of the communication signal, transitioning from the voltage control process to the safety mode.
- 11. The apparatus of claim 9, wherein the DC power source comprises one or more solar cells.
- 12. The apparatus of claim 9, wherein the controller is further configured to detect receipt of the communication signal by detecting receipt of the communication signal from a signaling mechanism integrated in an inverter.
- 13. The apparatus of claim 9, wherein the power converter comprises a direct current to direct current (DC/DC) converter.
  - **14**. The apparatus of claim **9**, wherein the controller is further configured to detect receipt of the communication signal by one of:
    - detecting the communication signal at a frequency of an electrical grid;
    - detecting the communication signal at a second frequency, wherein the second frequency is up-converted from the frequency of the electrical grid; and
    - detecting the communication signal at a frequency of an inverter.
  - 15. The apparatus of claim 9, the controller is further configured to detect receipt of the communication signal by one of:
    - detecting the communication signal delivered over an electrical conductor; and
    - detecting the communication signal delivered over a wireless medium.
- 16. The apparatus of claim 9, wherein the controller is55 further configured to detect receipt of the communication signal based on a change in voltage, current, or power corresponding to an inverter or a power grid.
  - 17. A method comprising:
  - receiving power from a direct current (DC) power source at an input of a power converter;
  - performing, with a controller, the following steps:
    - operating one or more switches of the power converter in a safety mode by limiting output voltage at an output of the power converter below a predetermined voltage;
    - detecting, while limiting the output voltage in the safety mode, receipt of a communication signal;

21

responsive to the detecting receipt of the communication signal, transitioning from the safety mode to a voltage control process including:

operating the one or more switches of the power converter to cause increases of the output voltage, and

detecting, for each of the increases of the output voltage, an amount of current being drawn, from the output of the power converter;

after detecting the amount of current being drawn exceeds a preexisting level, and responsive to continuously detecting receipt of the communication signal, the controller transitioning the power converter from the voltage control process to a maximum power point tracking mode; and

responsive to an interruption in receipt of the communication signal, transitioning from the voltage control process to the safety mode.

18. The method of claim 17, further comprising: after transitioning to the maximum power point tracking mode and responsive to a different interruption in receipt of the communication signal, transitioning from the maximum power point tracking mode to the safety mode.

19. The method of claim 17, wherein the DC power source comprises one or more solar cells.

22

20. The method of claim 17, wherein the detecting receipt of the communication signal comprises detecting receipt of the communication signal from a signaling mechanism integrated in an inverter.

21. The method of claim 17, wherein the power converter comprises a direct current to direct current (DC/DC) converter.

22. The method of claim 17, wherein the detecting receipt of the communication signal comprises one of:

detecting the communication signal at a frequency of an electrical grid;

detecting the communication signal at a second frequency, wherein the second frequency is up-converted from the frequency of the electrical grid; and

detecting the communication signal at a frequency of an inverter.

23. The method of claim 17, wherein the detecting receipt of the communication signal comprises one of:

detecting the communication signal delivered over an electrical conductor; and

detecting the communication signal delivered over a wireless medium.

24. The method of claim 17, wherein the detecting receipt of the communication signal is based on a change in voltage, current, or power corresponding to an inverter or a power grid.

\* \* \* \* \*