

# US Patent & Trademark Office

## Patent Public Search | Text View

United States Patent Application Publication

20250261942

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Belson; Amir et al.

### Closure Apparatuses and Methods for Ulcers and Irregular Skin Defects

#### Abstract

An apparatus for closing a surgical incision comprises left and right base panels, a plurality of closure components, and a plurality of left and right axial supports coupled to the respective base panels. The closure components couple the left and right base panels to each other laterally and have left and right ends coupled to the respective base panels. The closure components are positioned laterally across the left and right panels, the left axial supports are disposed between pairs of left closure component ends, the right axial supports are disposed between pairs of right closure component ends, and the left and right axial supports are offset from one another such that a serpentine arrangement of consecutive closure components and axial supports is formed. The apparatus can be made of antimicrobial materials or materials impregnated with antimicrobial agents. A flexible adhesive cover can be provided over the apparatus when in use.

**Inventors:** Belson; Amir (Savyon, IL), Ichiryu; Keiichiro (Campbell, CA), Storne; Eric (Menlo Park, CA), Schaer; Alan (San Jose, CA), Rathi; Pankaj (Mountain View, CA), D'Aquanni; Peter (Murrieta, CA), Clauson; Luke (Redwood City, CA), Feezor; Chris (San Jose, CA)

**Applicant:** ZipLine Medical, Inc. (Campbell, CA)

**Family ID:** 1000008576864

**Appl. No.:** 18/999264

**Filed:** December 23, 2024

#### Related U.S. Application Data

parent US continuation 17879958 20220803 parent-grant-document US 12171432 child US 18999264

parent US continuation 16573765 20190917 parent-grant-document US 11439395 child US 17879958

parent US continuation 15369293 20161205 parent-grant-document US 10456136 child US

16573765  
parent US continuation 15130149 20160415 parent-grant-document US 9561034 child US 15369293  
parent US continuation 14180564 20140214 parent-grant-document US 9089328 child US 14625366  
parent US continuation-in-part 14625366 20150218 parent-grant-document US 9642621 child US 15130149  
parent US continuation-in-part 13665160 20121031 parent-grant-document US 10123800 child US 14180564  
parent US continuation-in-part 13286757 20111101 parent-grant-document US 8323313 child US 13665160  
us-provisional-application US 62148863 20150417  
us-provisional-application US 61889569 20131011  
us-provisional-application US 61958259 20130724  
us-provisional-application US 61958254 20130724

---

## Publication Classification

**Int. Cl.:** A61B17/08 (20060101); A61B17/00 (20060101)

**U.S. Cl.:**

**CPC** A61B17/085 (20130101); A61B2017/00889 (20130101); A61B2017/086 (20130101)

---

## Background/Summary

[0001] CROSS-REFERNECE TO RELATED APPLICATIONS [0002] This application is a continuation of U.S. patent application Ser. No. 17/879,958, filed Aug. 3, 2022, now U.S. Pat. No. 12,171,432, which is a continuation of U.S. patent application Ser. No. 16/573,765, filed Sep. 17, 2019, now U.S. Pat. No. 11,439,395, which is a continuation of U.S. patent application Ser. No. 15/369,293, filed Dec. 5, 2016, now U.S. Pat. No. 10,456,136; which is a continuation of U.S. patent application Ser. No. 15/130,149, filed Apr. 15, 2016, now U.S. Pat. No. 9,561,034; which is a continuation-in-part of U.S. patent application Ser. No. 14/625,366, filed Feb. 18, 2015; which is a continuation of U.S. patent application Ser. No. 14/180,564, filed Feb. 14, 2014, now U.S. Pat. No. 9,089,328; which is a continuation-in-part of U.S. patent application Ser. No. 13/665,160, filed Oct. 31, 2012; which is a continuation-in-part of U.S. patent application Ser. No. 13/286,757, filed Nov. 1, 2011, now U.S. Pat. No. 8,323,313; the full disclosures of which are incorporated by reference; and U.S. patent application Ser. No. 14/180,564 also claims the benefit of U.S. Provisional Applications Nos. 61/889,569, filed Oct. 11, 2013; 61/958,259, filed Jul. 24, 2013; and 61/958,254, filed Jul. 24, 2013; the full disclosures of which are incorporated herein by reference; and U.S. patent application Ser. No. 15/130,149 claims the benefit of U.S. Provisional Application No. 62/148,863, filed Apr. 17, 2015; the full disclosure of which is incorporated herein by reference. [0003] The subject matter of this application is related to co-pending U.S. patent application Ser. No. 14/180,524 (Attorney Docket No. 35383-712.201), now U.S. Pat. No. 9,050,086, filed Feb. 14, 2014, the full disclosures of which are incorporated herein by reference.

## BACKGROUND OF THE INVENTION

[0004] 1. Field of the invention. The present invention relates generally to medical apparatus and methods. More particularly, present invention relates to apparatus and methods for forming and

closing surgical incisions.

[0005] Surgical closure devices including an adhesive based patch with right and left panels are known. Of particular interest of the present invention, such devices are described in co-pending, commonly owned PCT application US 2010/000430, full disclosure which is incorporated herein by reference. As described in the PCT application, an adhesive patch is placed over a patient's skin at a site where it is desired to form a surgical incision. After the patch is placed, an incision is formed along an axial line extending through the middle of the patch. After it is formed, the incision can be opened to perform a desired procedure, and after the procedure is completed the incision may be closed by drawing the inner edges of the panels together with a clip, zipper, or other closure member.

[0006] The principal objective of such surgical closure devices is to improve healing and reduce scarring from the incision. This objective, however, has been inhibited by certain characteristics of the presently available devices. For example, the tissue edges are not always brought together along a line evenly, which can increase the eventual scarring. Many such closure devices do not have the ability to adjust the closure force or distance on the tissue edges, limiting the ability to slightly “pucker” tissue which has been found to reduce scarring. Other shortcomings of the available incision and wound closure devices include difficulty of use and inability to conform to tissue manipulation during subsequent surgical protocols, i.e. those devices which are sufficiently rigid to securely close the tissue are often unable to conform to the tissue movement during the surgical procedure.

[0007] A particular problem arises with self-adhesive wound closure patches when they're used beneath an adherent surgical incision drape. Such drapes are used to help maintain the sterility of a tissue surface during a surgical procedure, and the drapes may be placed over a previously positioned tissue closure patch. As the surgical incision drape has an adhesive lower surface which adheres to the tissue, the drape will adhere to an upper surface of an underlying tissue closure patch. Removal of the surgical incision drape will thus often remove or at least displace a previously placed tissue closure patch. If any significant portion of the tissue closure patch is removed or displaced, the patch will no longer be useful for closing a surgical wound.

[0008] For these reasons, it would be desirable to provide improved surgical incision closure devices and methods for their use. It would be particularly desirable to provide incision closure devices which are able to adhere to the tissue, allow formation of the incision, conform to the deformation of the tissue during a subsequent surgical procedure, and provide controlled closure of the adjacent tissue edges subsequent to the procedure. In particular, it would be desirable if the incision closure devices were able to provide for the control and the uniform distribution of closure forces on the tissue edges while causing minimum restraint or stretching of the tissue during the surgical procedure. It would be still further desirable to provide improved surgical incision closure devices and methods for their use where the devices will resist removal and dislocation when used beneath a surgical incision drape. At least some of these objectives will be met by the inventions described below.

[0009] 2. Description of the Background Art. Surgical closure devices are described in U.S. Pat. Nos. 2,012,755; 3,516,409; 3,863,640; 3,933,158; 4,114,624; 3,926,193; 4,535,772; 4,676,245; 4,881,546; 4,905,694; 5,377,695; and 7,455,681; and U.S. Patent Publication Nos. 2005/0020956 and 2008/0114396. Further surgical closure devices are described in commonly owned U.S. Pat. Nos. 8,313,508, 8,323,313, and 8,439,945; U.S. Patent Publication No. 2013/0066365; and PCT Publication nos. WO 2011/139912, WO 2011/159623, WO 2011/043786, and WO 2013/067024, the full disclosures of which are incorporated herein by reference. Commercial incision closure devices available from Ethicon, a division of Johnson & Johnson, under the trade name Ethizip™ temporary abdominal wound closure device.

## SUMMARY OF THE INVENTION

[0010] The present invention provides improved apparatus and methods for closing wounds,

particularly wounds resulting from incisions performed during surgical procedures. The incisions would usually be formed in a patient's skin, such as through the abdomen, but in some cases could also be on internal organs, within the oral cavity, within body cavities, or alike.

[0011] The devices and methods of the present invention will present minimum disruption of or interference with the surgical procedure which is performed after the incision is made. In particular, the devices and methods will permit the opposed edges of the incised tissue to be opened, stretched, and freely deformed with minimal restraint resulting from the presence of the closure device. Once the procedure has been completed, however, the devices and methods of the present invention will provide for a uniform distribution of closure forces to draw the tissue edges together in a manner which minimizes scarring. In particular, the closure devices can draw the tissue edges together at a slightly closer spacing than initially present at the forming of the incision in order to upwardly evert the tissue edges and cause a "pucker" which can reduce scarring.

[0012] The devices and methods of the present invention will also be able to avoid or reduce disruption when an incision closure appliance is used beneath surgical incision drape which must be removed from over the closure appliance. A sacrificial layer is provided over at least part of the upper surface of the closure appliance, where the sacrificial cover is held in place while the surgical incision drape is placed over the incision closure appliance. After the incision and surgical procedure have been completed, the surgical incision drape will be pulled from the patient's skin. Instead of adhering to and dislodging the tissue closure appliance, the surgical drape adheres to the sacrificial cover, and only the sacrificial cover is pulled from the patient with the drape, leaving the remainder of the incision closure appliance in place.

[0013] In a first aspect of the present invention, an incision closure appliance comprises a base including a left panel and a right panel. Each panel has a tissue adherent lower surface, an upper surface, an inner edge, and an outer edge. The lower tissue adherent surface will typically be coated at least partially with a common tissue-adherent adhesive such as those used in surgical bandages and patches.

[0014] The incision closure appliance further includes a force distribution structure coupled to each panel (i.e. each panel will have at least one force distribution structure coupled thereto), where each force distribution structure is adapted to allow axial expansion of the panel along the inner edge while limiting lateral expansion over the entire length and axial expansion along the outer edge. By permitting axial expansion of the panel along the inner edge, the tissue edges are minimally constrained to allow the tissue to deform when stretched during the surgical procedure. Conversely, by limiting both lateral expansion and axial expansion along the outer edge, the panel will be able to apply a controlled and distributed closure force when the panels are drawn together after the surgical procedure is complete, as described in more detail below.

[0015] The incision closure appliance still further includes a closure component or assembly which attaches to the force distribution structure to draw the inner edges of the panels together after they had been adhered to the tissue on opposite sides of an incision site and the surgical procedure completed. Each panel of the base will typically comprise an at least partially elastic matrix, typically having an isotropic elasticity (i.e. the panel stretches evenly in all directions) but optionally having an anisotropic elasticity (where the matrix stretches preferentially in one direction or over a portion thereof). The elastic matrix may comprise an elastomeric membrane or sheet (for example Polyurethane sheet or Thermo Plastic Elastomers (TPE)), a woven fabric (typically woven at least partially from elastomeric filaments, threads, or fibers), a spun fabric, or the like. In certain embodiments, the elastomeric matrix may comprise a fabric woven from both elastic elements (typically threads, filaments, fibers, or the like) and having inelastic elements disposed along the outer edge and extending laterally there across in order to provide the expansion characteristics described above with respect to the force distribution structure. That is, in some cases, the force distribution structure may include or consist of inelastic elements woven or otherwise incorporated within a fabric membrane.

[0016] Typically, the force distribution structure will comprise a separate component of the incision closure appliance, for example including a spine disposed axially adjacent to the outer edge of the panel and a plurality of axially spaced-apart lateral supports disposed laterally and extending from the spine toward the inner edge of the panel. Such a “comb-like” structure will typically be formed from flexible but non-distensible materials so that the elements can flex together with the tissue deformation but will not stretch along their lengths so that they may provide dimensional stability in the lateral direction as well as along the outer edge of the panel. Examples of such materials include Nylon, Polypropylene, Polyethylene and Polycarbonate or other thermoplastic polymers. Notably, the force distribution structure will not limit the axial stretching of the inner edge of the panel in order to provide the desired expansibility and conformability to the tissue during the surgical procedure. Such separate force distribution structures may be attached to the upper surface of the panel, or alternatively may be embedded in or laminated within the panel. Typically, the force distribution structure will not extend into or past the lower surface of the panel so that it will not interfere with adherence of the panel to the skin or other tissue.

[0017] The assembly of the base panels and the force distribution structures will typically be carried on a removable backing which covers and protects the adherent surface of the panels prior to use. The backing may be removed in order to apply the base to the skin or other tissue at the site of the surgical intervention. Additionally, the right and left panels will typically be held together by removable tabs, an axial strip, or other removable covers or structures in order to hold the inner edges of the panel at a pre-determined distance or spacing as they are being adhered to the tissue. For example, removable tabs may be placed at each axial end of the base to temporarily secure the two base panels together. Alternatively, a removable strip or tape may be placed over an axial gap between the right and left panels to hold the panels in place relative to each other as the base is being adhered to the tissue surface. Such tabs or strips will typically be self-adhesive so that they may be secured to the panels and then removed by simply pulling off after the panels are properly placed on the tissue. The cover, tabs, or strip may then be removed to leave the panels in place but unconnected prior to forming the surgical incision therebetween.

[0018] A first exemplary construction of the closure component or assembly comprises a right engagement member, a left engagement member, and a plurality of lateral struts holding the engagement members laterally apart by a pre-determined distance. The right engagement member is adapted to releasably engage the supports of the right panel along an inner edge thereof, and the left engagement member is adapted to releasably engage the supports of the left panel along an inner edge thereof. In the specific embodiments, at least some of the supports of the force distribution component will have cleats near their inner edges, and the engagement members will have slots which receive the cleats. After the surgical intervention is complete, the closure component may then be placed over the force distribution structure with the cleats on one side first being engaged by an engagement member and then the opposite engagement member being pulled over the cleats on the opposite side.

[0019] Alternatively, the closure component or assembly may comprise a plurality of independent lateral ties attached to at least some of the lateral supports. Such lateral ties are configured to be secured between the lateral supports, typically being fixed to one panel and being adjustably attachable to the other panel. For the exemplary embodiments, the adjustably attachable end may comprise a ratchet tightening mechanism or similar structure which allows each lateral tie to be independently adjusted at a different spacing between the right and left panels. In this way, the right and left panels may be differentially tensioned along their inner edges in order to control and optimize the forces applied to the adjacent tissue edges which are being drawn together.

[0020] Optionally, the closure appliance of the present invention may further comprise a securing layer which is adapted to be placed over the assembly of the base and the closure component after the assembly has been secured over an incision on a patient's skin and the surgical procedure has been completed. A securing layer will typically have a self-adhesive lower surface which can be

placed over the assembly of the base and closure component to help secure it in place and to maintain cleanliness. The securing layer may optionally have openings to permit access to the wound for observation, delivery of antiseptics, and the like.

[0021] In a further aspect of the present invention, methods for forming an incision in tissue comprise providing an incision closure appliance as described above. The right and left panels of the appliance are adhered to the patient's skin, where the inner edges of the panels are spaced-apart by a pre-selected distance typically from 0.5 mm to 15 mm. An incision (typically linear) is formed in the tissue or skin surface between the inner edges of the panels, and the edges of the incised tissue are then separated to perform a desired surgical procedure. The inner edges of the panels can stretch and conform along with movement and deformation of the tissue edges while the outer edge and lateral extent of each panel remain dimensionally stable. After the procedure is complete, the closure component is secured to the force distribution structure to draw the inner edges of the panels back together. Optionally, the closure component has dimensions (or an adjustable inter-panel spacing) which draw the tissue edges closer together than they were immediately after the incision was formed. Such drawing together of the tissue causes the edges to evert and the tissue to "pucker" which can reduce scarring.

[0022] In yet a further aspect of the present invention, an incision closure appliance is provided. The incision closure appliance may comprise left and right base panels, a plurality of closure components for coupling the left and right base panels to each other laterally, and a plurality of left and right axial supports coupled, respectively, to the left and right base panels. Each closure component comprises left and right closure component ends coupled, respectively, to the left and right base panels. The plurality of closure components may be positioned laterally across the left and right panels with (i) one or more of the left axial supports disposed between at least some axially adjacent left closure component ends and (ii) one or more of the right axial supports disposed between at least some axially adjacent right closure component ends to form a serpentine arrangement.

[0023] To form the serpentine arrangement, a left axial support couples every other axially adjacent pair of left closure component ends together on the left panel and/or a right axial support couples every other axially adjacent pair of right closure component ends together on the right panel. The left and/or right panels may have one or more perforations disposed between axially adjacent the respective left and/or right closure component ends having no axial support disposed therebetween. The one or more perforations may comprise a plurality of perforations that facilitate the separation of the base panel into base panel segments upon axial stretching of the base panel.

[0024] One or more of the left or right base panels may comprise a plurality of separate base panel segments. At least two left closure component ends or at least two right closure component ends may be coupled to each base panel segment. The left base panel may comprise a plurality of left base panel segments, and the right base panel may comprise a plurality of right base panel segments. The left base panel segments and the right base panel segments may be axially offset from one another when applied to an incision and surrounding tissue. The plurality of closure components may couple the left and right base panel segments to each other laterally to form the serpentine arrangement.

[0025] One or more of the left or right base panels may comprise a tissue adherent lower surface for adhering to the tissue adjacent the incision. One or more of the left or right base panels may comprise a lower adhesive layer comprising the tissue adherent lower surface and an upper layer comprising an upper surface. The upper layer may be more rigid than the lower adhesive layer. The lower adhesive layer may be sufficiently elastic such that blistering and adhesion loss due to movement of tissue laterally adjacent the incision closure device when covering the incision and surrounding tissue are minimized. The adhesive lower layer may comprise a hydrophilic adhesive material. The hydrophilic adhesive material may comprise one or more of a hydrocolloid, a hydrogel, an acrylic polymer, or poly (ethylene glycol). The upper layer may comprise one or more

of rubber, latex, urethane, polyurethane, silicone, a thermo plastic elastomer (TPE), a woven fabric, or a spun fabric. One or more of the left closure component ends, right closure component ends, left axial supports, or right axial supports may be embedded in or laminated to the upper surfaces of the left and right base panels.

[0026] One or more of the left closure component ends, right closure component ends, left axial supports, or right axial supports may be formed from flexible, non-distensible materials.

[0027] The plurality of closure component, left axial supports, and right axial supports may together be sufficiently rigid such that movement of tissue laterally adjacent the incision closure device when covering an incision and surrounding tissue does not substantially distend the covered incision and surrounding tissue. Accordingly, movement of a first tissue region laterally adjacent a periphery of the incision closure device may substantially translate into a same movement of a second tissue region laterally adjacent the periphery and opposite the first tissue region.

[0028] One or more closure component of the plurality of closure components may comprise a tie securely coupled to the left or right closure component end and adjustably attached to the opposite closure component end. The opposite closure component end may comprise a ratchet tightening mechanism.

[0029] The plurality of closure components may be configured to draw inner edges of the left and right base panels together to compress an incision covered by the incision closure appliance.

[0030] One or more of the plurality of left axial supports or the plurality of right axial support may be C-shaped. The C-shaped left and/or right axial supports may each comprise an axial portion for limiting axial expansion of the respective base panel and a lateral portion for limiting lateral expansion of the respective base panel.

[0031] This aspect of the present invention may also provide a system for closing an incision in tissue. The system may comprise the incision closure device and a flexible cover for overlying the incision closure device and the covered incision and surrounding tissue.

[0032] The flexible cover may be configured to extend over lateral and axial edges of the left and right base panels. The cover may have one or more perforations to allow the cover to at least partially stretch axially in response to axial stretching of the incision and surrounding tissue covered by the incision closure device. The one or more perforations may be disposed along a central axial line of the cover. The cover may comprise one or more reinforcing members coupled to at least a portion of an adhesive layer of the cover. The reinforcing members may comprise one or more of rubber, latex, urethane, polyurethane, silicone, a thermo plastic elastomer (TPE), a woven fabric, or a spun fabric. The cover may comprise a hydrophilic adhesive layer which may comprise one or more of a hydrocolloid, a hydrogel, an acrylic polymer, or poly (ethylene glycol).

[0033] In yet a further aspect of the present invention, an incision closure appliance is provided. The incision closure appliance comprises a flexible adhesive bottom layer, a middle layer, and a top layer. The flexible adhesive bottom layer may have a first elasticity. The middle layer may be coupled to and cover at least a portion of the flexible adhesive layer and have a second elasticity less than the first elasticity. The top layer may be coupled to and cover at least a portion of the middle layer and have a third elasticity less than the second elasticity. An elasticity gradient between the flexible adhesive bottom layer and the top layer may provide sufficient stiffness for the incision closure appliance such that movement of tissue laterally adjacent the appliance when covering an incision and surrounding tissue does not substantially distend the covered incision and surrounding tissue.

[0034] The elasticity gradient may provide sufficient elasticity for the incision closure appliance such that blistering and adhesion loss due to movement of tissue adjacent the appliance when covering the incision and surrounding tissue are minimized.

[0035] The incision closure appliance may be axially flexible in response to axial stretching of the incision and surrounding tissue covered by the incision closure appliance. Movement of a first tissue region adjacent the periphery of the flexible adhesive bottom layer may substantially

translates into a same movement of a second tissue region adjacent the periphery of the flexible adhesive bottom layer and opposite the first tissue region.

[0036] The flexible adhesive bottom layer may comprise a hydrophilic adhesive material. The hydrophilic adhesive material may comprise one or more of a hydrocolloid, a hydrogel, an acrylic polymer, or poly (ethylene glycol).

[0037] The upper layer may comprise one or more of rubber, latex, urethane, polyurethane, silicone, a thermo plastic elastomer (TPE), a woven fabric, or a spun fabric.

[0038] The flexible adhesive bottom layer may comprise first and second adhesive bottom layers. The middle layer may comprise a first upper layer coupled to the first adhesive bottom layer and a second upper layer coupled to the second adhesive bottom layer. The top layer may comprise an arrangement of a plurality of axial support structures and a plurality of lateral closure components coupled to the axial support structures for fastening the first adhesive bottom layer and the first upper layer to the second adhesive bottom layer and the second upper layer. The plurality of axial support structures and the plurality of closure components may be coupled to one another to form a serpentine pattern for allowing the one or more of the lower adhesive layer or the middle layer to at least partially stretch in the axial direction of the closure device in response to axial stretching of the incision and surrounding tissue covered by the incision closure device. The plurality of axial support structures and the plurality of lateral closure components may be coupled to one another to form a ladder pattern. One or more of the plurality of axial support structures or the plurality of lateral closure components may be formed from flexible, non-distensible materials. The plurality of lateral closure components may be configured to draw inner edges of one or more of the first or second adhesive bottom layers and the first or second upper layers together after flexible adhesive bottom layer is adhered to tissue on opposite sides of the incision. One or more of the lateral closure components may comprise a left end, a right end, and a tie securely coupled to the left or right end and adjustably attached to the opposite end. One or more of the plurality of axial support structures or the plurality of lateral closure components may be embedded in or laminated to the first and second upper layers.

[0039] This aspect of the present invention may also provide a system for closing an incision in tissue. The system comprises the incision closure appliance and a flexible cover for overlying the incision closure appliance and the covered incision and surrounding tissue.

[0040] The flexible cover may be configured to extend over lateral and axial edges of the flexible adhesive bottom layer. The cover may have one or more perforations to allow the cover to at least partially stretch in the axial direction of the cover in response to axial stretching of the incision and surrounding tissue covered by the incision closure appliance. The one or more perforations may be disposed along a central axial line of the cover. The cover may comprise one or more reinforcing members coupled to at least a portion of an adhesive layer of the cover. The reinforcing members may comprise one or more of rubber, latex, urethane, polyurethane, silicone, a thermo plastic elastomer (TPE), a woven fabric, or a spun fabric. The cover may comprise a hydrophilic adhesive layer. The hydrophilic adhesive layer may comprise one or more of a hydrocolloid, a hydrogel, an acrylic polymer, or poly (ethylene glycol).

[0041] In yet a further aspect of the present invention, an incision closure appliance is provided. The incision closure appliance may comprise a lower portion having a first elasticity, an upper portion having a second elasticity less than the first elasticity, and an elasticity gradient between the lower portion and the upper portion. The elasticity gradient may provide sufficient stiffness for the incision closure appliance such that movement of tissue laterally adjacent the appliance when covering an incision and surrounding tissue does not substantially distend the covered incision and surrounding tissue. The elasticity gradient may provide sufficient elasticity for the incision closure appliance such that blistering and adhesion loss to due to movement of tissue laterally adjacent the appliance when covering an incision and surrounding tissue is minimized.

[0042] In yet a further aspect of the present invention, an incision closure appliance is provided.



The incision closure appliance may comprise a base including a left panel and a right panel, left and right force distribution structures, and a plurality of closure components. Each panel may have a tissue adherent lower surface, an upper surface, a first lateral edge, a second lateral edge. The left and right force distribution structures may be coupled to the left and right panels, respectively. Each force distribution structure may be adapted to allow axial expansion of the panel along one of the first or second lateral edges and to limit lateral expansion across the panel and axial expansion along the opposite lateral edge. The plurality of closure components may be secured to the left and right panels to draw the panels together after the panels are adhered to tissue and an incision made therebetween.

[0043] The first lateral edges of each panel may comprise inner edges of each panel. The inner edges of each panel may face toward one another.

[0044] The second lateral edges of each panel may comprise outer edges of each panel. The outer edges of each panel may face away from one another.

[0045] One or more of the left and right panels of the base may comprise an elastic matrix. The elastic matrix may comprise an elastomeric membrane, a woven fabric, or a spun fabric. The elastic matrix may comprise a fabric woven from elastic elements and having inelastic elements along the first or second lateral edge and extending laterally thereacross.

[0046] Each force distribution structure may comprise a spine disposed axially adjacent to the first lateral edge of the panel and a plurality of axially spaced-apart lateral supports disposed laterally and extending from the spine toward the first lateral edge of the panel. The spine and lateral supports may be formed from flexible, non-distensible materials. The force distribution structures may be embedded in or laminated to the upper surface of each panel.

[0047] The closure component may comprise a right engagement member, a left engagement member and a plurality of lateral struts holding the engagement members laterally spaced apart by a predefined distance. The right engagement member may be adapted to releasably engage the supports of the right panel and the left engagement member may be adapted to releasably engage the supports of the left panel. At least some of the supports may have cleats near the one or more of the first or second lateral edges and the engagement members may have slots which receive the cleats. The lateral struts may be adjustably connected to at least one of the engagement members to permit adjustment of the predefined distance. The closure component may comprise a plurality of independent lateral ties attached to at least some of the lateral supports. The lateral ties may be configured to be secured between lateral supports. The independent lateral ties may each have one end fixed to a panel and a second end adjustably attached to the other panel. The second end may comprise a ratchet tightening mechanism.

[0048] The incision closure appliance may further comprise a securing layer adapted to be placed over an assembly of the base and the closure components after the assembly has been secured over an incision on a patient's skin. The securing layer may have an inner self-adhesive surface.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0049] FIG. 1 is an exploded view of an incision closure appliance constructed in accordance with the principles of the present invention.

[0050] FIG. 2 is a top view of the assembly of a base and a force distribution structure which is part of the incision closure appliance.

[0051] FIG. 3 is a cross-sectional view taken along line 3-3 of FIG. 2.

[0052] FIGS. 4-7 illustrate use of the incision closure appliance of the present invention for forming and closing an incision in a patient's skin.

[0053] FIG. 8 illustrates an alternative construction of a closure component for the closure

appliance of the present invention.

[0054] FIG. **9** is an exploded view of a further embodiment of an incision closure appliance constructed in accordance with the principles of the present invention.

[0055] FIG. **10** is an enlarged isometric view of the base and force distribution structure of the system of FIG. **9**.

[0056] FIGS. **11A** and **11B** illustrate an alternative lateral tie construction which can be used in the appliances of either FIG. **1** or FIG. **9**.

[0057] FIG. **12** illustrates a sacrificial cover positioned over an incision closure appliance in accordance with the principles of the present invention.

[0058] FIGS. **13A** through **13E** illustrate the principle of operation of the sacrificial cover illustrated in FIG. **12** when used together with a surgical incision drape and performing methods according to the present invention.

[0059] FIGS. **14A1-14A3** are perspective views of further embodiments of an incision closure appliance constructed in accordance with the principles of the present invention.

[0060] FIG. **14B** is a top view of an incision closure appliance similar to that of FIGS. **14A-14A3** and which is placed on the knee of a subject according to the present invention.

[0061] FIG. **15A** shows a schematic of an incision closure appliance having a pulley system to laterally couple two adjacent base panels in accordance with the principles of the present invention;

[0062] FIG. **15B** shows a sectional view of the incision closure appliance of FIG. **15A**.

[0063] FIG. **15C** shows the incision closure appliance of FIG. **15A** placed on a model knee according to the present invention.

[0064] FIG. **15D** shows a schematic of an incision closure appliance similar to that of FIG. **15A**.

[0065] FIGS. **15E** and **15F** show various lateral tie assembly structures for use with the incision closure appliance of FIGS. **15A** and **15D**, respectively.

[0066] FIGS. **16A-16D** show various locking mechanisms in accordance with the principles of the present invention.

[0067] FIG. **17** shows a hinging mechanism for incision closure appliances in accordance with the principles of the present invention.

[0068] FIG. **18** is a top view of an incision closure appliance similar to that of FIG. **14A** and placed on the knee of a subject according to the present invention.

[0069] FIG. **19** shows an incision closure appliance comprising individual pairs of base panel segments according to the present invention.

[0070] FIG. **20A** shows a perspective view of the incision closure appliance similar to that of FIGS. **9** and **10** in accordance with the principles of the present invention.

[0071] FIG. **20B** shows a magnified view of the lateral tie assembly of the incision closure appliance of FIG. **20A**.

[0072] FIG. **21** shows an exploded view of a portion of the incision closure appliance of FIG. **21**.

[0073] FIG. **22A** shows a perspective view of a cover for the incision closure appliances disclosed herein in accordance with the principles of the present invention.

[0074] FIG. **22B** shows an exploded view of the cover of FIG. **22A**.

[0075] FIG. **23A** shows an exploded view of an incision closure appliance assembly comprising the incision closure appliance of FIG. **21** and the cover of FIG. **22A** in accordance with the principles of the present invention.

[0076] FIG. **23B** shows a perspective view of the incision closure appliance assembly of FIG. **23A** adhered onto the skin of a patient.

[0077] FIG. **23C** shows a top view of the elastomeric reinforcement layer of the cover of FIG. **22A**.

[0078] FIG. **24A** shows a perspective view of the incision closure appliance assembly of FIG. **23A** adhered onto the skin of a patient in accordance with the principles of the present invention.

[0079] FIG. **24B** shows a sectional schematic diagram of the incision closure appliance of FIG. **23A** adhered onto the skin of a patient in accordance with the principles of the present invention.

[0080] FIGS. 25A-25C illustrate a method of applying the incision closure appliance assembly of FIG. 23A on the skin of a patient in accordance with the principles of the present invention.

[0081] FIGS. 26A-26E illustrate embodiments of a cover for wound dressings and incision closure appliances in accordance with the principles of the present invention.

[0082] FIGS. 27A-27E illustrate embodiments of a wound closure appliance having a medicinal agent incorporated thereon in accordance with the principles of the present invention.

[0083] FIGS. 28A-28E illustrate embodiments of a wound closure appliance cover having a medicinal agent incorporated thereon in accordance with the principles of the present invention.

[0084] FIG. 29 illustrates another sacrificial cover positioned over an incision closure appliance in accordance with the principles of the present invention.

[0085] FIG. 30 illustrates a top view of a wound closure apparatus with wavy outer lateral edges to reduce strain on the skin, in accordance with many embodiments.

[0086] FIGS. 31A and 31B illustrate top and section views, respectively, of a wound closure apparatus with a thinned outer lateral region to reduce strain on the skin, in accordance with many embodiments.

[0087] FIG. 32 illustrates a top view of a wound closure apparatus with perforation which increase in size laterally outward to reduce strain on the skin, in accordance with many embodiments.

[0088] FIGS. 33A and 33B illustrate top and section views, respectively, of a wound closure apparatus where the base panels comprise a wider bottom layer to reduce strain on the skin, in accordance with many embodiments.

[0089] FIGS. 34A, 34B, 34C, and 34D illustrate top views of a method of closing an incision using a wound closure apparatus in combination with tissue glue, in accordance with many embodiments.

[0090] FIG. 35A shows a top view of a closure device with a lateral tie assembly in the form of belt buckle locks and straps, in accordance with many embodiments.

[0091] FIG. 35B shows a perspective view of the lateral tie assembly of FIG. 35A.

[0092] FIG. 35C shows a magnified, perspective view of a lateral tie in the lateral tie assembly of FIG. 35A.

[0093] FIG. 35D shows a top view of a pair of lateral ties in the lateral tie assembly of FIG. 35A.

[0094] FIG. 36A shows a top view of a closure device with a lateral tie assembly with pinch locks, in accordance with many embodiments.

[0095] FIG. 36B shows a top view of a pinch lock of the lateral tie assembly of FIG. 36A.

[0096] FIG. 36C shows a perspective view of a pinch lock of the lateral tie assembly of FIG. 36A.

[0097] FIG. 36D shows a magnified, perspective view of a pinch lock of the lateral tie assembly in the closure device of FIG. 36A.

[0098] FIG. 36E shows a side view of a pinch lock of the lateral tie assembly of FIG. 36A being manipulated.

[0099] FIG. 36F shows a top view of a pinch lock of the lateral tie assembly of FIG. 36A being manipulated.

[0100] FIG. 36G shows a top view of a pinch lock of the lateral tie assembly of FIG. 36A.

[0101] FIG. 36H shows a perspective view of a pinch lock of the lateral tie assembly of FIG. 36A.

[0102] FIG. 37A shows a top view of a saw-tooth lock for a lateral tie assembly of a closure device, in accordance with many embodiments.

[0103] FIG. 37B shows a perspective view of the saw-tooth lock of FIG. 37A being manipulated.

[0104] FIG. 37C shows a side view of the saw-tooth lock of FIG. 37A.

[0105] FIG. 37D shows a top view of the saw-tooth lock of FIG. 37A in a locked configuration.

[0106] FIG. 38A shows a top view of a fish-scale strap and lock for a lateral tie assembly of a closure device, in accordance with many embodiments.

[0107] FIG. 38B shows a perspective view of the fish-scale strap and lock of FIG. 38A.

[0108] FIG. 38C shows a magnified top view of the fish-scale strap and lock of FIG. 38A in a locked configuration.

[0109] FIG. 38D shows a perspective view of the fish scape strap and lock of FIG. 38A being manipulated.

## DETAILED DESCRIPTION OF THE INVENTION

[0110] The apparatus and methods of the present invention will be used during both the formation and the closure of surgical incisions made to a patient's skin or other tissue during surgical procedures. As described hereinafter, the direction of the incision will define both "axial" and "lateral" directions as those terms are used herein. Most incisions will be made along a generally straight line which will define the axial direction. The lateral direction will generally be across the axial direction, typically but not necessarily being perpendicular or normal to the axial direction. Most incisions will be generally linear but in some cases the incisions could be curved or have other geometries. The term "axial" will then apply to the direction of the incision at any particular location, resulting in lateral directions which could also vary.

[0111] Referring now to FIGS. 1-3, an incision closure appliance **10** comprises a base assembly **12** including a right panel **14** and a left panel **16**. A right force distribution structure **18** is secured to the right panel **14**, typically by laminating the force distribution structure to an upper surface of the panel, and a left force distribution structure **20** is similarly attached to an upper surface of the left panel **16**. The incision closure appliance further comprises a closure component **22** which is removably attachable to the right and left forced distribution structures **18** and **20** in order to close an incision, as described in more detail below, and the appliance is completed with an optional securing layer **24** which may be placed over the combined base assembly **12** and closure component **22** after they have been secured to the patient and the incision has been closed by drawing the panels together using the closure component.

[0112] The closure component **22** is intended and adapted to draw the inner portions of the force distribution structures **18** and **20** inwardly toward each other to close a surgical incision which has been formed therebetween. In the illustrated embodiment, a plurality of cleats **26** are formed on lateral supports **36** which are held axially by spine **37** of the force distribution structures **18** and **20**. The cleats **26** are received in slots **38** formed along inner edges of opposed engagement members **40** of the closure component **22**. The opposed engagement members **40** are held together by lateral struts **42** so that the engagement members are held at a fixed, laterally spaced-apart distance (in other embodiments the spaced-apart distance may be adjustable). The slots **38** are preferably formed on flexible tab-like structures **44** which allow the slots to be pulled upwardly over the corresponding cleats in order to secure the closure component **22** over the force distribution structures **18** and **20**.

[0113] The lower surfaces **32** of each panel **18** and **20** will typically be covered with a pressure-responsive adhesive, where the adhesive is initially covered with a protective layer **48** which may be peeled away immediately prior to use. Additionally, pull-away tabs **50** or other similar structures may be provided in order to hold the right and left panels **14** and **16** together at a pre-determined spaced-apart distance after the layer **48** has been removed but prior to adhering the panels to a patient's skin or other tissue surface. It is important that the distance between the inner edges **28** of each panel **14** and **16** be maintained as close as possible to the original target spacing so that the tissue edges, when closed by the closure component **22**, will be precisely brought together, typically with a slight eversion.

[0114] Referring now to FIGS. 4 through 7, a protocol for both forming an incision and subsequently closing the incision in accordance with the principles of the present invention will be described. Initially, the right and left panels **14** and **16** are placed on the patient's skin followed by reference letter S, as shown in FIG. 4. The panels **14** and **16** are applied by first pulling away the protective layer **18** and placing the panels onto the tissue, after which time the tabs **50** may be removed, leaving an incision path **52** defined between the inner edges **28**. The spacing of the inner edges **28** will be selected to provide a fixed, pre-determined distance **d1**.

[0115] After the right and left panels **14** and **16** are in place, an incision I can be formed in the

space between the panels using a scalpel or other surgical cutting device CD, as shown in FIG. 5. [0116] After the incision I is made, a surgical procedure may be performed by opening the inner edges of the incision which in turn deforms the inner edges **28** of the right and left panels **14** and **16**, as shown in FIG. 6. As the inner most ends of the supports **36** are not connected, they are free to separate and allow the elastic matrix of the right and left panels **14** and **16** to expand, as clearly in FIG. 6. The dimensional stability of the remainder of the panels, however, will be preserved by the lateral supports **36** as well as the axial spines **37** which do not elongate under the influence of the force applied by stretching opening the incision.

[0117] After the surgical procedure is complete, the closure component **22** will be secured over the force distribution structures **18** and **20**, as illustrated in FIG. 7. In particular, the slots **38** in the tab-like structures **44** are engaged over opposed cleats **26** in order to draw opposed edges of the panels as well as of the tissue incision together. By properly spacing the depth of the slots **38**, the closure component **22** can be tailored so that the panels **14** and **16** are brought together by a pre-selected distance  $d_2$ . Typically, the distance  $d_2$  will be less than the initial separation  $d_i$  so that the inner edges of the tissue are brought together to cause the tissue edges along the incision to slightly evert (pucker upwardly) which can improve healing and reduce scarring.

[0118] Optionally, as shown in FIG. 8, a closure component **22'** may include engagement members **40'**, where one end of each lateral strut **42'** is joined by an adjustable clasp or other mechanism **54** so that the distance between the inner edges of the opposed engagement members **40'** can be adjusted in order to increase or lessen the distance  $d_2$  therebetween.

[0119] An alternative embodiment **100** of the incision closure appliance of the present invention is illustrated in FIGS. 9 and 10. The appliance **100** includes a base assembly **102** having a right panel **104** and a left panel **106**. A positioning or alignment strip **108** is provided to secure the inner edges of each panel together, as shown best in FIG. 10 and includes an end tab **109** that allows the user to pull the strip from the panels **104** and **106** after the panels have been put in place on a tissue surface.

[0120] The incision closure appliance **100** further includes a backing **110** having an end which may be partially folded back to expose an underlying adhesive backing on the panels and allow that end of the base assembly **102** to be adhered to the tissue while the remainder of the base assembly is still covered by the backing. A securing layer **112** which includes a reinforcement frame **113** is provided for placement over the right panel **104** and left panel **106** after the base assembly **102** has been closed over an incision, generally is described in connection with the previous embodiment. Usually, a holding tray **114** will be provided for maintain the components of the appliance together in a sterilized condition where the tray **114** will be covered with conventional medical packaging cover.

[0121] As illustrated in FIGS. 9 and 10, a right force distribution structure **116** and a left force distribution structure **118** are provided on the upper surfaces of the right panel **104** and the left panel **106**, respectively. The right force distribution structure **116** includes a right axial spine **120** and a plurality of lateral supports **122**. Typically, the right axial spine **120** comprises a serpentine or zig-zag number which is embedded in or laminated to a base strip **121**. The serpentine axial spine **120** would typically be formed from a flexible, resilient plastic, typically a hard plastic, while the base strip **121** will be comprised of a polyurethane or similar plastic layer. The lower surface of the polyurethane layer will be covered with a hydrocolloid layer for tissue adhesion. The structure of the left forced distribution structure **118** will be the same including a left axial spine **124**, left lateral supports **126**, and a left base strip **127**.

[0122] The incision closure appliance **100** will include a closure mechanism comprising a plurality of lateral tie assemblies **128** as shown on FIG. 9. As best seen in FIG. 10, each lateral tie assembly **128** will include a rod which is secured at one end to the left lateral support **126** and a ratchet mechanism **132** which is secured to the right lateral support **122**. Each rod **130** will usually be aligned with the axis of the left panel **106** parties so that a gap **129** between the right panel **104** and

left panel **106** will be left open so that an incision can be made there between. After the incision is made, each rod **130** will be pulled over to the associated ratchet **132** on the right panel **104**. A series of ratchet rings on each rod will be pulled into the associated ratchet mechanism **132**, and the rod then pulled laterally until the desired closing tension is applied at that point along the base assembly **102**. It is a particular advantage that each of the lateral tie assemblies **128** may be individually adjusted to supply the desired closing tension across the tissue along the length of the incision being closed. Once the desired closing tension has been provided along the entire incision, the securing layer **112** may be placed over base assembly **102** to hold the appliance and tissue in place.

[0123] Referring now to FIGS. **11A** and **11B**, an alternative design for the lateral tie assemblies **140** of the present invention is illustrated. These lateral tie assemblies **140** may be utilized with either of the incision closure appliances **10** or **100** described previously. Each lateral tie assembly **140** includes a right force distribution structure **142** and a left force distribution structure **144**. The right force distribution structure includes a right spine **146** and a plurality of lateral supports **148**.

Although three are shown, it will be appreciated that four, five, six or more lateral supports could be included. The left force distribution structure **144** similarly includes a left spine **150** and a plurality of left lateral supports **152**. To provide closure, the right force distribution structure **142** includes a rod **154** which extends from the center lateral support **148**. Typically, the rod **154** is joined to the support by a live or passive joint **158**. A pull loop **156** is provided at the free end of the rod **154**, and a plurality of ratchet teeth **162** are provided along the midsection of the rod **154**.

[0124] The left force distribution structure **144** includes a ratchet mechanism **160** adapted to receive the teeth **162** on the rod **154** of the right force distribution structure. In this way, the rod **154** can be lowered into the ratchet **160** to engage teeth **162**, allowing the rod to be pushed forward in order to draw the right and left force distribution structures **142** and **144** together in order to apply tension to the right and left panels.

[0125] As illustrated in FIG. **12**, a further aspect of the present invention is illustrated. The incision closure appliance **100** is illustrated schematically with only the right and left panels **104** and **106** and the right and left force distribution structures **116** and **118** being illustrated. The remaining system components are not shown for ease of illustration.

[0126] The right panel **104** is covered by a right sacrificial cover **170** and the left panel **106** is covered by a left sacrificial cover **172**. The right and left panels **104** and **106** may define a region **175** where the right and left sacrificial covers **170** and **172** separates from the right and left panels **104** and **106**. Each cover **170** and **172** is detachably secured along each edge of the associated base panel so that the covers remain in place during normal handling and placement of the incision closure appliance **100** over the tissue surface to be incised. The use and purpose of these sacrificial covers **170** and **172** is described with reference to FIGS. **13A** and **13E**.

[0127] FIG. **13A** illustrates the right and left panels **104** and **106** in place on a tissue surface **T** prior to an incision being made. The right panel **104** is covered by right sacrificial cover **170** and the left panel **106** is covered by left sacrificial cover **172**. As is common in many surgeries, an adherent surgical incision drape **180** is placed over the tissue surface **T**. Any conventional drape may be used such as the Ioban<sup>TM</sup> antimicrobial incise drape, available from 3M, St. Paul, Minnesota.

[0128] After the incision drape **180** is in place over the incision closure appliance, a surgical incision **I** may be made for performing a desired surgical intervention. As can be seen, the incision **I** will cut through the surgical drape **180** between the right and left panels **104** and **106**, respectively. After the surgical procedure is completed, the surgical drape **180** will be removed from the tissue surface **T**. As the surgical drape has a lower adherent surface, prior to the present invention, removal of the drape might have displaced either or both of the right panel **104** and left panel **106**. Presence of the sacrificial layers **170** and **172**, however, prevents such displacement. Removal of the surgical drape **180** will remove the sacrificial layer **170** and **172**, but as each of these layers is configured to break off with a relatively low separation force, removal of the

sacrificial layers will not cause the underlying panels **104** or **106** to be displaced. Thus, the panels **104** and **106** will be left in place, as shown in FIG. **13D**, and the force distribution structures **116** and **118** can be used as described previously for closing the panels together to close the incision as shown in FIG. **13E**.

[0129] Referring to FIG. **29**, the right and left sacrificial cover layers **170** and **172** may each be constructed from a thin sheet of urethane (e.g., 0.001" thick). The middle of the urethane sheets may be adhered to the top of the right and left panels **104** and **106**, with the force distribution structures **116**, **118** as well as any straps **130** and locks **132**, assembled on top of the urethane sheets. The urethane sheets may then be wrapped around the force distribution structures **116**, **118** (and the straps **130** may be bent inward as shown in FIG. **29** such that they are contained over the panel **106**) with the free ends of the urethane laminated to one another along their length. Thus, the urethane sheet may wrap over the force distribution structures **116**, **118** and closure elements **130**, **132** to protect them from the surgical drape **180**. The urethane sheet may preferably comprise a plurality of perforations disposed along its length and aligned adjacent with the inner and outer edges **104e**, **106e** of each panel **104**, **106**. The perforations may allow the urethane sheet to tear away with the surgical drape **180** in a controlled manner when a surgical drape, e.g., the surgical drape **180** described herein, is removed. The perforations may preferably be constructed of a 3 mm cut and 1 mm tie, though exact dimensions may be varied to control the desired tear force. The perforations may be formed along a single longitudinal line, or a plurality of lines. A plurality of longitudinal perforation lines may allow for reliable separation despite variations in which the surgical drape adheres to the sacrificial layers **170**, **172**. The perforations could be made to release more easily near the edge of the panels **104**, **106** to help improve the likelihood of separation near the edges **104e**, **106e** of the panels **104**, **106** and minimize excess urethane being left behind. To aid in the lift of the sacrificial layers **170**, **172**, tabs **170t**, **172t** may be adhered to each end of the urethane wrap comprising the sacrificial layers **170**, **172**. The tabs **170t**, **172t** may preferably be adhered to the inside of the upper surface of the urethane wrap. The tabs **170t**, **172t** may be shaped to prevent adhesion of the urethane to itself or to any exposed adhesive from the ends of each panel **104**, **106**. Pre-breaking of the perforations at the end of each panel **104**, **106** may aid in the initial lift of the tab **170t**, **172t** and initiation of the tear by the user.

[0130] Referring now to FIGS. **14A1-14A3**, further embodiments of incision closure appliances are illustrated. The base assemblies **1400a** (FIG. **14A1**), **1400b** (FIG. **14A2**), and **1400c** (FIG. **14A3**) may each comprise a right base panel **1402** and a left base panel **1404**. The right base panel **1402** may comprise an upper layer **1406** and a lower layer **1408**. Similarly, the left base panel **1404** may comprise an upper layer **1410** and a lower layer **1412**. The upper layers **1406**, **1410** will typically be flexible but stiff enough to securely close tissue and minimize disruption of the incision and surrounding tissue. The upper layers **1406**, **1410** may comprise a plastic layer made of rubber, latex, polyurethane, silicone, a thermoplastic elastomer, a woven fabric, a spun fabric, or similar materials. The adhesive bottom layers **1408**, **1412** will typically be flexible and more elastic than the upper layers **1406**, **1410** to follow any movement of the underlying skin and tissue to maintain adhesion, minimize blistering, and otherwise reduce irritation. The adhesive bottom layers **1408**, **1412** may comprise a hydrophilic adhesive material such as a hydrocolloid, a hydrogel, an acrylic polymer, poly (ethylene glycol), and the like.

[0131] The right and left base panels **1402**, **1404** may comprise structures to facilitate and limit axial and lateral stretching of the base assembly **1400**. These structures may also evenly distribute the closure force exerted on an incision and may be disposed on the base assemblies **1400a**, **1400b**, and **1400c** along their axial length. The right base panel **1402** may comprise one or more right force distribution structures or axial supports **1414**. Each right axial support **1414** may comprise an axial support portion or spine **1414a** and two lateral support portions **1414b** coupled to the axial ends of the spine **1414a**. Together, the spine **1414a** and the two lateral support portions **1414b** form a C-shape which in some embodiments can open axially to a degree to facilitate axial stretching of the

right base panel **1402** between two laterally adjacent lateral support portions **1414b** of adjacent supports **1414** while limiting the axial stretching between the two lateral support portions **1414b** of a single support **1414**. In many embodiments, the C-shaped axial support **1414** is only flexible enough to allow flexing vertically but is stiff to minimize axial and lateral stretching. As shown in FIG. **14A1**, the right axial supports **1414** may be inward facing. As shown in FIGS. **14A2** and **14A3**, the right axial supports **1414** may be outward facing which may help to distribute any mechanical load against the tissue closure to the incision I between the right and left base panels **1402**, **1404**. Similarly, the left base panel **1404** may comprise one or more left force distribution structures or axial supports **1416**. Each left axial support **1416** may comprise an axial support portion or spine **1416a** and two lateral support portions **1416b** coupled to the axial ends of the spine **1416a**. Together, the spine **1416a** and the two lateral support portions **1416b** form a C-shape which in some embodiments can open axially to a degree to facilitate axial stretching of the left base panel **1402** between two laterally adjacent lateral support portions **1416b** of adjacent supports **1416** while limiting the axial stretching between the two lateral support portions **1416b** of a single support **1416**. In many embodiments, the C-shaped axial support **1416** is only flexible enough to allow flexing vertically but is stiff to minimize axial and lateral stretching. As shown in FIG. **14A1**, the left axial supports **1416** may be inward facing. As shown in FIGS. **14A2** and **14A3**, the left axial supports **1416** may be outward facing which may help to distribute any mechanical load against the tissue closure to the incision I between the right and left base panels **1402**, **1404**.

[0132] As shown in FIG. **14A3**, the base panel assembly **1400c** may further comprise skirts **1424** and **1426**. The skirts **1424**, **1426** may be similar to the thin base assembly covers described below. For example, each skirt **1424**, **1426** may comprise a 0.001 inch thick urethane film coupled to a 0.002 inch thick acrylic adhesive. The adhesive may be applied to the whole under-surface of the skirts **1424**, **1426** or may just to the region of the skirts **1424**, **1426** beyond the base panels **1402** or **1404**. During construction of the base panel assembly **1400c**, the skirts **1424**, **1426** may be applied directly over all or a portion of the adhesive layers **1408**, **1412**, respectively. The skirts **1424**, **1426** may be applied in place of, or in addition to, the thin film upper layers **1406**, **1410**, respectively. Release liners as described herein may further be provided to line the adhesive under-surface of the skirts **1424**, **1426**. The skirts **1424**, **1426** may extend beyond the outer border of the base panels **1402**, **1404**, respectively, by 8 mm or in a range of 1 to 20 mm, for example, but does not span across the lateral area between the base panels **1402**, **1404** to improve the ability to visualize and/or clean the incision site. Thus, the skirts **1424**, **1426** may help provide additional adhesive support and/or creep reduction to the adhesive layers **1408**, **1412** of the base panels **1402**, **1404** without having to align and place a separate cover or cover sheet over the base panel assembly **1400**. After manufacturing, the skirts **1424**, **1426** are typically already precisely aligned relative to the base panels **1402**, **1404**. A separate cover or cover sheet as described herein may still be used to prevent tampering of the incision site and components of the base panel assembly **1400c**. As the skirts **1424**, **1426** already laterally extend over the base panels **1402**, **1404**, respectively, such a separate cover or cover sheet may not require precise placement relative to the base panel assembly **1400c** and could be more narrow compared with other covers or cover sheets described herein.

[0133] One or more perforations **1418** may be provided in-between axially adjacent right axial supports **1414** on right panel **1402** to facilitate the axial and/or lateral stretching of the right base panel **1402**. The perforations **1418** may be all the way through the upper and lower layers **1406**, **1408** to provide aeration to the underlying tissue or may only be present on the upper layer **1406**. Similarly, one or more perforations **1420** may be provided in-between axially adjacent left axial supports **1416** on left panel **1404** to facilitate the axial and/or lateral stretching of the base panel **1402**. The perforations **1420** may be all the way through the upper and lower layers **1410**, **1412** to provide aeration to the underlying tissue or may only be present on the upper layer **1410**. As shown in FIG. **14A1**, there may only be a single perforation **1418** or **1420** between the axial supports **1414** or **1418**. As shown in FIGS. **14A2** and **14A3**, there may be a plurality of perforations **1418** or **1420**



in a lateral line between the axial supports **1414** or **1418**. The perforations **1418**, **1420** may also reduce the stress incurred as the skin stretches radially outward from the incision I such as during joint articulation and swelling.

[0134] A plurality of perforations **1418**, **1420** may, for example, be provided in-between the axial ends of the right and/or left axial supports **1414**, **1416** along the right and left lines **1424**, **1426** shown in FIG. **14B**. A plurality of axially-aligned perforations may be provided on each line segment **1424** or **1426** such that at least the upper and lower layers **1410**, **1412** of the base panels **1402**, **1404**, respectively, may break into separate segments when axially stretched as further described below. In some instances, during the wear duration of the device **1400**, the perforations **1418**, **1420** may allow the layers **1406** and **1408** of right panel **1402** and the layers **1410** and **1412** of left panel **1404** to completely divide and separate at the perforation line, which is shown in FIGS. **14A2** and **14A3**. The ability to completely divide and separate further allows the skin to stretch axially as needed, with the elongation allowed (and limited) by the linkages of axial supports **1414** and **1416** and closure components **1422** discussed below. As discussed herein, a flexible, compliant cover may be applied over the base panels **1402**, **1404** after the incision I is closed. The cover may further serve to provide (and limit) axial and lateral movement of the base structure **1400b**. Alternatively or in combination, one or more of the right or left base panels **1402**, **1404** may be laterally cut and separated in-between the force distribution structures or axial supports **1414**, **1416** to facilitate the axial and/or lateral stretching of the right and/or left base panels **1402**, **1404**.

[0135] To couple the right and left base panels **1402**, **1404** laterally together and optionally to tighten the right and left base panels **1402**, **1404** against one another, the base assembly **1400** may further comprise a plurality lateral closure components or tie assemblies **1422**. The lateral closure components or tie assemblies **1422** may comprise a ratchet mechanism similar to that of lateral tie assemblies **128** and **140** described above. The lateral tie assemblies **1422** may couple laterally adjacent right and left axial supports **1414**, **1416** together, typically at their axial ends. As shown in FIGS. **14A1-14A3**, the placement of the right and left axial supports **1414**, **1416** on the right and left panels **1402**, **1404**, respectively, may be staggered or axially offset, and the right and left axial supports **1414**, **1416** may be C-shaped structures with lateral end portions **1414b**, **1416b** that laterally face and align with one another (and are connected to one another by a lateral tie assembly **1422**). For example, the far end lateral portion **1414b** of a first right axial support **1414** may be laterally aligned with the near end lateral portion **1416b** of a first left axial support **1416**, the far end lateral portion **1416b** of the first left axial support **1416** may be laterally aligned with the near end lateral portion **1414b** of a second right axial support **1414**, and so forth. Thus, the lateral tie assemblies **1422** and right and left axial supports **1414**, **1416** may be connected to one another to form a line of consecutive lateral tie assemblies **1422** and right and left axial supports **1414**, **1416**, and this line may have a serpentine arrangement that laterally spans the right and left base panels **1402**, **1404** (i.e., goes across the distance between the right and left base panels **1402**, **1404**) as shown in FIGS. **14A1-14A3**. The serpentine arrangement of lateral tie assemblies **1422** and right and left axial supports **1414**, **1416** may one or more of evenly distribute the closure forces provided by the base assembly **1400** on an incision, provide (and limit) axial flexibility of the base assembly **1400**, and provide rigidity or stiffness to the base assemblies **1400a**, **1400b**, and **1400c** to sufficiently close an incision and allow it to heal with minimized disruption and distension (i.e., provide lateral and axial stability). In many embodiments, the lateral supports **1414**, **1416** are stiff so that the areas of the base panels **1402**, **1404** that are not covered with the lateral supports **1414**, **1416** stretch. Because these uncovered areas are offset from one another from the right base panel **1402** to the left base panel **1404**, the tie assemblies **1422** may pivot axially from their anchor points as the incision I is axially stretched. Such axial pivoting of the tie assemblies **1422** may bring the left and right panels **1402**, **1404** closer together to maintain the closure of the incision I.

[0136] The material of the lateral tie assemblies **1422** and the right and left axial supports **1414**,

**1416** may include, for example, a flexible, resilient plastic, typically a hard plastic, such as Nylon, Polypropylene, Polyethylene, Poly carbonate, and other thermoplastic polymers. Often, the lateral tie assemblies **1422** and the right and left axial supports **1414**, **1416** may comprise a material less elastic than that of the right and left base panels **1402**, **1404**. Thus, as with many other base assemblies of incision closure appliance disclosed herein, greater stiffness (and less elasticity) may be provided toward the top of base assemblies **1400a**, **1400b**, and **1400c**. In other words, there may be an elasticity gradient between the top and bottom of the base assemblies **1400a**, **1400b**, and **1400c**. The tops of the base assemblies **1400a**, **1400b**, and **1400c** may be sufficiently rigid or stiff so that the incision closure appliance, when applied to an incision and surrounding tissue, prevents movement of tissue laterally adjacent the appliance to not substantially distend the covered incision and surrounding tissue. That is, movement of at least a portion of the applied incision closure appliance (e.g., a portion below the more stiff layers) is collective and does not disrupt the underlying incision. And, the bottoms of the base assemblies **1400a**, **1400b**, and **1400c** may be sufficiently elastic such that blistering and adhesion loss due to movement of tissue adjacent the applied incision closure appliance are minimized. While a primary function of lateral tie assemblies **1422** may be to apply tension to each base panel **1402**, **1404** to hold the incision I closed, in many embodiments, the lateral tie assemblies **1422** may also serve to provide columnar strength so as to isolate the incision I by minimizing effects of compression on (or bending/creasing along) the incision I from distraction forces that could disrupt the incision edge alignment and apposition. The axial spacing, material property, and dimension of the lateral ties **1422** may be optimized for sufficient axial bending flexibility and lateral compression and bending support. In preferred embodiments, the spacing between ties **1422** is 10 mm, the material of the ties **1422** is nylon, and the dimension is a round cross-section of 0.030 inch.

[0137] Referring now to FIG. **14B**, the base assembly **1400b** may be placed over an incision in the skin of a patient or subject's joint, such as the knee. In incisions placed in proximity to articulating joints, the knee in particular, closure device or closure appliance integrity is often challenged by a number of factors. These factors include longitudinal elongation, circumferential swelling, opening of the wound as articulation occurs, skin damage such as blistering, adhesion loss, and passage of wound exudates. Joints such as knee, elbow, ankle, and shoulder may undergo a movement which can sometimes result in articulation covering more than 135° movements, leading to the challenges noted above.

[0138] In a bent position, the skin around the knee can stretch up to 50% axially (i.e., parallel to the incision) and laterally (i.e., transverse or perpendicular to the incision). An incision closure appliance adhered to the skin in this area may preferably be able to provide enough tension to close the incision yet accommodate the stretch with minimal local stress. Minimizing the local stress may prevent local skin adhesion loss or damage to the skin if the adhesive loss does not occur. An important property for many incision closure appliances disclosed herein is the ability of the tension load of the appliance's closure elements to be distributed across an area larger than that of the tension element attachment point itself. Furthermore, the structure comprising the adhesive to which the tensioning elements are attached may in many cases have the ability to distribute the compliance of the structure across the region of skin stretch such that the appliance holds the incision in place while the skin moves around it. Embodiments described herein may include a composite design of non-stretching tension elements (commonly referred to as “straps”) that are linked to “locks” that hold the straps in place. For example, such elements may include the lateral tie assemblies **128**, **140**, and **1422** described above. These elements may be mounted over skin adhesives with elastic polymeric materials that help distribute the tension load. Such elastic polymers may in many cases have high elongation before yielding or permanently deforming and may include thermoplastic elastomers such as polyurethane as well as various grades of silicone. Such materials may also be easily formed into thin films necessary for maintaining a low profile and sufficient compliance.

[0139] The skin adhesive used in the appliance may also need to withstand the elongation of the skin and be able to retract/recoil when the skin is returned to an un-stretched condition (e.g., in the fully extended knee position). Hydrocolloid adhesives may provide such properties and may be preferably suited for this application. Other adhesives such as acrylic may also be used to provide this property. In general, such adhesives may need to be attached to an elastic thin film such as that described above in order to hold their structure during expansion and recoil. Without such support, the adhesive may tear and separate with repeated elongation.

[0140] Incision closure appliances constructed as a sequence of short segments may accommodate higher overall elongation without loss of adhesion or skin damage. Each individual segment may be subjected to the local stretching of the skin under it. The space between two adjacent segments may act as stress relieving space allowing the skin to stretch in that space. The segmentation may be achieved in number of ways: (1) by laying down individual segments along the incision line, or (2) allowing the device to divide into short segments as it is applied to the skin or after applying to the skin.

[0141] A preferred means of achieving segmentation after application to the skin comprises creating perforations (e.g., a lateral line of perforations to facilitate tearing) in the polyurethane layer (i.e., the upper layer **1406**, **1410** of a base panel **1402**, **1404**) as described above and leaving the underlying adhesive intact, as shown in FIG. **14B**. The perforations may result in tearing of at least the upper layers (e.g., upper layers **1406**, **1410**) of the base panels along the perforated lines (e.g., lines **1424**, **1426**) when it undergoes stretching as the knee flexes (i.e., is articulated). In preferred embodiments, the adhesive panel on each side of the incision may be 12 mm wide, and the perforations within a given panel are spaced about 12-20 mm apart. Experimentation was performed and showed that a perforation of 3 mm cut and 1 mm tie distances are effective in achieving segmentation in 0.001 inch thick urethane base panels when the knee flexes. As the knee flexes, the skin may elongate in axial (along the incision) and lateral directions up to 50% in some locations. Separation of the polyurethane can thus relieve stress in the device as it undergoes stretch.

[0142] As an example, a surgically repaired knee may be inflamed for a number of days, which may result in approximately 30% radial swelling of the joint after closure. Elastic materials like polyurethane may allow the incision closure appliance (for example, including the base assembly **1400b** adhered to the resulting incision I in FIG. **14B**) to expand with this circumferential swelling. Minimizing the width of the appliance (e.g., 12 mm or less for each base panel segment **1402**, **1404**) may minimize the amount of the appliance subject to expansion in a direction perpendicular to the incision I, and may thus preserve adhesion while minimizing potential for skin damage. FIG. **14B** shows perforations in adhesive segments running in the lateral direction to the incision along lines **1424**, **1426** to allow easier stretch axially. Perforations or other fenestrations could also be made near the outer edges of the adhesive segments parallel to the incision in order to reduce the stress incurred as the skin stretches radially outward from the incision such as during articulation and swelling.

[0143] Referring now to FIGS. **15A-15D**, an incision may often experience forces that tend to open the incision due to the flexion of the knee or other joint. In many embodiments, an incision closure appliance is provided with a locking mechanism that counters the opening forces by closing tightly during flexion to assist in keeping the incision closed. FIGS. **15A** and **15B** shows a base assembly **1500** of an incision closure appliance that comprises a mechanism that leverages the pulley effect, i.e., when the skin stretches along the incision, the distance between the locking points on either side of the incision shortens. In preferred embodiments, the adhesive panels **1510a**, **1510b** on each side of the incision between the base panel **1510a**, **1510b** pairs is 12 mm wide, and the lined perforations **1530** within a given panel **1510** are spaced about 18 mm apart. Typically, all the members of the locking mechanism are non-stretching. The triangle formed by the anchor **1540**, pulley **1520**, lock **1550**, and flexible locking element **1580** (e.g., a tether or a strap) has its base B

axially along the incision and its height H laterally across the incision, as shown in FIG. 15C. As the knee flexes the triangle base length increases. Typically, all the members of the triangle are non-stretching, which requires that the height must decrease in order to preserve the length of individual elements connecting between any two points, resulting in additional closure forces across the incision. FIGS. 15A and 15B further show that the lower surfaces of the base panels **1510a**, **1510b** may comprise a hydrocolloid adhesive **1560** and one of the panels **1510a** or **1510b** may comprise a locking arm **1570** for locking the strap **1580** in place. While the base of the triangle is shown in FIG. 15A on the left base panel **1510b**, it is contemplated that the base of the triangle may instead be on the right base panel **1510a**.

[0144] While a triangle is formed by the anchor **1540**, pulley **1520**, lock **1550**, and flexible locking element **1580** other shapes are also contemplated. For example, the pulley **1520** may be wrapped around two anchors **1540** to form a square or rectangular shape, or the pulley **1520** may be wrapped around three or more anchors **1540** to form a trapezoid shape. Referring to FIG. 15D, a base assembly **1500a** of an incision closure appliance which is similar to the base assembly **1500** is shown. In the base panel **1500a**, the anchor **1540**, the two pulleys **1520**, the lock **1550**, and the flexible locking element **1580** form a rectangle to provide additional closure at the incision I when the underlying skin stretches. In the rectangular configuration shown in FIG. 15D, the spacing between the two fixed points on either side of the incision I will typically be the same. Whereas in the triangular configuration shown in FIGS. 15A and 15C, the fixed points on the pulley **1520** side may be spaced further apart than the other side of the incision I. While the rectangle is shown as “open” on the left base panel **1510b**, it is contemplated that the rectangle may be “open” on the right base panel **1510a** instead.

[0145] In the incision closure appliance base assemblies **1400a**, **1400b**, and **1400c** shown in FIGS. 14A1-14A3 and other described herein, individual straps **1422** may be used to engage individual locks on the opposite side of the incision I. In FIGS. 15A-15D, each flexible locking element or strap **1580** is typically anchored on one side of the incision I, wraps around the other side, and then engages a lock **1550** on the same side of the incision I as the location of anchor **1540**. In the embodiment shown by FIG. 15D, the flexible locking element or strap **1580** wraps around two fixed spools (bobbin/pulley **1520**) on the other side of the incision I before engaging the lock **1550** on the same side. The spools **1520** around which the flexible strap **1580** are wrapped may preferably be linked with a rigid member so that the distance between them does not increase when the closure device base panel assembly **1500** is elongated in the axial direction. In alternative embodiments, allowing expansion between the pulleys or spools **1520** may be desirable. It should be noted that the flexible locking element **1580** may be anchored in one base panel segment while locked in the adjacent segment separated by perforations **1530** in the base panel **1510a** or **1510b**. Such anchoring and locking may create a connection among three segments of the base strips—two on the same side and one on the other. When taken together across the length of the incision closure device or base assembly **1500** or **1500a**, the attachment mechanism forms a continuous ‘S’ shaped (i.e., serpentine) connections across the incision I.

[0146] The tensioned flexible connectors **1580** which wrap around the spindles, spools, or pulley **1520** may be configured to provide extra compression of the incision I when the distraction forces attempt to open the incision and the underlying skin experiences stretching. The flexible strap **1580** may in some cases potentially slip from the spindle **1520** and become loose if the two base panels **1510a** are further compressed by external forces brought together without any stretching of the underlying skin. To prevent such slippage from occurring, the flexible wrapping member **1580** can be slideably contained or anchored within an element **1590** anchored on the base strip **1510a**. FIGS. 15E and 15F show the flexible element **1580** threaded through a tube **1590** which in turn is attached or anchored to the base panel **1510a**. When the base panels **1510a**, **1510b** are brought closer together, the flexible strap element **1580** will still be captured and will continue to provide the necessary closure function. In other embodiments, the spool features **1590** shown in FIGS. 15E

and **15F** may have holes through the center which the strap **1590** slides through. The flexible strap **1580** and element **1590** it slides through may preferably be designed to minimize friction between the elements **1580** and **1590**.

[0147] Experimentation was performed and showed that where the base **B** is 12 mm and the height **H** is determined by the distance between the strap connecting points on the two base panels **1510a**, **1510b** after the incision is closed (typically about 16 mm), flexing of the appliance **1500** on a human knee resulted in the height **H** decreasing by 5% in the areas where the elongation of the skin **S** was maximum. It should be noted that the decrease in height may be dependent on a number of factors such as base of the triangle, level of elongation of the underlying skin and distance between the two bases on either side of the incision. The connecting “straps” between the anchors **1540** and the locks **1550** may need to be at least partially flexible to allow looping around the pulley. In preferred embodiments, a monofilament plastic thread is integrated with features that engage into a locking mechanism. Such features could be rounded “teeth” that engage in a ratchet-like mechanism within the lock. Such a plastic can be used to achieve the desired flexibility, longitudinal rigidity, low propensity to harbor bacteria, and allow for extrusion and/or injection molding processes. A braided suture (preferably coated to limit harboring of bacteria) can also be used to create flexible yet un-stretchable connectors. A round wire or tubing made out of flexible material like silicone can also be used to achieve the flexibility. The strap of the pulley could be a composite of materials such as molded plastic and braided suture. In other embodiments, the strap of the pulley can be formed by necking a molded strap. Pulling a molded strap beyond its yield point can reduce the cross-section of the strap permanently and make it more flexible when it elongates. Heat can be used in the necking process to facilitate elongation and reduction in the cross-sectional area. Alternative mechanisms shown in FIGS. **16A-16B** can be used for locking strap materials such as suture and softer plastic once desired closure is achieved. FIG. **16A** shows a locking mechanism comprising a slot for sliding **1610** and an anchoring frame **1620**. FIG. **16B** shows a locking mechanism comprising a locking tooth **1630**. FIG. **16C** shows a locking mechanism comprising a slot for sliding **1640** and an anchoring frame **1650**. FIG. **16D** shows a locking mechanism comprising a cylindrical tube **1660** and locking teeth **1670**.

[0148] The additional closure force across the incision when the knee flexes may be achieved by using a hinging mechanism **1700** as shown in FIG. **17**. As shown in FIG. **17**, the four points on either side of the incision (two anchor points **1720** on each side or base panel **1710** of the incision closure appliance) may be connected with non-stretching arms **1730** in the shape of an X, with hinging provided at the intersection **1740**. As the knee flexes and the distance between two points on the same side of the incision increases, the distance between the segments on either side of the incision may decrease, resulting in additional closure force. As shown in FIG. **17**, the base panels **1710** may also be provided with a plurality of perforations **1750** to facilitate axial stretching to the base panel **1710** or its separation into discrete segments upon axial stretching.

[0149] As shown in FIG. **18**, the straps and locks of an incision closure appliance **1800** according to many embodiments can be configured to form an S-shaped or serpentine connection or arrangement across the entire length of the incision **I** on the skin **S** of a knee. The incision closure appliance **1800** may be similar in many respects to the incision closure appliance **1400** described above. The segments **1810a**, **1810b** of the device **1800** are connected to each other by connecting each segment **1810a** on one side of the incision **I** with two adjacent segments **1810b** on the opposite side of the incision. This may be achieved by mounting a pair of straps **1820** in each segment **1810a** and a pair of locks **1830** on the corresponding segments **1810b** on the other side. Each pair of locks **1830** and straps **1820** may be connected with each other. During closure of the wound or incision **I**, one of the straps **1820** (e.g., strap **1820a**) of a base panel segment **1810a** (e.g., **1810a1**) may be connected with a lock **1830** (e.g., **1830a**) on a segment **1810b** (e.g., segment **1810b1**) on the other side of the incision **I** and the second strap **1820** (e.g., strap **1820b**) may be connected with a lock **1830** (e.g., **1830b**) in the segment **1810** (e.g., segment **1810b2**) on the

opposite side of the incision I adjacent to segment **1810b** (e.g., **1810b1**) in which the previous paired strap **1820** (e.g., strap **1820a**) was connected. The aforementioned connections form a single loop of the S-shaped or serpentine arrangement of base panel segments **1810**, straps **1820**, and locks **1830**. Perforation lines **1850** may separate axially adjacent base panel segments **1810a** and **1810b**. The perforation lines **1850** on one side (e.g., with base panel segments **1810a**) may be staggered with the perforation lines **1850** on the other side (e.g., with base panel segments **1810b**). Similar to FIG. 15A, in preferred embodiments, the adhesive panel on each side of the incision may be 12 mm wide, and the perforations within a given panel may be spaced about 18 mm apart.

[0150] Incision closure appliances or devices as described herein may be applied in many ways. FIG. 19 shows an example incision closure appliance **190** according to some embodiments. Here, individual base pair segments **1910** arranged in pairs may be provided on individual carrier/release liners. Each base panel segment **1910** pair comprises a strap **1920** and lock **1930** that may be independently aligned with the incision and adhered to skin adjacent to each other. Individual segments **1910** may be held together in relation to one another with a release liner and outer carrier tape **1950**. The release liner **1950** may be removed to expose the adhesive, but the entire device **1900** or grouped portions of the device **1900** may be linked with the outer carrier tape. Upon application to the skin, the carrier tape **1950** may be removed, leaving adhesive segments **1910** which are aligned with one another but can move independently.

[0151] Perforated segments of base panel upper layers, typically comprising polyurethane, may be held together with a continuous layer of the adhesive bottom layer, typically comprising a hydrocolloid adhesive, to allow laying down on the skin in one continuous motion. The incision closure appliances **1400**, **1500**, and **1800** of FIGS. 14A-14B, 15A-15C, and **18**, respectively, may be provided with such a continuous adhesive bottom layer.

[0152] The base assembly or base panels of the incision closure appliances described herein preferably may be covered with a flexible adhesive film material at the end of a wound or incision closure. This film area preferably may be larger than the base incision closure panel elements such that it overlaps the elements onto the skin. The film may help prevent migration of the base and may prevent any accidental movements of the anchors and locking mechanisms. The cover film may be made from stretchable materials like rubber, latex, polyurethane, silicone or thermoplastic elastomer, etc. In preferred embodiments, a thin cover (e.g., laminate of 0.001" urethane and 0.002" thick acrylic adhesive), will have a greater compliance than the composite structure of the base panel elements. As a result, the cover may offer some strain relief between the exposed skin and the base segments. The cover may also be transparent to allow visual inspection of the incision. The cover may completely seal across the incision (e.g., as a barrier to infection) or there may be openings in the cover that are aligned with the incision line to allow passage of any exudates from the wound. The cover may also serve to improve the apposition of the incision edges by bridging the base panels and adhering to the skin edges between the base strips. The cover may also be constructed with additional reinforcing elements that improve the tensile strength between the base panel elements but allow for compliance along the incision length. A preferred embodiment may comprise a series of polyethylene adhesive tape strips applied to the cover.

[0153] While the user may apply the cover after the base assembly and panels are placed on the skin, it is also conceived that the cover material may be supplied as a "skirt" extending around the outer perimeter of the base segments. Thus, alignment of the cover materials relative to the base may not be dependent on the user placement. These same cover materials may provide the effects of preventing exposure of the hydrocolloid adhesive to patient clothing, limitation of migration of the hydrocolloid or other adhesive lower layer, providing strain relief for the tension on the base segments, etc.

[0154] In many embodiments, a hydrocolloid adhesive is used for tensioning skin for incision closure. The hydrocolloid may be prevented from creep by one or more of (1) using a laminate on the surface to limit creep or (2) applying an adhesive cover across the skin and the hydrocolloid

adhesive to prevent creep and to provide strain relief to the skin to prevent skin damage.

[0155] In many embodiments, a cover as used with the base assembly may include one or more of perforations or openings to allow removal of wound exudate (as well as any applied bandages/absorbant material) without removal of the adhered base assembly.

[0156] In many embodiments, the cover comprises a composite of flexible urethane and reinforced strips. The composite construction may provide strength across the incision as well as provide for compliance along the incision length.

[0157] In many embodiments, the cover in combination with the base assembly aligns the skin incision edges or significantly prevents subsequent misalignment of the skin edges, in both the axial and lateral directions.

[0158] In many embodiments, cover liner configurations are provided such that part of the cover can be applied to the skin first, which then aids in the removal of other liners and thus may help control the thin materials so they lay out evenly with minimal wrinkling.

[0159] In many embodiments, the removal of a first liner may allow visualization during placement and may prevent the remainder of the device from sticking to the user.

[0160] Referring back to FIGS. **9** and **10**, two adhesive panels **104**, **106** are in many preferred embodiments applied to either side of a surgical incision (either before or after the incision is made). A closure mechanism may be mounted on top of the adhesive panels **104**, **106** and may be preferably attached to a component **120** which helps to distribute the closure forces between attachment points of the closure mechanism. As shown in FIGS. **9** and **10** as well as FIGS. **20A** and **20B**, this closure mechanism may comprise a strap **130** and a lock **132**. The strap **130** may comprise an elongated component with engagement teeth. The lock **132** may comprise a feature for capturing the engagement teeth of the strap **130**. The strap **130** may be tightened in the lock **132** to pull the adhesive panels **104**, **106** (and thus the incision edges) together. The user may disengage and re-engage the strap **130** in the lock **132** as necessary to properly adjust the amount of skin closure. Together, the incision closure appliance illustrated in FIG. **20A** may be described as the base or base assembly **102**.

[0161] The skin adhesive used for each panel **104**, **106** may preferably comprise a hydrocolloid adhesive. Alternatively or in combination, the skin adhesive may comprise one of many acrylic formulations known in the art. Hydrocolloid adhesives may have the benefit of being very tacky and able to absorb moisture and shedding skin cells. Thus, hydrocolloid adhesives may be particularly suited for long-term wear applications (e.g., up to 14 days). In at least some instances, the hydrocolloid structure may be soft, however, and may be prone to creep under tension unless reinforced in some manner such as by covering the hydrocolloid adhesive layer with stiffer base panels **102**, **104** or other covering structures disclosed herein.

[0162] Accordingly, a further aspect of the present invention also provides various means of reinforcing and protecting the adhesive layer in the base assemblies of the incision closure appliances described herein as well as additional means of holding the skin edges together, particularly in the axial direction. In at least some cases, the hydrocolloid adhesive alone has very low tensile strength and may require a means of reinforcement to prevent it from tearing or creeping during use. As illustrated in FIG. **21**, the adhesive layer **211** used in the base panels **104**, **106** may be laminated with a thin layer of a compliant plastic or polymer **212**, such as urethane, preferably 0.001 inch thick, with a potential range up to 0.010" thick, that may help to maintain its structure during clinical use. The adhesive layer itself may nominally be 0.010 inch thick, but may range between 0.005 inch and 0.020 inch thick. Because tensioning elements comprising straps **130** or locks **132** attached to a load distribution component **118** may be mounted to the top of the adhesive structure **211**, the possibility exists that the material could creep over time. The laminate **212** as well as any other adhesive laminates **215a**, **215b** between the adhesive layer **211** and the load distribution component **118** may help provide the structure to prevent creep of the adhesive layer.

[0163] To further prevent migration of the adhesive panel **211**, a cover **220** may also be applied over the panels **104**, **106** as shown in FIG. 22A. As shown in FIG. 22B, the cover **220** may comprise a thin, adhesive coated compliant elastomer **221**. In many embodiments, the cover **220** further comprises a thin urethane layer (preferably 0.001 inch thick) coated with a skin adhesive, such as an acrylic adhesive (preferably 0.002 inch thick), which may be provided on one or more release liners **223a**, **223b**. The cover may further comprise reinforcing features **225**.

[0164] As shown in FIGS. 23A and 23B, the cover **220** may be constructed such that it may extend beyond the base panels **104**, **106**, thereby bridging a distance,  $d_3$ , between the skin S and the panels **104**, **106**. A typical minimum necessary distance,  $d_3$ , may be 8 mm but could range 2-15 mm.

Besides helping prevent creep of the adhesive layer of the base panels **104**, **106**, the urethane skin adhesive of the cover **220** may also help to strain relieve the tension applied to the base panels **104**, **106** from movement of the surrounding skin S. This may serve to prevent skin damage (e.g., from erosion or blistering) at the base panel **104**, **106** edges. It should be noted, however, that the compliant nature of the hydrocolloid offers local protection from blistering by itself being able to move with the skin S and thus resist damage to the skin S. In many embodiments, even with stiffer structures mounted to the outer surface of the adhesive layers, the compliance within the nominal 0.010" thickness of the adhesive layers down to the skin surface may provide resistance to skin damage.

[0165] Besides stabilizing and strain relieving the base panel structures, the cover **220** may serve other purposes. By covering the location where a strap **130** would engages a lock **132**, the cover **220** may prevent the patient from tampering with the locks **132** to the point where the straps **130** could be disengaged. As shown in FIGS. 23A-23C, the cover **220** may be fitted with openings **224**, **224'** along the length of the region overlapping an incision, such that externally applied gauze may absorb wound exudate. In other embodiments, the cover **220** may not have openings in order to protect the wound from sources of infection. The cover **220** itself may have reinforcing features **225**, **225'** to provide the base **102** with additional resistance to the incision opening, particularly in regions between the straps **130**. FIG. 23C shows a particular embodiment where the reinforcing features **225'** could be rectangular strips of adhesive tape. The tape **225'** may preferably be stiffer perpendicular to the skin incision than the surrounding compliant urethane layer **221**. The tape **225'** may be constructed from any combination of adhesive coated woven fabric, polymer fibers, polyethylene, polypropylene, nylon, PET, hydrocolloid, or other materials known in the art. The reinforcing features **225'** may also add "body" or stiffness to the cover **220** to aid in its placement. The urethane layer **210** may be constructed of such materials to give it a bi-directional stretch.

[0166] The spacing of the reinforcing features **225**, **225'** may be important to ensure the longitudinal (parallel to the incision line) compliance of the cover **220** (e.g., due to the compliant thin urethane). This may serve to improve patient comfort and the resistance to skin damage by allowing the cover **220** and the underlying base assembly **102** to move with motions of the body. This effect may be from the cover **220** alone or as a composite effect with features on the base assembly **102** which may allow longitudinal compliance. The reinforcements **225**, **225'** may also be of a uniform construct, but perforated, slit, or otherwise mechanically interrupted to allow stretch and/or controlled tearing with body motion. The thin urethane layer(s) of the cover **220** may also be mechanically interrupted to the same effect. In at least some cases, the reinforcing features **225**, **225'** of the cover **220** may not extend the entire width (perpendicular to incision) of the cover **220**. This limited covering width may help ensure strain relief to the body motion away from the base assembly **102** perpendicular to the incision I. In preferred embodiments, the region of the cover **220** reinforced by the reinforcement members **225**, **225'** extends 10 mm in each direction away from the incision edge, but this may range from 2-50 mm.

[0167] Another feature of the cover **220** may be to be able to add control to the incision edge, particularly between the tensioning elements **130**, **132** of the base assembly. As illustrated in FIG. 24A, the tensioning elements **130**, **132** combined with the base panels **104**, **106** may serve to



approximate the incision edges **205** together. Once the skin **S** is approximated, it may be important that the skin edges be aligned vertically (perpendicular to the skin surface). Vertical misalignment may lead to slower healing and visible “step-off”, or ledge, in the incision that may result in poor scar cosmesis. By having portions of the cover **220** adhere to each edge of the base panels **104**, **106** along the incision, each edge may be held under tension in vertical alignment as shown by arrows **201a**, **201b**. Adhesive on portions of the cover **220** crossing the incision **I** may also adhere directly to the skin **S** at the incision edge, further shortening the distance between the adhered incision edges and further enhancing vertical skin alignment. In preferred embodiments, the portions of the cover **220** crossing the incision **I** are rectangular strips **225'** of adhesive tape as shown in FIG. **23C**. The width of each strip **225'** and the axial gap between the strips **225'** may be optimized for incision edge control, incision visibility, and the escape of wound exudate. A preferred embodiment may comprise a strip 12 mm wide and spaced 6 mm apart, with the strips located between each strip. Other widths and spacing are also contemplated. By not bridging/tenting over each strap **130**, the strip **225** may lay flatter against the skin **S** for better adhesion and edge control.

[0168] In some embodiments, the reinforcing features **225**, **225'** may be constructed to limit the amount of bending at the incision site. The reinforcing features **225**, **225'** in these embodiments may be stiffer than the skin **S**, and preferably stiffer than the surrounding elements of the base panels **104**, **106**. In this way, bending or compression of the skin **S** through normal patient motion would be isolated, or the propagation limited, around the incision site. While this motion isolation or limitation would help strengthen the incision site in tension, a greater benefit may be to prevent the incision edges from significantly or unevenly inverting, everting, or shifting in a direction perpendicular to the skin surface. Reinforcing materials discussed above may be used, with the thickness tailored to create the desired stiffness. Preferably, the composite of the base assembly **102** and cover **220** may be constructed to create a smooth transition in stiffness and compliance from the surrounding skin to the isolated incision site.

[0169] In particular methods of use, after initial closure of the incision using the base assembly **102** to approximate the skin edges, the base panels **104**, **106** may be pushed together further to “pooch” the closed incision **I** upward to slightly evert the edges and/or compress the skin **S** around the incision edges to relieve tension. FIGS. **25A-25C** illustrate an embodiment of this method in an in-vivo tissue model. FIG. **25A** shows a step **250A** in which the base panels **104**, **106** are adhered to the skin **S** adjacent an incision **I** and are pushed together to “pooch” the closed incision **I** upward. The base panels **104**, **106** may be then pulled together further to hold the tissue in this orientation. These methods may be enhanced by positioning the base panels **104**, **106** away from the incision edge by 5-10 mm. In a step **250B** shown by FIG. **25B**, the base panels **104**, **106** may be locked in place relative to one another with the straps **130** and the locks **132**. In a step **250C** shown by FIG. **25C**, the cover **220** may then be applied to lock in the relative location of the base panels **104**, **106** and “pooched” incision **I**. The incision **I** could be further reinforced with the reinforcing elements **225**, **225'** discussed above.

[0170] A given cover **220** may in many embodiments be fitted with release liners to aid in user handling of the cover **220** before and during application to the patient. As shown in FIGS. **22A** and **22B**, the cover **220** may have release liners **223a**, **223b** applied in a three-part configuration. The user may first remove a longitudinal center liner **223b** to apply the center exposed adhesive to the base assembly **102** and skin incision region. Removal of this liner **223b** first, in combination with visualization through the clear plastic and/or openings in the center of the base **220**, may allow the user to see the base assembly **102** underneath such that the cover **220** can be properly aligned with the base assembly **102** as the cover **220** is applied. This may also help provide regions of the cover **220** that do not stick to the user until the cover **220** is initially secured to the base assembly **102** and/or the skin **S**. Next, the side release liners **223a** may be removed in a direction perpendicular to the incision **I**. The liners **223a** hold and tension the very thin urethane to keep it from substantially wrinkling as it is applied to the skin **S**. Also, by sticking the center of the cover **220** to the base

assembly **102** and/or the skin **S** first, the cover **220** may be held in place such that sufficient tension and control may be applied to the side release liners **223a** for smooth application of the remainder of thin adhesive coated cover **220** to the patient. Alternatively or in combination, the liners may be constructed such that the first liner is removed to expose a narrow strip over the full width of the cover **220** (perpendicular to the incision **I**) to allow initial placement on the base assembly **102** and/or skin **S**, followed by removal of one or two additional liners in a direction parallel to the incision **I**. The first liner may be in the middle of the length, on either end, or somewhere in between. If not on the end, two additional liners may be required, each removed in a direction from the location of the first liner outward along the length of the device. If the first liner was on one end, a second single liner may be removed from the location of the first liner out toward the end of the device.

[0171] Another release liner configuration may be to have a single liner which could be completely removed from the bottom of the cover **220** before application. This type of liner may require an outer film, or casting sheet, be lightly adhered to the outer surface of the cover **220** to help the thin urethane hold its shape and provide the user with locations at the sides and/or ends which do not have adhesive and thus would not stick to the user's hands during application. The outer film could be over the entire outer surface or just a particular width surrounding the perimeter of the cover **220**. The film and/or the release liner could also have an area extending beyond that of the thin urethane in the cover **220**. Once the cover adhesive is attached to the base assembly **102** or skin **S**, the casting sheet may be easily removed from the outside of the cover **220**.

[0172] As described herein, flexible wound dressings and wound or incision closure devices or appliances are typically flexible and stretchable to follow the contour of curved parts of the body (e.g., arm, longer incisions that are curvilinear, etc.) or the areas that undergo stretching (e.g., knee). To assist the draping of such devices, a backing material may be used which assists in maintaining the dressing shape during the application. Such temporary backing material described herein may have a number of advantages. The backing material may be clear to enable the visual of the wound. The material may be non-stretchable to prevent elongation of the dressing or closure device or appliance during application. The backing may be easily removable after the application of the wound dressing or closure device or appliance so as to not affect the adhesion of the actual dressing on the wound site. The backing material may also assist in the handling of the dressing during manufacturing process. In many embodiments, the backing material may couple to a dressing or closure device with peel-off release liners on the adhesive side of the dressing to enable easy and reliable removal of the backing material.

[0173] Referring now to FIG. **26A**, a wound dressing cover **2600** may comprise a flexible sheet **2610** made of a flexible material like rubber, urethane, silicone, etc. The flexible material **2610** may be laminated on a relatively stiffer material in the form of a casting sheet or carrier layer **2620**. The casting sheet **2620** prevents the flexible material **2610** from rolling onto itself and becoming unusable. The flexible sheet **2610** may have an adhesive on one side (e.g., the bottom side) and a relatively rigid (stiff) carrier layer or casting sheet **2620** on the other side. The adhesive side is protected by two liners **2630**, **2640** that can be sequentially removed to expose the adhesive in a controlled manner. To apply the dressing **2600** on the wound or incision, a small strip of adhesive is exposed by removing one of the release liners, usually the smaller release liner **2630**. This release liner **2630** may be attached to the casting sheet **2620** using a tape **2650**. The exposed part of the flexible sheet **2610** may then be adhered at one end of the wound or incision. The flexible cover **2600** then follows the contour of the wound or incision and the curvature on the body as the second release liner **2640** is slowly removed to expose the adhesive sequentially.

[0174] The first release liner **2630** which is typically still attached to the casting sheet **2620** with the tape **2650** may then be used to lift the casting sheet **2620** from the flexible dressing **2610**.

[0175] A manufacturing process for the wound dressing cover **2600** and associated liners **2630**, **2640** may be to use a single die to cut a common profile (perimeter) of the laminate of the release

liners **2630**, **2640**, the flexible dressing (with adhesive) **2610**, and the casting sheet **2620**. Upon removal of the liners **2630**, **2640** and application of the dressing sheet **2610** to the skin, the casting sheet **2620** may remain on the dressing sheet **2610**. Removal of the casting sheet **2620** may require initiation by delaminating and peeling back an edge of the casting sheet **2620** from the dressing sheet **2610**. Once initiated, the continued peel and removal of the casting sheet **2620** may be straightforward. Initiation and lift of the edge of the casting sheet **2620** may not always be intuitive and may require a free edge connected to the casting sheet **2620** to help identify the lift point and begin the peel. The tape **2650** may be used to bridge the casting sheet **2620** to the release liner **2630** and may provide an easily identifiable tab which can be used to initiate the peel.

[0176] Alternative configurations of the casting sheet **2620** may be used to initiate the peel of the casting sheet **2620** as shown in FIGS. **26B-26E**.

[0177] As shown in FIG. **26B**, the casting sheet die may be cut such that the casting sheet **2620a** extends axially beyond the flexible dressing sheet **2610** (e.g., the liners **2630**, **2640** and urethane material of the flexible dressing sheet **2610** may be “kiss cut” to the surface of the casting sheet **2620a**).

[0178] As shown in FIG. **26C**, the casting sheet **2620** may have tape **2650** applied to either one or both axial sides to extend beyond the casting sheet. The tape **2650** may not necessarily be attached to the release liner **2630**.

[0179] As shown in FIG. **26D**, casting sheet tape **2650** may be attached at or near the axial edge(s) of the casting sheet **2620** and also extends inside the profile of the casting sheet **2620**, with a loose non-adherent edge **2652** for the user to grasp.

[0180] As shown in FIG. **26E**, the casting sheet die may be cut (e.g., kiss cut such that the casting sheet **2620** is not cut into the flexible dressing sheet **2610**) from one axial edge to a partial or full-length distance to another axial edge of the casting sheet **2620**. The cut casting sheet **2620** may be separated with a “pinch” by the user to create an edge to grasp. The interior die cut edge may also have a tape or similar tab **2654** applied to one or both of the interior edges to grasp and peel as shown in FIG. **26E**.

[0181] In many embodiments, the casting sheet **2620**, **2620a** and/or tape **2650**, **2652**, **2654** may be of a different color or have markings to distinguish from the flexible dressing sheet **2610** and release liners **2630**, **2640**.

[0182] One or more of the components of the incision closure appliances or incision closure appliance assemblies disclosed herein, including one or more of the various base assemblies, base panels, force distribution structures, axial supports, lateral supports, closure components, tie assemblies, straps, locks, adhesive layers, adhesive layers, covers, cover structures, drapes, etc., may be comprised of, be coated with, or otherwise incorporate one or more of an antifungal, antibacterial, antimicrobial, antiseptic, anti-inflammatory, or medicated material. For example, such materials may be incorporated into the hydrocolloid adhesive layer, as another layer or coating between the skin and the adhesive layer (covering at least a portion of the adhesive layer), incorporated into the base assembly cover or at least its adhesive layer, etc. One or more wells, grooves, openings, pores, or similar structures may be provided on the device or apparatus components to facilitate such incorporation. In many embodiments, such materials may comprise one or more of silver, iodide, zinc, chlorine, copper, or natural materials such as tea tree oil as the active agent. Examples of such antifungal, antibacterial, antimicrobial, antiseptic, anti-inflammatory, or medicated materials include, but are not limited to, the Acticoat™ family of materials available from Smith & Nephew plc of the U.K., the Acticoat® Moisture Control family of materials available from Smith & Nephew plc of the U.K., the Contreet® Foam family of materials available from Coloplast A/S of Denmark, the UrgoCell® Silver family of materials available from Urgo Limited of the U.K. (a subsidiary of Laboratoires URGO of France), the Contreet® Hydrocolloid family of materials available from Smith & Nephew plc of the U.K., the Aquacel® Ag family of materials available from ConvaTec Inc. of Skillman, NJ, the Silvercel®

family of materials available from Kinetic Concepts, Inc. of San Antonio, TX, Actisorb® Silver **220** available from Kinetic Concepts, Inc. of San Antonio, TX, the Urgotul® SSD family of materials available from Urgo Limited of the U.K. (a subsidiary of Laboratoires URGO of France), the Inadine® family of materials available from Kinetic Concepts, Inc. of San Antonio, TX, the Iodoflex® family of materials available from Smith & Nephew plc of the U.K., the Sorbsan Silver™ family of materials available from Aspen Medical Europe Ltd. of the U.K., the Polymem Silver® family of materials available from Ferris Mfg. Corp. of Burr Ridge, IL, the Promogram™ family of materials available from Kinetic Concepts, Inc. of San Antonio, TX, the Promogram Prisma™ family of materials available from Kinetic Concepts, Inc. of San Antonio, TX, and the Arglaes® family of materials available from Medline Industries, Inc. of Mundelein, IL. Examples of anti-inflammatory agents that may be used may include the class of topical non-steroidal anti-inflammatory agents (e.g., NSAIDs) such as diclofenac sodium, diclofenac potassium, and diclofenac diethylamine, to name a few. {{PLEASE PROVIDE ALTERNATIVE TOPICAL ANTI-INFLAMMATORIES (AND FURTHER ANTI-MICROBIALS) AS APPROPRIATE.}}

Components of the closure devices described in commonly owned U.S. Pat. Nos. 8,313,508, 8,323,313, and 8,439,945; U.S. Patent Publication No. 2013/0066365; and PCT application nos. US 2010/000430, US 2011/139912, US 2011/40213, US 2011/34649, and US 2013/067024 may also be comprised of, be coated with, or otherwise incorporate one or more of an antifungal, antibacterial, antimicrobial, antiseptic, anti-inflammatory, or medicated material, including but not limited to one or more of the materials listed above.

[0183] In many embodiments, topical medicinal agents are incorporated directly into the wound closure appliances described herein. Because a wound closure device is often applied in close proximity to a wound or incision in need of medicinal protection, the incorporation of such medicines directly into the closure device may be beneficial. In wounds at risk of infection, incorporation of anti-microbial agents may be beneficial, for example. Anti-microbial agents may include antibiotic medicines as well as antiseptic metal ions and associated compounds which may include silver, iodine, copper, and chlorine, or natural materials such as tea tree oil. In wounds prone to fungus, medicinal agents such as zinc may be warranted, for example. To facilitate healing, various anti-inflammatory agents (e.g., NSAIDs) may be incorporated into the closure device. Combinations of any of these agents may also be of benefit and thus may be incorporated into wound closure appliances.

[0184] Topical medicinal agents may be incorporated into the closure devices in a way to give the closure devices the ability to wick exudate away from the wound (e.g., to direct unwanted organisms away from the wound and/or prevent skin maceration), while keeping the wound sufficiently hydrated for improved healing.

[0185] Referring now to FIG. 27A, a wound or incision closure appliance **2700** comprises a base comprising two base panels **2710R**, **2710L** comprising upper polymer layers **2720R**, **2720L** and lower adhesive layers **2730R**, **2730L** applied in close proximity to each side of a surgical incision I. Features of the panels **2710R**, **2710L**, such as straps **2740**, may allow the skin on either side of the incision I to be drawn together and held in place during the healing period. The adhesive may preferably comprise a hydrocolloid formulation, but may comprise acrylic or other adhesives known in the art. The upper polymer layers **2710R**, **2710L** (e.g., 1 mil polyurethane) are preferably applied to the top of the adhesive layers **2720R**, **2720L** to isolate the adhesive layers **2720R**, **2720L**. Medicinal agents may be incorporated into the structure of the base panels **2710R**, **2710L**. At a minimum, the agents may inhibit growth of unwanted organisms where they contact the skin from the base panels **2710R**, **2710L**. The agents may be released from the base panels **2710R**, **2710L** and may migrate to regions within or in close proximity to the wound. The agents may be contained with carrier structures, such as adhesive layers **2730R**, **2730L**, which are able to absorb fluid and aid in the release of the agents. Such structures may include hydrocolloids, hydrofibers (such as those containing sodium carbomethylcellulose), hydrogels, collagen, alginates, foams of

polyurethane or silicone, or other related materials known in the art. The carrier could alternatively or in combination be an ointment, cream, gel, or powder. The medicinal agent (such as silver ions) may alternatively or in combination be applied to metals or polymers (for example, in mesh form) via a solvent coating process or vapor deposition. Such mesh-like products may be bonded or imbedded in the structure of a closure device.

[0186] In exemplary embodiments, a medicinal agent comprising a silver compound such as silver sulfate may be incorporated into the base panels **2710R**, **2710L**. As the base panels **2710R**, **2710L** come into contact with wound exudate and/or sweat or external fluids, the agents may be carried toward the wound. As fluid is absorbed into the base panels **2710R**, **2710L**, the base panels **2710R**, **2710L** may be able to release the silver ions which interfere with bacterial growth. Examples of how an agent such as silver may be incorporated into the base panels are shown in FIGS. **28A-28B**, which show various embodiments of sample segment **2750** of the right base panel **2710R** in FIG. **27**. These examples may also apply for the left base panel **2710L**.

[0187] FIG. **27B** shows a medicinal agent **2760R** blended directly into the adhesive layer **2730R** in the sample segment **2750**. The adhesive is typically a hydrocollid, which may be able to absorb a significant percent of its weight in fluid, thereby aiding the release of the agents.

[0188] FIG. **27C** shows another embodiment of the sample segment **2750** of the base panel **2710R** in which the medicinal agent is incorporated into a carrier structure **2770R** which is incorporated on top of the base panel **2710R**, preferably concentrated on the part of the base panel **2710R** near the incision I. Further features may be incorporated to strip away (and replace as needed) the carrier structure **2770R** if it becomes saturated with exudate or other fluids, and/or the concentration of the medicinal agent drops below an effective level.

[0189] FIG. **27D** shows an embodiment similar to that of FIG. **27C** in which the carrier structure **2770R** comprising the medicinal agent is incorporated on the inside edge of the base panel **2710R**.

[0190] FIG. **27E** illustrates how the carrier **2770R** could be incorporated onto both the top and inside edge of the base panel **2710R**. In these examples, the carrier structure **2770R** on either or each inside edge of the base panel **2710R** may be compressed over the wound or incision I to aid in its stability over the wound or incision I.

[0191] Medicinal agents and their carrier structures may alternatively or in combination be incorporated into the cover for the incision closure appliance. As described above, the cover is typically applied over the base panels of the incision closure appliances to help secure the appliance to the skin and protect the skin. As shown in FIG. **28A**, a cover **2800** could have the medicinal agent **2810** incorporated into the entire surface of the cover **2800** with or without a carrier structure, such as adhesive layer **2810** mixed with the medicinal agent. Alternatively or in combination, the agent may be incorporated into a discreet portion of the cover **2800**, preferably within a carrier structure **2820** lying directly over the wound site as shown in FIG. **28B**.

[0192] In at least some instances, the carrier structure **2820** may become saturated over time and/or lose its medicinal strength, and replacing the medicinal structure **2820** will be of benefit. As shown in FIG. **28C**, the medicinal structure **2820** could be removable (e.g., through tear-away perforations **2830** in the cover **2800**) and optionally replaced with another medicinal structure **2821** coupled to the narrow cover strip **2801** shown in FIG. **28D**. In the narrow cover strip **2801**, the adhesive portion of the cover **2801** may extend beyond the medicinal structure **2821** to hold the structure **2821** against the skin. The narrow strip **2801** may alternatively be applied to the wound site before the cover **2800** is applied. The cover **2800** may be designed to cover the narrow strip **2801**, or the cover may have perforations **2830** to allow removal of the underlying strip.

[0193] For either or both the base panels **2710R**, **2710L** and the cover **2800**, the carrier structures **2770R** or **2820** (with or without the medicinal agent), or the medicinal agent alone, could be patterned with the adhesive layer of the respective structure. A patterned construction may comprise a repeating shape (e.g., circles, ovals, polygon, slots, etc.) of adhesive material adjacent a similar repeating shape (or remainder of the matrix) of the carrier structure. This would help ensure

adhesion of the base panels **2710R**, **2710L** or cover **2800** while integrating the medicinal agent within the carrier structure **2770R** or **2820**. A simple example is shown in FIG. **29E** in which the carrier structure **2820** comprises a repeating shape **2850**. The medicinal agent and carrier structure **2820** could also be applied to the base straps **2740** which cross the incision I.

[0194] Many embodiments also provide further features to reduce the strain or tension on the skin from an adhered closure device base panel. FIG. **30** shows an exemplary closure device **3000** which may be similar to the other closure device described herein. The closure device **3000** may comprise a first base panel **3010**, a second base panel **3015**, a plurality of lateral ties **3020** to adjustably couple the first and second base panels to one another, and a plurality of force distribution structures **3030**. The force distribution structures **3030** may support the base panels, may provide preferentially separating regions of the base panels between axially adjacent force distribution structures **3030**, and may couple axially adjacent ends of the attachment points of the lateral ties **3020**. The outer lateral edges **3012** and **3017** of the first and second base panels **3010** and **3015**, respectively, may be wavy so as to provide a greater contact length for the outer lateral edges **3012** and **3017**. The greater contact length of the outer lateral edges **3012** and **3017** may reduce the strain and/or tension on the skin from the adhered base panels **3010** and **3015**, particularly when the base panels **3010** and **3015** stretch and relax. As described above and herein, one or more additional skirts may be incorporated onto the closure device **3000** to provide additional strain or tension relief.

[0195] Referring to FIGS. **31A** and **31B**, other features to reduce the strain or tension on the skin from an adhered closure device base panel may be provided alternatively or in combination. A closure device **3100** may be similar to closure device **3000** and may comprise similar features such as first base panel **3110**, second base panel **3115**, lateral ties **3120**, and force distribution structures **3130**. Each of the base panels **3110**, **3115** may comprise laterally inward portions **3110A**, **3115A**, respectively, and laterally outward portions **3110B**, **3115B**, respectively. The laterally outward portions **3110B**, **3115B** may be thinner than the laterally inward portions **3110A**, **3115A**, respectively, so that the laterally outward portions **3110B**, **3115B** may be more easily stretched, thereby relieving strain and/or tension on the adjacent skin. As shown in FIG. **31B**, the height of the base panels **3110**, **3115** may taper down in the laterally outward direction to provide the thinned laterally outward portions **3110B**, **3115B**. In this manner, the each of the base panels **3110**, **3115** may be provided with an increasing inward, lateral elasticity gradient to the base panels. As described above, the assembly of the lateral ties **3120** and the force distribution structures **3130** may be made of a stiffer material than the base panels, thereby adding to the increasing inward, lateral elasticity gradient. As described above and herein, one or more additional skirts may be incorporated onto the closure device **3100** to provide additional strain or tension relief.

[0196] Referring to FIG. **32**, other features to provide more stretchable laterally outward portions for the base panels, thereby reducing the strain or tension on the skin, may be provided alternatively or in combination. A closure device **3200** may be similar to closure devices **3000**, **3100** and may comprise similar features such as first base panel **3210**, second base panel **3215**, lateral ties **3220**, and force distribution structures **3230**. Each of the base panels **3210**, **3215** may comprise a plurality of perforations to provide greater elasticity. The first base panel **3210** may provide a plurality of outer perforations **3240** and a plurality of inner perforations **3250**. Likewise, the second base panel **3225** may provide a plurality of outer perforations **3255** and a plurality of inner perforations **3245**. The outer perforations **3240**, **3255** may be larger than the inner perforations **3250**, **3245** to provide greater an increasing lateral elasticity gradient to the base panels. As described above, the assembly of the lateral ties **3220** and the force distribution structures **3230** may be made of a stiffer material than the base panels, thereby adding to the increasing inward, lateral elasticity gradient. As described above and herein, one or more additional skirts may be incorporated onto the closure device **3200** to provide additional strain or tension relief.

[0197] Referring to FIGS. 33A and 33B, other features to provide more stretchable laterally outward portions for the base panels, thereby reducing the strain or tension on the skin, may also be provided alternatively or in combination. A closure device **3300** may be similar to closure devices **3000**, **3100**, **3200** and may comprise similar features such as first base panel **3310**, second base panel **3315**, lateral ties **3320**, and force distribution structures **3330**. Each of the base panels **3210**, **3215** may comprise a two or more layers stacked on top of one another. The first base panel **3310** may comprise a first layer **3310A** and a second layer **3310B** below the first and extending laterally further beyond the first. Likewise, the second base panel **3315** may comprise a first layer **3315A** and a second layer **3315B** below the first and extending laterally further beyond the first. The many layers may be of the same or similar materials and may be fixed adhered to one another, but the additional thickness of the laterally inward portions of the base panels provides greater stiffness laterally inward and greater elasticity laterally outward. In this manner, an increasing lateral elasticity gradient is provided to the base panels. As described above, the assembly of the lateral ties **3320** and the force distribution structures **3330** may be made of a stiffer material than the base panels, thereby adding to the increasing inward, lateral elasticity gradient. As described above and herein, one or more additional skirts may be incorporated onto the closure device **3300** to provide additional strain or tension relief.

[0198] Referring to FIGS. 34A-34D, aspects of the present disclosure also provide methods of closing an incision or wound with a combination of a closure device and tissue glue. The closure device may be any of the closure devices described herein, and the tissue glue may comprise a medically acceptable cyanoacrylate adhesive or a cyanoacrylate, fibrin, albumin, or glutaraldehyde based adhesive. An example of such a tissue glue may be Dermabond® from Johnson & Johnson of New Brunswick, New Jersey, Krazy Glue® from Elmer's Products of Westerville, Ohio, and Super Glue® of Super Glue Corporation of Ontario, CA.

[0199] As shown in FIG. 34A, an incision I may have been made on a skin S of a subject. As shown in FIG. 34B, a closure device **1400b** may be adhered to the skin S, with its two base panels being axially aligned with and on opposite lateral sides of the incision I. The tissue underlying the incision I may be brought together to close the incision I prior to the closure device **1400b** placement. As shown in FIG. 34C, the lateral ties **1422** may be adjusted to bring the base panels closer together and further tighten closure of the incision I. As shown in FIG. 34D, tissue glue **3401** may be applied over the incision I between the base panels, such as with an applicator **3406**. As shown in FIG. 34D, the tissue glue **3401** may be applied over the incision I such that the tissue glue **3401** does not contact skin covered by the two base panels of the closure device **1400b**. As described above and herein, one or more additional skirts may be incorporated onto the closure device **3400** to provide additional strain or tension relief.

[0200] Various lateral tie assemblies may be provided for the closure devices described herein. These lateral tie assemblies may allow the base panels of the closure devices to be reversibly and adjustably coupled to one another, that is, the intra-panel spacing can be adjusted. Many of these lateral tie assemblies may be low profile so that the closure device can be very thin and low profile as well.

[0201] Belt-buckle lock and strap. Referring now to FIGS. 35A-35D, an exemplary lateral tie assembly of a closure device **3500** may comprise one or more belt-buckle locks and straps.

[0202] One or more straps **3501** may be affixed to one strip of a flexible, tissue adhering member **3502** and locks or buckles **3503** may be affixed to a second flexible, tissue-adhering member. The straps may pass across the top surface of the buckles, which may have one or more protrusions or pawls **3504** to engage, one or more slots or features on the strap.

[0203] In the current embodiment, engagement between the pawl protruding from the buckle and the strap may be maintained, by the incorporation of two slots positioned on either side of the pawl and through which the straps pass. The slots can prevent the strap from passively lifting off of the pawl by restricting the displacement of the straps with respect to the pawl. Other embodiments may

prevent the lifting of straps by creating a downward pressure or force on the straps. This may be accomplished by stretching and adhering a flexible or elastic film over the top surface of the pawl-strap assembly in such a manner as to allow the strap to freely slide underneath the film and the pawl to deflect.

[0204] The pawl may be flexible so that it can deflect out of the way as the strap slides in one direction then returns to its original position to engage a feature on the strap preventing the strap from slide in the opposite direction.

[0205] The surface **3505** into which the slots are cut can be flared in the direction of the pawls as a way to reduce drag on the strap and reduce the amount of force required to advance the straps.

[0206] The force required to reverse motion of the strap or fail the locking mechanism may be increased by altering the stiffness of the pawl either through material changes, design changes to improve the pawl's resistance to buckling, or by adding additional pawls in series for simultaneous engagement with multiple features on the strap.

[0207] Resolution of the advancement stops can be altered by changing the size and spacing between engagement features on the strap or adding one or more pawls in series with a spacing that differs from the distance between engagement features on the strap such that only one pawl is engaged at a time.

[0208] Both straps and locks can be manufactured as two-dimensional structures (i.e. die-cut from sheets of material, molded as thin patterns) which can generally reduce the profile of the part.

[0209] The system may be releasable or reversible by actively lifting the strap off of the pawl (disengaging the pawl) (as indicated by lifted pawl **3506**) and sliding the strap in the reverse direction.

[0210] The bending stiffness of the straps may be altered by increasing the thickness of the strap or by adding curvature to the strap along the length of the strap (as indicated by curved strap **3507**).

[0211] Another embodiment may have the lock broken into different parts, which can make the closure device more amenable to volume/low-cost manufacturing processes (e.g. die-cut parts assembled in a conversion process) by placing components down in layers: In a step 1, the buckle may be bonded (at location **3528**) to first tissue-adhering member. In a step 2, the strap may be bonded at a location **3529** to second tissue-adhering member such that the tail of the strap is positioned over the buckles. In a step 3, the strap restraints may be bonded at a location **3530** to the first tissue adhering member on either side of the buckle such that they are positioned on top of the strap but bonded to the tissue adhering member on either side of the strap.

[0212] Pinch lock. Referring now to FIGS. **36A-36H**, an exemplary lateral tie assembly of a closure device **3600** may comprise one or more pinch locks.

[0213] A lock may be created by placing a hole **3608** in one or more surfaces through which a strap is passed. The shape of the holes can be such that they have an edge upon, which protrusions or ridges on the strap will catch, preventing the strap from sliding when a non-preferred alignment is established between the strap and the surface containing the holes.

[0214] A “normally locked” state can be established by adapting the locks and holes in such a way that the default position of the locks **3609** can create a non-preferred alignment between the strap and the surfaces) with the holes.

[0215] Protrusions on the strap may be conical, wedge-shaped, or have a preferred orientation to facilitate sliding of the strap through the holes in a preferred direction, but catch on the edges of the holes when attempting to slide in the opposite direction.

[0216] In one of the current embodiments, the locks form a V shape with the opening of the lock pointing toward the incision. The locks may be bonded to one of the tissue-adhering strips along one side of the lock **3611** with the opposing tails **3612** of the locks not bonded or are free floating. The non-bonded tails may also be linked together (with an elongate section **3613**) to improve grip and ease releasing the lock.

[0217] The lock may be releasable by actively establishing a preferred alignment between the strap



and the holes **3610** and preventing the protrusions or ridges on the strap from catching on the edge of the holes. In the current embodiments, this is accomplished by pinching the lock.

[0218] In another embodiment, the locks form a block, U shape with the opening of the lock pointing away from the incision **3614**. These locks may be bonded to one of the tissue-adhering strips between the two arms of the lock **3615**. The lock may be releasable by pinching the two arms.

[0219] Saw Tooth Lock. Referring now to FIGS. **37A-37D**, an exemplary lateral tie assembly of a closure device may comprise one or more saw-tooth locks.

[0220] A strap may be constructed from a two-dimensional, saw-toothed pattern **3716**. The strap may interface with opposing pawls or followers **3717** on the lock. The shape of the teeth and followers is such that they can slide past each other in a preferred direction but interfere and lock with movement in the opposing direction.

[0221] In order for the teeth to slip past the follower, either the teeth or the followers or both may flex or deflect allowing the opposing teeth to slide past. Deflection may be accomplished by utilizing flexible materials or by removing material from behind the teeth or followers such that voids will allow the features to deflect as the strap is advanced.

[0222] Engagement/planer-alignment between the teeth and followers can be maintained by sandwiching the strap **3718** and lock between two constraining surfaces **3719**. The bottom constraining surface may be the tissue adhering strip as opposed to a separate layer of material.

[0223] Teeth can be limited to a single side of the strap to reduce the number of sharp points **3721**.

[0224] Resolution between each advancement stop may be improved by increasing the density of teeth along the length of the strap, by including multiple followers placed in series within the lock, each with a spacing that differs compared to the spacing between teeth of the strap, or by offsetting the teeth on either side of the strap such that only one side of the strap engages a tooth on the lock at any given stop.

[0225] Releasing the strap from lock may be accomplished by raising the strap above the level of the locking followers. Space above the locks may be created by using a flexible material as the top constraint or only partially attaching the top constraint **3720**.

[0226] Lifting the strap to release the lock may be facilitated through the use of a tool and sliding it between the strap and the bottom constraint.

[0227] Fish-scale strap and lock. Referring now to FIGS. **38A-38D**, an exemplary lateral tie assembly of a closure device may comprise one or more fish-scale straps and locks.

[0228] A strap may be formed or cut from a film or generally planer piece of material and fixed to a flexible, tissue-adhering member. A series of flaps/pawls/fish scales **3822** may be formed in such that they sit higher than the planer surface of the strap **3823**. The pawls may have a preferred orientation such that when a lock **3824** slides across the surface of the strap in the preferred direction, the pawls will deflect down and allow the lock to slide; however, when the lock slides across the surface of the strap in the non preferred direction the pawls will catch an edge or other feature on the lock and prevent the lock from sliding any further in that direction.

[0229] In one embodiment, the lock is an edge of a second film or generally planer piece **3825** of material which is fixed to a second flexible tissue-adhering member and lies across the top of the strap.

[0230] Releasing the lock and allowing the strap to slide in the non-preferred direction can be accomplished by lifting the edge of the lock higher than the pawl **3826** allowing the strap to slide.

[0231] While preferred embodiments of the present invention have been shown and described herein, it will be obvious to those skilled in the art that such embodiments are provided by way of example only. Numerous variations, changes, and substitutions will now occur to those skilled in the art without departing from the invention. It should be understood that various alternatives to the embodiments of the invention described herein may be employed in practicing the invention. It is

intended that the following claims define the scope of the invention and that methods and structures within the scope of these claims and their equivalents be covered thereby.

## Claims

1. An incision closure apparatus comprising: a first base panel configured to be adhered to a first side of an incision or wound, wherein the first base panel comprises: a first upper surface, a first lower surface, and a first adhesive on the first lower surface; a second base panel configured to be adhered to a second side of the incision or wound opposite the first side, wherein the second base panel comprises: a second upper surface, a second lower surface, and a second adhesive on the second lower surface; a first axial spine coupled to the first upper surface of the first base panel; a second axial spine coupled to the second upper surface of the second base panel; and a plurality of lateral ties coupling the first base panel to the second base panel, wherein each lateral tie of the plurality of lateral ties has (i) a first end permanently fixed relative to and integrally formed with one of the first axial spine or the second axial spine, and (ii) a second end reversibly and adjustably attached to another of the first axial spine or the second axial spine such that the plurality of lateral ties are configured to reversibly adjust a lateral spacing between the first base panel and the second base panel while adhered on opposing sides of the wound or incision.
2. The incision closure apparatus of claim 1, wherein the first axial spine is disposed axially adjacent to a first lateral edge of the first base panel, and the second axial spine is disposed axially adjacent to a second lateral edge of the second base panel.
3. The incision closure apparatus of claim 2, wherein the first axial spine comprises two lateral support portions coupled to axial ends of the first axial spine, and the second axial spine comprises two lateral support portions coupled to axial ends of the second axial spine, wherein the two lateral support portions of the first axial spine extend in a direction toward the first lateral edge, and wherein the two lateral support portions of the second axial spine extend in a direction toward the second lateral edge.
4. The incision closure apparatus of claim 1, wherein the first axial spine and the second axial spine are formed from a flexible, non-distensible material.
5. The incision closure apparatus of claim 1, wherein the first axial spine and the second axial spine are configured as force distribution structures that are configured to assist in drawing the first base panel and the second base panel towards each other responsive to adjustment of the plurality of lateral ties.
6. The incision closure apparatus of claim 1, wherein the second end of each lateral tie is configured to couple to the other of the another of the first axial spine or the second axial spine by a ratchet tightening mechanism.
7. The incision closure apparatus of claim 1, wherein the first base panel and the second base panel each comprise an elastic matrix.
8. The incision closure apparatus of claim 7, wherein the elastic matrix comprises an elastomeric membrane, a woven fabric, a spun fabric, rubber, latex, urethane, polyurethane, silicone, or a thermo plastic elastomer (TPE).
9. The incision closure apparatus of claim 8, wherein the elastic matrix comprises a fabric woven from elastic elements.
10. The incision closure apparatus of claim 1, wherein the first adhesive of the first base panel and the second adhesive of the second base panel each comprises a hydrophilic adhesive material.
11. The incision closure apparatus of claim 10, wherein the hydrophilic adhesive material comprises one or more of a hydrocolloid, a hydrogel, an acrylic polymer, or poly (ethylene glycol).
12. A method of forming a wound or incision closure apparatus, comprising: forming a first base panel comprising a first upper surface and a first lower surface, wherein the first lower surface comprises an adhesive; forming a second base panel comprising a second upper surface and a

second lower surface, wherein the second lower surface comprises an adhesive; coupling a first axial spine to the first upper surface of the first base panel; coupling a second axial spine to the second upper surface of the second base panel; and forming a plurality of lateral ties coupling the first base panel and the second base panel to each other, wherein each lateral tie of the plurality of lateral ties has (i) a first end permanently fixed relative to and integrally formed with one of the first axial spine or the second axial spine, and (ii) a second end reversibly and adjustably attached to another of the first axial spine or the second axial spine such that the plurality of lateral ties are configured to reversibly adjust a lateral spacing between the first base panel and the second base panel while adhered on opposing sides of the wound or incision.

**13.** The method claim 12, wherein coupling a first axial spine to the first upper surface of the first base panel comprises coupling the first axial spine axially adjacent to a first lateral edge of the first base panel, and coupling a second axial spine to the second upper surface of the second base panel comprises coupling the second axial spine axially adjacent to a second lateral edge of the second base panel.

**14.** The method of claim 13, wherein the first axial spine comprises two lateral support portions coupled to axial ends of the first axial spine, and the second axial spine comprises two lateral support portions coupled to axial ends of the second axial spine, wherein the two lateral support portions of the first axial spine extend in a direction toward the first lateral edge, and wherein the two lateral support portions of the second axial spine extend in a direction toward the second lateral edge.

**15.** The method of claim 12, further comprising forming the first axial spine and the second axial spine from a flexible, non-distensible material.

**16.** The method of claim 12, wherein the second end of each lateral tie is configured to couple to the other of the another of the first axial spine or the second axial spine by a ratchet tightening mechanism.

**17.** The method of claim 12, wherein the first base panel and the second base panel are each formed from an elastic matrix.

**18.** The method of claim 17, wherein the elastic matrix comprises an elastomeric membrane, a woven fabric, a spun fabric, rubber, latex, urethane, polyurethane, silicone, or a thermo plastic elastomer (TPE).

**19.** The method of claim 18, wherein the elastic matrix comprises a fabric woven from elastic elements.

**20.** The method of claim 12, wherein the adhesive of the first base panel and the adhesive of the second base panel each comprises one or more of a hydrophilic adhesive material, a hydrocolloid, a hydrogel, an acrylic polymer, or poly (ethylene glycol).

---