

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12391480
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Kalouche; Simon

---

### Robotic order fulfilment system

---

#### Abstract

A robotic order fulfilment system for picking inventory. The system includes a piece picking robot configured to pick inventory from a plurality of containers arranged on shelving. The robot includes a base moveable relative to the shelving in a horizontal direction, a vertical post extending from the base, a platform linearly moveable along the vertical post, a suction system arranged to secure and move a select one of the containers from the shelving to expose an open top of the select one of the containers, and a picking arm configured to pick an item from the select one of the containers after the open top has been exposed. An order fulfilment method using the piece picking robot is also provided.

---

<b>Inventors:</b>	<b>Kalouche; Simon (San Francisco, CA)</b>
<b>Applicant:</b>	<b>Nimble Robotics, Inc. (San Francisco, CA)</b>
<b>Family ID:</b>	<b>1000008767345</b>
<b>Assignee:</b>	<b>Nimble Robotics, Inc. (San Francisco, CA)</b>
<b>Appl. No.:</b>	<b>18/389068</b>
<b>Filed:</b>	<b>November 13, 2023</b>

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20240092582 A1	Mar. 21, 2024

#### Related U.S. Application Data

continuation parent-doc US 17708223 20220330 US 11834271 child-doc US 18389068  
continuation parent-doc US 17343894 20210610 US 12258216 child-doc US 17708223  
us-provisional-application US 63037741 20200611

---

## Publication Classification

**Int. Cl.:** **B25J9/02** (20060101); **B25J15/00** (20060101); **B60P1/36** (20060101); **B60P1/43** (20060101); **B60P3/00** (20060101); **B60W60/00** (20200101); **B65G1/137** (20060101); **B65G67/24** (20060101)

**U.S. Cl.:**

**CPC** **B65G1/1376** (20130101); **B25J9/026** (20130101); **B60P3/007** (20130101); **B65G67/24** (20130101); **B25J15/00** (20130101); **B60P1/36** (20130101); **B60P1/43** (20130101); **B60W60/00256** (20200201)

## Field of Classification Search

**CPC:** B65G (1/1376); B65G (67/24); B25J (9/026); B25J (15/00); B25J (9/162); B25J (5/02); B25J (15/0683); B60P (3/007); B60P (1/36); B60P (1/43); B60W (60/00256)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6059092	12/1999	Jerue	198/364	B65G 1/1373
8632294	12/2013	Subotincic	414/737	B65B 5/08
9256852	12/2015	Myllymaki	N/A	N/A
9272845	12/2015	Honkanen et al.	N/A	N/A
9520012	12/2015	Stiernagle	N/A	N/A
9796080	12/2016	Lindbo et al.	N/A	N/A
9868596	12/2017	Worsley et al.	N/A	N/A
10273085	12/2018	Battles et al.	N/A	N/A
10327583	12/2018	Hiatt	N/A	A47J 44/00
10729281	12/2019	Knuepfel	N/A	A47J 31/521
10875057	12/2019	Wagner et al.	N/A	N/A
10890921	12/2020	Gillett	N/A	N/A
11136153	12/2020	Langen	N/A	B65B 61/26
11332311	12/2021	Fosnight	N/A	B65G 1/02
11390049	12/2021	Langen	N/A	B31B 50/262
11474531	12/2021	Reiserer	N/A	G05D 1/0291
11834271	12/2022	Kalouche	N/A	B60P 3/007
2006/0133917	12/2005	Clark	414/729	B25J 15/0052
2008/0267759	12/2007	Morency	414/788.1	B65G 60/00
2011/0238207	12/2010	Bastian, II et al.	N/A	N/A
2015/0069001	12/2014	French et al.	N/A	N/A
2015/0274420	12/2014	Krommer	414/807	B65G 49/067
2016/0247212	12/2015	Shimmerlik et al.	N/A	N/A
2016/0349350	12/2015	Borders et al.	N/A	N/A
2017/0225601	12/2016	Borders et al.	N/A	N/A
2017/0290345	12/2016	Garden et al.	N/A	N/A
2018/0086575	12/2017	McCarthy et al.	N/A	N/A

2018/0099415	12/2017	McCollum et al.	N/A	N/A
2018/0154399	12/2017	Wagner et al.	N/A	N/A
2018/0265296	12/2017	Beckman et al.	N/A	N/A
2018/0290845	12/2017	McMurrough et al.	N/A	N/A
2018/0349872	12/2017	Ahmed et al.	N/A	N/A
2018/0362270	12/2017	Clucas et al.	N/A	N/A
2019/0034857	12/2018	Ferguson et al.	N/A	N/A
2019/0050798	12/2018	Goldberg et al.	N/A	N/A
2019/0050952	12/2018	Goldberg et al.	N/A	N/A
2019/0161190	12/2018	Gil et al.	N/A	N/A
2020/0017317	12/2019	Yap et al.	N/A	N/A
2020/0062505	12/2019	Chirnomas	N/A	N/A
2020/0150674	12/2019	Ferguson et al.	N/A	N/A
2020/0209865	12/2019	Jarvis et al.	N/A	N/A
2020/0354171	12/2019	Vincent	N/A	N/A
2020/0377317	12/2019	Zoghzoghy et al.	N/A	N/A
2021/0032034	12/2020	Kalouche	N/A	N/A
2021/0132625	12/2020	Gillett	N/A	N/A
2021/0179364	12/2020	Zhang et al.	N/A	N/A
2021/0261337	12/2020	Schedlbauer et al.	N/A	N/A
2021/0283783	12/2020	Gillett	N/A	N/A
2021/0316945	12/2020	Lui	N/A	N/A
2021/0387808	12/2020	Kalouche	N/A	N/A
2022/0129831	12/2021	Gil	N/A	N/A
2022/0129832	12/2021	Gil	N/A	N/A
2022/0129833	12/2021	Gil	N/A	N/A
2022/0306403	12/2021	Iacaruso	N/A	B65G 47/917
2023/0050724	12/2022	Iacaruso	N/A	B65G 49/067
2024/0174464	12/2023	Moser et al.	N/A	N/A

## FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
107415795	12/2016	CN	N/A
2256703	12/2009	EP	N/A
3115319	12/2016	EP	N/A
3845474	12/2020	EP	N/A
2551909	12/2017	GB	N/A
2568768	12/2018	GB	N/A
2019232505	12/2018	WO	N/A
2020057571	12/2019	WO	N/A

## OTHER PUBLICATIONS

International Search Report for Appln. No. PCT/US2021/036800 dated Oct. 20, 2021. (3 pages). cited by applicant

International Preliminary Report on Patentability for International Application No. PCT/US2021/036800, mailed Dec. 22, 2022, 7 Pages. cited by applicant

*Primary Examiner:* Rodriguez; Saul

*Assistant Examiner:* Romano; Ashley K

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 17/708,223, filed Mar. 30, 2022, which is a continuation of U.S. application Ser. No. 17/343,894, filed Jun. 10, 2021, which claims the benefit of the filing date of U.S. Provisional Patent Application No. 63/037,741 filed Jun. 11, 2020, all of which are hereby incorporated herein by reference.

### BACKGROUND OF THE DISCLOSURE

- (1) The present disclosure relates to delivery vehicles and, more particularly, to delivery vehicles equipped with robotic systems for picking, packing, and fulfilling orders while traversing a delivery route.
- (2) Consumers generally find purchasing items online more convenient than purchasing items from brick-and-mortar stores. Using the internet, consumers can browse a greater selection of inventory, quickly compare the prices of similar items from one or more merchants, analyze reviews from previous consumers and order items directly to their doorstep without having to leave the comfort of their home.
- (3) Not all sectors of consumer goods, however, have seamlessly expanded to include convenient delivery options. For example, grocery and convenience stores have only recently began to take a small market share from their brick-and-mortar counterparts. It was previously surmised that consumers prefer to see and touch their groceries, particularly produce, meat, dairy, and bakery goods, to ensure item quality before purchase. Nevertheless, as delivery options for groceries and convenience items have become more readily available, it has become apparent that a large subset of the population appreciates the convenience of delivered groceries. This is especially true in cities and other densely populated areas where consumers often do not have access to personal vehicles that can easily transport groceries from the supermarket to their homes.
- (4) Despite the increased availability of grocery delivery services, these services are not without shortcomings. For example, grocery delivery services often include relatively expensive subscription costs and also require a minimum order before “free delivery” is provided, thus leaving consumers with no choice but to order several days-worth of groceries or pay an expensive delivery fee on top of their subscription. Moreover, delivery times often need to be reserved one or more days in advance, thereby making it difficult and expensive to impulsively buy and quickly receive only a few items. Furthermore, while some grocery delivery services allow consumers to modify and/or add to a pending order immediately after placing the order, once the order has been processed, further modifications are not permitted. In this respect, if a consumer wishes to modify and/or add one or more items after the purchase has been processed, the consumer is left with limited choices: pick-up the item from a brick-and-mortar store, pay another delivery fee and wait for the additional item, or forgo the additional item all together.

### BRIEF SUMMARY OF THE INVENTION

- (5) In accordance with a first aspect of the present disclosure, an automated delivery vehicle is provided. Among other advantages, the automated delivery vehicle is equipped with a robotic system for fulfilling orders using inventory stored within the delivery vehicle. In this regard, new orders can be processed and fulfilled while the delivery vehicle traverses a delivery route. As a result, the orders can be delivered to customers more quickly and cost effectively than traditional grocery and convenience delivery services that fulfill orders in a warehouse and then subsequently transport and deliver the orders to customers in two distinct steps. In addition, orders can be modified much later in the order fulfillment process compared to the conventional delivery

services. The automated delivery vehicle described herein can thus capitalize on profits from additional orders and/or add on items without meaningfully increasing delivery costs.

(6) In one embodiment, an order fulfillment and delivery system includes a vehicle having a storage area, a robotic system disposed at least partially within the storage area, and one or more processors. The processors are configured to receive an order of one or more inventory items, generate container retrieval or pick instructions for the robotic system to perform based on the received order and transmit to the robotic system the container retrieval instructions to perform. The robotic system includes an extendable container retrieval device to engage and move a container from a first location within the delivery vehicle to a second location within the delivery vehicle.

(7) In another embodiment, a method of fulfilling and delivering orders includes: receiving, by one or more processors, an order comprising one or more items; generating, by the one or more processors, instructions for a robotic system disposed at least partially within a storage area of a delivery vehicle, the robotic system including a container retrieval device; providing, by the one or more processors, the instructions to the robotic system; extending the container retrieval device to engage a first container; moving the engaged container from a storage location within the delivery vehicle to a picking area located within the delivery vehicle; and picking an item from the first container and placing the picked item within a second container.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) Various embodiments of the present disclosure are described herein with reference to the drawings, wherein:

(2) FIG. 1 is a block diagram of an order fulfillment system including an automated delivery vehicle provided with a robotic system having a piece-picking robot according to an embodiment of the present disclosure;

(3) FIG. 2A is a schematic cutaway view of an example automated delivery vehicle including a robotic system with a gantry according to an embodiment of the present disclosure;

(4) FIG. 2B is a perspective view of the delivery vehicle of FIG. 2A;

(5) FIG. 2C is a plan view of a storage bed of the delivery vehicle of FIG. 2A provided with an example storage structure for arranging containers.

(6) FIG. 3 is a schematic view of a gripper plate designed to be suspended from the gantry of FIG. 2A according to an embodiment of the present disclosure;

(7) FIGS. 4A and 4B are schematic views of a gripper plate including a retractable manipulator designed to be suspended from the gantry of FIG. 2A according to another embodiment of the present disclosure;

(8) FIG. 5 is a schematic view of a gripper plate including a plurality of suction cups designed to be suspended from the gantry of FIG. 2A according to yet another embodiment of the present disclosure;

(9) FIG. 6 is a cross-section view illustrating the coupling between a gripping tool and a picking arm of the piece-picking robot of FIG. 1;

(10) FIG. 7 is a perspective view of a tool holder for storing a plurality of gripping tools interchangeably coupleable to a picking arm of the piece-picking robot of FIG. 1;

(11) FIG. 8 is a perspective view illustrating a method loading containers into a delivery vehicle using an example gantry according to an embodiment of the present disclosure;

(12) FIG. 9 is a flowchart illustrating an example order placement process;

(13) FIG. 10 is a flowchart illustrating an example order delivery process; and

(14) FIG. 11 is a partial perspective view of an example automated delivery vehicle according to

another embodiment of the present disclosure.

## DETAILED DESCRIPTION

(15) The technology disclosed herein relates to an automated fulfillment and delivery vehicle. The vehicle includes a robotic system designed to fulfill new orders, modify earlier placed orders and stage completed orders while en route to a delivery location. As a result, the time from order placement to order delivery can be drastically reduced. While the orders discussed herein are primarily described as groceries and/or other items traditionally purchased at a supermarket or convenience store, the terms “inventory,” “item,” and the like, are intended to encompass any type of product purchasable at a traditional brick-and-mortar store, restaurant, or online. Also as used herein, the terms “substantially,” “generally,” “approximately” and “about” are intended to mean that slight deviations from absolute are included within the scope of the term so modified.

(16) FIG. 1 is a block diagram of an example order fulfillment and delivery system **10** according to an embodiment of the present disclosure. System **10** includes an automated delivery vehicle **12** equipped with a robotic system such as robotic system **14** (FIG. 2A), or robotic system **16** (FIG. 11), to fulfill orders as the delivery vehicle traverses a delivery route. While delivery vehicle **12** is described herein as a delivery truck, it will be understood that the term “vehicle” is inclusive of any motor vehicle such as trucks, sports utility vehicles (SUV), step vans, buses, or commercial motor vehicles such as eighteen-wheelers; watercraft including boats, ferries, and ships; and aircraft including but not limited to drones, blimps, planes and helicopters. Order fulfillment and delivery system **10** further includes one or more processors **18** associated with robotic systems **14**, **16**, one or more remote processors **20**, data store **22**, memory **24**, one or more network devices **26** and optionally one or more consumer devices **30**.

(17) Processor **18** and remote processor **20** may be a commercially available central processing unit (“CPU”), a System on a Chip (“SOC”), an application specific integrated circuit (“ASIC”), a microprocessor, microcontroller, or other such hardware-based processor. In some instances, system **10** may include multiple processor types. Although FIG. 1 illustrates a single delivery vehicle **12**, it will be appreciated that the system can include more than one delivery vehicle, each of which are in communication with one or more remote processors **20**. As used herein, the term “remote processor” refers to a processor in communication with and located remote from the robotic systems within delivery vehicle **12** and may include one or more processors or a single central processor for coordinating and automating fulfillment tasks between multiple delivery vehicles. When the term “processor” is used herein, the term refers to either a processor of robotic system **14**, robotic system **16**, remote processor **20**, another processor, or a combination of the foregoing, unless explicitly indicated otherwise.

(18) Memory, such as memory **24**, may be configured to read, write, and store data. Memory **24** may be any solid state or other such non-transitory type memory device. For example, memory **24** may include one or more of a hard-drive, a solid state hard drive, NAND memory, flash memory, ROM, EEPROM, RAM, DVD, CD-ROM, write-capable, and read-only memories, or any other device capable of storing data. Data may be retrieved, manipulated, and/or stored by processor **18** or remote processor **20** in memory **24**.

(19) The network device, such as network device **26**, is configured to communicatively couple the components of robotic system **14** and/or the components of robotic system **16** to other components of the robotic systems and to other devices or systems, such as data store **22** and consumer device **30**. In this regard, network device **26** may enable processor **18** and processor **20** to communicate and receive data, such as inventory and order information, and signal other computing devices or data store **22**. The network device **26** may include a network interface card (NIC), Wi-Fi card, Bluetooth receiver/transmitter, or other such device capable of communicating data over a network via one or more communication protocols, such as point-to-point communication (e.g., direct communication between two devices), Ethernet, Wi-Fi, HTTP, Bluetooth, LTE, 3G, 4G, 5G, Edge, etc., and various combinations of the foregoing. Consumer device **30** may be a computer, tablet,

smartphone, smartwatch or the like which a consumer may use to purchase one or more inventory items over network **26**.

(20) Referring to FIG. 2A, delivery vehicle **12** may be a delivery truck in the form of a step van and thus is sometimes be referred to herein as a “delivery truck” or simply a “truck.” Delivery truck **12** includes a cab **32**, a storage area **34** in which a plurality of stackable containers **36** may be stored and a staging area **33** in which fulfilled orders are placed prior to delivery. In some embodiments, a driver may sit within cab **32** while driving truck **12** along its delivery route. The driver and/or another passenger riding within cab **32** may assist the robotic systems in performing any automated order fulfillment task including, for example, picking items from retrieved storage containers and placing those items in order containers, delivering order containers from the truck to designated drop zones at a delivery location and retrieving empty containers from pickup locations and placing the empty containers into the truck. In other embodiments, delivery truck **12** is autonomously operable and designed to drive itself along a delivery route as is generally known in the art. Delivery truck **12** may be equipped with Light Detection and Ranging (LIDAR), visual sensors, cameras, or other mapping sensors that capture environmental data to map out the environment and localize the vehicle along the delivery routes to improve the truck's self-driving capabilities. When delivery truck **12** is autonomously operable, cab **32** is not necessary.

(21) As shown in FIG. 2A, containers **36** may be arranged within the storage area **34** of delivery truck **12** in a plurality of rows extending in a direction along the length of the truck (e.g., the y-direction), a plurality of rows extending in a direction along the width of the truck (e.g., the x-direction) and in vertical stacks extending from the storage bed toward the roof of the truck (e.g., the z-direction) such that little to no gap exists between adjacent rows of containers. This storage configuration maximizes storage density and also inhibits lateral movement of containers **36** as the truck traverses a delivery route. It will be appreciated that the containers may be arranged in any number of rows and any number of levels (e.g., the number of containers in each stack).

(22) Delivery truck **12** may be stocked with containers **36** of orderable items (e.g., items that have not yet been assigned to a particular customer) and/or containers of pre-picked orders. The term “container” encompasses bins, totes, cartons, boxes, bags, and any other vessel capable of storing inventory items. To distinguish between containers holding orderable items and containers designated for a particular customer (e.g., containers holding pre-picked orders or containers holding items picked in transit), the term “storage container” will be used to identify containers housing orderable items and the term “order container” will be used to identify containers designated for a particular customer. Containers **36** may be configured to hold inventory items of a single product type or of a variety of product types and in certain instances may be subdivided into isolated sections using sub-divider walls. In some embodiments, containers **36** may be of uniform size to one another. In other embodiments, containers **36** may be of varying sizes and configured to hold particular product items.

(23) In situations where the inventory items are groceries that require refrigeration, containers **36** may be provided with a section configured to hold dry ice, ice packs, or other disposable or decomposable refrigeration devices thereby alleviating the need for truck **12** to have a separate refrigeration unit. Alternatively, storage area **34** may include temperature regulators that control the temperature of one or more isolated refrigeration or freezer areas. One or more insulated walls or barriers may be used to isolate and insulate the zones and maintain the desired temperature or climate within the zones. Each refrigeration or freezer area may rely on cryogenic cooling to achieve a desired temperature, or may alternatively utilize a separate refrigeration system formed, for example, of a condenser, a compressor and an evaporator configured to cycle gas through the system to refrigerate and/or freeze the insulated area. The groceries may be arranged within storage area **34** in the refrigerated area, the frozen area or at ambient temperature based upon the storage requirements of that particular item. In some instances, grocery products may be naturally slotted closer to or further from the frozen and refrigerated area based upon the items temperature and

storage climate requirements. In situations where the inventory items include food that requires preparation, the cab **32** or the storage area **34** of delivery truck **12** may include one or more convection ovens, microwaves, toasters, convection pans, stoves, coffee machines, or any other type of food preparation machine typically found in a commercial kitchen. The foregoing machines may thus be utilized by an operator, robotic system **14** or robotic system **16** to prepare one or more meals for a customer by mixing ingredients or preparing pre-made meal kits.

(24) With reference to FIG. **2B**, delivery truck **12** may include a port **35** (e.g., a “hand picking area”) through which items can be presented to curbside customers. While port **35** is shown as a pivotable door, the term “port,” as used herein, means any mechanism through which items can be presented to a customer located outside of truck **12** and may include a slidable door, an extendable tray or merely a hole. In this regard, if a customer prefers to hand-select a grocery item such as produce, meat, dairy, or a bakery good, the items may be retrieved by robotic system **14** or robotic system **16** (as requested by the customer through consumer device **30** or through a separate interface **28** on truck **12**) and presented to the customer who may then hand-select one or more of the items from a container **36**. Put differently, truck **12** may serve as a mobile store provided with a robotic system that retrieves products for the consumer to hand-select and purchase. A camera **37**, or scanner, may be placed adjacent to port **35** to detect and verify the items and quantity of items taken by the customer so that the customer's account can be debited accordingly. Alternatively, a scale or weighing sensor (not shown) may be embedded within port **35** to detect and verify items removed from the port. An exterior of delivery truck **12** and/or ramp **41** may optionally include an additional alignment cameras **39**, or sensor, to assist the driver (or self-driving program) in aligning the ramp with a designated drop zone at a delivery location in order to deliver the order container or to assist in aligning the ramp with a designated pickup location in order to retrieve an empty container.

(25) Referring back to FIG. **2A**, each container **36** preferably has an open or openable top through which inventory items can be deposited or retrieved. The bottom of containers **36** may include bomb bay doors or a wall that is slidable, pivotable, or otherwise actuatable from a closed position to an open position to dispense the inventory items into other containers, such as order containers, or elsewhere. In some embodiments, storage containers **36** may include a camera that transmits images to consumer device **30** thereby allowing the customer operating the device to select specific inventory items contained within the storage container. Order containers, on the other hand, may be sealed or have a lockable door (not shown) that is openable only by the intended consumer, for example, by entering a code, a manual lock (combination lock, pad lock, etc.), or confirming a wireless communication etc. The storage containers and the order containers may be foldable or otherwise collapsible to facilitate storage and improve transportability of the containers between uses.

(26) Robotic system **14** includes a gantry **38**, a retrieval robot **40** moveable about the gantry, a pick and place robot **42** and/or one or more delivery devices such as a delivery ramp **41**, delivery robot **44** or drone **47**. Gantry **38** includes a pair of opposing beams **46** extending in a first direction (e.g., the length direction of delivery truck **12**) and a cross-connector **48** extending between the beams (in a direction perpendicular to the first direction) upon which retrieval robot **40** is movably mounted. The cross-connector **48** may include rollers, linear bearings and guides, linear actuators, lead or ball screws, belts or chain transmissions and actuators, or similar mechanisms, configured to controllably slide the cross-connector to a desired location along beams **46** upon executing a processor executable signal. Beams **46** may thus act as a track along which cross-connector **48** can slide, in the length direction of the truck, while the cross-connector acts as a track along which retrieval robot **40** can slide, in the width direction of the truck, to allow robotic system **14** to move containers **36** in three dimensions about the interior of the truck and complete various order fulfillment tasks. In some embodiments, containers **36** may include a position sensor capable of sending data to processor **18** to track the location of the containers as the containers are moved



about the interior of truck **12**. Alternatively, processor **18** can systematically log and track where each container is moved thereby removing the need to have sensors within each container **36**.

(27) Retrieval robot **40** includes a body **50** moveably mounted on cross-connector **48** and a lifting device **52**. The body **50** of retrieval robot **40** may include rollers, linear bearings and guides, linear actuators, lead or ball screws, belts or chain transmissions and actuators, or another mechanism, that allows the body of the retrieval robot to slide along the cross-connector upon executing a processor executable signal. In this regard, body **50** can be moved quickly about gantry **38** to position lifting device **52** in two dimensions above any one of the stacks of containers **36**.

(28) The lifting device **52**, as shown in more detail in FIG. **3**, includes a gripper plate **54** suspended from the body **50** of retrieval robot **40** by cables **56** which are connected to a winding mechanism **53** such as a spool, hoist, or winch housed within or otherwise coupled to the body of the retrieval robot. Cables **56** can be wound and unwound, or spooled into and out from, the body **50** of retrieval robot **40** to move gripper plate **54** in the z-direction. An encoder **55** may be coupled to winding mechanism **53** to measure the distance gripper plate **54** moves in the z-direction. Winding mechanism **53** may also include a torque sensor (not shown) to measures the weight of a container **36** supported by gripper plate **54**. Alternatively, load cells **57**, force sensors, strain gauges, contact switches or other sensors may be positioned between the body **50** of the retrieval robot **40** and gripper plate **54** to detect the weight of a payload. In this regard, autonomous inventory audits can be performed during order fulfillment tasks allowing processor **18** to determine the number of product items that have been removed from a container **36** to ascertain, for example, the number of items purchased by a customer or to determine when inventory within the containers are running low and need to be replenished.

(29) Gripper plate **54** may include hooks **59** that are slidable, extendable, or otherwise moveable, relative to the plate such that the hooks may be slid into engagement with a container **36** or, more specifically, into a cavity, underneath a rib, or against another feature (“the engagement feature”) formed within the top surface forming the rim and/or sidewalls of the container. Hooks **59** may be driven by a suitable drive mechanism housed within gripper plate **54**, which may be powered and controlled by signals carried through cables **56**, through a separate control cable (not shown), or wirelessly. Thus, when gripper plate **54** is lowered into engagement with the rim of a container **36**, or to a position around the sidewall of the container, hooks **59** may be transitioned to engage the engagement feature of the container, thereby securely gripping the container and allowing retrieval robot **40** to move the container about the interior of delivery truck **12**. Gripper plate **54** may also include a sensor **63**, such as a camera, depth imager, contact switch, contact sensor, inductive sensor, capacitive sensor, IR sensor or similar device, to assist in aligning the gripper plate to the engagement feature of container **36**. Sensor **63** can utilize markers such as AR tags or barcodes provided on containers **36**, or other features of the container itself, to facilitate proper alignment. In addition to facilitating alignment, sensor **63** can capture images of inventory stored inside of the storage containers. The images may then be transmitted via network device **26** to user device **30** to allow a consumer to manually select specific groceries based upon actual images of the inventory items.

(30) If retrieval robot **40** is tasked with retrieving a container (“target container”) that is not located on the top of a particular stack of containers, then the overlying container **36a** (“non-target containers”) must first be moved to allow the retrieval robot access to target container **36b**. The act of retrieving a target container **36b** from underneath one or more non-target container **36b** is referred to herein as “digging.”

(31) To perform a digging operation, retrieval robot **40** must first lift each of the overlying non-target containers **36a** from the stack of containers in which the target container **36b** is stored. Each of the non-target containers **36a** may be lifted, transported, lowered and placed in a temporary location in which no containers are located, or on the top of another stack of containers. After each of the non-target containers **36a** have been removed from the stack and relocated, target container

**36b** can be extracted by retrieval robot **40** and transported to another location, for example, another storage location or a picking area. After target container **36b** has been extracted, non-target containers **36a** may be placed back in the original stack to restore the original order of the stack less the target container. As mentioned above, each individual container may be tracked and logged, so that the appropriate containers can be transported by retrieval robot **40** about the interior (or exterior) of delivery truck **12** as needed. In one embodiment, vehicle **12** may additionally include a conveyor **61** (FIG. 1), or carousel, to assist in transporting, queuing, staging, or buffering containers **36** between storage area **34**, the picking area, staging area **33** and a loading/unloading area.

(32) In a preferred embodiment, gripper plate **54** may be detachably coupleable to the body **50** of retrieval robot **40** such that the gripper plate may be autonomously swapped (upon receiving control instructions from processor **18**) with a different gripper plate such as gripper plate **65** (FIGS. 4A and 4B) or gripper plate **67** (FIG. 5). As shown in FIG. 5, gripper plate **67** includes an array of suction cups **69** which may be utilized to move containers **36**, including without limitation, bins, boxes or cartons. On the other hand, gripper plate **65** may include all of the features of gripper plate **54** and additionally include a manipulator **71** having at least three degrees of freedom relative to the gripper plate and a gripping tool, such as a suction cup, attached to the manipulator. As shown in FIG. 4A, manipulator **71** may be extended to freely position the suction cup within a target container **36b** to grasp and pick individual items from the target container (so long as there is not a non-target container **36a** positioned on top of the target container). After the items have been picked, manipulator **71** may be retracted, as shown in FIG. 4B (e.g., upwards in the z-direction), to increase the clearance between gripper plate **65** and containers **36** as the gripping plate is moved about the interior of truck **12**.

(33) Referring back to FIG. 2A, one or more pick and place robots **42** may be positioned within a picking area of vehicle **12** and tasked with picking individual items from the storage containers and depositing the picked items into order containers. Pick and place robot **42** may operate in one of two modes: an autonomous mode, by executing autonomous control instructions, or a teleoperated mode, in which the control instructions are manually piloted (e.g., directly controlled) by a teleoperator located within vehicle **12** or by a teleoperator located outside the vehicle.

(34) Pick and place robot **42** includes a base **58**, a picking arm **60** coupleable to a gripping tool **62** for picking and packing items and one or more vision devices **64**. The one or more vision devices **64** may be directly connected to the base **58**, the picking arm **60**, the gripping tool **62** or located in the environment surrounding the robot in a manner in which the vision devices are oriented to capture pictures, point clouds, video etc. (generally referred to herein as “an image” or “images”) of the items stored within containers **36**. The image(s) may be transmitted to processor **18** or processor **20** (and in some instances may additionally be relayed to operator interface **66** (shown in FIG. 1). In this manner, the processor may implicitly or explicitly analyze the images and then execute a machine learning algorithm, or a grasping or motion algorithm, located for example within data store **22**, to predict a grasping pose (e.g., position and/or orientation and/or posture of the robotic picking arm). The predicted grasping pose may then be transmitted as control instructions to pick and place robot **42** which, when executed by the pick and place robot, causes the gripping tool **62** to approach and attempt to grasp the item. Successfully grasping an item can require a set of consecutively run poses. Nevertheless, as used herein, the term “grasping pose” may refer to a single pose or a set of consecutively run poses. If the control instructions were unsuccessful in grasping the item, the processor can request intervention from the teleoperator, allowing pick and place robot **42** to be teleoperatively controlled. Although operator interface **66** is primarily described herein in connection with assisting pick and place robot **42** in performing a failed pick and place task, it will be appreciated that the operator interface may be used by the teleoperator at any time (including prior to a failed attempt) to allow a teleoperator to manually control or otherwise assist the robot in performing any manipulation task including picking,

packing, nudging, relocating or rearranging inventory items within a container **36** or any other order fulfillment task. For this reason, the term control instructions may also include instructions for moving items within a single container, instructions for moving items from one container to another container or instructions for packing an item in a particular location or in a specific orientation within a container to assist in densely packing the items.

(35) Operator interfaces **66** includes one or more input devices to capture control instructions from the teleoperator and one or more output devices. Operator interface **66** may be, for example, a personal computer, a tablet, (smart) phone, or a wearable computer. Exemplary input devices include keyboards, mice, touch screen displays, displays (e.g., LCD or OLED screen), controllers, joysticks and the like. Exemplary output devices include, without limitation, displays (e.g., LCD or OLED screen), head mounted displays, speakers, and/or haptic feedback controllers (e.g., vibration element, piezo-electric actuator, rumble, kinesthetic, rumble motor). Operator interface **66** may thus be utilized by the teleoperator to observe robotic picking and assist the pick and place robot **42** in grasping items during edge case scenarios or to assist with any other order fulfillment task including, without limitation, item manipulation tasks, vehicle driving assistance tasks (e.g., assisting truck **12** along a delivery route) or guiding any of the delivery devices and/or ramps to a drop location.

(36) The gripping tool **62** may be any electrically or pneumatically actuated tool such as a suction cup designed to grasp inventory items. When gripping tool **62** is a suction cup, pick and place robot **42** includes a pneumatic source such as a vacuum source or a compressor (not shown) in fluid communication with the gripping tool. If the pneumatic source is a compressor, a Venturi pump (not shown), or similar device capable of using the compressed air to produce a vacuum or suction force, may be used to generate a suction force for operating the suction cup. There is not a single gripping tool that can optimally handle a large variety of inventory. For this reason, gripping tool **62** may be removably coupleable to picking arm **60** such that pick and place robot **42** may autonomously decide, or be instructed by the teleoperator, to switch between a plurality of different gripping tools. Alternatively, pick and place robot **42** may include a plurality of picking arms each of which are equipped with one or more gripping tools **62** and/or the gripping tool may include a plurality of gripping elements (e.g., distinct elements on a single tool that are individually actuatable and designed to individually grasp an item, or act in concert with one another to grasp the item, such as an array of suction cups and/or actuatable grasping fingers).

(37) Referring to FIG. **6**, picking arm **60** includes a magnet **68**, such as a ring magnet or another magnet arrangement, to magnetically couple gripping tool **62** to the picking arm. As shown in FIG. **6**, gripping tool **62** may be in the form of suction cup and include a sidewall **70** with bellows **72** formed of a resilient material such as rubber and a groove **74** positioned above the bellows. The sidewall **70** of gripping tool **62** is thus configured to compress when the suction cup engages an object. The suction cup may further include a lip **76** formed from a resilient material, which also may be a rubber, such that the lip of the gripping tool is adapted to deform and create a seal with the surface of an item in which it engages. A magnet **78** may be provided on gripping tool **62** to attract the magnet **68** of picking arm **60** and to magnetically couple the gripping tool to the picking arm. In some embodiments, gripping tool **62** may have an additional groove (not shown) that cooperates with a protrusion (not shown) on picking arm **60** to prevent rotational and axial movement of the gripping tool relative to the picking arm when the gripping tool is coupled to the picking arm. In other embodiments, gripping tool **62** may be coupled to picking arm **60** via another mechanical connection such as a push/pull connection or a twist-locked connection.

(38) A tool holder **80**, as shown in FIG. **7**, may be attached to pick and place robot **42** or otherwise provided within the picking area of delivery truck **12** near pick and place robot **42**. Tool holder **80** may have a plurality of retainers **82a**, **82b** (collectively “retainers **82**”) such as arcuate or rectangular cutouts for receiving the groove **74** of gripping tool **62**. Tool holder **80** may alternatively define a cup-like holding area in which gripping tool **62** can be housed when not

coupled to the picking arm of pick and place robot **42**. In this manner, a plurality of different gripping tools **62** can be selectively and interchangeably coupled to the picking arm **60** of pick and place robot **42** based upon the size, shape, material or weight of the product in which the pick and place robot is tasked with grasping. Upon receiving control instructions from processor **18**, or operator interface **66**, piece picking robot **42** may swap a first gripping tool for a second gripping tool having a different size, material, shape or configuration. To swap gripping tools, picking arm **60** may slide the groove of a first gripping tool attached to the picking arm into the retainer **82a** of tool holder **80** before retracting the picking arm to decouple the magnet **68** of the picking arm from the magnet **78** of the first gripping tool. The picking arm **60** of pick and place robot **42** may then be positioned over a second gripping tool, positioned within the retainer **82b** of tool holder **80**, to magnetically couple the picking arm to the second gripping tool. With the second gripping tool coupled to picking arm **60**, the picking arm may be moved laterally to slide the second gripping tool out of retainer **82b**. Each gripping tool **62** (or picking arm **60**) may include a sensor to detect if the gripping tool has been properly connected to the picking arm **60** and/or whether an inventory item has been successfully grasped.

(39) One or more scanners **83** (shown in FIG. **1**) may optionally be attached to pick and place robot **42** or otherwise provided within the picking area of delivery truck **12**. Scanner **83** may be communicatively coupled to processor **18** via network device **26** and adapted to scan a barcode, RFID, SKU, or ID on the packaging of an inventory item, or perform an image analysis on the product type, to verify the identity of the item. Thus, after an item has been grasped and before the item has been placed into an order container, scanner **83** can scan the barcode, RFID, SKU, or LOT number and transmit this information to the processor which, in turn, can verify the identity of the item and direct pick and place robot **42** to dispense the item into an appropriate order container pertaining to a particular customer. In one embodiment, an auto-bagging, auto-boxing, or container wrapping, closing or sealing machine may also be provided within the vehicle **12** such that pick and place robot **42** can pick items directly from a container **36** and quickly bag or box the picked items into completed order containers.

(40) Referring back to FIGS. **2A** and **2B**, robotic system **14** further includes one or more delivery devices such as ramp **41**, delivery robot(s) **44** or drone(s) **47**. With specific reference to FIG. **2B**, ramp **41** may include a conveyor belt **45** designed to deliver an order container to a designated curbside drop zone such as the driveway of a customer without the assistance of delivery robot **44** or drone **47**. Ramp **41** may further include arms **43** for engaging with and retrieving empty containers from a pickup location. In an exemplary embodiment, arms **43** may be coupled to opposite sides of ramp **41** such that the arms are extendable away from the ramp **41** of delivery truck **12** and pivotable outwardly to surround an empty container and then subsequently pivotable inwardly to engage and secure the container between the pair of arms before the container is pulled onto the conveyor belt **45** of the ramp.

(41) Delivery robots **44** and drones **47** are designed to transport fulfilled order containers from delivery truck **12** to a drop area at a designated delivery location and, in some instances, retrieve empty containers from a pickup location. Delivery robot **44** may be an autonomous ground vehicle (AGV) that includes a propulsion system **84** and a payload carriage **86** for securing one or more containers **36**. In a non-limiting example, propulsion system **84** may include wheels, legs, or be a wheel/leg hybrid with multiple degrees of freedom configured to move payload carriage **86** and, in turn, a container secured to the payload carriage, down the ramp **41** of delivery truck **12** to the designated drop zone such as a doorstep of a customer's residence. Similarly, drones **47** may include a payload carriage for securing one or more order containers as the drone flies through the air from delivery vehicle **12** to a drop location and for storing empty containers after the drone has retrieved the container from a pick-up location. It will be appreciated that delivery robots **44** and drones **47** allow the order containers to be delivered to and/or retrieved from locations that are not directly accessible to delivery truck **12**, for example, the doorstep of a residence or a storage locker

or mailbox set back from the roadway.

(42) In the event that the drop location is a storage locker, the storage locker may include a lock for securely storing the order containers until the authorized customer retrieves his or her order. In certain aspects, the storage locker may have insulated and climate controlled sections to store items at an appropriate temperature prior to being retrieved by the customer (i.e., the locker may have a refrigerated section, a freezer section and an atmospheric temperature section, or may simply be well insulated). In dense urban areas containing large multi-unit complexes, a common storage locker may house several individual lockers or cubbies.

(43) In an optional embodiment, containers **36** may be arranged within a storage structure or a grid-based storage structure (not shown) provided within the storage area **34** of vehicle **12**. The storage structure may be similar to the storage structure disclosed in U.S. Pat. Pub. No. 2021/0032034 which is incorporated herein by reference in its entirety.

(44) In a first aspect, the storage structure may include a frame formed entirely of vertical members **31** (shown in FIG. 2C). The vertical members **31** may be disposed between adjacent stacks of containers to prevent the containers from shifting as delivery truck **12** traverses a delivery route. In a second aspect, the storage structure may be formed of the vertical members **31** and additionally include first horizontal members (not shown) extending in a first direction (e.g., in the length direction of the truck) and second horizontal members (not shown) extending in a second direction (e.g., in the width direction of the truck) substantially orthogonal to the first direction. The first and second set of horizontal members may be secured to the vertical members in a plurality of rows to collectively form spaces in which a respective stack of containers **36** may be arranged. The spaces are arranged to reduce, if not eliminate, lateral movement of the containers as the vehicle traverses a delivery route.

(45) A grid may optionally be disposed above either of the earlier mentioned framed storage structures. The grid includes a first set of parallel rails extending in the length direction of the truck and a second set of parallel rails extending in the width direction of the truck to form a plurality of grid spaces. Each stack of containers **36** is designed to sit underneath and completely within the footprint of a single grid space. The first and second set of parallel rails collectively define a profiled track upon which a robotic vehicle may be disposed. The robotic vehicle may include a wheel assembly configured to engage the tracks of the first and second set of rails to selectively move the vehicle above any one of the stacks of containers and a gripper plate, similar to any of the gripper plates disclosed herein, configured to retrieve a target containers **36** as described above with respect to retrieval robot **40**.

(46) The vertical members and/or the horizontal members of the storage structure may be sized and arranged to be slightly larger than the gripper plates described herein. In this manner, as the gripper plate is lowered in the z-direction toward a container **36**, and within the frame, the vertical and/or horizontal members will prevent the gripper plate from swaying laterally (in x-y directions) and will guide the gripper plate towards the container. Similarly, after the container has been secured, the members of the storage structure will prevent the container from swinging back-and-forth and discharging its contents or colliding with other stacks of containers due to the motion of delivery truck **12** (e.g., turning, braking, accelerating or hitting a pothole, etc.).

(47) A method of fulfilling and delivering orders using order fulfillment and delivery system **10** and robotic system **14** will now be described. The desired items, for example, groceries may be packaged into order containers and/or storage containers and loaded within the storage area **34** of vehicle **12** at a warehouse or other order fulfillment center. The containers **36** may either be loaded into the truck by a warehouse worker or with assistance of gantry **38**, a gantry **38'** (shown in FIG. 8), and/or other devices. Gantry **38'** may be constructed and operate similarly to gantry **38** with the exception that gantry **38'** is not secured within delivery truck **12**. Instead, gantry **38'** may be provided at any loading/unloading dock and may be on rollers or another mechanism which allows the gantry to be slid into and out from the truck to assist with loading and/or unloading containers

**36** from the truck in a more efficient manner than can be performed by a warehouse worker.

(48) When containers **36** are loaded into a truck by a warehouse worker, the containers may be walked into the storage area **34** and placed adjacent to cab **32** in one or more stacks before other containers are placed behind the earlier placed containers (e.g., toward the rear of delivery truck **12**). This process makes stacking containers **36** in orderly stacks more difficult. In contrast, when containers **36** are loaded by gantry **38**, the containers may be loaded in levels. In other words, containers **36** may be loaded in one or more rows (along the length of the vehicle) and one or more rows (along the width of the vehicle) before the containers are stacked on top of one another. Loading containers **36** into the storage area **34** of delivery truck **12** in this manner builds a stronger foundation for subsequently loaded containers to be stacked on top of the earlier loaded containers and eases and expedites the stacking process. The foundation building process is made possible by gantry **38** which can pass over one or more rows of boxes to grab another container located in a rear of the truck or located outside of the truck, for example, on a conveyor (as shown in FIG. **8**) or within a staging area. It will be appreciated that a warehouse worker who walks along the storage bed of the truck cannot load delivery truck **12** in this manner without stepping on or jumping over the earlier loaded containers or without the assistance of gantry **38**.

(49) Other efficient loading methods may alternatively be utilized. For example, containers **36** may be stored within the warehouse on top of a pallet or pod in a series of levels (with little to no space in between adjacent rows of containers). When delivery truck **12** arrives at the warehouse, a fork-lift or other lifting machine can lift and place the entire pallet, including containers **36**, into the storage area of the delivery truck for quick replenishment.

(50) It will be appreciated that the storage density of containers **36** may be increased by loading the containers into the storage area **34** of delivery truck **12** with little to no space between adjacent containers. Containers **36** may also be stacked in levels to a height just below retrieval robot **40** or to a height of the lifting device **52** of the retrieval robot. If containers **36** are stacked to the height of retrieval robot **40** (for the purpose of storing more containers) it will be appreciated that the retrieval robot will not be able to freely move a container that it is holding along the full area of the gantry but must rather navigate itself and, in turn the container it is holding, through available spaces on the top layer that are not occupied by other containers. So long as the top level is not completely filled with containers, the retrieval robot can engage a container that it is tasked with retrieving and slide that container between adjacent containers of the top level (e.g., within empty spaces not filled by containers in the top level).

(51) To facilitate efficient delivery, pre-picked or otherwise pre-consolidated order containers may be loaded into vehicle **12**, with the assistance of gantry **38**, based upon a predetermined delivery schedule. For example, the order containers may be loaded into storage **34**, or staging area **33** located adjacent to any one of the delivery devices described herein (e.g., ramp **41**, delivery robot **44** or drone **47**), based upon the pre-scheduled order of delivery stops. In other words, an order container that is scheduled to be dropped off at the first delivery location may be loaded directly into staging area **33** whereas containers that will be delivered to the last delivery location may be loaded furthest from the staging area. Alternatively, the storage containers and the order containers may be loaded in any other manner, including one that is fastest, and sorted while truck **12** is in transit. For example, the order containers may be grouped within the storage area **34** of vehicle **12** based upon the scheduled delivery order. In this regard, gantry **38** and/or conveyor **61** can continuously and easily move a group of containers scheduled to be delivered within the next few delivery stops to staging area **33** before the delivery truck reaches those stops, thereby allowing the driver and/or any of the delivery devices described herein to quickly collect the containers that it needs to deliver from the staging location instead of sifting through all of the containers within storage area **34** at each delivery location.

(52) In one embodiment, the storage area **34** of delivery truck **12** may be loaded with pre-picked order containers as well as storage containers holding items that may be in high demand for a

particular route. For example, if delivery truck **12** is scheduled for a 5 am-8 am route in the summer time, then the truck may include one or more storage containers of iced coffees. In contrast, if delivery truck **12** is scheduled for a 6-9 pm route, then the truck may include, for example, one or more storage containers of ice cream. Still yet, delivery truck **12** may be loaded with non-grocery items, such as new-release products (books, shoes, clothes, electronics, smartphones, etc.), or mail, scheduled to be delivered along the truck's delivery route. Historical and geographical sales data may be analyzed periodically to selectively stock truck **12** with the most in demand inventory for a truck operating on that particular time and day and driving along that particular delivery route.

(53) As delivery truck **12** departs the warehouse, each of the customers that placed an order, as well as previous customers within a predetermined distance of the delivery route, may receive a notification to their consumer device **30** informing the consumers as to the schedule of the delivery truck. By logging onto the delivery service provider's website and/or mobile application, the consumers may view the location of delivery truck **12**, as well the orderable inventory on that truck and, other nearby trucks, in real-time. The consumer may then select and purchase one or more desired items and the order will be transmitted to processor **20** which, in turn, will appropriately assign the order to a respective delivery truck **12**. For example, if the consumer already purchased a pre-picked order on a particular vehicle **12**, processor **20** will assign the new order to that vehicle if it contains the desired item. On the other hand, if the consumer does not have a pre-picked order en route, processor **20** can assign the order to one or more delivery trucks that are presently around the consumers desired delivery location.

(54) While delivery truck **12** is described herein as traversing pre-planned delivery routes, the truck may make deviations therefrom when instructed from processor **20** to deliver orders placed after the pre-planned delivery route was established. In other instances, vehicles **12** may be stationary or patrol certain areas based on instructions from processor **20** and past order history. Each delivery truck **12** is thus designed to deliver "scheduled orders" (orders scheduled prior to the delivery truck leaving the warehouse) and "on-demand orders" (an order that is at least partially placed and fulfilled when the delivery truck is en-route to a delivery location) which may include the supplementation of one or more items to a scheduled order.

(55) FIG. **9** is a flow chart **100** illustrating the steps of an example order placement process in further detail. A consumer may place an order, such as a grocery order, on consumer device **30** by accessing the website and/or mobile application (hereinafter "app") of the delivery provider. As shown in block **102**, the consumer may visualize, on a map displayed on consumer device **30**, the locations of nearby delivery trucks **12** relative to the desired delivery location which may be, for example, the home of the consumer or the consumer's current location.

(56) Using an algorithm that accounts for the then current locations of the trucks, pending orders not yet fulfilled and scheduled delivery routes of the nearby delivery trucks, the app will automatically identify the delivery truck capable of providing the quickest delivery to the consumer. The consumer may then browse the orderable inventory on the identified delivery truck. Alternatively, the consumer can browse for a desired item in a product catalogue containing the orderable inventory across the fleet of deployed delivery trucks. Upon selecting one or more item types and desired quantities thereof from the product catalogue, using the input device of consumer device **30**, the desired items and quantity thereof will be displayed in the apps virtual order basket as shown at block **104**.

(57) The app's algorithm may then identify the delivery truck capable of most quickly and efficiently delivering the order to the consumer. Before the order is transmitted to that particular delivery truck, the app may transmit a prompt to the user, at block **106**, inquiring whether the user wants to "manually-select" or "hand-select" one or more of the items or if the user prefers a "generic item" in which case an item of the type selected will be chosen at random. In the event that the consumer desires to manually-select one or more items, such as a banana, images of the actual bananas available on the identified delivery truck will be output and displayed on consumer

device **30**. The consumer may then scroll through the images and “manually-select” one or more bananas. In some aspects, as shown in block **108**, the app may include one or more filters that may be optionally and selectively applied to the images and that act as a visual aid in determining various properties of the banana such as ripeness, size etc. In the event that the consumer is not satisfied with any of the bananas available on the identified delivery truck, the consumer may skip to the next nearest delivery truck and scroll through the images of bananas available on that truck. At block **110**, the consumer may select the image corresponding to a specific item such as a banana. This process can be repeated, as necessary, until a truck(s) is identified that can most quickly and efficiently deliver the order. The consumer may then confirm and place the order, as shown in block **112**, and visualize a representation of the delivery truck carrying the consumers order on a map as the delivery truck travels to the delivery location. In some instance, the app may also provide updates, for example, via messages on the app or external SMS messages pertaining to the order fulfillment status.

(58) When an on-demand order has been received by delivery truck **12**, retrieval robot **40** may retrieve one or more containers **36** as described hereinafter. For example, if the consumer modified an earlier order (e.g., exchanged, removed and/or added an item to an existing pre-picked order), the gantry can retrieve the order container as well as the storage container(s) holding the desired additional items and transport the containers to the picking area for further processing. On the other hand, if the consumer is placing a new order (e.g., the consumer does not have a pre-picked order on delivery truck **12**), gantry **38** may retrieve one or more storage containers and transport the containers to the picking area for further processing.

(59) To remove a target container **36b** from the top of a stack, retrieval robot **40** is moved as necessary in the x and y directions so that gripper plate **54**, or another appropriate gripper plate, is positioned above the stack in which the desired container is located. Specifically, the cross-connector **48** of gantry **38** may be driven along the beams **46** of the gantry to position retrieval robot **40** over a particular row of containers in which the target container is located. Retrieval robot **40** may then be driven along the cross-connector to align gripper plate **54** to the target container in the x-direction. Gripper plate **54** may then be lowered in the z-direction and brought into engagement with container **36b**. Hooks **59** may then be driven by the driving mechanism into engagement with the target container **36b** to secure gripper plate **54** to the container. Gripper plate **54** and the container may then be pulled upwards by spooling cables **56**. At the peak of its vertical travel, container **36b** may be accommodated directly beneath the body **50** of retrieval robot **40** and above the other stacks of containers. In this way, retrieval robot **40** can transport container **36b** to one or more picking areas within the truck (e.g., internal picking areas) or to delivery port **35** (e.g., an external picking area). If, on the other hand, target container **36b** needs to be removed from a stack of containers when the target container is located beneath non-target containers **36a**, retrieval robot **40** is first aligned in the x and y directions with target container **36b** as previously described, before the above described “digging operation” is performed to relocate each of the non-target containers and extract the target container. Target container **36b** may then be transported to the picking area by gantry **38** or with the assistance of conveyor **61**.

(60) Once the storage containers are within one of the picking areas, the customer, driver, passenger, or pick and place robot **42** may pick one or more desired items from the storage container. Pick and place robot **42** picks an item as follows. First, vision device **64** may scan the inventory items located in the retrieved container and the image may be sent to processor **18** or processor **20** for further processing to determine viable grasping and manipulation motions. For example, processor **18** or processor **20** may then implement a policy, which utilizes one or more metrics, checks and filters to select one or more predicted grasping pose candidates for pick and place robot **42** to execute sequentially or to add to its queue. Then, the processor generates a signal including processor readable information that represents the selected grasping pose and sends the signal to the picking arm **60** of pick and place **42**. After pick and place robot **42** receives the



selected grasping pose signal, the robot executes the signal, causing the picking arm **60** to perform the selected grasping pose. That is, gripping tool **62** approaches the product item, as instructed by the processor and contacts the inventory item.

(61) After the grasping attempt, a sensor of pick and place robot **42**, or the processor, may characterize the grasp as either successful or unsuccessful. If the attempt resulted in a successful grasp such that the item was removed from target container **36b** and deposited into the order container, the sensor may characterize the pick and place as successful and transmit a successful pick and place signal to the processor via network device **26**. On the other hand, if gripping tool **62** was unable to remove the item from the container, or the gripping tool drops the item before the processor instructs the pick and place robot to release the item in the order container, the sensor will characterize the grasp as unsuccessful and transmit an unsuccessful grasp signal to the processor via network device **26**. Upon characterizing the grasp as unsuccessful, the processor can either: (1) immediately signal to teleoperator interface **66** and request intervention; or (2) attempt to determine a new grasping pose to autonomously pick up the item based upon a new or modified grasping pose. If the processor elects to autonomously determine a new grasping pose, the steps described above may be repeated until either the grasp is characterized as successful or until intervention is requested. On the other hand, if intervention is requested, a teleoperator may send control instructions to pick and place robot **42** to assist the pick and place robot in grasping and/or packing the product item into the order container, or the teleoperator may send a signal to the driver or passenger located within the cab **32** of delivery truck **12** and request that the driver, passenger, or customer assist in picking and/or packing the product. The control instructions may include any of: 1) determining a location of the item to grasp; 2) determining a grasping pose; 3) selecting the gripping tool to grasp the inventory item; 4) determining the packing pose of the item; 5) repositioning/nudging an item; or 6) performing any manipulation task.

(62) Once the order container has been filled with each ordered item (but for any items to be hand-selected), retrieval robot **40** may move the completed order container to staging area **33** (which may be a subset of the picking area, the storage area, or another location adjacent to an exit of the vehicle such as ramp **41**) or to a reserved portion of storage area **34** to conserve space in the staging area for more immediate deliveries. If retrieval robot **40** moves a fulfilled order to the reserved portion of storage area **34**, the robot may subsequently stage orders (e.g., move the completed order containers from the reserved area of storage area **34** to staging area **33**) prior to the delivery truck **12** reaching the delivery location. Thus, when delivery truck **12** arrives at the delivery location, the delivery devices (e.g., ramp **41**, delivery robot **33**, operator, or drone **47**) may quickly deliver containers **36**. For example, upon arriving at a delivery location, ramp **41** may be lowered and aligned with a drop zone. An image feed from alignment camera **39** may assist the self-driving program, the driver or teleoperator in correctly aligning the ramp to the drop zone and lowering the ramp to the correct angle based on the height of the drop zone. If ramp **41** is initially misaligned, truck **12** may be driven to correctly align the ramp. In this regard, order containers **36** may be quickly placed on the conveyor belt **45** of the ramp which can be actuated to deliver the container to a curbside delivery location. Alternatively, one of the autonomous delivery robots **44** or drones **47**, gantry **38** can grab the order container from staging area **33** and transport the container to a designated drop spot such as the door step of the consumer. If multiple consumers in a single neighborhood placed orders, a plurality of autonomous delivery devices may be used to simultaneously deliver/retrieve orders to increase efficiency. The delivery devices may also retrieve empty containers (that were previously delivered to customers in that particular neighborhood) while delivering containers of new orders.

(63) In the event that a customer prefers to “hand-select” one or more items, the customer may prompt the app to send a delivery truck **12** to the customer's location. Using consumer device **30** or interface **28**, the customer can select one or more items to hand-select. In response to the selection, robotic system **14** or robotic system **16**, will retrieve a container housing the selected items, as

described above, and transport the retrieved container to the port (e.g., picking location) through which the inventory items can be presented. The customer may pick the desired quantity of items from the container and, when finished, prompt the system to return the container to a location within delivery truck **12**. If necessary, robotic system **14** or robotic system **16** can continue to present containers (of the same item type or of a different item type) until the customer has hand-selected all of the desired items. The camera **37** or other detection device may automatically detect the items and the quantity of the items taken by the customer so that the customer's account can be debited accordingly. Truck **12** may thus serve as a mobile store provided with a robotic system that retrieves products for the consumer to hand-select and purchase.

(64) FIG. **10** is a flow chart **200** illustrating the steps of an example process of delivering one or more orders to a multi-unit storage locker. The process begins, at block **202**, when delivery truck **12** arrives at the delivery location with the order(s) staged in the staging area **33** of the truck. At block **204**, the fulfilled order container may be transported directly to one or more entry points of the storage locker using any of the delivery devices described herein such as ramp **41**, delivery robot **44**, drone **47**, or another delivery device associated with the truck such as gantry **38**. Alternatively, the storage locker may have a retrieval device such as a conveyor, a mobile robot, or a gantry system for retrieving order containers from truck **12** without assistance from ramp **41**, delivery robot **44**, drone **47**, the gantry **38** or another delivery devices associated with the truck. A worker or an Automated Storage and Retrieval System (ASRS), such as a single or multi-axis shuttle, may then transfer each of the order containers, at block **206**, from the entry point of the multi-unit storage locker into an individual lockers or cubbies which may then be locked or otherwise secured to prevent unauthorized entry. At block **208**, the consumers may receive an SMS message, email, or the like ("Notification"), informing them that their order was delivered. Alternatively, the notification may be sent earlier in the process to inform the customer about the expected delivery time. The Notification may also include a personalized key code which can be used to open the lock placed on the customer's individual locker or cubby. Using the personalized code provided in the Notification, the customer may access their individual storage locker and retrieve the container containing their order, at block **210**, before returning the empty container, at block **212**, either to their individual storage locker or a central drop-off location within the multi-unit storage locker.

(65) FIG. **11** illustrates an alternative embodiment of delivery truck **12** that includes robotic system **16** instead of robotic system **14**. Robotic system **16** includes all of the features of robotic system **14** but replaces gantry **38** and retrieval robot **40** with a multi-axis shuttle **88**. For this reason, containers **36** may be housed on shelving **90** provided on the lateral walls of the storage area **34** of delivery truck **12**. To increase storage density, containers **36** may be arranged in multiple rows on a single shelf (e.g., in a width direction of the truck) as shown in FIG. **11**.

(66) Shuttle **88** includes a track **92** extending along the storage bed (or the ceiling) of vehicle **12** (in the y direction), a base **94** that is slidable along the track, a vertical post **96**, a platform **98** that is slidable along the post (in the z direction) and a pair of opposing arms **99**. Shuttle **88** is also communicatively coupled to processor **18** and/or processor **20** via network **26** and thus is able to be autonomously controlled by the processor.

(67) The base **94** of shuttle device **88** may additionally include one or more rollers and actuators to assist the base in sliding along track **92**. Post **96** is attached to the base **94** of shuttle **88** and may be oriented in a substantially vertical direction away from the base. Platform **98** is coupled to post **96** along a track or via another mechanism, for example, a system of one or more rollers, linear bearings and guides, linear actuators, lead or ball screws, belts or chain transmissions and actuators (not shown), or similar mechanisms, configured to controllably move the platform along the post in a vertical direction. Put another way, platform **98** can be moved to any location along the length of truck **12** by moving the base **94** along the track **92** and the platform can be moved to any location along the height of the truck by adjusting the height of the platform along post **96**.

(68) The arms **99** may be utilized to engage a container **36** located on either side of shuttle **88** and to pull the container onto an upper surface of platform **98**. For example, the pair of arms **99** may be coupled to opposite sides of platform **98** such that the arms are extendable away from the platform (in the x-direction) toward shelving **90** and pivotable outwardly to surround a target container and then subsequently pivotable inwardly to engage and secure the container between the pair of arms. Alternatively, arms **99** may include a suction system **169**, hooks or another mechanism for securing the top or sides of containers **36** and pulling the container onto platform. To displace a container **36** (or an item) provided on the platform **98** of the platform **98** of shuttle **88** back onto shelving **90** (or a container stored on the shelving), the platform may optionally include a push tray **97**, a cross-belt, or another similar mechanism capable of dispensing the container from the platform onto the shelving.

(69) In a further embodiment, shuttle **88** may also include a picking arm **160**, similar to picking arm **60**, to pick directly from a target container **36 b** that has been pulled onto platform **98**. In this manner, orders of a single item, or relatively few items, can quickly be fulfilled without having to transport the entire storage container to the picking area. In yet another embodiment (not shown), a track may extend along the front side of each shelf in the y direction of delivery truck **12**. A platform, similar to platform **88**, may be coupled to each one of the tracks such that the platform is configured to slide directly along the shelving to retrieve containers **36**. In this embodiment, each of the platforms are movable only in the y direction and configured to pull/push containers in the x direction. Put differently, the platforms are not movable in the z-direction. Therefore, a platform is preferably coupled to each shelf.

(70) Use of robotic system **16** to fulfill orders will now be described only with reference to retrieving a target container **36** from the storage area **34** of truck **12** and transporting the retrieved container to the picking area of the truck as the rest of the order fulfillment process is the same as the order fulfillment process previously described above with respect to robotic system **14**. After the control instructions have been transmitted to shuttle **88**, the control instruction may be executed, causing the base **94** of shuttle device **88** to slide along track **92** and platform **98** to move along post **96** to position the platform laterally adjacent to a target container **36b** (e.g., in the y and z directions). If target container **36b** is located behind a non-target container **30a**, shuttle **88** may move the non-target containers from one shelf to another shelf (or an open location on the same shelf) in order to access the target container behind the non-target container. The platform **98** may then be returned to a location located laterally adjacent to target container **36b**. Arms **99** may then be pivoted outwardly and extended toward the target container **36b** before the arms are subsequently pivoted inwardly to secure the target container between the arms. The arms **99** of shuttle **88** may then be retracted to position container **36** on platform **98** which may then transport the container to the picking area. With container **36** located in the picking area, arms **99** or push tray **97** may be actuated to release the container at a location adjacent to pick and place robot **42**.

(71) Although delivery vehicle **12** is primarily described herein as a delivery truck, it is again reiterated that the term “vehicle” is inclusive of any apparatus configured to convey a person or item whether by land, water or air. Similarly, while the delivery devices such as ramp **41**, delivery robot **44** or drone **47** are suited to transport order containers from truck **12** across land to a drop zone, the term delivery device is inclusive of any operator, operator controlled robotic system, or autonomous device suitable for delivering the order containers from the delivery vehicle across land, water or through the air and to the delivery location. For example, in embodiments in which delivery vehicle **12** is a blimp provided with robotic system **14**, the delivery device may be gantry **38** itself, which can deliver the order containers to a drop zone located on the ground, by winding and unwinding cables **56** into and out from the body **50** of retrieval robot **40** to move gripper plate **54** in the z-direction, or any other delivery device configured to transport the delivery devices through the air.

(72) The order fulfillment and delivery systems described herein are thus designed to deliver orders

to consumers more quickly and with reduced operating costs compared to traditional delivery systems. Consumer satisfaction may be further increased as orders can be added to or modified much later in the order fulfillment process without additional and costly delivery fees.

(73) Although the invention herein has been described with reference to particular embodiments, it is to be understood that these embodiments are merely illustrative of the principles and applications of the present invention. It is therefore to be understood that numerous modifications may be made to the illustrative embodiments and that other arrangements may be devised without departing from the spirit and scope of the present invention as defined by the appended claims.

## Claims

1. A system, comprising: shelving and a plurality of containers arranged on the shelving, each of the containers having an open top; and a piece picking robot, including: a base moveable relative to the shelving in a horizontal direction; a vertical post extending from the base; a platform linearly moveable along the vertical post; a suction system arranged to secure and move a select one of the containers from the shelving to expose the open top of the select one of the containers; and a picking arm configured to pick an item from the select one of the containers after the open top has been exposed.
2. The system of claim 1, wherein the piece picking robot includes rollers for moving the base in the horizontal direction.
3. The system of claim 1, wherein the suction system is part of an extendable and retractable engagement device.
4. The system of claim 1, wherein a component of the suction system is configured to be secured to a side of the select one of the containers to pull the select one of the containers onto the platform.
5. The system of claim 1, wherein the picking arm includes a suction cup.
6. A piece picking robot, comprising: a base moveable in a horizontal direction; a vertical post extending from the base; a platform linearly moveable along the vertical post; an extendable engagement system arranged to engage a container located on shelving and move the container toward the platform; and a picking arm configured to pick an item from the container after the container has been moved.
7. The piece picking robot of claim 6, wherein the engagement system comprises at least one engagement arm.
8. The piece picking robot of claim 7, wherein the at least one engagement arm comprises a pair of engagement arms.
9. The piece picking robot of claim 6, wherein the engagement system includes a suction system configured to be secured to a side of the container to pull the container towards the platform.
10. The piece picking robot of claim 6, further comprising rollers for moving the base in the horizontal direction.
11. The piece picking robot of claim 6, wherein the platform is slidable along the vertical post.
12. The piece picking robot of claim 6, wherein the picking arm includes a suction cup.
13. A method of operating a piece picking robot including a base, a vertical post extending from the base, a platform, an engagement system, and a picking arm, the method comprising the steps of: moving the base in a horizontal direction; moving the platform linearly along the vertical post in a vertical direction; extending the engagement system; securing the engagement system to a container disposed on shelving; retracting the engagement system and the container away from the shelving to expose an open top of the container; picking an item located within the container using the picking arm; and returning the container to the shelving after the item has been picked.
14. The method of claim 13, wherein the engagement system includes a suction system and the securing step includes securing a component of the suction system to a side of the container.
15. The method of claim 13, wherein the retracting step further comprises retracting the container

onto the platform.

16. The method of claim 13, wherein the picking step includes actuating a suction cup.

17. The method of claim 13, wherein the moving the base step comprises actuating rollers.

18. The method of claim 13, wherein the moving the platform step includes sliding the platform along the vertical post.

---