

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12394034
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Shinnae; Toru

Inspecting print quality of a print product with coordinate information acquired without printing the image data

Abstract

A client computer which has generated a print job related to printing of a print product to be inspected transmits image data and layout information used for generating the print job to an inspection apparatus. The inspection apparatus receives and stores image data and layout information used for generating the print job from the client computer. The image scanned from the print product printed based on the print job and image data used for generating the print job are compared based on the layout information to inspect the print quality of the print product.

Inventors:	Shinnae; Toru (Tokyo, JP)
Applicant:	CANON KABUSHIKI KAISHA (Tokyo, JP)
Family ID:	1000008767899
Assignee:	CANON KABUSHIKI KAISHA (Tokyo, JP)
Appl. No.:	17/885717
Filed:	August 11, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230064686 A1	Mar. 02, 2023

Foreign Application Priority Data

JP	2021-136148	Aug. 24, 2021
----	-------------	---------------

Publication Classification

Int. Cl.: G06T7/00 (20170101); H04N1/00 (20060101)

U.S. Cl.:

CPC **G06T7/0004** (20130101); **H04N1/00005** (20130101); G06T2207/30144 (20130101)

Field of Classification Search

CPC: G06T (7/0004); G06T (2207/30144); G06T (2207/10008); G06T (7/001); H04N (1/00005)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10726556	12/2019	Oki	N/A	N/A
2013/0141767	12/2012	LeCostaouec	358/448	H04N 1/00045
2022/0261975	12/2021	Hershman	N/A	G06F 3/1219

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2004279445	12/2003	JP	N/A
2018179699	12/2017	JP	N/A

Primary Examiner: Wait; Christopher

Attorney, Agent or Firm: ROSSI, KIMMS & McDOWELL LLP

Background/Summary

BACKGROUND OF THE INVENTION

Field of the Invention

(1) The present invention relates to an inspection apparatus, an inspection system, a control method for the inspection apparatus, and a storage medium for inspecting print quality of print product.

Description of the Related Art

(2) There is known an inspection apparatus which reads print product printed by an image forming apparatus and inspects print quality. The inspection apparatus is capable of detecting image defects such as stains and missing prints, character errors, bar code print quality, and the like. The print product in which these defects are detected is separated from the print product without defects by changing the sheet discharge destination, for example.

(3) Print product inspection includes an inspection preparation and an inspection. In the inspection preparation, a reference image is registered in the inspection apparatus by scanning a good print product. In the inspection, an image to be inspected obtained by scanning the print product as an object of inspection is compared with a reference image to detect errors in the print product. In order to perform image comparison, it is necessary to associate the print product with the reference image. In this method, in order to register the reference image, it is necessary to print the print product once and register the print product. In the case of variable printing, since the content to be printed changes each time, it is very troublesome to print, scan, and register as a reference image each time. As a print product inspection in variable printing, there is a prior art in which a character and a region other than the character are extracted from image data and inspected using the image

data (Japanese Patent Application Laid-Open No. 2018-179699).

(4) However, in the method disclosed in Japanese Patent Application Laid-Open No. 2018-179699, it is necessary to perform inspection of the print product after dividing the print product into characters and other regions, which is time-consuming and inefficient.

(5) The present invention has been made to solve the above problems. An object of the present invention is to provide a scheme for efficiently inspecting print product without labor.

SUMMARY OF THE INVENTION

(6) According to an aspect of the present invention, an inspection apparatus inspecting print quality of a print product based on comparing an image scanned from the print product with a reference image comprises a memory and at least one processor in communication with the memory, wherein the at least one processor is configured to receive an image data used for generating a print job and layout information indicating an arrangement of the image data on a sheet from an information processing apparatus generating the print job and perform an inspection of print quality of a print product by comparing, based on the layout information, an image scanned from the print product printed based on the print job with the image data used for generating the print job.

(7) Further features of the present invention will become apparent from the following description of exemplary embodiments with reference to the attached drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 illustrates a schematic diagram of an image forming system (inspection system) in the present embodiment.

(2) FIG. 2 illustrates a block diagram of a control configuration of an image forming apparatus, an inspection apparatus, a large-capacity stacker, an information processing apparatus, and a client computer.

(3) FIG. 3A illustrates an example of print data generated by the client computer.

(4) FIG. 3B illustrates an example of layout information of print data generated by the client computer.

(5) FIG. 4 illustrates an image diagram of a correspondence table between a print job and a reference image for inspection.

(6) FIG. 5 illustrates a flowchart of an example of processing of the client computer.

(7) FIG. 6 illustrates a flowchart of an example of processing of the inspection apparatus according to the first embodiment.

(8) FIG. 7 illustrates an image of a stored inspection result in the first embodiment.

(9) FIG. 8 illustrates a flowchart of an example of processing of the inspection apparatus according to the second embodiment.

(10) FIG. 9 illustrates an image of a stored inspection result in the second embodiment.

DESCRIPTION OF THE EMBODIMENTS

(11) Hereinafter, an embodiment of the present invention will be described with reference to the drawings. It should be noted that the following embodiments do not limit the claimed invention, and not all of the combinations of features described in the embodiments are essential to the means for solving the invention.

First Embodiment

(12) FIG. 1 is a schematic view showing an example of a configuration of an image forming system (inspection system) including an information processing apparatus, an inspection apparatus, and an image forming apparatus according to an embodiment of the present invention. Although the printing apparatus of the present embodiment will be described using an electrophotographic printing apparatus, the printing apparatus of the present embodiment may be a printing apparatus of

a different image forming method such as an inkjet method or an offset method.

(13) An image forming apparatus **101** is communicatively connected to an information processing apparatus **109** via a cable **112**. The information processing apparatus **109** is communicatively connected to a client computer **110** and an inspection apparatus **108** via a network **113**.

(14) The image forming apparatus **101** includes a UI panel **102**, a sheet feed deck **103**, and a sheet feed deck **104**. Further, the image forming apparatus **101** is connected to an option deck **105** consisting of three stages of sheet feed decks. The image forming apparatus **101** is, for example, an electrophotographic image forming apparatus. The UI panel **102** is a user interface having, for example, a capacitive touch panel.

(15) The image forming apparatus **101** further includes an inspection unit **106** and a large-capacity stacker **107**. The inspection unit **106** is communicably connected to the inspection apparatus **108** via a cable **114**. The large-capacity stacker **107** is provided with a main tray and a top tray, and thousands of sheets of paper can be loaded on the main tray at a time.

(16) A print job is generated by the client computer **110**, transmitted to the information processing apparatus **109** via the network **113**, and managed by the information processing apparatus **109**. The print job is transmitted from the information processing apparatus **109** to the image forming apparatus **101** via the cable **112**, and the image forming apparatus **101** performs printing on a sheet. The print job may be generated and managed by the information processing apparatus **109**, transmitted to the image forming apparatus **101** via the cable **112**, and managed by the image forming apparatus **101**.

(17) The client computer **110**, the information processing apparatus **109**, and the inspection apparatus **108** may be connected to the cable **112** to communicate with the image forming apparatus **101**. That is, the connection configuration of the image forming apparatus **101**, the information processing apparatus **109**, and the client computer **110** shown in the present embodiment is an example, and it goes without saying that there are various connection configurations other than those shown in the present embodiment.

(18) The client computer **110** imposes a plurality of image data to obtain an image data for printing. Therefore, the client computer **110** has information about how the image data for printing is laid out. Therefore, in the present embodiment, instead of intentionally extracting a region required for the inspection from the image data as in the prior art, the efficient inspection is performed by inspecting the image data based on layout information included in the image data for printing.

(19) FIG. 2 illustrates a block diagram of an example of a control configuration of the image forming apparatus **101**, the inspection apparatus **108**, the large-capacity stacker **107**, the information processing apparatus **109**, and the client computer **110**. First, the image forming apparatus **101** will be described. A central processing unit (CPU) **201** controls and calculates each section of the image forming apparatus **101** via a system bus **212**. The CPU **201** controls the execution of a program stored in the storage unit **205** and loaded into a RAM (Random Access Memory) **202**.

(20) The RAM **202** is a type of general volatile storage device directly accessible from the CPU **201**, and is used as a work area of the CPU **201** or other temporary data storage area. A storage unit **205** stores control programs and data of the image forming apparatus **101**, and functions as a temporary storage area and a work memory during the operation of the image forming apparatus **101**. The storage unit **205** includes an HDD (Hard Disk Drive), SSD (Solid State Drive), and the like.

(21) An engine I/F **209** controls communication and control with a printer engine **210**. A sheet feed deck I/F **204** controls communication and control with a sheet feed deck **211**. The sheet feed deck **211** is generally referred to as a hard structure of sheet feed decks **103**, **104** and the option deck **105**. A UI panel **203** is a hard structure of the UI panel **102**, and is a user interface for performing general operations of the image forming apparatus **101**. In this embodiment, the UI panel **203** is provided with a capacitive touch panel.

(22) A network interface (NW I/F) **207** is connected to a NW I/F **238** of the information processing apparatus **109** via a cable **213**, and controls communication between the information processing apparatus **109** and the image forming apparatus **101**. In this example, the interfaces connected to the system buses **212** and **239** are directly connected to each other, but the information processing apparatus **109** and the image forming apparatus **101** may be connected by a network, for example, and the connection type is not limited. A video I/F **206** is connected to a video I/F **233** of the information processing apparatus **109** via a video cable **241** and controls communication of image data between the information processing apparatus **109** and the image forming apparatus **101**. The connection interface between the information processing apparatus **109** and the image forming apparatus **101** may be of a form integrating the functions of the NW I/F **238** and the video I/F **233**. The connection interface with the information processing apparatus **109** in the image forming apparatus **101** may be of a form integrating the functions of the NW I/F **207** and the video I/F **206**. In FIG. 1, the cable **213** and the video cable **241** are combined and shown as the cable **112**.

(23) An accessory I/F **208** is connected to an accessory I/F **214** of the inspection unit **106** and an accessory I/F **220** of the large-capacity stacker **107** via a cable **225**. That is, the image forming apparatus **101** communicates with the inspection unit **106** and the large-capacity stacker **107** via the accessory I/Fs **208**, **214**, and **220**.

(24) Next, the inspection unit **106** will be described. A CPU **216** controls and calculates each section of the inspection unit **106** via a system bus **219**, and executes a program stored in a storage unit **247** and loaded into a RAM **217**. The RAM **217** is a type of general volatile storage device directly accessible from the CPU **216**, and is used as a work area of the CPU **216** or other temporary data storage area. The storage unit **247** stores control programs and data of the inspection unit **106**, and functions as a temporary storage area and a work memory during operation of the inspection device. The storage unit **247** includes an HDD, an SSD, or the like.

(25) An inspection apparatus I/F **215** is connected to an inspection unit I/F **231** of the inspection apparatus **108** via the cable **248**. That is, the inspection unit **106** communicates with the inspection apparatus **108** via the inspection apparatus I/F **215** and the inspection unit I/F **231**. The accessory I/F **214** is connected to the accessory I/F **208** of the image forming apparatus **101** via the cable **225**.

(26) A capturing unit **218** has a photographing function equipped with, for example, a conductor image sensor (hereinafter CIS), captures a sheet passing through the inspection unit **106**, and transmits the captured image to the inspection apparatus **108** via the inspection apparatus I/F **215**. The CIS for the capturing unit **218** is an example of a sensor, and may be another type of sensor such as a CCD image sensor, and the imaging method thereof is not limited.

(27) Next, the large-capacity stacker **107** will be described. A CPU **221** controls and calculates each section of the large-capacity stacker **107** via a system bus **224**, and executes a program stored in a storage unit **248** and loaded into a RAM **222**. The RAM **222** is a type of general volatile storage device directly accessible from the CPU **221**, and is used as a work area of the CPU **221** or other temporary data storage area.

(28) The storage unit **248** stores control programs and data of the large-capacity stacker **107**, and functions as a temporary storage area and a work memory during the large-capacity stacker operation. The storage unit **248** includes an HDD, an SSD, or the like. The accessory I/F **220** is connected to the accessory I/F **208** of the image forming apparatus **101** via the cable **225**. The discharge unit **223** controls the sheet discharge operation to the main tray and the top tray, and the monitoring and control of the loading conditions of the main tray and the top tray.

(29) Next, the inspection apparatus **108** will be described. A CPU **226** controls and calculates each section of the inspection apparatus **108** via the system bus **230**, and executes a program stored in a storage unit **228** and loaded into a RAM **227**. The RAM **227** is a type of general volatile storage device directly accessible from the CPU **226**, and is used as a work area of the CPU **226** or other temporary data storage area. The storage unit **228** stores control programs and data, and functions as a temporary storage area and a work memory during operation of the inspection apparatus **108**.

The storage unit **228** includes an HDD, an SSD, or the like.

(30) A PDL analysis unit **229** reads PDL data such as PDF, PostScript, PCL, and the like, received from the client computer **110** or the information processing apparatus **109** and executes interpretation processing. A display unit **245** is, for example, a liquid crystal display connected to the inspection apparatus **108**, and receives user input to the inspection apparatus **108** and displays the state of the inspection apparatus **108**. The inspection unit I/F **231** is connected to an inspection apparatus I/F **215** of the inspection unit **106** via the cable **248**. A NW I/F **232** is connected to the network **113**.

(31) Next, the information processing apparatus **109** will be described. A CPU **234** controls and calculates each section of the information processing apparatus **109** via a system bus **239**, and executes a program stored in a storage unit **236** and loaded into a RAM **235**. The RAM **235** is a type of general volatile storage device directly accessible from the CPU **234**, and is used as a work area of the CPU **234** or other temporary data storage area. The storage unit **236** stores control programs and data of the information processing apparatus **109**, and functions as a temporary storage area and a work memory during the operation of the information processing apparatus. The storage unit **236** includes an HDD, an SSD, or the like.

(32) The NW I/F **238** is connected to the NW I/F **207** of the image forming apparatus **101** via the cable **213**. The video I/F **233** is connected to the video I/F **206** of the image forming apparatus **101** via the video cable **241**.

(33) A NW I/F **237** is connected to the NW I/F **232** of the inspection apparatus **108** and a NW I/F **240** of the client computer **110** via the network **113**. That is, the information processing apparatus **109** communicates with the inspection apparatus **108** via the NW I/F **237** and the NW I/F **232**. The information processing apparatus **109** communicates with the client computer **110** via the NW I/F **237** and the NW I/F **240**.

(34) The client computer **110** will be described. A CPU **243** controls and calculates each section of the client computer **110** via a system bus **246**, and executes a program stored in a storage unit **244** and loaded into the RAM **242**.

(35) The RAM **242** is a type of general volatile storage device directly accessible from the CPU **243**, and is used as a work area of the CPU **243** or other temporary data storage area. The storage unit **244** stores control programs and data, and functions as a temporary storage area and a work memory during client computer operation. The storage unit **244** includes an HDD, an SSD, or the like. The NW I/F **240** is connected to the network **113**.

(36) FIGS. **3A** and **3B** illustrate diagrams of an example of print data and layout information generated by the client computer **110**. FIG. **3A** illustrates an example of print data. A reference sign **301** denotes print data. Reference signs **302**, **303**, and **304** denote image data, respectively. The CPU **243** of the client computer **110** can impose a plurality of image data such as image data **302**, **303**, and **304** on one page to create print data such as print data **301**.

(37) FIG. **3B** illustrates an example of layout information. The layout information **305** is information indicating how the print data **301** is printed. The coordinates **306** are information on which positions the data is imposed in the print data **301**. The data ID **307** and the data name **308** are information indicating which image data is included in the print data **301**. The data size **309** is information indicating what size image data is imposed in the print data **301**. By using the information of **306** to **309**, it is possible to know which image data is arranged at which position and with what size, and thereby the print data **301** is generated. That is, the layout information **305** indicates the arrangement of the image data used to generate the print job on the sheet.

(38) FIG. **4** illustrates an image diagram of a table showing how the print job is associated with the reference image of the inspection stored in the storage unit **228** of the inspection apparatus **108**. A correspondence table **401** shows which reference image and which inspection setting are associated with which print job. The correspondence table **401** is created by the CPU **226** of the inspection apparatus **108** and stored in the storage unit **228** of the inspection apparatus **108**.

(39) A job ID **402** is a job ID of a print job, and is information for identifying the print job. A data ID **403** and a data name **404** are information indicating what kind of image data is used in the print job as in FIG. 3B. A reference image **405** is information indicating what reference image is registered (associated) with the data ID **403** and the data name **404**. An inspection setting **406** is information indicating what kind of inspection is to be performed on the job ID **402**, the data ID **403**, the data name **404**, and the reference image **405**. Using the information of **402** to **406**, it is possible to know what kind of inspection is performed for which image data of which job and which reference image are used.

(40) An entire flow of the inspection processing system according to the present embodiment will be described with reference to FIGS. 5, 6, and 7. FIG. 5 illustrates a flowchart of an example of processing performed by the client computer **110**. This process corresponds to a process in which the client computer **110** generates a print job, and transmits a correspondence table **401** indicating which reference image or inspection setting corresponds to which print job, and layout information **305** to the inspection apparatus **108**. The processing of the flowchart is realized by the CPU **243** of the client computer **110** reading the program stored in the storage unit **244** into the RAM **242** and executing it as necessary.

(41) In step S501, the CPU **243** generates a print job. In step S502, the CPU **243** transmits the job ID of the print job generated in step S501 to the inspection apparatus **108** via the network **113**. The CPU **226** of the inspection apparatus **108** receives the job ID and stores the job ID in the storage unit **228**. Next, in step S503, the CPU **243** identifies what image data is used in the generation of the print job in step S501.

(42) Next, in step S504, the CPU **243** converts one of the data identified in step S503 into a bitmap image for use in the inspection. Next, in step S505, the CPU **243** transmits the image converted in step S504 to the inspection apparatus **108** as a reference image for use in the inspection along with the data ID, the data name, and the job ID of the print job via the network **113**. The CPU **226** of the inspection apparatus **108** receives the information, associates the information with the job ID, and stores the information in the storage unit **228**. Thus, the reference image used in the inspection is registered in the inspection apparatus **108**.

(43) Next, in step S506, the CPU **243** sets the kind of inspection to be performed using the reference image registered in step S505, and transmits the information (inspection setting) together with the job ID and the data ID to the inspection apparatus **108** via the network **113**. The CPU **226** of the inspection apparatus **108** receives this information, associates the information with the job ID and the data ID, and stores the information in the storage unit **228**. In the inspection setting, for example, a user sets an inspection setting as shown in **406** in FIG. 4 from an operation unit (not shown) of the client computer **110**.

(44) Next, in step S507, the CPU **243** checks whether the processes in steps S504 to S506 have been performed for all the image data used for the print job. If the processes have not been performed for all the image data used for the print job (No in step S507), the CPU **243** returns the processing to step S504 and controls to repeat the processing for all the image data. On the other hand, if the processes have already been performed for all the image data used for the print job (Yes in step S507), the CPU **243** proceeds to step S508. As a result of the processing up to step S507, the information shown in FIG. 4 (correspondence table **401**) is completed. That is, information such as the correspondence table **401** is stored in the storage unit **228** of the inspection apparatus **108**.

(45) In step S508, the CPU **243** transmits the layout information of the print job generated in step S501 with the job ID to the inspection apparatus **108** via the network **113**. The CPU **226** of the inspection apparatus **108** receives the information, associates the information with the job ID, and stores the information in the storage unit **228**. Here, the layout information represents information as shown in FIG. 3B.

(46) FIG. 6 illustrates a flowchart of an example of processing of the inspection apparatus **108** according to the first embodiment. This processing corresponds to the processing in which the

inspection apparatus **108** performs inspection based on the information received from the client computer **110**. The processing of the flowchart is realized by the CPU **226** of the inspection apparatus **108** reading the program stored in the storage unit **228** into the RAM **227** and executing it as necessary.

(47) When the CPU **226** of the inspection apparatus **108** receives the image of the inspection object captured by the capturing unit **218** of the inspection unit **106** via the inspection apparatus I/F **215** at step **S601**, the processing proceeds to step **S602**.

(48) In step **S602**, the CPU **226** checks the job ID corresponding to the image to be inspected in step **S601** in order to obtain information necessary for performing the inspection. The CPU **226** checks the job ID with the information processing apparatus **109** or the image forming apparatus **101**, for example. The CPU **226** may receive the job ID corresponding to the printing of the image with the image to be inspected in step **S601**. Further, when the print job for printing the image to be inspected is started by the image forming apparatus **101**, the CPU **226** may receive the job ID from the information processing apparatus **109** or the image forming apparatus **101**.

(49) In step **S603**, the CPU **226** acquires reference image information including the data ID, the data name, and the like associated with the job ID acquired in **S602**. Further, in step **S604**, the CPU **226** acquires inspection setting information on what kind of inspection is to be performed based on the reference image information including the job ID acquired in **S602**, the data ID, the data name, and the like acquired in **S603**. Next, in step **S605**, the CPU **226** acquires the layout information of the print job using the job ID acquired in step **S602**.

(50) Next, in step **S606**, the CPU **226** inspects the image to be inspected acquired in step **S601** based on the information acquired in steps **S602** to **605**. In the present embodiment, the image to be inspected is inspected for each region based on the layout information **305** (that is, the region corresponding to one set of information in **306** to **309**). When the layout information **305** of FIG. **3B** is used, for example, an image of the region having a data size (width: 100, Height: 55) with respect to the coordinates (X: 20, Y: 20) of the image to be inspected is inspected (compared) using the reference image (AAA.bmp) of the data A. In this case, the inspection setting is performed by using the inspection setting (stain inspection: level **1**, streak inspection: level **2**) corresponding to the “data A” set by being associated with the job ID “0001” in the inspection setting **406** of FIG. **4**.

(51) Next, in step **S607**, the CPU **226** checks whether all the regions to be inspected have been inspected (the inspection in step **S605**). If there is a region to be inspected that has not been inspected yet (No in step **S607**), the CPU **226** returns the process to step **S606** and performs control to inspect the next region to be inspected. On the other hand, if the inspection is completed for all the regions to be inspected (Yes in step **S607**), the CPU **226** proceeds to step **S608**.

(52) Although the inspection is performed for each inspection target region based on the layout information in the present embodiment, the inspection apparatus **108** may synthesize the image data for inspection based on the information from steps **S602** to **S605**, and perform the inspection using the synthesized image as the reference image.

(53) In step **S608**, the CPU **226** stores (outputs) a comprehensive inspection result acquired by inspecting all the regions to be inspected on one page to the storage unit **228** of the inspection apparatus **108**. The data stored at this time is as shown in FIG. **7**, which will be described later.

(54) FIG. **7** illustrates an image diagram showing how inspection results are stored in the first embodiment. The inspection result is stored in the storage unit **228** of the inspection apparatus **108**. The correspondence table **701** shows inspection results when the inspection is performed by using the inspection apparatus **108**. The inspection result includes a job ID **702** indicating the inspection result of which job, a page number **703** indicating the inspection result of which page, and an inspection result **704** indicating how the inspection result was.

(55) In the inspection result **704**, information indicating “passed” is stored when the image passed the inspection, and information indicating “failed” is stored when the image failed the inspection. Although “passed” and “failed” are described here as examples, they are examples only, and any

information can be used as long as “passed” and “failed” can be expressed in accordance with the meaning.

(56) As described above, in the first embodiment, the client computer **110** transmits layout information such as which image data is imposed and how image data is imposed, reference image information, and inspection setting information to the inspection apparatus **108**, and the inspection apparatus **108** performs inspection. Thus, the inspection can be efficiently performed without the trouble of printing once, scanning, and registering the reference image.

Second Embodiment

(57) In the first embodiment, an overall result for each page is stored as an inspection result. However, since the inspection is performed based on grasping where and which image data is arranged with the layout information of the print job, the inspection result may be stored for each region. Thus, the inspection result of each unit region in one page can be grasp in more detail.

(58) Referring to FIGS. **8** and **9**, the flow of storing the inspection results in each region will be described. FIG. **8** illustrates a flowchart of an example of processing of the inspection apparatus **108** according to the second embodiment. The processing of the flowchart is realized by the CPU **226** of the inspection apparatus **108** reading the program stored in the storage unit **228** into the RAM **227** and executing it as necessary. First, the processes of steps **S801** to **S806** are the same as the processes of steps **S601** to **S606** of FIG. **6** in the first embodiment, and therefore the description thereof is omitted.

(59) In step **S807**, the CPU **226** associates the information inspected in step **S806** with the layout information shown in FIG. **3B** and stores the information in the storage unit **228** of the inspection apparatus **108**. Specifically, it is stored as shown in FIG. **9**, which will be described later. That is, the inspection result is stored for each region to be inspected.

(60) Next, in step **S808**, the CPU **226** checks whether all the regions to be inspected have been inspected (the inspection in step **S806**). If there is a region to be inspected that has not yet been inspected (No in step **S808**), the CPU **226** returns the process to step **S806** and performs control to inspect the next region to be inspected. On the other hand, if the inspection is completed for all the regions to be inspected (Yes in step **S808**), the CPU **226** terminates the processing of this flowchart.

(61) FIG. **9** illustrates an image diagram showing how inspection results are stored in the second embodiment. The inspection result is stored in the storage unit **228** of the inspection apparatus **108**. The correspondence table **901** shows inspection results when the inspection is performed using the inspection apparatus **108**. The inspection result includes a job ID **902**, a page number **903**, coordinates **904**, a data ID **905**, a data name **906**, a data size **907**, and an inspection result **908**.

(62) The job ID **902** indicates the print job corresponding to the inspection result. The page number **903** indicates the page corresponding to the inspection result. The coordinates **904** are information corresponding to the region in the page where the data are imposed, that is, indicate which region in the page the inspection results is. The data ID **905** and the data name **906** are information indicating what kind of image data is used. The data size **907** is information indicating the size of the image data to be imposed, and indicates the size of the inspected image data. The inspection result **908** indicates the inspected result. The inspection result **908** stores information indicating “passed” when the image passed the inspection and information indicating “failed” when the image failed the inspection. Although “passed” and “failed” are described here as examples, they are examples only, and any information can be used as long as “passed” and “failed” can be expressed in accordance with the meaning. In addition to the individual inspection results for each region, a comprehensive result for each page may also be stored. In this case, if there is even one “failed” region, the overall result may be set as “failed”, and if there is even one “passed” region, the overall result may be set as “passed” (the same applies to the first embodiment).

(63) As described above, it is possible to grasp an inspection result indicating where something is wrong in the page efficiently, more precisely and in more detail by associating the image data with

layout information such as which image data is imposed and how image data is imposed and storing the inspection result.

(64) The inspection apparatus **108** may be connected to the client computer **110** or the inspection unit **106** via the Internet or the like. For example, the cloud service may be used to realize the function of the inspection apparatus **108**.

(65) As described above, in each embodiment of the present invention, the image data and layout information used for generating the print job are received from the client computer **110** generating the print job, instead of printing, scanning, and registering the reference image. An image scanned from the print product printed based on the print job and image data used for generating the print job are compared based on the layout information to inspect the print quality of the print product. As a result, it is not necessary to print, scan, and register the reference image, and the print quality of the print product can be efficiently inspected without a trouble.

(66) The configuration and contents of the various data described above are not limited thereto, and it is needless to say that the various configurations and contents are configured according to the use and purpose. Although one embodiment has been described above, the present invention may be implemented, for example, as a system, apparatus, method, program, or storage medium. Specifically, the present invention may be applied to a system comprising a plurality of apparatuses, or may be applied to an apparatus comprising one apparatus. Further, all the configurations in which the above embodiments are combined are also included in the present invention.

(67) According to the present invention, the print product can be inspected efficiently without a trouble.

Other Embodiment

(68) Embodiment(s) of the present invention can also be realized by a computer of a system or apparatus that reads out and executes computer executable instructions (e.g., one or more programs) recorded on a storage medium (which may also be referred to more fully as a ‘non-transitory computer-readable storage medium’) to perform the functions of one or more of the above-described embodiment(s) and/or that includes one or more circuits (e.g., application specific integrated circuit (ASIC)) for performing the functions of one or more of the above-described embodiment(s), and by a method performed by the computer of the system or apparatus by, for example, reading out and executing the computer executable instructions from the storage medium to perform the functions of one or more of the above-described embodiment(s) and/or controlling the one or more circuits to perform the functions of one or more of the above-described embodiment(s). The computer may comprise one or more processors (e.g., central processing unit (CPU), micro processing unit (MPU)) and may include a network of separate computers or separate processors to read out and execute the computer executable instructions. The computer executable instructions may be provided to the computer, for example, from a network or the storage medium. The storage medium may include, for example, one or more of a hard disk, a random-access memory (RAM), a read only memory (ROM), a storage of distributed computing systems, an optical disk (such as a compact disc (CD), digital versatile disc (DVD), or Blu-ray Disc (BD)TM), a flash memory device, a memory card, and the like.

(69) While the present invention has been described with reference to exemplary embodiments, it is to be understood that the invention is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

(70) This application claims the benefit of Japanese Patent Application No. 2021-136148, filed Aug. 24, 2021, which is hereby incorporated by reference herein in its entirety.

Claims

1. An inspection apparatus inspecting print quality of a print product based on comparing an image scanned from the print product with a reference image comprising: a memory; and at least one processor in communication with the memory, wherein the at least one processor is configured to: receive image data used for generating a print job and layout information including coordinate information indicating an arrangement of the image data on a sheet from an information processing apparatus that generated the print job; and perform an inspection of print quality of a print product by (i) acquiring, without printing the image data, the layout information including the coordinate information and (ii) comparing, based on the layout information including the coordinate information that was acquired without printing the image data, an image scanned from the print product printed based on the print job with the image data used for generating the print job.
2. The inspection apparatus according to claim 1, wherein the at least one processor is further configured to: receive an inspection setting for the inspection using the image data as a reference image from the information processing apparatus; and perform the inspection according to the image data based on the inspection setting by comparing, based on the layout information, the image scanned from the print product printed based on the print job with the image data used for generating the print job.
3. The inspection apparatus according to claim 1, wherein the at least one processor is configured to perform the inspection of the image scanned from the print product for each region corresponding to the image data based on the layout information.
4. The inspection apparatus according to claim 3, wherein the at least one processor is configured to output results of the inspection for each region.
5. The inspection apparatus according to claim 1, wherein the at least one processor is configured to generate an image synthesized from the image data based on the layout information to inspect the print quality of the print product by comparing the generated image with the image scanned from the print product printed based on the print job.
6. An inspection system comprising: an information processing apparatus configured to generate a print job, the information apparatus comprising: a first memory; and at least one first processor in communication with the first memory; and an inspection apparatus configured to inspect print quality of a print product based on comparing an image scanned from the print product with a reference image, the inspection apparatus comprising: a second memory; and at least one second processor in communication with the second memory, wherein the at least one first processor is configured to deliver image data used for generating the print job and layout information including coordinate information indicating an arrangement of the image data on a sheet to the inspection apparatus, wherein the at least one second processor is configured to: receive the image data used for generating the print job and the layout information including coordinate information indicating the arrangement of the image data on the sheet from the information processing apparatus; and perform an inspection of print quality of a print product by (i) acquiring, without printing the image data, the layout information including the coordinate information and (ii) comparing, based on the layout information including the coordinate information that was acquired without printing the image data, an image scanned from the print product printed based on the print job with the image data used for generating the print job.
7. A control method for controlling an inspection apparatus inspecting print quality of a print product based on comparing an image scanned from the print product with a reference image, the control method comprising: receiving image data used for generating a print job and layout information including coordinate information indicating an arrangement of the image data on a sheet from an information processing apparatus that generated the print job; and performing an inspection of print quality of a print product by (i) acquiring, without printing the image data, the layout information including the coordinate information and (ii) comparing, based on the layout information including the coordinate information that was acquired without printing the image

data, an image scanned from the print product printed based on the print job with the image data used for generating the print job.

8. A non-transitory computer-readable storage medium storing program to cause a computer to perform a control method for controlling an inspection apparatus inspecting print quality of a print product based on comparing an image scanned from the print product with a reference image, the control method comprising: receiving image data used for generating a print job and layout information including coordinate information indicating an arrangement of the image data on a sheet from an information processing apparatus that generated the print job; and performing an inspection of print quality of a print product by (i) acquiring, without printing the image data, the layout information including the coordinate information and (ii) comparing, based on the layout information including the coordinate information that was acquired without printing the image data, an image scanned from the print product printed based on the print job with the image data used for generating the print job.

9. The non-transitory computer-readable storage medium according to claim 8, wherein the control method further comprises: receiving an inspection setting for the inspection using the image data as a reference image from the information processing apparatus; and performing the inspection according to the image data based on the inspection setting by comparing, based on the layout information, the image scanned from the print product printed based on the print job with the image data used for generating the print job.

10. The non-transitory computer-readable storage medium according to claim 8, wherein the inspection of the image scanned from the print product is performed for each region corresponding to the image data based on the layout information.

11. The non-transitory computer-readable storage medium according to claim 10, wherein the control method further comprises outputting results of the inspection for each region.

12. The non-transitory computer-readable storage medium according to claim 8, wherein the control method further comprises generating an image synthesized from the image data based on the layout information to inspect the print quality of the print product by comparing the generated image with the image scanned from the print product printed based on the print job.

13. The control method according to claim 7, wherein the control method further comprises: receiving an inspection setting for the inspection using the image data as a reference image from the information processing apparatus; and performing the inspection according to the image data based on the inspection setting by comparing, based on the layout information, the image scanned from the print product printed based on the print job with the image data used for generating the print job.

14. The control method according to claim 7, wherein the inspection of the image scanned from the print product is performed for each region corresponding to the image data based on the layout information.

15. The control method according to claim 14, wherein the control method further comprises outputting results of the inspection for each region.

16. The control method according to claim 7, wherein the control method further comprises generating an image synthesized from the image data based on the layout information to inspect the print quality of the print product by comparing the generated image with the image scanned from the print product printed based on the print job.

17. The inspection system according to claim 6, wherein the at least one second processor is further configured to: receive an inspection setting for the inspection using the image data as a reference image from the information processing apparatus; and perform the inspection according to the image data based on the inspection setting by comparing, based on the layout information, the image scanned from the print product printed based on the print job with the image data used for generating the print job.

18. The inspection system according to claim 6, wherein the at least one second processor is

configured to perform the inspection of the image scanned from the print product for each region corresponding to the image data based on the layout information.

19. The inspection system according to claim 18, wherein the at least one second processor is configured to output results of the inspection for each region.

20. The inspection system according to claim 6, wherein the at least one second processor is configured to generate an image synthesized from the image data based on the layout information to inspect the print quality of the print product by comparing the generated image with the image scanned from the print product printed based on the print job.
