

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250265722

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Sibley; Gabriel Thurston et al.

TARGETING AGRICULTURAL OBJECTS VIA IMAGE PIXEL TRACKING

Abstract

Various embodiments relate generally to computer vision and automation to autonomously identify and deliver for application a treatment to an object among other objects, data science and data analysis, including machine learning, deep learning, and other disciplines of computer-based artificial intelligence to facilitate identification and treatment of objects, and robotics and mobility technologies to navigate a delivery system, more specifically, to an agricultural delivery system configured to identify and apply, for example, an agricultural treatment to an identified agricultural object. In some examples, a method may include, at least, detecting an optical sight to align with an associated agricultural object, tracking the agricultural objects relative to the optical sight, predicting a parameter to track in association with agricultural object, and activating an emitter to apply an action based on the parameter.

Inventors: Sibley; Gabriel Thurston (Menlo Park, CA), Garner; Curtis Dale (Modesto, CA), Michelin; Andre Robert Daniel (Topanga, CA), Ibarria; Lorenzo (Dublin, CA), Leger; Patrick Christopher (Belmont, CA), Rewis; Benjamin (Oakland, CA), Yan; Shi (San Jose, CA)

Applicant: Verdant Robotics, Inc. (Hayward, CA)

Family ID: 1000008578010

Appl. No.: 19/200855

Filed: May 07, 2025

Related U.S. Application Data

parent US continuation 18079784 20221212 parent-grant-document US 12315171 child US 19200855

parent US continuation 16724263 20191221 parent-grant-document US 11526997 child US 18079784

Publication Classification

Int. Cl.: **G06T7/246** (20170101); **A01C15/00** (20060101); **A01G7/06** (20060101); **A01M1/20** (20060101); **G06N20/00** (20190101); **G06Q50/02** (20240101); **G06V20/10** (20220101)

U.S. Cl.:

CPC **G06T7/246** (20170101); **A01C15/00** (20130101); **A01G7/06** (20130101); **A01M1/20** (20130101); **G06N20/00** (20190101); **G06V20/188** (20220101); **G06Q50/02** (20130101); **G06T2207/30188** (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 18/079,784, filed on Dec. 12, 2022, which is a continuation of U.S. patent application Ser. No. 16/724,263, filed on Dec. 21, 2019, which are hereby incorporated by reference in their entirety.

FIELD

[0002] Various embodiments relate generally to computer software and systems, computer vision and automation to autonomously identify and deliver for application a specific treatment to an object among other objects, data science and data analysis, including machine learning, deep learning, and other disciplines of computer-based artificial intelligence to facilitate identification and treatment of objects, wired and wireless network communications, and robotics and mobility technologies to navigate a delivery system, as well as vehicles including associated mechanical, electrical and electronic hardware, among objects in a geographic boundary to apply any number of treatments to objects, and, more specifically, to an agricultural delivery system configured to identify and apply, for example, an agricultural treatment to an identified agricultural object.

BACKGROUND

[0003] Global human population growth is expanding at a rate projected to reach 10 billion or more persons within the next 40 years, which, in turn, will concomitantly increase demands on producers of food. To support such population growth, food producers, including farmers, need to generate collectively an amount of food that is equivalent to an amount that the entire human race, from the beginning of time, has consumed up to that point in time. Many obstacles and impediments, however, likely need to be overcome or resolved to feed future generations in a sustainable manner. For example, changes to the Earth's climate and unpredictable weather patterns negatively impact maintenance or enhancements in crop yields. Furthermore, limited or shrinking amounts of arable land on which to farm reduces opportunities to grow crops or dedicate land for other food production purposes.

[0004] Increased scarcity and costs of resources to produce food affects most farmers in less developed countries, as well as smaller farmers in developed countries. For example, the costs of crops sold (“cost of goods sold,” or “COGS”) are likely to increase beyond a range 60% to 70% of revenue. Costs of producing food, such as crops, may include costs due to labor, chemicals (e.g., fertilizer, pesticides, etc.), packaging, provenance tracking, and capital equipment (e.g., tractors, combines, and other farm implements), among other activities or resources. Labor costs are expected to rise as the demand for agricultural labor increases while fewer persons enter the agricultural workforce. Some agricultural workers are relocating to urban areas in numbers that increase scarcity of labor, thereby causing an average age of an agricultural worker to rise. Equipment costs, including tractors and sprayers, as well as other farm implements (e.g., combines,

plows, spreaders, planters, etc.) may require relatively large expenses to purchase or lease, as well as to maintain, fuel, and operate.

[0005] Costs relating to chemical inputs are likely to rise, too. For instance, health-related and environmental concerns may limit amounts and/or types of chemicals, such as certain pesticides, that can be used to produce vegetables, fruits, and other agricultural products. Also, while some advances in chemistries may be beneficial, these advanced chemistries may be unaffordable for most applications by smaller farms, or farms in underdeveloped countries, thereby possibly depriving farmers of optimal means to produce food. Further, applications of some chemistries, such as herbicides, pesticides, and fertilizers, on agricultural crops require sprayers to disperse chemicals in very small liquid droplets (e.g., using boom sprayers, mist sprayers, etc.). Spray nozzles generally have orifices or apertures oriented in a line substantially perpendicular to and facing the ground at a distance above the crops (relative to the soil), with the apertures designed to form overlapping flat fan or cone-shaped patterns of spray. Such conventional approaches to applying chemistries, however, usually results in amounts of spray falling upon non-intended targets, such as on the soil, which is wasteful.

[0006] The above-described costs likely contribute to increases in food prices and farm closures, and such costs may further hinder advances to improve crop yields to meet sufficiently the projected increases in human population. While functional, a few approaches to improve crop yields have been developed, and typically have a number of drawbacks. In some traditional approaches, information to assist crop development relies on multi-spectral imagery from satellites, aircraft, and/or drones. Multi-spectral imagery combined with location information, such as provided by Global Positioning Systems (“GPS”), enables coarse analysis of portions of a farm to determine soil characteristics, fertilizer deficiencies, topological variations, drainage issues, vegetation levels (e.g., chlorophyll content, absorption, reflection, etc.), and the like. Thus, multi-spectral may be used to identify various spectral, spatial, and temporal features with which to evaluate the status of a group of crops as well as changes over time. There are various drawbacks to rely on this approach. For example, data based on multi-spectral imagery are generally limited to coarse resolutions related to crop-related management. That is, multi-spectral imagery generally provides information related to certain areas or region including multiple rows of crops or specific acreage portions. Further, multi-spectral imagery is not well-suited for monitoring or analyzing botanical items granularly over multiple seasons. In particular, such imagery may be limited to detectable foliage, for example, midway through a crop season. Otherwise, multi-spectral imagery may be limited, at least in some cases, to a set of abiotic factors, such as the environmental factors in which a crop is grown, and, thus, may be insufficient to identify a specific prescriptive action (e.g., applying fertilizer, a herbicide, etc.) for one or more individual plants that may not be detectable using multi-spectral imagery techniques. As such, multi-spectral imagery may not be well-suited to analyze biotic factors, among other things.

[0007] In another traditional approach, known computer vision techniques have been applied to monitor agricultural issues at plant-level (e.g., as a whole plant, imaged from a top view generally). While functional, there are a number of drawbacks to such an approach. For instance, some computer-based analyses have been adapted to perform agricultural assessments with reliance on incumbent or legacy machinery and hardware, such as conventional tractors. The conventional tractors and other known implements are not well-suited to integrate with recent autonomous technologies to sufficiently navigate among crops to perform functions or tasks less coarsely, or to identify and perform less coarse tasks or treatments. For example, some conventional applications may vary rates of dispensing fertilizer based on specific prescriptive maps that rely on resolutions provided by GPS and multi-spectral imagery (e.g., satellite imagery). Hence, some conventional rates of applying fertilizer are generally at coarse resolutions in terms of square meters (i.e., over multiple plants).

[0008] In some traditional approaches, known computer vision techniques are typically

implemented to identify whether vegetation is either an individual crop or a non-crop vegetation (i.e., a weed). Further, these traditional approaches spray a chemical to generally treat a plant holistically, such as applying an herbicide to a weed or fertilizer to a crop. However, there is a variety of drawbacks to these traditional approaches. These approaches are typically directed to annual, row-based crops, such as lettuce, cotton, soybeans, cabbage, or other annual vegetation, which generally grow shorter than other vegetation. Row-based crops, also known as “row crops,” typically are crops tilled and harvested in row sizes relative to agricultural machinery, whereby row crops naturally are rotated annually to replace entire vegetative entities (e.g., removal of corn stalks, etc.). Also, row-based crops are typically planted in row widths of, for example, 15, 20, or 30 inch row widths, with conventional aims to drive row widths narrower to reduce weed competition and increase shading of the soil, among other things.

[0009] In some traditional approaches, known computer vision techniques applied to row crops rely on capturing imagery of vegetation at a distance above the ground and oriented generally parallel to a direction of gravity (e.g., top-down). As such, the background of imagery is typically soil, which may simplify processes of detecting vegetation relative to non-vegetation (e.g., the ground).

Further, images captured by a camera may have relatively minimal a depth of view, such as a distance from the soil (e.g., as a farthest element) to the top of an individual crop, which may be a row crop. Row crops have relatively shorter depth of view than other vegetation, including trees or the like, or other configurations. Known computer vision techniques have also been used, in some cases, to apply a fertilizer responsive to identifying an individual plant. In these cases, fertilizer has been applied as a liquid, whereby the liquid is typically applied using streams or trickles of liquid fertilizer. Further, the application of liquid fertilizer generally relies on a gravitational force to direct a stream of fertilizer to the individual crop.

[0010] Thus, what is needed is a solution for facilitating application of a treatment to an identified agricultural object, without the limitations of conventional techniques.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] Various embodiments or examples (“examples”) of the invention are disclosed in the following detailed description and the accompanying drawings:

[0012] FIG. 1A is a diagram depicting an example of an agricultural treatment delivery system, according to some embodiments;

[0013] FIG. 1B is a diagram depicting an example of an emitter configured to apply a treatment, according to some examples;

[0014] FIG. 2A is a diagram depicting examples of sensors and components of an agricultural treatment delivery vehicle, according to some examples;

[0015] FIG. 2B depicts generation of indexed agricultural object data, according to some embodiments;

[0016] FIG. 3 is an example of a flow diagram to control agricultural treatment delivery system autonomously, according to some embodiments;

[0017] FIG. 4 is a functional block diagram depicting a system including a precision agricultural management platform communicatively coupled via a communication layer to an agricultural treatment delivery vehicle, according to some examples;

[0018] FIG. 5 is a diagram depicting another example of an agricultural treatment delivery system, according some examples;

[0019] FIG. 6 is an example of a flow diagram to align an emitter to a target autonomously, according to some embodiments;

[0020] FIGS. 7A and 7B depict examples of data generated to identify, track, and perform an action

for one or more agricultural objects in an agricultural environment, according to some examples;

[0021] FIG. 7C is a diagram depicting parameters with which to determine activation of an emitter to apply a treatment, according to some examples;

[0022] FIG. 8 is a diagram depicting a perspective view of an agricultural projectile delivery vehicle configured to propel agricultural projectiles, according to some examples;

[0023] FIG. 9 is a diagram depicting an example of trajectory configurations to intercept targets autonomously using an agricultural projectile delivery vehicle, according to some examples;

[0024] FIG. 10 is a diagram depicting examples of different emitter configurations of agricultural projectile delivery systems, according to some examples;

[0025] FIG. 11 is a diagram depicting yet another example of an emitter configuration of an agricultural projectile delivery system, according to some examples;

[0026] FIGS. 12 and 13 are diagrams depicting examples of a trajectory processor configured to activate emitters, according to some examples;

[0027] FIG. 14 is a diagram depicting an example of components of an agricultural projectile delivery system that may constitute a portion of an emitter propulsion subsystem, according to some examples;

[0028] FIG. 15 is a diagram depicting an example of an arrangement of emitters oriented in one or more directions in space, according to some examples;

[0029] FIG. 16 is a diagram depicting an example of another arrangement of emitters configured to be oriented in one or more directions in space, according to some examples;

[0030] FIG. 17 is a diagram depicting one or more examples of calibrating one or more emitters of an agricultural projectile delivery system, according to some examples;

[0031] FIG. 18 is a diagram depicting another one or more examples of calibrating one or more emitters of an agricultural projectile delivery system, according to some examples;

[0032] FIG. 19 is an example of a flow diagram to calibrate one or more emitters, according to some embodiments;

[0033] FIGS. 20 and 21 are diagrams depicting an example of calibrating trajectories of agricultural projectiles in-situ, according to some examples;

[0034] FIG. 22 is a diagram depicting deviations from one or more optical sights to another one or more optical sights, according to some examples;

[0035] FIG. 23 is a diagram depicting an agricultural projectile delivery system configured to implement one or more payload sources to provide multiple treatments to one or more agricultural objects, according to some examples;

[0036] FIG. 24 is an example of a flow diagram to implement one or more subsets of emitters to deliver multiple treatments to multiple subsets of agricultural objects, according to some embodiments;

[0037] FIG. 25 is an example of a flow diagram to implement one or more cartridges as payload sources to deliver multiple treatments to multiple subsets of agricultural objects, according to some embodiments;

[0038] FIGS. 26 to 31 are diagrams depicting components of an agricultural treatment delivery vehicle configured to sense, monitor, analyze, and treat one or more agricultural objects of a fruit tree through one or more stages of growth, according to some examples;

[0039] FIG. 32 is a diagram depicting an example of a flow to manage stages of growth of a crop, according to some examples;

[0040] FIG. 33 is a diagram depicting an agricultural projectile delivery vehicle implementing an obscurant emitter, according to some examples;

[0041] FIG. 34 is a diagram depicting an example of a flow to facilitate imaging a crop in an environment with backlight, according to some examples;

[0042] FIG. 35 is a diagram depicting a pixel projectile delivery system configured to replicate an image on a surface using pixel projectiles, according to some embodiments;

[0043] FIG. **36** is a diagram depicting an example of a pixel projectile delivery system, according to some examples;

[0044] FIG. **37** is a diagram depicting an example of a flow to implement a pixel projectile delivery system, according to some examples; and

[0045] FIG. **38** illustrates examples of various computing platforms configured to provide various functionalities to components of an autonomous agricultural treatment delivery vehicle and fleet service, according to various embodiments.

DETAILED DESCRIPTION

[0046] Various embodiments or examples may be implemented in numerous ways, including as a system, a process, an apparatus, a user interface, or a series of program instructions on a computer readable medium such as a computer readable storage medium or a computer network where the program instructions are sent over optical, electronic, or wireless communication links. In general, operations of disclosed processes may be performed in an arbitrary order, unless otherwise provided in the claims.

[0047] A detailed description of one or more examples is provided below along with accompanying figures. The detailed description is provided in connection with such examples, but is not limited to any particular example. The scope is limited only by the claims, and numerous alternatives, modifications, and equivalents thereof. Numerous specific details are set forth in the following description in order to provide a thorough understanding. These details are provided for the purpose of example and the described techniques may be practiced according to the claims without some or all of these specific details. For clarity, technical material that is known in the technical fields related to the examples has not been described in detail to avoid unnecessarily obscuring the description.

[0048] FIG. **1A** is a diagram depicting an example of an agricultural treatment delivery system, according to some embodiments. Diagram **100** depicts an agricultural treatment delivery system configured to identify an agricultural object to apply an agricultural treatment. Examples of an agricultural treatment delivery system includes agricultural treatment delivery system **111a** and agricultural treatment delivery system **111b**, whereby agricultural treatment delivery systems **111a** and **111b** may be configured to deliver same or different treatments into an environment in which agricultural objects may be present. Agricultural treatment delivery system **111a** may include one or more emitters, such as emitter **112c**. Emitter **112c** may be configured emit a treatment **112b**, for example, via a trajectory **112d** in any direction to intercept a target (“T”) **112a** as vehicle **110** traverses path portions **119** at a velocity, v . In some cases, vehicle **110** may be in a static position. A direction of trajectory **112d** may be within a two- or three-dimensional space described relative to an XYZ coordinate system or the like. Examples of target **112a** may include a bud, blossom, or any other botanical or agricultural object likely to be sensed in an environment within a geographic boundary **120**, which may include at least a portion of a farm, an orchard, or the like.

[0049] Agricultural treatment delivery system **111a** may be disposed in a vehicle, such as vehicle **110**, to facilitate mobility to any number of targets **112a** within a geographic boundary **120** to apply a corresponding treatment **112b**. In some examples, vehicle **110** may include functionalities and/or structures of any motorized vehicle, including those powered by electric motors or internal combustion engines. For example, vehicle **110** may include functionalities and/or structures of a truck, such as a pick-up truck (or any other truck), an all-terrain vehicle (“ATV”), a utility task vehicle (“UTV”), or any multipurpose off-highway vehicle, including any agricultural vehicle, including tractors or the like. Also, agricultural treatment delivery systems **111a** and **112b**, as well as other agricultural treatment delivery systems (not shown), may be implemented in a trailer (or other mobile platform) that may be powered or pulled separately by a vehicle, which may navigate path portions **119** manually or autonomously. As shown, vehicle **110** may include a manual controller or control module (“cab”) **115**, which may accommodate a human driver and include any mechanical control system, such as a steering wheel and associated linkages to steerable wheels, as

well as manually controlled braking and accelerator subsystems, among other subsystems.

[0050] In some examples, vehicle **110** may include a mobility platform **114** that may provide logic (e.g., software or hardware, or both), and functionality and/or structure (e.g., electrical, mechanical, chemical, etc.) to enable vehicle **110** to navigate autonomously over one or more paths **119**, based on, for example, one or more treatments to be applied to one or more agricultural objects. Any of agricultural treatment delivery systems **111a** or **111b** may be configured to detect, identify, and treat agricultural objects autonomously (e.g., without manual intervention) independent of whether vehicle **110** is configured to navigate and traverse path portions **119** either manually or autonomously.

[0051] In the example shown, agricultural treatment delivery system **111** may be configured to traverse path portions **119** adjacent to agricultural objects, such as trees, disposed in arrangements **122a**, **122b**, **122c**, **122d**, and **122n**, or any other agricultural objects associated therewith. In some cases, arrangements **122a**, **122b**, **122c**, **122d**, and **122n** may be any trellis-based structure, such as any espalier-supported pattern or any trellis configuration (e.g., substantially perpendicular configurations, an example of which is shown in diagram **100**, or “V-shaped” trellises, or any other structure). Note that agricultural treatment delivery system **111** need not be limited to trellis-based structures, but rather may be used with any plant or vegetative structure.

[0052] Any of agricultural treatment delivery systems **111a** or **111b** may be configured to operate, for example, in a sensor mode during which a sensor platform **113** may be configured to receive, generate, and/or derive sensor data from any number of sensors as vehicle **110** traverses various path portions **119**. For example, sensor platform **113** may include one or more image capture devices to identify and/or characterize an agricultural object, thereby generating. Examples of image capture devices include cameras (e.g., at any spectrum, including infrared), Lidar sensors, and the like. Image-based sensor data may include any data associated with an agricultural object, such as images and predicted images, that may describe, identify, or characterize physical attributes. Sensor platform **113** may also include one or more location or position sensors, such as one or more global positioning system (“GPS”) sensors and one or more inertial measurement units (“IMU”), as well as one or more radar devices, one or more sonar devices, one or more ultrasonic sensors, one or more gyroscopes, one or more accelerometers, one or more odometry sensors (e.g., wheel encoder or direction sensors, wheel speed sensors, etc.), and the like. Position-based sensors may provide any data configured to determine locations of an agricultural object relative to a reference coordinate system, to vehicle **110**, to emitter **112c**, or to any other object based, for example, GPS data, inertial measurement data, and odometry data, among data generated by other position and/or location-related sensors.

[0053] Note that any sensor or subset of sensors in sensor platform **113** may be configured to provide sensor data for any purpose. For example, any image capture device may be configured to detect a visual fiducial marker or any other optically-configured item (e.g., a QS code, barcode, or the like) that may convey information, such as position or location information, or other information. As agricultural treatment delivery system **111** and/or sensory platform **113** traverses path portions **119**, image capture devices may detect fiducial markers, reflective surfaces, or the like, so that logic within sensory platform **113** or vehicle **110** (e.g., one or more processors and one or more applications including executable instructions) may be configured to detect or confirm a position of vehicle **110** or emitter **112c**, or both, as a position within geographic boundary **120** or relative to an agricultural object.

[0054] In some implementations, one or more sensors in sensor platform **113** may be distributed among any portion of vehicle in any combination. For example, sensors in sensor platform **113** may be disposed in any of agricultural treatment delivery systems **111a** or **111b**. As such, any of agricultural treatment delivery systems **111a** or **111b** may each be configured to localize or determine a position of emitter **112c** relative to an agricultural object independently. That is, agricultural treatment delivery systems **111a** or **111b** may include sensors and logic to determine

the position of an emitter **112c** in association with, or relative to, an agricultural object, and may be configured to identify an agricultural object autonomously, orient or otherwise target that agricultural object for action autonomously, and/or perform an action or apply a treatment autonomously regardless of whether vehicle **110** is navigating manually or autonomously.

[0055] One or more of agricultural treatment delivery systems **111a** and **111b** may be implemented as a modular structure that may be loaded into a bed of a pickup truck or an ATV/UTV, or any other vehicle that may be configured to manually navigate agricultural treatment delivery system **111** along path portions **119** to sense an agricultural object and to perform an action therewith. In some implementations, one or more sensors in sensor platform **113** may be distributed among any portion of vehicle, for example, including mobility platform **114**, to facilitate autonomous navigation, agricultural object identification, and perform an action (e.g., apply a treatment). Hence, agricultural treatment delivery system **111** may implement sensors or sensor data (e.g., individually or collectively), or may share or use sensors and sensor data used in association with mobility platform **114** to facilitate autonomous navigation of vehicle **110**. In one example, sensor platform **113** may be disposed in mobility platform **114**, or in or among any other portion. Mobility platform **114** may include hardware or software, or any combination thereof, to enable vehicle **110** to operate autonomously.

[0056] Sensor platform **113** may be configured to sense, detect, analyze, store, and/or communicate data associated with one or more agricultural objects. For example, sensor platform **113** may be configured to at least detect or sense a subset **123b** of one or more agricultural objects associated with tree **121a** positioned adjacent path portion **119a**. Sensor platform **113** also may be configured to detect subset **123b** of agricultural objects as, for example, a limb, a branch, or any portion of agricultural object (“tree”) **121a**, and may further detect other sub-classes of agricultural objects of subset **123b**. Sub-classes of agricultural objects of subset **123b** may include buds, such as growth buds **125** (e.g., a bud from which a leaf or shoot may develop) and fruit buds **124** and **126**, each of which may be an agricultural object. Branch **123a** may also include a limb **127** as an agricultural object, and may include other agricultural objects, such as a spur (e.g., a shoot that may develop fruit), a water sprout (e.g., a young shoot growing within tree **121a**), and the like.

[0057] In some embodiments, agricultural treatment delivery system **111** may be configured to communicate agricultural object data **197** via any communication media, such as wireless radio transmissions, to a precision agricultural management platform **101**. Precision agricultural management platform **101** may include hardware (e.g., processors, memory devices, etc.) or software (e.g., applications or other executable instructions to facilitate machine learning, deep learning, computer vision techniques, statistical computations, and other algorithms), or any combination thereof. Precision agricultural management platform **101** (or portions thereof) may reside at any geographic location, whether at or external to geographic location **120**. In one or more examples, logic associated with either precision agricultural management platform **101** or agricultural treatment delivery system **111**, or both, may be configured to implement or facilitate implementation of simultaneous localization and mapping (“SLAM”) to support autonomous navigation of vehicle **110**, as well as autonomous operation of agricultural treatment delivery systems **111a** and **111b**. Hence, agricultural treatment delivery systems **111a** and **111b** may implement SLAM, or any other technique, to apply a treatment to an agricultural object autonomously.

[0058] Precision agricultural management platform **101** may be configured to, index and assign a uniquely identifier to each agricultural object in transmitted data **197** (e.g., as a function of a type of agricultural object, such as a blossom, a location of the agricultural object, etc.). Precision agricultural management platform **101** also may operate to store and manage each agricultural object (in agricultural object data **197**) as indexed agricultural object data **102a**, whereby each data arrangement representing each indexed agricultural object may be accessed using an identifier.

[0059] In some cases, either precision agricultural management platform **101** or agricultural

treatment delivery system **111**, or both, may be configured to implement computer vision and machine learning algorithms to construct and maintain a spatial semantic model (e.g., at resolutions of sub-centimeter, or less) and/or a time-series model of plant physiology and state-of-growth. Data representing any of these models may be disposed in data representing indexed agricultural object data **102a**. For example, agricultural treatment delivery system **111** may be configured to navigate path portions **119** at any time in autumn, winter, spring, and summer to monitor a status of tree **121a** and associated subsets of agricultural objects. For example, sensor platform **113** and/or agricultural treatment delivery system **111** may capture sensor data associated with fruit bud **126**, which may develop over time through progressive stages of growth. At stage **130**, fruit bud **126** is shown in an “open cluster” stage with flower buds **131** being, for example, pink in color and prior to blossom. The open cluster stage is indicated at time, T , equivalent to $t(\text{OC})$, with “OC” referring to “open cluster.” At stage **132**, the open cluster may transition over time (and through other intermediate stages, which are not shown) into a “blossom” stage in which a first (e.g., King) blossom **133** opens. The blossom stage is indicated at time, T , equivalent to $t(1.\text{sup.st BL})$, with “BL” referring to “blossom.” At stage **133**, the blossom stage may transition over time (and through other intermediate stages, which are not shown) into a “fruit” stage in which a first blossom ripens into a fruit **135**. The fruit stage is indicated at time, T , equivalent to $t(\text{opt})$, with “opt” referring to an optimal time at which fruit **135** may be optimally ripened for harvest.

[0060] Continuing with the example of detecting various stages in the growth of a crop, sensor platform **113** may transmit sensor data as agricultural object data **197** to precision agricultural management platform **101**, which may analyze sensor data representing one of stages **130**, **132**, and **134** to determine an action to be performed for a corresponding stage. For example, at stage **132**, logic in precision agricultural management platform **101** may be configured to identify at least one action to be performed in association with blossom **133**. An action may include applying a treatment to blossom **133**, such as causing emitter **112c** to apply treatment **112b** to blossom **133** as target **112a**. The treatment may include applying pollen to, for example, a stigma of blossom **133** to effect germination. In various examples, precision agricultural management platform **101** may be configured to generate and store policy data **102b** in repository **102**, and be further configured to transmit policy and/or index data **195** to agricultural treatment delivery system **111a**.

[0061] Any of agricultural treatment delivery systems **111a** or **111b** may be configured to operate, for example, in an action mode during which a sensor platform **113** may be configured to receive policy data **195** associated with blossom **133**, which may be uniquely identifiable as an indexed agricultural object. Policy data may specify that blossom **133** is to be pollinated. Sensor platform **113** may be configured further to receive and/or generate sensor data from any number of sensors as vehicle **110** traverses various path portions **119**, the sensor data being configured to identify an image of blossom **133** as vehicle traverses path portion **119a**. When sensor platform **113** detects blossom **133**, agricultural treatment delivery system **111a** may be configured to trigger emission of treatment **112b** autonomously. Note that agricultural treatment delivery systems **111a** or **111b** each may operate in sensor and action modes, individually or simultaneously, and may operate in any number of modes. Each mode may be implemented individually or collectively with any other mode of operation.

[0062] In some examples, agricultural treatment delivery systems **111** and vehicle **110** may operate to provide “robotics-as-a-service,” and in particular, “robotics-as-an-agricultural-service” to enhance automation of crop load management and yield enhancement at least an agricultural object basis (or at finer resolution). For example, an apple crop may be monitored (e.g., during each pass of vehicle **110**) and treated with micro-precision, such as on a per-cluster basis or a per-blossom basis. Vehicle **110** and other equivalent vehicles **199** may constitute a fleet of autonomous agricultural vehicles **110**, each of which may identify agricultural objects and apply corresponding treatments autonomously. In at least one example, vehicle **110** may be configured to traverse, for example, 50 acres (or more) at least two times each day to generate and monitor sensor data, as

well as to apply various treatments. In some cases, a computing device **109** may be configured to receive sensor data (e.g., image data) and to transmit executable instructions to perform a remote operation (e.g., a teleoperation) under guidance of user **108**, who may be an agronomist or any other user including data analysts, engineers, farmers, and the like. Computing device **109** may provide remote operation to either navigate vehicle **110** or apply a treatment **112b** via emitter **112c**, or both.

[0063] FIG. **1B** is a diagram depicting an example of an emitter configured to apply a treatment, according to some examples. Diagram **150** includes an emitter **152c** that may be configured to apply treatments to agricultural objects, such as one or more portions of agricultural object depicted as a blossom. An agricultural treatment delivery system may be configured to apply units (e.g., distinct units) of treatment that may include, for example, packetized portions of a fertilizer, a thinning chemical, an herbicide, a pesticide, or any other applicable agricultural material or substance. As shown, emitter **152c** may be configured to apply a treatment with micro-precision by emitting an agricultural projectile **152b** to intercept a target **152ab** at or within a target dimension **151**. For example, target dimension **151** may have a dimension (e.g., a diameter) of 1 centimeter (“cm”) or less. Hence, emitter **152c** may deliver a treatment with a micro-precision of, for example, 1 cm or less, at any trajectory angle.

[0064] Agricultural projectile **152b** may be configured as a liquid-based projectile propelled from emitter **152c** for a programmable interval of time to form the projectile having, for example, an envelope **156b**, at least in one example. Emitter **152c** may be configured to emit agricultural projectile **152b** along a trajectory direction **155a**, which may be any direction in two or three-dimensional space. In at least one example, emitter **152c** may be configured to propel agricultural projectile **152b** in trajectory direction **155a** with a force having a vertical component (“F_{vc}”) and a horizontal component (“F_{hc}”). As shown, the vertical component of the propulsion force may be in a direction opposite than the force of gravity (“F_g”). Note, however, any of vertical component (“F_{vc}”) and a horizontal component (“F_{hc}”) may be negligible or zero, at least in one implementation. Note, too, that horizontal component (“F_{hc}”) may have a magnitude sufficient to propel agricultural projectile **152b** over a trajectory distance **154**. In treatments applied to, for example, trellis or orchard crops, trajectory distance **154** may be 3 meters or less. In treatments applied to, for example, row crops, trajectory distance **154** may be 1 meter or less. In at least one example, trajectory distance **154** may be any distance within a geographic boundary.

[0065] In at least one other example, emitter **152c** may be configured to emit agricultural projectile **152b** along trajectory direction **155a** in an envelope **156a** to intercept a target **152aa** having a target dimension **153**. As an example, target dimension **153** may have a dimension (e.g., a diameter) equivalent to a size of an apple (or a size equivalent to any other agricultural object). Thus, emitter **152c** may be configured to modify a rate of dispersal with which portions of agricultural projectile **152b** disperses at or about a range of a target of a particular size. According to some examples, trajectory direction **155a** may be coaxial with an optical ray extending, for example, from at least one of a first subset of pixels of an image capture device to at least one pixel of a second subset of pixels including an image of target **152ab**. Further, one or more of the first subset of pixels may be configured as an optical sight. Thus, when at least one pixel of the optical sight aligns with at least one pixel of the target image, an agricultural projectile may be propelled to intercept target **152ab**. In some examples, emitter **152c** may include an aperture that is aligned coaxially with the optical ray. An example of emitter **152c** includes a nozzle. According to at least one implementation, disposing and orienting emitter **152** coaxially to an optical ray facilitates, for example, two-dimensional targeting. Therefore, a range or distance of target **152b** may be positioned anywhere, such as at points A, B, or C, along the optical ray and may be intercepted without calculating or confirming an actual or estimated distance or three-dimensional position, at least in some examples.

[0066] In some examples, a dosage or amount of treatment (e.g., fertilizer) may be applied at

variable amounts by, for example, slowing a speed of vehicle and extending an interval during which agricultural projectile **152b** is propelled or emitted. In at least one case, an amount of propulsion (e.g., a value of pressure of a propellant, such as a compressed gas) may be modified as a function of trajectory distance **154** or any other factor, such as an amount of wind. In some cases, multiple agricultural projectile **152b** of the same or different amounts may be propelled to intercept a common target **152a**. Agricultural projectile **152b** may include an inert liquid to increase viscosity, which may reduce a rate of dispersal, at least in some implementations. In some cases, emitter **152c** can be configured to emit agricultural projectile **152b** having a liquid configured to be emitted with a laminar flow characteristics (e.g., with minimal or negligible turbulent flow characteristics). According to other examples, an emitter need not align with an optical ray and may use multiple image devices to orient alignment of an emitter to a target independently of an optical ray associated with an in-line camera.

[0067] FIG. 2A is a diagram depicting examples of sensors and components of an agricultural treatment delivery vehicle, according to some examples. Diagram **200** depicts expanded component view of an agricultural treatment delivery vehicle **210** that may provide a mechanical and electrical structure, such as structures implemented in pick-up trucks, flatbed trucks, ATVs, UTVs, tractors, and the like. Agricultural treatment delivery vehicle **210** may include a power plant, such as an internal combustion engine or an electric battery-powered motor. As shown, agricultural treatment delivery vehicle **210** may include a sensor platform **213** including any number and type of sensor, whereby any sensor may be located and oriented anywhere on agricultural treatment delivery vehicle **210**. For example, sensors depicted in diagram **200** may be implemented as sensor platform **213** (or a portion thereof). Sensors in FIG. 2A include one or more image capture sensors **236** (e.g., light capture devices or cameras of any type, including infrared camera to perform action at night or without sunlight), one or more radar devices **237**, one or more sonar devices **238** (or other like sensors, including ultrasonic sensors or acoustic-related sensors), and one or more Lidar devices **234**, among other sensor types and modalities (some of which may not be shown, such as inertial measurement units, or “IMUs,” global positioning system (“GPS”) sensors, temperature sensors, soil composition sensors, humidity sensors, barometric pressure sensors, light sensors, etc.). In some cases, sensor platform **213** may also include an airflow direction sensor **201** (e.g., wind direction) and/or an airflow speed sensor **202** (e.g., wind speed), where the direction and speed of air flow may be relative to a direction and velocity of agricultural treatment delivery vehicle **210**.

[0068] Agricultural treatment delivery vehicle **210** may include an agricultural treatment delivery system **211** including any number of emitters **212**, each of which may be oriented to propel an agricultural projectile at any direction from a corresponding emitter. In some examples, each emitter **212** may be oriented to propel an agricultural projectile via a trajectory that may be coaxial to an optical ray associated with a portion of a digitized image of an agricultural environment that includes one or more crops, or agriculture objects.

[0069] Further, agricultural treatment delivery vehicle **210** may include a motion estimator/localizer **219** configured to perform one or more positioning and localization functions. In at least one example, motion estimator/localizer **219** may be configured to determine a location of one or more component of agricultural treatment delivery vehicle **210** relative to a reference coordinate system that may facilitate identifying a location at specific coordinates (i.e., within a geometric boundary, such as an orchard or farm). For example, motion estimator/localizer **219** may compute a position of agricultural treatment delivery vehicle **210** relative to a point associated with vehicle **210** (e.g., a point coincident with a center of mass, a centroid, or any other point of vehicle **210**). As another example, a position of agricultural treatment delivery system **211** or any emitter **212** may be determined relative to a reference coordinate system, or relative to any other reference point, such as relative to a position of agricultural treatment delivery vehicle **210**. In yet another example, a position of an agricultural object may be determined using sensors in platform **213** and motion estimator/localizer **219** to calculate, for example, a relative position of an agricultural object

relative to a position of emitter **212** to facilitate identification of an indexed agricultural object (e.g., using image sensors data) and to enhance accuracy and precision of delivering an agricultural project to a target. According to some embodiments, data describing a position may include one or more of an x-coordinate, a y-coordinate, a z-coordinate (or any coordinate of any coordinate system), a yaw value, a roll value, a pitch value (e.g., an angle value), a rate (e.g., velocity), altitude, and the like.

[0070] In some examples, motion estimator/localizer **219** may be configured to receive sensor data from one or more sources, such as GPS data, wheel data (e.g., odometry data, such as wheel-related data including steering angles, angular velocity, etc.), IMU data, Lidar data, camera data, radar data, and the like, as well as reference data (e.g., 2D map data and route data). Motion estimator/localizer **219** may integrate (e.g., fuse the sensor data) and analyze the data by comparing sensor data to map data to determine a local position of agricultural treatment delivery vehicle **210** or emitter **212** relative to an agricultural object as a target, or relative to a waypoint (e.g., a fiducial marker affixed adjacent a path). According to some examples, motion estimator/localizer **219** may generate or update position data in real-time or near real-time.

[0071] Agricultural treatment delivery vehicle **210** may include a mobility controller **214** configured to perform one or more operations to facilitate autonomous navigation of agricultural treatment delivery vehicle **210**. For example, mobility controller **214** may include hardware, software, or any combination thereof, to implement a perception engine (not shown) to facilitate classification of objects in accordance with a type of classification, which may be associated with semantic information, including a label. A perception engine may classify objects for purposes of navigation (e.g., identifying a path, other vehicles, trellis structures, etc.), as well as for purposes of identifying agricultural objects to which a treatment may be applied. For example, a perception engine may classify an agricultural object as a bud, a blossom, a branch, a spur, a tree, a cluster, a fruit, etc. Mobility controller **214** may include hardware, software, or any combination thereof, to implement a planner (not shown) to facilitate generation and evaluation of a subset of vehicle trajectories based on at least a location of agricultural treatment delivery vehicle **210** against relative locations of external dynamic and static objects. The planner may select an optimal trajectory based on a variety of criteria over which to direct agricultural treatment delivery vehicle **210** in way that provides for collision-free travel or to optimize delivery of an agricultural projectile to a target. In some examples, a planner may be configured to calculate the trajectories as probabilistically-determined trajectories. Mobility controller **214** may include hardware, software, or any combination thereof, to implement a motion controller (not shown) to facilitate conversion any of the commands (e.g., generated by the planner), such as a steering command, a throttle or propulsion command, and a braking command, into control signals (e.g., for application to actuators, linkages, or other mechanical interfaces **217**) to implement changes in steering or wheel angles and/or velocity autonomously.

[0072] In some examples, agricultural treatment delivery system **211**, sensor platform **213** (including any sensor), and motion estimator/localizer **219** may be implemented as a modular agricultural treatment delivery system **221**, which can be configured to autonomously identify agricultural objects and apply a treatment to each agricultural object in accordance with a policy (e.g., application of a certain treatment responsive to stage of growth, and environmental condition, biotic data, abiotic data, etc.). Therefore, modular agricultural treatment delivery system **221** may be disposed in a truck, ATV, tractor, etc., any of which may be navigated manually (e.g., by a human driver) using manual control order **215**. In some example, agricultural treatment delivery system **211** may have logic, similar or equivalent to that in mobility controller **214**. For instance, agricultural treatment delivery system **211** may be configured to implement one or more of a perception engine to detect and classify agricultural objects, a planner to determine actions (e.g., one or more trajectories over which to propel an agricultural projectile), and a motion controller to control, for example, position or orientation of emitter **212**. In other examples, agricultural

treatment delivery system **211**, sensor platform **213** (including any sensor), and motion estimator/localizer **219** each may be integrated into a modular agricultural treatment delivery system **221**, which, in turn, may be integrated into agricultural treatment delivery vehicle **210**, along with mobility controller **214**, to facilitate autonomous navigation of vehicle **210** and autonomous operation of agricultural treatment delivery system **211**.

[0073] While agricultural treatment delivery vehicle **210** is described for applications in agriculture, delivery vehicle **210** need not be so limiting and may be implemented in any other type of vehicle, whether on land, in air, or at sea. Further, any agricultural projectile described herein, need not be limited to liquid-based projectiles, and may include solid and gas-based emissions or projectiles. Moreover, agricultural treatment delivery vehicle **210** need not be limited to agriculture, but may be adapted for any of a number of non-agricultural applications. Also, agricultural treatment delivery vehicle **210** may be configured to communicate with a fleet **299** of equivalent delivery vehicles to coordinate performance of one or more policies for any geographic boundary.

[0074] FIG. 2B depicts generation of indexed agricultural object data, according to some embodiments. Diagram **250** depicts an agricultural treatment delivery system **211**, which, in turn, may optionally include a sensor platform **213** and a motion estimator/localizer **219**, according to some examples. While sensor platform **213** is shown to include motion estimator/localizer **219**, each may be separate or distributed over any number of structures (as well as constituent components thereof). Diagram **250** also depicts a precision agricultural management platform **201** configured to receive agricultural object data **251** from agricultural treatment delivery system **211**, and further configured to generate indexed agricultural object data **252a**, which may be stored in a data repository **252**. Note that elements depicted in diagram **250** of FIG. 2B may include structures and/or functions as similarly-named elements described in connection to one or more other drawings.

[0075] Agricultural object data **251** may include data associated with a non-indexed agricultural object, an updated agricultural object, or any other information about an agricultural object. In some instances, a non-indexed agricultural object may be an agricultural object detected at sensor platform **213**, and may yet to be identified in, or indexed into, a database of indexed agricultural object data **252a**. Precision agricultural management platform **201** may be configured to identify agricultural object data **251** as “non-indexed,” and may activate executable instructions to invoke indexing logic **253** to generate indexed agricultural object data **252a** based on agricultural object data **251**, whereby indexed identifier data **254** (e.g., a unique identifier) may be associated with agricultural object data **251**. Also, agricultural object data **251** may include data associated with an updated agricultural object, such as when an agricultural object identified as being in a bud state at one point in time transitions to a blossom state (or any other intermediate states) at another point in time. In this case, agricultural object data **251** may also include image data (e.g., data representing a blossom) as well as any other sensor-based or derived data associated therewith, including an identifier (e.g., previously determined).

[0076] In various examples, precision agricultural management platform **201** may be configured to determine for agricultural object data **251** any other associated data provided or derived by, for example, sensors in sensor platform **213** and motion estimator/localizer **219**. For example, precision agricultural management platform **201** may be configured to generate one or more of location data **255**, botanical object data **260** (e.g., crop-centric data), biotic object data **272**, abiotic object data **274**, predicted data **282**, action data **290**, as well as any other data associated with agricultural object data **251**, including agricultural object characteristics, attributes, anomalies, associated activities, environmental factors, ecosystem-related items and issues, conditions, etc. Any one or more of location data **255**, botanical object data **260** (e.g., crop-centric data), biotic object data **272**, abiotic object data **274**, predicted data **282**, and action data **290** may be included or omitted, in any combination.

[0077] Precision agricultural management platform **201** may be configured to identify a location

(e.g., a spatial location relative to a two-dimensional or three-dimensional coordinate system) of an agricultural object associated with agricultural object data **251**, the location being represented by geographic location data **255a**. In some cases, geographic location data **255a** may include a geographic coordinate relative to a geographic boundary, such as a boundary of an orchard or farm. Geographic location data **255a** may include GPS data representing a geographic location, or any other location-related data (e.g., derived from position-related data associated with a sensor, vehicle, or agricultural treatment delivery system). Location data **255** may also include positioning data **255b** that may include one or more subsets of data that may be used to determine or approximate a spatial location of the agricultural object associated with agricultural object data **251**. For example, position data for one or more optical markers (e.g., reflective tape, visual fiduciary markers, etc.) may be included in positioning data **255b** to locate or validate a spatial location for agricultural object data **251**.

[0078] Botanical object data **260** may include any data associated with a plant, such as a crop (e.g., a specifically cultivated plant). For example, botanical object data **260** may include growth bud-related data **260**, fruit bud-related data set **262**, limb data **264**, and trunk/stem data **266**, and include other sub-classification of agricultural objects. Growth bud-related data **260** may include status data **261a** that may identify a bud as being in a “bud state” at one point in time, which may be determined (at another point in time) to be in another state when the bud develops into either one or more leaves or a shoot. Physical data **261b** may describe any attribute or characteristic of an agricultural object originating as a bud and that develops into one or more leaves or a shoot. For example, physical data **261b** may include a shape, color, orientation, anomaly, or the like, including image data, or any characteristic that may be associated with a leaf as an agricultural object.

[0079] Fruit bud-related data set **262** may include status data **262a** that may identify a fruit bud as being in a “fruit bud state” at one point in time, which may be determined (at another point in time) to be in another state when the bud develops into, for example, one or more blossoms as well as one or more fruit, such as one or more apples. For example, status data **262a** may include a subset of data **264a** to **264k** to describe a status or a state of growth associated with a fruit bud. The following description of sets of data **264a** to **264k** are illustrative regarding stages of growth of apples, and is not intended to be limiting and can be modified for any fruit crop, vegetable crop, or any plant-related stages of growth, including ornamental plants, such as flowers (e.g., roses), and the like.

[0080] Dormant data **264a** may include data associated with an identified dormant fruit bud, including image data acquired or otherwise sensed at one or more points in time as physical data **262b**. Silver tip data **264b** may include data associated with a stage of growth relative to a fruit bud transitioning to a “silver tip” stage of growth, including one or more images thereof as physical data **262b**. In this stage, image data depicting a fruit bud may include digitized images of scales that may be separated at the tip of the bud, thereby exposing light gray or silver tissue. Green tip data **264c** may include data associated with a stage of growth relative to a fruit bud transitioning to a “green tip” stage of growth, including one or more images thereof as physical data **262b**. In this stage, a fruit bud may have developed to include image data depicting a broken tip at which green tissue may be visible. Half-inch green data **264d** may include data associated with a stage of growth relative to a fruit bud transitioning to a “half-inch” stage of growth, including one or more images thereof as physical data **262b**. At this stage, a fruit bud may have developed to include image data depicting a broken tip at which approximately one-half inch of green tissue may be detectable in an image. Tight cluster data **264e** may include data associated with a stage of growth relative to a fruit bud transitioning to a “tight cluster” stage of growth, including one or more images thereof as physical data **262b**. At this stage, a fruit bud may have developed to include image data depicting a subset of blossom buds at various levels of visibility that may be detectable in an image, the blossom buds being tightly grouped.

[0081] Pink/pre-blossom data **264f** may include data associated with a stage of growth relative to

an initial fruit bud transitioning to a “pink” stage of growth (also known as “first pink,” “pre-pink,” or “full pink” stages) as well as (or up to) an “open cluster” stage, and one or more images thereof may be included in physical data **262b**. At this stage, image data may depict a subset of blossom buds at various levels of pink colors that may be detectable in an image prior to blossom. Blossom data **264g** may include data associated with a stage of growth relative to an initial fruit bud that may transition to a “blossom” stage of growth (also known as a “king bloom” or “king blossom” stage), and one or more images thereof may be included in physical data **262b**. At this stage, image data may depict a subset of pink blossom buds that include at least one blossom, such as a “king blossom,” in an image.

[0082] Multi-blossom data **264h** may include data associated with a stage of growth relative to a “multi-blossom” stage of growth (also known as a “full bloom” stage). One or more images of an agricultural object in a “multi-blossom” stage of growth may be included in associated physical data **262b**. At this stage, image data may depict a number of blossoms (e.g., after pink blossom buds bloom). Petal fall data **264j** may include data based on a transition from a “multi-blossom” stage to a “petal fall” stage of growth. One or more images of an agricultural object in a “petal fall” stage of growth may be included in associated physical data **262b**. At this stage, image data may depict a cluster of blossoms that have a threshold amount of lost petals (e.g., 60% to 80% fallen) that have detached from a central structure in an image. Fruit **264k** may include data based on transitioning from a “petal fall” stage to a “fruit” stage of growth (also known as a “fruit set” stage). One or more images of an agricultural object in a “fruit” stage of growth may be included in associated physical data **262b**. At this stage, image data may depict a number of fruit (e.g., one or more apples relative to a cluster).

[0083] Limb data **264** may include status data **264a** that may identify or classify a limb (e.g., a branch, a shoot, etc.) as being in a particular state at one point in time, which may be determined (at another point in time) to be in another state when the limb develops and grows. For example, limb data **264** can include data specifying a limb as being in a “non-supportive” state (i.e., the limb size and structure may be identified as being less likely to support growth of one or more apples to harvest). In this state, an agricultural treatment delivery system may be configured to apply a treatment, such as a growth hormone, to promote growth of the limb into, for example, a “supportive” state to facilitate growth of apples. Physical data **264b** may describe any attribute or characteristic of an agricultural object identified as a limb. For example, physical data **264b** may include a shape, size, color, orientation, anomaly, or the like, including image data, or any characteristic that may be associated with a limb as an agricultural object. Similarly, trunk/stem data **266** may include status data **266a** that may identify or classify a trunk or a stem (or a portion thereof) as being in a particular state at a point in time, whereas physical data **266b** may describe any attribute or characteristic of an agricultural object identified as a trunk or stem (or a portion thereof). For example, physical data **266b** may include a shape, size, dimensions, color, orientation, anomaly, or the like, including image data, or any characteristic that may be associated with a trunk or a stem as an agricultural object.

[0084] Biotic object data **272** may describe a living organism present in an ecosystem or a location in a geographic boundary. For example, biotic object data **272** may include status data **272a** that may identify a type of bacteria, a type of fungi (e.g., apple scab fungus), a plant (e.g., a non-crop plant, such as a weed), and an animal (e.g., an insect, a rodent, a bird, etc.), and other biotic factors that may influence or affect growth and harvest of a crop. Status data **272a** may also identify describe any attribute or characteristic of a biotic object. Positioning data **272b** may include data describing whether a biotic object is positioned relative to, or independent from, another agricultural object (e.g., apple scab fungus may be identified as being positioned on an apple, which is another agricultural object). Positioning data **272b** may be configured to locate or validate a spatial location of a biotic object as agricultural object data **251**.

[0085] Abiotic object data **274** may describe a non-living element (e.g., a condition, an

environmental factor, a physical element, a chemical element, etc.) associated with an ecosystem or a location in a geographic boundary that may influence or affect growth and harvest of a crop. For example, abiotic object data **274** may include status data **274a** that may identify soil constituents (e.g., pH levels, elements, and chemicals), a time of day when abiotic data is sensed, amounts, intensities, directions of light, types of light (e.g., visible, ultraviolet, and infrared light, etc.), temperature, humidity levels, atmospheric pressure levels, wind speeds and direction, amounts of water or precipitation, etc. Positioning data **272b** may include data describing whether an abiotic object is associated with another agricultural object, or any other data configured to locate or validate a spatial location of an abiotic object, such as portion of soil that may be acidic. Further, agricultural object data **251** may include any other data **280**, which may include any other status data **280a** and/or any other supplemental data **280b**.

[0086] Further to FIG. 2B, precision agricultural management platform **201** may include analyzer logic **203** and a policy generator **205**. Analyzer logic **203** may be configured to implement computer vision algorithms and machine learning algorithms (or any other artificial intelligence-related techniques), as well as statistical techniques, to construct and maintain a spatial semantic model as well as a time-series model of physiology and/or physical characteristics of a crop (or any other agricultural object, such as a limb or branch) relative to a stage-of-growth. Analyzer logic **203** may be further configured to predict a next state or stage of growth and an associated timing (e.g., a point in time or a range of time) at which a transition may be predicted. Hence, analyzer logic **203** may be configured to generate predicted data **282** that may include predicted status data **282a** to describe a predicted status of an agricultural object associated with indexed identifier data **254**. For example, a predicted status of a cluster of blossoms, as an agricultural object, may specify a predicted transition from a single opened blossom (e.g., a king blossom as an agricultural object) to one or more lateral blossoms opening (e.g., as corresponding agricultural objects), as well as a predicted range of time during which the predicted state transition may (likely) occur. Predicted data **282** may include predicted image data **282b** that may be provided or transmitted to agricultural treatment delivery system **211** to facilitate detecting and identifying an agricultural object. Predicted image data **282b** may be used to determine whether it may have transitioned from one state to the next (e.g., since previously being sensed or monitored). Further, predicted data **282** may include predicted action data **282c** and any other predicted data **282d**, which may facilitate navigation and positioning of an emitter to apply a treatment optimally (e.g., emitting an agricultural projectile within a range of accuracy and/or a range of precision), for example, as a function of context (e.g., season, stage of growth, associated biotic and abiotic conditions, time of day, amount of sunlight, etc.).

[0087] In some examples, policy generator **205** may be configured to analyze a status (e.g., a current or last sensed status) of an agricultural object and a predicted status, and may be further configured to derive one or more actions as action data **290** as a policy. Action data **290** may be implemented as policy data that is configured to guide performance of one or more treatments to an agricultural object. For example, action data **290** associated with an agricultural object identified as a king blossom may include data representing a policy (e.g., a definition, rules, or executable instructions) to perform an action (e.g., pollinate a king blossom), whereas action data **290** associated with an agricultural object identified as a lateral blossom (e.g., in association with a cluster including a king blossom) may include policy data to perform a thinning action to terminate growth of the lateral blossom. Action data **290** may also include data representing prior actions performed as well as results based on those prior actions, as well as any other action-related data.

[0088] FIG. 3 is an example of a flow diagram to control agricultural treatment delivery system autonomously, according to some embodiments. At **302**, flow **300** begins to receive data configured to implement a policy to perform an action in association with an agricultural object. In some cases, data representing one or more actions to be performed relative to a subset of agricultural objects may be received at, for example, an agricultural treatment delivery system. Policy data may be

configured to implement an action based on a context associated with an agricultural object, such as a stage of growth during which, for example, pests and weeds may be more prominent than in other time intervals.

[0089] At **304**, data representing a subset of agricultural objects may be received. In some cases, each agricultural object may be associated with data representing an identifier. The data representing each of the agricultural objects may be indexed into a data repository. Further, the data representing each of the agricultural objects may be received from, or otherwise originate at, a precision agricultural management platform, which may include one or more processors configured to analyze sensor data (e.g., image data) captured from one or more sensors at, for example, an agricultural treatment delivery system. The sensor data may be analyzed to validate recently captured sensor data (e.g., for an agricultural object) correlates with at least a subset of indexed agricultural object data (e.g., previously sensed data for a specific agricultural object). Also, the sensor data may be analyzed to determine a stage of growth or any other agriculturally-related condition for which a treatment may be applied or delivered. Further, the image data may be used to form a modified or predicted image of an agricultural object at the precision agricultural management platform.

[0090] As an agricultural treatment delivery system traverses adjacent to arrangements of agricultural objects (e.g., fruit trees), sensed image data from one or more cameras may be compared to data representing a predicted image of the agricultural object. The predicted image may be derived at a precision agricultural management platform to predict a change in an image or physical appearance (or any other characteristic) based on predicted growth of an agricultural object. The predicted image then may be used to detect the corresponding agricultural object in a geographic boundary to which a treatment may be applied.

[0091] At **306**, a mobility platform may be activated to control autonomously motion and/or position of an agricultural treatment delivery vehicle. A mobility platform may be configured to implement a map, which may include data configured to position one or more emitters of an agricultural projectile delivery system adjacent to an agricultural object within a geographic boundary. Hence, a map may include data specifying a location of an indexed agricultural object, and can be used to navigate a vehicle autonomously to align an emitter with an agricultural object to deliver a treatment.

[0092] At **308**, an agricultural object may be detected based on or in association with one or more sensors (e.g., one or more image capture devices). Image data of an agricultural object may be generated to form an imaged agricultural object. Then, the imaged agricultural object may be correlated to data representing an indexed agricultural object in a subset of agricultural objects. A correlation may validate that the imaged agricultural object is a same object as described in data associated with the indexed agricultural object. Further, a spatial position of an imaged agricultural object may be correlated to a position and/or an orientation of an emitter.

[0093] At **310**, an emitter from a subset of one or more emitters may be selected to perform an action. Further, a corresponding action to be performed in association with a particular agricultural object may be identified, the agricultural object being an actionable object (e.g., an agricultural object for which an action is performed, whether chemical or mechanical, such as robotic pruners or de-weeding devices). In some cases, an optical sight associated with an emitter may be identified, and a corresponding action may be associated with the optical sight to determine a point in time to activate emission of an agricultural projectile.

[0094] At **312**, an agricultural treatment may be emitted as a function of a policy. For example, an emitter may be activated to align an emitter to a spatial position (e.g., at which an agricultural object may be disposed). Upon alignment, propulsion of an agricultural projectile may be triggered to intercept an agricultural object.

[0095] In an implementation in which a vehicle including an agricultural treatment delivery system is controlled manually, logic in association with an agricultural treatment delivery system may be

configured to detect displacement of the vehicle and compute a spatial position of an emitter. Further, an agricultural treatment delivery system may be configured to detect a point or a line (e.g., an optical ray) at which a spatial position of an emitter intersects a path specified by a map. The path may be associated with a subset of agricultural objects for which one or more emitters may be configured to perform a subset of actions. Also, a subset of agricultural objects may be detected in association with one or more sensors. A subset of actions may be identified to be performed in association with a subset of agricultural objects, such as a number of blossoms on one or more trees. One or more emitters may be selected autonomously to perform a subset of actions, whereby one or more emitters may emit a subset of agricultural projectiles to intercept a subset of agricultural objects. In one instance, at least two different agricultural projectiles may be emitted to perform different actions.

[0096] In a vehicle that includes an agricultural treatment delivery system, and is controlled autonomously, logic in association with an agricultural treatment delivery system may be configured to generate control signals (e.g., at a mobility platform) to drive the vehicle autonomously, compute a spatial position of the vehicle relative to, for example, an agricultural object, and calculate a vehicular trajectory to intersect a path based on, for example, data representing a map. Further, a spatial position of an emitter may be determined to be adjacent to a path specified by the map, the path also being associated with a subset of agricultural objects for which one or more emitters are configured to perform a subset of actions. In some examples, a rate of displacement of the vehicle may be adjusted autonomously to, for example, enhance accuracy, an amount of dosage, or the like. Upon detect a subset of agricultural objects in association with one or more sensors, one or more emitters may be configured to emit a subset of agricultural projectiles to intercept the subset of agricultural objects at the rate of displacement.

[0097] In at least one implementation, control signals to drive the vehicle autonomously may be supplemented by receiving a first subset of data representing a vehicular trajectory, the data being generating at a teleoperator controller. One or more emitters may emit a subset of agricultural projectiles responsive to a second subset of data originating at the teleoperator controller.

[0098] FIG. 4 is a functional block diagram depicting a system including a precision agricultural management platform communicatively coupled via a communication layer to an agricultural treatment delivery vehicle, according to some examples. Diagram 400 depicts a mobility controller 447 disposed in an agricultural treatment delivery vehicle 430, which, in turn, may include any number of sensors 470 of any type. One or more sensors 470 may be disposed within, or coupled to, either mobility controller 447 or an agricultural treatment delivery system 420, or both. Sensors 470 may include one or more Lidar devices 472, one or more cameras 474, one or more radars 476, one or more global positioning system (“GPS”) data receiver-sensors, one or more inertial measurement units (“IMUs”) 475, one or more odometry sensors 477 (e.g., wheel encoder sensors, wheel speed sensors, and the like), and any other suitable sensors 478, such as infrared cameras or sensors, hyperspectral-capable sensors, ultrasonic sensors (or any other acoustic energy-based sensor), radio frequency-based sensors, etc.

[0099] Other sensor(s) 478 may include air flow-related sensors to determine magnitudes and directions of ambient airflow relative to agricultural treatment delivery system 420 and one or more emitters configured to emit an agricultural projectile 412. Air flow-related sensors may include an anemometer to detect a wind speed and a wind vane to detect wind direction. Values of wind speed and direction may be determined relative to a direction and velocity of agricultural treatment delivery vehicle 430, and may further be used to adjust a time at which to emit agricultural projectile 412 and/or modify a trajectory as a function of windage (e.g., wind speed and direction). In some cases, wheel angle sensors configured to sense steering angles of wheels may be included as odometry sensors 477 or suitable sensors 478. Sensors 470 may be configured to provide sensor data to components of mobility controller 447 and/or agricultural treatment delivery vehicle 430, as well as to elements of precision agricultural management platform 401. As shown in diagram 400,

mobility controller **447** may include a planner **464**, a motion controller **462**, a motion estimator/localizer **468**, a perception engine **466**, and a local map generator **440**. Note that elements depicted in diagram **400** of FIG. **4** may include structures and/or functions as similarly-named elements described in connection to one or more other drawings.

[0100] Motion estimator/localizer **468** may be configured to localize agricultural treatment delivery vehicle **430** (i.e., determine a local pose) relative to reference data, which may include map data, route data, and the like. Route data may be used to determine path planning over one or more paths (e.g., unstructured paths adjacent to one or more plants, crops, etc.), whereby route data may include paths, path intersections, waypoints (e.g., reflective tape or other visual fiducial markers associated with a trellis post), and other data. As such, route data may be formed similar to road network data, such as RNDF-like data, and may be derived and configured to navigate paths in an agricultural environment. In some cases, motion estimator/localizer **468** may be configured to identify, for example, a point in space that may represent a location of agricultural treatment delivery vehicle **430** relative to features or objects within an environment. Motion estimator/localizer **468** may include logic configured to integrate multiple subsets of sensor data (e.g., of different sensor modalities) to reduce uncertainties related to each individual type of sensor. According to some examples, motion estimator/localizer **468** may be configured to fuse sensor data (e.g., Lidar data, camera data, radar data, etc.) to form integrated sensor data values for determining a local pose. According to some examples, motion estimator/localizer **468** may retrieve reference data originating from a reference data repository **405**, which may include a map data repository **405a** for storing 2D map data, 3D map data, 4D map data, and the like. Motion estimator/localizer **468** may be configured to identify at least a subset of features in the environment to match against map data to identify, or otherwise confirm, a position of agricultural treatment delivery vehicle **430**. According to some examples, motion estimator/localizer **468** may be configured to identify any amount of features in an environment, such that a set of features can be one or more features, or all features. In a specific example, any amount of Lidar data (e.g., most or substantially all Lidar data) may be compared against data representing a map for purposes of localization. In some cases, non-matched objects resulting from a comparison of environment features and map data may be classified as a dynamic object. A dynamic object may include a vehicle, a farm laborer, an animal, such as a rodent, a bird, or livestock, etc., or any other mobile object in an agricultural environment. Note that detection of dynamic objects, including obstacles, such as fallen branches in a path, may be performed with or without map data. In particular, dynamic or static objects may be detected and tracked independently of map data (i.e., in the absence of map data). In some instances, 2D map data and 3D map data may be viewed as “global map data” or map data that has been validated at a point in time by precision agricultural management platform **401**. As map data in map data repository **405a** may be updated and/or validated periodically, a deviation may exist between the map data and an actual environment in which agricultural treatment delivery vehicle **430** is positioned. Therefore, motion estimator/localizer **468** may retrieve locally-derived map data generated by local map generator **440** to enhance localization. For example, locally-derived map data may be retrieved to navigate around a large puddle of water on a path, the puddle being omitted from global map data.

[0101] Local map generator **440** is configured to generate local map data in real-time or near real-time. Optionally, local map generator **440** may receive static and dynamic object map data to enhance the accuracy of locally-generated maps by, for example, disregarding dynamic objects in localization. According to at least some embodiments, local map generator **440** may be integrated with, or formed as part of, motion estimator/localizer **468**. In at least one case, local map generator **440**, either individually or in collaboration with motion estimator/localizer **468**, may be configured to generate map and/or reference data based on simultaneous localization and mapping (“SLAM”) or the like. Note that motion estimator/localizer **468** may implement a “hybrid” approach to using map data, whereby logic in motion estimator/localizer **468** may be configured to select various

amounts of map data from either map data repository **405a** or local map data from local map generator **440**, depending on the degrees of reliability of each source of map data. Therefore, motion estimator/localizer **468** may use out-of-date map data in view of locally-generated map data.

[0102] In various examples, motion estimator/localizer **468** or any portion thereof may be distributed in or over mobility controller **447** or agricultural treatment delivery system **420** in any combination. In one example, motion estimator/localizer **468** may be disposed as motion estimator/localizer **219a** in agricultural treatment delivery system **420**. Also, agricultural treatment delivery system **420** may also include sensors **470**. Therefore, agricultural treatment delivery system **420** may be configured to autonomously apply treatments to agricultural objects independent of mobility controller **447** (i.e., agricultural treatment delivery vehicle **430** may navigate manually). In another example, agricultural treatment delivery vehicle **430** may navigate autonomously. Hence, motion estimator/localizer **468** may be disposed in either mobility controller **447** or agricultural treatment delivery system **420**, with its functionalities being shared by mobility controller **447** and agricultural treatment delivery system **420**. According to some examples, motion estimator/localizer **468** may include NavBox logic **469** configured to provide functionalities and/or structures as described in U.S. Provisional Patent Application No. 62/860,714 filed on Jun. 12, 2019 and titled “Method for Factoring Safety Components into a Software Architecture and Software and Apparatus Utilizing Same.”

[0103] Perception engine **466** may be configured to, for example, assist planner **464** in planning routes and generating trajectories by identifying objects of interest (e.g., agricultural objects) in a surrounding environment in which agricultural treatment delivery vehicle **430** is traversing. As shown, perception engine **466** may include an object detector **442a** configured to detect and classify an agricultural object, which may be static or dynamic. Examples of classifications with which to classify an agricultural object includes a class of leaf, a class of bud (e.g., including leaf buds and fruit buds), a class of blossom, a class of fruit, a class of pest (e.g., insects, rodents, birds, etc.), a class of disease (e.g., a fungus) a class of a limb (e.g., including a spur as an object), a class of obstacles (e.g., trellis poles and wires, etc.), and the like. Object detector **442a** may be configured to distinguish objects relative to other features in the environment, and may be configured to further identify features, characteristics, and attributes of an agricultural object to confirm that the agricultural object relates to an indexed agricultural object and/or policy stored in memory **421**. Further, perception engine **466** may be configured to assign an identifier to an agricultural object that specifies whether the object is (or has the potential to become) an obstacle that may impact path planning at planner **464**. Although not shown in FIG. 4, note that perception engine **466** may also perform other perception-related functions, predicting “freespace” (e.g., an amount of unencumbered space about or adjacent an agricultural object) or whether a subset of agricultural objects (e.g., leaves) may obstruct agricultural projectile trajectories directed to another subset of agricultural objects (e.g., blossoms) to calculate alternative actions or agricultural projectile trajectories. In some examples, object detector **442a** may be disposed in SenseBox logic **442**, which may be configured to provide functionalities and/or structures as described in U.S. Provisional Patent Application No. 62/860,714 filed on Jun. 12, 2019 and titled “Method for Factoring Safety Components into a Software Architecture and Software and Apparatus Utilizing Same.”

[0104] Planner **464** may be configured to generate a number of candidate vehicle trajectories for accomplishing a goal of traversing within a geographic boundary via a number of available paths or routes, and planner **464** may further be configured to evaluate candidate vehicle trajectories to identify which subsets of candidate vehicle trajectories may be associated with higher degrees of confidence levels of providing collision-free paths adjacent one or more plants. As such, planner **464** can select an optimal vehicle trajectory based on relevant criteria for causing commands to generate control signals for vehicle components **450** (e.g., actuators or other mechanisms). Note

that the relevant criteria may include any number of factors that define optimal vehicle trajectories, the selection of which need not be limited to reducing collisions. In some cases, at least a portion of the relevant criteria can specify which of the other criteria to override or supersede, while maintain optimized, collision-free travel. In some examples, planner **464** may include ActionBox logic **465**, which may be configured to provide functionalities and/or structures as described in U.S. Provisional Patent Application No. 62/860,714 filed on Jun. 12, 2019 and titled “Method for Factoring Safety Components into a Software Architecture and Software and Apparatus Utilizing Same.”

[0105] In some examples, motion controller **462** may be configured to generate control signals that are configured to cause propulsion and directional changes at the drivetrain and/or wheels of agricultural treatment delivery vehicle **430**. In this example, motion controller **462** is configured to transform commands into control signals (e.g., velocity, wheel angles, etc.) for controlling the mobility of agricultural treatment delivery vehicle **430**. In the event that planner **464** has insufficient information to ensure a confidence level high enough to provide collision-free, optimized travel, planner **464** can generate a request to teleoperator controller **404** (e.g., a teleoperator computing device), for teleoperator support. In some examples, motion controller **462** may include SafetyBox logic **443**, which may be configured to provide functionalities and/or structures as described in U.S. Provisional Patent Application No. 62/860,714 filed on Jun. 12, 2019 and titled “Method for Factoring Safety Components into a Software Architecture and Software and Apparatus Utilizing Same.”

[0106] Autonomous vehicle service platform **401** includes reference data repository **405**, a map updater **406**, and an object indexer **410**, among other functional and/or structural elements. Note that each element of autonomous vehicle service platform **401** may be independently located or distributed and in communication with other elements in autonomous vehicle service platform **401**. Further, any component of autonomous vehicle service platform **401** may independently communicate with the agricultural treatment delivery vehicle **430** via the communication layer **402**. Map updater **406** is configured to receive map data (e.g., from local map generator **440**, sensors **460**, or any other component of mobility controller **447**), and is further configured to detect deviations, for example, of map data in map data repository **405a** from a locally-generated map. Map updater **406** may be configured to update reference data within repository **405** including updates to 2D, 3D, and/or 4D map data. Object indexer **410** may be configured to receive data, such as sensor data, from sensors **470** or any other component of mobility controller **447**. According to some embodiments, a classification pipeline of object indexer **410** may be configured to annotate agricultural objects (e.g., manually by a human and/or automatically using an offline labeling algorithm), and may further be configured to train a classifier (e.g., on-board agricultural treatment delivery vehicle **430**), which can provide real-time classification of agricultural object types during autonomous operation. In some examples, object indexer **410** may be configured to implement computer vision and machine learning algorithms to construct and maintain a spatial semantic model (e.g., at resolutions of sub-centimeter, or less) and/or a time-series model of plant physiology and state-of-growth. Data representing any of these models may be linked to, or disposed in, data representing indexed agricultural object data.

[0107] Agricultural treatment delivery system **420** may include hardware or software, or any combination thereof, and may include a memory **421**, a motion estimator/localizer **219a**, a target acquisition processor **422**, a trajectory processor **424**, an emitter propulsion subsystem **426**, and calibration logic **409**. Memory **421** may be configured to store policy data to specify an action or treatment for an associated indexed agricultural object, and may also store indexed agricultural object data (e.g., describing a specific agricultural object of interest, including identifier data and image data, which may be predicted). Motion estimator/localizer **219a** may be configured to determine a position of agricultural treatment delivery system **420** or an emitter relative to an agricultural object targeted for treatment. Target acquisition processor **422** may be configured to

sense or otherwise detect an agricultural object, such as a blossom, that may be identified in association with indexed agricultural object data. Hence, target acquisition processor **422** may acquire an agricultural object as a target for treatment, whereby an acquired agricultural object may be detected in a subset of pixels in image data. Trajectory processor **424** may be configured to track an acquired agricultural object as a subset of pixels in image data relative to, for example, an optical sight. In event the tracked subset of pixels aligns with the optical sight, trajectory processor **424** may generate a control signal to initiate delivery of a payload (i.e., a treatment) as agricultural projectile **412**. Responsive to receiving a control signal, emitter propulsion subsystem **426** may be configured to propel agricultural projectile **412** toward a target. Calibrator **409** may include logic configured to perform calibration of various sensors, such as image sensors, of the same or different types. In some examples, calibrator **409** may be configured to compute a trajectory direction (e.g., in Cartesian space (x, y, z) and/or orientation of an emitter (e.g., roll, pitch and yaw). As such, a position and orientation of an emitter may be calibrated to intercept a target, such as visual fiducial marker or a laser light beam on a surface, whereby a pixel associated with an optical sight may cause an agricultural projectile **412** to be emitted when a subset of pixels of target in an image aligns with a subset of pixels associated with an optical sight. In this example, alignment of an optical sight to a target may be in line with an optical ray extending through the optical sight. [0108] FIG. 5 is a diagram depicting another example of an agricultural treatment delivery system, according to some examples. Diagram **500** depicts an agricultural projectile delivery system **581** implemented as an agricultural treatment delivery system, whereby agricultural projectile delivery system **581** may be configured to detect an agricultural object, identify a course of action (e.g., based on policy data), track an image of the agricultural object, and emit an agricultural projectile **512** to intercept an agricultural object as a target. Agricultural projectile delivery system **581** may include one or more image capture devices, such as a camera **504** and a Lidar **505**, the imaged sensor data from each may or may not be integrated or “fused,” according to various examples. As shown, one or more image capture devices **504** and **505** may be configured to capture an image of an agricultural environment **501** in a field of view of, for example, image capture device **504**, the captured image being received into agricultural projectile delivery system **581** via, for example, sensor data **576**, as agricultural environment image **520**.

[0109] In accordance with some examples, agricultural projectile delivery system **581** includes one or more emitters **503** disposed in a field of view between image capture device **504** and objects of interest, such as agricultural objects disposed in agricultural environment **501**. Therefore, emitters **503** may be presented as image data **511** in agricultural environment image **520**, the image data **511** of emitters thereby occluding images of one or more agricultural objects in agricultural environment **501**. In examples in which image data **511** obscures or occludes a portion of agricultural environment **501**, agricultural projectile delivery system **581** may be configured to generate optical sights **513** that, at least in some cases, may be coaxial with an orientation of an aperture of a corresponding emitter. For example, an optical sight **513a** may be centered coaxially about a line **514** coincident with a trajectory direction of a corresponding aperture. Further, line **514** may be an optical ray extending from at least one pixel in a subset of pixels associated with a center of **513a** (or any other portion of an optical sight) to a target in agricultural environment **501**. In at least one implementation, an emitter may be a nozzle and an aperture may refer to a nozzle opening.

[0110] Agricultural environment image **520** includes image data representing one or more agricultural objects, such as objects **522** to **529**. Object **522** is a blossom, object **524** is an open cluster, object **525** is a spur, object **527** is a leaf or other foliage, and object **529** is a portion of a trunk or stem. Other objects—as agricultural objects—based on agricultural applications, associations, and implementations, may be depicted in agricultural environment image **520**, such as a post **532**, a wire **533**, soil **534**, and a marker **531**, among others. Marker **531** may be detected and analyzed to determine positioning information, to facilitate in-situ positioning or calibration, or to

perform any other function.

[0111] Note that image frame **509** and image data **511** of emitters **503** may be affixed to a frame of reference of, for example, an agricultural treatment delivery vehicle (not shown) as it travels in direction **543**, at least in this example. Therefore, objects within image frame **509** including agricultural objects **522** to **529** may traverse agricultural environment image **520** in a direction of image travel **541**. Consequently, agricultural objects for which a treatment may be applied may move toward, for example, an array of optical sights **513** (e.g., to the right in diagram **500**).

[0112] Agricultural projectile delivery system **581** may be configured to receive policy data **572** to specify an action, a treatment, or the like for an agricultural object, as well as indexed object data **574** to provide data (including imagery data for comparison) that specifies any number of characteristics, attributes, actions, locations, etc., of an agricultural object. Agricultural projectile delivery system **581** may receive or derive sensor data **576** (e.g., image data, wind speed data, wind direction data, etc.) as well as position data **578** (e.g., a position of an agricultural object). Agricultural projectile delivery system **581** also may be configured to receive any other types of data.

[0113] Agricultural projectile delivery system **581** is shown to include a target acquisition processor **582**, a trajectory processor **583**, and an emitter propulsion subsystem **585**. In various examples, target acquisition processor **582** may be able to identify an agricultural object, such as object **522**, that may be correlatable to a subset of indexed agricultural object data **574**, which may include previously-sensed data and data predicting an image of the identified agricultural object with a predicted amount of growth. Among other things, a predicted image may facilitate image-based identification of a uniquely identified agricultural object among many others in geographic location, such as an orchard. Further, target acquisition processor **582** may detect whether policy data **572** specifies whether an action is to be taken. If not, one or more sensors may monitor and capture data regarding a non-targeted identified agricultural object. As a non-targeted object, however, it need not be tracked as a target (e.g., identifying an optical sight may be omitted as well as a treatment). In some cases, an identified agricultural object may be associated with an action, such as object **522**. Trajectory processor **583** may be configured to select an optical sight for implementing an action, and may be further configured to track an identified agricultural object indicated as requiring treatment as its image data traverses in direction **541**. Trajectory processor **583** may also be configured to predict an emission parameter (e.g., emission time) at which an agricultural object aligns with an optical sight. At a detected emission time, trajectory processor **583** may generate a control signal to transmit to emitter propulsion subsystem **585**, which, in turn may activate an emitter to propel agricultural projectile **512** to intercept object **522** at a calculated time.

[0114] FIG. **6** is an example of a flow diagram to align an emitter to a target autonomously, according to some embodiments. Flow **600** begins at **602**, at which sensor data representing presence of agricultural objects disposed in an agricultural environment may be received. In some examples, an image capture device, such as a camera, may capture an image of one or more agricultural objects in a subset of agricultural objects. Also, image data representing a number of agricultural objects in a field of view of an image capture device may be received at **602**. Consider that the one or more agricultural objects are blossoms. The image capture device may receive light (e.g., reflective sunlight) from an agricultural object in a field of view of image capture device. Image data representing the agricultural object may be captured at any rate (e.g., 30 frames a minute, or fewer or more). In one example, reflective light may be received from an agricultural object in one or more time intervals during which reflective light is visible (e.g., within a visible light spectrum, such as when sunlight is available). In other examples, the reflected light received into an image capture device may be infrared light or any other spectrum of light. As such, an agricultural treatment delivery system may operate in the absence of sunlight. In at least one embodiment, one or more emitters may be disposed in between an image capture device and an

agricultural object. For example, one or more emitters may be disposed or positioned in a field of view of a camera, whereby an aperture of an emitter (e.g., aperture of a nozzle) may be aligned coaxially with an optical ray corresponding to a pixel at the center of aperture of an emitter in a captured image. In other examples, an aperture of an emitter need not be aligned coaxially with an optical ray.

[0115] At **604**, an agricultural object may be identified as, for example, a bloom that is associated with indexed agricultural object data, which may include previously captured image data and an identifier that uniquely distinguishes the identified agricultural object from other agricultural objects throughout, for example, an orchard. A subset of agricultural objects may also be captured as image data in a field of view.

[0116] At **606**, a determination is made as to whether an identified agricultural object is correlatable to indexed data (e.g., previously sensed data regarding the agricultural object that may be processed and indexed into a data arrangement stored in a data repository). In no, flow **600** moves to **612**. If yes, flow **600** may move to **608** to determine, optionally, a spatial location of an identified agricultural object, as a function of a position of an agricultural treatment delivery vehicle or an emitter. At **610**, a spatial location of the identified agricultural object may be compared to location data in indexed agricultural object data to analyze whether the identified agricultural object is correlated to indexed data (i.e., the identified agricultural object and indexed agricultural object data relate to the same object).

[0117] At **612**, an action may be associated to data representing the identified agricultural object. For example, policy data may be linked to indexed agricultural object data, which may specify a first policy to germinate king blossoms and a second policy to terminate lateral blossoms, whereby these two policies may be implemented individually or in combination (simultaneously or nearly simultaneously). For example, consider that an identified agricultural object is identified using indexed data or other image processing that predicts a classification for the identified agricultural object, whereby the identified agricultural object is predicted to be a “king blossom.” Therefore, an action relating to the first policy (e.g., germination) may be linked to the identified agricultural object to perform that action. Note that a subset of agricultural objects of the same or different classifications (or types) may be detected in a field of view and correlated to one or more corresponding actions to be performed in association with one or more emitters.

[0118] At **614**, an identified agricultural object may be locked onto and tracked as a target for applying a treatment. In some cases, one or more optical sights may be configured to detect alignment with one or more identified agricultural objects.

[0119] At **616**, each optical sight may be predicted to align with an associated agricultural object at **616**, the optical sight being associated with an emitter. In particular, an optical sight may be selected to align with a target relative to other optical sights, the optical sight being associated with an emitter for applying a treatment to a corresponding identified agricultural object. In some cases, an emitter is oriented to emit an emission parallel (e.g., coaxially) with an optical ray extending from an optical sight to a target, the optical sight being associated with one or more pixels of an image capture device. Further, one or more agricultural objects may be tracked relative to one or more optical sights. For example, reflective light from one or more of the agricultural objects may be tracked in a field of view of an image captured by a camera. A field of view of an image capture device may be a parameter (e.g., an angle) through which observable light or electromagnetic radiation may be captured in an image, according to some examples. Also, the reflective light from an agricultural object can be captured in an image and tracked in association with a visible image portion (e.g., a non-occluded image portion).

[0120] At **618**, a trajectory of an agricultural projectile may be computed (e.g., relative to an emission parameter). In other examples, a trajectory of an agricultural projectile may be computed to adjust an orientation of an emitter, at least in one instance.

[0121] At **620**, a value of an elapsed time to alignment of an optical sight to an agricultural object

may be calculated and tracked. Based on a velocity of an agricultural treatment delivery vehicle, a time to emit an agricultural projectile may be computed and tracked. Hence, tracking an optical sight relative to an agricultural object may be a function of a rate of displacement of one or more emitters or a vehicle (e.g., relative to the soil or the agricultural environment). Further, a portion of the value of the elapsed time may be calculated. The portion of the elapsed time value may describe an amount of time during which the agricultural object is associated with an occluded image portion.

[0122] At **622**, a determination is made as to whether any of sensor data detects a variance, such as a change in emitter altitude (e.g., a bump or raised elevation, or dip or depression) or any other change in sensor data, such as a variation in vehicle speed. If there is a variance, a trajectory may be recomputed at **624** (e.g., recomputing an emission parameter associated with the trajectory). For example, if a change in emitter altitude changes relative to the ground, an initial optical sight may be misaligned. Thus, another optical sight may be selected at **626**. But if there is no variance, flow **600** moves from **622** to **628**.

[0123] At **628**, an agricultural object can be predicted to align with an optical sight to form a predicted emission parameter, which may be monitored to detect alignment of an optical sight and a target. The predicted emission parameter may be tracked in association with agricultural object. For example, a predicted emission parameter may be a predicted emission time, either a duration or elapsed amount of time, or a point in time at which alignment occurs, thereby providing a trajectory via, for example, an optical ray. Further, alignment of an agricultural object with an optical sight may be detected at the predicted emission parameter.

[0124] At **630**, an emitter is activated to apply an action based on a predicted emission parameter. Thus, emission of an agricultural projectile may be triggered at a predicted emission time. In one example, an emission time may specify a time at which a pixel associated with an optical sight is aligned with an optical ray that extends from the pixel to at least a portion of a targeted agricultural object.

[0125] FIGS. 7A and 7B depict examples of data generated to identify, track, and perform an action for one or more agricultural objects in an agricultural environment, according to some examples. FIG. 7A is a diagram depicting an image frame **700** in which an agricultural environmental image **720a** includes agricultural objects identified as targets **722a**, **722b**, **722c**, **722d**, **722e**, **722f**, **722g**, **722h**, **722j**, **724a**, and **724b**. In various examples, agricultural environmental image **720a** may be presented to a user in a graphical user interface (not shown), or may represent data calculations, derivations, functions, and the like based on image data and other data. Agricultural environmental image **720a** also includes image data **711a** representing emitters and corresponding optical sights, such as optical sights **726a**, **726b**, **726c**, **726d**, **726e**, **726f**, and **726g**.

[0126] An agricultural projectile delivery system (not shown) may be configured to identify and select optical sight **726a** (and corresponding emitter) to apply a treatment to target **722a**. Further, agricultural projectile delivery system may be configured to identify and select optical sights **726b**, **726c**, **726d**, **726e**, **726f**, **726g**, and **726g** to emit agricultural projectiles to targets **722e**, **722f**, **722b**, **722g**, **722c**, **722h**, and **722d**, respectively. Note that optical sight **726g** may be configured to propel an agricultural projectile to both target **722h** and target **722d** at, for example, different alignments. Note that dotted lines **723** may represent data configured to specify a distance **727** (e.g., a number of pixels) or a time until a target aligns with an optical sight. Solid lines **725** represent data configured to specify a distance or time subsequent to a treatment, as applied to targets **724a** and **724b**. Both targets **724a** and **724b** are depicted with crosshatch to signify that one or more treatments have been performed. Any of the above-described actions may be performed by hardware and/or software that provide functionality to an agricultural projectile delivery system. FIG. 7A depicts targets **722g**, **724a**, and **724b** being occluded by image data **711a** of emitters at a first point in time, **t1**.

[0127] FIG. 7B is a diagram depicting an image frame **750** depicting an image frame **750** in which

an agricultural environmental image **720b** includes agricultural objects identified as targets **722a**, **722b**, **722c**, **722d**, **722e**, **722f**, **722g**, **722h**, **722j**, **724a**, and **724b**, as well as targets **772x**, **772y**, and **772z**, whereby targets **772e**, **772b**, **772g**, and **772j** are occluded or partially occluded by image data **711b** of an array of emitters. Agricultural environmental image **720b** depicts a state in which targets **724a**, **724b**, **772f**, **772e**, **772g**, **772h**, and **772j** have received treatment by at least at time, **t2**. These treated targets are depicted in crosshatch. Targets identified at time, **t2**, including targets **772x**, **772y**, and **772z**, may be calculated to receive treatment at or within time, **t3**. As such, targets **772x**, **772y**, and **772z** have been associated with optical sights, such as **776z**, to detect alignment and trigger propulsion of agricultural projectiles to apply various treatments.

[0128] FIG. **7C** is a diagram depicting parameters with which to determine activation of an emitter to apply a treatment, according to some examples. FIG. **7C** depicts an image capture device **774** capturing image data representing an agricultural environment **770**, which includes a target **777z**, and image data representing an array of emitters **711c** disposed in a field of view of image capture device **774**. Hence, image capture device **774** may be configured to generate an agricultural environment image **720a** within an image frame **750a**. Logic of an agricultural projectile delivery system may be configured to identify visible image fields **785a** and **785b** in which one or more agricultural objects, such as target **777za**, are visible (i.e., not occluded). Therefore, digitized or pixelated image data associated with targets, such as target **777za**, may be observed, identified, and tracked, among other things. Logic of an agricultural projectile delivery system also may be configured to identify occluded image field **787a** associated with image data **711bb** of emitter **711c**. While pixelated data associated with target **777za** may be tracked in visible image field **785a**, it may become occluded as motion moves the image of target **777za** to an optical sight **776za**.

[0129] In at least one example, an agricultural projectile delivery system may be configured to identify target **777za** and one or more pixels association therewith (e.g., as a pixelated target **777zb**). The agricultural projectile delivery system may also be configured to derive a predicted emission parameter **790** (e.g., a predicted time) that may be used determine a point in time to activate an emitter to propel a projectile to a target. Further, an agricultural projectile delivery system may also be configured to determine a visible parameter **791a** during which visible target pixels **780a** may be analyzed to track, evaluate, and modify predicted emission parameter **790** (e.g., changes in vehicle speed, a gust of wind, or the like). The agricultural projectile delivery system may computationally predict an occluded parameter **791b** during which occluded target pixels **780b** may not be visible due to occluded image field **787a** associated with image data **711b** of the emitters. As pixels of target **777za** travel to optical sight **776za** in an occluded image field **787**, a rate at which a pixel of a target **777za** may align with optical sight **776za** may be modified based on sensor data (e.g., vehicle speed), which, in turn, may modify data values representing occluded parameter **791b**, thereby modifying an emission time.

[0130] FIG. **8** is a diagram depicting a perspective view of an agricultural projectile delivery vehicle configured to propel agricultural projectiles, according to some examples. Diagram **800** depicts an agricultural projectile delivery vehicle **810** traveling in a direction of motion **813** at a distance **815**. Further, diagram **800** depicts an agricultural projectile delivery system **811** detecting blossoms as targets **722f**, **724b**, and **724a** of FIG. **7B** and propels agricultural projectiles **812**, **814**, and **813** to intercept respective targets. In some examples, each of agricultural projectiles **812**, **814**, and **813** each may be emitted at any angle along a trajectory that lies in a plane that include an optical ray, such as optical ray **877**.

[0131] FIG. **9** is a diagram depicting an example of trajectory configurations to intercept targets autonomously using an agricultural projectile delivery vehicle, according to some examples. Diagram **900** depicts an agricultural projectile delivery vehicle **910** including an agricultural projectile delivery system **952a** configured to propel agricultural projectiles, such as agricultural projectile **912**, at any angle **909** relative to plane **911**. One or more emitters of agricultural projectile delivery system **952a** may be configured to propel agricultural projectiles via one or

more trajectories **999** to intercept any target **722f** relative to any height above ground. As shown, agricultural projectile delivery system **952a** may be configured to propel agricultural projectile **912** with a force having a vertical component (“F_{vc}”) and a horizontal component (“F_{hc}”). As shown, the vertical component of the propulsion force may be in a direction opposite than the force of gravity (“F_g”). Note that horizontal component (“F_{hc}”) may have a magnitude sufficient to propel agricultural projectile **912** over a horizontal distance to target **722f**. According to some examples, agricultural projectile delivery vehicle **910** may include an agricultural projectile delivery system **952b** configured to apply treatments via one or more trajectories **954** within a space **950**. Therefore, agricultural projectile delivery vehicle **910** may be configured to identify agricultural objects along both sides of agricultural projectile delivery vehicle **910**. For example, agricultural projectile delivery vehicle **910** may be configured to identify groups **990** and **991** of agricultural objects (e.g., fruit trees) and may simultaneously apply a treatment or different treatments to either side as agricultural projectile delivery vehicle **910** traverses a path (in the X-direction) between groups **990** and **991** of agricultural objects.

[0132] FIG. **10** is a diagram depicting examples of different emitter configurations of agricultural projectile delivery systems, according to some examples. Diagram **1000** depicts an agricultural projectile delivery vehicle **1010** having at least two exemplary configurations, each of which may be implemented separately (e.g., at different times). Configuration **1001** includes an agricultural projectile delivery system **1052a** having any number of emitters configured to emit agricultural projectiles substantially horizontally (e.g., orthogonal or substantially orthogonal to a direction of gravitational force) to target agricultural objects **722f**. Configuration **1002** includes a boom **1060** configured to support an agricultural projectile delivery system **1012** configured to identify, monitor, track, and apply a treatment via an agricultural projectile to one or more agricultural objects constituting row crops, such as soybean plant **1061a** and soybean plant **1061b**, or portions thereof.

[0133] FIG. **11** is a diagram depicting yet another example of an emitter configuration of an agricultural projectile delivery system, according to some examples. Diagram **1100** depicts an agricultural projectile delivery vehicle **1110** having an exemplary configuration in which emitters may be configured to propel an agricultural projectile via any trajectory **1112** from an encompassing structure **1125**, which may be configured to apply treatments to any nut or fruit tree having three dimensions of growth. As shown, encompassing structure **1125** may have articulating members that can be positioned in either arrangement **1160a** or **1160b**. The articulating members may include emitters to apply one or more treatments to one or more agricultural objects associated with a three dimensional vegetative structure, such as an orange tree or walnut tree. The configuration shown in diagram **1100** is not limiting and any configuration of agricultural projectile delivery system may be used to apply treatments to tree **1190**.

[0134] FIGS. **12** and **13** are diagrams depicting examples of a trajectory processor configured to activate emitters, according to some examples. Diagram **1200** of FIG. **12** includes a rear view of an array of emitters **1211** and a side view of an agricultural projectile delivery system **1230**. As shown in the rear view, array of emitters **1211** is disposed in a field of view of an image capture device **1204**. In particular, array of emitters **1211** may be interposed between a scene being imaged (e.g., agricultural environment **1210**, which includes targets **1222a**) and image capture device **1204**. In some examples, image capture device **1204** may be configured to be “in-line” with optical sights **1214** to determine alignment of an optical sight with a target, such as target **1222a**. In diagram **1200**, an array of emitters **1211** include groups **1219** of emitters that are each positioned offset in an X-direction and a Y-direction. Note, however, arrangements of emitters into groups **1219** of emitters is a non-limiting example as array of emitters **1211** may each be arranged in any position and in any orientation. Also shown in the rear view, array of emitters **1211** is opaque (e.g., depicted as a shaded region) and occludes images in agricultural environment **1210**.

[0135] Diagram **1200** also depicts an agricultural environment image **1220**, which may be

generated by image capture device **1204** and disposed within image frame **1250**. Agricultural environment image **1220** includes image data **1279** representing emitters and corresponding optical sights, such as an optical sight **1226a**. As array of emitters **1211** traverses in agricultural environment **1210**, images of target **1222a**, such as target image **1222b** in a first position may travel to a second position as target image **1222c** (e.g., a position at which target **1222a** in agricultural environment **1210** may be occluded).

[0136] Diagram **1200** also includes a trajectory processor **1283**, which may be configured to track positions of target image **1222b** and to determine a distance **1227** (or any other parameter, including time) at which an image of the target (i.e., target image **1222c**) aligns with optical sight **1226a**. Target processor **1283** may also be configured to calculate and monitor deviations of predicted distance (“D”) **1203** during which target **1222** may be occluded by array of emitters **1211**. Predicted distance **1203** may correlate to a time from which target **1222a** becomes occluded until alignment with an optical sight **1226a**. Trajectory processor **1283** may detect a point in time at which target image **1222c** aligns (or is predicted to align) with optical sight **1226a**, and in response, trajectory processor may generate control data **1229**. Control data may be transmitted to an emission propulsion system (not shown) in emitter **1230**. In addition, control data **1229** may include executable instructions or any data configured to activate emitter **1213b** to propel agricultural project **1212** to intercept **1222d**.

[0137] FIG. **13** depicts a trajectory processor **1383** configured to operate similarly or equivalently as trajectory processor **1283** of FIG. **12**. Diagram **1300** of FIG. **13** includes a rear view of an array of emitters **1311** and a side view of an agricultural projectile delivery system **1330**. As shown in the rear view, array of emitters **1311** may be disposed in a field of view of an image capture device **1304**. Therefore, array of emitters **1311** may be positioned between an agricultural environment **1310**, which includes targets **1322a**, and image capture device **1304**. In diagram **1300**, an array of emitters **1311** are arranged in a line (or substantially in a line) in a Y-direction. Note that in some cases, array of emitters **1311** may be arranged in an X-direction. In this example, a predicted distance (“D”) **1303** during which a target **1322a** may be occluded may be less than, for example, predicted distance **1203** of FIG. **12**, thereby enhancing or prolonging visibility of target **1322a** as it traverses within an image. According to other examples, each emitter may be arranged in any position and in any orientation. Also shown in the rear view, array of emitters **1311** is depicted with shading to represent that it may be opaque, and may occlude images in agricultural environment **1310**.

[0138] Diagram **1300** also depicts an agricultural environment image **1320**, generated by image capture device **1304** and disposed within image frame **1350**. Agricultural environment image **1320** includes image data **1379** representing emitters and corresponding optical sights, such as an optical sight **1326a**. As array of emitters **1311** traverses in an agricultural environment **1310**, images of target **1322a**, such as target image **1322b** in a first position may travel to a second position as target image **1322c** (e.g., a position at which target **1322a** in agricultural environment **1310** may be occluded).

[0139] Diagram **1300** also includes a trajectory processor **1383**, which may be configured to track positions of target image **1322b** and to determine a distance **1327** (or any other parameter, including time) at which an image of the target (i.e., target image **1322c**) aligns with optical sight **1326a**. Target processor **1383** may also be configured to calculate and monitor deviations of predicted distance (“D”) **1303** during which target **1322** may be occluded by array of emitters **1311**. Predicted distance **1303** may correlate to a time from which target **1322a** becomes occluded until alignment with an optical sight **1326a**. Trajectory processor **1383** may detect a point in time at which target image **1322c** aligns (or is predicted to align) with optical sight **1326a**, and in response, trajectory processor **1383** may generate control data **1329**. Control data may be transmitted to an emission propulsion system (not shown) in emitter **1330**. In addition, control data **1329** may include executable instructions or any data configured to activate emitter **1313b** to propel

agricultural project **1312** to intercept **1322d**.

[0140] FIG. **14** is a diagram depicting an example of components of an agricultural projectile delivery system that may constitute a portion of an emitter propulsion subsystem, according to some examples. Diagram **1400** includes an agricultural projectile delivery system **1430** that includes a number of emitters **1437** (or portions thereof), as well as at least one in-line camera **1401**, according to some implementations.

[0141] In one example, agricultural projectile delivery system **1430** may include a storage for compressed gas (“compressed gas store”) **1431**, which may store any type of gas (e.g., air), a gas compressor **1432** to generate one or more propulsion levels (e.g., variable levels of pressure), and a payload source **1433**, which may store any treatment or payload (e.g., a liquid-based payload), such as fertilizer, herbicide, insecticide, etc. In another example, agricultural projectile delivery system **1430** may omit compressed gas store **1431** and gas compressor **1432**, and may include a pump **1434** to generate one or more propulsion levels with which to propel a unit of payload source **1433**. In various implementations, one or more of the components shown in agricultural projectile delivery system **1430** may be included or may be omitted.

[0142] Agricultural projectile delivery system **1430** may also include any number of conduits **1435** (e.g., hoses) to couple payload source **1433** to a number of activators **1436**, each of which is configured to activate to deliver a unit of payload as, for example, an agricultural projectile, to an identified target. To illustrate operation, consider that control data **1470** is received into agricultural projectile delivery system **1430** to launch one or more units of treatment or payload. Logic in agricultural projectile delivery system **1430** may be configured to analyze control data **1470** to that identify activator **1441** is to be triggered at a point in time, or at a position that aligns a corresponding emitter **1442** to target **1460**. When activated, activator **1441** may release an amount of payload (e.g., a programmable amount) with an amount of propulsion (e.g., a programmable amount), thereby causing emitter **1442** to emit a projectile **1412**. According to some examples, agricultural projectile delivery system **1430** may be adapted for non-agricultural uses, and may be used to deliver any type of projectile, including units of solids or gases, for any suitable application.

[0143] FIG. **15** is a diagram depicting an example of an arrangement of emitters oriented in one or more directions in space, according to some examples. Diagram **1500** includes an arrangement of emitters **1537**, one or more of which may be oriented at an angle **1538** relative to, for example, the ground. Alternatively, one or more subsets of emitters **1537** may be oriented in any angle in the Y-Z plane, any angle in the X-Z plane, or at any angle or vector in an X-Y-Z three-dimensional space. In some examples, one or more optical arrays aligned with emitters **1537** may intersect at one or more locations in space, at which an image capture device may be disposed.

[0144] FIG. **16** is a diagram depicting an example of another arrangement of emitters configured to be oriented in one or more directions in space, according to some examples. Diagram **1600** includes an arrangement of emitters **1637**, whereby one or more emitters may be configurable to adjust one or more orientations to implement agricultural projectile trajectories in any direction. In this example, a subset of emitters **1637** is depicted to include emitters **1639a**, **1639b**, **1639c**, and **1639d** being oriented to, for example, select a trajectory that may optimally deliver a treatment to a target. In some implementations, orientations of each of emitters **1639a**, **1639b**, **1639c**, and **1639d** may be configured to deliver at least one agricultural projectile **1612** in the presence of obstructive objects **1640**, such as a cluster of blossoms growing over and in front of (e.g., in between) a target agricultural object **1699**. As shown, obstructive objects **1640** obstruct trajectories **1690** associated with emitters **1639a**, **1639b**, and **1639c**. Thus, an orientation and/or a position of emitter **1639d** facilitates implementing an unobstructed trajectory over which to propel agricultural object **1612** to intercept target objects **1699**.

[0145] In some examples, emitters **1639a**, **1639b**, **1639c**, and **1639d** may each be associated with a camera, such as one of cameras **1641a**, **1641b**, **1641c**, and **1641d**. Cameras **1641a**, **1641b**, **1641c**,

and **1641d** may be implemented to detect alignment (e.g., unobstructed alignment) with a target. Note that while diagram **1600** depicts cameras **1641a**, **1641b**, **1641c**, and **1641d** adjacent to corresponding emitters, any of cameras **1641a**, **1641b**, **1641c**, and **1641d** may be implemented as “in-line” cameras in which an emitter is disposed in a field of view.

[0146] According to various examples, emitters **1639a**, **1639b**, **1639c**, and **1639d** may have configurable orientations that may be fixed during application of treatments. In other examples, one or more of emitters **1639a**, **1639b**, **1639c**, and **1639d** may have programmable or modifiable orientations or trajectories. As shown, an alignment device **1638** may include logic and one or more motors to orient an emitter to align a trajectory in any direction in three-dimensional space. As such, alignment device **1638** may be configured to modify orientations of emitters in-situ (e.g., during application of treatments).

[0147] FIG. **17** is a diagram depicting one or more examples of calibrating one or more emitters of an agricultural projectile delivery system, according to some examples. Diagram **1700** includes an in-line camera **1701** and an agricultural projectile delivery system **1730** including any number of emitters, such as emitter **1713**, disposed in the field of view of in-line camera **1701**. Diagram **1700** also includes a target **1760** disposed on surface **1703** and calibration logic **1740**, which may include hardware and/or software to facilitate calibration of a trajectory of emitter **1713** to guide an emitted agricultural projectile **1712** via a calibrated trajectory to intercept target **1760**. In calibration mode, emitter **1713** may be identified or selected for calibration. In some examples, an agricultural projectile trajectory associated with emitter **1713**, such as uncalibrated trajectory **1719**, may be adjusted to align, for example, coaxially with an optical ray **1717**. In at least one alternative example, a timing of activation (e.g., a trigger or activation event at a point in time or within a time interval) may be calibrated to cause agricultural projectile **1712** to optimally intercept target **1760** within a range of accuracy and precision. In other examples, any other operational characteristic of either emitter **1713** or agricultural projectile delivery system **1730** may be calibrated, including, but not limited to, pressure, time-of-flight, rates of dispersal, windage (e.g., to compensate for airflow, whether vehicle-based or wind), etc.

[0148] Diagram **1700** also depicts an in-line targeting image **1720** generated by in-line camera **1701**. As a number of emitters are disposed in the field of view of in-line camera **1701**, a portion of optical ray **1717** may be an occluded portion **1717a**. In-line targeting image **1720**, which is a subset of image data, includes image data representing an emitter array **1730a** that may occlude visibility to target **1760**. Also included is image data representing an optical sight image **1713b**. Calibration logic **1740** may be configured to access image data to calculate adjustment parameters. In some examples, calibration logic **1740** may be configured to compute an alignment (or associated calibration parameters) of one or more pixels associated with optical sight image **1713b** to target **1760**, and through one or more points in space associated with an aperture of emitter **1712**. Hence, each of optical sight image **1713b**, emitter **1713**, and target **1760** may be calibrated to lie (or substantially lie) on an optical ray **1717**, thereby forming a calibrated trajectory. In some examples, any emitter may be calibrated to coaxially align with any optical ray that extends from any optical sight to a corresponding target. As such, one or more emitters may be calibrated within a two dimensional plane that may include optical rays extending from optical sight images (and pixels thereof) at different angles.

[0149] In a first calibration implementation, calibration logic **1740** may be configured to calculate or predict a projectile impact site **1762** at surface **1703** that may be relative to a reference of alignment. In at least some examples, a focused light source may be implemented to provide a reference alignment mark. In one implementation, a focused light source may project coherent light, such as generated by a laser **1715** (e.g., a laser pointer or other generator of a beam of laser light), as a reference mark onto surface **1703**. To calibrate emitter **1713**, a laser **1715** may be affixed in relation to uncalibrated trajectory **1719** of emitter **1713** so that emitted laser light terminates or impinges on surface **1703** (i.e., forms a reference mark) that coincides with a

projectile impact site **1762** if projectile **1712** was propelled to impact surface **1703**. Hence, a point on surface **1703** at which coherent light impinges may be aligned with projectile impact site **1762**. In this configuration, a direction of emitted laser light and a direction of emitter **1713** may be varied in synchronicity to adjust a predicted impact site **1762** (i.e., reflected laser light) to coincide with target **1760**, which may be aligned with optical array.

[0150] In some examples, calibration logic **1740** may be configured to access in-line targeting image data **1720**, or any other image data, to receive image data depicting reflected laser light emanating from predicted projectile impact site **1762**. Calibration logic **1740** may be configured to calculate one or more calibration parameters to align predicted projectile impact site **1762** with optical ray **1717**. For example, calibration logic **1740** may calculate calibration parameters that include an elevation angle and/or an elevation distance **1761** (e.g., in a Y-Z plane) as well as an azimuthal angle and/or an azimuthal distance **1763** (e.g., in an X-Z plane). In at least one implementation, a direction of emission of emitter **1713** may be adjusted to align reflected laser light with optical ray **1717** by, for example, adjusting direction of an aperture of a nozzle. Therefore, predicted impact site **1762** may be adjusted by an elevation angle and an azimuthal angle to coincide with target **1760**. Note that adjusting projectile impact site image **1762b** may cause it to become occluded in image **1720** as it is aligned with target image **1760b**.

[0151] In at least one case, to confirm calibration, a confirmatory agricultural projectile **1712** may be propelled to confirm sufficient calibration upon intercepting target **1760**. Calibration logic **1740** may be configured to detect impact of confirmatory agricultural projectile **1712** at target **1760**, and if adjustment may be available, then calibration logic **1740** may further compute calibration parameters. Target **1760** may be implemented at a horizontal distance from emitter **1713**, the horizontal distance being perpendicular or substantially perpendicular to a direction of gravity.

[0152] In a second calibration implementation, a visual fiducial marker (not shown) may be attached to a back of each emitter **1713**, and an alignment arm (not shown) may be coupled to each emitter such that an alignment arm may be configured to rotate a nozzle. The alignment arm may be manually or autonomously rotated to cause visual fiducial marker to become visible an image. When visible, calibration logic **1740** may deem emitter **1713** (e.g., a nozzle) aligned with optical ray **1717**. This implementation enables servoing to effectuate calibration using image **1720**, with optional use of target **1760**.

[0153] In yet another calibration implementation, one or more cameras, such as AR camera **1703**, may be implemented with in-line camera **1701** to calibrate an emitter trajectory, whereby AR camera and in-line camera **1701** may capture imagery in synchronicity. In this example, AR camera **1703** may be configured to facilitate imagery with augmented reality ("AR"). Hence, AR camera **1703** may be configured to generate a virtual target image **1762a** for target **1760** in calibration target image **1722**. As shown, calibration target image **1722** includes a virtual target image **1762a** that may include one or more image pixels **1770** that coincide with optical sight **1713b**. As shown, virtual target image **1762a** is not occluded by an array of emitters. Therefore, projectile impact site image **1760a**, which may be identified by reflective laser light, may facilitate adjustment to align with virtual target image **1762a**. When aligned, optical sight **1713b**, aperture direction of emitter **1713**, and target **1760** may be aligned with optical ray **1717**. In this implementation, calibration target image **1722** omits occluded imagery associated with image **1720**.

[0154] FIG. **18** is a diagram depicting another one or more examples of calibrating one or more emitters of an agricultural projectile delivery system, according to some examples. Diagram **1800** includes an in-line camera **1801** and an agricultural projectile delivery system **1830** including any number of emitters, such as emitter **1813**, disposed in the field of view of in-line camera **1801**. Diagram **1800** also includes one or more light sources **1862** disposed on surface **1803**, such as light sources **1862**. In some examples, light sources **1862** may be reflective light (e.g., reflective laser light) originated at points **1863a** and **1863b** (lasers not shown). Diagram **1800** includes calibration logic **1840** that may include hardware and/or software configured to facilitate calibration of a

trajectory **1815** of emitter **1813** to guide an emitted agricultural projectile via a calibrated trajectory to intercept a target (not shown). In calibration mode, emitter **1813** may be identified or selected for calibration. In some examples, an agricultural projectile trajectory **1815** associated with emitter **1813** may be adjusted to align, for example, coaxially with an optical ray **1817**.

[0155] In this example, emitter **1813** may be coupled (e.g., rigidly) to one or more boresights **1814**. As shown, boresight **1814a** and boresight **1814b** are affixed at a distance **1811** to emitter **1813**, and each boresight includes an interior space through which light may pass as a boresight is aligned with a source of light (or beam of light). In some examples, each interior space of boresight **1814a** and boresight **1814b** may be oriented coaxially with a line in three-dimensional space at any angle, regardless whether boresight **1814a** and boresight **1814b** are similarly or differently oriented. In this configuration, boresight **1814a** and boresight **1814b** are oriented such that when corresponding sources of light passes through each, emitter **1813** is deemed aligned with optical ray **1817**. For example, if beams of light **1818a** and **1819b**, originating at respective sources of light **1862**, are detected to pass through boresight **1814a** and boresight **1814b**, respectively, a trajectory for emitter **1813** is aligned with optical ray **1817**. Note that distance **1811** may be sufficient to enable beams of light **1818a** and **1819b** to pass through boresight **1814a** and boresight **1814b**, respectively, and be detectable as aligned beam images **1818b** and **1819b**, respectively, in in-line targeting image **1820**.

[0156] Diagram **1800** also depicts an in-line targeting image **1820** generated by in-line camera **1801**. As a number of emitters are disposed in the field of view of in-line camera **1801**, a portion of optical ray **1817** may be an occluded portion. In-line targeting image **1820**, which is a subset of image data, includes image data representing an emitter array **1830a** that may occlude visibility to a target. Also included is image data representing an optical sight image **1813b**. Calibration logic **1840** may be configured to access image data, such as aligned beam images **1818b** and **1819b**, to calculate adjustment parameters to align boresight **1814a** and boresight **1814b** to beams of light **1818a** and **1819b**, thereby causing alignment of emitter **1813** coaxially to optical ray **1817**. Calibration logic **1840** may further be configured to detect aligned beam images **1818b** and **1819b** during calibration to indicate projectile trajectory **1815** is aligned.

[0157] FIG. **19** is an example of a flow diagram to calibrate one or more emitters, according to some embodiments. Flow **1900** begins at **1902**. At **1902**, a calibration mode is entered to calibrate one or more emitters during which a trajectory of an emitter (e.g., a nozzle) may be adjusted to intercept a target, such as an agricultural object. In calibration mode, hardware and/or software may be configured to implement calibration logic to facilitate calibration. In calibration mode, an emitter of an agricultural projectile delivery system may be identified or otherwise selected for calibration. For example, an emitter may be adjusted to calibrate a trajectory of an agricultural projectile to intercept a target. Hence, an uncalibrated trajectory may be adjusted to align, for example, coaxially with an optical ray, at least in some examples.

[0158] At **1904**, a determination is made as to whether multiple cameras may be used during calibration. For example, at least one additional camera may be used to generate augmented reality-based imagery. If no, flow **1900** continues to **1906**, at which focused light sources may be implemented to calibrate alignment. Examples of focused light sources include coherent light sources (e.g., laser light sources), or any other type of light source. At **1908**, a determination is made as to whether one or more boresights may be implemented. If not, flow **1900** continues to **1910**, at which a laser beam may be aligned with an emitter aperture (e.g., trajectory) direction to align to a reference mark (e.g., laser light) that may be coincident to a predicted projectile impact site (e.g., via the trajectory). A determination is made at **1912** as to whether a reference laser light coincides with a target, which may be aligned with an optical ray. If there is not a deviation, then an emitter trajectory may be deemed calibrated. But if there is a deviation, flow **1900** continues to **1914** at which one or more calibration parameters may be determined (e.g., elevation-related parameters, azimuthal-related parameters, and the like). At **1916**, emitter (e.g., nozzle) may be adjusted relative to a number of elevation degrees or azimuthal degrees, and flow **1900** continues to

determine if another calibration adjustment results in calibration.

[0159] Referring back to **1908**, if a determination indicates a boresight is implemented, flow **1900** continues to **1930**. At **1930**, one or more boresights may be implemented with an emitter. In some cases, one or more boresights may be oriented with one or more lines, and may be rigidly affixed to an emitter. In other cases, one or more boresights need not be rigidly affixed and may be adjustably moveable relative to an emitter. At **1932**, one or more light sources may be identified for alignment, the light being reflective light from one or more lasers. At **1934**, an emitter may be adjusted manually or autonomously to align one or more boresights with one or more light sources. At **1936**, calibration may be evaluated by, for example, detecting light beams passing through each boresight. If each boresight is detected to allow light to pass through its interior, then an emitter is calibrated. Otherwise, flow **1900** continues back to **1934** to perform a next calibration operation.

[0160] Referring back to **1904**, if a determination indicates multiple camera may be used, flow **1900** continues to **1960**. At **1960**, an automated reality (“AR”)-aided calibration camera may be implemented. At **1962**, at least two cameras may be synchronized to capture images of a target or other objects in synchronicity. For example, an in-line camera and an AR camera may be synchronized such that, for example, each pixel in an image generated by the AR camera is similar or equivalent to a corresponding pixel in the in-line camera. At **1964**, a virtual target image may be generated in an image generated by an AR camera, the virtual target image including pixels associated with an optical sight in another image generated by an in-line camera. At **1966**, a laser beam aligned with a direction of an emitter may be generated. At **1968**, an emitter (or nozzle) may be adjusted to align an image of a laser beam with a virtual target image, thereby calibrating an emitter. At **1970**, calibration of an emitter may be evaluated, and may be recalibrated if so determined at **1972**. If recalibration is needed, flow **1900** returns to **1966**. Otherwise, flow **1900** terminates.

[0161] FIGS. **20** and **21** are diagrams depicting an example of calibrating trajectories of agricultural projectiles in-situ, according to some examples. Diagram **2000** of FIG. **20**, which is a rear view of exemplary calibration components, includes an agricultural projectile delivery system **2001** including a motion estimator/localizer **2019** and one or more sensors **2070**, including airflow direction sensor **2027** and airflow speed sensor **2029**. Diagram **2000** also includes a windage emitter **2017** and an emitter **2013**, as well as image capture devices **2041a** and **2041b**. Windage emitter **2017** may be configured to emit a sacrificial or test emission, such as projectile **2011a**, to determine, for example, effects of abiotic or environmental factors, including effects of a gust of wind on a trajectory of emitter **2013**. Emitter **2013** may be configured to deliver a treatment to an agricultural target **2022a** at an emission time at which target **2022a** aligns with a point at optical sight **2026a**. Note that elements depicted in diagram **2000** of FIG. **20** may include structures and/or functions as similarly-named elements described in connection to one or more other drawings.

[0162] In operation, target **2022a** may be identified as an agricultural object to which a treatment may be applied via emitter **2013**. Sensors **2070** may be used to identify a non-actionable target, such as a leaf **2023a**, to perform a windage evaluation. Hence, logic in agricultural projectile delivery system **2001** may classify leaf **2023a** as a windage target **2023a**. In some examples, windage emitter **2017** may be configured to emit an inert material, such as water, as projectile **2011a** to evaluate wind as a factor. Camera **2041a** may be used to determine whether water-based projectile **2011a** intercepts windage target **2023a**. Based on whether projectile **2011a** intercepts windage target **2023a**, a trajectory for emitter **2013** may be modified in-situ (e.g., during application of one or more treatments) to enhance probabilities that an agricultural projectile **2012a** intercepts target **2022a**. Camera **2041b** may be used to determine whether projectile **2012a** intercepts target **2022a**. Note that in some cases, windage emitter **2017** may be implemented as another emitter **2013** that applies a treatment.

[0163] FIG. **21** is a diagram **2100** that includes a top view of exemplary calibration components, whereby sensors **2027** and **2029** and cameras **2041a** and **2041b** may be implemented to adjust

trajectories of emitter **2013** to counter environmental effects including wind. Note that elements depicted in diagram **2100** of FIG. **21** may include structures and/or functions as similarly-named elements described in connection to FIG. **20** or any other one or more other drawings. In operation, consider an example in which an original trajectory **2132** of a windage projectile **2111b** may be generated by logic of agricultural projectile delivery system **2001** to counter wind as sensed by sensors **2027** and **2029**. Further, the logic may be configured to track a time to emit windage projectile **2111b**. As shown, camera **2014a** may capture imagery depicting windage projectile **2111b** being deflected onto a deflected trajectory **2133** due to, for example, wind or other external forces. In response, logic of agricultural projectile delivery system **2001** may be configured to adjust original trajectory **2137** of emitter **2013** to calculate an adjusted trajectory **2139** so that an agricultural projectile may be delivered to a target via a predicted trajectory **2136**. In some cases, adjusted trajectory **2139** may be associated with an adjusted activation time **2126b** at which emitter **2013** may propel agricultural projectile **2112b** via a predicted trajectory **2139** so as to intercept target **2022a** as if aligned with optical sight **2026a**. Note that adjusted activation time **2126b** may be adjusted from an initial activation time by an amount identified as differential activation time **2138**. In some alternative examples, payloads **2192** emitted by windage emitter **2017** and emitter **2013** may be associated with heating/cooling (“H/C”) elements **2190** to apply or extract different amounts of thermal energy. In examples in which cameras **2041a** and **2041b** are configured to detect infrared light, payloads **2192** may be elevated or cooled to different temperatures for application to agricultural objects at night time (e.g., without sunlight). Temperature differentials of payloads may be distinguishable from each other as well as from infrared light reflected from various agricultural objects. As such, one or more agricultural treatments may be applied to agricultural objects at any time of the day regardless of the presence of sunlight.

[0164] FIG. **22** is a diagram depicting deviations from one or more optical sights to another one or more optical sights, according to some examples. Diagram **2200** includes an image capture device **2204** configured to generate an agricultural environment image **2201b** based on agricultural environment **2201a**. Diagram **2200** also includes an agricultural treatment delivery vehicle **2219** with a ground-mapping sonar/radar sensor unit **2270** and a trajectory processor **2283** of an agricultural treatment delivery system **1284**. At a time, **t1**, trajectory processor **2283** may be configured to detect a first subset of optical sights for images of targets **2222a**, **2222b**, and **2222c**, and may be further configured to track movement of pixels representing images of targets **2222a**, **2222b**, and **2222c** via, for example, a projected alignment tracking line, such as line **2223**. Here, trajectory processor **2283** at time, **t1**, may be configured to select optical sight **2226b** to align with target **2222a**, select optical sight **2226c** to align with target **2222b**, and select optical sight **2226d** to align with target **2222c**.

[0165] At time, **t2**, initial positions of an array of emitters **2291** at time, **t1**, is changed to another position (e.g., relative to positions of targets **2222a** to **2222c**) and is depicted as an array of emitters **2292** at time, **t2**. For example, one or more sensors (e.g., accelerometers and the like) may detect a change in elevation **2239** as vehicle **2210** traverses uneven soil topology **2290**. Responsive to a change in elevation, a second subset of optical sights may be selected to align with targets **2222a** to **2222c**. For example, optical sight **2227a** may be selected to align with target **2222a**, optical sight **2227b** may be selected to align with target **2222b**, and optical sight **2227c** may be selected to align with target **2222c**. Therefore, trajectory processor **2283** may be configured to de-select and select any optical sight as a function of whether an optical sight is optimal. Ground-mapping sonar/radar sensor unit **2270** may be configured to scan a surface of ground topology **2290** to identify elevations (e.g., bumps) to predict changes in optical sight selection.

[0166] FIG. **23** is a diagram depicting an agricultural projectile delivery system configured to implement one or more payload sources to provide multiple treatments to one or more agricultural objects, according to some examples. Diagram **2300** includes an image capture device **2304** configured to capture an agricultural environment image **2320** of an agricultural environment **2301**,

which may include any number of plants (e.g., trees), at least in the example shown. Diagram **2300** also includes an agricultural projectile delivery system **2381** configured to identify multiple types of agricultural objects via image **2320** in agricultural environment **2301**, select an action associated with at least a subset of different types of agricultural objects, and deliver a specific treatment to a subset of agricultural objects as a function of, for example, a type or classification of agricultural object, as well as other factors, including context (e.g., season, stage of growth, etc.). Agricultural projectile delivery system **2381** may be configured to receive policy data **2372**, indexed object data **2374**, sensor data **2376**, and position data **2378**, one or more of which may be implemented as described herein. Further, agricultural projectile delivery system **2381** may be configured to select one or more payload sources **2390** (and amounts thereof) to apply as multiple agricultural projectiles either sequentially or simultaneously. For example, agricultural projectile delivery system **2381** may be configured to select different payload sources **2390** to deliver different agricultural projectiles, such as agricultural projectiles **2312a** to **2312j**. As shown, agricultural projectile delivery system **2381** may include a target acquisition processor **2382**, a trajectory processor **2383**, and an emitter propulsion subsystem **2385**, one or more of which may have one or more functionalities and/or structures as described herein. Note that elements depicted in diagram **2300** of FIG. **23** may include structures and/or functions as similarly-named elements described in connection to one or more other drawings.

[0167] In at least one example, target acquisition processor **2382** may include an object identifier **2384**, an event detector **2386**, an action selector **2388** and an emitter selector **2387**. In some implementations, functions and structures of emitter selector **2387** may be disposed in trajectory processor **2383**. Object identifier **2384** may be configured to identify and/or classify agricultural objects detected in agricultural environment image **2320** based on, for example, index object data **2374** and sensor data **2376**, among other data. To illustrate operation of object identifier **2384**, consider that object identifier **2384** may be configured to detect one or more objects **2322a** to **2329a**, each of which may be classifiable. For example, object identifier **2384** may detect and classify object **2322a** as a blossom **2322b**. Object identifier **2384** may detect and classify object **2321a** as a spur **2321b**, and may detect and classify object **2323a** as a spur **2323b**. Object identifier **2384** may detect and classify object **2324a** as a weed **2324b**, and may detect and classify object **2325a** as a rodent **2325b**. Object identifier **2384** may detect and classify object **2326a** as a disease **2326b**, such as a fungus. Object identifier **2384** may detect and classify object **2327a** as a pest **2327b**, such as a wooly aphid. Object identifier **2384** may detect and classify object **2328a** as a fruit **2328b** to be applied with an identifying liquid that operates similar to a biological “bar code” to identity provenance. And, object identifier **2384** may detect and classify object **2329a** as a leaf **2329b**.

[0168] One or more of event detector **2386** and action selector **2388** may be configured to operate responsive to policy data **2372**. Event detector **2386** may be configured to identify an event associated with one or more objects **2322a** to **2329a**. For example, event detector **2386** may be configured to detect an event for blossom **2322b**, whereby associated event data may indicate blossom **2322b** is a “king blossom.” Responsive to an event identifying a king blossom, action selector **2388** may be configured to determine an action (e.g., based on policy data **2372**), such as applying a treatment that pollinates blossom **2322b**. As another example, consider that event detector **2386** may be configured to detect an event for weed **2324b**, whereby associated event data may indicate that weed **2324b** has sufficient foliage prior to germination to be optimally treated with an herbicide. Responsive to generation of data specifying that an event identifies a growth stage of a weed, action selector **2388** may be configured to determine an action (e.g., based on policy data **2372**), such as applying a treatment that applies an herbicide to weed **2324b**. Event detector **2386** and action selector **2388** may be configured to operate similarly for any identified agricultural object.

[0169] Emitter selector **2387** is configured to identify one or more optical sights for each subset of

a class of agricultural objects (e.g., one or more optical sights may be associated with agricultural objects identified as pests **2327b**). In various examples, one or more groups of optical sights may be used to treat multiple types or classes of agricultural objects. Trajectory processor **2383** may be configured to identify each subset of optical sights configured for a type or class of agricultural object and may track identified/classified agricultural objects as they move to corresponding optical sights. Upon detecting alignment of a type or class of agricultural object as a target with an optical sight, emitter propulsion subsystem **2385** may be configured to select one of payload sources **2390** to apply a specific treatment for a type or class of target that aligns with an associated optical sight. [0170] In various examples, agricultural projectile delivery system **2381** may deliver customized treatments as agricultural projectiles to one or more types or classes of agricultural objects **2322a** to **2329a**, any treatment may be performed individually and sequentially, or in combination of subsets thereof. To apply a treatment to blossom **2322b**, one or more agricultural projectiles **2312a** originating from one of payload sources **2390** may be applied to blossom **2322b**. To apply a treatment to spur **2321b**, one or more agricultural projectiles **2312b** originating from one of payload sources **2390** may be applied to spur **2321b** to encourage growth (e.g., one or more agricultural projectiles **2312b** may include a growth hormone). To apply a treatment to spur **2323b**, one or more agricultural projectiles **2312c** originating from one of payload sources **2390** may be applied to spur **2323b** to regulate growth (e.g., one or more agricultural projectiles **2312c** may include a growth regulator to implement, for example, chemical pruning). To apply a treatment to weed **2324b**, one or more agricultural projectiles **2312d** originating from one of payload sources **2390** may be applied to weed **2324b** to terminate growth (e.g., one or more agricultural projectiles **2312d** may include an herbicide).

[0171] To apply a treatment to rodent **2325b**, one or more agricultural projectiles **2312e** originating from one of payload sources **2390** may be applied to rodent **2325b** to reduce rodent population (e.g., one or more agricultural projectiles **2312e** may include a rodenticide to disperse rodents, including voles, etc.). To apply a treatment to disease **2326b**, one or more agricultural projectiles **2312f** originating from one of payload sources **2390** may be applied to disease **2326b** to reduce a disease (e.g., one or more agricultural projectiles **2312g** may include a fungicide to reduce, for example, apple scab fungi). To apply a treatment to pest **2327b**, one or more agricultural projectiles **2312g** originating from one of payload sources **2390** may be applied to pest **2327b** to reduce an infestation of an insect (e.g., one or more agricultural projectiles **2312g** may include an insecticide to reduce, for example, wooly aphid populations). To apply a treatment to leaf **2329b**, one or more agricultural projectiles **2312h** originating from one of payload sources **2390** may be applied to leaf **2329b** to apply a foliage fertilizer or reduce leaf-related diseases (e.g., one or more agricultural projectiles **2312h** may include a fungicide to reduce, for example, peach leaf curl for peach trees). To apply a treatment to fruit **2328b**, one or more agricultural projectiles **2312j** originating from one of payload sources **2390** may be applied to fruit **2328b** to apply a biological or molecular-based tag (e.g., one or more agricultural projectiles **2312j** may include a synthetic DNA to apply to a crop to identify provenance at various degrees of resolution, such as from a portion of an orchard to a tree to an agricultural object.).

[0172] According to some examples, payload sources **2390** each may be contained a vessel that may be configured as a “cartridge,” which may be adapted for efficient connection and re-filling over multiple uses in context of employing autonomous agricultural treatment delivery vehicles as, for example, a “robotic-agricultural-vehicles-as-a-service.” In some examples, payload sources **2390** may include any type or amount of chemistries, any of which may be mixed together in-situ (e.g., during application of treatments), whereby logic in agricultural projectile delivery system **2381** may be configured to determine ratios, proportions, and components of mixtures, whereby any one of agricultural projectiles **2312a** to **2312j** may be composed of a mixture of chemistries (e.g., derived from two or more payload sources **2390**). Mixture of the chemistries may occur as an agricultural treatment delivery vehicle traverses paths when applying treatments. As such, mixing

of chemistries in real-time (or near real-time) provides for “just-in-time” chemistries for application to one or more agricultural objects. In some cases, “recipes” for mixing chemistries may be received and update in real time as a vehicle is traversing paths of an orchard. According to some examples, payload sources **2390**, as cartridges, may be configured to apply an agricultural projectile as an experimental treatment. As such, application of an experimental agricultural projectile may include applying an experimental treatment to agricultural objects to implement a test including A/B testing or any other testing technique to determine an efficacy of a treatment. [0173] FIG. **24** is an example of a flow diagram to implement one or more subsets of emitters to deliver multiple treatments to multiple subsets of agricultural objects, according to some embodiments. Flow **2400** begins at **2402**. At **2402**, sensor-based data describing an environment may be received, the sensor-based data representing agricultural objects for a geographic boundary. For example, as an agricultural projectile delivery vehicle traverses one or more paths to deliver multiple treatments to multiple subsets of agricultural objects, sensor data (e.g., image data) may also be captured for later analysis or to facilitate delivery one or more treatments to one or more agricultural objects.

[0174] At **2404**, data representing one or more subsets of indexed agricultural objects may be received. For example, each subset of indexed agricultural objects may relate to a different type or class of agricultural object. One subset of indexed agricultural objects may relate to a class or type of fruit disease, whereas another subset of indexed agricultural objects may relate to a class or type of pest. Another subset of indexed objects may relate to a class or type of stage-of-growth of, for example, a fruit bud.

[0175] At **2406**, data representing one or more policies may be received. At least one policy may be received in association with a subset of indexed agricultural objects, whereby at least one policy may specify one or more actions or treatments to be performed for a class or type of agricultural objects.

[0176] At **2408**, each agricultural object in a subset of agricultural objects may be identified. For example, indexed agricultural object data may include identifier data that uniquely relates to a unique agricultural object, such as a one cluster of apple buds, whereby the cluster of apple buds may be distinguishable for any other cluster on the tree, or throughout an orchard, or other geographic boundary. Or, a determination to apply a treatment to an agricultural object may be determined in-situ absent policy information for a particular agricultural object. For example, an agricultural object may be changed state, which had been undetected or unpredicted. Agricultural projectile delivery vehicle may detect the changed state in real time and apply a treatment absent a policy for that object.

[0177] At **2410**, an action to be applied may be selected, based on policy data, the action being linked to the agricultural object. At **2412**, an emitter may be selected to apply the action. For example, an emitter may be configured to deliver one or more units of treatment (e.g., one or more agricultural projectiles) to an agricultural object. At **2414**, a determination is made whether there is another agricultural object in a subset or class of agricultural objects. If so, flow **2400** moves back to **2410**. Otherwise, flow **2400** moves to **2416** at which a determination is made as to whether there is another subset of agricultural objects for which a treatment may be applied. If so, flow **2400** moves back to **2410**, otherwise flow **2400** moves to **2418**. At **2418**, various subsets of emitters may be activated to provide treatment to multiple sets of agricultural objects, for example, as an agricultural treatment delivery vehicle traverses over one or more paths adjacent to the multiple subsets of agricultural objects.

[0178] FIG. **25** is an example of a flow diagram to implement one or more cartridges as payload sources to deliver multiple treatments to multiple subsets of agricultural objects, according to some embodiments. According to various examples, an agricultural treatment delivery system may granularly, with micro-precision, monitor agricultural objects over time (e.g., through stages-of-growth), whereby an agricultural object may be a basic unit or feature of a tree (e.g., a leaf, a

blossom, a bud, a limb, etc.) that may be treated with micro-precision rather than, for example, spraying a plant as a whole. Therefore, implementation of one or more agricultural treatment delivery vehicles, which may operate autonomously to navigate and apply agricultural treatments, may conserve amounts of chemistries (e.g., amounts of fertilizers, herbicides, insecticides, fungicides, growth hormones, etc.). Further, as agricultural treatment delivery systems may be implemented in a fleet of autonomous agricultural treatment delivery vehicles, an entity that provides “robotic-agricultural-vehicles-as-a-service” may be able to access and use a variety of chemistries from a variety of manufacturers, including relatively expensive chemistries under research and development that are often out of the reach of small and impoverished farmers. As such, an entity can distribute costs over a broad user base, thereby enabling smaller farmers and impoverished farmers to access chemistries they might otherwise may not have access via use of an agricultural treatment delivery vehicle as described herein.

[0179] Normatively, agricultural chemicals are available for purchase predominantly in units of 275 gallons (e.g., in a tote container), 5 gallon buckets, or 2.5 gallon jugs, among others. Cost savings by buying in bulk may be less cost effective if amounts remain unused. According to various examples, autonomous agricultural treatment delivery vehicles described herein may implement “cartridges” as payload sources that facilitate ease of replacement or refilling (e.g., in-situ). For example, an autonomous agricultural treatment delivery vehicle may autonomously detect insufficient amounts of a chemistry (e.g., based on policy data that requires an action to consume that chemistry), and then may autonomously refill its payload at refilling stations located on a farm or remotely. Or, cartridges may be shipped to a destination to replace empty or near-empty cartridges.

[0180] In view of the foregoing, flow **2500** begins at **2502**. At **2502**, action data may be received, for example, to perform one or more policies. For example, action data may be received from a precision agricultural management platform configured to employ computational resources to analyze previously-recorded sensor data from autonomous agricultural treatment delivery vehicles for purposes of generating policies with which to treat numerous agricultural objects in a geographic boundary, such as in an orchard. At **2504**, a determination is made as to whether action data is received into an autonomous agricultural treatment delivery vehicle or an agricultural projectile delivery system (e.g., with manual navigation) for performing one or more policies associated with an orchard or a farm. If yes, flow **2500** moves to **2511**. At **2511**, action data may be stored in on-board memory as policy data, which may be configured to specify specific treatments that are to be applied to specific agricultural objects, at particular times and/or amounts, or in accordance with any other parameter.

[0181] At **2513**, a target acquisition processor may be configured to apply one or more actions for a subset agricultural objects. For example, the target acquisition processor may be configured to identify and enumerate each agricultural object that is identified as receiving particular action, and thus may determine an amount of payload that is to be distributed over a number of agricultural projectiles to treat a number of agricultural objects. At **2515**, computations are performed to determine whether payload sources (e.g., in cartridges) are sufficient to implement actions over a group of identified agricultural objects. At **2517**, a determination is made as to whether payload source amount is insufficient. If not, at least one cartridge may need to be charged (e.g., filled to any level) or replaced at **2519**. For example, an autonomous agricultural treatment delivery vehicle may drive autonomously to a refilling station local to, for example, an orchard or farm. As such, a cartridge may be charged with one of a germination payload (e.g., pollen) or a cluster-thinning payload (e.g., ATS/Lime Sulfur, or the like). Or, one or more cartridges may be shipped to that location. Regardless, flow **2500** moves to **2531** to optionally generate one or more maps to navigate at least one or more emitters to apply one or more actions associated with the group of identified agricultural objects. At **2533**, an autonomous agricultural treatment delivery vehicle may be navigated in accordance with the map. At **2535**, one or more emitters may be configured to execute

the actions to, for example, deliver treatments to one or more targeted agricultural objects. [0182] Referring back to **2504**, if action data is not received into an autonomous agricultural treatment delivery vehicle or an agricultural projectile delivery system, then flow **2500** continues to **2506**. At **2506**, a computing device is identified that may be configured to provision one or more cartridges to include one or more payload sources. For example, the computer device may be implemented at a geographic location at which cartridges may be provisioned at distances relatively close to a geographic boundary, such as a farm or an orchard. At **2508**, a subset of cartridges may be provisioned as a function of one or more policies with which to implement the action data. At **2510**, a determination is made as to whether a policy ought to be updated. For example, recently received sensor data may indicate, for example, a sufficient number of crops have entered a later stage of growth, which may cause flow **2500** to move to **2522** to select payloads types customized to accommodate modifications in policies (e.g., changes in payload types to be applied to agricultural objects). At **2524**, one or more cartridges may be filled, for example, remotely from a geographic boundary (e.g., an orchard) and shipped to a destination via a package-delivering service or via an entity providing an autonomous agricultural treatment delivery vehicle as a service. At **2526**, one or more cartridges may be transported to the geographical boundary for which policy data applies. At **2528**, action data (i.e., policy data) may be transmitted to an agricultural projectile delivery system for implementation along with cartridges shipped to a location at which the agricultural projectile delivery system is located.

[0183] FIGS. **26** to **31** are diagrams depicting components of an agricultural treatment delivery vehicle configured to sense, monitor, analyze, and treat one or more agricultural objects of a fruit tree through one or more stages of growth, according to some examples. FIG. **26** includes one or more components of an agricultural treatment delivery vehicle **2601**, including various vehicle components **2610** (e.g., drivetrain, steering mechanisms, etc.), a mobility platform **2614**, a sensor platform **2613**, one or more payload sources **2612**, and an agricultural projectile delivery system **2611**. Agricultural treatment delivery vehicle **2601** may be configured to identify one or more stages of growth for an agricultural object, and may be further configured to determine policies describing one or more actions or treatments to apply to various agricultural objects all year round, including a life cycle of a fruit crop from bud to harvest. Note that elements depicted in diagrams **2600** of FIG. **26** through diagram **3100** of FIG. **31** may include structures and/or functions as similarly-named elements described in connection to one or more other drawings or as otherwise described herein. Note, too, while FIGS. **26** to **31** may refer to stages of growth for an apple crop, any one or more of the functions described herein may be applicable to other fruit trees, nut trees, or any other vegetation or plant, including vegetable crops (e.g., row crops, ground crops, etc.) and ornamental plants.

[0184] In some examples, one or more policies may include various actions to provide various treatments to agricultural objects depicted in diagrams **2600** to **3100**. For example, one or more policies may include data configured to manage apple crops with an aim to “save the king” (i.e., save a king bloom). One or more policies may be implemented over one or more stages of growth of an apple-related agricultural object. Agricultural projectile delivery system **2611** may be configured to apply one or more treatments to an agricultural object, such as a bud or blossom, with micro-precision by, for example, delivering a treatment as an agricultural projectile. Thus, agricultural projectile delivery system **2611** may treat portions of an apple tree on at least a per-cluster basis as well as a per-blossom basis, according to various examples. One or more policies may be configured to perform an action to isolate a king blossom on each cluster, and to perform another action to track one or more clusters (e.g., at an open cluster stage of growth) to detect, via sensor platform **2613**, whether a king blossom (as an agricultural object) has “popped.” Also, a policy may also track whether any lateral blossoms (as agricultural objects) have remained closed. Another policy may include performing an action to germinate a king blossom and to terminate neighboring lateral blossoms of a common cluster. Thus, lateral blossom may be autonomously

terminated rather than being mechanically (e.g., manually by hand) terminated. In various examples, one or more policies configured to “save the king” may facilitate enhanced crop yields. For example, performing actions and treatments with micro-precision facilitates optimizing attributes of an apple, such as color, size, etc. Thus, agricultural projectile delivery system **2611** may assist in managing apple crops with micro-precision to enhance yields of apples that are sized optimally, for example, for packing. In some examples, about 88 apples per box may be obtained (e.g., rather than 100 apples per box). Also, terminating lateral blossom in accordance with functions and/or structures described herein facilitates increased amount of nutrients a fruit tree may supply to remaining blossoms to help produce larger, healthier fruit. A few policies may be implement to “thin a cluster,” thereby terminating each bud or blossom associated with a particular cluster. Hence, the various functions and/or structures described herein may enhance fruit production while reducing costs of labor.

[0185] Diagram **2600** depicts a portion of a limb, for example, in late winter or early spring (e.g., in the northern hemisphere) during a “dormant” stage of growth. As shown, the limb may include fruit buds **2621a**, leaf buds **2621c**, one or more spurs **2621b**, and one or more shoots **2621d**. Also shown is a fruit bud **2622** in a dormant state. One or more policies may cause agricultural projectile delivery system **2611** to inspect one or more portions of a limb to determine whether a treatment may be applied. For example, a foliar growth hormone may be applied as one or more agricultural projectiles to a spur to encourage growth. An example of a foliar growth hormone includes gibberellic acid, or gibberellin, or the like. By contrast, one or more policies may cause agricultural projectile delivery system **2611** to inspect a portion of a limb to determine whether “chemical pruning” may be implemented by applying a growth regulator (e.g., paclobutrazol or the like) as one or more agricultural projectiles.

[0186] Diagram **2700** depicts one or more buds **2722** (as agricultural objects) transitioning to a next stage of growth, such as a “half-inch” green **2724** (as an agricultural object). One or more policies may be configured to direct agricultural projectile delivery system **2611** to inspect and track development of buds **2722** and “half-inch” greens **2724**, and, if available, apply a treatment.

[0187] Diagram **2800** depicts one or more “half-inch” greens for FIG. 27 transitioning to next stages of growth, such as a “tight cluster” **2826** (as an agricultural object), or a “full/pink cluster” **2827** (as an agricultural object). Full/pink cluster **2827** may also be referred to as an open cluster. One or more policies may be configured to cause agricultural projectile delivery system **2611** to inspect and track development of agricultural objects **2826** and **2827**, and, if available, apply a treatment. For example, a determination may be made that tight cluster **2826** may be growing slower than as expected. As such, a policy may cause agricultural projectile delivery system **2611** to apply a growth hormone, with micro-precision, to tight cluster **2826** to promote growth.

[0188] Diagram **2900** depicts one or more agricultural objects **2826** and **2827** of FIG. 28 transitioning to a next stage of growth. For example, a full/pink cluster **2927** may transition into a “king blossom” stage in which a king blossom **2928** (e.g., a first blossom) opens. In various examples, agricultural projectile delivery system **2611** may be configured to apply a treatment with micro-precision to center **2928b** within a perimeter **2928a** of king blossom **2928**. For example, a policy may cause agricultural projectile delivery system **2611** to apply a treatment to center **2928b** by, for example, emitting an agricultural projectile to intercept center **2928b** to germinate the blossom. In some cases, two or more king blossoms may be germinated and saved.

[0189] Diagram **3000** depicts one or more agricultural objects **2928** of FIG. 29 transitioning to a next stage of growth. For example, a king blossom **2928** may transition into a “lateral” stage in which lateral blossoms **3029** open about king blossom **3028**. In various examples, agricultural projectile delivery system **2611** may be configured to apply a treatment with micro-precision to lateral blossoms **3029** (e.g., to the centers or portions thereof). For example, a policy may cause agricultural projectile delivery system **2611** to apply a treatment (e.g., a caustic chemical) to lateral blossoms **3029** to terminate growth of the lateral blossoms, thereby “saving the king.”

Alternatively, some policies may cause agricultural projectile delivery system **2611** to apply a caustic treatment to both lateral blossoms **3029** and a king blossom **3028**, thereby thinning an entire cluster.

[0190] Diagram **3100** depicts one or more agricultural objects **3028** and **3029** of FIG. **30** transitioning to next stages of growth. For example, lateral blossoms **3029** and king blossom **3028** may transition into a “fruit set” or “pedal fall” stage (as an agricultural object) in which petal have fallen. Also, king blossom **3028** of FIG. **30** may transition to a “fruit” stage of growth in which a fruit **3130** develops and ripens. Agricultural projectile delivery system **2611** may emit an agricultural projectile to apply a synthetic DNA to fruit **3130** to identify its origins later in the food production process. Note that other policies, such as applying herbicides, insecticides, fungicides, and the like, may be implemented at one or more of the stages of growth described in FIGS. **26** to **31**.

[0191] FIG. **32** is a diagram depicting an example of a flow to manage stages of growth of a crop, according to some examples. Flow **3200** starts at **3202**. At **3202**, an agricultural projectile delivery system may navigate autonomously to inspect, monitor, and treat one or more agricultural objects. At **3204**, sensors may be implemented to capture data representing agricultural objects. At **3205**, a predictive state of an agricultural object may be predicted, such as at a precision agricultural management platform, according to some examples. At **3206**, policy data configured to perform one or more actions for one or more agricultural objects may be accessed. At **3208**, a determination is made as to whether an action is associated with a pre-blossom stage. If so, flow **3200** moves to **3221** to apply a first subset of actions, such as applying growth hormone to a spur to promote limb growth. Otherwise, flow **3200** moves to **3210**, at which a determination is made as to whether an associated action relates to a blossom stage. If not, flow **3200** moves to **3232**. But if so, flow **3200** moves to **3223** to identify a blossom as “king” of a cluster. At **3225**, a second subset of actions may be performed, including germinating a blossom. Flow **3200** then moves to **3227**, at which a determination is made as to whether lateral blossoms are identified. If so, flow **3200** moves to **3229** to perform another action in the second subset of action, such as killing the lateral blossoms. Flow **3200** then moves to **3232**, at which a determination is made as to whether an action applies to a post-blossom stage. If so, flow **3200** moves to **3241** to perform a third subset of actions, such as applying a fungicide to a fruit exhibiting “apple scab.” Flow **3200** then moves **3234**, at which a determination is made as to whether a harvest is complete. If not, flow **3200** moves to **3202**, otherwise flow **3200** terminates. One or more of the above regarding flow **3200** may be implemented using an agricultural projectile delivery system, which may include one or more processors and one or more applications or executable instructions stored in memory.

[0192] FIG. **33** is a diagram depicting an agricultural projectile delivery vehicle implementing an obscurant emitter, according to some examples. Diagram **3300** includes an agricultural projectile delivery vehicle **3310** including an imaging device **3312** (e.g., a camera) and an optional illumination device **3314**, which may be omitted. Further, agricultural projectile delivery vehicle **3310** also may include an obscurant emitter **3321c** that is configured to generate an obscurant wall **3320** interposed between, for example, a source of backlight, such as sun **3302**, and an agricultural object **3399**. As agricultural projectile delivery vehicle **3310** traverses a path adjacent a crop, such as a fruited tree, data generated by imaging sensors may be degraded when trying to capture an image of object **3399** that is disposed in between a bright source of backlight, such as sun **3302**, and camera **3312**. Generation of obscurant wall **3320** may facilitate an increase of a dynamic range for image capture device **3312** (e.g., enhancing a ratio between a largest value and a smallest value of luminous intensity). Obscurant wall **3320** forms a dynamic (e.g., temporary) enclosure as a light barrier to reduce an amount of light from backlight source **3302** relative to the agricultural object **3399**. In some examples, obscurant emitter **3321c** may be implemented as a mist generator configured to generate portions **3332** and/or **3334** of mist or water vapor using, for example, an ultrasonic generator or transducers. Ultrasonic transducers may be configured to convert liquid

water into a mist of the one or more clouds of water droplets, which may be viewed as “eco-friendly.”

[0193] In operation, a light intensity sensor (not shown) may be configured to detect a value of luminous intensity originating, for example, from backlight source **3302**. If a value of luminous intensity exceeds a threshold value, obscurant emitter **3321c** may be configured to generate obscurant wall **3320** in, for example, a region between a medial line **3305** and backlight source **3302**. The obscurant may be directed that region using, for example, one or more blowers **3322c** or directional fans. Portions of mist or fog provides a dynamic enclosure that may not have drawbacks of physical enclosures, such a shrouds, that are typically adapted for a specific row crop. Such a dynamic enclosure may adapt to differently-sized trees or crops. Further, by reducing backlight, obscurant wall may obviate a need to synchronize a camera sensor (e.g., a camera shutter synchronized with a flash) or perform additional image processing involving, for example, using multiple exposures or tone mapping algorithms. In some examples, one or more obscurant emitters **3321a** and **3321b** and one or more blowers **3322a** and **3322b** may be disposed on an encompassing structure **3325**, which may be omitted.

[0194] FIG. **34** is a diagram depicting an example of a flow to facilitate imaging a crop in an environment with backlight, according to some examples. In some examples, flow **3400** enhances a dynamic range of captured images of agricultural objects with environments with backlight, such as sunlight or moonlight (e.g., a full moon). At **3402**, location and/or sensor data of an environment including an agricultural object may be received. At **3404**, an agricultural object may be identified based on the location and/or sensor data received at **3402**. At **3406**, a determination is made as to whether an identified agricultural object may be correlated to index data. If so, flow **3400** moves to **3408**, at which a spatial location of an agricultural object may be determined. At **3410**, an identified agricultural object may be correlated to index object data, thereby confirming that sensor data (e.g., image data) being received at a sensor is identifying an agricultural object that is the same in the indexed data. At **3412**, an action may be associated with the indexed object data. That is, a policy to perform an action (e.g., a treatment) may be associated with indexed object data. At **3414**, an agricultural object may be identified as a target to, for example, perform an action. At **3416**, determination is made as to whether a value of backlight is above a threshold value. For example, if an intensity of light is above a threshold value, and that light originates behind the identified target, then flow **3400** moves to **3418** to generate an obscurant, such as generating water vapor using ultrasonic generator. At **3420**, an obscurant may be emitted at a location relative to the targeted agricultural object, the obscurant being disposed between a source of backlight and a target agricultural object. At **3422**, an image of the agricultural object may be captured.

[0195] FIG. **35** is a diagram depicting a pixel projectile delivery system configured to replicate an image on a surface using pixel projectiles, according to some embodiments. Diagram **3500** includes a pixel projectile delivery system **3511**, which may include any number of pixel emitters **3542a**, and a mobile computing device **3590**, which may include a processor configured to execute an application that may provide inputs (e.g., control data) to pixel projectile delivery system **3511**. In various examples, pixel projectile delivery system **3511** may be configured to emit subsets of pixel projectiles **3512** to “paint” or replicate portions of an image, such as image **3560**, upon a surface **3502**. In some examples, an application executing on mobile computing device **3590** may identify an image **3560** to be replicated on surface **3502**, and may further be configured to determine a reference with which to align inputs associated with mobile computing device **3590** and corresponding outputs associated with a replicated image on surface **3502**. As shown, a reference **3515a** of image **3560** is aligned with reference **3515b** of the image in the user interface of mobile computing device **3590**, which, in turn, may establish a reference **3515c** associated with surface **3502**. Therefore, inputs into the user interface of mobile computing device **3590** may be correlated to reference **3515b**, and, similarly, outputs emitted out of emitters **3542a** (and impacted points on surface **3502**) may be correlated to reference **3515c**.

[0196] To illustrate operation of pixel projectile delivery system **3511**, consider that pixel projectile delivery system **3511** may be configured to receive data **3578** representing image **3560**. At least one portion **3515a** of image **3560** may be a reference **3515a** to align with a surface reference **3515c** associated with surface **3502**. Pixel projectile delivery system **3511** may be configured to establish electronic communication with mobile computing device **3590**, which may be configured to transmit control data **3578** as a function of one or more spatial translations as inputs, whereby one or more spatial translations simulate replication on surface **3502**. Examples of one or more spatial translations are depicted as spatial transitions **3520a**, **3521a**, **3522a**, **3523a**, and **3524a**. In some cases, each of spatial transitions **3520a**, **3521a**, **3522a**, **3523a**, and **3524a** may be referred to as a unit of spatial translation (e.g., a unit be determined by, for example, a momentary pause or delay in applying an input).

[0197] Pixel projectile delivery system **3511** may be configured to receive data representing a unit of spatial translation, such as one of units of spatial translation **3520a**, **3521a**, **3522a**, **3523a**, and **3524a**, whereby the unit of spatial translation may specify a translation relative to a reference associated with mobile computing device **3590**. In one example, spatial translations may be determined based on translations of, for example, a simulated targeting sight **3592** that may produce each of spatial transitions **3520a**, **3521a**, **3522a**, **3523a**, and **3524a** relative to reference **3515b**, the translations of simulated targeting sight **3592** being caused by input into a touch-sensitive graphics user interface. In another example, spatial translations may be determined based on translations of, for example, motion in two-dimensional space that may produce each of spatial transitions **3520a**, **3521a**, **3522a**, **3523a**, and **3524a** relative to reference **3515d**. Thus, moving mobile computing device **3590** (e.g., within an X-Y plane) may produce spatial translations **3520a**, **3521a**, **3522a**, **3523a**, and **3524a** relative to reference **3515d**, whereby one or more motion sensors or accelerometers in mobile computing device **3590** generates inputs representing the spatial translations sent via control data **3578**.

[0198] Further, pixel projectile delivery system **3511** may be configured to determine one or more portions **3520c**, **3521c**, **3522c**, **3523c**, **3524c** of image **3560** respectively associated with each unit of spatial translation **3520b**, **3521b**, **3522b**, **3523b**, and **3524b** relative to reference **3515c**. Note that pixel projectile delivery system **3511** may be configured to respectively map spatial transitions **3520a**, **3521a**, **3522a**, **3523a**, and **3524a** relative to reference **3515d** to spatial translation **3520b**, **3521b**, **3522b**, **3523b**, and **3524b** relative to reference **3515c**.

[0199] Pixel projectile delivery system **3511** may be configured to identify one or more subsets of pixels (e.g., one or more portions **3520c**, **3521c**, **3522c**, **3523c**, **3524c** of image **3560**) to be formed on surface **3502** responsive to detecting a unit of spatial translation. And, pixel projectile delivery system **3511** may be configured to cause emission of one or more subsets of pixel projectiles **3512** directed to impact one or more portions of surface to form one or more subset of pixels **3520d**, **3521d**, **3522d**, **3523d**, and **3524d** relative to surface reference **3515c** to form a replica **3550b** of a portion **3550a** of image **3560**.

[0200] FIG. **36** is a diagram depicting an example of a pixel projectile delivery system, according to some examples. Pixel projectile delivery system **3611** may include a target acquisition processor **3682**, which may include an object identifier **3684**. Pixel projectile delivery system **3611** may also include an emitter selector **3687**, a trajectory processor **3683**, and an emitter propulsion subsystem **3685**. Note that elements depicted in diagram **3600** may include structures and/or functions as similarly-named elements described in connection to one or more other drawings or as otherwise described herein, regardless of whether an implementation non-agricultural.

[0201] Target acquisition processor **3682** may be configured to receive data representing pixel inputs to be replicated on a surface. Object identifier **3684** may be configured to detect an image object, such as a reference with which to replicate an image. Emitter selector **3687** may be configured to select a subset of emitters responsive to inputs selecting a subset of pixels to be replicated. Trajectory processor **3683** may be configured to coordinate and manage emission of

pixel projectiles, and may further be configured to generate activation signals to cause emission propulsion subsystem **3685** to propel pixel projectiles to impact a surface relative to a reference. [0202] In some cases, a pixel emitter **3642a** may include, or may be associated with, one or more pigment sources, such as pigment source **3644a**, pigment source **3644b**, and pigment source **3644n**, where pigment sources may include RED, GREEN, and BLUE pigments, or may include CYAN, MAGENTA, and YELLOW, or any other pigment combination. Trajectory **3683** may be configured to control amounts of pigments into chamber **3643** for proper color mixing. When activated, emitter propulsion subsystem **3685** may trigger chamber **3643** to propel pixel projectile **3612** from aperture **3641**. In some cases, an input **3647** is configured to push out (e.g., blow out) any remaining pigment out through output **3645** so that chamber **3643** may be used to emit other pixel projectiles of different colors. Note that the above is one example and other implements may be used to replicate an image using a pixel projectile delivery system, according to various examples. [0203] FIG. **37** is a diagram depicting an example of a flow to implement a pixel projectile delivery system, according to some examples. At **3702**, data representing at least one portion of an image may be received. The portion of the image may be configured to provide a reference with which to align with a surface reference, which may be associated with a surface. Alignment of a reference of an image and a reference on a surface may facilitate synchronicity between input portions of an image to be replicated or “painted” and outputs of a pixel projectile delivery system to “paint” or emit pixel projectiles to impact a surface relative to a surface reference.

[0204] At **3704**, electronic communication with a computing device configured to transmit data representing simulation of an application may be established. For example, a mobile computing device (e.g., smart phone) may generate inputs describing which portions of an image are to be replicated on a surface, the communication being established between a mobile computing device and a pixel projectile delivery system.

[0205] At **3706**, data representing a unit of spatial translation specifying a translation relative to a reference may be received, for example, into a pixel projectile delivery system. At **3708**, one or more portions of an image associated with a unit of spatial translation relative to a reference may be detected. The unit of spatial translation may be considered an input to cause replication at a surface. At **3710**, a subset of pixels to be formed or replicated on a surface may be identified. At **3712**, emission of a subset of pixel projectiles may be caused, responsive to an input. The subset of pixel projectiles may be directed to impact a portion of a surface to form a replica of a portion of the image

[0206] FIG. **38** illustrates examples of various computing platforms configured to provide various functionalities to components of an autonomous agricultural treatment delivery vehicle and fleet service, according to various embodiments. In some examples, computing platform **3800** may be used to implement computer programs, applications, methods, processes, algorithms, or other software to perform the above-described techniques.

[0207] In some cases, computing platform **3800** can be disposed in any device, such as a computing device **3890a**, which may be disposed in an autonomous agricultural treatment delivery vehicle **3891**, and/or mobile computing device **3890b**.

[0208] Computing platform **3800** includes a bus **3802** or other communication mechanism for communicating information, which interconnects subsystems and devices, such as processor **3804**, system memory **3806** (e.g., RAM, etc.), storage device **3808** (e.g., ROM, etc.), an in-memory cache (which may be implemented in RAM **3806** or other portions of computing platform **3800**), a communication interface **3813** (e.g., an Ethernet or wireless controller, a Bluetooth controller, NFC logic, etc.) to facilitate communications via a port on communication link **3821** to communicate, for example, with a computing device, including mobile computing and/or communication devices with processors. Processor **3804** can be implemented with one or more graphics processing units (“GPUs”), with one or more central processing units (“CPUs”), such as those manufactured by Intel® Corporation, or one or more virtual processors, as well as any combination of CPUs and

virtual processors. Computing platform **3800** exchanges data representing inputs and outputs via input-and-output devices **3801**, including, but not limited to, keyboards, mice, audio inputs (e.g., speech-to-text devices), user interfaces, displays, monitors, cursors, touch-sensitive displays, LCD or LED displays, and other I/O-related devices.

[0209] According to some examples, computing platform **3800** performs specific operations by processor **3804** executing one or more sequences of one or more instructions stored in system memory **3806**, and computing platform **3800** can be implemented in a client-server arrangement, peer-to-peer arrangement, or as any mobile computing device, including smart phones and the like. Such instructions or data may be read into system memory **3806** from another computer readable medium, such as storage device **3808**. In some examples, hard-wired circuitry may be used in place of or in combination with software instructions for implementation. Instructions may be embedded in software or firmware. The term “computer readable medium” refers to any tangible medium that participates in providing instructions to processor **3804** for execution. Such a medium may take many forms, including but not limited to, non-volatile media and volatile media. Non-volatile media includes, for example, optical or magnetic disks and the like. Volatile media includes dynamic memory, such as system memory **3806**.

[0210] Common forms of computer readable media includes, for example, floppy disk, flexible disk, hard disk, magnetic tape, any other magnetic medium, CD-ROM, any other optical medium, punch cards, paper tape, any other physical medium with patterns of holes, RAM, PROM, EPROM, FLASH-EPROM, any other memory chip or cartridge, or any other medium from which a computer can read. Instructions may further be transmitted or received using a transmission medium. The term “transmission medium” may include any tangible or intangible medium that is capable of storing, encoding or carrying instructions for execution by the machine, and includes digital or analog communications signals or other intangible medium to facilitate communication of such instructions. Transmission media includes coaxial cables, copper wire, and fiber optics, including wires that comprise bus **3802** for transmitting a computer data signal.

[0211] In some examples, execution of the sequences of instructions may be performed by computing platform **3800**. According to some examples, computing platform **3800** can be coupled by communication link **3821** (e.g., a wired network, such as LAN, PSTN, or any wireless network, including WiFi of various standards and protocols, Bluetooth®, NFC, Zig-Bee, etc.) to any other processor to perform the sequence of instructions in coordination with (or asynchronous to) one another. Computing platform **3800** may transmit and receive messages, data, and instructions, including program code (e.g., application code) through communication link **3821** and communication interface **3813**. Received program code may be executed by processor **3804** as it is received, and/or stored in memory **3806** or other non-volatile storage for later execution.

[0212] In the example shown, system memory **3806** can include various modules that include executable instructions to implement functionalities described herein. System memory **3806** may include an operating system (“O/S”) **3832**, as well as an application **3836** and/or logic module(s) **3859**. In the example shown in FIG. **38**, system memory **3806** includes a mobility controller module **3850** and/or its components as well as an agricultural projectile delivery controller module **3851**, any of which, or one or more portions of which, can be configured to facilitate an autonomous agricultural treatment delivery vehicle and fleet of services by implementing one or more functions described herein.

[0213] The structures and/or functions of any of the above-described features can be implemented in software, hardware, firmware, circuitry, or a combination thereof. Note that the structures and constituent elements above, as well as their functionality, may be aggregated with one or more other structures or elements. Alternatively, the elements and their functionality may be subdivided into constituent sub-elements, if any. As software, the above-described techniques may be implemented using various types of programming or formatting languages, frameworks, syntax, applications, protocols, objects, or techniques. As hardware and/or firmware, the above-described

techniques may be implemented using various types of programming or integrated circuit design languages, including hardware description languages, such as any register transfer language (“RTL”) configured to design field-programmable gate arrays (“FPGAs”), application-specific integrated circuits (“ASICs”), or any other type of integrated circuit. According to some embodiments, the term “module” can refer, for example, to an algorithm or a portion thereof, and/or logic implemented in either hardware circuitry or software, or a combination thereof. These can be varied and are not limited to the examples or descriptions provided.

[0214] In some embodiments, modules **3850** and **3851** of FIG. **38**, or one or more of their components, or any process or device described herein, can be in communication (e.g., wired or wirelessly) with a mobile device, such as a mobile phone or computing device, or can be disposed therein.

[0215] In some cases, a mobile device, or any networked computing device (not shown) in communication with one or more modules **3850** and **3851**, or one or more of their components (or any process or device described herein), can provide at least some of the structures and/or functions of any of the features described herein. As depicted in the above-described figures, the structures and/or functions of any of the above-described features can be implemented in software, hardware, firmware, circuitry, or any combination thereof. Note that the structures and constituent elements above, as well as their functionality, may be aggregated or combined with one or more other structures or elements. Alternatively, the elements and their functionality may be subdivided into constituent sub-elements, if any. As software, at least some of the above-described techniques may be implemented using various types of programming or formatting languages, frameworks, syntax, applications, protocols, objects, or techniques. For example, at least one of the elements depicted in any of the figures can represent one or more algorithms. Or, at least one of the elements can represent a portion of logic including a portion of hardware configured to provide constituent structures and/or functionalities.

[0216] As hardware and/or firmware, the above-described structures and techniques can be implemented using various types of programming or integrated circuit design languages, including hardware description languages, such as any register transfer language (“RTL”) configured to design field-programmable gate arrays (“FPGAs”), application-specific integrated circuits (“ASICs”), multi-chip modules, or any other type of integrated circuit.

[0217] According to some embodiments, the term “circuit” can refer, for example, to any system including a number of components through which current flows to perform one or more functions, the components including discrete and complex components. Examples of discrete components include transistors, resistors, capacitors, inductors, diodes, and the like, and examples of complex components include memory, processors, analog circuits, digital circuits, and the like, including field-programmable gate arrays (“FPGAs”), application-specific integrated circuits (“ASICs”). Therefore, a circuit can include a system of electronic components and logic components (e.g., logic configured to execute instructions, such that a group of executable instructions of an algorithm, for example, and, thus, is a component of a circuit). According to some embodiments, the term “module” can refer, for example, to an algorithm or a portion thereof, and/or logic implemented in either hardware circuitry or software, or a combination thereof (i.e., a module can be implemented as a circuit). In some embodiments, algorithms and/or the memory in which the algorithms are stored are “components” of a circuit. Thus, the term “circuit” can also refer, for example, to a system of components, including algorithms. These can be varied and are not limited to the examples or descriptions provided.

[0218] Although the foregoing examples have been described in some detail for purposes of clarity of understanding, the above-described inventive techniques are not limited to the details provided. There are many alternative ways of implementing the above-described invention techniques. The disclosed examples are illustrative and not restrictive.

Claims

1. A method of treating objects by a mobile agricultural delivery system comprising one or more emitters and one or more image capture devices, the method comprising: receiving, via the one or more image capture devices, sensor data comprising images having pixels representing one or more objects; determining an emission parameter for at least one of the objects depicted in one or more of the images by performing the operation of: inputting into an object identifier, a subset of the pixels of at least one object; identifying a type of the at least one object depicted in the subset of pixels; and generating the emission parameter based on the type of identified object; and activating the one or more emitters to perform an action based on the generated emission parameter, wherein the emission parameter is an emission time when the action is triggered, the action comprising emitting a projectile at a target, wherein the target is an object depicted in the subset of pixels.
2. The method of claim 1, wherein the one or more emitters are configured to emit the projectile along a trajectory to intercept the target.
3. The method of claim 1, wherein the one or more emitters are configured to modify a rate of dispersal with which portions of the projectile are dispersed at or about a range of the target.
4. The method of claim 1, further comprising: causing the projectile to intercept at least a portion of at least one of the one or more objects where the subset of pixels of the one or more objects is tracked.
5. The method of claim 1, further comprising the operations of: wherein the one or more objects comprise one or more agricultural objects and one or more non-agricultural objects; tracking a subset of the pixels of at least one of the agricultural objects; determining that at least one agricultural objects has changed from a first position relative to the one or more image capture devices to a second position relative to the one or more image capture devices; and tracking a value of an elapsed time to an alignment of the pixels of the one or more non-agricultural objects to the subset of the pixels of the agricultural objects; wherein the first position and second position are determined by identifying that the subset of pixels have changed location from a first image frame to another image frame.
6. The method of claim 5, wherein tracking the subset of the pixels of the agricultural objects relative to the pixels of the one or more non-agricultural objects comprises: tracking the pixels of the one or more non-agricultural objects relative to the subset of the pixels of the agricultural objects as a function of a rate of displacement of the one or more emitters.
7. The method of claim 5, further comprising: performing the action when the subset of pixels of the one or more agricultural objects is in alignment with the pixels of the one or more non-agricultural objects.
8. The method of claim 5, wherein the one or more non-agricultural objects are disposed in a field of view between the one or more agricultural objects and one or more image capture devices positioned on a mobile agricultural delivery system.
9. The method of claim 5, further comprising: predicting when the subset of pixels of the one or more agricultural objects aligns with pixels of the one or more non-agricultural objects to form a predicted emission parameter, the predicted emission parameter being tracked in association with the at least one of the agricultural objects.
10. The method of claim 9, wherein the predicted emission parameter is a predicted emission time to trigger a projectile.
11. A mobile agricultural treatment delivery system comprising: one or more emitters; one or more image capture devices; a memory including executable instructions; and a processor, responsive to executing the instructions, is configured to perform the operations of: receiving, via the one or more image capture devices, sensor data comprising images having pixels representing one or more objects; determining an emission parameter for at least one of the objects depicted in one or more

of the images by performing the operation of: inputting into an object identifier, a subset of the pixels of at least one object; identifying a type of the at least one object depicted in the subset of pixels; and generating the emission parameter based on the type of identified object; and activating the one or more emitters to perform an action based on the generated emission parameter, wherein the emission parameter is an emission time when the action is triggered, the action comprising emitting a projectile at a target, wherein the target is an object depicted in the subset of pixels.

12. The system of claim 11, wherein the one or more emitters are configured to emit the projectile along a trajectory to intercept the target.

13. The system of claim 11, wherein the one or more emitters are configured to modify a rate of dispersal with which portions of the projectile are dispersed at or about a range of the target.

14. The system of claim 11, further comprising the operations of: causing the projectile to intercept at least a portion of at least one of the one or more objects where the subset of pixels of the one or more objects is tracked.

15. The system of claim 11, further comprising the operations of: wherein the one or more objects comprise one or more agricultural objects and one or more non-agricultural objects; tracking a subset of the pixels of at least one of the agricultural objects; determining that at least one agricultural objects has changed from a first position relative to the one or more image capture devices to a second position relative to the one or more image capture devices; and tracking a value of an elapsed time to an alignment of the pixels of the one or more non-agricultural objects to the subset of the pixels of the agricultural objects; wherein the first position and second position are determined by identifying that the subset of pixels have changed location from a first image frame to another image frame.

16. The system of claim 15, wherein tracking the subset of the pixels of the agricultural objects relative to the pixels of the one or more non-agricultural objects comprises: tracking the pixels of the one or more non-agricultural objects relative to the subset of the pixels of the agricultural objects as a function of a rate of displacement of the one or more emitters.

17. The system of claim 15, further comprising the operations of: performing the action when the subset of pixels of the one or more agricultural objects is in alignment with the pixels of the one or more non-agricultural objects.

18. The system of claim 15, wherein the one or more non-agricultural objects are disposed in a field of view between the one or more agricultural objects and one or more image capture devices positioned on a mobile agricultural delivery system.

19. The system of claim 15, further comprising the operations of: predicting when the subset of pixels of the one or more agricultural objects aligns with pixels of the one or more non-agricultural objects to form a predicted emission parameter, the predicted emission parameter being tracked in association with the at least one of the agricultural objects.

20. The system of claim 19, wherein the predicted emission parameter is a predicted emission time to trigger a projectile.
