

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12393059
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Hovinga; Kristen et al.

---

### Ophthalmic lens including a peripheral zone having an add-power offset and a spatially-modulated optical parameter

---

#### Abstract

An ophthalmic lens, comprising a central zone having at least a first power, and a peripheral zone having an add-power offset relative to the at least first power and a spatially-modulated optical parameter. In some embodiments, the central zone has a diameter in the range 2.0 to 5.0 mm. In some embodiments, the central zone is not more than 1 mm smaller than a wearer's pupil. The spatially-modulated optical parameter may include optical power, light scattering or light transmission.

---

**Inventors:** Hovinga; Kristen (Honeoye Falls, NY), Musleh; Mohammad (Rochester, NY), Xu; Mengchen (West Henrietta, NY)

**Applicant:** Bausch + Lomb Ireland Limited (Dublin, IE)

**Family ID:** 1000008762844

**Assignee:** BAUSCH + LOMB IRELAND LIMITED (Dublin, IE)

**Appl. No.:** 18/409320

**Filed:** January 10, 2024

#### Prior Publication Data

Document Identifier	Publication Date
US 20240142801 A1	May. 02, 2024

#### Related U.S. Application Data

division parent-doc US 17089233 20201104 US 12019311 child-doc US 18409320

---

#### Publication Classification

**Int. Cl.:** G02C7/04 (20060101)

**U.S. Cl.:**

**CPC** G02C7/044 (20130101); G02C7/049 (20130101);

## Field of Classification Search

**CPC:** G02C (7/049); G02C (7/044)

**USPC:** 351/159.02

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7025460	12/2005	Smith et al.	N/A	N/A
7503655	12/2008	Smith, III et al.	N/A	N/A
7637612	12/2008	Menezes	N/A	N/A
7665842	12/2009	Ho et al.	N/A	N/A
8240847	12/2011	Holden	N/A	N/A
8770745	12/2013	Lindacher	N/A	N/A
8876287	12/2013	Back	N/A	N/A
8950860	12/2014	Tse et al.	N/A	N/A
8998408	12/2014	Wei et al.	N/A	N/A
9720253	12/2016	Neitz	N/A	N/A
9827250	12/2016	Chehab	N/A	A61K 31/46
10191300	12/2018	Holden	N/A	N/A
11061253	12/2020	Back et al.	N/A	N/A
2008/0218687	12/2007	Phillips	N/A	N/A
2010/0036489	12/2009	Lindacher	623/6.27	G02C 7/028
2018/0243082	12/2017	Zheleznyak et al.	N/A	N/A
2018/0275427	12/2017	Lau et al.	N/A	N/A
2019/0293963	12/2018	Holden et al.	N/A	N/A
2022/0187622	12/2021	Lin et al.	N/A	N/A
2022/0404639	12/2021	Lam et al.	N/A	N/A
2023/0050507	12/2022	Dou	N/A	N/A

### FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2 988 163	12/2015	EP	N/A
3 336 600	12/2017	EP	N/A
WO-2013166308	12/2012	WO	A61F 2/1618
2019/102415	12/2018	WO	N/A

### OTHER PUBLICATIONS

Zheleznyak et al., Optical and neural anisotropy in peripheral vision, Journal of Vision (2016) 16(5):1, 1-11. cited by applicant  
Qiuzhi et al., Through-focus optical characteristics of monofocal and bifocal soft contact lenses across the peripheral visual field, The Authors Ophthalmic & Physiological Optics, The College of Optometrists Ophthalmic & Physiological Optics 38 (2018) 326-336. cited by applicant  
Yifei et al., (ARVO meeting abstract) a potential optical mechanism of bifocal contact lenses in myopia control. cited by applicant

---

*Primary Examiner:* Stoffa; Wyatt A

*Assistant Examiner:* Dean; Ray Alexander

*Attorney, Agent or Firm:* Simpson & Simpson, PLLC

---

## **Background/Summary**

CROSS-REFERENCE TO RELATED APPLICATION (1) The present application is a divisional of U.S. patent application Ser. No. 17/089,233 having a filing date of Nov. 4, 2020, which is incorporated herein by reference in its entirety.

### **FIELD**

(1) and apparatus for reducing or eliminating myopia progression including an ophthalmic lens, and more particularly methods and apparatus for reducing or eliminating myopia progression including an ophthalmic lens with a peripheral zone having an add-power offset and a spatially-modulated optical parameter.

### **BACKGROUND**

(2) Myopia is a condition of the eye resulting in objects at a far distance (e.g., greater than six meters) being focused in front of the retina, thereby causing blurred vision. Myopia is normally corrected with the use of ophthalmic lenses of sufficient negative power to bring distant objects into focus on the central retina, while allowing near objects to be focused on the central region of the retina by accommodation of the lens of the eye.

(3) Most commonly, myopia occurs when eye growth is excessive, resulting in an imbalance between the axial length of the eye relative to focal power of the eye. Myopia is commonly a progressive disorder associated with gradual elongation of the eye. A number of undesirable pathologies (e.g., retinal detachment and glaucoma) may occur as a result of eye elongation arising from progressive myopia.

(4) It is now generally accepted that increases in axial length of an eye of a growing animal is controlled by a feedback mechanism that occurs within the eye, which allows light entering the eye to be focused onto the central region of the retina. In an emmetropic eye, this mechanism works well and axial length and focal power of the eye remain in balance allowing for light to be focused onto the central region of the retina as the eye grows; however, in a myopic eye, the elongation is excessive and, in a hyperopic eye, elongation is insufficient thereby resulting in poorly focused light being projected onto the central region of the retina.

(5) Multiple theories exist regarding the feedback mechanism of the eye. According to one theory, the location of the peripheral image controls eye growth. More particularly, under this theory, a stimulus for increased eye length is created when the peripheral focal plane lies behind (i.e., posterior to) the retina. According to this theory, a multizonal ophthalmic lens to control myopia progression is provided with a peripheral zone having a refractive add-power offset relative to the central zone of the lens thereby shifting the focal plane in front of (i.e., anterior to) the peripheral

retina and eliminating the stimulus for growth.

(6) In lenses made according to this theory, the lens is constructed such that visual rays (i.e., rays forming perceivable visual images) essentially pass only through a central zone of such a multizonal lens, and the peripheral zone is located radially outward of the central zone so as to direct light outside of the central, visual portion of the retina. Accordingly, if the central zone is configured for single vision, given normal accommodation of an eye, only an image formed by the central zone will be focused on the retina and light passing through the peripheral zone is focused in front of the retina. At a given time, the image formed by the central zone can be of a distant object or a near object depending on the accommodative state of the eye.

(7) Multizonal lenses having a peripheral zone with an add-power offset relative to the central zone are understood to be distinct from multizonal, bifocal contact lenses where a central zone and an outer zone of the lens overlie the pupil such that visual rays intercept both the central zone and the outer zone. In bifocal lenses, because the outer zone has a different power than the central zone, visual rays from the zones form two images on the central retina at all times (one focused and the other out of focus). At a given time, the in-focus image can be of a distant object or a near object depending on the accommodative state of the eye.

(8) While lenses having a peripheral zone with an add-power offset relative to the central zone of the lens have been shown to be effective in achieving suppression of myopia progression for some wearers, other wearers have not achieved the desired suppression and/or have had their vision compromised by disturbances (e.g., glares and halos) resulting from stray light passing through the peripheral zone of the lens.

#### SUMMARY

(9) It is believed that the lack of efficacy for some wearers of conventional lenses designed to suppress the progression of myopia using a peripheral zone add-power offset results from (1) a prescribed lens allowing peripheral hyperopic defocus to occur at some accommodative states of a given wearer's eye and/or (2) some wearer's eyes being less responsive to a peripheral defocus.

(10) Aspects of the present invention are directed to a multizonal ophthalmic lens comprising a peripheral zone having an add-power offset relative to a central zone, the peripheral zone also having a spatially-modulated optical parameter. In the event that a given wearer's eye is exposed to peripheral hyperopic defocus when the eye is in a given accommodative state, the spatially modulated optical parameter provides suppression of progression of myopia. Additionally, for those wearer's that are less responsive to peripheral defocus, the modulated optical parameter provides an additional mode of operation to suppress progression of myopia.

(11) A multizonal lens according the aspects of the present invention (i.e., a lens comprising a peripheral zone having an add-power offset relative to a central zone, with a spatially-modulated optical parameter) provides a given efficacy for reducing or eliminating progression of myopia that is less likely to give rise to a perceivable visual disturbances (e.g., glare and halos) than a multizonal lens providing the same efficacy but comprising a peripheral region having a uniform (i.e., non-modulated) power offset. For example, as a result of effects caused by the modulation of the optical parameter, the add-power offset between the central zone and the peripheral zone may be reduced leading to decreased glare and halos.

(12) As progressive myopia most commonly afflicts children and young adults, the diameter of the central optical zone of lenses according to aspects of the present invention may be greater than about 3 mm to reasonably ensure that the central zone is larger than a wearer's pupil under photopic conditions. However, as is understood in the art, due to the existence of what is known as the Stiles-Crawford effect, light rays that pass close to the edge of visual image forming portion of the eye (also called "peripheral rays"), have less visual significance than those rays that travel nearer the center of the pupil. Thus, the central optical zone need not be greater than the pupil diameter of the eye to be effective. Accounting for the Stiles-Crawford effect, it is typically desirable that the radius of a central optical zone of a lens be no more than 1 mm smaller than the radius of the pupil

of a wearer's eye (e.g., 2 mm in diameter).

(13) As is understood in the art, lenses are typically not custom-made for a wearer. Accordingly, lenses may be designed such that a central zone diameter of a lens is not more than 1 mm less than a normal (i.e., average) pupil diameter of an eye of a selected population.

(14) An aspect of the present invention is directed to an ophthalmic lens, comprising a central zone having at least a first power, and a peripheral zone disposed radially outward of the central zone. The peripheral zone having an add-power offset relative to the at least first power and a spatially-modulated optical parameter. In some embodiments, the central zone has a diameter in the range 2.0 to 5.0 mm. In some embodiments, the central zone is not more than 1 mm smaller than a wearer's pupil. In some embodiments, the central zone has a diameter of at least 3 mm. In some embodiments, the central zone has a diameter of at least 2.0 mm.

(15) In some embodiments, the add power offset is in the range 0.5 diopters to 5 diopters. The lens may further comprise a transition zone between the central zone and the peripheral zone such that the power profile from the optical axis to the outer diameter of the peripheral zone varies continuously. In some embodiments, there is a step in power between the central zone and the peripheral zone.

(16) In some embodiments, the spatially-modulated optical parameter is optical power. In some embodiments, the spatially-modulated optical power has a plurality of maxima and minima along a radial dimension, and the maxima and/or the minima increase as a function of radial position. In some embodiments, the spatially-modulated optical power has a plurality of maxima and minima along a radial dimension, and the maxima have a same dioptric value as one another, and minima have a same dioptric value as one another.

(17) In some embodiments, the add power offset is in the range 0.5 diopters to 5 diopters. In some embodiments, the peripheral zone has a base power and power differences between the base power and each of the maxima is in the range 0.05 diopters to 2 diopters.

(18) The spatially-modulated optical parameter may be light scattering. The spatially-modulated optical parameter may be light transmission.

(19) The lens may be a contact lens. The central zone may have only a single power.

(20) In some embodiments, the peripheral zone is characterized by a smoothly varying power profile. In other embodiments, the peripheral zone is characterized by a power profile having one or more discontinuities between a power minima and a power maxima.

(21) In some embodiments, the base power is uniform across the peripheral zone. In other embodiments, the base power increases as a function of radial position across the peripheral zone. The lens may be rotationally symmetric.

(22) These and other aspects of the present invention will become apparent upon a review of the following detailed description and the claims appended thereto.

(23) It is understood that a multizonal contact lens is a contact lens where different portions or areas of the lens have different optical parameters or functions, for example, different refractive powers. Multifocal contact lenses are a sub-class of multi-zonal contact lenses characterized by the fact that the central zone of the lens, corresponding roughly to normal pupil diameter, has at least two zones of different refractive power corresponding to objects at different distances (e.g. corresponding to near vision and far vision). Multifocal lenses provide a wearer with two images (simultaneously) and, possibly, with a transition zone between the zones.

(24) The term "optical parameter" is defined herein as a characteristic of a lens that effects the quality of the image formed by the lens. For example, optical parameters include optical power, transparency, aberration (e.g., including higher order aberrations) or scattering. For example, modulations can be realized using changes in surface curvature, index of refraction, surface texture, and material properties.

(25) The term "spatially-modulated" is defined herein to mean a variation over a given distance (i.e., radially and/or circumferentially), for example along a surface of a lens or within the body of

a lens. A spatially modulated optical parameter has a plurality of maxima and minima over the given distance. The maxima (or minima) may be of equal value or different values. A spatially-modulated optical parameter decreases the ability of a lens to form a quality image due to localized variation of a characteristic of the lens. For example, spatial modulation of an optical parameter may comprise variation in optical power of the lens, variation in aberration content, variation in the light transmission (e.g., introducing localized translucent inclusions, surface texturing, film or coating) or variations in light scattering (e.g., introducing localized scattering inclusions, surface texturing, film or coating). Scattering may occur due to light absorption and re-emission or due to specular or diffuse reflection of light. For example, spatial modulation of optical power can be illustrated using a power profile.

(26) The term “greater” and the term “add-power offset” as used herein mean that an identified value (e.g., an optical power) is more positive than or less negative than a specified reference value. For example, a peripheral power may be greater than a central zone power. Alternatively, it may be stated that the peripheral power has an add-power offset relative to the central zone power.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1A is a schematic plan view of an example of an ophthalmic lens according to aspects of the present invention;

(2) FIG. 1B is a schematic cross-sectional view of the lens of FIG. 1A taken along line 1B-1B of FIG. 1A;

(3) FIG. 2A illustrates one example of a power profile of an ophthalmic lens in which spatial-modulation of an optical parameter of a peripheral zone is achieved using a variation in optical power;

(4) FIG. 2B illustrates examples of characteristics of a power profile that may be varied to balance myopia progression suppression efficacy and likelihood of a wearer experiencing visual disturbances;

(5) FIG. 2C illustrates another example of a power profile of an ophthalmic lens in which spatial-modulation of an optical parameter of a peripheral zone is achieved using variation in optical power in the radial direction; and

(6) FIG. 3 illustrates one example of a lens in which spatial-modulation of an optical parameter of a peripheral zone is achieved using variations of an optical parameter other than optical power.

### DETAILED DESCRIPTION

(7) Aspects of the invention will be further illustrated with reference to specific examples. It is understood that these examples are given by way of illustration and are not meant to limit the scope of the claims to specific examples.

(8) FIGS. 1A and 1B are schematic illustrations of an example of an ophthalmic lens according to aspects of the present invention.

(9) Ophthalmic lens **100** comprises an optical axis OA, a central zone **110** and a peripheral zone **120**. Although the illustrated lens is circularly symmetric and has optical axis OA aligned with the mechanical axis of the lens, deviation from such an arrangement is possible. Ophthalmic lens **100** is illustrated as a contact lens; however, lenses according to aspects of the invention may be embodied as other ophthalmic lenses that remain stationary relative to the eye. For example, a lens may be a corneal inlay, a corneal only, an intraocular lens or other such ophthalmic lens.

(10) Central zone **110** has at least a first power. The central zone may be of any suitable power profile and includes at least one region providing distance vision correction. For example, the central zone may have only a single power or a progressive power design or a multifocal design.

(11) As stated above, because progressive myopia most commonly afflicts children and young

adults, the diameter of central optical zone **110** of lenses according to aspects of the present invention will typically be greater than about 3 mm to reasonably ensure that the central zone is larger than a wearer's pupil under photopic conditions. However, light rays that pass close to the edge of visual image forming portion of the eye as they progress toward the retina have less visual significance than those rays that travel nearer the center of the pupil. Thus, the central optical zone need not be equal to or greater than the pupil diameter of the eye to be effective. Accounting for the Stiles-Crawford effect, it is typically desirable that a central optical zone is not more than 1 mm smaller than the diameter of the pupil of a wearer's eye. For example, the central zone may have a diameter of at least 2.0 mm or a diameter of at least 3.0 mm or a diameter of at least 4.0 mm. The diameter of the central zone will typically be in the range 2.5 to 5.0 mm and chosen (in part) to avoid visual disturbances in a given population during selected lighting conditions.

(12) Peripheral zone **120** is disposed radially outward from the central zone. The peripheral zone has an add-power offset **115** relative to the at least first power. As shown in the embodiment of FIG. 2A, the offset may be achieved by a step in power at the edge of the central zone; however, in some embodiments, a transition zone may be present between the central zone and the peripheral zone such that the power profile from the optical axis to the outer diameter of the peripheral zone varies continuously such that the offset may be achieved by a more gradual increase in power. The transition zone may be a non-optical surface smoothening feature. Regardless of whether the offset is achieved by a step or a more gradual increase, a discontinuity in the power profile is typically present at the edge of the central zone. The add power offset is usually relative to a central zone power providing distance vision correction. The peripheral zone power is typically greater than any power present in the central zone.

(13) In addition to the add-power offset, the peripheral zone is adapted to have a spatially-modulated optical parameter. As indicated above, a spatially-modulated optical parameter decreases the ability of a lens to form a quality image due to localized variation of a characteristic of the lens. For example, embodiments of lenses according to aspects of the present invention may include spatial modulation of one or more of the following optical parameters: optical power, optical aberrations, light transmission (e.g., using translucent inclusions) or light scattering (e.g., using scattering inclusions).

(14) Under nominal accommodative conditions, the peripheral zone provides a myopic defocus due to the add power offset which, as indicated above, acts to suppress myopia progression; however, should the eye of a wearer deviate from nominal such that peripheral hyperopic focus occur, spatial modulation of the optical parameter in the peripheral zone will continue to provide suppression of myopia progression.

(15) Additionally, for those wearers that are less responsive to the suppression of myopia progression resulting from peripheral defocus, the spatial modulation of the optical parameter provides another mode of action for suppression of progression.

(16) The central zone is designed to achieve optimal vision correction using conventional techniques. Typically, achieving optimal vision corrections, means that the central zone is corrected for distance vision and is free of spatial modulation of the optical parameter.

(17) FIG. 2A illustrates one example of a power profile of a lens in which spatial-modulation of an optical parameter of a peripheral zone is achieved using a variation in optical power. The radial power profile of peripheral zone **220** includes a plurality of maxima **122a** and minima **122b**. That is to say, the power is modulated in the radial direction to achieve power of varying magnitude along the peripheral zone. Radial power may be varied using localized variations in surface curvature or localized variations in index of refraction.

(18) A radial power profile of the peripheral zone can have any of a variety of shapes comprising maxima and minima. For example, the power profile may smoothly vary as shown in FIG. 2A or the shape may include non-continuous transitions between regions of higher power and lower power. The shape can comprise sinusoidally-shaped portions, linear portions or other

configurations.

(19) The base power in the peripheral zone may be uniform in the radial direction with the spatial modulation causing offsets from the base power. Alternatively, the base power may vary (increase or decrease) in the radial direction with the spatial modulation causing offsets from the base power at a given location.

(20) As shown in FIG. 2B, various characteristics of a power profile of a lens having a peripheral zone with a spatially-modulated power profile are selected to achieve myopia progression suppression. Typically, the power profile is selected to balance myopia progression suppression efficacy and visual disturbances. Suppression of myopia progression and the presence of visual disturbances can be modeled using optical design software and/or by clinical testing.

(21) An add power offset between the first power and the base power of the peripheral zone will typically be in the range of 0.5 diopters to 5 diopters. For example, the offset may be 3.0 diopters.

(22) The power difference between the base power of the peripheral zone and the maxima will typically be in the range 0.05 diopters to 2 diopters, and in some instances in the range 0.25 diopters to 1.5 diopters. In some instances, in a given radial profile, all maxima have a same dioptric power and all minima have a same dioptric power; however, in some embodiments (see FIG. 2C), the maxima and/or the minima in a given radial profile may have different dioptric powers.

(23) FIG. 2C illustrates another example of a power profile of an ophthalmic lens in which spatial-modulation of an optical parameter of a peripheral zone **230** is achieved using optical power in the radial direction, however, the maximum dioptric values and the minimum dioptric values vary as a function of radial location. In particular, in the illustrated embodiment, the dioptric values of the maxim and minima increase as a function of radial location. In such a lens, the reduced variation at radially inward locations results in less visual disturbance (i.e., spurious directing of light into the visual portion of the retina), while the increased variation at radially outward locations increase efficacy (i.e., suppression of myopia progression).

(24) The embodiments of FIGS. 2A-2C may be rotationally symmetric or may also have spatial modulation of the power in the circumferential direction. According to aspects of the present invention, a lens may have spatial modulation in the radial and/or circumferential directions.

(25) FIG. 3 is a schematic illustration of one example of a lens **300** in which spatial-modulation of an optical parameter of a peripheral zone is achieved using variations of an optical parameter other than optical power. For example, variation may be achieved using variation in optical aberrations, variation in the light transmission (e.g., using a translucent inclusion) or light scattering (e.g., using scattering inclusions). Other than the type of optical parameter that is varied, lens **300** is the same as lens **100** described above.

(26) Like spatial-modulated power as described above, spatial modulation of other optical parameter as described with reference to FIG. 3 operate to decrease the ability of a lens to form a quality image, and thereby suppress myopia progression. However, an advantage of using spatially modulated power is that, although the power modulation reduces image quality at any given focal plane, the resultant lens provides depth of field which can provide visual advantages.

(27) In FIG. 3, localized variations are illustrated with x's. It will be appreciated that although the localized variations are shown in FIG. 3 as non-rotationally symmetric, in other embodiments such spatial modulation of optical parameters may be rotationally symmetric.

(28) Hydrogel contact lenses are typically packaged in a buffered saline solution. If desired, the packaging solutions may include a pharmaceutical agent that reduces the progression of myopia. Representative pharmaceutical agents include muscarinic agents, such as atropine, pilocarpine, pirenzepine and derivatives and salts thereof.

(29) If desired, the contact lens may be used to deliver other therapeutic agents, for example, various drug formulations, medications or active agents for treatment, inhibition and/or prevention of various diseases and disorders. Examples include: glaucoma treatment agents, such as



brimonidine and salts thereof; anti-allergy agents such as ketotifen, phenylephrine and salts thereof; and vitamins, anti-oxidants and nutraceuticals including Vitamins A, D and E, lutein, zeaxanthin, taurine, fatty acids, and the like.

(30) Although various embodiments have been depicted and described in detail herein, it will be apparent to those skilled in the relevant art that various modifications, additions, substitutions, and the like can be made without departing from the spirit of the invention and these are therefore considered to be within the scope of the invention as defined in the claims which follow.

## Claims

1. An ophthalmic lens, comprising: a central zone having at least a first power; and a peripheral zone disposed radially outward of the central zone, the peripheral zone having an add-power offset relative to the at least first power, and the peripheral zone comprises at least one of (1) localized scattering inclusions, surface texturing, a film, or a coating to generate spatial modulation of light scattering and (2) localized translucent inclusions, surface texturing, a film, or a coating to generate spatial modulation of light transmission.
  2. The lens of claim 1, wherein the central zone has a diameter of at least 3 mm.
  3. The lens of claim 1, wherein the central zone is not more than 1 mm smaller than a wearer's pupil.
  4. The lens of claim 1, wherein the central zone has a diameter of at least 2.0 mm.
  5. The lens of claim 1, wherein the central zone has a diameter in the range 2.0 to 5.0 mm.
  6. The lens of claim 5, wherein the add power offset is in the range 0.5 diopters to 5 diopters.
  7. The lens of claim 1, further comprising a transition zone between the central zone and the peripheral zone such that the power profile from an optical axis of the lens to the outer diameter of the peripheral zone varies continuously.
  8. The lens of claim 1, wherein there is a step in power between the central zone and the peripheral zone.
  9. The lens of claim 1, wherein the lens is configured to scatter light due to light absorption and re-emission of light.
  10. The lens of claim 1, wherein the lens is configured to scatter light due to specular reflection of light.
  11. The lens of claim 1, wherein the lens is configured to scatter light due to diffuse reflection of light.
  12. The lens of claim 1, wherein the central zone has a single power.
  13. The lens of claim 1, wherein the peripheral zone is characterized by a smoothly varying power profile.
  14. The lens of claim 1, wherein the peripheral zone is characterized by a power profile having one or more discontinuities between a power minima and a power maxima.
  15. The lens of claim 1, wherein the lens is rotationally symmetric.
  16. The lens of claim 1, wherein the lens is a hydrogel contact lens packaged in combination with a buffered saline solution containing a pharmaceutical agent that reduces the progression of myopia.
-