

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12392433
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Dias; Libardo Ochoa et al.

Press fitting device, components and method

Abstract

A press fitting device, components and method provide one or more indicators to provide a visual indication that the fitting has been properly pressed around a tube and that the correct amount of pressure has been provided to create a permanent seal. In embodiments, a sealing ring and a latching band are retained within a main body component of the fitting and the latching band can be formed with a radially inwardly extending latch that extends through an opening in the sealing ring.

Inventors: Dias; Libardo Ochoa (West Warwick, RI), Bouchard; Herbert J. (West Greenwich, RI)

Applicant: Quick Fitting Holding Company, LLC (East Providence, RI)

Family ID: 1000008766667

Assignee: Quick Fitting Holding Company, LLC (East Providence, RI)

Appl. No.: 18/536532

Filed: December 12, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240102592 A1	Mar. 28, 2024

Related U.S. Application Data

continuation parent-doc US 17481804 20210922 US 11885448 child-doc US 18536532

Publication Classification

Int. Cl.: F16L37/086 (20060101); F16L13/14 (20060101); F16L37/091 (20060101)

U.S. Cl.:

CPC **F16L37/086** (20130101); **F16L13/142** (20130101); **F16L37/091** (20130101);
F16L2201/10 (20130101)

Field of Classification Search

CPC: F16L (13/141); F16L (13/142); F16L (37/091); F16L (37/0925); F16L (21/03)

USPC: 285/379

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2010/0102038	12/2009	Baum	N/A	F16L 21/03
2015/0102595	12/2014	Crompton	N/A	N/A
2019/0093807	12/2018	Crompton	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102013015895	12/2014	DE	N/A
2677225	12/2012	EP	N/A

OTHER PUBLICATIONS

European Patent Office, Extended European Search Report in EP Application No. 22873457.0, Nov. 29, 2024. cited by applicant

Primary Examiner: Dragicevich; Zachary T

Attorney, Agent or Firm: Williams Mullen

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) The present application is a continuation of U.S. patent application Ser. No. 17/481,804, filed on Sep. 22, 2021, now U.S. Pat. No. 11,885,448, the disclosure of which is hereby incorporated herein in its entirety by reference.

TECHNICAL FIELD

(1) The present invention relates to fluid flow systems, and more particularly to press fittings with visual indicators for use in fluid flow systems.

BACKGROUND

(2) Piping systems exist to facilitate the flow of fluids (e.g., liquid, steam, gas (such as air) or plasma). For example, homes, schools, medical facilities, commercial buildings and other occupied structures generally require integrated piping systems so that water and/or other fluids can be circulated for a variety of uses. Liquids and/or gases such as cold and hot water, breathable air, glycol, compressed air, inert gases, cleaning chemicals, waste water, plant cooling water and paint and coatings are just some examples of the types of fluids and gases that can be deployed through piping systems. Tubing and piping types can include, for example, copper, stainless steel, CPVC

(chlorinated polyvinyl chloride), iron, black iron, gray iron, HDPE (high density polyethylene) and PEX (cross-linked polyethylene). For purposes of the present disclosure, the term “pipe” or “piping” will be understood to encompass one or more pipes, tubes, piping elements and/or tubing elements.

(3) Piping connections are necessary to join various pieces of pipe and must be versatile in order to adapt to changes of pipe direction required in particular piping system implementations. For example, fittings and valves may be employed at the ends of open pieces of pipe that enable two pieces of pipe to fit together in a particular configuration. Among fitting types there are elbows, “tees”, couplings adapted for various purposes such as pipe size changes, ends, ball valves, stop valves, and partial angle connectors, for example.

(4) In the past, pipe elements have been traditionally connected by welding and/or soldering them together using a torch. Soldering pipe fittings can be time-consuming, unsafe, and labor intensive. Soldering also requires employing numerous materials, such as copper pipes and fittings, emery cloths or pipe-cleaning brushes, flux, silver solder, a soldering torch and striker, a tubing cutter and safety glasses, for example. The process for soldering pipes can proceed by first preparing the pipe to be soldered, as the copper surface must be clean in order to form a good joint. The end of the pipe can be cleaned on the outside with emery cloth or a specially made wire brush. The inside of the fitting must be cleaned as well. Next, flux (a type of paste) can be applied to remove oxides and draw molten solder into the joint where the surfaces will be joined. The brush can be used to coat the inside of the fitting and the outside of the pipe with the flux. Next, the two pipes are pushed together firmly into place so that they “bottom out”—i.e., meet flush inside the fitting. The tip of the solder can be bent to the size of the pipe in order to avoid over-soldering. With the pipes and fitting in place, the torch is then ignited with the striker or by an auto-strike mechanism to initiate soldering. After heating for a few moments, if the copper surface is hot enough such that it melts when touched by the end of the solder, the solder can then be applied to the joint seam so that it runs around the joint and bonds the pipe and fitting together.

(5) In addition to welding methods, pipe elements have been secured together through pressure. A press fitting, which is also known as a friction fit or an interference fit, is a fastening of parts that takes place through friction after the parts are pushed or compressed together, as opposed to being connected by threads, glue, solder or other methods. Press fittings of fluid flow parts such as plumbing parts can be created by force, through the use of a hand tool, for example. Hand tools, often called press tools, can take the form of a pair of movably engaged jaws similar to a pair of pliers, for example, where the jaws have a head portion of a certain size designed to fit around parts that are to be connected. For instance, a pipe can be inserted into a fitting made of a somewhat compressible material, whereupon pressure can be applied through the press tool to the outside of the fitting in order to compress the fitting around the pipe. It is critical that the press tool be appropriately applied around the entire circumference of the fitting in order to ensure a tight connection. Once connected, the parts can be used for various purposes. In the field of fluid flow, the connected parts can be used to direct the flow of fluids, such as gases, water and other liquids as described above.

(6) Traditional press fittings are frequently improperly sealed or only partially sealed. If an installer has not properly pressed the fitting to provide a permanent seal, fluid can leak, causing great damage and cost. Imperfections or scarring in the tubing being inserted also presents an opportunity for the connection to leak following compression. In many installation environments, installers take work breaks or otherwise become distracted as to which of a number of press fittings have been properly compressed and which have been either improperly compressed or not at all. When this happens, there has been no simple and fast way (other than catastrophic failure or leakage) to determine which fittings have been properly pressed, which can result in lost time spent determining which fittings need to be pressed or have been damaged in the application environment.

(7) Press-fit technology for piping systems with visual indicators can be obtained, for example, through Quick Fitting Holding Company, LLC of Providence, Rhode Island, USA, suppliers of the CoPro®, ProBite®, LocJaw™, BlueHawk™, CopperHead® and Push Connect® lines of push fittings and related products. Also, such technology is described, for example, in U.S. Pat. Nos. 8,888,145 and 9,416,897, the disclosures of which are incorporated herein by reference in their entireties.

SUMMARY

(8) Embodiments of the device of the present disclosure, in part, assist in providing one or more visual indicators to assist an individual in determining whether a piping element such as a fitting has been pressed, and whether the correct amount of force has been applied to create a positive and/or permanent seal. In embodiments of the present disclosure, a fitting is provided having a main body component, with a sealing ring and a latching band securely maintained, at least in part, against a portion of the interior wall of the main body component. The sealing ring is malleable and expandable when properly compressed so as to extend outside of the fitting around an inserted pipe. In this way, an installer, inspector or other individual can visually determine very quickly whether a press fitting has been compressed, and whether there is a proper and complete seal. In various embodiments, the latching band is formed with a radially inwardly extending latch that extends through an opening in the sealing ring within a cavity of the fitting, such that an inserted pipe will be snugly retained within the main body component when the fitting has been compressed.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is an exploded perspective view of a fitting and components in accordance with embodiments of the present disclosure.
- (2) FIG. 2 is a right side view of the main body component of FIG. 1.
- (3) FIG. 3 is a cross-sectional view of the main body component of FIG. 1.
- (4) FIG. 4 is a detailed view of encircled portion 4-4 of FIG. 3.
- (5) FIG. 5 is a cross-sectional view of a fitting with installed components according to embodiments of the present disclosure.
- (6) FIG. 6 is a perspective view of a fitting with installed components according to embodiments of the present disclosure.
- (7) FIG. 7 is a detailed view of encircled portion 7-7 of FIG. 6.
- (8) FIG. 8 is a side view of a sealing ring according to embodiments of the present disclosure.
- (9) FIG. 9 is a front cross-sectional view of the sealing ring taken along line 9-9 of FIG. 8.
- (10) FIG. 10 is a front view of the sealing ring of FIG. 8.
- (11) FIGS. 11 through 14C are cross-sectional views of a sealing ring as mated with a latching band according to multiple embodiments of the present disclosure.
- (12) FIG. 15 is a side view of a latching band according to embodiments of the present disclosure.
- (13) FIG. 16 is a cross-sectional view of the latching band taken along line 16-16 of FIG. 15.
- (14) FIG. 17 is a cross-sectional view of an alternative latching band according to embodiments of the present disclosure.
- (15) FIG. 18 is a detailed view of encircled portion 18-18 of FIG. 17.
- (16) FIG. 19 is a front view of a latching band according to embodiments of the present disclosure.
- (17) FIG. 20 is a side view of the latching band of FIG. 19.
- (18) FIG. 21 is a cross-sectional view of the latching band of FIG. 19 taken along line 21-21 of FIG. 20.
- (19) FIG. 22 is a detailed view of encircled portion 22-22 of FIG. 20.

(20) FIG. **23** is a detailed view of encircled portion **23-23** of FIG. **21**.

(21) FIG. **24** is a front view of an alternative latching band according to embodiments of the present disclosure.

(22) FIG. **25** is a side view of the latching band of FIG. **24**.

(23) FIG. **26** is a detailed view of encircled portion **26-26** of FIG. **25**.

(24) FIG. **27** is a cross-sectional view of the latching band of FIG. **24** taken along line **27-27** of FIG. **25**.

(25) FIG. **28** is a perspective view of a fitting with pipes inserted on either end and prior to compression by a press tool in accordance with embodiments of the present disclosure.

(26) FIG. **29** is a perspective view of the arrangement of FIG. **28** during compression by a press tool in accordance with embodiments of the present disclosure.

(27) FIG. **30** is a perspective view in cross section showing inserted pipes in a fitting according to embodiments of the present disclosure prior to compression.

(28) FIG. **31** is a detailed view of encircled portion **31-31** of FIG. **30**.

(29) FIG. **32** is a perspective view of a fitting according to embodiments of the present disclosure with pipe installed at two ends.

(30) FIG. **33** is a cross-sectional view of the fitting of FIG. **32**.

(31) FIG. **34** is a detailed view of encircled portion **34-34** of FIG. **33**.

DETAILED DESCRIPTION OF EMBODIMENTS

(32) The presently disclosed subject matter now will be described more fully hereinafter with reference to the accompanying drawings, in which some, but not all embodiments of the presently disclosed subject matter are shown. Like numbers refer to like elements throughout. The presently disclosed subject matter may be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will satisfy applicable legal requirements. Indeed, many modifications and other embodiments of the presently disclosed subject matter set forth herein will come to mind to one skilled in the art to which the presently disclosed subject matter pertains having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is to be understood that the presently disclosed subject matter is not to be limited to the specific embodiments disclosed and that modifications and other embodiments are intended to be included within the scope of the appended claims.

(33) It will be appreciated that reference to “a”, “an” or other indefinite article in the present disclosure encompasses one or a plurality of the described element. Thus, for example, reference to a processor may encompass one or more processors, a message may encompass one or more messages, a topic may encompass one or more topics and so forth. For purposes of the present disclosure, it will be appreciated that a fitting can encompass a valve member and other piping elements including, but not limited to: a coupling joint, an elbow joint, a tee joint, a stop end, a ball valve member, tubing and other objects having cylindrical openings.

(34) As shown in FIGS. **1** through **34**, embodiments of the present disclosure provide a fitting **10** having a somewhat cylindrically shaped main body component **20** with an interior surface **14** and an exterior surface **16**. The main body component **20** is formed with an axially outer edge **11**. In various embodiments, the main body component **20** can be formed (e.g., forged, cast, extruded and/or pressed) in brass, aluminum, steel, malleable iron or copper, with full porting and full flow fitting, for example. FIGS. **1**, **6** and **30** illustrate embodiments of the main body component **20** with a solid exterior surface **16**, whereas FIGS. **32** through **34** illustrate embodiments of the main body component **20** with openings **132**, **134** formed through and around the periphery of the main body component **20**. Such openings **132**, **134** can be employed to view internal components of a packing arrangement **50** as described elsewhere herein.

(35) As further shown in the drawings, the interior surface **14** defines a cavity **18** extending through the main body component **20** along a central axis A, and includes a tube stop element **21** extending

radially inwardly at the general axial midpoint of the main body component **20**. The tube stop **21** separates the interior **14** into first **31** and second **33** interior compartments, and when a pipe **25** of appropriate diameter is inserted into either compartment **31**, **33**, the pipe's axial end wall **27** abuts the tube stop **21** as shown in FIGS. **30** and **33** so that the pipe cannot be inserted axially further into main body component **20**. It will be appreciated that embodiments of the present disclosure may provide a fitting having only a first interior compartment **31**.

(36) As shown in FIGS. **1** through **5**, the interior surface **14** includes an axially inner segment **30** and axially outer segment **40**. The axially inner segment **30** extends a radial distance B from the axis A and the axially outer segment **40** extends different radial distances at different axial locations. For example, the axially outer segment **40** of the main body component **20** can be formed with first **41** and second **42** indentations and a floor **43**, where the radial distance C from the axis A to the second indentation **42** is greater than the radial distance D from the axis A to the first indentation **41** as well as the radial distance E from the axis A to the floor **43**. Further, the radial distance D to the first indentation **41** is greater than the radial distance E to the floor **43**. In various embodiments, the various radial distances C, D and E of the axially outer segment **40** are each greater than the radial distance B from the axis A to the axially inner segment **30**. In various embodiments, the first indentation **41** extends parallel to the axis A and the second indentation **42** is rounded. The first indentation **41** facilitates mating reception of a latching band **54** and the second indentation facilitates mating reception of a sealing ring **52** as described elsewhere herein.

(37) As shown in the embodiment of FIG. **4**, the first indentation **41** lies axially outwardly of the second indentation **42** and includes an axially outer wall **76** extending radially outwardly from an outer ledge **77** and an axially inner wall **74** extending radially outwardly from an inner ridge **73**. The first indentation **41** further includes an indentation floor **75** extending axially outwardly from the axially inner wall **74** to the axially outer wall **76**. In the embodiment shown in FIG. **4**, the second indentation **42** includes a rounded supporting floor **72** extending from an axially inner segment edge **71** to inner ridge **73**. The floor **43** which can include inner ridge **73** has a greater radial distance E from axis A than the radial distance B from the axis A to the axially inner segment **30** in order to accommodate a sealing ring **52** of the packing arrangement **50**, as described elsewhere herein.

(38) As shown in FIGS. **3** and **5**, the exterior surface **16** includes an axially inner segment **34** and an axially outer segment **35** that generally correspond on an axial basis with respective axially inner **30** and outer **40** segments of the interior surface **14**. An exterior ridge **37** on the exterior surface **16** corresponds to the second indentation **42**. A radially indented groove **36** can also be formed on the exterior surface **16** corresponding to the axial position of the tube stop **21**, as shown in FIG. **3**. The main body component **20** can be formed so as to have a first radial thickness corresponding to the axially inner segment **30** and a second radial thickness corresponding to the axially outer segment **40**, wherein the first radial thickness is greater than the second radial thickness. Further, the main body component **20** can be formed so as to have a variable radial thickness corresponding to the axially outer segment **40**, wherein the radial thickness corresponding to the first indentation **41** is less than the radial thickness corresponding to the second indentation **42**. The different radial thicknesses facilitate engagement with the packing arrangement **50** and inserted piping during operation.

(39) In various embodiments, the axially outer segment **40** of the main body component **20** can be provided or compressed into a fluted form, whereby its radial distance from axis A increases as the axially outer segment **40** extends axially outwardly from the axially intermediate segment **40**. In this way, the main body component **20** provides an expanding surface area for the sealing ring **52** to expand into as one or more pipes or tubes (illustrated at **25** in FIGS. **28** through **34**) are inserted and clamping pressure is applied, as explained in more detail elsewhere herein.

(40) In various embodiments, as shown in FIGS. **1** and **5** through **34**, a packing arrangement **50** is provided and can include one or more of the following components: a sealing or indicator ring **52**

and a latching band **54**. The sealing ring **52** can be a substantially ring-shaped, monolithic body having a substantially circular body cross-section, and can be formed from a rubber, synthetic or similar non-metallic and compressible material. Optionally, ring **52** can be lubricated with a food grade lubricant, for example, when installed and during use. The latching band **54** can be formed of a metallic material, such as brass, aluminum, steel, malleable iron or copper, in various embodiments. Each of the indicator ring **52** and latching band **54** can comprise individual pieces which are not formed together.

(41) As shown in FIG. 5, the latching band **54** can be securely maintained within the first indentation **41** of the interior surface **14** of the main body component **20**. As shown in FIGS. 11 through 27, the latching band **54** can be formed with a radially inner surface **56**, a radially outer surface **57** and a radially inwardly extending latch **58**. The radially inwardly extending latch **58** can be formed as a concave band **82**, one or more rings **84**, one or more teeth **80** and/or a row of teeth **83** and a concave band **82**. In embodiments with a row of teeth **83**, the row of teeth **83** can lie axially inwardly of the concave band **82**, which can contribute to overall retention of an inserted pipe during operation. In the ring **84** arrangement, the ring **84** can be formed with slots **85** to permit limited flexibility during operation. In still other embodiments as shown in FIGS. 15 through 18, the radially inwardly extending latch **58** can be formed as first **110** and second **112** ridges extending axially and radially outwardly from the radially inner surface **56** of the latching band **54**. In such embodiments, the first ridge **110** and/or the second ridge **112** can be split and/or can be formed with a ridge edge surface **116** between a ridge inner surface **114** and a ridge front surface **115**. As the radially innermost element, the ridge edge surface **116** engages an inserted pipe during operation. As shown in FIG. 18, an opening **118** can be formed between the first ridge **110** and a ridge interior wall **117**, as well as between the second ridge **112** and ridge interior wall **119**. Further, in some embodiments such as shown in FIG. 14A, for example, the first ridge **110** extends axially and radially outwardly at a first angle from the latching band **54** (e.g., to the axis A), whereas the second ridge **112** extends axially and radially outwardly at a second angle from the latching band **54** (e.g., to the axis A), wherein the first angle is smaller than the second angle. The first ridge **110** can lie axially inwardly of the second ridge **112**.

(42) In embodiments as shown in FIGS. 14C, 21 and 23, for example, the latching band **54** can be formed with one or more openings **59**, wherein a perimeter P extends around the opening **59**, and wherein the radially inwardly extending latch **58** is formed at the perimeter P. The latching band may also be split as indicated at **90** in FIGS. 15, 20, 21 and 25. In various embodiments, the split nature of the latching band **54** allows it to compress and/or collapse during insertion into the cavity **18** of main body component **20**, as well as during compression when the outer surface **16** of the main body component **20** is compressed, effectively narrowing the split. During such operation, the diameter of the latching band **54** when compressed becomes less than the diameter of the main body component **20** when at rest, and the latching band **54** forms a tighter seal around the inserted pipe **25**. As shown in FIGS. 16, 19 and 24, in various embodiments, the latching band **54** can be provided with a substantially constant width between edges **101** and **102** or can be provided with a varying width where wider segments such as formed between edges **103**, **104** are adjacent narrower segments such as formed between edges **105**, **106**. The staggered width arrangement shown by edge pairs **103**, **104** and **105**, **106** can facilitate easy manipulation of the latching band **54** during installation and removal.

(43) In various embodiments, the radially inwardly extending latch **58** extends into the cavity **18** a radial distance from the axis A that is less than the radial distance B from the axis A to the axially inner segment **30**. By extending to a position closer to the axis A than axially inner segment **30**, the radially inwardly extending latch **58** can ensure engagement with an inserted pipe in order to provide movement resistance when the pipe is installed. It will be appreciated that the radially inwardly extending latch **58** can extend into the cavity **18** at different lengths so as to be a variable radial distance from the axis A.

(44) As shown in FIG. 5, the sealing ring 52 is securely maintained within the second indentation 42 and against the radially inner surface 56 of the latching band 54. As shown in FIGS. 8 through 10, the sealing ring 52 can be formed with one or more openings 60 through which the one or more radially inwardly extending latches 58 can extend when the packing arrangement 50 is installed. The sealing ring 52 can be formed as a monolithic component with a retaining bulb 61 and a sealing ring body 62, wherein the retaining bulb 61 and sealing ring body 62 form a sealing ring radially inner surface 63, radially outer surface 64, axially outer edge 65 and axially inner edge 66. The rounded nature of retaining bulb 61 and second indentation 42 can assist in preventing an inserted pipe 25 from extracting the sealing ring 52 from the cavity 18 during operation. The axially outer edge 65 is a portion of the sealing ring 52 that first extends outwardly of the fitting 10 upon proper compression of the fitting 10 with a suitable press tool, as described elsewhere herein.

(45) In various embodiments, when the resilient sealing ring 52 is inserted and retained in the second indentation 42 and against the axially outer segment 40 of the interior 14 of the component 20, the radial distance from axis A to the sealing member's radially inner surface 63 is substantially the same as radial distance B, as can be seen in FIG. 5. In various embodiments, the axially outer segment 40 has a shorter axial length L1 than the axial length L2 of axially inner segment 30. Further, it will be appreciated that the radially inwardly extending latch 58 can extend into the cavity 18 a radial distance from the axis A that is less than a radial distance from the axis to the sealing ring 52, which can ensure engagement with an inserted pipe in order to provide movement resistance when the pipe is installed. In various embodiments, the sealing ring axially outer edge 65 lies axially aligned with or inwardly of the axially outer edge 11 of the main body component 20 when the sealing ring 52 is at rest (as shown in FIG. 5) and lies axially outwardly of the axially outer edge 11 of the main body component 20 when the sealing ring 52 is compressed, such as when a pipe is inserted during operation as shown in FIG. 34, for example.

(46) As shown in FIGS. 5, 8 through 10 and 31, for example, the sealing ring 52 includes surfaces that provide structure to support interoperation, connection and engaged movement with other surfaces of other components of the present disclosure, as shown and described herein. For instance, the radially interior surface 63 of the sealing ring 52 extends exclusively axially and engages the outer surface 152 of an inserted pipe 25 during operation as shown in FIG. 34.

(47) In operation, as shown in FIGS. 1, 5 and 28 through 34, prior to compression of the packing arrangement 50, the packing arrangement 50 is inserted into the main body component 20 so as to reside within the axially outer segment 40 of the inner surface 14 thereof. The latching band 54 is positioned in the first indentation 41, with radially outer surface 57 contacting the indentation floor 75 of the axially outer segment 40 of the interior surface 14. The sealing ring 52 is positioned in second indentation 42 of axially outer segment 40. A pipe 25 is then inserted into the cavity 18 with little or no resistance from the packing arrangement 50 or its elements 52, 54, as the pipe outer surface 152 can be of smaller diameter than the diameters of the uncompressed elements 52, 54. In various embodiments, the pipe outer surface 152 can be of substantially the same diameter of the uncompressed elements 52, 54 other than the diameter of the radially inwardly extending latch 58 of the latching band 54, which is necessarily of smaller diameter in order to function as described herein.

(48) As shown in FIGS. 28 and 29, a press tool 150 can be applied around the ridge 37 of the outer surface 16 of the main body component 20 when a pipe or tube 25 has been inserted into the cavity thereof. As the press tool 150 is properly applied, the sealing member 52 and latching band 24 are drawn into contact with the pipe outer surface 152, as shown in FIG. 31, and the sealing ring 52 is extruded outwardly of the axial end wall 11 of the main body component 20, as shown in FIGS. 29, 32 and 34.

(49) The radially inwardly extending latch 58 of the latching band 54 digs into the outer surface 152 of the pipe 25 as the press tool 150 applies pressure. As described elsewhere herein, should the pipe 25 seek to move or escape axially outwardly of the component interior surface 14, the latching

band **54** and particularly the radially inwardly extending latch **58** provides additional retaining strength for retaining the pipe **25** within the fitting cavity.

(50) It will thus be appreciated that a single application of the press tool **150** about the circumference of the axially outer segment **40** of the main body component **20** acts to extrude the sealing ring **52** outside of the axially outer end **11** of the main body component **20**. If the sealing ring **52** is viewable around the entire circumference of the pipe **25**, then an individual will know that the fitting has been appropriately pressed and properly sealed.

(51) It will be appreciated that the sealing ring **52** can be of sufficient durometer and have sufficient expandable material in order to appropriately extrude outside of the fitting **10** when a pipe **25** is inserted, while also filling in any voids, scarring or imperfections in the pipe **25** being inserted as well as in the fitting interior surface **14**. The sealing ring **52** can also be of sufficient durometer in order to roll up or pinch when a pipe **25** is improperly inserted, such as when the pipe **25** is inserted at too oblique an angle into the fitting **10**.

(52) Embodiments of the present disclosure may be embodied in other specific forms without departing from the spirit or essential characteristics thereof. The present embodiments are therefore to be considered in all respects as illustrative and not restrictive, the scope of the invention being indicated by the claims of the application rather than by the foregoing description, and all changes which come within the meaning and range of equivalency of the claims are therefore intended to be embraced therein.

Claims

1. A fitting, comprising: a main body component comprising interior and exterior surfaces, wherein the interior surface defines a cavity extending through the main body component along an axis, and wherein the interior surface comprises an axially inner segment and an axially outer segment; a latching band securely maintained within the interior surface, wherein the latching band comprises a radially inner surface and a radially inwardly extending latch, wherein the radially inwardly extending latch comprises a radial distance from the axis that is less than a radial distance from the axis to the axially inner segment; a sealing ring securely maintained within the interior surface and against the radially inner surface of the latching band, wherein the sealing ring is formed with an opening, and wherein the radially inwardly extending latch extends through the sealing ring opening; and wherein the main body component comprises an axially outer edge and wherein the sealing ring comprises an expandable material comprising an axially outer edge that lies axially aligned with or inwardly of the axially outer edge of the main body component when the sealing ring is at rest and lies axially outwardly of the axially outer edge of the main body component when the sealing ring is compressed.
2. The fitting of claim 1, wherein the axially outer segment comprises an axially outer segment axial length, and wherein the axially inner segment comprises an axially inner segment axial length that is larger than the axially outer segment axial length.
3. The fitting of claim 1, wherein the latching band and the sealing ring are maintained within the axially outer segment.
4. The fitting of claim 1, wherein the main body component comprises a first radial thickness corresponding to the axially inner segment and a second radial thickness corresponding to the axially outer segment, and wherein the first radial thickness is greater than the second radial thickness.
5. The fitting of claim 1, wherein the latching band is maintained within the interior surface axially outwardly of the sealing ring.
6. A fitting, comprising: a main body component comprising interior and exterior surfaces, wherein the interior surface defines a cavity extending through the main body component along an axis; a latching band securely maintained within the interior surface, wherein the latching band comprises

a radially inner surface and a radially inwardly extending latch; a sealing ring securely maintained within the interior surface and against the radially inner surface of the latching band, wherein the sealing ring is formed with an opening, and wherein the radially inwardly extending latch extends through the sealing ring opening, wherein the radially inwardly extending latch comprises a radial distance from the axis that is less than a radial distance from the axis to the sealing ring; and wherein the main body component comprises an axially outer edge and wherein the sealing ring comprises an expandable material comprising an axially outer edge that lies axially aligned with or inwardly of the axially outer edge of the main body component when the sealing ring is at rest and lies axially outwardly of the axially outer edge of the main body component when the sealing ring is compressed.

7. The fitting of claim 6, wherein the interior surface comprises an axially inner segment and an axially outer segment, wherein the latching band and the sealing ring are maintained within the axially outer segment.

8. The fitting of claim 7, wherein the main body component comprises a first radial thickness corresponding to the axially inner segment and a second radial thickness corresponding to the axially outer segment, and wherein the first radial thickness is greater than the second radial thickness.

9. The fitting of claim 6, wherein the latching band is maintained within the interior surface axially outwardly of the sealing ring.

10. A fitting, comprising: a main body component comprising interior and exterior surfaces, wherein the main body component is formed with first and second radially outwardly extending indentations; a latching band maintained within the first indentation, wherein the latching band comprises a radially inner surface; and a sealing ring maintained within the second indentation and against the radially inner surface of the latching band, wherein the sealing ring is formed with an opening, and wherein a portion of the latching band extends through the sealing ring opening.

11. The fitting of claim 10, wherein the latching band further comprises a radially inwardly extending latch comprising one or more rings.

12. The fitting of claim 10, wherein the latching band is formed with an opening, wherein a perimeter extends around the opening, wherein the latching band further comprises a radially inwardly extending latch and wherein the radially inwardly extending latch is formed at the perimeter.

13. The fitting of claim 10, wherein the latching band is formed with a plurality of openings.

14. The fitting of claim 10, wherein the main body component comprises an axially outer edge and wherein the sealing ring comprises an expandable material comprising an axially outer edge that lies axially aligned with or inwardly of the axially outer edge of the main body component when the sealing ring is at rest and lies axially outwardly of the axially outer edge of the main body component when the sealing ring is compressed.

15. The fitting of claim 10, wherein the interior surface comprises an axially inner segment and an axially outer segment, wherein the latching band and the sealing ring are maintained within the axially outer segment, wherein the main body component comprises a first radial thickness corresponding to the axially inner segment and a second radial thickness corresponding to the axially outer segment, and wherein the first radial thickness is greater than the second radial thickness.

16. The fitting of claim 10, wherein the first indentation is axially outward of the second indentation.

17. The fitting of claim 10, wherein the first indentation comprises a radial distance from the axis that is less than a radial distance from the axis to the second indentation.

18. A fitting, comprising: a main body component comprising interior and exterior surfaces, wherein the main body component is formed with first and second radially outwardly extending indentations; a latching band maintained within the first indentation, wherein the latching band

comprises a radially inner surface, wherein the latching band further comprises a radially inwardly extending latch comprising one or more rings; and a sealing ring maintained within the second indentation and against the radially inner surface of the latching band.

19. A fitting, comprising: a main body component comprising interior and exterior surfaces, wherein the main body component is formed with first and second radially outwardly extending indentations; a latching band maintained within the first indentation, wherein the latching band comprises a radially inner surface, wherein the latching band is formed with an opening, wherein a perimeter extends around the opening, wherein the latching band further comprises a radially inwardly extending latch and wherein the radially inwardly extending latch is formed at the perimeter; and a sealing ring maintained within the second indentation and against the radially inner surface of the latching band.

20. A fitting, comprising: a main body component comprising interior and exterior surfaces, wherein the main body component is formed with first and second radially outwardly extending indentations; a latching band maintained within the first indentation, wherein the latching band comprises a radially inner surface, wherein the latching band is formed with a plurality of openings; and a sealing ring maintained within the second indentation and against the radially inner surface of the latching band.

21. A fitting, comprising: a main body component comprising interior and exterior surfaces, wherein the main body component is formed with first and second radially outwardly extending indentations; a latching band maintained within the first indentation, wherein the latching band comprises a radially inner surface; a sealing ring maintained within the second indentation and against the radially inner surface of the latching band; and wherein the main body component comprises an axially outer edge and wherein the sealing ring comprises an expandable material comprising an axially outer edge that lies axially aligned with or inwardly of the axially outer edge of the main body component when the sealing ring is at rest and lies axially outwardly of the axially outer edge of the main body component when the sealing ring is compressed.
