

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12394293
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Sandler; Ryan Nathaniel

Life safety device with machine learning based analytics

Abstract

A detector is provided. The detector includes a sensor configured to detect airborne particulates at a premises and processing circuitry. The processing circuitry is configured to determine a characteristic associated with the detected airborne particulates, compare the characteristic associated with the detected airborne particles to data associated with predefined characteristics of burned materials, detect, based at least on the comparison, presence of a fire; and determine, if the presence of the fire is detected, a characteristic of the fire based on the characteristic associated with the detected airborne particles and the comparison.

Inventors:	Sandler; Ryan Nathaniel (Santee, CA)
Applicant:	The ADT Security Corporation (Boca Raton, FL)
Family ID:	1000008763354
Assignee:	The ADT Security Corporation (Boca Raton, FL)
Appl. No.:	18/600274
Filed:	March 08, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240212469 A1	Jun. 27, 2024

Related U.S. Application Data

continuation parent-doc US 17845743 20220621 US 11961381 child-doc US 18600274

Publication Classification

Int. Cl.: G08B17/117 (20060101); G08B29/18 (20060101)

U.S. Cl.:

CPC **G08B17/117** (20130101); **G08B29/186** (20130101);

Field of Classification Search

CPC: G08B (21/12); G01N (2015/0046); G01N (1/2273); G01N (2015/03); G01N (33/0067)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6078050	12/1999	Castleman	250/342	G08B 25/002
7142105	12/2005	Chen	N/A	N/A
7170418	12/2006	Rose-Pehrsson et al.	N/A	N/A
8077046	12/2010	Wong	N/A	N/A
9677986	12/2016	Baldwin	N/A	G01S 7/481
9752436	12/2016	Pavetic et al.	N/A	N/A
9990824	12/2017	Rao et al.	N/A	N/A
10429289	12/2018	Knox et al.	N/A	N/A
11468761	12/2021	Antar	N/A	H04N 7/183
2014/0028803	12/2013	Hanses et al.	N/A	N/A
2017/0169683	12/2016	Ryder	N/A	N/A
2018/0266933	12/2017	Tamraz	N/A	G01N 35/00871
2022/0026334	12/2021	Tamraz	N/A	G01N 1/2273

Primary Examiner: Alam; Mirza F

Attorney, Agent or Firm: Weisberg I.P. Law, P.A.

Background/Summary

CROSS-REFERENCE TO RELATED PATENT APPLICATION (1) This application is a continuation of and claims priority to U.S. Utility patent application Ser. No. 17/845,743, filed on Jun. 21, 2022, entitled LIFE SAFETY DEVICE WITH MACHINE LEARNING BASED ANALYTICS, the entirety of which is incorporated herein by reference.

FIELD

(1) This disclosure relates in general to detection of an alarm condition at a premises, and in particular determining characteristics associated with detected airborne particulates.

BACKGROUND

(2) Some existing premises fire detection system rely on smoke detectors that generally use one of two methods for detecting smoke. The first, used by ionization smoke detectors, uses a small amount of radioactive material to ionize air between two conductive plates. The ionized air allows current to pass between the plates. If the space between the plates becomes obstructed by smoke, the current is disrupted. The disruption is detected by circuitry, which sounds an alarm. The second method, used by photoelectric smoke detectors, aims light away from a sensor within a chamber. When smoke enters the chamber, it reflects a portion of the light toward the sensor. Processing

circuitry in communication with the sensor then sounds an alarm.

(3) When fire occurs at a premises, smoke within a premises negatively impacts visibility. This impact is particularly potent when an occupant is unfamiliar with the premises or the route for egress involves small enclosures with short travel distances. Heat from the fire raises the temperature. As the temperature within the premises rises, the exposure time before an occupant suffers hyperthermia, body surface burns, respiratory tract burns, or other ailments drops rapidly. Toxins, including particulates and gasses, can be byproducts of the fire and can build up in the air within the premises, causing an occupant to suffer from, e.g., cardiac arrest, shortness of breath, and disorientation. As the fire consumes oxygen, the oxygen saturation level can drop as well, making it more difficult for an occupant to breathe.

(4) However, the aforementioned conditions within the premises are not homogenous, i.e. within the premises visibility, temperature, toxic conditions, and oxygen saturation can vary based on the location relative to the fire. It follows, then, that the conditions will vary along and among routes for ingress or egress. Moreover, the nature of the fire, including spread rate, spread pattern, temperature, and amount and nature of toxicity, can vary depending on the fuel source. For example, the nature of a lithium fire in a premises associated with solar energy storage will differ from other fire occurrences. Hence, existing fire alarm systems that monitor for an alarm condition within a premises based on whether a predefined threshold may fail to adequately analyze a fire condition.

SUMMARY

(5) The techniques of this disclosure generally relate to detection of a fire at a premises, and in particular comparing characteristics associated with detected airborne particulates to data associated with predefined characteristics of burned materials. A detector in accordance with the present disclosure may provide for earlier and more reliable detection of fire events while reducing or eliminating false alarms, as compared to more traditional detectors.

(6) According to one aspect of the invention, the present disclosure provides a detector. The detector has at least one sensor configured to detect airborne particulates at a premises. The detector further has processing circuitry. The processing circuitry is configured to determine at least one characteristic associated with the detected airborne particulates. The processing circuitry compares the at least one characteristic associated with the detected airborne particles to data associated with predefined characteristics of burned materials. Based on the comparison, the processing circuitry detects whether a fire is present at the premises. If the presence of the fire is detected, the processing circuitry determines at least one characteristic of the fire based on the at least one characteristic associated with the detected airborne particles and the comparison.

(7) According to some embodiments of this aspect, the processing circuitry is further configured to determine, based on the at least one characteristic of the fire, at least one fire response characteristic. The fire response characteristic includes at least one of an egress point and an ingress point. The egress point may be for, by way of example, occupants of the premises to safely exit the premises. The ingress point may be for, by way of example, emergency response personnel to safely enter the premises. According to some embodiments of this aspect, the processing circuitry is configured to indicate an aspect of the fire response characteristic. For example, the processing circuitry may transmit an alarm that indicates an egress or ingress point, which may assist to guide occupants or emergency response personnel. According to some embodiments of this aspect, the processing circuitry is further configured to determine a condition at the premises. According to some embodiments of this aspect, based on at least one characteristic associated with the detected airborne particulates, the condition may be a visibility condition. According to some embodiments of this aspect, the condition may be temperature. According to some embodiments of this aspect, the at least one characteristic of the fire includes at least one of burn rate, spread pattern, and an identity of a substance that is burning.

(8) According to some embodiments of this aspect, the sensor is configured to detect gas at the

premises. The processing circuitry is further configured to determine at least one characteristic associated with the detected gas. By way of non-limiting example, the characteristic of the detected gas may be a gas level for at least one of CO, CO₂, NCH, HCl, NO₂, and O₂. According to some embodiments of this aspect, the at least one characteristic of the fire comprises burn rate. According to some embodiments of this aspect, the at least one characteristic of the fire comprises the fire's spread pattern. According to some embodiments of this aspect, the at least one characteristic of the fire comprises an identity of a substance that is burning. According to some embodiments of this aspect, the processing circuitry is further configured to transmit an alarm signal where the alarm signal includes an indication of a fire response characteristic comprising one of an egress point and an ingress point.

(9) According to some embodiments of this aspect, the predefined characteristics of burned materials comprises at least one of smoke yield, smoke composition, soot yield, and soot composition. According to some embodiments of this aspect, the processing circuitry is further configured to request data specific to the detected airborne particulates from a database to retrieve the predefined characteristics of burned materials.

(10) According to some embodiments of this aspect, the processing circuitry is further configured to train a model to determine the characteristic of the fire using machine learning.

(11) In another aspect of the present invention, the present disclosure provides a method implemented by a detector is provided. Airborne particles at a premises are detected. At least one characteristic associated with the detected airborne particulates is determined. The at least one characteristic associated with the detected airborne particulates is compared to data associated with predefined characteristics of burned materials. The processing circuitry detects, based at least on the comparison, a presence of a fire. If the presence of the fire is detected, at least one characteristic of the fire is determined based on the at least one characteristic associated with the detected airborne particles and the comparison.

(12) According to some embodiments of this aspect, based on the at least one characteristic of the fire, at least one fire response characteristic is determined. The fire response characteristic includes at least one of an egress point and an ingress point. According to some embodiments of this aspect, an aspect of the fire response characteristic is indicated. For example, the processing circuitry may transmit an alarm that indicates an egress or ingress point, which may assist to guide occupants or emergency response personnel. According to some embodiments of this aspect, a condition at the premises is determined. In at least one aspect, based on at least one characteristic associated with the detected airborne particulates, the condition may be a visibility condition. According to some embodiments of this aspect, the condition may be temperature.

(13) According to some embodiments of this aspect, information is received from the at least one sensor where the information pertains to a detected gas at the premises, and determines at least one characteristic associated with the detected gas. According to some embodiments of this aspect, the characteristic of the detected gas a gas level for at least one of CO, CO₂, NCH, HCl, NO₂, and O₂. According to some embodiments of this aspect, the at least one characteristic of the fire includes burn rate. According to some embodiments of this aspect, the at least one characteristic of the fire includes spread pattern. According to some embodiments of this aspect, the at least one characteristic of the fire includes identity of a substance that is burning. In another aspect, an alarm signal is transmitted where the alarm signal includes an indication of a fire response characteristic including one of an egress point and ingress point.

(14) According to some embodiments of this aspect, the predefined characteristics of burned materials includes at least one of smoke yield, smoke composition, soot yield, and soot composition. According to some embodiments of this aspect, data specific to the detected airborne particulates is requested from a database to retrieve the predefined characteristics of burned materials. According to some embodiments of this aspect, a model is trained to determine the characteristic of the fire using machine learning. According to some embodiments of this aspect,

the at least one characteristic of the fire includes at least one of burn rate, spread pattern, and an identity of a substance that is burning.

(15) According to another aspect of the present invention, a detector is provided. The detector includes at least one sensor configured to detect airborne particulates at a premises, and processing circuitry. The processing circuitry is configured to determine at least one characteristic associated with the detected airborne particulates, request data specific to the detected airborne particulates from a database to retrieve predefined characteristics of burned materials, compare the at least one characteristic associated with the detected airborne particles to the predefined characteristics of burned materials, detect, based at least on the comparison, a presence of a fire, determine, if the presence of the fire is detected, at least one characteristic of the fire based on the at least one characteristic associated with the detected airborne particles and the comparison; and train a model to determine the characteristic of the fire using machine learning.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) A more complete understanding of the present invention, and the attendant advantages and features thereof, will be more readily understood by reference to the following detailed description when considered in conjunction with the accompanying drawings wherein:

(2) FIG. 1 is a schematic diagram of a system according to the present invention;

(3) FIG. 2 is a block diagram of several elements of the system according to some embodiments disclosed herein;

(4) FIG. 3 is a flowchart of an example process implemented by detector according to at least one embodiment disclosed herein; and

(5) FIG. 4 is a flowchart of an example process implemented by detector according to at least one embodiment disclosed herein.

DETAILED DESCRIPTION

(6) Before describing in detail exemplary embodiments, it is noted that the embodiments reside primarily in combinations of apparatus components and processing steps related to detection of an alarm condition at a premises, and in particular determining characteristics associated with detected airborne particulates. Accordingly, components have been represented where appropriate by conventional symbols in the drawings, showing only those specific details that are pertinent to understanding the embodiments so as not to obscure the disclosure with details that will be readily apparent to those of ordinary skill in the art having the benefit of the description herein.

(7) As used herein, relational terms, such as “first” and “second,” “top” and “bottom,” and the like, may be used solely to distinguish one entity or element from another entity or element without necessarily requiring or implying any physical or logical relationship or order between such entities or elements. The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the concepts described herein. As used herein, the singular forms “a,” “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprises,” “comprising,” “includes” and/or “including” when used herein, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

(8) In embodiments described herein, the joining term, “in communication with” and the like, may be used to indicate electrical or data communication, which may be accomplished by physical contact, induction, electromagnetic radiation, radio signaling, infrared signaling or optical signaling, for example. One having ordinary skill in the art will appreciate that multiple

components may interoperate and modifications and variations are possible of achieving the electrical and data communication.

(9) In some embodiments described herein, the term “coupled,” “connected,” and the like, may be used herein to indicate a connection, although not necessarily directly, and may include wired and/or wireless connections.

(10) The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the concepts described herein. As used herein, the singular forms “a,” “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprises,” “comprising,” “includes” and/or “including” when used herein, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

(11) In some embodiments, the general description elements in the form of “one of A and B” corresponds to A or B. In some embodiments, at least one of A and B corresponds to A, B or AB, or to one or more of A and B. In some embodiments, at least one of A, B and C corresponds to one or more of A, B and C, and/or A, B, C or a combination thereof.

(12) Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this disclosure belongs. It will be further understood that terms used herein should be interpreted as having a meaning that is consistent with their meaning in the context of this specification and the relevant art and will not be interpreted in an idealized or overly formal sense unless expressly so defined herein.

(13) Referring now to drawing figures in which like reference designators refer to like elements, there is shown in FIG. 1 an example system for detection of an alarm condition at a premises, and in particular determining characteristics associated with detected airborne particulates in accordance with the principles of the invention and designated generally as “**10**.” System **10** may be associated with premises **11** and may include one or more premises devices **12** (collectively referred to as premises device **12**) for monitoring a premises, one or more detectors **14** (collectively referred to as detector **14**) for performing life safety detections using analytics as described herein, a control unit **16** (also referred to as controller **16**) in communication with one or more of the premises devices **12**, detector **14** and remote monitoring center **18**.

(14) Premises device **12** may include one or more types of sensors, control and/or image capture devices. For example, the types of sensors may include various safety related sensors such as motion sensors, fire sensors, carbon monoxide sensors, flooding sensors and contact sensors, among other sensor types that are known in the art. The control devices may include, for example, one or more life style related devices configured to adjust at least one premises setting such as lighting, temperature, energy usage, door lock and power settings, among other settings associated with the premises or devices on the premises. Image capture devices may include a digital camera and/or video camera, among other image captures devices that are well known in the art. Detector **14** may communicate with control unit **16** via proprietary wireless communication protocols and may also use Wi-Fi, both of which are known in the art. Other communication technologies can also be used, and the use of Wi-Fi is merely for example. Those of ordinary skill in the art will also appreciate that various additional sensors and control and/or image capture devices may relate to life safety or life style depending on both what the sensors, control and image capture devices do and how these sensors, control and image devices are used by system **10**.

(15) Detector **14** may correspond to an artificial intelligence (AI) based detector that is configured to provide one or more functions described herein. Detector **14** may be in communication with one or more networks for communicating with remote monitoring center **18**, one or more databases and/or one or more servers. Detector **14** includes machine learning unit **19** that is configured to perform one or more detector **14** functions as described herein such as with respect to AI based

alarm condition analysis and/or alarm triggering. For example, detector **14** may analyze conditions associated with fire **20**.

(16) Control unit **16** may provide management functions such as power management, premises device management and alarm management, among other functions. In particular, control unit **16** may manage one or more life safety and life style features. Life safety features may correspond to security system functions and settings associated with premises conditions that may result in life threatening harm to a person such as carbon monoxide detection and intrusion detection. Life style features may correspond to security system functions and settings associated with video capturing devices and non-life-threatening conditions of the premises such as lighting and thermostat functions.

(17) Control unit **16** may communicate with one or more network via one or more communication links. In particular, the communications links may be broadband communication links such as a wired cable modem or Ethernet communication link, and digital cellular communication link, e.g., long term evolution (LTE) and/or New Radio (NR) based link, among other broadband communication links known in the art. Broadband as used herein may refer to a communication link other than a plain old telephone service (POTS) line. Ethernet communication link may be an IEEE 802.3 or 802.11 based communication link. The network may be a wide area network, local area network, wireless local network and metropolitan area network, among other networks known in the art. The network provides communications between one or more of control unit **16**, remote monitoring center **18** and database(s).

(18) Example implementations, in accordance with one or more embodiments, of detector **14** discussed in the preceding paragraphs will now be described with reference to FIG. 2.

(19) The detector **14** includes processing circuitry **22**, a sensor **24**, and a communication interface **26**. The processing circuitry **22** may include a processor **28** and a memory **30**. In particular, in addition to or instead of a processor, such as a central processing unit, and memory, the processing circuitry **22** may comprise integrated circuitry for processing and/or control, e.g., one or more processors and/or processor cores and/or FPGAs (Field Programmable Gate Array) and/or ASICs (Application Specific Integrated Circuitry) adapted to execute instructions. The processor **28** may be configured to access (e.g., write to and/or read from) the memory **30**, which may comprise any kind of volatile and/or nonvolatile memory, e.g., cache and/or buffer memory and/or RAM (Random Access Memory) and/or ROM (Read-Only Memory) and/or optical memory and/or EPROM (Erasable Programmable Read-Only Memory).

(20) Thus, the detector **14** further has software stored internally in, for example, memory **30**, or stored in external memory (e.g., database, storage array, network storage device, etc.) accessible by the detector **14** via an external connection. The software may be executable by the processing circuitry **22**. The processing circuitry **22** may be configured to control any of the methods and/or processes described herein and/or to cause such methods, and/or processes to be performed, e.g., by detector **14**. Processor **28** corresponds to one or more processors **28** for performing detector **14** functions described herein. The memory **30** is configured to store data, programmatic software code and/or other information described herein. In some embodiments, the software may include instructions that, when executed by the processor **28** and/or processing circuitry **22**, causes the processor **28** and/or processing circuitry **22** to perform the processes described herein with respect to detector **14**. For example, processing circuitry **22** of the detector **14** may include machine learning unit **19** which is configured to perform one or more functions described herein such as with respect to AI based alarm triggering. In particular, machine learning unit **19** is trained based on the processes and methods disclosed herein. Thus, the detector **14** may learn how to more accurately and quickly detect a fire **20** and determine an appropriate response (as compared with known solutions). For example, deployment of the detector **14** on the premises **11** allows the detector **14** to gather information regarding typical, expected environmental conditions on the premises **11**. This may include, for example, normal and expected deviations of the environmental

conditions that do not indicate presence of a fire or warrant an alert. The machine learning unit **19** thereby learns what conditions are normal, and can more readily and accurately identify environmental conditions that fall outside normal conditions. This leads to more accurate detection with fewer false positives.

(21) For example, the detector **14** detects the presence of a fire **20** within the premises **11**. In at least one embodiment, the detector **14** indicates to occupants a safe egress point and indicates to emergency response personnel a safe ingress point. In at least one embodiment, the detector **14** additionally indicates a path for ingress and egress. In doing so, the detector **14** accounts for characteristics of the fire, including location, spread rate, and spread pattern, as further described herein.

(22) The detector **14** communicates via the communication interface **26** which may wirelessly communicate with one or more devices on an existing local area network (such as via a home or commercial Wi-Fi router) and/or via Bluetooth, ZigBee, or Zwave, or may instead or additionally communicate by wire. The detector **14** accordingly may be in communication, either directly or indirectly, with devices including but not limited to other detectors (including detectors in accordance with the present disclosure), external alarms, external displays, and local or remote databases.

(23) In at least one embodiment, detector **14** includes one or more sensors **24** (collectively referred to as sensor **24**) that are configured to detect airborne particulates at the premises **11**, such as soot (often but not necessarily referring to carbonaceous particulates produced from incomplete combustion) and smoke (often but not necessarily referring to byproducts of combustion). The sensor **24** may additionally be configured to detect at least one gas at the premises **11**, which may be a byproduct of combustion. The gas may be, for example, at least one of CO, CO₂, NCH, HCl, NO₂, and O₂, although sensor **24** may be configured to detect one or more other gases or fluids. In at least one embodiment, the sensor **24** can detect the temperature at the premises **11** and/or of the fire **20**. In at least one embodiment, the sensor **24** can detect at least one of volatile organic compounds (VOCs), bacteria, and viruses. For example, sensor **24** may detect one or more characteristics associated with VOCs, bacteria and/or a virus based at least on airborne particulates where the detector **14** is configured to access a database of known signatures (e.g., VOC signatures, bacteria signatures, virus signatures) to compare the detected one or more characteristics (e.g., molecular structure of particulate) with the known signatures. Based at least on the comparison, the detector **14** is able to trigger some action. Examples of such actions are described herein.

Therefore, in one or more embodiments, detector **14** may be configured with various sensors **24** for performing separate detections of airborne particulates, i.e., sensor **24a** detects airborne particulates for fire related determinations while sensor **24b** detects airborne particulates for VOC related determinations, etc.

(24) In at least one embodiment, the detector **14** may provide various information to emergency response personnel. The information includes one or more environmental conditions before, during, and after an alert, as compared to the expected environmental conditions. This information is additionally shared with any stakeholders, including but not limited to any control systems or monitoring systems. In another example, the information provided by the detector **14** may indicate that it is unsafe for first responders to enter the premises/building based on one or more determined characteristics associated with the detected airborne particles.

(25) FIG. 3 is a flowchart of an example process in a detector according to some embodiment of the present invention. One or more blocks described herein may be performed by one or more elements of detector **14** such as by one or more of processing circuitry **36** (including the machine learning unit **19**), processor **38**, etc. Detector **14** is configured to detect (Block **S100**) airborne particulates at a premises. Detector **14** is configured to determine (Block **S102**) at least one characteristic associated with the detected airborne particulates. Detector **14** is configured to compare (Block **S104**) the at least one characteristic associated with the detected airborne particles

to data associated with predefined characteristics of burned materials.

(26) Detector **14** is configured to detect (Block **S106**), based at least on the comparison, a presence of a fire **20**. Detector **14** is configured to determine (Block **S108**), if the presence of the fire **20** is detected, at least one characteristic of the fire **20** based on the at least one characteristic associated with the detected airborne particles and the comparison.

(27) According to some embodiments, the detector **14** is configured to determine, based on the at least one characteristic of the fire **20**, at least one fire response characteristic. According to some embodiments, the fire response characteristic includes at least one of an egress point and an ingress point. According to some embodiments, the detector **14** is configured to determine, based on the at least one characteristic associated with the detected airborne particulates, a visibility condition.

(28) According to some embodiments, the detector **14** is configured to detect gas at the premises, and the processing circuitry **22** is configured to determine at least one characteristic associated with the detected gas. According to some embodiments, the characteristic of the detected gas is a gas level for at least one of CO, CO₂, NCH, HCl, NO₂, and O₂. According to some embodiments, at least one characteristic of the fire comprises burn rate. According to some embodiments, the at least one characteristic of the fire includes at least one of burn rate, spread pattern, and an identity of a substance that is burning.

(29) According to some embodiments, the characteristic of the fire includes spread pattern. According to some embodiments, the characteristic of the fire comprises an identity of a substance that is burning. According to some embodiments, the processing circuitry **22** is configured to transmit an alarm signal where the alarm signal includes an indication of a fire response characteristic including one of an egress point and an ingress point. According to some embodiments, the predefined characteristics of burned materials includes at least one of smoke yield, smoke composition, soot yield, and soot composition.

(30) According to some embodiments, the processing circuitry **22** is configured to request data specific to the detected airborne particulates from a database to retrieve the predefined characteristics of burned materials. According to some embodiments, the processing circuitry **22** is configured to train a model to determine the characteristic of the fire **20** using machine learning.

(31) FIG. **4** is a flowchart of an example process in a detector according to some embodiment of the present invention. One or more blocks described herein may be performed by one or more elements of detector **14** such as by one or more of processing circuitry **36** (including the machine learning unit **19**), processor **28**, etc. Detector **14** includes at least one sensor that is configured to detect (Block **S110**) airborne particulates at a premises **11**. Detector **14** is configured to determine (Block **S112**) at least one characteristic associated with the detected airborne particulates. Detector **14** is configured to request (Block **S114**) data specific to the detected airborne particulates from a database **32** to retrieve predefined characteristics of burned materials. Detector **14** is configured to compare (Block **S116**) the at least one characteristic associated with the detected airborne particles to the predefined characteristics of burned materials.

(32) Detector **14** is configured to detect (Block **S118**), based at least on the comparison, a presence of a fire **20**. Detector **14** is configured to determine (Block **S120**), if the presence of the fire **20** is detected, at least one characteristic of the fire **20** based on the at least one characteristic associated with the detected airborne particles and the comparison. Detector **14** is configured to train (Block **S122**) a model to determine the characteristic of the fire using machine learning.

(33) According to some embodiments, the detector **14** is configured to determine, based on the at least one characteristic of the fire **20**, at least one fire response characteristic. According to some embodiments, the fire response characteristic includes at least one of an egress point and an ingress point. According to some embodiments, the detector **14** is configured to determine, based on the at least one characteristic associated with the detected airborne particulates, a visibility condition.

(34) According to some embodiments, the detector **14** is configured to detect gas at the premises **11**, and the processing circuitry **22** is configured to determine at least one characteristic associated

with the detected gas. According to some embodiments, the characteristic of the detected gas is a gas level for at least one of CO, CO₂, NCH, HCl, NO₂, and O₂. According to some embodiments, at least one characteristic of the fire **20** includes a burn rate. According to some embodiments, the characteristic of the fire **20** includes a spread pattern. According to some embodiments, the at least one characteristic of the fire includes at least one of burn rate, spread pattern, and an identity of a substance that is burning.

(35) According to some embodiments, the characteristic of the fire **20** includes an identity of a substance that is burning. According to some embodiments, the processing circuitry **22** is configured to transmit an alarm signal where the alarm signal includes an indication of a fire **20** response characteristic including one of an egress point and an ingress point. According to some embodiments, the predefined characteristics of burned materials comprises at least one of smoke yield, smoke composition, soot yield, and soot composition.

(36) In some embodiments by way of non-limiting example, the predefined characteristics of burned materials includes known yields from the combustion of various fuel sources. The yields may include smoke yield, smoke composition, soot yield, and soot composition.

(37) In some embodiments, if fire **20** is detected, then a characteristic of the fire **20** based on the characteristic associated with the detected airborne particles and the comparison is determined by the detector **14**. The characteristic of the fire **20** may vary depending on, for example, inherent and environmental factors. Inherent factors include the fuel source. Environmental factors include location of the fire on the premises. The determined characteristic may include one of the fire **20**'s burn rate, spread pattern, and a fuel source (i.e., at least one substance that is burning).

(38) In some embodiments, based on information received from the sensor **24**, the processing circuitry **22** determines at least one condition at the premises **11**. In the case where the sensor **24** detects airborne particulates, the processing circuitry **22** determines at least one characteristic of the airborne particulates. Other examples of characteristics of the airborne particulates determined in the various embodiments include the composition of the particulates.

(39) Further, detector **14** compares at least one characteristic of the detected airborne particulates with predefined characteristics of burned materials. By way of non-limiting example, the predefined characteristics of burned materials includes known yields from the combustion of various fuel sources. The yields may include smoke yield, smoke composition, soot yield, and soot composition. In at least one embodiment, the processing circuitry **22** requests the predefined characteristics of burned materials from a database **32**. The database **32** may be on a local network or may be remote. The request may be performed using the communication interface **26**.

(40) In some embodiments, characteristics of the fire **20** may vary depending on, for example, inherent and environmental factors. Inherent factors include the fuel source. Environmental factors include location of the fire **20** on the premises **11**.

(41) In the various embodiments, the determined characteristic may include one of the fire **20**'s burn rate, spread pattern, and a fuel source (i.e., at least one substance that is burning).

(42) In some embodiments, the ingress and/or egress point may be indicated by transmission by the processing circuitry **22** of an alarm signal. The alarm signal may result in an auditory alarm, such as a siren or verbal announcement, or a visual alarm, such as a light pattern or indicia on signage or a display.

(43) In at least one embodiment, the processing circuitry **22** accounts for various characteristics of the premises **11**, including structural features such as layout of interior and exterior spaces. The processing circuitry **22** additionally accounts for the characteristics of the fire **20**, such as location within the premises **11** and speed and pattern of spread. Accordingly, the processing circuitry **22** can then determine a fire **20** response characteristic that includes a path through the premises **11** for occupants to safely exit. Additionally or alternatively, the processing circuitry **22** may determine a point of ingress for emergency response personnel to enter the premises **11** to, for example, address the fire **20** or attend to occupants.

(44) As will be appreciated by one of skill in the art, the concepts described herein may be embodied as a method, data processing system, computer program product and/or computer storage media storing an executable computer program. Accordingly, the concepts described herein may take the form of an entirely hardware embodiment, an entirely software embodiment or an embodiment combining software and hardware aspects all generally referred to herein as a “circuit” or “module.” Any process, step, action and/or functionality described herein may be performed by, and/or associated to, a corresponding module, which may be implemented in software and/or firmware and/or hardware. Furthermore, the disclosure may take the form of a computer program product on a tangible computer usable storage medium having computer program code embodied in the medium that can be executed by a computer. Any suitable tangible computer readable medium may be utilized including hard disks, CD-ROMs, electronic storage devices, optical storage devices, or magnetic storage devices.

(45) Some embodiments are described herein with reference to flowchart illustrations and/or block diagrams of methods, systems and computer program products. It will be understood that each block of the flowchart illustrations and/or block diagrams, and combinations of blocks in the flowchart illustrations and/or block diagrams, can be implemented by computer program instructions. These computer program instructions may be provided to a processor of a general purpose computer (to thereby create a special purpose computer), special purpose computer, or other programmable data processing apparatus to produce a machine, such that the instructions, which execute via the processor of the computer or other programmable data processing apparatus, create means for implementing the functions/acts specified in the flowchart and/or block diagram block or blocks.

(46) These computer program instructions may also be stored in a computer readable memory or storage medium that can direct a computer or other programmable data processing apparatus to function in a particular manner, such that the instructions stored in the computer readable memory produce an article of manufacture including instruction means which implement the function/act specified in the flowchart and/or block diagram block or blocks.

(47) The computer program instructions may also be loaded onto a computer or other programmable data processing apparatus to cause a series of operational steps to be performed on the computer or other programmable apparatus to produce a computer implemented process such that the instructions which execute on the computer or other programmable apparatus provide steps for implementing the functions/acts specified in the flowchart and/or block diagram block or blocks.

(48) It is to be understood that the functions/acts noted in the blocks may occur out of the order noted in the operational illustrations. For example, two blocks shown in succession may in fact be executed substantially concurrently or the blocks may sometimes be executed in the reverse order, depending upon the functionality/acts involved. Although some of the diagrams include arrows on communication paths to show a primary direction of communication, it is to be understood that communication may occur in the opposite direction to the depicted arrows.

(49) Computer program code for carrying out operations of the concepts described herein may be written in an object oriented programming language such as Python, Java® or C++. However, the computer program code for carrying out operations of the disclosure may also be written in conventional procedural programming languages, such as the “C” programming language. The program code may execute entirely on the user's computer, partly on the user's computer, as a stand-alone software package, partly on the user's computer and partly on a remote computer or entirely on the remote computer. In the latter scenario, the remote computer may be connected to the user's computer through a local area network (LAN) or a wide area network (WAN), or the connection may be made to an external computer (for example, through the Internet using an Internet Service Provider).

(50) Many different embodiments have been disclosed herein, in connection with the above

description and the drawings. It will be understood that it would be unduly repetitious and obfuscating to literally describe and illustrate every combination and subcombination of these embodiments. Accordingly, all embodiments can be combined in any way and/or combination, and the present specification, including the drawings, shall be construed to constitute a complete written description of all combinations and subcombinations of the embodiments described herein, and of the manner and process of making and using them, and shall support claims to any such combination or subcombination.

(51) It will be appreciated by persons skilled in the art that the present invention is not limited to what has been particularly shown and described herein above. In addition, unless mention was made above to the contrary, it should be noted that all of the accompanying drawings are not to scale. A variety of modifications and variations are possible in light of the above teachings without departing from the scope and spirit of the invention, which is limited only by the following claims.

Claims

1. A detector, comprising: at least one sensor configured to detect airborne particulates at a premises; at least one processor in communication with the at least one sensor; at least one memory storing instructions that, when executed by the at least one processor, cause the at least one processor to: determine at least one characteristic associated with the airborne particulates, the at least one characteristic associated with the airborne particulates comprising a composition of the airborne particulates; compare the at least one characteristic associated with the airborne particulates to data associated with predefined characteristics of reference particulates; detect, based at least on a result of the comparison, a presence of an alarm condition; and determine, in response to the presence of the alarm condition being detected, at least one characteristic of the alarm condition based at least on the at least one characteristic associated with the airborne particulates and the result of the comparison, the at least one characteristic of the alarm condition comprising an identity of a substance that is a source of the airborne particulates; and indicate an egress point or an ingress point based on the at least one characteristic of the alarm condition.
2. The detector of claim 1, wherein the at least one characteristic associated with the airborne particulates further comprises at least one of a spread pattern or a burn rate.
3. The detector of claim 1, wherein the instructions are further configured to cause the at least one processor to determine, based on the at least one characteristic associated with the airborne particulates, a visibility condition at the premises.
4. The detector of claim 1, wherein the airborne particulates correspond to a detected gas.
5. The detector of claim 4, wherein the detected gas comprises at least one of carbon monoxide (CO), carbon dioxide (CO₂), nitrogen dioxide (NCH), hydrochloric acid (HCL), nitrogen dioxide (NO₂), or oxygen (O₂).
6. The detector of claim 4, wherein the at least one characteristic associated with the detected gas further comprises a burn rate of the detected gas.
7. The detector of claim 6, wherein the at least one characteristic associated with the detected gas further comprises a gas level.
8. The detector of claim 7, wherein the instructions are further configured to cause the at least one processor to transmit an alarm signal based at least on at least one of the burn rate of the detected gas or the gas level.
9. The detector of claim 1, wherein the instructions are further configured to cause the at least one processor to obtain the data associated with the predefined characteristics of the reference particulates from a remote database.
10. The detector of claim 1, wherein the sensor is further configured to detect at least one of volatile organic compounds or bacteria.
11. The detector of claim 1, wherein the sensor is further configured to detect viruses.

12. The detector of claim 1, wherein the airborne particulates are at least one of volatile organic compounds, bacteria, or viruses; and the instructions are further configured to cause the at least one processor to request data specific to the at least one of volatile organic compounds, bacteria, or viruses from a database.
 13. The detector of claim 1, wherein the instructions are further configured to cause the at least one processor to apply a machine learning model to determine the at least one characteristic associated with the airborne particulates.
 14. A method implemented by a detector, the detector comprising at least one sensor configured to detect airborne particulates at a premises, the method comprising: determining at least one characteristic associated with the airborne particulates, the at least one characteristic associated with the airborne particulates comprising a composition of the airborne particulates; comparing the at least one characteristic associated with the airborne particulates to data associated with predefined characteristics of reference particulates; detecting, based at least on a result of the comparison, a presence of an alarm condition; and determining, in response to the presence of the alarm condition being detected, at least one characteristic of the alarm condition based at least on the at least one characteristic associated with the airborne particulates and the result of the comparison, the at least one characteristic of the alarm condition comprising an identity of a substance that is a source of the airborne particulates; and indicating an egress point or an ingress point based on the at least one characteristic of the alarm condition.
 15. The method of claim 14, where the at least one characteristic associated with the airborne particulates further comprises at least one of a spread pattern or a burn rate.
 16. The method of claim 14, further comprising determining, based on the at least one characteristic associated with the airborne particulates, a visibility condition at the premises.
 17. The method of claim 14, wherein the airborne particulates correspond to a detected gas; and the at least one characteristic associated with the detected gas further comprises at least one of a burn rate of the detected gas or a gas level.
 18. The method of claim 17, further comprising transmitting an alarm signal based at least on at least one of the burn rate of the detected gas or the gas level.
 19. The method of claim 14, wherein the sensor is further configured to detect at least one of volatile organic compounds or bacteria.
 20. The method of claim 17, wherein the airborne particulates are at least one of volatile organic compounds, bacteria, or viruses; and the method further comprising requesting data specific to the at least one of volatile organic compounds, bacteria, or viruses from a database.
-