

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12391424
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Darr; Richard C. et al.

Lightweight plastic container and preform

Abstract

A plastic container includes a hollow body portion including a lower supporting base portion; a sidewall portion extending upwardly from the base portion; and a neck portion extending upwardly from the sidewall portion. The neck portion includes a support flange having an upper and lower surface, at least one thread, and a dispensing opening at the top of the neck portion. In embodiments, a closure may be provided to form an assembly. A preform and method for making a container are also disclosed.

Inventors: Darr; Richard C. (Medina, OH), Morgan; Edward V. (Northville, MI)

Applicant: Plastipak Packaging, Inc. (Plymouth, MI)

Family ID: 1000008765508

Assignee: Plastipak Packaging, Inc. (Plymouth, MI)

Appl. No.: 18/614065

Filed: March 22, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240228101 A1	Jul. 11, 2024

Related U.S. Application Data

continuation parent-doc US 18377493 20231006 US 11939104 child-doc US 18614065
continuation parent-doc US 18084064 20221219 US 11780634 child-doc US 18377493
continuation parent-doc US 17314721 20210507 US 11560250 child-doc US 18084064
continuation parent-doc US 16598452 20191010 ABANDONED child-doc US 17314721
continuation parent-doc US 16013139 20180620 US 10457437 child-doc US 16598452
continuation parent-doc US 16012302 20180619 US 10266299 child-doc US 16013139
continuation parent-doc US 15495084 20170424 US 10023345 child-doc US 16012302

continuation parent-doc US 15404731 20170112 US 9738409 child-doc US 15495084
continuation parent-doc US 15383179 20161219 US 9850019 child-doc US 15404731
continuation parent-doc US 15220731 20160727 US 9522759 child-doc US 15383179
continuation parent-doc US 14803505 20150720 US 9403310 child-doc US 15220731
continuation parent-doc US 14688734 20150416 US 9139326 child-doc US 14803505
continuation parent-doc US 14511848 20141010 US 9033168 child-doc US 14688734
division parent-doc US 11749501 20070516 US 8857637 child-doc US 14511848

Publication Classification

Int. Cl.: **B65D1/02** (20060101); **B29B11/08** (20060101); **B29B11/14** (20060101); **B29C48/14** (20190101); **B29C49/00** (20060101); **B29C49/06** (20060101); **B29C49/08** (20060101); **B29C49/46** (20060101); **B29K67/00** (20060101); **B29K105/00** (20060101); **B29K105/26** (20060101); **B29L31/00** (20060101); **B65D1/40** (20060101); **B65D1/44** (20060101); **B65D1/46** (20060101); **B65D43/02** (20060101)

U.S. Cl.:

CPC **B65D1/0246** (20130101); **B29B11/08** (20130101); **B29B11/14** (20130101); **B29C48/141** (20190201); **B29C49/06** (20130101); **B29C49/071** (20220501); **B29C49/08** (20130101); **B65D1/0207** (20130101); **B65D1/023** (20130101); **B65D1/0284** (20130101); **B65D1/40** (20130101); **B65D1/44** (20130101); **B65D1/46** (20130101); **B65D43/0235** (20130101); B29C2049/4664 (20130101); B29C2949/072 (20220501); B29C2949/073 (20220501); B29C2949/0732 (20220501); B29C2949/0733 (20220501); B29C2949/074 (20220501); B29C2949/0773 (20220501); B29C2949/0774 (20220501); B29C2949/0777 (20220501); B29C2949/0812 (20220501); B29C2949/0816 (20220501); B29C2949/0821 (20220501); B29C2949/0822 (20220501); B29C2949/0825 (20220501); B29C2949/0829 (20220501); B29C2949/0831 (20220501); B29C2949/0832 (20220501); B29C2949/0833 (20220501); B29C2949/0834 (20220501); B29C2949/0872 (20220501); B29K2067/00 (20130101); B29K2067/003 (20130101); B29K2105/258 (20130101); B29K2105/26 (20130101); B29L2031/7158 (20130101); Y10T428/1352 (20150115); Y10T428/1397 (20150115)

Field of Classification Search

CPC: B29B (11/14); B29B (11/08); B29C (48/141); B29C (49/06); B29C (49/071); B29C (49/08); B29C (2049/4664); B29C (2949/072); B29C (49/46); B29C (2949/073); B29C (2949/0733); B29C (2949/0732); B29C (2949/074); B29C (2949/0773); B29C (2949/0774); B29C (2949/0777); B29C (2949/0821); B29C (2949/0825); B29C (2949/0812); B29C (2949/0829); B29C (2949/0816); B29C (2949/0822); B29C (2949/0831); B29C (2949/0832); B29C (2949/0833); B29C (2949/0872); B29C (2949/0834); B29C (49/087); B29C (2049/023); B29C (49/42808); B29C (2049/7879); B29C (2949/0715); B65D (1/0246); B65D (1/023); B65D (1/40); B65D (1/44); B65D (1/0284); B65D (1/0207); B65D (1/46); B65D (43/0235); B29K (2067/00); B29K (2067/003); B29K (2105/258); B29K (2105/26); Y10T (428/1397); Y10T (428/1352); B29L (2031/7158)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
198528	12/1876	Woodward	N/A	N/A
2367317	12/1944	Thomas	N/A	N/A
2914206	12/1958	Lowen	N/A	N/A
3235115	12/1965	Duke	N/A	N/A
3398427	12/1967	John	N/A	N/A
3470282	12/1968	Scalora	N/A	N/A
3559833	12/1970	Alonso	N/A	N/A
3598270	12/1970	Adomaitis	N/A	N/A
3733309	12/1972	Wyeth et al.	N/A	N/A
3774795	12/1972	Leenaards	N/A	N/A
3830893	12/1973	Steingiser	N/A	N/A
3881622	12/1974	Dockery	N/A	N/A
4098419	12/1977	Virog, Jr. et al.	N/A	N/A
4117050	12/1977	Appel et al.	N/A	N/A
4126658	12/1977	Rupert et al.	N/A	N/A
4156490	12/1978	Peraboni	N/A	N/A
4177906	12/1978	Von Hagel	N/A	N/A
4180175	12/1978	Virog, Jr. et al.	N/A	N/A
4301937	12/1980	Von Hagel	N/A	N/A
4307137	12/1980	Ota et al.	N/A	N/A
4342395	12/1981	Brown	N/A	N/A
4342398	12/1981	Chang	N/A	N/A
4401227	12/1982	Pehr	N/A	N/A
4463056	12/1983	Steele	N/A	N/A
4469234	12/1983	Deussen	N/A	N/A
4534930	12/1984	Nohara	N/A	N/A
4541536	12/1984	Davis et al.	N/A	N/A
4573599	12/1985	Fillmore	N/A	N/A
4606723	12/1985	Pasternicki	N/A	N/A
4615667	12/1985	Roy	N/A	N/A
4715504	12/1986	Chang et al.	N/A	N/A
4756438	12/1987	Ryder	N/A	N/A
4830251	12/1988	Conrad	N/A	N/A
4842153	12/1988	Hulon	N/A	N/A
4901873	12/1989	Weiler	N/A	N/A
4928835	12/1989	Collette et al.	N/A	N/A
4936474	12/1989	Szczesniak et al.	N/A	N/A
5027964	12/1990	Banich, Sr.	N/A	N/A
5040692	12/1990	Julian	N/A	N/A
5104704	12/1991	Labes et al.	N/A	N/A
5143235	12/1991	Repp	N/A	N/A
5366774	12/1993	Pinto et al.	N/A	N/A
5383779	12/1994	Robinson	N/A	N/A
5403538	12/1994	Maeda	N/A	N/A
5409983	12/1994	Jones et al.	N/A	N/A
5431291	12/1994	LaBombarbe, Jr.	N/A	N/A
5447766	12/1994	Orimoto et al.	N/A	N/A
5450972	12/1994	Zemlo	N/A	N/A
5464106	12/1994	Slat et al.	N/A	N/A

5480045	12/1995	Molinaro et al.	N/A	N/A
5593055	12/1996	Repp et al.	N/A	N/A
5645183	12/1996	Slat et al.	N/A	N/A
5647495	12/1996	Orimoto et al.	N/A	N/A
5674448	12/1996	Slat et al.	N/A	N/A
5676267	12/1996	Slat et al.	N/A	N/A
5688572	12/1996	Slat et al.	N/A	N/A
5690244	12/1996	Darr	N/A	N/A
5756172	12/1997	Semersky	N/A	N/A
5804305	12/1997	Slat et al.	N/A	N/A
5850932	12/1997	Beck et al.	N/A	N/A
5888598	12/1998	Brewster et al.	N/A	N/A
5918753	12/1998	Ogg et al.	N/A	N/A
5927525	12/1998	Darr et al.	N/A	N/A
5951938	12/1998	Takeuchi et al.	N/A	N/A
5954216	12/1998	Meisner et al.	N/A	N/A
5971184	12/1998	Krishnakumar et al.	N/A	N/A
5975320	12/1998	Bietzer et al.	N/A	N/A
6006930	12/1998	Dreyer et al.	N/A	N/A
6011132	12/1999	Paschke et al.	N/A	N/A
6041953	12/1999	Goodall	N/A	N/A
6060140	12/1999	Sprayberry et al.	N/A	N/A
6063325	12/1999	Nahill et al.	N/A	N/A
6082568	12/1999	Flanagan	N/A	N/A
6085924	12/1999	Henderson	N/A	N/A
6105800	12/1999	Czesak	N/A	N/A
6168749	12/2000	Koch	N/A	N/A
6203870	12/2000	Darr	N/A	N/A
6217818	12/2000	Collette et al.	N/A	N/A
6276546	12/2000	Davis et al.	N/A	N/A
6298638	12/2000	Bettle	N/A	N/A
6305564	12/2000	Takeuchi et al.	N/A	N/A
6349838	12/2001	Saito et al.	N/A	N/A
6391408	12/2001	Hutchinson	N/A	N/A
6461697	12/2001	Slat et al.	N/A	N/A
6464486	12/2001	Barray et al.	N/A	N/A
6548133	12/2002	Schmidt et al.	N/A	N/A
6557714	12/2002	Babcock et al.	N/A	N/A
6568156	12/2002	Silvers et al.	N/A	N/A
6569370	12/2002	Amin et al.	N/A	N/A
6635325	12/2002	Hebert	N/A	N/A
6637611	12/2002	Luch	N/A	N/A
6641774	12/2002	Slat et al.	N/A	N/A
6673303	12/2003	White et al.	N/A	N/A
6745919	12/2003	Moros	N/A	N/A
6749796	12/2003	Hansen	N/A	N/A
6779677	12/2003	Chupak	N/A	N/A
6796450	12/2003	Prevot et al.	N/A	N/A
6808820	12/2003	Lee et al.	N/A	N/A
6837390	12/2004	Lane et al.	N/A	N/A

6841262	12/2004	Beck et al.	N/A	N/A
6854614	12/2004	Sprick	N/A	N/A
6929139	12/2004	Darr	N/A	N/A
6939498	12/2004	Wong	N/A	N/A
6939591	12/2004	Hutchinson et al.	N/A	N/A
6948630	12/2004	Julian et al.	N/A	N/A
6971530	12/2004	Darr	N/A	N/A
6977104	12/2004	Nahill et al.	N/A	N/A
6991336	12/2005	Matsui	N/A	N/A
7028857	12/2005	Peronek	N/A	N/A
7037099	12/2005	Linke et al.	N/A	N/A
7080747	12/2005	Lane et al.	N/A	N/A
7150902	12/2005	Farha	N/A	N/A
7207451	12/2006	Taylor et al.	N/A	N/A
7226648	12/2006	Al Ghatta et al.	N/A	N/A
7332204	12/2007	Hutchinson et al.	N/A	N/A
7531125	12/2008	Dygert	N/A	N/A
7531226	12/2008	Lee et al.	N/A	N/A
7553441	12/2008	Shi	N/A	N/A
7574938	12/2008	Andrews	N/A	N/A
7654168	12/2009	O'Brien	N/A	N/A
7708159	12/2009	Darr	N/A	N/A
7735663	12/2009	Tanaka et al.	N/A	N/A
7770745	12/2009	Weissmann et al.	N/A	N/A
7798357	12/2009	Hanafusa et al.	N/A	N/A
7820257	12/2009	Kjorlaug et al.	N/A	N/A
7882977	12/2010	Johnson	N/A	N/A
7918355	12/2010	Penny	N/A	N/A
7918356	12/2010	Penny	N/A	N/A
7976767	12/2010	Ungrady et al.	N/A	N/A
8037734	12/2010	Hanafusa et al.	N/A	N/A
8132439	12/2011	Hanafusa et al.	N/A	N/A
8308002	12/2011	Penny	N/A	N/A
8308005	12/2011	Penny	N/A	N/A
8317042	12/2011	Cervený	N/A	N/A
8413829	12/2012	Penny	N/A	N/A
8499601	12/2012	Hanafusa et al.	N/A	N/A
8740001	12/2013	Hanafusa et al.	N/A	N/A
8857637	12/2013	Darr	N/A	N/A
9033168	12/2014	Darr	N/A	N/A
9139326	12/2014	Darr	N/A	N/A
9403310	12/2015	Darr	N/A	N/A
9522759	12/2015	Darr	N/A	N/A
9738409	12/2016	Darr	N/A	N/A
9850019	12/2016	Darr	N/A	N/A
10023345	12/2017	Darr	N/A	N/A
10214312	12/2018	Darr	N/A	N/A
10266299	12/2018	Darr	N/A	N/A
10457437	12/2018	Darr	N/A	N/A
11560250	12/2022	Darr	N/A	N/A

11780634	12/2022	Darr	N/A	N/A
11834222	12/2022	Darr	N/A	N/A
11939104	12/2023	Darr	N/A	N/A
2001/0038171	12/2000	Darr	N/A	N/A
2001/0054779	12/2000	Collette et al.	N/A	N/A
2002/0022099	12/2001	Schmidt et al.	N/A	N/A
2002/0134747	12/2001	Babcock et al.	N/A	N/A
2002/0162818	12/2001	Williams	N/A	N/A
2003/0001311	12/2002	Collette et al.	N/A	N/A
2003/0041568	12/2002	Seidita	N/A	N/A
2003/0071007	12/2002	Ma et al.	N/A	N/A
2003/0102278	12/2002	Chupak	N/A	N/A
2003/0116522	12/2002	Julian et al.	N/A	N/A
2003/0155320	12/2002	Peronek et al.	N/A	N/A
2003/0235667	12/2002	Darr et al.	N/A	N/A
2004/0084333	12/2003	Boyd	N/A	N/A
2004/0091651	12/2003	Rule et al.	N/A	N/A
2004/0129669	12/2003	Kelley et al.	N/A	N/A
2004/0146675	12/2003	Hashimoto et al.	N/A	N/A
2004/0209022	12/2003	Ghatta et al.	N/A	N/A
2005/0053739	12/2004	Lee et al.	N/A	N/A
2005/0072751	12/2004	Price	N/A	N/A
2005/0092390	12/2004	Krulitsch	N/A	N/A
2005/0139566	12/2004	Uesugi et al.	N/A	N/A
2005/0153089	12/2004	Lynch et al.	N/A	N/A
2005/0158495	12/2004	Nahill	N/A	N/A
2005/0167879	12/2004	Smith	N/A	N/A
2005/0258127	12/2004	Darr	N/A	N/A
2005/0271843	12/2004	Collette et al.	N/A	N/A
2006/0105127	12/2005	Akiyama et al.	N/A	N/A
2006/0121222	12/2005	Andrich et al.	N/A	N/A
2006/0207961	12/2005	Kurtz	N/A	N/A
2006/0255049	12/2005	McCarthy et al.	N/A	N/A
2007/0087214	12/2006	Portnoy et al.	N/A	N/A
2007/0108668	12/2006	Hutchinson et al.	N/A	N/A
2007/0175854	12/2006	Penny	N/A	N/A
2007/0175855	12/2006	Penny	N/A	N/A
2007/0205175	12/2006	Darr et al.	N/A	N/A
2007/0210026	12/2006	Darr et al.	N/A	N/A
2007/0224374	12/2006	Kelley	N/A	N/A
2007/0257001	12/2006	Paz	N/A	N/A
2008/0050546	12/2007	Kitano et al.	N/A	N/A
2008/0290099	12/2007	MacDonald et al.	N/A	N/A
2010/0270255	12/2009	Penny	N/A	N/A
2010/0270256	12/2009	Penny	N/A	N/A
2024/0034508	12/2023	Darr	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2638351	12/1976	DE	N/A

2814952	12/1977	DE	N/A
2807949	12/1978	DE	N/A
2910609	12/1979	DE	N/A
4107011	12/1991	DE	N/A
10021961	12/2000	DE	N/A
10201850	12/2001	DE	N/A
10349753	12/2004	DE	N/A
202005017075	12/2005	DE	N/A
0049876	12/1981	EP	N/A
0269920	12/1987	EP	N/A
0316167	12/1988	EP	N/A
0574472	12/1992	EP	N/A
1371477	12/2002	EP	N/A
1417141	12/2003	EP	N/A
1468925	12/2003	EP	N/A
1529736	12/2004	EP	N/A
1633639	12/2005	EP	N/A
1714887	12/2005	EP	N/A
07101873	12/2006	EP	N/A
1885602	12/2007	EP	N/A
2167385	12/2009	EP	N/A
2933201	12/2014	EP	N/A
2933201	12/2017	EP	N/A
2758800	12/1997	FR	N/A
2846946	12/2003	FR	N/A
1531783	12/1977	GB	N/A
2085395	12/1981	GB	N/A
2124543	12/1983	GB	N/A
2357491	12/2002	GB	N/A
S54-140687	12/1978	JP	N/A
S59-184627	12/1983	JP	N/A
H09-239852	12/1996	JP	N/A
2578523	12/1997	JP	N/A
2000-211017	12/1999	JP	N/A
2001-122237	12/2000	JP	N/A
2002-080021	12/2001	JP	N/A
2002-240136	12/2001	JP	N/A
2002-248675	12/2001	JP	N/A
2002-249651	12/2001	JP	N/A
2002-284132	12/2001	JP	N/A
2003-011211	12/2002	JP	N/A
2003-267334	12/2002	JP	N/A
2004-083128	12/2003	JP	N/A
2005-001383	12/2004	JP	N/A
2007-039109	12/2006	JP	N/A
4074143	12/2007	JP	N/A
4570838	12/2009	JP	N/A
4908544	12/2011	JP	N/A
1020050005232	12/2004	KR	N/A
WO 1992/015442	12/1991	WO	N/A

WO 1996/33062	12/1995	WO	N/A
WO 1998/25752	12/1997	WO	N/A
WO 1998/29314	12/1997	WO	N/A
WO 1999/61325	12/1998	WO	N/A
WO 1999/61337	12/1998	WO	N/A
WO 2003/008293	12/2002	WO	N/A
WO 2003/057572	12/2002	WO	N/A
WO 2004/030895	12/2003	WO	N/A
WO 2004/035394	12/2003	WO	N/A
WO 2004/043794	12/2003	WO	N/A
WO 2004/065105	12/2003	WO	N/A
WO 2004/106174	12/2003	WO	N/A
WO 2005/047120	12/2004	WO	N/A
WO 2006/013443	12/2005	WO	N/A
WO 2006/066356	12/2005	WO	N/A
WO 2007/085896	12/2006	WO	N/A
WO 2007/089552	12/2006	WO	N/A
WO 2007/089566	12/2006	WO	N/A
WO 2008/095842	12/2007	WO	N/A
WO 2008/144417	12/2007	WO	N/A

OTHER PUBLICATIONS

Certified English translation of FR 2 846 946 (FR 2 846 946 has a filing date of Nov. 12, 2002, and the reference was previously cited in the IDS provided on Jul. 22, 22 in parent U.S. Appl. No.

17/314,721). cited by applicant

New BERICAP Neck Finish According to New ISBT's PCO 1881 (1 page) Dec. 8, 2006. cited by applicant

Novembal, "Closures for the Beverage Market—Alternative Solutions" Jun. 19, 2007, 37 pages (publication date, if any, unknown). cited by applicant

Bericap Supershorty for PCT 1881, SuperShorty from Bericap for new PCO1881 short height neck finish standard. (1 page) Dec. 14, 2006. cited by applicant

Unipack.RU Packaging Portal, Logoplaste launches Europe's lightest PET Bottle. (1 page) Aug. 30, 2006. cited by applicant

Bericap, Ferrarelle, A lightweight closure for 28 mm two-start thread neck finish for sparkling water. (1 page) Jun. 27, 2006. cited by applicant

Defosse, Matt, "Trim that neck with low-profile closures", Plastics Today. (3 pages) Feb. 1, 2007. cited by applicant

Keep Up with Blow Molding, "Shorter Closure Cuts PET Bottle Weight & Cost." (author unknown) access www.ptonline.com (1 page). Jan. 1, 2007. cited by applicant

I.I. Moroz, et al., "Investigation of the Organization of Lightweight Bottle Production," Ukrainian Scientific Research Institute of the Glass and Porcelain_Faience Industry (UNISP) (5 pages) Feb. 1, 1971. cited by applicant

(Author Unknown) The "Ugly Duckling" is hatched, PET container weight halved. (publication date, if any, unknown) (1 page). cited by applicant

Husky Exhibit 1006 Drawing (1 page) International Society of Beverage Technologies (Drawing dated May 15, 2002). cited by applicant

Exhibit 4, Email Invitation to Speak: Plastics Caps and Closures Nov. 7-8, 2006, Brussels from Victor Cooper to Lothar Brauer. (2 pages) Apr. 30, 2021. cited by applicant

Plastics Caps & Closures 2006 Innovative Technical Advances and Business Solutions for Cost Reduction and Quality Preservation Throughout the Value Chain, Brussels, Belgium. (4 pages)

Nov. 7, 2006. cited by applicant

Exhibit 15, Nanetti, Luca, Sacmi Imola, SlideShow for ML27 Multi Lok 27 mm, “It is not just another short neck for still beverages.” (24 pages) (publication, if any unknown). cited by applicant

Google Books: Library of the University of Wisconsin, S.E. Slocum, B.E., Ph.D., et al. “Text-Book on the Strength of Materials,” Ginn & Company. (346 pages) (1907). cited by applicant

Kazmer>000017/000018—Revised Index by John S. Bowers of Nissei Asb Company (2 pages: (ii), (iii), 70, 71) (Dated Jun. 1, 1999, publication unknown). cited by applicant

LogoPlaste Lights Its Bottles, Editorial Staff of Emballages Mazazine; posted on Aug. 24, 2006. (4 pages) Apr. 1, 2020. cited by applicant

Conference Proceedings, “Packaging Closures and Sealing System,” N. Theobald and B. Winder, 2006 (52 pages). cited by applicant

Exhibit 5, Plastics Caps & Closures 2006, “Innovative technical advances and business solutions for cost reduction and quality preservation throughout the value chain”, Nov. 7-8, 2006, Brussels, Belgium (4 pages). cited by applicant

English translation of DE10349753 (DE10349753 already provided on Jul. 22, 2022 in parent U.S. Appl. No. 17/314,721). cited by applicant

Husky Exhibit 1012, Declaration of James D. Sykes dated Dec. 17, 2019, 11 pages. cited by applicant

Co-pending U.S. Appl. No. 18/669,243, filed May 20, 2024. cited by applicant

[No Author Listed], “28mm Carbonated Soft Drink (CSD), 38mm Carbonated Soft Drink (CSD),” 1 page (publication date, if any, unknown). cited by applicant

[No Author Listed], “Attendee List,” Plastics Caps & Closures 2006, Brussels, Belgium, Nov. 7-8, 2006, 5 pages (publication date, if any, unknown). cited by applicant

[No Author Listed], “Capping resin price rises,” European Plastics News, Dec. 22, 2006. cited by applicant

[No Author Listed], “Green? Environment Yes But Cost Savings Also,” Tetra Pak, Brussels Conference, Nov. 27, 2007, 35 pages (publication date, if any, unknown). cited by applicant

[No Author Listed], “Multi Lok* 27 mm,” 14 pages (publication date, if any, unknown). cited by applicant

[No Author Listed], “Novembal Business News,” Journal d'information de Novembal, Jan. 5, 2007, 9 pages (with English translation). cited by applicant

[No Author Listed], “SACMI ML-27 Short CSD Closure—Ambient & Elevated T CO2 Tests, Cold & Ambient Removal Torque Tests (JML-0017),” Jun. 2006, 2 pages (publication date, if any, unknown). cited by applicant

[No Author Listed], “SFR 9/27 Specifications and possible bi configurations,” SIPA at PETnology Forum 2004, May 2004, 1 page (publication date, if any, unknown). cited by applicant

[No Author Listed], “SIPA latest development in two step technology,” SIPA at PETnology Forum 2004, May 2004, 19 pages (publication date, if any, unknown). cited by applicant

[No Author Listed], “Standard Specification for Dimensions and Tolerances for Plastic Bottles,” ASTM International, reapproved 2001, 1-16. cited by applicant

[No Author Listed], “Thread Finish Standards,” Husky, Aug. 2006, 32 pages. cited by applicant

[No Author Listed], “Updated Programme—new speakers confirmed,” Plastics Caps & Closures 2006, Brussels, Belgium, Nov. 7-8, 2006, 4 pages (publication date, if any, unknown). cited by applicant

[No Author Listed], Declarations relating to cited “Bottles, Preforms, Closures: A Design Guide for PET Packaging,” edited by Ottmar Brandau, 19 pages (publication date, if any, unknown). cited by applicant

Blow Molding of Thermoplastics, Plastics Engineering Handbook of the Society of the Plastics Industry, 5th ed., Berins (ed.), 1991, 363, 5 pages. cited by applicant

bottledwaterworld.com [online], “Best Bottle in PET,” Design Awards 2006, Sep.-Oct. 2006,

38:26-47. cited by applicant

Bottles, Preforms, Closures: A Design Guide for PET Packaging, Brandau (ed.), vol. 4, 2005, 142-143, 5 pages. cited by applicant

Brandau, "Stretch Blow Molding," Plastic Design Library (POL), POL Handbook Series, 3rd Ed., 2017, 1-4, 8 pages. cited by applicant

Budynas, Advanced Strength and Applied Stress Analysis, 2nd ed., 1999, 348-357, 509-511, 15 pages. cited by applicant

data.europa.eu [online], "European Parliament and Council Directive 94/62/EC of Dec. 20, 1994 on packaging and packaging waste," Dec. 31, 1994, retrieved from URL

<<http://data.europa.eu/eli/dir/1994/62/2015-05-26>>, 29 pages. cited by applicant

devtechpet.com [online], "Preforma 38SP400," retrieved on Jul. 22, 2020, retrieved at URL <devtechpet.com/en/packaging-solutions/group-product-catalogue/pet-packaging/productdetails/?filter8y=&product=16728>, 1 page (publication date unknown). cited by applicant

Extended European Search Report in European Appln. No. 07749157.9, dated Jun. 2, 2010, 5 pages. cited by applicant

Extended European Search Report in European Appln. No. 08755571.0, mailed Jan. 7, 2011, 5 pages. cited by applicant

Extended European Search Report in European Appln. No. 15164122.2, dated Aug. 31, 2015, 5 pages. cited by applicant

Husky Injection molding Systems, Ltd. And Husky Injection Molding Systems, Inc., Petitioner, v. *Plastipak Packaging, Inc.*, Case No. IPR2020-00428, Patent Owner; U.S. Pat. No. 8,857,637, Decision Denying Institution of Inter Partes Review, Jul. 28, 2020, 21 pages. cited by applicant

Husky Injection molding Systems, Ltd. And Husky Injection Molding Systems, Inc., Petitioner, v. *Plastipak Packaging, Inc.*, Case No. IPR2020-00429, Patent Owner; U.S. Pat. No. 9,033,168, Decision Denying Institution of Inter Partes Review, Jul. 28, 2020, 22 pages. cited by applicant

Husky Injection molding Systems, Ltd. And Husky Injection Molding Systems, Inc., Petitioner, v. *Plastipak Packaging, Inc.*, Case No. IPR2020-00430, Patent Owner; U.S. Pat. No. 9,139,326, Decision Denying Institution of Inter Partes Review, Jul. 28, 2020, 23 pages. cited by applicant

Husky Injection molding Systems, Ltd. And Husky Injection Molding Systems, Inc., Petitioner, v. *Plastipak Packaging, Inc.*, Case No. IPR2020-00431, Patent Owner; U.S. Pat. No. 9,403,310, Decision Denying Institution of Inter Partes Review, Jul. 28, 2020, 24 pages. cited by applicant

Husky Injection molding Systems, Ltd. And Husky Injection Molding Systems, Inc., Petitioner, v. *Plastipak Packaging, Inc.*, Case No. IPR2020-00432, Patent Owner; U.S. Pat. No. 9,522,759, Decision Denying Institution of Inter Partes Review, Jul. 28, 2020, 23 pages. cited by applicant

Husky Injection molding Systems, Ltd. And Husky Injection Molding Systems, Inc., Petitioner, v. *Plastipak Packaging, Inc.*, Case No. IPR2020-00433, Patent Owner; U.S. Pat. No. 9,850,019, Decision Denying Institution of Inter Partes Review, Jul. 28, 2020, 23 pages. cited by applicant

Husky Injection molding Systems, Ltd. And Husky Injection Molding Systems, Inc., Petitioner, v. *Plastipak Packaging, Inc.*, Case No. IPR2020-00434, Patent Owner; U.S. Pat. No. 9,738,409, Decision Denying Institution of Inter Partes Review, Jul. 28, 2020, 23 pages. cited by applicant

Husky Injection molding Systems, Ltd. And Husky Injection Molding Systems, Inc., Petitioner, v. *Plastipak Packaging, Inc.*, Case No. IPR2020-00435, Patent Owner; U.S. Pat. No. 10,023,345, Decision Denying Institution of Inter Partes Review, Jul. 28, 2020, 24 pages. cited by applicant

Husky Injection molding Systems, Ltd. And Husky Injection Molding Systems, Inc., Petitioner, v. *Plastipak Packaging, Inc.*, Case No. IPR2020-00436, Patent Owner; U.S. Pat. No. 10,266,299, Decision Denying Institution of Inter Partes Review, Jul. 28, 2020, 23 pages. cited by applicant

Husky Injection molding Systems, Ltd. And Husky Injection Molding Systems, Inc., Petitioner, v. *Plastipak Packaging, Inc.*, Case No. IPR2020-00437, Patent Owner; U.S. Pat. No. 10,214,311, Decision Denying Institution of Inter Partes Review, Jul. 29, 2020, 23 pages. cited by applicant

Husky Injection molding Systems, Ltd. And Husky Injection Molding Systems, Inc., Petitioner, v.

Plastipak Packaging, Inc., Case No. IPR2020-00438, Patent Owner; U.S. Pat. No. 10,214,312, Decision Denying Institution of Inter Partes Review, Jul. 29, 2020, 22 pages. cited by applicant

Husky Injection molding Systems, Ltd. And Husky Injection Molding Systems, Inc., Petitioner, v. *Plastipak Packaging, Inc.*, Case No. IPR2020-00439, Patent Owner; U.S. Pat. No. 10,457,437, Decision Denying Institution of Inter Partes Review, Jul. 28, 2020, 23 pages. cited by applicant

Ifuku et al., “International News,” Beverage Japan, 2006, 299(11):80, 6 pages (with English translation). cited by applicant

International Search Report and Written Opinion in International Appln. No. PCT/US07/01880, mailed Nov. 19, 2007, 5 pages. cited by applicant

International Search Report and Written Opinion in International Appln. No. PCT/US08/63744, mailed Sep. 2, 2008, 8 pages. cited by applicant

ISBT Threadssecs, “Alcoa-1690 Voluntary Standard 38mm CSD finish,” 1 page (drawing dated Jun. 6, 2001; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, “Alcoa-1716 Voluntary Standard 28mm CSD finish,” 1 page (drawing dated Apr. 15, 1999; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, “Alcoa-1788 Voluntary Standard 28mm CSD finish,” 1 page (drawing dated Apr. 15, 1999; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, “BPF-C Voluntary Standard 28mm CSD finish,” 1 page (drawing dated Oct. 19, 2000; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, “Flat Water,” 1 page (drawing dated Dec. 12, 2011; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, “Hot-Fill,” 1 page (publication date, if any, unknown). cited by applicant

ISBT Threadssecs, “ISBT Threadssecs Nomenclature,” 2 pages (publication date, if any, unknown). cited by applicant

ISBT Threadssecs, “ISBT Threadssecs Voluntary Standard Thread Finish Specifications Nomenclature Feature Terminologies,” 2 pages (publication date, if any, unknown). cited by applicant

ISBT Threadssecs, “ISBT Voluntary Standard Flatwater Finish PCF-26P-1 (“US Standard”),” 1 page (drawing dated May 15, 2002; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, “Obrist-28 (18mm) Voluntary Standard Flatwater Finish,” 1 page (drawing dated Feb. 23, 1999; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, “Obrist-28 (19mm) Voluntary Standard Flatwater Finish,” 1 page (drawing dated Feb. 23, 1999; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, “PCF-33P-1 Voluntary Standard Hot Fill Finish,” 1 page (drawing dated Dec. 10, 1999; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, “PCF-38G-3 Voluntary Standard Hot Fill Finish,” 1 page (drawing dated Dec. 10, 1999; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, “PCF-38P-2 Voluntary Standard Hot Fill Finish,” 1 page (drawing dated Dec. 10, 1999; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, “PCF-38P-4 Voluntary Standard Hot Fill Finish,” 1 page (drawing dated Dec. 10, 1999; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, “PCF-38P-5 Voluntary Standard Non-Carbonated beverage finish (extrusion blown),” 1 page (drawing dated Nov. 21, 2001; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, “PCF-38P-1 Voluntary Standard Hot Fill Finish,” 1 page (drawing dated Dec. 10, 1999; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, “PCF-43P-1 Voluntary Standard Hot Fill Finish,” 1 page (drawing dated Jan. 17, 2000; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, “PCF-48P-2 Voluntary Standard Hot Fill Finish,” 1 page (drawing dated Jan. 17, 2000; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, "PCF-48P-3 Voluntary Standard Hot Fill Finish," 1 page (drawing dated Jan. 17, 2000; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, "PCF-48P-4 Voluntary Standard Hot Fill Finish," 1 page (drawing dated Jan. 17, 2000; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, "PCF-48P-5 Voluntary Standard Hot Fill Finish," 1 page (drawing dated Jan. 17, 2000); publication date, if any, unknown). cited by applicant

ISBT Threadssecs, "PCF-26P-2 Voluntary Standard Flatwater Finish," 1 pages (drawing dated May 15, 2002; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, "PCO-1810 Voluntary Standard 28mm CSD finish," 1 page (drawing dated May 29, 1998; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, "PCO-1815 Voluntary Standard 28mm CSD finish," 1 page (drawing dated May 29, 1998; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, "PCO-1816 Voluntary Standard 28mm CSD finish," 1 page (drawing dated May 29, 1998; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, "PCO-1817 Voluntary Standard 28mm CSD finish," 1 page (drawing dated May 29, 1998; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, "PCO-1820 Voluntary Standard 28mm CSD finish," 1 page (drawing dated May 29, 1998; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, "PCO-1823 Voluntary Standard 28mm CSD finish," 1 page (drawing dated May 29, 1998; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, "PCO-1881 Voluntary Standard 28mm CSD finish," 1 page (drawing dated Feb. 14, 2007; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, "PCO-38 Voluntary Standard 38mm CSD Finish," 1 page (drawing dated Oct. 19, 2000; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, "SP-400 Voluntary Standard," 1 page (drawing dated Mar. 10, 1999; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, "SP-410 Voluntary Standard," 1 page (drawing dated Mar. 10, 1999; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, "SP-415 Voluntary Standard," 1 page (drawing dated Mar. 10, 1999; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, "SPI-Series," 1 page (publication date, if any, unknown). cited by applicant

ISBT Threadssecs, "Terminologies for Bottle Finishes," 1 page (drawing dated Jun. 12, 2001; publication date, if any, unknown). cited by applicant

ISBT Threadssecs, "Voluntary Standard PET Finish Dimension Nomenclature," 1 page (drawing dated May 29, 1998; publication date, if any, unknown). cited by applicant

ISBT, "Reduced height/Lightweight PCO 1881 Finish Subcommittee: Minutes of Meeting," Meeting #10, Oct. 17, 2006, 8 pages (publication date, if any, unknown). cited by applicant

ISBT, "Reduced height/Lightweight PCO 1881 Finish Subcommittee: Minutes of Meeting," Meeting #11, Oct. 24, 2006, 6 pages (publication date, if any, unknown). cited by applicant

ISBT, "Reduced height/Lightweight PCO 1881 Finish Subcommittee: Minutes of Meeting," Meeting #12, Nov. 2, 2006, 6 pages (publication date, if any, unknown). cited by applicant

ISBT, "Reduced height/Lightweight PCO 1881 Finish Subcommittee: Minutes of Meeting," Meeting #13, Nov. 14, 2006, 6 pages (publication date, if any, unknown). cited by applicant

ISBT, "Reduced height/Lightweight PCO 1881 Finish Subcommittee: Minutes of Meeting," Meeting #14, Nov. 28, 2006, 7 pages (publication date, if any, unknown). cited by applicant

ISBT, "Reduced height/Lightweight PCO 1881 Finish Subcommittee: Minutes of Meeting," Meeting #15, Dec. 12, 2006, 7 pages (publication date, if any, unknown). cited by applicant

ISBT, "Reduced height/Lightweight PCO 1881 Finish Subcommittee: Minutes of Meeting," Meeting #6, Aug. 1, 2006, 7 pages (publication date, if any, unknown). cited by applicant

ISBT, "Reduced height/Lightweight PCO 1881 Finish Subcommittee: Minutes of Meeting,"

Meeting #7, Aug. 22 & 23, 2006, 7 pages (publication date, if any, unknown). cited by applicant

ISBT, "Reduced height/Lightweight PCO 1881 Finish Subcommittee: Minutes of Meeting," Meeting #89, Jul. 9, 2013, 8 pages (publication date, if any, unknown). cited by applicant

ISBT, "Reduced height/Lightweight PCO 1881 Finish Subcommittee: Minutes of Meeting," Meeting #9, Oct. 5, 2006, 8 pages (publication date, if any, unknown). cited by applicant

ISBT, "Reduced height/Lightweight PCO Finish Subcommittee: Minutes of Meeting," Meeting #3, Jun. 15, 2006, 5 pages (publication date, if any, unknown). cited by applicant

ISBT, "Reduced height/Lightweight PCO Finish Subcommittee: Minutes of Meeting," Meeting #4, Jun. 27, 2006, 6 pages (publication date, if any, unknown). cited by applicant

ISBT, "Reduced height/Lightweight PCO Finish Subcommittee: Minutes of Meeting," Meeting #5, Jul. 12, 2006, 6 pages (publication date, if any, unknown). cited by applicant

ISBT, "Short Height Finish Subcommittee: Minutes of Meeting," Meeting #1, Apr. 24, 2006, 3 pages (publication date, if any, unknown). cited by applicant

ISBT, "Short Height Finish Subcommittee: Minutes of Meeting," Meeting #2, May 2, 2006, 3 pages (publication date, if any, unknown). cited by applicant

Krautkramer, "Short Necks and Closures for Carbonated Beverages—a PET saving initiative," Bericap, 27 pages (publication date, if any, unknown). cited by applicant

Krupp Corpoplast Maschinenbau GmbH, "Operating Instructions: Blow Moulding Machine B 177," Operator Reference Manual, 1995, 9 pages. cited by applicant

Lamarche, "Solutions to lighter plastic closures for use in water bottles," Plastics Caps & Closures 2006, Brussels, Belgium, Nov. 7-8, 2006, 28 pages (publication date, if any, unknown). cited by applicant

linkplas.com [online], "Winners at Bottled Water Awards," Sep. 19, 2006, retrieved at URL <<https://www.linkplas.com/Awards/Winners+at+Bottled+Water+Awards.html>>, 1 page. cited by applicant

Novembal, "Danone Innovation Day," May 31, 2006, 3 pages (publication date, if any, unknown). cited by applicant

Novembal, "Novaqua 29.4," 2 pages (publication date, if any, unknown). cited by applicant

Opposition, ""foodproductiondaily", [gefunden04.02.2021]," Exhibit D59 in European Appln. No. 15164122.2, dated Feb. 5, 2021, 2 pages. cited by applicant

Opposition, ""Interempresas", [gefunden04.02.2021]," Exhibit D64 in European Appln. No. 15164122.2, dated Feb. 5, 2021, 4 pages (with English translation). cited by applicant

Opposition, "Affidavit Paulo Correia," Exhibit D17 in European Appln. No. 15164122.2, dated Sep. 2, 2020, 7 pages. cited by applicant

Opposition, "Auszug aus Wayback-Machine," Exhibit D31 in European Appln. No. 15164122.2, dated Oct. 7, 2020, 1 page. cited by applicant

Opposition, "Data Sheet Packaging Glass," Exhibit D32 in European Appln. No. 15164122.2, dated Oct. 7, 2020, 3 pages. cited by applicant

Opposition, "Eidesstattliche Versicherung Herr Thomas Anderegg," Exhibit D56 in European Appln. No. 15164122.2, dated Feb. 5, 2021, 3 pages (with English translation). cited by applicant

Opposition, "Eidesstattliche Versicherung van Dr. Michael Kruger," Exhibit D57 in European Appln. No. 15164122.2, dated Feb. 5, 2021, 4 pages (with English translation). cited by applicant

Opposition, "Eidesstattliche Versicherung van Frau Barbara Appel," Exhibit D42 in European Appln. No. 15164122.2, dated Feb. 5, 2021, 4 pages (with English translation). cited by applicant

Opposition, "Eidesstattliche Versicherung van Frau Barbara Appel," Exhibit D55 in European Appln. No. 15164122.2, dated Feb. 5, 2021, 4 pages (with English translation). cited by applicant

Opposition, "Eidesstattliche Versicherung van Herr Alexander Krautkramer," Exhibit D54 in European Appln. No. 15164122.2, dated Feb. 5, 2021, 3 pages (with English translation). cited by applicant

Opposition, "Eidesstattliche Versicherung van Herr Andreas Reich," Exhibit D45 in European

Appln. No. 15164122.2, dated Feb. 5, 2021, 3 pages (with English translation). cited by applicant
Opposition, "Eidesstattliche Versicherung van Herr Fiorenza Parrinello," Exhibit D43 in European Appln. No. 15164122.2, dated Feb. 5, 2021, 3 pages. cited by applicant
Opposition, "Eidesstattliche Versicherung van Herr Jochen Forsthovel," Exhibit D44 in European Appln. No. 15164122.2, dated Feb. 5, 2021, 3 pages (with English translation). cited by applicant
Opposition, "Eidesstattliche Versicherung van Herr Werner Rosenberger," Exhibit D63 in European Appln. No. 15164122.2, dated Feb. 5, 2021, 2 pages (with English translation). cited by applicant
Opposition, "Handbook bottles front and p143," Exhibit D15 in European Appln. No. 15164122.2, dated Sep. 20, 2019, 2 pages. cited by applicant
Opposition, "Handout," Exhibit D39 in European Appln. No. 15164122.2, dated Feb. 5, 2021, 17 pages. cited by applicant
Opposition, "Husky Zeichnung," Exhibit D14 in European Appln. No. 15164122.2, dated Apr. 25, 2019, 1 page. cited by applicant
Opposition, "In response to the Patent Proprietor's written statement dated Oct. 2, 2020," European Appln. No. 15164122.2, dated Feb. 5, 2021, 98 pages (with English translation). cited by applicant
Opposition, "In response to the summons dated Oct. 16 to an oral hearing," European Appln. No. 15164122.2, dated Feb. 5, 2021, 12 pages (with English translation). cited by applicant
Opposition, "Invoice 1," Exhibit D18 in European Appln. No. 15164122.2, dated Sep. 2, 2020, 3 pages. cited by applicant
Opposition, "Invoice 2," Exhibit D19 in European Appln. No. 15164122.2, dated Sep. 2, 2020, 3 pages. cited by applicant
Opposition, "Invoice 3," Exhibit D20 in European Appln. No. 15164122.2, dated Sep. 2, 2020, 2 pages. cited by applicant
Opposition, "Invoice 4," Exhibit D21 in European Appln. No. 15164122.2, dated Sep. 2, 2020, 3 pages. cited by applicant
Opposition, "Invoice 5," Exhibit D22 in European Appln. No. 15164122.2, dated Sep. 2, 2020, 3 pages. cited by applicant
Opposition, "Katalog Husky," Exhibit D30 in European Appln. No. 15164122.2, dated Oct. 7, 2020, 32 pages. cited by applicant
Opposition, "Letter Plastipak to Cetie Jan. 2021," Exhibit D69 in European Appln. No. 15164122.2, dated Apr. 2, 2021, 1 page. cited by applicant
Opposition, "Letter Plastipak to Cetie," Exhibit D68 in European Appln. No. 15164122.2, dated Apr. 2, 2021, 2 pages. cited by applicant
Opposition, "MHT is part of Krones as one party," Exhibit D16 in European Appln. No. 15164122.2, dated Sep. 20, 2019, 1 page. cited by applicant
Opposition, "Norm GME 30.28," Exhibit D71 in European Appln. No. 15164122.2, dated Apr. 2, 2021, 3 pages. cited by applicant
Opposition, "Norm GME 30.38," Exhibit D70 in European Appln. No. 15164122.2, dated Apr. 2, 2021, 4 pages. cited by applicant
Opposition, "On the correspondence of patent-holder of Feb. 8, 2021," European Appln. No. 15164122.2, dated Mar. 9, 2021, 36 pages (with English translation). cited by applicant
Opposition, "Prasentation, 27.11.07," Exhibit D13 in European Appln. No. 15164122.2, dated Apr. 25, 2019, 35 pages. cited by applicant
Opposition, "Preform 11, 5g 0, 33 I," Exhibit D23 in European Appln. No. 15164122.2, dated Sep. 2, 2020, 4 pages. cited by applicant
Opposition, "Preform 15g 0,5 I," Exhibit D24 in European Appln. No. 15164122.2, dated Sep. 2, 2020, 2 pages. cited by applicant
Opposition, "Signiert Frau Appel," Exhibit D34 in European Appln. No. 15164122.2, dated Feb. 5, 2021, 20 pages. cited by applicant
Opposition, "Signiert Frau Appel," Exhibit D50 in European Appln. No. 15164122.2, dated Feb. 5,

2021, 28 pages. cited by applicant

Opposition, “Signiert Herr Anderegg,” Exhibit D53 in European Appln. No. 15164122.2, dated Feb. 5, 2021, 28 pages. cited by applicant

Opposition, “Signiert Herr Forsthovel,” Exhibit D37 in European Appln. No. 15164122.2, dated Feb. 5, 2021, 20 pages. cited by applicant

Opposition, “Signiert Herr Krautkramer,” Exhibit D51 in European Appln. No. 15164122.2, dated Feb. 5, 2021, 28 pages. cited by applicant

Opposition, “Signiert Herr Kruger,” Exhibit D41 in European Appln. No. 15164122.2, dated Feb. 5, 2021, 17 pages. cited by applicant

Opposition, “Signiert Herr Kruger,” Exhibit D48 in European Appln. No. 15164122.2, dated Feb. 5, 2021, 2 pages. cited by applicant

Opposition, “Signiert Herr Kruger,” Exhibit D52 in European Appln. No. 15164122.2, dated Feb. 5, 2021, 28 pages. cited by applicant

Opposition, “Signiert Herr Parrinello,” Exhibit D36 in European Appln. No. 15164122.2, dated Feb. 5, 2021, 20 pages. cited by applicant

Opposition, “Signiert Herr Parrinello,” Exhibit D40 in European Appln. No. 15164122.2, dated Feb. 5, 2021, 12 pages. cited by applicant

Opposition, “Signiert Herr Parrinello,” Exhibit D47 in European Appln. No. 15164122.2, dated Feb. 5, 2021, 2 pages. cited by applicant

Opposition, “Signiert Herr Reich,” Exhibit D35 in European Appln. No. 15164122.2, dated Feb. 5, 2021, 20 pages. cited by applicant

Opposition, “Signiert Signiert Herr Kruger,” Exhibit D38 in European Appln. No. 15164122.2, dated Feb. 5, 2021, 20 pages. cited by applicant

Opposition, “Zeichnung 191476,” Exhibit D66 in European Appln. No. 15164122.2, dated Feb. 5, 2021, 1 page. cited by applicant

Opposition, “Zeichnung 2770143,” Exhibit D65 in European Appln. No. 15164122.2, dated Feb. 5, 2021, 1 page. cited by applicant

Opposition, “Zeichnung 2874756,” Exhibit D67 in European Appln. No. 15164122.2, dated Feb. 5, 2021, 1 page. cited by applicant

Opposition, “Zeichnung 9406_137_067 02,” Exhibit D62 in European Appln. No. 15164122.2, dated Feb. 5, 2021, 1 page. cited by applicant

packagingconnections.com [online], Good Morning Packaging Keeping Pace with Packaging Around the World Issue 24, vol. 1, 2006, Sep. 5, 2006, retrieved on Apr. 1, 2020, retrieved at URL <<https://www.packagingconnections.com/news/good-morning-packaging-keeping-pace-packaging-around-worldissue-24-vol-1-2006.htm>>, 6 pages. cited by applicant

packagingconnections.com [online], “Good Morning Packaging Keeping Pace with Packaging Around the World Issue 24, vol. 1, 2006,” Sep. 2006, retrieved on Dec. 3, 2020, Packaging Connections, 7 pages (this item is a part of Exhibit A to Affidavit of Paulo Correia (Cited as Desig. ID 399)—this item not subject to the Attorney's Eyes Only designation). cited by applicant

Papiewski, “The Advantages of Plastic Bottles,” retrieved on Dec. 13, 2019, retrieved at URL <<https://education.seattlepi.com/advantages-plastic-bottles-4834.html>>, 4 pages. cited by applicant

Parker, “How the Plastic Bottle went from Miracle Container to Hated Garbage,” Aug. 23, 2019, retrieved at URL <<https://www.nationalgeographic.com/environment/2019/08/plastic-bottles>>, 5 pages. cited by applicant

PETnology GmbH, “Focus PET: Experts Presentations in Sessions and Knowledge Exchange in Workshops,” The PETnology Forum 2004, IV. Annual Business and Technology Conference for the PET Packaging Industry, Munich, Germany, May 3-4, 2004, 1 page (publication date, if any, unknown). cited by applicant

Pitman, “Logoplaste Launches Europe's Lightest PET Bottle,” Aug. 22, 2006, retrieved on Apr. 1, 2020, retrieved at URL <<https://www.beveragedaily.com/Article/2006/08/23/Logoplaste-launches->

Europe-s-lightest-PET-bottle>, 3 pages. cited by applicant

plasticsnews.com [online], “Plastics Resin Pricing—Commodity Thermoplastics: Bottle-grade PET resin with annual volumes greater than 20 million pounds,” retrieved on Nov. 11, 2019, retrieved from URL <<https://www.plasticsnews.com/resin/historicPricing/commodity-thermoplastics/pet/bottleresin/1?CSAuthResp=1%3A%3A383902%3A311%3A24%3As%E2%80%A6>>, 9 pages. cited by applicant

plasticsnews.com [online], “Plastics Resin Pricing—Commodity Thermoplastics: Injection general purpose HDPE resin with annual volumes greater than 20 million pounds,” retrieved on Nov. 11, 2019, retrieved from URL: <<https://www.plasticsnews.com/resin/historicPricing/commodity-thermoplastics/hdpe/injection-gp/1/>>, 9 pages. cited by applicant

plasticsnews.com [online], “Plastics Resin Pricing—Commodity Thermoplastics: Random copolymer injection PP resin with annual volumes greater than 20 million pounds,” retrieved on Nov. 11, 2019, retrieved from URL: <<https://www.plasticsnews.com/resin/historicPricing/commodity-thermoplastics/pp/randomcopolymer-injection/1>> 10 pages. cited by applicant

Plastipak Packaging Inc., Plaintiff, v. *Ice River Springs USA, Inc. and Ice River Springs Water Co. Inc.*, Defendants, submitted in Civil Action No. 1: 19-cv-11193-IT [U.S. District Court for the District of Massachusetts], Exhibit B to Affidavit of Paulo Correia, dated Sep. 16, 2020, 13 pages. Note: With respect to Exhibits A and C of the Correia Affidavit (Cited as Desig. ID 399), portions of the Exhibits filed with the Court were not available to Applicant—portions of of Exhibit A were designated “Confidential—For Counsel Only”—the public portions of Exhibit A have been provided herein; Exhibit C was designated “Confidential—Outside Counsel of Record Only.” cited by applicant

Plastipak Packaging, Inc., Plaintiff, v. *Ice River Springs Water Co. Inc. and Ice River Springs USA, Inc.*, Civil Action No. 1:19-cv-11193-IT, Affidavit of Paulo Correia on Behalf of Logoplaste Consultores Tecnicos, S.A., Sep. 16, 2020—submitted in Civil Action No. 1: 19-cv-11193-IT [U.S. District Court for the District of Massachusetts], 14 pages. cited by applicant

Plastipak Packaging, Inc., Plaintiff, v. *Nestle Waters North America, Inc.*, Defendant, Case No. 1:20-cv-01288 (RDA-IDD), Declaration of Julio Manuel Da Rocha Cabral, May 27, 2021, 5 pages. cited by applicant

Plastipak Packaging, Inc., Plaintiff, v. *Nestle Waters North America, Inc.*, Defendant, Case No. 1:20-cv-01288 (RDA-IDD), Declaration of Pierre-Christophe Lamarche, Jul. 20, 2021, 9 pages. cited by applicant

Plastipak Packaging, Inc., Plaintiff, v. *Premium Waters, Inc.*, Defendant, Case No. 3:20-cv-00098-wmc, Document 183, filed Aug. 19, 2021, 37 pages. cited by applicant

Preforms Plus, “30.0-Gram Preform,” Print dated Feb. 25, 2011, published purportedly Sep. 24, 2012, 1 page. cited by applicant

Preforms Plus, Print dated Dec. 10, 2010, published purportedly Sep. 24, 2012, 1 page. cited by applicant

Premium Waters, Inc., Petitioner, v. *Husky Injection Molding Systems, Inc.*, Respondent, Case: 1:20-cv-06098, Document #: 5-9, Filed: Oct. 13, 2020, Drawing Exhibit I—Husky, drawing purportedly dated 2004, 2 pages (publication date, if any, unknown). cited by applicant

Radicles3.rssing.com [online], “GCS Press Releases,” Feb. 4, 2007 Press Release, retrieved from URL <<http://radicles3.rssing.com/chan-3122006/latest.php#item42>>, 16 pages. cited by applicant

Sacmi 1295 Invoice, Sep. 2005, 2 pages (publication date, if any, unknown). cited by applicant

Sacmi, “ML 27,” Jul. 25, 2006, 15 pages (publication date, if any, unknown). cited by applicant

Sacmi, “ML 27,” Sep. 10, 2006, 35 pages (publication date, if any, unknown). cited by applicant

Scudellari, “Proforma Invoice No. OKUS05-045,” Sacmi 1386, Sep. 2005, 23 pages (publication date, if any, unknown). cited by applicant

sec.gov [online], “2005 Annual Report of Danone S.A.,” as filed with the Securities and Exchanges Commission on Apr. 20, 2006, retrieved from URL <<https://www.sec.gov/Archives/edgar/data/1048515/000119312506084606/d20f.htm>>, 210 pages. cited by applicant

Steeman, “Worldwide innovations in packaging technology with a ‘touch of greenness’ and an accent on sustainability and recyclability,” Nov. 4, 2009, retrieved on Oct. 16, 2019, retrieved from URL <<https://bestinpackaging.com/2009/11/04/short-shorter-the-shortest>>, 2 pages. cited by applicant

Stone et al., “Closures for the Beverage Market—Alternative Solutions,” PIRA Conference, Atlanta, GA, Jun. 19 and 21, 2007, 37 pages (publication date, if any, unknown). cited by applicant

The Editorial Staff of Emballages Magazine, “LogoPlaste allège ses bouteilles,” Emballages Magazine, Aug. 24, 2006, retrieved on Apr. 1, 2020, retrieved at URL <<https://www.emballagesmagazine.com/actualites/logoplaste-allege-ses-bouteilles.3493>>, 9 pages (with English translation). cited by applicant

threadspecs.com [online], “ISBT Threadspecs Nomenclature,” 2 pages (publication date, if any, unknown). cited by applicant

Velas et al., Blog Posts, retrieved on Jun. 18, 2020, retrieved at URL ><http://chunk-o-funk.blogspot.com/2006/>>, various 2006 dates, 28 pages (with English translation). cited by applicant

Zacarias, “Technology News,” Logoplaste Technology, Lda, N°6, Jan. 2006, 6 pages. cited by applicant

Related Co-Pending U.S. Appl. No. 17/531,637, filed Nov. 19, 2021—which is a reissue application pertaining to U.S. Pat. No. 7,708,159, U.S. Appl. No. 11/368,860, filed Mar. 6, 2006, from which the instant application claims priority. cited by applicant

Primary Examiner: Miggins; Michael C

Attorney, Agent or Firm: Fishman Stewart PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 18/377,493, filed Oct. 6, 2023, which is a continuation of U.S. patent application Ser. No. 18/084,064, filed Dec. 19, 2022, now U.S. Pat. No. 11,780,634, which is a continuation of U.S. patent application Ser. No. 17/314,721, filed May 7, 2021, now U.S. Pat. No. 11,560,250, which is a continuation of U.S. patent application Ser. No. 16/598,452, filed Oct. 10, 2019, which is a continuation of U.S. patent application Ser. No. 16/013,139, filed Jun. 20, 2018, now U.S. Pat. No. 10,457,437, which is a continuation of U.S. patent application Ser. No. 16/012,302, filed Jun. 19, 2018, now U.S. Pat. No. 10,266,299, which is a continuation of U.S. patent application Ser. No. 15/495,084, filed Apr. 24, 2017, now U.S. Pat. No. 10,023,345, which is a continuation of U.S. patent application Ser. No. 15/404,731, filed Jan. 12, 2017, now U.S. Pat. No. 9,738,409, which is a continuation of U.S. patent application Ser. No. 15/383,179, filed Dec. 19, 2016, now U.S. Pat. No. 9,850,019, which is a continuation of U.S. patent application Ser. No. 15/220,731, filed Jul. 27, 2016, now U.S. Pat. No. 9,522,759, which is a continuation of U.S. patent application Ser. No. 14/803,505, filed Jul. 20, 2015, now U.S. Pat. No. 9,403,310, which is a continuation of U.S. patent application Ser. No. 14/688,734, filed Apr. 16, 2015, now U.S. Pat. No. 9,139,326, which is a continuation of U.S. patent application Ser. No. 14/511,848, filed Oct. 10, 2014, now U.S. Pat. No. 9,033,168, which is a divisional of U.S. patent application Ser. No.

TECHNICAL FIELD

(1) The present invention relates to plastic containers, including injection molded and/or blow molded containers.

BACKGROUND

(2) It is desirable to improve the stability of plastic containers and the handling of preforms that are used to form containers. At the same time, for economic and efficiency reasons, it is also desirable to provide containers and preforms that are suitable for their intended applications yet have a reduced weight.

SUMMARY

(3) A plastic container is provided that includes a hollow body portion including a lower supporting base portion; a sidewall portion extending upwardly from the base portion; and a neck portion extending upwardly from the sidewall portion. The neck portion includes a support flange having an upper and lower surface, at least one thread, and a dispensing opening at the top of the neck portion. In embodiments, a closure may be provided to form an assembly. In embodiments, the container may be comprised of PET, the weight of the neck portion from the lower surface of the support flange to a top of the dispensing opening may be 3.0 grams or less, and the vertical distance from the top of the dispensing opening to the lower surface of the support flange may be 0.580 inches or less. A preform and method for making a container are also disclosed.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Embodiments of the invention will now be described, by way of example, with reference to the accompanying drawings, wherein:

(2) FIG. 1 is a front elevational view of a plastic container according to an embodiment of the invention.

(3) FIG. 2 is a front elevation view of a preform according to another embodiment of the invention.

(4) FIG. 3 is a cross-sectional view of a preform according to an embodiment of the invention.

(5) FIG. 4 is a partial enlarged view of the area illustrated in FIG. 2.

(6) FIG. 5 is a partial cross sectional view of an upper portion of a container or preform according to an embodiment of the invention.

DETAILED DESCRIPTION

(7) Reference will now be made in detail to embodiments of the present invention, examples of which are described herein and illustrated in the accompanying drawings. While the invention will be described in conjunction with embodiments, it will be understood that they are not intended to limit the invention to these embodiments. On the contrary, the invention is intended to cover alternatives, modifications and equivalents, which may be included within the spirit and scope of the invention as defined by the appended claims.

(8) A representative container **10** according to an embodiment of the present invention is generally shown in FIG. 1. Container **10** includes a lower supporting base portion **12**, a sidewall portion **14**, and a neck portion **16**.

(9) The sidewall portion may be cylindrical or non-cylindrical, and may include various formations, for example, without limitation, label panels, strengthening ribs, etc. The neck portion **16** includes a support flange **18** having an upper surface **20** and a lower surface **22**. Support flange **18** is generally provided to facilitate the handling of containers, during formation and thereafter. Neck portion **16** further includes a tamper-evident formation **28** and a dispensing opening **24** positioned at, and formed by, the top of the neck portion **16**. In an embodiment, the dispensing

opening has an inner diameter that is at least 22 mm. However, the dispensing opening may be of various conventional or non-conventional sizes and may for example, comprise a circular opening having an inner diameter from 22 mm to 29 mm.

(10) Container **10** is comprised of plastic. In an embodiment, the container may be comprised of polymer, such as a polymer that provides good visual clarity when bi-axially oriented like polyethylene terephthalate (PET). However, the invention is not limited to a specific polymer, and containers and preforms that are provided according to the teachings of the present invention may be comprised of a wide number of polymers and/or blends, including those that included recycled material.

(11) The tamper-evident formation **28**, may be continuous, as generally illustrated, or may include one or more discontinuous formations. In other embodiments, the tamper-evident formation may comprise a formation (e.g., a lug or lugs) that extends from the upper and/or lower surface of the support ring. However, the invention is not limited to the illustrated means for indicating tampering and other means for indicating tampering, such as a covering (e.g., a foil covering) may be used instead of or in addition to other tamper-evident formations.

(12) Embodiments of the container may additionally include a shoulder portion **15**, a plurality of threads **26** for receiving a closure (not shown). Shoulder portion **15** may comprise an upper portion of the sidewall portion **14**, and may extend inwardly into the neck portion **16**, although many container configurations do not include a shoulder portion. A feature of containers according to embodiments of the present invention is a lowering of the center of gravity. For most configurations and applications, a lower center of gravity provides a container that is more stable and less likely to tip during manufacturing, processing, and/or handling. The center of gravity is the point at which if a body is suspended it would be perfectly balanced. For uniformly consistent, symmetrical bodies, the center of gravity is at the geometrical center. For non-consistent or non-symmetrical bodies, the center of gravity needs to be determined. Moreover, for purposes of the instant disclosure, the center of gravity is associated with preforms and with containers that are in an unfilled condition.

(13) The center of gravity for container **10** illustrated in FIG. **1** is generally shown at **50**. It is noted that for the instant container configuration, the center of gravity **50** is above the mid-height of the container due to the additional material, and hence weight, that is provided in the container finish portion—i.e., the neck portion **16**. However, as described further herein, with a reduction in the vertical length and weight of the neck portion **16** (or elements thereof), the center of gravity for a container produced in accordance with the teachings of the present invention may have a center of gravity (e.g., **50**) that is vertically lower than that of a container that employs a conventional (vertically longer and heavier) neck portion. For example, without limitation, the ratio of the vertical height of the center of gravity to the vertical height of the container may be less than 0.57. Notably, for some embodiments the ratio may be less than 0.53.

(14) Additionally, in an embodiment of the invention, portions of the container—exclusive of the neck portion—may be stretched (e.g., in a stretch blow molding operation) to more than 3 times their initial (i.e., preform component) length in the axial direction.

(15) As one would also expect, with a reduction in the vertical length and weight of the neck portion, the center of gravity for an associated preform will also be reduced when compared to an preform of like material and design below the neck portion that includes a longer vertical and heavier neck portion.

(16) FIGS. **2** and **3** generally illustrate a preform **40** according to an embodiment of the invention. Preform **40** can, for instance, be used to form a wide variety of containers, including a container such as that illustrated in FIG. **1**. By way of example, without limitation, preform **40** may be injection molded and/or blow molded, and may form an almost limitless number of container configurations. FIG. **4**. depicts an enlarged portion of FIG. **2**.

(17) Preform **40** is also shown including a neck portion **42**. For many applications, the neck portion

provided in connection with a preform will remain substantially the same, and have substantially the same dimensions, as the neck portion of a molded container produced from the preform. Consequently, the neck portion **16** of the container **10** and the neck portion **42** of the preform may be substantially consistent, while the remaining portions of the preform and container; i.e., those below the respective neck portions—may change significantly. For ease of reference, common elements in the neck portion of the illustrated container and the neck portion of the illustrated preforms are provided with common reference numerals.

(18) FIG. 5 illustrates a partial cross sectional view of an upper portion of a preform or a container formed from preform. In an embodiment, such as that generally illustrated, the vertical distance X from the top of the dispensing opening/neck portion (e.g., point **30**) to the lower surface **22** of the support flange **18** (e.g., point **32**) is 0.580 inches or less. For some embodiments, X may be 0.500 inches or less; for other embodiments, vertical distance X may be less than 0.450 inches.

(19) Moreover, as generally illustrated, the vertical distance H from the top of the dispensing opening/neck portion (e.g., point **30**) to the upper surface **20** of the support flange **18** may be 0.50 inches or less. For some embodiments, H may be 0.40 inches or less. Also, for some embodiments, the vertical distance D from the top of the dispensing opening/neck portion (e.g., point **30**) to the lower surface of the tamper-evident formation (e.g., point **34**) may be 0.30 inches or less.

(20) In an embodiment, the vertical distance J from a furthest radially-extending portion of the lower surface of the tamper-evident formation **28** (e.g., point **36**) to the upper surface **20** of the support flange **18**, which generally equates to H minus D, may be 0.15 inches or less. For some embodiments, J may be 0.10 inches or less, and for other embodiments, vertical distance J may be less than 0.09 inches. For yet other embodiments, vertical distance J may be less than 0.08 inches.

(21) Also, in an embodiment of the invention, the vertical distance between a furthest outwardly radially-extending portion of the lower surface of the tamper-evident formation (e.g., point **36**) to the lower surface **22** of the support flange **18** at the same outward radial distance—which may generally equate or coincide with X minus D—is 0.20 inches or less, and for some embodiments may be 0.15 inches or less.

(22) In an embodiment, support flange **18** has a radially extending length $L_{sub.1}$ that is 0.20 inches or less. For some applications, length $L_{sub.1}$ may be further reduced to 0.17 inches or less. With further reference to support flange **18**, the angle—from horizontal—provided by a furthest outward radially extending portion of the lower surface **22** of support flange **18** (e.g., point **32**) to the nearest radially-extending portion of the upper surface **20** of the support flange **18** is 16° or greater, and may be $20.0^\circ \pm 2^\circ$. However, for some embodiments, such as that generally depicted in FIG. 5, whereas a blending radius is provided to transition supporting flange **18** into an adjacent vertical portion of the neck (e.g., segment **39**), the nearest radially-extending portion of the upper surface **20** of support flange **18** may be a theoretical position within supporting flange **18**—e.g., point **38**. Furthermore, for some embodiment, the least distance from a furthest radially-extending portion of the support flange (e.g., point **32**) to the upper surface of the dispensing opening (e.g., at or about **30**) is 0.60 inches or less, and for some neck portions may be 0.50 inches or less.

(23) Embodiments of preforms and containers may have a neck portion that weighs 3.0 grams or less. For some embodiments, the weight of the neck portion can be 2.3 grams or less. Further, for a 500 ml version of a container made in accordance with an embodiment of the invention, the total weight of the preform and an unfilled weight of a container produced from such a preform may be 11 grams or less, and for some embodiments may be 10 grams or less. Of course, for many embodiments, without limitation, the preform and resulting container will weigh at least 9 grams.

(24) By providing a neck portion **16** for a container **10** that incorporates one or more aspects of the foregoing embodiments, the center of gravity (see, e.g., **50** in FIG. **1**) for the container may be lowered. For e.g., for a 500 ml container of with a configuration as generally shown in FIG. **1**, the weight of the neck portion may be reduced from a conventional 3.4 to 2.0 g. Based on such a reduction in weight, the center of gravity (see, e.g., **50**) may become at least about 0.48 inches

lower than that provided for a similarly configured container having a 3.4 g finish—and will likely be about 0.48 and 0.58 inches lower than with the heavier (e.g., 3.4 g) conventional finish. Providing a neck portion in accordance with embodiments disclosed herein for such a container can provide a lowering of center of gravity as a percentage of height from bottom that ranged from about 4.5% to about 6% when compared to a similar container with a conventional 3.4 g neck portion. Moreover, when a container such as that discussed in this paragraph (e.g., 2.0 g neck portion/finish) is compared to a conventional container (e.g. 3.4 g neck portion/finish), the calculations provide a drop or lowering in center of gravity that provides an approximately 10.5% to 12.2% relative percent change (i.e., percent improvement).

(25) It is noted that in addition to the material and economic benefits that may be achieved by “light-weighting” and lowering a comparative center of gravity in a resultant container, a lowering in the center of gravity of a preform may also provide certain manufacturing benefits. For example, without limitation, a preform with a comparatively lower center of gravity may provide for improved sorting and/or handling during production and manufacturing. That is, among other things, a preform with a lower center of gravity can provide for comparatively more stable or improved retention and processing. Similarly, a container with a lower center of gravity may exhibit improved handling, for instance, without limitation, in connection with de-palletizing or with “table top” conveying systems. Further, a lower center of gravity can provide a container, filled or unfilled, with improved stability. It is further noted, however, that the present invention is not limited to containers that are blown and filled in distinct or separate operations. That is, without limitation, preforms and containers provided in accordance with the teachings of the present invention also lend themselves for use in connection with various conventional “blow-and-fill” operations, including those in which a container is filled just after formation (e.g., within seconds of formation) in close proximity to where the container is formed. The operation comprising the blow-and-fill may be a single, integrated machine, or may be comprised of two or more separate devices that are adjacent or in close proximity to one another.

(26) The foregoing descriptions of specific embodiments of the present invention have been presented for purposes of illustration and description. They are not intended to be exhaustive or to limit the invention to the precise forms disclosed, and various modifications and variations are possible in light of the above teaching. The embodiments were chosen and described in order to explain the principles of the invention and its practical application, to thereby enable others skilled in the art to utilize the invention and various embodiments with various modifications as are suited to the particular use contemplated. It is intended that the scope of the invention be defined by the claims appended hereto and their equivalents.

Claims

1. A plastic preform comprising: a lower supporting base portion; a sidewall portion extending upwardly from the lower supporting base portion; and a neck portion extending upwardly from the sidewall portion, the neck portion including: a dispensing opening positioned at a top of the neck portion; threads positioned below the dispensing opening; a tamper-evident formation positioned directly below the threads, the tamper-evident formation having a lower surface; and a support flange positioned below the tamper-evident formation, the support flange having an upper surface and a lower surface; wherein the plastic preform is formed of a material comprising polyethylene terephthalate (PET); a vertical distance from the lower surface of the support flange to the top of the neck portion is from 0.425 to 0.500 inches; a vertical distance from the top of the neck portion to the lower surface of the tamper-evident formation is 0.30 inches or less; an outside diameter of the support flange is greater than 22 mm and less than or equal to 39.2 mm, and a weight of the neck portion is 2.3 grams or less.

2. The plastic preform according to claim 1, wherein a vertical distance from the lower surface of

the tamper-evident formation to the lower surface of the support flange is from 0.125 to 0.150 inches.

3. The plastic preform according to claim 1, wherein the threads comprise non-vented threads.

4. The plastic preform according to claim 1, wherein the threads comprise multiple-lead threads.

5. The plastic preform according to claim 1, wherein the threads comprise triple-lead threads.

6. The plastic preform according to claim 1, wherein a vertical distance from the upper surface of the support flange to the top of the neck portion is 0.40 inches or less.

7. The plastic preform according to claim 1, wherein a vertical distance from the lower surface of the tamper-evident formation to the upper surface of the support flange is from 0.08 to 0.10 inches.

8. The plastic preform according to claim 1, wherein a vertical distance from the lower surface of the support flange to the top of the neck portion is from 0.425 to 0.450 inches.

9. The plastic preform according to claim 1, wherein the plastic preform comprises recycled material.

10. A plastic preform comprising: a lower supporting base portion; a sidewall portion extending upwardly from the lower supporting base portion; and a neck portion extending upwardly from the sidewall portion, the neck portion including: a dispensing opening positioned at a top of the neck portion; threads positioned below the dispensing opening; a tamper-evident formation positioned directly below the threads, the tamper-evident formation having a lower surface; and a support flange positioned below the tamper-evident formation, the support flange having an upper surface and a lower surface; wherein the plastic preform is formed of a material comprising polyethylene terephthalate (PET); a vertical distance from the lower surface of the support flange to the top of the neck portion is from 0.425 to 0.450 inches; a vertical distance from the top of the neck portion to the lower surface of the tamper-evident formation is 0.30 inches or less; and a weight of the neck portion is 2.3 grams or less.

11. The plastic preform according to claim 10, wherein a vertical distance from the lower surface of the tamper-evident formation to the lower surface of the support flange is from 0.125 to 0.150 inches.

12. The plastic preform according to claim 10, wherein the threads comprise non-vented threads.

13. The plastic preform according to claim 10, wherein the threads comprise multiple-lead threads.

14. The plastic preform according to claim 10, wherein the threads comprise triple-lead threads.

15. The plastic preform according to claim 10, wherein a vertical distance from the upper surface of the support flange to the top of the neck portion is from 0.40 inches or less.

16. The plastic preform according to claim 10, wherein a vertical distance from the lower surface of the tamper-evident formation to the upper surface of the support flange is from 0.08 to 0.10 inches.

17. The plastic preform according to claim 10, wherein an outside diameter of the support flange is greater than 22 mm and less than or equal to 39.2 mm.

18. The plastic preform according to claim 10, wherein the plastic preform comprises recycled material.

19. A method for blow molding a plastic container from a plastic preform, comprising: blow molding the plastic preform as recited in claim 1 to form a plastic container.

20. A plastic container, comprising: a plastic container blow molded from the plastic preform recited in claim 1.
