

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250263952

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Uyeda; Alan et al.

WIRELESS LOCKSET WITH INTEGRATED ANTENNA, TOUCH ACTIVATION, AND LIGHT COMMUNICATION METHOD

Abstract

A wireless electromechanical lock with one or more of an internal antenna, touch activation, and/or a light communication device that acts as a user interface. In some embodiments, the lock utilizes an antenna near the exterior face of the lockset, designed inside the metal body of the lockset itself. A light communication device is provided in some embodiments to communicate information, visually, to the user via animations and dynamic displays of light. In some embodiments, the lockset includes a touch activation capability, which can be used to lock/unlock the lock and/or otherwise provide input.

Inventors: Uyeda; Alan (Irvine, CA), Maridakis; Michael (Garden Grove, CA), Czerwinski, JR.; Jerome F. (Ladera Ranch, CA), Scheider; Elliott B. (Foothill Ranch, CA), Brown; Troy M. (Lake Forest, CA), Kim; David KJ (Mission Viejo, CA)

Applicant: ASSA ABLOY Americas Residential Inc. (New Haven, CT)

Family ID: 1000008574935

Appl. No.: 19/031577

Filed: January 18, 2025

Related U.S. Application Data

parent US continuation 18418002 20240119 parent-grant-document US 12320154 child US 19031577

parent US continuation 17817703 20220805 parent-grant-document US 11913252 child US 18418002

parent US continuation 16987053 20200806 parent-grant-document US 11408201 child US 17817703

parent US continuation 14689766 20150417 parent-grant-document US 10738504 child US 16987053

parent US continuation 14202047 20140310 parent-grant-document US 9024759 child US

Publication Classification

Int. Cl.: E05B47/00 (20060101); E05B17/10 (20060101); E05B17/22 (20060101); E05B47/02 (20060101); E05B47/06 (20060101); E05C1/02 (20060101); G07C9/00 (20200101)

U.S. Cl.:

CPC E05B47/0001 (20130101); E05B17/10 (20130101); E05B17/22 (20130101); E05B47/00 (20130101); E05B47/026 (20130101); E05B47/06 (20130101); E05C1/02 (20130101); G07C9/00182 (20130101); G07C9/00904 (20130101); G07C9/00944 (20130101); E05B2047/0053 (20130101); E05B2047/0054 (20130101); G07C2209/62 (20130101); Y10T70/70 (20150401); Y10T292/1014 (20150401)

Background/Summary

RELATED APPLICATIONS [0001] This application is a continuation of U.S. application Ser. No. 18/418,002, filed Jan. 19, 2024, which is a continuation of U.S. application Ser. No. 17/817,703, filed Aug. 5, 2022, now U.S. Pat. No. 11,913,252; which is a continuation of U.S. application Ser. No. 16/987,053, filed Aug. 6, 2020, now U.S. Pat. No. 11,408,201; which is a continuation of U.S. application Ser. No. 14/689,766, filed Apr. 17, 2015, now U.S. Pat. No. 10,738,504; which is a continuation of U.S. application Ser. No. 14/202,047, filed Mar. 10, 2014, now U.S. Pat. No. 9,024,759; which claims the benefit of U.S. Provisional Application Ser. No. 61/792,896, filed Mar. 15, 2013. These applications are hereby expressly incorporated by reference in their entirety into the present application.

TECHNICAL FIELD

[0002] This disclosure relates generally to electro-mechanical locks.

BACKGROUND AND SUMMARY

[0003] Electronic locks have gained increasing acceptance and widespread use in residential and commercial markets. These locksets control ingress through doors in a building by requiring certain electronic credentials. For example, these locksets typically include a control circuit that determines whether to unlock the lockset based on credentials provided by the user. In some cases, for example, the credentials and/or commands may be provided wirelessly to the lockset, such as disclosed in Pre-Grant Publication No. US 2012/0234058 for a “Wireless Access Control System and Related Methods,” filed Mar. 8, 2012, which is hereby incorporated by reference.

[0004] In the access control and security industries, wireless locksets typically include an antenna located on the interior side of the door, usually behind a plastic “RF window” to not interfere with the RF propagation. Some locksets attempt to place an antenna on the exterior side of the door, but must deal with the challenge of making the antenna aesthetically appealing, RF communication efficient, tamper resistant, and easy to manufacture.

[0005] According to one aspect, this disclosure provides a wireless electromechanical lock with one or more of an internal antenna, touch activation, and/or a light communication device that acts as a user interface. Although this disclosure describes these features as implemented on a deadbolt for purposes of example, these features are applicable to any type of lockset, including but not limited to deadbolts, knobset locks, handleset locks, etc.

[0006] In one embodiment, the lock is made of mixed metals and plastic, with engineered cavities

to contain electronics and RF antennas. For example, in some embodiments, the lock utilizes an antenna near the exterior face of the lockset, designed inside the metal body of the lockset itself. This is unique in that the metal body has been engineered to meet strict physical security requirements and also allow the embedded front-facing antenna to propagate RF energy efficiently. This holds many advantages over other means of antenna placement including compact size, cleaner aesthetic appearance, simplistic manufacturing, and tamper resistance.

[0007] A light communication device is provided in some embodiments to communicate information, visually, to the user via animations and dynamic displays of light. For example, a light communication device could be formed in a ring-shape in some embodiments that is incorporated into the exterior of the lock. In some cases, the light communication device can be used to selectively illuminate regions to create animations of dynamic multi-color light and configurations of static light along the circumference of the exterior light ring to communicate multiple user messages. These animations allow mimicking of lock operation to be possible. For example, animations may include, but are not limited to, sequentially illuminating light segments to show the direction of bolt movement or slow animation of light to indicate the lockset is busy, etc. Embodiments are contemplated in which the light communication device could be formed in shapes other than circular for a ring, such as rectangular, square, triangular, etc.

[0008] In some cases, the lockset includes a touch activation capability, which can be used to lock/unlock the lock and/or otherwise provide input. In some embodiments, for example, the entire outside cover of the lock is touch sensitive and allows a user to touch the lock to activate various functions of the lockset. This capability is unique because it does not require any special keypad area, button press, or glass capacitive touch sensor area, but rather allows the entire diameter of the lockset cover to act as a capacitive touch sensor for activation.

[0009] According to a further aspect, this disclosure provides a lockset with a latch assembly including a bolt movable between an extended position and a retracted position. The lockset has a controller configured to electronically control movement of the bolt between the extended position and the retracted position. An interior assembly is provided that includes a turn piece for manually actuating the bolt between the extended position and the retracted position. The lockset has an exterior assembly including a mechanical lock assembly configured to manually actuate the bolt between the extended position and the retracted position. The exterior assembly includes a light communication device with a plurality of independently controllable regions in electrical communication with the controller. In some embodiments, the controller is configured to actuate multiple of the regions in a predefined configuration to identify a condition of the lockset.

[0010] Depending on the circumstances, the controller could be configured to actuate the predefined configuration by adjusting (a) illumination of multiple regions of the light communication device, (b) intensity of multiple regions of the light communication device, and/or (c) color of multiple regions of the light communication device. In some embodiments, the controller is configured to actuate the predefined configuration by sequentially adjusting adjacent regions of the light communication device in illumination, intensity, and/or color.

[0011] In some embodiments, the light communication device includes at least three regions that are configured to sequentially adjust in illumination, intensity, and/or color. For example, the controller could be configured to sequentially adjust adjacent regions in a first order to identify a first condition of the lockset. Likewise, the controller could be configured to sequentially adjust adjacent regions in a second order, which is opposite of the first order, to identify a second condition of the lockset. For example, the orders in which adjustments are made could indicate the direction of the bolt.

[0012] Embodiments are contemplated in which at least a portion of the regions of the light communication device are arranged in a ring-like shape. In some cases, for example, the controller could be configured to sequentially adjust adjacent regions in a generally clockwise fashion to indicate movement of the bolt in a first direction. The movement of the bolt in the opposition

direction could be indicated with a counter-clockwise actuation of the regions. In some embodiments, the exterior assembly includes a cylinder guard cover having a generally frustoconical shape. In some cases, the light communication device is generally concentric to a frustum of the cylinder guard cover.

[0013] According to yet another embodiment, this disclosure provides a lockset with a latch assembly including a bolt movable between an extended position and a retracted position. A controller is provided to electronically control movement of the bolt between the extended position and the retracted position. The lockset includes an interior assembly including a turn piece for manually actuating the bolt between the extended position and the retracted position. An exterior assembly is provided with a mechanical lock assembly configured to manually actuate the bolt between the extended position and the retracted position. The exterior assembly includes a touch surface. The controller is configured to actuate movement of the bolt between the extended position and the retracted position responsive to capacitive touch sensing of the touch surface.

[0014] In some embodiments, the exterior assembly includes a cylinder guard cover extending from the mechanical lock assembly and the touch surface comprises an external surface of the cylinder guard cover. For example, in some cases, the touch surface comprises substantially the entire external surface of the cylinder guard cover. Embodiments are contemplated in which the cylinder guard cover has a generally frustoconical shape. For example, the touch surface could include substantially an entire side wall of the cylinder guard cover.

[0015] According to a further aspect, this disclosure provides a lockset with a locking device movable between a locked position and an unlocked position. The locking device includes a cylinder guard cover, a handle, and/or a rose. A touch surface is formed as part of the lockset. An electrical circuit is provided that is configured to identify touching of the touch surface. In some embodiments, an insulator separates the touch surface and the electrical circuit. A conductive medium could be provided that electrically connects the touch surface and the electrical circuit.

[0016] According to yet another aspect, the disclosure provides a lockset with a latch assembly including a bolt movable between an extended position and a retracted position. The lockset includes a controller configured to electronically control movement of the bolt between the extended position and the retracted position. An antenna is in electrical communication with the controller. An interior assembly is provided that includes a turn piece for manually actuating the bolt between the extended position and the retracted position. An exterior assembly is also provided with a mechanical lock assembly with a cylinder configured to manually actuate the bolt between the extended position and the retracted position. The exterior assembly includes a cylinder guard surrounding the cylinder that is configured to structurally protect the cylinder. The cylinder guard defines an internal cavity in which the antenna is at least partially disposed. In some cases, the antenna is entirely disposed in the internal cavity.

[0017] In some embodiments, the cylinder guard has a front side and a rear side. The cavity has an open end on the front side of the cylinder guard. A front cover extends from the open end of the cavity that is generally coplanar with a front face of the cylinder. Typically, the front cover is formed from a generally RF transparent material. In some cases, a light communication device extends between the open end of the cavity and the front cover. In some such situations, the light communication device is formed from a generally RF transparent material.

[0018] Additional features and advantages of the invention will become apparent to those skilled in the art upon consideration of the following detailed description of the illustrated embodiment exemplifying the best mode of carrying out the invention as presently perceived. It is intended that all such additional features and advantages be included within this description and be within the scope of the invention.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0019] The present disclosure will be described hereafter with reference to the attached drawings which are given as non-limiting examples only, in which:

[0020] FIG. **1** is an exploded view of an example lock assembly according to one embodiment of the disclosure;

[0021] FIG. **2** is a side cross-sectional view of the example lock assembly shown in FIG. **1** in an assembled state;

[0022] FIG. **3** is an exploded view of the example exterior assembly shown in FIGS. **1** and **2**;

[0023] FIG. **4** is a front perspective view of the example exterior assembly shown in FIGS. **1** and **2** with a section removed to show interior components;

[0024] FIG. **5** is a partial side cross-sectional view of the example exterior assembly shown in FIGS. **1** and **2**;

[0025] FIG. **6** is a rear perspective view of the example exterior assembly shown in FIGS. **1** and **2**;

[0026] FIG. **7** is a rear perspective view of an example insulator top that could be used in the exterior assembly according to one embodiment of the disclosure;

[0027] FIG. **8** is a front perspective view of the insulator shown in FIG. **7**;

[0028] FIG. **9** is a rear view of the insulator shown in FIGS. **7** and **8**;

[0029] FIG. **10** is a sectional view of the insulator along line **10-10** of FIG. **9**;

[0030] FIG. **11** is a sectional view of the insulator along line **11-11** of FIG. **9**;

[0031] FIG. **12** is a rear perspective view of an example lockset body that could be used in the exterior assembly, according to one embodiment of the disclosure;

[0032] FIG. **13** is a front perspective view of the example lockset body shown in FIG. **12**;

[0033] FIG. **14** is a rear view of the example lockset body shown in FIG. **12**;

[0034] FIG. **15** is a sectional view of the example lockset body along line **15-15** of FIG. **14**;

[0035] FIG. **16** is a front view of the example lockset body shown in FIG. **13**;

[0036] FIG. **17** is a sectional view of the example lockset body along line **17-17** of FIG. **16**;

[0037] FIG. **18** is a sectional view of the example lockset body along line **18-18** of FIG. **16**;

[0038] FIG. **19** is a front perspective view of an example light pipe that could be used in the exterior assembly according to one embodiment of the disclosure;

[0039] FIG. **20** is a rear perspective view of the example light pipe shown in FIG. **19**;

[0040] FIG. **21** is a rear view of the example light pipe shown in FIG. **20**;

[0041] FIG. **22** is a sectional view of the example light pipe along line **22-22** of FIG. **21**;

[0042] FIG. **23** is a sectional view of the example light pipe along line **23-23** of FIG. **21**;

[0043] FIG. **24** is a sectional view of the example light pipe along line **24-24** of FIG. **21**;

[0044] FIG. **25** is a sectional view of the example light pipe along line **25-25** of FIG. **21**;

[0045] FIG. **26** is a sectional view of the example light pipe along line **26-26** of FIG. **21**;

[0046] FIG. **27** is a diagrammatical view showing an electrical connection from the lockset to the PCB through capacitive sensing;

[0047] FIGS. **28-31** are a diagrammatical representation showing an example communication by the light pipe according to one embodiment of the disclosure;

[0048] FIG. **32** is an exploded view of an example battery contact assembly that may be used with a key fob to wirelessly provide security credentials to the lock according to one embodiment of the disclosure;

[0049] FIG. **33** is a perspective view the example battery contact assembly shown in FIG. **32** mounted to a PCB assembly;

[0050] FIG. **34** is a perspective view of the example battery contact assembly shown in FIG. **33** with a battery inserted between the contacts;

[0051] FIG. **35** is a perspective view of the example battery contact assembly shown in FIG. **33** mounted on an opposite side of the PCB;

[0052] FIG. **36** is a bottom perspective view of a contact of the example battery contact assembly shown in FIG. **32**;

[0053] FIG. **37** is a side perspective view of the example contact shown in FIG. **36**;

[0054] FIG. **38** is a side view of the example contact shown in FIG. **36**; and

[0055] FIG. **39** is a top view of the example contact shown in FIG. **36**.

[0056] Corresponding reference characters indicate corresponding parts throughout the several views. The components in the figures are not necessarily to scale, emphasis instead being placed upon illustrating the principals of the invention. The exemplification set out herein illustrates embodiments of the invention, and such exemplification is not to be construed as limiting the scope of the invention in any manner.

DETAILED DESCRIPTION OF THE DRAWINGS

[0057] While the concepts of the present disclosure are susceptible to various modifications and alternative forms, specific exemplary embodiments thereof have been shown by way of example in the drawings and will herein be described in detail. It should be understood, however, that there is no intent to limit the concepts of the present disclosure to the particular forms disclosed, but on the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the disclosure.

[0058] This disclosure generally relates to an electromechanical lock with certain features. The term “electronic lock” is broadly intended to include any type of lockset that uses electrical power in some manner, including but not limited to electronic deadbolts, electronic lever sets, etc. This disclosure encompasses the integration of one or more of features described herein into any type of electronic lock and is not intended to be limited to any particular type of electronic lock.

[0059] FIG. **1** shows an example lock assembly **100** according to one embodiment of the disclosure. In the example shown, the lock assembly **100** includes an exterior assembly **102**, a latch assembly **104**, and an interior assembly **106**. Typically, the exterior assembly **102** is mounted on the outside of a door, while the interior assembly **106** is mounted inside a door. The latch assembly **104** is typically mounted in a bore formed in the door. The term “outside” is broadly used to mean an area outside a door and “inside” is broadly used to denote an area inside a door. With an exterior entry door, for example, the exterior assembly **102** may be mounted outside a building, while the interior assembly **106** may be mounted inside a building. With an interior door, the exterior assembly may be mounted inside a building, but outside a room secured by the lock assembly **100**; the interior assembly **106** may be mounted inside the secured room. The lock assembly **100** is applicable to both interior and exterior doors.

[0060] In the example shown, the exterior assembly **102** is in the form of a deadbolt. As discussed above, however, this disclosure is not intended to be limited to only an electronic deadbolt, but encompasses any kind of electronic lock. As shown, the exterior assembly **102** includes a cylinder guard cover **108** that houses internal components of the exterior assembly **102**. In the example shown, the cylinder guard cover **108** has a decorative shape with a rear portion **110** that would be adjacent a door (not shown) and a front portion **112** extending from the door. In this example, the cylinder guard cover **108** has a tapered shape from the rear portion **110** to the front portion **112**, but the exterior assembly **102** and cylinder guard cover **108** could have a wide variety of different sizes and shapes depending on the particular circumstances.

[0061] In the embodiment shown, the front portion **112** of the exterior assembly **102** includes a front cover **114** that surrounds a mechanical locking assembly **116**. A mechanical key (not shown) may be inserted into the mechanical locking assembly **116** to mechanically unlock the lock assembly **100**.

[0062] In the embodiment shown, a light communication device **118** surrounds the front cover **114**. In this example, the light communication device **118** is formed in the shape of a ring surrounding the front cover **114** and mechanical locking assembly **116**. However, the light communication device **118** could be formed in other shapes or positioned differently on the exterior assembly **102**.

[0063] As explained further below, the light communication device **118** includes a plurality of regions that could be independently controlled to visually communicate messages to the user, including but not limited to, an action currently being processed by the lock assembly **100**, information about the status of the lock assembly **100**, and/or requests for user input. By way of example, the light communication device **118** could visually communicate the direction of bolt movement by illuminating regions in sequence to create a rotation animation showing a direction of movement. The light communication device **118** could visually communicate messages to the user by controlling various attributes of the regions, such as turning regions on/off, changing intensity of regions, changing colors illuminated by regions, or other manners of changing the illumination of the light communication device **118**.

[0064] In some embodiments, the lock assembly **100** may be touch activated. For example, the lock assembly **100** may use capacitive sensing to determine whether the user wants to actuate the lock assembly **100**. The touch surface for capacitive sensing to actuate the lock assembly **100** could be any external surface, including but not limited to, a cylinder guard cover, a cylinder guard, a keyway, a handle, a rose, or other exterior surface of the lock assembly **100**. In the example shown, the exterior assembly **102** uses capacitive sensing to determine when a user touches the cylinder guard cover **108**. Accordingly, in the embodiment shown, the user is able to touch anywhere on the cylinder guard cover **108** to lock or unlock the lock assembly **100**, or otherwise activate various functions of the lock assembly **100**.

[0065] In the example shown, the exterior lock assembly **102** has a torque blade **120** extending from the rear portion **110**. The torque blade extends through an adaptor **122** in the embodiment shown, which is received within a bore in a door to which the lock assembly **100** is being installed or mounted.

[0066] The latch assembly **104** is disposed in a core in a door and may be actuated manually by the mechanical locking assembly **116**, or electronically by touching anywhere on the cylinder guard cover **108** (in the embodiment shown) to extend/retract a bolt **124**. The bolt **124** moves linearly in and out of a sleeve **126**. When the bolt **124** is retracted, an end of the bolt **124** is generally flush with a base plate **128**. When the bolt **124** is extended, the bolt **124** protrudes through an edge bore in the door into an opening **130** of a strike plate **132**, which is positioned in a jamb adjacent the door. As is typical, the strike plate **132** is attached to the jamb using fasteners **134**. Likewise, fasteners **136** attach the base plate **128** of the latch assembly **104** to the door.

[0067] In the embodiment shown, the latch assembly **104** includes a spindle **138** that is drivable in a first direction to extend the bolt **124** and a second direction to retract the bolt **124**. The spindle **138** is configured to receive the torque blade **120** such that rotation of the torque blade **120** in a first direction retracts the bolt **124**; whereas, rotation of the torque blade **120** in the opposite direction causes the spindle to retract the bolt **124**.

[0068] The torque blade **120** extends through the latch assembly **104** into an opening **140** in a mounting plate **142**, which is attached to an interior side of the door. The torque blade **120** passes through the opening **140** and is received by a spindle driver **144**. The spindle driver **144** provides electronic control of the bolt **124**, such as using a motor to rotate the spindle driver **144** in either a first direction or in a second direction. Since the torque blade **120** is disposed within the spindle **138**, rotation of the spindle driver **144** may be used to extend and/or retract the bolt **124** of the latch assembly **104**. In the embodiment shown, fasteners **146** extend through holes **148** in the mounting plate, which are aligned with openings **150** in the latch assembly **104**. A wiring harness (not shown) electrically connects electronics between the exterior assembly **102** and the interior assembly **106**.

[0069] FIG. 2 is a side cross-sectional view of the lock assembly **100** in an assembled state. In the example shown, the torque blade **120** can be seen extending from the rear portion **110** of the exterior assembly **102** through the spindle **138** of the latch assembly **104** into the spindle driver **144** of the interior assembly **106**. The torque blade **120** may be driven to extend/retract the bolt **124** in several ways. For example, the mechanical locking assembly **116** could be actuated by a

mechanical key to rotate the torque blade **120**, which would allow the bolt **124** to be extended/retracted. The exterior assembly **102** could be used to electronically actuate the latch assembly **104** by touching anywhere on the cylinder guard cover **108** (assuming the lock assembly **100** received authenticated credentials prior to the user touching the cylinder guard cover **108**). By touching anywhere on the exterior assembly **102** to actuate the bolt **124**, a message is sent from the exterior assembly **102** to the interior assembly **106** using a wiring harness to actuate a motor in the interior assembly **106** that drives the torque blade **120** using the spindle driver **144**. Additionally, if the user is inside the door, a turn piece **152** could be manually rotated by the user to actuate the torque blade **120** (via the spindle driver **144**), thereby moving the bolt **124** between its extended and retracted positions.

[0070] FIG. **3** is an exploded view of the exterior assembly **102**. As shown, the mechanical locking assembly **116**, which could be a pin-tumbler locking arrangement, has the torque blade **120** extending therefrom. As shown, the front end of the mechanical locking assembly **116** is received by an opening **154** in the front cover **114**. Preferably, the front cover **114** is made of a RF transparent material, such as a plastic. By way of example only, the front cover **114** could be made of a material called Terluran GP-22 by BASF of Ludwigshafen, Germany or Polylac PA-727 by Chi Mei Corporation of Taiwan.

[0071] In the embodiment shown, referring also to FIGS. **7-11**, the exterior assembly **102** includes an insulator **156** that is received within the rear portion **110** of the cylinder guard cover **108**. The insulator **156** is formed from an electrical insulator material, such as Polycarbonate PC-110 by Chi Mei Corporation of Taiwan. In this example, the insulator **156** includes a recessed portion **158** that houses several internal components. In the example shown, an O-ring **160**, a light pipe **162**, a PCB board **164**, and a conductive wave washer **166** are housed in the recessed portion **158** between the insulator **156** and the cylinder guard cover **108**.

[0072] In the example shown, the light communication device **118** is a light pipe **162**. As shown, referring also to FIGS. **19-24**, the light pipe **162** includes a recessed portion **163** on the front end that is dimensioned to receive the front cover **114**. A flange **165**, which is a ring-shape in the embodiment shown, surrounding the front cover **114** can be selectively illuminated. Accordingly, in the embodiment shown, the flange **165** or ring surrounding the front cover **114** may light up during operation. As discussed above, for example, the light pipe **162** may include a plurality of regions that are independently controllable to visually display messages to the user, which could be animations in some embodiments. In some embodiments, the light pipe **162** is translucent or transparent. By way of example only, the light pipe **162** could be made from a product called Polycarbonate PC-110 by Chi Mei Corporation of Taiwan. As shown, the light pipe **162** includes a groove dimensioned to receive a seal, which is an O-ring **160** in this example. The O-ring prevents moisture from entering the front portion **112** of the exterior assembly **102**. In the example shown, fasteners **168** extend through the light pipe **162**, PCB board **164**, and insulator **156** to connect within threaded openings **170** of a cylinder housing **172**.

[0073] Referring also to FIGS. **12-18**, the cylinder housing (also called cylinder guard) **172** provides impact strength and structural reinforcement for the exterior assembly **102**. For example, the cylinder housing **172** may be formed from a zinc alloy in some embodiments. In the embodiment shown, the cylinder housing **172** is received in a rear portion of the insulator **156**. As shown, the cylinder housing **172** includes a cavity **174** that is configured to receive an antenna. Despite having a cavity in the cylinder housing **172**, the cylinder housing **172** provides sufficient reinforcement for the exterior assembly **102** in tests.

[0074] A clip **176** retains a rear portion of the mechanical locking assembly **116** within the exterior assembly **102**. A retainer **178** and plate **180** are attached to a rear portion of the cylinder housing **172** for added tamper resistance and structural reinforcement of the cylinder housing **172**. Fasteners **182**, **184** are received within threaded openings in a back portion of the cylinder housing **172** to fasten the retainer **178** and plate **180**.

[0075] FIG. 4 is a front perspective view of the exterior assembly **102** with a portion removed to expose internal components. In this view, the cavity **174** formed in the cylinder housing **172** can be seen. This allows an antenna to be internal to the exterior assembly **102** (within the cylinder housing **172** as shown) to transmit signals outside the exterior assembly **102**. With an antenna on the front portion of the exterior assembly **102**, behind the light pipe **162** and front cover **114**, which are both plastic, this allows wireless signals to be transmitted out of the exterior assembly **102**. From this view, it can also be seen that the flange **165** of the light pipe **162** extends around the front cover **114**, which can be used to communicate with the user.

[0076] FIG. 5 is a side cross-sectional view of a portion of the exterior assembly **102**. As shown, an air gap **186** is formed by the insulator **156** between the cylinder guard cover **108** and the cylinder housing **172**. The insulator **156** also separates the touch surface, which is the cylinder guard cover **108** in this example, from the PCB **164** that hosts the touch electronics. In this example, the conductive wave washer **166** is compressed between the PCB **164** and the cylinder guard cover **108** to make electrical contact. With this electrical connector, the PCB **164** can sense when a user touches anywhere on the cylinder guard cover **108**. Although the cylinder guard cover **108** is shown for purposes of example, the touch surface could be any mechanical feature of a lockset, including but not limited to, a cylinder guard cover, cylinder guard, cylinder, keyway, handle, rose, or other exterior/interior features of a lockset. Although the conductive wave washer **166** is shown for purposes of example, the conductive medium could be a conductive foam, conductive tape, conductive grease, or any other mechanical device electrically connecting the touch surface of the lockset to the PCB that hosts the touch electronics. This is shown diagrammatically in FIG. 27. Also visible from the view is the cavity **174** for housing the antenna.

[0077] FIG. 6 is a rear perspective view of the exterior assembly **102**. As can be seen in this example, the torque blade **120** extends from the rear portion of the exterior assembly for actuating the spindle **138** and the latch assembly **104**. This view also shows the plate **180** and retainer **178** that have been attached to the rear portion of the cylinder housing **172**.

[0078] FIGS. 28-31 show an example of how the light pipe **162** (which is shown diagrammatically) may be used to communicate with the user. In the example shown, the light pipe includes a plurality of regions that may be independently illuminated or adjusted by intensity or color. These regions may be illuminated in a coordinated manner to display information about the exterior assembly **102**, such as a static image (e.g., solid or flashing the same regions) or as an animation (e.g., illuminating regions in a particular sequence). In the example shown, the light pipe **162** includes a first region **188**, a second region **190**, a third region **192**, a fourth region **194**, a fifth region **196**, a sixth region **198**, a seventh region **200**, and an eighth region **202**. Although eight regions are shown in this example, more or fewer regions could be used. Although these regions are represented by a circle, these are merely shown for purposes of example to indicate a region of the light pipe **162** that may be independently drivable. Consider an example in which the user has provided an authentication code to the lock assembly **100** and would like to touch the cylinder guard cover **108** to unlock the lock assembly **100**. One example communication that may be made by the light pipe **162** could be indicating the direction of movement of the bolt **124**. If the bolt **124** was moving to the right, for example, the light pipe **162** may illuminate regions in a sequence to animate a clockwise movement.

[0079] For example, the light pipe may first indicate the first and second regions **188**, **190**, as shown in FIG. 28. The next two regions **192**, **194** may then be illuminated and then the next regions **196**, **198**, and finally regions **200**, **202** to show an animation of a clockwise direction. If the bolt **124** was moving to the left, the animation could be in the opposite direction. The light pipe **162** could be used to communicate a wide variety of information, such as whether the lock assembly **100** is either in a locked state or in an unlocked state. Moreover, in some embodiments, the light pipe **162** could be used to request additional information from a user, such as requesting the user touch the touch surface to either lock or unlock the lock assembly **100**. If the user needs to touch

the cylinder guard cover **108** multiple times to activate a certain function of the lock assembly **100**, for example, the light pipe **162** could indicate the number of touches by flashing that number of times. Accordingly, the light pipe **162** acts as a user interface to communicate and interact with the user.

[0080] In operation, the user may approach the exterior assembly **102**, which could cause the light pipe **162** to illuminate to indicate the user is in range. If an authentication code transmitted by the user to the lock assembly **100** is authenticated or recognized, the light pipe **162** may indicate this, such as by flashing green or some sort of animation. The user may then touch anywhere on the cylinder guard cover **108** to unlock the lock assembly **100**. For example, this may cause a motor to rotate the spindle driver **144**, which rotates the torque blade **120** to retract the bolt **124**. As the lock assembly **100** is actuating the bolt to the retracted position, the light pipe **162** may indicate this through some sort of animation, such as a clockwise animation. When the bolt **124** has been fully retracted, the light pipe **162** may indicate that the bolt **124** is unlocked. If there was an error in retracting the bolt **124**, the light pipe **162** could indicate this.

[0081] FIGS. **32-39** show a battery contact assembly **210** for electrically connecting a battery **212**, such as a coin battery, to a PCB board **214** for supplying electrical power. In some cases, this assembly could be in a key fob that interacts with the lock assembly **100**. For example, the PCB **214** could be configured to transmit wireless messages to the lock assembly **100**, such as security credentials. The battery contact assembly **210** is configured to provide a low-profile key fob that is thinner than existing key fobs.

[0082] In the embodiment shown, the battery contact assembly **210** includes a first contact **216** and a second contact **218**. For example, the first contact **216** may connect a negative terminal of the battery **212** to the PCB **214** while the second contact **218** may connect the positive terminal of the battery **212**. The first contact **216** includes a mounting portion **220** for mounting the first contact to the PCB **214**. The second contact **218** includes a mounting portion **222** for mounting the second contact to the PCB **214**. In the example shown, the mounting portion **220** includes legs **224** that extend through holes **226** in the PCB **214** for soldering the first contact **216** to the PCB **214** to establish an electrical connection between the PCB **214** and the first contact **216**. In the example shown, the mounting portion **220** is mounted to the face of the PCB **214** (either the front or back as shown in FIGS. **34** and **35**). A projection **228** extends from the PCB **214** and is suspended above the second contact **218**. In the example shown, the projection **228** includes a straight portion **230** that extends along a longitudinal axis of the PCB and an angled portion **232**. The projection **228** includes a spring **234** surrounded by a holder **236**. The spring **234** urges against a first side of the battery to create a frictional fit with the second contact **218**.

[0083] In the example shown, the mounting portion **222** of the second contact **218** includes legs **238** that extend through holes **240** in the PCB **214** for soldering the second contact **218** to the PCB **214** to establish an electrical connection between the PCB **214** and the second contact **218**. In the example shown, the mounting portion **222** includes a face portion **242** and an edge portion **244** to straddle the PCB **214** (see FIGS. **33-35**). As shown, the edge portion **244** has a top end extending transverse from the face portion **242** and a bottom end with a projection **246** extending from the PCB **214** and is positioned on an opposing side of the battery **212** than the first contact **216**. As with the first contact **216**, the second contact **218** can be mounted to either the front or back of the PCB **214**. In the example shown, the projection **246** includes a straight portion **248** that extends along a longitudinal axis of the PCB and an angled portion **250**. The projection **246** includes a spring **252** surrounded by a holder **254**. The spring **252** urges against a second side of the battery to create a frictional fit with the first contact **216**. In use, a user may slide the battery **212** between the first contact **216** and the second contact **218**. The urging of springs **234**, **252** on opposing faces of the battery **212** creates a frictional fit to hold the battery **212** in place. Since the first contact **216** and the second contact **218** have an electrical connection with the PCB **214**, the battery **212** supplies power to the PCB **214**. If the user wants to remove the battery **212**, the battery **212** may

pulled out with sufficient force to overcome the friction of the springs 234, 252.

[0084] Although the present disclosure has been described with reference to particular means, materials, and embodiments, from the foregoing description, one skilled in the art can easily ascertain the essential characteristics of the invention and various changes and modifications may be made to adapt the various uses and characteristics without departing from the spirit and scope of the invention.

Claims

1. (canceled)

2. A lockset comprising: a latch assembly including a bolt movable between an extended position and a retracted position; a wireless communication interface; a controller configured to electronically control movement of the bolt between the extended position and the retracted position; and an exterior assembly including: a front surface comprising: a front cover made of a non-conductive and generally RF transparent material; and a light device configured to selectively illuminate a plurality of regions of the front surface; a guard cover at least partially surrounding the front surface, the guard cover constructed from a metal material and forming a body of the exterior assembly; and wherein the controller actuates movement of the bolt between the extended position and the retracted position in response to: receiving a touch input at a touch-sensitive surface; and receiving an authentication code.

3. The lockset of claim 2, wherein the authentication code is received from a user device.

4. The lockset of claim 2, wherein the guard cover includes the touch-sensitive mechanism.

5. The lockset of claim 2, wherein the light device is made of generally RF transparent material.

6. The lockset of claim 2, wherein the light device illuminates to visually indicate a request for user input.

7. The lockset of claim 2, wherein the light device is configured to illuminate in response to a user approaching the exterior assembly.

8. The lockset of claim 2, wherein the exterior assembly further comprises an antenna configured for wireless communication with a user device.

9. The lockset of claim 2, wherein the antenna is at least partially disposed in an internal cavity of the body defined by the guard cover.

10. A lockset comprising: a latch assembly including a bolt movable between an extended position and a retracted position; a controller configured to electronically control movement of the bolt between the extended position and the retracted position; and an exterior assembly including: a front surface comprising a front cover made of generally RF transparent material; a guard cover constructed from a metal material and at least partially surrounding the front surface; and an antenna configured for wireless communication with a user device, wherein the antenna is at least partially disposed in an internal cavity defined by the guard cover; wherein the controller is configured to: when the user device is in range of the exterior assembly, receive credentials from the user device; and in response to an indication that a user is located proximate to the exterior assembly and authenticating the credentials, actuate movement of the bolt between the extended position and the retracted position.

11. The lockset of claim 10, wherein the indication that the user is located proximal to the exterior assembly includes receipt of a touch input at a touch-sensitive mechanism of the exterior assembly.

12. The lockset of claim 11, wherein the guard cover includes the touch-sensitive mechanism.

13. The lockset of claim 10, wherein the front surface further comprises a light device.

14. The lockset of claim 13, wherein the light device is configured to illuminate to indicate that the user is in range of the exterior assembly.

15. The lockset of claim 14, wherein the light device is further configured to illuminate in response to the authentication of the credentials.

16. A lockset comprising: a latch assembly including a bolt movable between an extended position and a retracted position; a controller configured to electronically control movement of the bolt between the extended position and the retracted position; and an exterior assembly including: a front surface comprising a front cover made of generally RF transparent material; a guard cover constructed from a metal material and positioned at least partially surrounding the front surface, the guard cover forming a body having an internal cavity; and an antenna configured for wireless communication with a user device, wherein the antenna is at least partially disposed in the internal cavity defined by the guard cover; wherein the controller is configured to: determine a position of the user device; receive credentials from the user device when the user device is in range of the exterior assembly; and actuate movement of the bolt between the extended position and the retracted position based, at least in part, on authentication of the credentials.

17. The lockset of claim 16, wherein the guard cover includes a touch-sensitive surface.

18. The lockset of claim 17, wherein actuation of movement of the bolt between the extended position and the retracted position is further based on a touch input received at the touch-sensitive surface.

19. The lockset of claim 16, wherein the front surface further comprises a light device.

20. The lockset of claim 19, wherein the light device is configured to illuminate when the position of the user device is determined to be within range of the exterior assembly.

21. The lockset of claim 19, wherein the light device is configured to illuminate based on authentication of the credentials.
