US Patent & Trademark Office
Patent Public Search | Text View

United States Patent	12403837
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Thomas; Gregory Paul

Glove box for a vehicle

Abstract

A glove box for a vehicle includes a bin having an upper rim and defining a storage cavity accessible via an opening defined by the upper rim. The glove box further includes a retainer pivotably coupled to the bin and operable to pivot relative to the bin between a first position and a second position. In the first position, a portion of the retainer is positioned within the storage cavity. In the second position, the retainer is positioned wholly outside of the storage cavity.

Inventors: **Thomas; Gregory Paul (Canton, MI)**

Applicant: **Ford Global Technologies, LLC** (Dearborn, MI)

Family ID: **90355276**

Assignee: **Ford Global Technologies, LLC (Dearborn, MI)**

Appl. No.: **18/045653**

Filed: **October 11, 2022**

Prior Publication Data

Document Identifier	Publication Date
US 20240116449 A1	Apr. 11, 2024

Publication Classification

Int. Cl.: **B60R7/06** (20060101)

U.S. Cl.:

CPC **B60R7/06** (20130101);

Field of Classification Search

CPC: B60R (7/04); B60R (7/06); B60R (7/08); B60R (2011/0005)

USPC: 296/37.8; 296/37.12

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5915776	12/1998	Bieri	N/A	N/A
6109493	12/1999	Bieri	N/A	N/A
6854779	12/2004	Gehring	224/483	B60N 3/102
8398139	12/2012	Blackmore	312/274	B60R 7/06
8556320	12/2012	Yamagishi	296/37.8	B60R 7/04
10449907	12/2018	Dunham	N/A	B60Q 3/225
10533351	12/2019	Yano	N/A	B60R 7/04
2006/0197353	12/2005	Hanzel et al.	N/A	N/A
2011/0220705	12/2010	Acevedo et al.	N/A	N/A
2020/0130593	12/2019	Sukumar	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3510405	12/1984	DE	N/A
19906052	12/1999	DE	N/A

Primary Examiner: Daniels; Jason S

Attorney, Agent or Firm: Price Heneveld LLP

Background/Summary

FIELD OF THE DISCLOSURE

(1) The present disclosure generally relates to a glove box for a vehicle. More specifically, the present disclosure relates to a glove box for a vehicle that includes a retainer pivotably coupled to a bin of the glove box.

BACKGROUND OF THE DISCLOSURE

(2) Vehicles often include glove boxes and other storage compartments.

SUMMARY OF THE DISCLOSURE

(3) According to a first aspect of the present disclosure, a glove box for a vehicle includes a bin having an upper rim and defining a storage cavity accessible via an opening defined by the upper rim. The glove box further includes a retainer pivotably coupled to the bin and operable to pivot relative to the bin between a first position and a second position. In the first position, a portion of the retainer is positioned within the storage cavity. In the second position, the retainer is positioned wholly outside of the storage cavity.

(4) Embodiments of the first aspect of the disclosure can include any one or a combination of the following features: the retainer includes a cradle that defines a receiving space, wherein, in the first position of the retainer, the cradle is positioned within the storage cavity and oriented such that a base of the cradle extends beneath the receiving space; in the second position of the retainer, the cradle is oriented such that a side wall of the cradle that extends outward from the base extends

beneath the receiving space; the bin includes at least one retention feature, and the retainer includes at least one engagement feature configured to elastically deform due to contact with the at least one retention feature as the retainer enters at least one of the first position and the second position, such that contact between the at least one engagement feature and the at least one retention feature yieldingly maintains the retainer in the at least one of the first position and the second position; the at least one retention feature includes a first retention feature that protrudes into the storage cavity, and the at least one engagement feature includes a first engagement feature that extends outward from the base of the cradle opposite the receiving space defined by the cradle, wherein contact between the first engagement feature and the first retention feature yieldingly maintains the retainer in the first position; the at least one retention feature further includes a second retention feature that is positioned outside of the storage cavity, and the at least one engagement feature further includes a second engagement feature that is positioned nearer than the first engagement feature to a hinge that pivotably couples the retainer with the bin, wherein contact between the second engagement feature and the second retention feature yieldingly maintains the retainer in the second position; the bin is operably coupled to a dashboard of the vehicle and is operable to translate relative to the dashboard of the vehicle between an open position and a closed position; the retainer is configured to pivot relative to the bin about a pivot axis, wherein the pivot axis is substantially parallel to the direction that the bin translates from the open position to the closed position; and the retainer is integrally coupled with the bin and operable to pivot relative to the bin via deformation of a living hinge that extends between the retainer and the bin.
(5) According to second aspect of the present disclosure, a glove box for a vehicle includes a bin defining a storage cavity and being operable to translate in a first direction relative to a dashboard of the vehicle from an open position to a closed position. In the open position, the storage cavity is accessible. In the closed position, the storage cavity is covered by the dashboard. The glove box further includes a retainer pivotably coupled to the bin and operable to pivot relative to the bin between a first position and a second position about a pivot axis that is substantially parallel to the first direction.
(6) Embodiments of the second aspect of the disclosure can include any one or a combination of the following features: the retainer is integrally coupled with the bin and operable to pivot relative to the bin via deformation of a living hinge that extends between the retainer and the bin; a portion of the retainer is positioned within the storage cavity in the first position, and the retainer is positioned wholly outside of the storage cavity in the second position; the retainer includes a cradle that defines a receiving space, wherein, in the first position of the retainer, the cradle is positioned within the storage cavity and oriented such that a base of the cradle extends beneath the receiving space; and in the second position of the retainer, the cradle is oriented such that a side wall of the cradle that extends outward from the base extends above the receiving space.
(7) According to a third aspect of the present disclosure, a storage compartment includes a bin defining a storage cavity, and a retainer pivotably coupled to the bin and having a cradle. The retainer is pivotable relative to the bin from a first position to a second position. In the first position, the cradle is positioned within the storage cavity. In the second position, the cradle is positioned outside of the storage cavity.
(8) Embodiments of the third aspect of the disclosure can include any one or a combination of the following features: the bin is operably coupled to a dashboard of a vehicle and operable to move relative to the dashboard of the vehicle between an open position and a closed position; the bin is operable to translate relative to the dashboard of the vehicle between the open and closed positions; the retainer pivots relative to the bin about a pivot axis that is substantially parallel to the direction that the bin translates from the open position to the closed position; the retainer is integrally coupled with the bin and operable to pivot relative to the bin via deformation of a living hinge that extends between the retainer and the bin; and in the first position of the retainer, the cradle is positioned within the storage cavity and oriented such that a base of the cradle extends beneath a

receiving space defined by the cradle.
(9) These and other aspects, objects, and features of the present disclosure will be understood and appreciated by those skilled in the art upon studying the following specification, claims, and appended drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS
(1) In the drawings:
(2) FIG. **1** is a side perspective view of a glove box of a vehicle in a closed position, wherein a storage cavity of the glove box is covered by a dashboard of the vehicle, according to at least one embodiment;
(3) FIG. **2** is a side perspective view of the glove box, illustrating the glove box in an open position and a retainer coupled to a bin of the glove box in a first position, according to at least one embodiment;
(4) FIG. **3** is a cross-sectional view of the bin and the retainer of the glove box taken through line III-III of FIG. **2**, illustrating the retainer in the first position, wherein a cradle of the retainer is positioned within the storage cavity defined by the bin, according to at least one embodiment;
(5) FIG. **4** is a side perspective view of the glove box, illustrating the retainer pivoted to a second position relative to the bin, according to at least one embodiment;
(6) FIG. **5** is a cross-sectional view of the bin and the retainer of the glove box taken through line V-V of FIG. **4**, illustrating the retainer in a second position, wherein the cradle of the retainer is positioned outside of the storage cavity defined by the bin, according to at least one embodiment;
(7) FIG. **6** is a side perspective view of the glove box in the open position, illustrating retainers coupled to the bin of the glove box in first positions, respectively, and a plurality of file cabinet dividers engaged with the retainers within the storage cavity defined by the bin of the glove box, according to at least one embodiment; and
(8) FIG. **7** is a cross-sectional view of the bin and the retainer of the glove box taken through line VII-VII of FIG. **6**, illustrating the retainer in the first position and the divider engaged with the cradle of the retainer, according to at least one embodiment.
DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS
(9) Additional features and advantages of the disclosure will be set forth in the detailed description which follows and will be apparent to those skilled in the art from the description, or recognized by practicing the disclosure as described in the following description, together with the claims and appended drawings.
(10) As used herein, the term “and/or,” when used in a list of two or more items, means that any one of the listed items can be employed by itself, or any combination of two or more of the listed items can be employed. For example, if a composition is described as containing components A, B, and/or C, the composition can contain A alone; B alone; C alone; A and B in combination; A and C in combination; B and C in combination; or A, B, and C in combination.
(11) In this document, relational terms, such as “first” and “second,” “top” and “bottom,” and the like, are used solely to distinguish one entity or action from another entity or action, without necessarily requiring or implying any actual such relationship or order between such entities or actions.
(12) For purposes of this disclosure, the term “coupled” (in all of its forms: couple, coupling, coupled, etc.) generally means the joining of two components (electrical or mechanical) directly or indirectly to one another. Such joining may be stationary in nature or movable in nature. Such joining may be achieved with the two components (electrical or mechanical) and/or any additional intermediate members. Such joining may include members being integrally formed as a single

unitary body with one another (i.e., integrally coupled) or may refer to joining of two components. Such joining may be permanent in nature, or may be removable or releasable in nature, unless otherwise stated.
(13) The terms “substantial,” “substantially,” and variations thereof as used herein are intended to note that a described feature is equal or approximately equal to a value or description. For example, a “substantially planar” surface is intended to denote a surface that is planar or approximately planar. Moreover, “substantially” is intended to denote that two values are equal or approximately equal. In some embodiments, “substantially” may denote values within about 10% of each other, such as within about 5% of each other, or within about 2% of each other.
(14) As used herein, the terms “the,” “a,” or “an,” mean “at least one,” and should not be limited to “only one” unless explicitly indicated to the contrary. Thus, for example, reference to “a component” includes embodiments having two or more such components unless the context clearly indicates otherwise.
(15) Referring now to FIGS. **1-7**, a glove box **10** for a vehicle **12** includes a bin **14**. The bin **14** has an upper rim **16** and defines a storage cavity **18** that is accessible via an opening **20** defined by the upper rim **16**. A retainer **22** is pivotably coupled to the bin **14** and is operable to pivot relative to the bin **14** between a first position and a second position. In the first position, a portion of the retainer **22** is positioned within the storage cavity **18**. In the second position, the retainer **22** is positioned wholly outside of the storage cavity **18**.
(16) Referring now to FIGS. **1** and **2**, a storage compartment **24** is illustrated. In various embodiments, the storage compartment **24** can be a storage compartment **24** within the vehicle **12**. For example, as illustrated in FIGS. **1** and **2**, the storage compartment **24** is the glove box **10** of the vehicle **12**. The glove box **10** is operably coupled to a dashboard **26** of the vehicle **12**. It is contemplated that the storage compartment **24** of the vehicle **12** can be positioned at a variety of locations within the vehicle **12**.
(17) Referring now to FIGS. **1-4**, the storage compartment **24** of the vehicle **12** can include the bin **14**. As illustrated in FIG. **4**, the bin **14** defines the storage cavity **18**, and the storage cavity **18** is accessible via the opening **20** to the storage cavity **18**. As illustrated in FIG. **4**, the opening **20** to the storage cavity **18** can be defined by the upper rim **16** of the bin **14**. The bin **14** can include a plurality of walls **28**. In the embodiments illustrated in FIGS. **2** and **4**, the bin **14** includes two side walls **30** that are opposite each other and extend vehicle-forward from a door panel **32** of the glove box **10** to a back wall **34** of the bin **14**.
(18) Referring now to FIGS. **1** and **2**, the storage compartment **24** can be operable to move between the open position and the closed position. In the open position, the storage cavity **18** defined by the bin **14** of the storage compartment **24** is accessible. In the closed position, the storage cavity **18** is covered. In the embodiment illustrated in FIGS. **1** and **2**, wherein the storage compartment **24** is the glove box **10** of the vehicle **12**, the storage cavity **18** is accessible in the open position of the glove box **10**, as illustrated in FIG. **2**. In the closed position of the glove box **10** illustrated in FIG. **1**, the storage cavity **18** defined by the bin **14** of the glove box **10** is covered by the dashboard **26** of the vehicle **12**. In some embodiments, the storage compartment **24** is operable to translate between the open and closed positions. For example, as illustrated in FIGS. **1** and **2**, the glove box **10** is operable to translate relative to the dashboard **26** of the vehicle **12** between the closed and open positions, as illustrated in FIGS. **1** and **2**, respectively. It is contemplated that the storage compartment **24** may move between the open and closed positions in a variety of manners (e.g., translation, pivotal movement, etc.). In the embodiment illustrated in FIGS. **1** and **2**, the glove box **10** is slidingly engaged with a portion of the dashboard **26** and is operable to translate vehicle-rearward from the closed position, as illustrated in FIG. **1**, to the open position, as illustrated in FIG. **2**.
(19) Referring now to FIGS. **2-5**, the bin **14** of the storage compartment **24** can include at least one retention feature **36**. In some implementations, the at least one retention feature **36** protrudes into

the storage cavity **18** defined by the bin **14**. For example, the at least one retention feature **36** can be a protuberance **38** that extends outward from an interior surface **62** of the side wall **30** of the bin **14** into the storage cavity **18** defined by the bin **14**. In some implementations, the at least one retention feature **36** can be positioned outside of the storage cavity **18** defined by the bin **14**. For example, in some implementations, the at least one retention feature **36** can be a protuberance **38** that extends outward from an exterior surface **64** of the side wall **30** of the bin **14**, generally away from the storage cavity **18** defined by the bin **14**. In various embodiments, the at least one retention feature **36** can include a plurality of retention features **36**. For example, in the embodiments illustrated in FIGS. **3** and **5**, the at least one retention feature **36** includes a first retention feature **36**A and a second retention feature **36**B. In the illustrated embodiment, the first retention feature **36**A protrudes into the storage cavity **18** from the interior surface **62** of the side wall **30** of the bin **14**. Further, the second retention feature **36**B is positioned outside of the storage cavity **18**, wherein the second retention feature **36**B is coupled to an exterior surface **64** of the bin **14** and protrudes outward therefrom. As described further herein, in various implementations, the at least one retention feature **36** may be configured to be engaged with an engagement feature **40** of the retainer **22** to yieldingly maintain the position of the retainer **22** relative to the bin **14**. A variety of types of retention features **36** configured for engagement with corresponding engagement features **40** are contemplated.
(20) Referring now to FIGS. **2-5**, the retainer **22** can be pivotably coupled to the bin **14**. In various embodiments, the retainer **22** is operable to pivot relative to the bin **14** between a first position and a second position. In the first position of the retainer **22**, a portion of the retainer **22** is positioned within the storage cavity **18**, as illustrated in FIG. **3**. In the second position, a portion of the retainer **22** can be positioned outside of the storage cavity **18**. In some implementations, in the second position of the retainer **22**, the retainer **22** is positioned wholly outside of the storage cavity **18**. For example, as illustrated in FIG. **5**, wherein the retainer **22** is disposed in the second position, the retainer **22** is positioned wholly outside of the storage cavity **18** defined by the bin **14**. In various embodiments, a portion of the retainer **22** passes through the opening **20** defined by the upper rim **16** of the storage cavity **18** as the retainer **22** pivots between the first and second positions. In various embodiments, the retainer **22** is configured to pivot relative to the bin **14** about a pivot axis **42**, as illustrated in FIG. **4**. In some implementations, wherein the bin **14** is configured to translate between the open and closed positions, the pivot axis **42** about which the retainer **22** pivots between the first and second positions is substantially parallel to the direction that the bin **14** translates from the open position to the closed position. In various embodiments, in the second position of the retainer **22**, the bin **14** is operable to translate between the open and closed positions without interference between the retainer **22** and the dashboard **26** of the vehicle **12**.
(21) In various embodiments, the retainer **22** is pivotably coupled with the bin **14** via a hinge **44** coupled to the retainer **22**. A variety of types of hinges **44** are contemplated. In some embodiments, the hinge **44** can be a living hinge **46**. For example, as illustrated in FIGS. **3** and **5**, the retainer **22** is integrally coupled with the bin **14** and is operable to pivot relative to the bin **14** via deformation of the living hinge **46** that extends between the retainer **22** and the bin **14**. In the illustrated embodiment, the living hinge **46** is positioned proximate to the upper rim **16** of the bin **14**, outside of the storage cavity **18** defined by the bin **14**.
(22) Referring now to FIGS. **2-5**, the retainer **22** can include a cradle **48**. The cradle **48** defines a receiving space **50**. As described further herein, in operation of the storage compartment **24**, the receiving space **50** defined by the cradle **48** of the retainer **22** may be configured to receive a corresponding attachment feature **52**, such as a hook **54** of a divider **56** that extends within the storage cavity **18** defined by the bin **14** for organizational purposes. In the embodiment illustrated in FIG. **3**, the cradle **48** includes side walls **58** and a base **60** that extends between the side walls **58**. As illustrated in FIG. **3**, the first side wall **58**A of the cradle **48** is positioned distally from the hinge **44** that couples the retainer **22** with the bin **14**. The base **60** extends outward from the first side wall

58A of the cradle **48** and is positioned between the hinge **44** and the first side wall **58**A. The second side wall **58**B extends outward from the base **60** and is positioned between the base **60** and the hinge **44**. As illustrated in FIG. **3**, the first side wall **58**A, the base **60**, and the second side wall **58**B of the cradle **48** define the receiving space **50**.

(23) Referring still to FIGS. **2-5**, in the first position of the retainer **22**, as illustrated in FIGS. **2** and **3**, the cradle **48** of the retainer **22** is positioned within the storage cavity **18**. As illustrated in FIG. **3**, in the first position of the retainer **22**, the cradle **48** is oriented such that the base **60** of the cradle **48** extends beneath the receiving space **50**. In other words, the base **60** of the cradle **48** is positioned vehicle-downward of the receiving space **50** in the first position of the retainer **22**. As illustrated in FIGS. **4** and **5**, in the second position of the retainer **22**, the cradle **48** of the retainer **22** is positioned outside of the storage cavity **18** defined by the bin **14**. Further, as illustrated in FIG. **5**, the cradle **48** is oriented such that at least one side wall **58** of the cradle **48** extends outward from the base **60** of the cradle **48** beneath the receiving space **50**. In the embodiment illustrated in FIG. **5**, the first side wall **58**A of the cradle **48** extends beneath the receiving space **50** defined by the cradle **48** in the second position of the retainer **22**.

(24) Referring now to FIGS. **3** and **5**, the retainer **22** includes the at least one engagement feature **40** that is configured to be engaged with the at least one retention feature **36** of the bin **14**. In various embodiments, the at least one engagement feature **40** of the retainer **22** is configured to elastically deform due to contact with the at least one retention feature **36** of the bin **14** as the retainer **22** enters at least one of the first position and the second position. The contact between the at least one engagement feature **40** and the at least one retention feature **36** may yieldingly maintain the retainer **22** in the at least one of the first position and the second position of the retainer **22**. In various embodiments, the at least one engagement feature **40** can include a plurality of engagement features **40**. For example, as illustrated in FIGS. **3** and **5**, the at least one engagement feature **40** includes a first engagement feature **40**A and a second engagement feature **40**B. As illustrated in FIGS. **3** and **5**, the first engagement feature **40**A extends outward from the base **60** of the cradle **48** opposite the receiving space **50** defined by the cradle **48**. In the illustrated embodiment, the first engagement feature **40**A is generally L-shaped and configured to contact and/or be deformed by the first retention feature **36**A of the bin **14** in the first position of the retainer **22**, as illustrated in FIG. **3**. In operation, contact between the first engagement feature **40**A and the first retention feature **36**A in the first position of the retainer **22** yieldingly maintains the retainer **22** in the first position, as illustrated in FIG. **3**. The second engagement feature **40**B is coupled to the retainer **22** between the base **60** of the retainer **22** and the hinge **44** that pivotably couples the retainer **22** and the bin **14**. As illustrated in FIG. **5**, the second engagement feature **40**B is positioned nearer than the first engagement feature **40**A to the hinge **44** that pivotally couples the retainer **22** with the bin **14**. Contact between the second engagement feature **40**B and the second retention feature **36**B in the second position of the retainer **22** yieldingly maintains the retainer **22** in the second position, as illustrated in FIG. **5**.

(25) Referring now to FIGS. **2**, **6**, and **7**, in various embodiments, the storage compartment **24** can include a plurality of retainers **22** coupled to the bin **14**. For example, as illustrated in FIG. **2**, the glove box **10** includes a first retainer **22**A that is coupled with the first side wall **30**A of the bin **14** and a second retainer **22**B that is coupled with the second side wall **30**B of the bin **14** opposite the first side wall **30**A. In operation, the first and second retainers **22**A, **22**B can cooperate to selectively provide first and second cradles **48**A, **48**B, the receiving spaces **50** of which receive attachment features **52** of dividers **56** therein, as illustrated in FIGS. **6** and **7**. As illustrated in FIG. **7**, the receiving space **50** receives the attachment features **52** (e.g., hooks **54**) of the dividers **56** disposed within the storage cavity **18** of the bin **14**, such that the dividers **56** can be supported by, and movable along the cradle **48** of the retainer **22**. The dividers **56** disposed within the storage cavity **18** may advantageously allow for organization of documents and/or other items within the storage cavity **18** of the storage compartment **24**. Further, as illustrated in FIGS. **4** and **5**, the

plurality of retainers **22** may be pivoted to the respective second positions of the retainers **22** to provide additional space within the storage cavity **18** for storing items when dividers **56** are not desired.
(26) The storage compartment **24** of the present disclosure may provide a variety of advantages. First, the retainer **22** being operable to receive an attachment feature **52** of a divider **56** while in the first position may conveniently allow for insertion of dividers **56** into the storage cavity **18** for organizational purposes. Second, the retainer **22** being pivotably coupled to the bin **14** and operable to pivot from the first position to the second position, wherein the retainer **22** is positioned wholly outside of the storage cavity **18**, may conveniently allow the user to maximize the space available within the storage cavity **18** for storage of larger objects. Third, various portions of the storage compartment **24**, such as the bin **14**, the retainer **22**, the at least one retention feature **36**, and/or the at least one engagement feature **40**, being integrally coupled with each other may reduce the complexity of assembly and the number of parts necessary, which can reduce the cost of the storage compartment **24**.
(27) It is to be understood that variations and modifications can be made on the aforementioned structure without departing from the concepts of the present disclosure, and further it is to be understood that such concepts are intended to be covered by the following claims unless these claims by their language expressly state otherwise.

Claims

1. A glove box for a vehicle, comprising: a bin having an upper rim and defining a storage cavity accessible via an opening defined by the upper rim; and a retainer integrally coupled with the bin and operable to pivot relative to the bin via deformation of a living hinge that extends between the retainer and the bin between a first position, wherein a portion of the retainer is positioned within the storage cavity, and a second position, wherein the retainer is positioned wholly outside of the storage cavity.
2. The glove box of claim 1, wherein the retainer includes a cradle that defines a receiving space, wherein, in the first position of the retainer, the cradle is positioned within the storage cavity and oriented such that a base of the cradle extends beneath the receiving space.
3. The glove box of claim 2, wherein, in the second position of the retainer, the cradle is oriented such that a side wall of the cradle that extends outward from the base and beneath the receiving space.
4. The glove box of claim 3, wherein the bin includes at least one retention feature, and the retainer includes at least one engagement feature configured to elastically deform due to contact with the at least one retention feature as the retainer enters at least one of the first position and the second position, such that contact between the at least one engagement feature and the at least one retention feature yieldingly maintains the retainer in the at least one of the first position and the second position.
5. The glove box of claim 4, wherein the at least one retention feature includes a first retention feature that protrudes into the storage cavity, and the at least one engagement feature includes a first engagement feature that extends outward from the base of the cradle opposite the receiving space defined by the cradle, wherein contact between the first engagement feature and the first retention feature yieldingly maintains the retainer in the first position.
6. The glove box of claim 5, wherein the at least one retention feature further includes a second retention feature that is positioned outside of the storage cavity, and the at least one engagement feature further includes a second engagement feature that is positioned nearer than the first engagement feature to a hinge that pivotably couples the retainer with the bin, wherein contact between the second engagement feature and the second retention feature yieldingly maintains the retainer in the second position.

7. The glove box of claim 1, wherein the bin is operably coupled to a dashboard of the vehicle and is operable to translate relative to the dashboard of the vehicle between an open position and a closed position.
8. The glove box of claim 7, wherein the retainer is configured to pivot relative to the bin about a pivot axis, wherein the pivot axis is substantially parallel to the direction that the bin translates from the open position to the closed position.
9. A glove box for a vehicle, comprising: a bin defining a storage cavity and being operable to translate in a first direction relative to a dashboard of the vehicle from an open position, wherein the storage cavity is accessible, to a closed position, wherein the storage cavity is covered by the dashboard; and a retainer pivotably coupled to the bin and operable to pivot relative to the bin between a first position and a second position about a pivot axis that is substantially parallel to the first direction.
10. The glove box of claim 9, wherein the retainer is integrally coupled with the bin and operable to pivot relative to the bin via deformation of a living hinge that extends between the retainer and the bin.
11. The glove box of claim 9, wherein a portion of the retainer is positioned within the storage cavity in the first position, and the retainer is positioned wholly outside of the storage cavity in the second position.
12. The glove box of claim 9, wherein the retainer includes a cradle that defines a receiving space, wherein, in the first position of the retainer, the cradle is positioned within the storage cavity and oriented such that a base of the cradle extends beneath the receiving space.
13. The glove box of claim 12, wherein, in the second position of the retainer, the cradle is oriented such that a side wall of the cradle that extends outward from the base extends above the receiving space.
14. A storage compartment, comprising: a bin defining a storage cavity; and a retainer integrally coupled with the bin and having a cradle, the retainer being operable to pivot relative to the bin via deformation of a living hinge that extends between the retainer and the bin from a first position, wherein the cradle is positioned within the storage cavity, to a second position, wherein the cradle is positioned outside of the storage cavity.
15. The storage compartment of claim 14, wherein the bin is operably coupled to a dashboard of a vehicle and operable to move relative to the dashboard of the vehicle between an open position and a closed position.
16. The storage compartment of claim 15, wherein the bin is operable to translate relative to the dashboard of the vehicle between the open and closed positions.
17. The storage compartment of claim 16, wherein the retainer pivots relative to the bin about a pivot axis that is substantially parallel to the direction that the bin translates from the open position to the closed position.
18. The storage compartment of claim 14, wherein, in the first position of the retainer, the cradle is positioned within the storage cavity and oriented such that a base of the cradle extends beneath a receiving space defined by the cradle.