

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12395381
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Thasari; Sri Venkata Gautham et al.

Method, apparatus, and computer readable medium

Abstract

A method includes determining a least squares channel estimate (LSE) of a channel, removing a first Orthogonal cover code (OCC) sequence from the LSE thereby generating a first signal, determining an estimated timing offset of the first signal, adjusting a first timing of the LSE based on the estimated timing offset thereby generating a second signal with an adjusted timing, removing a second OCC sequence from the second signal thereby generating a third signal, determining a channel estimate of the channel based on the third signal, determining a noise power of a received signal, determining a signal power of the received signal, determining a signal to noise ratio (SNR) of the received signal based on the noise power and the signal power, adjusting a data rate of the channel based on the SNR, and transmitting an output signal based on an adjusted data rate of the channel.

Inventors:	Thasari; Sri Venkata Gautham (Bangalore, IN), Muralidhara; Venkatesh (Bangalore, IN), Kanzal Venkatesha; Hari Swaroop (Bangalore, IN), Agrawal; Ayush (Bangalore, IN)
Applicant:	RAKUTEN SYMPHONY, INC. (Tokyo, JP)
Family ID:	1000008766483
Assignee:	RAKUTEN SYMPHONY, INC. (Tokyo, JP)
Appl. No.:	18/248055
Filed (or PCT Filed):	December 22, 2022
PCT No.:	PCT/US2022/053861
PCT Pub. No.:	WO2024/136868
PCT Pub. Date:	June 27, 2024

Prior Publication Data

Publication Classification

Int. Cl.: H04L25/02 (20060101); H04B17/309 (20150101); H04L27/26 (20060101)

U.S. Cl.:

CPC H04L25/025 (20130101); H04B17/346 (20230501); H04L27/26035 (20210101); H04L27/2675 (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4150867	12/1978	Knickerbocker	439/402	H05K 7/186
5918680	12/1998	Maranghides	169/46	A62C 99/0018
6792052	12/2003	Johansson	375/354	H04L 25/0242
7035353	12/2005	Fimoff	375/346	H04L 25/025
7706324	12/2009	Sutivong	370/442	H04W 74/002
8073393	12/2010	Yu	370/320	H04L 25/025
8259669	12/2011	Sutivong	370/332	H04W 74/04
8339930	12/2011	Gore	370/500	H04L 5/0048
10693621	12/2019	Bendlin	N/A	H04L 5/001
10771133	12/2019	Lin	N/A	H04L 5/0048
11190329	12/2020	Sengupta	N/A	H04W 72/23
11930465	12/2023	Xiong	N/A	H04L 5/0094
12028198	12/2023	Lu	N/A	H04J 13/0062
12113657	12/2023	Thasari	N/A	H04W 72/23
12218863	12/2024	Thasari	N/A	H04L 27/2636
2007/0283220	12/2006	Kim	714/758	H03M 13/1148
2010/0070091	12/2009	Watson	700/278	H02J 13/00004
2010/0195751	12/2009	Orlik	375/267	H04L 25/20
2011/0182340	12/2010	Primo	375/224	H04B 17/345
2012/0054577	12/2011	Kim	714/755	H03M 13/1148
2013/0064313	12/2012	Gatti	375/316	H04L 25/022
2013/0117623	12/2012	Kim	714/752	H03M 13/2972
2014/0071233	12/2013	Lim	348/43	H04N 19/597
2014/0211833	12/2013	Schoeneich	375/346	H04L 25/0232
2018/0198580	12/2017	Nammi	N/A	H04L 27/0012

2019/0049594	12/2018	Yoshino	N/A	G01S 19/44
2019/0356462	12/2018	Bendlin	N/A	H04L 5/001
2020/0116248	12/2019	Yamaguchi	N/A	G03G 21/1647
2020/0127801	12/2019	Sengupta	N/A	H04L 27/262
2021/0091984	12/2020	Kuchi	N/A	H03H 17/02
2021/0119751	12/2020	Mundarath	N/A	H04L 1/0045
2021/0125437	12/2020	Lee	N/A	G07C 9/00309
2022/0029870	12/2021	Lu	N/A	H04J 13/0062
2022/0393922	12/2021	Geng	N/A	H04L 27/2607
2023/0007520	12/2022	Yao	N/A	H04L 43/20
2023/0179450	12/2022	Golebiowski	370/230	H04L 47/27
2023/0327916	12/2022	Upalekar	N/A	H04L 1/0061
2023/0327917	12/2022	Upalekar	N/A	H04J 13/18
2023/0327918	12/2022	Upalekar	N/A	H04L 25/0232
2024/0067822	12/2023	Tanabe	N/A	C08G 73/14
2024/0259246	12/2023	Hamidi-Sepehr	N/A	H04L 27/26522
2024/0275531	12/2023	Thasari	N/A	H04L 1/1825
2024/0283876	12/2023	Tsuchiya	N/A	H04N 1/00315
2024/0320790	12/2023	Iwahana	N/A	G06T 5/00
2025/0023759	12/2024	Xu	N/A	H04L 1/00
2025/0088391	12/2024	Thasari	N/A	H04L 5/0091

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2723083	12/2017	CA	F25D 21/04
1350379	12/2001	CN	H04J 13/0055
1146163	12/2003	CN	H04J 13/0055
101083515	12/2006	CN	N/A
101364966	12/2008	CN	N/A
102844991	12/2011	CN	H04J 13/18
104426820	12/2014	CN	N/A
107979548	12/2017	CN	H04L 25/0204
107979556	12/2017	CN	H04L 25/0204
104426820	12/2017	CN	N/A
110855595	12/2019	CN	H04L 27/0014
111082907	12/2019	CN	G01S 5/0036
111245750	12/2019	CN	H04L 25/0202
106063163	12/2019	CN	H04B 17/318
112165370	12/2020	CN	H04L 1/0009
113852381	12/2020	CN	N/A
114257481	12/2021	CN	H04L 27/0014
114338306	12/2021	CN	N/A
114500184	12/2021	CN	N/A
112165370	12/2021	CN	H04L 1/0009
114697169	12/2021	CN	H04L 27/0014
114500184	12/2022	CN	N/A

114338306	12/2023	CN	N/A
119210966	12/2023	CN	N/A
2723083	12/1977	DE	B60R 25/1004
2723083	12/2013	EP	G06T 9/00
3188392	12/2016	EP	H04L 1/02
3614608	12/2019	EP	H04B 17/327
3657871	12/2019	EP	H04L 1/00
3790311	12/2020	EP	H04L 41/00
3790311	12/2021	EP	H04L 41/00
2723083	12/1995	FR	C04B 35/571
2002129828	12/2001	JP	E05D 15/26
2005006343	12/2004	JP	H04J 13/0022
2005006346	12/2004	JP	H04J 13/0022
3657871	12/2004	JP	E05D 15/26
4150867	12/2007	JP	C08J 5/2237
5918680	12/2015	JP	H04L 1/0026
2020064111	12/2019	JP	F16G 1/20
2008514076	12/2019	JP	N/A
2019520728	12/2019	JP	H04W 52/36
2023028935	12/2022	JP	N/A
2024103265	12/2023	JP	N/A
2024118047	12/2023	JP	H04N 1/00315
2024118048	12/2023	JP	N/A
2024136868	12/2023	JP	B60R 1/26
20060040014	12/2005	KR	H04H 20/02
20140112905	12/2012	KR	H04B 7/24
2723083	12/2019	RU	H04L 5/0007
WO-9959216	12/1998	WO	C08J 5/2237
WO-0161950	12/2000	WO	H04L 25/0224
WO-0243271	12/2001	WO	H04B 7/005
WO-2006124810	12/2005	WO	H04B 1/69
WO-2010114167	12/2009	WO	H04L 25/022
WO-2011073915	12/2010	WO	H04L 25/0212
WO-2011083876	12/2010	WO	H04L 25/0204
WO-2014054344	12/2013	WO	H04L 1/0026
WO-2015131314	12/2014	WO	H04B 1/7113
WO-2016150094	12/2015	WO	H04L 25/02
WO-2017138502	12/2016	WO	G01C 21/16
WO-2017197075	12/2016	WO	H04L 5/0005
WO-2018082045	12/2017	WO	H04L 5/0007
WO-2018132944	12/2017	WO	H04B 7/0456
WO-2018135495	12/2017	WO	B32B 1/00
WO-2019047553	12/2018	WO	H04L 1/00
WO-2019084397	12/2018	WO	C08G 77/08
WO-2019229774	12/2018	WO	H04B 1/1027
WO-2020001171	12/2019	WO	H04L 41/00
WO-2020033373	12/2019	WO	H04L 43/0817
WO-2020037257	12/2019	WO	H04L 5/0053
WO-2020064111	12/2019	WO	N/A

WO-2020147726	12/2019	WO	H04B 17/364
WO-2021165729	12/2020	WO	H04L 27/2602
WO-2021228599	12/2020	WO	H04L 25/0224
WO-2022097547	12/2021	WO	C08G 73/10
WO-2022236969	12/2021	WO	H04L 25/03159
WO-2023028935	12/2022	WO	H04L 1/08
WO-2024103265	12/2023	WO	N/A
WO-2024118047	12/2023	WO	H04L 12/12
WO-2024118048	12/2023	WO	H04L 1/1671
WO-2024136868	12/2023	WO	H04B 17/346
WO-2024158394	12/2023	WO	H04B 17/336
WO-2025014492	12/2024	WO	N/A

Primary Examiner: Tadesse; Berhanu

Attorney, Agent or Firm: HAUPTMAN HAM, LLP

Background/Summary

RELATED APPLICATIONS

(1) The present application is a National Phase of International Application No. PCT/US2022/053861 filed Dec. 22, 2022.

FIELD

(2) The present application relates to a method of determining a robust signal to noise ratio (SNR) that avoids SNR saturation at higher operating signal levels, and an apparatus for determining the robust SNR that avoids SNR saturation at higher operating signal levels.

BACKGROUND

(3) In a wireless communications system, user equipment (UE) communicates with a network node (e.g., a base station, or the like) to transmit data on one or more uplink channels, and to receive data on one or more downlink channels. The UE sends data and signaling to the network node on one or more uplink channels. For example, the data and signaling sent from the UE to the network node is sent on a Physical Uplink Shared Channel (PUSCH).

SUMMARY

(4) In some approaches, the processing of signals for the Physical Uplink Shared Channel (PUSCH)—Cyclic Prefix_Orthogonal Frequency Division Multiplexing (CP_OFDM) involves the removal of the demodulation reference signal (DMRS) base sequence, removal of Orthogonal cover code (OCC) and estimation of a timing offset followed by compensation of the timing offset. In other words, the compensation of the timing offset in some approaches is performed on a signal that has had removal of the OCC sequence. As the OCC removal of some approaches happens before compensation of any possible timing offsets, it results in erroneous least squares channel estimates (LSEs). As a result, by having erroneous LSEs in some approaches, simulation and field deployment have observed that the estimated SNR saturates at a higher operating SNR thereby underrating the user equipment's (UE's) capability to handle advanced scheduling configuration, and resulting in an SNR that is not robust.

(5) One or more embodiments of the present disclosure utilize a two-step OCC removal, and timing compensation performed on a least squares estimate of a channel that add robustness to the estimated SNR. For example, one or more embodiments of the present disclosure disclose

determining the least squares channel estimate of the channel, generating a first signal by removing a first OCC sequence from the least squares channel estimate, determining at least an estimated timing offset of the first signal, generating a second signal with an adjusted timing by adjusting a first timing of the least squares channel estimate based on at least the estimated timing offset, generating a third signal by removing a second OCC sequence from the second signal, determining a channel estimate of the channel, determining a first noise power of a first received signal, determining a first signal power of the first received signal, and determining a SNR of the first received signal. In some embodiments, the channel is configured to receive a first received signal, the first received signal including a DMRS symbol sequence, a number of DMRS symbols, and a number of subcarriers.

(6) Thus, one or more embodiments of the present disclosure reduces the likelihood of saturated SNR results, thereby significantly enhancing the robustness of the estimated SNR at higher operating SNRs compared to other approaches. In some embodiments, by significantly enhancing the robustness of the estimated SNR results in better scheduling for the UE than other approaches.

(7) An aspect of this description relates to a method. In some embodiments, the method includes determining, by a processor of a receiver, a least squares channel estimate of a channel, the channel being configured to receive a first received signal, the first received signal including a demodulation reference signal (DMRS) symbol sequence, a number of DMRS symbols, and a number of subcarriers. In some embodiments, the method further includes removing, by the processor, a first Orthogonal cover code (OCC) sequence from the least squares channel estimate, thereby generating a first signal. In some embodiments, the method further includes determining, by the processor, at least an estimated timing offset of the first signal. In some embodiments, the method further includes adjusting, by the processor, a first timing of the least squares channel estimate based on at least the estimated timing offset, thereby generating a second signal with an adjusted timing. In some embodiments, the method further includes removing, by the processor, a second OCC sequence from the second signal, thereby generating a third signal. In some embodiments, the method further includes determining, by the processor, a channel estimate of the channel based on the third signal. In some embodiments, the method further includes determining, by the processor, a first noise power of the first received signal based on at least the channel estimate, the first received signal or the DMRS symbol sequence. In some embodiments, the method further includes determining, by the processor, a first signal power of the first received signal based on at least the channel estimate. In some embodiments, the method further includes determining, by the processor, a signal to noise ratio of the first received signal based on the first noise power and the first signal power. In some embodiments, the method further includes adjusting a data rate of the channel based on the SNR. In some embodiments, the method further includes transmitting, by a transmitter, an output signal based on an adjusted data rate of the channel based on the SNR.

(8) Another aspect of this description relates to an apparatus that includes a memory having non-transitory instructions stored therein, a transceiver coupled to the memory, and a processor coupled to the memory, and being configured to execute the non-transitory instructions, thereby causing the apparatus to determine a least squares channel estimate of a channel, the channel being configured to receive a first received signal, the first received signal including a demodulation reference signal (DMRS) symbol sequence, a number of DMRS symbols, and a number of subcarriers. In some embodiments, the processor is configured to execute the non-transitory instructions, thereby further causing the apparatus to remove a first Orthogonal cover code (OCC) sequence from the least squares channel estimate, thereby generating a first signal. In some embodiments, the processor is configured to execute the non-transitory instructions, thereby further causing the apparatus to determine at least an estimated timing offset of the first signal. In some embodiments, the processor is configured to execute the non-transitory instructions, thereby further causing the apparatus to adjust a first timing of the least squares channel estimate based on at least the estimated timing

offset, thereby generating a second signal with an adjusted timing. In some embodiments, the processor is configured to execute the non-transitory instructions, thereby further causing the apparatus to remove a second OCC sequence from the second signal, thereby generating a third signal. In some embodiments, the processor is configured to execute the non-transitory instructions, thereby further causing the apparatus to determine a channel estimate of the channel based on the third signal. In some embodiments, the processor is configured to execute the non-transitory instructions, thereby further causing the apparatus to determine a first noise power of the first received signal based on at least the channel estimate, the first received signal or the DMRS symbol sequence. In some embodiments, the processor is configured to execute the non-transitory instructions, thereby further causing the apparatus to determine a first signal power of the first received signal based on at least the channel estimate. In some embodiments, the processor is configured to execute the non-transitory instructions, thereby further causing the apparatus to determine a signal to noise ratio (SNR) of the first received signal based on the first noise power and the first signal power. In some embodiments, the processor is configured to execute the non-transitory instructions, thereby further causing the apparatus to determine an adjusted data rate of the channel based on the SNR. In some embodiments, the transceiver is configured to send a signal based on the adjusted data rate of the channel, the signal instructing a device to adjust a data rate to the adjusted data rate.

(9) Still another aspect of this description relates to a computer-readable medium. In some embodiments, the computer-readable medium includes instructions executable by a controller of a system to cause the system to perform operations including determining a least squares channel estimate of a channel, the channel being configured to receive a first received signal, the first received signal including a demodulation reference signal (DMRS) symbol sequence, a number of DMRS symbols, and a number of subcarriers. In some embodiments, the computer-readable medium includes instructions executable by the controller of the system to further cause the system to perform operations including removing a first Orthogonal cover code (OCC) sequence from the least squares channel estimate, thereby generating a first signal. In some embodiments, the computer-readable medium includes instructions executable by the controller of the system to further cause the system to perform operations including determining at least an estimated timing offset of the first signal. In some embodiments, the computer-readable medium includes instructions executable by the controller of the system to further cause the system to perform operations including adjusting a first timing of the least squares channel estimate based on at least the estimated timing offset, thereby generating a second signal with an adjusted timing. In some embodiments, the computer-readable medium includes instructions executable by the controller of the system to further cause the system to perform operations including removing a second OCC sequence from the second signal, thereby generating a third signal. In some embodiments, the computer-readable medium includes instructions executable by the controller of the system to further cause the system to perform operations including determining a channel estimate of the channel based on the third signal. In some embodiments, the computer-readable medium includes instructions executable by the controller of the system to further cause the system to perform operations including determining a first noise power of the first received signal based on at least the channel estimate, the first received signal or the DMRS symbol sequence. In some embodiments, the computer-readable medium includes instructions executable by the controller of the system to further cause the system to perform operations including determining a first signal power of the first received signal based on at least the channel estimate. In some embodiments, the computer-readable medium includes instructions executable by the controller of the system to further cause the system to perform operations including determining a signal to noise ratio (SNR) of the first received signal based on the first noise power and the first signal power. In some embodiments, the computer-readable medium includes instructions executable by the controller of the system to further cause the system to perform operations including determining an adjusted data rate of the

channel based on the SNR. In some embodiments, the computer-readable medium includes instructions executable by the controller of the system to further cause the system to perform operations including sending a signal based on the adjusted data rate of the channel, the signal instructing a device to adjust a data rate to the adjusted data rate.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Aspects of the present disclosure are best understood from the following detailed description when read with the accompanying figures. It is noted that, in accordance with the standard practice in the industry, various features are not drawn to scale. In fact, the dimensions of the various features may be arbitrarily increased or reduced for clarity of discussion.
- (2) FIG. 1 is a block diagram of a mobile network, in accordance with some embodiments.
- (3) FIG. 2 is a flowchart of a method of operating a system, in accordance with some embodiments.
- (4) FIG. 3 is a flowchart of a method of operating a system, in accordance with some embodiments.
- (5) FIG. 4 is a schematic view of a system, in accordance with some embodiments.

DETAILED DESCRIPTION

(6) The following disclosure provides different embodiments, or examples, for implementing features of the provided subject matter. Specific examples of components, materials, values, steps, arrangements, or the like, are described below to simplify the present disclosure. These are, of course, merely examples and are not limiting. Other components, materials, values, steps, arrangements, or the like, are contemplated. For example, the formation of a first feature over or on a second feature in the description that follows may include embodiments in which the first and second features are formed in direct contact, and may also include embodiments in which additional features may be formed between the first and second features, such that the first and second features may not be in direct contact. In addition, the present disclosure may repeat reference numerals and/or letters in the various examples. This repetition is for the purpose of simplicity and clarity and does not in itself dictate a relationship between the various embodiments and/or configurations discussed.

(7) Further, spatially relative terms, such as “beneath,” “below,” “lower,” “above,” “upper” and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. The spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. The apparatus may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein may likewise be interpreted accordingly.

(8) Terms “system” and “network” in embodiments of this application are used interchangeably. “At least one” means one or more, and “a plurality of” means two or more. The term “and/or” describes an association relationship between associated objects and indicates that three relationships exist. For example, A and/or B indicate the following cases: Only A exists, both A and B exist, and only B exists, where A and B is singular or plural. The character “/” generally indicates an “or” relationship between the associated objects. “At least one of” or a similar expression thereof means any combination of items, including any combination of singular items (pieces) or plural items (pieces). For example, “at least one of A, B, and C” includes A, B, C, AB, AC, BC, or ABC, and “at least one of A, B, or C” includes A, B, C, A and B, A and C, B and C, or A and B and C.

(9) FIG. 1 is a block diagram of a mobile network **100**, in accordance with some embodiments.

(10) In FIG. 1, a mobile telecommunication network couples User Equipment (UE) **110** through Radio Access Network (RAN) **120** to a Core Network (CN) **150**. RAN **120** connects individual

devices, such as UE **110** to other parts of a network, e.g., CN **150**, through radio connections. RAN **120** is responsible for managing radio resources, including strategies and algorithms for controlling power, channel allocation and data rate.

(11) RANs **120** have evolved over time, from 3G to 5G. For example, RANs **120** are implemented in various configurations, such as Global System for Mobile Communications (GSM) RAN (GRAN), GSM Enhanced Data Rates for GSM Evolution (EDGE) RAN (GERAN), Universal Mobile Telecommunications Service (UMTS) Terrestrial RAN (UTRAN), Evolved UMTS Terrestrial RAN (E-UTRAN), Centralized/Cloud RAN (CRAN), Virtualized RAN (VRAN), and Open RAN (ORAN).

(12) In some embodiments, RAN **120** includes one or more of 3G network **121**, 4G network **132** or 5G network **140**.

(13) In a 3G network **121**, RAN **120** includes the base station for Cell Sites **122**, **123**, which is called a Node B (NB) **124**, **125**, and a Radio Network Controller (RNC) **126**. RNC **126** controls and manages the radio transceivers in Node Bs **124**, **125**, as well as manages operational functions, such as handoffs, and the radio channels. The RNC **126** handles communication with the 3G Core Network **152**.

(14) In a 4G network **132**, Cell Sites **130**, **131** are implemented using Evolved Node Bs (eNodeBs or eNBs) **134**, **135** for the radio base station. The eNodeBs **134**, **135** are able to perform the radio access functions that are equivalent to the combined work that Node Bs **124**, **125** and RNC perform in 3G and connect to the Evolved Packet Core **154**.

(15) In a 5G network **140**, Cell Sites **141**, **142** are implemented using one of two types of RANs: Next Generation Node B (gNodeB) **144** and Next Generation Evolved Node B (ng-eNB) **146**. The ng-eNB **146** is an enhanced version of 4G eNodeB and connects 5G UE **110** to the 5G Core Network (5GC) **156** using 4G LTE air interface. The gNB **144** allows 5G UE **110** to connect with a 5GC **156** using 5G NR air interface. The gNBs **144** and ng-eNBs **146** are interconnected by means of the Xn interface. The gNBs **144** and ng-eNBs **146** are also connected by means of the NG interfaces to the 5GC **156**.

(16) In 5G, for example, an Open RAN environment is able to be implemented wherein the RAN **120**, provided by the gNBs **144** and ng-eNBs **146**, is separated into the Radio Unit (RU) **147**, the Distributed Unit (DU) **148**, and the Centralized Unit (CU) **149**. The RU **147** is where the radio frequency signals are transmitted, received, amplified, and digitized. The RU **147** is located near or integrated into, the antenna. The DU **148** and CU **149** are the computation parts of the base station, sending the digitalized radio signal into the network. The DU **148** is physically located at or near the RU **147** whereas the CU **149** is often located near the Core Network **150**. The different interfaces associated with the Open RAN **120** include the Fronthaul (FH) that lies between the RU **147** and the DU **148**, the Midhaul (MH) that lies between the DU **148** and the CU **149**, and the Backhaul (BH) that lies between the CU **149** and the Core Network **150**.

(17) Core Network (CN) **150** connects RAN **120** to networks **160**, such as a Public Landline Mobile Network (PLMN), a Public Switched Telephone Network (PSTN) and a Packet Data Network (PDN). CN **150** provides high-level traffic aggregation, routing, call control/switching, user authentication and charging. The 3G CN **152** involves two different domains: circuit switched elements and packet switched elements. The 4G Evolved Packet Core (EPC) **154** includes four main network elements: the Serving Gateway (S-GW), the packet data network (PDN) Gateway (P-GW), the mobility management entity (MME), and the Home Subscriber Server (HSS). The S-GW routes and forwards data packets from the UE and acts as the mobility anchor during inter-eNodeB handovers. The P-GW acts as an ingress and egress point to the EPC from a PDN (Packet Data Network) such as the Internet. The MME manages UE access network and mobility, as well as establishing the bearer path for User Equipment (UE). The MME is also concerned with the bearer activation/deactivation process. The HSS is the master database for a given subscriber, acting as a central repository of information for network nodes. Subscriber related information held by the

HSS includes user identification, security, location, and subscription profile. The EPC is connected to the external networks, which includes the IP Multimedia Core Network Subsystem (IMS). 5GC **156** supports new network functions (NFs) associated with the packet core and user data management domains. 5GC **156** provides a decomposed network architecture with the introduction of a service-based interface (SBI), and control plane and user plane separation (CUPS). 5GC decomposes the 4G MME into an Access and Mobility Management Function (AMF) and a Session Management Function (SMF). The AMF receives connection and session related information from the UE, but is responsible for handling connection and mobility management tasks. Messages related to session management are forwarded to the SMF.

(18) The mobile network **100** is managed by the network management system (NMS) **170**, which provides several network management functionalities. According to at least one embodiment, the NMS **170** provides a customer care representative the real-time network experiences of one or more customers. For example, in some embodiments, the NMS **170** provides the customer care representative FM information, PM information, cell site coverage information, cell site information and NW data of the customer.

(19) There is a maximum number of users that may be accommodated by the mobile network **100** before either the quality or performance of the mobile network **100** is negatively impacted. The carrying capacity of a mobile network **100** is the total amount of data or voice traffic that a cell site, e.g., Cell Sites **122, 123, 130, 131, 141, 142**, of the mobile network **100** is able to transfer to and from customers. Wireless data are carried by modulating radio waves. The quantity of waves (or amount of spectrum) a wireless system is allowed to modulate each second is called its bandwidth, and is measured in hertz (Hz). In some embodiments, a signal with a higher bandwidth (i.e., more Hz) can carry more data per second than a signal of lower bandwidth (i.e., less Hz). The total amount of data that a cell site transfers over a given period of time relates to the rate at which Cell Sites **122, 123, 130, 131, 141, 142** transfer data bytes. In some embodiments, a faster cell site will transfer more bytes than a slower cell site. Rates of data transfer are measured in terms of bits per second (bps).

(20) As the number of users increases, so does the amount of traffic that occurs in a given period of time. As a consequence, Cell Sites **122, 123, 130, 131, 141, 142** progressively become more and more congested. As a result, the channels of Cell Sites **122, 123, 130, 131, 141, 142** will continue to diminish.

(21) According to at least one embodiment, the UE **110** can adjust a data rate of an uplink signal sent, by the UE **110**, to the RAN **120**.

(22) One or more embodiments are applicable to PUSCH DMRS signal generation and mapping to physical resources, as described in the 3.sup.rd Generation Partnership Project (3GPP), at the following sections: Technical Specification (TS) 38.211, at 6.4.1.1 Demodulation reference signal for PUSCH.

(23) FIG. 2 is a flowchart of a method **200** of operating a system, in accordance with some embodiments.

(24) In some embodiments, method **200** includes a series of steps or operations (e.g., **201-203**) performed by system **100** or **400**. In some embodiments, method **300** is a method of estimating a robust signal to noise (SNR) ratio that avoids SNR saturation at higher operating signal levels.

(25) In some embodiments, FIG. 2 is a flowchart of a method **200** of operating system **100** of FIG. 1 or system **400** of FIG. 4, and similar detailed description is therefore omitted. It is understood that additional operations may be performed before, during, and/or after the method **200** depicted in FIG. 2, and that some other operations may only be briefly described herein. In some embodiments, other order of operations of method **200** is within the scope of the present disclosure. In some embodiments, one or more operations of method **200** are not performed.

(26) Method **200** includes exemplary operations, but the operations are not necessarily performed in the order shown. Operations may be added, replaced, changed order, and/or eliminated as

appropriate, in accordance with the spirit and scope of disclosed embodiments. It is understood that method **200** utilizes features of one or more of system **100** or **400** or method **300**.

(27) In some embodiments, one or more or all operations of method **200** are performed by at least one processor **401**, a user equipment corresponding to the UE **110**, and/or a network device corresponding to a base station or a RAN **120**.

(28) At operation **201** of method **200**, a user equipment (e.g., UE **110**) receives at least one signal **190** from a network device over a channel **191a**. For example, the received signal is received by an antenna, such as antenna **406** and corresponding receiver circuitry **408** of the user equipment, in accordance with some embodiments. In some embodiments, the user equipment (e.g., UE **110**) receives the at least one signal from the network device, such as RAN **120**, over a Physical Uplink Shared Channel (PUSCH). Other channel types are within the scope of the present disclosure.

(29) In some embodiments, operation **201** is performed by at least receiver circuitry **408**.

(30) At operation **202** of method **200**, a processor **401** of the UE **110**, which is coupled to the receiver circuitry **408**, performs processing on the received signal to obtain decoded data from the network device (e.g., RAN **120**). In some embodiments, operation **202** includes one or more of operations **301-311** of FIG. **3**.

(31) At operation **203** of method **200**, the processor **401** is configured to utilize the decoded data for handling further communications with the network device, for example, as described with respect to one or more of operations **310** or **311** of method **300** (FIG. **3**).

(32) In some embodiments, operation **203** includes transmitting an output signal **392** by a transmitter on a channel **193a**. In some embodiments, the output signal **392** has an adjusted data rate. In some embodiments, operation **203** is performed by at least transmitter circuitry **409**.

(33) In some embodiments, operation **203** includes at least one of operation **310**, operation **311** or operation **312**.

(34) In at least one embodiment, one or more advantages described herein are achievable by the method **200**.

(35) The described methods and algorithms include example operations, but they are not necessarily required to be performed in the order shown. Operations may be added, replaced, changed order, and/or eliminated as appropriate, in accordance with the spirit and scope of embodiments of the disclosure. Embodiments that combine different features and/or different embodiments are within the scope of the disclosure and will be apparent to those of ordinary skill in the art after reviewing this disclosure.

(36) FIG. **3** is a flowchart of a method **300** of operating a system, in accordance with some embodiments.

(37) Method **300** is an embodiment of at least operations **201**, **202** or **203** of method **200** of FIG. **2**, and similar detailed description is therefore omitted. For example, in some embodiments, method **300** is a method of estimating a robust signal to noise (SNR) ratio that avoids SNR saturation at higher operating signal levels.

(38) In some embodiments, one or more of operations **301-312** is an embodiment of one or more of operations **201-203** of method **200**, and similar detailed description is therefore omitted. In some embodiments, at least one of operation **301**, **302**, **303**, **304**, **305**, **306**, **307**, **308**, **309** or **310** is an embodiment of operation **202** of method **200**, and similar detailed description is therefore omitted. In some embodiments, at least one of operation **309** or **310** is an embodiment of operation **203** of method **200**, and similar detailed description is therefore omitted.

(39) In some embodiments, method **300** includes a series of steps or operations (e.g., **301-312**) performed by system **100** or **400**.

(40) In some embodiments, FIG. **3** is a flowchart of a method **300** of operating system **100** of FIG. **1** or system **400** of FIG. **4**, and similar detailed description is therefore omitted. It is understood that additional operations may be performed before, during, and/or after the method **300** depicted in FIG. **3**, and that some other operations may only be briefly described herein. In some embodiments,

other order of operations of method **300** is within the scope of the present disclosure. In some embodiments, one or more operations of method **300** are not performed.

(41) Method **300** includes exemplary operations, but the operations are not necessarily performed in the order shown. Operations may be added, replaced, changed order, and/or eliminated as appropriate, in accordance with the spirit and scope of disclosed embodiments. It is understood that method **300** utilizes features of one or more of system **100** or **400** or method **200**.

(42) In some embodiments, one or more or all operations of method **300** are performed by at least one processor **401**, a user equipment corresponding to the UE **110**, and/or a network device corresponding to a base station or a RAN **120**.

(43) In operation **301** of method **300**, a least squares channel estimate $H_{\text{sub.LS}}$ of a channel is determined. In some embodiments, the channel of method **300** includes channel **191a** or channel **193a**. In some embodiments, operation **301** is performed by the processor **401** of system **400**.

(44) In some embodiments, the channel is configured to receive a first received signal $Y_{\text{sub.DMRS}}$. In some embodiments, the channel is a PUSCH channel, and the first received signal $Y_{\text{sub.DMRS}}$ is a signal received over the PUSCH channel. In some embodiments, the first received signal $Y_{\text{sub.DMRS}}$ is a Cyclic Prefix (CP)-OFDM waveform or a Discrete Fourier Transform Spread OFDM (DFT-s-OFDM) waveform.

(45) In some embodiments, the first received signal $Y_{\text{sub.DMRS}}$ includes a demodulation reference signal (DMRS) symbol sequence $X_{\text{sub.DMRS}}$, a number of DMRS symbols l , and a number of subcarriers k . In some embodiments, the DMRS symbol sequence $X_{\text{sub.DMRS}}$ includes a Zadoff-Chu sequence in Discrete Fourier Transform (DFT) Orthogonal Frequency Multiplexing (OFDM). In some embodiments, Zadoff-Chu sequence includes orthogonal sequences that are generated with different cyclic shifts for a group number and sequence number.

(46) In some embodiments, operation **301** includes determining the least squares channel estimate $H_{\text{sub.LS}}(k, l)$ of the channel by Equation 1, as follows:

(47) $H_{\text{LS}}(k, l) = Y_{\text{DMRS}}(k, l) * \text{conj}(x_{\text{DMRS}}(k, l))$, (Equation1) where $k=1, 2, \dots$, number of subcarriers; and $l=1, 2, 3, \dots$, number of DMRS symbols.

(48) $H_{\text{sub.LS}}(k, l)$ is the least squares channel estimate of the channel for index k and index l , k is an integer corresponding to a number of subcarriers, l is an integer corresponding to the number of DMRS symbols, $Y_{\text{sub.DMRS}}$ is the first received signal, and $X_{\text{sub.DMRS}}$ is the DMRS symbol sequence.

(49) In some embodiments, equation 1 is determined for each subcarrier index value and for each DMRS symbol value. For brevity, the least squares channel estimate $H_{\text{sub.LS}}(k, l)$ of the channel is abbreviated as “the least squares channel estimate $H_{\text{sub.LS}}$ of the channel.”

(50) In operation **302** of method **300**, a first Orthogonal cover code (OCC) sequence is removed from the least squares channel estimate $H_{\text{sub.LS}}$, thereby generating a first signal $H_{\text{sub.deOCC1}}(k, l)$. In some embodiments, the first signal $H_{\text{sub.deOCC1}}(k, l)$ corresponds to the least squares channel estimate $H_{\text{sub.LS}}$ with the first OCC sequence removed. In some embodiments, operation **302** is performed by processor **401**.

(51) In some embodiments, operation **302** includes removing the first OCC sequence from the least squares channel estimate $H_{\text{sub.LS}}$, thereby generating the first signal $H_{\text{sub.deOCC1}}(k, l)$ by Equation 2 as follows:

(52) $H_{\text{deOCC1}}(k, l) = \text{fn1}(H_{\text{LS}}(k, l))$ (Equation2) where $k=1, 2, \dots$, number of subcarriers; and $l=1, 2, 3, \dots$, number of DMRS symbols.

(53) $H_{\text{sub.deOCC1}}(k, l)$ is the first signal, and fn1 is a first deOCC function.

(54) In some embodiments, the first deOCC function fn1 is configured to filter pairs of values of a first input vector (e.g., the first signal $H_{\text{sub.deOCC1}}(k, l)$) with a configured first OCC code. In some embodiments, the configured first OCC code includes at least one of OCC code $[1,1]$ or $[1,-1]$. Other expressions for the first configured OCC code is within the scope of the present

disclosure. Other equations for the first deOCC function fn1 is within the scope of the present disclosure.

(55) In some embodiments, equation 2 is determined for each subcarrier index value and for each DMRS symbol value. For brevity, the first signal H.sub.deOCC1(k, l) is abbreviated as “first signal H.sub.deOCC1.”

(56) In operation **303** of method **300**, at least an estimated timing offset Ω of the first signal H.sub.deOCC1 is determined. In some embodiments, operation **303** corresponds to determining the estimated timing offset Ω of the first signal H.sub.deOCC1 with the first OCC sequence removed.

(57) In some embodiments, operation **303** is performed by processor **401**.

(58) In some embodiments, operation **303** includes determining at least the estimated timing offset Ω of the first signal H.sub.deOCC1 by Equation 3 as follows:

$$(59) \quad = \tan^{-1} \left(\frac{\text{imag}(TA_{\text{metric}})}{\text{real}(TA_{\text{metric}})} \right) \quad (\text{Equation 3})$$

(60) Ω is the estimated timing offset of the first signal H.sub.deOCC1, and TA.sub.metric is a timing advance. In some embodiments, Ω is expressed in radians. In some embodiments the timing advance TA.sub.metric is the timing advance or the time difference between the expected time of arrival and actual time of arrival of signals at the gNB receiver antenna. In some embodiments the timing advance TA.sub.metric is expressed in microseconds. Other units for the timing advance TA.sub.metric is within the scope of the present disclosure.

(61) The timing advance TA.sub.metric is determined according to Equation 4. In some embodiments, operation **303** further includes determining the timing advance TA.sub.metric, by Equation 4 as follows:

$$(62) \quad TA_{\text{metric}} = E[H_{\text{deOCC1}}(k, l) * \text{conj}(H_{\text{deOCC1}}(k + u, l))] \quad (\text{Equation 4}) \quad \text{where } k=1, 2, \dots, \text{ number of subcarriers; and } l=1, 2, 3, \dots, \text{ number of DMRS symbols.}$$

(63) $E[H_{\text{deOCC1}}(k, l) * \text{conj}(H_{\text{deOCC1}}(k + u, l))]$ is the expected value of the product of the first signal H.sub.deOCC1 and the conjugate (e.g., “conj”) of a first intermediary value H.sub.deOCC1(k+u, l), u is an integer and is a fixed offset, and the first intermediary value H.sub.deOCC1(k+u, l) is a version of the first signal H.sub.deOCC1 shifted by the fixed offset u. In some embodiments, the conjugate multiplication expressed by equation 4 is between an estimated channel (e.g., $E[H_{\text{deOCC1}}(k, l)]$) on a given sub-carrier (e.g., k) and an estimated channel (e.g., $E[H_{\text{deOCC1}}(k + u, l)]$) of another sub-carrier (e.g., k+u) that is u subcarriers away.

(64) In some embodiments, equations 3 and 4 are determined for each subcarrier index value and for each DMRS symbol value.

(65) In operation **304** of method **300**, a first timing of the least squares channel estimate H.sub.LS is adjusted based on at least the estimated timing offset Ω , thereby generating a second signal EstH.sub.LS(k, l). In some embodiments, the second signal EstH.sub.LS(k, l) has an adjusted timing

$$(66) \quad e^{-j \frac{\Omega}{u * (\text{FFT_Size})}}.$$

(67) In some embodiments, operation **304** corresponds to compensating for the estimated timing offset Ω on the least squares channel estimate H.sub.LS.

(68) In some embodiments, operation **304** is performed by processor **401**.

(69) In some embodiments, operation **304** includes adjusting the first timing of the least squares channel estimate H.sub.LS based on at least the estimated timing offset Ω , thereby generating the second signal EstH.sub.LS(k, l) by Equation 5 as follows:

$$(70) \quad \text{EstH}_{\text{LS}}(k, l) = H_{\text{LS}}(k, l) * e^{-j \frac{\Omega}{u * (\text{FFT_Size})}} \quad (\text{Equation 5}) \quad \text{where } k=1, 2, \dots, \text{ number of subcarriers; and } l=1, 2, 3, \dots, \text{ number of DMRS symbols.}$$

(71) EstH.sub.LS(k, l) is the second signal, H.sub.LS is the least squares channel estimate of the channel,

$$(72) \quad e^{-j \frac{\Omega}{u * (\text{FFT_Size})}}$$

is the adjusted timing of the second signal $\text{EstH.sub.LS}(k, l)$, and FFT_Size is a size of a fast Fourier transform (FFT).

(73) In some embodiments, the FFT size FFT_Size corresponds to a size of the FFT that is performed on a received time domain signal. In some embodiments, the FFT is used to determine a frequency domain grid of the received time domain signal. In some embodiments, the received time domain signal is the received signal that is received by an antenna, such as antenna **406** and corresponding receiver circuitry **408** of the user equipment, in accordance with some embodiments. In some embodiments, the user equipment (e.g., UE **110**) receives the received time domain signal from the network device, such as RAN **120**, over a Physical Uplink Shared Channel (PUSCH). Other channel types are within the scope of the present disclosure. In some embodiments, the FFT size FFT_Size ranges from about 512 to about 4096. Other values for the FFT size FFT_Size are within the scope of the present disclosure.

(74) In some embodiments, equation 5 is determined for each subcarrier index value and for each DMRS symbol value. For brevity, the second signal $\text{EstH.sub.LS}(k, l)$ is abbreviated as “the second signal EstH.sub.LS .”

(75) In operation **305** of method **300**, a second OCC sequence is removed from the second signal EstH.sub.LS , thereby generating a third signal $\text{H.sub.deOCC2}(k, l)$. In some embodiments, the third signal $\text{H.sub.deOCC2}(k, l)$ corresponds to the second signal EstH.sub.LS with the second OCC sequence removed. In some embodiments, the second OCC sequence is the same as the first OCC sequence. In some embodiments, the second OCC sequence is different from the first OCC sequence.

(76) In some embodiments, operation **305** is performed by processor **401**.

(77) In some embodiments, operation **305** includes removing the second OCC sequence from the second signal EstH.sub.LS , thereby generating the third signal $\text{H.sub.deOCC2}(k, l)$ by Equation 6 as follows:

(78) $H_{\text{deOCC2}}(k, l) = \text{fn2}(\text{EstH}_{\text{LS}}(k, l))$ (Equation6) where $k=1, 2, \dots$, number of subcarriers; and $l=1, 2, 3, \dots$, number of DMRS symbols. $\text{H.sub.deOCC2}(k, l)$ is the third signal, and fn2 is a second deOCC function.

(79) In some embodiments, the second deOCC function fn2 is configured to filter pairs of values of a second input vector (e.g., the second signal $\text{EstH.sub.LS}(k, l)$) with a configured second OCC code. In some embodiments, the second configured OCC code includes at least one of OCC code $[1,1]$ or $[1,-1]$. Other expressions for the second configured OCC code is within the scope of the present disclosure. Other equations for the second deOCC function fn2 is within the scope of the present disclosure.

(80) In some embodiments, equation 6 is determined for each subcarrier index value and for each DMRS symbol value. For brevity, the third signal $\text{H.sub.deOCC2}(k, l)$ is abbreviated as “the third signal H.sub.deOCC2 .”

(81) In operation **306** of method **300**, a channel estimate $\text{H.sub.EST}(k, l)$ of the channel is determined based on the third signal H.sub.deOCC2 . In some embodiments, operation **306** is performed by processor **401**.

(82) In some embodiments, operation **306** includes determining the channel estimate $\text{H.sub.EST}(k, l)$ of the channel based on the third signal H.sub.deOCC2 by Equation 7A as follows:

(83) $H_{\text{Est}}(k, l) = \text{fn3}(H_{\text{deOCC2}}(k, l))$ (Equation7A) where $k=1, 2, \dots$, number of subcarriers; and $l=1, 2, 3, \dots$, number of DMRS symbols. $\text{H.sub.EST}(k, l)$ is the channel estimate, and fn3 is a channel estimate function.

(84) In some embodiments, the channel estimate function fn3 is expressed by equation 7B as follows:

(85) $0 \text{ fn3}(H_{\text{deOCC2}}(k, l) = \text{mean}(H_{\text{deOCC2}}(k, l))$ (Equation7B) where $k=1, 2, \dots$, number of subcarriers; and $l=1, 2, 3, \dots$, number of DMRS symbols.

- (86) In some embodiments, mean ($H_{\text{sub.deOcc2}}(k, l)$) is the mean of the third signal $H_{\text{sub.deOCC2}}$, and is equal to the channel estimate function fn3 . Other equations for determining the channel estimate function fn3 are within the scope of the present disclosure.
- (87) In some embodiments, equation 7A is determined for each subcarrier index value and for each DMRS symbol value. For brevity, the channel estimate $H_{\text{sub.EST}}(k, l)$ is abbreviated as “the channel estimate $H_{\text{sub.EST}}$.”
- (88) In operation **307** of method **300**, a first noise power NP of the first received signal $Y_{\text{sub.DMRS}}$ is determined based on at least one of the channel estimate $H_{\text{sub.EST}}$, the first received signal $Y_{\text{sub.DMRS}}$ or the DMRS symbol sequence $X_{\text{sub.DMRS}}$.
- (89) In some embodiments, operation **307** is performed by processor **401**.
- (90) In some embodiments, operation **307** includes determining the first noise power NP of the first received signal $Y_{\text{sub.DMRS}}$ based on Equations 8 and 9 as follows:
- (91)
$$\text{NP} = \frac{1}{\text{numDMRS}} \sum_{l=1}^{\text{numDMRS}} \frac{1}{\text{numSC}} \sum_{k=1}^{\text{numSC}} N(k, l) * \text{conj}(N(k, l)) \quad (\text{Equation 8})$$
 where $k=1, 2, \dots$, number of subcarriers; and $l=1, 2, 3, \dots$, number of DMRS symbols.
- (92) NP is the first noise power of the first received signal $Y_{\text{sub.DMRS}}$, $N(k, l)$ is a second intermediary value, and $\text{conj}(N(k, l))$ is the conjugate of the second intermediary value $N(k, l)$.
- (93) The second intermediary value $N(k, l)$ is determined according to Equation 9. In some embodiments, operation **307** further includes determining the second intermediary value $N(k, l)$ by Equation 9 as follows:
- (94)
$$N(k, l) = Y_{\text{sub.DMRS}}(k, l) - H_{\text{Est}}(k, l) * x_{\text{sub.DMRS}}(k) \quad (\text{Equation 9})$$
 where $k=1, 2, \dots$, number of subcarriers; and $l=1, 2, 3, \dots$, number of DMRS symbols. $N(k, l)$ is the second intermediary value, $Y_{\text{sub.DMRS}}(k, l)$ is the first received signal, $x_{\text{sub.DMRS}}(k)$ is the DMRS symbol sequence of the k th subcarrier, and $H_{\text{sub.EST}}(k, l)$ is the channel estimate of the channel.
- (95) In some embodiments, equations 8 and 9 are determined for each subcarrier index value and for each DMRS symbol value. For brevity, the second intermediary value $N(k, l)$ is abbreviated as “the second intermediary value N.”
- (96) In operation **308** of method **300**, a first signal power SP of the first received signal $Y_{\text{sub.DMRS}}$ is determined based on at least the channel estimate $H_{\text{sub.EST}}$. In some embodiments, operation **308** is performed by processor **401**.
- (97) In some embodiments, operation **308** includes determining the first signal power SP of the first received signal $Y_{\text{sub.DMRS}}$ based on Equation 10 as follows:
- (98)
$$\text{SP} = \frac{1}{\text{numDMRS}} \sum_{l=1}^{\text{numDMRS}} \frac{1}{\text{numSC}} \sum_{k=1}^{\text{numSC}} H_{\text{Est}}(k, l) * \text{conj}(H_{\text{Est}}(k, l)) \quad (\text{Equation 10})$$
 where $k=1, 2, \dots$, number of subcarriers; and $l=1, 2, 3, \dots$, number of DMRS symbols. SP is the first signal power of the first received signal $Y_{\text{sub.DMRS}}$, numDMRS corresponds to the number of DMRS symbols I, numSC corresponds to the number of subcarriers k, $H_{\text{sub.EST}}(k, l)$ is the channel estimate of the channel, and $\text{conj}(H_{\text{sub.EST}}(k, l))$ is the conjugate of the channel estimate $H_{\text{sub.EST}}(k, l)$ of the channel.
- (99) In operation **309** of method **300**, a signal to noise ratio SNR1 of the first received signal $Y_{\text{sub.DMRS}}$ is determined based on the first noise power NP and the first signal power SP. In some embodiments, operation **309** is performed by processor **401**.
- (100) In some embodiments, operation **309** includes determining the signal to noise ratio (SNR) of the first received signal $Y_{\text{sub.DMRS}}$ based on Equation 11 as follows:
- (101)
$$\text{SNR1} = \text{SP} / \text{NP} \quad (\text{Equation 11})$$
- (102) SNR1 is the SNR of the first received signal $Y_{\text{sub.DMRS}}$, SP is the first signal power of the first received signal $Y_{\text{sub.DMRS}}$, and NP is the first noise power of the first received signal $Y_{\text{sub.DMRS}}$.
- (103) In operation **310** of method **300**, an adjusted data rate of the channel is determined based on the SNR, and a command is sent to adjust the data rate. In some embodiments, operation **310** is

performed by processor **401** or transceiver **405**.

(104) In some embodiments, operation **310** includes determining, by the base station, to adjust the data rate of the channel on the SNR, and sending a command to the UE **110** to adjust the data rate. In some embodiments, if the SNR is greater than an estimated SNR, then in operation **310**, the base station determines that the data rate of the channel can be increased in accordance with the upper limit of the channel capacity of the channel based on the Shannon-Hartley channel capacity theorem, and sends a command to the UE **110** to adjust the data rate to the adjusted data rate. For example, in some embodiments, the data rate can be adjusted in increments of 1-2% until the upper limit of the channel capacity based on the Shannon-Hartley channel capacity theorem is reached. Other increments are within the scope of the present disclosure. In some embodiments, if the SNR is less than the estimated SNR, then in operation **310**, the base station determines that the data rate of the channel can be decreased to be lower than the upper limit of the channel capacity of the channel based on the Shannon-Hartley channel capacity theorem, and sends the command to the UE **110** to adjust the data rate to the adjusted data rate. For example, in some embodiments, the data rate can be adjusted in decrements of 1-2% until the upper limit of the channel capacity based on the Shannon-Hartley channel capacity theorem is reached. Other decrements are within the scope of the present disclosure.

(105) In operation **311** of method **300**, a data rate of the channel is adjusted based on the command. In some embodiments, operation **311** is performed by a processor **401** of the UE **110**.

(106) In some embodiments, operation **311** includes the UE **110** receiving the command from the base station to adjust the data rate to the adjusted data rate, and the UE **110** adjusts the data rate of the channel based on the command.

(107) In operation **312** of method **300**, an output signal is transmitted based on an adjusted data rate of the channel. In some embodiments, operation **312** includes a transmitter circuitry **409** of the transmitter of the UE **110** transmitting the output signal based on the adjusted data rate of the channel. In some embodiments, operation **312** is performed by transceiver **405**.

(108) In some embodiments, operation **312** includes transmitting, by the UE **110**, the output signal to the base station based on the adjusted data rate of the channel.

(109) While method **300** is described in operations **310-312** with respect to adjusting the data rate of the channel based on the SNR, method **300** is also applicable to adjusting other parameters of system **100** or **400**, in accordance with some embodiments. For example, in some embodiments, a throughput of the channel is determined to be increased or decreased based on the SNR. Other parameters are within the scope of the present disclosure.

(110) In some embodiments, one or more of operations **301-312** are performed by a base station, and one or more of operations are performed by the UE **110**. In some embodiments, one or more of operations **301-312** are performed by the UE **110**, and one or more of operations are performed by a base station.

(111) In some embodiments, one or more of the operations of methods **200** or **300** is not performed.

(112) By utilizing method **300**, one or more elements of system **100** or **400** is configured to achieve the benefits discussed within the present disclosure. For example, as shown in FIG. 3, method **300** utilizes a two-step OCC removal in operations **302** and **305**, and further utilizes a timing compensation, in operation **304**, that is performed on a least squares estimate of a channel that reduces the likelihood of saturated SNR results, thereby significantly enhancing the robustness of the estimated SNR at higher operating SNRs compared to other approaches. In some embodiments, by significantly enhancing the robustness of the estimated SNR results in better scheduling for the UE than other approaches.

(113) FIG. 4 is a block diagram of an example hardware configuration of equipment **400** in a communications system, in accordance with some embodiments.

(114) The equipment **400** is configurable to operate as user equipment **110** or a network device (e.g., base station), as described herein. The equipment **400** comprises a hardware processor **401**, a

non-transitory, computer-readable storage medium **402**, an input/output (I/O) interface **403**, network interface circuitry **404**, transceiver circuitry **405** with at least one antenna **406**, and a bus **407** which couples the processor **401**, the storage medium **402**, the I/O interface **403**, the network interface circuitry **404**, and the transceiver circuitry **405** together. In equipment where wireless communication is not configured, the transceiver circuitry **405** and the associated antenna **406** are omitted.

(115) The processor **401** is configured to execute non-transitory computer program codes encoded in the storage medium **402** in order to cause the equipment **400** to perform a portion or all of the described processes and/or methods. In one or more embodiments, the processor **401** comprises a central processing unit (CPU), a multi-processor, a distributed processing system, an application specific integrated circuit (ASIC), and/or a suitable processing unit.

(116) The storage medium **402**, amongst other things, is encoded with, i.e., stores, non-transitory computer program codes, i.e., a set of executable non-transitory instructions to be executed by the processor **401**, such as one or more algorithms, programs, applications for a system, component, equipment, and/or module, as described with respect to one or more of FIGS. **1-3**. Execution of the sets of non-transitory instructions by hardware processor **401** implements a portion or all of the processes and/or methods described herein in accordance with one or more embodiments (hereinafter, the noted processes and/or methods). In one or more embodiments, the storage medium **402** comprises an electronic, magnetic, optical, electromagnetic, infrared, and/or a semiconductor system (or apparatus or device). For example, the storage medium **402** includes a semiconductor or solid-state memory, a magnetic tape, a removable computer diskette, a random access memory (RAM), a read-only memory (ROM), a PROM, an EPROM, a FLASH-EPROM, an EEPROM, a flash memory, another memory chip or cartridge, or another medium from which a computer can read, a rigid magnetic disk, and/or an optical disk. In one or more embodiments using optical disks, the storage medium **402** includes a compact disk-read only memory (CD-ROM), a compact disk-read/write (CD-R/W), and/or a digital video disc (DVD).

(117) The I/O interface **403** includes an input device, an output device and/or a combined input/output device for enabling a user and/or external circuitry/equipment to interact with equipment **400**. An input device comprises, for example, a keyboard, keypad, mouse, trackball, trackpad, touchscreen, and/or cursor direction keys for communicating information and commands to the processor **401**. An output device comprises, for example, a display, a printer, a voice synthesizer, etc. for communicating information to a user.

(118) The network interface circuitry **404** is coupled to a network **410** so that the processor **401** and storage medium **402** are capable of connecting to other equipment via the network **410**. The network interface circuitry **404** includes wireless network interfaces such as OFDMA, CDMA, BLUETOOTH, WIFI, WIMAX, GPRS, WCDMA, LTE, 2G, 3G, 3.5G, 5G, 6G, or the like; or wired network interfaces such as ETHERNET, USB, IEEE-864, or the like. In one or more embodiments, a portion or all of noted processes and/or methods, is implemented in two or more equipment **400** connected over the network **410**.

(119) The transceiver circuitry **405** includes receiver circuitry **408** with an associated decoder, and transmitter circuitry **409** with an associated encoder. The receiver circuitry **408** and the transmitter circuitry **409** are coupled to the at least one antenna **406** to correspondingly receive and transmit data through the at least one antenna **406**. In some embodiments, the receiver circuitry **408** and the transmitter circuitry **409** are coupled to the same antenna. In one or more embodiments, the receiver circuitry **408** and the transmitter circuitry **409** are coupled to different antennas. The transceiver circuitry **405** is configured to receive and transmit data, using the at least one antenna **406** and the receiver circuitry **408** and/or transmitter circuitry **409**, over wireless communication under control of the processor **401**. In some embodiments, at least one of the receiver circuitry **408** or the transmitter circuitry **409** comprises one or more of integrated circuits, power amplifier circuitry, low-noise input amplifier circuitry, passive radio frequency (RF) components, other

circuitry for handling RF wireless signals, or the like.

(120) In some embodiments, a portion or all of the described processes and/or methods is implemented as a standalone software application for execution by a processor. In some embodiments, a portion or all of the described processes and/or methods is implemented as a software application that is a part of an additional software application. In some embodiments, a portion or all of the described processes and/or methods is implemented as a plug-in to a software application.

(121) In some embodiments, a portion or all of the noted processes and/or methods is realized as functions of a program stored in a non-transitory computer readable recording medium. The non-transitory computer readable recording medium having the program stored therein is a computer program product. Examples of a non-transitory computer-readable recording medium include, but are not limited to, external/removable and/or internal/built-in storage or memory unit, e.g., one or more of an optical disk, such as a DVD, a magnetic disk, such as a hard disk, a semiconductor memory, such as a ROM, a RAM, a PROM, an EPROM, a FLASH-EPROM, an EEPROM, a flash memory, another memory chip or cartridge, or another medium from which a computer can read, a memory card, or the like.

(122) It will be readily seen by one of ordinary skill in the art that one or more of the disclosed embodiments fulfill one or more of the advantages set forth above. After reading the foregoing specification, one of ordinary skill will be able to affect various changes, substitutions of equivalents and various other embodiments as broadly disclosed herein. It is therefore intended that the protection granted hereon be limited only by the definition contained in the appended claims and equivalents thereof.

(123) One aspect of this description relates to a method. In some embodiments, the method includes determining, by a processor of a receiver, a least squares channel estimate of a channel, the channel being configured to receive a first received signal, the first received signal including a demodulation reference signal (DMRS) symbol sequence, a number of DMRS symbols, and a number of subcarriers. In some embodiments, the method further includes removing, by the processor, a first Orthogonal cover code (OCC) sequence from the least squares channel estimate, thereby generating a first signal. In some embodiments, the method further includes determining, by the processor, at least an estimated timing offset of the first signal. In some embodiments, the method further includes adjusting, by the processor, a first timing of the least squares channel estimate based on at least the estimated timing offset, thereby generating a second signal with an adjusted timing. In some embodiments, the method further includes removing, by the processor, a second OCC sequence from the second signal, thereby generating a third signal. In some embodiments, the method further includes determining, by the processor, a channel estimate of the channel based on the third signal. In some embodiments, the method further includes determining, by the processor, a first noise power of the first received signal based on at least the channel estimate, the first received signal or the DMRS symbol sequence. In some embodiments, the method further includes determining, by the processor, a first signal power of the first received signal based on at least the channel estimate. In some embodiments, the method further includes determining, by the processor, a signal to noise ratio of the first received signal based on the first noise power and the first signal power. In some embodiments, the method further includes adjusting a data rate of the channel based on the SNR. In some embodiments, the method further includes transmitting, by a transmitter, an output signal based on an adjusted data rate of the channel based on the SNR.

(124) In some embodiments, the determining the least squares channel estimate of the channel includes determining the least squares channel estimate of the channel by Equation 1.

(125) In some embodiments, removing the first OCC sequence from the least squares channel estimate, thereby generating the first signal includes removing the first OCC sequence from the least squares channel estimate, thereby generating the first signal by Equation 2.

(126) In some embodiments, determining at least the estimated timing offset of the first signal includes determining at least the estimated timing offset of the first signal by Equation 3, and a timing advance is determined by Equation 4.

(127) In some embodiments, adjusting the first timing of the least squares channel estimate based on at least the estimated timing offset, thereby generating the second signal with the adjusted timing includes adjusting the first timing of the least squares channel estimate based on at least the estimated timing offset, thereby generating the second signal with the adjusted timing by Equation 5.

(128) In some embodiments, removing the second OCC sequence from the second signal, thereby generating the third signal includes removing the second OCC sequence from the second signal, thereby generating the third signal by Equation 6.

(129) In some embodiments, determining the channel estimate of the channel based on the third signal includes determining the channel estimate of the channel based on the third signal by Equation 7A.

(130) Another aspect of this description relates to an apparatus that includes a memory having non-transitory instructions stored therein, a transceiver coupled to the memory, and a processor coupled to the memory, and being configured to execute the non-transitory instructions, thereby causing the apparatus to determine a least squares channel estimate of a channel, the channel being configured to receive a first received signal, the first received signal including a demodulation reference signal (DMRS) symbol sequence, a number of DMRS symbols, and a number of subcarriers. In some embodiments, the processor is configured to execute the non-transitory instructions, thereby further causing the apparatus to remove a first Orthogonal cover code (OCC) sequence from the least squares channel estimate, thereby generating a first signal. In some embodiments, the processor is configured to execute the non-transitory instructions, thereby further causing the apparatus to determine at least an estimated timing offset of the first signal. In some embodiments, the processor is configured to execute the non-transitory instructions, thereby further causing the apparatus to adjust a first timing of the least squares channel estimate based on at least the estimated timing offset, thereby generating a second signal with an adjusted timing. In some embodiments, the processor is configured to execute the non-transitory instructions, thereby further causing the apparatus to remove a second OCC sequence from the second signal, thereby generating a third signal. In some embodiments, the processor is configured to execute the non-transitory instructions, thereby further causing the apparatus to determine a channel estimate of the channel based on the third signal. In some embodiments, the processor is configured to execute the non-transitory instructions, thereby further causing the apparatus to determine a first noise power of the first received signal based on at least the channel estimate, the first received signal or the DMRS symbol sequence. In some embodiments, the processor is configured to execute the non-transitory instructions, thereby further causing the apparatus to determine a first signal power of the first received signal based on at least the channel estimate. In some embodiments, the processor is configured to execute the non-transitory instructions, thereby further causing the apparatus to determine a signal to noise ratio (SNR) of the first received signal based on the first noise power and the first signal power. In some embodiments, the processor is configured to execute the non-transitory instructions, thereby further causing the apparatus to determine an adjusted data rate of the channel based on the SNR. In some embodiments, the transceiver is configured to send a signal based on the adjusted data rate of the channel, the signal instructing a device to adjust a data rate to the adjusted data rate.

(131) In some embodiments, the non-transitory instructions that cause the apparatus to determine the least squares channel estimate of the channel includes the processor being further configured to cause the apparatus to determine the least squares channel estimate of the channel by Equation 1.

(132) In some embodiments, the non-transitory instructions that cause the apparatus to remove the first OCC sequence from the least squares channel estimate, thereby generating the first signal

includes the processor being further configured to cause the apparatus to remove the first OCC sequence from the least squares channel estimate, thereby generating the first signal by Equation 2. (133) In some embodiments, the non-transitory instructions that cause the apparatus to determine at least the estimated timing offset of the first signal includes the processor being further configured to cause the apparatus to determine at least the estimated timing offset of the first signal by Equation 3, and a timing advance is determined by Equation 4.

(134) In some embodiments, the non-transitory instructions that cause the apparatus to adjust the first timing of the least squares channel estimate based on at least the estimated timing offset, thereby generating the second signal with the adjusted timing includes the processor being further configured to cause the apparatus to adjust the first timing of the least squares channel estimate based on at least the estimated timing offset, thereby generating the second signal with the adjusted timing by Equation 5.

(135) In some embodiments, the non-transitory instructions that cause the apparatus to remove the second OCC sequence from the second signal, thereby generating the third signal includes the processor being further configured to cause the apparatus to remove the second OCC sequence from the second signal, thereby generating the third signal by Equation 6.

(136) In some embodiments, the non-transitory instructions that cause the apparatus to determine the channel estimate of the channel based on the third signal includes the processor being further configured to cause the apparatus to determine the channel estimate of the channel based on the third signal by Equation 7A.

(137) Still another aspect of this description relates to a computer-readable medium. In some embodiments, the computer-readable medium includes instructions executable by a controller of a system to cause the system to perform operations including determining a least squares channel estimate of a channel, the channel being configured to receive a first received signal, the first received signal including a demodulation reference signal (DMRS) symbol sequence, a number of DMRS symbols, and a number of subcarriers. In some embodiments, the computer-readable medium includes instructions executable by the controller of the system to further cause the system to perform operations including removing a first Orthogonal cover code (OCC) sequence from the least squares channel estimate, thereby generating a first signal. In some embodiments, the computer-readable medium includes instructions executable by the controller of the system to further cause the system to perform operations including determining at least an estimated timing offset of the first signal. In some embodiments, the computer-readable medium includes instructions executable by the controller of the system to further cause the system to perform operations including adjusting a first timing of the least squares channel estimate based on at least the estimated timing offset, thereby generating a second signal with an adjusted timing. In some embodiments, the computer-readable medium includes instructions executable by the controller of the system to further cause the system to perform operations including removing a second OCC sequence from the second signal, thereby generating a third signal. In some embodiments, the computer-readable medium includes instructions executable by the controller of the system to further cause the system to perform operations including determining a channel estimate of the channel based on the third signal. In some embodiments, the computer-readable medium includes instructions executable by the controller of the system to further cause the system to perform operations including determining a first noise power of the first received signal based on at least the channel estimate, the first received signal or the DMRS symbol sequence. In some embodiments, the computer-readable medium includes instructions executable by the controller of the system to further cause the system to perform operations including determining a first signal power of the first received signal based on at least the channel estimate. In some embodiments, the computer-readable medium includes instructions executable by the controller of the system to further cause the system to perform operations including determining a signal to noise ratio (SNR) of the first received signal based on the first noise power and the first signal power. In some embodiments, the

computer-readable medium includes instructions executable by the controller of the system to further cause the system to perform operations including determining an adjusted data rate of the channel based on the SNR. In some embodiments, the computer-readable medium includes instructions executable by the controller of the system to further cause the system to perform operations including sending a signal based on the adjusted data rate of the channel, the signal instructing a device to adjust a data rate to the adjusted data rate.

(138) In some embodiments, the instructions executable by the controller of the system cause the controller to perform operations including determining the least squares channel estimate of the channel includes the controller being further configured to perform operations including determining the least squares channel estimate of the channel by Equation 1.

(139) In some embodiments, the instructions executable by the controller of the system cause the controller to perform operations including removing the first OCC sequence from the least squares channel estimate, thereby generating the first signal includes the controller being further configured to perform operations including removing the first OCC sequence from the least squares channel estimate, thereby generating the first signal by Equation 2.

(140) In some embodiments, the instructions executable by the controller of the system cause the controller to perform operations including determining at least the estimated timing offset of the first signal includes the controller being further configured to perform operations including determining at least the estimated timing offset of the first signal by Equation 3, and a timing advance is determined by Equation 4.

(141) In some embodiments, the instructions executable by the controller of the system cause the controller to perform operations including adjusting the first timing of the least squares channel estimate based on at least the estimated timing offset, thereby generating the second signal with the adjusted timing includes the controller being further configured to perform operations including adjusting the first timing of the least squares channel estimate based on at least the estimated timing offset, thereby generating the second signal with the adjusted timing by Equation 5.

(142) In some embodiments, the instructions executable by the controller of the system cause the controller to perform operations including removing the second OCC sequence from the second signal, thereby generating the third signal includes the controller being further configured to perform operations including removing the second OCC sequence from the second signal, thereby generating the third signal by Equation 6.

(143) In some embodiments, the instructions executable by the controller of the system cause the controller to perform operations including determining the channel estimate of the channel based on the third signal includes the controller being further configured to perform operations including determining the channel estimate of the channel based on the third signal by Equation 7A.

(144) The foregoing outlines features of several embodiments so that those skilled in the art may better understand the aspects of the present disclosure. Those skilled in the art should appreciate that they may readily use the present disclosure as a basis for designing or modifying other processes and structures for carrying out the same purposes and/or achieving the same advantages of the embodiments introduced herein. Those skilled in the art should also realize that such equivalent constructions do not depart from the spirit and scope of the present disclosure, and that they may make various changes, substitutions, and alterations herein without departing from the spirit and scope of the present disclosure.

Claims

1. A method, comprising: determining, by a processor of a receiver, a least squares channel estimate of a channel, the channel being configured to receive a first received signal, the first received signal including a demodulation reference signal (DMRS) symbol sequence, a number of DMRS symbols, and a number of subcarriers; removing, by the processor, a first Orthogonal cover code

(OCC) sequence from the least squares channel estimate, thereby generating a first signal; determining, by the processor, at least an estimated timing offset of the first signal; adjusting, by the processor, a first timing of the least squares channel estimate based on at least the estimated timing offset, thereby generating a second signal with an adjusted timing; removing, by the processor, a second OCC sequence from the second signal, thereby generating a third signal; determining, by the processor, a channel estimate of the channel based on the third signal; determining, by the processor, a first noise power of the first received signal based on at least the channel estimate, the first received signal or the DMRS symbol sequence; determining, by the processor, a first signal power of the first received signal based on at least the channel estimate; determining, by the processor, a signal to noise ratio (SNR) of the first received signal based on the first noise power and the first signal power; adjusting a data rate of the channel based on the SNR; and transmitting, by a transmitter, an output signal based on an adjusted data rate of the channel based on the SNR.

2. The method of claim 1, wherein determining the least squares channel estimate of the channel comprises: determining the least squares channel estimate of the channel by Equation 1 as follows:

$H_{LS}(k, l) = Y_{DMRS}(k, l) * \text{conj}(X_{DMRS}(k, l))$, (Equation1) where $H_{LS}(k, l)$ is the least squares channel estimate of the channel, k is the number of subcarriers, l is the number of DMRS symbols, $Y_{DMRS}(k, l)$ is the first received signal, $X_{DMRS}(k, l)$ is the DMRS symbol sequence, and $\text{conj}(X_{DMRS}(k, l))$ is the conjugate of the DMRS symbol sequence $X_{DMRS}(k, l)$.

3. The method of claim 2, wherein removing the first OCC sequence from the least squares channel estimate, thereby generating the first signal comprises: removing the first OCC sequence from the least squares channel estimate, thereby generating the first signal by Equation 2 as follows:

$H_{deOcc1}(k, l) = \text{fn1}(H_{LS}(k, l))$, (Equation2) where $H_{deOcc1}(k, l)$ is the first signal, and $\text{fn1}(H_{LS}(k, l))$ is a first orthogonal cover code removal (deOCC) function.

4. The method of claim 3, wherein determining at least the estimated timing offset of the first signal comprises: determining at least the estimated timing offset of the first signal by Equation 3 as follows:

$\Omega = \tan^{-1} \left(\frac{\text{imag}(TA_{\text{metric}})}{\text{real}(TA_{\text{metric}})} \right)$, (Equation3) where Ω is the estimated timing offset of the first signal, and TA_{metric} is a timing advance, and is determined by Equation 4 as follows:

$TA_{\text{metric}} = E(H_{deOcc1}(k, l) * \text{conj}(H_{deOcc1}(k + u, l)))$, (Equation4) where $E(H_{deOcc1}(k, l) * \text{conj}(H_{deOcc1}(k + u, l)))$ is the expected value of the product of the first signal and the conjugate of an intermediary signal ($H_{deOcc1}(k + u, l)$), and u is a fixed offset.

5. The method of claim 4, wherein adjusting the first timing of the least squares channel estimate based on at least the estimated timing offset, thereby generating the second signal with the adjusted timing comprises: adjusting the first timing of the least squares channel estimate based on at least the estimated timing offset, thereby generating the second signal with the adjusted timing by

Equation 5 as follows: $\text{Est}H_{LS}(k, l) = H_{LS}(k, l) * e^{-\frac{j\Omega}{u * (\text{FFT_Size})}}$, (Equation5) where

$\text{Est}H_{LS}(k, l)$ is the second signal with the adjusted timing, $H_{LS}(k, l)$ is the least squares channel estimate of the channel, $e^{-\frac{j\Omega}{u * (\text{FFT_Size})}}$ is the adjusted timing, FFT_Size is a size of a fast Fourier transform (FFT).

6. The method of claim 5, wherein removing the second OCC sequence from the second signal, thereby generating the third signal comprises: removing the second OCC sequence from the second signal, thereby generating the third signal by Equation 6 as follows:

$H_{deOcc2}(k, l) = \text{fn2}(\text{Est}H_{LS}(k, l))$, (Equation6) where $H_{deOcc2}(k, l)$ is the third signal, and $\text{fn2}(\text{Est}H_{LS}(k, l))$ is a second deOCC function.

7. The method of claim 6, wherein determining the channel estimate of the channel based on the third signal comprises: determining the channel estimate of the channel based on the third signal by

Equation 7 as follows: $H_{\text{Est}}(k, l) = \text{fn3}(H_{\text{deOcc2}}(k, l))$, (Equation7) where $H_{\text{sub.EST}}(k, l)$ is the channel estimate, and $\text{fn3}(H_{\text{sub.deOcc2}}(k, l))$ is a channel estimate function.

8. An apparatus, comprising: a memory having non-transitory instructions stored therein; and a transceiver coupled to the memory; and a processor coupled to the memory, and being configured to execute the non-transitory instructions, thereby causing the apparatus to: determine a least squares channel estimate of a channel, the channel being configured to receive a first received signal, the first received signal including a demodulation reference signal (DMRS) symbol sequence, a number of DMRS symbols, and a number of subcarriers; remove a first Orthogonal cover code (OCC) sequence from the least squares channel estimate, thereby generating a first signal; determine at least an estimated timing offset of the first signal; adjust a first timing of the least squares channel estimate based on at least the estimated timing offset, thereby generating a second signal with an adjusted timing; remove a second OCC sequence from the second signal, thereby generating a third signal; determine a channel estimate of the channel based on the third signal; determine a first noise power of the first received signal based on at least the channel estimate, the first received signal or the DMRS symbol sequence; determine a first signal power of the first received signal based on at least the channel estimate; determine a signal to noise ratio (SNR) of the first received signal based on the first noise power and the first signal power; and determine an adjusted data rate of the channel based on the SNR; and the transceiver is configured to: send a signal based on the adjusted data rate of the channel, the signal instructing a device to adjust a data rate to the adjusted data rate.

9. The apparatus of claim 8, wherein the non-transitory instructions that cause the apparatus to determine the least squares channel estimate of the channel comprises the processor being further configured to cause the apparatus to: determine the least squares channel estimate of the channel by Equation 1 as follows: $H_{\text{LS}}(k, l) = Y_{\text{DMRS}}(k, l) * \text{conj}(X_{\text{DMRS}}(k, l))$, (Equation1) where $H_{\text{sub.LS}}(k, l)$ is the least squares channel estimate of the channel, k is the number of subcarriers, l is the number of DMRS symbols, $Y_{\text{sub.DMRS}}(k, l)$ is the first received signal, $X_{\text{sub.DMRS}}(k, l)$ is the DMRS symbol sequence, and $\text{conj}(X_{\text{sub.DMRS}}(k, l))$ is the conjugate of the DMRS symbol sequence $X_{\text{sub.DMRS}}(k, l)$.

10. The apparatus of claim 9, wherein the non-transitory instructions that cause the apparatus to remove the first OCC sequence from the least squares channel estimate, thereby generating the first signal comprises the processor being further configured to cause the apparatus to: remove the first OCC sequence from the least squares channel estimate, thereby generating the first signal by Equation 2 as follows: $H_{\text{deOcc1}}(k, l) = \text{fn1}(H_{\text{LS}}(k, l))$, (Equation2) where $H_{\text{sub.deOcc1}}(k, l)$ is the first signal, and $\text{fn1}(H_{\text{sub.LS}}(k, l))$ is a first orthogonal cover code removal (deOCC) function.

11. The apparatus of claim 10, wherein the non-transitory instructions that cause the apparatus to determine at least the estimated timing offset of the first signal comprises the processor being further configured to cause the apparatus to: determine at least the estimated timing offset of the first signal by Equation 3 as follows: $\Omega = \tan^{-1} \left(\frac{\text{imag}(\text{TA}_{\text{metric}})}{\text{real}(\text{TA}_{\text{metric}})} \right)$, (Equation3) where Ω is the estimated timing offset of the first signal, and $\text{TA}_{\text{sub.metric}}$ is a timing advance, and is determined by Equation 4 as follows:

$\text{TA}_{\text{metric}} = E(H_{\text{deOcc1}}(k, l) * \text{conj}(H_{\text{deOcc1}}(k + u, l)))$, (Equation4) where $E(H_{\text{sub.deOcc1}}(k, l) * \text{conj}(H_{\text{sub.deOcc1}}(k + u, l)))$ is the expected value of the product of the first signal and the conjugate of an intermediary signal ($H_{\text{sub.deOcc1}}(k + u, l)$), and u is a fixed offset.

12. The apparatus of claim 11, wherein the non-transitory instructions that cause the apparatus to adjust the first timing of the least squares channel estimate based on at least the estimated timing offset, thereby generating the second signal with the adjusted timing comprises the processor being further configured to cause the apparatus to: adjust the first timing of the least squares channel

estimate based on at least the estimated timing offset, thereby generating the second signal with the adjusted timing by Equation 5 as follows: $EstH_{LS}(k, l) = H_{LS}(k, l) * e^{-j\Omega_{u*(FFT_Size)}}$, (Equation5) where $EstH_{LS}(k, l)$ is the second signal with the adjusted timing, $H_{LS}(k, l)$ is the least squares channel estimate of the channel, $e^{-j\Omega_{u*(FFT_Size)}}$ is the adjusted timing, FFT_Size is a size of a fast Fourier transform (FFT).

13. The apparatus of claim 12, wherein the non-transitory instructions that cause the apparatus to remove the second OCC sequence from the second signal, thereby generating the third signal comprises the processor being further configured to cause the apparatus to: remove the second OCC sequence from the second signal, thereby generating the third signal by Equation 6 as follows: $H_{deOcc2}(k, l) = fn2(EstH_{LS}(k, l))$, (Equation6) where $H_{deOcc2}(k, l)$ is the third signal, and $fn2(EstH_{LS}(k, l))$ is a second deOCC function.

14. The apparatus of claim 13, wherein the non-transitory instructions that cause the apparatus to determine the channel estimate of the channel based on the third signal comprises the processor being further configured to cause the apparatus to: determine the channel estimate of the channel based on the third signal by Equation 7 as follows: $H_{Est}(k, l) = fn3(H_{deOcc2}(k, l))$, (Equation7) where $H_{Est}(k, l)$ is the channel estimate, and $fn3(H_{deOcc2}(k, l))$ is a channel estimate function.

15. A computer-readable medium including instructions executable a system to cause the system to perform operations comprising: determining a least squares channel estimate of a channel, the channel being configured to receive a first received signal, the first received signal including a demodulation reference signal (DMRS) symbol sequence, a number of DMRS symbols, and a number of subcarriers; removing a first Orthogonal cover code (OCC) sequence from the least squares channel estimate, thereby generating a first signal; determining at least an estimated timing offset of the first signal; adjusting a first timing of the least squares channel estimate based on at least the estimated timing offset, thereby generating a second signal with an adjusted timing; removing a second OCC sequence from the second signal, thereby generating a third signal; determining a channel estimate of the channel based on the third signal; determining a first noise power of the first received signal based on at least the channel estimate, the first received signal or the DMRS symbol sequence; determining a first signal power of the first received signal based on at least the channel estimate; determining a signal to noise ratio (SNR) of the first received signal based on the first noise power and the first signal power; determining an adjusted data rate of the channel based on the SNR; and sending a signal based on the adjusted data rate of the channel, the signal instructing a device to adjust a data rate to the adjusted data rate.

16. The computer-readable medium of claim 15, wherein the instructions executable by the system cause the system to perform operations comprising determining the least squares channel estimate of the channel comprises the system being further configured to perform operations comprising: determining the least squares channel estimate of the channel by Equation 1 as follows:

$H_{LS}(k, l) = Y_{DMRS}(k, l) * conj(X_{DMRS}(k, l))$, (Equation1) where $H_{LS}(k, l)$ is the least squares channel estimate of the channel, k is the number of subcarriers, l is the number of DMRS symbols, $Y_{DMRS}(k, l)$ is the first received signal, $X_{DMRS}(k, l)$ is the DMRS symbol sequence, and $conj(X_{DMRS}(k, l))$ is the conjugate of the DMRS symbol sequence $X_{DMRS}(k, l)$.

17. The computer-readable medium of claim 16, wherein the instructions executable by the system cause the system to perform operations comprising removing the first OCC sequence from the least squares channel estimate, thereby generating the first signal comprises the system being further configured to perform operations comprising: removing the first OCC sequence from the least squares channel estimate, thereby generating the first signal by Equation 2 as follows:

$H_{deOcc1}(k, l) = fn1(H_{LS}(k, l))$, (Equation2) where $H_{deOcc1}(k, l)$ is the first signal, and

fn1(H.sub.LS(k, l)) is a first orthogonal cover code removal (deOCC) function.

18. The computer-readable medium of claim 17, wherein the instructions executable by the system cause the system to perform operations comprising determining at least the estimated timing offset of the first signal comprises the system being further configured to perform operations comprising: determining at least the estimated timing offset of the first signal by Equation 3 as follows:

$\Omega = \tan^{-1} \left(\frac{\text{imag}(TA_{\text{metric}})}{\text{real}(TA_{\text{metric}})} \right)$, (Equation3) where Ω is the estimated timing offset of the first signal, and TA.sub.metric is a timing advance, and is determined by Equation 4 as follows:

$TA_{\text{metric}} = E(H_{\text{deOCC1}}(k, l) * \text{conj}(H_{\text{deOCC1}}(k + u, l)))$, (Equation4) where $E(H_{\text{deOCC1}}(k, l) * \text{conj}(H_{\text{deOCC1}}(k + u, l)))$ is the expected value of the product of the first signal and the conjugate of an intermediary signal ($H_{\text{deOCC1}}(k + u, l)$), and u is a fixed offset.

19. The computer-readable medium of claim 18, wherein the instructions executable by the system cause the system to perform operations comprising adjusting the first timing of the least squares channel estimate based on at least the estimated timing offset, thereby generating the second signal with the adjusted timing comprises the system being further configured to perform operations comprising: adjusting the first timing of the least squares channel estimate based on at least the estimated timing offset, thereby generating the second signal with the adjusted timing by Equation

5 as follows: $EstH_{LS}(k, l) = H_{LS}(k, l) * e^{-\frac{j\Omega}{u * (\text{FFT_Size})}}$, (Equation5) where $EstH_{LS}(k, l)$ is the second signal with the adjusted timing, $H_{LS}(k, l)$ is the least squares channel estimate of the channel, $e^{-\frac{j\Omega}{u * (\text{FFT_Size})}}$ is the adjusted timing, FFT_Size is a size of a fast Fourier transform (FFT).

20. The computer-readable medium of claim 19, wherein the instructions executable by the system cause the system to perform operations comprising: removing the second OCC sequence from the second signal, thereby generating the third signal comprises the system being further configured to perform operations comprising: removing the second OCC sequence from the second signal, thereby generating the third signal by Equation 6 as follows:

$H_{\text{deOCC2}}(k, l) = \text{fn2}(EstH_{LS}(k, l))$, (Equation6) where $H_{\text{deOCC2}}(k, l)$ is the third signal, and $\text{fn2}(EstH_{LS}(k, l))$ is a second deOCC function; and determining the channel estimate of the channel based on the third signal comprises the system being further configured to perform operations comprising: determining the channel estimate of the channel based on the third signal by Equation 7 as follows: $H_{Est}(k, l) = \text{fn3}(H_{\text{deOCC2}}(k, l))$, (Equation7) where $H_{Est}(k, l)$ is the channel estimate, and $\text{fn3}(H_{\text{deOCC2}}(k, l))$ is a channel estimate function.
