

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12394523
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Mistri; Afshad M. et al.

Wellness aggregator

Abstract

The present disclosure relates to aggregating and sharing wellness data. The wellness data can be received by a user device from any number of sensors external or internal to the user device, from a user manually entering the wellness data, or from other users or entities. The user device can securely store the wellness data on the user device and transmit the wellness data to be stored on a remote database. A user of the device can share some or all of the wellness data with friends, relatives, caregivers, healthcare providers, or the like. The user device can further display a user's wellness data in an aggregated view of different types of wellness data. Wellness data of other users can also be viewed if authorizations from those users have been received.

Inventors: Mistri; Afshad M. (Mountain View, CA), Beberg; Adam L. (San Jose, CA), Davydov; Anton M. (Gilroy, CA), Edwards; Dylan R. (San Jose, CA), Kennedy; Zachery W. (Marina Del Rey, CA), Minjack; Zachury B. (San Francisco, CA), Park; Dennis S. (San Francisco, CA), Yang; Lawrence Y. (Bellevue, WA)

Applicant: Apple Inc. (Cupertino, CA)

Family ID: 1000008767121

Assignee: Apple Inc. (Cupertino, CA)

Appl. No.: 18/774704

Filed: July 16, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240371516 A1	Nov. 07, 2024

Related U.S. Application Data

continuation parent-doc US 17735395 20220503 US 12080421 child-doc US 18774704
continuation parent-doc US 16820383 20200316 US 11996190 20240528 child-doc US 17735395
continuation parent-doc US 14732773 20150607 ABANDONED child-doc US 16820383
continuation-in-part parent-doc WO PCT/US2015/032474 20150526 PENDING child-doc US 14732773
continuation-in-part parent-doc US 14599424 20150116 US 10270898 20190423 child-doc US 14732773
continuation-in-part parent-doc WO PCT/US2013/073195 20131204 PENDING child-doc US 14732773
us-provisional-application US 62129945 20150308
us-provisional-application US 62006032 20140530

Publication Classification

Int. Cl.: G16H40/67 (20180101); G06Q50/00 (20240101); G16H10/60 (20180101); G16H50/30 (20180101); G16H50/70 (20180101); G16H80/00 (20180101)

U.S. Cl.:

CPC G16H40/67 (20180101); G06Q50/01 (20130101); G16H10/60 (20180101); G16H50/30 (20180101); G16H50/70 (20180101); G16H80/00 (20180101);

Field of Classification Search

CPC: G16H (40/67); G16H (10/60); G16H (50/30); G16H (50/70); G16H (80/00); G06Q (50/01)

USPC: 705/3

References Cited

U.S. PATENT DOCUMENTS				
Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC

3480943	12/1968	Manber	N/A	N/A
4205628	12/1979	Null	N/A	N/A
4842266	12/1988	Sweeney et al.	N/A	N/A
5349962	12/1993	Lockard et al.	N/A	N/A
5423863	12/1994	Felblinger et al.	N/A	N/A
5458548	12/1994	Crossing et al.	N/A	N/A
5474077	12/1994	Suga	N/A	N/A
5642731	12/1996	Kehr	N/A	N/A
5685723	12/1996	Ladin et al.	N/A	N/A
5730141	12/1997	Fain et al.	N/A	N/A
5788655	12/1997	Yoshimura et al.	N/A	N/A
5812983	12/1997	Kumagai	N/A	N/A
5845235	12/1997	Luukkanen et al.	N/A	N/A
5944633	12/1998	Wittrock	N/A	N/A
6013008	12/1999	Fukushima	N/A	N/A
6061592	12/1999	Nigam	N/A	N/A
6095949	12/1999	Arai	N/A	N/A
6095984	12/1999	Amano et al.	N/A	N/A
6097371	12/1999	Siddiqui et al.	N/A	N/A
6097385	12/1999	Robinson	N/A	N/A
6199012	12/2000	Hasegawa	N/A	N/A
6244988	12/2000	Delman	N/A	N/A
6302789	12/2000	Harada et al.	N/A	N/A
6323846	12/2000	Westerman et al.	N/A	N/A
6416471	12/2001	Kumar et al.	N/A	N/A
6570557	12/2002	Westerman et al.	N/A	N/A
6603477	12/2002	Tittle	N/A	N/A
6639584	12/2002	Li	N/A	N/A
6662023	12/2002	Helle	N/A	N/A
6677932	12/2003	Westerman	N/A	N/A
6705972	12/2003	Takano et al.	N/A	N/A
6837827	12/2004	Lee et al.	N/A	N/A
6866613	12/2004	Brown et al.	N/A	N/A
7020514	12/2005	Wiesel	N/A	N/A
7081905	12/2005	Raghunath	N/A	N/A
7107546	12/2005	Coulthard et al.	N/A	N/A
7128693	12/2005	Brown et al.	N/A	N/A
7130664	12/2005	Williams	N/A	N/A
7251454	12/2006	White	N/A	N/A
7302272	12/2006	Ackley	N/A	N/A
7534206	12/2008	Lovitt et al.	N/A	N/A
7614008	12/2008	Ording	N/A	N/A
7633076	12/2008	Hupi et al.	N/A	N/A
7653883	12/2009	Hotelling et al.	N/A	N/A
7657849	12/2009	Chaudhri et al.	N/A	N/A
7662065	12/2009	Kahn et al.	N/A	N/A
7663607	12/2009	Hotelling et al.	N/A	N/A
7695406	12/2009	Waters	N/A	N/A
7739148	12/2009	Suzuki et al.	N/A	N/A
7771320	12/2009	Riley et al.	N/A	N/A
7844914	12/2009	Andre et al.	N/A	N/A
7853428	12/2009	Usui et al.	N/A	N/A
7870013	12/2010	Allemann et al.	N/A	N/A
7957762	12/2010	Herz et al.	N/A	N/A
7970827	12/2010	Cumberbatch et al.	N/A	N/A
8006002	12/2010	Kalayjian et al.	N/A	N/A
8060229	12/2010	Gupta et al.	N/A	N/A
8105208	12/2011	Oleson et al.	N/A	N/A
8152694	12/2011	Srinivasan et al.	N/A	N/A
8200323	12/2011	Dibenedetto et al.	N/A	N/A
8239784	12/2011	Hotelling et al.	N/A	N/A
8279180	12/2011	Hotelling et al.	N/A	N/A
8321006	12/2011	Snyder et al.	N/A	N/A
8341557	12/2011	Pisula et al.	N/A	N/A
8381135	12/2012	Hotelling et al.	N/A	N/A
8475339	12/2012	Hwang et al.	N/A	N/A
8479122	12/2012	Hotelling et al.	N/A	N/A
8496563	12/2012	Komatsu et al.	N/A	N/A
8543081	12/2012	Scott et al.	N/A	N/A
8595798	12/2012	Anand et al.	N/A	N/A
8666361	12/2013	Chu et al.	N/A	N/A
8676170	12/2013	Porrati et al.	N/A	N/A
8700158	12/2013	Mass et al.	N/A	N/A
8725527	12/2013	Kahn et al.	N/A	N/A
8734296	12/2013	Brumback et al.	N/A	N/A

8768648	12/2013	Panther et al.	N/A	N/A
8784115	12/2013	Chuang	N/A	N/A
8784271	12/2013	Brumback et al.	N/A	N/A
8825445	12/2013	Hoffman et al.	N/A	N/A
8849610	12/2013	Molettiere et al.	N/A	N/A
8888707	12/2013	Shirasaki et al.	N/A	N/A
8910299	12/2013	Michalske	N/A	N/A
8934963	12/2014	Farazi	N/A	N/A
8947239	12/2014	Park	N/A	N/A
8990006	12/2014	Wallace et al.	N/A	N/A
9011292	12/2014	Weast et al.	N/A	N/A
9020538	12/2014	White et al.	N/A	N/A
9063164	12/2014	Yuen et al.	N/A	N/A
9087234	12/2014	Hoffman et al.	N/A	N/A
9148483	12/2014	Molettiere et al.	N/A	N/A
9164663	12/2014	Berard	N/A	N/A
9173576	12/2014	Yuen et al.	N/A	N/A
9224291	12/2014	Moll-Carrillo et al.	N/A	N/A
9230076	12/2015	King et al.	N/A	N/A
9449365	12/2015	Roberts	N/A	N/A
9532734	12/2016	Hoffman et al.	N/A	N/A
9557881	12/2016	Jain et al.	N/A	N/A
9579060	12/2016	Lisy et al.	N/A	N/A
9582165	12/2016	Wilson et al.	N/A	N/A
9589445	12/2016	White et al.	N/A	N/A
9606695	12/2016	Matas	N/A	N/A
9712629	12/2016	Molettiere et al.	N/A	N/A
9721066	12/2016	Funaro et al.	N/A	N/A
9723381	12/2016	Swanson	N/A	N/A
9730621	12/2016	Cohen et al.	N/A	N/A
9734477	12/2016	Weast et al.	N/A	N/A
9740825	12/2016	Sansale et al.	N/A	N/A
9798443	12/2016	Gray	N/A	N/A
9800525	12/2016	Lerner et al.	N/A	N/A
9808206	12/2016	Zhao et al.	N/A	N/A
9813642	12/2016	Chen et al.	N/A	N/A
9817481	12/2016	Pantelopoulos et al.	N/A	N/A
9854653	12/2016	Ackmann et al.	N/A	N/A
9880805	12/2017	Guralnick	N/A	N/A
9910571	12/2017	Chen et al.	N/A	N/A
9918664	12/2017	Blahnik et al.	N/A	N/A
9931539	12/2017	De Pablos et al.	N/A	N/A
9940682	12/2017	Hoffman et al.	N/A	N/A
10056006	12/2017	Hsu-Hoffman et al.	N/A	N/A
10105573	12/2017	Park et al.	N/A	N/A
10150002	12/2017	Kass et al.	N/A	N/A
10220258	12/2018	Gu et al.	N/A	N/A
10226195	12/2018	Briante et al.	N/A	N/A
10254911	12/2018	Yang	N/A	N/A
10270898	12/2018	Soli et al.	N/A	N/A
10272294	12/2018	Williams et al.	N/A	N/A
10275262	12/2018	Bull et al.	N/A	N/A
10300334	12/2018	Chuang	N/A	N/A
10304347	12/2018	Wilson et al.	N/A	N/A
10339830	12/2018	Han et al.	N/A	N/A
10365811	12/2018	Robinson et al.	N/A	N/A
10398381	12/2018	Heneghan et al.	N/A	N/A
10489508	12/2018	Zhai et al.	N/A	N/A
10500441	12/2018	Lagree	N/A	N/A
10576327	12/2019	Kim et al.	N/A	N/A
10592088	12/2019	Robinson et al.	N/A	N/A
10602964	12/2019	Kerber	N/A	N/A
10635267	12/2019	Williams	N/A	N/A
10639521	12/2019	Foley et al.	N/A	N/A
10674942	12/2019	Williams et al.	N/A	N/A
10692593	12/2019	Young et al.	N/A	N/A
10736543	12/2019	Chen et al.	N/A	N/A
10762990	12/2019	Schilling et al.	N/A	N/A
10777314	12/2019	Williams et al.	N/A	N/A
10796549	12/2019	Roberts et al.	N/A	N/A
10898132	12/2020	White et al.	N/A	N/A
10973422	12/2020	Pantelopoulos et al.	N/A	N/A
10978195	12/2020	Blahnik et al.	N/A	N/A
11103161	12/2020	Williams et al.	N/A	N/A
11107567	12/2020	Blahnik et al.	N/A	N/A

11107569	12/2020	Devoto	N/A	N/A
11107580	12/2020	Felton et al.	N/A	N/A
11152100	12/2020	Crowley et al.	N/A	N/A
11202598	12/2020	Soli et al.	N/A	N/A
11209957	12/2020	Dryer et al.	N/A	N/A
11216119	12/2021	De Vries et al.	N/A	N/A
11317833	12/2021	Williams et al.	N/A	N/A
11446548	12/2021	Devine et al.	N/A	N/A
11452915	12/2021	Devine et al.	N/A	N/A
11458363	12/2021	Powers et al.	N/A	N/A
11514813	12/2021	Bell et al.	N/A	N/A
11529074	12/2021	Vaterlaus	N/A	N/A
11801423	12/2022	Bissonnette et al.	N/A	N/A
2001/0049470	12/2000	Mault et al.	N/A	N/A
2002/0015024	12/2001	Westerman et al.	N/A	N/A
2002/0045960	12/2001	Phillips et al.	N/A	N/A
2002/0086774	12/2001	Warner	N/A	N/A
2002/0118121	12/2001	Lehrman et al.	N/A	N/A
2003/0023178	12/2002	Bischoff et al.	N/A	N/A
2003/0064860	12/2002	Yamashita et al.	N/A	N/A
2003/0134714	12/2002	Oishi et al.	N/A	N/A
2003/0140044	12/2002	Mok et al.	N/A	N/A
2003/0179229	12/2002	Van et al.	N/A	N/A
2003/0181291	12/2002	Ogawa	N/A	N/A
2003/0182628	12/2002	Lira	N/A	N/A
2003/0216971	12/2002	Sick et al.	N/A	N/A
2003/0226695	12/2002	Mault	N/A	N/A
2004/0014567	12/2003	Mendel	N/A	N/A
2004/0034288	12/2003	Hennessy et al.	N/A	N/A
2004/0077462	12/2003	Brown et al.	N/A	N/A
2004/0077958	12/2003	Kato et al.	N/A	N/A
2004/0085316	12/2003	Malik	N/A	N/A
2004/0128286	12/2003	Yasushi et al.	N/A	N/A
2004/0236189	12/2003	Hawthorne et al.	N/A	N/A
2005/0015803	12/2004	Macrae et al.	N/A	N/A
2005/0075214	12/2004	Brown et al.	N/A	N/A
2005/0079905	12/2004	Martens	N/A	N/A
2005/0113650	12/2004	Pacione et al.	N/A	N/A
2005/0124324	12/2004	Thomas et al.	N/A	N/A
2005/0130802	12/2004	Kinnunen et al.	N/A	N/A
2005/0139852	12/2004	Chen et al.	N/A	N/A
2005/0165627	12/2004	Fotsch	707/999.009	G16H 10/60
2005/0171410	12/2004	Hjelt et al.	N/A	N/A
2005/0172311	12/2004	Hjelt et al.	N/A	N/A
2005/0190059	12/2004	Wehrenberg	N/A	N/A
2005/0197063	12/2004	White et al.	N/A	N/A
2005/0215848	12/2004	Lorenzato et al.	N/A	N/A
2005/0216867	12/2004	Marvit et al.	N/A	N/A
2005/0228735	12/2004	Duquette	N/A	N/A
2005/0272564	12/2004	Pyles et al.	N/A	N/A
2006/0017692	12/2005	Wehrenberg et al.	N/A	N/A
2006/0020174	12/2005	Matsumura et al.	N/A	N/A
2006/0026536	12/2005	Hotelling et al.	N/A	N/A
2006/0033724	12/2005	Chaudhri et al.	N/A	N/A
2006/0047208	12/2005	Yoon	N/A	N/A
2006/0048076	12/2005	Vronay et al.	N/A	N/A
2006/0052727	12/2005	Palestrant	N/A	N/A
2006/0094969	12/2005	Nissila	N/A	N/A
2006/0098109	12/2005	Ooki	N/A	N/A
2006/0106741	12/2005	Janarthanan	N/A	N/A
2006/0117014	12/2005	Qi	N/A	N/A
2006/0136173	12/2005	Case, Jr. et al.	N/A	N/A
2006/0136449	12/2005	Parker et al.	N/A	N/A
2006/0155578	12/2005	Eisenberger et al.	N/A	N/A
2006/0160090	12/2005	Macina et al.	N/A	N/A
2006/0184800	12/2005	Rosenberg	N/A	N/A
2006/0197753	12/2005	Hotelling	N/A	N/A
2006/0205564	12/2005	Peterson	N/A	N/A
2006/0240959	12/2005	Huang	N/A	N/A
2006/0250524	12/2005	Roche	N/A	N/A
2007/0016091	12/2006	Butt et al.	N/A	N/A
2007/0021269	12/2006	Shum	N/A	N/A
2007/0032733	12/2006	Burton	N/A	N/A
2007/0033069	12/2006	Rao et al.	N/A	N/A
2007/0056727	12/2006	Newman	N/A	N/A

2007/0071256	12/2006	Ito	N/A	N/A
2007/0113726	12/2006	Oliver et al.	N/A	N/A
2007/0135043	12/2006	Hayes et al.	N/A	N/A
2007/0136093	12/2006	Rankin et al.	N/A	N/A
2007/0143433	12/2006	Daigle	N/A	N/A
2007/0169614	12/2006	Sasaki et al.	N/A	N/A
2007/0249949	12/2006	Hadley	N/A	N/A
2007/0250505	12/2006	Yang et al.	N/A	N/A
2007/0250613	12/2006	Gulledge	N/A	N/A
2007/0271065	12/2006	Gupta et al.	N/A	N/A
2008/0012701	12/2007	Kass et al.	N/A	N/A
2008/0020803	12/2007	Rios et al.	N/A	N/A
2008/0027673	12/2007	Trumm	N/A	N/A
2008/0051919	12/2007	Sakai et al.	N/A	N/A
2008/0052945	12/2007	Matas et al.	N/A	N/A
2008/0058626	12/2007	Miyata et al.	N/A	N/A
2008/0076637	12/2007	Gilley et al.	N/A	N/A
2008/0077026	12/2007	Banet et al.	N/A	N/A
2008/0082145	12/2007	Skwarek et al.	N/A	N/A
2008/0086318	12/2007	Gilley et al.	N/A	N/A
2008/0096726	12/2007	Riley et al.	N/A	N/A
2008/0133742	12/2007	Southiere et al.	N/A	N/A
2008/0141135	12/2007	Mason et al.	N/A	N/A
2008/0146892	12/2007	Leboeuf et al.	N/A	N/A
2008/0150731	12/2007	Laukkanen et al.	N/A	N/A
2008/0161161	12/2007	Pipinich et al.	N/A	N/A
2008/0161707	12/2007	Farringdon et al.	N/A	N/A
2008/0177569	12/2007	Chen et al.	N/A	N/A
2008/0195600	12/2007	Deakter	N/A	N/A
2008/0200312	12/2007	Tagliabue	N/A	N/A
2008/0228045	12/2007	Gao et al.	N/A	N/A
2008/0229226	12/2007	Rowbottom et al.	N/A	N/A
2008/0254767	12/2007	Jin	N/A	N/A
2008/0262946	12/2007	Wren	N/A	N/A
2008/0278333	12/2007	Fennell et al.	N/A	N/A
2008/0300110	12/2007	Smith et al.	N/A	N/A
2008/0320391	12/2007	Lemay et al.	N/A	N/A
2009/0007017	12/2008	Anzures et al.	N/A	N/A
2009/0012821	12/2008	Besson et al.	N/A	N/A
2009/0012988	12/2008	Brown	N/A	N/A
2009/0047645	12/2008	Dibenedetto et al.	N/A	N/A
2009/0054743	12/2008	Stewart	N/A	N/A
2009/0065578	12/2008	Peterson et al.	N/A	N/A
2009/0075782	12/2008	Joubert et al.	N/A	N/A
2009/0106685	12/2008	Care et al.	N/A	N/A
2009/0118100	12/2008	Oliver et al.	N/A	N/A
2009/0144639	12/2008	Nims et al.	N/A	N/A
2009/0149299	12/2008	Tchao et al.	N/A	N/A
2009/0158167	12/2008	Wang et al.	N/A	N/A
2009/0164567	12/2008	Hara	N/A	N/A
2009/0170532	12/2008	Lee et al.	N/A	N/A
2009/0192823	12/2008	Hawkins et al.	N/A	N/A
2009/0199130	12/2008	Tsern et al.	N/A	N/A
2009/0205041	12/2008	Michalske	N/A	N/A
2009/0210078	12/2008	Crowley	N/A	N/A
2009/0216556	12/2008	Martin et al.	N/A	N/A
2009/0222056	12/2008	Lindh et al.	N/A	N/A
2009/0222761	12/2008	Hayashi	N/A	N/A
2009/0233771	12/2008	Quatrochi et al.	N/A	N/A
2009/0249076	12/2008	Reed et al.	N/A	N/A
2009/0259134	12/2008	Levine	N/A	N/A
2009/0262088	12/2008	Moll-Carrillo et al.	N/A	N/A
2009/0268949	12/2008	Ueshima et al.	N/A	N/A
2009/0276463	12/2008	Miller et al.	N/A	N/A
2009/0287103	12/2008	Pillai	N/A	N/A
2009/0291805	12/2008	Blum et al.	N/A	N/A
2009/0292561	12/2008	Itoh	N/A	N/A
2009/0307105	12/2008	Lemay et al.	N/A	N/A
2009/0319243	12/2008	Suarez-Rivera et al.	N/A	N/A
2010/0030094	12/2009	Lundback	N/A	N/A
2010/0031202	12/2009	Morris et al.	N/A	N/A
2010/0042949	12/2009	Chen	N/A	N/A
2010/0048358	12/2009	Tchao et al.	N/A	N/A
2010/0060586	12/2009	Pisula et al.	N/A	N/A
2010/0062818	12/2009	Haughay et al.	N/A	N/A

2010/0062905	12/2009	Rottler et al.	N/A	N/A
2010/0063840	12/2009	Hoyme et al.	N/A	N/A
2010/0064255	12/2009	Rottler et al.	N/A	N/A
2010/0076331	12/2009	Chan et al.	N/A	N/A
2010/0079291	12/2009	Kroll et al.	N/A	N/A
2010/0094658	12/2009	Mok et al.	N/A	N/A
2010/0099539	12/2009	Haataja	N/A	N/A
2010/0103101	12/2009	Song et al.	N/A	N/A
2010/0121700	12/2009	Wigder et al.	N/A	N/A
2010/0130890	12/2009	Matsumura et al.	N/A	N/A
2010/0137106	12/2009	Oshima et al.	N/A	N/A
2010/0145209	12/2009	Lee et al.	N/A	N/A
2010/0152600	12/2009	Droitcour et al.	N/A	N/A
2010/0161353	12/2009	Mayaud	N/A	N/A
2010/0179832	12/2009	Van et al.	N/A	N/A
2010/0179833	12/2009	Roizen et al.	N/A	N/A
2010/0184564	12/2009	Molyneux et al.	N/A	N/A
2010/0190468	12/2009	Scott et al.	N/A	N/A
2010/0194692	12/2009	Orr et al.	N/A	N/A
2010/0197463	12/2009	Haughay et al.	N/A	N/A
2010/0198453	12/2009	Dorogusker et al.	N/A	N/A
2010/0202368	12/2009	Hans	N/A	N/A
2010/0222645	12/2009	Nadler et al.	N/A	N/A
2010/0222859	12/2009	Govari et al.	N/A	N/A
2010/0231612	12/2009	Chaudhri et al.	N/A	N/A
2010/0264097	12/2009	Sun et al.	N/A	N/A
2010/0269055	12/2009	Daikeler et al.	N/A	N/A
2010/0269157	12/2009	Experton	726/28	G06F 21/6245
2010/0273610	12/2009	Johnson	N/A	N/A
2010/0281374	12/2009	Schulz et al.	N/A	N/A
2010/0292599	12/2009	Oleson et al.	N/A	N/A
2010/0292600	12/2009	Dibenedetto et al.	N/A	N/A
2010/0298899	12/2009	Donnelly et al.	N/A	N/A
2010/0305965	12/2009	Benjamin et al.	N/A	N/A
2010/0309149	12/2009	Blumenberg et al.	N/A	N/A
2010/0331145	12/2009	Lakovic et al.	N/A	N/A
2011/0003665	12/2010	Burton et al.	N/A	N/A
2011/0010195	12/2010	Cohn et al.	N/A	N/A
2011/0010200	12/2010	Firozvi et al.	N/A	N/A
2011/0016120	12/2010	Haughay et al.	N/A	N/A
2011/0032105	12/2010	Hoffman et al.	N/A	N/A
2011/0052005	12/2010	Selner	N/A	N/A
2011/0066051	12/2010	Moon et al.	N/A	N/A
2011/0071869	12/2010	O'Brien et al.	N/A	N/A
2011/0074699	12/2010	Marr et al.	N/A	N/A
2011/0087076	12/2010	Brynnelsen et al.	N/A	N/A
2011/0088086	12/2010	Swink et al.	N/A	N/A
2011/0098928	12/2010	Hoffman et al.	N/A	N/A
2011/0106553	12/2010	Tanaka et al.	N/A	N/A
2011/0106557	12/2010	Gazula	N/A	N/A
2011/0112418	12/2010	Feild et al.	N/A	N/A
2011/0113430	12/2010	Fuse	N/A	N/A
2011/0125041	12/2010	Fischell et al.	N/A	N/A
2011/0137678	12/2010	Williams	N/A	N/A
2011/0137836	12/2010	Kuriyama et al.	N/A	N/A
2011/0159469	12/2010	Hwang et al.	N/A	N/A
2011/0167369	12/2010	Van Os	N/A	N/A
2011/0201911	12/2010	Johnson et al.	N/A	N/A
2011/0213276	12/2010	Sarussi et al.	N/A	N/A
2011/0214162	12/2010	Brakensiek et al.	N/A	N/A
2011/0227872	12/2010	Huska et al.	N/A	N/A
2011/0230169	12/2010	Ohki	N/A	N/A
2011/0230986	12/2010	Lafortune et al.	N/A	N/A
2011/0246509	12/2010	Migita et al.	N/A	N/A
2011/0257638	12/2010	Boukhny et al.	N/A	N/A
2011/0261079	12/2010	Ingrassia et al.	N/A	N/A
2011/0275940	12/2010	Nims et al.	N/A	N/A
2011/0281249	12/2010	Gammell et al.	N/A	N/A
2011/0306389	12/2010	Nagayama	N/A	N/A
2011/0307821	12/2010	Martens	N/A	N/A
2012/0015778	12/2011	Lee	482/8	G16H 40/63
2012/0015779	12/2011	Powch et al.	N/A	N/A
2012/0022884	12/2011	Chillemi	N/A	N/A
2012/0030623	12/2011	Hoellwarth	N/A	N/A
2012/0034897	12/2011	Kreitzer et al.	N/A	N/A

2012/0041767	12/2011	Hoffman et al.	N/A	N/A
2012/0042039	12/2011	Mark	N/A	N/A
2012/0046784	12/2011	Malina et al.	N/A	N/A
2012/0059664	12/2011	Georgiev et al.	N/A	N/A
2012/0060118	12/2011	Gupta et al.	N/A	N/A
2012/0071770	12/2011	Grey et al.	N/A	N/A
2012/0089419	12/2011	Huster et al.	N/A	N/A
2012/0092379	12/2011	Tsuji et al.	N/A	N/A
2012/0092383	12/2011	Hysek et al.	N/A	N/A
2012/0105225	12/2011	Valtonen	N/A	N/A
2012/0112908	12/2011	Prykaeri et al.	N/A	N/A
2012/0116550	12/2011	Hoffman et al.	N/A	N/A
2012/0116684	12/2011	Ingrassia et al.	N/A	N/A
2012/0119911	12/2011	Jeon et al.	N/A	N/A
2012/0143094	12/2011	Jallon	N/A	N/A
2012/0143095	12/2011	Nakamura	N/A	N/A
2012/0150759	12/2011	Tarjan	N/A	N/A
2012/0159380	12/2011	Kocienda et al.	N/A	N/A
2012/0169882	12/2011	Millar et al.	N/A	N/A
2012/0171649	12/2011	Wander et al.	N/A	N/A
2012/0179278	12/2011	Riley et al.	N/A	N/A
2012/0179319	12/2011	Gilman et al.	N/A	N/A
2012/0203124	12/2011	Lim	N/A	N/A
2012/0209829	12/2011	Thomas et al.	N/A	N/A
2012/0215115	12/2011	Takahashi	N/A	N/A
2012/0215328	12/2011	Schmelzer	N/A	N/A
2012/0232414	12/2011	Mollicone et al.	N/A	N/A
2012/0232929	12/2011	Experton	N/A	N/A
2012/0245447	12/2011	Karan et al.	N/A	N/A
2012/0251079	12/2011	Meschter et al.	N/A	N/A
2012/0253485	12/2011	Weast et al.	N/A	N/A
2012/0253488	12/2011	Shaw et al.	N/A	N/A
2012/0254263	12/2011	Hiestermann et al.	N/A	N/A
2012/0258684	12/2011	Franz et al.	N/A	N/A
2012/0272186	12/2011	Kraut	N/A	N/A
2012/0274508	12/2011	Brown et al.	N/A	N/A
2012/0283524	12/2011	Kiani et al.	N/A	N/A
2012/0283855	12/2011	Hoffman et al.	N/A	N/A
2012/0290109	12/2011	Engelberg et al.	N/A	N/A
2012/0302840	12/2011	Kubo	N/A	N/A
2012/0302843	12/2011	Otsubo et al.	N/A	N/A
2012/0310389	12/2011	Martin	N/A	N/A
2012/0310674	12/2011	Faulkner et al.	N/A	N/A
2012/0313776	12/2011	Utter	N/A	N/A
2012/0317167	12/2011	Rahman et al.	N/A	N/A
2012/0317430	12/2011	Rahman et al.	N/A	N/A
2012/0323129	12/2011	Fujita et al.	N/A	N/A
2012/0326873	12/2011	Utter	N/A	N/A
2013/0011819	12/2012	Horseman	N/A	N/A
2013/0012788	12/2012	Horseman	N/A	N/A
2013/0013331	12/2012	Horseman	N/A	N/A
2013/0053990	12/2012	Ackland	N/A	N/A
2013/0054150	12/2012	Sacks et al.	N/A	N/A
2013/0054720	12/2012	Kang et al.	N/A	N/A
2013/0067050	12/2012	Kotteri et al.	N/A	N/A
2013/0072765	12/2012	Kahn et al.	N/A	N/A
2013/0081083	12/2012	Yu et al.	N/A	N/A
2013/0093715	12/2012	Marsden et al.	N/A	N/A
2013/0095459	12/2012	Tran	N/A	N/A
2013/0106603	12/2012	Weast et al.	N/A	N/A
2013/0106684	12/2012	Weast et al.	N/A	N/A
2013/0110264	12/2012	Weast et al.	N/A	N/A
2013/0115583	12/2012	Gordon et al.	N/A	N/A
2013/0117696	12/2012	Robertson et al.	N/A	N/A
2013/0132028	12/2012	Crankson et al.	N/A	N/A
2013/0137073	12/2012	Nacey et al.	N/A	N/A
2013/0138734	12/2012	Crivello et al.	N/A	N/A
2013/0141233	12/2012	Jacobs et al.	N/A	N/A
2013/0142495	12/2012	Terai	N/A	N/A
2013/0143512	12/2012	Hernandez et al.	N/A	N/A
2013/0144653	12/2012	Poe et al.	N/A	N/A
2013/0151285	12/2012	Mc'Laren et al.	N/A	N/A
2013/0158367	12/2012	Pacione et al.	N/A	N/A
2013/0184613	12/2012	Homsí et al.	N/A	N/A
2013/0185097	12/2012	Saria et al.	N/A	N/A

2013/0187923	12/2012	Yoshimoto et al.	N/A	N/A
2013/0188322	12/2012	Lowe et al.	N/A	N/A
2013/0191034	12/2012	Weast et al.	N/A	N/A
2013/0191647	12/2012	Ferrara et al.	N/A	N/A
2013/0197679	12/2012	Balakrishnan et al.	N/A	N/A
2013/0198672	12/2012	Yoon et al.	N/A	N/A
2013/0203475	12/2012	Shin et al.	N/A	N/A
2013/0209972	12/2012	Carter et al.	N/A	N/A
2013/0215119	12/2012	Vanhoecke	N/A	N/A
2013/0217253	12/2012	Golko et al.	N/A	N/A
2013/0217979	12/2012	Blackadar et al.	N/A	N/A
2013/0223707	12/2012	Stephenson	N/A	N/A
2013/0225118	12/2012	Jang et al.	N/A	N/A
2013/0231575	12/2012	Erkkila et al.	N/A	N/A
2013/0231711	12/2012	Kaib	N/A	N/A
2013/0233097	12/2012	Hayner et al.	N/A	N/A
2013/0238287	12/2012	Hoffman et al.	N/A	N/A
2013/0245966	12/2012	Burroughs et al.	N/A	N/A
2013/0262155	12/2012	Hinkamp	N/A	N/A
2013/0263719	12/2012	Watterson et al.	N/A	N/A
2013/0274904	12/2012	Coza et al.	N/A	N/A
2013/0290013	12/2012	Forrester et al.	N/A	N/A
2013/0295872	12/2012	Guday et al.	N/A	N/A
2013/0310726	12/2012	Miller et al.	N/A	N/A
2013/0324210	12/2012	Doig et al.	N/A	N/A
2013/0325358	12/2012	Oshima et al.	N/A	N/A
2013/0325394	12/2012	Yuen et al.	N/A	N/A
2013/0325396	12/2012	Yuen et al.	N/A	N/A
2013/0325493	12/2012	Wong et al.	N/A	N/A
2013/0325758	12/2012	Alphin et al.	N/A	N/A
2013/0330694	12/2012	Watterson	N/A	N/A
2013/0332286	12/2012	Medelius et al.	N/A	N/A
2013/0345978	12/2012	Lush et al.	N/A	N/A
2014/0005947	12/2013	Jeon et al.	N/A	N/A
2014/0019162	12/2013	Skowronski et al.	N/A	N/A
2014/0035761	12/2013	Burton et al.	N/A	N/A
2014/0037107	12/2013	Marino et al.	N/A	N/A
2014/0038781	12/2013	Foley et al.	N/A	N/A
2014/0039840	12/2013	Yuen et al.	N/A	N/A
2014/0059125	12/2013	Hillier	N/A	N/A
2014/0067096	12/2013	Aibara	N/A	N/A
2014/0073486	12/2013	Ahmed et al.	N/A	N/A
2014/0081666	12/2013	Teller	705/3	G16H 10/60
2014/0088995	12/2013	Damani	N/A	N/A
2014/0089836	12/2013	Damani et al.	N/A	N/A
2014/0100885	12/2013	Stern	N/A	N/A
2014/0107524	12/2013	Brull et al.	N/A	N/A
2014/0108998	12/2013	Chaudhri et al.	N/A	N/A
2014/0127996	12/2013	Park et al.	N/A	N/A
2014/0129007	12/2013	Utter	N/A	N/A
2014/0129243	12/2013	Utter	N/A	N/A
2014/0135955	12/2013	Burroughs	N/A	N/A
2014/0139637	12/2013	Mistry et al.	N/A	N/A
2014/0142403	12/2013	Brumback et al.	N/A	N/A
2014/0143678	12/2013	Mistry et al.	N/A	N/A
2014/0156292	12/2013	Kozicki et al.	N/A	N/A
2014/0164611	12/2013	Molettiere et al.	N/A	N/A
2014/0171266	12/2013	Hawkins et al.	N/A	N/A
2014/0172460	12/2013	Kohli	N/A	N/A
2014/0176335	12/2013	Brumback et al.	N/A	N/A
2014/0176346	12/2013	Brumback et al.	N/A	N/A
2014/0176475	12/2013	Myers et al.	N/A	N/A
2014/0180595	12/2013	Brumback et al.	N/A	N/A
2014/0180786	12/2013	Sullivan	N/A	N/A
2014/0184422	12/2013	Mensing et al.	N/A	N/A
2014/0189584	12/2013	Weng et al.	N/A	N/A
2014/0197946	12/2013	Park et al.	N/A	N/A
2014/0199966	12/2013	Schushan	N/A	N/A
2014/0200426	12/2013	Taub et al.	N/A	N/A
2014/0200691	12/2013	Lee et al.	N/A	N/A
2014/0213415	12/2013	Parker et al.	N/A	N/A
2014/0218369	12/2013	Yuen et al.	N/A	N/A
2014/0221790	12/2013	Pacione et al.	N/A	N/A
2014/0222446	12/2013	Ash et al.	N/A	N/A
2014/0228647	12/2013	Sakamoto et al.	N/A	N/A

2014/0239065	12/2013	Zhou et al.	N/A	N/A
2014/0240122	12/2013	Roberts et al.	N/A	N/A
2014/0240349	12/2013	Tuukkanen	N/A	N/A
2014/0244009	12/2013	Mestas	N/A	N/A
2014/0245161	12/2013	Yuen et al.	N/A	N/A
2014/0257537	12/2013	Stroupe et al.	N/A	N/A
2014/0266731	12/2013	Malhotra	N/A	N/A
2014/0266776	12/2013	Miller et al.	N/A	N/A
2014/0274413	12/2013	Chelst	N/A	N/A
2014/0275852	12/2013	Hong et al.	N/A	N/A
2014/0275854	12/2013	Venkatraman et al.	N/A	N/A
2014/0276119	12/2013	Venkatraman et al.	N/A	N/A
2014/0277628	12/2013	Nieminen et al.	N/A	N/A
2014/0278220	12/2013	Yuen	N/A	N/A
2014/0278229	12/2013	Hong et al.	N/A	N/A
2014/0280498	12/2013	Frankel et al.	N/A	N/A
2014/0282153	12/2013	Christiansen et al.	N/A	N/A
2014/0288680	12/2013	Hoffman et al.	N/A	N/A
2014/0297217	12/2013	Yuen	N/A	N/A
2014/0310598	12/2013	Sprague et al.	N/A	N/A
2014/0310643	12/2013	Karmanenko et al.	N/A	N/A
2014/0331314	12/2013	Fujioka	N/A	N/A
2014/0336796	12/2013	Agnew	N/A	N/A
2014/0337041	12/2013	Madden et al.	N/A	N/A
2014/0337450	12/2013	Choudhary et al.	N/A	N/A
2014/0337451	12/2013	Choudhary et al.	N/A	N/A
2014/0344687	12/2013	Durham et al.	N/A	N/A
2014/0344693	12/2013	Reese et al.	N/A	N/A
2014/0344723	12/2013	Malik et al.	N/A	N/A
2014/0344951	12/2013	Brewer	N/A	N/A
2014/0354494	12/2013	Katz	N/A	N/A
2014/0358473	12/2013	Goel et al.	N/A	N/A
2014/0358584	12/2013	Worden et al.	N/A	N/A
2014/0365913	12/2013	Santamaria et al.	N/A	N/A
2014/0371887	12/2013	Hoffman et al.	N/A	N/A
2015/0004578	12/2014	Gilley et al.	N/A	N/A
2015/0011204	12/2014	Seo et al.	N/A	N/A
2015/0018632	12/2014	Khair	N/A	N/A
2015/0033149	12/2014	Kuchoor	N/A	N/A
2015/0046814	12/2014	Haughay et al.	N/A	N/A
2015/0052618	12/2014	Michalske	N/A	N/A
2015/0057942	12/2014	Self et al.	N/A	N/A
2015/0057943	12/2014	Self et al.	N/A	N/A
2015/0057945	12/2014	White et al.	N/A	N/A
2015/0058093	12/2014	Jakobs	N/A	N/A
2015/0058263	12/2014	Landers	N/A	N/A
2015/0061891	12/2014	Oleson et al.	N/A	N/A
2015/0065095	12/2014	Seo et al.	N/A	N/A
2015/0065302	12/2014	Ou et al.	N/A	N/A
2015/0066172	12/2014	Yi	N/A	N/A
2015/0066521	12/2014	Buckley et al.	N/A	N/A
2015/0067513	12/2014	Zambetti et al.	N/A	N/A
2015/0067811	12/2014	Agnew et al.	N/A	N/A
2015/0074571	12/2014	Marti et al.	N/A	N/A
2015/0080023	12/2014	Yang et al.	N/A	N/A
2015/0081059	12/2014	Hwang et al.	N/A	N/A
2015/0081060	12/2014	Hwang et al.	N/A	N/A
2015/0081529	12/2014	Lee et al.	N/A	N/A
2015/0082167	12/2014	Yeh et al.	N/A	N/A
2015/0083970	12/2014	Koh et al.	N/A	N/A
2015/0089536	12/2014	Byerley	N/A	N/A
2015/0098309	12/2014	Adams et al.	N/A	N/A
2015/0100245	12/2014	Huang et al.	N/A	N/A
2015/0100348	12/2014	Connery et al.	N/A	N/A
2015/0106025	12/2014	Keller et al.	N/A	N/A
2015/0112700	12/2014	Sublett et al.	N/A	N/A
2015/0112990	12/2014	Van Os et al.	N/A	N/A
2015/0113553	12/2014	Pan	N/A	N/A
2015/0118657	12/2014	Shrake et al.	N/A	N/A
2015/0120633	12/2014	Norlander et al.	N/A	N/A
2015/0124067	12/2014	Bala et al.	N/A	N/A
2015/0125832	12/2014	Tran	N/A	N/A
2015/0130830	12/2014	Nagasaki et al.	N/A	N/A
2015/0133748	12/2014	Edmonds et al.	N/A	N/A
2015/0142689	12/2014	Squires	N/A	N/A

2015/0153943	12/2014	Wang	N/A	N/A
2015/0164349	12/2014	Gopalakrishnan et al.	N/A	N/A
2015/0173686	12/2014	Furuta et al.	N/A	N/A
2015/0180746	12/2014	Day et al.	N/A	N/A
2015/0181314	12/2014	Swanson	N/A	N/A
2015/0182843	12/2014	Esposito et al.	N/A	N/A
2015/0185967	12/2014	Ly et al.	N/A	N/A
2015/0186602	12/2014	Pipke et al.	N/A	N/A
2015/0193217	12/2014	Xiang et al.	N/A	N/A
2015/0193805	12/2014	Filipiak	N/A	N/A
2015/0196804	12/2014	Koduri et al.	N/A	N/A
2015/0196805	12/2014	Koduri et al.	N/A	N/A
2015/0199494	12/2014	Koduri et al.	N/A	N/A
2015/0205492	12/2014	Nobil	N/A	N/A
2015/0205930	12/2014	Shaanan et al.	N/A	N/A
2015/0205947	12/2014	Berman et al.	N/A	N/A
2015/0217163	12/2014	Amis et al.	N/A	N/A
2015/0220523	12/2014	Lagree	N/A	N/A
2015/0220883	12/2014	Bfar et al.	N/A	N/A
2015/0230717	12/2014	Wan	N/A	N/A
2015/0248535	12/2014	Cho	N/A	N/A
2015/0251053	12/2014	Hoffman et al.	N/A	N/A
2015/0261918	12/2014	Thornbury, Jr.	N/A	N/A
2015/0262497	12/2014	Landau et al.	N/A	N/A
2015/0262499	12/2014	Wicka et al.	N/A	N/A
2015/0269848	12/2014	Yuen et al.	N/A	N/A
2015/0286800	12/2014	Kanagala et al.	N/A	N/A
2015/0289823	12/2014	Rack-Gomer et al.	N/A	N/A
2015/0293592	12/2014	Cheong et al.	N/A	N/A
2015/0294440	12/2014	Roberts	N/A	N/A
2015/0297134	12/2014	Albert et al.	N/A	N/A
2015/0301691	12/2014	Qin	N/A	N/A
2015/0324751	12/2014	Orenstein et al.	N/A	N/A
2015/0331589	12/2014	Kawakita	N/A	N/A
2015/0334546	12/2014	Diamond	N/A	N/A
2015/0343709	12/2014	Gerstle et al.	N/A	N/A
2015/0347690	12/2014	Keen et al.	N/A	N/A
2015/0347711	12/2014	Soli et al.	N/A	N/A
2015/0350861	12/2014	Soli et al.	N/A	N/A
2015/0351655	12/2014	Coleman	N/A	N/A
2015/0364057	12/2014	Catani et al.	N/A	N/A
2015/0374267	12/2014	Laughlin	N/A	N/A
2015/0374310	12/2014	Lee	N/A	N/A
2016/0000379	12/2015	Pougatchev et al.	N/A	N/A
2016/0004432	12/2015	Bernstein et al.	N/A	N/A
2016/0012294	12/2015	Bouck	N/A	N/A
2016/0015275	12/2015	Samadani et al.	N/A	N/A
2016/0019360	12/2015	Pahwa et al.	N/A	N/A
2016/0027282	12/2015	Lee	N/A	N/A
2016/0034133	12/2015	Wilson et al.	N/A	N/A
2016/0034148	12/2015	Wilson et al.	N/A	N/A
2016/0038038	12/2015	Kovacs	N/A	N/A
2016/0048298	12/2015	Choi et al.	N/A	N/A
2016/0055420	12/2015	Karanam et al.	N/A	N/A
2016/0058331	12/2015	Keen et al.	N/A	N/A
2016/0058336	12/2015	Blahnik et al.	N/A	N/A
2016/0058337	12/2015	Blahnik et al.	N/A	N/A
2016/0062464	12/2015	Moussette et al.	N/A	N/A
2016/0062540	12/2015	Yang et al.	N/A	N/A
2016/0062582	12/2015	Wilson et al.	N/A	N/A
2016/0062589	12/2015	Wan et al.	N/A	N/A
2016/0063215	12/2015	Zamer	N/A	N/A
2016/0063748	12/2015	Kim et al.	N/A	N/A
2016/0065505	12/2015	Iskander	N/A	N/A
2016/0066842	12/2015	Kokkoneva et al.	N/A	N/A
2016/0070275	12/2015	Anderson et al.	N/A	N/A
2016/0072896	12/2015	Petersen et al.	N/A	N/A
2016/0078778	12/2015	Holland	N/A	N/A
2016/0085397	12/2015	Jain	N/A	N/A
2016/0085937	12/2015	Dettinger et al.	N/A	N/A
2016/0086500	12/2015	Kaleal, III	N/A	N/A
2016/0089569	12/2015	Blahnik	N/A	N/A
2016/0098160	12/2015	Groset	N/A	N/A
2016/0098522	12/2015	Weinstein	N/A	N/A
2016/0103970	12/2015	Liu et al.	N/A	N/A

2016/0103985	12/2015	Shim et al.	N/A	N/A
2016/0107031	12/2015	Palatsi et al.	N/A	N/A
2016/0110523	12/2015	Francois	N/A	N/A
2016/0132645	12/2015	Charpentier et al.	N/A	N/A
2016/0135731	12/2015	Drennan	N/A	N/A
2016/0140828	12/2015	Deforest	N/A	N/A
2016/0150978	12/2015	Yuen et al.	N/A	N/A
2016/0156584	12/2015	Hum et al.	N/A	N/A
2016/0166195	12/2015	Radecka et al.	N/A	N/A
2016/0180026	12/2015	Kim et al.	N/A	N/A
2016/0189051	12/2015	Mahmood	N/A	N/A
2016/0193500	12/2015	Webster et al.	N/A	N/A
2016/0196635	12/2015	Cho et al.	N/A	N/A
2016/0196759	12/2015	Kim et al.	N/A	N/A
2016/0196760	12/2015	Koo et al.	N/A	N/A
2016/0199697	12/2015	Orfield	N/A	N/A
2016/0203691	12/2015	Arnold et al.	N/A	N/A
2016/0210099	12/2015	Hampapuram et al.	N/A	N/A
2016/0210434	12/2015	Al-Sharif	N/A	N/A
2016/0210568	12/2015	Krupa et al.	N/A	N/A
2016/0220175	12/2015	Tam et al.	N/A	N/A
2016/0220225	12/2015	Wang et al.	N/A	N/A
2016/0220867	12/2015	Flaherty	N/A	N/A
2016/0235374	12/2015	Miller et al.	N/A	N/A
2016/0246880	12/2015	Battiah et al.	N/A	N/A
2016/0249864	12/2015	Kang et al.	N/A	N/A
2016/0250517	12/2015	Tilvis et al.	N/A	N/A
2016/0256082	12/2015	Ely et al.	N/A	N/A
2016/0256741	12/2015	Holma et al.	N/A	N/A
2016/0263435	12/2015	Venkatraman et al.	N/A	N/A
2016/0270717	12/2015	Luna et al.	N/A	N/A
2016/0270740	12/2015	Raisoni et al.	N/A	N/A
2016/0278659	12/2015	Kaib et al.	N/A	N/A
2016/0278667	12/2015	Villard et al.	N/A	N/A
2016/0279475	12/2015	Aragones et al.	N/A	N/A
2016/0285985	12/2015	Molettiere et al.	N/A	N/A
2016/0287177	12/2015	Huppert et al.	N/A	N/A
2016/0296798	12/2015	Balakrishnan et al.	N/A	N/A
2016/0301794	12/2015	Schlakman et al.	N/A	N/A
2016/0302680	12/2015	Narusawa et al.	N/A	N/A
2016/0302717	12/2015	Tawa et al.	N/A	N/A
2016/0313869	12/2015	Jang et al.	N/A	N/A
2016/0314670	12/2015	Roberts et al.	N/A	N/A
2016/0317341	12/2015	Galvan	N/A	N/A
2016/0321932	12/2015	Mitchell et al.	N/A	N/A
2016/0324457	12/2015	Dagum	N/A	N/A
2016/0324488	12/2015	Olsen	N/A	N/A
2016/0328736	12/2015	Wang et al.	N/A	N/A
2016/0332025	12/2015	Repka	N/A	N/A
2016/0346607	12/2015	Rapfogel	N/A	N/A
2016/0357403	12/2015	Chang et al.	N/A	N/A
2016/0357616	12/2015	Yu et al.	N/A	N/A
2016/0360972	12/2015	Kusakabe et al.	N/A	N/A
2016/0367138	12/2015	Kim et al.	N/A	N/A
2016/0371464	12/2015	Bricker	N/A	N/A
2016/0373631	12/2015	Titi et al.	N/A	N/A
2016/0375306	12/2015	Gu et al.	N/A	N/A
2016/0379511	12/2015	Dawson et al.	N/A	N/A
2017/0000348	12/2016	Karsten et al.	N/A	N/A
2017/0001073	12/2016	Krueger et al.	N/A	N/A
2017/0007882	12/2016	Werner	N/A	N/A
2017/0011210	12/2016	Cheong et al.	N/A	N/A
2017/0014037	12/2016	Coppola et al.	N/A	N/A
2017/0021184	12/2016	Pavel et al.	N/A	N/A
2017/0024399	12/2016	Boyle et al.	N/A	N/A
2017/0024539	12/2016	Webb et al.	N/A	N/A
2017/0032168	12/2016	Kim	N/A	N/A
2017/0039327	12/2016	Bitran et al.	N/A	N/A
2017/0042485	12/2016	Chung et al.	N/A	N/A
2017/0043214	12/2016	Higashi	N/A	N/A
2017/0045866	12/2016	Hou et al.	N/A	N/A
2017/0046052	12/2016	Lee et al.	N/A	N/A
2017/0046108	12/2016	Kang et al.	N/A	N/A
2017/0053542	12/2016	Wilson et al.	N/A	N/A
2017/0056722	12/2016	Singh et al.	N/A	N/A

2017/0061091	12/2016	Mcelhinney et al.	N/A	N/A
2017/0065224	12/2016	Rahko et al.	N/A	N/A
2017/0071551	12/2016	Jain et al.	N/A	N/A
2017/0075551	12/2016	Robinson et al.	N/A	N/A
2017/0076619	12/2016	Wallach et al.	N/A	N/A
2017/0080288	12/2016	Roh et al.	N/A	N/A
2017/0083542	12/2016	Roskowick et al.	N/A	N/A
2017/0087412	12/2016	Blahnik	N/A	N/A
2017/0087469	12/2016	Hardee et al.	N/A	N/A
2017/0095695	12/2016	Mangusson et al.	N/A	N/A
2017/0124276	12/2016	Tee	N/A	N/A
2017/0126510	12/2016	Jones-McFadden et al.	N/A	N/A
2017/0128003	12/2016	Lim	N/A	N/A
2017/0132395	12/2016	Futch	N/A	N/A
2017/0136297	12/2016	Penie	N/A	N/A
2017/0140143	12/2016	Ahmad et al.	N/A	N/A
2017/0143262	12/2016	Kurunmäki et al.	N/A	N/A
2017/0147197	12/2016	Yang et al.	N/A	N/A
2017/0153606	12/2016	Pitis et al.	N/A	N/A
2017/0153804	12/2016	Kim et al.	N/A	N/A
2017/0156593	12/2016	Ferber et al.	N/A	N/A
2017/0161014	12/2016	Kikugawa et al.	N/A	N/A
2017/0161462	12/2016	Parker et al.	N/A	N/A
2017/0177086	12/2016	Yuen et al.	N/A	N/A
2017/0177797	12/2016	Kurniawan et al.	N/A	N/A
2017/0181645	12/2016	Mahalingam et al.	N/A	N/A
2017/0188893	12/2016	Venkatraman et al.	N/A	N/A
2017/0209766	12/2016	Riley et al.	N/A	N/A
2017/0213001	12/2016	Harrison	N/A	N/A
2017/0225034	12/2016	Kass et al.	N/A	N/A
2017/0237694	12/2016	Choudhary et al.	N/A	N/A
2017/0239524	12/2016	Lee et al.	N/A	N/A
2017/0239525	12/2016	Kim et al.	N/A	N/A
2017/0243508	12/2016	Cheng et al.	N/A	N/A
2017/0249417	12/2016	Gosieski et al.	N/A	N/A
2017/0255169	12/2016	Lee et al.	N/A	N/A
2017/0266494	12/2016	Crankson et al.	N/A	N/A
2017/0266531	12/2016	Elford et al.	N/A	N/A
2017/0269792	12/2016	Xu et al.	N/A	N/A
2017/0274149	12/2016	Aeschlimann	N/A	N/A
2017/0274267	12/2016	Blahnik	N/A	N/A
2017/0281026	12/2016	Nick et al.	N/A	N/A
2017/0281057	12/2016	Blahnik et al.	N/A	N/A
2017/0294174	12/2016	Albadawi et al.	N/A	N/A
2017/0300186	12/2016	Kuhar et al.	N/A	N/A
2017/0300643	12/2016	Bezark et al.	N/A	N/A
2017/0301039	12/2016	Dyer et al.	N/A	N/A
2017/0319941	12/2016	Smith et al.	N/A	N/A
2017/0329933	12/2016	Brust et al.	N/A	N/A
2017/0330297	12/2016	Cronin et al.	N/A	N/A
2017/0332980	12/2016	Fifield et al.	N/A	N/A
2017/0333752	12/2016	Korkala et al.	N/A	N/A
2017/0337033	12/2016	Duyan et al.	N/A	N/A
2017/0348562	12/2016	Jung et al.	N/A	N/A
2017/0348576	12/2016	Pajonk-Taylor	N/A	N/A
2017/0352287	12/2016	Arnold et al.	N/A	N/A
2017/0354845	12/2016	Williams et al.	N/A	N/A
2017/0357520	12/2016	De Vries et al.	N/A	N/A
2017/0359623	12/2016	Folse et al.	N/A	N/A
2017/0364637	12/2016	Kshepakaran et al.	N/A	N/A
2018/0000426	12/2017	Li	N/A	N/A
2018/0001184	12/2017	Tran et al.	N/A	N/A
2018/0032234	12/2017	Michalske	N/A	N/A
2018/0036591	12/2017	King et al.	N/A	N/A
2018/0042559	12/2017	Cabrera et al.	N/A	N/A
2018/0053200	12/2017	Cronin et al.	N/A	N/A
2018/0056130	12/2017	Bitran et al.	N/A	N/A
2018/0056132	12/2017	Foley et al.	N/A	N/A
2018/0064388	12/2017	Heneghan et al.	N/A	N/A
2018/0065025	12/2017	Toda et al.	N/A	N/A
2018/0070861	12/2017	Eastman et al.	N/A	N/A
2018/0074462	12/2017	Helder et al.	N/A	N/A
2018/0074464	12/2017	Essery et al.	N/A	N/A
2018/0078182	12/2017	Chen et al.	N/A	N/A
2018/0078197	12/2017	Ware et al.	N/A	N/A

2018/0081918	12/2017	Gravenites et al.	N/A	N/A
2018/0085058	12/2017	Chakravarthi et al.	N/A	N/A
2018/0107962	12/2017	Lundin et al.	N/A	N/A
2018/0110465	12/2017	Naima	N/A	N/A
2018/0117414	12/2017	Miyasaka et al.	N/A	N/A
2018/0120985	12/2017	Wallace et al.	N/A	N/A
2018/0121040	12/2017	Liu	N/A	N/A
2018/0126248	12/2017	Dion et al.	N/A	N/A
2018/0132768	12/2017	Sasahara et al.	N/A	N/A
2018/0133537	12/2017	Montantes	N/A	N/A
2018/0137937	12/2017	Gass et al.	N/A	N/A
2018/0140211	12/2017	Nakazawa et al.	N/A	N/A
2018/0140903	12/2017	Poure et al.	N/A	N/A
2018/0140927	12/2017	Kito et al.	N/A	N/A
2018/0150709	12/2017	Ha	N/A	N/A
2018/0154212	12/2017	Park et al.	N/A	N/A
2018/0177437	12/2017	Yoshioka	N/A	N/A
2018/0182491	12/2017	Belliveau et al.	N/A	N/A
2018/0189077	12/2017	Gupta et al.	N/A	N/A
2018/0189343	12/2017	Embiricos et al.	N/A	N/A
2018/0206786	12/2017	Blahnik et al.	N/A	N/A
2018/0211020	12/2017	Fukuda	N/A	N/A
2018/0232494	12/2017	Leppala et al.	N/A	N/A
2018/0239869	12/2017	Laing et al.	N/A	N/A
2018/0247706	12/2017	Riley et al.	N/A	N/A
2018/0256036	12/2017	Kogure et al.	N/A	N/A
2018/0256078	12/2017	Vaterlaus	N/A	N/A
2018/0256095	12/2017	Arnold et al.	N/A	N/A
2018/0263510	12/2017	Cronin et al.	N/A	N/A
2018/0263517	12/2017	Kubo	N/A	N/A
2018/0272190	12/2017	Miura et al.	N/A	N/A
2018/0279885	12/2017	Bulut	N/A	N/A
2018/0294053	12/2017	Runyon et al.	N/A	N/A
2018/0300037	12/2017	Takeda et al.	N/A	N/A
2018/0316964	12/2017	Dillon et al.	N/A	N/A
2018/0318647	12/2017	Foley et al.	N/A	N/A
2018/0329584	12/2017	Williams et al.	N/A	N/A
2018/0336530	12/2017	Johnson et al.	N/A	N/A
2018/0339195	12/2017	Bernotas	N/A	N/A
2018/0345078	12/2017	Blahnik et al.	N/A	N/A
2018/0350453	12/2017	Nag et al.	N/A	N/A
2018/0364648	12/2017	Chi et al.	N/A	N/A
2018/0367484	12/2017	Rodriguez et al.	N/A	N/A
2018/0376107	12/2017	Shibaev et al.	N/A	N/A
2019/0008394	12/2018	Rao et al.	N/A	N/A
2019/0008467	12/2018	Averina et al.	N/A	N/A
2019/0014205	12/2018	Miloseski et al.	N/A	N/A
2019/0018588	12/2018	Debates et al.	N/A	N/A
2019/0025995	12/2018	Williams	N/A	N/A
2019/0026011	12/2018	Wang et al.	N/A	N/A
2019/0034049	12/2018	Williams et al.	N/A	N/A
2019/0034050	12/2018	Williams et al.	N/A	N/A
2019/0034494	12/2018	Bradley et al.	N/A	N/A
2019/0057306	12/2018	Xue et al.	N/A	N/A
2019/0089701	12/2018	Mercury et al.	N/A	N/A
2019/0090800	12/2018	Bosworth et al.	N/A	N/A
2019/0090816	12/2018	Horseman	N/A	N/A
2019/0102049	12/2018	Anzures et al.	N/A	N/A
2019/0104951	12/2018	Valys et al.	N/A	N/A
2019/0108908	12/2018	Faulks et al.	N/A	N/A
2019/0122523	12/2018	Roberts et al.	N/A	N/A
2019/0126099	12/2018	Hoang	N/A	N/A
2019/0138696	12/2018	Carpenter et al.	N/A	N/A
2019/0141418	12/2018	Harma et al.	N/A	N/A
2019/0143194	12/2018	Evancho et al.	N/A	N/A
2019/0150854	12/2018	Chung et al.	N/A	N/A
2019/0184234	12/2018	Packles et al.	N/A	N/A
2019/0192086	12/2018	Menon et al.	N/A	N/A
2019/0206538	12/2018	Xing et al.	N/A	N/A
2019/0209777	12/2018	O'Connell et al.	N/A	N/A
2019/0228179	12/2018	Rakshit et al.	N/A	N/A
2019/0228847	12/2018	Soli	N/A	N/A
2019/0232110	12/2018	Williams et al.	N/A	N/A
2019/0232111	12/2018	Williams et al.	N/A	N/A
2019/0240534	12/2018	Black	N/A	N/A

2019/0240536	12/2018	Dibenedetto et al.	N/A	N/A
2019/0240537	12/2018	Hisada et al.	N/A	N/A
2019/0252054	12/2018	Dirani et al.	N/A	N/A
2019/0274563	12/2018	Soli et al.	N/A	N/A
2019/0274565	12/2018	Soli et al.	N/A	N/A
2019/0279520	12/2018	Wilson et al.	N/A	N/A
2019/0298230	12/2018	Nicholson et al.	N/A	N/A
2019/0302995	12/2018	Robinson et al.	N/A	N/A
2019/0336044	12/2018	Williams et al.	N/A	N/A
2019/0336045	12/2018	Williams et al.	N/A	N/A
2019/0336827	12/2018	Intonato et al.	N/A	N/A
2019/0339849	12/2018	Williams et al.	N/A	N/A
2019/0339860	12/2018	Chen et al.	N/A	N/A
2019/0342616	12/2018	Domm et al.	N/A	N/A
2019/0364120	12/2018	Bandela et al.	N/A	N/A
2019/0365332	12/2018	Fedichev et al.	N/A	N/A
2019/0380624	12/2018	Ota et al.	N/A	N/A
2019/0380653	12/2018	Benson et al.	N/A	N/A
2019/0385708	12/2018	Hong et al.	N/A	N/A
2019/0387982	12/2018	Buller	N/A	N/A
2020/0014967	12/2019	Putnam	N/A	N/A
2020/0026398	12/2019	Kim	N/A	N/A
2020/0054931	12/2019	Martin et al.	N/A	N/A
2020/0069258	12/2019	Grinberg	N/A	N/A
2020/0098278	12/2019	Doti et al.	N/A	N/A
2020/0100693	12/2019	Velo	N/A	N/A
2020/0101365	12/2019	Wilson et al.	N/A	N/A
2020/0110814	12/2019	Abuelsaad et al.	N/A	N/A
2020/0126673	12/2019	Tanabe et al.	N/A	N/A
2020/0149921	12/2019	Hoffman et al.	N/A	N/A
2020/0152305	12/2019	Pelliccioni et al.	N/A	N/A
2020/0160961	12/2019	Wadhawan et al.	N/A	N/A
2020/0203012	12/2019	Kamath et al.	N/A	N/A
2020/0214650	12/2019	Lee et al.	N/A	N/A
2020/0245928	12/2019	Kang et al.	N/A	N/A
2020/0249632	12/2019	Olwal et al.	N/A	N/A
2020/0261011	12/2019	Seppänen et al.	N/A	N/A
2020/0261763	12/2019	Park et al.	N/A	N/A
2020/0273566	12/2019	Bhowmik et al.	N/A	N/A
2020/0276475	12/2019	Casalini	N/A	N/A
2020/0289919	12/2019	Gruben	N/A	N/A
2020/0297249	12/2019	Williams et al.	N/A	N/A
2020/0323441	12/2019	Deno et al.	N/A	N/A
2020/0341610	12/2019	Quintana et al.	N/A	N/A
2020/0356242	12/2019	Wilson et al.	N/A	N/A
2020/0356687	12/2019	Salzman et al.	N/A	N/A
2020/0357522	12/2019	Pahwa et al.	N/A	N/A
2020/0359913	12/2019	Ghodrati et al.	N/A	N/A
2020/0366386	12/2019	Bugos et al.	N/A	N/A
2020/0374682	12/2019	Newman et al.	N/A	N/A
2020/0381099	12/2019	Crowley et al.	N/A	N/A
2020/0381100	12/2019	Williams et al.	N/A	N/A
2020/0382613	12/2019	Sundstrom et al.	N/A	N/A
2020/0384314	12/2019	Lee et al.	N/A	N/A
2021/0001226	12/2020	Suzuki et al.	N/A	N/A
2021/0007632	12/2020	Blahnik et al.	N/A	N/A
2021/0007633	12/2020	Blahnik et al.	N/A	N/A
2021/0008413	12/2020	Asikainen et al.	N/A	N/A
2021/0035674	12/2020	Volosin et al.	N/A	N/A
2021/0042132	12/2020	Park et al.	N/A	N/A
2021/0093919	12/2020	Lyke et al.	N/A	N/A
2021/0101052	12/2020	Gore	N/A	N/A
2021/0110908	12/2020	Blahnik et al.	N/A	N/A
2021/0113116	12/2020	Chen et al.	N/A	N/A
2021/0113137	12/2020	Soli et al.	N/A	N/A
2021/0145321	12/2020	Chen et al.	N/A	N/A
2021/0191584	12/2020	Williams et al.	N/A	N/A
2021/0193293	12/2020	Blahnik et al.	N/A	N/A
2021/0204815	12/2020	Koskela et al.	N/A	N/A
2021/0210182	12/2020	Nag et al.	N/A	N/A
2021/0225482	12/2020	Crowley et al.	N/A	N/A
2021/0236903	12/2020	Briel	N/A	N/A
2021/0252337	12/2020	Devine et al.	N/A	N/A
2021/0252341	12/2020	Devine et al.	N/A	N/A
2021/0252369	12/2020	Devine et al.	N/A	N/A

2021/0255747	12/2020	Devine et al.	N/A	N/A
2021/0255758	12/2020	Devine et al.	N/A	N/A
2021/0255826	12/2020	Devine et al.	N/A	N/A
2021/0294438	12/2020	Yang et al.	N/A	N/A
2021/0316185	12/2020	Mckenna et al.	N/A	N/A
2021/0350900	12/2020	Blahnik et al.	N/A	N/A
2021/0352118	12/2020	Ahn et al.	N/A	N/A
2021/0366608	12/2020	Podobas et al.	N/A	N/A
2021/0369130	12/2020	Felton et al.	N/A	N/A
2021/0373746	12/2020	Felton et al.	N/A	N/A
2021/0373747	12/2020	Felton et al.	N/A	N/A
2021/0373748	12/2020	Felton et al.	N/A	N/A
2021/0375450	12/2020	Felton et al.	N/A	N/A
2021/0379447	12/2020	Lee	N/A	N/A
2021/0394020	12/2020	Killen et al.	N/A	N/A
2022/0047212	12/2021	Balsamo et al.	N/A	N/A
2022/0047918	12/2021	Williams et al.	N/A	N/A
2022/0062707	12/2021	Bedekar et al.	N/A	N/A
2022/0066902	12/2021	Narra et al.	N/A	N/A
2022/0121299	12/2021	De Vries et al.	N/A	N/A
2022/0157143	12/2021	Panneer Selvam et al.	N/A	N/A
2022/0157184	12/2021	Wilson et al.	N/A	N/A
2022/0160258	12/2021	Williams et al.	N/A	N/A
2022/0180980	12/2021	Alencar et al.	N/A	N/A
2022/0262485	12/2021	Meschter et al.	N/A	N/A
2022/0262509	12/2021	Pahwa et al.	N/A	N/A
2022/0287629	12/2021	Forsyth et al.	N/A	N/A
2022/0328161	12/2021	Gilravi et al.	N/A	N/A
2022/0336077	12/2021	Chen et al.	N/A	N/A
2022/0386901	12/2021	Chen et al.	N/A	N/A
2023/0012755	12/2022	D'auria et al.	N/A	N/A
2023/0013809	12/2022	D'auria et al.	N/A	N/A
2023/0013932	12/2022	Blahnik et al.	N/A	N/A
2023/0014053	12/2022	Devine et al.	N/A	N/A
2023/0014290	12/2022	Davydov et al.	N/A	N/A
2023/0017793	12/2022	Williams et al.	N/A	N/A
2023/0019337	12/2022	D'auria et al.	N/A	N/A
2023/0024084	12/2022	D'auria et al.	N/A	N/A
2023/0025724	12/2022	Gilravi et al.	N/A	N/A
2023/0027358	12/2022	Williams et al.	N/A	N/A
2023/0066552	12/2022	Van Os et al.	N/A	N/A
2023/0079396	12/2022	Sokolowski	N/A	N/A
2023/0107803	12/2022	Dugan	N/A	N/A
2023/0114054	12/2022	Crowley et al.	N/A	N/A
2023/0119253	12/2022	Sundstrom et al.	N/A	N/A
2023/0136700	12/2022	Williams et al.	N/A	N/A
2023/0191198	12/2022	Lee et al.	N/A	N/A
2023/0260416	12/2022	Wilson et al.	N/A	N/A
2023/0310935	12/2022	Su et al.	N/A	N/A
2023/0390606	12/2022	Bolton et al.	N/A	N/A
2023/0390626	12/2022	Bolton et al.	N/A	N/A
2023/0390627	12/2022	Bolton et al.	N/A	N/A
2023/0393723	12/2022	Arney et al.	N/A	N/A
2024/0013889	12/2023	Crowley et al.	N/A	N/A
2024/0077309	12/2023	Felton et al.	N/A	N/A
2024/0081751	12/2023	Murphy et al.	N/A	N/A
2024/0139608	12/2023	Bolton et al.	N/A	N/A
2024/0256115	12/2023	Arney et al.	N/A	N/A
2024/0257940	12/2023	Williams et al.	N/A	N/A
2024/0257986	12/2023	Damani et al.	N/A	N/A
2024/0306941	12/2023	Williams et al.	N/A	N/A
2024/0316404	12/2023	Williams et al.	N/A	N/A
2024/0325821	12/2023	Yu	N/A	N/A
2024/0366111	12/2023	Chen et al.	N/A	N/A
2024/0370137	12/2023	Williams et al.	N/A	N/A
2024/0397323	12/2023	Devine et al.	N/A	N/A
2024/0399208	12/2023	Mikolay et al.	N/A	N/A
2024/0399209	12/2023	Mikolay et al.	N/A	N/A
2024/0402880	12/2023	Lareau et al.	N/A	N/A
2024/0402881	12/2023	Bignell et al.	N/A	N/A
2025/0022570	12/2024	Blahnik et al.	N/A	N/A
2025/0032886	12/2024	Chao et al.	N/A	N/A
2025/0117127	12/2024	Arney et al.	N/A	N/A
2025/0153004	12/2024	Williams et al.	N/A	N/A
2025/0157646	12/2024	Mistri et al.	N/A	N/A

2025/0166759	12/2024	Soli	N/A	N/A
2025/0174142	12/2024	Wilson et al.	N/A	N/A
2025/0195954	12/2024	D'Auria et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2011302438	12/2012	AU	N/A
2815518	12/2011	CA	N/A
2826239	12/2016	CA	N/A
1337638	12/2001	CN	N/A
1397904	12/2002	CN	N/A
1443427	12/2002	CN	N/A
1523500	12/2003	CN	N/A
1585943	12/2004	CN	N/A
1628609	12/2004	CN	N/A
1767789	12/2005	CN	N/A
1824358	12/2005	CN	N/A
1997050	12/2006	CN	N/A
101061484	12/2006	CN	N/A
101150810	12/2007	CN	N/A
101219046	12/2007	CN	N/A
101444419	12/2008	CN	N/A
101541387	12/2008	CN	N/A
101651870	12/2009	CN	N/A
101658423	12/2009	CN	N/A
101668482	12/2009	CN	N/A
101836894	12/2009	CN	N/A
101890217	12/2009	CN	N/A
101894206	12/2009	CN	N/A
101910992	12/2009	CN	N/A
101978374	12/2010	CN	N/A
102339201	12/2011	CN	N/A
102438521	12/2011	CN	N/A
102448555	12/2011	CN	N/A
102449560	12/2011	CN	N/A
102449561	12/2011	CN	N/A
102449566	12/2011	CN	N/A
102549590	12/2011	CN	N/A
102804238	12/2011	CN	N/A
102814037	12/2011	CN	N/A
102834079	12/2011	CN	N/A
102989159	12/2012	CN	N/A
103003668	12/2012	CN	N/A
103154954	12/2012	CN	N/A
103182175	12/2012	CN	N/A
103210355	12/2012	CN	N/A
103212197	12/2012	CN	N/A
103270540	12/2012	CN	N/A
103294124	12/2012	CN	N/A
103297610	12/2012	CN	N/A
103370924	12/2012	CN	N/A
103403627	12/2012	CN	N/A
203276086	12/2012	CN	N/A
103561640	12/2013	CN	N/A
103581456	12/2013	CN	N/A
103646570	12/2013	CN	N/A
103682785	12/2013	CN	N/A
103701504	12/2013	CN	N/A
103876721	12/2013	CN	N/A
104122994	12/2013	CN	N/A
104288983	12/2014	CN	N/A
104464010	12/2014	CN	N/A
104501043	12/2014	CN	N/A
104508426	12/2014	CN	N/A
104815428	12/2014	CN	N/A
104857692	12/2014	CN	N/A
104917794	12/2014	CN	N/A
105187282	12/2014	CN	N/A
105260078	12/2015	CN	N/A
105320454	12/2015	CN	N/A
105388998	12/2015	CN	N/A
105392064	12/2015	CN	N/A
105681328	12/2015	CN	N/A
105721667	12/2015	CN	N/A
105808959	12/2015	CN	N/A

106310638	12/2016	CN	N/A
106415559	12/2016	CN	N/A
106510719	12/2016	CN	N/A
106537397	12/2016	CN	N/A
106709235	12/2016	CN	N/A
106878550	12/2016	CN	N/A
107469327	12/2016	CN	N/A
107545930	12/2017	CN	N/A
107580776	12/2017	CN	N/A
107749310	12/2017	CN	N/A
107921317	12/2017	CN	N/A
108200464	12/2017	CN	N/A
108211310	12/2017	CN	N/A
108604327	12/2017	CN	N/A
110456971	12/2018	CN	N/A
110517749	12/2018	CN	N/A
111796657	12/2019	CN	N/A
0943290	12/1998	EP	N/A
1559372	12/2004	EP	N/A
1935339	12/2007	EP	N/A
1938233	12/2007	EP	N/A
2025368	12/2008	EP	N/A
1964022	12/2009	EP	N/A
2309475	12/2010	EP	N/A
2407219	12/2011	EP	N/A
2529663	12/2011	EP	N/A
2568409	12/2012	EP	N/A
2631830	12/2012	EP	N/A
2632139	12/2012	EP	N/A
2728680	12/2013	EP	N/A
2733578	12/2013	EP	N/A
2921899	12/2014	EP	N/A
2993602	12/2015	EP	N/A
3096235	12/2015	EP	N/A
3101882	12/2015	EP	N/A
3117767	12/2016	EP	N/A
3122038	12/2016	EP	N/A
3130997	12/2016	EP	N/A
3132740	12/2016	EP	N/A
3557590	12/2018	EP	N/A
3739439	12/2022	EP	N/A
5-288869	12/1992	JP	N/A
6-187118	12/1993	JP	N/A
8-126632	12/1995	JP	N/A
11-84030	12/1998	JP	N/A
2001-76078	12/2000	JP	N/A
2001-216336	12/2000	JP	N/A
2001-325372	12/2000	JP	N/A
2002-190007	12/2001	JP	N/A
2002-346013	12/2001	JP	N/A
2003-16185	12/2002	JP	N/A
2003-102868	12/2002	JP	N/A
2003-126291	12/2002	JP	N/A
2003-131655	12/2002	JP	N/A
2003-157323	12/2002	JP	N/A
2003-216739	12/2002	JP	N/A
2003-248721	12/2002	JP	N/A
2003-319912	12/2002	JP	N/A
2003-330763	12/2002	JP	N/A
2003-337863	12/2002	JP	N/A
2004-102609	12/2003	JP	N/A
2004-113466	12/2003	JP	N/A
2004-174006	12/2003	JP	N/A
2004-364184	12/2003	JP	N/A
2005-79814	12/2004	JP	N/A
3635663	12/2004	JP	N/A
2005-352766	12/2004	JP	N/A
2006-107134	12/2005	JP	N/A
2006-155104	12/2005	JP	N/A
2006-180899	12/2005	JP	N/A
2006-230679	12/2005	JP	N/A
3830956	12/2005	JP	N/A
2006-338233	12/2005	JP	N/A
2007-199819	12/2006	JP	N/A
2007-260288	12/2006	JP	N/A

2007-330513	12/2006	JP	N/A
2008-104758	12/2007	JP	N/A
2008-183339	12/2007	JP	N/A
2008-272301	12/2007	JP	N/A
2008-305358	12/2007	JP	N/A
2009-50471	12/2008	JP	N/A
2009-68265	12/2008	JP	N/A
2009-78134	12/2008	JP	N/A
2009-88989	12/2008	JP	N/A
2009-112731	12/2008	JP	N/A
2009-211241	12/2008	JP	N/A
2009-282670	12/2008	JP	N/A
2010-12335	12/2009	JP	N/A
2010-88886	12/2009	JP	N/A
2010-108145	12/2009	JP	N/A
2010-517725	12/2009	JP	N/A
2010-122901	12/2009	JP	N/A
2010-162297	12/2009	JP	N/A
2010-181280	12/2009	JP	N/A
2010-182287	12/2009	JP	N/A
2010-186249	12/2009	JP	N/A
2010-206668	12/2009	JP	N/A
2011-514192	12/2010	JP	N/A
2011-12-5633	12/2010	JP	N/A
2011-183101	12/2010	JP	N/A
2011-192126	12/2010	JP	N/A
2011-525414	12/2010	JP	N/A
2011-525648	12/2010	JP	N/A
2011-198184	12/2010	JP	N/A
2011-200575	12/2010	JP	N/A
2011-206323	12/2010	JP	N/A
2011-210119	12/2010	JP	N/A
2011-229141	12/2010	JP	N/A
2011-259253	12/2010	JP	N/A
2012-20134	12/2011	JP	N/A
2012-35071	12/2011	JP	N/A
2012-45373	12/2011	JP	N/A
2012-59264	12/2011	JP	N/A
2012-86088	12/2011	JP	N/A
2012-524640	12/2011	JP	N/A
2012-230503	12/2011	JP	N/A
2012-232114	12/2011	JP	N/A
2012-239808	12/2011	JP	N/A
2012-533117	12/2011	JP	N/A
2013-78593	12/2012	JP	N/A
2013-103020	12/2012	JP	N/A
2013-117690	12/2012	JP	N/A
2013-146557	12/2012	JP	N/A
2013-530776	12/2012	JP	N/A
2013-192608	12/2012	JP	N/A
2013-543156	12/2012	JP	N/A
5346115	12/2012	JP	N/A
2013-544140	12/2012	JP	N/A
2014-500740	12/2013	JP	N/A
2014-45782	12/2013	JP	N/A
2014-45783	12/2013	JP	N/A
2014-104139	12/2013	JP	N/A
2014-123169	12/2013	JP	N/A
2014-143473	12/2013	JP	N/A
2014-519126	12/2013	JP	N/A
2014-168685	12/2013	JP	N/A
2014-171831	12/2013	JP	N/A
2014-216001	12/2013	JP	N/A
2014-230630	12/2013	JP	N/A
2015-58218	12/2014	JP	N/A
2015-507811	12/2014	JP	N/A
2015-509019	12/2014	JP	N/A
2015-69430	12/2014	JP	N/A
2015-509755	12/2014	JP	N/A
2015-515287	12/2014	JP	N/A
2015-134111	12/2014	JP	N/A
2015-531916	12/2014	JP	N/A
2015-213686	12/2014	JP	N/A
2016-17331	12/2015	JP	N/A
2016-21175	12/2015	JP	N/A

2016-502875	12/2015	JP	N/A
2016-52512	12/2015	JP	N/A
2016-517329	12/2015	JP	N/A
2016-158867	12/2015	JP	N/A
2016-528016	12/2015	JP	N/A
2016-177151	12/2015	JP	N/A
2016-185288	12/2015	JP	N/A
2016-202751	12/2015	JP	N/A
2016-538926	12/2015	JP	N/A
2017-503264	12/2016	JP	N/A
2017-83978	12/2016	JP	N/A
2017-117265	12/2016	JP	N/A
2017-515520	12/2016	JP	N/A
2017-134689	12/2016	JP	N/A
2017-521804	12/2016	JP	N/A
2017-156267	12/2016	JP	N/A
2017-526073	12/2016	JP	N/A
2017-182393	12/2016	JP	N/A
2017-529880	12/2016	JP	N/A
2017-531235	12/2016	JP	N/A
2017-211994	12/2016	JP	N/A
2017-532069	12/2016	JP	N/A
2018-504660	12/2017	JP	N/A
2018-102908	12/2017	JP	N/A
201-8523554	12/2017	JP	N/A
6382433	12/2017	JP	N/A
2018-202174	12/2017	JP	N/A
2019-3670	12/2018	JP	N/A
2019-28806	12/2018	JP	N/A
2019-32461	12/2018	JP	N/A
2019-505035	12/2018	JP	N/A
2019-55076	12/2018	JP	N/A
2019-63558	12/2018	JP	N/A
2019-197521	12/2018	JP	N/A
2019-207536	12/2018	JP	N/A
2000-0076025	12/1999	KR	N/A
2003-0070871	12/2002	KR	N/A
10-2006-0117570	12/2005	KR	N/A
10-2011-0017076	12/2010	KR	N/A
10-2011-0121394	12/2010	KR	N/A
10-2012-0023657	12/2011	KR	N/A
10-2012-0076559	12/2011	KR	N/A
10-2012-0098854	12/2011	KR	N/A
10-2012-0132732	12/2011	KR	N/A
10-2013-0043698	12/2012	KR	N/A
10-2013-0097235	12/2012	KR	N/A
10-2013-0111569	12/2012	KR	N/A
10-2013-0111570	12/2012	KR	N/A
10-2013-0135282	12/2012	KR	N/A
10-2014-0147563	12/2013	KR	N/A
10-2015-0026635	12/2014	KR	N/A
10-2015-0062761	12/2014	KR	N/A
10-2016-0027943	12/2015	KR	N/A
10-2016-0028351	12/2015	KR	N/A
10-2016-0076264	12/2015	KR	N/A
10-2016-0077199	12/2015	KR	N/A
10-2016-0084705	12/2015	KR	N/A
10-2016-0105129	12/2015	KR	N/A
10-2016-0142418	12/2015	KR	N/A
10-2017-0003608	12/2016	KR	N/A
10-2017-0019040	12/2016	KR	N/A
10-2017-0019745	12/2016	KR	N/A
10-2017-0020085	12/2016	KR	N/A
10-2017-0029014	12/2016	KR	N/A
10-2017-0032471	12/2016	KR	N/A
10-2017-0056300	12/2016	KR	N/A
10-2018-0026066	12/2017	KR	N/A
10-2018-0129188	12/2017	KR	N/A
10-2019-0022883	12/2018	KR	N/A
10-2019-0081500	12/2018	KR	N/A
10-2019-0129850	12/2018	KR	N/A
10-2019-0141702	12/2018	KR	N/A
201210368	12/2011	TW	N/A
201240499	12/2011	TW	N/A
97/06492	12/1996	WO	N/A

97/38626	12/1996	WO	N/A
98/38909	12/1997	WO	N/A
99/41682	12/1998	WO	N/A
02/27530	12/2001	WO	N/A
02/41134	12/2001	WO	N/A
2004/047440	12/2003	WO	N/A
2005/029242	12/2004	WO	N/A
2005/070289	12/2004	WO	N/A
2006/103965	12/2005	WO	N/A
2007/081629	12/2006	WO	N/A
2009/129402	12/2008	WO	N/A
2009/152608	12/2008	WO	N/A
2010/126821	12/2009	WO	N/A
2010/128825	12/2009	WO	N/A
2010/129221	12/2009	WO	N/A
2011/072111	12/2010	WO	N/A
2011/108335	12/2010	WO	N/A
2012/021507	12/2011	WO	N/A
2012/036891	12/2011	WO	N/A
2012/061438	12/2011	WO	N/A
2012/061440	12/2011	WO	N/A
2012/078079	12/2011	WO	N/A
2012/086910	12/2011	WO	N/A
2012/095712	12/2011	WO	N/A
2012/127484	12/2011	WO	N/A
2012/170446	12/2011	WO	N/A
2013/052789	12/2012	WO	N/A
2013/109762	12/2012	WO	N/A
2013/109776	12/2012	WO	N/A
2013/109777	12/2012	WO	N/A
2013/109916	12/2012	WO	N/A
2013/157307	12/2012	WO	N/A
2013/169870	12/2012	WO	N/A
2013/173838	12/2012	WO	N/A
2014/006862	12/2013	WO	N/A
2014/022711	12/2013	WO	N/A
2014/059259	12/2013	WO	N/A
2014/105276	12/2013	WO	N/A
2014/144258	12/2013	WO	N/A
2014/200730	12/2013	WO	N/A
2014/207294	12/2013	WO	N/A
2014/207875	12/2013	WO	N/A
2015/27133	12/2014	WO	N/A
2015/027178	12/2014	WO	N/A
2015/84353	12/2014	WO	N/A
2015/091228	12/2014	WO	N/A
2015/179592	12/2014	WO	N/A
2015/183756	12/2014	WO	N/A
2015/183828	12/2014	WO	N/A
2015/198488	12/2014	WO	N/A
2016/22203	12/2015	WO	N/A
2016/25036	12/2015	WO	N/A
2016/36472	12/2015	WO	N/A
2016/36582	12/2015	WO	N/A
2016/36582	12/2015	WO	N/A
2017/013770	12/2016	WO	N/A
2017/14403	12/2016	WO	N/A
2017/30646	12/2016	WO	N/A
2017/37242	12/2016	WO	N/A
2017/172046	12/2016	WO	N/A
2017/193515	12/2016	WO	N/A
2018/048510	12/2017	WO	N/A
2018/213066	12/2017	WO	N/A
2018/222313	12/2017	WO	N/A
2018/236291	12/2017	WO	N/A
2019/017508	12/2018	WO	N/A
2019/024383	12/2018	WO	N/A
2019/024603	12/2018	WO	N/A
2019/183422	12/2018	WO	N/A
2019/190001	12/2018	WO	N/A
2019/217005	12/2018	WO	N/A
2019/217009	12/2018	WO	N/A
2019/217249	12/2018	WO	N/A
2019/231982	12/2018	WO	N/A
2019/240513	12/2018	WO	N/A

OTHER PUBLICATIONS

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/210,920, mailed on Jul. 3, 2024, 4 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/951,945, mailed on Jul. 9, 2024, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 18/135,056, mailed on Jul. 17, 2024, 6 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 18/135,056, mailed on Jul. 22, 2024, 3 pages. cited by applicant

Decision to Grant received for European Patent Application No. 21714460.9, mailed on Jun. 20, 2024, 4 pages. cited by applicant

Intention to Grant received for European Patent Application No. 23153898.4, mailed on Jul. 2, 2024, 11 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/031,723, mailed on Jul. 22, 2024, 14 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/210,920, mailed on Aug. 1, 2024, 17 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 202210326960.1, mailed on Jun. 21, 2024, 5 pages (1 page of English Translation and 4 pages of Official Copy). cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2023-7025320, mailed on Jul. 31, 2024, 7 pages (2 pages of English Translation and 5 pages of Official Copy). cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2023-7034892, mailed on Jul. 15, 2024, 7 pages (2 pages of English Translation and 5 pages of Official Copy). cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/951,945, mailed on Jun. 26, 2024, 10 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/952,181, mailed on Jul. 26, 2024, 5 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/135,056, mailed on Jul. 10, 2024, 10 pages. cited by applicant

Office Action received for Australian Patent Application No. 2023210876, mailed on Jun. 21, 2024, 2 pages. cited by applicant

Office Action received for Chinese Patent Application No. 202210312775.7, mailed on Jun. 19, 2024, 13 pages (6 pages of English Translation and 7 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202211193170.7, mailed on Jul. 12, 2024, 22 pages (12 pages of English Translation and 10 pages of Official Copy). cited by applicant

Office Action received for European Patent Application No. 20760607.0, mailed on Jul. 12, 2024, 10 pages. cited by applicant

Office Action received for European Patent Application No. 22731852.4, mailed on Jun. 26, 2024, 7 pages. cited by applicant

Office Action received for European Patent Application No. 23153899.2, mailed on Jun. 25, 2024, 11 pages. cited by applicant

Office Action received for European Patent Application No. 23153900.8, mailed on Jun. 26, 2024, 11 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2021-565912, mailed on Jun. 18, 2024, 3 pages (1 page of English Translation and 2 pages of Official Copy). cited by applicant

Office Action received for Japanese Patent Application No. 2023-041035, mailed on Jul. 16, 2024, 4 pages (2 pages of English Translation and 2 pages of Official Copy). cited by applicant

Office Action received for Japanese Patent Application No. 2023-097896, mailed on Jul. 5, 2024, 10 pages (5 pages of English Translation and 5 pages of Official Copy). cited by applicant

Office Action received for Japanese Patent Application No. 2023-158326, mailed on Jul. 25, 2024, 6 pages (3 pages of English Translation and 3 pages of Official Copy). cited by applicant

Office Action received for Japanese Patent Application No. 2023-171409, mailed on Jul. 29, 2024, 8 pages (4 pages of English Translation and 4 pages of Official Copy). cited by applicant

Office Action received for Korean Patent Application No. 10-2021-7036242, mailed on May 31, 2024, 7 pages (2 pages of English Translation and 5 pages of Official Copy). cited by applicant

Workout and Fitness Tracker for Humans, Available online at <https://gentler.app/>, retrieved on; May 14, 2024, 11 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/952,236, mailed on Oct. 15, 2024, 2 pages. cited by applicant

Blackburn Ian, “How Using Custom Workouts on Apple Watch will make you a better Athlete (and everything you need to know about creating them)—The Apple Triathlete”, Available online at: <https://theapplewatchtriathlete.com/blog-1/2022/8/23/how-using-custom-workouts-on-apple-watch-will-make-you-a-better-athlete-everything-you-need-to-know-about-creating-them>, Aug. 23, 2022, pp. 1-51. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 18/405,969, mailed on Oct. 17, 2024, 2 pages. cited by applicant

Examiner's Pre-Review Report received for Japanese Patent Application No. 2022-130087, mailed on Sep. 20, 2024, 2 pages (1 page of English Translation and 1 page of Official Copy). cited by applicant

Final Office Action received for U.S. Appl. No. 17/210,920, mailed on Oct. 9, 2024, 20 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2023-098692, mailed on Oct. 11, 2024, 4 pages (1 page of English Translation and 3 pages of Official Copy). cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2023-7018399, mailed on Sep. 30, 2024, 8 pages (2 pages of English Translation and 6 pages of Official Copy). cited by applicant

Office Action received for Australian Patent Application No. 2024200284, mailed on Sep. 30, 2024, 2 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2023-097896, mailed on Oct. 15, 2024, 8 pages (4 pages of English Translation and 4 pages of Official Copy). cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/210,920, mailed on Oct. 30, 2024, 5 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/398,810, mailed on Nov. 4, 2024, 3 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 18/135,056, mailed on Oct. 25, 2024, 17 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/952,181, mailed on Oct. 31, 2024, 5 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/633,120, mailed on Nov. 5, 2024, 12 pages. cited by applicant

Office Action received for Australian Patent Application No. 2023258443, mailed on Oct. 21, 2024, 4 pages. cited by applicant

Office Action received for Chinese Patent Application No. 202080039364.4, mailed on Sep. 28, 2024, 17 pages (9 pages of English Translation and 8 pages of Official Copy). cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/952,236, mailed on Sep. 16, 2024, 16 pages. cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2023-0129766, mailed on Sep. 11, 2024, 8 pages (2 pages of English Translation and 6 pages of Official Copy). cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/951,624, mailed on Sep. 20, 2024, 9 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/405,969, mailed on Sep. 19, 2024, 7 pages. cited by applicant

Office Action received for Australian Patent Application No. 2023285859, mailed on Aug. 29, 2024, 2 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2023-168815, mailed on Sep. 6, 2024, 10 pages (5 pages of English Translation and 5 pages of Official Copy). cited by applicant

Adeniyi Samuel, “How to connect a second PS4 controller to a PlayStation 4 console”, Online available on:—https://www.youtube.com/watch?v=mOZX_SrN8, 2017, 2 pages. cited by applicant

Advisory Action received for U.S. Appl. No. 16/144,864, mailed on Jul. 29, 2019, 6 pages. cited by applicant

Advisory Action received for U.S. Appl. No. 14/732,773, mailed on Aug. 23, 2019, 6 pages. cited by applicant
Advisory Action received for U.S. Appl. No. 14/732,773, mailed on Nov. 9, 2018, 6 pages. cited by applicant
Advisory Action received for U.S. Appl. No. 14/839,922, mailed on Mar. 24, 2017, 4 pages. cited by applicant
Advisory Action received for U.S. Appl. No. 16/144,849, mailed on Aug. 12, 2019, 5 pages. cited by applicant
Advisory Action received for U.S. Appl. No. 16/144,864, mailed on Jul. 6, 2020, 6 pages. cited by applicant
Advisory Action received for U.S. Appl. No. 16/249,627, mailed on May 21, 2024, 3 pages. cited by applicant
Advisory Action received for U.S. Appl. No. 16/377,892, mailed on Apr. 9, 2021, 4 pages. cited by applicant
Advisory Action received for U.S. Appl. No. 16/378,136, mailed on Apr. 12, 2021, 4 pages. cited by applicant
Advisory Action received for U.S. Appl. No. 17/031,779, mailed on Oct. 20, 2022, 5 pages. cited by applicant
Advisory Action received for U.S. Appl. No. 17/381,570, mailed on May 23, 2023, 5 pages. cited by applicant
Advisory Action received for U.S. Appl. No. 17/398,810, mailed on Dec. 11, 2023, 4 pages. cited by applicant
Advisory Action received for U.S. Appl. No. 17/591,184, mailed on Nov. 14, 2023, 5 pages. cited by applicant
Advisory Action received for U.S. Appl. No. 17/744,500, mailed on Nov. 14, 2023, 5 pages. cited by applicant
Advisory Action received for U.S. Appl. No. 17/952,133, mailed on Oct. 20, 2023, 7 pages. cited by applicant
Allen Ray, "Join the Nike Training Club and let your iPhone be your fitness instructor", Apr. 19, 2011, 26 pages. cited by applicant
Allison Conon, "Working out with Fiit's wearable-powered boutique fitness classes", Oniine available at:—<<https://www.wearable.com/wearable-tech-fiit-fitness-review-3849>>, May 14, 2018, 8 pages. cited by applicant
Androidanddyuk, "Endomondo Android App Review", Available online at: <https://www.youtube.com/watch?v=Wyjyrza-P1E>, Jan. 9, 2013, 17 pages. cited by applicant
Apple Inc., "iPhone User Guide For iOS 7.1 Software", available online at <https://manuals.info.apple.com/MANUALS/1000/MA1681/en_US/iphone_ios7_1_guide.pdf>, Mar. 10, 2014, pp. 1-162. cited by applicant
Apple, "iPhone User's Guide", Available at <<http://mesnotices.20minutes.fr/manuel-notice-mode-emploi/APPLE/IPHONE%2D%5FE#>>, Retrieved on Mar. 2007, 137 pages. cited by applicant
Applicant Initiated Interview Summary received for U.S. Appl. No. 16/994,352, mailed on Nov. 2, 2021, 4 pages. cited by applicant
Applicant Initiated Interview Summary received for U.S. Appl. No. 15/608,848, mailed on Apr. 13, 2021, 4 pages. cited by applicant
Applicant Initiated Interview Summary received for U.S. Appl. No. 15/608,848, mailed on May 12, 2020, 5 pages. cited by applicant
Applicant Initiated Interview Summary received for U.S. Appl. No. 15/608,848, mailed on Oct. 26, 2020, 3 pages. cited by applicant
Applicant Initiated Interview Summary received for U.S. Appl. No. 15/627,069, mailed on Nov. 4, 2019, 6 pages. cited by applicant
Applicant Initiated Interview Summary received for U.S. Appl. No. 16/144,735, mailed on Jun. 18, 2020, 3 pages. cited by applicant
Applicant Initiated Interview Summary received for U.S. Appl. No. 16/144,753, mailed on Jun. 18, 2020, 3 pages. cited by applicant
Applicant Initiated Interview Summary received for U.S. Appl. No. 16/144,849, mailed on Jan. 21, 2020, 6 pages. cited by applicant
Applicant Initiated Interview Summary received for U.S. Appl. No. 16/144,864, mailed on Apr. 29, 2020, 4 pages. cited by applicant
Applicant Initiated Interview Summary received for U.S. Appl. No. 16/894,309, mailed on Jan. 26, 2021, 3 pages. cited by applicant
Applicant Initiated Interview Summary received for U.S. Appl. No. 17/030,318, mailed on Jul. 30, 2021, 4 pages. cited by applicant
Applicant Initiated Interview Summary received for U.S. Appl. No. 17/030,321, mailed on Jul. 30, 2021, 2 pages. cited by applicant
Applicant Initiated Interview Summary received for U.S. Appl. No. 17/381,570, mailed on Apr. 26, 2022, 5 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 15/600,243, mailed on Nov. 1, 2019, 6 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 15/608,848, mailed on Nov. 1, 2019, 3 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 15/627,069, mailed on Jan. 22, 2021, 4 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 15/627,069, mailed on Jul. 20, 2020, 5 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 15/705,849, mailed on Feb. 14, 2020, 3 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 15/705,849, mailed on Jun. 29, 2020, 3 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 15/925,652, mailed on Nov. 3, 2020, 4 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 15/978,126, mailed on Jan. 19, 2021, 4 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 15/978,126, mailed on Jul. 1, 2020, 6 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/138,809, mailed on Dec. 16, 2020, 7 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/138,809, mailed on Jun. 9, 2020, 4 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/144,753, mailed on Nov. 4, 2020, 3 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/144,864, mailed on Jun. 22, 2020, 3 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/249,627, mailed on Aug. 1, 2023, 3 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/249,627, mailed on Jun. 2, 2021, 5 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/249,627, mailed on Mar. 1, 2023, 4 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/249,627, mailed on Mar. 23, 2022, 3 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/249,627, mailed on May 2, 2024, 5 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/249,627, mailed on Nov. 21, 2023, 5 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/249,627, mailed on Oct. 6, 2021, 4 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/249,627, mailed on Sep. 28, 2022, 4 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/377,892, mailed on Mar. 26, 2021, 2 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/377,892, mailed on Oct. 13, 2020, 5 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/378,136, mailed on Mar. 26, 2021, 2 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/378,136, mailed on Oct. 13, 2020, 4 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/418,786, mailed on Mar. 30, 2021, 4 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/418,786, mailed on May 9, 2022, 2 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/418,786, mailed on Sep. 23, 2022, 2 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/820,383, mailed on Aug. 12, 2022, 2 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/820,383, mailed on Mar. 11, 2021, 2 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/820,383, mailed on May 10, 2022, 2 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/880,714, mailed on Feb. 26, 2021, 5 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/888,629, mailed on Aug. 4, 2021, 5 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/894,309, mailed on Jun. 25, 2021, 4 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/987,275, mailed on Feb. 3, 2022, 4 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/030,337, mailed on Jul. 27, 2022, 2 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/031,543, mailed on Apr. 21, 2022, 2 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/031,704, mailed on Feb. 9, 2021, 3 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/031,704, mailed on Jun. 25, 2021, 3 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/031,717, mailed on Jun. 29, 2021, 5 pages. cited by applicant

[illegible]

Bagala et al., "Evaluation of Accelerometer-Based Fall Detection Algorithms on Real-World Falls", PLoS One, vol. 7, No. 5, May 16, 2012, 9 pages. cited by applicant

Board Decision received for Chinese Patent Application No. 201380081349.6, mailed on Nov. 23, 2020, 2 pages. cited by applicant

Brief Communication Regarding Oral Proceedings received for European Patent Application No. 18727543.3, mailed on Mar. 23, 2023, 1 page. cited by applicant

Brief Communication Regarding Oral Proceedings received for European Patent Application No. 20182116.2, mailed on Apr. 13, 2022, 3 pages. cited by applicant

Brief Communication Regarding Oral Proceedings received for European Patent Application No. 20203526.7, mailed on Dec. 23, 2022, 4 pages. cited by applicant

Brief Communication Regarding Oral Proceedings received for European Patent Application No. 20203526.7, mailed on Jan. 18, 2023, 1 page. cited by applicant

Brief Communication Regarding Oral Proceedings received for European Patent Application No. 20721342.2, mailed on Oct. 18, 2022, 1 page. cited by applicant

Brief Communication Regarding Oral Proceedings received for European Patent Application No. 21165295.3, mailed on Feb. 27, 2024, 1 page. cited by applicant

CBS This Morning, "This smart mirror puts a personal trainer in your reflection", Available on: <https://www.youtube.com/watch?v=nSmTTZcpVGg>, Oct. 13, 2023, 1 page. cited by applicant

Certificate of Examination received for Australian Patent Application No. 2018101855, mailed on Aug. 6, 2019, 2 pages. cited by applicant

Certification of Examination received for Australian Patent Application No. 2018100158, mailed on Oct. 23, 2018, 2 pages. cited by applicant

Chengcheng et al., "Platform of Development of Motion Control Systems Experimental Software", Experimental Technology and Management, vol. 30, No. 1, 2017, 1 page. cited by applicant

Cho H.S., "Satisfactory Innovative Smartwatch (fitbit force) review after seven days of use, such as the amount of sleep and movement improving sleep is the Blue", Online Available at: <<https://x-blueuv.blogspot.com/2013/12/fitbit-force.html>>, Dec. 3, 2013, 8 pages. cited by applicant

CNET, "Google Fit's automatic activity tracking is getting smarter on Android Wear", Available online at: https://www.youtube.com/watch?v=IttzlCid_d8, Mar. 1, 2017, 1 page. cited by applicant

Codrington Simon, "Intuitive Scrolling Interfaces with CSS Scroll Snap Points", Online Available at: <https://www.sitepoint.com/intuitive-scrolling-interfaces-scroll-snap-points/>, Dec. 8, 2015, 14 pages. cited by applicant

Communication of the Board of Appeal received for European Patent Application No. 13811085.3, mailed on Jul. 28, 2022, 13 pages. cited by applicant

Communication of the Board of Appeal received for European Patent Application No. 15771747.1, mailed on Aug. 25, 2021, 9 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 14/732,773, mailed on Feb. 10, 2020, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 14/732,773, mailed on Mar. 24, 2020, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 15/183,663, mailed on Feb. 25, 2019, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 15/183,663, mailed on Mar. 27, 2019, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 15/600,243, mailed on Feb. 5, 2020, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 15/600,243, mailed on Mar. 13, 2020, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 15/600,243, mailed on Mar. 31, 2020, 5 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/377,892, mailed on Aug. 11, 2021, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/378,136, mailed on Aug. 11, 2021, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/378,136, mailed on Jun. 11, 2021, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/418,786, mailed on Jan. 5, 2022, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/418,786, mailed on Jun. 23, 2022, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/820,383, mailed on Apr. 28, 2023, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/820,383, mailed on Aug. 13, 2021, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/820,383, mailed on Aug. 19, 2021, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/820,383, mailed on Mar. 27, 2024, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/820,383, mailed on Oct. 5, 2021, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/888,629, mailed on Jan. 21, 2022, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 16/987,275, mailed on Jun. 8, 2022, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/030,318, mailed on Jan. 24, 2022, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/030,318, mailed on Jun. 1, 2023, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/030,321, mailed on Aug. 15, 2022, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/030,337, mailed on Aug. 31, 2022, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/030,337, mailed on Feb. 10, 2023, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/030,337, mailed on Feb. 17, 2023, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/030,337, mailed on Nov. 3, 2022, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/030,337, mailed on Nov. 15, 2022, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/030,337, mailed on Oct. 18, 2022, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/030,337, mailed on Sep. 21, 2022, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/031,543, mailed on Aug. 22, 2022, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/031,543, mailed on Jul. 18, 2022, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/031,543, mailed on Jun. 8, 2022, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/031,704, mailed on Nov. 2, 2021, 7 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/031,717, mailed on Apr. 15, 2022, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/031,717, mailed on May 19, 2022, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/031,779, mailed on Jun. 14, 2023, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/041,438, mailed on Dec. 1, 2023, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/041,438, mailed on Mar. 28, 2024, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/041,438, mailed on Sep. 27, 2023, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/157,728, mailed on Apr. 4, 2022, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/157,728, mailed on Apr. 14, 2022, 6 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/192,161, mailed on Apr. 22, 2022, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/192,161, mailed on Mar. 23, 2022, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/197,628, mailed on Apr. 27, 2022, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/197,628, mailed on Jul. 29, 2022, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/735,395, mailed on Jul. 16, 2024, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/744,500, mailed on Jan. 12, 2024, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/892,534, mailed on Jun. 5, 2024, 6 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/896,791, mailed on Jan. 2, 2024, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/896,791, mailed on Jun. 7, 2024, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/951,613, mailed on Jan. 2, 2024, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/952,027, mailed on Jan. 22, 2024, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/952,185, mailed on Mar. 27, 2024, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/952,233, mailed on May 9, 2024, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/952,239, mailed on Jul. 12, 2023, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/952,239, mailed on Nov. 15, 2023, 2 pages. cited by applicant

Cyclespeed Tours, "The Most Useful Data Fields to Display on Your Garmin", Online Available at: <https://www.youtube.com/watch?v=AN0Eo50yxdg>, Nov. 2017, 7 pages. cited by applicant

Dabek et al., "A timeline-based framework for aggregating and summarizing electronic health records", IEEE Workshop on Visual Analytics in Healthcare (V. 2017), available online at: https://www.researchgate.net/publication/325833364_A_timeline-based_framework_for_aggregating_and_summarizing_electronic_health, 2017, 7 pages. cited by applicant

DC Rainmaker, "Garmin Fenix3 New Auto Climb Functionality", Available online at: <https://www.youtube.com/watch?v=iuavOSnpVRc>, Feb. 19, 2015, 1 page. cited by applicant

Decision of Appeal received for European Patent Application No. 15771747.1, mailed on Dec. 14, 2021, 21 pages. cited by applicant

Decision on Appeal received for Korean Patent Application No. 10-2019-7025538, mailed on Feb. 24, 2021, 20 pages. cited by applicant

Decision on Appeal received for Korean Patent Application No. 10-2020-0124134, mailed on Oct. 20, 2023, 24 pages. cited by applicant

Decision to Grant received for Danish Patent Application No. PA201670656, mailed on Jun. 21, 2021, 2 pages. cited by applicant

Decision to Grant received for Danish Patent Application No. PA201870379, mailed on Jul. 5, 2019, 2 pages. cited by applicant

Decision to Grant received for Danish Patent Application No. PA202070614, mailed on Nov. 10, 2022, 2 pages. cited by applicant

Decision to Grant received for Danish Patent Application No. PA202070615, mailed on Jul. 29, 2022, 2 pages. cited by applicant

Decision to Grant received for Danish Patent Application No. PA202070619, mailed on Aug. 11, 2022, 2 pages. cited by applicant

Decision to Grant received for Danish Patent Application No. PA202070815, mailed on Dec. 23, 2022, 1 page. cited by applicant

Decision to Grant received for European Patent Application No. 16837432.0, mailed on Dec. 21, 2023, 2 pages. cited by applicant

Decision to Grant received for European Patent Application No. 18727543.3, mailed on Aug. 18, 2023, 2 pages. cited by applicant

Decision to Grant received for European Patent Application No. 19721883.7, mailed on Aug. 31, 2023, 4 pages. cited by applicant

Decision to Grant received for European Patent Application No. 20182116.2, mailed on Mar. 23, 2023, 3 pages. cited by applicant

Decision to Grant received for European Patent Application No. 20203526.7, mailed on Jun. 22, 2023, 4 pages. cited by applicant

Decision to Grant received for German Patent Application No. 112015002326.7, mailed on Jun. 15, 2021, 10 pages. cited by applicant

Decision to Grant received for German Patent Application No. 112015007285.3, mailed on Jul. 25, 2023, 11 pages. cited by applicant

Decision to Refuse received for European Patent Application No. 13811085.3, mailed on Sep. 11, 2018, 21 pages. cited by applicant

Decision to Refuse received for European Patent Application No. 15771747.1, mailed on Aug. 10, 2018, 22 pages. cited by applicant

Decision to Refuse received for European Patent Application No. 17810749.6, mailed on Jan. 29, 2021, 24 pages. cited by applicant

Decision to Refuse received for European Patent Application No. 18154145.9, mailed on Feb. 17, 2021, 20 pages. cited by applicant

Decision to Refuse received for European Patent Application No. 20721342.2, mailed on Nov. 10, 2022, 14 pages. cited by applicant

Decision to Refuse received for European Patent Application No. 21165295.3, mailed on Apr. 29, 2024, 14 pages. cited by applicant

Decision to Refuse received for Japanese Patent Application No. 2022-130087, mailed on Apr. 30, 2024, 6 pages. cited by applicant

Dicristina John, "Fitness Monitoring Equipment Goes Wireless". Frontier Technology, China Academic Journal Electronic Publishing House, Online Available at: <http://www.cnki.net>, Dec. 2012, pp. 44-45. cited by applicant

DwProgressBar v2: Stepping and Events, davidwalsh.name/dwprogressbar-2-stepping-events-mootools-progress-bar, retrieved from the Wayback Machine, A. 2017, 4 pages. cited by applicant

European Search Report received for European Patent Application No. 20182116.2, mailed on Oct. 21, 2020, 4 pages. cited by applicant

European Search Report received for European Patent Application No. 21165295.3, mailed on Jun. 18, 2021, 4 pages. cited by applicant

European Search Report received for European Patent Application No. 21168916.1, mailed on Jul. 14, 2021, 5 pages. cited by applicant

Evergreen et al., "Bar Chart", Better Evaluation, Available Online at: <https://www.betterevaluation.org/en/evaluation-options/BarChart>, Oct. 31, 2014, 8 pages. cited by applicant

Examiner-Initiated Interview received for U.S. Appl. No. 17/896,791, mailed on Sep. 1, 2023, 2 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 16837432.0, mailed on Mar. 11, 2019, 10 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 18154145.9, mailed on Mar. 2, 2018, 8 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 19163212.4, mailed on Jun. 25, 2019, 11 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 20203526.7, mailed on Jan. 29, 2021, 13 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 22194355.8, mailed on Dec. 23, 2022, 10 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 23150297.2, mailed on Mar. 28, 2023, 8 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 23153898.4, mailed on May 4, 2023, 11 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 23153899.2, mailed on May 4, 2023, 10 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 23153900.8, mailed on May 4, 2023, 10 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 23189089.8, mailed on Nov. 23, 2023, 11 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 23192409.3, mailed on Feb. 20, 2024, 13 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 23217005.0, mailed on Mar. 13, 2024, 12 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 23218255.0, mailed on Mar. 27, 2024, 10 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 24152191.3, mailed on Apr. 15, 2024, 11 pages. cited by applicant

FAQSleep Score, Available Online at: <https://www.sleepscore.com/sleepscore-app/faq/>, Retrieved on May 26, 2021, 31 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 16/994,352, mailed on Dec. 6, 2021, 14 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 12/205,847, mailed on Apr. 25, 2012, 42 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 14/599,424, mailed on Jun. 28, 2018, 12 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 14/599,425, mailed on Jun. 12, 2018, 45 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 14/599,425, mailed on May 19, 2017, 24 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 14/599,425, mailed on Oct. 8, 2015, 20 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 14/732,773, mailed on Jul. 13, 2018, 48 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 14/732,773, mailed on Jun. 21, 2019, 32 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 14/839,922, mailed on Dec. 14, 2016, 22 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 15/608,848, mailed on Aug. 21, 2020, 15 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 15/608,848, mailed on Jun. 26, 2019, 27 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 15/627,069, mailed on Mar. 2, 2020, 22 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 15/627,069, mailed on Oct. 20, 2020, 25 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 15/705,849, mailed on May 1, 2020, 17 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 15/925,652, mailed on Aug. 1, 2019, 30 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 15/978,126, mailed on Sep. 30, 2020, 23 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 16/138,809, mailed on Aug. 27, 2020, 24 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 16/144,735, mailed on May 4, 2020, 12 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 16/144,753, mailed on Sep. 22, 2020, 9 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 16/144,849, mailed on Jun. 7, 2019, 29 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 16/144,864, mailed on May 17, 2019, 24 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 16/144,864, mailed on May 28, 2020, 29 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 16/249,627, mailed on Apr. 3, 2024, 23 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 16/249,627, mailed on Feb. 14, 2022, 19 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 16/249,627, mailed on Jun. 30, 2023, 19 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 16/377,892, mailed on Jan. 28, 2021, 11 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 16/378,136, mailed on Jan. 28, 2021, 9 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 16/418,786, mailed on Jan. 13, 2021, 14 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 16/820,383, mailed on Jun. 22, 2022, 21 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 16/894,309, mailed on Feb. 24, 2021, 30 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/030,318, mailed on Nov. 28, 2022, 13 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/030,318, mailed on Sep. 30, 2021, 28 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/030,321, mailed on Apr. 2, 2021, 28 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/031,704, mailed on Apr. 1, 2021, 31 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/031,717, mailed on Feb. 24, 2021, 23 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/031,723, mailed on Jul. 12, 2022, 25 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/031,723, mailed on Oct. 4, 2023, 13 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/031,779, mailed on Jul. 14, 2022, 19 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/031,854, mailed on Feb. 23, 2023, 19 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/031,854, mailed on Jun. 10, 2022, 15 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/031,854, mailed on May 16, 2024, 21 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/031,859, mailed on Apr. 16, 2021, 14 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/031,859, mailed on Feb. 8, 2023, 15 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/031,859, mailed on Jun. 10, 2022, 13 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/031,859, mailed on Nov. 13, 2023, 15 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/031,874, mailed on Apr. 16, 2021, 17 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/031,874, mailed on Jun. 2, 2022, 19 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/031,874, mailed on Mar. 17, 2023, 24 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/192,161, mailed on Aug. 16, 2021, 22 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/192,161, mailed on Oct. 18, 2021, 22 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/210,920, mailed on May 6, 2024, 27 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/381,570, mailed on Feb. 10, 2023, 22 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/381,570, mailed on Jul. 20, 2022, 22 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/398,810, mailed on Oct. 4, 2023, 17 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/516,537, mailed on Oct. 11, 2022, 9 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/591,184, mailed on Dec. 23, 2022, 10 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/591,184, mailed on Sep. 22, 2023, 19 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/735,395, mailed on Dec. 7, 2023, 29 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/735,395, mailed on May 17, 2023, 31 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/744,500, mailed on Sep. 19, 2023, 35 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/892,534, mailed on Nov. 9, 2023, 17 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/951,624, mailed on Jan. 25, 2024, 48 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/951,875, mailed on May 30, 2023, 12 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/951,945, mailed on Dec. 7, 2023, 20 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/951,945, mailed on May 18, 2023, 18 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/952,027, mailed on Aug. 21, 2023, 47 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/952,133, mailed on Sep. 26, 2023, 20 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/952,233, mailed on Jun. 26, 2023, 18 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 18/135,056, mailed on May 2, 2024, 18 pages. cited by applicant

Fitbit App, Available online at: <<http://web.archive.org/web/20180114083150/https://www.fitbit.com/au/app>>, Jan. 14, 2018, 8 pages. cited by applicant

Garmin Edge 520, Owner's Manual, online available at: https://www8.garmin.com/manuals/webhelp/edge520/EN-US/Edge_520_OM_EN-US.pdf, 2015, 24 p
applicant

Garmin, "Edge 520 Plus Owner's Manual", Online Available at: https://www8.garmin.com/manuals/webhelp/edge520plus/EN-US/Edge_520_Plus_OM_EN-US.pdf,
30 pages. cited by applicant

Garmin, "Fenix 5x Owner's Manual", Online Available at:—https://web.archive.org/web/20180127170640/https://static.garmin.com/pumac/fenix5x_OM_EN-US.pdf,
2018, 42 pages. cited by applicant

GPSCity, "Garmin Connect 2.0 Overview with GPS City", Available online at: https://www.youtube.com/watch?v=EJ6U10y_8y0, Feb. 28, 2014, 8 pages. cited by applicant

GPSCity, "Garmin Connect Mobile App iOS Overview with GPS City", Available on: <https://www.youtube.com/watch?v=rD-KPOJpmOA>, 2014, 9 pages. cited by applicant

applicant

Graphs and Charts, online available at: <<https://www.teachervision.com/lesson-planning/graph-chart-teacher-resources>, retrieved on Dec. 12, 2018, 4 pages. cited by applicant

applicant

Gym Book—Strength Training Planner, Logger and Analyzer, GymBookApp, Available Online at: <https://web.archive.org/web/20160401104508/https://gymbk.com>,
Apr. 1, 2016, 10 pages. cited by applicant

Hamilton Jim, "Peloton Tips", Online available on:—<<https://www.youtube.com/watch?app=desktop&v=OneXtB0kaD4>>, Oct. 22, 2015, 3 pages. cited by applicant

Heinrich Peter, "More Player Engagement Potential: GameCircle Now Rewards Player Experience across Games", Available online at: <https://www.developer.amazon.com/es-mx/blogs/home/tag/badges>, Apr. 11, 2014, 9 pages. cited by applicant

Intention to Grant received for Danish Patent Application No. PA201570668, mailed on Mar. 27, 2017, 2 pages. cited by applicant

Intention to Grant received for Danish Patent Application No. PA201670656, mailed on Jan. 18, 2021, 2 pages. cited by applicant

Intention to Grant received for Danish Patent Application No. PA201870379, mailed on May 2, 2019, 2 pages. cited by applicant

Intention to Grant received for Danish Patent Application No. PA202070614, mailed on Aug. 8, 2022, 2 pages. cited by applicant

Intention to Grant received for Danish Patent Application No. PA202070615, mailed on Jan. 27, 2022, 2 pages. cited by applicant

Intention to Grant received for Danish Patent Application No. PA202070619, mailed on Jan. 17, 2022, 2 pages. cited by applicant

Intention to Grant received for Danish Patent Application No. PA202070815, mailed on Sep. 13, 2022, 2 pages. cited by applicant

Intention to Grant received for European Patent Application No. 16837432.0, mailed on Apr. 14, 2023, 8 pages. cited by applicant

Intention to Grant received for European Patent Application No. 16837432.0, mailed on Sep. 7, 2023, 9 pages. cited by applicant

Intention to Grant received for European Patent Application No. 18727543.3, mailed on Apr. 12, 2023, 9 pages. cited by applicant

Intention to Grant received for European Patent Application No. 19721883.7, mailed on May 11, 2023, 9 pages. cited by applicant

Intention to Grant received for European Patent Application No. 20182116.2, mailed on Jun. 2, 2022, 8 pages. cited by applicant

Intention to Grant received for European Patent Application No. 20182116.2, mailed on Nov. 11, 2022, 9 pages. cited by applicant

Intention to Grant received for European Patent Application No. 20203526.7, mailed on Feb. 10, 2023, 9 pages. cited by applicant

Intention to Grant received for European Patent Application No. 21714460.9, mailed on Feb. 8, 2024, 12 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Application No. PCT/US2016/037686, mailed on Mar. 1, 2018, 12 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Application No. PCT/US2020/035164, mailed on Dec. 16, 2021, 19 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Application No. PCT/US2020/035199, mailed on Dec. 16, 2021, 14 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Application No. PCT/US2013/073195, mailed on Jun. 16, 2016, 10 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Application No. PCT/US2015/032474, mailed on Dec. 15, 2016, 7 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Application No. PCT/US2015/047282, mailed on Mar. 16, 2017, 26 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Application No. PCT/US2017/035554, mailed on Dec. 20, 2018, 39 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Application No. PCT/US2018/023303, mailed on Dec. 12, 2019, 8 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Application No. PCT/US2018/031662, mailed on Nov. 28, 2019, 12 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Application No. PCT/US2019/014215, mailed on Aug. 6, 2020, 14 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Application No. PCT/US2019/024570, mailed on Nov. 19, 2020, 10 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Application No. PCT/US2020/025997, mailed on Nov. 18, 2021, 10 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Application No. PCT/US2021/017736, mailed on Aug. 25, 2022, 19 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Application No. PCT/US2021/035227, mailed on Dec. 15, 2022, 10 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Application No. PCT/US2021/045375, mailed on Feb. 23, 2023, 15 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Application No. PCT/US2022/029297, mailed on Nov. 30, 2023, 10 pages. cited by applicant

International Search Report and Written Opinion received for PCT Application No. PCT/US2015/032474, mailed on Aug. 19, 2015, 8 pages. cited by applicant

International Search Report and Written Opinion received for PCT Application No. PCT/US2015/047282, mailed on May 9, 2016, 33 pages. cited by applicant

International Search Report and Written Opinion received for PCT Application No. PCT/US2016/037686, mailed on Sep. 9, 2016, 19 pages. cited by applicant

International Search Report and Written Opinion received for PCT Application No. PCT/US2017/035554, mailed on Sep. 22, 2017, 42 pages. cited by applicant

International Search Report and Written Opinion received for PCT Application No. PCT/US2018/023303, mailed on Jun. 19, 2018, 10 pages. cited by applicant

International Search Report and Written Opinion received for PCT Application No. PCT/US2018/031662, mailed on Sep. 27, 2018, 17 pages. cited by applicant

International Search Report and Written Opinion received for PCT Application No. PCT/US2019/014215, mailed on Jun. 4, 2019, 17 pages. cited by applicant

International Search Report and Written Opinion received for PCT Application No. PCT/US2019/024570, mailed on Aug. 8, 2019, 18 pages. cited by applicant

International Search Report and Written Opinion received for PCT Application No. PCT/US2020/025997, mailed on Jul. 1, 2020, 16 pages. cited by applicant

International Search Report and Written Opinion received for PCT Application No. PCT/US2020/025997, mailed on Jul. 14, 2020, 15 pages. cited by applicant

International Search Report and Written Opinion received for PCT Application No. PCT/US2020/035164, mailed on Feb. 8, 2021, 26 pages. cited by applicant

International Search Report and Written Opinion received for PCT Application No. PCT/US2020/035199, mailed on Oct. 30, 2020, 20 pages. cited by applicant

International Search Report and Written Opinion received for PCT Application No. PCT/US2021/017736, mailed on Sep. 2, 2021, 25 pages. cited by applicant

International Search Report and Written Opinion received for PCT Application No. PCT/US2021/035227, mailed on Oct. 6, 2021, 17 pages. cited by applicant

International Search Report and Written Opinion received for PCT Application No. PCT/US2021/045375, mailed on Jan. 10, 2022, 21 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2022/029297, mailed on Aug. 11, 2022, 13 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2023/024104, mailed on Oct. 18, 2023, 18 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2023/024185, mailed on Sep. 18, 2023, 12 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2023/030718, mailed on Jan. 9, 2024, 12 pages. cited by applicant

International Search Report received for PCT Patent Application No. PCT/US2013/073195, mailed on Jun. 23, 2014, 3 pages. cited by applicant

International Written Opinion received for PCT Patent Application No. PCT/US2013/073195, mailed on Jun. 23, 2014, 8 pages. cited by applicant

Invitation to Pay Addition Fees and Partial International Search Report received for PCT Patent Application No. PCT/US2018/031662, mailed on Jul. 16, 2018, 2 pages. cited by applicant

Invitation to Pay Addition Fees and Partial International Search Report received for PCT Patent Application No. PCT/US2019/014215, mailed on Apr. 12, 2020, 2 pages. cited by applicant

Invitation to Pay Additional Fees and Partial International Search Report received for PCT Patent Application No. PCT/US2020/035164, mailed on Oct. 16, 2021, 2 pages. cited by applicant

Invitation to Pay Additional Fees received for PCT Patent Application No. PCT/US2015/047282, mailed on Dec. 22, 2015, 7 pages. cited by applicant

Invitation to Pay Additional Fees received for PCT Patent Application No. PCT/US2017/035554, mailed on Jul. 20, 2017, 2 pages. cited by applicant

Invitation to Pay Additional Fees received for PCT Patent Application No. PCT/US2020/035199, mailed on Sep. 8, 2020, 12 pages. cited by applicant

Invitation to Pay Additional Fees received for PCT Patent Application No. PCT/US2021/017736, mailed on Jun. 15, 2021, 14 pages. cited by applicant

Invitation to Pay Additional Fees received for PCT Patent Application No. PCT/US2021/045375, mailed on Nov. 16, 2021, 12 pages. cited by applicant

Invitation to Pay Search Fees received for European Patent Application No. 19703582.7, mailed on Sep. 12, 2022, 3 pages. cited by applicant

Invitation to Pay Search Fees received for European Patent Application No. 20760607.0, mailed on Nov. 21, 2022, 3 pages. cited by applicant

Invitation to Pay Search Fees received for European Patent Application No. 21714460.9, mailed on Aug. 8, 2023, 3 pages. cited by applicant

JENBSJOURNEY, "Wondering About a Fitbit?", Available at: <https://jenbsjourney.blogspot.kr/2013/08/wondering-about-fitbit.html>, Aug. 6, 2013, 12 pages. cited by applicant

Kamijo Noboru, "Next Generation Mobile System—WatchPad1.5", Available at <http://researcher.ibm.com/researcher/view_group_subpage.php?id=5617>, IBM Research, Jul. 4, 2015, 2 pages. cited by applicant

Li-Yu et al., "Influence of exercise prescription on body composition of college students", Clinical Rehabilitation in China, vol. 9 Issue 24, Jun. 28, 2005, pp. 15-18. cited by applicant

Minutes of Oral Proceedings received for European Patent Application No. 13811085.3, mailed on Sep. 11, 2018, 3 pages. cited by applicant

Minutes of Oral Proceedings received for European Patent Application No. 15771747.1, mailed on Aug. 10, 2018, 11 pages. cited by applicant

Minutes of Oral Proceedings received for European Patent Application No. 20721342.2, mailed on Nov. 8, 2022, 5 pages. cited by applicant

Minutes of Oral Proceedings received for European Patent Application No. 21165295.3, mailed on Apr. 26, 2024, 6 pages. cited by applicant

Minutes of the Oral Proceedings received for European Patent Application No. 15771747.1, mailed on Dec. 1, 2021, 4 pages. cited by applicant

Minutes of the Oral Proceedings received for European Patent Application No. 17810749.6, mailed on Jan. 26, 2021, 8 pages. cited by applicant

Minutes of the Oral Proceedings received for European Patent Application No. 18154145.9, mailed on Feb. 12, 2021, 8 pages. cited by applicant

Minutes of the Oral Proceedings received for European Patent Application No. 20182116.2, mailed on May 24, 2022, 7 pages. cited by applicant

Minutes of the Oral Proceedings received for European Patent Application No. 21168916.1, mailed on Jan. 3, 2024, 5 pages. cited by applicant

Mugs, Online Available at: <https://web.archive.org/web/20151029034349/http://le-mugs.com/>, Oct. 29, 2015, 7 pages. cited by applicant

Multi-Set Bar Chart, The Data Visualization Catalogue, Available Online at: https://datavizcatalogue.com/methods/multiset_barchart.html, Feb. 8, 2014, 3 pages. cited by applicant

My CalStep, <http://www.surprisesoftware.com/mycalstep/>, retrieved from the Wayback Machine, May 9, 2007, 2 pages. cited by applicant

Nakasuji Yoshito, “Apple Watch”, First Edition 1st Printing, Japan, Incorporated Company Technical Hyoronsha, Jun. 15, 2015, 4 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/839,916, mailed on Feb. 4, 2016, 19 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/839,922, mailed on Feb. 25, 2016, 20 pages. cited by applicant

Non-Final Office Action Received for U.S. Appl. No. 16/144,864, mailed on Dec. 18, 2018, 19 pages., cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/994,352, mailed on Jul. 30, 2021, 11 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 12/205,847, mailed on Oct. 3, 2011, 59 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/503,372, mailed on Dec. 5, 2014, 11 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/599,424, mailed on Jan. 17, 2018, 13 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/599,425, mailed on Jan. 11, 2018, 42 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/599,425, mailed on Mar. 17, 2015, 16 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/599,425, mailed on Oct. 26, 2016, 22 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/732,773, mailed on Feb. 8, 2019, 32 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/732,773, mailed on Jan. 19, 2018, 45 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/839,916, mailed on May 1, 2017, 18 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/839,922, mailed on Aug. 17, 2016, 25 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/183,663, mailed on Jul. 9, 2018, 13 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/600,243, mailed on Jun. 27, 2019, 17 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/608,848, mailed on Feb. 6, 2020, 12 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/608,848, mailed on Feb. 12, 2021, 14 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/608,848, mailed on Nov. 2, 2018, 21 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/627,069, mailed on Jun. 21, 2019, 22 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/627,069, mailed on May 26, 2020, 25 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/705,849, mailed on Nov. 12, 2019, 15 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/925,652, mailed on Apr. 5, 2019, 28 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/925,652, mailed on Aug. 7, 2020, 39 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/978,126, mailed on Mar. 26, 2020, 16 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/138,809, mailed on Feb. 28, 2020, 22 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/144,735, mailed on Feb. 19, 2020, 10 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/144,753, mailed on Mar. 5, 2020, 9 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/144,849, mailed on Dec. 31, 2018, 28 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/144,849, mailed on Sep. 17, 2019, 9 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/144,864, mailed on Jan. 31, 2020, 29 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/249,627, mailed on Aug. 22, 2022, 21 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/249,627, mailed on Aug. 31, 2021, 18 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/249,627, mailed on Jan. 19, 2023, 19 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/249,627, mailed on Mar. 11, 2021, 21 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/249,627, mailed on Oct. 31, 2023, 23 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/377,892, mailed on May 21, 2020, 9 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/378,136, mailed on Jun. 2, 2020, 8 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/418,786, mailed on Apr. 24, 2020, 16 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/418,786, mailed on Aug. 1, 2022, 18 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/418,786, mailed on Mar. 28, 2022, 14 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/418,786, mailed on Oct. 4, 2021, 10 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/820,383, mailed on Dec. 14, 2020, 11 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/820,383, mailed on Jan. 10, 2022, 18 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/880,714, mailed on Oct. 28, 2020, 11 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/880,629, mailed on Mar. 31, 2021, 14 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/894,309, mailed on Oct. 15, 2020, 24 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/987,275, mailed on Nov. 23, 2021, 17 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/030,318, mailed on Apr. 2, 2021, 28 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/030,318, mailed on Dec. 3, 2020, 22 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/030,318, mailed on Jun. 14, 2022, 9 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/030,321, mailed on Dec. 15, 2020, 25 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/030,321, mailed on Oct. 18, 2021, 28 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/030,337, mailed on Jun. 14, 2022, 13 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/030,340, mailed on Jun. 14, 2022, 15 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/031,543, mailed on Apr. 1, 2022, 9 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/031,704, mailed on Dec. 10, 2020, 30 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/031,717, mailed on Nov. 19, 2020, 22 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/031,717, mailed on Sep. 14, 2021, 35 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/031,723, mailed on Dec. 5, 2022, 27 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/031,723, mailed on Jan. 24, 2022, 17 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/031,723, mailed on Jun. 2, 2023, 23 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/031,779, mailed on Feb. 16, 2022, 17 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/031,854, mailed on Dec. 27, 2021, 13 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/031,854, mailed on Oct. 18, 2023, 22 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/031,854, mailed on Sep. 26, 2022, 17 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/031,859, mailed on Dec. 15, 2020, 13 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/031,859, mailed on Dec. 24, 2021, 16 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/031,859, mailed on Jul. 10, 2023, 15 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/031,859, mailed on Sep. 12, 2022, 17 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/031,874, mailed on Dec. 28, 2020, 14 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/031,874, mailed on Jan. 24, 2022, 18 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/031,874, mailed on Oct. 4, 2022, 20 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/041,415, mailed on Mar. 29, 2022, 11 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/041,438, mailed on May 25, 2023, 47 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/157,728, mailed on Nov. 26, 2021, 18 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/192,161, mailed on May 13, 2021, 28 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/210,920, mailed on Sep. 28, 2023, 22 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/381,570, mailed on Apr. 1, 2022, 29 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/381,570, mailed on Sep. 28, 2022, 20 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/398,810, mailed on Jun. 2, 2023, 19 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/516,537, mailed on May 5, 2022, 8 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/566,521, mailed on May 15, 2023, 12 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/591,184, mailed on Apr. 21, 2023, 15 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/591,184, mailed on Aug. 4, 2022, 18 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/666,301, mailed on Feb. 16, 2023, 24 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/735,395, mailed on Feb. 10, 2023, 28 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/735,395, mailed on Mar. 19, 2024, 32 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/735,395, mailed on Sep. 20, 2023, 29 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/744,500, mailed on Apr. 19, 2023, 30 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/892,534, mailed on Dec. 19, 2022, 20 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/892,534, mailed on May 10, 2023, 17 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/896,791, mailed on Aug. 30, 2023, 11 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/951,613, mailed on Aug. 2, 2023, 42 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/951,624, mailed on Sep. 19, 2023, 41 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/951,875, mailed on Jan. 23, 2023, 12 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/951,945, mailed on Mar. 20, 2024, 22 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/951,945, mailed on Mar. 24, 2023, 14 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/951,945, mailed on Sep. 20, 2023, 19 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/951,976, mailed on Aug. 3, 2023, 16 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/952,027, mailed on Apr. 28, 2023, 46 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/952,075, mailed on Jan. 16, 2024, 27 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/952,133, mailed on Feb. 28, 2024, 22 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/952,133, mailed on Jun. 2, 2023, 28 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/952,181, mailed on Aug. 7, 2023, 18 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/952,233, mailed on Apr. 28, 2023, 21 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/952,233, mailed on Feb. 2, 2024, 18 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/952,239, mailed on Apr. 4, 2023, 45 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 18/135,056, mailed on Dec. 7, 2023, 16 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 18/204,217, mailed on Feb. 13, 2024, 21 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2015267240, mailed on Apr. 10, 2018, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2015312215, mailed on Oct. 9, 2017, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2017277971, mailed on Feb. 17, 2021, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2018268972, mailed on Dec. 18, 2020, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2019201583, mailed on Jul. 15, 2019, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2019210192, mailed on Dec. 2, 2021, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2019222943, mailed on May 5, 2020, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2019250251, mailed on Feb. 18, 2021, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2020204153, mailed on Jul. 6, 2020, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2020239692, mailed on Apr. 6, 2022, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2020239740, mailed on Feb. 22, 2022, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2020239743, mailed on Jan. 13, 2022, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2020239748, mailed on Mar. 7, 2022, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2020239752, mailed on Jan. 31, 2022, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2020256383, mailed on Aug. 3, 2021, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2020288139, mailed on Feb. 2, 2023, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2021200787, mailed on Mar. 19, 2021, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2021201130, mailed on Mar. 28, 2022, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2021203636, mailed on Apr. 14, 2022, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2021204422, mailed on Aug. 15, 2022, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2021266294, mailed on Mar. 3, 2023, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2022201761, mailed on Jun. 15, 2023, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2022201823, mailed on Sep. 26, 2023, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2022202977, mailed on Sep. 26, 2023, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2022203508, mailed on Jun. 27, 2023, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2022204568, mailed on Jul. 27, 2023, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2022209277, mailed on Apr. 28, 2023, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2022235614, mailed on Jul. 6, 2023, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2023203050, mailed on Oct. 24, 2023, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2023203776, mailed on Dec. 12, 2023, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2023237090, mailed on Feb. 23, 2024, 3 pages. cited by applicant
Notice of Allowance received for Chinese Patent Application No. 201380081349.6, mailed on Dec. 17, 2021, 2 pages. cited by applicant
Notice of Allowance received for Chinese Patent Application No. 201520358505.5, mailed on Jan. 13, 2016, 3 pages. cited by applicant
Notice of Allowance received for Chinese Patent Application No. 201580028677.9, mailed on Apr. 2, 2019, 2 pages. cited by applicant
Notice of Allowance received for Chinese Patent Application No. 201580037927.5, mailed on Oct. 17, 2019, 3 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 201680047983.1, mailed on Apr. 28, 2021, 3 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 201710439448.7, mailed on Jan. 26, 2021, 2 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 201780034203.4, mailed on Jan. 17, 2022, 2 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 201810105846.X, mailed on Feb. 18, 2020, 2 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 201811303556.2, mailed on Jul. 28, 2023, 2 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 201880032190.1, mailed on Oct. 7, 2023, 4 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 201911396643.1, mailed on Jun. 15, 2023, 8 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 201911396744.9, mailed on Aug. 3, 2023, 5 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 201911396819.3, mailed on Aug. 3, 2023, 5 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 201911396876.1, mailed on Sep. 6, 2023, 5 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 201911401161.0, mailed on Apr. 24, 2023, 11 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 201911401375.8, mailed on Nov. 26, 2023, 2 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 201980018078.7, mailed on Mar. 28, 2024, 2 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 202010606407.4, mailed on Jan. 24, 2022, 2 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 202111611270.2, mailed on Sep. 21, 2022, 4 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 202210238202.4, mailed on Jan. 13, 2023, 7 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 202310775734.6, mailed on Apr. 18, 2024, 4 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 202311059240.4, mailed on May 23, 2024, 2 pages. cited by applicant

Notice of Allowance received for Danish Patent Application No. PA201570666, mailed on Sep. 15, 2016, 1 page. cited by applicant

Notice of Allowance received for Danish Patent Application No. PA201570668, mailed on Oct. 30, 2017, 2 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2016-535045, mailed on Mar. 2, 2018, 4 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2016-557650, mailed on Apr. 9, 2019, 4 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2018-014096, mailed on Jan. 5, 2021, 3 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2018-068846, mailed on Dec. 9, 2019, 4 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2018-184532, mailed on Jan. 17, 2022, 4 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2019-044107, mailed on Jul. 11, 2022, 31 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2019-162293, mailed on Apr. 9, 2021, 4 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2019-563407, mailed on Aug. 20, 2021, 4 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2020-000492, mailed on Jul. 16, 2021, 4 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2020-104679, mailed on Jan. 4, 2021, 4 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2020-115940, mailed on Oct. 22, 2021, 4 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2020-160023, mailed on Apr. 11, 2022, 4 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2020-160052, mailed on Jun. 3, 2022, 4 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2020-160053, mailed on Jan. 16, 2023, 4 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2020-160054, mailed on Apr. 4, 2022, 4 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2020-551585, mailed on Jul. 22, 2022, 4 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2020-560883, mailed on Oct. 29, 2021, 4 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2021-153558, mailed on Jun. 9, 2023, 4 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2021-188824, mailed on Feb. 13, 2023, 4 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2021-192437, mailed on May 19, 2023, 4 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2021-571468, mailed on May 19, 2023, 4 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2022-022159, mailed on Aug. 10, 2023, 4 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2022-076722, mailed on Jul. 28, 2023, 4 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2022-078280, mailed on Sep. 4, 2023, 4 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2022-107902, mailed on Aug. 26, 2022, 4 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2022-107903, mailed on Sep. 1, 2023, 4 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2022-131993, mailed on Dec. 18, 2023, 4 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2022-110196, mailed on Feb. 13, 2024, 4 pages. cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2016-7014577, mailed on May 30, 2019, 5 pages. cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2016-7033638, issued on May 31, 2017, 5 pages. cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2019-7025538, mailed on Mar. 10, 2021, 5 pages. cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2019-7025781, mailed on Jun. 29, 2021, 5 pages. cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2019-7033834, mailed on Jul. 3, 2021, 4 pages. cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2020-0123815, mailed on Aug. 26, 2022, 7 pages. cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2020-0123821, mailed on Mar. 28, 2023, 8 pages. cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2020-0123840, mailed on May 26, 2023, 9 pages. cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2020-0124134, mailed on Nov. 21, 2023, 8 pages. cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2020-7023277, mailed on Jul. 18, 2022, 5 pages. cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2020-7026035, mailed on Aug. 23, 2021, 4 pages. cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2021-7026284, mailed on Jul. 28, 2022, 6 pages. cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2021-7031939, mailed on Apr. 5, 2022, 4 pages. cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2021-7038005, mailed on Dec. 14, 2021, 4 pages. cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2022-0061486, mailed on Nov. 22, 2022, 7 pages. cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2022-7008569, mailed on May 19, 2022, 5 pages. cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2022-7017918, mailed on Jun. 13, 2022, 6 pages. cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2022-7031866, mailed on May 1, 2023, 7 pages. cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2022-7036278, mailed on Jan. 30, 2024, 8 pages. cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2022-7036381, mailed on Jul. 12, 2023, 7 pages. cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2023-0023706, mailed on Mar. 27, 2023, 8 pages. cited by applicant

Notice of Allowance received for Taiwanese Patent Application No. 104117509, mailed on Mar. 31, 2017, 3 pages. cited by applicant

Notice of Allowance received for Taiwanese Patent Application No. 104128685, mailed on May 3, 2017, 3 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 12/205,847, mailed on Aug. 20, 2012, 13 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 14/599,424, mailed on Dec. 13, 2018, 6 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 14/599,425, mailed on Dec. 19, 2018, 9 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 14/732,773, mailed on Dec. 18, 2019, 21 pages. cited by applicant

[illegible]

Notice of Allowance received for U.S. Appl. No. 17/031,779, mailed on May 26, 2023, 9 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/041,415, mailed on Aug. 31, 2022, 7 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/041,438, mailed on Jan. 22, 2024, 10 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/041,438, mailed on Oct. 19, 2023, 2 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/041,438, mailed on Sep. 20, 2023, 11 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/157,728, mailed on Feb. 24, 2022, 7 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/192,161, mailed on Feb. 16, 2022, 8 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/192,161, mailed on May 27, 2022, 8 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/197,628, mailed on Jun. 24, 2022, 8 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/197,628, mailed on Mar. 23, 2022, 35 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/317,084, mailed on Aug. 29, 2022, 10 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/317,084, mailed on Jan. 6, 2023, 6 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/381,570, mailed on Jul. 26, 2023, 14 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/516,537, mailed on Apr. 17, 2023, 8 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/516,537, mailed on Dec. 27, 2022, 7 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/591,184, mailed on Dec. 11, 2023, 9 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/591,184, mailed on Feb. 22, 2023, 5 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/666,301, mailed on May 4, 2023, 10 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/735,395, mailed on Jul. 3, 2024, 11 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/744,500, mailed on Dec. 22, 2023, 38 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/852,020, mailed on Jul. 12, 2023, 9 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/892,534, mailed on Feb. 21, 2024, 7 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/896,791, mailed on Dec. 15, 2023, 9 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/896,791, mailed on Mar. 13, 2024, 8 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/951,613, mailed on Dec. 8, 2023, 13 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/951,613, mailed on Feb. 2, 2024, 5 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/951,875, mailed on Dec. 26, 2023, 7 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/951,875, mailed on Jul. 26, 2023, 7 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/951,875, mailed on Oct. 20, 2023, 8 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/951,976, mailed on Mar. 12, 2024, 5 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/951,976, mailed on Nov. 17, 2023, 9 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/952,027, mailed on Dec. 29, 2023, 6 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/952,027, mailed on Oct. 4, 2023, 13 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/952,181, mailed on Sep. 27, 2023, 9 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/952,185, mailed on Aug. 30, 2023, 12 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/952,185, mailed on Dec. 13, 2023, 9 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/952,233, mailed on May 1, 2024, 9 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/952,239, mailed on Jun. 23, 2023, 5 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/952,239, mailed on Oct. 20, 2023, 5 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 18/078,444, mailed on Aug. 31, 2023, 6 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 18/078,444, mailed on May 12, 2023, 9 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 18/204,217, mailed on Mar. 26, 2024, 7 pages. cited by applicant
Office Action received for Japanese Patent Application No. 2016-569945, mailed on Nov. 10, 2017, 8 pages. cited by applicant
Office Action received for Australian Patent Application No. 2015100734, issued on Jul. 29, 2015, 5 pages. cited by applicant
Office Action received for Australian Patent Application No. 2015267240, mailed on Apr. 10, 2017, 5 pages. cited by applicant
Office Action received for Australian Patent Application No. 2015267240, mailed on Mar. 21, 2018, 5 pages. cited by applicant
Office Action received for Australian Patent Application No. 2015312215, mailed on Oct. 13, 2016, 3 pages. cited by applicant
Office Action received for Australian Patent Application No. 2017100667, mailed on Aug. 3, 2017, 9 pages. cited by applicant
Office Action received for Australian Patent Application No. 2017277971, mailed on Aug. 12, 2020, 3 pages. cited by applicant
Office Action received for Australian Patent Application No. 2017277971, mailed on Jun. 3, 2020, 3 pages. cited by applicant
Office Action received for Australian Patent Application No. 2018100158, mailed on Apr. 23, 2018, 5 pages. cited by applicant
Office Action received for Australian Patent Application No. 2018101855, mailed on Feb. 22, 2019, 4 pages. cited by applicant
Office Action received for Australian Patent Application No. 2018200428, mailed on Mar. 7, 2018, 4 pages. cited by applicant
Office Action received for Australian Patent Application No. 2018200428, mailed on Nov. 15, 2018, 4 pages. cited by applicant
Office Action received for Australian Patent Application No. 2018206772, mailed on Apr. 1, 2019, 4 pages. cited by applicant
Office Action received for Australian Patent Application No. 2018206772, mailed on Nov. 6, 2019, 4 pages. cited by applicant
Office Action received for Australian Patent Application No. 2018268972, mailed on Jul. 9, 2020, 4 pages. cited by applicant
Office Action received for Australian Patent Application No. 2019100495, mailed on Mar. 6, 2020, 3 pages. cited by applicant
Office Action received for Australian Patent Application No. 2019100495, mailed on Mar. 16, 2020, 3 pages. cited by applicant
Office Action received for Australian Patent Application No. 2019100495, mailed on Sep. 17, 2019, 7 pages. cited by applicant
Office Action received for Australian Patent Application 2019210192, mailed on May 25, 2021, 4 pages. cited by applicant
Office Action received for Australian Patent Application 2019210192, mailed on Sep. 9, 2021, 4 pages. cited by applicant
Office Action received for Australian Patent Application 2019222943, mailed on Oct. 3, 2019, 3 pages. cited by applicant
Office Action received for Australian Patent Application 2019250251, mailed on Aug. 6, 2020, 3 pages. cited by applicant
Office Action received for Australian Patent Application 2020239692, mailed on Jan. 27, 2022, 3 pages. cited by applicant
Office Action received for Australian Patent Application 2020239692, mailed on Jul. 20, 2021, 5 pages. cited by applicant
Office Action received for Australian Patent Application No. 2020239740, mailed on Jul. 9, 2021, 4 pages. cited by applicant
Office Action received for Australian Patent Application No. 2020239740, mailed on Sep. 28, 2021, 5 pages. cited by applicant
Office Action received for Australian Patent Application No. 2020239743, mailed on Mar. 25, 2021, 8 pages. cited by applicant
Office Action received for Australian Patent Application No. 2020239743, mailed on Sep. 3, 2021, 4 pages. cited by applicant
Office Action received for Australian Patent Application No. 2020239748, mailed on Apr. 21, 2021, 6 pages. cited by applicant
Office Action received for Australian Patent Application No. 2020239748, mailed on Feb. 11, 2022, 2 pages. cited by applicant
Office Action received for Australian Patent Application No. 2020239748, mailed on Sep. 1, 2021, 4 pages. cited by applicant
Office Action received for Australian Patent Application No. 2020239752, mailed on Jun. 4, 2021, 8 pages. cited by applicant
Office Action received for Australian Patent Application No. 2020239752, mailed on Oct. 25, 2021, 5 pages. cited by applicant

[illegible]

[illegible]

Office Action received for Indian Patent Application No. 202315061713, mailed on Feb. 14, 2024, 8 pages. cited by applicant

Office Action received for Indian Patent Application No. 202315061718, mailed on Feb. 14, 2024, 8 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2016-535045, mailed on May 12, 2017, 10 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2016-557650, mailed on Apr. 13, 2018, 9 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2016-557650, mailed on Aug. 10, 2017, 10 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2016-557650, mailed on Nov. 9, 2018, 6 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2016-569945, mailed on Jul. 29, 2019, 6 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2016-569945, mailed on Sep. 10, 2018, 11 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2018-014096, mailed on Aug. 28, 2020, 4 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2018-014096, mailed on Jan. 6, 2020, 17 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2018-014096, mailed on Jun. 29, 2018, 20 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2018-014096, mailed on May 8, 2019, 14 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2018-014096, mailed on Nov. 6, 2018, 15 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2018-068846, mailed on Jan. 8, 2019, 6 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2018-184532, mailed on Mar. 1, 2021, 11 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2019-044107, mailed on Jul. 30, 2021, 9 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2019-044107, mailed on May 29, 2020, 6 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2019-162293, mailed on Jan. 31, 2020, 8 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2019-162293, mailed on Jul. 27, 2020, 9 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2019-563407, mailed on Feb. 5, 2021, 5 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2020-000492, mailed on Dec. 11, 2020, 6 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2020-104679, mailed on Sep. 18, 2020, 13 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2020-115940, mailed on May 7, 2021, 3 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2020-160023, mailed on Jan. 17, 2022, 11 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2020-160052, mailed on Dec. 17, 2021, 10 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2020-160053, mailed on Aug. 1, 2022, 8 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2020-160053, mailed on Jan. 31, 2022, 8 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2020-160054, mailed on Jan. 21, 2022, 8 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2020-551585, mailed on Jan. 6, 2022, 11 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2021-153558, mailed on Nov. 21, 2022, 8 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2021-192437, mailed on Dec. 16, 2022, 4 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2021-565912, mailed on Jan. 12, 2023, 9 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2021-565912, mailed on Jun. 26, 2023, 3 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2021-571468, mailed on Jan. 5, 2023, 14 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2022-022159, mailed on Feb. 20, 2023, 10 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2022-076722, mailed on Mar. 13, 2023, 6 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2022-078280, mailed on Jul. 24, 2023, 8 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2022-130087, mailed on Oct. 2, 2023, 12 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2022-131993, mailed on Sep. 15, 2023, 6 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2023-041035, mailed on Feb. 9, 2024, 13 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2023-065859, mailed on Mar. 11, 2024, 8 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2023-110196, mailed on Nov. 6, 2023, 4 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2016-7014577, mailed on Dec. 26, 2017, 14 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2016-7014577, mailed on Oct. 31, 2018, 11 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2016-7033638, mailed on Jan. 31, 2017, 6 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2019-7025538, mailed on Aug. 15, 2020, 8 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2019-7025538, mailed on Feb. 17, 2020, 12 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2019-7025781, mailed on Nov. 26, 2019, 10 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2019-7025781, mailed on Oct. 30, 2020, 10 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2019-7033834, mailed on Jan. 22, 2021, 13 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2020-0123815, mailed on May 31, 2022, 10 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2020-0123821, mailed on Sep. 20, 2022, 11 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2020-0123840, mailed on Nov. 21, 2022, 18 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2020-0124134, mailed on Jul. 28, 2022, 22 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2020-0124134, mailed on Jun. 23, 2023, 8 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2020-0124134, mailed on Mar. 28, 2023, 9 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2020-7023277, mailed on Jan. 26, 2022, 11 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2020-7026035, mailed on Feb. 19, 2021, 13 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2020-7033395, mailed on Aug. 29, 2022, 11 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2021-7026284, mailed on Aug. 31, 2021, 10 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2021-7031939, mailed on Oct. 19, 2021, 11 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2021-7036242, mailed on Sep. 19, 2023, 13 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2022-0061486, mailed on Aug. 29, 2022, 5 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2022-7031866, mailed on Nov. 18, 2022, 11 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2022-7036278, mailed on Jun. 30, 2023, 10 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2022-7036381, mailed on Jan. 6, 2023, 10 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2023-0114488, mailed on Apr. 30, 2024, 16 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2023-7018399, mailed on Jan. 24, 2024, 11 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2023-7025320, mailed on Mar. 11, 2024, 9 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2023-7034892, mailed on Nov. 8, 2023, 5 pages. cited by applicant

Office Action received for Taiwanese Patent Application No. 104117509, issued on Aug. 22, 2016, 6 pages. cited by applicant

Office Action received for Taiwanese Patent Application No. 104128685, mailed on Jan. 4, 2017, 40 pages. cited by applicant

Partial Supplementary European Search Report received for European Patent Application No. 17810749.6, mailed on Apr. 25, 2019, 8 pages. cited by applicant

Prasad et al., "Understanding Sharing Preferences and Behavior for Mhealth Devices", Proceedings of the 2012 ACM workshop on Privacy in the electronic s

Available online at: <https://dl.acm.org/doi/10.1145/2381966.2381983>, Oct. 15, 2012, pp. 117-128. cited by applicant

Pre-Appel Review Report received for Japanese Patent Application No. 2021-565912, mailed on Oct. 12, 2023, 5 pages. cited by applicant

Preliminary Opinion received for European Patent Application No. 15730890.9, mailed on Mar. 7, 2019, 4 pages. cited by applicant

Razykdreviews, “In Depth Review of Apple Watch Activity and Workout App”, available at <URL: <https://www.youtube.com/watch?v=GkKI3qlK0ow>>, Category: X Claims: 1-5 Category: L Reason: Internet citation/video, May 11, 2015, 1 page. cited by applicant

Result of Consultation received for European Patent Application No. 17810749.6, mailed on Dec. 15, 2020, 3 pages. cited by applicant

Result of Consultation received for European Patent Application No. 17810749.6, mailed on Jan. 18, 2021, 3 pages. cited by applicant

Result of Consultation received for European Patent Application No. 17810749.6, mailed on Jan. 21, 2021, 18 pages. cited by applicant

Result of Consultation received for European Patent Application No. 18154145.9, mailed on Nov. 30, 2020, 17 pages. cited by applicant

Result of Consultation received for European Patent Application No. 18154145.9, mailed on Sep. 4, 2020, 3 pages. cited by applicant

Result of Consultation received for European Patent Application No. 18727543.3, mailed on Mar. 15, 2023, 6 pages. cited by applicant

Result of Consultation received for European Patent Application No. 19721883.7, mailed on Oct. 7, 2020, 3 pages. cited by applicant

Result of Consultation received for European Patent Application No. 20203526.7, mailed on Jan. 13, 2023, 3 pages. cited by applicant

Result of Consultation received for European Patent Application No. 20721342.2, mailed on Oct. 18, 2022, 3 pages. cited by applicant

Result of Consultation received for European Patent Application No. 21165295.3, mailed on Apr. 18, 2024, 3 pages. cited by applicant

Result of Consultation received for European Patent Application No. 21168916.1, mailed on Dec. 11, 2023, 25 pages. cited by applicant

Rizknows, “Garmin Connect Mobile App—Review #2”, <https://www.youtube.com/watch?v=7my3wMpeRbE>, Category: X Claims: 1-5 Category: L Reason: Internet citation/video, Oct. 22, 2015, 1 page. cited by applicant

Rizknows, “TomTom Multisport Cardio Review”, Online available at:—<https://www.youtube.com/watch?v=WoVCzLrSN9A>, Sep. 4, 2015, 1 page. cited by applicant

Search report and opinion received for Danish Patent Application No. PA201770191, mailed on Jun. 30, 2017, 9 pages. cited by applicant

Search Report and Opinion received for Danish Patent Application No. PA201770423, mailed on Oct. 4, 2017, 10 pages. cited by applicant

Search Report and Opinion received for Danish Patent Application No. PA201870378, mailed on Sep. 10, 2018, 9 pages. cited by applicant

Search Report and Opinion received for Danish Patent Application No. PA201870379, mailed on Sep. 14, 2018, 9 pages. cited by applicant

Search Report and Opinion received for Danish Patent Application No. PA201970532, mailed on Nov. 8, 2019, 9 pages. cited by applicant

Search Report and Opinion received for Danish Patent Application No. PA202070612, mailed on Jun. 7, 2021, 9 pages. cited by applicant

Search Report and Opinion received for Danish Patent Application No. PA202070613, mailed on Jan. 22, 2021, 9 pages. cited by applicant

Search Report and Opinion received for Danish Patent Application No. PA202070614, mailed on Jan. 14, 2021, 9 pages. cited by applicant

Search Report and Opinion received for Danish Patent Application No. PA202070615, mailed on Jan. 22, 2021, 9 pages. cited by applicant

Search Report and Opinion received for Danish Patent Application No. PA202070616, mailed on Feb. 3, 2021, 8 pages. cited by applicant

Search Report and Opinion received for Danish Patent Application No. PA202070619, mailed on Dec. 2, 2020, 11 pages. cited by applicant

Search Report and Opinion received for Danish Patent Application No. PA202070620, mailed on Dec. 11, 2020, 9 pages. cited by applicant

Search Report and Opinion received for Danish Patent Application No. PA202070815, mailed on Mar. 16, 2021, 8 pages. cited by applicant

Search Report and Opinion received for Danish Patent Application No. PA202170113, mailed on Nov. 30, 2021, 9 pages. cited by applicant

Smith, “Garmin Fenix 5 Activity/Smart Watch Review”, Online Available at:—<https://www.youtube.com/watch?v=6PkQxXQxpOu>, Sep. 2, 2017, 1 page. cited by applicant

Sportstechguides, “Garmin Fenix 5: How to Add Power Data Fields”, Online Available at:—<https://www.youtube.com/watch?v=ZkPptnnXEiQ>, Apr. 29, 2017, 2 pages. cited by applicant

Sportstechguides, “Garmin Fenix 5: How to Set Up Run Alerts”, Online Available at:—<https://www.youtube.com/watch?v=gSMwv8vlhB4>, May 13, 2017, 2 pages. cited by applicant

Summons to attend oral proceedings received for European Patent Application No. 13811085.3, mailed on Jan. 26, 2018, 14 pages. cited by applicant

Summons to Attend Oral Proceedings received for European Patent Application No. 13811085.3, mailed on Mar. 3, 2022, 3 pages. cited by applicant

Summons to Attend Oral Proceedings received for European Patent Application No. 15730890.9, mailed on Sep. 10, 2018, 11 pages. cited by applicant

Summons to Attend Oral Proceedings received for European Patent Application No. 17810749.6, mailed on Aug. 12, 2020, 11 pages. cited by applicant

Summons to Attend Oral Proceedings received for European Patent Application No. 18154145.9, mailed on Sep. 17, 2020, 11 pages. cited by applicant

Summons to Attend Oral Proceedings received for European Patent Application No. 18727543.3, mailed on Oct. 25, 2022, 8 pages. cited by applicant

Summons to Attend Oral Proceedings received for European Patent Application No. 20182116.2, mailed on Dec. 21, 2021, 7 pages. cited by applicant

Summons to Attend Oral Proceedings received for European Patent Application No. 20203526.7, mailed on Jun. 23, 2022, 9 pages. cited by applicant

Summons to Attend Oral Proceedings received for European Patent Application No. 20721342.2, mailed on May 20, 2022, 11 pages. cited by applicant

Summons to Attend Oral Proceedings received for European Patent Application No. 21165295.3, mailed on Jul. 25, 2023, 14 pages. cited by applicant

Summons to Attend Oral Proceedings received for European Patent Application No. 21168916.1, mailed on Jul. 14, 2023, 12 pages. cited by applicant

Summons to Attend Oral Proceedings received for European Patent Application No. 15771747.1, mailed on May 25, 2018, 17 pages. cited by applicant

Summons to Oral Proceedings received for European Patent Application No. 15771747.1, mailed on Apr. 29, 2021, 8 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 15/616,480, mailed on Mar. 28, 2019, 2 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 15/627,069, mailed on Jul. 12, 2021, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 15/925,652, mailed on Feb. 17, 2021, 3 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 15/925,652, mailed on Jan. 6, 2021, 3 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 15/925,652, mailed on Jan. 26, 2021, 3 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 16/144,849, mailed on Mar. 31, 2020, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 16/556,023, mailed on Feb. 3, 2021, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 16/588,950, mailed on Apr. 1, 2020, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 16/588,950, mailed on Jul. 29, 2020, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 16/588,950, mailed on Jun. 18, 2020, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 16/880,714, mailed on Sep. 16, 2021, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 16/894,309, mailed on Apr. 8, 2022, 3 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 16/894,309, mailed on Dec. 24, 2021, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 16/894,309, mailed on Jan. 25, 2022, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 16/994,352, mailed on Jun. 20, 2022, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/030,318, mailed on Apr. 4, 2022, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/030,318, mailed on Feb. 22, 2022, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/030,318, mailed on Mar. 16, 2022, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/030,321, mailed on Apr. 15, 2022, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/030,321, mailed on Jul. 27, 2022, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/030,321, mailed on Jun. 10, 2022, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/030,321, mailed on May 27, 2022, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/030,343, mailed on Jan. 6, 2023, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/030,343, mailed on Nov. 9, 2022, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/030,343, mailed on Oct. 5, 2022, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/031,727, mailed on Jan. 15, 2021, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/041,415, mailed on Oct. 13, 2022, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/041,415, mailed on Sep. 20, 2022, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/192,161, mailed on Jun. 13, 2022, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/192,161, mailed on May 13, 2022, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/317,084, mailed on Jan. 19, 2023, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/317,084, mailed on Sep. 20, 2022, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/381,570, mailed on Aug. 11, 2023, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/381,570, mailed on Sep. 13, 2023, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/666,301, mailed on Jun. 5, 2023, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/666,301, mailed on May 17, 2023, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/852,020, mailed on Aug. 4, 2023, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/951,875, mailed on Aug. 25, 2023, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/952,181, mailed on Dec. 20, 2023, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/952,181, mailed on Oct. 6, 2023, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/952,181, mailed on Oct. 27, 2023, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/952,185, mailed on Nov. 30, 2023, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/952,185, mailed on Oct. 2, 2023, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 18/078,444, mailed on Jun. 15, 2023, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 18/078,444, mailed on Oct. 16, 2023, 4 pages. cited by applicant

Supplementary European Search Report received for European Patent Application No. 17810749.6, mailed on Aug. 6, 2019, 6 pages. cited by applicant

Suunto Spartan Trainer Wrist HR 1.12, Online Available at:—https://web.archive.org/web/20180127155200/https://ns.suunto.com/Manuals/Spartan_Trainer_WristHR/Userguides/Suunto_Spartan_Trainer_WristHR_User

Jan. 17, 2018, 47 pages. cited by applicant

Suunto, “Suunto Spartan—Heart Rate Zones”, Online Available at:—<https://www.youtube.com/watch?v=aixfoCnS0OU>, Mar. 19, 2018, 2 pages. cited by applicant

Tech, Kalyani, “I See Some Problems in Honor Band 5”, retrieved from: <https://www.youtube.com/watch?v=5XPnYJFqajl>, May 19, 2020, 1 page. cited by applicant

Teunmo, “Data field: Visual Pace Alarm”, Garmin Forum; Available online at: <https://forums.garmin.com/forum/developers/connect-iq/connect-iq-showcase/visual-pace-alarm>, Nov. 17, 2015, 10 pages. cited by applicant

Ticks, Smartwatch, “Senbono S10 IP67 Waterproof Multi-Function Blood Pressure Sports Smartwatch: One Minute Overview”, Retrieved from: <https://www.youtube.com/watch?v=rMxLJvKIVBs>, Oct. 30, 2019, 1 page. cited by applicant

TomTom, “TomTom Runner & Multi-Sport Reference Guide”, Online available at:—https://web.archive.org/web/20150908075934/http://download.tomtom.com/open/manuals/Runner_Multi-Sport/refman/TomTom-Runner-Multi-Sport-RG-en

2015, 44 pages. cited by applicant

Updated Notice of Allowance received for U.S. Appl. No. 17/030,318, mailed on Feb. 23, 2023, 3 pages. cited by applicant

Updated Notice of Allowance received for U.S. Appl. No. 17/030,340, mailed on Dec. 2, 2022, 2 pages. cited by applicant

Updated Notice of Allowance received for U.S. Appl. No. 17/030,340, mailed on Nov. 2, 2022, 2 pages. cited by applicant

Updated Notice of Allowance received for U.S. Appl. No. 17/030,340, mailed on Nov. 10, 2022, 2 pages. cited by applicant

Utilization of Galaxy S4-S Health, ChatOn and Samsung Hub, Available at: <http://seeit.kr/1263>, Jun. 12, 2013, 25 pages. cited by applicant

Venusivenus, “Nike Training Club”, Available online at: https://www.youtube.com/watch?v=_pe6fqJPA04, Mar. 28, 2011, 6 pages. cited by applicant

Vicky's Blog, “How to Log In to PS4 Automatically with Particular User?”, Online available on:—<https://www.youtube.com/watch?v=kqdlzXAvOkY>, May 30, 2017, 3 pages. cited by applicant

Visual Pace Alarm app, Available Online at: <https://apps.garmin.com/en-US/apps/3940f3a2-4847-4078-a911-d77422966c82>, Oct. 19, 2016, 1 page. cited by applicant

Wesley, “Apple Watch Series 1”, online available at:—<http://tool-box.info/blog/archives/1737-unknown.html>, May 28, 2015, 5 pages. cited by applicant

Wikipedia, “Enhanced Multi-Level Precedence and Pre-emption Service”, Available online at: https://de.wikipedia.org/w/index.php?title=Enhanced_Multi-Level_Precedence_And_Pre-emption_Service&oldid=123047429, Oct. 2013, 2 pages. cited by applicant

Youtube, “Apple Watch Series 3”, Online available at:—<https://www.youtube.com/watch?v=iBPr9gEfK8>, Nov. 21, 2017, 15 pages. cited by applicant

Yoyodavid, “How to Use Multiple Accounts on the PlayStation 4”, Online available at:—<https://www.youtube.com/watch?v=5V21obRMeKE>, Jan. 9, 2014, 3 pages. cited by applicant

Yuling et al., “Research on Motion Modeling of Virtual Gear Measuring Center”, Tool Technology, vol. 43, No. 2. 2009, pp. 85-87. cited by applicant

Zlelik, “Garmin Fenix 5 Open Water Swimming Activity Demo”, Online Available at:—<https://www.youtube.com/watch?v=iSVhdvw2dcs>, Jun. 9, 2017, 1 page. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2021-131726, mailed on Mar. 17, 2023, 4 pages (1 page of English Translation and 3 pages of Copy). cited by applicant

Office Action received for Japanese Patent Application No. 2021-131726, mailed on Aug. 22, 2022, 8 pages (4 pages of English Translation and 4 pages of Office Copy). cited by applicant

Office Action received for Japanese Patent Application No. 2021-131726, mailed on Dec. 2, 2022, 4 pages (2 pages of English Translation and 2 pages of Office Copy). cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/210,920, mailed on Sep. 3, 2024, 5 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/952,181, mailed on Aug. 28, 2024, 2 pages. cited by applicant

Notice of Acceptance received for Australian Patent Application No. 2023210876, mailed on Aug. 20, 2024, 3 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2023-065859, mailed on Aug. 16, 2024, 4 pages (1 page of English Translation and 3 pages of Copy). cited by applicant

Office Action received for German Patent Application No. 112015007313.2, mailed on Aug. 6, 2024, 12 pages (6 pages of English Translation and 6 pages of Office Copy). cited by applicant

Office Action received for Japanese Patent Application No. 2023-098692, mailed on Aug. 16, 2024, 6 pages (3 pages of English Translation and 3 pages of Office Copy). cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/951,624, mailed on Oct. 3, 2024, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 18/405,969, mailed on Oct. 1, 2024, 2 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/398,810, mailed on Oct. 4, 2024, 18 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 202210312775.7, mailed on Sep. 23, 2024, 5 pages (1 page of English Translation and 4 pages of Copy). cited by applicant

Office Action received for Australian Patent Application No. 2023214377, mailed on Sep. 25, 2024, 4 pages. cited by applicant

Office Action received for Australian Patent Application No. 2023233077, mailed on Sep. 19, 2024, 3 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2023-133506, mailed on Sep. 20, 2024, 6 pages (3 pages of English Translation and 3 pages of Office Copy). cited by applicant

Office Action received for Japanese Patent Application No. 2023-158326, mailed on Sep. 30, 2024, 3 pages (1 page of English Translation and 2 pages of Office Action). cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/031,723, mailed on Aug. 13, 2024, 3 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/952,181, mailed on Aug. 13, 2024, 2 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 24179066.6, mailed on Aug. 8, 2024, 10 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 202310828052.7, mailed on Jul. 29, 2024, 4 pages (1 page of English Translation and 3 pages of Office Action). cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2022-7026884, mailed on Jul. 30, 2024, 8 pages (2 pages of English Translation and 6 pages of Office Action). cited by applicant

Office Action received for Chinese Patent Application No. 202310774963.6, mailed on Jul. 17, 2024, 21 pages (13 pages of English Translation and 8 pages of Office Action). cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 18/135,056, mailed on Nov. 19, 2024, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/952,181, mailed on Nov. 12, 2024, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 18/405,969, mailed on Nov. 13, 2024, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 18/633,120, mailed on Nov. 12, 2024, 9 pages. cited by applicant

Decision to Grant received for German Patent Application No. 112015007313.2, mailed on Nov. 6, 2024, 7 pages (1 page of English Translation and 6 pages of Office Action). cited by applicant

Decision to Grant received for Japanese Patent Application No. 2021-565912, mailed on Nov. 14, 2024, 12 pages (1 page of English Translation and 11 pages of Office Action). cited by applicant

Decision to Grant received for Japanese Patent Application No. 2023-158326, mailed on Nov. 12, 2024, 3 pages (2 pages of English Translation and 1 page of Office Action). cited by applicant

Intention to Grant received for European Patent Application No. 23153898.4, mailed on Nov. 12, 2024, 10 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/210,920, mailed on Nov. 15, 2024, 22 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 202210312598.2, mailed on Nov. 6, 2024, 4 pages (1 page of English Translation and 3 pages of Office Action). cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2023-041035, mailed on Nov. 8, 2024, 4 pages (1 page of English Translation and 3 pages of Office Action). cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/031,723, mailed on Nov. 20, 2024, 8 pages. cited by applicant

Office Action received for Australian Patent Application No. 2023233077, mailed on Oct. 31, 2024, 3 pages. cited by applicant

Office Action received for Australian Patent Application No. 2023251432, mailed on Nov. 13, 2024, 4 pages. cited by applicant

Office Action received for Chinese Patent Application No. 202310774963.6, mailed on Oct. 31, 2024, 19 pages (12 pages of English Translation and 7 pages of Office Action). cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 18/370,833, mailed on Feb. 12, 2025, 4 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2023-097896, mailed on Jan. 31, 2025, 4 pages (1 page of English Translation and 3 pages of Office Action). cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2023-168815, mailed on Jan. 31, 2025, 4 pages (1 page of English Translation and 3 pages of Office Action). cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2024-004643, mailed on Feb. 10, 2025, 4 pages (1 page of English Translation and 3 pages of Office Action). cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2023-0114488, mailed on Jan. 23, 2025, 8 pages (2 pages of English Translation and 6 pages of Office Action). cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/589,265, mailed on Feb. 18, 2025, 10 pages. cited by applicant

Office Action received for Chinese Patent Application No. 202210140789.5, mailed on Jan. 3, 2025, 15 pages (8 pages of English Translation and 7 pages of Office Action). cited by applicant

Office Action received for Chinese Patent Application No. 202210151291.9, mailed on Jan. 9, 2025, 29 pages (18 pages of English Translation and 11 pages of Office Action). cited by applicant

Office Action received for European Patent Application No. 22194355.8, mailed on Dec. 6, 2024, 10 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2024-7013569, mailed on Dec. 16, 2024, 12 pages (5 pages of English Translation and 7 pages of Office Action). cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2024-213755, mailed on Mar. 10, 2025, 4 pages (1 page of English Translation and 3 pages of Office Action). cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/370,833, mailed on Mar. 19, 2025, 10 pages. cited by applicant

Office Action received for Australian Patent Application No. 2024200029, mailed on Mar. 12, 2025, 4 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 18/589,265, mailed on Feb. 26, 2025, 2 pages. cited by applicant

Examiner's Answer to Appeal Brief received for U.S. Appl. No. 16/249,627, mailed on Feb. 26, 2025, 9 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 18/789,495, mailed on Mar. 4, 2025, 39 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 202310774963.6, mailed on Feb. 18, 2025, 4 pages (1 page of English Translation and 3 pages of Office Action). cited by applicant

Office Action received for Chinese Patent Application No. 202310774963.6, mailed on Feb. 12, 2025, 2 pages (1 page of English Translation and 1 page of Office Action). cited by applicant

Office Action received for European Patent Application No. 23150297.2, mailed on Feb. 28, 2025, 4 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 18/789,495, mailed on Jan. 24, 2025, 6 pages. cited by applicant

Board Decision received for Chinese Patent Application No. 202211193170.7, mailed on Nov. 21, 2024, 17 pages (1 page of English Translation and 16 pages of Office Action). cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/031,723, mailed on Dec. 6, 2024, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/031,723, mailed on Dec. 19, 2024, 2 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/210,920, mailed on Jan. 30, 2025, 21 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/398,810, mailed on Jan. 13, 2025, 11 pages. cited by applicant

Intention to Grant received for European Patent Application No. 20760607.0, mailed on Dec. 23, 2024, 10 pages. cited by applicant

Intention to Grant received for European Patent Application No. 22731852.4, mailed on Dec. 17, 2024, 9 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2023/024104, mailed on Dec. 19, 2024, 11 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2023/024185, mailed on Dec. 19, 2024, 9 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2024/023603, mailed on Aug. 14, 2024, 17 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2024/027314, mailed on Aug. 23, 2024, 13 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2024/031346, mailed on Dec. 6, 2024, 17 pages. cited by applicant

Invitation to Pay Additional Fees and Partial International Search Report received for PCT Patent Application No. PCT/US2024/031346, mailed on Oct. 14, 2024, 2 pages (1 page of English Translation and 1 page of Official Copy). cited by applicant

Invitation to pay search fee received for European Patent Application No. 23735495.6, mailed on Jan. 28, 2025, 5 pages. cited by applicant

Invitation to Pay Search Fees received for European Patent Application No. 21763459.1, mailed on Nov. 21, 2024, 3 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 18/370,833, mailed on Jan. 29, 2025, 11 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 18/628,586, mailed on Dec. 2, 2024, 13 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 18/663,024, mailed on Dec. 18, 2024, 13 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 18/789,495, mailed on Oct. 22, 2024, 37 pages. cited by applicant

Notice of Acceptance received for Australian Patent Application No. 2023233077, mailed on Jan. 6, 2025, 3 pages. cited by applicant

Notice of Acceptance received for Australian Patent Application No. 2023251432, mailed on Jan. 17, 2025, 3 pages. cited by applicant

Notice of Acceptance received for Australian Patent Application No. 2023285859, mailed on Nov. 28, 2024, 3 pages. cited by applicant

Notice of Acceptance received for Australian Patent Application No. 2024200284, mailed on Jan. 16, 2025, 3 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 202311811912.2, mailed on Dec. 1, 2024, 5 pages (1 page of English Translation and 4 pages of Official Copy). cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2023-133506, mailed on Nov. 22, 2024, 4 pages (1 page of English Translation and 3 pages of Official Copy). cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2023-171409, mailed on Nov. 15, 2024, 4 pages (1 page of English Translation and 3 pages of Official Copy). cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/951,624, mailed on Jan. 15, 2025, 5 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/952,236, mailed on Nov. 25, 2024, 10 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/135,056, mailed on Jan. 16, 2025, 9 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/589,265, mailed on Dec. 6, 2024, 9 pages. cited by applicant

Office Action received for Australian Patent Application No. 2023214377, mailed on Jan. 17, 2025, 3 pages. cited by applicant

Office Action received for Australian Patent Application No. 2023258443, mailed on Jan. 15, 2025, 4 pages. cited by applicant

Office Action received for Australian Patent Application No. 2024200029, mailed on Dec. 4, 2024, 3 pages. cited by applicant

Office Action received for Australian Patent Application No. 2024200029, mailed on Jan. 17, 2025, 3 pages. cited by applicant

Office Action received for Chinese Patent Application No. 202080039364.4, mailed on Jan. 1, 2025, 13 pages (7 pages of English Translation and 6 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202210141337.9, mailed on Dec. 31, 2024, 14 pages (7 pages of English Translation and 7 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202210312598.2, mailed on Jun. 27, 2024, 22 pages (7 pages of English Translation and 15 pages of Official Copy). cited by applicant

Office Action received for European Patent Application No. 21763459.1, mailed on Jan. 29, 2025, 10 pages. cited by applicant

Office Action received for European Patent Application No. 23192409.3, mailed on Dec. 10, 2024, 9 pages. cited by applicant

Office Action received for European Patent Application No. 23735495.6, mailed on Nov. 22, 2024, 7 pages. cited by applicant

Office Action received for Korean Patent Application No. 10-2021-7043369, mailed on Nov. 18, 2024, 14 pages (6 pages of English Translation and 8 pages of Official Copy). cited by applicant

Office Action received for Korean Patent Application No. 10-2024-7034316, mailed on Dec. 2, 2024, 7 pages (3 pages of English Translation and 4 pages of Official Copy). cited by applicant

Summons to Attend Oral Proceedings received for European Patent Application No. 19703582.7, mailed on Jan. 3, 2025, 11 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 18/589,265, mailed on Dec. 18, 2024, 2 pages. cited by applicant

Decision to Grant received for European Patent Application No. 23153898.4, mailed on Mar. 6, 2025, 4 pages. cited by applicant

Invitation to Pay Search Fees received for European Patent Application No. 21734715.2, mailed on Mar. 6, 2025, 4 pages. cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2021-7036242, mailed on Feb. 24, 2025, 7 pages (2 pages of English Translation and 5 pages of Official Copy). cited by applicant

Anonymous, "Forerunner 935 Owner's Manual", XP055953951, Available online at: <<https://www8.garmin.com/manuals/webhelp/forerunner935/EN-US/GUID-00000000-0000-0000-0000-000000000000/C95D-460A-A165-729F18B5D827-homepage.html>, Jun. 30, 2020, 46 pages. cited by applicant

Board Opinion received for Chinese Patent Application No. 201910858933.7, mailed on Mar. 24, 2025, 13 pages (5 pages of English Translation and 8 pages of Official Copy). cited by applicant

Intention to Grant received for European Patent Application No. 20760607.0, mailed on Mar. 25, 2025, 10 pages. cited by applicant

Intention to Grant received for European Patent Application No. 23189089.8, mailed on Apr. 3, 2025, 9 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2023/030718, mailed on Mar. 20, 2025, 8 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2024-032418, mailed on Mar. 21, 2025, 4 pages (1 page of English Translation and 3 pages of Official Copy). cited by applicant

Office Action received for European Patent Application No. 23153899.2, mailed on Apr. 4, 2025, 4 pages. cited by applicant

Office Action received for European Patent Application No. 23735495.6, mailed on Mar. 31, 2025, 13 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 18/789,495, mailed on Jun. 5, 2025, 5 pages. cited by applicant

Board Decision received for Chinese Patent Application No. 201910858933.7, mailed on May 7, 2025, 21 pages (5 pages of English Translation and 16 pages of Official Copy). cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 18/370,833, mailed on Apr. 23, 2025, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 18/370,833, mailed on Jun. 5, 2025, 2 pages. cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 18/663,024, mailed on May 20, 2025, 2 pages. cited by applicant

Decision to Grant received for European Patent Application No. 20760607.0, mailed on May 15, 2025, 3 pages. cited by applicant

Decision to Grant received for European Patent Application No. 22731852.4, mailed on Apr. 17, 2025, 3 pages. cited by applicant

Examiner's Answer to Appeal Brief received for U.S. Appl. No. 17/210,920, mailed on May 23, 2025, 14 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 25156484.5, mailed on May 13, 2025, 8 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 25159768.8, mailed on May 27, 2025, 10 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 25164739.2, mailed on Jun. 2, 2025, 8 pages. cited by applicant

Intention to Grant received for European Patent Application No. 21734715.2, mailed on May 12, 2025, 12 pages. cited by applicant

Intention to Grant received for European Patent Application No. 23153900.8, mailed on Apr. 16, 2025, 11 pages. cited by applicant

Kordiyak et al., "Analytical Review of Medical Mobile Diagnostic Systems", Econtechmod, An International Quarterly Journal, vol. 05, No. 2, 2016, pp. 11-14. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2022-130087, mailed on May 12, 2025, 3 pages (1 page of English Translation and 2 pages of Official Copy). cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2025-033114, mailed on Jun. 16, 2025, 4 pages (1 page of English Translation and 3 pages of Official Copy). cited by applicant

Copy), cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/370,833, mailed on May 22, 2025, 6 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/663,024, mailed on May 7, 2025, 9 pages. cited by applicant

Office Action received for Australian Patent Application No. 2024203043, mailed on May 8, 2025, 2 pages. cited by applicant

Office Action received for European Patent Application No. 23734424.7, mailed on May 22, 2025, 8 pages. cited by applicant

Office Action received for European Patent Application No. 24152191.3, mailed on Jun. 13, 2025, 6 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2025-033114, mailed on May 12, 2025, 4 pages (2 pages of English Translation and 2 pages of Office Action). cited by applicant

Result of Consultation received for European Patent Application No. 23189089.8, mailed on Jun. 2, 2025, 3 pages. cited by applicant

Primary Examiner: Sun; Hai Tao

Attorney, Agent or Firm: DLA Piper LLP (US)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. non-provisional patent application Ser. No. 17/735,395, entitled "WELLNESS AGGREGATOR," filed May 3, 2022, which is a continuation of U.S. non-provisional patent application Ser. No. 16/820,383, entitled "WELLNESS AGGREGATOR," filed Mar. 16, 2020, which is a continuation of U.S. non-provisional patent application Ser. No. 14/732,773, entitled "WELLNESS AGGREGATOR", filed Jun. 7, 2015, which is a continuation-in-part of International Application PCT/US2013/073195, entitled "WELLNESS AGGREGATOR", filed Dec. 4, 2013, and a continuation-in-part of International Application PCT/US2015/032474, entitled "WELLNESS AGGREGATOR", filed May 26, 2015, which claims priority to U.S. Provisional Patent Application Ser. No. 62/129,945, entitled "WELLNESS AGGREGATOR", filed Mar. 8, 2015, and U.S. Provisional Patent Application Ser. No. 62/006,032, entitled "WELLNESS AGGREGATOR", filed May 30, 2014. U.S. non-provisional patent application Ser. No. 14/732,773 is a continuation-in-part of U.S. non-provisional patent application Ser. No. 14/599,424, entitled "WELLNESS AGGREGATOR", filed Jan. 16, 2015, which claims priority to U.S. Provisional Patent Application Ser. No. 62/006,032, entitled "WELLNESS AGGREGATOR", filed May 30, 2014. The content of these applications is hereby incorporated by reference herein. (2) This application relates to U.S. Provisional Patent Application Ser. No. 62/006,031, entitled "MANAGING USER INFORMATION," filed May 30, 2014, the content of which is hereby incorporated by reference herein.

FIELD

(1) The following disclosure relates generally to data management and, more specifically, to aggregating and sharing wellness data.

BACKGROUND

(2) Approximately 133 million Americans currently suffer from at least one chronic condition. This number is expected to rise to approximately 165 million by the year 2020. As a result, the cost of healthcare in the United States is expected to increase dramatically. Attempts have been made to improve the health of individuals by providing them with tools to monitor and, track their wellness data. Wellness data can generally include any type of data associated with a person's health, such as their weight, heart rate, blood pressure, blood glucose level, medication compliance, activity level, or the like. Users can monitor their wellness using devices, such as blood pressure cuffs, blood glucose monitors, electrocardiograms, step counters, and the like. Software applications (e.g., Apps) associated with each of these devices have also been developed to allow users to track their wellness data over time. While each application can be used to view useful information about a user's health, current applications are limited in their ability to allow users to store, view, and share wellness data collected by different devices.

SUMMARY

(3) The present disclosure relates to processes for aggregating and sharing wellness data. One example process can include causing a display of an aggregated view of a plurality of types of wellness data, wherein the aggregated view comprises a plurality of partitions, each partition of the plurality of partitions associated with a type of the plurality of types of wellness data; receiving a selection of a partition of the plurality of partitions; and causing a display of an expanded view of the selected partition of the plurality of partitions.

(4) An example process can include display, on the display screen, a graph comprising: a first data-set representation of a first data set in which a first dependent variable varies as an independent variable changes and a second data-set representation of a second data set in which a second dependent variable varies as the independent variable changes, wherein the first data-set representation comprises a plurality of indicators corresponding to values of the dependent variables of the first data-set representation, wherein the second data-set representation is associated with a range of vertical positions within the graph, wherein the dependent variables of the first data set are chosen from a set of discrete values; detect, at a respective location on the display screen, a user input; in response to detecting the user input: in accordance with a determination that the respective location corresponds to an indicator of the plurality of indicators, display, on the display screen, an indication that the first data-set representation has been selected; and in accordance with a determination that the respective location is within the range of vertical positions associated with the second data-set representation, but away from the plurality of indicators, display, on the display screen, an indication that the second data-set representation has been selected.

(5) Devices and non-transitory computer-readable storage media for performing these processes are also provided.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) For a better understanding of the various described embodiments, reference should be made to the Description of Embodiments below, in conjunction with the following drawings in which like reference numerals refer to corresponding parts throughout the figures.

(2) FIG. 1A is a block diagram illustrating a portable multifunction device with a touch-sensitive display in accordance with some embodiments.

(3) FIG. 1B is a block diagram illustrating exemplary components for event handling in accordance with some embodiments.

(4) FIG. 2 illustrates a portable multifunction device having a touch screen in accordance with some embodiments.

(5) FIG. 3 is a block diagram of an exemplary multifunction device with a display and a touch-sensitive surface in accordance with some embodiments.

(6) FIG. 4A illustrates an exemplary user interface for a menu of applications on a portable multifunction device in accordance with some embodiments.

(7) FIG. 4B illustrates an exemplary user interface for a multifunction device with a touch-sensitive surface that is separate from the display in accordance with some embodiments.

(8) FIG. 5A illustrates a personal electronic device in accordance with some embodiments.

(9) FIG. 5B is a block diagram illustrating a personal electronic device in accordance with some embodiments.

(10) FIG. 6 illustrates a block diagram of an example system for aggregating wellness data according to various examples.

(11) FIG. 7 illustrates a block diagram of an example system for sharing wellness data according to various examples.
 (12) FIG. 8 illustrates an example process for authorizing and pushing wellness data to authorized other users according to various examples.
 (13) FIG. 9 illustrates an example process for authorizing users to pull wellness data according to various examples.
 (14) FIG. 10 illustrate example interfaces for displaying aggregated wellness data according to various examples.
 (15) FIG. 11 illustrates example interfaces for displaying aggregated wellness data according to various examples.
 (16) FIG. 12 illustrates example interfaces for displaying aggregated wellness data according to various examples.
 (17) FIG. 13 illustrates example interfaces for displaying aggregated wellness data according to various examples.
 (18) FIG. 14 illustrates example interfaces for displaying aggregated wellness data according to various examples.
 (19) FIG. 15 illustrates example interfaces for displaying aggregated wellness data according to various examples.
 (20) FIG. 16 illustrates an example process for displaying aggregated wellness data according to various examples.
 (21) FIG. 17 illustrates an example interface for displaying aggregated wellness data according to various examples.
 (22) FIG. 18 illustrates an example process for displaying aggregated wellness data according to various examples.
 (23) FIG. 19 illustrates an example interface for displaying aggregated wellness data of other users according to various examples.
 (24) FIG. 20 illustrates another example interface for displaying aggregated wellness data of other users according to various examples.
 (25) FIG. 21 illustrates an example process for displaying aggregated wellness data of other users according to various examples.
 (26) FIG. 22 illustrates example interfaces for displaying wellness or non-wellness data according to various examples.
 (27) FIG. 23 illustrates example interfaces for displaying wellness or non-wellness data according to various examples.
 (28) FIG. 24 illustrates example interfaces for displaying wellness or non-wellness data according to various examples.
 (29) FIGS. 25A and 25B illustrate example interfaces for displaying wellness or non-wellness data according to various examples.
 (30) FIG. 26 illustrates example interfaces for displaying wellness or non-wellness data according to various examples.
 (31) FIG. 27 illustrates an example process for displaying wellness or non-wellness data according to various examples.
 (32) FIG. 28 illustrates example interfaces for displaying wellness or non-wellness data according to various examples.
 (33) FIG. 29 illustrates example interfaces for displaying wellness or non-wellness data according to various examples.
 (34) FIG. 30 illustrates example interfaces for displaying wellness or non-wellness data according to various examples.
 (35) FIG. 31 illustrates example interfaces for displaying wellness or non-wellness data according to various examples.
 (36) FIG. 32 illustrates example interfaces for displaying wellness or non-wellness data according to various examples.
 (37) FIG. 33 illustrates example interfaces for displaying wellness or non-wellness data according to various examples.
 (38) FIG. 34 illustrates example interfaces for displaying wellness or non-wellness data according to various examples.
 (39) FIG. 35 illustrates example interfaces for displaying wellness or non-wellness data according to various examples.
 (40) FIG. 36 illustrates example interfaces for displaying wellness or non-wellness data according to various examples.
 (41) FIG. 37 illustrates example interfaces for displaying wellness or non-wellness data according to various examples.
 (42) FIGS. 38A and 38B illustrate an example process for managing and displaying wellness or non-wellness data according to various examples.
 (43) FIG. 39 illustrates example interfaces for displaying emergency medical information according to various examples.
 (44) FIG. 40 illustrates example interfaces for displaying emergency medical information according to various examples.
 (45) FIG. 41 illustrates example interfaces for displaying emergency medical information according to various examples.
 (46) FIG. 42 illustrates example interfaces for displaying emergency medical information according to various examples.
 (47) FIG. 43 illustrates example interfaces for displaying emergency medical information according to various examples.
 (48) FIG. 44 illustrates example interfaces for displaying emergency medical information according to various examples.
 (49) FIG. 45 illustrates an example process for displaying emergency medical information according to various examples.
 (50) FIG. 46 illustrates an example computing system for aggregating and sharing wellness data according to various examples.
 (51) FIG. 47 illustrates a functional block diagram of an electronic device configured to display wellness or non-wellness data according to various examples.
 (52) FIG. 48 illustrates a functional block diagram of an electronic device configured to manage and display wellness or non-wellness data according to various examples.
 (53) FIG. 49 illustrates a functional block diagram of an electronic device configured to display emergency medical information according to various examples.
 (54) FIG. 50 illustrates a functional block diagram of an electronic device configured to display wellness or non-wellness data according to various examples.
 (55) FIG. 51 illustrates a functional block diagram of an electronic device configured to display wellness or non-wellness data according to various examples.
 (56) FIG. 52 illustrates a functional block diagram of an electronic device configured to display wellness or non-wellness data according to various examples.
 (57) FIG. 53 illustrates a functional block diagram of an electronic device configured to display wellness or non-wellness data according to various examples.
 (58) FIG. 54 illustrates a functional block diagram of an electronic device configured to display wellness or non-wellness data according to various examples.
 (59) FIGS. 55A and 55B illustrate exemplary interfaces for displaying wellness or non-wellness data according to various examples.
 (60) FIGS. 56A-56D illustrate exemplary interfaces for displaying wellness or non-wellness data according to various examples.
 (61) FIGS. 57A-57D illustrate exemplary interfaces for displaying wellness or non-wellness data according to various examples.
 (62) FIGS. 58A-58D illustrate exemplary interfaces for displaying wellness or non-wellness data according to various examples.
 (63) FIGS. 59A-59D illustrate exemplary interfaces for displaying wellness or non-wellness data according to various examples.
 (64) FIGS. 60A-60D illustrate exemplary interfaces for displaying wellness or non-wellness data according to various examples.
 (65) FIGS. 61A-61D illustrate exemplary interfaces for displaying wellness or nonwellness data according to various examples.
 (66) FIGS. 62A and 62B illustrate exemplary interfaces for displaying wellness or nonwellness data according to various examples.
 (67) FIG. 63 illustrates an example interface for inputting wellness or non-wellness data according to various examples.
 (68) FIGS. 64A-64F illustrate exemplary interfaces for displaying wellness or non-wellness data according to various examples.
 (69) FIGS. 65A-65C illustrate exemplary interfaces for displaying wellness or non-wellness data according to various examples.
 (70) FIGS. 66A and 66B illustrate exemplary interfaces for displaying wellness or nonwellness data according to various examples.

DESCRIPTION OF EMBODIMENTS

(71) The following description sets forth exemplary methods, parameters, and the like. It should be recognized, however, that such description is not intended as a limitation on the scope of the present disclosure but is instead provided as a description of exemplary embodiments.

(72) The present disclosure relates to aggregating and sharing wellness data. The wellness data can be received by a user device from any number of sensors external or internal to the user device, from a user manually entering the wellness data, or from other users or entities. The user device can securely store the wellness data on the user device and transmit the wellness data to be stored on a remote database. A user of the device can share some or all of the wellness data with friends, relatives, caregivers, healthcare providers, or the like. The user device can further display a user's

wellness data in an aggregated view of different types of wellness data. For example, the aggregated view can include a set of partitions, where each partition corresponds to a different type of wellness data. Wellness data of other users can also be viewed if authorizations from those users have been received. In some examples, the partitions can be displayed as having the appearance and associated animations of a stack of cards, where each card corresponds to a different partition (and thus, a different type of wellness data). In this view of stacked cards, each card can display a partial view of a portion of its corresponding wellness data. When the user selects one of the cards, a first expanded view of the selected card including at least one of first reconfigured data, additional data, or an expanded view of the original data can be displayed. A second expanded view of the selected card can be displayed in response to a change in the orientation of the user device. The second expanded view can include at least one of second reconfigured data, additional data, or an expanded view of the original data can be displayed. In one example, the second expanded view can include a graph of the wellness data over time.

(73) Below, FIGS. 1A-1B, 2, 3, 4A-4B, and 5A-5B provide a description of exemplary devices for performing the techniques for sharing wellness data. FIGS. 10-15, 17, 19-20, 22-26, 28-37, 39-44, and 55-66 illustrate exemplary user interfaces for sharing wellness data. The user interfaces in the figures are also used to illustrate the processes described below, including the processes in FIGS. 8, 9, 16, 18, 21, 27, 38A-B, and 45.

(74) Although the following description uses terms “first,” “second,” etc. to describe various elements, these elements should not be limited by the terms. These terms are only used to distinguish one element from another. For example, a first touch could be termed a second touch, and, similarly, a second touch could be termed a first touch, without departing from the scope of the various described embodiments. The first touch and the second touch are both touches, but they are not the same touch.

(75) The terminology used in the description of the various described embodiments herein is for the purpose of describing particular embodiments only and is not intended to be limiting. As used in the description of the various described embodiments and the appended claims, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will also be understood that the term “and/or” as used herein refers to and encompasses any and all possible combinations of one or more of the associated listed items. It will be further understood that the terms “includes,” “including,” “comprises,” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

(76) The term “if” may be construed to mean “when” or “upon” or “in response to determining” or “in response to detecting,” depending on the context. Similarly, the phrase “if it is determined” or “if [a stated condition or event] is detected” may be construed to mean “upon determining” or “in response to determining” or “upon detecting [the stated condition or event]” or “in response to detecting [the stated condition or event],” depending on the context.

(77) Embodiments of electronic devices, user interfaces for such devices, and associated processes for using such devices are described. In some embodiments, the device is a portable communications device, such as a mobile telephone, that also contains other functions, such as PDA and/or music player functions. Exemplary embodiments of portable multifunction devices include, without limitation, the iPhone®, iPod Touch®, and iPad® devices from Apple Inc. of Cupertino, California. Other portable electronic devices, such as laptops or tablet computers with touch-sensitive surfaces (e.g., touch screen displays and/or touchpads), are, optionally, used. It should also be understood that, in some embodiments, the device is not a portable communications device, but is a desktop computer with a touch-sensitive surface (e.g., a touch screen display and/or a touchpad).

(78) In the discussion that follows, an electronic device that includes a display and a touch-sensitive surface is described. It should be understood, however, that the electronic device optionally includes one or more other physical user-interface devices, such as a physical keyboard, a mouse, and/or a joystick.

(79) The device may support a variety of applications, such as one or more of the following: a drawing application, a presentation application, a word processing application, a website creation application, a disk authoring application, a spreadsheet application, a gaming application, a telephone application, a video conferencing application, an e-mail application, an instant messaging application, a workout support application, a photo management application, a digital camera application, a digital video camera application, a web browsing application, a digital music player application, and/or a digital video player application.

(80) The various applications that are executed on the device optionally use at least one common physical user-interface device, such as the touch-sensitive surface. One or more functions of the touch-sensitive surface as well as corresponding information displayed on the device are, optionally, adjusted and/or varied from one application to the next and/or within a respective application. In this way, a common physical architecture (such as the touch-sensitive surface) of the device optionally supports the variety of applications with user interfaces that are intuitive and transparent to the user.

(81) Attention is now directed toward embodiments of portable devices with touch-sensitive displays. FIG. 1A is a block diagram illustrating portable multifunction device **100** with touch-sensitive display system **112** in accordance with some embodiments. Touch-sensitive display **112** is sometimes called a “touch screen” for convenience and is sometimes known as or called a “touch-sensitive display system.” Device **100** includes memory **102** (which optionally includes one or more computer-readable storage mediums), memory controller **122**, one or more processing units (CPUs) **120**, peripherals interface **118**, RF circuitry **108**, audio circuitry **110**, speaker **111**, microphone **113**, input/output (I/O) subsystem **106**, other input control devices **116**, and external port **124**. Device **100** optionally includes one or more optical sensors **164**. Device **100** optionally includes one or more contact intensity sensors **165** for detecting intensity of contacts on device **100** (e.g., a touch-sensitive surface such as touch-sensitive display system **112** of device **100**). Device **100** optionally includes one or more tactile output generators **167** for generating tactile outputs on device **100** (e.g., generating tactile outputs on a touch-sensitive surface such as touch-sensitive display system **112** of device **100** or touchpad **355** of device **300**). These components optionally communicate over one or more communication buses or signal lines **103**.

(82) As used in the specification and claims, the term “intensity” of a contact on a touch-sensitive surface refers to the force or pressure (force per unit area) of a contact (e.g., a finger contact) on the touch-sensitive surface, or to a substitute (proxy) for the force or pressure of a contact on the touch-sensitive surface. The intensity of a contact has a range of values that includes at least four distinct values and more typically includes hundreds of distinct values (e.g., at least 256). Intensity of a contact is, optionally, determined (or measured) using various approaches and various sensors or combinations of sensors. For example, one or more force sensors underneath or adjacent to the touch-sensitive surface are, optionally, used to measure force at various points on the touch-sensitive surface. In some implementations, force measurements from multiple force sensors are combined (e.g., a weighted average) to determine an estimated force of a contact. Similarly, a pressure-sensitive tip of a stylus is, optionally, used to determine a pressure of the stylus on the touch-sensitive surface. Alternatively, the size of the contact area detected on the touch-sensitive surface and/or changes thereto, the capacitance of the touch-sensitive surface proximate to the contact and/or changes thereto, and/or the resistance of the touch-sensitive surface proximate to the contact and/or changes thereto are, optionally, used as a substitute for the force or pressure of the contact on the touch-sensitive surface. In some implementations, the substitute measurements for contact force or pressure are used directly to determine whether an intensity threshold has been exceeded (e.g., the intensity threshold is described in units corresponding to the substitute measurements). In some implementations, the substitute measurements for contact force or pressure are converted to an estimated force or pressure, and the estimated force or pressure is used to determine whether an intensity threshold has been exceeded (e.g., the intensity threshold is a pressure threshold measured in units of pressure). Using the intensity of a contact as an attribute of a user input allows for user access to additional device functionality that may otherwise not be accessible by the user on a reduced-size device with limited real estate for displaying affordances (e.g., on a touch-sensitive display) and/or receiving user input (e.g., via a touch-sensitive display, a touch-sensitive surface, or a physical/mechanical control such as a knob or a button).

(83) As used in the specification and claims, the term “tactile output” refers to physical displacement of a device relative to a previous position of the device, physical displacement of a component (e.g., a touch-sensitive surface) of a device relative to another component (e.g., housing) of the device,

or displacement of the component relative to a center of mass of the device will be detected by a user with the user's sense of touch. For example, in situations where the device or the component of the device is in contact with a surface of a user that is sensitive to touch (e.g., a finger, palm, or other part of a user's hand), the tactile output generated by the physical displacement will be interpreted by the user as a tactile sensation corresponding to a perceived change in physical characteristics of the device or the component of the device. For example, movement of a touch-sensitive surface (e.g., a touch-sensitive display or trackpad) is, optionally, interpreted by the user as a "down click" or "up click" of a physical actuator button. In some cases, a user will feel a tactile sensation such as an "down click" or "up click" even when there is no movement of a physical actuator button associated with the touch-sensitive surface that is physically pressed (e.g., displaced) by the user's movements. As another example, movement of the touch-sensitive surface is, optionally, interpreted or sensed by the user as "roughness" of the touch-sensitive surface, even when there is no change in smoothness of the touch-sensitive surface. While such interpretations of touch by a user will be subject to the individualized sensory perceptions of the user, there are many sensory perceptions of touch that are common to a large majority of users. Thus, when a tactile output is described as corresponding to a particular sensory perception of a user (e.g., an "up click," a "down click," "roughness"), unless otherwise stated, the generated tactile output corresponds to physical displacement of the device or a component thereof that will generate the described sensory perception for a typical (or average) user.

(84) It should be appreciated that device **100** is only one example of a portable multifunction device, and that device **100** optionally has more or fewer components than shown, optionally combines two or more components, or optionally has a different configuration or arrangement of the components. The various components shown in FIG. **1A** are implemented in hardware, software, or a combination of both hardware and software, including one or more signal processing and/or application-specific integrated circuits.

(85) Memory **102** may include one or more computer-readable storage mediums. The computer-readable storage mediums may be tangible and non-transitory. Memory **102** may include high-speed random access memory and may also include non-volatile memory, such as one or more magnetic disk storage devices, flash memory devices, or other non-volatile solid-state memory devices. Memory controller **122** may control access to memory **102** by other components of device **100**.

(86) Peripherals interface **118** can be used to couple input and output peripherals of the device to CPU **120** and memory **102**. The one or more processors **120** run or execute various software programs and/or sets of instructions stored in memory **102** to perform various functions for device **100** and to process data. In some embodiments, peripherals interface **118**, CPU **120**, and memory controller **122** may be implemented on a single chip, such as chip **104**. In some other embodiments, they may be implemented on separate chips.

(87) RF (radio frequency) circuitry **108** receives and sends RF signals, also called electromagnetic signals. RF circuitry **108** converts electrical signals to/from electromagnetic signals and communicates with communications networks and other communications devices via the electromagnetic signals. RF circuitry **108** optionally includes well-known circuitry for performing these functions, including but not limited to an antenna system, an RF transceiver, one or more amplifiers, a tuner, one or more oscillators, a digital signal processor, a CODEC chipset, a subscriber identity module (SIM) card, memory, and so forth. RF circuitry **108** optionally communicates with networks, such as the Internet, also referred to as the World Wide Web (WWW), an intranet and/or a wireless network, such as a cellular telephone network, a wireless local area network (LAN) and/or a metropolitan area network (MAN), and other devices by wireless communication. The RF circuitry **108** optionally includes well-known circuitry for detecting near field communication (NFC) fields, such as by a short-range communication radio. The wireless communication optionally uses any of a plurality of communications standards, protocols, and technologies, including but not limited to Global System for Mobile Communications (GSM), Enhanced Data GSM Environment (EDGE), high-speed downlink packet access (HSDPA), high-speed uplink packet access (HSUPA), Evolution, Data-Only (EV-DO), HSPA, HSPA+, Dual-Cell HSPA (DC-HSPDA), long term evolution (LTE), near field communication (NFC), wideband code division multiple access (W-CDMA), code division multiple access (CDMA), time division multiple access (TDMA), Bluetooth, Bluetooth Low Energy (BTLE), Wireless Fidelity (Wi-Fi) (e.g., IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, and/or IEEE 802.11ac), voice over Internet Protocol (VoIP), Wi-MAX, a protocol for e-mail (e.g., Internet message access protocol (IMAP) and/or post office protocol (POP)), instant messaging (e.g., extensible messaging and presence protocol (XMPP), Session Initiation Protocol for Instant Messaging and Presence Leveraging Extensions (SIMPLE), Instant Messaging and Presence Service (IMPS)), and/or Short Message Service (SMS), or any other suitable communication protocol, including communication protocols not yet developed as of the filing date of this document.

(88) Audio circuitry **110**, speaker **111**, and microphone **113** provide an audio interface between a user and device **100**. Audio circuitry **110** receives audio data from peripherals interface **118**, converts the audio data to an electrical signal, and transmits the electrical signal to speaker **111**. Speaker **111** converts the electrical signal to human-audible sound waves. Audio circuitry **110** also receives electrical signals converted by microphone **113** from sound waves. Audio circuitry **110** converts the electrical signal to audio data and transmits the audio data to peripherals interface **118** for processing. Audio data may be retrieved from and/or transmitted to memory **102** and/or RF circuitry **108** by peripherals interface **118**. In some embodiments, audio circuitry **110** also includes a headset jack (e.g., **212**, FIG. **2**). The headset jack provides an interface between audio circuitry **110** and removable audio input/output peripherals, such as output-only headphones or a headset with both output (e.g., a headphone for one or both ears) and input (e.g., a microphone).

(89) I/O subsystem **106** couples input/output peripherals on device **100**, such as touch screen **112** and other input control devices **116**, to peripherals interface **118**. I/O subsystem **106** optionally includes display controller **156**, optical sensor controller **158**, intensity sensor controller **159**, haptic feedback controller **161**, and one or more input controllers **160** for other input or control devices. The one or more input controllers **160** receive/send electrical signals from/to other input control devices **116**. The other input control devices **116** optionally include physical buttons (e.g., push buttons, rocker buttons, etc.), dials, slider switches, joysticks, click wheels, and so forth. In some alternate embodiments, input controller(s) **160** are, optionally, coupled to any (or none) of the following: a keyboard, an infrared port, a USB port, and a pointer device such as a mouse. The one or more buttons (e.g., **208**, FIG. **2**) optionally include an up/down button for volume control of speaker **111** and/or microphone **113**. The one or more buttons optionally include a push button (e.g., **206**, FIG. **2**).

(90) A quick press of the push button may disengage a lock of touch screen **112** or begin a process that uses gestures on the touch screen to unlock the device, as described in U.S. patent application Ser. No. 11/322,549, "Unlocking a Device by Performing Gestures on an Unlock Image," filed Dec. 23, 2005, U.S. Pat. No. 7,657,849, which is hereby incorporated by reference in its entirety. A longer press of the push button (e.g., **206**) may turn power to device **100** on or off. The user may be able to customize a functionality of one or more of the buttons. Touch screen **112** is used to implement virtual or soft buttons and one or more soft keyboards.

(91) Touch-sensitive display **112** provides an input interface and an output interface between the device and a user. Display controller **156** receives and/or sends electrical signals from/to touch screen **112**. Touch screen **112** displays visual output to the user. The visual output may include graphics, text, icons, video, and any combination thereof (collectively termed "graphics"). In some embodiments, some or all of the visual output may correspond to user-interface objects.

(92) Touch screen **112** has a touch-sensitive surface, sensor, or set of sensors that accepts input from the user based on haptic and/or tactile contact. Touch screen **112** and display controller **156** (along with any associated modules and/or sets of instructions in memory **102**) detect contact (and any movement or breaking of the contact) on touch screen **112** and convert the detected contact into interaction with user-interface objects (e.g., one or more soft keys, icons, web pages, or images) that are displayed on touch screen **112**. In an exemplary embodiment, a point of contact between touch screen **112** and the user corresponds to a finger of the user.

(93) Touch screen **112** may use LCD (liquid crystal display) technology, LPD (light emitting polymer display) technology, or LED (light emitting diode) technology, although other display technologies may be used in other embodiments. Touch screen **112** and display controller **156** may detect contact and any movement or breaking thereof using any of a plurality of touch sensing technologies now known or later developed, including but

not limited to capacitive, resistive, infrared, and surface acoustic wave technologies, as well as other proximity sensor arrays or other elements for determining one or more points of contact with touch screen **112**. In an exemplary embodiment, projected mutual capacitance sensing technology is used, such as that found in the iPhone® and iPod Touch® from Apple Inc. of Cupertino, California.

(94) A touch-sensitive display in some embodiments of touch screen **112** may be analogous to the multi-touch sensitive touchpads described in the following U.S. Pat. No. 6,323,846 (Westerman et al.), U.S. Pat. No. 6,570,557 (Westerman et al.), and/or U.S. Pat. No. 6,677,932 (Westerman), and/or U.S. Patent Publication 2002/0015024A1, each of which is hereby incorporated by reference in its entirety. However, touch screen **112** displays visual output from device **100**, whereas touch-sensitive touchpads do not provide visual output.

(95) A touch-sensitive display in some embodiments of touch screen **112** may be as described in the following applications: (1) U.S. patent application Ser. No. 11/381,313, "Multipoint Touch Surface Controller," filed May 2, 2006; (2) U.S. patent application Ser. No. 10/840,862, "Multipoint Touchscreen," filed May 6, 2004; (3) U.S. patent application Ser. No. 10/903,964, "Gestures For Touch Sensitive Input Devices," filed Jul. 30, 2004; (4) U.S. patent application Ser. No. 11/048,264, "Gestures For Touch Sensitive Input Devices," filed Jan. 31, 2005; (5) U.S. patent application Ser. No. 11/038,590, "Mode-Based Graphical User Interfaces For Touch Sensitive Input Devices," filed Jan. 18, 2005; (6) U.S. patent application Ser. No. 11/228,758, "Virtual Input Device Placement On A Touch Screen User Interface," filed Sep. 16, 2005; (7) U.S. patent application Ser. No. 11/228,700, "Operation Of A Computer With A Touch Screen Interface," filed Sep. 16, 2005; (8) U.S. patent application Ser. No. 11/228,737, "Activating Virtual Keys Of A Touch-Screen Virtual Keyboard," filed Sep. 16, 2005; and (9) U.S. patent application Ser. No. 11/367,749, "Multi-Functional Hand-Held Device," filed Mar. 3, 2006. All of these applications are incorporated by reference herein in their entirety.

(96) Touch screen **112** may have a video resolution in excess of 100 dpi. In some embodiments, the touch screen has a video resolution of approximately 160 dpi. The user may make contact with touch screen **112** using any suitable object or appendage, such as a stylus, a finger, and so forth. In some embodiments, the user interface is designed to work primarily with finger-based contacts and gestures, which can be less precise than stylus-based input due to the larger area of contact of a finger on the touch screen. In some embodiments, the device translates the rough finger-based input into a precise pointer/cursor position or command for performing the actions desired by the user.

(97) In some embodiments, in addition to the touch screen, device **100** may include a touchpad (not shown) for activating or deactivating particular functions. In some embodiments, the touchpad is a touch-sensitive area of the device that, unlike the touch screen, does not display visual output. The touchpad may be a touch-sensitive surface that is separate from touch screen **112** or an extension of the touch-sensitive surface formed by the touch screen.

(98) Device **100** also includes power system **162** for powering the various components. Power system **162** may include a power management system, one or more power sources (e.g., battery, alternating current (AC)), a recharging system, a power failure detection circuit, a power converter or inverter, a power status indicator (e.g., a light-emitting diode (LED)) and any other components associated with the generation, management and distribution of power in portable devices.

(99) Device **100** may also include one or more optical sensors **164**. FIG. 1A shows an optical sensor coupled to optical sensor controller **158** in I/O subsystem **106**. Optical sensor **164** may include charge-coupled device (CCD) or complementary metal-oxide semiconductor (CMOS) phototransistors. Optical sensor **164** receives light from the environment, projected through one or more lenses, and converts the light to data representing an image. In conjunction with imaging module **143** (also called a camera module), optical sensor **164** may capture still images or video. In some embodiments, an optical sensor is located on the back of device **100**, opposite touch screen display **112** on the front of the device so that the touch screen display may be used as a viewfinder for still and/or video image acquisition. In some embodiments, an optical sensor is located on the front of the device so that the user's image may be obtained for video conferencing while the user views the other video conference participants on the touch screen display. In some embodiments, the position of optical sensor **164** can be changed by the user (e.g., by rotating the lens and the sensor in the device housing) so that a single optical sensor **164** may be used along with the touch screen display for both video conferencing and still and/or video image acquisition.

(100) Device **100** optionally also includes one or more contact intensity sensors **165**. FIG. 1A shows a contact intensity sensor coupled to intensity sensor controller **159** in I/O subsystem **106**. Contact intensity sensor **165** optionally includes one or more piezoresistive strain gauges, capacitive force sensors, electric force sensors, piezoelectric force sensors, optical force sensors, capacitive touch-sensitive surfaces, or other intensity sensors (e.g., sensors used to measure the force (or pressure) of a contact on a touch-sensitive surface). Contact intensity sensor **165** receives contact intensity information (e.g., pressure information or a proxy for pressure information) from the environment. In some embodiments, at least one contact intensity sensor is collocated with, or proximate to, a touch-sensitive surface (e.g., touch-sensitive display system **112**). In some embodiments, at least one contact intensity sensor is located on the back of device **100**, opposite touch screen display **112**, which is located on the front of device **100**.

(101) Device **100** may also include one or more proximity sensors **166**. FIG. 1A shows proximity sensor **166** coupled to peripherals interface **118**. Alternately, proximity sensor **166** may be coupled to input controller **160** in I/O subsystem **106**. Proximity sensor **166** may perform as described in U.S. patent application Ser. No. 11/241,839, "Proximity Detector In Handheld Device"; Ser. No. 11/240,788, "Proximity Detector In Handheld Device"; Ser. No. 11/620,702, "Using Ambient Light Sensor To Augment Proximity Sensor Output"; Ser. No. 11/586,862, "Automated Response To And Sensing Of User Activity In Portable Devices"; and Ser. No. 11/638,251, "Methods And Systems For Automatic Configuration Of Peripherals," which are hereby incorporated by reference in their entirety. In some embodiments, the proximity sensor turns off and disables touch screen **112** when the multifunction device is placed near the user's ear (e.g., when the user is making a phone call).

(102) Device **100** optionally also includes one or more tactile output generators **167**. FIG. 1A shows a tactile output generator coupled to haptic feedback controller **161** in I/O subsystem **106**. Tactile output generator **167** optionally includes one or more electroacoustic devices such as speakers or other audio components and/or electromechanical devices that convert energy into linear motion such as a motor, solenoid, electroactive polymer, piezoelectric actuator, electrostatic actuator, or other tactile output generating component (e.g., a component that converts electrical signals into tactile outputs on the device). Contact intensity sensor **165** receives tactile feedback generation instructions from haptic feedback module **133** and generates tactile outputs on device **100** that are capable of being sensed by a user of device **100**. In some embodiments, at least one tactile output generator is collocated with, or proximate to, a touch-sensitive surface (e.g., touch-sensitive display system **112**) and, optionally, generates a tactile output by moving the touch-sensitive surface vertically (e.g., in/out of a surface of device **100**) or laterally (e.g., back and forth in the same plane as a surface of device **100**). In some embodiments, at least one tactile output generator sensor is located on the back of device **100**, opposite touch screen display **112**, which is located on the front of device **100**.

(103) Device **100** may also include one or more accelerometers **168**. FIG. 1A shows accelerometer **168** coupled to peripherals interface **118**. Alternately, accelerometer **168** may be coupled to an input controller **160** in I/O subsystem **106**. Accelerometer **168** may perform as described in U.S. Patent Publication No. 20050190059, "Acceleration-based Theft Detection System for Portable Electronic Devices," and U.S. Patent Publication No. 20060017692, "Methods And Apparatuses For Operating A Portable Device Based On An Accelerometer," both of which are incorporated by reference herein in their entirety. In some embodiments, information is displayed on the touch screen display in a portrait view or a landscape view based on an analysis of data received from the one or more accelerometers. Device **100** optionally includes, in addition to accelerometer(s) **168**, a magnetometer (not shown) and a GPS (or GLONASS or other global navigation system) receiver (not shown) for obtaining information concerning the location and orientation (e.g., portrait or landscape) of device **100**.

(104) In some embodiments, the software components stored in memory **102** include operating system **126**, communication module (or set of instructions) **128**, contact/motion module (or set of instructions) **130**, graphics module (or set of instructions) **132**, text input module (or set of instructions) **134**, Global Positioning System (GPS) module (or set of instructions) **135**, and applications (or sets of instructions) **136**. Furthermore, in some embodiments, memory **102** (FIG. 1A) or **370** (FIG. 3) stores device/global internal state **157**, as shown in FIGS. 1A and 3. Device/global

internal state **157** includes one or more of: active application state, including applications, if any, are currently active; display state, indicating what applications, views or other information occupy various regions of touch screen display **112**; sensor state, including information obtained from the device's various sensors and input control devices **116**; and location information concerning the device's location and/or attitude.

(105) Operating system **126** (e.g., Darwin, RTXC, LINUX, UNIX, OS X, iOS, WINDOWS, or an embedded operating system such as VxWorks) includes various software components and/or drivers for controlling and managing general system tasks (e.g., memory management, storage device control, power management, etc.) and facilitates communication between various hardware and software components.

(106) Communication module **128** facilitates communication with other devices over one or more external ports **124** and also includes various software components for handling data received by RF circuitry **108** and/or external port **124**. External port **124** (e.g., Universal Serial Bus (USB), FIREWIRE, etc.) is adapted for coupling directly to other devices or indirectly over a network (e.g., the Internet, wireless LAN, etc.). In some embodiments, the external port is a multi-pin (e.g., 30-pin) connector that is the same as, or similar to and/or compatible with, the 30-pin connector used on iPod® (trademark of Apple Inc.) devices.

(107) Contact/motion module **130** optionally detects contact with touch screen **112** (in conjunction with display controller **156**) and other touch-sensitive devices (e.g., a touchpad or physical click wheel). Contact/motion module **130** includes various software components for performing various operations related to detection of contact, such as determining if contact has occurred (e.g., detecting a finger-down event), determining an intensity of the contact (e.g., the force or pressure of the contact or a substitute for the force or pressure of the contact), determining if there is movement of the contact and tracking the movement across the touch-sensitive surface (e.g., detecting one or more finger-dragging events), and determining if the contact has ceased (e.g., detecting a finger-up event or a break in contact). Contact/motion module **130** receives contact data from the touch-sensitive surface. Determining movement of the point of contact, which is represented by a series of contact data, optionally includes determining speed (magnitude), velocity (magnitude and direction), and/or an acceleration (a change in magnitude and/or direction) of the point of contact. These operations are, optionally, applied to single contacts (e.g., one finger contacts) or to multiple simultaneous contacts (e.g., "multitouch"/multiple finger contacts). In some embodiments, contact/motion module **130** and display controller **156** detect contact on a touchpad.

(108) In some embodiments, contact/motion module **130** uses a set of one or more intensity thresholds to determine whether an operation has been performed by a user (e.g., to determine whether a user has "clicked" on an icon). In some embodiments, at least a subset of the intensity thresholds are determined in accordance with software parameters (e.g., the intensity thresholds are not determined by the activation thresholds of particular physical actuators and can be adjusted without changing the physical hardware of device **100**). For example, a mouse "click" threshold of a trackpad or touch screen display can be set to any of a large range of predefined threshold values without changing the trackpad or touch screen display hardware. Additionally, in some implementations, a user of the device is provided with software settings for adjusting one or more of the set of intensity thresholds (e.g., by adjusting individual intensity thresholds and/or by adjusting a plurality of intensity thresholds at once with a system-level click "intensity" parameter).

(109) Contact/motion module **130** optionally detects a gesture input by a user. Different gestures on the touch-sensitive surface have different contact patterns (e.g., different motions, timings, and/or intensities of detected contacts). Thus, a gesture is, optionally, detected by detecting a particular contact pattern. For example, detecting a finger tap gesture includes detecting a finger-down event followed by detecting a finger-up (liftoff) event at the same position (or substantially the same position) as the finger-down event (e.g., at the position of an icon). As another example, detecting a finger swipe gesture on the touch-sensitive surface includes detecting a finger-down event followed by detecting one or more finger-dragging events, and subsequently followed by detecting a finger-up (liftoff) event.

(110) Graphics module **132** includes various known software components for rendering and displaying graphics on touch screen **112** or other display, including components for changing the visual impact (e.g., brightness, transparency, saturation, contrast, or other visual property) of graphics that are displayed. As used herein, the term "graphics" includes any object that can be displayed to a user, including, without limitation, text, web pages, icons (such as user-interface objects including soft keys), digital images, videos, animations, and the like.

(111) In some embodiments, graphics module **132** stores data representing graphics to be used. Each graphic is, optionally, assigned a corresponding code. Graphics module **132** receives, from applications etc., one or more codes specifying graphics to be displayed along with, if necessary, coordinate data and other graphic property data, and then generates screen image data to output to display controller **156**.

(112) Haptic feedback module **133** includes various software components for generating instructions used by tactile output generator(s) **167** to produce tactile outputs at one or more locations on device **100** in response to user interactions with device **100**.

(113) Text input module **134**, which may be a component of graphics module **132**, provides soft keyboards for entering text in various applications (e.g., contacts module **137**, e-mail module **140**, IM module **141**, browser module **147**, and any other application that needs text input).

(114) GPS module **135** determines the location of the device and provides this information for use in various applications (e.g., to telephone module **138** for use in location-based dialing; to camera module **143** as picture/video metadata; and to applications that provide location-based services such as weather widgets, local yellow page widgets, and map/navigation widgets).

(115) Applications **136** may include the following modules (or sets of instructions), or a subset or superset thereof: Contacts module **137** (sometimes called an address book or contact list); Telephone module **138**; Video conference module **139**; E-mail client module **140**; Instant messaging (IM) module **141**; Workout support module **142**; Camera module **143** for still and/or video images; Image management module **144**; Video player module; Music player module; Browser module **147**; Calendar module **148**; Widget modules **149**, which may include one or more of: weather widget **149-1**, stocks widget **149-2**, calculator widget **149-3**, alarm clock widget **149-4**, dictionary widget **149-5**, and other widgets obtained by the user, as well as user-created widgets **149-6**; Widget creator module **150** for making user-created widgets **149-6**; Search module **151**; Video and music player module **152**, which merges video player module and music player module; Notes module **153**; Map module **154**; and/or Online video module **155**.

(116) Examples of other applications **136** that may be stored in memory **102** include other word processing applications, other image editing applications, drawing applications, presentation applications, JAVA-enabled applications, encryption, digital rights management, voice recognition, and voice replication.

(117) In conjunction with touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, and text input module **134**, contacts module **137** may be used to manage an address book or contact list (e.g., stored in application internal state **192** of contacts module **137** in memory **102** or memory **370**), including: adding name(s) to the address book; deleting name(s) from the address book; associating telephone number(s), e-mail address(es), physical address(es) or other information with a name; associating an image with a name; categorizing and sorting names; providing telephone numbers or e-mail addresses to initiate and/or facilitate communications by telephone module **138**, video conference module **139**, e-mail module **140**, or IM module **141**; and so forth.

(118) In conjunction with RF circuitry **108**, audio circuitry **110**, speaker **111**, microphone **113**, touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, and text input module **134**, telephone module **138** may be used to enter a sequence of characters corresponding to a telephone number, access one or more telephone numbers in contacts module **137**, modify a telephone number that has been entered, dial a respective telephone number, conduct a conversation, and disconnect or hang up when the conversation is completed. As noted above, the wireless communication may use any of a plurality of communications standards, protocols, and technologies.

(119) In conjunction with RF circuitry **108**, audio circuitry **110**, speaker **111**, microphone **113**, touch screen **112**, display controller **156**, optical sensor **164**, optical sensor controller **158**, contact/motion module **130**, graphics module **132**, text input module **134**, contacts module **137**, and telephone module **138**, video conference module **139** includes executable instructions to initiate, conduct, and terminate a video conference between a user and one or more other participants in accordance with user instructions.

(120) In conjunction with RF circuitry **108**, touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, and text

input module **134**, e-mail client module **140** includes executable instructions to create, send, receive, and manage e-mail in accordance with user instructions. In conjunction with image management module **144**, e-mail client module **140** makes it very easy to create and send e-mails with still or video images taken with camera module **143**.

(121) In conjunction with RF circuitry **108**, touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, and text input module **134**, the instant messaging module **141** includes executable instructions to enter a sequence of characters corresponding to an instant message, to modify previously entered characters, to transmit a respective instant message (for example, using a Short Message Service (SMS) or Multimedia Message Service (MMS) protocol for telephony-based instant messages or using XMPP, SIMPLE, or IMPS for Internet-based instant messages), to receive instant messages, and to view received instant messages. In some embodiments, transmitted and/or received instant messages may include graphics, photos, audio files, video files and/or other attachments as are supported in an MMS and/or an Enhanced Messaging Service (EMS). As used herein, “instant messaging” refers to both telephony-based messages (e.g., messages sent using SMS or MMS) and Internet-based messages (e.g., messages sent using XMPP, SIMPLE, or IMPS).

(122) In conjunction with RF circuitry **108**, touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, text input module **134**, GPS module **135**, map module **154**, and music player module, workout support module **142** includes executable instructions to create workouts (e.g., with time, distance, and/or calorie burning goals); communicate with workout sensors (sports devices); receive workout sensor data; calibrate sensors used to monitor a workout; select and play music for a workout; and display, store, and transmit workout data.

(123) In conjunction with touch screen **112**, display controller **156**, optical sensor(s) **164**, optical sensor controller **158**, contact/motion module **130**, graphics module **132**, and image management module **144**, camera module **143** includes executable instructions to capture still images or video (including a video stream) and store them into memory **102**, modify characteristics of a still image or video, or delete a still image or video from memory **102**.

(124) In conjunction with touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, text input module **134**, and camera module **143**, image management module **144** includes executable instructions to arrange, modify (e.g., edit), or otherwise manipulate, label, delete, present (e.g., in a digital slide show or album), and store still and/or video images.

(125) In conjunction with RF circuitry **108**, touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, and text input module **134**, browser module **147** includes executable instructions to browse the Internet in accordance with user instructions, including searching, linking to, receiving, and displaying web pages or portions thereof, as well as attachments and other files linked to web pages.

(126) In conjunction with RF circuitry **108**, touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, text input module **134**, e-mail client module **140**, and browser module **147**, calendar module **148** includes executable instructions to create, display, modify, and store calendars and data associated with calendars (e.g., calendar entries, to-do lists, etc.) in accordance with user instructions.

(127) In conjunction with RF circuitry **108**, touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, text input module **134**, and browser module **147**, widget modules **149** are mini-applications that may be downloaded and used by a user (e.g., weather widget **149-1**, stocks widget **149-2**, calculator widget **149-3**, alarm clock widget **149-4**, and dictionary widget **149-5**) or created by the user (e.g., user-created widget **149-6**). In some embodiments, a widget includes an HTML (Hypertext Markup Language) file, a CSS (Cascading Style Sheets) file, and a JavaScript file. In some embodiments, a widget includes an XML (Extensible Markup Language) file and a JavaScript file (e.g., Yahoo! Widgets).

(128) In conjunction with RF circuitry **108**, touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, text input module **134**, and browser module **147**, the widget creator module **150** may be used by a user to create widgets (e.g., turning a user-specified portion of a web page into a widget).

(129) In conjunction with touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, and text input module **134**, search module **151** includes executable instructions to search for text, music, sound, image, video, and/or other files in memory **102** that match one or more search criteria (e.g., one or more user-specified search terms) in accordance with user instructions.

(130) In conjunction with touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, audio circuitry **110**, speaker **111**, RF circuitry **108**, and browser module **147**, video and music player module **152** includes executable instructions that allow the user to download and play back recorded music and other sound files stored in one or more file formats, such as MP3 or AAC files, and executable instructions to display, present, or otherwise play back videos (e.g., on touch screen **112** or on an external, connected display via external port **124**). In some embodiments, device **100** optionally includes the functionality of an MP3 player, such as an iPod (trademark of Apple Inc.).

(131) In conjunction with touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, and text input module **134**, notes module **153** includes executable instructions to create and manage notes, to-do lists, and the like in accordance with user instructions.

(132) In conjunction with RF circuitry **108**, touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, text input module **134**, GPS module **135**, and browser module **147**, map module **154** may be used to receive, display, modify, and store maps and data associated with maps (e.g., driving directions, data on stores and other points of interest at or near a particular location, and other location-based data) in accordance with user instructions.

(133) In conjunction with touch screen **112**, display controller **156**, contact/motion module **130**, graphics module **132**, audio circuitry **110**, speaker **111**, RF circuitry **108**, text input module **134**, e-mail client module **140**, and browser module **147**, online video module **155** includes instructions that allow the user to access, browse, receive (e.g., by streaming and/or download), play back (e.g., on the touch screen or on an external, connected display via external port **124**), send an e-mail with a link to a particular online video, and otherwise manage online videos in one or more file formats, such as H.264. In some embodiments, instant messaging module **141**, rather than e-mail client module **140**, is used to send a link to a particular online video. Additional description of the online video application can be found in U.S. Provisional Patent Application No. 60/936,562, “Portable Multifunction Device, Method, and Graphical User Interface for Playing Online Videos,” filed Jun. 20, 2007, and U.S. patent application Ser. No. 11/968,067, “Portable Multifunction Device, Method, and Graphical User Interface for Playing Online Videos,” filed Dec. 31, 2007, the contents of which are hereby incorporated by reference in their entirety.

(134) Each of the above-identified modules and applications corresponds to a set of executable instructions for performing one or more functions described above and the methods described in this application (e.g., the computer-implemented methods and other information processing methods described herein). These modules (e.g., sets of instructions) need not be implemented as separate software programs, procedures, or modules, and thus various subsets of these modules may be combined or otherwise rearranged in various embodiments. For example, video player module may be combined with music player module into a single module (e.g., video and music player module **152**, FIG. 1A). In some embodiments, memory **102** may store a subset of the modules and data structures identified above. Furthermore, memory **102** may store additional modules and data structures not described above.

(135) In some embodiments, device **100** is a device where operation of a predefined set of functions on the device is performed exclusively through a touch screen and/or a touchpad. By using a touch screen and/or a touchpad as the primary input control device for operation of device **100**, the number of physical input control devices (such as push buttons, dials, and the like) on device **100** may be reduced.

(136) The predefined set of functions that are performed exclusively through a touch screen and/or a touchpad optionally include navigation between user interfaces. In some embodiments, the touchpad, when touched by the user, navigates device **100** to a main, home, or root menu from any user interface that is displayed on device **100**. In such embodiments, a “menu button” is implemented using a touchpad. In some other embodiments, the menu button is a physical push button or other physical input control device instead of a touchpad.

(137) FIG. 1B is a block diagram illustrating exemplary components for event handling in accordance with some embodiments. In some

embodiments, memory **102** (FIG. 1A) or **370** (FIG. 3) includes event sorter **170** (e.g., in operating system **126**) and a respective application **136-1** (e.g., any of the aforementioned applications **137-151**, **155**, **380-390**).

(138) Event sorter **170** receives event information and determines the application **136-1** and application view **191** of application **136-1** to which to deliver the event information. Event sorter **170** includes event monitor **171** and event dispatcher module **174**. In some embodiments, application **136-1** includes application internal state **192**, which indicates the current application view(s) displayed on touch-sensitive display **112** when the application is active or executing. In some embodiments, device/global internal state **157** is used by event sorter **170** to determine which application(s) is (are) currently active, and application internal state **192** is used by event sorter **170** to determine application views **191** to which to deliver event information.

(139) In some embodiments, application internal state **192** includes additional information, such as one or more of: resume information to be used when application **136-1** resumes execution, user interface state information that indicates information being displayed or that is ready for display by application **136-1**, a state queue for enabling the user to go back to a prior state or view of application **136-1**, and a redo/undo queue of previous actions taken by the user.

(140) Event monitor **171** receives event information from peripherals interface **118**. Event information includes information about a sub-event (e.g., a user touch on touch-sensitive display **112**, as part of a multi-touch gesture). Peripherals interface **118** transmits information it receives from I/O subsystem **106** or a sensor, such as proximity sensor **166**, accelerometer(s) **168**, and/or microphone **113** (through audio circuitry **110**). Information that peripherals interface **118** receives from I/O subsystem **106** includes information from touch-sensitive display **112** or a touch-sensitive surface.

(141) In some embodiments, event monitor **171** sends requests to the peripherals interface **118** at predetermined intervals. In response, peripherals interface **118** transmits event information. In other embodiments, peripherals interface **118** transmits event information only when there is a significant event (e.g., receiving an input above a predetermined noise threshold and/or for more than a predetermined duration).

(142) In some embodiments, event sorter **170** also includes a hit view determination module **172** and/or an active event recognizer determination module **173**.

(143) Hit view determination module **172** provides software procedures for determining where a sub-event has taken place within one or more views when touch-sensitive display **112** displays more than one view. Views are made up of controls and other elements that a user can see on the display.

(144) Another aspect of the user interface associated with an application is a set of views, sometimes herein called application views or user interface windows, in which information is displayed and touch-based gestures occur. The application views (of a respective application) in which a touch is detected may correspond to programmatic levels within a programmatic or view hierarchy of the application. For example, the lowest level view in which a touch is detected may be called the hit view, and the set of events that are recognized as proper inputs may be determined based, at least in part, on the hit view of the initial touch that begins a touch-based gesture.

(145) Hit view determination module **172** receives information related to sub-events of a touch-based gesture. When an application has multiple views organized in a hierarchy, hit view determination module **172** identifies a hit view as the lowest view in the hierarchy which should handle the sub-event. In most circumstances, the hit view is the lowest level view in which an initiating sub-event occurs (e.g., the first sub-event in the sequence of sub-events that form an event or potential event). Once the hit view is identified by the hit view determination module **172**, the hit view typically receives all sub-events related to the same touch or input source for which it was identified as the hit view.

(146) Active event recognizer determination module **173** determines which view or views within a view hierarchy should receive a particular sequence of sub-events. In some embodiments, active event recognizer determination module **173** determines that only the hit view should receive a particular sequence of sub-events. In other embodiments, active event recognizer determination module **173** determines that all views that include the physical location of a sub-event are actively involved views, and therefore determines that all actively involved views should receive a particular sequence of sub-events. In other embodiments, even if touch sub-events were entirely confined to the area associated with one particular view, views higher in the hierarchy would still remain as actively involved views.

(147) Event dispatcher module **174** dispatches the event information to an event recognizer (e.g., event recognizer **180**). In embodiments including active event recognizer determination module **173**, event dispatcher module **174** delivers the event information to an event recognizer determined by active event recognizer determination module **173**. In some embodiments, event dispatcher module **174** stores in an event queue the event information, which is retrieved by a respective event receiver **182**.

(148) In some embodiments, operating system **126** includes event sorter **170**. Alternatively, application **136-1** includes event sorter **170**. In yet other embodiments, event sorter **170** is a stand-alone module, or a part of another module stored in memory **102**, such as contact/motion module **130**.

(149) In some embodiments, application **136-1** includes a plurality of event handlers **190** and one or more application views **191**, each of which includes instructions for handling touch events that occur within a respective view of the application's user interface. Each application view **191** of the application **136-1** includes one or more event recognizers **180**. Typically, a respective application view **191** includes a plurality of event recognizers **180**. In other embodiments, one or more of event recognizers **180** are part of a separate module, such as a user interface kit (not shown) or a higher level object from which application **136-1** inherits methods and other properties. In some embodiments, a respective event handler **190** includes one or more of: data updater **176**, object updater **177**, GUI updater **178**, and/or event data **179** received from event sorter **170**. Event handler **190** may utilize or call data updater **176**, object updater **177**, or GUI updater **178** to update the application internal state **192**. Alternatively, one or more of the application views **191** include one or more respective event handlers **190**. Also, in some embodiments, one or more of data updater **176**, object updater **177**, and GUI updater **178** are included in a respective application view **191**.

(150) A respective event recognizer **180** receives event information (e.g., event data **179**) from event sorter **170** and identifies an event from the event information. Event recognizer **180** includes event receiver **182** and event comparator **184**. In some embodiments, event recognizer **180** also includes at least a subset of: metadata **183**, and event delivery instructions **188** (which may include sub-event delivery instructions).

(151) Event receiver **182** receives event information from event sorter **170**. The event information includes information about a sub-event, for example, a touch or a touch movement. Depending on the sub-event, the event information also includes additional information, such as location of the sub-event. When the sub-event concerns motion of a touch, the event information may also include speed and direction of the sub-event. In some embodiments, events include rotation of the device from one orientation to another (e.g., from a portrait orientation to a landscape orientation, or vice versa), and the event information includes corresponding information about the current orientation (also called device attitude) of the device.

(152) Event comparator **184** compares the event information to predefined event or sub-event definitions and, based on the comparison, determines an event or sub-event, or determines or updates the state of an event or sub-event. In some embodiments, event comparator **184** includes event definitions **186**. Event definitions **186** contain definitions of events (e.g., predefined sequences of sub-events), for example, event **1** (**187-1**), event **2** (**187-2**), and others. In some embodiments, sub-events in an event (**187**) include, for example, touch begin, touch end, touch movement, touch cancellation, and multiple touching. In one example, the definition for event **1** (**187-1**) is a double tap on a displayed object. The double tap, for example, comprises a first touch (touch begin) on the displayed object for a predetermined phase, a first liftoff (touch end) for a predetermined phase, a second touch (touch begin) on the displayed object for a predetermined phase, and a second liftoff (touch end) for a predetermined phase. In another example, the definition for event **2** (**187-2**) is a dragging on a displayed object. The dragging, for example, comprises a touch (or contact) on the displayed object for a predetermined phase, a movement of the touch across touch-sensitive display **112**, and liftoff of the touch (touch end). In some embodiments, the event also includes information for one or more associated event handlers **190**.

(153) In some embodiments, event definition **187** includes a definition of an event for a respective user-interface object. In some embodiments, event comparator **184** performs a hit test to determine which user-interface object is associated with a sub-event. For example, in an application view in which three user-interface objects are displayed on touch-sensitive display **112**, when a touch is detected on touch-sensitive display **112**, event

comparator **184** performs a hit test to determine which of the three user-interface objects is associated with the touch (sub-event). If each displayed object is associated with a respective event handler **190**, the event comparator uses the result of the hit test to determine which event handler **190** should be activated. For example, event comparator **184** selects an event handler associated with the sub-event and the object triggering the hit test. (154) In some embodiments, the definition for a respective event (**187**) also includes delayed actions that delay delivery of the event information until after it has been determined whether the sequence of sub-events does or does not correspond to the event recognizer's event type. (155) When a respective event recognizer **180** determines that the series of sub-events do not match any of the events in event definitions **186**, the respective event recognizer **180** enters an event impossible, event failed, or event ended state, after which it disregards subsequent sub-events of the touch-based gesture. In this situation, other event recognizers, if any, that remain active for the hit view continue to track and process sub-events of an ongoing touch-based gesture. (156) In some embodiments, a respective event recognizer **180** includes metadata **183** with configurable properties, flags, and/or lists that indicate how the event delivery system should perform sub-event delivery to actively involved event recognizers. In some embodiments, metadata **183** includes configurable properties, flags, and/or lists that indicate how event recognizers may interact, or are enabled to interact, with one another. In some embodiments, metadata **183** includes configurable properties, flags, and/or lists that indicate whether sub-events are delivered to varying levels in the view or programmatic hierarchy. (157) In some embodiments, a respective event recognizer **180** activates event handler **190** associated with an event when one or more particular sub-events of an event are recognized. In some embodiments, a respective event recognizer **180** delivers event information associated with the event to event handler **190**. Activating an event handler **190** is distinct from sending (and deferred sending) sub-events to a respective hit view. In some embodiments, event recognizer **180** throws a flag associated with the recognized event, and event handler **190** associated with the flag catches the flag and performs a predefined process. (158) In some embodiments, event delivery instructions **188** include sub-event delivery instructions that deliver event information about a sub-event without activating an event handler. Instead, the sub-event delivery instructions deliver event information to event handlers associated with the series of sub-events or to actively involved views. Event handlers associated with the series of sub-events or with actively involved views receive the event information and perform a predetermined process. (159) In some embodiments, data updater **176** creates and updates data used in application **136-1**. For example, data updater **176** updates the telephone number used in contacts module **137**, or stores a video file used in video player module. In some embodiments, object updater **177** creates and updates objects used in application **136-1**. For example, object updater **177** creates a new user-interface object or updates the position of a user-interface object. GUI updater **178** updates the GUI. For example, GUI updater **178** prepares display information and sends it to graphics module **132** for display on a touch-sensitive display. (160) In some embodiments, event handler(s) **190** includes or has access to data updater **176**, object updater **177**, and GUI updater **178**. In some embodiments, data updater **176**, object updater **177**, and GUI updater **178** are included in a single module of a respective application **136-1** or application view **191**. In other embodiments, they are included in two or more software modules. (161) It shall be understood that the foregoing discussion regarding event handling of user touches on touch-sensitive displays also applies to other forms of user inputs to operate multifunction devices **100** with input devices, not all of which are initiated on touch screens. For example, mouse movement and mouse button presses, optionally coordinated with single or multiple keyboard presses or holds; contact movements such as taps, drags, scrolls, etc. on touchpads; pen stylus inputs; movement of the device; oral instructions; detected eye movements; biometric inputs; and/or any combination thereof are optionally utilized as inputs corresponding to sub-events which define an event to be recognized. (162) FIG. 2 illustrates a portable multifunction device **100** having a touch screen **112** in accordance with some embodiments. The touch screen optionally displays one or more graphics within user interface (UI) **200**. In this embodiment, as well as others described below, a user is enabled to select one or more of the graphics by making a gesture on the graphics, for example, with one or more fingers **202** (not drawn to scale in the figure) or one or more styluses **203** (not drawn to scale in the figure). In some embodiments, selection of one or more graphics occurs when the user breaks contact with the one or more graphics. In some embodiments, the gesture optionally includes one or more taps, one or more swipes (from left to right, right to left, upward and/or downward), and/or a rolling of a finger (from right to left, left to right, upward and/or downward) that has made contact with device **100**. In some implementations or circumstances, inadvertent contact with a graphic does not select the graphic. For example, a swipe gesture that sweeps over an application icon optionally does not select the corresponding application when the gesture corresponding to selection is a tap. (163) Device **100** may also include one or more physical buttons, such as "home" or menu button **204**. As described previously, menu button **204** may be used to navigate to any application **136** in a set of applications that may be executed on device **100**. Alternatively, in some embodiments, the menu button is implemented as a soft key in a GUI displayed on touch screen **112**. (164) In some embodiments, device **100** includes touch screen **112**, menu button **204**, push button **206** for powering the device on/off and locking the device, volume adjustment button(s) **208**, subscriber identity module (SIM) card slot **210**, headset jack **212**, and docking/charging external port **124**. Push button **206** is, optionally, used to turn the power on/off on the device by depressing the button and holding the button in the depressed state for a predefined time interval; to lock the device by depressing the button and releasing the button before the predefined time interval has elapsed; and/or to unlock the device or initiate an unlock process. In an alternative embodiment, device **100** also accepts verbal input for activation or deactivation of some functions through microphone **113**. Device **100** also, optionally, includes one or more contact intensity sensors **165** for detecting intensity of contacts on touch screen **112** and/or one or more tactile output generators **167** for generating tactile outputs for a user of device **100**. (165) FIG. 3 is a block diagram of an exemplary multifunction device with a display and a touch-sensitive surface in accordance with some embodiments. Device **300** need not be portable. In some embodiments, device **300** is a laptop computer, a desktop computer, a tablet computer, a multimedia player device, a navigation device, an educational device (such as a child's learning toy), a gaming system, or a control device (e.g., a home or industrial controller). Device **300** typically includes one or more processing units (CPUs) **310**, one or more network or other communications interfaces **360**, memory **370**, and one or more communication buses **320** for interconnecting these components. Communication buses **320** optionally include circuitry (sometimes called a chipset) that interconnects and controls communications between system components. Device **300** includes input/output (I/O) interface **330** comprising display **340**, which is typically a touch screen display. I/O interface **330** also optionally includes a keyboard and/or mouse (or other pointing device) **350** and touchpad **355**, tactile output generator **357** for generating tactile outputs on device **300** (e.g., similar to tactile output generator(s) **167** described above with reference to FIG. 1A), sensors **359** (e.g., optical, acceleration, proximity, touch-sensitive, and/or contact intensity sensors similar to contact intensity sensor(s) **165** described above with reference to FIG. 1A). Memory **370** includes high-speed random access memory, such as DRAM, SRAM, DDR RAM, or other random access solid state memory devices; and optionally includes non-volatile memory, such as one or more magnetic disk storage devices, optical disk storage devices, flash memory devices, or other non-volatile solid state storage devices. Memory **370** optionally includes one or more storage devices remotely located from CPU(s) **310**. In some embodiments, memory **370** stores programs, modules, and data structures analogous to the programs, modules, and data structures stored in memory **102** of portable multifunction device **100** (FIG. 1A), or a subset thereof. Furthermore, memory **370** optionally stores additional programs, modules, and data structures not present in memory **102** of portable multifunction device **100**. For example, memory **370** of device **300** optionally stores drawing module **380**, presentation module **382**, word processing module **384**, website creation module **386**, disk authoring module **388**, and/or spreadsheet module **390**, while memory **102** of portable multifunction device **100** (FIG. 1A) optionally does not store these modules. (166) Each of the above-identified elements in FIG. 3 may be stored in one or more of the previously mentioned memory devices. Each of the above-

identified modules correspond to a set of instructions for performing a function described above. The above-identified modules or programs (e.g., sets of instructions) need not be implemented as separate software programs, procedures, or modules, and thus various subsets of these modules may be combined or otherwise rearranged in various embodiments. In some embodiments, memory 370 may store a subset of the modules and data structures identified above. Furthermore, memory 370 may store additional modules and data structures not described above.

(167) Attention is now directed towards embodiments of user interfaces that may be implemented on, for example, portable multifunction device 100.

(168) FIG. 4A illustrates an exemplary user interface for a menu of applications on portable multifunction device 100 in accordance with some embodiments. Similar user interfaces may be implemented on device 300. In some embodiments, user interface 400 includes the following elements, or a subset or superset thereof: Signal strength indicator(s) 402 for wireless communication(s), such as cellular and Wi-Fi signals; Time 404; Bluetooth indicator 405; Battery status indicator 406; Tray 408 with icons for frequently used applications, such as: Icon 416 for telephone module 138, labeled “Phone,” which optionally includes an indicator 414 of the number of missed calls or voicemail messages; Icon 418 for e-mail client module 140, labeled “Mail,” which optionally includes an indicator 410 of the number of unread e-mails; Icon 420 for browser module 147, labeled “Browser,” and Icon 422 for video and music player module 152, also referred to as iPod (trademark of Apple Inc.) module 152, labeled “iPod;” and Icons for other applications, such as: Icon 424 for IM module 141, labeled “Messages;” Icon 426 for calendar module 148, labeled “Calendar;” Icon 428 for image management module 144, labeled “Photos;” Icon 430 for camera module 143, labeled “Camera;” Icon 432 for online video module 155, labeled “Online Video;” Icon 434 for stocks widget 149-2, labeled “Stocks;” Icon 436 for map module 154, labeled “Maps;” Icon 438 for weather widget 149-1, labeled “Weather;” Icon 440 for alarm clock widget 149-4, labeled “Clock;” Icon 442 for workout support module 142, labeled “Workout Support;” Icon 444 for notes module 153, labeled “Notes;” and Icon 446 for a settings application or module, labeled “Settings,” which provides access to settings for device 100 and its various applications 136.

(169) It should be noted that the icon labels illustrated in FIG. 4A are merely exemplary. For example, icon 422 for video and music player module 152 may optionally be labeled “Music” or “Music Player.” Other labels are, optionally, used for various application icons. In some embodiments, a label for a respective application icon includes a name of an application corresponding to the respective application icon. In some embodiments, a label for a particular application icon is distinct from a name of an application corresponding to the particular application icon.

(170) FIG. 4B illustrates an exemplary user interface on a device (e.g., device 300, FIG. 3) with a touch-sensitive surface 451 (e.g., a tablet or touchpad 355, FIG. 3) that is separate from the display 450 (e.g., touch screen display 112). Device 300 also, optionally, includes one or more contact intensity sensors (e.g., one or more of sensors 357) for detecting intensity of contacts on touch-sensitive surface 451 and/or one or more tactile output generators 359 for generating tactile outputs for a user of device 300.

(171) Although some of the examples which follow will be given with reference to inputs on touch screen display 112 (where the touch-sensitive surface and the display are combined), in some embodiments, the device detects inputs on a touch-sensitive surface that is separate from the display, as shown in FIG. 4B. In some embodiments, the touch-sensitive surface (e.g., 451 in FIG. 4B) has a primary axis (e.g., 452 in FIG. 4B) that corresponds to a primary axis (e.g., 453 in FIG. 4B) on the display (e.g., 450). In accordance with these embodiments, the device detects contacts (e.g., 460 and 462 in FIG. 4B) with the touch-sensitive surface 451 at locations that correspond to respective locations on the display (e.g., in FIG. 4B, 460 corresponds to 468 and 462 corresponds to 470). In this way, user inputs (e.g., contacts 460 and 462, and movements thereof) detected by the device on the touch-sensitive surface (e.g., 451 in FIG. 4B) are used by the device to manipulate the user interface on the display (e.g., 450 in FIG. 4B) of the multifunction device when the touch-sensitive surface is separate from the display. It should be understood that similar methods are, optionally, used for other user interfaces described herein.

(172) Additionally, while the following examples are given primarily with reference to finger inputs (e.g., finger contacts, finger tap gestures, finger swipe gestures), it should be understood that, in some embodiments, one or more of the finger inputs are replaced with input from another input device (e.g., a mouse-based input or stylus input). For example, a swipe gesture is, optionally, replaced with a mouse click (e.g., instead of a contact) followed by movement of the cursor along the path of the swipe (e.g., instead of movement of the contact). As another example, a tap gesture is, optionally, replaced with a mouse click while the cursor is located over the location of the tap gesture (e.g., instead of detection of the contact followed by ceasing to detect the contact). Similarly, when multiple user inputs are simultaneously detected, it should be understood that multiple computer mice are, optionally, used simultaneously, or a mouse and finger contacts are, optionally, used simultaneously.

(173) FIG. 5A illustrates exemplary personal electronic device 500. Device 500 includes body 502. In some embodiments, device 500 can include some or all of the features described with respect to devices 100 and 300 (e.g., FIGS. 1A-4B). In some embodiments, device 500 has touch-sensitive display screen 504, hereafter touch screen 504. Alternatively, or in addition to touch screen 504, device 500 has a display and a touch-sensitive surface. As with devices 100 and 300, in some embodiments, touch screen 504 (or the touch-sensitive surface) may have one or more intensity sensors for detecting intensity of contacts (e.g., touches) being applied. The one or more intensity sensors of touch screen 504 (or the touch-sensitive surface) can provide output data that represents the intensity of touches. The user interface of device 500 can respond to touches based on their intensity, meaning that touches of different intensities can invoke different user interface operations on device 500.

(174) Techniques for detecting and processing touch intensity may be found, for example, in related applications: International Patent Application Serial No. PCT/US2013/040061, titled “Device, Method, and Graphical User Interface for Displaying User Interface Objects Corresponding to an Application,” filed May 8, 2013, and International Patent Application Serial No. PCT/US2013/069483, titled “Device, Method, and Graphical User Interface for Transitioning Between Touch Input to Display Output Relationships,” filed Nov. 11, 2013, each of which is hereby incorporated by reference in their entirety.

(175) In some embodiments, device 500 has one or more input mechanisms 506 and 508. Input mechanisms 506 and 508, if included, can be physical. Examples of physical input mechanisms include push buttons and rotatable mechanisms. In some embodiments, device 500 has one or more attachment mechanisms. Such attachment mechanisms, if included, can permit attachment of device 500 with, for example, hats, eyewear, earrings, necklaces, shirts, jackets, bracelets, watch straps, chains, trousers, belts, shoes, purses, backpacks, and so forth. These attachment mechanisms may permit device 500 to be worn by a user.

(176) FIG. 5B depicts exemplary personal electronic device 500. In some embodiments, device 500 can include some or all of the components described with respect to FIGS. 1A, 1B, and 3. Device 500 has bus 512 that operatively couples I/O section 514 with one or more computer processors 516 and memory 518. I/O section 514 can be connected to display 504, which can have touch-sensitive component 522 and, optionally, touch-intensity sensitive component 524. In addition, I/O section 514 can be connected with communication unit 530 for receiving application and operating system data, using Wi-Fi, Bluetooth, near field communication (NFC), cellular, and/or other wireless communication techniques. Device 500 can include input mechanisms 506 and/or 508. Input mechanism 506 may be a rotatable input device or a depressible and rotatable input device, for example. Input mechanism 508 may be a button, in some examples.

(177) Input mechanism 508 may be a microphone, in some examples. Personal electronic device 500 can include various sensors, such as GPS sensor 532, accelerometer 534, directional sensor 540 (e.g., compass), gyroscope 536, motion sensor 538, and/or a combination thereof, all of which can be operatively connected to I/O section 514.

(178) Memory 518 of personal electronic device 500 can be a non-transitory computer-readable storage medium, for storing computer-executable instructions, which, when executed by one or more computer processors 516, for example, can cause the computer processors to perform the techniques described above, including processes 800, 900, 1600, 1800, 2100, 2700, 3800, and 4500 (FIGS. 8, 9, 16, 18, 21, 27, 38A-B, and 45, respectively). The computer-executable instructions can also be stored and/or transported within any non-transitory computer-readable storage medium for use by or in connection with an instruction execution system, apparatus, or device, such as a computer-based system, processor-

containing system, or other system that can fetch the instructions for execution by the instruction execution system, apparatus, or device and execute the instructions. For purposes of this document, a “non-transitory computer-readable storage medium” can be any medium that can tangibly contain or store computer-executable instructions for use by or in connection with the instruction execution system, apparatus, or device. The non-transitory computer-readable storage medium can include, but is not limited to, magnetic, optical, and/or semiconductor storages. Examples of such storage include magnetic disks, optical discs based on CD, DVD, or Blu-ray technologies, as well as persistent solid-state memory such as flash, solid-state drives, and the like. Personal electronic device **500** is not limited to the components and configuration of FIG. 5B, but can include other or additional components in multiple configurations.

(179) As used here, the term “affordance” refers to a user-interactive graphical user interface object that may be displayed on the display screen of devices **100**, **300**, and/or **500** (FIGS. **1**, **3**, and **5**). For example, an image (e.g., icon), a button, and text (e.g., hyperlink) may each constitute an affordance.

(180) As used herein, the term “focus selector” refers to an input element that indicates a current part of a user interface with which a user is interacting. In some implementations that include a cursor or other location marker, the cursor acts as a “focus selector” so that when an input (e.g., a press input) is detected on a touch-sensitive surface (e.g., touchpad **355** in FIG. **3** or touch-sensitive surface **451** in FIG. **4B**) while the cursor is over a particular user interface element (e.g., a button, window, slider or other user interface element), the particular user interface element is adjusted in accordance with the detected input. In some implementations that include a touch screen display (e.g., touch-sensitive display system **112** in FIG. **1A** or touch screen **112** in FIG. **4A**) that enables direct interaction with user interface elements on the touch screen display, a detected contact on the touch screen acts as a “focus selector” so that when an input (e.g., a press input by the contact) is detected on the touch screen display at a location of a particular user interface element (e.g., a button, window, slider, or other user interface element), the particular user interface element is adjusted in accordance with the detected input. In some implementations, focus is moved from one region of a user interface to another region of the user interface without corresponding movement of a cursor or movement of a contact on a touch screen display (e.g., by using a tab key or arrow keys to move focus from one button to another button); in these implementations, the focus selector moves in accordance with movement of focus between different regions of the user interface. Without regard to the specific form taken by the focus selector, the focus selector is generally the user interface element (or contact on a touch screen display) that is controlled by the user so as to communicate the user’s intended interaction with the user interface (e.g., by indicating, to the device, the element of the user interface with which the user is intending to interact). For example, the location of a focus selector (e.g., a cursor, a contact, or a selection box) over a respective button while a press input is detected on the touch-sensitive surface (e.g., a touchpad or touch screen) will indicate that the user is intending to activate the respective button (as opposed to other user interface elements shown on a display of the device).

(181) As used in the specification and claims, the term “characteristic intensity” of a contact refers to a characteristic of the contact based on one or more intensities of the contact. In some embodiments, the characteristic intensity is based on multiple intensity samples. The characteristic intensity is, optionally, based on a predefined number of intensity samples, or a set of intensity samples collected during a predetermined time period (e.g., 0.05, 0.1, 0.2, 0.5, 1, 2, 5, 10 seconds) relative to a predefined event (e.g., after detecting the contact, prior to detecting liftoff of the contact, before or after detecting a start of movement of the contact, prior to detecting an end of the contact, before or after detecting an increase in intensity of the contact, and/or before or after detecting a decrease in intensity of the contact). A characteristic intensity of a contact is, optionally based on one or more of: a maximum value of the intensities of the contact, a mean value of the intensities of the contact, an average value of the intensities of the contact, a top 10 percentile value of the intensities of the contact, a value at the half maximum of the intensities of the contact, a value at the 90 percent maximum of the intensities of the contact, or the like. In some embodiments, the duration of the contact is used in determining the characteristic intensity (e.g., when the characteristic intensity is an average of the intensity of the contact over time). In some embodiments, the characteristic intensity is compared to a set of one or more intensity thresholds to determine whether an operation has been performed by a user. For example, the set of one or more intensity thresholds may include a first intensity threshold and a second intensity threshold. In this example, a contact with a characteristic intensity that does not exceed the first threshold results in a first operation, a contact with a characteristic intensity that exceeds the first intensity threshold and does not exceed the second intensity threshold results in a second operation, and a contact with a characteristic intensity that exceeds the second threshold results in a third operation. In some embodiments, a comparison between the characteristic intensity and one or more thresholds is used to determine whether or not to perform one or more operations (e.g., whether to perform a respective operation or forgo performing the respective operation) rather than being used to determine whether to perform a first operation or a second operation.

(182) In some embodiments, a portion of a gesture is identified for purposes of determining a characteristic intensity. For example, a touch-sensitive surface may receive a continuous swipe contact transitioning from a start location and reaching an end location, at which point the intensity of the contact increases. In this example, the characteristic intensity of the contact at the end location may be based on only a portion of the continuous swipe contact, and not the entire swipe contact (e.g., only the portion of the swipe contact at the end location). In some embodiments, a smoothing algorithm may be applied to the intensities of the swipe contact prior to determining the characteristic intensity of the contact. For example, the smoothing algorithm optionally includes one or more of: an unweighted sliding-average smoothing algorithm, a triangular smoothing algorithm, a median filter smoothing algorithm, and/or an exponential smoothing algorithm. In some circumstances, these smoothing algorithms eliminate narrow spikes or dips in the intensities of the swipe contact for purposes of determining a characteristic intensity.

(183) The intensity of a contact on the touch-sensitive surface may be characterized relative to one or more intensity thresholds, such as a contact-detection intensity threshold, a light press intensity threshold, a deep press intensity threshold, and/or one or more other intensity thresholds. In some embodiments, the light press intensity threshold corresponds to an intensity at which the device will perform operations typically associated with clicking a button of a physical mouse or a trackpad. In some embodiments, the deep press intensity threshold corresponds to an intensity at which the device will perform operations that are different from operations typically associated with clicking a button of a physical mouse or a trackpad. In some embodiments, when a contact is detected with a characteristic intensity below the light press intensity threshold (e.g., and above a nominal contact-detection intensity threshold below which the contact is no longer detected), the device will move a focus selector in accordance with movement of the contact on the touch-sensitive surface without performing an operation associated with the light press intensity threshold or the deep press intensity threshold. Generally, unless otherwise stated, these intensity thresholds are consistent between different sets of user interface figures.

(184) An increase of characteristic intensity of the contact from an intensity below the light press intensity threshold to an intensity between the light press intensity threshold and the deep press intensity threshold is sometimes referred to as a “light press” input. An increase of characteristic intensity of the contact from an intensity below the deep press intensity threshold to an intensity above the deep press intensity threshold is sometimes referred to as a “deep press” input. An increase of characteristic intensity of the contact from an intensity below the contact-detection intensity threshold to an intensity between the contact-detection intensity threshold and the light press intensity threshold is sometimes referred to as detecting the contact on the touch-surface. A decrease of characteristic intensity of the contact from an intensity above the contact-detection intensity threshold to an intensity below the contact-detection intensity threshold is sometimes referred to as detecting liftoff of the contact from the touch-surface. In some embodiments, the contact-detection intensity threshold is zero. In some embodiments, the contact-detection intensity threshold is greater than zero.

(185) In some embodiments described herein, one or more operations are performed in response to detecting a gesture that includes a respective press input or in response to detecting the respective press input performed with a respective contact (or a plurality of contacts), where the respective press input is detected based at least in part on detecting an increase in intensity of the contact (or plurality of contacts) above a press-input intensity threshold. In some embodiments, the respective operation is performed in response to detecting the increase in intensity of the respective contact above the press-input intensity threshold (e.g., a “down stroke” of the respective press input). In some embodiments, the press input includes an

increase in intensity of the respective contact above the press-input intensity threshold and a subsequent decrease in intensity of the contact below the press-input intensity threshold, and the respective operation is performed in response to detecting the subsequent decrease in intensity of the respective contact below the press-input threshold (e.g., an “up stroke” of the respective press input).

(186) In some embodiments, the device employs intensity hysteresis to avoid accidental inputs sometimes termed “jitter,” where the device defines or selects a hysteresis intensity threshold with a predefined relationship to the press-input intensity threshold (e.g., the hysteresis intensity threshold is X intensity units lower than the press-input intensity threshold or the hysteresis intensity threshold is 75%, 90%, or some reasonable proportion of the press-input intensity threshold). Thus, in some embodiments, the press input includes an increase in intensity of the respective contact above the press-input intensity threshold and a subsequent decrease in intensity of the contact below the hysteresis intensity threshold that corresponds to the press-input intensity threshold, and the respective operation is performed in response to detecting the subsequent decrease in intensity of the respective contact below the hysteresis intensity threshold (e.g., an “up stroke” of the respective press input). Similarly, in some embodiments, the press input is detected only when the device detects an increase in intensity of the contact from an intensity at or below the hysteresis intensity threshold to an intensity at or above the press-input intensity threshold and, optionally, a subsequent decrease in intensity of the contact to an intensity at or below the hysteresis intensity, and the respective operation is performed in response to detecting the press input (e.g., the increase in intensity of the contact or the decrease in intensity of the contact, depending on the circumstances).

(187) For ease of explanation, the descriptions of operations performed in response to a press input associated with a press-input intensity threshold or in response to a gesture including the press input are, optionally, triggered in response to detecting either: an increase in intensity of a contact above the press-input intensity threshold, an increase in intensity of a contact from an intensity below the hysteresis intensity threshold to an intensity above the press-input intensity threshold, a decrease in intensity of the contact below the press-input intensity threshold, and/or a decrease in intensity of the contact below the hysteresis intensity threshold corresponding to the press-input intensity threshold. Additionally, in examples where an operation is described as being performed in response to detecting a decrease in intensity of a contact below the press-input intensity threshold, the operation is, optionally, performed in response to detecting a decrease in intensity of the contact below a hysteresis intensity threshold corresponding to, and lower than, the press-input intensity threshold.

(188) As used herein, the term “closed application” refers to software applications without retained state information (e.g., state information for closed applications is not stored in a memory of the device). Accordingly, closing an application includes stopping and/or removing application processes for the application and removing state information for the application from the memory of the device. Generally, opening a second application while in a first application does not close the first application. When the second application is displayed and the first application ceases to be displayed, the first application becomes a background application.

(189) System Overview

(190) FIG. 6 illustrates an example system 600 for aggregating and sharing wellness data. As mentioned above, wellness data can include, but is not limited to, any type of data associated with a person's health, such as their weight, heart rate, blood pressure, blood glucose level, medication compliance, activity level, or the like. System 600 can be used to collect wellness data associated with a user, store the wellness data, present the wellness data to the user in useful ways, and selectively share the user's wellness data with other users or entities based on permissions set by the user. In addition, in some examples, system 600 can further be used to collect non-wellness data along with wellness data, correlate the non-wellness data with the wellness data, and display the non-wellness data with the wellness data.

(191) System 600 can include one or more user devices 610 including any electronic device, such as a mobile phone, tablet computer, desktop computer, laptop computer, PDA, or the like. In some examples, user device 610 can include a device similar or identical to those shown in FIGS. 1A and 3 and described above. For example, user device 610 can include an operating system and a wellness database 611 for securely storing wellness or non-wellness data along with associated metadata, such as the time the data was recorded, type of data, device used to record the data, user associated with the data, and the like. User device 610 can further include application programming interfaces (APIs) with access controls for storing data in the wellness database 611 and for accessing data stored in the wellness database 611.

(192) User device 610 can be configured to receive wellness or non-wellness data from various sources and can store the received data in the wellness database 611. For example, user device 610 can be configured to receive wellness or non-wellness data from sensors 602, 604, 606, and 608. These sensors can include any type of sensor capable of obtaining wellness data, such as a biometric sensor, activity tracker, or the like. For example, sensors 602, 604, 606, and 608 can include, but are not limited to, a scale, blood pressure cuff, blood glucose monitor, electrocardiogram, step counter, gyroscope, accelerometer, SpO2 sensor, respiration sensor, posture sensor, stress sensor, photoplethysmogram, galvanic skin response sensor, temperature sensor, asthma inhaler, or the like. Sensors 602, 604, 606, and 608 can also include other types of sensors, such as audio sensors, ambient light sensors, electromagnetic sensors, touch sensors, capacitive sensors, and the like, for obtaining non-wellness data, such as situational data, temporal data, personal data, contact data, and the like data. In some examples, each sensor can be a separate device, while, in other examples, any combination of two or more of the sensors can be included within a single device. For example, the gyroscope, accelerometer, photoplethysmogram, galvanic skin response sensor, and temperature sensor can be included within a wearable electronic device, such as a smart watch, while the scale, blood pressure cuff, blood glucose monitor, SpO2 sensor, respiration sensor, posture sensor, stress sensor, and asthma inhaler can each be separate devices. While specific examples are provided, it should be appreciated that other sensors can be used and other combinations of sensors can be combined into a single device.

(193) Sensors 602, 604, 606, and 608 can be used to measure wellness or non-wellness data continuously, intermittently, periodically, or at any other desired frequency or interval of time. For example, sensors 602, 604, 606, and 608 can be used to obtain a single measurement or multiple measurements over a length of time. Sensors 602, 604, 606, and 608 can be configured to measure wellness or non-wellness data at the same intervals of time, or can be configured to measure wellness or non-wellness data at different intervals of time. These intervals may be set by a user or may be a default setting for each sensor. Additionally, sensors 602, 604, 606, and 608 can be used to measure wellness or non-wellness data at any time or location desired by the user. Moreover, sensors 602, 604, 606, and 608 can be used with or without the supervision of a healthcare provider. For example, a user can use sensors 602, 604, 606, and 608 to obtain sensor measurements at home without the supervision of a medical professional.

(194) In some examples, user device 610 can include software sensor applications 613 (e.g., third party applications) associated with each of sensors 602, 604, 606, and 608 for interfacing with the sensors to allow user device 610 to receive the wellness or non-wellness data. In these examples, the applications 613 can use the device's APIs to store the wellness or non-wellness data in the wellness database 611 of user device 610. In some examples, the software sensor applications 613 can be Apps and device 610 can be a smart phone, tablet computer, or the like. It should be understood that “third party” can correspond to an entity different than the manufacturer of device 610 and/or the entity that created and/or maintains the operating system of device 610. In these instances, third party applications and their corresponding sensors can communicate and function within the operating system of device 610 according to a predefined device protocol associated with device 610.

(195) The applications 613 can similarly use the device's APIs to access data stored in the wellness database 611. In other examples, user device 610 can be configured to share one or more communication formats with sensors 602, 604, 606, and 608 to allow user device 610 to receive and interpret the wellness or non-wellness data from the sensors. The received data can then be stored in the wellness database 611 of user device 610.

(196) User device 610 can further receive wellness or non-wellness data from its own wellness or non-wellness data sensors 615, such as a GPS sensor, clock, gyroscope, accelerometer, or the like, from a user interacting with user device 610, from another entity, such as a physician, or from other non-sensor sources. For example, using the device's APIs, wellness or non-wellness data can be received from applications 617 on user device 610, such as a clock application, a calendaring application, a gaming application, an application from a healthcare provider, a messaging application, or the like. The wellness or non-wellness data from the applications 617 can originate from a user interacting with the applications, a remote database

(e.g., database for a medical website), a healthcare provider institution (e.g., via the institution's App), or the like. In these examples, the usage of the application **617** (e.g., how long you play a video game application, when you play the video game, number of times interacting with a stock application, number of times interacting with a social networking application, length of time interacting with a social networking application, etc.), usage of user device **610** (e.g., length of time on the phone or number of text messages sent as determined from a phone payment application, time spent browsing the Internet as determined from the device's browser, etc.), time spent listening to music as determined from a music or streaming radio application, time spent using a remote application for controlling a television, amount of time or money spent on shopping websites, time spent on pornographic websites (e.g., to identify addictions), weather data from a weather application (e.g., to determine how weather affects a user's health), type of events occurring in the user's life as determined from a calendar (e.g., meetings, birthdays, holidays, etc.), interactions with certain people as determined from a contact list and/or calendar application and/or a messaging application and/or phone of user device **610**, or the like, can be received by user device **610** and stored in the wellness database **611**.

(197) In some examples, default or user-selected settings can be provided to restrict the access that at least one application (e.g., at least one of applications **613** and **617**) on user device **610** has to the wellness database **611** of user device **610** (for both storage and retrieval purposes) and to the sensor data generated by sensors **615** within user device **610** and/or sensor data generated by sensors **602**, **604**, **606**, and **608**. For example, an application for tracking a user's running sessions can be granted access to the data generated by the GPS sensor of user device **610**, but can be prevented from accessing the user's blood pressure data stored in the wellness database **611**. In some examples, an entity other than the owner of user device **610** can set the authorization settings for various applications on user device **610**. For example, the manufacturer of user device **610** and/or the entity that created and/or maintains the operating system of user device **610** can evaluate the applications to determine if they should be given access to the user's wellness data and/or sensor data generated or received by user device **610**. In some examples, these settings can be overridden by the user.

(198) User device **610** can further include a display for displaying the stored wellness data or non-wellness data. A more detailed description of the interface of the display of user device **610** is described below with respect to FIGS. **10-15**, **17**, **19-20**, **22-26**, **28-37**, **39-44**, **55-62**, and **64-66**.

(199) FIG. **7** illustrates system **700** for sharing user wellness data. Referring to FIG. **7**, user server **614** can be communicatively coupled to user device **610** via network **612**, which can include the Internet, an intranet, or any other wired or wireless public or private network. User device **610** can be configured to securely transmit the aggregated wellness or non-wellness data and associated metadata stored on the device to user server **614** for storage in user database **616**. In some examples, the wellness or non-wellness data and associated metadata can be transmitted to user server **614** for storage in user database **616** in response to an explicit request for such a transfer by the user of device **610**, while, in other examples, the wellness or non-wellness data can be synced with the data in user database **616** continuously, periodically, intermittently, or at any desired frequency. In yet other examples, the user's wellness or non-wellness data can be stored only on user device **610** and may not be stored in an external database.

(200) In some examples, user server **614** and user database **616** can be configured to securely store a user's wellness or non-wellness data using a public/private key system that only allows the owner of the wellness or non-wellness data to decrypt the data. Additionally, the wellness or non-wellness data stored in user database **616** can be stored anonymously (e.g., without identifying and/or personal information about the user, such as a legal name, username, time and location data, or the like). In this way, other users, hackers, and the owner/operator of user database **616** cannot determine the identity of the user associated with the data stored in database **616**. In some examples, a user can access their wellness or non-wellness data stored in user database **616** from a user device that is different than the one used to upload the wellness or non-wellness data to user server **614**. In these instances, the user can be required to provide login credentials to access their wellness or non-wellness data. User server **614** can be configured to perform the authorization process to restrict access to the data within user database **616**.

(201) System **700** can further include any number of other user devices **622** and **624** coupled to network **612**. In some examples, user devices **622** and **624** can be operated by the same user as user device **610**. In these instances, the user can access their wellness or non-wellness data stored in user database **616** by providing user server **614** with the appropriate credentials. In some examples, wellness and non-wellness data can be synced between user database **616** and one or more of user device **610**, **622**, and **624**. In other examples, the user of user devices **622** and **624** can be a person that is different than the user of user device **610**. In these examples, the users of devices **622** and **624** cannot access the wellness or non-wellness data of the user of user device **610** without the authorization of the user of user device **610**. If authorization is given, wellness or non-wellness data can be shared with the users of user devices **622** and **624**. The sharing of this data will be discussed in greater detail below with respect to FIGS. **7-8**.

(202) In some examples, any of the above described sources of wellness or non-wellness data can be configured to measure, generate, or receive wellness or non-wellness data continuously, intermittently, periodically, or at any other desired frequency or interval of time. As such, the wellness or non-wellness data can similarly be stored or updated in wellness database **611** or user database **616** continuously, intermittently, periodically, or at any other desired frequency or interval of time. The frequencies and intervals of time used for measuring, generating, receiving, or storing wellness or non-wellness can be the same or they can be different. Additionally, these frequencies and intervals can be default values or they can be set by a user to provide the user with wellness or non-wellness data that has been updated within a desired length of time.

(203) While not shown, it should be appreciated that many other user devices can be coupled to user server **614** through network **612** to collect and store wellness or non-wellness data for other users in a manner similar to that described above.

(204) User Database

(205) As discussed above, a user's wellness or non-wellness data can be stored in user database **616** and can be shared with other users with the owning user's authorization. The other users can be any type of user, such as a friend, family member, caregiver, physician, social media provider, or the like. Different types and levels of authorization can be granted for the wellness or non-wellness data contained in wellness database **616**.

(206) In some examples, the shared wellness or non-wellness data can be pushed to the user device (e.g., user device **622** or **624**) of the authorized other user. FIG. **8** illustrates an example process **800** for authorizing and pushing wellness or non-wellness data to authorized other users. At block **802**, an identification of an authorized other user can be received. This can be received by a user device (e.g., user device **610**) from the user associated with the shared wellness or non-wellness data. The identification can include a username, legal name, contact information, or any other identifier or credential for the other user, along with a level of access, such as access to all of the wellness or non-wellness data or a subset of the wellness or non-wellness data. In some examples, the authorized other user can be grouped into categories of users (e.g., family, friends, other, etc.), where each category is associated with a particular set of wellness data types that those authorized other users are allowed to view. For example, users in the family category can be allowed to view all types of wellness data, while users in the friend category can only view activity data.

(207) At block **804**, the user's wellness or non-wellness data can be monitored by the user's device to determine if any updates to the data have been made. If no update has been made, the process can repeat block **804**. If, however, an addition or change to the user's wellness or non-wellness data has been identified, the process can proceed to block **806**. In some examples, any change to the user's wellness or non-wellness data can cause process **800** to proceed to block **806**, while, in other examples, only changes to certain types of the user's wellness or non-wellness data can cause process **800** to proceed to block **806**.

(208) At block **806**, a notification can be transmitted to one or more authorized other users. For example, a notification can be transmitted from the user's device (e.g., user device **610**) to the device of the authorized other user (e.g., user device **622** or **624**). The notification can include a message indicating that an update has been made to the user's wellness or non-wellness data. The process can then proceed to block **808**.

(209) At block **808**, the updated wellness or non-wellness data can be transmitted to the authorized other user. For example, the updated wellness or non-wellness data can be transmitted from the user's device (e.g., user device **610**) to the device of the authorized other user (e.g., user device **622** or **624**). In some examples, this data can only be transmitted if the authorized other user indicated a desire to view the updated wellness or non-wellness

data, while, in other examples, the updated wellness or non-wellness data can be transmitted to the user device of the authorized other user without receiving a request from the authorized other user to view the data.

(210) The pushing of wellness or non-wellness data performed using process **800** can be useful in situations in which a user wants to keep a caregiver or family member (or other user) updated with his/her wellness or non-wellness data. For instance, an elderly parent can grant authorization to push his/her wellness or non-wellness data to a child to allow the child to easily monitor the elderly user's health or medication compliance without having to constantly request this information from the parent.

(211) In other examples, a user's wellness or non-wellness data can be shared with other users by allowing other users to pull the wellness or non-wellness data. FIG. **9** illustrates an example process **900** for authorizing other users to pull wellness or non-wellness data. At block **902**, a request to access a particular user's wellness or non-wellness data can be received. The request can identify the user associated with the requested wellness or non-wellness data and, optionally, the portion of the wellness or non-wellness data to be accessed. The identification can include a username, legal name, contact information, or any other identifier or credential for the user. The request can be received by a user device (e.g., user device **610**) of the user associated with the requested data from a user device (e.g., user device **622** or **624**) of the requesting user.

(212) At block **904**, a request for authorization can be transmitted to the user associated with the requested wellness or non-wellness data. In some examples, the request can be transmitted from the user device (e.g., user device **622** or **624**) of the requesting user to the user device (e.g., user device **610**) of the user associated with the requested data. The request can then be displayed to the user associated with the requested data by the user's device (e.g., user device **610**).

(213) At block **906**, it can be determined if an authorization has been received from the user associated with the requested wellness or non-wellness data. The authorization can be received in any manner. For example, a prompt can be displayed to the user associated with the requested data on their user device **610**. If authorization is denied, the process can return to block **902**. If, however, authorization is granted, the process can proceed to block **908**.

(214) At block **908**, the requested wellness or non-wellness data can be transmitted to the entity that requested access to the wellness or non-wellness data at block **902**. The requested wellness or non-wellness data can be transmitted from the user's device (e.g., user device **610**) to the requesting entity's device (e.g., user device **622** or **624**).

(215) In some examples, if authorization to access a user's wellness or non-wellness data is granted before a request is made at block **902**, process **900** can proceed from block **902** to block **908** without performing blocks **904** or **906**. For example, if a parent grants access to their wellness or non-wellness data to their child, a request by the child for the parent's wellness or non-wellness data can be received at block **902** and the requested wellness or non-wellness data can be transmitted to the child at block **908** without any intervening action by the parent.

(216) The pulling of wellness or non-wellness data using process **900** can be useful in situations where an authorized other user does not want to be constantly updated with updates to a user's wellness or non-wellness data, but would like occasional access to the data. For example, a physician may want access to a patient's medical records and wellness or non-wellness data just prior to meeting with the patient. In this situation, the physician can request the patient's wellness or non-wellness data and can either receive the requested data or cause a request to be sent to the user device **610** of the patient. In response to receiving an authorization from the patient, the requested data can be sent from user device **610** to the physician's computing device (e.g., user device **622** or **624**). In some examples, the received wellness or non-wellness data can be added to an electronic medical record (EMR) associated with the user.

(217) In some examples, whether using a push or pull sharing model, the wellness or non-wellness data of a user may not be permanently stored on the user device of authorized other users. In this way, authorization to these other users can be revoked, causing the user's wellness data to be inaccessible by the formerly authorized other users. Additionally, in some examples, reports detailing or summarizing a user's wellness or non-wellness data can be generated. These reports can then be transmitted via email, secure transfer, or the like, to any desired recipient. In yet other examples, user device **610** can be configured to communicate some or all of the user's wellness or non-wellness data, such as medical insurance information, blood type, medical history, etc., to medical personnel using near field communication or another communication protocol. This can be useful when checking in to a hospital or during medical emergencies when relevant medical data is needed.

(218) Aggregated Data View

(219) As discussed above, user device **610** can be configured to aggregate wellness or non-wellness data associated with a user that was received from the user, from one or more sensors **602**, **604**, **606**, and **608**, or from a non-sensor source. User device **610** can also be configured to display the user's aggregated wellness or non-wellness data in various ways using various interfaces.

(220) FIG. **10** illustrates one example interface **1000** that can be used by user device **610** to display a user's aggregated wellness or non-wellness data. Interface **1000** can include any number of partitions **1002**, **1004**, **1006**, **1008**, **1010**, and **1012**, each containing a different type of wellness data associated with the user. In the aggregated view of FIG. **10**, the partitions can be used to display a partial view of a portion of the different types of wellness data. In the examples shown in FIGS. **10-15**, **17**, and **19-20**, the partitions are illustrated as having the appearance and associated animations of a stack of cards, where each card corresponds to a different partition (and thus, a different type of wellness data). It should be appreciated, however, that the partitions can be displayed in any other desired manner.

(221) Interface **1000** can include a first partition **1002** displayed at the top of the interface that can include an identifier (e.g., name) of the user. As shown, the name "John Smith" of the user of user device **610** is displayed on partition **1002**. Interface **1000** can further include button **1001** for viewing wellness data associated with other users. This feature is described in greater detail below with respect to FIGS. **15** and **16**.

(222) Interface **1000** can further include another partition **1004** displayed adjacent to partition **1002** such that it appears to be overlapping partition **1002** like a stacked card. This partition can include an indication of the type of wellness data contained on the partition as well as a partial view (e.g., summary, example, or the like) of a portion the partition's wellness data. Specifically, partition **1004** includes the word "Weight" to indicate that the partition contains weight data associated with the user "John Smith." Partition **1004** can further include the most recent weight "185 lbs" of "John Smith."

(223) Interface **1000** can further include another partition **1006** displayed adjacent to partition **1004** such that it appears to be overlapping partition **1004** like a stacked card. This partition can include an indication of the type of wellness data contained on the partition as well as a partial view (e.g., summary, example, or the like) of a portion the partition's wellness data. Specifically, partition **1006** includes the words "Blood Sugar" to indicate that the partition contains blood sugar data associated with the user "John Smith." Partition **1006** can further include the most recent blood sugar level "164 mg/dL" of "John Smith."

(224) Interface **1000** can further include another partition **1008** displayed adjacent to partition **1006** such that it appears to be overlapping partition **1006** like a stacked card. This partition can include an indication of the type of wellness data contained on the partition as well as a partial view (e.g., summary, example, or the like) of a portion the partition's wellness data. Specifically, partition **1008** includes the words "Blood Pressure" to indicate that the partition contains blood pressure data associated with the user "John Smith." Partition **1008** can further include the most recent blood pressure measurement "117/67 mmHg" of "John Smith."

(225) Interface **1000** can further include another partition **1010** displayed adjacent to partition **1008** such that it appears to be overlapping partition **1008** like a stacked card. This partition can include an indication of the type of wellness data contained on the partition as well as a partial view (e.g., summary, example, or the like) of a portion of the partition's wellness data. Specifically, partition **1010** includes the word "Activity" to indicate that the partition contains activity data (e.g., calories burned) associated with the user "John Smith." Partition **1010** can further include the current daily number of calories burned "467 kcal" by "John Smith."

(226) Interface **1000** can further include another partition **1012** displayed adjacent to partition **1010** such that it appears to be overlapping partition

1010 like a stacked card. This partition can include an indication of the type of wellness data associated with the partition as well as a partial view (e.g., summary, example, or the like) of a portion of the partition's wellness data. Specifically, partition **1012** includes the words "Heart Rate" to indicate that the partition contains heart rate data associated with the user "John Smith." Partition **1012** can further include the most recent heart rate measurement "122 bpm" of "John Smith." Additionally, since partition **1012** is at the top of the stack of partitions, additional information **1014** and/or options **1016** can be displayed on the face of the partition. In the illustrated example, the additional information includes the minimum, maximum, and resting heart rate of "John Smith" over the span of a week, which was selected using options **1016**.

(227) The ordering of some or all of the partitions can be static or dynamic. For example, partition **1002** containing the user's name can remain at the top of the display, while the remaining partitions can be ordered based on the time of day, how recently the wellness data associated with the partition is updated, the frequency that the wellness data associated with the partition is updated, whether a notable event is approaching (e.g., medication that should be taken, a sensor measurement that should be performed, etc.), or the like. The ordering can also be manually changed by the user. If interface **1000** includes more partitions than can be displayed on a single screen, a vertical scrolling can be performed to display the remaining partitions. Alternatively, a 3D scrolling of the partitions may be performed to give the appearance of flipping through a stack of cards.

(228) While specific example partition types have been provided above, it should be appreciated that partitions containing different types of wellness data can be included within interface **1000**. Additionally, users can generate customized partitions that can be used to display any desired type of user-entered data. For example, a partition can be created to track the medication compliance of a user. The user can enter the time, amount, and type of medicine taken and this data can be displayed on the created partition. Other custom partitions for different wellness data types, such as nutrition, sleep, smoking, or the like can also be generated.

(229) Additionally, while specific examples of partial views (e.g., summary, example, or the like) of a portion of the partitions' wellness data have been provided above, it should be appreciated that the partial views can summarize or provide examples of the wellness data in different ways. For example, rather than display the most recent value of a particular wellness data type, a mean, mode, median, another single data point, or the like of the wellness data over all or a portion of time (e.g., a week, month, year, etc.) can be displayed on the partitions in the aggregated view. Alternatively, in other examples, a current and average value can be displayed on the partitions in the aggregated view. In yet other examples, the partitions in the aggregated view can include a display of a current value and a goal value for the type of wellness data.

(230) The partitions **1002**, **1004**, **1006**, **1008**, **1010**, and **1012** can be selected to display an expanded view of the partition containing reconfigured data, additional data, or an enlarged view of the original data contained on the partition. For example, a user can select a partition by tapping on the desired partition displayed on a touch sensitive display, can highlight and click on the partition using a mouse or other input device, or select the desired partition using any other input means. In response to a selection of a partition, user device **610** can hide the contents of the other partitions and display the selected partition on all or most of the display of user device **610**.

(231) For example, FIG. **11** illustrates an example interface **1100** that can be displayed in response to a user selecting partition **1004** in interface **1000**. In interface **1100**, expanded view **1005** of partition **1004** can be displayed prominently within the display of user device **610**, while the remaining partitions can be animated as being collapsed off the display into the stack of partitions **1102** displayed at the bottom of the display. In the illustrated example, expanded view **1005** can include additional weight-related data, such as the user's weight, body mass index (BMI), and fat percentage, that were not shown in interface **1000**. Expanded view **1005** can further include summaries of the user's weight data, such as a sliding scale **1140** indicating the user's weight relative to a range of weights and a graph **1141** tracking the user's weight throughout the day, week, month, or year. Interface **1100** can further include button **1104** that can cause user device **610** to display options for sharing some or all of their wellness data using any desired communication medium, such as text message, email, social media provider, or the like. In these examples, the wellness data can be encrypted and sent from the user device **610** directly to the user device of the recipient (rather than from user server **614**), where the wellness data can be decrypted. To return to the aggregated view of partitions shown in interface **1000**, the user can select (e.g., tap, click, or otherwise select) the stack of partitions **1102**. It should be appreciated that the contents of interface **1100** and expanded view **1005** are provided as examples, and that expanded view **1005** can instead include any type or summary of weight-related data.

(232) FIG. **12** illustrates an example interface **1200** that can be displayed in response to a user selecting partition **1006** in interface **1000**. In interface **1200**, expanded view **1007** of partition **1006** can be displayed prominently within the display of user device **610**, while the remaining partitions can be animated as being collapsed off the display into the stack of partitions **1102** displayed at the bottom of the display. In the illustrated example, expanded view **1007** can include additional blood sugar-related data, such as the user's blood sugar and units that were not shown in interface **1000**. Expanded view **1007** can further include summaries of the user's blood sugar data, such as a sliding scale **1142** indicating the user's blood sugar after a meal relative to a range of typical blood sugar level and a graph **1143** tracking the user's blood sugar throughout the day, week, month, or year. Interface **1200** can also include button **1104**, described above. To return to the aggregated view of partitions shown in interface **1000**, the user can select (e.g., tap, click, or otherwise select) the stack of partitions **1102**. It should be appreciated that the contents of interface **1200** and expanded view **1007** are provided as examples, and that expanded view **1007** can instead include any type or summary of blood sugar-related data.

(233) FIG. **13** illustrates an example interface **1300** that can be displayed in response to a user selecting partition **1008** in interface **1000**. In interface **1300**, expanded view **1009** of partition **1008** can be displayed prominently within the display of user device **610**, while the remaining partitions can be animated as being collapsed off the display into the stack of partitions **1102** displayed at the bottom of the display. In the illustrated example, expanded view **1009** can include additional blood pressure-related data, such as the user's blood pressure and beats per minute (bpm) that were not shown in interface **1000**. Expanded view **1009** can further include summaries of the user's blood pressure data, such as a sliding scale **1044** indicating the user's blood pressure relative to typical blood pressure values and a graph **1045** tracking the user's blood pressure throughout the day, week, month, or year. Interface **1300** can also include button **1004**, described above. To return to the aggregated view of partitions shown in interface **1000**, the user can select (e.g., tap, click, or otherwise select) the stack of partitions **1102**. It should be appreciated that the contents of interface **1300** and expanded view **1009** are provided as examples, and that expanded view **1009** can instead include any type or summary of blood pressure-related data.

(234) FIG. **14** illustrates an example interface **1400** that can be displayed in response to a user selecting partition **1010** in interface **1000**. In interface **1400**, expanded view **1011** of partition **1010** can be displayed prominently within the display of user device **610**, while the remaining partitions can be animated as being collapsed off the display into the stack of partitions **1102** displayed at the bottom of the display. In the illustrated example, expanded view **1011** can include additional activity-related data, such as the calories burned, steps taken, and miles traveled by the user that were not shown in interface **1000**. Expanded view **1011** can further include summaries of the user's blood pressure data, such as a graph **1146** tracking the intensity of their activity throughout the day, week, month, or year, and summaries **1147** showing the total time spent active, idle, and exercising. Interface **1400** can also include button **1104**, described above. To return to the aggregated view of partitions shown in interface **1000**, the user can select (e.g., tap, click, or otherwise select) the stack of partitions **1102**. It should be appreciated that the contents of interface **1400** and expanded view **1011** are provided as examples, and that expanded view **1011** can instead include any type or summary of activity-related data.

(235) FIG. **15** illustrates an example interface **1500** that can be displayed in response to a user selecting partition **1012** in interface **1000**. In interface **1500**, expanded view **1013** of partition **1012** can be displayed prominently within the display of user device **610**, while the remaining partitions can be animated as being collapsed off the display into the stack of partitions **1102** displayed at the bottom of the display. In the illustrated example, expanded view **1013** can include additional heart rate-related data, such as minimum, maximum, and resting heart rate of the user over a day, week, month, or year. However, unlike partitions **1004**, **1006**, **1008**, and **1010**, this data was previously displayed within interface **1000** since partition **1012** was displayed in the aggregated view as being located at the top of the stack of partitions. Expanded view **1013** can further include a summary of the user's heart rate data, such as a graph **1148** tracking the user's heart rate throughout the day, week, month, or year. Interface **1500** can also include

button **1100**, described above. To return to the aggregated view of partitions shown in interface **1000**, the user can select (e.g., tap, click, or otherwise select) the stack of partitions **1102**. It should be appreciated that the contents of interface **1500** and expanded view **1013** are provided as examples, and that expanded view **1013** can instead include any type or summary of heart rate-related data.

(236) In some examples, a user's wellness data used to generate the interfaces shown in FIGS. **10-15** and **55** may have been received from one or more sensor devices and/or applications. In these examples, the wellness data of the same type from different devices may be combined and displayed on a single partition. For example, the weight data shown in interface **1100** in FIG. **11** can be obtained from repeated measurements taken using the same scale. Alternatively, some of the measurements could have been obtained from one scale, while the remaining measurements could have been obtained from one or more different scales. As a result, some points in graph **1141** could have been generated using weight data from one scale, while other points in graph **1141** could have been generated using weight data from one or more other scales. In another example, the activity data shown in interface **1400** in FIG. **14** may have been obtained from a single step counting device. Alternatively, the data may be aggregated from a step counting device, a first GPS-enabled watch used to record a user's running session, and a second GPS-enabled watch used to record a user's rowing session. In these examples, graph **1146** showing the intensity of the user's activity can be a segmented graph generated from a combination of the data obtained from the step tracking device and the first and second GPS-enabled watches, with each segment coming from one of the devices. In particular, graph **1146** can include a first segment **1150** generated from data from the step counting device, a second segment **1152** generated from data from the first GPS-enabled watch, and a third segment **1154** generated from data from the second GPS-enabled watch. Aggregating data in this way advantageously allows a user to record and view wellness data in a manner that does not directly tie the wellness data to a particular device or application (e.g., smartphone applications). While three segments are shown in FIG. **14**, it should be appreciated that the segmented graph can include any number of segments corresponding to different sensors and/or applications.

(237) FIG. **16** illustrates an example process **1600** for displaying wellness data according to various examples. At block **1602**, an aggregated view of wellness data containing a plurality of partitions similar or identical to partitions **1002**, **1004**, **1006**, **1008**, **1010**, and **1012** can be displayed on a user device similar or identical to user device **610**. The partitions can include an identifier for the type of wellness data displayed on the partition and a partial view (e.g., summary, example, or the like) of a portion of the type of wellness data associated with the partition. For example, an interface similar or identical to interface **1000** can be displayed containing various wellness data partitions **1002**, **1004**, **1006**, **1008**, **1010**, and **1012**.

(238) At block **1604**, a selection of one of the displayed partitions can be received. The selection can be received by the user device, and can be in the form of a mouse click, tap on a touch sensitive display, or the like. In response to a selection of the partition, an expanded view of the selected partition can be displayed at block **1606**. The expanded view can include a view showing a larger portion of the selected partition and at least one of reconfigured wellness data (e.g., a rearranged view of the wellness data displayed on the selected partition in the aggregated view displayed at block **1602**), additional wellness data (e.g., wellness data that was not previously displayed on the selected partition in the aggregated view displayed at block **1602**), or an enlarged view of the wellness data displayed in the aggregated view displayed at block **1602** (e.g., a larger view of the same wellness data displayed on the selected partition in the aggregated view displayed at block **1602**). Additionally, partitions that were not selected can be reduced in size or removed from the display. For example, any of interfaces **1100**, **1200**, **1300**, **1400**, or **1500** can be displayed in response to a selection of partition **1004**, **1006**, **1008**, **1010**, or **1012** of interface **1000**, respectively.

(239) In some examples, the display presented at block **1606** can include a selectable option (e.g., button **1204**) to share wellness data. In other examples, the display presented at block **1606** can further include a selectable option (e.g., partitions **1202**) to cause the aggregated view containing partitions displayed at block **1602** to again be displayed. The process can then return to block **1604**, where a selection of another partition can be received.

(240) FIG. **17** illustrates an example interface **1700** that can be displayed in response to a user rotating user device **610** to a landscape view. In this orientation, user device **610** can display expanded views of a smaller subset of partitions than displayed in the aggregated view of interface **1000**. For example, interface **1700** can include expanded view **1702** of partition **1008**, expanded view **1704** of partition **1006**, and expanded view **1706** of partition **1012**. In the illustrated example, the expanded views of the partitions can include graph representations of the wellness data over various lengths of time. This can allow a user to view the displayed types of wellness data and see how they change relative to each other over time and to evaluate how a change in one type of wellness data relates to a change (or lack thereof) in another type of wellness data. For example, one type of wellness data that can be displayed can include medications taken over time. This data can be compared to a user's blood pressure and heart rate to determine if the medication is having a beneficial or detrimental effect. In some examples, user device **610** can select the types of wellness data to be displayed when user device **610** is rotated into landscape orientation. The selection can be made based on predetermined combinations of wellness data types that are often associated with each other or can be made based on an analysis of the various types of wellness data. In the latter example, wellness data types that are identified as potentially being correlated can be displayed. Wellness data types not shown in the initial display of interface **1700** can be viewed by scrolling through the partitions. Additionally, the partitions can be selected to display more detailed information in the same way as performed in interface **1000**.

(241) FIG. **18** illustrates an example process **1800** for displaying wellness data based on an orientation of the device according to various examples. At block **1802**, an aggregated view containing a plurality of partitions similar or identical to partitions **1002**, **1004**, **1006**, **1008**, **1010**, and **1012** can be displayed by a user device similar or identical to user device **610**. The partitions can include an identifier for the type of wellness data displayed on the partition and a partial view (e.g., summary, example, or the like) of a portion the type of wellness data associated with the partition. For example, an interface similar or identical to interface **1000** can be displayed containing various wellness data partitions **1002**, **1004**, **1006**, **1008**, **1010**, and **1012**.

(242) At block **1804**, a change in orientation of the user device can be detected. For example, a gyroscope and/or an accelerometer within the user device can indicate that the orientation of the device has been changed from portrait to landscape. In response to a detected change in orientation by a threshold amount, the process can proceed to block **1806**.

(243) At block **1806**, a subset of the plurality of partitions displayed at block **1802** can be selected for display. In some examples, the subset can be a predetermined subset of the plurality of partitions. In other examples, the subset can be selected based on user-defined preferences for display. In yet other examples, the subset of the plurality of partitions can be selected based on an analysis of the wellness data sets associated with each partition to determine if any of the types of wellness data are potentially correlated. If a potential correlation is identified, the partitions associated with the potentially correlated data can be selected at block **1806**.

(244) At block **1808**, expanded views of the subset of partitions selected at block **1806** can be displayed. In some examples, the identifier for the type of wellness data displayed on the expanded view of the partition and/or the summary, example, or other view of the type of wellness data associated with the partition can be different than that shown on the partitions at block **1802**. For example, the summary or example data on each expanded view can be replaced with a graph representation of the wellness data over time, as shown in FIG. **17**. In this way, relationships between the displayed types of wellness data can be observed. In some examples, in response to detecting a change in the orientation of the user device to a portrait orientation, the process can return to block **1802**.

(245) As discussed above, in some examples, the user of user device **610** can be granted access to the wellness data of other users. In these examples, user device **610** can allow the user to view the wellness data of other users in a similar format as discussed above with respect to FIGS. **10-18**. For example, as shown by interface **1900** in FIG. **19**, to view the wellness data of other users, the user can laterally scroll the contents of the interface in direction **1906** to cause a first set of partitions **1904** from a first user to be displayed in place of the second set of partitions **1902** from a second user. In particular, the second set of partitions **1902** for the second user can be translated off the display in the direction **1906** of the scroll, while the first plurality of partitions **1904** can be translated onto the display in the same direction **1906** but from the opposite side of the display. It should be

appreciated that FIG. 19 illustrates a transitional state in which partitions **1902** and partitions **1904** are being scrolled in direction **1906** onto the display. As such, only the left side of partitions **1902** and the right side of partitions **1904** are visible. As partitions **1902** and **1904** continue to be scrolled in direction **1906**, a smaller portion of partitions **1902** may be visible while a larger portion of partitions **1904** may be visible until partitions **1902** are completely removed from the display and partitions **1904** occupy all or most of the display. While not shown, the top partition of partitions **1904** can include the first user's name and can be displayed as the screen continues to be scrolled in direction **1906**. This scrolling operation can be performed any number of times (and in any direction) to scroll through the partitions for all users that the user of device **610** is authorized to access.

(246) FIG. 20 illustrates another example interface **2000** for viewing the wellness data of other users. In some examples, interface **2000** can be displayed in response to a selection of button **1001** of interface **1000**. As shown, interface **2000** can include a list of users **2002**, **2004**, **2006**, and **2008** that have authorized the user of user device **610** to access their wellness data. In some examples, the circles next to each user's name can be replaced with an image associated with the user. These images can be the same image as used in device **610**'s contact list or can include another image. In the illustrated example, users **2002**, **2004**, **2006**, and **2008** have been grouped into different categories (e.g., self, family, and friends). The categories can be used to logically group users together or, as discussed above, can indicate a level of authorization to view the wellness data of the other users. For example, users in the "family" category may have authorized a larger set of their wellness data to be viewed, while users in the "friend" category may have authorized a smaller set of their wellness data to be viewed. In response to a selection of one of users **2002**, **2004**, **2006**, and **2008**, partitions **2010** can be updated to reflect the wellness data of the selected user. This can include updating the types of wellness data displayed on the partitions (e.g., based on the types of wellness data the other user has authorized the user of user device **610** to view) as well as the associated partial views (e.g., summary, example, or the like) of portions the wellness data. In other examples, the list of users **2002**, **2004**, **2006**, and **2008** can be displayed in response to vertically scrolling interface **1000** up or down to expose the list of users.

(247) FIG. 21 illustrates an exemplary process **2100** for displaying wellness data associated with two or more users according to various examples. At block **2102**, a display of a first plurality of partitions associated with a first user can be displayed. The partitions can be similar or identical to partitions **1002**, **1004**, **1006**, **1008**, **1010**, and **1012** and can be displayed by a user device similar or identical to user device **610**. The partitions can include an identifier for the type of wellness data displayed on the partition and a partial view (e.g., summary, example, or the like) of a portion the type of wellness data associated with the partition. For example, an interface similar or identical to interface **1000** can be displayed containing various wellness data partitions **1002**, **1004**, **1006**, **1008**, **1010**, and **1012**.

(248) At block **2104**, a request to view a second plurality of partitions of a second user can be received. The second user can be a user that has authorized the first user to view their wellness data as described above. In some examples, the request can include a user input to scroll the display of the first plurality of partitions displayed at block **2102** and can be received by the user device in the form of rotation of a mouse wheel, an arrow key on a keyboard, a touch and/or swipe on a touch sensitive display, or the like. Similar to the example shown in FIG. 19, the scroll direction can be in a horizontal direction relative to the contents of the display and can be perpendicular to a scroll direction that causes additional partitions associated with the first user to be displayed. However, it should be appreciated that other scroll directions can be used. In other examples, the request to view the second plurality of partitions can be received in the form of a selection of the second user from a list of users. For example, the second user can be selected from a list of users similar to that shown in FIG. 20. The list can be displayed in response to a selection of a button (e.g., button **1001**) or other selection mechanism, such as vertically scrolling the first plurality of partitions displayed at block **2102** to expose the list of users. In response to receiving the request to view the second plurality of partitions at block **2104**, the process can proceed to block **2106**.

(249) At block **2106**, a display of the second plurality of partitions associated with the second user can be displayed. In some examples, when the request to view the second plurality of partitions received at block **2104** included a request to scroll the display of the first plurality of partitions, the first plurality of partitions can be translated off the display in the direction of the scroll, while the second plurality of partitions can be translated onto the display in the same direction but from the opposite side of the display, as shown in FIG. 19. In other examples, when the request to view the second plurality of partitions received at block **2104** included a selection of the second user from a list of users, the first plurality of partitions can be replaced with a display of the second plurality of partitions, as shown in FIG. 20. Additional requests to view wellness data partitions of other users can be received and blocks **2104** and **2106** can be repeated to display some or all of the sets of partitions associated with users that have authorized the user of device **610** to view their wellness data.

(250) It should be appreciated that the processes described above can be combined. For example, process **1800** can be combined with process **1600** such that after the plurality of partitions are displayed at block **1502**, a change in orientation of the user device can cause blocks **1804**, **1806**, and **1808** to be performed. Similarly, process **2100** can be combined with process **1500** such that after the plurality of partitions are displayed at block **1602**, the receipt of a request to view partitions associated with other users can cause blocks **2104** and **2106** to be performed to display a plurality of partitions associated with another user.

(251) As mentioned above, systems **600** and **700** can be configured to measure, generate, receive, or store wellness or non-wellness data continuously, intermittently, periodically, or at any other desired frequency or interval of time. Processes **1600**, **1800**, and **2100** can similarly be performed to update the display of wellness or non-wellness data continuously, intermittently, periodically, or at any other desired frequency or interval of time. For example, the device performing process **1600**, **1800**, or **2100** can receive updated wellness or non-wellness data from wellness database **611** or user database **616** continuously, intermittently, periodically, or at any other desired frequency or interval of time. In some examples, the device performing process **1600**, **1800**, or **2100** can receive updates to all wellness or non-wellness data at the same frequency or interval of time. In other examples, the device performing process **1600**, **1800**, or **2100** can be configured to receive updates to different types of data at different frequencies or intervals of time. For example, heart rate data can be updated every second, while weight data and menstrual flow data can be updated daily. These intervals and frequencies can be default values or can be selected by the user.

(252) Dashboard View

(253) FIG. 22 illustrates one example interface **2200** that can be displayed by user device **610** to display a detailed view of a user's wellness or non-wellness data. Interface **2200** can include any number of partitions **2202**, **2204**, and **2206**, each representing a different type of wellness or non-wellness data associated with the user (e.g., data stored in wellness database **611**). In some examples, the partitions can be displayed in a color based on the type of wellness or non-wellness data that it represents. For example, a partition representing nutrition data can be displayed in one color, and a partition representing of fitness data can be displayed in another.

(254) In some examples, a partition can include an identification of the type of wellness or non-wellness data that the partition represents (e.g., calories, steps, weight, or the like), a numerical daily value of the represented type of wellness or non-wellness data, and a graph representation of the represented type of wellness or non-wellness data. For example, partition **2202** can include the text "Calories" to indicate that it represents Calorie data, a current daily value **2210** of 1250 Calories burned, and a graph representation **2208** of the Calorie data over time throughout the day. Similarly, partition **2204** can include the text "Steps" to indicate that it represents step data, a current daily value **2211** of 3100 steps, and a graph representation **2209** of the step data over time throughout the day. Interface **2200** can further include a partial view of partition **2206** showing the text "Weight" to indicate that it represents weight data, as well as a daily value **2212** of 160 lbs. In the illustrated example, the graphs of each partition are non-overlapping with each other.

(255) In some examples, the detailed view of the user's wellness or non-wellness data can include partitions not shown in interface **2200**. In these examples, a user can initiate a scroll request by swiping up or down on a touch sensitive display, by clicking and dragging on a display using a mouse or other input device, by manipulating a scroll-wheel, by performing a swiping gesture on a touch pad, or the like. In response to detecting the scroll request, user device **610** can scroll the view of interface **2200** to display other partitions that were not previously displayed (or were partially

displayed, such as partition **2206**).

(256) For example, FIG. 23 illustrates an example interface **2300** that can be displayed in response to a user initiating a scroll request to scroll the view of interface **2200** in an upward direction. In interface **2300**, the remainder of partition **2206** can be displayed to show a graph representation **2214** of the weight data over time throughout the week. Another partition **2216** can also be displayed below partition **2206** in interface **2300**.

Partition **2316** can include the text “Blood Pressure” to indicate that it represents blood pressure data, a current daily value **2210** of 117/67 mmHg, and a graph representation **2218** of the blood pressure data over time throughout the week. In the example shown in FIG. 23, graph **2218** includes two vertical bars for each day. The top and bottom of the upper vertical bar for each day can represent the high and low diastolic blood pressure values, respectively, for the day. Similarly, the top and bottom of the lower vertical bar for each day can represent the high and low systolic blood pressure values, respectively, for that day.

(257) In some examples, the order of partitions within interface **2200** or **2300** can be changed in response to detecting a user request to reorder the partitions. In some examples, the request to reorder can include a selecting and holding of one of the partitions for greater than a threshold length of time. After detecting that the threshold length of time has elapsed, user device **610** can animate the partitions in a way that indicates that the partitions can be reordered. In some examples, the partitions can be reordered by dragging a selected partition to a desired location. However, in other examples, the partitions can be reordered in any other desired manner.

(258) While only four partitions **2202**, **2204**, **2206**, and **2216** are shown in the detailed view illustrated by interfaces **2200** and **2300**, it should be appreciated that the detailed view can include additional partitions representing any number and any type of wellness or non-wellness data. Similar to partitions **2202**, **2204**, **2206**, and **2216**, these additional partitions can include identifications of the type of wellness or non-wellness data that the partitions represent, numerical daily values of the represented types of wellness or non-wellness data, and graph representations of the represented types of wellness or non-wellness data.

(259) In some examples, a graph view of some or all of the wellness or non-wellness data displayed in the detailed view can be displayed in response to a graph-view input. In some examples, the graph-view input can include a detected change in orientation of user device **610**. For example, FIG. 24 illustrates an example interface **2400** that can be displayed in response detecting a rotation of user device **610** to a landscape view. The graph view of interface **2400** can include data-set representations **2402**, **2404**, **2406**, and **2408**, each representing a different set of wellness or non-wellness data. In the illustrated example, the y-axis of the graph can represent a dependent variable of the various data sets, and the x-axis of the graph can represent an independent variable. For example, if data-set representation **2402** represents a set of Calorie data, then the y-axis dependent variable can be Calories, and the x-axis independent variable can be time. Similarly, if data-set representation **2404** represents step data, then the y-axis dependent variable can be a number of steps, and the x-axis independent variable can be time.

(260) In some examples, the data-set representations can be displayed in a color based on the type of wellness or non-wellness data that it represents. For example, a data-set representation representing nutrition data can be displayed in one color, and a data-set representation of fitness data can be displayed in another. In some examples, the colors used for the different types of wellness or non-wellness data can correspond to the colors used to display the partitions in the detailed views of interfaces **2200** and **2300**. For example, a partition representing a set of nutrition data can be displayed in the same color as a data-set representation representing the same set of nutrition data.

(261) In some examples, the independent variable of the x-axis can be the same for all data-set representations shown in the graph view. For example, the time represented by the x-axis can be the same for each data-set representation.

(262) In some examples, the dependent variable of the y-axis can be measured or reported in a different unit for some or all of the data-set representations. For example, the dependent variable for data-set representation **2402** can be expressed in Calories, the dependent variable for data-set representation **2404** can be expressed in a number of steps, the dependent variable for data-set representation **2406** can be expressed in pounds (representing weight data), and the dependent variable for data-set representation **2408** can be expressed in mmHg (representing blood pressure data). Since these data-set representations having different units of measurement can be shown overlaid on the same display, a different vertical y-axis scaling can be used to display the various data-set representations. In some examples, to determine a vertical scale for one of the data-set representations, the minimum and maximum value of the represented data set that are to be displayed within the graph can be determined. For example, to determine the scaling factor for data-set representation **2402** representing Calorie data, the maximum and minimum values of the Calorie data can be determined over the span of time represented by the x-axis of the display. In the example shown in FIG. 24, this can include determining the maximum and minimum values of the Calorie data over a week. The determined maximum value can be multiplied by a first scaling factor that can have any value (e.g., a value greater than or equal to 1, such as 1.1), and the determined minimum value can be multiplied by a second scaling factor that can be the same or different from the first scaling factor (e.g., a value less than or equal to 1, such as 0.9). The products of the maximum and minimum values multiplied by the first and second scaling factors can be assigned to the maximum vertical position (e.g., highest position on the y-axis) and the minimum vertical position within the graph (e.g., lowest position on the y-axis), respectively. This allows the data-set representation to be fully displayed within the graph. For example, if the maximum and minimum values of the Calorie data represented by data-set representation **2402** is 1000 Calories and 300 Calories, respectively, and if a first scaling factor of 1.1 and a second scaling factor of 0.9 are used, then the maximum vertical position of the y-axis can represent 1100 Calories and the minimum vertical position of the y-axis can represent 270 Calories for data-set representation **2402**. This process can be repeated for each of the displayed data-set representations, resulting in a different scale for each of the data-set representations. This advantageously allows the data-set representations to be clearly displayed overlaid on the same graph. For example, if the same scaling factor were instead used for all sets of data, it is possible that the values for one data-set representation can be substantially larger than another, causing the other data-set representation to appear as a flat line.

(263) In some examples, one or more of the displayed data-set representations can be selected to display additional data associated with the selected data-set representation. In some examples, for the purpose of selecting a particular data-set representation by a user, the data-set representations of the graph view shown in interface **2400** can be associated with a range (e.g., a unique range) of vertical positions within the graph. For example, the graph shown in interface **2400** can be divided into four ranges of vertical positions **2410**, **2412**, **2414**, and **2416** separated by the dashed lines. In this example, data-set representation **2402** can be associated with first range of vertical positions **2410**, data-set representation **2404** can be associated with second range of vertical positions **2412**, data-set representation **2406** can be associated with third range of vertical positions **2414**, and data-set representation **2408** can be associated with fourth range of vertical positions **2416**.

(264) A selection of one of the data-set representations can be made by entering a user input within a range of vertical positions corresponding to the desired data-set representation, regardless of the horizontal position of the user input. For example, to select data-set representation **2402**, a user input in the form of a touch event by a finger or other device on a touch sensitive display, a click of a mouse or other device, a touch event on a touch pad, or the like, can be made at location **2418** having a vertical position located within the first range of vertical positions **2410**.

(265) In response to detecting the user input at location **2418** having a vertical position within first range **2410**, user device **610** can display an indication that data-set representation **2402** was selected. For example, FIG. 25A shows interface **2500** that can be displayed in response to detecting the input received at location **2418** in interface **2400**. As shown, a circle marker can be displayed overlaid on data-set representation **2410** at a horizontal position corresponding to the horizontal position of location **2418**. Additionally, a numerical value of 480 kcal can be displayed, indicating that the value of the data set represented by data-set representation **2402** has a value of 480 at the horizontal position of the user input (e.g., horizontal position of location **2418**). As shown, data-set representation **2402** can be selected by a user input at location **2418** even though the line of data-set representation **2402** is not located near location **2418**. This can advantageously allow a user to select a desired data-set representation without having to select a particular portion of the data-set representation, which can be difficult at locations where multiple data-set representations overlap. In some examples, one of the data-set representations **2402**, **2404**, **2406**, or **2408** can represent blood pressure data. In these examples, for

purposes of generating the line of the data-set representation, the dependent variable for the blood pressure data can include an average of the diastolic and the systolic blood pressure. However, the numerical value displayed in response to a selection of the data-set representation for blood pressure data can include a high value for diastolic blood pressure, a low value for diastolic blood pressure, a high value for systolic blood pressure, and a low value for systolic blood pressure associated with the time corresponding to the horizontal position of the user input.

(266) In some examples, one of the data-set representations **2402**, **2404**, **2406**, or **2408** can represent heart rate data. In these examples, the numerical value displayed in response to a selection of the data-set representation for heart rate data can include a high value for heart rate and a low value for heart rate associated with the time corresponding to the horizontal position of the user input.

(267) In some examples, the indication of a selection displayed in response to detecting a user input can further include highlighting an area below the line of the selected data-set representation, as shown in FIG. 25B. For example, the area below the line of the selected data-set representation can be darkened, brightened, displayed with a different color, or otherwise highlighted relative to other portions of the graph to change the line graph into an area graph of the selected data set. In addition, as is the case in FIG. 25B, indicator **2522** can provide a read-out of the value of a dependent variable (e.g., sexual activity events) corresponding to an independent variable corresponding to location **2512**. In some examples, the data-set representations that are not currently selected can be removed from the display, greyed out, or otherwise made less visible within the graph.

(268) In some examples, a user input can be continuously applied to the displayed graph and moved in a horizontal direction within one of the range of vertical positions to scrub through values of the selected data-set representation. For example, in response to detecting that the user input received at location **2418** is moved in the left direction, the circle marker displayed over data-set representation **2402** can be animated such that it appears to move along the line of data-set representation **2402** at horizontal positions corresponding to the current horizontal position of the user input. Similarly, the displayed value can change to reflect the value of the data set represented by data-set representation **2402** at the horizontal position of the user input.

(269) In some examples, the vertical ranges of values within the graph associated with the data-set representations can be static. In other examples, the vertical ranges of values within the graph associated with the data-set representations can change. For example, in response to detecting a user input at a location within first range **2410**, the size of first range **2410** can expand based on a length of time that the detected user input remains within first range **2410**. As a result, the other vertical ranges can contract, or decrease in size. In some examples, the size of first range **2410** can expand to cover the entire graph. In other examples, the size of first range **2410** can expand to a predefined limit. Expanding the size of a selected range of vertical positions advantageously provides the user with a greater tolerance for vertical deviation as the user moves their user input in a horizontal direction to select different portions of a data-set representation.

(270) In some examples, interface **2400** or **2500** can include a compare option **2420** to select the sets of wellness or non-wellness data that are to be displayed within the graph view. For example, FIG. 26 illustrates an example interface **2600** that can be displayed in response to a user selection of compare option **2420** in interface **2400** or **2500**. As shown, interface **2600** includes a list of types of wellness or non-wellness data that can be displayed within the graph view. Each type of wellness or non-wellness data can be associated with a selectable option, such as option **2602**, to allow the user to add or remove the associated type of wellness or non-wellness data from the graph view. In the illustrated example, the data sets corresponding to Calorie data, step data, blood pressure data, and heart rate data are selected to be displayed within the graph view, while weight data is not. In some examples, the list of wellness or non-wellness data displayed within interface **2600** can include the types of wellness or non-wellness represented by the partitions of interfaces **2200** and **2300**.

(271) As another example, FIG. 64A illustrates exemplary user interface **6400** that can be displayed in response detecting a rotation of user device **610** to a landscape view. The graph view of interface **6400** can include data-set representations **6402**, **6404**, and **6406**, each representing a different set of wellness or non-wellness data. In the illustrated example, the y-axis of the graph can represent a dependent variable of the various data sets, and the x-axis of the graph can represent an independent variable. For example, if data-set representation **6402** represents a set of Calorie data, then the y-axis dependent variable can be Calories, and the x-axis independent variable can be time.

(272) Data-set representation **6404**, which is shown with discrete dependent variable values, can represent various wellness or non-wellness information. Examples of underlying data represented by data-set representation **6404** are discussed with reference to FIGS. 64B-64F.

(273) Turning to FIG. 64B, data-set representation **6404** can represent the wellness information of basal temperature in some examples. As can be seen, user interface **6410** in user interface **6400** is displayed responsive to touch input **6410** on an indicator of data-set representation **6404** in user interface **6400** (FIG. 64A). User interface **6410** provides basal body temperature range **6424** corresponding to the location of touch input **6410**. Range **6424** has a high value as indicated by marker **6426** and a low value as indicated by marker **6428**, which are also provided in text read-out **6422**.

(274) Turning to FIG. 64C, data-set representation **6404** can represent the wellness information of cervical mucus information in some examples. As can be seen, user interface **6420** is displayed responsive to touch input **6410** on an indicator of data-representation **6404** in user interface **6400** (FIG. 64A). User interface **6420** provides cervical mucus information, which can take on discrete values such as “dry,” “watery,” or “creamy,” for example. As shown, indicator **6414** corresponding to touch input **6410** shows a text read-out **6412** of “creamy”.

(275) Turning to FIG. 64D, data-set representation **6404** can represent the wellness information of menstrual flow in some examples. As can be seen, user interface **6430** is displayed responsive to touch input **6410** on an indicator of data-representation **6404** in user interface **6400** (FIG. 64A). User interface **6420** provides menstrual flow information, which can take on discrete values such as “light,” “medium,” or “heavy,” for example. As shown, indicator **6434** corresponding to touch input **6410** shows a text read-out **6434** of “heavy”.

(276) Turning to FIG. 64E, data-set representation **6404** can represent the wellness information of sexual activity in some examples. As can be seen, user interface **6440** is displayed responsive to touch input **6410** on an indicator of data-representation **6404** in user interface **6400** (FIG. 64A). User interface **6440** provides sexual activity information, such as the number of sexual activity events at a given time interval. As shown, indicator **6444** corresponding to touch input **6410** shows a text read-out **6442** that one sexual activity event has occurred at the time corresponding to the horizontal location of touch input **6410**.

(277) Turning to FIG. 64F, data-set representation **6404** can represent the wellness information of menstrual spotting in some examples. As can be seen, user interface **6450** is displayed responsive to touch input **6410** on an indicator of data-representation **6404** in user interface **6400** (FIG. 64A). User interface **6450** provides menstrual spotting information, such as the occurrence of spotting at a given time interval. As shown, indicator **6458** corresponding to touch input **6410** shows a text read-out **6452** indicating menstrual spotting at the time corresponding to the horizontal location of touch input **6410**.

(278) As another example, FIG. 65A illustrates exemplary user interface **6500** that can be displayed in response detecting a rotation of user device **610** to a landscape view. The graph view of interface **6500** can include, among others, data-set representations **6506** and **6508** each representing a different set of wellness or non-wellness data. In the illustrated example, the y-axis of the graph can represent a dependent variable of the various data sets, and the x-axis of the graph can represent an independent variable. For example, if data-set representation **6506** represents a set of Calorie data, then the y-axis dependent variable can be Calories, and the x-axis independent variable can be time.

(279) Data-set representation **6508**, which is shown as horizontal bar(s), can represent various wellness or non-wellness information. Examples of underlying data represented by data-set representation **6504** are discussed with reference to FIGS. 65B-65C.

(280) Turning to FIG. 65B, data-set representation **6508** can represent the wellness information of cervical mucus information in some examples. As can be seen, user interface **6510** is displayed responsive to touch input **6504** on an indicator of data-representation **6508** in user interface **6500** (FIG. 65A). User interface **6510** provides cervical mucus information, which can take on discrete values such as “dry,” “watery,” or “creamy,” for example. As shown, range **6512** corresponding to touch input **6504** shows a text read-out **6514** of “creamy”. In this example, the dependent variable of data-set

representation 6508 takes on values from a set of discrete values (e.g., “dry”, “watery”, and “creamy”). In some examples, range 6512 covers the weekdays corresponding to the location of touch input 6510.

(281) Turning to FIG. 65C, data-set representation 6508 can represent the wellness information of menstrual flow in some examples. As can be seen, user interface 6520 is displayed responsive to touch input 6504 on an indicator of data-representation 6508 in user interface 6500 (FIG. 65A). User interface 6520 provides menstrual flow information, which can take on discrete values such as “light,” “medium,” or “heavy,” for example. As shown, range 6522 corresponding to touch input 6504 shows a text read-out 6524 of “light”. In this example, the dependent variable of data-set representation 6508 takes on values from a set of discrete values (e.g., “light,” “medium,” and “heavy”). In some examples, range 6522 covers the weekdays corresponding to the location of touch input 6510.

(282) As another example, FIG. 66A illustrates exemplary user interface 6600 that can be displayed in response detecting a rotation of user device 610 to a landscape view. The graph view of interface 6600 can include, among others, data-set representations 6602 and 6604 each representing a different set of wellness or non-wellness data. In the illustrated example, the y-axis of the graph can represent a dependent variable of the various data sets, and the x-axis of the graph can represent an independent variable. For example, if data-set representation 6602 represents a set of Calorie data, then the y-axis dependent variable can be Calories, and the x-axis independent variable can be time.

(283) Data-set representation 6604, which is shown as a horizontal bar, can represent wellness or non-wellness information. Examples of underlying data represented by data-set representation 6604 are discussed with reference to FIG. 66B. As can be seen in FIG. 66B, data-set representation 6604 can represent the wellness information of menstrual spotting in some examples. User interface 6610 provides menstrual spotting information, such as the occurrence of spotting at a given time interval. As shown, range 6612 shows a text read-out 6614 indicating menstrual spotting at the time corresponding to the horizontal location of touch input 6606. In this example, the dependent variable of data-set representation 6604 takes on values from a set of discrete values (e.g., Boolean values of “positive” or “negative”). In some examples, range 6612 covers the weekdays corresponding to the location of touch input 6606.

(284) In some examples, the detailed view of the wellness or non-wellness data can be displayed in response to a detailed-view input received while any of interfaces 2400, 2500, 2510, 6400, 6410, 6420, 6430, 6440, 6500, 6510, 6520, 6600, or 6610 (FIGS. 24, 25, and 64-66) are being displayed. In some examples, the detailed-view input can include a detected change in orientation of user device 610. For example, interface 2200, 2300, 5600, 5610, 5620, 5630, 5700, 5710, 5720, 5730, 5800, 5810, 5820, 5830, 5900, 5910, 5920, 5930, 6000, 6010, 6020, 6030, 6100, 6110, 6120, or 6130 (FIGS. 22, 23, and 56-61) can be displayed in response to detecting a rotation of user device 610 to a portrait view.

(285) While the graph view shown in interfaces 2400, 2500, 6400, 6500, or 6660 (FIGS. 24, 25, 64, 65, and 66) include three or four data-set representations, it should be appreciated that the graph can include any number of data-set representations. Additionally, the number of ranges of vertical positions can change based on the number of displayed data-set representations (e.g., to be equal to the number of displayed data-set representations). For example, if six data-set representations are displayed within the graph, then six discrete ranges of vertical positions can be associated with the data-set representations to allow a user to select the desired data-set representation.

(286) FIG. 27 illustrates an example process 2700 for displaying continuous and/or discrete wellness or non-wellness data according to various examples. Process 2700 can be performed at an electronic device (e.g., device 610) with a display. In some examples, the display can include a touch-sensitive display. In other examples, the display can be separate from a touch-sensitive surface. Some blocks of process 2700 can be combined and/or the order of some blocks can be changed.

(287) As described below, process 2700 provides an intuitive way to select overlapping data-set representations in a graph view. At block 2702, a graph view of wellness or non-wellness data can be displayed on a display of a user device (e.g., user device 610). For example, an interface similar or identical to interface 2400, 2500, 6400, 6500, or 6660 (FIGS. 24, 25, 64, 65, and 66) can be displayed. The graph view can include a first data-set representation (e.g., data set representation 2402) of a first data set in which a first dependent variable varies as an independent variable changes and a second data-set representation (e.g., data set representation 2404) of a second data set in which a second dependent variable varies as the independent variable changes.

(288) In some examples, the first data set can include a first set of wellness data, and the second data set can include a second set of wellness data.

(289) In some examples, the first data-set representation can be associated with a first range of vertical positions within the graph (e.g., first range 2410) and the second data-set representation can be associated with a second range of vertical positions within the graph (e.g., second range 2412).

(290) In some examples, the first data-set representation can be displayed in the graph overlapping the second data-set representation. For example, in FIGS. 24 and 25, data-set representations 2402, 2404, 2406, and 2408 are shown as overlapping in interfaces 2400 and 2500. As another example, FIG. 64, data-set representations 6402, 6404, and 6406 are shown as overlapping. In some examples, the first data-set representation and the second data-set representation can be colored-coded based on a type of data that they represent.

(291) In some examples, the first range of vertical positions can be uniquely associated with the first data-set representation, and the second range of vertical positions can be uniquely associated with the second data-set representation. For example, first range 2410 is uniquely associated with data-set representation 2402 and second range 2412 is uniquely associated with data-set representation 2404 in interfaces 2400 and 2500.

(292) In some examples, a vertical scale for displaying the first data-set representation can be different from a vertical scale for displaying the second data-set representation. In these examples, displaying the graph can include determining a vertical scale for the first data-set representation based on the maximum and minimum values of the first dependent variable of the first data-set representation that are to be displayed in the graph. Displaying the graph can further include determining a vertical scale for the second data-set representation based on the maximum and minimum values of the second dependent variable of the second data-set representation that are to be displayed in the graph. In some examples, the vertical scale for the first data-set representation can be defined by a maximum vertical position within the graph corresponding to a first multiplying factor multiplied by the maximum value of the first dependent variable of the first data-set representation that are to be displayed in the graph, and a minimum vertical position within the graph corresponding to a second multiplying factor multiplied by the minimum value of the first dependent variable of the first data-set representation that are to be displayed in the graph. In some examples, the vertical scale for the second data-set representation can be defined by a maximum vertical position within the graph corresponding to a third multiplying factor multiplied by the maximum value of the second dependent variable of the second data-set representation that are to be displayed in the graph, and a minimum vertical position within the graph corresponding to a fourth multiplying factor multiplied by the minimum value of the second dependent variable of the second data-set representation that are to be displayed in the graph. In some examples, the dependent variable for the first data set can be measured or reported in different units from the dependent variable for the second data set.

(293) In some examples, the first data set has dependent variables that represent discrete data values, and the second data set has dependent variables that represent values along a continuous range of possible values. As used here, the word “discrete” value refers to distinct, non-continuous values, such as the category values of “heavy,” “medium,” and “light”. A (first) data-set where dependent variables are aligned with discrete elements stands in contrast to a (second) data-set where dependent variables can take on any value along a given range, such as a temperature range, in that dependent variables of the first data set can take on values drawn from a finite set of discrete values, but dependent variables of the second data set can take on an infinite number of value along the applicable range. For example, body temperature can be represented using the discrete values (e.g., categories) of “hot,” “normal,” and “cold,” as well as be represented using data points along a continuous range, such as the value 97.4 degrees along the range of 90 to 110 degrees.

(294) At block 2704, a user input can be detected at a location on the display. Detecting the user input can include detecting a touch or hover event by a finger or other device on a touch sensitive display, a click of a mouse or other device, a touch or hover event on a touch pad, or the like.

(295) At block 2706, a location of the user input can be determined. For example, the vertical and horizontal positions (e.g., y and x-axis coordinates)

of the user input can be determined. In some examples, an indication of a selection of the first data-set representation can be displayed, in response to determining that the location of the user input on the display detected at block **2704** has a vertical position associated with the first range of vertical positions. Alternatively, in response to determining that the location of the user input on the display detected at block **2704** has a vertical position associated with the second range of vertical positions, an indication of a selection of the second data-set representation can be displayed. In some examples, an indication of a selection of the first data-set representation can be displayed, in response to determine that the location of the user input on the display detected at block **2704** is located at an indicator representing the value of a discrete dependent variable.

(296) In some examples, displaying the indication of a selection can include displaying a marker overlaid on the selected data-set representation at a horizontal position corresponding to the horizontal position of the location of the user input. For example, a circle marker can be displayed over data-set representation **2402** in interface **2500** of FIG. **25** in response to detecting a user input at location **2418** in interface **2400**. In another example, a filled circle marker can be displayed at over an indicator of data-set representation **6404** corresponding to touch input **6410** as shown in FIG. **64D**.

(297) In some examples, displaying the indication of a selection can include displaying a numerical and/or textual representation of a data entry of the data set represented by the selected data-set representation. The data entry can be associated with a category value corresponding to the horizontal position of the location of the detected user input. For example, a numerical value of 480 kcal can be displayed in response to receiving a user input at location **2418**, as can be seen in FIGS. **24** and **25**. In another example, a textual representation **6434** of “Heavy” can be displayed in response to receiving a user input at location **6410** as shown in FIG. **61D**.

(298) In some examples, the first data set or the second data set can include blood pressure data. In these examples, the displayed numerical value of the data entry can include a high value for diastolic blood pressure, a low value for diastolic blood pressure, a high value for systolic blood pressure, and a low value for systolic blood pressure. In some examples, the dependent variable of the first data-set representation or the second data-set representation can include average of blood pressure values.

(299) In other examples, the first data set or the second data set can include heart rate data. In these examples, the displayed numerical value of the data entry can include a high value for heart rate and a low value for heart rate.

(300) In some examples, the first data set or second data set can include reproductive health data, such as cervical mucus data, basal body temperature, or menstrual flow data. In these examples, the textual representation displayed in response to a selection of the data-set representation for cervical mucus can include “Creamy,” “Dry,” or “Egg white” associated with the time corresponding to the horizontal position of the user input. The textual representation displayed in response to a selection of the data-set representation for basal body temperature can include a temperature reading associated with the time corresponding to the horizontal position of the user input. The textual representation displayed in response to a selection of the data-set representation for menstrual flow can include “Heavy,” “Medium,” or “Light” associated with the time corresponding to the horizontal position of the user input.

(301) In some examples, the first data-set representation can include a first line in the graph. In these examples, displaying the indication that the first data-set representation has been selected can include highlighting an area below the first line. For example, the area below the line of the selected data-set representation can be darkened, brightened, displayed with a different color, or otherwise highlighted relative to other portions of the graph to change the line graph into an area graph of the selected data set. In some examples, the data-set representations that are not currently selected can be removed from the display, greyed out, or otherwise made less visible within the graph.

(302) In some examples, when a given data-set representation is selected, other data-set representations provide an indication that they are not selected, for example, by greying out.

(303) In some examples, the first range of vertical positions within the graph can expand based on a length of time that the user input is detected while a vertical position of the location of the user input is within the first range of vertical positions. In other examples, the second range of vertical positions within the graph can expand based on a length of time that the user input is detected while the vertical position of the location of the user input is within the second range of vertical positions.

(304) At block **2708**, a detailed-view input can be detected at the electronic device. In some examples, detecting the detailed-view input can include detecting a change in orientation of the electronic device while displaying the graph. For example, detecting the detailed-view input can include detecting a change in orientation of the electronic device from a landscape view (e.g., shown in FIGS. **24-26**) to a portrait view (e.g., shown in FIGS. **22-23**). In other examples, the detailed-view input can include other types of inputs.

(305) At block **2710**, in response to detecting the detailed-view input, a detailed view of the first data set and the second data set can be displayed. For example, a detailed view similar or identical to those shown in interfaces **2200** and **2300** can be displayed. The detailed view can include a first partition associated with the first data set (e.g., partition **2202**) and a second partition associated with the second data set (e.g., partition **2204**).

(306) In some examples, the first partition can include a first graph representation of the first data set (e.g., graph **2208**), and the second partition can include a second graph representation of the second data set (e.g., graph **2210**). In some examples, unlike the first and second data-set representation of the graph view, the first graph representation can be non-overlapping with the second graph representation in the detailed view.

(307) In some examples, the first partition can be displayed in a color matching a color of the first data-set representation, and the second partition can be displayed in a color matching a color of the second data-set representation. For example, partition **2202** can be displayed in a color matching a color of data-set representation **2402**, and partition **2204** can be displayed in a color matching a color of data-set representation **2404**.

(308) In some examples, process **2700** can further include detecting a request to scroll the detailed view and, in response to detecting the request to scroll the detailed view, scrolling the detailed view. For example, the detailed view shown in interface **2200** can be scrolled in the upward direction to display interface **2300** containing other partitions that were not previously displayed.

(309) In some examples, process **2700** can further include detecting a request to reorder the first partition and the second partition and, in response to detecting the request to reorder the first partition and the second partition, reordering the first partition and the second partition within the detailed view. In some examples, detecting the request to reorder can include detecting a selection of one of the partitions for greater than a threshold length of time. After detecting the selection for the threshold length of time, user device **610** can animate the partitions in a way that indicates that the partitions can be reordered. The partitions can be displayed reordered in response to detecting that a selected partition is dragged to a new location within the detailed view.

(310) In some examples, process **2700** can further include detecting a graph-view input at the electronic device and, in response to detecting the graph-view input, displaying the graph comprising the first data-set representation of the first data set and the second data-set representation of the second data set. In some examples, detecting the graph-view input can include detecting a change in orientation of the electronic device. For example, interface **2400** can be displayed in response to detecting a change in orientation of the electronic device from a portrait view to a landscape view.

(311) It should be understood that the particular order in which the operations in FIG. **27** have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other processes described herein (e.g., processes **900**, **1600**, **1800**, **2100**, **2700**, **3800**, or **4500**) are also applicable in an analogous manner to process **2700** described above with respect to FIG. **27**. For brevity, these details are not repeated here.

(312) Input and Output of Heath Data with Granularity

(313) FIG. **28** illustrates one example interface **2800** that can be displayed by user device **610** to display a user's wellness or non-wellness data. Interface **2800** can include a list **2802** of categories of wellness or non-wellness data. The categories can include one or more sub-categories of wellness or non-wellness data. The sub-categories can further include any number of additional sub-categories. For example, the category “Fitness”

can include sub-categories “Body Mass Index,” “Body Fat Percentage,” “Height,” “Body Mass,” “Lean Body Mass,” “Steps,” “Distance,” “Calories Burned,” “Active Hours,” and “Flights of Stairs.” The category “Vital Signs” can include sub-categories “Heart Rate,” “Systolic Blood Pressure,” “Diastolic Blood Pressure,” “Oxygen Saturation,” “Respiratory Rate,” and “Body Temperature.” The category “Lab Results” can include sub-categories “Blood Glucose” and “Blood Alcohol Content.” The category “Nutrition” can include sub-categories “Total Fat,” “Polyunsaturated Fat,” “Monounsaturated Fat,” “Saturated Fat,” “Cholesterol,” “Sodium,” “Potassium,” “Carbohydrates from Sugar,” “Dietary Fiber,” “Sugars,” “Dietary Calories,” “Calories from Fat,” “Protein,” “Vitamin A,” “Vitamin B6,” “Vitamin B12,” “Vitamin C,” “Vitamin D,” “Vitamin E,” “Vitamin K,” “Calcium,” “Iron,” “Thiamin,” “Riboflavin,” “Niacin,” “Folic Acid,” “Biotin,” “Pantothenic Acid,” “Phosphorus,” “Iodine,” “Magnesium,” “Zinc,” “Selenium,” “Copper,” “Manganese,” “Chromium,” “Molybdenum,” and “Chloride.” The category “Diagnostics” can include sub-categories “Number of Time Fallen,” “Galvanic Skin Response,” and “Body Heat Flux.” The category “Medications” can include sub-category “Inhaler Use.” The category “Sleep” can include subcategories “Hours Slept.” The category “Me” can include sub-categories “Name,” “Birthdate,” “Gender,” “Blood Type.” It should be appreciated that the lists above are provided only as examples, and that additional or fewer categories can be included within interface **2800**. Additionally, it should be appreciated that the categories of interface **2800** can include additional or fewer sub-categories.

(314) In some examples, each item in list **2802** can include an indicator **2804** that can be color-coded based on the type of wellness or non-wellness data of the associated item in list **2802**. For example, the indicator **2804** associated with “Fitness” can have a different color than the indicator **2804** associated with “Vital Signs.” In some examples, the items in list **2802** can further include a selectable option **2806** that can be used to expand the associated category.

(315) For example, FIG. **29** illustrates interface **2900** that can be displayed in response to a selection of option **2806** associated with “Fitness.” As shown, interface **2900** can include a list **2902** of sub-categories that fall under the broader category of “Fitness” that was selected in interface **2800**. The list **2902** of sub-categories can be displayed in place of the previously displayed list **2802**. Similar to list **2802**, the items in list **2902** can include an indicator **2904** that can be color-coded based on the type of wellness or non-wellness data of the associated item in list **2902**. In this example, since all of the sub-categories displayed within list **2902** fall under the same category or type of wellness or non-wellness data, the indicators **2904** associated with each item can be the same color. In some examples, the color of indicators **2904** associated with the items in list **2902** can be the same color as indicator **2804** associated with “Fitness.” In other examples, the color of indicators **2904** associated with the items in list **2902** can be a different shade of the color of indicator **2804** associated with “Fitness.” For example, indicators **2904** can be light green, while indicator **2804** associated with “Fitness” can be dark green.

(316) Referring back to FIG. **28**, interface **2800** (and interface **2900**) can further include search box **2808** for performing keyword searches within the categories listed in list **2802**. For example, FIG. **30** illustrates interface **3000** that can be displayed in response to a user entering the search query “Calories” in search box **2808**. As shown, interface **3000** can include a list **3002** of sub-categories that match the search query “Calories.” The sub-categories can be sub-categories of any of the categories of list **2802**. For “Calories Burned” can be a sub-category of “Fitness,” “Dietary Calories” can be a sub-category of “Nutrition,” and “Calories From Fat” can be a sub-category of “Nutrition.” Interface **3000** can further include indicators **3004** associated with the items in list **3002**. Similar to indicators **2804** and **2904**, indicators **3004** can be color-coded based on the type of wellness or non-wellness data of the associated item in list **3002**. In this example, indicator **3004** of “Dietary Calories” can be the same color as indicator **3004** of “Calories From Fat” since they both fall within the broader category of “Nutrition.” In some examples, the color of indicators **3004** of “Dietary Calories” and “Calories From Fat” can be the same color as indicator **2804** for “Nutrition.” In other examples, the color of indicators **3004** of “Dietary Calories” and “Calories From Fat” can be a different shade of the color of indicator **2804** for “Nutrition.” The indicator **3004** for “Calories Burned” can be a different color from indicators **3004** of “Dietary Calories” and “Calories From Fat” since “Calories Burned” falls within a different category (e.g., “Fitness”). In some examples, the color of indicator **3004** of “Calories Burned” can be the same color as indicator **2804** for “Fitness.” In other examples, the color of indicator **3004** of “Calories Burned” can be a different shade of the color of indicator **2804** for “Fitness.”

(317) In some examples, any of the sub-categories shown in interfaces **2900** and **3000** can be selected to display a detailed view of the sub-category. For example, FIG. **31** illustrates an example interface **3100** that can be displayed in response to a selection of “Calories Burned” from either interface **2900** or **3000**. As shown, interface **3100** can include a text indication of the type of wellness or non-wellness data being displayed in the detailed view. For example, interface **3100** include the text “Calories Burned” to indicate that the information displayed within interface **3100** represents information associated with Calories burned.

(318) In some examples, interface **3100** can further include a current daily value **3104** of 1250 kcal and a graph representation **3102** showing the number of Calories burned over time throughout the day. Interface **3100** can further include “Show All Data” option **3106** that can be used to display all data that falls within the sub-category of “Calories Burned.” For example, FIG. **33** illustrates an example interface **3300** that can be displayed in response to a selection of option **3106** in interface **3100**. As shown, interface **3300** can include a list **3302** of all data entries that represent calories burned (e.g., stored in wellness database **611**). As shown, the data entries in list **3302** can include a numerical value of the data entry and an associated date (and can also include a time) that the corresponding data entry was recorded. For example, the first data entry in list **3302** can include the number **860** associated with date 3/1/2014, indicating that 860 Calories were burned on 3/1/2014. The data entries in list **3302** can further include an indicator **3304**. Indicator **3304** can include a graphic, text, or other image that represents the source of the data entry. For example, if the first data entry was obtained from a wearable electronic Device **1**, indicator **3304** associated with that data entry can include an image of the logo of the company that manufactured Device **1** or some other image associated with Device **1**. Similarly, if the second data entry in list **3302** was obtained from a software application App **1**, indicator **3304** associated with the second data entry can include an image associated with a logo of the company that created App **1** or some other image associated with App **1**.

(319) While shown for Calories burned, it should be appreciated that a list of data entries associated with any type of sub-category of wellness or non-wellness data can be displayed in a similar manner.

(320) Referring back to FIG. **31**, interface **3100** can further include “Add Data Point” option **3108** that can be used to display an interface for manually entering a data entry within the sub-category of “Calories Burned.” For example, FIG. **34** illustrates an example interface **3400** that can be displayed in response to a selection of option **3108** in interface **3100**. As shown, interface **3400** can include fields **3402**, **3404**, and **3406** for entering the date, time, and number of Calories burned, respectively, for the data entry being input. Interface **3400** can further include numerical input pad **3408** for populating fields **3402**, **3404**, and **3406**. Interface **3400** can further include “Add” button **3410** that can be selected to add the information contained in interface **3400** as a data entry within the Calories burned sub-category (e.g., to be stored in wellness database **611**). Interface **3400** can further include “Cancel” button **3412** for canceling entry of the data entry.

(321) Referring back to FIG. **31**, interface **3100** (and interface **3200**) can further include “Show On Dashboard” option **3112** having option **3120** for selectively causing the associated sub-category of data (e.g., Calories Burned) to be displayed in the detailed view of interfaces **2200** and **2300**. When the switch of option **3120** is placed in the on position, the associated sub-category of data can be included within the detailed view of interfaces **2200** and **2300**. However, when the switch of option **3120** is placed in the off position, the associated sub-category of data may not be included within the detailed view of interfaces **2200** and **2300**.

(322) As shown in FIG. **31**, interface **3100** can further include graphic **3114**. Graphic **3114** can include any image or other graphical representation of the wellness or non-wellness data represented displayed in interface **3100**. For example, graphic **3114** can include a balance showing the relative values of Calories consumed and Calories expended by the user. However, it should be appreciated that any other graphic or image can be shown.

(323) In some examples, the detailed view of the sub-category can further include additional information not shown in interface **3100**. In these examples, a user can initiate a scroll request by swiping up or down on a touch sensitive display, by clicking and dragging on a display using a mouse or other input device, by manipulating a scroll-wheel, by performing a swiping gesture on a touch pad, or the like. In response to detecting the scroll

request, user device **610** can scroll the view of interface **3100** to display information that was previously displayed (or was partially displayed).

(324) For example, FIG. **32** illustrates an example interface **3200** that can be displayed in response to a user initiating a scroll request to scroll the view of interface **3100** in an upward direction. In interface **3200**, graphic **3114** and options **3106**, **3108**, **3110**, and **3112** can still be displayed, but can be located closer to the top of the display. Interface **3200** can further include text description **3122** below graphic **3114**. Text description **3122** can include a text describing what the wellness or non-wellness data shown in interface **3200** represents. For example, text description **3122** can provide an explanation about what “Calories Burned” represents, such as how it is calculated, what an average daily value is for a typical person, how to increase the amount of Calories burned, or the like.

(325) Referring back to FIG. **31**, interface **3100** can further include “Share Data” option **3110** having option **3116** for turning data sharing on or off. Data sharing can represent the ability for other devices or applications to access a user's wellness or non-wellness data (e.g., stored in wellness database **611**). For example, FIG. **35** illustrates an example interface **3500** that can be displayed in response to a selection of option **3110** in interface **3100**. As shown, interface **3500** can include share option **3502** having selectable option **3512**. The position of the switch of option **3512** can be used to turn data sharing on or off. For example, when moved to the right, as shown in FIG. **35**, the switch of option **3512** can turn on sharing option **3502**. However, when moved to the left, the switch of option **3512** can turn off sharing option **3502**.

(326) Interface **3500** can further include a list **3504** of known possible destinations of wellness or non-wellness data. This list can include known devices or software applications that can potentially receive a user's wellness or non-wellness data (e.g., stored in wellness database **611**). When option **3512** of share option **3502** is moved to the off position, data sharing for all listed devices and applications can be turned off. As such, selectable options **3514**, **3516**, and **3518** can be removed from interface **3500** or otherwise made inactive. When option **3512** of share option **3502** is moved to the on position, selectable options **3514**, **3516**, and **3518** associated with the destinations in list **3504** can be displayed or made selectable. Similar to option **3512**, the position of the switches of options **3514**, **3516**, and **3518** can be changed to turn data sharing on or off for the associated destination. For example, option **3514** for Device **1** is in the off position, indicating that data sharing is not turned on for Device **1**. Options **3516** and **3518**, however, are in the on position, indicating that data sharing is turned on for App **1** and App **2**. When data sharing is turned on, the associated device or application can access the user's wellness or non-wellness data (e.g., stored in wellness database **611**). For example, App **1**, which can represent a weight tracking application, can access a user's fitness and nutrition data to track the user's caloric intake and outtake. When data sharing is turned off, the associated device or application may be prevented from accessing the user's wellness or non-wellness data (e.g., stored in wellness database **611**). For example, Device **1** may be unable to access data stored in wellness database **611**.

(327) Interface **3500** can further include source list **3506** containing a list of known devices and applications that can potentially provide wellness or non-wellness data (e.g., to be stored in wellness database **611**). The devices and applications in source list **3506** can be arranged in an order based on their priority. For example, as shown, Device **1** has priority over Device **2**, which has priority over App **3**. These relative priorities can be used to de-duplicate wellness or non-wellness data generated by two or more of the sources. For example, if Device **1** represents a fitness-tracking watch, and Device **2** represents a mobile phone, it is possible that both devices can provide step data associated with the user. Thus, by prioritizing the different sources, data from a higher ranked source can be used in place of data from a lower ranked source, or otherwise prioritized over data from the lower ranked source. This can be advantageous when one device is more likely to produce more accurate results than another. In some examples, duplicate data entries can be detected by identifying two or more data entries having metadata indicating that they are of the same type (e.g., step data, Calories burned, etc.) and having an associated timestamp that is within a threshold length of time from each other.

(328) In some examples, interface **3500** can further include edit option **3508** for changing the order of the sources of source list **3506**. For example, in response to a selection of option **3508**, each item in source list **3506** can be moved (e.g., by clicking and dragging, etc.) relative to each other. The new order of sources within source list **3506** can define a new prioritization between sources.

(329) In some examples, the “Sources” option of source list **3506** can be selected to display a more detailed view of the sources. For example, FIG. **36** illustrates an example interface **3600** that can be displayed in response to a selection of the “Sources” option of source list **3506**. As shown, interface **3600** can include a source list **3606** similar to source list **3506**. However, source list **3606** can further include sources App **2** and App **1**, which were not displayed within interface **3500** because they were unable to be fit within the display. Interface **3600** can further include a numerical indicator associated with a source (e.g., Device **1**) that indicates a number of new types of wellness or non-wellness data that the associated source can provide. For example, since the last time the user viewed interface **3600**, Device **1** is now able to provide two new types of data (e.g., Calories burned and flights of stairs climbed). Interface **3600** can further include option **3610** associated with the sources in source list **3606** to provide more detailed control over the types of data that each source can provide.

(330) For example, FIG. **37** illustrates an example interface **3700** that can be displayed in response to a selection of option **3610** in interface **3600** or option **3510** in interface **3500** associated with Device **1**. As shown, interface **3700** can include upload option **3702** having selectable option **3704**. The position of the switch of option **3704** can be used to turn data uploading from the device or application on or off (e.g., to be stored in wellness database **611**). For example, when moved to the right, as shown in FIG. **37**, the switch of option **3704** can turn on data uploading by Device **1**. However, when moved to the left, the switch of option **3704** can turn off data uploading by Device **1**.

(331) Interface **3700** can further include a list **3706** of data types that can be provided by Device **1**. When option **3512** of share option **3704** is moved in the off position, data uploading for all listed types of data can be turned off. As such, selectable options **3708**, **3710**, **3712**, and **3714** can be removed from interface **3700** or otherwise made inactive. When option **3704** of upload data option **3702** is moved to the on position, selectable options **3708**, **3710**, **3712**, and **3714** associated with the list **3706** of data types can be displayed or made selectable. Similar to option **3704**, the position of the switches of options **3708**, **3710**, **3712**, and **3714** can be changed to turn data uploading on or off for the associated types of data. For example, option **3708** for Blood Pressure is in the off position, indicating that data uploading is not turned on for Blood Pressure data from Device **1**. Options **3710**, **3712**, and **3714**, however, are in the on position, indicating that data uploading is turned on for Calorie, Step, and Stairs Climbed data. When data uploading is turned on, the associated type of data can be provided by the device or application to be stored by user device **610** (e.g., in wellness database **611**). For example, Calorie data generated by Device **1** can be received by user device **610** from Device **1** and stored in wellness database **611**. When data uploading is turned off, the associated type of data may not be provided by the device or application to be stored by user device **610** (e.g., in wellness database **611**). For example, blood pressure data generated by Device **1** may not be received by user device **610** from Device **1** and stored in wellness database **611**. The options of interface **3700** advantageously allow a user to specifically define what types of data can be provided by a particular device or application.

(332) While the examples shown in FIGS. **30-34** were for Calories burned, it should be appreciated that similar interfaces can also be displayed for other types of wellness or non-wellness data.

(333) FIGS. **55A-55B** illustrate other exemplary interfaces that can be displayed by user device **610** to display a user's wellness or non-wellness data. As seen in FIG. **55A**, interface **5500** can include Selection Box **5502** that allows a user to select whether to view the data in a list view or calendar view. When the list view is selected, as depicted in FIG. **55**, interface **5500** shows a list **5504** of categories of wellness or non-wellness data. Responsive to selection of option **5506** (reproductive health), device **610** displays interface **5510** which shows the sub-categories of wellness information associated with option **5506**. These sub-categories of wellness information is described with respect to FIGS. **56-61**.

(334) Turning to FIGS. **56A-56D**, responsive to selection of option **5508** (FIG. **55B**), one of interfaces **5600**, **5610**, **5620**, or **5630** (FIGS. **56A-56D**) is displayed, in some examples. As can be seen in FIG. **56A**, interface **5600** depicts basal body temperature information at the hourly level of detail for a given day. Interface **5600** includes temperature label **5608**, and indicator **5606** indicating temperature (e.g., dependent variable) for a given time (e.g., independent variable). Turning to FIG. **56B**, interface **5610** depicts basal body temperature information at the daily level of detail for a given week. Notably, indicator **5611** depicts the high basal body temperature for a given day, indicator **5612** depicts the low basal body temperature for a

given day, and range **5614** depicts the range of basal body temperatures for a given day. In addition, category label **5616** takes on the lowest basal body temperature for the week, while category label **5618** takes on the highest basal body temperature for the week. Similarly, interface **5620** depicted in FIG. **56C** depicts basal body temperatures for a given month, and interface **5630** depicted in FIG. **56D** depicts basal body temperatures for a given year. In some embodiments, a user navigates between user interfaces **5600**, **5610**, **5620**, and **5630** (FIGS. **56A-56D**) by pinching or de-pinching touch input on device **610**.

(335) Turning to FIGS. **57A-57D**, responsive to selection of option **5510** (FIG. **55B**), one of interfaces **5700**, **5710**, **5720**, or **5730** (FIGS. **57A-57D**) is displayed, in some examples. As can be seen in FIG. **57A**, interface **5700** depicts cervical mucus information at the hourly level of detail for a given day. Interface **5700** includes indicator **5706** whose horizontal position corresponds to an independent variable (e.g. time of day) of the data set, and whose vertical position corresponds to a dependent variable (e.g., mucus consistency) of the data set. Turning to FIG. **57B**, interface **5710** depicts cervical mucus information at the daily level of detail for a given week. Notably, range indicator **5716** depicts the median consistency of cervical mucus for a period during which cervical mucus is observed. Similarly, interface **5720** depicted of FIG. **57C** depicts median cervical mucus consistency across different periods **5726** and **5728** during which cervical discharge is observed, across the timeframe of a month. Similarly, interface **5730** depicted of FIG. **57D** depicts median cervical mucus consistency across different periods **5736** and **5738** during which cervical discharge is observed, across the timeframe of a year. In some embodiments, a user navigates between user interfaces **5700**, **5710**, **5720**, and **5730** (FIGS. **57A-57D**) by pinching or de-pinching to zoom touch input on device **610**.

(336) Turning to FIGS. **58A-58D**, responsive to selection of option **5512** (FIG. **55B**), one of interfaces **5800**, **5810**, **5820**, or **5830** (FIGS. **58A-58D**) is displayed, in some examples. As can be seen in FIG. **58A**, interface **5800** depicts menstrual flow information at the hourly level of detail for a given day. Interface **5800** includes indicator **5806** whose horizontal position corresponds to an independent variable (e.g. time of day) of the data set, and whose vertical position corresponds to a dependent variable (e.g., menstrual flow) of the data set. Turning to FIG. **58B**, interface **5810** depicts menstrual flow information at the daily level of detail for a given week. Notably, indicator **5818** marks the beginning of a period of menstrual flow as indicated by range **5816**. Similarly, interface **5820** of FIG. **58C** depicts menstrual flow for a month, with indicator **5828** marking the beginning of a period of menstrual flow as indicated by range **5826**. Similarly, interface **5830** of FIG. **58D** depicts menstrual flow for a year. Exemplary range indicators include **5836** and **5838**. Exemplary beginning-of-cycle indicators include **5837** and **5839**. In some embodiments, a user navigates between user interfaces **5800**, **5810**, **5820**, and **5830** (FIGS. **58A-58D**) by pinching or de-pinching to zoom touch input on device **610**.

(337) Turning to FIGS. **59A-59D**, responsive to selection of option **5514** (FIG. **55B**), one of interfaces **5900**, **5910**, **5920**, or **5930** (FIGS. **59A-59D**) is displayed, in some examples. As can be seen in FIG. **59A**, interface **5900** depicts ovulation information at the hourly level of detail for a given day. Interface **5900** includes indicators **5906** whose horizontal positions correspond to independent variables (e.g. times of day) of the data set, and whose vertical positions correspond to dependent variables (e.g., ovulation levels) of the data set. Turning to FIG. **59B**, interface **5910** depicts ovulation information at the daily level of detail for a given week. Notably, indicator **5918** marks the end of a period of ovulation as indicated by range **5916**. Similarly, interface **5920** depicted of FIG. **59C** depicts ovulation information for a month, while interface **5930** (FIG. **59D**) depicts ovulation information for a year. In interface **5920**, the end of range indicator **5926** is marked by indicator **5926** to indicate the end of an ovulation cycle. In interface **5930**, range indicator **5936** includes indicator **5937** indicating positive ovulation and end-of-ovulation indicator **5938** indicating the end of an ovulation cycle. In some embodiments, a user navigates between user interfaces **5900**, **5910**, **5920**, and **5930** (FIGS. **59A-59D**) by pinching or de-pinching to zoom touch input on device **610**.

(338) Turning to FIGS. **60A-60D**, responsive to selection of option **5516** (FIG. **55B**), one of interfaces **6000**, **6010**, **6020**, or **6030** (FIGS. **60A-60D**) is displayed, in some examples. As can be seen in FIG. **60A**, interface **6000** depicts sexual activity information at the hourly level of detail for a given day. Category label **6006** is provided to indicate that the vertical location of indicator **6008** corresponds to one sexual activity event. Turning to FIG. **60B**, interface **6010** depicts sexual activity information at the daily level of detail for a given week, with indicators **6016** and **6018** showing activity levels for different days of the week. Similarly, interface **6020** depicted of FIG. **60C** depicts sexual activity information for a month, while interface **6030** (FIG. **60D**) depicts sexual activity information at the monthly level of detail for a year. For example, indicator **6038** in interface **6030** indicates five sexual events have occurred in December 2014. In some embodiments, a user navigates between user interfaces **6000**, **6010**, **6020**, and **6030** (FIGS. **60A-60D**) by pinching or de-pinching to zoom touch input on device **610**.

(339) Turning to FIGS. **61A-61D**, responsive to selection of option **5518** (FIG. **55B**), one of interfaces **6100**, **6110**, **6120**, or **6130** (FIGS. **61A-61D**) is displayed, in some examples. As can be seen in FIG. **61A**, interface **6100** depicts menstrual spotting information at the hourly level of detail for a given day. Interface **6100** includes indicators **6106** whose horizontal positions correspond to independent variables (e.g. times of day) of the data set, and whose vertical positions correspond to dependent variables (e.g., positive or no spotting) of the data set. Turning to FIG. **61B**, interface **6110** depicts menstrual spotting information at the daily level of detail for a given week, with range indicator **6116** showing that spotting has occurred on multiple days of the week. Similarly, interface **6120** depicted of FIG. **61C** depicts spotting information for a month, while interface **6130** (FIG. **61D**) depicts menstrual spotting information at for a year. In some embodiments, a user navigates between user interfaces **6100**, **6110**, **6120**, and **6130** (FIGS. **61A-61D**) by pinching or de-pinching to zoom touch input on device **610**.

(340) As previously described with respect to FIG. **28**, a category of wellness or non-wellness data can include one or more sub-categories. For example, the category “Reproductive Health” can include sub-categories “Menstrual Flow,” “Cervical Mucus,” “Basal Temperature,” “Sexual Activity,” “Ovulation,” and so forth. The category “Lab Results” can include sub-categories “Blood Glucose” and “Blood Alcohol Content.” It should be appreciated that list **5504** is provided only as an example, and that additional or fewer categories can be included within interface **5500**. Additionally, it should be appreciated that the categories of interface **5500** can include additional or fewer sub-categories.

(341) FIGS. **62A** and **62B** illustrate another example interface **6200** that can be displayed by user device **610** to display a user's wellness or non-wellness data. In this example, the calendar view in Selection Box **6202** is selected, rather than the list view as depicted in FIGS. **55A** and **55B**. When the calendar view is selected, interface **6200** displays calendar **6208** with a selected day **6210**. Interface **6200** can include wellness or non-wellness data associated with the selected day **6210**. For example, interface **6200** can include wellness or non-wellness data for a list **6204** of wellness or non-wellness categories, such as “Reproductive Health” category **6202**. List **6204** also includes sub-categories, along with the value **6212** of applicable sub-categories for the selected day **5710**. List **6204** of sub-categories is associated with the list **5504** of categories depicted in the list view of FIG. **55A**. For example, list **6204** lists sub-categories such as menstrual flow, cervical mucus, and basal temperature as being associated with the category **6206** of “Reproductive Health.”

(342) In some examples, the list of sub-categories can be scrolled to display sub-categories associated with additional categories. For example, as depicted in FIG. **62B**, scrolling list **6204** reveals sub-categories associated with the “Lab Results” category. In some examples, the categories (and associated sub-categories) are displayed in interfaces **6200** and **6210** in the order in which they appear in the list view of interface **5500**; e.g., in the order of list **5504** (FIGS. **55A** and **55B**). Thus, in this example, scrolling list **6204** causes the sub-categories associated with the “Lab Results” category **6216** to appear after the sub-categories associated with the “Reproductive Health” category as this is the order in which these categories appear in list **5504** (FIGS. **55A** and **55B**).

(343) FIG. **63** illustrates an example interface **6300** for entering discrete wellness or non-wellness data, in this example menstruation sample information. Interface **6300** allows a user to enter a category value for the “Menstrual Flow” sub-category of the “Reproductive Health” category. Interface **6300** includes selection box **6302** to allow a user to select a data type corresponding to a category or sub-category. In the example depicted in FIG. **63**, the selected data type, “Menstruation Sample,” corresponds to data that can be entered for the “Menstrual Flow” sub-category. Interface **6300** includes data value picker **6304** to enable the user to pick a value for the menstruation sample. In this example, possible values that may be picked include Light, Medium, and Heavy. Restated, “Menstruation Sample” takes on values from a discrete set of values listed in picker **6304**.

(344) Interface **6300** also includes option **6306** for entering a date associated with the menstruation sample, and option **6308** for indicating whether the date is the start of the menstrual cycle. Information regarding the start of a particular cycle is useful for determining the range of a period of wellness activity. For example, information entered via option **6308** is used to derive the position of marker **5828** representing the beginning of a menstrual flow (FIG. **58C**) in some examples.

(345) FIG. **38A** illustrates an example process **3800** for managing and displaying wellness or non-wellness data according to various examples. Process **3800** can be performed at an electronic device (e.g., device **610**) with a display. In some examples, the display can include a touch-sensitive display. In other examples, the display can be separate from a touch-sensitive surface. Some blocks of process **3800** can be combined and/or the order of some blocks can be changed.

(346) As described below, process **3800** provides an intuitive way to manage sources and destinations of data stored in wellness database **611**. The process allows a user to specify which devices and applications can access data in wellness database **611**, as well as to specify the devices and applications that can serve as sources for data to be stored in wellness database **611**. Additionally, for the sources, the user can specify what types of data those sources can provide and which sources take priority over others. This can be advantageous when one device is more likely to produce more accurate results than another.

(347) At block **3802**, information identifying a plurality of approved sources of wellness data can be received by a user device (e.g., user device **610**) from a user. In some examples, the information identifying the plurality of approved sources can identify one or more types of wellness or non-wellness data that are approved to be received from the plurality of approved sources and stored in a wellness database (e.g., wellness database **611**). For example, the information identifying the plurality of approved sources can be received via an interface similar or identical to interfaces **3500**, **3600**, and **3700**. In these examples, a user can specify which types of data can be provided by each of the plurality of approved sources to be stored in the wellness database.

(348) At block **3804**, information identifying a plurality of approved destinations of wellness or non-wellness data can be received by a user device (e.g., user device **610**) from the user. For example, the information identifying the plurality of approved destinations can be received via an interface similar or identical to interface **3500**. In these examples, a user can specify which destinations are approved to access data from the wellness database.

(349) In some examples, the plurality of approved sources can include an electronic device or a software application. For example, an approved electronic device, such as a watch, a mobile phone, or the like, can provide wellness or non-wellness data to user device **610** to be stored in wellness database **611**. Similarly, an approved software application on or otherwise associated with user device **610** can provide wellness or non-wellness data to user device **611** to be stored in wellness database **611**. In some examples, the approved software application can be a software application associated with an electronic device and is capable of communicating with the electronic device.

(350) Similarly, in some examples, the plurality of approved destinations can include an electronic device or a software application. For example, an approved electronic device, such as a watch, a mobile phone, or the like, can access wellness or non-wellness data stored in wellness database **611**. Similarly, an approved software application on or otherwise associated with user device **610** can access wellness or non-wellness data stored in wellness database **611**. In some examples, the approved software application can be a software application associated with an electronic device and is capable of communicating with the electronic device.

(351) In some examples, the plurality of approved sources can be ranked amongst each other. In some examples, an interface similar or identical to interface **3500** can be used to display and adjust the relative ranking of the approved sources. For example, as shown in interface **3500**, Device **1** can be ranked higher than Device **2** to prioritize data from Device **1** over data from Device **2**, and Device **2** can be ranked higher than App **3** to prioritize data from Device **1** and Device **2** over data from App **3**.

(352) In some examples, process **3800** can further include, at block **3806**, identifying a first wellness data entry and a second wellness data entry that are duplicates of one another. In some examples, this can include identifying a first wellness data entry in the wellness database that was received from a first approved source of the plurality of approved sources, the first wellness data entry comprising a first wellness data type and a first timestamp, and identifying a second wellness data entry in the wellness database that was received from a second approved source of the plurality of approved sources, the second wellness data entry comprising a second wellness data type and a second timestamp, wherein the first wellness data type and the second wellness data type are the same, and wherein the first timestamp is within a threshold length of time from the second timestamp. For example, a first data entry can have a type of “step data” and an associated timestamp of 2:30 p.m. on 3/1/2014. The second data entry can have a type of “step data” and an associated timestamp of 2:31 p.m. on 3/1/2014. If the threshold length of time used at block **3806** is 5 minutes, it can be determined that the first data entry and the second data entry are of the same data type and include timestamps that are within a threshold length of time from each other. This can indicate that the first data entry and the second data entry are likely duplicate entries representing the same actions performed by the user.

(353) At block **3808**, one of the first data entry and the second data entry can be prioritized or otherwise identified as being preferred over the other based on a ranking of the plurality of sources. For example, as discussed above, the plurality of approved sources can be ranked amongst each other (e.g., as shown in interface **3500**). In some examples, if the first approved source providing the first data entry is identified by the user as being preferred over the second approved source, block **3808** can include using the first wellness data entry instead of using the second wellness data entry. For example, this can include deleting the second data entry from wellness database **611** or otherwise ignoring the second data entry for purposes of being displayed or presented to the user. In other examples, if the first approved source has been identified by the user as being preferred over the second approved source, then block **3806** can include prioritizing the first wellness data entry over the second wellness data entry. A data entry that is prioritized over another can be used in place of the other (e.g., displayed, used in calculations, or the like in favor of the other data entry).

(354) In other examples, if the second approved source has been identified by the user as being preferred over the first approved source, then block **3806** can include prioritizing the second wellness data entry over the first wellness data entry. A data entry that is prioritized over another can be used in place of the other (e.g., displayed, used in calculations, or the like in favor of the other data entry).

(355) In some examples, as shown in FIG. **38B**, process **3800** can further include, at block **3810**, displaying, by the electronic device on the display, a plurality of categories of wellness data stored in the wellness database. For example, an interface similar or identical to interface **2800** can be displayed. The interface can include any amount or any type of categories of wellness or non-wellness data.

(356) At block **3812**, a selection of a category of wellness data from the displayed plurality of categories of wellness data can be detected at the electronic device. For example, a selection of one of the categories displayed in an interface similar or identical to interface **2800** made via a touch event by a finger or other device on a touch sensitive display, a click of a mouse or other device, a touch event on a touch pad, or the like, can be detected. In some examples, each of the displayed plurality of categories can include an indicator (e.g., indicator **2804**) that can be color-coded based on the type of wellness or non-wellness data of the category. For example, the indicator associated with “Fitness” can have a different color than the indicator associated with “Vital Signs.”

(357) At block **3814**, one or more sub-categories of the category of wellness data can be displayed in response to detecting the selection of the category of wellness data. For example, an interface similar or identical to interface **2900** containing a list of sub-categories falling within the category selected at block **3812** can be displayed. In some examples, the displayed interface can include indicators that can be color-coded based on the type of wellness or non-wellness data that it represents.

(358) At block **3816** a selection of a sub-category from the displayed one or more sub-categories can be detected. For example, a selection of one of the sub-categories displayed in an interface similar or identical to interface **2900** made via a touch event by a finger or other device on a touch sensitive display, a click of a mouse or other device, a touch event on a touch pad, or the like, can be detected.

(359) At block **3818**, a detailed view of the selected sub-category can be displayed in response to detecting the selection of the sub-category at block **3816**. For example, an interface similar or identical to interface **3200** can be displayed. The detailed view of the sub-category can include a graphical representation of the sub-category of data (e.g., graph **3102**) and a numerical daily value (e.g., daily value **3104**). The detailed view can further include options to show all data (e.g., option **3106**), add a data point (e.g., option **3108**), share data (e.g., option **3110**), and show on dashboard (e.g., option **3112**). The detailed view can further include a graphic representation of the sub-category (e.g., graphic **3114**) and a text description of the sub-category (e.g., description **3122**).

(360) In some examples, process **3800** can include displaying an interface similar or identical to interface **3400** in response to a selection of the add a data point option (e.g., option **3108**). The interface can include one or more input fields (e.g., fields **3402**, **3404**, and **3406**) for entering information associated with the wellness data entry. In some examples, process **3800** can further include receiving a wellness data entry to be stored in the wellness database that was input into the input field (e.g., input into fields **3402**, **3404**, and **3406**).

(361) In some examples, process **3800** can further include displaying an interface similar or identical to interface **3300** in response to a selection of the show all data option (e.g., option **3106**). The interface can include a plurality of wellness data entries corresponding to the sub-category stored in the wellness database (e.g., entries in list **3302**). In some examples, each of the plurality of wellness data entries can include a numerical value of the data entry, a timestamp, and an identification of a source of the data entry (e.g., indicator **3304**).

(362) In some examples, process **3800** can further include displaying a data sharing interface similar or identical to interface **3500** in response to a selection of the share data option (e.g., option **3110**). The interface can include the plurality of approved sources (e.g., source list **3506**) and the plurality of approved destinations (e.g., list **3504**). In some examples, a request to reorder the displayed plurality of approved sources can be detected by the electronic device. For example, a selection of edit button **3508** can be received and movement of one or more of the sources in source list **3506** can be detected. In response to detecting the request to reorder the displayed plurality of approved sources, the displayed plurality of approved sources can be reordered in accordance with the detected request to reorder the displayed plurality of approved sources.

(363) In some examples, the data sharing interface (e.g., interface **3500**) can further include options to add an approved destination to the plurality of approved destinations and to remove an approved destination from the plurality of approved destinations (e.g., options **3512**, **3514**, **3516**, and **3518**).

(364) In some examples, process **3800** can further include receiving, at the electronic device, a search query. In response, one or more sub-categories of the plurality of categories that match the search query can be displayed. The displayed one or more sub-categories that match the search query can be color-coded based on their respective categories. For example, a search query can be received from a search box (e.g., search box **2808**) displayed within an interface similar or identical to interface **2800** or **2900**. A search results interface similar or identical to interface **3000** can be displayed in response to the search query. The search results interface can include the one or more sub-categories that match the search query.

(365) In some examples, process **3800** can further include displaying, on the display, a source interface comprising a list of known sources. For example, an interface similar or identical to interface **3600** can be displayed having a list of known sources (e.g., list **3606**). The source interface can further include a numerical indicator associated a known source of the known sources that represents a number of new types of wellness data that can be provided by the known source. For example, the number “2” is shown for Device **1**, indicating the two new types of data (e.g., Calories burned and flights of stairs climbed) are available.

(366) In some examples, process **3800** can further include detecting a selection of a known source from the list of displayed sources. In response to detecting the selection of the known source, a list of types of wellness data that the known source can provide can be displayed. For example, a source from source list **3606** of interface **3600** can be received by a user selecting an option **3610** associated with the source. In response, an interface similar or identical to interface **3700** can be displayed. The displayed interface can include a list (e.g., list **3706**) of known types of data that the source can provide. In some examples, the list of types of wellness data that the known source can provide can include a selectable option (e.g., options **3704**, **3708**, **3710**, **3712**, and **3714**) for each of the types of wellness data that the known source can provide to approve or reject the associated type of wellness data.

(367) In some examples, process **3800** can further include detecting a selection of the selectable option for a type of wellness data that the known source can provide at the electronic device. In response to detecting the selection of the selectable option, process **3800** can further include approving or rejecting the type of wellness data that the known source can provide in accordance with the detected selection of the selectable option. For example, user device **610** can accept or reject the types of wellness data shown in interface **3700** based on the positions of the switches of options **3704**, **3708**, **3710**, **3712**, and **3714**.

(368) It should be understood that the particular order in which the operations in FIGS. **38A** and **38B** have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other processes described herein (e.g., processes **800**, **1500**, **1700**, **2000**, **2700**, or **4400**) are also applicable in an analogous manner to process **3800** described above with respect to FIGS. **38A** and **38B**. For brevity, these details are not repeated here.

(369) Medical Identification Information

(370) FIG. **39** illustrates one example lock screen interface **3900** that can be displayed by user device **610** while the user device is in a locked state. In some examples, the locked state can represent a state in which user device **610** restricts one or more functions from being performed. For example, user device **610** can prevent a user from running applications, changing settings, or the like, while in the locked state. In other examples, the locked state can represent a state in which user device **610** additionally or alternatively prevents access at least a subset of data stored on the device. For example, user device **610** can prevent a user from viewing photos or videos, accessing documents, or the like, while in the locked state. In other examples, the locked state can represent a state in which user device **610** additionally or alternatively restricts communications from the electronic device. For example, user device **610** can prevent a user from sending SMS messages or emails, or making calls to non-emergency phone numbers.

(371) As shown in FIG. **39**, lock screen interface **3900** can include the current date and time. Lock screen interface **3900** can further be responsive to user input to allow a user to unlock the device. For example, a swiping gesture can cause user device **610** to display a numerical input pad to allow the user to enter a passcode to unlock the device. Lock screen interface **3900** can further include emergency option **3902** for accessing emergency features of user device **610**. For example, FIG. **40** illustrates an example emergency dialing interface **4000** that can be displayed in response to a selection of emergency option **3902**. As shown, emergency dialing interface **4000** can include numerical input pad **4004** for allowing a temporary user to enter an emergency phone number to dial while the device is in the locked state. In some examples, user device **610** can call a number entered using input pad **4004** if the entered number is predefined phone number (e.g., 9-1-1). In some examples, the temporary user can be a first responder or other person that encounters the primary user of the device when the primary user of the device is unable to operate user device **610** (e.g., because the primary user is unconscious or injured). Thus, emergency dialing interface **4000** allows the temporary user to place calls to predetermined emergency phone numbers without requiring the temporary user to unlock user device **610**.

(372) Interface **4000** can further include Medical ID or emergency information option **4002** for viewing medical information associated with a user by the temporary user. In this example, the user can be a primary user or owner of user device **610** that has customized the device by installing applications and/or entering personal information to user device **610**. Thus, Medical ID or emergency information option **4002** can be selected by the temporary user to view emergency information associated with the primary user without requiring the temporary user to unlock user device **610**.

(373) For example, FIG. **41** illustrates an example emergency information interface **4100** that can be displayed in response to a selection of Medical ID or emergency information option **4002** in interface **4000**. As shown, interface **4100** can include user information **4102** including the user's name and birthdate. Interface **4100** can further include a free-form field **4104** that can be used to store and display a description of any medical conditions that the user may have. Interface **4100** can further include a free-form field **4106** that can be used to store and display any other relevant medical

notes about the user. Interface **4100** can further include free-form field **4108** that can be used to store and display a description of any allergies or reactions that the user may have to drugs or any other substance. Interface **4100** can further include free-form field **4110** that can be used to store and display a description of any medications that the user may be taking or that the user may require.

(374) Interface **4100** can further include emergency contacts **4112**. Emergency contacts **4112** can include a list of one or more people that the user has designated as being his/her emergency contact. Emergency contacts **4112** can include a name of each emergency contact and a relationship between the user and the emergency contact. For example, one entry for an emergency contact can include the name “Jane Smith” having a relationship with the user of “mother.” In some examples, emergency contacts **4112** can further include contact information for the emergency contact, such as a phone number, email address, or the like. In other examples, emergency contact **4112** can exclude contact information for the emergency contact, such as a phone number, email address, or the like. This can be done to protect the privacy of the emergency contact. In either example, user device **610** can allow a temporary user to select one of the displayed emergency contacts to initiate communication with that contact (even if the phone number of the emergency contact is not displayed) while user device **610** remains in the locked state. For example, in response to a selection of one of the emergency contacts, user device **610** can initiate a phone call to the contact, send an SMS message to the contact, send an email to the emergency contact, or the like, while the device remains in the locked state. In some examples, when user device **610** initiates a call to an emergency contact in response to a selection of that emergency contact, user device **610** can flag the call as being an emergency call. In some examples, emergency calls can be accepted by a receiving device in any state of operation. For example, a call flagged as being an emergency call can cause the receiving device to ring while in a do-not-disturb mode, a silent mode, or the like. Additionally, an indicator can be displayed on the receiving device notifying the recipient that the call is an emergency call.

(375) In some examples, a primary user can create their medical identification from the contact list of user device **610**. For example, FIG. **42** illustrates an example interface **4200** that can be displayed to display the user's contact list. As shown, interface **4200** can include a “Create Medical ID” button **4202** for creating a medical identification. FIG. **43** illustrates an example interface **4300** that can be displayed in response to a selection of button **4202**. As shown, interface **4300** includes a text description **4302** that can provide information about the medical identification, such as the purpose of the medical identification, the privacy settings for information contained in the medical identification, and the like.

(376) FIG. **44** illustrates an example interface **4400** that can be displayed in response to a user accepting or acknowledging the contents of description **4302** in interface **4300**. As shown, interface **4400** can include user information **4402** that can correspond to user information **4102** in interface **4100**. In some examples, this information can be auto-populated by user device **610** based on information previously known about the user. In other examples, the user can enter this information manually. Interface **4400** can further include free-form text fields **4404**, **4406**, **4408**, and **4410** that can correspond to fields **4104**, **4106**, **4108**, and **4110** of interface **4100**. Thus, information entered into fields **4404**, **4406**, **4408**, and **4410** can be displayed in fields **4104**, **4106**, **4108**, and **4110** of interface **4100**. Interface **4400** can further include contacts **4412** to allow a user to enter one or more emergency contacts. In some examples, the one or more emergency contacts can be selected from the user's contact list on user device **610**. In other examples, the one or more emergency contacts can be entered manually by the user. In yet other examples, the emergency contact can be selected from the user's contact list on user device **610** and additional information (e.g., relationship information) can be manually added by the user. Interface **4400** can further include “Show Medical ID” option **4414** having selectable option **4416**. The position of the switch of option **4416** can be used to turn on or off the showing of the user's medical information while the device is in the locked state. For example, when moved to the right, as shown in FIG. **44**, the switch of option **4416** can cause user device **610** to display option **4002** in the emergency dialing interface **4000** and to display interface **4100** in response to a selection of option **4002**. However, when moved to the left, the switch of option **4416** can prevent user device **610** from displaying option **4002** in the emergency dialing interface **4000** and can prevent user device **610** from displaying interface **4100** in response to a selection of option **4002**.

(377) FIG. **45** illustrates an exemplary process **4500** for displaying medical information on a locked device. Process **4500** can be performed at an electronic device (e.g., device **610**) with a display. In some examples, the display can include a touch-sensitive display. In other examples, the display can be separate from a touch-sensitive surface. Some blocks of process **4500** can be combined and/or the order of some blocks can be changed.

(378) As described below, process **4500** provides a way for a temporary user to view medical information associated with a primary user or owner of an electronic device while the device remains in a locked state. Process **4500** also allows a temporary user to initiate communication with the primary user's emergency contacts while the device remains in the locked state. This advantageously allows a temporary user that finds the primary user (e.g., in a state in which the primary user is unable to operate the electronic device or communicate) to assist the primary user in getting the appropriate medical care.

(379) At block **4502**, at an electronic device (e.g., user device **610**) while the electronic device is in a locked state, a request to display emergency information about a user of the device can be detected. For example, the request to display the emergency information can be received while an emergency dialing interface similar or identical to interface **4000** is being displayed, and the request can include a selection of an emergency information option similar or identical to option **4002**. The emergency information about the user of the device can include the user's name, birthday, medical conditions, allergies and reactions, medications, and one or more emergency contacts of the user. As discussed above, the user can be a primary user or owner of user device **610** that has customized the device by installing applications and/or entering personal information to user device **610**. The request to display the medical information can be made by a temporary user, such as a first responder or other person that encounters the primary user of the device when the primary user of the device is unable to operate user device **610** (e.g., because the primary user is unconscious or injured).

(380) At block **4504**, in response to detecting the request, an emergency information interface comprising emergency information about the user of the device can be displayed without unlocking the device. For example, an interface similar or identical to interface **4100** can be displayed.

(381) In some examples, the emergency information about the user can include information associated with an emergency contact. The information associated with the emergency contact can include a name of the emergency contact and a relationship between the user and the emergency contact. For example, information about an emergency contact can be displayed in a manner similar or identical to emergency contact **4112** in interface **4100**. One example emergency contact can include the contact's name “Jane Smith,” and the relationship “mother” between the user and the contact.

(382) At block **4506**, user device **610** can detect a request to communicate with an emergency contact while the electronic device is in the locked state. For example, a selection of a contact **4112** from interface **4100** can be detected.

(383) At block **4508**, user device **610** can initiate communication with the emergency contact in response to detecting the request to communicate. In some examples, initiating communication with the emergency contact includes sending an SMS message or email to the emergency contact. In other examples, initiating communication with the emergency contact can include calling a phone number associated with the emergency contact. In some examples, calling the phone number associated with the emergency contact can include flagging the call to the phone number as an emergency call. In some examples, the phone number associated with the emergency contact can be included in the information associated with the emergency contact displayed within the emergency information interface (e.g., interface **4100**). In other examples, the phone number associated with the emergency contact may not be included in the information associated with the emergency contact displayed within the emergency information interface (e.g., interface **4100**). However, a call or other communication can still be made to this emergency contact. This can be done to protect the privacy of the emergency contact.

(384) In some examples, process **4500** can include displaying an emergency dialing interface prior to displaying the emergency information interface. The emergency dialing interface can include a numerical input pad and an emergency information option. For example, an emergency dialing interface similar or identical to interface **4000** can be displayed prior to displaying emergency information interface **4100**. The emergency dialing interface **4000** can include a numerical input pad similar or identical to input pad **4004** and an emergency information option similar or

identical to option **4002**. In some examples, the emergency information interface (e.g., interface **4100**) can be displayed in response to a selection of the emergency information option (e.g., option **4002**).

(385) In some examples, process **4500** can further include detecting a predefined phone number entered using the numerical input pad while the electronic device is in the locked state. In response to detecting the predefined phone number, process **4500** can further include calling the predefined phone number. For example, user device **610** can detect a predefined number (e.g., 9-1-1) entered in the numerical input pad (e.g., input pad **4004**). In response to detecting the predefined phone number, user device **610** can call the predefined number while still in the locked state. In some examples, calling the predefined phone number can include flagging the call to the predefined phone number as an emergency call.

(386) In some examples, calls flagged as being emergency calls can be accepted by a receiving electronic device in any state of operation. For example, a call flagged as being an emergency call can cause the receiving device to ring while in a do-not-disturb mode, a silent mode, or the like. Additionally, an indicator can be displayed on the receiving device notifying the recipient that the call is an emergency call.

(387) In some examples, process **4500** can further include displaying a lock screen interface comprising an emergency option prior to displaying the emergency dialing interface. For example, an interface similar or identical to interface **3900** can be displayed having an emergency option similar or identical to option **3902**. The lock screen interface can further include one or more controls for unlocking the device. For example, a numerical input pad can be displayed to allow a user to enter a passcode, or user device **610** can be configured to detect predefined gestures to unlock the device. In these examples process **4500** can further include detecting a selection of the emergency option and displaying the emergency dialing interface in response to detecting the selection of the emergency option. For example, user device **610** can detect a selection of option **3902** and display interface **4000** in response to detecting the selection of option **3902**.

(388) It should be understood that the particular order in which the operations in FIG. **45** have been described is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein. Additionally, it should be noted that details of other processes described herein with respect to other processes described herein (e.g., processes **900**, **1600**, **1800**, **2100**, **2700**, or **3800**) are also applicable in an analogous manner to process **4500** described above with respect to FIG. **45**. For brevity, these details are not repeated here.

(389) In some examples, the interfaces shown in FIGS. **22-23**, **28-36**, **41-43**, and **56-59** can include menu bar **2250** for navigating between the various interfaces. For example, in response to a selection of “Dashboard” in menu **2250**, interface **2100** or **2200** can be displayed. In response to a selection of “My Health” in menu **2250**, interface **2700** can be displayed. In response to a selection of “Medical ID” in menu **2250**, interface **4400** can be displayed. In response to a selection of “Settings” in menu **2250**, interface **3600** can be displayed.

(390) One or more of the functions relating to aggregating and sharing wellness data can be performed by a system similar or identical to system **4600** shown in FIG. **46**. System **4600** can include instructions stored in a non-transitory computer readable storage medium, such as memory **4604** or storage device **4602**, and executed by processor **4606**. The instructions can also be stored and/or transported within any non-transitory computer readable storage medium for use by or in connection with an instruction execution system, apparatus, or device, such as a computer-based system, processor-containing system, or other system that can fetch the instructions from the instruction execution system, apparatus, or device and execute the instructions. In the context of this document, a “non-transitory computer readable storage medium” can be any medium that can contain or store the program for use by or in connection with the instruction execution system, apparatus, or device. The non-transitory computer readable storage medium can include, but is not limited to, an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor system, apparatus or device, a portable computer diskette (magnetic), a random access memory (RAM), a read-only memory (ROM), an erasable programmable read-only memory (EPROM) (magnetic), a portable optical disc such as a CD, CD-R, CD-RW, DVD, DVD-R, or DVD-RW, or flash memory such as compact flash cards, secured digital cards, USB memory devices, memory sticks, and the like.

(391) The instructions can also be propagated within any transport medium for use by or in connection with an instruction execution system, apparatus, or device, such as a computer-based system, processor-containing system, or other system that can fetch the instructions from the instruction execution system, apparatus, or device and execute the instructions. In the context of this document, a “transport medium” can be any medium that can communicate, propagate or transport the program for use by or in connection with the instruction execution system, apparatus, or device. The transport medium can include, but is not limited to, an electronic, magnetic, optical, electromagnetic or infrared wired or wireless propagation medium.

(392) In some examples, system **4600** can be included within user device **610** or user server **614**. Processor **4606** can be configured to perform processes **800**, **900**, **1500**, **1800**, **2100**, **2700**, **3800**, or **4500**. It is to be understood that the system is not limited to the components and configuration of FIG. **46**, but can include other or additional components in multiple configurations according to various examples.

(393) In accordance with some examples, FIG. **47** shows a functional block diagram of an electronic device **4700** configured in accordance with the principles of the various described examples. The functional blocks of the device can be implemented by hardware, software, or a combination of hardware and software to carry out the principles of the various described examples. It is understood by persons of skill in the art that the functional blocks described in FIG. **47** can be combined or separated into sub-blocks to implement the principles of the various described examples. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

(394) As shown in FIG. **47**, electronic device **4700** can include a display unit **4704** for displaying a user interface and, optionally, sensor units **4702** configured to receive touch input. Electronic device **4700** can further include a processing unit **4708** coupled to the optional sensor units **4702** and display unit **4704**. In some examples, processing unit **4708** can include one or more of a display enabling unit **4710**, a receiving unit **4712**, and a generating unit **4714**.

(395) Processing unit **4708** may be configured to: enable display (e.g., with display enabling unit **4710**) of an aggregated view of a plurality of types of wellness data, wherein the aggregated view comprises a plurality of partitions, each partition of the plurality of partitions associated with a type of the plurality of types of wellness data; receive (e.g., with receiving unit **4712**) a selection of a partition of the plurality of partitions; and enable display (e.g., with display enabling unit **4710**) of an expanded view of the selected partition of the plurality of partitions.

(396) In some embodiments, in the aggregated view, each partition of the plurality of partitions comprises an identifier of an associated type of wellness data and a first portion of the associated type of wellness data displayed therewith, and wherein the expanded view comprises a larger view of the selected partition of the plurality of partitions and a second portion of the associated type of wellness data displayed therewith.

(397) In some embodiments, the first portion of the wellness data comprises a most recent value of the associated type of wellness data, and wherein the second portion of the associated type of wellness data comprises a representation of the associated type of wellness data over time.

(398) In some embodiments, the processing unit is configured to: enable the display (e.g., with display enabling unit **4710**) of the expanded view of the selected partition by at least enabling the display of a collapsed set of partitions representing partitions of the plurality of partitions that were not selected.

(399) In some embodiments, the plurality of partitions are ordered within the display based on a frequency of use of an associated type of wellness data, a time of most recently added value of the associated type of wellness data, or a time of day.

(400) In some embodiments, the expanded view of the selected partition comprises a selectable element to share the wellness data associated with the partition through email or text message.

(401) In some embodiments, the plurality of types of wellness data comprises weight data, blood sugar data, blood pressure data, activity data, or heart rate data.

(402) In some embodiments, the electronic device further includes a plurality of sensor units coupled to the processing unit **4708** and the display unit **4704**. The processing unit **4708** is further configured to generate (e.g., with generating unit **4714**) at least one of the plurality of types of wellness

data from sensor data obtained from the plurality of sensors.

(403) In some embodiments, the expanded view comprises a graph of the associated type of wellness data, and wherein the graph comprises segments generated from wellness data obtained from different sensors.

(404) In some embodiments, a partition of the plurality of partitions is a user-generated partition.

(405) In some embodiments, the plurality of partitions have the appearance of a plurality of cards displayed in a stack.

(406) The operations described above with reference to FIG. 16 are, optionally, implemented by components depicted in FIGS. 1A-1B or FIG. 47. For example, displaying operations 1602 and 1606 and receiving operation 1604 may be implemented by event sorter 170, event recognizer 180, and event handler 190. Event monitor 171 in event sorter 170 detects a contact on touch-sensitive display 112, and event dispatcher module 174 delivers the event information to application 136. A respective event recognizer 180 of application 136 compares the event information to respective event definitions 186, and determines whether a first contact at a first location on the touch-sensitive surface corresponds to a predefined event or sub-event, such as activation of an affordance on a user interface. When a respective predefined event or sub-event is detected, event recognizer 180 activates an event handler 190 associated with the detection of the event or sub-event. Event handler 190 may utilize or call data updater 176 or object updater 177 to update the application internal state 192. In some embodiments, event handler 190 accesses a respective GUI updater 178 to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. 1A-1B.

(407) In accordance with some examples, FIG. 48 shows a functional block diagram of an electronic device 4800 configured in accordance with the principles of the various described examples. The functional blocks of the device can be implemented by hardware, software, or a combination of hardware and software to carry out the principles of the various described examples. It is understood by persons of skill in the art that the functional blocks described in FIG. 48 can be combined or separated into sub-blocks to implement the principles of the various described examples. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

(408) As shown in FIG. 48, electronic device 4800 can include a display unit 4802 for displaying a user interface and, optionally, a gyroscope and/or accelerometer unit 4810. Electronic device 4800 can further include a processing unit 4804 coupled to the display unit 4802 and optionally, to the gyroscope and/or accelerometer unit 4810. In some examples, processing unit 4804 can include one or more of a display enabling unit 4806, a selecting unit 4808, a detecting unit 4812, and an identifying unit 4814.

(409) Processing unit 4804 may be configured to: enable display (e.g., with display enabling unit 4806) of a plurality of partitions, wherein each partition of the plurality of partitions is associated with a type of wellness data of a plurality of types of wellness data; in response to detecting a change in an orientation of the device, select (e.g., with selecting unit 4808) a subset of the plurality of partitions; and enable display (e.g., with display enabling unit 4806) of the selected subset of the plurality of partitions.

(410) In some embodiments, the electronic device further includes a gyroscope and/or accelerometer unit 4810 coupled to the processing unit 4804 which is further configured to: detect (e.g., with detecting unit 4812) the change in orientation of the device based on data from the gyroscope and/or accelerometer unit.

(411) In some embodiments, the processing unit is further configured to: detect (e.g., with detecting unit 4812) the change in the orientation of the device by at least detecting a threshold amount of change in the orientation of the electronic device.

(412) In some embodiments, each of the displayed subset of the plurality of partitions comprises a graph representation of at least a portion of the associated type of wellness data displayed therewith.

(413) In some embodiments, the processing unit is further configured to: select (e.g., with selecting unit 4808) a subset of the plurality of partitions by at least: identifying (e.g., with identifying unit 4814) correlations between the plurality of types of wellness data; and selecting (e.g., with selecting unit 4808) partitions associated with correlated types of wellness data as the subset of the plurality of partitions.

(414) The operations described above with reference to FIG. 18 are, optionally, implemented by components depicted in FIGS. 1A-1B or FIG. 48. For example, displaying operations 1802 and 1808 and detecting operation 1804 may be implemented by event sorter 170, event recognizer 180, and event handler 190. Event monitor 171 in event sorter 170 detects a contact on touch-sensitive display 112, and event dispatcher module 174 delivers the event information to application 136. A respective event recognizer 180 of application 136 compares the event information to respective event definitions 186, and determines whether a first contact at a first location on the touch-sensitive surface corresponds to a predefined event or sub-event, such as activation of an affordance on a user interface. When a respective predefined event or sub-event is detected, event recognizer 180 activates an event handler 190 associated with the detection of the event or sub-event. Event handler 190 may utilize or call data updater 176 or object updater 177 to update the application internal state 192. In some embodiments, event handler 190 accesses a respective GUI updater 178 to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. 1A-1B.

(415) In accordance with some examples, FIG. 49 shows a functional block diagram of an electronic device 4900 configured in accordance with the principles of the various described examples. The functional blocks of the device can be implemented by hardware, software, or a combination of hardware and software to carry out the principles of the various described examples. It is understood by persons of skill in the art that the functional blocks described in FIG. 49 can be combined or separated into sub-blocks to implement the principles of the various described examples. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

(416) As shown in FIG. 49, electronic device 4900 can include a display unit 4902 for displaying a user interface. Electronic device 4900 can further include a processing unit 4904 coupled to the display unit 4902. In some examples, processing unit 4904 can include a display causing unit 4906 and a receiving unit 4908.

(417) Processing unit 4904 may be configured to: cause display (e.g., with display causing unit 4906) of a first plurality of partitions associated with a first user, wherein each partition of the first plurality of partitions is associated with a type of wellness data of the first user; and in response to receiving a request (e.g., with receiving unit 4908) to view a second plurality of partitions associated with a second user, cause a display (e.g., with display causing unit 4906) of a second plurality of partitions associated with a second user, wherein each partition of the second plurality of partitions is associated with a type of wellness data of the second user.

(418) In some embodiments, the request to view the second plurality of partitions comprises a request to scroll the displayed first plurality of partitions in a lateral direction.

(419) In some embodiments, the request to view the second plurality of partitions comprises a selection of the second user from a list of users.

(420) In some embodiments, the first user has been authorized by the second user to view the second plurality of partitions.

(421) The operations described above with reference to FIG. 21 are, optionally, implemented by components depicted in FIGS. 1A-1B or FIG. 49. For example, displaying operations 2102 and 2106 and receiving operation 2104 may be implemented by event sorter 170, event recognizer 180, and event handler 190. Event monitor 171 in event sorter 170 detects a contact on touch-sensitive display 112, and event dispatcher module 174 delivers the event information to application 136. A respective event recognizer 180 of application 136 compares the event information to respective event definitions 186, and determines whether a first contact at a first location on the touch-sensitive surface corresponds to a predefined event or sub-event, such as activation of an affordance on a user interface. When a respective predefined event or sub-event is detected, event recognizer 180 activates an event handler 190 associated with the detection of the event or sub-event. Event handler 190 may utilize or call data updater 176 or object updater 177 to update the application internal state 192. In some embodiments, event handler 190 accesses a respective GUI updater 178 to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. 1A-1B.

(422) In accordance with some examples, FIG. 50 shows a functional block diagram of an electronic device **5000** configured in accordance with the principles of the various described examples. The functional blocks of the device can be implemented by hardware, software, or a combination of hardware and software to carry out the principles of the various described examples. It is understood by persons of skill in the art that the functional blocks described in FIG. 50 can be combined or separated into sub-blocks to implement the principles of the various described examples. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

(423) As shown in FIG. 50, electronic device **5000** can include a display unit **5002** for displaying a user interface. Electronic device **5000** can further include a processing unit **5004** coupled to the display unit **5002**. In some examples, processing unit **5004** can include a receiving unit **5006** and a transmitting unit **5008**.

(424) Processing unit **5004** may be configured to: receive (e.g., with receiving unit **5006**) an identification of a user authorized to access a set of wellness data; in response to detecting an update to the set of wellness data, transmit (e.g., with transmitting unit **5008**) a notification to the user authorized to access the set of wellness data notifying the user authorized to access the set of wellness data that the update to the set of wellness data has been detected; and transmit (e.g., with transmitting unit **5108**) at least a portion of the set of wellness data to the user authorized to access the set of wellness data.

(425) In some embodiments, the identification of the user authorized to access the set of wellness data comprises a name, a username, or contact information.

(426) In some embodiments, the at least a portion of the set of wellness data is transmitted in response to receiving a request from the user authorized to access the set of wellness data.

(427) The operations described above with reference to FIG. 8 are, optionally, implemented by components depicted in FIGS. 1A-1B or FIG. 50. For example, receiving operation **802** and transmitting operations **806** and **808** may be implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136**. A respective event recognizer **180** of application **136** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface corresponds to a predefined event or sub-event, such as activation of an affordance on a user interface. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** may utilize or call data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. 1A-1B.

(428) In accordance with some examples, FIG. 51 shows a functional block diagram of an electronic device **5100** configured in accordance with the principles of the various described examples. The functional blocks of the device can be implemented by hardware, software, or a combination of hardware and software to carry out the principles of the various described examples. It is understood by persons of skill in the art that the functional blocks described in FIG. 51 can be combined or separated into sub-blocks to implement the principles of the various described examples. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

(429) As shown in FIG. 51, electronic device **5100** can include a display unit **5102** for displaying a user interface. Electronic device **5100** can further include a processing unit **5104** coupled to the display unit **5102**. In some examples, processing unit **5104** can include one or more of a receiving unit **5106** and a transmitting unit **5108**.

(430) Processing unit **5104** may be configured to: receive (e.g., with receiving unit **5106**), from a first user, a request to access wellness data associated with a second user; transmit (e.g., with transmitting unit **5108**), to the second user, a request to authorize the first user to access the wellness data associated with the second user; and in response to receiving an authorization from the second user, transmit (e.g., with transmitting unit **5108**) the wellness data associated with the second user to the first user.

(431) In some embodiments, the first user is a health care provider and the second user is a patient, and wherein the request to access the wellness data associated with the second user is received prior to an appointment between the first user and the second user.

(432) In some embodiments, the request to authorize the first user to access the wellness data associated with the second user is displayed on a mobile device of the second user.

(433) The operations described above with reference to FIG. 9 are, optionally, implemented by components depicted in FIGS. 1A-1B or FIG. 51. For example, receiving operation **902** and transmitting operations **904** and **908** may be implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136**. A respective event recognizer **180** of application **136** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface corresponds to a predefined event or sub-event, such as activation of an affordance on a user interface. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** may utilize or call data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. 1A-1B.

(434) In accordance with some examples, FIG. 52 shows a functional block diagram of an electronic device **5200** configured in accordance with the principles of the various described examples. The functional blocks of the device can be implemented by hardware, software, or a combination of hardware and software to carry out the principles of the various described examples. It is understood by persons of skill in the art that the functional blocks described in FIG. 52 can be combined or separated into sub-blocks to implement the principles of the various described examples. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

(435) As shown in FIG. 52, electronic device **5200** can include a display unit **5202** for displaying a user interface. Electronic device **5200** can further include a processing unit **5204** coupled to the display unit **5202**. In some examples, processing unit **5204** can include one or more of a display enabling unit **5206**, a detecting unit **5208**, a scroll enabling unit **5210**, and a reordering unit **5212**.

(436) Processing unit **5204** may be configured to: enable display (e.g., with displaying enabling unit **5206**) of, on the display, a graph comprising a first data-set representation of a first data set in which a first dependent variable varies as an independent variable changes and a second data-set representation of a second data set in which a second dependent variable varies as the independent variable changes, wherein the first data-set representation is associated with a first range of vertical positions within the graph and the second data-set representation is associated with a second range of vertical positions within the graph; detect (e.g., with detecting unit **2108**), at a respective location on the display, a user input; in response to detecting the user input: in accordance with a determination that the respective location is within the first range of vertical positions associated with the first data-set representation, enable display (e.g., with display enabling unit **5206**) of, on the display, an indication that the first data-set representation has been selected; and in accordance with a determination that the respective location is within the second range of vertical positions associated with the second data-set representation, enable display (e.g., with display enabling unit **5206**) of, on the display, an indication that the second data-set representation has been selected.

(437) In some embodiments, the processing unit **5204** is further configured to: enable display (e.g., with display enabling unit **5206**) of the first data-set representation in the graph overlapping the second data-set representation.

(438) In some embodiments, the first data set comprises a first set of wellness data, and wherein the second data set comprises a second set of wellness data.

(439) In some embodiments, the first range of vertical positions is uniquely associated with the first data-set representation, and wherein the second range of vertical positions is uniquely associated with the second data-set representation.

(440) In some embodiments, the first data-set representation and the second data-set representation are colored-coded based on a type of data that they represent.

(441) In some embodiments, processing unit **5204** is further configured to: enable display (e.g., with display enabling unit **5206**) of the indication that the first data-set representation has been selected by at least enabling display, on the display, of a marker overlaid on the first data-set representation at a horizontal position corresponding to a horizontal position of the respective location on the display.

(442) In some embodiments, processing unit **5204** is further configured to enable display (e.g., with display enabling unit **5206**) of the indication that the second data-set representation has been selected by at least enabling display, on the display, of a marker overlaid on the second data-set representation at a horizontal position corresponding to a horizontal position of the respective location on the display.

(443) In some embodiments, processing unit **5204** is configured to enable display (e.g., with display enabling unit **5206**) of the indication that the first data-set representation has been selected by at least enabling display, on the display, of a numerical value of a first data entry of the first data set associated with a value of the independent variable corresponding to a horizontal position of the respective location on the display.

(444) In some embodiments, processing unit **5204** is further configured to: enable display (e.g., with display enabling unit **5206**) of the indication that the second data-set representation has been selected by at least enabling display, on the display, of a numerical value of a second data entry of the second data set associated with a value of the independent variable corresponding to a horizontal position of the respective location on the display.

(445) In some embodiments, the first data set or the second data set comprises blood pressure data, and wherein the numerical value of the first data entry or the second data entry comprises a high value for diastolic blood pressure, a low value for diastolic blood pressure, a high value for systolic blood pressure, and a low value for systolic blood pressure.

(446) In some embodiments, the first data-set representation or the second data-set representation is generated based on an average of blood pressure values.

(447) In some embodiments, the first data set or the second data set comprises heart rate data, and wherein the numerical value of the first data entry or the second data entry comprises a high value for heart rate and a low value for heart rate.

(448) In some embodiments, the first data-set representation comprises a first line in the graph, and wherein displaying the indication that the first data-set representation has been selected comprises highlighting an area below the first line.

(449) In some embodiments, the second data-set representation comprises a second line in the graph, and wherein displaying the indication that the second data-set representation has been selected comprises highlighting an area below the second line.

(450) In some embodiments, the first range of vertical positions within the graph expands based on a length of time that the user input is detected while a vertical position of the respective location on the display is within the first range of vertical positions, and wherein the second range of vertical positions within the graph expands based on a length of time that the user input is detected while the vertical position of the respective location on the display is within the second range of vertical positions.

(451) In some embodiments, the dependent variable for the first data set is measured in different units from the dependent variable for the second data set.

(452) In some embodiments, a vertical scale for displaying the first data-set representation is different from a vertical scale for displaying the second data-set representation.

(453) In some embodiments, the vertical scale for the first data-set representation is determined based on the maximum and minimum values of the first dependent variable of the first data-set representation that are to be displayed in the graph, and wherein the vertical scale for the second data-set representation is determined based on the maximum and minimum values of the second dependent variable of the second data-set representation that are to be displayed in the graph.

(454) In some embodiments, the vertical scale for the first data-set representation of the plurality of sets of wellness data is defined by: a maximum vertical position within the graph corresponding to a first multiplying factor multiplied by the maximum value of the first dependent variable of the first data-set representation that are to be displayed in the graph; and a minimum vertical position within the graph corresponding to a second multiplying factor multiplied by the minimum value of the first dependent variable of the first data-set representation that are to be displayed in the graph.

(455) In some embodiments, the vertical scale for the second data-set representation of the plurality of sets of wellness data is defined by: a maximum vertical position within the graph corresponding to a third multiplying factor multiplied by the maximum value of the second dependent variable of the second data-set representation that are to be displayed in the graph; and a minimum vertical position within the graph corresponding to a fourth multiplying factor multiplied by the minimum value of the second dependent variable of the second data-set representation that are to be displayed in the graph.

(456) In some embodiments, the processing unit **5204** is further configured to: detect (e.g., with detecting unit **5208**) detailed-view input; and in response to detecting the detailed-view input, enable display of a detailed view of the first data set and the second data set, wherein the detailed view comprises a first partition associated with the first data set and a second partition associated with the second data set.

(457) In some embodiments, processing unit **5204** is configured to detect (e.g., with detecting unit **5208**) the detailed-view input by at least detecting a change in orientation of the electronic device while displaying the graph.

(458) In some embodiments, processing unit **5204** is further configured to: detect (e.g., with detecting unit **5208**) a request to scroll the detailed view; and in response to detecting the request to scroll the detailed view, enable scrolling (e.g., with scroll enabling unit **5210**) of the detailed view.

(459) In some embodiments, the first partition comprises a first graph representation of the first data set, and wherein the second partition comprises a second graph representation of the second data set.

(460) In some embodiments, the first graph representation is non-overlapping with the second graph representation.

(461) In some embodiments, processing unit **5204** is further configured to: enable display (e.g., with display enabling unit **5206**) of the first partition in a color matching a color of the first data-set representation, and wherein the second partition is displayed in a color matching a color of the second data-set representation.

(462) In some embodiments, the processing unit **5204** is configured to: enable display (e.g., with display enabling unit **5206**) of the first partition in a color matching a color of the first data-set representation, and enable display of the second partition in a color matching a color of the second data-set representation.

(463) In some embodiments, processing unit **5204** is further configured to: detect (e.g., with detecting unit **5208**) a request to reorder the first partition and the second partition; and in response to detecting the request to reorder the first partition and the second partition, reorder (e.g., with reordering unit **5212**) the first partition and the second partition within the detailed view.

(464) In some embodiments, processing unit **5204** is further configured to: detect graph-view input; and in response to detecting the graph-view input, display the graph comprising the first data-set representation of the first data set and the second data-set representation of the second data set.

(465) The operations described above with reference to FIG. 27 are, optionally, implemented by components depicted in FIGS. 1A-1B or FIG. 52. For example, display operation **2702**, detection operation **2704**, display operation **2706**, and display operation **2710** may be implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136**. A respective event recognizer **180** of application **136** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface

corresponds to a predefined event or sub event, such as activation of an affordance on a user interface. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** may utilize or call data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1A-1B**.

(466) In accordance with some examples, FIG. **53** shows a functional block diagram of an electronic device **5300** configured in accordance with the principles of the various described examples. The functional blocks of the device can be implemented by hardware, software, or a combination of hardware and software to carry out the principles of the various described examples. It is understood by persons of skill in the art that the functional blocks described in FIG. **53** can be combined or separated into sub-blocks to implement the principles of the various described examples. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

(467) As shown in FIG. **53**, electronic device **5300** can include a display unit **5302** for displaying a user interface. Electronic device **5300** can further include a processing unit **5304** coupled to the display unit **5302**. In some examples, processing unit **5304** can include one or more of a detecting unit **5306**, a display enabling unit **5308**, a restricting unit **5310**, initiating unit **5312**, sending unit **5314**, calling unit **5316**, and flagging unit **5318**.

(468) Processing unit **5304** may be configured to: while the electronic device is in a locked state: detect (e.g., with detecting unit **5306**) a request to display emergency information about a user of the device; and in response to detecting the request, enable display (e.g., with display enabling unit **5308**), on the display, of an emergency information interface comprising emergency information about the user of the device without unlocking the device.

(469) In some embodiments, processing unit **5304** is further configured to: while the electronic device is in the locked state, restrict (e.g., with restricting unit **5310**) use of one or more functions of the electronic device.

(470) In some embodiments, while the electronic device is in the locked state, at least a subset of data stored on the device is not accessible.

(471) In some embodiments, while the electronic device is in the locked state, communications from the electronic device are restricted.

(472) In some embodiments, the emergency information about the user comprises information associated with an emergency contact, and wherein the information associated with the emergency contacts comprises a name of the emergency contact and a relationship between the user and the emergency contact.

(473) In some embodiments, processing unit **5304** is further configured to: detect (e.g., with detecting unit **5306**) a request to communicate while the electronic device is in the locked state; and in response to detecting the request to communicate, initiate (e.g., with initiating unit **5312**) communication with the emergency contact.

(474) In some embodiments, processing unit **5304** is configured to initiate communication with the emergency contact by at least sending (e.g., with sending unit **5314**) an SMS message or email to the emergency contact.

(475) In some embodiments, processing unit **5304** is configured to initiate communication with the emergency contact by at least calling (e.g., with calling unit **5316**) a phone number associated with the emergency contact.

(476) In some embodiments, processing unit **5304** is configured to call the phone number associated with the emergency contact by at least flagging (e.g., with flagging unit **5318**) the call to the phone number as an emergency call.

(477) In some embodiments, the information associated with the emergency contacts further comprises the phone number associated with the emergency contact.

(478) In some embodiments, the information associated with the emergency contacts excludes the phone number associated with the emergency contact.

(479) In some embodiments, processing unit **5304** is further configured to: prior to displaying the emergency information interface: enable display (e.g., with display enabling unit **5308**) of an emergency dialing interface comprising a numerical input pad and an emergency information option; while displaying the emergency dialing interface, detect (e.g., with detecting unit **5306**) a selection of the emergency information option; and in response to detecting selection of the emergency information option, enable display (e.g., with display enabling unit **5308**) of the emergency information interface.

(480) In some embodiments, processing unit **5304** is further configured to: detect (e.g., with detecting unit **5306**) a predefined phone number entered using the numerical input pad while the electronic device is in the locked state; and in response to detecting the predefined phone number, call the predefined phone number.

(481) In some embodiments, processing unit **5304** is configured to call (e.g., with calling unit **5316**) the predefined phone number by at least flagging (e.g., with flagging unit **5318**) the call to the predefined phone number as an emergency call.

(482) In some embodiments, calls flagged as an emergency call are to be accepted by a receiving electronic device in any state of operation.

(483) In some embodiments, processing unit **5304** is further configured to: prior to displaying the emergency dialing interface: enable display (e.g., with display enabling unit **5308**) of a lock screen interface comprising an emergency option; detect (e.g., with detecting unit **5306**) a selection of the emergency option; and in response to detecting the selection of the emergency option, enable display (e.g., with display enabling unit **5308**) of the emergency dialing interface.

(484) In some embodiments, the emergency information about the user comprises one or more of: the user's name, birthday, medical conditions, allergies and reactions, medications, and one or more emergency contacts of the user.

(485) The operations described above with reference to FIG. **45** are, optionally, implemented by components depicted in FIGS. **1A-1B** or FIG. **53**. For example, detection operation **4502** and display operation **4504** may be implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136**. A respective event recognizer **180** of application **136** compares the event information to respective event definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface corresponds to a predefined event or sub event, such as activation of an affordance on a user interface. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** may utilize or call data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. **1A-1B**.

(486) In accordance with some examples, FIG. **54** shows a functional block diagram of an electronic device **5400** configured in accordance with the principles of the various described examples. The functional blocks of the device can be implemented by hardware, software, or a combination of hardware and software to carry out the principles of the various described examples. It is understood by persons of skill in the art that the functional blocks described in FIG. **54** can be combined or separated into sub-blocks to implement the principles of the various described examples. Therefore, the description herein optionally supports any possible combination or separation or further definition of the functional blocks described herein.

(487) As shown in FIG. **54**, electronic device **5400** can include a display unit **5402** for displaying a user interface. Electronic device **5400** can further include a processing unit **5404** coupled to the display unit **5402**. In some examples, processing unit **5404** can include one or more of a receiving unit **5406**, an identifying unit **5408**, a using unit **5410**, a prioritizing unit **5412**, a display enabling unit **5414**, a detecting unit **5416**, a reordering unit **5418**, and an approving or rejecting unit **5420**.

(488) Processing unit **5404** may be configured to: receive (e.g., with receiving unit **5406**), from a user, information identifying a plurality of approved sources of wellness data, wherein the information identifying the plurality of approved sources identifies one or more types of wellness

data that are approved to be received from the plurality of approved sources and stored in a wellness database; and receive (e.g., with receiving unit **5406**), from the user, information identifying a plurality of approved destinations of wellness data, wherein the information identifying the plurality of approved destinations identifies one or more types of wellness data that are approved to be accessed from the wellness database by the plurality of approved destinations of wellness data.

(489) In some embodiments, the plurality of approved sources comprises an electronic device or software application.

(490) In some embodiments, the plurality of approved destinations comprises an electronic device or software application.

(491) In some embodiments, the plurality of approved sources is ranked amongst each other.

(492) In some embodiments, processing unit **5404** is further configured to: identify (e.g., with identifying unit **5408**) a first wellness data entry in the wellness database that was received from a first approved source of the plurality of approved sources, the first wellness data entry comprising a first wellness data type and a first timestamp; and identify (e.g., with identifying unit **5408**) a second wellness data entry in the wellness database that was received from a second approved source of the plurality of approved sources, the second wellness data entry comprising a second wellness data type and a second timestamp, wherein the first wellness data type and the second wellness data type are the same, and wherein the first timestamp is within a threshold length of time from the second timestamp.

(493) In some embodiments, the first approved source has been identified by the user as being preferred over the second approved source, and wherein processing unit **5404** is further configured to: use (e.g., with using unit **5410**) the first wellness data entry instead of using the second wellness data entry.

(494) In some embodiments, the first approved source has been identified by the user as being preferred over the second approved source, and wherein processing unit **5404** is further configured to: prioritize (e.g., with prioritizing unit **5412**) the first wellness data entry over the second wellness data entry.

(495) In some embodiments, processing unit **5404** is further configured to: in accordance with a determination that the first wellness data entry is prioritized over the second wellness data entry, use (e.g., with using unit **5410**) the first wellness data entry instead of using the second wellness data entry.

(496) In some embodiments, the second approved source has been identified by the user as being preferred over the first approved source, and wherein processing unit **5404** is further configured to: prioritize (e.g., with prioritizing unit **5412**) the second wellness data entry over the first wellness data entry.

(497) In some embodiments, processing unit **5404** is further configured to: in accordance with a determination that the second wellness data entry is prioritized over the first wellness data entry, use (e.g., with using unit **5410**) the second wellness data entry instead of using the first wellness data entry.

(498) In some embodiments, processing unit **5404** is further configured to: enable display (e.g., with display enabling unit **5414**), on the display, of a plurality of categories of wellness data stored in the wellness database.

(499) In some embodiments, processing unit **5404** is further configured to: detect (e.g., with detecting unit **5416**) a selection of a category of wellness data from the displayed plurality of categories of wellness data; and in response to detecting the selection of the category of wellness data, enable display (e.g., with display enabling unit **5414**), on the display, of one or more sub-categories of the category of wellness data.

(500) In some embodiments, processing unit **5404** is further configured to: detect (e.g., with detecting unit **5416**) a selection of a sub-category from the displayed one or more sub-categories; and in response to detecting the selection of the sub-category, enable display (e.g., with display enabling unit **5414**), on the display, of a detailed view of the sub-category.

(501) In some embodiments, the detailed view of the sub-category comprises a graph representation of the sub-category of wellness data over time and a numerical daily value of the sub-category of wellness data.

(502) In some embodiments, the detailed view of the sub-category further comprises an input field for entering a wellness data entry, and processing unit **5404** is further configured to: receive (e.g., with receiving unit **5406**) a wellness data entry to be stored in the wellness database that was input into the input field.

(503) In some embodiments, the detailed view of the sub-category further comprises a textual description of the sub-category.

(504) In some embodiments, the detailed view of the sub-category further comprises an option to view wellness data entries corresponding to the sub-category, and wherein processing unit **5404** is further configured to: enable display (e.g., with display enabling unit **5414**), on the display, of a plurality of wellness data entries corresponding to the sub-category stored in the wellness database.

(505) In some embodiments, each of the plurality of wellness data entries comprises a numerical value of the data entry, a timestamp, and an identification of a source of the data entry.

(506) In some embodiments, the detailed view of the sub-category further comprises an option to share wellness data, and processing unit **5404** is further configured to: enable display (e.g., with display enabling unit **5414**), on the display, of a data sharing interface comprising the plurality of approved sources and the plurality of approved destinations.

(507) In some embodiments, processing unit **5404** is further configured to: detect (e.g., with detecting unit **5416**) a request to reorder the displayed plurality of approved sources; and in response to detecting the request to reorder the displayed plurality of approved sources, reorder (e.g., with reordering unit **5418**) the displayed plurality of approved sources in accordance with the detected request to reorder the displayed plurality of approved sources.

(508) In some embodiments, the data sharing interface further comprises options to add an approved destination to the plurality of approved destinations and to remove an approved destination from the plurality of approved destinations.

(509) In some embodiments, processing unit **5404** is further configured to: receive (e.g., with receiving unit **5406**) a search query; and enable display (e.g., with display enabling unit **5414**), on the display, of one or more sub-categories of the plurality of categories that match the search query, wherein the displayed one or more sub-categories that match the search query are color-coded based on their respective categories.

(510) In some embodiments, processing unit **5404** is further configured to: enable display (e.g., with display enabling unit **5414**), on the display, of a source interface comprising a list of known sources.

(511) In some embodiments, the source interface further comprises a numerical indicator associated a known source of the known sources that represents a number of new types of wellness data that can be provided by the known source.

(512) In some embodiments, processing unit **5404** is further configured to: detect (e.g., with detecting unit **5416**) a selection of a known source from the displayed list of known sources; and in response to detecting the selection of the known source, enable display (e.g., with display enabling unit **5414**), on the display, of a list of types of wellness data that the known source can provide.

(513) In some embodiments, the list of types of wellness data that the known source can provide comprises a selectable option for each of the types of wellness data that the known source can provide to approve or reject the associated type of wellness data.

(514) In some embodiments, processing unit **5404** is further configured to: detect a selection of the selectable option for a type of wellness data that the known source can provide; and in response to detecting the selection of the selectable option, approve or reject (e.g., with approving or rejecting unit **5420**) the type of wellness data that the known source can provide in accordance with the detected selection of the selectable option.

(515) The operations described above with reference to FIGS. **38A** and **38B** are, optionally, implemented by components depicted in FIGS. **1A-1B** or FIG. **54**. For example, receiving operation **3802** and identifying operation **3806** may be implemented by event sorter **170**, event recognizer **180**, and event handler **190**. Event monitor **171** in event sorter **170** detects a contact on touch-sensitive display **112**, and event dispatcher module **174** delivers the event information to application **136**. A respective event recognizer **180** of application **136** compares the event information to respective event

definitions **186**, and determines whether a first contact at a first location on the touch-sensitive surface corresponds to a predefined event or sub event, such as activation of an affordance on a user interface. When a respective predefined event or sub-event is detected, event recognizer **180** activates an event handler **190** associated with the detection of the event or sub-event. Event handler **190** may utilize or call data updater **176** or object updater **177** to update the application internal state **192**. In some embodiments, event handler **190** accesses a respective GUI updater **178** to update what is displayed by the application. Similarly, it would be clear to a person having ordinary skill in the art how other processes can be implemented based on the components depicted in FIGS. 1A-1B.

(516) The foregoing description, for purpose of explanation, has been described with reference to specific embodiments. However, the illustrative discussions above are not intended to be exhaustive or to limit the invention to the precise forms disclosed. Many modifications and variations are possible in view of the above teachings. The embodiments were chosen and described in order to best explain the principles of the techniques and their practical applications. Others skilled in the art are thereby enabled to best utilize the techniques and various embodiments with various modifications as are suited to the particular use contemplated.

(517) Although the disclosure and examples have been fully described with reference to the accompanying drawings, it is to be noted that various changes and modifications will become apparent to those skilled in the art. Such changes and modifications are to be understood as being included within the scope of the disclosure and examples as defined by the claims.

(518) As described above, one aspect of the present technology is the gathering and use of data available from various sources to improve the delivery to users of invitational content or any other content that may be of interest to them. The present disclosure contemplates that in some instances, this gathered data can include personal information data that uniquely identifies or can be used to contact or locate a specific person. Such personal information data can include demographic data, location-based data, telephone numbers, email addresses, home addresses, or any other identifying information.

(519) The present disclosure recognizes that the use of such personal information data, in the present technology, can be used to the benefit of users. For example, the personal information data can be used to deliver targeted content that is of greater interest to the user. Accordingly, use of such personal information data enables calculated control of the delivered content. Further, other uses for personal information data that benefit the user are also contemplated by the present disclosure.

(520) The present disclosure further contemplates that the entities responsible for the collection, analysis, disclosure, transfer, storage, or other use of such personal information data will comply with well-established privacy policies and/or privacy practices. In particular, such entities should implement and consistently use privacy policies and practices that are generally recognized as meeting or exceeding industry or governmental requirements for maintaining personal information data private and secure. For example, personal information from users should be collected for legitimate and reasonable uses of the entity and not shared or sold outside of those legitimate uses. Further, such collection should occur only after receiving the informed consent of the users. Additionally, such entities would take any needed steps for safeguarding and securing access to such personal information data and ensuring that others with access to the personal information data adhere to their privacy policies and procedures. Further, such entities can subject themselves to evaluation by third parties to certify their adherence to widely accepted privacy policies and practices.

(521) Despite the foregoing, the present disclosure also contemplates examples in which users selectively block the use of, or access to, personal information data. That is, the present disclosure contemplates that hardware and/or software elements can be provided to prevent or block access to such personal information data. For example, in the case of advertisement delivery services, the present technology can be configured to allow users to select to “opt in” or “opt out” of participation in the collection of personal information data during registration for services. In another example, users can select not to provide location information for targeted content delivery services. In yet another example, users can select to not provide precise location information, but permit the transfer of location zone information.

(522) Therefore, although the present disclosure broadly covers use of personal information data to implement one or more various disclosed examples, the present disclosure also contemplates that the various examples can also be implemented without the need for accessing such personal information data. That is, the various examples of the present technology are not rendered inoperable due to the lack of all or a portion of such personal information data. For example, content can be selected and delivered to users by inferring preferences based on non-personal information data or a bare minimum amount of personal information, such as the content being requested by the device associated with a user, other non-personal information available to the content delivery services, or publicly available information.

Claims

1. An electronic device comprising: a display; one or more processors; and memory storing one or more programs configured to be executed by the one or more processors, the one or more programs including instructions for: receiving, from a first user associated with a set of wellness data, an identification of a second user authorized to access the set of wellness data and a category indicating a relationship between the first user and the second user, wherein the identification of the second user includes a level of access to a particular subset of the set of wellness data, wherein the category includes the second user, and wherein the category is associated with a particular set of wellness data types that users belonging to the category are allowed to view; in response to detecting an update to the set of wellness data: transmitting a notification to the second user authorized to access the set of wellness data notifying the second user authorized to access the set of wellness data that the update to the set of wellness data has been detected; encrypting at least a portion of the set of wellness data; and transmitting at least the encrypted portion of the set of wellness data to the second user authorized to access the set of wellness data.
2. The electronic device of claim 1, wherein the identification of the second user authorized to access the set of wellness data comprises a name, a username, or contact information.
3. The electronic device of claim 1, wherein the at least the encrypted portion of the set of wellness data is transmitted in response to receiving a request from the second user authorized to access the set of wellness data.
4. The electronic device of claim 1, wherein transmitting a notification to the second user authorized to access the set of wellness data notifying the second user authorized to access the set of wellness data that the update to the set of wellness data has been detected; encrypting at least a portion of the set of wellness data; and transmitting at least the encrypted portion of the set of wellness data to the second user authorized to access the set of wellness data are performed without detecting an input to transmit the set of wellness data.
5. A non-transitory computer-readable storage medium storing one or more programs configured to be executed by one or more processors of an electronic device with a display, the one or more programs including instructions for: receiving, from a first user associated with a set of wellness data, an identification of a second user authorized to access the set of wellness data and a category indicating a relationship between the first user and the second user, wherein the identification of the second user includes a level of access to a particular subset of the set of wellness data, wherein the category includes the second user, and wherein the category is associated with a particular set of wellness data types that users belonging to the category are allowed to view; in response to detecting an update to the set of wellness data: transmitting a notification to the second user authorized to access the set of wellness data notifying the second user authorized to access the set of wellness data that the update to the set of wellness data has been detected; encrypting at least a portion of the set of wellness data; and transmitting at least the encrypted portion of the set of wellness data to the second user authorized to access the set of wellness data.
6. The non-transitory computer-readable storage medium of claim 5, wherein the identification of the second user authorized to access the set of wellness data comprises a name, a username, or contact information.

7. The non-transitory computer-readable storage medium of claim 5, wherein the at least the encrypted portion of the set of wellness data is transmitted in response to receiving a request from the second user authorized to access the set of wellness data.
8. The non-transitory computer-readable storage medium of claim 5, wherein transmitting a notification to the second user authorized to access the set of wellness data notifying the second user authorized to access the set of wellness data that the update to the set of wellness data has been detected; encrypting at least a portion of the set of wellness data; and transmitting at least the encrypted portion of the set of wellness data to the second user authorized to access the set of wellness data are performed without detecting an input to transmit the set of wellness data.
9. A method comprising: at an electronic device that includes a display: receiving, from a first user associated with a set of wellness data, an identification of a second user authorized to access the set of wellness data and a category indicating a relationship between the first user and the second user, wherein the identification of the second user includes a level of access to a particular subset of the set of wellness data, wherein the category includes the second user, and wherein the category is associated with a particular set of wellness data types that users belonging to the category are allowed to view; in response to detecting an update to the set of wellness data: transmitting a notification to the second user authorized to access the set of wellness data notifying the second user authorized to access the set of wellness data that the update to the set of wellness data has been detected; encrypting at least a portion of the set of wellness data; and transmitting at least the encrypted portion of the set of wellness data to the second user authorized to access the set of wellness data.
10. The method of claim 9, wherein the identification of the second user authorized to access the set of wellness data comprises a name, a username, or contact information.
11. The method of claim 9, wherein the at least the encrypted portion of the set of wellness data is transmitted in response to receiving a request from the second user authorized to access the set of wellness data.
12. The method of claim 9, wherein transmitting a notification to the second user authorized to access the set of wellness data notifying the second user authorized to access the set of wellness data that the update to the set of wellness data has been detected; encrypting at least a portion of the set of wellness data; and transmitting at least the encrypted portion of the set of wellness data to the second user authorized to access the set of wellness data are performed without detecting an input to transmit the set of wellness data.
-