

# US Patent & Trademark Office

## Patent Public Search | Text View

United States Patent Application Publication

20250263776

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

BUSE; David Aaron et al.

### METHOD FOR RECEIVING AND STORING REAGENT PACKS IN AN INSTRUMENT

#### Abstract

A method for analyzing samples is performed within a housing. Each sample is contacted in a separate receptacle with a magnetically-responsive solid support for binding and immobilizing a nucleic acid of interest that may be present in one or more of the samples. Each sample is processed to isolate and purify any nucleic acid of interest that is present. An elution buffer is provided to each separate receptacle, thereby forming an eluate containing the nucleic acid of interest, if present in the associated sample. A unit-dose reagent for performing a nucleic acid amplification reaction is reconstituted for each sample, and the reconstituted reagent is combined with the eluate in one of a plurality of processing vials. Each of the processing vials containing reconstituted reagent and eluate is closed with a cap and transferred to an incubator and the contents are subjected to nucleic acid amplification conditions.

**Inventors:** BUSE; David Aaron (San Diego, CA), OPALSKY; David (San Diego, CA), RHUBOTTOM; Jason F. (Oceanside, CA), HAGEN; Norbert D. (Carlsbad, CA), TIDD; Jennifer (Vista, CA)

**Applicant:** GEN-PROBE INCORPORATED (San Diego, CA)

**Family ID:** 1000008578431

**Assignee:** GEN-PROBE INCORPORATED (San Diego, CA)

**Appl. No.:** 19/027072

**Filed:** January 17, 2025

#### Related U.S. Application Data

parent US continuation 18750680 20240621 PENDING child US 19027072

parent US continuation 18230549 20230804 parent-grant-document US 12173352 child US 18750680

parent US continuation 17668775 20220210 parent-grant-document US 11434521 child US

17877776  
parent US continuation 17033395 20200925 parent-grant-document US 11788115 child US 17036730  
parent US continuation 16829230 20200325 parent-grant-document US 10889851 child US 17033395  
parent US continuation 15675206 20170811 parent-grant-document US 10711297 child US 16829230  
parent US continuation 14213900 20140314 parent-grant-document US 9732374 child US 15675206  
parent US division 17877776 20220729 parent-grant-document US 11761027 child US 18230549  
parent US division 17036730 20200929 parent-grant-document US 11279967 child US 17668775  
us-provisional-application US 61784994 20130314

---

## Publication Classification

**Int. Cl.:** **C12Q1/6806** (20180101); **B01L3/00** (20060101); **B01L7/00** (20060101); **C12Q1/686** (20180101); **G01N35/04** (20060101)

**U.S. Cl.:**

**CPC** **C12Q1/6806** (20130101); **B01L3/50825** (20130101); **B01L3/565** (20130101); **B01L7/5255** (20130101); **C12Q1/686** (20130101); **G01N35/04** (20130101); B01L3/527 (20130101); B01L2200/026 (20130101); B01L2200/0689 (20130101); B01L2300/046 (20130101); G01N2035/0418 (20130101); G01N2035/0436 (20130101)

---

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This is a continuation of U.S. application Ser. No. 18/750,680, filed Jun. 21, 2024, which is a continuation of U.S. application Ser. No. 18/230,549, filed Aug. 4, 2023, now U.S. Pat. No. 12,173,352, which is a divisional of U.S. application Ser. No. 17/877,776, filed Jul. 29, 2022, now U.S. Pat. No. 11,761,027, which is a continuation of U.S. application Ser. No. 17/668,775, filed Feb. 10, 2022, now U.S. Pat. No. 11,434,521, which is a divisional of U.S. application Ser. No. 17/036,730, filed Sep. 29, 2020, now U.S. Pat. No. 11,279,967, which is continuation of U.S. application Ser. No. 17/033,395, filed Sep. 25, 2020, which is a continuation of U.S. application Ser. No. 16/829,230, filed Mar. 25, 2020, now U.S. Pat. No. 10,889,851, which is a continuation of U.S. application Ser. No. 15/675,206, filed Aug. 11, 2017, now U.S. Pat. No. 10,711,297, which is a continuation of U.S. application Ser. No. 14/213,900, filed Mar. 14, 2014, now U.S. Pat. No. 9,732,374, which claims the benefit under 35 U.S.C. § 119 (e) of the filing date of U.S. Provisional Application No. 61/784,994, filed Mar. 14, 2013, the disclosures of which are hereby incorporated by reference herein.

## FIELD

[0002] The present disclosure relates to systems and methods for performing molecular assays that comprise target nucleic acid amplification reactions by heating the contents of a capped vial containing a reaction mixture and measuring an optical signal from the contents of the vial.

## BACKGROUND

[0003] None of the references described or referred to herein are admitted to be prior art to the claimed invention.

[0004] Molecular assays are nucleic acid-based tests that are used in clinical diagnosis, screening,

monitoring, industrial and environmental testing, health science research, and other applications to detect the presence or amount of an analyte of interest in a sample, such as a microbe or virus, or to detect genetic abnormalities or mutations in an organism. Molecular assays enabling quantification may permit practitioners to better calculate the extent of infection or disease and to determine the state of a disease over time. Quantitative molecular assays are also useful for monitoring the effectiveness of a therapy. A variety of known molecular assays can be employed to detect various diagnostic indicators.

[0005] Molecular assays generally include multiple steps leading to the detection or quantification of a target nucleic acid in a sample. Targeted nucleic acids often include a region that is specific to an identifiable “group” of organisms or viruses, where the group is defined by at least one shared sequence of nucleic acid that is common to all members of the group and is specific to the group in the particular sample being assayed. Examples of nucleic acid-based detection methods are disclosed by Kohne in U.S. Pat. No. 4,851,330 and Hogan et al. in U.S. Pat. No. 5,541,308.

[0006] Most molecular assays include a detection step in which the sample is exposed to a detection probe or amplification primer that is designed or selected to exhibit specificity under the particular conditions of use for a nucleic acid sequence belonging to an organism or virus of interest. The detection probe or amplification primer can be labeled for detection with a reporter moiety, such as a chemiluminescent or fluorescent agent, or an intercalating dye can be used to indiscriminately detect the presence of double-stranded nucleic acids in a sample. See, e.g., Livak et al. in U.S. Pat. No. 5,538,848, Hogan et al. in U.S. Pat. No. 5,541,308, Tyagi et al. in U.S. Pat. No. 5,925,517, Higuchi in U.S. Pat. No. 5,994,056, Wittwer et al. in U.S. Pat. No. 6,174,670, Whitcombe et al. in U.S. Pat. No. 6,326,145, and Wittwer et al. in U.S. Pat. No. 6,569,627. To render a nucleic acid available for hybridization to the detection probe or amplification primer, cells may be lysed or permeabilized by a variety of known techniques, including by chemical (e.g., detergent), mechanical (e.g., sonication), and/or thermal procedures. See, e.g., Clark et al. in U.S. Pat. No. 5,786,208.

[0007] Before or after exposing a target nucleic acid to a detection probe or amplification primer, the target nucleic acid can be immobilized on a solid support (e.g., particles or beads comprising a magnetically-responsive material) that directly or indirectly binds the target nucleic acid. A solid-phase extraction method for directly binding nucleic acids onto silica beads in the presence of a chaotropic substance is described by Boom et al. in U.S. Pat. No. 5,234,864. An example of indirect immobilization is described by Weisburg et al. in U.S. Pat. No. 6,534,273, which discloses the use of a capture probe that binds to the target nucleic acid under a first set of sample conditions and to an oligonucleotide covalently attached to the solid support under a second set of sample conditions. If the solid support comprises a magnetically-responsive particle or bead, magnets can be used to attract the solid support to the side of a receptacle containing the solid support. Once the immobilized target nucleic acid is isolated within the receptacle, the isolated target nucleic acid can be separated from at least a portion of the fluid contents of the sample by, for example, contacting and aspirating the fluid contents of the receptacle with a robotic pipettor or other substance transfer device. See, e.g., Ammann et al. in U.S. Pat. No. 6,605,213. One or more wash steps with a buffered solution or water may be performed to further purify the isolated nucleic acid.

[0008] To increase the sensitivity of an assay, a target nucleic acid can be amplified by a nucleic acid amplification reaction, many of which are well known in the art. Known methods of amplification include Polymerase Chain Reaction (“PCR”) (see, e.g., Mullis et al. in U.S. Pat. Nos. 4,683,195, 4,683,202 and 4,800,159; and Mullis et al., *Methods in Enzymology*, 155:335-350 (1987)); Strand Displacement Amplification (“SDA”) (see, e.g., Walker, *PCR Methods and Applications*, 3:25-30 (1993); Walker et al., *Nucleic Acids Res.*, 20:1691-1996 (1992); and Walker et al., *Proc. Natl. Acad. Sci.*, 89:392-396 (1991)); Ligase Chain Reaction (“LCR”) (see, e.g., Birkenmeyer in U.S. Pat. No. 5,427,930 and Carrino et al., in U.S. Pat. No. 5,686,272); and transcription-based methods of amplification (Boothroyd et al. in U.S. Pat. No. 5,437,990; Kacian

et al., in U.S. Pat. Nos. 5,399,491 and 5,480,784; Davey et al. in U.S. Pat. No. 5,409,818; Malek et al. in U.S. Pat. No. 5,130,238; and Gingeras et al. in International Publication Nos. WO 88/01302 and WO 88/10315). A review of many amplification reactions, including PCR and Transcription-Mediated Amplification (“TMA”), is provided in Lee et al., *Nucleic Acid Amplification Technologies*, BioTechniques Books (1997).

[0009] PCR is the oldest and most common form of amplification. Like other amplification methods, PCR amplifies one or more copies of a region of nucleic acid by several orders of magnitude, generating thousands to millions of copies of a particular nucleic acid sequence. PCR has broad applications in clinical and biological research labs. The uses of this procedure are too enumerable, and well known at this time, to recite in this patent application.

[0010] PCR employs thermal cycling, which consists of repeated cycles of heating and cooling of a reaction mixture. The reaction is generally initiated with primers (short DNA fragments containing sequences complementary to the target nucleic acid region), along with enzymes and additional reaction materials. Once under way, the replicated nucleic acid can be used as an additional template in the amplification reaction, thereby leading to the exponential amplification of a target nucleic acid sequence.

[0011] Because a probe hybridizes to the targeted sequence, the strength of a signal associated with the probe is proportional to the amount of target nucleic acid sequence that is present in a sample. Accordingly, by periodically measuring, during the amplification process, a signal indicative of the presence of amplicon, the growth of amplicon over time can be detected. Based on the data collected during this “real-time” monitoring of the amplification process, the amount of the target nucleic acid that was originally in the sample can be ascertained. In one context, collecting data in “real-time” means collecting data while a reaction or other process is in progress, as opposed to collecting data at the conclusion of the reaction or process. Systems and methods for real-time detection and for processing real-time data to ascertain nucleic acid levels are disclosed by, for example, Lair et al. in U.S. Pat. No. 7,932,081.

[0012] To detect different nucleic acids in a single assay, distinct probes may be designed or selected to separately hybridize to the different nucleic acids, where the probes may include reporter moieties that can be differentiated from each other. See, e.g., Livak et al. in U.S. Pat. No. 5,538,848, Tyagi et al. in U.S. Pat. No. 5,925,517, Morrison in U.S. Pat. No. 5,928,862, Mayrand in U.S. Pat. No. 5,691,146, and Becker et al. in U.S. Pat. No. 5,928,862. For example, different probes designed or selected to hybridize to different targets can have fluorophores that fluoresce at a predetermined wavelength when exposed to excitation light of a prescribed excitation wavelength. Assays for detecting different target nucleic acids can be performed in parallel by alternately exposing the sample material to different excitation wavelengths and detecting the level of fluorescence at the wavelength of interest corresponding to the probe for each target nucleic acid during the real-time monitoring process. Parallel processing can be performed using different signal detecting devices configured to periodically measure signal emissions during the amplification process, and with different signal detecting devices being configured to generate excitation signals of different wavelengths and to measure emission signals of different wavelengths.

## SUMMARY

[0013] Aspects of the present disclosure are embodied in systems, apparatuses, and processes that, inter alia, enhance the functionality of certain diagnostic first modules by supporting processing capabilities that are not available in the base first module or existing modules within the base first module. In one embodiment, the systems, apparatuses, and processes extend the functionality of a nucleic acid diagnostic first module by supporting PCR assay processing and analysis capabilities in addition to isothermal amplification processing and analysis capabilities. A second module is operatively coupled to the base first module to extend the overall system capabilities of the diagnostic system. Providing this extension module imparts sample-to-answer capabilities for a

single automated instrument that, when incorporated, will be capable of automatically performing both thermal cycling and isothermal amplification assays, and which may incorporate end-point and real-time formats using chemiluminescent and/or fluorescent labels.

[0014] In some embodiments, a diagnostic system can be configured to perform a first nucleic acid amplification reaction and a second nucleic acid amplification reaction different than the first nucleic acid amplification reaction. The diagnostic system comprises at least one bulk reagent container compartment configured to store at least a first bulk reagent container comprising a first bulk reagent for performing a sample preparation process, and a second bulk reagent container comprising a second bulk reagent for performing the first nucleic acid amplification reaction. The at least one bulk reagent container compartment is further configured to store a unit-dose reagent compartment configured to store at least one unit-dose reagent pack comprising a plurality of unit-dose reagents for performing the second nucleic acid amplification reaction. The diagnostic system is configured to perform the sample preparation process using the first bulk reagent on a first subset of the plurality of samples provided to the diagnostic system. The diagnostic system is also configured to perform the first nucleic acid amplification reaction using a second bulk reagent on the first subset of the plurality of samples. And the diagnostic system is configured to perform the second nucleic acid amplification reaction using the plurality of unit-dose reagents on a second subset of the plurality of samples.

[0015] In some embodiments, an automated method for analyzing a plurality of samples comprises performing a first assay on a first sample subset of the plurality of samples. The first assay comprises a first reaction that uses a first unit-dose reagent. The method also comprises performing a second assay on a second sample subset of the plurality of samples. The second assay comprises a second reaction that uses at least one of (a) a second unit-dose reagent different than the first unit-dose reagent and (b) a first bulk reagent. Performing the first assay and performing the second assay occur within a same diagnostic system that stores the first unit-dose reagent and at least one of the second unit-dose reagent and the first bulk reagent.

[0016] In one exemplary embodiment, the base first module comprises a dual format molecular diagnostic instrument designed to run specific target-amplified assays, utilizing chemiluminescence and fluorescence detection technologies for both qualitative and real-time quantitative assays. With the addition of the second module, additional automated assays, such as PCR assays, can be run (intermixed) with assays performed by the base first module and achieve similar throughput that is achieved by the base first module.

[0017] In one exemplary embodiment, the second module comprises a thermal cycler with real-time fluorescence detection capabilities, a reagent pack storage bay that allows for loading and cooled storage of new reagent packs containing reagents (e.g., PCR reagents), additional disposable pipette tip trays, PCR- and assay-specific reagents, and one or more pipettor systems to perform the assay steps needed for the PCR or other reaction and/or receptacle transport. The second module may rely on the base first module for sample input, sample preparation, target capture, and other processing steps, such as the addition of elution for subsequent PCR assays, and thus the second module further leverages those capabilities of the base first module and supports additional processing and detection capabilities without requiring that the sample input and preparation functionality be built into the second module.

[0018] Aspects of the disclosure are embodied in a second module for enhancing the capabilities of a first module configured to process substances within each of a plurality of receptacles and including a first substance transfer device configured to dispense substances into each receptacle and a receptacle transfer device configured to move receptacles within the first module. The second module is configured to be coupled to or decoupled from the first module and comprises a container transport configured to transport at least one container from a location within the second module to a location within the first module that is accessible to the first substance transfer device to transfer substance from the container to a receptacle within the first module, a receptacle

distribution module configured to receive a receptacle from the receptacle transfer device of the first module, transfer the receptacle into the second module, and move the receptacle between different locations within the first module, and a second substance transfer device configured to dispense substances into or remove substances from the receptacle within the second module.

[0019] According to some aspects of the disclosure, the receptacle distribution module comprises a receptacle distributor configured to move a receptacle onto the receptacle distributor at a first location on the second module, carry the receptacle from the first location to a second location on the second module that is different from the first location, and move the receptacle off the receptacle distributor at the second location on the second module. A receptacle handoff device can be configured to receive a receptacle from the receptacle transfer device of the first module and to reposition the receptacle to present the receptacle to the receptacle distributor to be moved by the receptacle distributor from the receptacle handoff device onto the receptacle distributor.

[0020] According to some aspects of the disclosure, the receptacle distributor is configured to rotate about an axis of rotation to move a receptacle carried thereby in an arced path between locations within the second module. Other configurations for moving a receptacle between locations within the second module are contemplated. Therefore, the disclosure is not limited to receptacle distributors that rotate about an axis of rotation.

[0021] According to some aspects of the disclosure, the second module further comprises receptacle storage stations for holding one or more receptacles transferred from the first module to the second module, wherein the receptacle storage stations are arranged in a configuration corresponding to the arced path of the receptacle distributor.

[0022] According to some aspects of the disclosure, the receptacle distributor is configured to move vertically a receptacle carried thereby between different vertically-disposed locations within the second module.

[0023] According to some aspects of the disclosure, the receptacle handoff device is configured to rotate between a first position for receiving a receptacle from the receptacle transfer device of the first module and a second position for presenting the receptacle to the receptacle distributor.

[0024] According to some aspects of the disclosure, the second module further comprises a container compartment, configured to hold one or more fluid containers. In certain embodiments, the container compartment can be a container drawer configured to be moved between an open position and a closed position and to, when moved to the closed position, place at least one fluid container into an operative position with respect to the container transport so that the container can be transported by the container transport from the container compartment into the first module. In an alternate embodiment, the container compartment can comprise a door with a sliding tray that is configured to be moved between an open position and a closed position and to, when moved to the closed position, place at least one fluid container into an operative position with respect to the container transport so that the container can be transported by the container transport from the container compartment into the first module.

[0025] According to some aspects of the disclosure, the second module further comprises a container carriage configured to carry one or more containers and to be movable with the container compartment and further configured to be engaged by the container transport when the container compartment is in the closed position such that the container transport is operable to move the container carriage and the one or more containers carried thereby from the container compartment into the first module.

[0026] According to some aspects of the disclosure, the second module further comprises a carriage transport and a carriage lock. The carriage transport is moveable with the container receptacle and configured to carry the container carriage between a first position when the container receptacle is in the open position and a second position when the container receptacle is in the closed position. The carriage lock is configured to lock the container carriage to the carriage transport when the carriage transport is in the first position and to release the container from the carriage transport

when the carriage transport is in the second position to permit the container carriage to be removed from the carriage transport by the container transport.

[0027] According to some aspects of the disclosure, the container transport comprises a track extending from the container compartment into the first module, a carriage hook configured to engage the container carriage when the container compartment is in the closed position, and a motorized carriage hook drive system configured to move carriage hook along the carriage track.

[0028] According to some aspects of the disclosure, the motorized carriage hook drive system comprises a motor and a belt driven by the motor and coupled to the carriage hook.

[0029] According to some aspects of the disclosure, the processing apparatus further comprises one or more position sensors disposed at one or more locations along the track to detect a position of the carriage on the track.

[0030] According to some aspects of the disclosure, the second module further comprises a reagent pack changer comprising a pack input device and a pack storage compartment. The pack input device is configured to enable an operator to place a reagent pack containing at least one reagent into the second module or remove a reagent pack from the second module. The pack storage compartment is configured to hold a plurality of reagent packs until a reagent pack is needed for processing within the second module. The receptacle distribution module is further configured to move a reagent pack between the pack input device and the pack storage compartment.

[0031] According to some aspects of the disclosure, the second module further comprises one or more reagent pack loading stations, each configured to hold a reagent pack in a manner that permits the second substance transfer device to transfer a substance to or from the reagent pack. Therefore, in some embodiments, the reagent pack loading station is configured to change the orientation of the reagent pack from an initial loaded position to a position aligned with the second substance transfer device.

[0032] According to some aspects of the disclosure, the second module further comprises a charged field generator operatively associated with at least one of the pack input device, the pack storage compartment, and the reagent pack loading stations and configured to generate electrostatic forces to position and hold a reagent present in a reagent pack held in the pack input device or pack storage compartment. In related aspects the charged field generator is situated below at least one of the pack input device, the pack storage compartment, and the reagent pack loading stations such that electromagnetic forces are applied to, or adjacent to, the bottom of one or more wells of a reagent pack, when present.

[0033] According to some aspects of the disclosure, wherein the pack input device comprises a reagent pack carousel that is rotatable about an axis of rotation, wherein the pack carousel includes a plurality of reagent pack stations, each configured to hold a reagent pack, disposed around the axis of rotation.

[0034] According to some aspects of the disclosure, the pack carousel is disposed in a compartment, such as a drawer, that is movable between an open position providing access to the pack carousel and a closed position closing off access to the pack carousel. The pack carousel can also be accessed through an access panel revealing a slidable tray on which is mounted the pack carousel.

[0035] According to some aspects of the disclosure, the second module further comprises a code reader operatively disposed with respect to the pack input device and configured to read a machine readable code on each reagent pack carried in the pack input device. In some embodiments, the code reader reads the machine readable code on a respective reagent pack in close proximity to the code reader.

[0036] According to some aspects of the disclosure, the second module further comprises a pack storage carousel disposed within the pack storage compartment. The pack storage carousel is rotatable about an axis of rotation and includes a plurality of reagent pack stations, each configured to hold a reagent pack, disposed around the axis of rotation.

[0037] According to some aspects of the disclosure, the reagent pack stations of the pack storage carousel are disposed on more than one level of the second module.

[0038] According to some aspects of the disclosure, the second module further includes a cooling system for maintaining the storage compartment at a lower than ambient temperature.

[0039] According to some aspects of the disclosure, the second substance transfer device comprises a robotic pipettor having a pipettor probe, and the second module further comprises one or more disposable tip compartments configured to hold a plurality of disposable tips configured to be placed on the pipettor probe of the robotic pipettor.

[0040] According to some aspects of the disclosure, the second module further comprises a cap/vial tray configured to hold a plurality of processing vials and/or associated caps. Each cap is configured to be coupled to an associated vial to close the associated vial. The vials are accessible by the robotic pipettor to dispense processing material into the vials, and the associated caps are accessible by the robotic pipettor to move each cap into an associated vial to form a cap/vial assembly. The robotic pipettor is configured to move the cap/vial assembly from the cap/vial tray to another location on the second module.

[0041] According to some aspects of the disclosure, the second module further comprises a centrifuge, wherein the robotic pipettor is configured to move a cap/vial assembly from the cap/vial tray to the centrifuge.

[0042] According to some aspects of the disclosure, the second module further comprises a thermal cycler configured to hold a plurality of cap/vial assemblies and to subject the contents of the plurality of cap/vial assemblies to cyclically varying temperatures and a robotic vial transfer arm configured to move a cap/vial assembly from the centrifuge to the thermal cycler.

[0043] According to some aspects of the disclosure, the second module further comprises one or more magnetic receptacle holding slots configured to hold a receptacle transferred from the first module to the second module. Each magnetic receptacle holding slot comprises a magnet and is configured to draw magnetic particles contained within the receptacle to a wall of the receptacle and out of solution within the fluid contents of the receptacle.

[0044] According to some aspects of the disclosure, the first module and the second module are configured to conduct nucleic acid amplification reactions.

[0045] According to some aspects of the disclosure, the nucleic acid amplification reactions conducted in the first module and the second module are different types of amplification reactions.

[0046] According to some aspects of the disclosure, the nucleic acid amplification reaction conducted in the first module comprises a qualitatively monitored reaction and the nucleic acid amplification reaction conducted in the second module comprises a quantitatively monitored reaction.

[0047] According to some aspects of the disclosure, the nucleic acid amplification reaction conducted in the second module comprises a reaction monitored in real-time.

[0048] According to some aspects of the disclosure, wherein the nucleic acid amplification reaction conducted in the first module is an isothermal reaction, and the nucleic acid amplification reaction conducted in the second module comprises the use of a polymerase chain reaction.

[0049] Aspects of the disclosure are further embodied in an automated system capable of performing multiple molecular assays on a single sample. The system comprises a sample input portal configured to accept samples contained in one or more receptacles, a sample preparation module configured to prepare a sample provided to the sample input portal for a nucleic acid amplification reaction, a first module configured to conduct an isothermal nucleic acid amplification assay with the sample, a second module configured to conduct a nucleic acid amplification assay involving temperature cycling with the sample, and a transport mechanism configured to effect automated transport of one or more receptacles containing the sample between the sample input portal, the sample preparation module, the first module, and the second module.

[0050] According to some aspects of the disclosure, the automated system further comprises a



substance transfer device configured to access the sample when present in the sample second module, the first module, or the second module.

[0051] According to some aspects of the disclosure, the system further comprises a reagent storage compartment configured to hold a plurality of reagent containers, wherein the reagent storage compartment is held at a temperature below ambient temperature.

[0052] According to some aspects of the disclosure, the system further comprises a reagent container transport mechanism configured to transport one or more reagent containers between the reagent storage compartment and a separate location within the second module.

[0053] According to some aspects of the disclosure, the reagent container transport mechanism is configured to transport the reagent containers within the second module and to transport the receptacles within the second module.

[0054] Some aspects of the disclosure are embodied in a method for improved thermal cycling of low volume nucleic acid amplification reaction mixtures. The method comprises combining a fluid sample together with one or more amplification reaction reagents in a reaction receptacle using an automated pipettor, transporting the reaction receptacle to a centrifuge using the automated pipettor, centrifuging the fluid contents of the reaction receptacle, automatically removing the reaction receptacle from the centrifuge after centrifugation and placing the reaction receptacle in a thermal cycler, and subjecting the fluid contents of the reaction receptacle to one or more temperature cycles within the thermal cycler.

[0055] According to some aspects of the disclosure, the reaction receptacle is removed from the centrifuge and transported to the thermal cycler using the vial transfer arm.

[0056] According to some aspects of the disclosure, the reaction receptacle is placed in the centrifuge at a first location, and the reaction receptacle is removed from the centrifuge at a second, different location.

[0057] According to some aspects of the disclosure, the method further comprises a second automated pipettor, and the second automated pipettor automatically removes the reaction receptacle from the centrifuge after centrifugation and places the reaction receptacle in the thermal cycler.

[0058] According to some aspects of the disclosure, the receptacle is sealed by a cap before transporting the sealed receptacle to the centrifuge.

[0059] According to some aspects of the disclosure, the automated pipettor transports the cap to the receptacle and seals the receptacle by coupling the cap to the receptacle.

[0060] Some aspects of the disclosure are embodied in an improved method of preparing multiple different nucleic acid reaction mixtures within the workflow of an automated molecular instrument. The method comprises providing two or more reaction receptacles, providing two or more unit dose reagent containers, each unit dose reagent container corresponding to a respective reaction receptacle, and each unit dose reagent container containing a nucleic acid amplification reagent that is specific for one or more target nucleic acids, providing a receptacle containing a first bulk reagent, and combining at least a portion of the sample with at least a portion of the unit dose reagent and at least a portion of the bulk reagent in each of the two or more reaction receptacles. After combination, each reaction receptacle contains a different sample, a different unit dose reagent, and the same first bulk reagent.

[0061] According to further aspects of the disclosure, the method further comprises a receptacle containing a second bulk reagent, wherein the second bulk reagent is dispensed into each of the two or more unit dose reagent containers before combining at least a portion of the sample with at least a portion of the unit dose reagent and at least a portion of the bulk reagent in each of the two or more reaction receptacles.

[0062] According to some aspects of the disclosure, the second bulk reagent comprises a reconstitution reagent.

[0063] According to some aspects of the disclosure, the method further comprises transporting each

of the two or more reaction receptacles to a heater, such as a heated incubator or a heating plate, to conduct a nucleic acid amplification assay.

[0064] Other features and characteristics of the present disclosure, as well as the methods of operation, functions of related elements of structure and the combination of parts, and economies of manufacture, will become more apparent upon consideration of the following description and the appended claims with reference to the accompanying drawings, all of which form a part of this specification, wherein like reference numerals designate corresponding parts in the various figures.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0065] The accompanying drawings, which are incorporated herein and form part of the specification, illustrate various, non-limiting embodiments of the present disclosure. In the drawings, common reference numbers indicate identical or functionally similar elements.

[0066] FIG. 1 is a perspective view of a diagnostic system comprising a first module and a second module according to an embodiment.

[0067] FIG. 2 is a perspective view of a multiple receptacle device (“MRD”) according to an embodiment.

[0068] FIG. 3 is a partial bottom view of the MRD of FIG. 2.

[0069] FIG. 4 is a top plan view of a first module of a diagnostic system according to an embodiment.

[0070] FIG. 5 is an exploded, top plan view of the first module and the second module according to an embodiment.

[0071] FIG. 6 is a top plan view of an amplification processing deck of the second module according to an embodiment.

[0072] FIG. 7 is a partial, front perspective view of the second module with a bulk reagent container compartment in an open position according to an embodiment.

[0073] FIG. 8 is a partial, top plan view of the second module and first module showing the bulk reagent container compartment in a closed position according to an embodiment.

[0074] FIG. 9 is a top perspective view of the bulk reagent container compartment and bulk reagent container transport of the second module, with the bulk reagent container compartment in an open position according to an embodiment.

[0075] FIG. 10 is a top perspective view of the bulk reagent container compartment and bulk reagent container transport of the second module, with the bulk reagent container compartment in a closed position and elution containers transported to an end of the bulk reagent container transport according to an embodiment.

[0076] FIG. 11 is a partial cross-sectional view of bulk reagent container compartment, with the bulk reagent container compartment in an open position according to an embodiment.

[0077] FIG. 12 is a partial cross-sectional view of bulk reagent container compartment and the bulk reagent container transport, with the bulk reagent container compartment in a closed position according to an embodiment.

[0078] FIG. 13 is a partial end view of bulk reagent container compartment, with the bulk reagent container compartment in a closed position according to an embodiment.

[0079] FIG. 14 is a top perspective view of a receptacle processing deck of the second module according to an embodiment.

[0080] FIG. 15 is a partial, front perspective view of the second module with a carousel compartment of a reagent pack changer in an open position according to an embodiment.

[0081] FIG. 16 is a partial, top perspective view of the pack carousel compartment according to an embodiment.

[0082] FIG. **17** is a partial, side perspective view of the pack carousel compartment according to an embodiment.

[0083] FIG. **18** is a cross-sectional, rear perspective view of an alternative embodiment of a reagent pack changer and a reagent pack storage compartment.

[0084] FIG. **19** is a top perspective view of a reagent pack embodying aspects of the present disclosure according to an embodiment.

[0085] FIG. **20** is a top perspective, cross-sectional view of a reagent pack along the line XX-XX in FIG. **19** according to an embodiment.

[0086] FIG. **21** is a perspective view of a robotic pipettor of the second module according to an embodiment.

[0087] FIG. **22** is a perspective view of a substance transfer pipettor of the robotic pipettor according to an embodiment.

[0088] FIG. **23** is an exploded, perspective view of a processing vial, a processing vial cap, and a pipettor probe according to an embodiment.

[0089] FIG. **24** is a transverse cross-section of the processing vial and the processing vial cap disposed within a processing vial well and a cap well, respectively, of a processing cap/vial compartment tray according to an embodiment.

[0090] FIG. **25** is a transverse cross-section of the processing vial cap removed from the cap well and inserted into the processing vial with the processing vial disposed within the processing vial well according to an embodiment.

[0091] FIG. **26** is an exploded, perspective view of an alternative embodiment of a processing vial, a processing vial cap, and a pipettor probe.

[0092] FIG. **27** is a top perspective view of an embodiment of a receptacle distribution module of the second module.

[0093] FIG. **28** is a bottom perspective view of the receptacle distribution module according to an embodiment.

[0094] FIG. **29** is a perspective view of an embodiment of a distributor head of a rotary distributor of the receptacle distribution module with a receptacle hook in a retracted position.

[0095] FIG. **30** is a perspective view of the distributor head with the receptacle hook in an extended position according to an embodiment.

[0096] FIG. **31** is an opposite side perspective view of the distributor head according to an embodiment.

[0097] FIG. **32** is a transverse cross-section of the rotary distributor with a reagent pack disposed therein according to an embodiment.

[0098] FIG. **33** is a transverse cross-section of the rotary distributor with an MRD disposed therein according to an embodiment.

[0099] FIG. **34** is a top front perspective view of an embodiment of a distributor moving system of the receptacle distribution module.

[0100] FIG. **35** is a top rear perspective view of the distributor moving system.

[0101] FIG. **36** is a top plan view of an embodiment of magnetic elution slots and reagent pack loading stations of the second module.

[0102] FIG. **37** is a front end perspective view of the magnetic elution slots and reagent pack loading stations according to an embodiment.

[0103] FIG. **38** is a back end perspective view of the magnetic elution slots and reagent pack loading stations according to an embodiment.

[0104] FIGS. **39** and **40** are perspective views of an embodiment of an MRD handoff device of the second module.

[0105] FIG. **41** is a flowchart illustrating the steps of a sample eluate preparation process according to an embodiment.

[0106] FIG. **42** is a flowchart illustrating the steps of a reaction mixture preparation process

according to an embodiment.

[0107] FIG. **43** is a flowchart illustrating the steps of a process for performing an automated nucleic acid amplification reaction, such as PCR, according to an embodiment.

[0108] FIG. **44** is a flowchart illustrating a method of using diagnostic system according to one such embodiment.

[0109] FIGS. **45-48** show a receptacle of the present disclosure. FIG. **45** is a side view of the receptacle. FIG. **46** is a cross-sectional view of the receptacle taken along a vertical axis of view shown in FIG. **45**. FIG. **47** is a top view of the receptacle. FIG. **48** is a perspective view of the receptacle.

[0110] FIGS. **49-54** show a cap of the present disclosure. FIG. **49** is a side view of the cap.

[0111] FIG. **50** is a cross-sectional view of the cap taken along a vertical axis of the view shown in FIG. **49**. FIG. **51** is a top view of the cap. FIG. **52** is a bottom view of the cap. FIGS. **53** and **54** are top and bottom perspective views of the cap.

[0112] FIG. **55** is a cross-sectional view of the cap secured to the receptacle, and insertion of an automated pipettor into the open end of the cap.

[0113] FIG. **56** shows an apparatus of the present disclosure.

[0114] FIG. **57** shows an apparatus of the present disclosure mounted in a housing.

[0115] FIGS. **58-60** show a receptacle holder of the present disclosure.

[0116] FIGS. **61** and **62** show a receptacle holder slidably mounted to a support. The support is mounted in thermal communication with a heat sink (FIG. **61**). A cross-brace may be mounted to the support to exert a force onto a front surface of the receptacle holder (FIG. **62**).

[0117] FIGS. **63-67** show exemplary covers and stripper plates disposed within the apparatus of the present disclosure.

[0118] FIG. **68** shows an exemplary embodiment of an apparatus of the present disclosure.

[0119] FIGS. **69-71** show a modified pipettor for use as a receptacle transport mechanism within a system of the present disclosure.

[0120] FIGS. **72-74** show an embodiment providing movement of the optical fibers of the apparatus of the present disclosure and the forces associated therewith prior to and after seating receptacles within the receptacle wells of a receptacle holder.

[0121] FIG. **75** shows an apparatus in optical communication with an excitation signal source and/or an emission signal detector within a housing of an instrument for performing a biochemical assay.

[0122] FIGS. **76** and **77** are flow charts showing exemplary steps involved in a method for establishing optical communication between a receptacle and an excitation signal source and/or an emission signal detector within a housing of the apparatus while allowing maximal contact between the surface of the receptacle well and the receptacle.

[0123] FIG. **78** is a perspective view of a signal detection module embodying aspects of the present disclosure.

[0124] FIG. **79** is a perspective view of a signal detector head.

[0125] FIG. **80** is a transverse cross-section of the signal detector head along the line XIII-XIII in FIG. **79**.

[0126] FIG. **81** is a schematic view of an embodiment of an exemplary optical path within a signal detector.

[0127] FIG. **82** is a schematic view of the signal detection module embodying aspects of the present disclosure and a power and data control system incorporated therewith.

#### DETAILED DESCRIPTION

[0128] Unless defined otherwise, all terms of art, notations and other scientific terms or terminology used herein have the same meaning as is commonly understood by one of ordinary skill in the art to which this disclosure belongs. Many of the techniques and procedures described or referenced herein are well understood and commonly employed using conventional

methodology by those skilled in the art. As appropriate, procedures involving the use of commercially available kits and reagents are generally carried out in accordance with manufacturer defined protocols and/or parameters unless otherwise noted. All patents, applications, published applications and other publications referred to herein are incorporated by reference in their entirety. If a definition set forth in this section is contrary to or otherwise inconsistent with a definition set forth in the patents, applications, published applications, and other publications that are herein incorporated by reference, the definition set forth in this section prevails over the definition that is incorporated herein by reference.

[0129] References in the specification to “one embodiment,” “an embodiment,” a “further embodiment,” “an example embodiment,” “some aspects,” “a further aspect,” “aspects,” etc., indicate that the embodiment described may include a particular feature, structure, or characteristic, but every embodiment may not necessarily include the particular feature, structure, or characteristic. Moreover, such phrases are not necessarily referring to the same embodiment. Further, when a particular feature, structure, or characteristic is described in connection with an embodiment, such feature, structure, or characteristic is also a description in connection with other embodiments whether or not explicitly described.

[0130] As used herein, “a” or “an” means “at least one” or “one or more.”

[0131] As used herein, “sample” refers to any substance suspected of containing a virus or organism of interest or, alternatively, nucleic acid derived from the virus or organism of interest, or any substance suspected to have a nucleic acid of interest, such as a nucleic acid suspected of having genetic abnormalities or mutations. The substance may be, for example, an unprocessed clinical specimen, such as a blood or genitourinary tract specimen, a buffered medium containing the specimen, a medium containing the specimen and lytic agents for releasing nucleic acid belonging to the virus or organism, or a medium containing nucleic acid derived from the virus or organism which has been isolated and/or purified in a reaction receptacle or on a reaction material or device. For this reason, the term “sample” will be understood to mean a specimen in its raw form or to any stage of processing to release, isolate and purify nucleic acid derived from the virus or organism. Thus, references to a “sample” may refer to a substance suspected of containing nucleic acid derived from a virus or organism at different stages of processing and is not limited to the initial form of the substance.

[0132] This description may use relative spatial and/or orientation terms in describing the position and/or orientation of a component, apparatus, location, feature, or a portion thereof. Unless specifically stated, or otherwise dictated by the context of the description, such terms, including, without limitation, top, bottom, above, below, under, on top of, upper, lower, left of, right of, inside, outside, inner, outer, proximal, distal, in front of, behind, next to, adjacent, between, horizontal, vertical, diagonal, longitudinal, transverse, etc., are used for convenience in referring to such component, apparatus, location, feature, or a portion thereof in the drawings and are not intended to be limiting.

[0133] The section headings used in the present application are merely intended to orient the reader to various aspects of the disclosed system. The section headings are not intended to limit the disclosed and claimed inventions. Similarly, the section headings are not intended to suggest that materials, features, aspects, methods, or procedures described in one section do not apply in another section. Therefore, descriptions of materials, features, aspects, methods or procedures described in one section are intended to apply to other sections.

#### Nucleic Acid Diagnostic Assays

[0134] Aspects of the present disclosure involve diagnostic systems and methods that can be used in conjunction with nucleic acid diagnostic assays, including “real-time” amplification assays and “end-point” amplification assays.

[0135] Real-time amplification assays can be used to determine the presence and amount of a target nucleic acid in a sample which, by way of example, is derived from a pathogenic organism (e.g.,

bacterium, fungus, or protozoan) or virus. Thus, real-time amplification assays are often referred to as quantitative assays. By determining the quantity of a target nucleic acid in a sample, a practitioner can approximate the amount or load of the organism or virus in the sample. In one application, a real-time amplification assay may be used to screen blood or blood products intended for transfusion for blood borne pathogens, such as hepatitis C virus (HCV) and human immunodeficiency virus (HIV). In another application, a real-time assay may be used to monitor the efficacy of a therapeutic regimen in a patient infected with a pathogenic organism or virus, or that is afflicted with a disease characterized by aberrant or mutant gene expression. Real-time amplification assays may also be used for diagnostic purposes, as well as in gene expression determinations. Exemplary systems and methods for performing real-time amplification assays are disclosed by Macioszek et al. in U.S. Pat. No. 7,897,337.

[0136] In addition to implementation of embodiments of the disclosure in conjunction with real-time amplification assays, embodiments of the disclosure may also be implemented in conjunction with end-point amplification assays. In end-point amplification assays, the presence of amplification products containing the target sequence or its complement is determined at the conclusion of an amplification procedure. Thus, end-point amplification assays are often referred to as qualitative assays in that such assays do not indicate the amount of a target analyte present, but provide a qualitative indication regarding the presence or absence of the target analyte. Exemplary systems and methods for end-point detection are disclosed by Ammann et al. in U.S. Pat. No. 6,335,166. The determination may occur in a detection station that is integral with or at an external location relative to the incubator(s) in which the amplification reactions occur. In contrast, in “real-time” amplification assays, the amount of amplification products containing the target sequence or its complement is determined during an amplification procedure. In a real-time amplification assay, the concentration of a target nucleic acid can be determined using data acquired by making periodic measurements of signals that are a function of the amount of amplification product in the sample containing the target sequence or its complement, and calculating the rate at which the target sequence is being amplified from the acquired data. An example of such a real-time amplification assay is described by Light et al. in U.S. Pat. No. 8,615,368.

[0137] In an exemplary real-time amplification assay, the interacting labels include a fluorescent moiety, or other emission moiety, and a quencher moiety, such as, for example, 4-(4-dimethylaminophenylazo) benzoic acid (DABCYL). The fluorescent moiety emits light energy (i.e., fluoresces) at a specific emission wavelength when excited by light energy at an appropriate excitation wavelength. When the fluorescent moiety and the quencher moiety are held in close proximity, light energy emitted by the fluorescent moiety is absorbed by the quencher moiety. But when a probe hybridizes to a nucleic acid present in the sample, the fluorescent and quencher moieties are separated from each other and light energy emitted by the fluorescent moiety can be detected. Fluorescent moieties having different and distinguishable excitation and emission wavelengths are often combined with different probes. The different probes can be added to a sample, and the presence and amount of target nucleic acids associated with each probe can be determined by alternately exposing the sample to light energy at different excitation wavelengths and measuring the light emission from the sample at the different wavelengths corresponding to the different fluorescent moieties. In another embodiment, different fluorescent moieties having the same excitation wavelength, but different and distinguishable emission wavelengths are combined with different probes. The presence and amount of target nucleic acids associated with each probe can be determined by exposing the sample to a specific wavelength of light energy and the light emission from the sample at the different wavelengths corresponding to the different fluorescent moieties is measured.

[0138] A variety of different labeled probes and probing mechanisms are known in the art, including those where the probe does not hybridize to the target sequence. See, e.g., Brow et al. in U.S. Pat. No. 5,846,717 and Chun et al. in U.S. Patent Application Publication No. 2013/0109588.

Some embodiments of the present disclosure operate regardless of the particular labeling scheme utilized, provided the moiety to be detected can be excited by a particular wavelength of light and emits a distinguishable emission spectra.

[0139] Where a nucleic acid amplification reaction is used to increase the amount of target sequence and/or its complement present in a sample before detection, it is desirable to include a “control” to ensure that amplification has taken place. See, for example, the amplification controls described by Wang in U.S. Pat. No. 5,476,774. Such a control can be a known nucleic acid sequence that is unrelated to the sequence(s) of interest. A probe (i.e., a control probe) having specificity for the control sequence and having a unique fluorescent dye (i.e., the control dye) and quencher combination is added to the sample, along with one or more amplification reagents needed to amplify the control sequence, as well as the target sequence(s). After exposing the sample to appropriate amplification conditions, the sample is alternately exposed to light energy at different excitation wavelengths (including the excitation wavelength for the control dye) and emission light is detected. Detection of emission light of a wavelength corresponding to the control dye confirms that the amplification was successful (i.e., the control sequence was indeed amplified), and thus, any failure to detect emission light corresponding to the probe(s) of the target sequence(s) is not likely due to a failed amplification. Conversely, failure to detect emission light from the control dye may be indicative of a failed amplification, thus calling into question the results from that assay. Alternatively, failure to detect emission light may be due to failure or deteriorated mechanical and/or electrical performance of an instrument for detecting the emission light.

[0140] In some embodiments, the assays performed in accordance with the description herein capture, amplify, and detect nucleic acids from target organisms in patient samples employing technologies, such as target capture, reverse transcription, and real-time polymerase chain reaction. The combination of reverse transcription and PCR is abbreviated as “RT-PCR.” The following is a generalized assay processing description of the different technologies that may be implemented in accordance with aspects of the disclosure.

[0141] The target capture process isolates nucleic acid of the target (e.g., virus, bacterium, fungus, protozoan, mammalian cells, etc.) and purifies nucleic acid for amplification. The target organism, which can be in a variety of biological matrices from urine to blood, can be lysed by target capture reagents (“TCR”), whereby the nucleic acid is released. In one approach, capture oligonucleotide probes hybridize to a target nucleic acid. The capture probe/target nucleic acid complexes attach to magnetic particles in the TCR through nucleic acid hybridization. Exemplary disclosures for performing these methods are provided by U.S. Pat. Nos. 6,140,678, 5,234,809, 5,693,785, and 5,973,138, and EP Patent No. 0 389 063. The magnetic particles are pulled to the side of a container and isolated by a magnet, and potential inhibitory substances are washed away (multiple wash cycles may be performed) to thereby provide a target nucleic acid. Hogan et al. provide an exemplary disclosure of this protocol in U.S. Pat. No. 7,172,863. See also International Publication No. WO 2003/097808 by Fort et al. If the target capture process is specific for the target nucleic acid, then it is the target nucleic acid that will primarily remain after the purification step. As a result, target capture enables the enrichment of a variety of sample types and significantly reduces the inhibition rate and can increase assay sensitivity. Exemplary methods of target nucleic acid capture are disclosed by, for example, Boom et al. in U.S. Pat. No. 5,234,864, Hawkins in U.S. Pat. No. 5,705,628, Collins et al. in U.S. Pat. No. 5,750,338, and Weisburg et al. in U.S. Pat. No. 6,534,273.

[0142] After completing the target capture process, the magnetic particles on which the target nucleic acid is immobilized are re-suspended, for example, with 20-60  $\mu$ L of a wash solution comprising a low salt buffer or water. This will de-hybridize the target nucleic acid from the magnetic particles and, in the presence of a strong magnet, allow 5-50  $\mu$ L of purified nucleic acid to be recovered as input into the amplification process.

[0143] Reverse transcription and PCR can be optimized to run in a single receptacle using common reagents as a one-step process. This method provides a sensitive means to detect low-abundance RNAs, and, although the method is not necessarily quantitative, specific controls can be included in the experiment if quantitative results are desired. (A reverse-transcription step is not required if the target nucleic acid is DNA.) In an exemplary implementation, before performing the real-time PCR reaction, RNAs are incubated with a retroviral enzyme (reverse transcriptase) under oil at 42° C. for approximately 30 minutes. This process creates a single-stranded DNA copy of the RNA target sequence. If the goal is to copy all RNAs present in the source material into DNA, non-specific primers or primer sets are used. In the case of mRNA, which has a polyadenylated (poly A) tail, an oligo dT primer can be used. Alternatively, a collection of randomized hexanucleotide primers can be used to ensure a primer will be present that is complementary to each of the messages. If only one RNA target is sought, a sequence-specific primer complementary to the 3' end of the desired amplification product is used. RNase H is used to degrade the RNA molecule contained in the hybrid RNA-DNA duplex, so that the DNA strand is available to direct second-strand synthesis. Single-stranded DNA thus generated can serve as the template for PCR using sequence-specific primers to amplify the region of interest.

[0144] The polymerase is inactive at low temperatures and can be heat activated at 95° C. for several minutes (for example, approximately 10 minutes) before beginning PCR. Both reactions occur inside a thermal cycler (i.e., a module configured to expose the contents of the receptacle to temperatures that are cycled between two or more different temperatures), but real-time PCR requires accurate/rapid thermal cycling between denaturation (~95° C.), annealing (~55° C.), and synthesis (~72° C.) temperatures. Fluorescence monitoring occurs at one or many color wavelengths-relating to one or many probes adapted to detect one or many target analytes-during each cycle or at another predetermined interval. PCR components may include, for example, the forward and reverse primers and a fluorogenic probe containing a reporter fluorescent dye on 5' end and a quencher dye on 3' end. (See, e.g., Holland et al., Proc. Natl. Acad. Sci. USA, 88 (16): 7276-7280 (1991).) During PCR, nucleic acid primers hybridize to opposite strands of the target nucleic acid and are oriented with their 3' ends facing each other so that synthesis by a nucleic acid polymerization enzyme, such as a DNA polymerase, extends across the segment of the nucleic acid between them. While the probe is intact, the proximity of the quencher dye to the reporter dye greatly reduces the fluorescence emitted by the reporter dye. During amplification if the target nucleic acid is present, the fluorogenic probe anneals downstream from one of the primer sites and is cleaved by 5' nuclease activity of the polymerization enzyme during primer extension. The cleavage of the probe separates the reporter dye from the quencher dye, thus rendering detectable the reporter dye signal and removing the probe from the target strand, allowing primer extension to continue to the end of the template strand.

[0145] One round of PCR synthesis will result in new strands of indeterminate length which, like the parental strands, can hybridize to the primers upon denaturation and annealing. These products accumulate arithmetically with each subsequence cycle of denaturation, annealing to primers, and synthesis. The second cycle of denaturation, annealing, and synthesis produces two single-stranded products that together compose a discrete double-stranded product which is exactly the length between the primer ends. Each strand of this discrete product is complementary to one of the two primers and can therefore participate as a template in subsequent cycles. The amount of this product doubles with every subsequent cycle of synthesis, denaturation and annealing. This accumulates exponentially so that 30 cycles should result in a 2<sup>sup.28</sup>-fold (270 million-fold) amplification of the discrete product.

#### Multiple Receptacle Devices

[0146] FIG. 2 illustrates one embodiment of MRD **160** that comprises a plurality of individual receptacles, or tubes, **162**, preferably five. The receptacles **162** are formed to have open top ends and closed bottom ends (preferably in the form of cylindrical tubes), and are connected to one



another by a connecting rib structure **164** which defines a downwardly facing shoulder extending longitudinally along either side of the MRD **160**.

[0147] Alternatively, the receptacle may be any container suitable for holding a fluid or liquid, including, for example, a cuvette, vial, beaker, well of a microtiter plate, test tube, and in some embodiments, a pipette tip. Unless explicitly stated or the context dictates otherwise, descriptions of an MRD or receptacle of an MRD are exemplary and should not be construed as limiting of the scope of the disclosure, as aspects of the disclosure are applicable to any suitable “receptacle.”

[0148] The MRD **160** in certain embodiments is formed from injection molded polypropylene, such as those sold by Montell Polyolefins, of Wilmington, Delaware, product number PD701NW or Huntsman, product number P5M6K-048. In an alternative embodiment, the receptacles **162** of the MRD are releasably fixed with respect to each other by means such as, for example, a sample tube rack or other holding structure.

[0149] An arcuate shield structure **169** can be provided at one end of the MRD **160**. An MRD manipulating structure **166** extends from the shield structure **169**. In certain embodiments, the manipulating structure **166** is configured to be engaged by an extendible and retractable hook of a receptacle distributor or a transport mechanism for moving the MRD **160** between different components of a first module of a diagnostic system. An exemplary transport mechanism that is compatible with the MRD **160** is disclosed by Ammann et al. in U.S. Pat. No. 6,335,166. The transport mechanism, in certain embodiments, engages the manipulating structure **166** from the underside of the manipulating structure as shown with arrow **60**. In certain embodiments, the MRD manipulating structure **166** comprises a laterally extending plate **168** extending from shield structure **169** with a vertically extending piece **167** on the opposite end of the plate **168**. A gusset wall **165** can extend downwardly from lateral plate **168** between shield structure **169** and vertical piece **167**.

[0150] As shown in FIG. 3, the shield structure **169** and vertical piece **167** have mutually facing convex surfaces. This, however, is just one way that the shield structure **169** and vertical piece **167** can be configured. The MRD **160** may be engaged by a receptacle distributor, a transport mechanism, and other components, by moving an engaging member, such as an extendible and retractable hook, laterally (in the direction “A”) into the space between the shield structure **169** and the vertical piece **167**. The convex surfaces of the shield structure **169** and vertical piece **167** provide for wider points of entry for an engaging member undergoing a lateral relative motion into the space between the shield structure **169** and the vertical piece **167**. Of course, as the engaging member is robotically controlled, it is understood that the convex surfaces are merely a design choice of the present embodiment and that other shaped surfaces are contemplated.

[0151] A label-receiving structure **174** having a flat label-receiving surface **175** can be provided on an end of the MRD **160** opposite the shield structure **169** and MRD manipulating structure **166**. Human and/or machine-readable labels, such as scannable bar codes, can be placed on the surface **175** to provide identifying and instructional information on the MRD **160**.

[0152] Further details regarding a representative MRD **160** are disclosed by Horner et al. in U.S. Pat. No. 6,086,827.

#### Diagnostic System

[0153] FIG. 1 illustrates a diagnostic system **10** according to an embodiment. Diagnostic system **10** can be configured to perform a plurality of different molecular assays on a plurality of samples. In some embodiments, diagnostic system **10** can be configured to perform different target nucleic acid amplification reactions. For example, diagnostic system **10** can be configured to perform a first target nucleic acid amplification reaction on a first subset of a plurality of samples, and perform a second, different target nucleic acid amplification reaction on a second subset of the plurality of samples.

[0154] In some embodiments, diagnostic system **10** comprises a first module **100** configured to perform at least one of the steps of a first target nucleic acid amplification reaction, and a second

module **400** configured to perform at least one of the steps of a second target nucleic acid amplification.

[0155] In some embodiments, diagnostic system **10** is an integral, self-contained structure—first module **100** cannot be selectively coupled to and decoupled from second module **400**.

[0156] In some embodiments, diagnostic system **10** is configured such that first module **100** can be selectively and operatively coupled to second module **400**, and first module **100** can be selectively decoupled from second module **400**. In some embodiments, first module **100** can be selectively coupled to second module **400** using, for example, mechanical fasteners (for example, bolts or screws), clamps, any combination thereof, or any other suitable attachment device. In some embodiments, suitable power and/or data lines are provided between the second module **400** and the first module **100**. For example, in embodiments in which first module **100** can be selectively coupled to second module **400**, second module **400** can extend the overall system capabilities of a diagnostic system including only first module **100** that was previously purchased by a customer.

[0157] The configurations and functions of first module **100** and second module **400** according to various embodiments are described below.

#### First Module

[0158] A first module **100** in which embodiments of the present disclosure may be implemented is shown schematically in plan view and designated by reference number **100** in FIG. **4**. The first module **100** includes various devices configured to receive one or more reaction receptacles (described in more detail below), within each of which is performed one or more steps of a multi-step nucleic acid test (NAT) designed to detect a virus or organism (e.g., bacterium, fungus, or protozoan). First module **100** can include receptacle-receiving components configured to receive and hold one or more reaction receptacles and, in some instances, to perform processes on the contents of the receptacles. Exemplary processes include, but are not limited to, adding substances such as sample fluid, reagents (e.g., target capture reagents, amplification reagents, buffers, oils, labels, probes, or any other reagent) and/or removing substances from a reaction receptacle; agitating a receptacle to mix the contents thereof; maintaining and/or altering the temperature of the contents of a reaction receptacle; heating or chilling the contents of a reaction receptacle; altering the concentration of one or more components of the contents of a reaction receptacle; separating or isolating constituent components of the contents of a reaction receptacle; detecting an electromagnetic signal emission (e.g., light) from the contents of a reaction receptacle; deactivating or halting an on-going reaction; or any combination of two or more of such processes.

[0159] In some embodiments, the first module **100** may include a receptacle input device **102** that includes structure for receiving and holding one or more empty reaction receptacles before the receptacles are used for performing one or more process steps of a NAT. The receptacle input device **102** may comprise a compartment, for example, a drawer or cabinet, that may be opened and loaded with a plurality of receptacles and may include a receptacle feeding device for moving receptacles, for example, one or more at a time, into a receptacle pick-up position. In some embodiments, the receptacle pick-up position comprises a registered or known position of the receptacle to facilitate removal of the receptacle by a receptacle distributor.

[0160] In some embodiments, the first module **100** may further include one or more bulk reagent container compartments configured to store one or more bulk containers that hold bulk reagents or hold waste material. In some embodiments, the bulk reagents include fluids such as water, buffer solution, target capture reagents, nucleic acid amplification reagents. In some embodiments, the bulk reagent container compartments may be configured to maintain the contents of such containers at prescribed storage temperatures and/or to agitate such containers to maintain the contents of the containers in solution or suspension.

[0161] In some embodiments, first module **100** comprises a first bulk reagent container compartment configured to store at least one bulk container that holds a nucleic acid amplification reagent, for example, a reagent for performing TMA, and a separate second bulk reagent container

compartment configured to store at least one bulk container that holds a sample preparation reagent, for example, a target capture reagent. In some embodiments, first module **100** comprises a bulk reagent container compartment that stores both a bulk container that holds a nucleic acid amplification reagent and a bulk container that holds a sample preparation reagent, for example, a target capture reagent. In some embodiments, a bulk reagent container compartment that is configured to store at least one bulk container can be a compartment that houses a mixer, for example, an orbital mixer, that is configured to carry a container holding a sample preparation reagent, for example, a target capture reagent. In some embodiments, the one or more bulk container compartments can comprise a holding structure for carrying and agitating containers (e.g., containers of TCR with magnetically-responsive solid supports). Buse et al. in U.S. Provisional Application No. 61/783,670, "Apparatus for Indexing and Agitating Fluid Containers," filed Mar. 14, 2013, which enjoys common ownership herewith, discloses an exemplary holding structure. In some embodiments, one or more bulk container compartments comprise a slidable tray that defines at least one recess configured to closely receive respective bulk containers.

[0162] In some embodiments, one or more of the bulk reagent container compartments of first module **100** can be configured to store at least two containers containing sample preparation reagents, for example, target capture reagents. In some embodiments, each target capture reagent is specific for a particular assay type (i.e., target nucleic acid), the type of nucleic acid (e.g., RNA or DNA), and/or the sample type (e.g., stool, urine, blood, etc.). For example, the target capture reagents can comprise probes having a region specific for the target nucleic acid. See, e.g. Weisburg et al. in U.S. Pat. No. 6,534,273.

[0163] The first module **100** may further include a sample loading device configured to receive and hold containers, such as test tubes, containing samples. The first module **100** may also include one or more substance transfer devices for transferring fluids, for example, sample fluids, reagents, bulk fluids, waste fluids, etc., to and from reaction receptacles and/or other containers. In some embodiments, the substance transfer devices may comprise one or more robotic pipettors configured for controlled, automated movement and access to the reaction receptacles, bulk containers holding reagents, and containers holding samples. In some embodiments, the substance transfer devices may also include fluid dispensers, for example, nozzles, disposed within other devices and connected by suitable fluid conduits to containers, for example, bulk containers holding the reagents, and to pumps or other devices for causing fluid movement from the containers to the dispensers.

[0164] In some embodiments, the first module **100** may further include a plurality of load stations, such as load stations **104**, **106**, **108** depicted in FIG. 4, which are configured to receive racks and other forms of holders for carrying sample receptacles and various reagent containers that can be accessed by a substance transfer device. Examples of a load station and receptacle holder that can be used with embodiments are illustrated and described by Clark et al. in U.S. Pat. No. 8,309,036. In an embodiment where the first module **100** comprises a platform for performing a NAT, reaction reagents may comprise target capture reagents, lysis reagents, nucleic acid amplification reagents (e.g., the polymerases and nucleoside triphosphates needed for amplification), and/or nucleic acid detection reagents, such as detectable probes or intercalating dyes.

[0165] In some embodiments, the first module **100** may further comprise temperature ramping stations **110** configured to hold one or more reaction receptacles in an environment that is maintained at higher than ambient temperatures so as to raise the temperature of the contents of the receptacles. Exemplary temperature ramping stations are disclosed by Ammann et al. in U.S. Pat. No. 8,192,992.

[0166] In some embodiments, the first module **100** may further include one or more heater modules. The illustrated first module **100** includes three heated incubators **112**, **114**, **116**, each of which is configured to receive a plurality of reaction receptacles and maintain the receptacles in an elevated temperature environment. Exemplary incubators are disclosed by Macioszek et al. in U.S.

Pat. No. 7,964,413 and Heinz et al. in U.S. Patent Application Publication No. 2012/0221252. A heater module may alternatively be a heating plate. In certain embodiments, it is possible to have a heater module configured with one or more heated incubators and one or more heating plates. [0167] Also, in an embodiment in which the first module **100** comprises a platform for performing a NAT, the first module may include sample-processing components, such as magnetic separation wash stations **118**, **120**, adapted to separate or isolate a target nucleic acid immobilized on a magnetically-responsive solid support from the remaining contents of the receptacle. Exemplary magnetic separation wash stations are disclosed by Hagen et al. in U.S. Patent Application Publication No. 2010/0288395 and Ammann et al. in U.S. Pat. No. 6,605,213.

[0168] Although not exemplified in the plan drawings of first module **100**, the first module **100** may comprise one or more substance transfer devices, for example, robotic pipettors, in some embodiments. FIG. **21**, which is a perspective view of the robotic pipettor of the second module **400**, exemplifies at least one way to configure a substance transfer device for the first module **100**.

[0169] In some embodiments, the first module **100** may further include chiller modules **122** adapted to receive one or more reaction receptacles and hold the receptacles in a lower than ambient temperature environment so as to reduce the temperature of the contents of the receptacles.

[0170] And in some embodiments, the first module **100** may include a detector **124** configured to receive a reaction receptacle and detect a signal (e.g., an optical signal) emitted by the contents of the reaction receptacle. In one implementation, detector **124** may comprise a luminometer for detecting luminescent signals emitted by the contents of a receptacle and/or a fluorometer for detecting fluorescent emissions. The first module **100** may also include one or more signal detecting devices, such as fluorometers, coupled to one or more of the incubators **112**, **114**, **116** and which are configured and controlled to detect, preferably at specified, periodic intervals, signals emitted by the contents of the receptacles contained in the incubator while a process, such as nucleic acid amplification, is occurring within the reaction receptacles. An exemplary luminometer and an exemplary fluorometer are disclosed by Macioszek et al. in U.S. Pat. No. 7,964,413 and another exemplary fluorometer is disclosed by Heinz et al. in U.S. Patent Application Publication No. 2012/0221252.

[0171] The first module **100** further includes a receptacle transfer device, which, in the illustrated embodiment, comprises a receptacle distributor **150**. The components of first module **100**, for example, incubators **112**, **114**, **116**, load stations **104**, **106**, **108**, temperature ramping stations **110**, wash stations **118**, **120**, and chiller modules **122**, can also include a receptacle transfer portal through which receptacles can be inserted into or removed from the respective components. Each component may or may not include an openable door covering its receptacle portal. The receptacle distributor **150** is configured to move receptacles between the various components and retrieve receptacles from the components and deposit receptacles into the components. In one exemplary embodiment, the receptacle distributor **150** includes a receptacle distribution head **152** configured to move in an X direction along a transport track assembly **154**, rotate in a theta ( $\Theta$ ) direction, and move receptacles in an R direction into and out of the receptacle distribution head **152** and one of the components of first module **100**. An exemplary receptacle distributor is disclosed by Hagen et al. in U.S. Patent Application Publication No. 2012/0128451.

## Second Module

[0172] Aspects of the disclosure are embodied in a second module **400** a diagnostic system. In some embodiments, the second module **400** is integral with the first module **100**, and in other embodiments, the second module **400** may be selectively and operatively coupled to the first module **100** as described above. In some embodiments, the first module **100** to which the second module **400** can be operatively coupled include, for example, molecular instruments, such as the Panther® instrument system available from Hologic, Inc.

[0173] In one exemplary embodiment, the second module **400** is configured to perform nucleic acid amplification reactions, for example, PCR, and, in certain embodiments, to measure

fluorescence in real-time (i.e., as the amplification reaction is occurring). A controller directs the components of the first module **100** and components of the second module **400** to perform the assay steps. In one exemplary embodiment, the first module **100** houses a computer and all fluids, reagents, consumables, and mechanical modules needed to perform the specified amplification-based assays, such as assays based on transcription-based amplification methods, for example, TMA or nucleic acid sequence-based amplification (NASBA). (TMA methods are described by Kacian et al. in U.S. Pat. Nos. 5,399,491 and 5,480,784; and NASBA methods are described by Davey et al. in U.S. Pat. No. 5,409,818 and Malek et al. in U.S. Pat. No. 5,130,238.) As explained above, the controller may comprise a computer and preferably can accommodate LIS (“laboratory information system”) connectivity and as well as remote user access. In some embodiments, second module **400** houses component modules that enable second amplification assays, melting analyses, and optionally additional functionalities. Other components may include a printer and an optional uninterruptible power supply.

[0174] Embodiments of the general configuration of the second module **400** are shown in FIGS. **1**, **5**, **6**, and **14**. FIG. **1** is a perspective view of diagnostic system **10** comprising a second module **400** and the first module **100**. FIG. **5** is a top plan view of the second module **400** separated from the first module **100**. FIG. **6** is a top plan view of an amplification processing deck **430**, for example, a deck containing components for performing PCR, of the second module **400**. FIG. **14** is a top plan view of a receptacle processing deck **600** of the second module **400**. Referring to FIGS. **1**, **5**, **6**, and **14**, the component of the second module **400** can include, for example, a substance transfer device (for example, a robotic pipettor **402**), a thermal cycler/signal detector **432**, tip compartments **580** (e.g., two or more) configured to contain trays of disposable tips for the pipettor(s), processing cap/vial compartments **440** (e.g., two or more) configured to contain trays of disposable processing vials and associated caps, a bulk reagent container compartment **500**, a bulk reagent container transport **550**, a receptacle distribution system comprising a receptacle handoff device **602** and a receptacle distributor **312**, which, in the exemplary embodiment shown, comprises a rotary distributor, MRD storage units **608**, **610**, **612** configured to store MRDs **160**, magnetic elution slots **620** (e.g., two or more), a waste bin access door **652**, a waste bin **652**, a centrifuge **588**, a reagent pack changer **700**, reagent pack loading stations (e.g., two or more) **640**, and a compartment **590** configured to store accessories, including, for example, consumables, output cards, and/or post-processing cap/vial assemblies.

[0175] As shown in FIG. **1**, the components may be positioned on different levels, or decks, arranged vertically through the module **400**. In some embodiments, the substance transfer and handling device **402** can be a robotic pipettor **402** as shown in FIG. **1**. The robotic pipettor **402** is disposed near the top of the second module **400**, above all other components, in some embodiments. The depicted configurations represent only a single embodiment. The vertical order of the decks and components may vary according to the intended use of diagnostic system **10**. In the depicted embodiment, below the robotic pipettor **402**, the amplification processing deck **430** includes the bulk reagent container compartment **500** and bulk reagent container transport **520**, the centrifuge **588**, the top of the thermal cycler/signal detector **432**, the tip compartments **580**, and the processing cap/vial compartments **440**. Below the amplification processing deck **430**, the receptacle processing deck **600** includes the receptacle handoff device **602**, the rotary distributor **312**, the MRD storage units **608**, **610**, **612**, the magnetic elution slots **620**, the reagent pack changer **700**, and the reagent pack loading stations **640**. As can be seen in FIG. **6**, the magnetic elution slots **620** and the reagent pack loading stations **640** on the receptacle processing deck **600** are accessible by the robotic pipettor **402** through a gap between modules of the amplification processing deck **430**.

[0176] The receptacle distribution system comprising the receptacle handoff device **602** and the rotary distributor **312**, is configured to receive a receptacle or group of receptacles (e.g., MRD **160**) from the receptacle transfer device (e.g., the receptacle distributor **150**) of the first module **100** and

transfer the receptacle to the second module **400** and configured to move the receptacle into different positions in the second module **400**. The rotary distributor **312** and the receptacle handoff device **602** are shown schematically in FIG. **14**. Further details regarding these components are described below.

[0177] In some embodiments, the second module **400** is operatively positioned adjacent to the first module **100**, with the bulk reagent container transport **550** extending into the first module **100** so that elution containers **502**, **504** can be transported by the bulk reagent container transport **550** from the bulk reagent container compartment **500** to a position in the first module **100** at which a substance transfer device, for example, a robotic pipettor, in the first module **100** can access the containers **502**, **504**.

[0178] In some embodiments, the second module **400** is generally self-supporting relative to first module **100** such that the second-module/first-module assembly is not over-constrained. Thus, in some embodiments, the second module **400** does not include any feet that contact the ground beneath the second module and support some or all of the weight of the module. In some embodiments, if the second module **400** includes its own rigid feet (e.g., two, three, or four feet), the feet of the first module **100** and the feet of the second module **400** could create an over-constrained geometry. In this case, one would carefully level all feet of the second module **400** and the first module **100** relative to each other to ensure that the assembly is level and that excessive stresses are not applied to attachment points between the second module **400** and the first module **100**. To avoid such a potentially over-constrained geometry, the second module **400**, in some embodiments, is cantilevered off the first module **100** if the first module feet can support the additional weight of the second module. In some embodiments, some of the weight of the second module **400** may be supported by a single foot on a far edge of the second module **400** away from the first module **100**.

[0179] In some embodiments, second module **400** and first module **100** are mounted to an integral frame.

[0180] In some embodiments, the interface between the second module **400** and the first module **100** is blocked and sealed where possible to prevent airflow between the two modules. Existing air inlets on the side of the first module **100** facing the second module **400** may be ducted through the second module **400** to a fresh air source. The side wall of the second module **400** facing the first module **100** can be covered by panels to block airflow into the first module **100**. Such panels can include openings where necessary for receptacle or container transfer between the second module **400** and first module **100**, cable routing, etc.

[0181] Components of exemplary embodiments of the second module **400** are described below.  
Reagent Packs

[0182] In some embodiments, amplification reagents and other reagents may be provided in the second module **400** in lyophilized form in a reagent pack comprising a cartridge that includes wells within which the lyophilized reagent may be reconstituted. Examples of cartridges that can be used in this embodiment are disclosed by Knight et al. in U.S. Provisional Application No. 61/782,320, "Systems, Methods, and Apparatus for Performing Automated Reagent-Based Assays," filed Mar. 14, 2014, which enjoys common ownership herewith (these cartridges are both identified by reference number **500** in FIGS. **10A** and **10B**). The reagent pack is further configured to be stored within the second module **400** and, in some embodiments, to be moved within the second module **400** by the distributor **312**, and inserted and removed from the reagent pack changer **700**.

[0183] Details of a reagent pack **760**, according to one embodiment, are shown in FIGS. **19** and **20**. The reagent pack **760** may include a plurality of mixing wells **762**, each of which contains a lyophilized unit-dose, assay-specific reagent **768**, which may be in pellet form. (As used herein, "unit-dose" or "unitized" means an amount or concentration of a reagent sufficient to perform one or more steps of a single assay for a single sample.) In some embodiments, the unit-dose reagent **768** comprises a component for performing a nucleic acid amplification reaction. For example, the

nucleic acid amplification reaction component can be a polymerase, nucleoside triphosphates, or any other suitable component. In the illustrated embodiment, the reagent pack **760** includes ten mixing wells **762**. But in some embodiments, the reagent pack **760** may include more or fewer than ten mixing wells. Each mixing well **762** of a single reagent pack **760** may hold the same reagent, or the wells **762** may hold different reagents, or some wells **762** may hold the same reagent and some may hold different reagents. Exemplary assay specific reagents **768** held in the reagent pack **760** include unitized reagents for performing a single amplification reaction, for example, PCR and/or a detection reaction utilizing a sample. Such reagents may be specific for one target nucleic acid or a plurality of different target nucleic acids. For example, the plurality of different target nucleic acids may be part of a respiratory panel, and the unitized reagents are sufficient to conduct a PCR reaction targeting Flu A, Flu B, RSV, parainfluenza 1, 2, and 3, Human Metapneumovirus, Adenovirus, H1, H3, 2009 H1N1, and/or Tamiflu resistance. In an embodiment, each reagent pellet **768** is held at the bottom of the associated mixing well **762** with an electrostatic charge imparted to the pellet **768** and/or the mixing well **762**. In other embodiments, each reagent pellet **768** is held at the bottom of the associated mixing well **762** with one or more physical feature present in the mixing well **762**, for example, those disclosed by Knight et al. in U.S. Provisional Application No. 61/782,320.

[0184] In some embodiments, the mixing wells **762** are covered by a pierceable foil **766** adhered to the top of the reagent pack **760**. Foil **766** can be pierced by a pipette tip **584** to enable reconstitution agents or other substances to be dispensed into the mixing well **762** and to enable reconstituted reagent to be aspirated from the mixing well **762**.

[0185] In some embodiments, the reagent pack **760** further includes a manipulating structure **764**, for example, a manipulating hook, that is similar to the manipulating structure **166** of the MRD **160** and is configured to be engageable by a manipulating structure, for example, a hook, of the rotary distributor **312**. The reagent pack **760** may include a rear recess **770** that is configured to align the reagent pack within a reagent pack carrier, as will be described below.

#### Tip Compartments

[0186] As shown in FIGS. **1**, **5**, and **6**, tip compartments **580** are configured to hold trays **582** of disposable pipette tips in a manner that enables the tips held in the drawers **580** to be accessed by the robotic pipettor **402**. In the illustrated embodiment, the second module **400** includes two tip compartments **580**, each configured to hold up to three trays **582** of disposable pipette tips. The compartments **580** may be configured to accept commercially-available trays of disposable pipette tips. Exemplary, commercially available pipette tips and trays are available from TECAN (TECAN U.S. Inc., Research Triangle Park, North Carolina). Such tips are available in a variety of volumetric capacities, and each tip may be conductive to facilitate capacitive liquid level sensing and tip-present detection, as is well known in the art. Exemplary trays hold ninety-six pipette tips.

[0187] The tip compartments **580** are configured to be accessible to an operator for reloading of trays **582**. In one contemplated embodiment, the tip compartment **580** comprises a drawer configured to be pulled out of the second module **400** to enable an operator to place the trays **582** of tips into the drawers **580** and to remove empty trays from the drawers **580**. A door or cover panel that is either part of each drawer **580** or the housing of diagnostic system **10** is opened to access each tip compartment **580** behind it. The door or cover panels may provide an esthetically pleasing appearance to the front of the second module **400**. Manual or automated locks, controlled by the system controller, may be provided to prevent the compartment **580** from being opened when the second module **400** is operating. In some embodiments, visible and/or audible warning signals may be provided to indicate that a compartment **580** is not closed properly. In an alternative embodiment, compartment **580** comprises an access door and a slidable tray, wherein the tray is configured to slide out from second module to thereby provide loading access to an operator.

#### Substance Transfer and Handling System

[0188] The substance transfer and handling system **402**, for example, a robotic pipettor, shown in

FIGS. 1, 21, and 22 is a dual arm system comprising a front arm **408** and a back arm **416**. However, other robotic pipettor and handling configurations are contemplated, and the presently depicted embodiment is only exemplary. Substance transfer and handling system **402** can be configured to dispense and/or aspirate substances into and/or from a container, receptacle, well, etc., in second module **400**. In an exemplary embodiment, the front arm **408** includes a substance transfer pipettor **410** configured to aspirate fluid and dispense fluid and includes a pump, for example, an integrated syringe pump, and the back arm **416** includes a vial transfer arm **418** and does not perform substance transfer. The robotic pipettor system **402** comprises a Cartesian gantry assembly with two transverse tracks **404**, **406**, a back arm longitudinal track **420**, and a front arm longitudinal track **412**. The designations “longitudinal” and “transverse” are merely for distinguishing the two sets of tracks, which may be orthogonal to one another, but otherwise the designations are arbitrary. [0189] The substance transfer pipettor **410** may be driven back and forth along the front arm longitudinal track **412** by a belt, drive screw, or other motion transmission device coupled to a motor, and the vial transfer arm **418** may be driven back and forth along the back arm longitudinal track **420** by a belt, drive screw, or other motion transmission device coupled to a motor. The front arm longitudinal track **412** may be driven back and forth along the transverse tracks **404**, **406** by a belt, drive screw, or other motion transmission device coupled to a motor, and the back arm longitudinal track **420** may be driven back and forth along the transverse tracks **404**, **406** by a belt, drive screw, or other motion transmission device coupled to a motor. The substance transfer pipettor **410** and the vial transfer arm **418** include probes that are driven along the Z, or vertical, axis, for example, by a motor coupled to the probes, e.g., by a gear, a rack and pinion, a lead screw, or other suitable device. The motors may be under the control of a system controller. The motors may be stepper motors and may include rotary encoders for controlling and monitoring the position of the track or pipettor to which it is coupled. Each of the tracks has home sensors (or limit switches) for indicating when the substance transfer pipettor **410** or the vial transfer arm **418** is in one or more designated positions, such as a designated “home” position. Similarly, each device may have a vertical home sensor for indicating when the probe is in one or more designated vertical positions, such as a designated vertical “home” position. Such sensors for indicating a home position may include optical sensors (e.g., slotted optical sensors), proximity sensors, magnetic sensors, capacitive sensors, etc.

[0190] In one exemplary embodiment, the substance transfer pipettor **410** is configured to accept TECAN 1 mL disposable pipette tips by inserting the probe thereof into a disposable pipette tip, and an interference fit between the probe and the pipette tip frictionally secures the pipette tip to the end of the probe. The front arm **408** and the substance transfer pipettor **410** are configured to access at least parts of both the amplification processing deck **430** and the receptacle processing deck **600** on the second module **400**. The substance transfer pipettor **410** may include integrated tip sensing for confirming the presence or absence of a disposable pipette tip, capacitive level sensing for detecting contact by the pipette tip with the surface of the fluid contents of a reaction receptacle or other container and determining the level of the fluid contents based on the detected vertical position of the pipettor, and pressure sensing for sensing pressure fluctuations within the substance transfer system during fluid dispensing or aspiration. The substance transfer pipettor **410** is capable of transferring fluids, caps, or cap/processing vial assemblies such as those described below.

[0191] The vial transfer arm **418** is a “pick and place” device configured to pick up a cap/vial assembly by inserting the probe thereof into a cap that is coupled to a vial, as will be described below.

#### Pipettor Pump

[0192] In an exemplary embodiment, the pump for the substance transfer pipettor **410** comprises a ceramic piston driven by a servomotor and a lead screw. The servomotor is controlled by the system controller, and the device can include rotary encoder feedback to the system controller and home sensors for monitoring the position of the piston. The syringe may have a volume of between



0.5 and 3 mL (preferably 1.05 mL) and, in certain embodiments, is a ceramic. The pump can preferably dispense very small volumes (5  $\mu$ L) of fluid with  $\pm 5\%$  coefficient of variation (CV) measured across **30** discrete dispenses. To achieve this performance, in certain embodiments, the pump includes a solenoid valve to release pressure at the end of the stroke to ensure consistent fluid shear.

#### Processing Cap/Vial Assembly

[0193] In general, the processing vial provides a receptacle for containing reaction fluids for performing PCR or other process. The cap is configured to be placed into or onto the vial in an automated manner so as to close off the vial. In some embodiments, the cap is configured to receive the end of the vial transfer arm **418** with a friction fit, so that the transfer arm **418** can thereafter pick up the cap and place it into or onto the vial. The cap and vial are configured to lock together so that, once the cap is placed into or onto the vial, the cap and the vial are interlocked to form a cap/vial assembly. The robotic pipettor, with the probe of the transfer arm **418** inserted into the cap, can then pick up the cap/vial assembly and transfer it from one location within the second module **400** to another location. Exemplary caps and processing vials are disclosed by, for example, Knight et al. in U.S. Provisional Application No. 61/782,320.

[0194] Details of an exemplary embodiment of the processing vial **464**, the processing vial cap **476**, and a vial transfer arm probe **422** (which may be the probe of the substance transfer pipettor **410** or the vial transfer arm **418**) are shown in FIGS. 23-25.

[0195] In the embodiment shown in FIGS. 23-25, the processing vial **464** may have a conical shape and an open top end **465** surrounded by a locking collar **466** forming a peripheral wall around the open end **465**. Lateral through holes **468** are formed through the locking collar **466** at diametrically opposed locations. A latch hook, or tab or radial protrusion, **472** is located above each through hole **468** and protrudes radially inwardly from the locking collar **466**.

[0196] The processing vial cap **476** has an upper portion **477** with an open top end **478** that defines a probe recess to receive probe **422** and lower portion **483** with a closed lower end **480** at a distal end of the processing vial cap **476**. A peripheral chamfer **481** extends about the lower (distal) end **480** and forms a convex distal end surface of the cap **476**. An annular collar **482** extends about the cap **476** at a position between the upper portion **477** and the lower portion **483**. Collar **482** of the vial **476** sits atop the thermal cyclor when the vial **476** is placed therein, ensuring a close fit of the vial within the wells of the thermal cyclor. An exemplary thermal cyclor for use with processing vial **476** is disclosed by Buse et al. in U.S. Patent Application Publication No. 2014/0038192. The lower portion **483** of the cap **476** beneath the collar **482** defines a plug **485** that fits into the open top end **465** of the processing vial **464**. This plug **485** is sized so as to fit into the processing vial **464** with an interference, friction fit. A latch collar **484**—a radial protrusion—extends about the cap **476** and protrudes radially outwardly to provide a locking ridge at a position below the collar **482**. Seal rings **486**, **488** extend about the lower portion **483** of the cap **476** at positions below the latch collar **484**.

[0197] FIGS. 24 and 25 show, in cross-section, a processing vial cap **464**, initially held in a cap well **490** of a cap/vial tray **460**, and a processing vial **464** held in a vial well **474** of the cap/vial tray **460**. After fluids are dispensed into the processing vial **464** with the disposable pipette tip **584** (connected to a robotic pipettor), the processing vial **464** is capped by a processing vial cap **476** by inserting the closed lower end **480** of the cap **476** into the open top end **465** of the vial **464**, until a bottom surface of the collar **482** of the cap **476** abuts a top surface of the locking collar **466** of the vial **464**. The latch collar **484** of the cap **476** snaps in beneath the mating latch hooks **472** of the vial **464** which may function as locking detents to secure the cap **476** to the vial **464**. The cap **476** and the vial **464** are thereafter locked together and the cap/vial assembly may be picked up and moved by the pipettor. The cap/vial assembly can be removed from the pipettor probe **422** by an eject device engaging a rim **479** surrounding open end **478** to pull the cap/vial assembly off the probe **422**. The seal rings **486**, **488** of the cap **476** preferably have outer diameters that are slightly

larger than the inner diameter of the upper portion of the vial **464**, thereby forming a tight seal between the cap **476** and the vial **464** as the cap and vial are made of materials, such as suitable plastics, that are at least partially resilient.

[0198] An alternative processing cap/vial assembly is shown in FIG. **26**, which is an exploded perspective view of a processing vial **1100** and a processing vial cap **1200**. Processing vial cap **1200** includes a lower portion **1221** with a closed lower end **1220** defining a plug **1222**, a tapered opening, or open end, **1215** forming or defining a probe recess, and a latch collar **1240** having latch fingers **1250** (or locking fingers or locking members). A peripheral chamfer **1223** extends about the lower (distal) end **1220** and forms a convex distal end surface of the vial cap **1200**. The vial **1100** includes a radially-outwardly protruding lock collar, or lip, **1155** surrounding the open top end of the vial **1100** and a collar **1125**. Collar **1125** of vial **1100** sits atop the thermal cyclor when the vial **1100** is placed therein, ensuring a close fit of the vial within the wells of the thermal cyclor. After fluid is dispensed into the vial **1100**, the vial is capped by first inserting the pipettor probe **422** into the tapered opening **1215** of the processing vial cap **1200** to frictionally secure the cap **1200** to the pipettor probe **422** and then picking up the cap **1200** with the pipettor and inserting the plug **1222** of the closed lower end **1220** of the cap **1200** into the open top end of the vial **1100** until the latch fingers **1250** lockingly snap onto the lock collar **1155** of the vial **1100**. The cap **1200** and the vial **1100** are thereafter locked together and the cap/vial assembly may be picked up and moved by the pipettor. The cap/vial assembly can be removed from the probe **422** by an eject device engaging a rim **1225** surrounding opening **1215** to pull the cap/vial assembly off the probe **422**.

[0199] Details of the vial and cap of FIG. **26** are shown in FIGS. **45-55**.

[0200] As shown in FIGS. **45-48**, the vial **1100** is a single-piece receptacle that includes a body **1105** having a generally cylindrical upper portion **1110** and a tapered lower portion **1120**. Formed on an outer surface of the body **1105** is collar **1125**, which separates the upper and lower portions of the body. The upper portion **1110** of the body **1105** has an open end **1145** through which fluid samples are deposited or removed from the vial **1100**. The tapered lower portion **1120** has a closed end **1150** that may either be flat or rounded to provide optical communication with an optical system, for example, one or more optical fibers (not shown) of a biochemical analyzer. In various embodiments, the bottom surface of the closed-ended lower portion may be flat or curved.

[0201] The vial **1100** optionally containing a sample or reaction mixture is configured for insertion into a receptacle holder of an automated biochemical analyzer (not shown). As used herein, a receptacle that is “configured for insertion” refers to the exterior surface of the body **1105** of the vial **1100** being sized and shaped to maximize contact between the receptacle and a receptacle well of a receptacle holder. In certain embodiments, this maximal contact refers to physical contact of the receptacle well with at least a portion of the vial **1100**. Also in certain embodiments, this maximal contact refers to physical contact of the receptacle well with the tapered lower portion **1120** of the vial **1100**, or at least a portion of the tapered lower portion **1120** of the vial **1100**.

[0202] Formed in the inner surface **1140** of the upper portion **1110** of the body **1105** is one or more longitudinally oriented grooves **1135** to facilitate the venting of air displaced from the interior upon deposit of the test sample or attachment of a cap **1200** to the vial **1100**. In various embodiments, a plurality (i.e., 2, 3, 4, 5, 6, 7, or 8) of longitudinally oriented grooves may be formed in the inner surface **1140** of the upper portion **1110**, and the grooves **1135** may be equally spaced apart from one another around the entire circumference of the body **1105**.

[0203] Circumscribing the open end **1145** of the upper portion **1110** of the body **1105** is lock collar **1155** extending radially outward from a central axis thereof. In various embodiments, the lock collar **1155** tapers from the outer-most portion of the radially-extended lip towards the open end of the body, and is configured for securable attachment to a cap **1200** (FIGS. **49-55**).

[0204] With reference now to FIGS. **49-52**, the securable cap **1200** includes lower portion **1221** having an outer surface defining plug **1222** for sealing engagement of the inner surface **1140** of the upper portion **1110** of the vial **1100** and an upper portion **1210**. To ensure an essentially leak-proof

seal when the cap **1200** is securely attached to the open end **1145** of the upper portion **1110** of the vial **1100**, the outer surface of the lower portion **1221** of the cap **1200** is formed with one or more ribs **1230** circumscribing the plug **1222** for contacting the inner surface **1140** of the upper portion **1110** of the vial **1100**. In various embodiments, the lower portion **1221** of the cap **1200** is formed with 1, 2, or 3 ribs **1230** for contacting the inner surface **1140** of the upper portion **1110** of the vial **1100**. As shown in FIG. 50, lower portion **1221** has an open distal end **1234** defining an inner surface **1232**, which is different from the embodiment shown in FIG. 26 in which lower portion **1221** has a closed lower end **1220**. In an embodiment, a peripheral chamfer **1233** extends about the open distal end **1234** and forms a convex distal end surface of the vial cap **1200**.

[0205] The upper portion **1210** of the cap **1200** includes tapered opening **1215** forming or defining a probe recess for frictional attachment to a receptacle transport mechanism (FIG. 26), such as the probe **422** of a pipettor or pick-and-place robot. Guiding insertion of the receptacle transport mechanism **422** into the open end **1215** of the upper portion **1210** of the cap **200** are one or more linear ribs **1260** formed in the inner surface **1270** of the upper portion **1210**. The linear ribs **1260** protrude towards an axial center of the cap **1200**, thereby decreasing the inner fitment diameter of the upper portion **1210** of the cap **1200**. These linear ribs **1260** can, among other things, enhance the frictional attachment to the receptacle transport mechanism **422**. In various embodiments, 1, 2, 3, 4, 5, 6, 7, or 8 linear ribs **1260** are formed in the inner surface **1270** of the cap **1200** and extend at least a portion of the way down the length of the upper portion **1210** thereof.

[0206] At least one of the linear ribs **1260** may be formed with a portion **1265** thereof that gradually tapers radially inward toward a central axis of the upper portion **1210** of the cap. In other words, the amount of protrusion of the linear rib **1260** may gradually increase in size as the linear rib **1260** approaches the bottom **1245** of the upper portion **1210** of the cap **1200**. Alternatively, or in addition thereto, in certain embodiments, the linear rib **1260** may gradually increase in overall thickness as it approaches the bottom **1245** of the upper portion **1210** of the cap **1200**. Thus, gradual increase in thickness or radial geometry is contemplated for the gradual tapering of the one or more linear ribs **1260**, which serves to stabilize and center the receptacle transport mechanism **422** as it is lowered into the cap **1200** for transport.

[0207] Corresponding with each linear rib **1260** and disposed on the exterior surface of the upper portion **1210** of the cap **1200** are one or more indentations **1236** that extend along at least part of the length thereof. The indentations may be formed in any shape such as, for example, concave, notched, squared, etc. Thus, at least one indentation **1236** is formed in the exterior surface of the upper portion **1210** of the cap **1200**. In various embodiments, the length of the indentation **1236** is the same as the length of the corresponding linear rib **1260**, and each linear rib **1260** is positioned such that it lies on the inner surface **1270** of the cap **1200** in a location that directly opposes the position of the at least one indentation **1236** formed on the outer surface of the cap **1200** in a one-to-one relationship. The coupling of a linear rib **1260** with an indentation in this manner enhances the predictability of the frictional attachment of the cap **1200** to a receptacle transport mechanism **422**. In certain embodiments, as the receptacle transport mechanism **422** is lowered into the open end **1215** of the cap **1200**, it contacts the one or more linear ribs **1260**, thereby pressing against the one or more linear ribs **1260**. Such pressing against the linear ribs **1260** causes the cap **1200**, and indentations **1236** to flex and/or expand radially outward with respect to the axial center thereof to accommodate the receptacle transport mechanism **422** and enhance frictional attachment thereto. Accordingly, 1, 2, 3, 4, 5, 6, 7, or 8 indentations **1236** may be formed on the exterior surface of the upper portion **1210** of the cap **1200**.

[0208] Circumscribing the opening **1215** of the upper portion **1210** of the cap **1200** is the rim **1225** extending radially outward from a central axis thereof. In various embodiments, the rim **1225** tapers from the open end **1215** towards the lower portion **1221**. Protruding from the taper of the rim **1225** are a plurality of protrusions **1235**. The protrusions **1235** may be equally spaced apart from one another and facilitate stacking and/or docking within a well of a consumable card for use in an

automated biochemical analyzer. In various embodiments, 1, 2, 3, 4, 5, 6, 7, or 8 protrusions **400** are formed in the taper of the rim **1225**. Separating the upper portion **1210** from the lower portion **1221** of the cap **1200** is the latch collar **1240** that extends radially away from an axial center thereof such that the top and bottom of the latch collar **1240** form radially-extending, annular surfaces. The latch collar **1240** includes one or more locking members, such as the plurality of locking fingers **1250** that extend from the latch collar **1240** toward the lower portion **1221** of the cap **1200**. The locking fingers **1250** are shaped for securely engaging the lock collar **1155** of the vial **1100**, and may be disposed to allow for removable attachment of the cap **1200** to the vial **1100**, while maintaining a leak-proof seal of the contents thereof. In various embodiments, 1, 2, 3, 4, 5, 6, 7, or 8 locking fingers **1250** are formed in the cap **1200**. In an embodiment, as shown in FIG. 50, each locking finger **1250** may include a distal, beveled end **1280**, such that the locking finger(s) **1250** together define a radial locking groove **1282** surrounding the plug **1222** and a radially-protruding locking ridge **1284** surrounding the plug **1222** and disposed distally from the radial locking groove **1282**. The locking ridge **1284** operatively engages the mating, radially-protruding lock collar **1155** of the vial **1100**, which is received within the radial locking groove **1282** above the radial locking ridge **1284** when the plug **1222** of the closed lower end **1200** of the cap **1200** is inserted into the open top end of the vial **1100** and the locking finger(s) **1250** engage the lock collar **1155**.

[0209] The latch collar **1240** of the cap **1200** additionally serves to form a bottom **1245** to separate the upper portion **1210** from the lower portion **1221**, thereby closing the interior of the vial **1100** from the environment. However, in certain embodiments, the bottom **1245** is scored **1255** for piercing by a mechanism for collecting and/or adding reagents to the test sample within the vial **1100**. Such piercing avoids the need to remove the secured cap **200** from engagement with the vial **1100**, while providing access to the contents therein.

[0210] The vial **1100** and cap **1200** of the present invention may be prepared from a number of different polymer and heteropolymer resins, including, but not limited to, polyolefins (e.g., high density polyethylene (“HDPE”), low density polyethylene (“LDPE”), a mixture of HDPE and LDPE, or polypropylene), polystyrene, high impact polystyrene and polycarbonate. An example of an HDPE is sold under the tradename Alathon M5370 and is available from Polymerland of Huntsville, N.C.; an example of an LDPE is sold under the tradename **722** and is available from The Dow Chemical Company of Midland, Mich.; and an example of a polypropylene is sold under the tradename Rexene 13T10ACS279 and is available from the Huntsman Corporation of Salt Lake City, Utah. Although LDPE is a softer, more malleable material than HDPE, the softness of LDPE provides flexibility in the locking members **1250** of the cap **1200** to securably engage the lip **1155** of the vial **100**. And, while a cap made of HDPE is more rigid than one made of LDPE, this rigidity tends to make an HDPE cap more difficult to penetrate than one made of LDPE. It should be understood that the vial **1100** and cap **1200** may be comprised of a combination of resins, including, for example, a mixture of LDPE and HDPE, preferably in a mixture range of about 20% LDPE:80% HDPE to about 50% LDPE:50% HDPE by volume. In addition, the amounts of LDPE and HDPE used to form each of the vial **1100** and cap **1200** may be the same or different. In various embodiments, at least a portion of the cap **1200** is formed from an opaque material having low to no autofluorescence characteristics. Also, in certain embodiments, the portion of the cap **1200** formed from an opaque material having low to no autofluorescence characteristics is at least the lower portion **1221** thereof, including the inner surface **1232** of the lower portion **1221** of the cap **1200**.

[0211] Regardless of the type or mixture of resins chosen, the vial **1100** and cap **1200** are preferably injection molded as unitary pieces using procedures well-known to those skilled in the art of injection molding, including a multi-gate process for facilitating uniform resin flow into the receptacle and cap cavities used to form the shapes thereof. Uniform resin flow is desirable for achieving consistency in thickness, which is important for a variety of reasons, including for the penetrable bottom **1245** of the cap **1200**; to ensure a secure, such as an air-tight, engagement of the

cap **1200** and vial **1100**; to ensure a predictable engagement of the cap **1200** with the receptacle transport mechanism **422**; and to ensure maximal contact of the vial **1100** with a receptacle well of a receptacle holder.

[0212] The second module **400** may include “vial present” sensors. The vial present sensor is used as a process control measure to verify that a vial is attached to the cap. The substance transfer pipettor **410** (front arm **408**) and the vial transfer arm **418** (back arm **416**) will detect when a cap is attached to the arm. One way substance transfer pipettor **410** or the vial transfer arm **418** will detect when a cap is present is by a strip sleeve on the probe **422**. When the cap is picked by the probe, the upper rim of the cap pushes on and raises the sleeve (e.g., a few millimeters), and this movement may be detected by a sensor. However, pipettors often cannot detect if a vial is attached to the cap. In one exemplary embodiment, the vial present sensor is an optical sensor (or multiple sensors) that either arm **408**, **416** can move past/through as it transports a capped vial into or out of the centrifuge **588**. The vial present sensor will trigger on the vial (if present) as the arm moves past the sensor.

#### Bulk Reagent Container Compartment and Bulk Reagent Container Transport

[0213] In one exemplary embodiment, the bulk reagent container compartment **500** is configured to hold a plurality of bulk reagent containers. Each bulk reagent container can hold a reagent for use in multiple reaction receptacles. In some embodiments, the bulk reagent containers are bottles or any other container suitable for containing reagents in bulk. In some embodiments, the bulk reagents within the bulk reagent containers can include a sample preparation reagent (e.g., target capture reagent (TCR), a wash solution, an elution reagent, or any other sample preparation reagent), a reconstitution reagent, or any other required bulk reagent. In some embodiments, the bulk reagent containers hold a quantity of the bulk reagent sufficient to perform between about 50 to 2000 assays. In some embodiments, the bulk reagent containers hold a quantity of the bulk reagent sufficient to perform between about 250 to 1000 assays. In some embodiments, the bulk reagent containers hold a quantity of the bulk reagent sufficient to perform less than about 250 assays, or more than about 1000 assays. In some embodiments, the bulk reagents are for performing isothermal nucleic acid amplification reactions, for example, a transcription-based amplification reaction such as TMA.

[0214] In some embodiments, the bulk reagent container compartment **500** can be configured to hold two elution buffer containers, two oil containers, and four reconstitution fluid containers. The bulk reagent container compartment **500** may be opened by an operator to load containers. For example, bulk reagent container compartment **500** may be a drawer that is slid out from the main body of diagnostic system **10**. In some embodiments, once closed, the bulk reagent container transport **550** moves the elution buffer containers into the first module **100** to a location in which a substance transfer mechanism, for example, a robotic pipettor, can access the containers. In some embodiments, the bulk oil containers and the bulk reconstitution fluid containers remain in the bulk reagent container compartment **500**, where they are accessible to the substance transfer pipettor **410**.

[0215] Containers carried on the bulk reagent container compartment **500** may be identified by machine-readable code, such as RFID. An indicator panel **507** having visible (e.g., red and green LEDs) and/or audible indicators provides feedback to the operator regarding container status.

[0216] The bulk reagent container compartment **500** and bulk reagent container transport **550** are shown in FIGS. 5-10. In some embodiments, the bulk reagent container compartment **500** is located on the amplification processing deck **430** adjacent the tip compartments **580** and may be accessed from the front of the second module **400**. The bulk reagent container compartment **500** may be pulled out to enable an operator to place two containers **502**, **504** containing an elution buffer as well as a number of bulk containers, or other types of fluid containers, containing other reagents, such as, for example, oil or reconstitution buffer, into the drawer **500**. The number of containers accommodated by the drawer **500** is dictated by considerations of intended throughput

and desired time period between required re-stocking of supplies.

[0217] A door or cover panel, which is either part of the bulk reagent container compartment **500** or the housing of diagnostic system **10** is opened to access the bulk reagent container compartment **500** behind it. The door or cover panel can provide an esthetically pleasing appearance to the front of the second module **400**. Automated locks, controlled by the system controller, may be provided to prevent the bulk reagent container compartment **500** from being pulled open when the second module **400** is operating. In some embodiments, visible and/or audible warning signals may be provided to indicate that the bulk reagent container compartment **500** is not closed properly.

[0218] When the bulk reagent container compartment **500** is closed, the containers **502**, **504** are moved to the far end of the drawer **500**, where they are positioned in operative engagement with the bulk reagent container transport **550** extending laterally from an end of the drawer **500** into the first module **100**. Upon closing the bulk reagent container compartment **500**, the bulk reagent container transport **550** is activated to move the containers **502**, **504** into the first module **100** to a position at which the robotic pipettor of the first module **100** can access the containers **502**, **504**. The bulk reagent container transport **550** may be activated manually by an operator (e.g., pressing a button or switch) or automatically by the system controller upon receipt of an input signal indicating that the bulk reagent container compartment **500** has been fully closed, thereby placing the containers **502**, **504** into operative position with respect to the bulk reagent container transport **550**.

[0219] Details of the bulk reagent container compartment **500** are shown in FIGS. **9-13**. In some embodiments, the bulk reagent container compartment **500** includes a container tray **506** configured to hold the plurality of reagent containers, and a container carriage **512** disposed at the end of the container tray **506** and configured to carry elution reagent containers **502**, **504**. In some embodiments, the container tray **506** and the container carriage **512** are moveable along a track **508** between a withdrawn position as shown in FIG. **9** (see also FIG. **7**) and a closed position as shown in FIG. **10** (see also FIG. **8**).

[0220] The container carriage **512** is carried on a carriage transport **522** configured to be movable with the container tray **506** along the track **508**. As shown in FIGS. **11** and **12**, the carriage transport **522** includes horizontal carriage rails **524** and **526** that engage rail slots **514**, **516**, respectively, formed in the container carriage **512** to retain the container carriage **512** within the carriage transport **522**.

[0221] The bulk reagent container compartment **500** is configured to permit an operator to place reagent containers **502**, **504** within the container carriage **512** when the drawer is in the open position, as shown in FIGS. **7** and **9**. Upon closing the drawer, to the position shown in FIGS. **8** and **10**, the reagent container carriage **512** can be released from the carriage transport **522** and engaged by the bulk reagent container transport **550** to pull the carriage **512** to a lateral position with respect to the track **508** of the container tray **506**, as shown in FIG. **10**. In this manner, it is possible to transfer bulk reagents from the second module **400** to the first module **100**.

[0222] More particularly, the carriage transport **522** moves along the track **508** as the container tray **506** is moved into the open or closed positions. As shown in FIG. **11**, the carriage transport **522** includes a pivoting carriage lock **532** configured to pivot about pivot pin **534** and including a locking leg **536** that extends upwardly through an opening **528** formed in the bottom of the carriage transport **522** and into a lock recess **520** formed in the bottom of the container carriage **512**. A trigger leg **538** extends below the carriage transport **522**. As the container tray **506** is moved into the closed position (to the left in FIG. **11**) the trigger leg **538** of the pivoting carriage lock **532** engages a lock trigger **510** projecting upwardly from the track **508**, thereby causing the carriage lock **532** to pivot counterclockwise, as shown in FIG. **12**, to withdraw the end of the locking leg **536** from the lock recess **520** of the container carriage **512**. With the trigger leg **538** withdrawn from the lock recess **520**, the container carriage **512** and the containers **502**, **504** carried therein, are able to slide laterally out of the carriage transport **522** and onto the bulk reagent container transport

550.

[0223] The bulk reagent container transport **550** includes a powered carriage transport mechanism for moving the container carriage **512** and containers **502**, **504**. In one exemplary embodiment, as shown in FIGS. **9**, **10**, and **13**, the carriage transport comprises motor **552** and a continuous belt **554** disposed over the output shaft of the motor and an idler wheel **556** located on an opposite end of the container transport **550** from the motor **552**. Motor **552** may comprise a stepper motor and may include a rotary encoder for monitoring and controlling, via control signals and feedback data, the position of the motor.

[0224] The carriage transport mechanism further includes a sled **558** with a carriage hook **564** extending therefrom. The belt **554** is attached to a portion of the sled **558** so that movement of the belt by the motor **552** causes a corresponding translation of the sled **558** in one direction or the other along the transport **550**.

[0225] As shown in FIGS. **12** and **13**, as the container tray **506** is moved to a closed position in which the trigger leg **538** of the pivoting carriage lock **532** engages the lock trigger **510** to withdraw the locking leg **536** from the lock recess **520**, the carriage hook **564** passes into a carriage hook slot **530** formed in the carriage transport **522** and engages a hook catch **518** formed in the container carriage **512**. The sled **558** and carriage hook **564** may then be translated laterally along the container transport **550** by the belt **554** to pull the container carriage **512** off of the carriage transport **522** and onto the bulk reagent container transport **550**. As shown in FIG. **11**, the bulk reagent container transport includes carriage rails **566**, **568** that will engage the rail slots **514**, **516**, respectively, of the container carriage **512** as the container carriage **512** is pulled onto the bulk reagent container transport **550**.

[0226] As shown in FIG. **13**, a home flag **560** projects from the sled **558** and engages a slotted optical sensor **562** to indicate that the sled **558** and the carriage hook **564** are in the fully-extended position shown in FIG. **13**. A second slotted optical sensor **570** is provided closer to the motor **552** (see FIG. **9**). The second optical sensor **570** is engaged by the home flag **560** when the sled **558** and hook **564** are in the fully retracted position, as shown in FIG. **9**. Signals from the sensors **562**, **570** are communicated to a system controller to monitor the position of the sled **558**. Alternatively, the bulk reagent container transport **550** may include limit switches (e.g., contact switches) to stop operation movement of the sled **558** at the fully extended and/or fully retracted positions, for example, by generating stop signals communicated to a controller which then sends stop commands or terminates power to the motor **552**. Still other types of sensors may be used for indicating extended and retracted stop positions, including proximity sensors, magnetic sensors, capacitive sensors, etc.

#### Cycler/Signal Detector

[0227] Cycler deck **430** comprises a cycler/detector **432**, such as, for example, a thermal cycler. The cycler **432** is used in nucleic acid amplification reactions and the selection of cycler type depends on the nature of the amplification reaction intended to be run on the second module **400**. For purposes of the present disclosure, exemplification will be made using a thermal cycler. However, it is understood that the cycler type incorporated into the second module **400** depends on the amplification reaction intended to be run on the second module **400**.

[0228] An exemplary embodiment of a thermal cycler **432** is disclosed by Buse et al. in U.S. Patent Application Publication No. 2014/0038192. An exemplary embodiment of a signal detector **432** is disclosed by Hagen et al. in U.S. Pat. No. 9,465,161, "Indexing Signal Detection Module," filed Mar. 7, 2014, which enjoys common ownership herewith.

[0229] In certain embodiments, the thermal cycler can have different thermal zones. Such thermal cyclers allow the system to run separate assays under different conditions. For example, in a two zone thermal cycler, a first assay can be run under a first set of time and temperature conditions and a second assay can be run under a second set of time and temperature conditions. It is contemplated that the multi-zone thermal cycler can have two, three, four, five, or even six or more separate

thermal zones. Generally, to the extent that a multi-zone thermal cycler is implemented in the system, the number of zones for the multi-zone thermal cycler is evenly divisible into 96 (i.e., 2, 4, 6, 8, etc.).

#### Receptacle Holder

[0230] In an exemplary aspect, cyclers **432** comprises an apparatus **2100** to perform the heating (i.e., isothermal or temperature cycling) necessary for a nucleic acid amplification assay. As shown in FIG. **56**, the apparatus **2100** includes one or more (i.e., 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, or any whole number between 1 and 20, or more) receptacle holders **2110** (see also FIGS. **57-61**). In an exemplary embodiment, the apparatus **2100** includes two or more receptacle holders **2110**. Such an apparatus may include a housing **2050** (see FIG. **57**) within which the one or more receptacle holders **2110** are located. The housing **2050** may be made from any suitable structural material such as, for example, plastic or metal.

[0231] When multiple receptacle holders **2110** are provided in an apparatus described herein, each receptacle holder **2110** disposed within the apparatus may be disposed in alignment with one another to facilitate the automated processing steps involved in nucleic acid amplification assays. It should be understood that any alignment may be used in accordance with the size and shape of the apparatus. In an exemplary embodiment, the receptacle holders are disposed within the apparatus in one or more (i.e., 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, or more) rows of two receptacle holders per row. Thus, two receptacle holders may be disposed in a row either in thermal connection with, or thermally separated from, one another. In an exemplary embodiment, the apparatus **2100** includes six rows of two receptacle holders per row.

[0232] As shown in FIGS. **58-60**, the receptacle holder **2110** includes a plurality (i.e., two or more) of receptacle wells **2120** that are configured to receive a receptacle **2130** (e.g., vial **464** or vial **1100**) optionally containing a sample or reaction mixture **2140**. For purposes of explanation, the surface of the receptacle holder into which the receptacles **2130** are inserted will be referred to as the “top surface” **2150** thereof. Likewise, the surface of the receptacle holder opposite to the surface into which the receptacles **2130** are inserted will be referred to as the “bottom surface” **2160**. In an exemplary embodiment, each receptacle holder **2110** includes five or more (i.e., 5, 6, 7, 8, 9, 10, or any whole integer between 1 and 10, or more) receptacle wells **2120**. In another exemplary embodiment, each receptacle holder **2110** includes one to ten receptacle wells. In yet another exemplary embodiment, each receptacle holder includes three to six receptacle wells. In yet another exemplary embodiment, each receptacle holder includes five receptacle wells. Each of the plurality of receptacle wells within a respective receptacle holder may be disposed in alignment with one another. In an exemplary embodiment, the receptacle wells **2120** are disposed in a row extending along the length of the top surface **2150** of the receptacle holder **2110**.

[0233] Exemplary materials from which a receptacle holder may be made include, but are not limited to, aluminum, titanium, copper, steel, magnesium, metal composites, metal alloys, ceramics, plastics, plastic composites, or any suitable thermally-conductive material.

[0234] As used herein, a receptacle well of the receptacle holder that is “configured to receive” a particular size or shape of receptacle refers to a receptacle well whose dimensions are substantially similar to the size and shape of a receptacle **2130** (i.e., a sample tube) such that the receptacle **2130** fits snugly within the receptacle well **2120**, thereby maximizing contact between the surface of the receptacle well **2120** and the receptacle **2130**. In certain embodiments, this maximal contact refers to physical contact of the receptacle well **2120** with at least a portion of the receptacle **2130**. In various embodiments, receptacles **2130** in accordance with the present disclosure are individual reaction vessels made from suitable rigid or flexible materials, and shaped and dimensioned to fit within the receptacle wells of the apparatus described herein. In other embodiments, two or more (i.e., 2, 3, 4, 5, or more) receptacles may be manufactured as a single unit configured to fit within a receptacle holder. Each receptacle **2130** may be closed or sealed to prevent contamination of and/or evaporation of the contents therein, and/or to facilitate handling or transport of each receptacle.



Such seals may be permanent or semi-permanent and may be fluid-tight. In certain embodiments the seal comprises a cap or lid **2135**.

[0235] Within each receptacle well **2120** is at least one through-hole **2170**, which extends from an inner surface **2180** of the receptacle well to an outer surface of the receptacle holder. In an exemplary embodiment, the through-hole **2170** of a particular receptacle well **2120** extends from the bottom-center of inner surface **2180** of the receptacle well **2120** to the surface of the receptacle holder **2110** that is opposite to the surface of the receptacle holder within which the receptacles **2130** are inserted (i.e., in this embodiment, the through-hole extends from the bottom of the receptacle well **2120** to the bottom surface **2160** of the receptacle holder **2110**). In certain embodiments the diameter of the through-hole **2170** is the same as that of the bottom **2190** of the inner surface **2180** of receptacle well **2120**. In other embodiments, the through-hole **2170** comprises a hole or opening having dimensions smaller than the bottom **2190** of the inner surface **2180** of receptacle well **2120**. In other embodiments, the through-hole **2170** comprises a hole or opening having dimensions the same size as, or larger than, the bottom **2190** of the inner surface **2180** of receptacle well **2120**. The exact dimensions of the through-hole **2170** may vary, provided that the presence of the through-hole **2170** does not detrimentally affect the ability of the receptacle holder **2110** to efficiently transfer heat to and from a receptacle **2130** held within the receptacle well **2120**.

#### Thermal Element

[0236] As shown in FIGS. **61** and **62**, positioned proximal to the receptacle holder is one or more thermal elements **2200** for altering a temperature or temperatures of the receptacle holder **2110**. As used herein, the term “thermal element” may include any known heating element for heating and cooling applications. In one embodiment, the thermal element is a resistive heating element, such as a thin metal film that is applied to the receptacle holder **2110** by using well-known methods such as sputtering or controlled vapor deposition. The heating element also can be provided as a molded or machined insert (e.g., such as a cartridge) for incorporation into the receptacle holder **2110**.

[0237] In an exemplary embodiment, the thermal element **2200** is a thermoelectric device, such as a “Peltier device,” which is generally constructed from electron-doped n-p semiconductor pairs that act as miniature heat pumps. When current is applied to the semiconductor pairs, a temperature difference is established, where one side becomes hot and the other cold. If the current direction is reversed, the hot and cold faces will be reversed. Usually an electrically nonconductive material layer, such as aluminum nitride or polyimide, is disposed over the substrate faces of the thermoelectric modules so as to allow for proper isolation of the semiconductor element arrays.

[0238] As used herein, “altered temperature or temperatures” of the receptacle holder refers to the increase or decrease of the temperature of the receptacle holder **2110**. Often, the increase or decrease of the temperature is determined relative to the ambient temperature. Included in the term is the ability to individually adjust the temperature of one or more receptacle wells **2120**, while separately adjusting the temperature of other receptacle wells within the same receptacle holder. Thus, the term may refer to uniformly raising/lowering the temperature of all receptacle wells **2120** within a receptacle holder **2110** or may refer to altering a subset of the receptacle wells **2120** within a single receptacle holder **2110**. As used herein, “ambient temperature” refers to the temperature of a surrounding environment, which may include a fluid (e.g., air or liquid) or solid structure.

[0239] The thermal element **2200** may be electrically connected to a controllable power source **2210** for applying a current across the element to alter the temperature thereof. Control of the power source **2210** can be carried out by an appropriately programmed processor **2220** (such as a computer) which receives signals from one or more thermal sensors **2610** (see FIG. **61**) in thermal communication with the receptacle holder **2110**, as discussed below, and/or signals from another processor that controls the automated process steps involved with temperature cycling processes.

[0240] The thermal element **2200** may be held in contact with a side surface **2115** (see FIG. **58**) of the receptacle holder **2110** by one or more supports **2240**, which may be positioned in sliding

engagement with the receptacle holder **2110**. As used herein, being positioned “in sliding engagement” refers to a non-fixed contact between adjacent surfaces of different parts of the apparatus described herein. Thus, when the apparatus **2100** includes two or more receptacle holders **2110**, each of the two or more receptacle holders are configured in sliding engagement with a support **2240**. As used herein, the term “support” refers to a rigid structure, which can be thermally-conductive. Exemplary materials from which a support may be made include, but are not limited to, aluminum, titanium, copper, steel, magnesium, metal composites, metal alloys, ceramics, plastics, plastic composites, or any suitable rigid thermally-conductive material. Supports may also comprise a structure formed of, or from, a combination of materials, for example, plastic, metal (including alloys and composites), ceramic, or a combination of different types of one or more of these materials.

[0241] As is known in the art, thermal elements may require a specific force to achieve adequate thermal contact with a component that is to be heated. For example, certain Peltier devices require a mounting force of approximately 150-300 psi to effectively transfer thermal energy to a device. With reference to FIG. **62**, the apparatus may include one or more cross-braces **2248** mounted to a support **2240**, and exerting a force  $F_1$  onto a front surface **2117** of a receptacle holder **2110**. Force  $F_1$  is sufficient to effect thermal transfer of energy from thermal element **2200** to receptacle holder **2110**. In certain embodiments, the apparatus includes one cross-brace **2248** for each receptacle holder **2110**. In other embodiments, the apparatus includes one cross-brace **2248** per row of receptacle holders **2110**. In such embodiments, the cross-brace generally incorporates a portion or layer having low thermal conductivity as the portion that directly contacts the receptacle holder **2110**. As discussed below, in other embodiments, a body **2300** having low thermal conductivity is used to exert the force required for thermal transfer of energy to the receptacle holder **2110**.

#### Cover

[0242] As shown in FIGS. **57**, **58**, and **64-68**, the apparatus **2100** may also include a cover **2350** that is positioned in movable association with the receptacle holder **2110**. As can be expected, the cover **2350** is movable between an open position (FIG. **64**) and a closed position (FIG. **65**) relative to the receptacle holder **2110**, and may be moved to any position between open and closed, as necessary. In the open position, the cover **2350** does not obstruct access to the receptacle wells **2120** within the receptacle holder **2110** (see FIG. **63**). When in the closed position, the cover **2350** will block and/or obstruct access to the receptacle wells **2120**. In addition, when closed, the cover **2350** may exert a force  $F_2$  onto any receptacle within a receptacle well **2120** to seat or secure the receptacle **2130** in the receptacle well **2120** (see FIG. **65**). As discussed above, because the receptacle well **2120** is configured to receive a receptacle **2130**, the force  $F_2$  exerted by the cover **2350** serves to ensure that the receptacle **2130** fits snugly within the receptacle well **2120**, thereby allowing maximal contact between the inner surface **2180** of the receptacle well **2120** and the receptacle **2130**.

[0243] The cover **2350** may be made from any rigid or semi-rigid material suitable for exerting downward pressure onto a receptacle disposed within a receptacle well. Exemplary materials from which the cover may be made include, but are not limited to, beryllium copper, spring steel, chrome vanadium, chrome silicon, phosphor bronze, stainless steel, aluminum, titanium, tungsten, metal alloys, metal composites, plastic, or any suitable rigid or semi-rigid material.

[0244] The cover **2350** may be movable by any suitable mechanical element included in the apparatus. In one embodiment, the cover **2350** is hingedly attached to the apparatus **2100** so as to enable movement between the open and closed positions. Attachment points include, but are not limited to any of the one or more supports of the apparatus or any suitable location within a housing containing the apparatus. As shown in FIG. **56**, the cover **2350** may be fixedly attached to a rigid rotatable member **2352**, which is in movable communication with one or more electric motors **2355**. The rotatable member may be rotatably mounted to opposing sides of the housing **2050** of the apparatus or opposing sides of additional support members thereof, and span a length

of the apparatus parallel to the orientation of one or more receptacle holders such that actuation of the rotatable member **2352** results in the cover **2350** being moved into the open or closed position relative to the one or more receptacle holders **2110**. In an exemplary embodiment, the rotatable member **2352** is a cylindrical rod having a circular cross-section and an axis of rotation at the center thereof, as shown in FIG. **67**, which is a sectional view taken along A'-A' in FIG. **66**. Exemplary materials from which the rigid rotatable member may be made include, but are not limited to, steel, titanium, aluminum, or any suitable rigid material. As used herein, the term "rotatably mounted" refers to any mounting orientation that allows the rotatable member to rotate about its center axis.

[0245] The cover **2350** may comprise one or more (i.e., 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, or more) flexible extensions **2360** attached to and extending laterally away from, the rigid rotatable member **2352**. Such flexible extensions **2360** are configured to make contact with at least a portion of a receptacle **2130** disposed within the receptacle holder **2110** when the cover is in, approaching, or for a short distance after leaving, the closed position. As contact is made between the flexible extensions **2360** and at least a portion of the receptacle **2130**, the flexible extensions **2360** flex while applying force F2 directly to at least a portion of the receptacle **2130**. In an exemplary embodiment, the cover **2350** includes two or more (i.e., 2, 3, 4, 5, 6, 7, 8, 9, 10, or more) flexible extensions **2360** extending in the same direction away from the rigid rotatable member **2352**. In certain embodiments, the flexible extensions **2360** extend laterally away from the hinged attachment of the cover **2350** to the apparatus **2100**. In frequent embodiments, the cover **2350** includes one flexible extension **2360** per receptacle well **2120** of a receptacle holder **2110**. Also in frequent embodiments, one flexible extension **2360** of the cover **2350** may contact at least a portion of more than one receptacle **2130** disposed within the receptacle holder **2110**. Likewise, more than one flexible extension **2360** may contact at least a portion of more than one receptacle **2130** disposed within the receptacle holder **2110**.

[0246] The cover **2350** of the present disclosure often comprises multiple components, such as flexible extensions **2360**, a rotatable member **2352**, or other elements, as a single molded cover unit, or in multiple elements comprising the entire cover unit. For example, the flexible extensions **2360** may be attached to the rotatable member **2352**, or a single material may comprise the rotatable member **2352** and the flexible extensions **2360**.

[0247] The apparatus **2100** may include a single cover **2350** in moveable association with all receptacle holders **2110** (not shown), or may include a single cover **2350** for each row of receptacle holders **2110**, or may include a single cover **2350** for each individual respective receptacle holder **2110**. Movement of each cover **2350** may be actuated by an electric motor **2355** disposed either within the apparatus **2100** or within the housing **2050** in which the apparatus is located. When the apparatus **2100** includes more than one cover **2350**, each cover **2350** may be actuated by its own motor **2355**, or more than one cover **2350** may be actuated by the same motor **2355**. As such, when the apparatus **2100** includes more than one cover **2350**, each cover **2350** may move independent of the next and/or more than one cover **2350** may be moved simultaneously. One of skill in the art would appreciate that independent movement of multiple covers utilizing a single motor may be provided through, for example, appropriate camming of its connection to each cover. The electric motor **2355** is electrically connected to a controllable power source **2210** for applying a current thereto. Control of the power source **2210** can be carried out by an appropriately programmed processor **2370** (such as a computer) which may receive signals from another processor that controls the automated process steps involved with temperature cycling processes.

[0248] With reference now to FIG. **68**, there is provided a second exemplary embodiment of an apparatus **2800** described herein. The description will be provided based on the differences from the first exemplary embodiment discussed above. As such any reference to like elements should be understood as described above.

[0249] As shown in FIG. **68**, the apparatus **2800** may also include a primary cover **2840** that is

fixedly positioned over the receptacle holder **2110**. The primary cover **2840** may be formed with one or more (i.e., 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, or more) securing arms **2845** in direct alignment with and circumventing each receptacle well **2120** of the receptacle holder **2110**. In certain embodiments, the primary cover **2840** is formed with four securing arms **2845** in direct alignment with and disposed in a surrounding arrangement with each receptacle well **120** of the receptacle holder **2110**. The securing arms **2840** are configured for securable attachment to at least a portion of the receptacle or cap **2135** that is attached to a receptacle **2130**. Such securable attachment is analogous to the force  $F_2$  exerted by the cover **2350**, as discussed above, for ensuring that the receptacle **2130** fits snugly within the receptacle well **2120**, thereby allowing maximal contact between the inner surface **2180** of the receptacle well **2120** and the receptacle **2130**. The securing arms can be made of any suitable material, including plastic, metal, or a metal composite.

[0250] The apparatus **2800** may further include a secondary cover **2850** fixedly positioned over the primary cover **2840**. The secondary cover **2850** may be formed with one or more (i.e., 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, or more) releasing arms **2855**, each in direct alignment and in sliding contact with the securing arms **2845** of the primary cover. In various embodiments, the securing arms **2845** of the primary cover include an angled surface **2847** upon which the corresponding releasing arm **2855** of the secondary cover **2850** may slide when actuated during an automated process. The secondary cover **2850** may further include one or more (i.e., 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, or more) actuators **2860** that are fixedly connected to the releasing arms **2855**, and are positioned such that when a force is applied thereon, the force is transferred from the actuator **2860** to the releasing arms **2855**, which in turn, press onto the angled surface **2847** of the primary cover **2840** and release the securable attachment to the cap **2135** that is attached to a receptacle **2130**.

[0251] It is therefore contemplated that the housing **2050** within which the apparatus **2800** is located will include at least one modified pipettor **2900**, as shown in FIGS. **69** and **70**. As shown in FIG. **69**, the modified pipettor **2900** is modified such that the plunger **2910** is slidably connected to one or more limbs **2915**, which are hingedly attached to the body **2920** of the modified pipettor **2900**. Thus, when the modified pipettor **2900** causes the plunger **2910** to be in a first position (as shown in FIG. **69**), the one or more limbs **2915** are in a retracted position such that a lower portions **2915** thereof are placed in close proximity to the body **2920**. When the modified pipettor **2900** causes the plunger **2910** to be in a lowered second position (as shown in FIG. **70**), the one or more limbs **2915** are then moved into an extended position such that the lower portions **2915** thereof are moved away from the body **2920**.

[0252] This modified pipettor **2900** is useful for engaging the secondary cover **2850** and pressing on the secondary cover **2820** in a downward movement that actuates the release of the securing arms **2845** by the physical action of the releasing arms **2855**. When the releasing arms **2855** are depressed in this manner, the securing arms **2845** are pulled axially away from the receptacle **2130** and cap **2135**, permitting its unencumbered release and lifting out by the pipettor. In such circumstances it is advantageous that the securing arms maintain contact with, and depress in a radially outward manner, the releasing arms **2855** for the time period required for the pipettor plunger **2910** to frictionally engage the receptacle cap and to lift the receptacle and cap vertically clear of the securing arms **2845**.

[0253] In certain embodiments, any of the apparatuses described herein will not include a cover or a mechanism to exert force  $F_2$  onto the capped receptacle **2130**. In such embodiments, the receptacle **2130** fits snugly within the receptacle well **2120**, thereby allowing maximal contact between the inner surface **2180** of the receptacle well **2120** and the receptacle **2130** without the need for a force  $F_2$ .

#### Optical Fibers

[0254] With reference now to FIGS. **72-74**, the apparatus **2100** further includes a plurality of (i.e., more than one) optical fibers **2400** to provide optical communication of a receptacle well with at least one of an excitation signal source **2500** and an emission signal detector **2510** (see FIG. **75**). In

one embodiment, the apparatus **2100** includes one optical fiber **2400** per receptacle well **2120**. Thus, when the apparatus **2100** includes ten receptacle wells **2120**, at least ten optical fibers **2400** will be provided to establish optical communication between the receptacle well **2120** and one or more excitation signal sources **500** and/or one or more emission signal detectors **2510**.

[0255] As used herein, an “optical fiber” refers to a flexible, transparent fiber made of glass or plastic that functions as a waveguide to transmit light between the two ends (i.e., the first end and the second end) of the fiber. Typically, optical fibers include a transparent core surrounded by an opaque cladding material with a lower index of refraction and low to no autofluorescence characteristics. It should be understood that an optical pathway or assembly comprising the optical fiber may optionally include one or more filters, lenses, etc., to modify and/or focus and excitation or emission signals passing therethrough. Optionally, the apparatus **2100** may include an optical interface **2440** between the first end **2410** of each optical fiber **2400** and the receptacle **2130** (see FIG. 75). Such optical interface **2440** may include a filter, lens, nose, cap, or any other element having desired optical properties. However, it should be understood that in various embodiments, the interface **2440** is not, and/or does not function as a lens. Exemplary interfaces **2440** useful in the apparatus include, but are not limited to, glass or plastic balls, noses or caps covering the first end **2410** of the optical fiber **2400**, or any suitable optically clear material.

[0256] The first end **2410** of each of the plurality of optical fibers **2400** is disposed outside, within, or extending through a through-hole **2170** of the receptacle well **2110**, thereby providing optical communication with a receptacle well **2120**, and/or a receptacle **2130** disposed within the receptacle well **2120**. When disposed within the receptacle well **2120**, as shown in FIG. 72, the first end **2410** of the optical fiber **2400** may be moveable within the through-hole **2170** of the receptacle well **2120** relative to the inner surface **2180** thereof. In various exemplary embodiments, a variety of means of movement of the first end **2410** of the optical fiber **2400** within the through-hole **2170** are contemplated. For example, the first end **2410** of the optical fiber **2400** may extend into the receptacle well **2120**, and when a receptacle **2130** is placed within the well **2120**, the receptacle **2130** contacts the first end **2410** of the optical fiber **2400**, thereby providing optical communication between the receptacle **2130** and the optical fiber **2400**. In an exemplary embodiment, the presence of a receptacle **2130** within the receptacle well **2120** will cause the optical fiber **2400** to move within the through-hole **2170** (e.g., through the application of a direct force) in a direction opposite from the inner surface **2180** of the receptacle well **2120** such that the receptacle **2130** can make maximal contact with the inner surface **2180** of the receptacle well **2120** while maintaining optical communication with the optical fiber **2400**, as shown in FIG. 74. In another embodiment, the downward force **F2** exerted by the cover **2350** and/or the flexible extensions **2360** of the cover **2350** onto at least a portion of a receptacle **2130** disposed within a receptacle well **2120** causes the optical fiber **2400** to move within the through-hole **2170** when the receptacle **2130** contacts the optical fiber **2400**. In such embodiments, the receptacle **2130** may apply a force **F3** to the first end **2410** of optical fiber **2400** in substantially the same direction as the force **F2** being applied to the receptacle, which is disposed within the well such that the end **2410** of the optical fiber **2400** moves within the well **2120**.

[0257] As shown in FIG. 75, the system may further include one or more excitation signal sources **2500** and one or more emission signal detectors **2510** to which the second ends **2430** of the optical fibers **2400** of the apparatus **2100**, **2800** included therein are in optical communication. Excitation signal sources **2500** and emission signal detectors **2510** contemplated by the present disclosure include, but are not limited to, fluorometers, luminometers, spectrophotometers, infrared detectors and charged-coupled devices. Each of these types of optical detection systems can be positioned within the housing of the apparatus **2100**, **2800**, within the housing of the system, or within the overall housing of the biochemical analysis instrument, as appropriate. Multiple types of signal sources **2500** and signal detectors **2510** may be movably mounted on a platform to facilitate different detection methods for different processes. The system may also include multiple detectors

of the same or different types for detecting signals emitted from different receptacles **2130** simultaneously. As discussed above, though FIG. 75 depicts separate optical fibers branching out to the excitation signal source **2500** and emission signal detector **2510**, certain embodiments of the present disclosure utilize a single optical fiber (e.g., a light pipe) between the excitation signal source **2500** and its corresponding emission signal detector **2510**.

#### Methods of Establishing Optical Communication

[0258] In another aspect, disclosed herein is provided a method for establishing optical communication between a receptacle and an excitation signal source and/or an emission signal detector within a housing of the apparatus while allowing maximal contact between the surface of the receptacle well and the receptacle (FIG. 76). As discussed in detail above, the method includes providing a receptacle **2130** to a receptacle well **2120** of a receptacle holder **2110** (step **S110**). Thereafter, a force **F2** is applied to the receptacle **2130** or at least a portion of the receptacle **2130**, such that the receptacle **2130** fits snugly within the receptacle well **2120**, thereby allowing maximal contact between the inner surface **2180** of the receptacle well **2120** and the receptacle **2230** (step **S120**). While force **F2** is being applied to at least a portion of the receptacle **2130**, movement of a first end **2410** of an optical fiber **2400** is effected toward the inner surface **2180** of the receptacle well **2120** (step **S130**). In such embodiments, the receptacle **2130** may apply a force **F3** to the optical fiber **2400** in substantially the same direction as the force **F2** being applied to the receptacle **2130**, to the first end **2410** of the optical fiber **2400**, which is disposed within the receptacle well **2120** such that optical communication is established between the bottom **2138** of the receptacle **2130** and the first end **2410** of the optical fiber **2400** (step **S140**). As discussed above, movement of the first end **2410** of the optical fiber **2400** is coordinated with movement of cover **2350** into the closed position. As such, the method may further include movement of the cover **2350** in coordination with the movement of the first end **2410** of the optical fiber **2400**.

[0259] Another exemplary embodiment of the method for establishing optical communication between a receptacle and an excitation signal source and/or an emission signal detector within a housing of the apparatus while allowing maximal contact between the surface of the receptacle well and the receptacle is shown in FIG. 77. In this embodiment, the method includes providing a receptacle **2130** to a receptacle well **2120** of a receptacle holder **2110** (step **S210**). Thereafter, a cover **2350** is moved into the closed position (step **S220**), thereby exerting a force **F2** onto the receptacle **2130** or at least a portion of the receptacle **2130**, such that the receptacle **2130** fits snugly within the receptacle well **2120**, thereby allowing maximal contact between the inner surface **2180** of the receptacle well **2120** and the receptacle **2130** (step **S230**). Prior to, during, or after movement of the cover **2350** into the closed position, movement of a first end **2410** of an optical fiber **2400** is effected toward and into contact with the seated receptacle **2130** (step **S240**). Upon contact of the first end **2410** of the optical fiber **2400** with the closed end **2138** of the receptacle **2130**, force **F4** is exerted by the first end **2410** onto the receptacle **2130**. In such embodiments, the receptacle **2130** may apply a force **F3**, which is greater than force **F4**, onto the first end **2410** of the optical fiber **2400** in substantially the same direction as the force **F2**. As such, optical communication is established between the first end **2410** of the optical fiber and the receptacle **2130**, while ensuring maximal contact between the receptacle **2130** and the inner wall **2180** of the receptacle well **2120** (step **S250**). As discussed above, movement of the first end **2410** of the optical fiber **2400** is coordinated with movement of cover **2350** into the closed position.

[0260] Often, the first end **2410** of each of the plurality of optical fibers **2400**, or an area **2420** proximal to the first end **2410** of each of the plurality of optical fibers **2400**, is connected, directly or indirectly, to a respective through-hole **2170** of a receptacle well **2120** with a resilient element **2600**, as discussed above. The resilient element **2600** thereby compresses and/or deforms as the optical fiber **2400** moves within the through-hole **2170**, and returns to its uncompressed and/or original form when the optical fiber **2400** returns to its rest position.

#### Signal Detection Module

[0261] Detection, and, optionally, measurement, of emission signals from emission signal sources, such as vials containing reaction materials undergoing amplification as described above can be performed in accordance with aspects of the present invention with a signal detection module. In an exemplary aspect, signal detector **432** comprises a signal detection module indicated by reference number **3100** in FIG. **78**. The signal detection module **3100** includes an upright reformatter frame **3150**. Two signal detector heads **3200** are attached to a lower end of the reformatter frame **3150** and an interface plate **3160** is attached to an upper end of the reformatter frame **3150**. In general, the reformatter frame includes sides **3152**, **3154** which, in the illustrated embodiment, comprise generally vertical columns, and a base **3156** within which are formed a plurality of fiber-positioning holes **3158**. Note that the designation of the reformatter frame **3150** as being upright or the sides **3152**, **3154** as being vertical is merely to provide a convenient reference with respect to the orientation of the signal detection module **3100** as shown in FIG. **78**, and such terms of orientation are not intended to be limiting. Accordingly, the signal detection module **3100** could be oriented at any angle, including vertical or horizontal, or any angle therebetween. The reformatter frame has a variety of purposes, including organizing and arranging a plurality of optical transmission fibers **3180** between an excitation/emission area and a detection area in an optimum optical pathway orientation. In particular embodiments the reformatter also provides for controlled orientation of a plurality of optical transmission fibers **3180** between the fins of a heat sink to a detection area.

[0262] The signal detector head **3200** is shown in FIG. **79**. The signal detector head **3200** may be attached to a reformatter frame **3150** and is constructed and arranged to index one or more signal detectors into operative positions with respect to each transmission fiber disposed in a fiber-positioning hole of the base of the reformatter frame. In the embodiment shown in FIG. **79**, the signal detector head **3200** includes a base plate **3220** configured to be attached to the base **3156** of the reformatter frame **3150** and including a plurality of fiber tunnels **3226** arranged in a configuration corresponding to the spatial arrangement of fiber-positioning holes **3158** formed in the base **3156** of the reformatter frame **3150** so that each fiber tunnel **3226** will align with a corresponding one of the fiber-positioning holes **3158**.

[0263] In general, the signal detector head is configured to move one or more signal detectors to sequentially place each signal detector into an operative position with respect to each transmission fiber **3180** to detect a signal transmitted by the transmission fiber. The signal detector head **3200** further includes a detector carrier **3250**, which, in the illustrated embodiment, comprises a carousel that carries a plurality of signal detectors **3300** in a circular pattern. In the illustrated embodiment, the signal detector head **3200** includes six individual signal detectors **3300**, each mounted on a printed circuit board **3210** and each configured to excite and detect a different emission signal or an emission signal having different characteristics.

[0264] Further details of the signal detector head **3200** are shown in FIG. **80**, which is a transverse cross-sectional view of the detector head **3200** along the line XIII-XIII in FIG. **79**. Each signal detector **3300** includes a detector housing **3302** within which are formed an excitation channel **3304** and an emission channel **3306**, which, in the illustrated embodiment, are generally parallel to one another. An excitation source **3308**, such as an LED, is mounted on the printed circuit board **3210** at the base of the excitation channel **3304**. An emission detector **3314**, such as a photodiode, is coupled to the printed circuit board **3210** and is disposed within the emission channel **3306**.

[0265] The detector carrier **3350** further includes, positioned adjacent the signal detector housing **3302**, a filter plate **3264** having a central opening **3276** formed therein and defining an annulus. Within the annulus, an emission filter opening **3282** and an excitation filter opening **3280** are formed in alignment with the emission channel **3306** and the excitation channel **3304**, respectively, of each signal detector housing **3302**. An excitation lens **3310** and an excitation filter **3312** are disposed in the excitation opening **3280**. Although a single excitation lens **3310** and a single excitation filter **3312** are shown in FIG. **80**, the signal detector **3300** may include multiple

excitation filters and/or multiple excitation lenses. Similarly, an emission filter **3316** and an emission lens **3318** are disposed in the emission opening **3282**. Although a single emission filter **3316** and a single emission lens **3318** are shown in FIG. **80**, the signal detector **3300** may include multiple emission lenses and/or multiple emission filters.

[0266] The detector carrier **3250** further includes, adjacent the filter plate **3264**, a mirror plate **3260** having a central opening **3262** and defining an annulus. The annulus of the mirror plate **3260** has formed therein openings aligned with the emission opening **3282** and the excitation opening **3280** formed in the filter plate **3264** for each signal detector **3300**. A mirror **3320** is disposed in the mirror plate **3260** in general alignment with the excitation channel **3304**, and a dichroic filter **3322** is disposed in the mirror plate **3260** in general alignment with the emission channel **3306**. Mirror **3320** is oriented at an angle (e.g. 45°) with respect to the excitation channel **3304** so as to be configured to redirect a light beam.

[0267] The detector carrier **3250** further includes an objective lens plate **3252** having a central opening **3256** formed therein and defining an annulus. A lens opening **3254** is formed through the annulus of the objective lens plate **3252** in general alignment with the emission channel **3306** of each signal detector **3300**. An objective lens **3324** is disposed within the lens opening **3254**.

[0268] The base plate **3220** is disposed adjacent the objective lens plate **3252** and includes fiber tunnels **3226** formed about the perimeter thereof. Although base plate **3220** and objective lens plate **3252** are depicted as abutting one-another in FIG. **80**, it is contemplated that there can be a designated distance, forming an air gap, between the base plate **3220** and the objective lens plate **3252**. Also, while objective lens plate **3252** and mirror plate **3260** are depicted as abutting one-another in FIG. **80**, it is contemplated that there can be a designated distance, forming an air gap, between the objective lens plate **3252** and the mirror plate **3260**.

[0269] The detector carrier **3250**, comprising the objective lens plate **3252**, the mirror plate **3260**, and the filter plate **3264**, as well as the signal detectors **3300** carried thereon, are rotatable with respect to the base plate **3220** so that each objective lens **3324** associated with each of the signal detectors **3300** can be selectively placed into operative alignment with one of the fiber tunnels **3226** disposed in the base plate **3220**. Thus, in the illustrated embodiment having six signal detectors **3300**, at any given time, six of the fiber tunnels **3226** are in operative, optical alignment with one of the objective lenses **3324** and its corresponding signal detector **3300**.

[0270] Operation of the signal detector **3300** in an exemplary embodiment is illustrated schematically in FIG. **81**. The detector **3300** shown is a fluorometer that is constructed and arranged to generate an excitation signal of a particular, predetermined wavelength that is directed at the contents of a receptacle to determine if a probe or marker having a corresponding emission signal of a known wavelength is present. When the signal detector head **3200** includes multiple fluorometers—e.g., six—each fluorometer is configured to excite and detect an emission signal having a different wavelength to detect a different label associated with a different probe hybridized to a different target analyte. When a more frequent interrogation of a sample is desired for a particular emission signal, it may be desirable to incorporate two or more fluorometers configured to excite and detect a single emission signal on the signal detector head **3200**.

[0271] An excitation signal is emitted by the excitation source **3308**. As noted above, the excitation source may be an LED and may generate light at a predetermined wavelength, e.g. red, green, or blue light. Light from the source **3308** passes through and is focused by an excitation lens **3310** and then passes through the excitation filter **3312**. As noted, FIG. **82** is a schematic representation of the signal detector **3300**, and the focusing functionality provided by the excitation lens **3310** may be affected by one or more separate lenses disposed before and/or after the filter element **3312**. Similarly, the filter functionality provided by the filter element **3312** may be affected by one or more individual filters disposed before and/or after the one or more lenses that provide the focusing functionality. Filter element **3312** may comprise a low band pass filter and a high band pass filter so as to transmit a narrow wavelength band of light therethrough. Light passing through the



excitation lens **3310** and excitation filter element **3312** is reflected laterally by the mirror **3320** toward the dichroic **3322**. The dichroic **3322** is constructed and arranged to reflect substantially all of the light that is within the desired excitation wavelength range toward the objective lens **3324**. From the objective lens **3324**, light passes into a transmission fiber **3180** and toward the receptacle at the opposite end thereof. The excitation signal is transmitted by the transmission fiber **3180** to a receptacle so as to expose the contents of the receptacle to the excitation signal.

[0272] A label that is present in the receptacle and is responsive to the excitation signal will emit an emission signal. At least a portion of any emission from the contents of the receptacle enters the transmission fiber **3180** and passes back through the objective lens **3324**, from which the emission light is focused toward the dichroic **3322**. Dichroic **3322** is configured to transmit light of a particular target emission wavelength range toward the emission filter **3316** and the emission lens **3318**. Again, the filtering functionality provided by the emission filter **3316** may be affected by one or more filter elements and may comprise a high band pass and low band pass filter that together transmit a specified range of emission wavelength that encompasses a target emission wavelength. The emission light is focused by the emission lens **3318**, which may comprise one or more lenses disposed before and/or after the filter elements represented in FIG. **81** by emission filter **3316**. The emission lens **3318** thereafter focuses the emission light of the target wavelength at the detector **3314**. In one embodiment, the detector **3314**, which may comprise a photodiode, will generate a voltage signal corresponding to the intensity of the emission light at the prescribed target wavelength that impinges the detector.

#### Centrifuge

[0273] As shown in FIGS. **1**, **5**, and **6**, centrifuge **588** can be located on the amplification processing deck **430** of the second module **400**. In one exemplary embodiment, the centrifuge **588** will centrifuge one or more (up to five in one embodiment) capped processing vials **464**, **1100** at a time. In an exemplary embodiment, each vial is centrifuged before PCR to ensure that sample material is concentrated primarily in the bottom of the processing vial **464**, **1100** and to remove any air bubbles from the contents of the vial **464**, **1100**, which can affect heat transfer and optical transmission quality. The substance transfer pipettor **410** of the front arm **408** places the capped vial **464**, **1100** into the centrifuge **588** at an access port indicated at reference number **589**. After centrifuging is complete, the vial transfer arm **418** of the back arm **416** removes the capped vial **464**, **1100** from the centrifuge **588** at an access port indicated at reference number **587** and places it in the thermal cycler **432**. In an embodiment, the centrifuge configuration (e.g., by providing separate ports **587**, **589**) allows the substance transfer pipettor **410** (front arm **408**) and the vial transfer arm **418** (back arm **416**) to load/unload capped vials **464**, **1100** simultaneously without colliding with each other. As such, in one embodiment, the centrifuge not only performs its function of providing centrifugation of loaded vials, but also functions as a vial transport mechanism by transporting capped vials **464**, **1100** from a position **589** accessible to the substance transfer pipettor **410** to a position **587** where the capped vials **464**, **1100** are accessible to the vial transfer arm **418**. In certain embodiments the substance transfer pipettor **410** is unable to access position **587** and the vial transfer arm **418** is unable to access position **589**.

[0274] In addition, the centrifuge **588** may be configured to track the position(s) of the loaded vial(s) within the centrifuge and determine when a vial is positioned at either access port **587**, **589**. For example, a turntable or other rotating structure on which the loaded vial(s) is (are) centrifuged may be driven by a stepper motor that may include a rotary encoder for precise movement of the turntable and tracking motor counts and/or the turntable or rotating structure may include a rotational position indicator, such as a home flag sensor, configured to indicate one or more rotational positions or reference points.

[0275] In one exemplary embodiment, the maximum revolution speed of the centrifuge is 3000 revolutions per minute, but other revolution speeds are contemplated based on, inter alia, the composition of the solution being centrifuged and the time period required to provide adequate

centrifugation.

## Receptacle Distribution System and Rotary Distributor

[0276] In one embodiment, the receptacle distributor, which is configured to move a receptacle onto the receptacle distributor at a first location on the second module, carry the receptacle from the first location to a second location on the second module that is different from the first location, and move the receptacle off the receptacle distributor at the second location on the second module, comprises a rotary distributor. In an exemplary embodiment, the rotary distributor of the receptacle distribution system does not constitute a robotic pipettor, such as substance transfer and handling device **402** described above, or other substance transfer device comprising a vial transfer arm that is supported on a structure for automatically moving the pipettor in different Cartesian directions (i.e., a x-y-z directions), but is also a 3-axis robot designed to transport MRDs **160** and reagent packs **760** between different components of the second module **400**. In one exemplary embodiment, rotary distributor **312** works by a hook and rail system in which an extendible and retractable hook pulls or pushes MRDs **160** or reagent packs **760** into or from a distributor head of the rotary distributor **312**. Within the distributor head, the MRD **160** or reagent pack **760** is supported and guided by rail and wall features within the head. The rotary position of the distributor head is controlled and monitored by a rotary encoder on the motor for position feedback and has a home sensor. The distributor hook may be belt driven with home and end of travel sensors (e.g., slotted optical sensors, limit switches, etc.). The rotary distributor **312** is also configured for powered, vertical (or z-axis) motion of the distributor head for vertical translation of an MRD **160** or reagent pack **760**. In one exemplary embodiment, the rotary distributor **312** is configured to allow for at least 100 mm of z-axis travel. The distributor head may include an MRD/reagent pack presence sensor in the head. In one exemplary embodiment, the rotary distributor is configured to transfer an MRD **160** between any two modules of the second module **400** within four seconds. In certain embodiments, each axis can make a full travel move in approximately one second.

[0277] Details of an exemplary receptacle distribution system are shown in FIGS. **27** and **28**. In the illustrated embodiment, a receptacle distribution system **200** includes a frame **202** comprising legs **203**, **204** and **205** extending between a bottom panel **208** and a top panel **206**. The receptacle handoff station **602** is mounted on a handoff station bracket **606** attached to the bottom panel **208** of frame **202** and will be discussed further below. Magnetic elution slots **620** and reagent pack loading stations **640** are supported on a bracket **642** attached to legs **204** and **205** of frame **202** and will be discussed further below. A rotary distributor **312** is supported on a first upright wall **218** and a second upright wall **220** within the frame **202**.

[0278] Details of an exemplary rotary distributor **312** are shown in FIGS. **29-31**. The exemplified rotary distributor **312** includes a distributor head **314** defining a partial enclosure for holding an MRD **160** or reagent pack **760** and a receptacle hook **318** configured to engage the manipulating structure **166** of an MRD **160** or the manipulating hook **764** of the reagent pack **760**.

[0279] A hook actuator system **316** linearly translates the receptacle hook **318** with respect to the distributor head **314** between an extended position, as exemplified in FIG. **30**, and a retracted position, as exemplified in FIG. **29**. The exemplified hook actuator system **316** includes a hook carriage **320** to which the receptacle hook **318** is attached. A drive belt **344** is attached to the hook carriage **320** by a screw and bracket indicated at **322**. Drive belt **344** is carried on a drive wheel **334** and idler wheels **336**, **338**, **340**, **342**. Although exemplified using a drive belt-based system, it is understood that other mechanisms, such as screw-drive systems and linear piston actuators, are equally suited for the hook actuator system.

[0280] Referring to FIG. **31**, which is a perspective of an opposite side of the distributor head **314**, a drive belt motor **370** having a rotary encoder **372** is attached to the distributor head **314**. Drive belt motor **370** is coupled to the drive wheel **334** that drives the drive belt **344** of the hook actuator system **316**.

[0281] The hook actuator system **316** can include a belt tensioner **346** for maintaining proper tension in the belt **344**. Belt tensioner **346** includes a pivoting idler wheel bracket **348** to which idler wheel **336** is attached and which is pivotally attached to the distributor head **314** by a pivot screw **352**. A slot **350** is formed in an end of the pivoting idler wheel bracket **348**, and a position lock screw **354** extends through the slot **350** into the distributor head **314**. A spring **356** bears against a portion of the pivoting idler wheel bracket **348**. Tension in the belt **344** can be adjusted by loosening the position lock screw **354**, thereby allowing the spring **356** to pivot the pivoting idler wheel bracket **348** and thus urge the idler wheel **336** upwardly to create the proper tension in the drive belt **344**. When proper tension is achieved in the drive belt **344**, the position lock screw **354** can thereafter be retightened.

[0282] The hook carriage **320** includes a rail channel **324** that translates along a hook carriage guide rail **330** attached to an upper, internal portion of the distributor head **314**. The receptacle hook **318** is attached to a mount **326** disposed between the rail channel **324** and the hook **318**.

[0283] A hook home sensor, e.g., a slotted optical sensor or limit switch, may be provided to indicate when the hook **318** is in the retracted, or “home,” position when a sensor flag extending from the mount **326** extends into the slotted optical sensor. Other types of sensors may be used for indicating a home position, such as proximity sensors, magnetic sensors, capacitive sensors, etc. The receptacle hook **318** and hook carriage **320** are operatively coupled for electronic communication with the remainder of the rotary distributor **312** by means of a flexible cable **366** attached at one end to the hook carriage **320** and at a printed circuit board or other connector located on the distributor head **314**. Strain reliefs **368** and **369** may be provided for securing the flexible cable **366** to the distributor head **314** and the hook carriage **320**, respectively.

[0284] FIG. **32** illustrates a manner in which a reagent pack **760** may be transported within the module **400** by means of the rotary distributor **312**. As shown in FIG. **32**, the rotary distributor **312** may be configured to receive and hold a reagent pack **760** that is pulled into the distributor **312** by the manipulating hook of the rotary distributor **312** with the bottom edge **765** of the pack **760** supported on a rail **373** formed on the inner walls of the distributor **312**.

[0285] Similarly, FIG. **33** illustrates a manner in which an MRD **160** may be transported within the module **400** by the rotary distributor **312**. As shown in FIG. **33**, the rotary distributor **312** may be configured to receive and hold an MRD **160** that is pulled into the distributor **312** by the manipulating hook of the rotary distributor **312** with the connecting rib structure **164** of the MRD **160** supported on a rail **373** formed on the inner walls of the distributor **312**.

[0286] The receptacle distribution system **200** includes a distributor moving device configured to move the distributor head **314** in a circular path or in a vertical, linear path. More specifically, in one exemplary embodiment, the distributor moving device includes a rotary drive system **212** configured to move the distributor head **314** in a circular path and an elevation system **230** configured to move the distributor head **314** in a vertical direction.

[0287] Details of an exemplary rotary drive system **212** are shown in FIGS. **27**, **28**, **34**, and **35**. Although in certain embodiments, it is contemplated that the rotary drive system **212** is configured to freely rotate in 360°, it is understood that in at least certain embodiments the rotary drive system **212** is configured to rotate 180° between the two respective loading positions.

[0288] The first upright wall **218** and the second upright wall **220**, on which the distributor head **314** is supported, are mounted onto a turntable **214** that is mounted for rotation about its central axis on the bottom panel **208** of the frame **202**. A motor **222**, attached to the bottom panel **208** and having a rotary drive **224**, such as a rotary drive gear, extending above the bottom panel **208**, engages peripheral teeth of the turntable **214** so that powered rotation of the motor **222** effects rotation of the turntable **214**, as well as the first and second upright walls **218**, **220** and the distributor head **314** supported thereon. Although exemplified as having teeth configured to engage each other, it is understood that the rotary drive **224** and the turntable **214** can engage each other without having toothed parts. In such an embodiment, both the rotary drive and the turntable can be

wheels with rubberized outer surfaces to facilitate traction. Rotary motor **222** is preferably a stepper motor for providing precise control of the rotation of the turntable **214** and preferably includes a rotary encoder **223** for providing rotational position feedback to a control system controlling the rotary motor **222**. Other means for rotationally coupling the distributor head **314** to the motor **222** are encompassed within this disclosure and include, for example, belt(s) and pulley(s), gear trains comprising one or more gears, drive shafts and worm gears, etc.

[0289] As shown in FIG. **35**, a positional sensor **226**, which may comprise a slotted optical sensor including an optical transmitter-receiver pair, provides a rotational position feedback signal of the turntable **214**. Optical sensor **226** may be configured to detect a passing of one or more positional flags on the turntable **214** for indicating one or more specific rotational positions. Sensor **226** includes prongs, or portions, located above and below the turntable **214** and thus the positional flag(s) may comprise one or more openings (e.g., **227**) formed through the turntable. Passage of an opening between the portions of sensor **226** located above and below the turntable **214** complete the optical signal transmission between the transmitter and receiver portions of the sensor **226** and thus generate a signal corresponding to the passage of the opening. Other types of sensors may be used for indicating particular rotational positions, including proximity sensors, magnetic sensors, capacitive sensors, etc.

[0290] A second optical sensor **228** may be provided below the turntable **214**. Sensor **228** may comprise a slotted optical sensor including an optical transmitter-receiver pair for detecting the passage of one or more sensor flags (not shown) extending beneath the turntable **214** for indicating a rotational position. Other types of sensors may be used for indicating a home position, including proximity sensors, magnetic sensors, capacitive sensors, etc.

[0291] Details of a distributor elevation system **230** are shown primarily in FIG. **35**. The depicted elevation system **230** includes a threaded rod **232** extending upwardly from the turntable **214** through a motor **234** and internal thread drive **236** mounted to the distributor head **314** (see also FIG. **31**). Rotation of the internal thread drive **236** by the motor **234** causes the motor and the distributor head **314** to which it is attached to translate up or down the threaded rod **232**. A guide rail **238** extends vertically up one edge of the second upright wall **220**, and the motor **234** is coupled to the guide rail **238** by a rail coupling **240**. Alternatives to the threaded rod and the internal thread drive for moving the distributor head **314** vertically are encompassed in this disclosure and include, for example, a rack and pinion or a belt drive system.

[0292] Referring to the embodiment of FIGS. **27**, **28**, and **34**, a sensor **246** extends below the distributor head **314**. As the distributor head **314** is lowered by the elevation system **230**, separate prongs of the sensor **246** extend into openings **216** formed in the turntable **214**. Sensor **246** may be a slotted optical sensor with the prongs thereof forming a transmitted-receiver pair. An optical signal between the spaced prongs is broken when the prongs enter the openings **216**, thereby sending a signal to a control system that the distributor head **314** is at its lowermost position. Other types of sensors may be used for indicating a down position for the distributor head **314**, including, for example, proximity sensors, magnetic sensors, capacitive sensors, etc.

[0293] Data and power are communicated between the rotary distributor **312** and the module **400** by means of a coiled cable **244** that can accommodate rotation of the rotary distributor **312** with respect to the frame **202** by, for example, 180° in either direction.

[0294] To transfer an MRD **160**, the distributor head **314** is rotated a few degrees by the rotary drive system **212** of the rotary distributor **312**, the hook **318** is extended by the hook actuator system **316**, and the head **314** is rotated in an opposite direction to engage the manipulating structure **166** of the MRD **160**. The distributor hook **318** is then retracted, and the MRD **160** is coupled to the distributor head **314**. Similarly, to transfer a reagent pack **760**, the distributor head **314** is rotated a few degrees by the rotary drive system **212**, the hook is extended by the hook actuator system **316**, and the head **314** is then rotated in the opposite direction to engage the manipulating hook **764** of the reagent pack **760**. The distributor hook **318** is then retracted, and the

reagent pack **760** is pulled into the distributor head **314**.

#### Receptacle Handoff Device

[0295] The receptacle handoff device **602** is configured to transfer a receptacle, such as the MRD **160**, between the receptacle distributor **150** of the first module **100** and the rotary distributor **312** of the second module **400**. Both the receptacle distributor **150** of the first module **100** and the rotary distributor **312** of the second module **400** manipulate the MRD **160** using a hook or other similar device to engage the manipulating structure **166** of the MRD **160**. Therefore, after the MRD **160** is disengaged by the receptacle distributor **150** of the first module **100**, the MRD **160** is positioned and oriented in such a manner as to present the manipulating structure **166** to the rotary distributor **312** of the second module **400**. The handoff device **602** performs this function.

[0296] Details of the handoff device **602** are shown in FIGS. **27**, **28**, **39**, **40**. The receptacle handoff device **602** comprises a receptacle yoke **604** configured to receive and hold an MRD **160** placed into the yoke **604** by the receptacle distributor **150** of the first module **100**. The yoke **604** is mounted on a handoff device bracket **606**, attached to and extending from the bottom panel **208** of the frame **202**, so as to be rotatable about a vertical axis of rotation. In one exemplary embodiment, the yoke **604** is coupled to a handoff device motor **680** attached to the bracket **606**. Motor **680** may be a stepper motor for precise motion control and may include a rotary encoder **682** for providing rotational position feedback of the receptacle yoke **604** to a controller. A sensor **684**, which may be a slotted optical sensor comprising an optical transmitter-receiver pair, is mounted to the bracket **606** and detects a home flag **686** extending from the yoke **604** for providing rotational position feedback. Other types of sensors may be used for providing position or orientation feedback, including proximity sensors, magnetic sensors, capacitive sensors, etc. After the MRD **160** is placed in the yoke **604** by the receptacle distributor **150** of the first module **100** and the receptacle distributor **150** disengages the MRD **160**, the housing **604** is rotated to present the manipulating structure **166** of the MRD **160** to the rotary distributor **312** of the second module **400**.

[0297] Alternatively, the handoff device **602** may be passively actuated by the rotary distributor **312**. For example, the handoff device rotation may be tied to the rotation of the rotary distributor **312** (e.g., via a cable, belt, gear, or other means) such that when the rotary distributor **312** rotates to the handoff position, the handoff device **602** would spin around to face the rotary distributor **312**. When the rotary distributor **312** rotates away from the handoff device **602**, the handoff device **602** would rotate back toward the receptacle distributor **150** of the first module **100**.

#### MRD Storage Station

[0298] As shown in FIG. **14**, the MRD storage stations **608**, **610**, **612** are located on the receptacle processing deck **600** of the second module **400** and serve as temporary locations for MRDs in the second module **400**. Storage stations **608**, **610**, **612** include a number of slots **614**, each configured to receive an MRD **160**. The storage stations **608**, **610**, **612** are arranged in an arc, thereby accommodating the rotational path of motion of the rotary distributor **312**. Providing additional storage for MRDs within second module **400** provides the advantage of enhancing workflow by permitting flexibility in the timing that any particular MRD, or contents thereof, is/are utilized within second module **400**. This permits MRDs that may arrive in second module **400** later to be processed out of order, for example, to address urgent needs in a laboratory.

[0299] Although exemplified as having three MRD storage stations **608**, **610**, **612**, it is understood that embodiments can be constructed having two or more such storage stations. Similarly, although exemplified as being configured in an arc arrangement, it is understood that the distributor **312** in certain embodiments does not rotate about an arc and that the arc arrangement is convenient for the rotary distributor **312** embodiment. To the extent that an alternate configuration of the distributor **312** is implemented, the MRD storage stations similarly would match the alternate arrangement to maximize workflow of the system.

#### Magnetic Elution Slots/Reagent Pack Loading Stations

[0300] The magnetic elution slots **620** (two in the illustrated embodiment) and the reagent pack

loading stations **640** are supported on a bracket **642** attached to frame **202**. The purpose of each magnetic elution slot **620** is to hold an MRD **160** and apply magnetic force to the contents of the MRD to pull the magnetic beads to the side walls of each receptacle **162** while the substance transfer pipettor **410** aspirates the eluate fluid from the receptacles **162**.

[0301] Details of the magnetic elution slots **620** and the reagent pack loading stations **640** are shown in FIGS. **36-38**. Each magnetic elution slot **620** comprises a block **622** within which is formed a slotted opening **624**. An MRD **160** placed within the slotted opening **624** is supported within the opening **624** by the connecting rib structure **164** of the MRD **160** resting on the top of bracket **642**. The manipulating structure **166** extends out of the opening **624**, and a cutout **632** in each side wall of the block **622** enables the hook **318** of the rotary distributor **312** to move laterally into or laterally out of the MRD manipulating structure **166** of an MRD **160** located within the slotted opening **624**. The top of the MRD is uncovered, thus enabling pipettor access to the receptacles **162** of the MRD **160** held within the elution slot **620**. Magnets **628** are attached to or embedded within one or both walls defining the slotted opening **624**. Individual magnets **628** may be provided for each receptacle **162** of the MRD **160**, as shown in FIGS. **37** and **38**, or a single magnet may be provided for a receptacle that comprises one or more individual receptacles.

[0302] The reagent pack loading stations **640** are defined by spaced-apart, hold-down features **644** extending above the bracket **642** and a backstop **646** defining a back end of each reagent pack loading station **640**. A reagent pack **760** is inserted between the hold-down features **644**, under a lateral flange, and is pushed into the loading station **640** until the back end of the reagent pack **760** contacts the backstop **646**.

#### Reagent Pack Trash Chute

[0303] A reagent pack trash chute **428** is supported on the bracket **642**. In an exemplary embodiment, reagent pack trash chute **428** includes an entrance structure, defined by side walls **434**, **436** and a top panel **438**, through which a reagent pack **760** is inserted into the trash chute **428**. Side walls **434**, **436** are attached to the top of the bracket **642** and are bent or flared outwardly at their forward edges to provide a funneling entrance to the trash chute **428**. Resilient tabs **442** extend down from the top panel **438**.

[0304] To discard a reagent pack **760**, the rotary distributor **312** inserts the pack **760** into the trash chute **428** between the side walls **434**, **436**. When the reagent pack **760** is inserted into the trash chute **428**, there is a clearance between the top panel **438** and the top of the reagent pack **760**. The resilient tabs **442** bear against the top of the reagent pack **760** and hold the reagent pack **760** down within the trash chute **428**. The angle of the resilient tabs **442** permits the reagent pack **760** to be pushed into the trash chute **428**, but resists movement of the reagent pack **760** out of the trash chute.

[0305] When a subsequent reagent pack **760** is inserted into the reagent pack trash chute, it is pushed against the reagent pack **760** previously inserted into the trash chute **428**, thereby pushing the previously-inserted pack further into the trash chute **428**. A cut-out **648** is formed in the bracket **642**, so the previously-inserted pack **760** eventually falls from the trash chute **428** and, guided by a guide ramp **444** extending down from the bracket **642**, into a trash bin located below the trash chute **428**.

#### Reagent Pack Changer

[0306] Details of an exemplary reagent pack changer **700** are shown in FIGS. **15-17**. The purpose of the reagent pack changer **700** is to provide fully independent reagent pack loading and test execution whereby an operator may place reagent packs in a reagent pack input device and/or remove reagent packs **760** from the reagent pack input device while previously loaded reagent packs **760** are stored within a storage compartment, which may be temperature controlled, and are available for access by the instrument independently of the status of the reagent pack input device. The reagent pack changer is configured to move reagent packs **760** between the reagent pack input device and the storage compartment.

[0307] As shown in FIGS. 15-17, in one exemplary embodiment, the reagent pack input device comprises a reagent pack carousel compartment **702** which may be pulled open from the second module **400** and which contains a rotatable reagent pack carousel **704**. The pack carousel **704** includes a number of reagent pack stations **706**, each of which is adapted to receive and carry a reagent pack **760** and which are defined by radially inner dividers **708** and radially outer dividers **710**. As can be seen in FIGS. 15-17, the reagent pack stations **706** of the reagent pack carousel **704** are arranged about the outer perimeter of the reagent pack carousel **704**, but the elongated reagent pack stations **706**, and reagent packs **760** carried thereby, are not oriented in a radial direction with respect to the center of the reagent pack carousel **704**. Each reagent pack station **706** is oriented at an angle (e.g. 5-20°) with respect to a true radial orientation. This configuration of reagent packs optimizes the placement of reagent packs **760** on the carousel **704**, thereby enabling the reagent pack carousel **704** to carry the maximum number of reagent packs **760** and providing access of identifiable indicia present on each reagent pack **760** to the barcode reader **774**.

[0308] A gap **712** between each inner divider **708**—outer divider **710** pair enables an operator to insert his or her fingers into the gap **712** to thereby grasp the sides of the reagent pack **760** for placing the reagent pack **760** into the reagent pack station **706** or for removing the reagent pack **760** from the reagent pack station **706**. Each reagent pack station **706** of the reagent pack carousel **704** also includes an alignment block **714** at a radially inner end of the reagent pack station **706**. The alignment block within the rear recess **770** of the reagent pack **760** helps to maintain the proper alignment and position of the reagent pack **760** within the reagent pack station **706**.

[0309] In some embodiments, the reagent pack carousel compartment **702** includes a carousel frame **716**, preferably disposed on a track that enables the frame **716** to be slid into or out of the module **400** as a drawer. The frame **716** includes a drawer front **720**. The reagent pack carousel **704** is rotatably disposed within the frame **716**, which may include a circular recess **722** shaped so as to conform to the reagent carousel **704**.

[0310] The reagent pack carousel **704** is motorized to effect powered rotation of the carousel. In one exemplary embodiment, the reagent pack carousel compartment **702** may include a motor (not shown) that is coupled, for example by a belt and pulley arrangement (not shown), to the reagent pack carousel **704** for powered rotation of the reagent pack carousel **704**. The motor may be mounted to the reagent pack carousel frame **716** and move in and out with the reagent pack carousel compartment **702**, connected to the module **400** by a flex cable. The reagent pack carousel compartment **702** may include one or more position sensors for detecting when the carousel is in an open or closed position and communicating a corresponding signal to the system controller. Such sensor(s) may include optical sensors, proximity sensors, magnetic sensors, capacitive sensors, etc.

[0311] The reagent pack carousel compartment **702** may also include a software-controlled lock.

[0312] The reagent pack carousel compartment **702** can also include one or more sensors for tracking the positions of the reagent pack station **706**. For example, the reagent pack carousel **704** may include a home flag, such as a tab and an optical sensor that detects the position of the tab at a specified rotational position of the reagent pack carousel **704**. Other types of sensors may be used for indicating a home position, including proximity sensors, magnetic sensors, capacitive sensors, etc. Furthermore, the motor driving the reagent pack carousel **704** may be a stepper motor including a rotary encoder for generating signals corresponding to a rotational position of the reagent pack carousel **704**.

[0313] The second module **400** may include a machine pack reader configured to read a machine code provided on each reagent pack **760** providing information regarding the reagent pack **760**, such as the identity of the assay reagents carried within the reagent pack **760**, manufacturer, lot number, expiration date, etc. The machine code may also include a unique identifier specifically identifying that particular reagent pack **760**. The machine code reader device may comprise a barcode reader **774** configured to read a barcode label **772** disposed on the reagent pack **760**.

Barcode label **772** may be a two dimensional or one dimensional barcode. A scanning slot **718** formed in the carousel frame **716** provides an opening through which the barcode reader **774** may read a label **772** on the reagent pack **760**. Similarly, the orientation of the reagent pack **760** carried in the pack station **706** of the pack carousel **704**, may be set at an angle with respect to a true radial orientation, and the shape of the outer dividers **710**, being generally trapezoidal in shape, creates a clearance opening through which the barcode reader **774** can read the barcode label **772** disposed on the reagent pack **760**. Together with the rotary encoder, the barcode reader **772** provides an indication where each reagent pack **760** is positioned within each reagent pack station **706** of the reagent pack carousel **704**. Although a barcode scanner is exemplified, the use of other technologies such as RFID and QR codes are contemplated.

[0314] Each reagent pack station **706** may include a station empty barcode disposed on a side of each outer divider **710** that will be read by the barcode reader **774** if a reagent pack **760** is not positioned within the reagent pack station **706**.

[0315] In another exemplary embodiment, the reagent pack input device comprises an alternative reagent pack carousel **730** shown in FIG. **18**. Reagent pack carousel **730** is not carried on drawer be pulled out of the module **400**, but instead, includes radially oriented reagent pack stations **732** arranged about the perimeter of the reagent pack carousel **730** and is accessible through a slot in front of the second module **400** which may be covered by a door that is openable by the operator. Powered rotation of the reagent pack carousel **730** may be provided by a carousel drive system that may include a motor **734** having an output drive wheel **736** that is coupled to a drive pulley **739** of the carousel **730** by means of a drive belt **738**. Motor **734** may comprise a stepper motor having a rotary encoder, and a home flag may be provided on the carousel **730** to detect and monitor the rotational position of the reagent pack carousel **730** and thus each reagent pack station **732**.

[0316] FIG. **18** also shows an exemplary embodiment of a reagent pack storage compartment represented by reference number **740**. The storage compartment **740** is disposed beneath the reagent pack carousel **730**. In the embodiments described above, the reagent pack carousel compartment **702** would be disposed within the module **400** above the storage compartment **740** and would be movable with respect thereto.

[0317] In some embodiments, storage compartment **740** includes a housing **742** that defines a temperature controlled chamber therein. The desired storage temperature may be as low as 4° C., but could be any temperature at or below ambient temperature, for example, 15° C. In some embodiments, the chamber of the storage compartment **740** further has a humidity control module configured to control the humidity level of the air circulating within the temperature controlled chamber. As part of this process, the humidity control module is optionally equipped to collect condensed water, and route it outside the cooled storage area for disposal.

[0318] Housing **742** may be insulated and may be cooled by Peltier devices that can be mounted directly onto the housing **742** or by Peltier devices coupled to a heat cools a fluid, such as water or a refrigerant, which is circulated around the housing **742**. In one embodiment the storage compartment **740** is cooled by two separate Peltier devices mounted directly onto the housing **742**, each at different temperatures or temperature ranges. In this embodiment the first Peltier device is held at a temperature close to the freezing temperature of water. The second Peltier device is provided at a location within the storage compartment **740** distant or adjacent to that of the first Peltier device and is provided at a temperature higher than that of the first Peltier device, e.g., 15° C. The second Peltier device is in operable communication with a temperature sensor within the storage compartment **740**, positioned near the top of the storage compartment **740**. The second Peltier device would operate based on the measured temperature to maintain a predetermined temperature in the storage compartment **740**. In this embodiment a fan may be provided within the storage compartment **740** to cause air circulation within the storage compartment **740** through the fan, and past the first and second Peltier devices. When air passes the first Peltier device, which is held at a very low temperature, the air will cool, thus decreasing its capacity to hold moisture



which moisture will condensate on the Peltier device or another designated element. Therefore, this dual Peltier device embodiment provides both a temperature and humidity controlled environment, which is beneficial for increasing the shelf-life of lyophilized reagents which are vulnerable to rapid degradation in the presence of increased temperatures and atmospheric moisture.

[0319] Other ways to cool and/or dehumidify the storage compartment **740** are contemplated and the disclosure is not limited to the exemplified embodiments.

[0320] The housing **742** should be provided with a liquid collection and/or drainage system for handling condensing liquid inside the housing **742**. Such a system may, for example, include piping for directing the collected condensate away from the housing **742** and to a drain or an evaporator.

[0321] A storage carousel **744** is rotatably mounted within the housing **742**, for example, on shaft **745**. Storage carousel **744** includes a plurality of pack stations **746** disposed around the perimeter thereof and positioned on one or more levels of the carousel **744**. In the illustrated embodiment, storage carousel **744** includes pack stations **746** on two levels, one above the other.

[0322] A carousel drive can power rotation of the storage carousel **744** within the storage compartment **740**. The carousel drive may include a motor **748**, which may be a stepper motor, having an output drive wheel **750** coupled by means of a drive belt **752** to a drive pulley **749** of the pack carousel **744**. Motor **748** may be located outside the housing **742**—to keep heat generated by the motor **748** from heating the storage compartment **740**—and the drive belt **752** may extend through an opening in the housing **742**. Alternatively, a drive pulley coupled to the carousel **744** may be located outside the housing **740**. The motor **748** may include a rotary encoder, and the reagent pack carousel **744** may include a home flag for monitoring the rotational position of each of the reagent pack stations **746** of the pack carousel **744**.

[0323] Operation of the reagent pack changer **700** will now be described.

[0324] After the reagent packs **760** are placed in the reagent pack carousel **704** or reagent pack carousel **730** of the pack input device, the barcode of each reagent pack **760** is read by a barcode reader **774** and the identity and other information provided by the barcode is associated with a particular reagent pack station **706, 732** of the reagent pack carousel **704**. Alternatively, the reagent packs **760** may be scanned externally of the module **400**, for example, by a hand operated barcode scanner, before the reagent pack **760** being placed into the pack input device.

[0325] After reagent packs **760** have been placed into the reagent pack input device, such as reagent pack carousel **704** or reagent pack carousel **730**, pack carousel compartment **702** is shut or a door in front of the carousel access opening is closed. Next, the rotary distributor **312** removes one or more reagent packs **760** from the reagent pack carousel **704, 730** and moves the reagent pack **760** into a pack station **746** of the storage carousel **744** of the storage compartment **740**. As shown in FIG. **16**, the carousel frame **716** of the reagent pack carousel compartment **702** includes a reagent pack access slot **724** through which the rotary distributor **312** can access the manipulating hook **764** of a reagent pack **760** disposed within the reagent pack station **706**. To enable the rotary distributor **312** to transfer reagent pack **760** between the reagent pack input carousel **704** or **730**, to the one or more levels of the storage carousel **744** of the storage compartment **740**, the rotary distributor **312** provides powered and controlled vertical, i.e., z-axis, motion. It is preferable that access to the reagent pack access slot **724** by the rotary distributor **312** is controlled by a door when the reagent carousel **704** or **730** is temperature controlled.

[0326] Once a reagent pack **760** is present in the storage compartment **740**, it is available to be utilized in an amplification assay, for example, a PCR assay. When a sample is present requiring a particular assay, the carousel of the storage compartment **740** rotates to a position where a reagent pack **760** containing the specific unit dose reagents for that particular assay are accessible by the rotary distributor **312**. Generally, such access will be through a door to maintain a tightly controlled temperature environment in the storage compartment **740**. The distributor **312** will access the reagent pack **760** through the door and move it to a reagent pack loading station **640** for reconstitution of one or more lyophilized reagents contained on the reagent pack **760**. When the

reagent pack **760** is empty, or when the reagents of one or more wells on the reagent pack **760** have been reconstituted and removed, the distributor **312** will again move the reagent pack **760**. If there are reagents remaining in the reagent pack **760**, the distributor **312** will transfer the reagent pack **760** back to the storage compartment **740**. If the reagent pack **760** contains no more reagents, or is otherwise designated as inappropriate for continued use (e.g., contaminated or expired reagents), the distributor **312** will transfer the reagent pack **760** to either a waste chute **426** or back to the reagent pack input carousel **704** or **730** for removal.

[0327] A further alternative for scanning each reagent pack **760** is for the distributor **312** to present each reagent pack **760** to a barcode scanner as each reagent pack is removed from the reagent pack input carousel and before placing the reagent pack **760** into the storage carousel **744**.

[0328] Reagent identity control is maintained after the bar code (or other machine code) is read on the reagent pack **760** by monitoring the position of each reagent pack station **706**, **732** of carousel **704**, **730** and each reagent pack station **746** on the storage carousel **744** and associating the reagent pack **760** identity—from the bar code—with the reagent pack station position.

[0329] The reagent pack carousels **704**, **730** rotate independently of the storage carousel **744** of the storage compartment **740** to allow an operator to load and unload reagent packs **760** from the reagent pack carousel **704**, **730** while the module **400** (i.e., rotary distributor **312**) independently accesses reagent packs **760** stored in the storage carousel **744** for assay processing.

[0330] The reagent pack changer **700** preferably stores at least 28 to 30 or more reagent packs **760**.

[0331] The second module **400** may further include an electrostatic generator to impart an electrostatic charge for positioning and holding the lyophilized reagent **768** present in the reagent pack **760** at the bottom of each of the mixing wells **762** of the reagent pack **760**. Though the reagent **768** may be held at the bottom of the associated mixing well **768** with a previously-imparted electrostatic charge, as noted above, the inclusion of a mechanism, such as an electrostatic generator, to actively pull the lyophilized reagent **768** down to the bottom of the mixing well **762** at the time that the reagent is reconstituted will ensure its positioning in the correct spot in the mixing well during reconstitution. In an embodiment, the electrostatic generator is positioned below the reagent pack loading station **640**, **730**. Alternatively, or in addition, an electrostatic generator could be provided in the reagent pack carousel **704**, **730** present in the reagent pack loading drawer and/or the storage carousel **744** present in the storage compartment **740**. In such an embodiment, the electrostatic generator may be located under or operatively coupled to the reagent pack station **706**, **732** or the reagent pack station **746** below the reagent pack **760**, as providing an electrostatic generator within the storage compartment **740** will have an enhanced electrostatic effect due to the lower temperature and low humidity.

#### Storage/Expansion Module

[0332] Details of compartment **590** for storing accessories or to accommodate possible expansion of the second module **400** are shown in FIGS. **5**, **6**, **14**, and **15**. In one exemplary embodiment, compartment **590** can house a standard 96 well plate. The plate is located such that both pipettor arms **408**, **416** can access the 96 well plate location. The expansion space has access to the front (via a drawer mechanism) so that the operator can load and unload the plate. The expansion space can also be accessed from the side of the instrument. A drive system comprising, for example, a motor-driven belt, may be provided for translating a well plate or other container or component into or out of the second module **400**. Compartment **590** can be utilized as an area for collecting cap/vial assemblies that have undergone a PCR and/or melting assay to provide for the ability to perform additional assays (e.g., ELISAs) on the sample contained in the cap/vial assembly. (A procedure for performing a thermal melt analysis is disclosed by Wittwer et al. in U.S. Pat. No. 8,343,754.) In certain embodiments an arrangement of cap/vial assemblies in the format of a 96 well plate has advantages if further processing of the samples is desired since the 96 well plate size is compatible with a variety of known sample processing and molecular assay instruments.

#### Instrument Theory of Operation

[0333] The first module **100** is used for the sample preparation portion of the amplification assay (i.e., minimally the steps for isolating and purifying a target nucleic acid that may be present in a sample). Samples and TCR, which may include a magnetically-responsive solid supports, are loaded onto the first module **100**. Elution buffer containers **502**, **504** are loaded on the second module **400**. The second module **400** then automatically moves these containers into a space within the first module **100** that can be accessed by a substance transfer device, for example, a reagent pipettor (not shown in FIG. **1**), of the first module **100**. Through information provided to the first module **100** by, for example, an operator via a user interface or through automated, machine-readable information, such as a bar code, provided on the sample container (not shown in FIG. **1**), the first module recognizes that a particular amplification assay will be initiated. To process samples, the receptacle distributor **150** of the first module **100** pulls a new MRD **160** from an input queue **102** and places it into a sample dispense position within the first module **100**. TCR and sample are transferred from a reagent container and sample tube, respectively, to each receptacle **162** the MRD **160** by a pipettor within the first module **100**. The contents of the MRD **160** are then incubated for a prescribed period at a prescribed temperature before the MRD **160** is transferred to a magnetic separation wash station **118**, **120** for a magnetic wash procedure.

[0334] After the target capture process, the MRD **160** is moved by the receptacle distributor **150** to an amplification reagent dispense position in the first module **100**. The substance transfer device of the first module **100** then adds elution fluid to each receptacle **162** of the MRD **160** to separate target (sample) material from the magnetic particles, and the first module **100** mixes the contents of each receptacle **162** before sending the MRD **160** to the second module **400**. The second module **400** places the MRD **160** into one of a series of slots configured to hold MRD **160**. When signaled by the system controller, the second module **400** moves the MRD **160** to a magnetic elution slot **620** to separate the eluted nucleic acid material from the magnetic particles. The substance transfer device **402**, for example, a robotic pipettor, then initiates the amplification process. The pipettor **402** first dispenses oil to all processing vials **464**, **1100** queued for use in testing. The pipettor **402** then aspirates eluate/sample from the MRD **160**, and then aspirates a reconstitution reagent solution from a reconstitution reagent cartridge or reservoir, dispensing them into a lyophilized-reagent well of reagent pack **760**. The reconstitution reagent and a lyophilized amplification reagent in the reagent well of reagent pack **760** may be drawn into and released from the pipette tip one or more times to ensure adequate and rapid reconstitution. The reconstituted amplification reagent is pipetted to the processing vial **464**, **1100** and is then capped. The reconstituted amplification reagent, sample, and oil may be drawn into and released from the pipette tip one or more times to ensure adequate mixing. The capped vial **464**, **1100** is transferred to the centrifuge and then to the thermal cycler **432**, such as thermal cycler **432** for PCR amplification and fluorometric detection.

[0335] Results may be displayed on an instrument monitor or user interface and either printed or communicated to the LIS.

[0336] In an embodiment, the first module **100** is configured to perform one or more isothermal nucleic acid amplification reactions on nucleic acid material contained within an MRD **160**. In one embodiment, such an isothermal process may be performed on the contents of the MRD **160** before transporting the MRD **160** to the second module **400** to perform PCR on a portion of the MRD content material, as discussed above. Alternatively, after the MRD **160** is processed in the second module **400** and an amount of eluate/sample is transferred from the MRD to one or more vials **464**, **1100** for performing PCR or other process(es) that the second module **400** is configured to perform. The MRD **160** may be transported back to the first module **100** to perform an isothermal nucleic acid amplification reaction on the remaining contents of the MRD **160**.

#### Exemplary Processes

[0337] Details of operation and a process embodying aspects of the present disclosure are shown in the flow charts of FIGS. **41-43**. The following processes are exemplary. Other processes may be performed and/or the processes shown herein and described below may be modified, e.g., by

omitting and/or reordering certain steps.

[0338] A sample eluate preparation process that can be performed using the first module **100** and the second module **400** described above is represented by flow chart **800** in FIG. **41**. In step **S802** of method **800**, a reaction receptacle is moved to a location at which reaction materials can be added to the receptacle. See, e.g., Clark et al. in U.S. Pat. No. 8,309,036. For example, the receptacle distributor **150** of the first module **100** moves an MRD **160** from the input device **102** to one of the load stations **104**, **106** or **108**. See, e.g., Hagen et al. in U.S. Patent Application Publication No. 2012/0128451.

[0339] In step **S804** a substance transfer device of the first module **100** transfers reaction materials to the receptacle. See, e.g., Buse et al. in U.S. Provisional Application No. 61/783,670. For example, a robotic pipettor of the first module **100** transfers a target capture reagent (“TCR”) (e.g., 500  $\mu$ L), sample fluid (e.g., 360  $\mu$ L), and target enhancer reagent (“TER”) (e.g., 140  $\mu$ L) into each receptacle **162** of the MRD **160**.

[0340] In step **S806**, the reaction materials added to the receptacle in step **S804** are mixed. For example, the TCR, sample fluid, and TER added to the receptacles **162** of the MRD **160** are mixed by, for example, oscillating the MRD **160** at a high frequency (e.g., 60 seconds at 16 Hz).

[0341] In step **S808**, the receptacle is moved into an environment that will promote the desired reaction. For example, the receptacle distributor **150** removes the MRD **160** from the load station **104** and transfers the MRD **160** to one of the incubators **112**, **114**, **116** (referred to as the AT Binding Incubator “ATB Incubator” in FIG. **41**) to incubate the contents of the MRD **160** at a prescribed temperature for a prescribed period of time (e.g., 1800 seconds at 63° C.). Before moving the MRD **160** to an incubator, the MRD **160** may first be placed in one of the temperature ramping stations **110** (e.g., 300 seconds at 65° C.) to elevate the temperature of the MRD **160** and its contents to a temperature that is closer to that of the incubator into which the MRD **160** will be transferred so as to minimize temperature fluctuations within the incubator.

[0342] The desired reaction may require two or more incubations at different temperatures. Thus, in accordance with one implementation of the disclosure, in step **S810**, the receptacle distributor **150** removes the MRD **160** from one of the incubators and transfers the MRD **160** to another incubator (referred to as the “High Temp Incubator” in FIG. **41**) that is at a different (e.g., higher or lower) temperature than the first incubator to continue to incubate the contents of the MRD **160** at a prescribed temperature for a prescribed period of time (e.g., 600 seconds at 43.7° C.).

[0343] In step **S812**, the receptacle distributor **150** removes the MRD **160** from the second temperature incubator and returns the MRD **160** to another incubator at a different temperature, which may be the same incubator (e.g., the “ATB Incubator”) the MRD **160** was placed into in step **S808**.

[0344] At the conclusion of the incubation step(s), it may be desirable to cool the temperature of the contents of the receptacle, for example to terminate any reaction occurring within the receptacle. Thus, in one example, in step **S814**, the receptacle distributor **150** may remove the MRD **160** from the incubator and transfer the MRD **160** to a chiller module **122** (referred to as a “Chiller Ramp” in FIG. **41**), maintained at a predetermined temperature.

[0345] Next, assuming the reaction performed within the receptacle includes immobilizing a target nucleic acid on a magnetic-responsive solid support, a magnetic separation procedure is performed on the contents of the receptacle. Thus, in step **S816**, the receptacle distributor **150** removes the MRD **160** from a chiller module **122** after a predetermined period of time (e.g., 830 seconds), and transfers the MRD **160** to a magnetic parking station comprising magnets for attracting magnetically-responsive solid support within each receptacle **162** to the walls of the receptacles **162** to pull the solid support out of suspension. See, e.g., Davis et al. in U.S. Pat. No. 8,276,762. In step **S818**, after a prescribed period of time within the magnetic parking station (e.g., 300 seconds), the receptacle distributor **150** removes the MRD **160** from the magnetic parking station and transfers the MRD **160** to a magnetic separation wash station **118** or **120**. See, e.g., Hagen et al. in

U.S. Patent Application Publication No. 2010/0288395. In step **S820**, a magnetic wash procedure is performed on the contents of the MRD **160** placed into the magnetic wash station **118** or **120**. One exemplary embodiment of the magnetic separation procedure involves a number of magnetic dwells during which the contents of the receptacle are exposed to a magnetic force for a predetermined period of time, and after each magnetic dwell, while the contents are still exposed to the magnetic force, the fluid contents are aspirated from the receptacle, leaving the magnetic particles behind in the receptacle. In one exemplary embodiment, three magnetic dwells of 120 seconds each are performed. At the conclusion of each magnetic dwell, the magnetic force is removed from the contents of the receptacle. After each magnetic dwell, except the last magnetic dwell, an amount of wash fluid (e.g., 1000  $\mu$ L of wash buffer) is added to the receptacle to re-suspend the magnetic particles before beginning the next magnetic dwell.

[0346] After the magnetic wash process is complete (e.g., after the last magnetic dwell followed by an aspiration of the non-magnetic fluid contents of the receptacle), in step **S822**, the receptacle distributor **150** retrieves the MRD **160** from the magnetic separation wash station **118** or **120** and moves the MRD **160** to one of the load stations **104**, **106** or **108**. In the load station, an amount of elution buffer (e.g., 50-110  $\mu$ L) is transferred by, for example, a substance transfer device such as a robotic pipettor, from one of the elution containers **502**, **504** transferred into the first module **100** by the bulk reagent container transport **550** of the bulk reagent container compartment **500** of the second module **400**.

[0347] In some embodiments, it may be desirable to heat or incubate the contents of the MRD **160** to improve the efficiency of the nucleic acid elution.

[0348] In step **S824**, following the addition of the elution buffer, the contents of the MRD **160** are mixed by agitating the MRD **160**.

[0349] In step **S826**, the MRD **160** is transferred from the first module **100** to a magnetic elution slot **620** in the second module **400**. First, the receptacle distributor **150** of the first module **100** retrieves the MRD **160** from the load station **104**, **106** or **108** and transfers the MRD **160** to an end of the transport track assembly **154** closest to the second module **400**. The distribution head **152** of the receptacle distributor **150** places the MRD into the receptacle handoff device **602** of the second module **400**. The receptacle handoff device **602** then rotates the MRD **160** and presents it to the rotary distributor **312**. The rotary distributor **312** extends its hook **318** and engages the manipulation structure **166** of the MRD **160** by rotating a few degrees to place the hook **318** into the manipulation structure **166** and then withdraws the hook **318** to pull the MRD **160** into the distributor head **314** of the rotary distributor **312**. The rotary distributor **312** then rotates to align the MRD **160** carried therein with one of the magnetic elution slots **620** of the second module **400** (or optionally MRD storage **608**). The rotary distributor **312** then extends its hook **318** to push the MRD **160** into the magnetic elution slot **620** and rotates a few degrees to remove the hook **318** from the manipulation structure **166**.

[0350] The process next proceeds to process **830** shown in FIG. **42**.

[0351] Referring to FIG. **42**, a reaction mixture preparation process is represented by flow chart **830**. One or more of the steps of process **830** may proceed in parallel with one or more of the steps of process **800** shown in FIG. **41**.

[0352] At step **S832** the substance transfer pipettor **410** of the second module **400** picks up a disposable tip **584** from a disposable tip tray **582** carried in one of the tip compartments **580**.

[0353] In step **S834**, the substance transfer pipettor **410** transfers an amount of oil (e.g., 15  $\mu$ L) from an oil container carried in the bulk reagent container compartment **500** to one or more processing vials **464** held in the cap/vial trays **460** of the processing cap/vial compartment **440**.

[0354] In step **S836**, the substance transfer pipettor **410** moves to a trash chute **426** to strip the disposable pipette tip **584** therefrom and discard the tip into the trash chute **426**. Substance transfer pipettor **410** then returns to the disposable tip tray **582** and picks up another disposable pipette tip **584**.

[0355] In step **S838**, substance transfer pipettor **410** transfers an amount of reconstitution reagent (e.g., 20  $\mu$ L) from a reconstitution reagent container held in the bulk reagent container compartment **500** to a mixing well **762** of a PCR reagent pack **760** that was previously transferred by the rotary distributor **312** from the storage compartment **740** to a reagent pack loading station **640**. In one embodiment, before the reconstitution reagent is dispensed into the mixing well **762**, the pipettor **410** performs a level sense at the foil **766** before piercing the foil **766** with the pipette tip **584**. The level-sense performed on the foil of the reagent pack **760** to “calibrate” the height of the reagent pack **760** relative to the pipettor. Generally, the pipettor **410** is configured to extend the pipette tip to the bottom of the mixing well for more accurate reagent aspiration.

[0356] In step **S840**, the fluid within the mixing well **762** is mixed to dissolve the lyophilized reagent **768**. In one example, the substance transfer pipettor **410** mixes the fluid within the mixing well **762** by alternately aspirating the fluid into the pipette tip **584** and dispensing the fluid back in the well **762** one or more times to dissolve the lyophilized reagent **768**.

[0357] In step **S842**, the substance transfer pipettor **410** transfers an amount, (e.g., 20  $\mu$ L) of the reconstituted reagent from the mixing well **762** of the PCR reagent pack **760** (referred to as “Mastermix” in FIG. **42**), into a vial **464**. A PCR master mix provides the key ingredients necessary for performing PCR in a premixed and optimized format. Included in the master mix are Taq DNA polymerase, deoxynucleoside triphosphates (dNTPs), and magnesium chloride (MgCl.sub.2). Not typically included are the forward and reverse primers.

[0358] In step **S844**, the substance transfer pipettor **410** moves to the trash chute **426** and strips the pipettor tip **584** into the trash chute. The substance transfer pipettor **410** then moves to the disposable tip tray **582** and picks up a new disposable pipette tip **584**.

[0359] Block “B” in FIG. **42** represents the integration of process **800** shown in FIG. **41** with process **830** shown in FIG. **42**. An MRD **160** containing a sample mixture (which, in this exemplary embodiment, was purified in a magnetic separation procedure) and an elution buffer is held in a magnetic elution slot **620**, having been placed there in step **S826** of process **800**. In one embodiment, the MRD **160** is held in the magnetic elution slot **620** for dwell period of at least 120 seconds.

[0360] In step **S846** of process **830**, the substance transfer pipettor **410** transfers an amount of eluate (e.g., 5  $\mu$ L) from the MRD **160** held in the elution slot **620** to the processing vial **464** to which oil and reagent were added in steps **S834** and **S842**, respectively.

[0361] In step **S848**, the substance transfer pipettor **410** moves back to the trash chute **426** and strips the disposable pipette tip **584** into the trash chute.

[0362] The process now proceeds to process **850** shown in FIG. **43**.

[0363] Referring to FIG. **43**, a process for performing an automated biological process, such as a PCR reaction, is represented by flow chart **850**. Block “C” in FIG. **43** represents the integration of process **830** shown in FIG. **43** with process **850** shown in FIG. **43**.

[0364] In step **S852**, the substance transfer pipettor **410** picks up a processing vial cap **476** from the cap well **440** of the cap/vial tray **460** by inserting the pipettor probe **422** (without a disposable pipette tip thereon) into the cap **476** as shown in FIG. **23** (see FIG. **26**, which shows an alternative cap **1200** and vial **1100** combination). The substance transfer pipettor **410** then picks up the cap **476**, which is held onto the pipettor probe **422** by friction, and inserts the cap **476** into the processing vial **464** held in the processing vial well **474** until the cap **476** locks with the vial **464** to form a cap/vial assembly (see FIG. **25**).

[0365] In step **S854**, the substance transfer pipettor **410** (“PCR Module Pipettor” in FIG. **43**) transfers the cap/vial assembly held to the pipettor probe **422** by friction to the centrifuge **588**, where a stripping device removes the cap/vial assembly from the pipettor probe **422** to deposit the cap/vial assembly into the centrifuge **588**.

[0366] In Step **856**, following a specified period of time in the centrifuge, the vial transfer arm **418** (“PCR Module Pipettor” in FIG. **43**) inserts its pipettor probe **422** into the cap **476** of the cap/vial

assembly held in the centrifuge **588** and removes the cap/vial assembly from the centrifuge **588** and transfers the cap/vial assembly to an incubator module, such as the thermal cycler **432**. A stripping device removes the cap/vial assembly from the pipettor probe **422** of the vial transfer arm **418**.

[0367] In step **S858**, an incubation process is performed. The incubation process may include PCR thermal cycling comprising multiple cycles of temperatures varying between 95° C. for denaturation, 55° C. for annealing, and 72° C. for synthesis. During the thermal cycler process an emission signal from the contents of the processing vial may be monitored. For example, fluorescence monitoring at one or more colored wavelengths during each PCR cycle may be measured using a signal detecting device, such as a fluorometer, operatively integrated with the thermal cycler **432**. Periodic fluorescence intensity measurements at each wavelength may be made at regular intervals to generate fluorescence time series data for later processing and analysis.

[0368] In step **S860**, following the PCR process of step **S858**, the vial transfer arm **418** retrieves the cap/vial assembly from the thermal cycler **432** and transfers the cap/vial assembly to a trash chute **424** where the cap/vial assembly is stripped from the pipettor probe **422** into the trash chute **424**, or the cap/vial assembly is transported to an output reagent pack **760** in the storage/expansion module.

[0369] In some embodiments, diagnostic system **10** can be used to perform two or more assays that include nucleic acid amplification reactions that require different reagents, including one or more unit-dose reagents. FIG. **44** illustrates a method of using diagnostic system **10**, which includes first module **100** and second module **400**, according to one such embodiment.

[0370] At step **862**, a plurality of samples is loaded in diagnostic system **10**. A first sample subset of the plurality of samples has been designated for at least one assay, and a second sample subset of the plurality of samples has been designated for at least one different assay. In some embodiments, barcodes on the sample receptacles indicate the appropriate assay, and in other embodiments, the assay is entered manually into the system by an operator using a user-interface of diagnostic system **10**.

[0371] In some embodiments, a first assay comprising a first nucleic amplification reaction has been designated for the first sample subset. For example, the first nucleic amplification reaction can be PCR, and the target nucleic acid can be a nucleic acid associated with a particular virus or organism, for example. In some embodiments, the first nucleic amplification reaction uses a unit-dose reagent stored and operatively accessible within the diagnostic system **10**. For example, the first nucleic amplification reaction can be PCR or any other desired thermal cycling reaction that can be performed by second module **400** of diagnostic system **10**.

[0372] In some embodiments, a second assay comprising a second nucleic amplification reaction will be designated for the second sample subset. The second nucleic amplification reaction may be the same or a different nucleic acid amplification reaction than the first nucleic acid amplification reaction of the first assay, but the reagent used in the second nucleic amplification reaction may target a different nucleic acid than the target of the first reagent used in the first assay in some embodiments. In some embodiments, the second nucleic amplification reaction can be PCR or any other desired thermal cycling reaction that is performed, for example, by second module **400** of diagnostic system **10**. In some embodiments, the second nucleic amplification reaction is TMA or any other isothermal reaction that is performed, for example, by first module **100** of diagnostic system **10**. The reagent used for the second assay can be a unit-dose reagent different than the unit-dose reagent used for the first assay, a bulk reagent, or both. For example, if the second nucleic amplification reaction is PCR, the second reagent used in the second assay can be a unit-dose reagent, and if the second nucleic amplification reaction is TMA, the second reagent used in the second assay can be a bulk reagent. In some embodiments, the second unit-dose reagent, the first bulk reagent, or both are stored and operatively accessible within diagnostic system **10**.

[0373] Each of the first and second assays has a temporal workflow schedule associated with the respective assay. In some embodiments, at step **864**, the diagnostic system **10** coordinates the schedule for performing the first assay with the schedule for performing the second assay such that

use of resources of the diagnostic system is maximized. For example, the first assay schedule may require use of one of the substance transfer devices, and the second assay schedule may also require use of the same substance transfer device. Diagnostic system **10** can be configured to shift one or both of schedules such that once the first assay is finished with the substance transfer device, the substance transfer device can be used for the second assay. Such coordination increases throughput and minimizes processing time.

[0374] At step **866**, diagnostic system **10** performs the first assay on the first sample subset. At step **868**, diagnostic system **10** begins to perform the second assay on the second sample subset.

Accordingly, diagnostic system **10**, which stores and provides operative access to the first unit-dose reagent used in the first assay and at least one of the second unit-dose reagent or the first bulk reagent used in the second assay, performs both steps **866** and **868** according to an embodiment. In some embodiments, step **868** starts while step **866** is being performed—the diagnostic system can simultaneously perform the first assay and the second assay. In some embodiments, during steps **866** and **868** when the respective assays require a unit-dose reagent, for example, for a PCR assay, diagnostic system **10** verifies whether a reagent pack **760** containing the required reagent is positioned at one of the loading stations **640**. If not, the distributor system replaces a reagent pack **706** located at the loading station **640** with a reagent pack **760** containing the unit-dose reagent needed for the requested assay. In some embodiments, step **868** starts after step **866** is completed. And in some embodiments, although step **868** can start after step **866**, step **868** can be completed before step **866** is completed.

[0375] In some embodiments, diagnostic system **10** can alternate between step **866** and **868**. For example, diagnostic system **10** can perform the first assay on a first sample of the first sample subset, and then perform the second assay on a first sample of the second sample subset.

Diagnostic system **10** can then switch back to step **866** and perform the first assay on a second sample of the first sample subset.

[0376] In some embodiments, the first assay and the second assay each comprise preparing the respective sample subsets using a second bulk reagent different than the first bulk reagent that may be used in the second nucleic acid amplification reaction. For example, each sample of the first and second sample subsets can be prepared according to process **800** described above referencing FIG. **41**.

[0377] In some embodiments, the first sample subset and the second sample subset comprise different samples. In some embodiments, the first sample subset and the second sample subset comprise the same samples. In such embodiments, multiple assays, for example, the first and second assays explained above, are performed on the same samples.

[0378] In some embodiments, steps **866** and **868** are performed without additional equipment preparation (for example, wiping down the equipment of diagnostic system **10**), reagent preparation (replacing reagent bottles stored in diagnostic system **10**), and consumable preparation (replacing empty tip trays).

#### Hardware and Software

[0379] Aspects of the disclosure are implemented via control and computing hardware components, user-created software, data input components, and data output components. Hardware components include computing and control modules (e.g., system controller(s)), such as microprocessors and computers, configured to effect computational and/or control steps by receiving one or more input values, executing one or more algorithms stored on non-transitory machine-readable media (e.g., software) that provide instruction for manipulating or otherwise acting on the input values, and output one or more output values. Such outputs may be displayed or otherwise indicated to an operator for providing information to the operator, for example information as to the status of the instrument or a process being performed thereby, or such outputs may comprise inputs to other processes and/or control algorithms. Data input components comprise elements by which data is input for use by the control and computing hardware components. Such data inputs may comprise



position sensors, motor encoders, as well as manual input elements, such as graphic user interfaces, keyboards, touch screens, microphones, switches, manually-operated scanners, voice-activated input, etc. Data output components may comprise hard drives or other storage media, graphic user interfaces, monitors, printers, indicator lights, or audible signal elements (e.g., buzzer, horn, bell, etc.).

[0380] Software comprises instructions stored on non-transitory computer-readable media which, when executed by the control and computing hardware, cause the control and computing hardware to perform one or more automated or semi-automated processes.

[0381] While the present disclosure has been described and shown in considerable detail with reference to certain illustrative embodiments, including various combinations and sub-combinations of features, those skilled in the art will readily appreciate other embodiments and variations and modifications thereof as encompassed within the scope of the present disclosure. Moreover, the descriptions of such embodiments, combinations, and sub-combinations is not intended to convey that the disclosure requires features or combinations of features other than those expressly recited in the claims. Accordingly, the present disclosure is deemed to include all modifications and variations encompassed within the scope of the following appended claims.

## Claims

1. An automated method for analyzing a plurality of samples, the method comprising performing within a housing of a self-contained system the steps of: (a) loading the system with a plurality of samples; (b) contacting each of the plurality of samples with an aliquot of a sample preparation reagent obtained from a bulk reagent container, wherein the sample preparation reagent comprises a magnetically-responsive solid support for directly or indirectly binding and immobilizing a nucleic acid of interest that may be present in one or more of the plurality of samples, and wherein the contacting step occurs in a separate receptacle for each sample of the plurality of samples; (c) after step (b), processing each of the plurality of samples to isolate and purify the nucleic acid of interest, to the extent present in any of the plurality of samples; (d) after step (c), providing an elution buffer to each separate receptacle, thereby forming an eluate containing the nucleic acid of interest, if present in the associated sample; (e) for each sample, reconstituting a unit-dose reagent for performing a nucleic acid amplification reaction and, with a pipettor of the system, combining the reconstituted unit dose reagent with the eluate in one of a plurality of individual processing vials; (f) with the pipettor, closing each of the processing vials containing a reaction mixture comprising combined reconstituted unit dose reagent and the eluate with a cap; (g) transferring the closed processing vials to one or more incubators; and (h) within the one or more incubators, subjecting the contents of the closed processing vials to time and conditions for performing real-time amplification assays.

---