

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250266088

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Pio; Federico

---

### SYSTEMS AND TECHNIQUES FOR ACCESSING MULTIPLE MEMORY CELLS CONCURRENTLY

---

#### Abstract

Techniques are provided for accessing two memory cells of a memory tile concurrently. A memory tile may include a plurality of self-selecting memory cells addressable using a row decoder and a column decoder. A memory controller may access a first self-selecting memory cell of the memory tile using a first pulse having a first polarity to the first self-selecting memory cell. The memory controller may also access a second self-selecting memory cell of the memory tile concurrently with accessing the first self-selecting memory cell using a second pulse having a second polarity different than the first polarity. The memory controller may determine characteristics of the pulses to mitigate disturbances of unselected self-selecting memory cells of the memory tile.

---

**Inventors:** Pio; Federico (Brugherio (MB), IT)

**Applicant:** Micron Technology, Inc. (Boise, ID)

**Family ID:** 1000008576837

**Appl. No.:** 19/062967

**Filed:** February 25, 2025

#### Related U.S. Application Data

parent US continuation 18208103 20230609 parent-grant-document US 12249370 child US 19062967

parent US division 17733683 20220429 parent-grant-document US 11705194 child US 18208103

parent US division 16712682 20191212 parent-grant-document US 11335402 child US 17733683  
us-provisional-application US 62782015 20181219

---

#### Publication Classification

**Int. Cl.:** G11C13/00 (20060101)

## Background/Summary

CROSS REFERENCE [0001] The present application for patent is a continuation of U.S. patent application Ser. No. 18/208,103 by Pio, entitled “SYSTEMS AND TECHNIQUES FOR ACCESSING MULTIPLE MEMORY CELLS CONCURRENTLY,” filed Jun. 9, 2023, which is a divisional of U.S. patent application Ser. No. 17/733,683 by Pio, entitled “SYSTEMS AND TECHNIQUES FOR ACCESSING MULTIPLE MEMORY CELLS CONCURRENTLY,” filed Apr. 29, 2022, which is a divisional of U.S. patent application Ser. No. 16/712,682 by Pio, entitled “SYSTEMS AND TECHNIQUES FOR ACCESSING MULTIPLE MEMORY CELLS CONCURRENTLY,” filed Dec. 12, 2019, which claims priority to U.S. Provisional Patent Application No. 62/782,015 by Pio, entitled “SYSTEMS AND TECHNIQUES FOR ACCESSING MULTIPLE MEMORY CELLS CONCURRENTLY,” filed Dec. 19, 2018, each of which is assigned to the assignee hereof and each of which is expressly incorporated by reference in its entirety.

## BACKGROUND

[0002] The following relates generally to programming enhancement in memory cells and more specifically to programming enhancement in self-selecting memory.

[0003] Memory devices are widely used to store information in various electronic devices such as computers, wireless communication devices, cameras, digital displays, and the like. Information is stored by programing different states of a memory device. For example, binary devices have two states, often denoted by a logic ‘1’ or a logic ‘0’. In other systems, more than two states may be stored. To access the stored information, a component of the electronic device may read, or sense, the stored state in the memory device. To store information, a component of the electronic device may write, or program, the state in the memory device.

[0004] Multiple types of memory devices exist, including magnetic hard disks, random access memory (RAM), dynamic RAM (DRAM), synchronous dynamic RAM (SDRAM), ferroelectric RAM (FeRAM), magnetic RAM (MRAM), resistive RAM (RRAM), read only memory (ROM), flash memory, phase change memory (PCM), and others. Memory devices may be volatile or non-volatile. Non-volatile memory, e.g., FeRAM, may maintain their stored logic state for extended periods of time even in the absence of an external power source. Volatile memory devices, e.g., DRAM, may lose their stored state over time unless they are periodically refreshed by an external power source. Improving memory devices may include increasing memory cell density, increasing read/write speeds, increasing reliability, increasing data retention, reducing power consumption, or reducing manufacturing costs, among other metrics.

[0005] Some memory devices may include a plurality of memory tiles which comprise an array of memory cells. Each memory tile may include a single row decoder and a single column decoder, which may be used to access memory cells of the memory tile. In some memory tiles, only a single memory cell may be accessed during an access operation.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0006] FIG. 1 illustrates an example memory array that supports systems and techniques for

accessing multiple memory cells concurrently in accordance with various examples of the present disclosure.

[0007] FIG. 2 illustrates an example memory array that supports systems and techniques for accessing multiple memory cells concurrently in accordance with various examples of the present disclosure.

[0008] FIG. 3 illustrates examples of diagrams that support systems and techniques for accessing multiple memory cells concurrently in accordance with various examples of the present disclosure.

[0009] FIG. 4 illustrates an example of a memory tile that supports systems and techniques for accessing multiple memory cells concurrently in accordance with various examples of the present disclosure.

[0010] FIG. 5 illustrates examples of diagrams that support systems and techniques for accessing multiple memory cells concurrently in accordance with various examples of the present disclosure.

[0011] FIG. 6 illustrates an example of a memory tile that supports systems and techniques for accessing multiple memory cells concurrently in accordance with various examples of the present disclosure.

[0012] FIG. 7 illustrates an example of a diagram that supports systems and techniques for accessing multiple memory cells concurrently in accordance with various examples of the present disclosure.

[0013] FIG. 8 illustrates an example of a diagram that supports systems and techniques for accessing multiple memory cells concurrently in accordance with various examples of the present disclosure.

[0014] FIG. 9 illustrates an example of a circuit that supports systems and techniques for accessing multiple memory cells concurrently in accordance with various examples of the present disclosure.

[0015] FIG. 10 illustrates examples of memory tiles that support systems and techniques for accessing multiple memory cells concurrently in accordance with various examples of the present disclosure.

[0016] FIG. 11 illustrates examples of memory devices that support systems and techniques for accessing multiple memory cells concurrently in accordance with various examples of the present disclosure.

[0017] FIGS. 12 through 17 illustrate methods for systems and techniques for accessing multiple memory cells concurrently in accordance with embodiments of the present disclosure.

#### DETAILED DESCRIPTION

[0018] Some memory cells may be formed of a chalcogenide material that causes ions to migrate or crowd toward one side of the chalcogenide material when a voltage is applied. These memory cells, sometimes referred to as self-selecting memory cells, may leverage the ion migration or crowding to store a logic state (e.g., a logic '0' or a logic '1') on the memory cell. Due to the nature of the chalcogenide material, self-selecting memory cells may be programmed using programming pulses of different polarities and self-selecting memory cells may be read using read pulses of different polarities. In many memory tiles, only a single memory cell is addressable at a time, which leads to disadvantages and limitations. The use of different polarities in the access pulses may provide some advantages in the functioning of a memory device that includes self-selecting memory cells.

[0019] Techniques are provided for accessing multiple memory cells of a memory tile concurrently. A memory tile may include a plurality of self-selecting memory cells addressable using a row decoder and a column decoder. To access a first self-selecting memory cell of the memory tile, a memory controller may apply a first pulse having a first polarity to the first self-selecting memory cell. The memory controller may also access a second self-selecting memory cell of the memory tile concurrently with accessing the first self-selecting memory cell using a second pulse having a second polarity that is different than the first polarity. The memory controller may determine characteristics of the first pulse and second pulse to mitigate disturbances of unselected self-selecting memory cells of the memory tile. In such memory tiles, two self-selecting memory cells

may be read concurrently or two self-selecting memory cells may be programmed concurrently or a self-selecting memory cell may be read and another self-selecting memory cell may be programmed concurrently.

[0020] FIG. 1 illustrates an example of a memory tile **100** that supports systems and techniques for accessing multiple memory cells concurrently in accordance with various examples of the present disclosure. A memory device may include a plurality of memory tiles **100**. The memory tile **100** includes memory cells **105** that are programmable to store different states. Each memory cell **105** may be programmable to store two states, denoted a logic '0' and a logic '1'. In some cases, memory cell **105** is configured to store more than two logic states.

[0021] The memory tile **100** may represent a block of memory cells that are addressable during an access operation. The memory tile **100** may include a row decoder **120** and column decoder **130** for addressing the selected memory cell of the memory tile **100** during an access operation. In some memory technologies, only a single memory cell **105** of a memory tile **100** is accessible at a time. This is due to disturbances on unselected memory cells that may occur if a plurality of access lines (e.g., word lines **110** and/or digit lines **115**) are biased during the same access operation. Systems and techniques are provided herein for accessing two or more memory cells **105** of the same memory tile **100** during concurrently during the same access operation duration.

[0022] The memory tile **100** may be a three-dimensional (3D) memory array, where two-dimensional (2D) memory arrays are formed on top of one another. This may increase the number of memory cells that may be formed on a single die or substrate as compared with 2D arrays, which in turn may reduce production costs or increase the performance of the memory array, or both. According to the example depicted in FIG. 1, memory tile **100** includes two levels of memory cells **105** and may thus be considered a three-dimensional memory array; however, the number of levels is not limited to two. Each level may be aligned or positioned so that memory cells **105** may be approximately aligned with one another across each level, forming a memory cell stack **145**.

[0023] Each row of memory cells **105** is connected to an access line **110** and an access line **115**. Access lines **110** may also be known as word lines **110**, and digit lines **115**, respectively. Digit lines **115** may also be known as digit lines **115**. References to word lines and digit lines, or their analogues, are interchangeable without loss of understanding or operation. Word lines **110** and digit lines **115** may be substantially perpendicular to one another to create an array. The two memory cells **105** in a memory cell stack **145** may share a common conductive line such as a digit line **115**. That is, a digit line **115** may be in electronic communication with the bottom electrode of the upper memory cell **105** and the top electrode of the lower memory cell **105**. Other configurations may be possible; for example, memory cell **105** may be asymmetrically shaped, such as memory cell **105-c** with reference to FIG. 3.

[0024] In general, one memory cell **105** may be located at the intersection of two conductive lines such as a word line **110** and a digit line **115**. This intersection may be referred to as a memory cell's address. A target memory cell **105** (i.e., a selected memory cell) may be a memory cell **105** located at the intersection of an energized word line **110** and digit line **115**; that is, a word line **110** and digit line **115** may be energized in order to read or write a memory cell **105** at their intersection. Other memory cells **105** that are in electronic communication with (e.g., connected to) the same word line **110** or digit line **115** may be referred to as untargeted memory cells **105**. In some memory tiles, only a single memory cell **105** may be targeted during an access operation due to disturbances that may occur on other non-targeted memory cells **105** of the memory tile **100**. In the present disclosure, systems and techniques are discussed for targeting two or more memory cells of the memory tile **100** during a single access operation duration.

[0025] As discussed above, electrodes may be coupled to a memory cell **105** and a word line **110** or a digit line **115**. The term electrode may refer to an electrical conductor, and in some cases, may be employed as an electrical contact to a memory cell **105**. An electrode may include a trace, wire, conductive line, conductive layer, or the like that provides a conductive path between elements or

components of memory tile **100**.

[0026] Operations such as reading and writing may be performed on memory cells **105** by activating or selecting a word line **110** and digit line **115**, which may include applying a voltage or a current to the respective line (e.g., a read pulse). Word lines **110** and digit lines **115** may be made of conductive materials, such as metals (e.g., copper (Cu), aluminum (Al), gold (Au), tungsten (W), titanium (Ti), etc.), metal alloys, carbon, conductively-doped semiconductors, or other conductive materials, alloys, or compounds. Upon selecting a memory cell **105**, a migration of, for example, selenium (Se) ions may be leveraged to set a logic state of the cell. Additionally or alternatively, ions of other conductive materials may migrate in addition to or in replace of selenium (Se) ions.

[0027] For example, a memory cell may be programmed by providing an electric pulse to the memory cell **105** (e.g., programming pulse), which may include a memory storage element that includes selenium. The programming pulse may be provided via a first access line (e.g., word line **110**) or a second access line (e.g., digit line **115**), for example. Upon providing the programming pulse, ions may migrate within the memory storage element, depending on the polarity of the programming pulse and/or a current state of the memory cell **105**. Thus, a concentration of ions and/or selenium relative to the first side or the second side of the memory storage element may be based at least in part on a polarity and/or magnitude of a voltage applied to the memory storage element by the first access line and the second access line. In some cases, the memory storage element may have an asymmetrical shape. Such an asymmetrical shape may cause ions to be more crowded at one portion of the memory storage element over another portion of the memory storage element.

[0028] To read the cell, a voltage (e.g., read pulse) may be applied across memory cell **105** and the resulting current or the threshold voltage at which current begins to flow may be representative of a logic '1' or a logic '0' state. The crowding of selenium ions at one or the other ends of memory storage element may affect the resistivity and/or the threshold voltage, resulting in greater distinctions in cell response between logic states.

[0029] Accessing the memory cells **105** may be controlled through a row decoder **120** and a column decoder **130**. For example, a row decoder **120** may receive a row address from the memory controller **140** and activate the appropriate word line **110** based on the received row address. Similarly, a column decoder **130** receives a column address from the memory controller **140** and activates the appropriate digit line **115**. Thus, by activating a word line **110** and a digit line **115**, a memory cell **105** may be accessed.

[0030] Upon accessing, a memory cell **105** may be read, or sensed, by sense component **125**. For example, sense component **125** may be configured to determine the stored logic state of memory cell **105** based on a signal generated by accessing the memory cell **105**. The signal may include a voltage or electrical current, and sense component **125** may include voltage sense amplifiers, current sense amplifiers, or both. For example, a voltage may be applied to a memory cell **105** (using the corresponding word line **110** and digit line **115**) and the magnitude of the resulting current may depend on the electrical resistance of the memory cell **105**. Likewise, a current may be applied to a memory cell **105** and the magnitude of the voltage to create the current may depend on the electrical resistance of the memory cell **105**. Sense component **125** may include various transistors or amplifiers in order to detect and amplify a signal, which may be referred to as latching. The detected logic state of memory cell **105** may then be output as output **135**. In some cases, sense component **125** may be a part of column decoder **130** or row decoder **120**. Or, sense component **125** may be connected to or in electronic communication with column decoder **130** or row decoder **120**.

[0031] A memory cell **105** may be programmed, or written, by similarly activating the relevant word line **110** and digit line **115**—i.e., a logic value may be stored in the memory cell **105**. Column decoder **130** or row decoder **120** may accept data, for example input/output **135**, to be written to the memory cells **105**. In the case of self-selecting memory, a memory cell **105** may be written (or

programmed) by passing a current through the memory storage element. Depending on the logic state written to memory cell **105** (e.g., logic '1' or logic '0') selenium ions may crowd at or near a particular electrode in contact with the memory storage element. For example, based on the polarity of memory cell **105**, ion crowding at or near a first electrode may result in a first threshold voltage representative of a logic '1' state and ion crowding at or near a second electrode may result in a second threshold voltage, different from the first, representative of a logic '0' state. The difference between the first and second threshold voltages may be more pronounced in a memory storage element that is asymmetric, including those described with reference to FIG. 3.

[0032] In some memory architectures, accessing the memory cell **105** may degrade or destroy the stored logic state and re-write or refresh operations may be performed to return the original logic state to memory cell **105**. In DRAM, for example, the logic-storing capacitor may be partially or completely discharged during a sense operation, corrupting the stored logic state. So the logic state may be re-written after a sense operation. Additionally, activating a single word line **110** may result in the discharge of all memory cells in the row; thus, all memory cells **105** in the row may need to be re-written. But in non-volatile memory, such as PCM and/or self-selecting memory, accessing the memory cell **105** may not destroy the logic state and, thus, the memory cell **105** may not require re-writing after accessing.

[0033] Some memory architectures, including DRAM, may lose their stored state over time unless they are periodically refreshed by an external power source. For example, a charged capacitor may become discharged over time through leakage currents, resulting in the loss of the stored information. The refresh rate of these so-called volatile memory devices may be relatively high, e.g., tens of refresh operations per second for DRAM, which may result in significant power consumption. With increasingly larger memory arrays, increased power consumption may inhibit the deployment or operation of memory arrays (e.g., power supplies, heat generation, material limits, etc.), especially for mobile devices that rely on a finite power source, such as a battery. As discussed below, non-volatile PCM and/or self-selecting memory cells may have beneficial properties that may result in improved performance relative to other memory architectures. For example, PCM and/or self-selecting memory may offer comparable read/write speeds as DRAM but may be non-volatile and allow for increased cell density.

[0034] The memory controller **140** may control the operation (read, write, re-write, refresh, discharge, etc.) of memory cells **105** through the various components, for example, row decoder **120**, column decoder **130**, and sense component **125**. In some cases, one or more of the row decoder **120**, column decoder **130**, and sense component **125** may be co-located with the memory controller **140**. Memory controller **140** may generate row and column address signals in order to activate the desired word line **110** and digit line **115**. Memory controller **140** may also generate and control various voltages or currents used during the operation of memory tile **100**. For example, it may apply discharge voltages to a word line **110** or digit line **115** after accessing one or more memory cells **105**.

[0035] In general, the amplitude, shape, polarity, or duration of an applied voltage or current discussed herein may be adjusted or varied and may be different for the various operations discussed in operating the memory tile **100**. Furthermore, one, multiple, or all memory cells **105** within memory tile **100** may be accessed simultaneously; for example, multiple or all cells of memory tile **100** may be accessed simultaneously during a reset operation in which all memory cells **105**, or a group of memory cells **105**, are set to a single logic state.

[0036] FIG. 2 illustrates an example memory array **200** that supports systems and techniques for accessing multiple memory cells concurrently in accordance with various examples of the present disclosure. Memory array **200** may be an example of memory tile **100** described with reference to FIG. 1.

[0037] The memory array **200** may include a plurality of memory cells **105-a**, **105-b**, etc. a plurality of word lines **110-a**, **110-b**, and a plurality of digit lines **115-a**, **115-b**, which may be

examples of a memory cell **105**, word line **110**, and digit line **115** described with reference to FIG.

**1.** A memory cell **105-a** may include a top electrode **210**, a bottom electrode **215**, and memory storage element **205**, which may be referred to as a chalcogenide memory component. In some cases, the memory cell **105-a** may be an example of a self-selecting memory cell.

[0038] The architecture of memory array **200** may be referred to as a cross-point architecture. It may also be referred to as a pillar structure. For example, as shown in FIG. **2**, a pillar may be in contact with a first conductive line (e.g., access line such as word line **110-a**) and a second conductive line (e.g., access line such as digit line **115-a**). The pillar may comprise memory cell **105-a**, where memory cell **105-a** includes a first electrode (e.g., top electrode **210**), memory storage element **205**, and a second electrode (e.g., bottom electrode **215**). Memory storage element **205** may be an asymmetrical shape. This asymmetrical shape may cause ion crowding at the top electrode **210** or bottom electrode **215**, depending on the polarity of memory cell **105-a**. Ion crowding at top electrode **210** or bottom electrode **215** may allow for more-accurate sensing of memory cell **105-a**, as described above.

[0039] The cross-point or pillar architecture depicted in FIG. **2** may offer relatively high-density data storage with lower production costs compared to other memory architectures. For example, the cross-point architecture may have memory cells with a reduced area and thus an increased memory cell density compared to other architectures. For example, the architecture may have a  $4F_{\text{sup.2}}$  memory cell area, where  $F$  is the smallest feature size, compared to other architectures with a  $6F_{\text{sup.2}}$  memory cell area, such as those with a three-terminal selection. For example, DRAM may use a transistor, which is a three-terminal device, as the selection component for each memory cell and may have a larger memory cell area compared to the pillar architecture.

[0040] Memory storage element **205** may, in some cases, be connected in series between a first conductive line and a second conductive line, for example, between word line **110-a** and digit line **115-a**. The memory storage element **205** may be located between top electrode **210** and bottom electrode **215**; thus, memory storage element **205** may be located in series between digit line **115-a** and word line **110-a**. Other configurations are possible.

[0041] The memory storage element **205** may include a chalcogenide material, which may be referred to as a chalcogenide memory component. The chalcogenide memory component may be configured to use a non-uniform distribution of ions to indicate the logic state stored in the memory cell **105-a**. The threshold voltage of the chalcogenide memory component may be variable based on a polarity of a pulse used to program the memory cell **105-a**. For example, a self-selecting memory cell programmed with a first polarity pulse (e.g., a positive polarity) may have certain resistive and/or electrical properties and thus a first threshold voltage, while a self-selecting memory cell programmed with a second polarity pulse (e.g., a negative polarity) may have different resistive and/or electrical properties and thus a second threshold voltage. These electrical features of the chalcogenide material may be caused by differences in ion migration that occurs based on the characteristics of the programming pulse, including the polarity, magnitude, and/or shape of the programming pulse.

[0042] For example, ions may migrate towards a particular electrode, depending on the polarity of the programming pulse applied to a given memory cell. The logic state stored in the memory cell may be based on the distribution of ions in the chalcogenide memory component.

[0043] Cell programming may exploit the crystalline structure or atomic configuration of the chalcogenide memory component to achieve different logic states. For example, a material with a crystalline or an amorphous atomic configuration may exhibit different electrical properties based on differences in programming pulses applied to the material. The chalcogenide memory component may have at least two states.

[0044] In some cases, chalcogenide memory component may have a set state and a reset state. The set state may exhibit a low electrical resistance and may, in some cases, be referred to as the crystalline state. The reset state may exhibit a high electrical resistance and may be referred to as an

amorphous state. A voltage (e.g., a programming pulse) applied to the memory cell **105-a** may thus cause the memory storage element **205** to enter or maintain a certain state (e.g., a set state or a reset state). The magnitude and the polarity of the applied voltage (e.g., programming pulse) may affect the distribution of ions and thus may affect the logic state stored in the memory cell **105-a** that includes the memory storage element **205** formed using chalcogenide material.

[0045] Each state of the memory storage element **205** may have a threshold voltage associated with it—that is, current flows after the threshold voltage is exceeded. Thus, if the applied voltage is less than the threshold voltage, current may not flow through the memory storage element **205**. In some cases, one of the states of the memory storage element **205** may not have a threshold voltage (i.e., a threshold voltage of zero) and, thus, a current may flow in response to the applied voltage. In some cases, the memory storage element **205** may have more than two states that may result in a plurality of different resistances and a plurality of threshold voltages. In such cases, the memory cell **105-a** may be configured to have more than three states and may be configured to store more than one bit of digit logic data.

[0046] In some cases, the memory storage element **205** may be configured in an asymmetrical shape to facilitate ion crowding at or near top electrode **210** or bottom electrode **215**. For example, memory storage element **205** may be in the shape of a trapezoidal prism and a cross-section of memory storage element **205** may include a trapezoid. Alternatively, memory storage element **205** may be a frustum. A frustum, as used herein, includes a shape of or resembling the portion of a cone or pyramid with the upper portion removed, or a shape of or resembling the portion of a cone or pyramid between a first plane that intercepts the cone or pyramid below the top and a second plane at or above the base. Memory storage element **205** may be arranged in a series configuration between the first access line **110-a** and second access line **115-a**. Memory storage element **205** may include a first chalcogenide glass comprising selenium. In some examples, memory storage element **205** comprises a composition of at least one of selenium, arsenic (As), tellurium (Te), silicon (Si), germanium (Ge), or antimony (Sb). When a voltage is applied across the memory storage element **205** (or when there is a voltage difference between top electrode **210** and bottom electrode **215**, ions may migrate toward one or the other electrode. For example, Te and Se ions may migrate towards a positive electrode and Ge and As ions may migrate toward a negative electrode. Memory storage element **205** may also serve as a selector device. This type of memory architecture may be an example of self-selecting memory technology.

[0047] FIG. **3** illustrates examples of diagrams **300** that support systems and techniques for accessing multiple memory cells concurrently in accordance with various examples of the present disclosure. The diagrams **300** may illustrate the effects of different polarities of programming pulses and different polarities of read pulses on a memory cell **105-e** that includes a chalcogenide material. The memory cell **105-e** may include a memory storage element **205-a**, a top electrode **210-a**, a bottom electrode **215-a**. The memory cell **105-e** may be coupled with a word lines **110-e** and a digit line **115-c**.

[0048] Diagram **300-a** illustrates the effects of programming pulses that have different polarities on the memory cell **105-e**. If a first programming pulse **305** having a positive polarity (e.g., total voltage across the memory cell **105-e** is greater than zero) is applied to the memory cell **105-c**, the ions in the memory storage element **205-a** may crowd near the interface of the memory storage element **205-a** and the top electrode **210-a**. The first programming pulse **305** may generate a non-uniform distribution of an element (e.g., ions or selenium or selenium ions) in the memory storage element **205-a** with the element concentration being proximal to the top electrode **210-a**. To generate the first programming pulse **305** having the positive polarity, a first voltage may be applied to the digit line **115-e** and a second voltage less than the first voltage may be applied to the word line **110-c**.

[0049] If a second programming pulse **310** having a negative polarity (e.g., total voltage across the memory cell **105-e** is less than zero) is applied to the memory cell **105-e**, the ions in the memory



storage element **205-a** may crowd near the interface of the memory storage element **205-a** and the bottom electrode **215-a**. The second programming pulse **310** may generate a non-uniform distribution of an element (e.g., ions or selenium or selenium ions) in the memory storage element **205-a** with the element concentration being proximal to the bottom electrode **215-a**. To generate the second programming pulse **310** having the negative polarity, a first voltage may be applied to the word line **110-e** and a second voltage less than the first voltage may be applied to the digit line **115-c**.

[0050] Diagram **300-b** illustrates the effects of read pulses that have different polarities on the memory cell **105-e**. When reading the memory cell **105-e** the logic state identified by a memory controller as being stored in the memory cell **105-e** may be based on the distribution of an element in the memory storage element **205-a** and the polarity of the read pulse being applied during the read operation.

[0051] For example, a memory controller may apply a first read pulse **315** having a positive polarity (e.g., total voltage across the memory cell **105-e** is greater than zero) to the memory cell **105-e** as part of a read operation. The logic state identified by a memory controller as being stored in the memory cell **105-e** may be based on the distribution of ions in the memory cell. If the memory cell **105-e** was programmed with a positive polarity programming pulse (e.g., first programming pulse **305**), the memory controller may determine that a logic '1' is stored on the memory cell **105-c**. However, if the memory cell **105-e** was programmed with a negative polarity programming pulse (e.g., second programming pulse **310**), the memory controller may determine that a logic '0' is stored on the memory cell **105-c**.

[0052] Such a phenomenon may occur because of how distribution of ions in the memory storage element **205-a** interacts with the applied pulses. If the positive voltage of the read pulse is applied to the electrode (e.g., top electrode **210** or bottom electrode **215**) nearest the concentration of ions, the memory controller may detect a large amount of charge or a high resistivity. The memory controller may identify the high amount of charge as a logic '1.' If the positive voltage of the read pulse is applied to the electrode (e.g., top electrode **210** or bottom electrode **215**) farthest away from the concentration of ions, the memory controller may detect a low amount of charge or a low resistivity. The memory controller may identify the low amount of charge as a logic state '0.'

[0053] The same principles may apply when a second read pulse **320** having a negative polarity (e.g., total voltage across the memory cell **105-e** is less than zero) is applied to the memory cell **105-e** as part of a read operation. The logic state identified by a memory controller as being stored in the memory cell **105-e** may be based on the distribution of ions in the memory cell. If the memory cell **105-e** was programmed with a positive polarity programming pulse (e.g., first programming pulse **305**), the memory controller may determine that a logic '0' is stored on the memory cell **105-c**. However, if the memory cell **105-e** was programmed with a negative polarity programming pulse (e.g., second programming pulse **310**), the memory controller may determine that a logic '1' is stored on the memory cell **105-c**.

[0054] In some cases, the memory controller may be configured to invert data before it is output to a host device. To correctly identify a logic state stored on a self-selecting memory cell, the memory controller may need to know the distribution of ions in the memory storage element. One way to identify the distribution of ions is to know the polarity of the programming pulse used to program the self-selecting memory cell. In some instances, the memory controller may identify the polarity of the programming pulse used to program the self-selecting memory cell and the read pulse to read the self-selecting memory cell. The memory controller may identify the logic state stored on the self-selecting memory cell based on both the polarity of the programming pulse and the polarity of the read pulse. In some instances, the polarity of pulses applied to a specific memory cell of the memory tile may be statically or semi-statically configured. If the polarity of pulses to the specific memory cell are dynamically configured, the memory controller may perform additional operations to identify the polarities.

[0055] A memory controller may be configured to leverage the ability of a self-selecting memory cell to be accessed using pulses of multiple polarities to concurrently access to memory cells on the same memory tile at the same time. The voltages applied to the access lines for each memory cell access during a single access operation duration may be configured such that a voltage applied to the unselected memory cells of the memory tile does not exceed the programming threshold, a read threshold, or some other disturbance threshold of the unselected memory cells. In effect, the voltages applied to the different access lines during the access operation may be configured such that they negatively interfere with each for unselected cells but constructively interfere with each for selected memory cells on the memory tile.

[0056] FIG. 4 illustrates an example of a memory tile **400** that supports systems and techniques for accessing multiple memory cells concurrently in accordance with various examples of the present disclosure. Specifically, FIG. 4 illustrates two memory cells on the memory tile **400** being accessed concurrently using the same type of access operation during the same access operation duration. For example, any two memory cells in the memory tile **400** may be read concurrently or any two memory cells in the memory tile **400** may be programmed concurrently.

[0057] The memory tile **400** includes a plurality of memory cells **405**, **410**, a plurality of word lines **110-f**, and a plurality of digit lines **115-f**. The memory tile **400** illustrates how a first selected memory cell **405-a** may be accessed (e.g., read or write) using a first pulse having a first polarity and a second selected memory cell **405-b** may be accessed (e.g., read or write) using a second pulse having a second polarity different from the first polarity, where the selected memory cells **405** are accessed (e.g., read or written) concurrently. The memory tile **400** may also include a plurality of unselected memory cells **410**. The memory cells **405**, **410** may be examples of the memory cells **105** described with reference to FIGS. 1-3.

[0058] The memory controller (not shown) associated with the memory tile **400** may identify the first selected memory cell **405-a** and the second selected memory cell **405-b** to access concurrently using a read operation or a write operation during a single access operation duration. In many memory architectures, only a single memory cell may be accessed during the single access operation duration.

[0059] The memory controller may select the polarity of the pulses (e.g., a two read pulses or two programming pulses) to be applied to apply to the selected memory cells **405**. The specific polarity of the pulses for each selected memory cell may be selected based on a variety of factors, which may include the location of the selected memory cells **405**, the distribution of ions of the selected memory cells **405**, the characteristics (e.g., polarity and other characteristics) of the programming pulse used to program the selected memory cells **405**, **405-b**, or a combination thereof. The memory controller may determine that each selected memory cell **405**, **405-b** is to be accessed (e.g., read or write) using a different polarity of pulse. For example, if the first selected memory cell **405-a** is to be read with a positive polarity read pulse, then memory controller may determine that the second selected memory cell **405-b** is to be read with a negative polarity read pulse. In another example, if the first selected memory cell **405-a** is to be programmed with a positive polarity programming pulse, then the memory controller may determine that the second selected memory cell **405-b** is to be programmed with a negative polarity programming pulse.

[0060] The memory controller may control the biasing of the word lines **110-f** and the biasing of the digit lines **115-f** to achieve the pulses having selected polarity and magnitude. For example, a positive pulse may have a magnitude and polarity of  $+V_a$  (e.g.,  $+V_r$  for a read pulse or  $+V_p$  for a programming pulse, where  $V_r$  is different than  $V_p$ ) and a negative pulse may have a magnitude and polarity of  $-V_a$  (e.g.,  $-V_r$  for a read pulse or  $-V_p$  for a programming pulse, where  $V_r$  is different than  $V_p$ ).  $V_a$  may represent the total voltage difference across the selected memory cell during the access operation (e.g., read operation or write operation). The memory controller may control the voltages on the respective word lines **110-f** and digit lines **115-f** such that the voltage difference across the selected memory cell is the desired polarity and/or magnitude. In some cases, the

memory controller may hold one of the access lines of the first selected memory cell **405** at zero volts and may bias the other access line to the full magnitude of  $V_a$ . Such an operation will cause the selected memory cell **405** to be accessed (e.g., read or write), but it may also disturb unselected memory cells **410** coupled with the access line biased to  $V_a$ . An unselected memory cell **410** may be disturbed when the voltage difference across the memory cell exceeds a programming threshold, a read threshold, or some other disturbance threshold associated with the unselected memory cell **410**.

[0061] The memory controller may partition the pulse (e.g.,  $V_a$ ) into a first voltage (e.g.,  $+V_a/2$ ) applied to a first access line and a second voltage (e.g.,  $-V_a/2$ ) applied to a second access line. The combination of the first voltage and the voltage will result in a full voltage difference of  $V_a$  being applied to the selected memory cell **405**. The memory controller may identify a magnitude, polarity, shape, or combination thereof of the first voltage and the second voltage to achieve the full voltage difference across the selected memory cell **405**.

[0062] The memory controller may determine the polarity of each voltage based on the polarity of the pulse being applied to the selected memory cell **405**. For example, if the pulse (e.g., read pulse or programming pulse) is a positive polarity pulse, the memory controller may apply a positive polarity voltage of  $+V_a/2$  to the digit line **115-f** of the selected memory cell **405** and a negative polarity voltage of  $-V_a/2$  to the word line **110-f** of the selected memory cell **405**.

[0063] In some cases, the memory controller may partition the magnitude of the pulse ( $V_a$ ) equally between the two access lines (e.g., 50%-50% split where  $V_a/2$  is applied to both access lines). In other cases, the memory controller may partition the pulse unequally between the two access lines (e.g., 51%-49% split, 60%-40% split, 66%-33% split, 75%-25% split). The percentage splits shown here are for illustrative purposes only and are not limiting to this disclosure.

[0064] Partitioning the pulse into the first voltage and the second voltage may reduce a likelihood that a voltage difference across an unselected memory cell **410** exceeds a programming threshold, read threshold or some other disturb threshold of the unselected memory cell **410**. In this manner, the memory controller may reduce a likelihood that unselected memory cells **410** in the memory tile **400** are disturbed. For example, the memory tile **400** illustrates how the voltage difference seen across each memory cell **405**, **410** based on biasing some access lines to access the selected memory cells **405** (e.g., read or write).

[0065] As shown in the memory tile **400**, the voltages applied to the access lines may be configured to constructively interfere with each other at the selected memory cells **405**. As such, the first selected memory cell **405-a** sees a positive polarity pulse during the access operation duration and the second selected memory cell **405-b** sees a negative polarity pulse during the access operation. The voltages applied to the access lines are configured to cooperate together to access the first selected memory cell **405-a** and the second selected memory cell **405-b** concurrently.

[0066] As shown in the memory tile **400**, the voltages applied to the access lines may also be configured to destructively interfere with each other at some of the unselected memory cells **410**. For example, some of the unselected memory cells **410** may see a voltage difference of zero volts even though the access lines of that unselected memory cell are biased to some value for the access operation (e.g., read operation or write operation). By configuring the voltages (e.g., the first voltage and the second voltage) in such a way to constructively and/or destructively interfere with each other, the likelihood that unselected memory cells **410** that share access lines with the selected memory cells **405** are disturbed by the access operation is reduced.

[0067] The voltages applied to the access lines may also be configured such that if not constructive or destructive interference occurs in the memory tile, the voltage difference seen across the unselected memory cell **410** will not satisfy a disturb threshold (e.g., a programming threshold or a read threshold).

[0068] In some cases, if both of the selected memory cells **405** of the memory tile **400** are accessed using the same polarity of pulse, some of the unselected memory cells **410** may also be accessed

inadvertently. For example, if a positive pulse is used to access both the first selected memory cell **405-a** and the second selected memory cell **405-b**, then unselected memory cells **410-a**, **410-b** may also be inadvertently accessed. In such cases, the voltages applied to the access lines may constructively interfere with one another at four memory cells instead of the selected two memory cells.

[0069] In some cases, the selected memory cells **405** configured to be accessed concurrently cannot share a common access line. Meaning that the first selected memory cell **405-a** cannot be coupled with the same digit line **115-f** or word line **110-f** as the second selected memory cell **405-b**. Such a condition may increase a likelihood that one or more unselected memory cells **410** are disturbed during the access operation.

[0070] The memory controller may be configured to identify the selected memory cells **405** for the concurrent access operation based at least in part on the location of the memory cell, the access lines of the selected memory cells **405**, or whether the selected memory cells **405** share an access line. In some cases, the memory controller may be configured to determine whether the selected memory cells **405** share a common access line after the memory cells have been selected. If the memory controller determines that the selected memory cells **405** share a common access line, the memory controller may cancel the access operation for one of the selected memory cells **405**. In such cases, the access operation performed during the single access operation duration may be used to access only a single memory cell.

[0071] In some cases, any combination of memory cells may be accessed concurrently. In such cases, the memory controller may be configured to dynamically select the memory cells to be accessed during the single access operation duration based on commands received from a host device. To decrease the latency for performing a read command or a write command received from a host device, the memory device may access two or more memory cells **405** concurrently in the same memory tile **400**. In some cases, such concurrent accessing may reduce the total time taken by the memory device to execute the read command or the write command to a host device after receiving the command.

[0072] The principles described with reference to accessing two memory cells of the memory tile **400** concurrently using the same type of access operation (e.g., two read operations or two write operations), apply also more generally to any combination of access operations. For example, a memory controller may be configured to write to a first memory cell and read from a second memory cell on the same tile concurrently using similar principles as described in FIG. 4.

[0073] FIG. 5 illustrates examples of diagrams **500** of access pulses seen at an unselected memory cell in a memory tile that supports systems and techniques for accessing multiple memory cells concurrently in accordance with various examples of the present disclosure. In some circumstances, the memory controller may want to access two memory cells of a memory tile using two access pulses that will disturb unselected memory cells. To prevent disturbing unselected memory cells while still accessing two selected memory cells during a single access operation duration, the memory controller may delay one of the access pulses.

[0074] The features of the diagrams **500** may be implemented in the memory tile **400** described with reference to FIG. 4. The access pulses described with reference to the diagrams **500** may be examples of two read pulses or two programming pulses.

[0075] Diagram **500-a** illustrates voltages **505-a**, **510-a** seen by an unselected memory cell of a memory tile (e.g., unselected memory cell **410** of the memory tile **400**) during an access operation. In the diagram **500-a**, the voltages **505-a**, **510-a** may “destructively” interfere with each other to prevent the unselected memory cell from being disturbed. For example, the first voltage **505-a** may have a first polarity and first magnitude (e.g.,  $+V_a/2$ ) and the voltage **510** may have the same polarity and, in some cases, the same magnitude (e.g.,  $+V_a/2$ ). The combination of these two voltages **505-a**, **510-a** may result in a voltage difference **515** that fails to satisfy a disturb threshold of the unselected memory cell (e.g., a programming threshold or a read threshold or some other

threshold). In some cases, the magnitudes and/or polarities of the two voltages **505-a**, **510-a** may be different, but the resulting voltage difference still may fail to satisfy the disturb threshold.

[0076] Diagram **500-b** illustrates voltages **505-b**, **510-b** seen by an unselected memory cell of a memory tile (e.g., unselected memory cell **410** of the memory tile **400**) during an access operation. In the diagram **500-b**, the voltages **505-b**, **510-b** may “constructively” interfere with each other to cause the unselected memory cell to be disturbed during the access operation (e.g., read operation or write operation). For example, the first voltage **505-b** may have a first polarity and first magnitude (e.g.,  $+V_a/2$ ) and the voltage **510-b** may have a different polarity and, in some cases, the same magnitude (e.g.,  $-V_a/2$ ). The combination of these two voltages **505-b**, **510-b** may result in a voltage difference **520** that satisfies a disturb threshold of the unselected memory cell (e.g., a programming threshold or a read threshold or some other threshold). In some cases, the magnitudes and/or polarities of the two voltages **505**, **510** may be different, but the resulting voltage difference still may satisfy the disturb threshold.

[0077] The memory controller may identify when two access pulses for two selected memory cells of a memory tile (e.g., read-read pulses, programming-programming pulses, or programming-read pulses) may disturb one or more unselected memory cells. The memory controller may identify this condition using a variety of means. In some cases, the memory controller may compare the voltages of the access pulses to a predefined list of forbidden voltage combinations. In some cases, the memory controller may compare the memory cell locations, the magnitude, and/or the polarities of the access pulses to a predefined list of forbidden combinations. In some cases, memory controller may dynamically determine interactions for each memory cell to identify if an unselected memory cell may be disturbed.

[0078] The memory controller may be configured to delay one of the access pulses for one of the selected memory cells of the memory tile based on the potential that an unselected memory cell may be disturbed. Diagram **500-c** illustrates an example where the memory controller delays a second voltage **510-c** to occur sometime after the first voltage **505-c**. Diagram **500-d** illustrates an example where the memory controller delays a first voltage **505-d** to occur sometime after the second voltage **510-d**. By staggering the access pulses in such a manner, the memory controller may be configured to prevent the voltage difference **520** seen across an unselected memory cell from satisfying a disturbance threshold.

[0079] In some cases, the delayed pulse may occur after the initial pulse is complete. In some cases, the initial pulse and the delayed pulse may at least partially overlap. The memory controller may select which pulse is delay based on the memory cell location, the polarity of the pulses, the magnitude of the pulses, the shape of the pulses or a combination thereof. For example, based on their respective magnitudes and/or shapes, a first type of overlap of the pulses may be less likely to result in a disturbance of the unselected memory cell than a second type of overlap of the pulses.

[0080] In some cases, a programming operation may be accompanied with a pre-read operation. In such cases, if two cells are concurrently programmed only part of the programming operation and the pre-read operation may be delayed. For example, the pre-read operation may occur currently, but one of the programming pulses may be delayed.

[0081] FIG. **6** illustrates an example of a memory tile **600** that supports systems and techniques for accessing multiple memory cells concurrently in accordance with various examples of the present disclosure. Specifically, FIG. **6** illustrates two memory cells on the memory tile **600** being accessed concurrently using the different types of access operations (e.g., a read operation and write operation) during the same access operation duration. For example, a first selected memory cell **605-a** may be programmed during the access operation duration and a second selected memory cell **605-b** may be read during the access operation duration, or vice-versa.

[0082] The memory tile **600** includes a plurality of memory cells **605**, **610**, a plurality of word lines **110-g**, and a plurality of digit lines **115-g**. The memory tile **600** illustrates how a first selected memory cell **605-a** may be programmed using a programming pulse having a first polarity and a

second selected memory cell **605-b** may be read using a read pulse having a second polarity different from the first polarity, where the selected memory cells **605** are accessed concurrently. The memory tile **600** illustrates principles where two different types of pulses are used concurrently. The memory tile **600** may also include a plurality of unselected memory cells **610**. The memory tile **600** may be an example of the memory tiles **100** and **400** described with reference to FIGS. **1** and **4**. The memory cells **605**, **610** may be examples of the memory cells **105**, **405**, **410** described with reference to FIGS. **1-4**.

[0083] The memory controller (not shown) associated with the memory tile **600** may operate similarly as the memory controller for the memory tile **400**. For example, the memory controller may select memory cells to be accessed (e.g., selected memory cells **605**), may select characteristics (e.g., magnitude, polarity, or shape) of pulses to be applied to the selected memory cells **605**, may determine voltages to apply to access lines based on the identified pulses, may perform operations to ensure that unselected memory cells **610** are not disturbed, may perform other operations and functions, or a combination thereof.

[0084] When different access operations are performed on the same memory tile during the same access duration, differences between the different types of pulses may disturb cause disturbances on unselected memory cells **610**. For example, a programming pulse may have one or more characteristics that are different from one or more characteristics a read pulse. In some cases, a magnitude of the programming pulse may be greater than a magnitude of the read pulse. Further, differences in the shapes of the programming pulse and the read pulse may increase a likelihood of disturbing an unselected memory cell **610** during at least a portion of the access operation duration where both a write operation and a read operation are performed on different memory cells of the same memory tile **600**.

[0085] The memory controller may be configured to select the characteristics of the pulses and partition the pulses into voltages for access lines in a manner to reduce a likelihood of disturbing an unselected memory cell **610**. Diagrams **700** and **800** illustrate issues and solutions related to the interplay between programming pulses and read pulses in a memory tile.

[0086] FIG. **7** illustrates an example of a diagram **700** of access pulses seen at an unselected memory cell in a memory tile that supports systems and techniques for accessing multiple memory cells concurrently in accordance with various examples of the present disclosure. In some circumstances, the memory controller may want to access program a first memory cell of a memory tile concurrently with reading a second memory cell of the same memory tile. In some cases, performing both operations concurrently may disturb unselected memory cells of the memory tile. To prevent disturbing unselected memory cells while still accessing two selected memory cells during a single access operation duration, the memory controller may perform a variety of mitigation operations.

[0087] The features of the diagram **700** may be implemented in the memory tile **600** described with reference to FIG. **6**. The access pulses described with reference to the diagram **700** may be examples of a read pulse and a programming pulse.

[0088] The diagram **700** illustrates a plurality of voltages **705**, **710** seen by an unselected memory cell (e.g., unselected memory cell **610**) applied to access lines during a plurality of access operation durations **715**. The voltages **705**, **710** may be portions of a programming pulse and a read pulse. For example, during a first access operation duration **715-a**, a first programming voltage **705-a** may be applied to a first access line (e.g., word line **110-g** or digit line **115-g**) coupled with the unselected memory cell of the memory tile and a first read voltage **710-a** may be applied to a second access line (e.g., word line **110-g** or digit line **115-g**) coupled with the unselected memory cell of the memory tile. The first read voltage **710-a** may be applied concurrently with the first programming voltage **705-a** during the first access operation duration **715-a**.

[0089] During the first access operation duration **715-a**, the voltage difference **720** seen by the unselected memory cell may fail to satisfy a disturbance threshold (e.g., programming threshold,

read threshold, or other threshold) of the unselected memory cell. In effect, first programming voltage **705-a** and the first read voltage **710-a** may “destructively” interfere with each other and prevent the unselected memory cell from being disturbed.

[0090] In a contrasting example, during a third access operation duration **715-c**, the voltage difference **725** seen by the unselected memory cell may satisfy a disturbance threshold (e.g., programming threshold, read threshold, or other threshold) of the unselected memory cell. The third programming voltage **705-c** may have a first polarity and first magnitude that cooperate with a second polarity (different from the first polarity) and a second magnitude of the third read voltage **710-c** to produce the voltage difference **725** that satisfies the disturbance threshold. In effect, third programming voltage **705-c** and the third read voltage **710-c** may “constructively” interfere with each other and cause the unselected memory cell to be disturbed.

[0091] The memory controller may perform one or more mitigation operations to prevent the unselected memory cell from being disturbed in scenarios like those illustrated in the third access operation duration **715-c**. In some cases, the memory controller may cancel either programming operation or the read operation during the access operation duration where an unselected memory cell may be disturbed. In some cases, the memory controller may partition the programming pulse into voltages that will reduce a likelihood of or prevent disturbances of unselected memory cells. Because the programming pulse and the read pulse may have different magnitudes and/or shapes, the memory controller may partition the magnitudes in such of the two pulses in such a way that risk of disturbances of unselected memory cell is mitigated. In some cases, the memory controller may delay one of the voltages similar to what is described with reference to FIG. 5.

[0092] In some cases, the memory controller may partition the pulses into unequal partitions (e.g., not a **50/50** split). In some cases, each pulse and/or voltage may have a particular shape. For instance, the third programming voltage **705-c** may have a stepped shape or ramp shape and the third read voltage **710-c** may have a stepped shape or ramped shape. In such instances, the memory controller may cause the ramps or steps to coincide such that a voltage difference seen at the unselected memory cell does not satisfy the disturbance threshold. For example, the third programming voltage **705-c** may be an increasing ramp shape and the third read voltage **710-c** may be a decreasing ramp shape during the third access operation duration **715-c**.

[0093] In some cases, the memory controller may select the polarities of the programming pulse, the read pulse, and/or the partitioned voltages that result from those pulses to mitigate disturbances to unselected memory cells. In some cases, the memory controller may cause the polarities of the two voltages applied to an unselected memory cell to be different polarities (e.g., one negative and one positive).

[0094] FIG. 8 illustrates an example of a diagram **800** of access pulses seen at an unselected memory cell in a memory tile that supports systems and techniques for accessing multiple memory cells concurrently in accordance with various examples of the present disclosure. The diagram illustrates a process by the memory controller for mitigating disturbances on unselected memory cells when a first selected memory cell is programmed concurrently with a second selected memory cell being read on the same memory tile. The features of the diagram **800** may be implemented in the memory tile **600** described with reference to FIG. 6. The access pulses described with reference to the diagram **800** may be examples of a read pulse and a programming pulse.

[0095] Diagram illustrates an example where the memory controller selects the polarity of the read pulse (and by extension the read voltages) applied to the access lines of the memory tile based on the polarity of the programming pulse. By selecting the polarity of the read pulse based on the polarity of the programming pulse, the memory controller may mitigate the likelihood of disturbances on unselected memory cells of the memory tile. In some cases, the memory controller may select the polarity of the programming pulse based on the polarity of the read pulse.

[0096] The memory controller may identify a polarity of a programming pulse for the selected memory cell. The memory controller may make this identification based on a current state of the

selected memory cell (e.g., a current ion distribution of the selected memory cell). The memory controller may then select the polarity of the read pulse to be opposite the polarity of the programming pulse to minimize the likelihood that unselected memory cells of the memory tile will be disturbed by the simultaneous write and read of two memory cells on the memory tile. [0097] For example, the diagram **800** illustrates a plurality of voltages **805, 810** seen by an unselected memory cell (e.g., unselected memory cell **610**) applied to access lines during a plurality of access operation durations **815**. The voltages **805, 810** may be portions of a programming pulse and a read pulse. During each access operation duration **815**, the memory controller may identify a polarity of the programming voltage **805** applied to a first access line (e.g., word line **110-g** or digit line **115-g**) coupled with the unselected memory cell of the memory tile. The memory controller may also select a polarity of the read voltage **810** based on the identified polarity of the programming pulse.

[0098] For example, the memory controller may identify that during the first access operation duration **815-a** the first programming voltage **805-a** has a positive polarity. The memory controller may select the first read voltage **810-a** to have a negative polarity based on the programming pulse having a positive polarity. In effect, the memory controller may toggle the polarity of the read pulse based on the polarity of programming pulse used to program new data on the selected memory cell. In some cases, the memory controller may be configured to toggle the polarity of the programming pulse based on the polarity of the read pulse.

[0099] FIG. **9** illustrates an example of a circuit **900** that supports systems and techniques for accessing multiple memory cells concurrently in accordance with various examples of the present disclosure. The circuit **900** illustrates the components used to dynamically modify the polarity of programming pulses and/or read pulses during an access operation.

[0100] The circuit **900** may include a memory cell **905**, a word line **110-h**, and a digit line **115-h**. A positive polarity voltage source **910** and a negative polarity voltage source **915** may be selectively coupled to the access lines (e.g., word line **110-h** or digit line **115-h**). A switching component **920** may be configured to selectively couple one or more of the various voltage sources **910, 915** to the respective access line. The memory cell **905** may be an example of the memory cells **105, 405, 605** described with reference to FIGS. **1-8**.

[0101] The voltage sources **910, 915** may be configured to bias their respective access lines to voltage magnitudes associated with the voltage source. In some cases, each voltage source **910, 915** is configured to output a plurality of voltage magnitudes. For example, the positive polarity voltage source **910** may be configured to output a first voltage magnitude associated with a programming pulse, a second voltage magnitude associated with a read pulse, and/or a plurality of voltage magnitudes associated with different shaped pulses. In some cases, each voltage source **910, 915** is configured to output a single voltage magnitude with a single polarity. In such cases, the access lines (e.g., word line **110-h** and digit line **115-h**) may be selectively coupled with more than two voltage sources **910, 915** using the switching component **920**.

[0102] For example, the word line **110-h** may be configured to be coupled to a positive polarity voltage source for the programming pulse, a positive polarity voltage source for a read pulse, a negative polarity voltage source for the programming pulse, a negative polarity voltage source for a read pulse, or a combination thereof. In some cases, a single voltage source may be configured to generate all of the pulses (e.g., magnitudes, polarities, and shapes) used to access the memory cell **905**. In such cases, the circuit **900** may not include the switching component **920**. The memory controller may also be configured to isolate/decouple the voltage sources **910, 915** from the access lines during an access operation.

[0103] The switching components **920** may be one or more transistors positioned between the voltage sources **910, 915** and their respective access lines. The memory controller may be configured to select the various voltage sources **910, 915** by controlling the gate voltages of the transistors. In some cases, the switching components **920** may include a p-type transistor for one



voltage source and an n-type transistor for another voltage source. In such cases, the gates of the transistors may be tied so that only one voltage source may be coupled to an access line at a time. In some cases, both transistors may be the same type, the gates may be tied together, but one of the gates may also include an inverter. In some cases, the switching components **920** may be configured to toggle between different components. For example, the switching component **920** may couple an access with either the positive polarity voltage source **910** or the negative polarity voltage source **915**.

[0104] The circuit **900** may also include a first sense component **925** and a second sense component **930** selectively coupled with the digit line **115-h** using a switching component **935** (sometimes sense components are referred to as sense amplifiers). The first sense component **925** may be configured to sense a state of the memory cell **905** when a positive polarity read pulse is used during the access operation. The second sense component **930** may be configured to sense a state of the memory cell **905** when a negative polarity read pulse is used during the access operation.

[0105] The memory controller may be configured to selectively couple the digit line **115-h** to one of the sense components **925**, **930** based on the polarity of the read pulse being applied to the memory cell **905**. The memory controller may also be configured to isolate/decouple the digit line from one of the sense components **925**, **930** during an access operation. In some cases, a single sense component may be configured to sense using both positive polarity and negative polarity read pulses. In such cases, the circuit **900** may not include the switching component **935**. The sense components may be examples of the sense component **125** described with reference to FIG. **1**.

[0106] The switching component **935** may be one or more transistors positioned between the sense components **925**, **930** and their digit access lines **115-h**. The memory controller may be configured to select the various sense components **925**, **930** by controlling the gate voltages of the transistors.

[0107] In some cases, the switching components **935** may include a p-type transistor for one sense component and an n-type transistor for another sense component. In such cases, the gates of the transistors may be tied so that only one sense component may be coupled to an access line at a time. In some cases, both transistors may be the same type, the gates may be tied together, but one of the gates may also include an inverter. In some cases, the switching components **935** may be configured to toggle between different components. For example, the switching component **935** may couple an access with either of the sense components **925**, **930**.

[0108] In one embodiment, a memory device may include a memory cell **905**, a digit line **115-h** coupled with the memory cell **905**, a first sense component **925** coupled with the digit line **115-h**, the first sense component **925** may be configured to identify a logic state stored on the memory cell based at least in part on a first read pulse having a first polarity, and a second sense component **930** coupled with the digit line **115-h**, the second sense component **930** configured to identify the logic state stored on the memory cell based at least in part on a second read pulse having a second polarity different than the first polarity.

[0109] In some examples of the memory device described above, a first voltage source **910** coupled with the digit line **115-h**, the first voltage source **910** configured to supply at least a part of the first read pulse having the first polarity. In some examples of the device or system described above, a second voltage source **915** coupled with the digit line **115-h**, the second voltage source **915** configured to supply at least a part of the second read pulse having the second polarity.

[0110] In some examples of the memory device described above, a switching component **920** configured to selectively couple the digit line **115-h** with the first voltage source **910** or the second voltage source **915** during an access operation.

[0111] In some examples of the memory device described above, a switching component **935** configured to selectively output a signal from the first sense component **925** or the second sense component **930** based at least in part on a type of read pulse applied to the memory cell **905** during a read operation.

[0112] In some examples of the memory device described above, the memory cell **905** comprises a chalcogenide material configured to use a non-uniform distribution of ions to indicate the logic state. In some examples of the memory device described above, the memory cell **905** may be a self-selecting memory cell.

[0113] FIG. **10** illustrates examples of memory tiles **1000** that support systems and techniques for accessing multiple memory cells concurrently in accordance with various examples of the present disclosure. The memory tile **1000** may include semi-tiles **1005**, **1010** that are statically or semi-statically configured. The semi-tiles **1005**, **1010** may be used to implement the techniques of simultaneously accessing two memory cells of the memory tile **1000**. The memory tile **1000** may be an example of the memory tiles **100**, **400**, **600** described with reference to FIGS. **1**, **4**, and **6**.

[0114] Memory tiles that include a plurality of self-selecting memory cells may be configured to access nearly any pairing of memory cells concurrently. Dynamically accessing various of combinations of memory cells using various combinations of pulses may, however, increase a processing load of the memory controller. To reduce the processing needed to perform a concurrently access operations on two memory cells in the same memory tile, the memory tile **1000** may include a first semi-tile **1005** and a second semi-tile **1010**.

[0115] The first semi-tile **1005** may include a plurality of memory cells **1015** configured to be read using a positive polarity read pulse. The second semi-tile **1010** may include a plurality of memory cells **1020** configured to read using a negative polarity read pulse. The memory tile may include a plurality of word lines **110-i** and a plurality of digit lines **115-i**. Such a configuration may reduce the processing needed to perform a read operation because the same read pulse is used every time for a given semi-tile. In addition, such a configuration may reduce the amount of components needed to operate the memory tile **1000** (e.g., may reduce the number of sense components, switching components, voltage sources, or combinations thereof).

[0116] The memory tile **1000** may be divided into different semi-tiles in any manner. In some cases, a memory tile **1000-a** may include semi-tiles grouped by word lines **110-i**. Where the first semi-tile **1005-a** includes memory cells **1015-a** in electronic communication with a first set of word lines **110-i** and the second semi-tile **1010-a** includes memory cells **1020-a** in electronic communication with a second set of word lines **110-i** different than the first set. In some cases, a memory tile **1000-b** may include semi-tiles grouped by digit lines **115-i**. Where the first semi-tile **1005-b** includes memory cells **1015-b** in electronic communication with a first set of digit lines **115-i** and the second semi-tile **1010-b** includes memory cells **1020-b** in electronic communication with a second set of digit lines **115-i** different than the first set.

[0117] Even though memory cells **1015**, **1020** of the memory tile **1000** are configured to be read by a specific polarity of read pulse, every memory cell **1015**, **1020** of the memory cell may be configured to be programmed by a positive polarity programming pulse and a negative polarity programming pulses. Such a capability may be needed to change the distribution of ions in any given memory cell.

[0118] Access operation durations that include a read operation of a first memory cell and a read operation of a second memory cell may be performed as described with reference to FIGS. **4** and **5**. The memory controller may select a memory cell **1015** in the first semi-tile **1005** and a memory cell **1020** in the second semi-tile **1010** to be read during a single access operation duration. In semi-tile configuration, it may not be possible to read two memory cells that are coupled to the same access line because of how the semi-tiles are configured.

[0119] For example, in the memory tile **1000-a**, the word line **110-i** for the first semi-tile **1005-a** may be configured to have a negative polarity voltage during a read operation and the word line **110-i** for the second semi-tile **1010-a** may be configured to have a negative polarity voltage during the read operation. To read a memory cell, that means the corresponding digit line **115-i** for each semi-tile **1005-a**, **1010-a** may be biased to a voltage having an opposite polarity as its associated word line **110-i**. Because a single digit line **115-i** cannot be biased to both a positive polarity

voltage and a negative polarity voltage at the same time, if two memory cells in the semi-tile configurations are to be read during the same access operation duration they cannot share a common digit line **115-i** or a common word line **110-i**. In some cases, any two memory cells of the memory tile **1000** may be read concurrently as long as the two memory cells do not share a common access line (either a common word line or a common digit line).

[0120] In the semi-tile configurations of the memory tile **1000**, the polarity of the read pulses are statically configured for each semi-tile. For example, memory cells **1015** of the first semi-tile **1005** may be read using a positive polarity read pulse and memory cells **1020** of the second semi-tile **1010** may be read using a negative polarity read pulse, or vice-versa. Because of this static configuration of read pulses, the memory controller may be configured to select the polarity of programming pulse based on which semi-tile the memory cell is in, the desired logic state of the memory cell, the current state of the memory cell, or the polarity of the read pulse that will be used to read the memory cell, or a combination thereof.

[0121] For example, in the first semi-tile **1005** where memory cells **1015** are read using a positive polarity read pulse, if a positive polarity programming pulse is applied to the memory cell **1015**, a first distribution of ions may occur on the memory cell **1015**, which the positive polarity read pulse may interpret as a logic '1'. Similarly, if a negative polarity programming pulse is applied to the memory cell **1015**, a second distribution of ions different than the first distribution may occur on the memory cell **1015**, which the positive polarity read pulse may interpret as a logic '0'.

[0122] Conversely, in the second semi-tile **1010** where memory cells **1020** are read using a negative polarity read pulse, if a positive polarity programming pulse is applied to the memory cell **1020**, the first distribution of ions may occur on the memory cell **1020**, which the negative polarity read pulse may interpret as a logic '0'. Similarly, if a negative polarity programming pulse is applied to the memory cell **1020**, the second distribution of ions may occur on the memory cell **1020**, which the negative polarity read pulse may interpret as a logic '1'. In such cases, a logic '1' is written to the memory cells of the different semi-tiles using different polarity programming pulses. For example, a logic '1' is stored on the first semi-tile **1005** using a positive polarity programming pulse and a logic '1' is stored on the second semi-tile **1010** using a negative polarity programming pulse. In some cases, the memory controller may be configured to invert the sensed logic state before it is output. In such cases, a logic '1' may be stored to both semi-tiles using the same polarity of programming pulse.

[0123] In some cases, the memory controller may not apply a programming pulse during a write operation. For example, if a memory cell already stores a logic '1' stored thereon and the write command indicates that the next desired logic state is a logic '1,' the memory controller may take no action during the write operation and indicate that the desired value is written to the memory cell.

[0124] In the semi-tile configurations of the memory tile **1000**, various combinations of programming pulses, read pulses, bit transitions, or combinations thereof may disturb unselected memory cells of the memory tile **1000**. This may occur because the static configuration of read pulses reduces some of the flexibility of the access operations. The memory controller may be configured to identify "forbidden" combinations of access operations that may occur concurrently in a memory tile **1000** with semi-tiles **1005**, **1010**. Forbidden combinations of access operations may occur when an unselected memory cell of the memory tile **1000** sees a voltage difference that satisfies a disturb threshold (e.g., a programming threshold or a read threshold).

[0125] Table 1 illustrates voltage differences that may occur across an unselected memory cell of the memory tile **1000** when two memory cells in the memory tile **1000** are programmed concurrently (e.g., a first memory cell **1015** in the first semi-tile **1005** is programmed concurrently with programming a second memory cell **1020** in the second semi-tile **1010**). Table 1 indicates which programming bit transitions may result in an unselected memory cell of the memory tile **1000** seeing a voltage difference that satisfies a disturb threshold.

TABLE-US-00001 TABLE 1 Simultaneous Write Operations in Different Semi-Tiles Semi-tile 1005 Bit Transition: Bit Transition: Bit Transition: Bit Transition: 0.fwdarw.0 0.fwdarw.1 1.fwdarw.0 1.fwdarw.1 Semi-tile 1010 (V.sub.PRG-1005 = 0) (V.sub.PRG-1005 > 0) (V.sub.PRG-1005 < 0) (V.sub.PRG-1005 = 0) Bit Transition:  $\Delta V = 0$  .sup.  $\Delta V = V_{\text{sub.PRG}}/2$   $\Delta V = V_{\text{sub.PRG}}/2$   $\Delta V = 0$  .sup. 0.fwdarw.0 (V.sub.PRG-1010 = 0) Bit Transition:  $\Delta V = V_{\text{sub.PRG}}/2$   $\Delta V = V_{\text{sub.PRG}}$   $\Delta V = 0$  .sup.  $\Delta V = V_{\text{sub.PRG}}/2$  0.fwdarw.1 Disturb (V.sub.PRG-1010 < 0) Bit Transition:  $\Delta V = V_{\text{sub.PRG}}/2$   $\Delta V = 0$  .sup.  $\Delta V = V_{\text{sub.PRG}}$   $\Delta V = V_{\text{sub.PRG}}/2$  1.fwdarw.0 Disturb (V.sub.PRG-1010 > 0) Bit Transition:  $\Delta V = 0$  .sup.  $\Delta V = V_{\text{sub.PRG}}/2$   $\Delta V = V_{\text{sub.PRG}}/2$   $\Delta V = 0$  .sup. 1.fwdarw.1 (V.sub.PRG-1010 = 0)

[0126] In the semi-tile configurations, the memory controller may be configured to determine whether an unselected memory cell in the memory tile may be disturbed on a semi-tile level. Such a configuration may reduce processing for performing the concurrent write operations and thereby reduce power consumption, reduce processing time (e.g., latency), or a combination thereof. In some examples, the memory controller may identify the bit transition for each semi-tile during the concurrent access operation and may determine whether an unselected memory cell in the memory tile will be disturbed based on the bit transitions. In such examples, the memory controller may not have to check if the combination of write operations is permissible on a memory cell by memory cell basis, but rather may check on a semi-tile by semi-tile basis. In some cases, the memory controller may compare the bit transitions using a look-up table stored in memory.

[0127] Upon determining that one or more unselected memory cells may be disturbed by performing the two write operations concurrently in the same memory tile with semi-tiles, the memory controller may perform one or more disturbance mitigation operations. For example, the memory controller may cancel one of the write operations and perform it during a later access operation duration other than the current duration. In some examples, the memory controller may delay one of the programming pulses within the same access operation duration. In some cases, the memory controller may modify the shape of one or more voltages applied to the memory cells during the two concurrent write operations.

[0128] Table 2 illustrates voltage differences that may occur across an unselected memory cell of the memory tile **1000** when a first memory cell of the memory tile **1000** is programmed concurrently with reading a second memory cell of the memory tile **1000** (e.g., a first memory cell **1015** in the first semi-tile **1005** is programmed concurrently with reading a second memory cell **1020** in the second semi-tile **1010**). Table 2 indicates which programming pulse polarities in combination with a read pulse polarities may result in an unselected memory cell of the memory tile **1000** seeing a voltage difference that satisfies a disturb threshold.

TABLE-US-00002 TABLE 2 Simultaneous Read-Write Operations in Different Semi-Tiles Write Semi-tile 1005 Semi-tile 1005 Semi-tile 1010 Semi-tile 1010 Read (V.sub.PRG-1005 > 0) (V.sub.PRG-1005 < 0) (V.sub.PRG-1010 < 0) (V.sub.PRG-1010 > 0) Semi-tile 1005 — —  $\Delta V = (V_{\text{sub.PRG}} + \Delta V = (V_{\text{sub.PRG}} - (V_{\text{sub.READ}} > 0) V_{\text{sub.READ}})/2 V_{\text{sub.READ}})/2$  Disturb Semi-tile 1010  $\Delta V = (V_{\text{sub.PRG}} + \Delta V = (V_{\text{sub.PRG}} - — — (V_{\text{sub.READ}} < 0) V_{\text{sub.READ}})/2 V_{\text{sub.READ}})/2$  Disturb

In Table 2, only a positive polarity read pulse is shown for the semi-tile **1005** and only a negative polarity read pulse is shown for the semi-tile **1010** because by definition only a single polarity of read pulse is associated with each semi-tile. In some cases, the polarities of read pulses assigned to each semi-tile may be reversed.

[0129] In the semi-tile configurations, the memory controller may be configured to determine whether an unselected memory cell in the memory tile may be disturbed on a semi-tile level by concurrently performing a read operation and a write operation on the same memory tile **1000**. Such a semi-tile configuration may reduce processing for performing the concurrent write operation and read operation and thereby reduce power consumption, reduce processing time (e.g., latency), or a combination thereof. In some examples, the memory controller may identify the pulse

polarities and/or the bit transition for each semi-tile during the concurrent access operations and may determine whether an unselected memory cell in the memory tile will be disturbed based on the pulse polarities and/or the bit transitions.

[0130] In such examples, the memory controller may not have to check if the combination of the write operation and the read operation is permissible on a memory cell by memory cell basis, but rather may check on a semi-tile by semi-tile basis. In some cases, the memory controller may compare the pulse polarities and/or the pulse polarities using a look-up table stored in memory.

[0131] Upon determining that one or more unselected memory cells may be disturbed by performing the two write operations concurrently in the same memory tile with semi-tiles, the memory controller may perform one or more disturbance mitigation operations. For example, the memory controller may cancel one of the access operations (either the read operation or the write operation) and perform it during a later access operation duration other than the current duration. In some examples, the memory controller may delay one of the pulses (either the read pulse or the programming pulse) within the same access operation duration. In some cases, the memory controller may modify the shape of one or more voltages applied to the memory cells during the two concurrent access operations.

[0132] In one embodiment, a memory device may include a memory tile **1000** having a first section of memory cells (e.g., first semi-tile **1005**) and a second section of memory cells (e.g., second semi-tile **1010**), wherein the memory cells **1015** of the first section are configured to be read in response to application of a first read pulse having a first polarity and the memory cells **1020** of the second section are configured to be read in response to application of a second read pulse having a second polarity different than the first polarity, a first sense component (e.g., sense component **1120** or **1155**) coupled with the first section of memory cells of the memory tile **1000** and configured to identify a logic state of one memory cell of the first section of memory cells based at least in part on the first read pulse having the first polarity, and a second sense component (e.g., sense component **1120** or **1155**) coupled with the second section of memory cells of the memory tile and configured to identify the logic state of one memory cell of the second section of memory cells based at least in part on the second read pulse having the second polarity.

[0133] In some examples of the memory device described above, a first voltage source (e.g., voltage sources **910**, **915**) coupled with digit lines **115** of the first portion, the first voltage source (e.g., voltage sources **910**, **915**) configured to supply at least a portion of the first read pulse having the first polarity. In some examples of the device or system described above, a second voltage source (e.g., voltage sources **910**, **915**) coupled with digit lines of the second portion, the second voltage source (e.g., voltage sources **910**, **915**) configured to supply at least a portion of the second read pulse having the second polarity.

[0134] In some examples of the memory device described above, a memory cell **1015**, **1020** of the memory tile **1000** may be formed of a chalcogenide material configured to use a non-uniform distribution of ions to indicate the logic state. In some examples of the memory device described above one or more trim parameters for the first portion of memory cells may be independent from one or more trim parameters for the second portion of memory cells.

[0135] In some examples of the memory device described above, the first sense component (e.g., sense component **1120**) and the second sense component (e.g., sense component **1120**) may be positioned under a footprint (e.g., footprint **1170**) of the memory tile **1000**. In some examples of the memory device described above, the memory tile **1000** includes more than one deck of memory cells.

[0136] FIG. **11** illustrates examples of memory devices **1100** that supports systems and techniques for accessing multiple memory cells concurrently in accordance with various examples of the present disclosure. The memory devices **1100** may include a plurality of memory tiles. Each memory tile of the memory devices may be divided into two or more semi-tiles. The memory devices **1100** illustrate components configured to perform access operations on at least two

memory cells of a memory tile concurrently.

[0137] A first memory device **1100-a** may include a plurality of memory tiles **1105**, each memory tile **1105** being divided into a first semi-tile **1110** configured to be read by a positive polarity read pulse and a second memory tile **1115** configured to be read by a negative polarity read pulse. The memory tile **1105** may include a sense component **1120** coupled with each semi-tile **1110**, **1115**. The sense components **1120** may be configured to identify a logic state of the memory cell based on the polarity of the read pulse associated with that semi-tile.

[0138] In the memory tile **1105**, the sense components **1120** may be positioned outside of the footprint **1135** of an array of memory cells. The memory tile **1105** may include a row decoder **1125** and column decoder **1130** configured to address the memory cells of both of the semi-tiles **1110**, **1115**. In the memory tile **1105**, at least one of the row decoder **1125** or the column decoder **1130** or both may be positioned outside of the footprint **1135** of an array of memory cells. In some cases, at least one of the row decoder **1125** or the column decoder **1130** or both may be positioned within under the array of memory cells and/or within a footprint **1135** of the array of memory cells.

[0139] A second memory device **1100-b** may include a plurality of memory tiles **1140**, each memory tile **1140** being divided into a first semi-tile **1145** configured to be read by a positive polarity read pulse and a second memory tile **1150** configured to be read by a negative polarity read pulse. The memory tile **1140** may include a sense component **1155** coupled with each semi-tile **1145**, **1150**. The sense components **1155** may be configured to identify a logic state of the memory cell based on the polarity of the read pulse associated with that semi-tile. In the memory tile **1140**, the sense components **1155** may be positioned in the footprint **1170** of an array of memory cells.

[0140] In such configurations, the sense components **1155** may be positioned in a CMOS under the array. The memory tile **1140** may include a row decoder **1160** and column decoder **1165** configured to address the memory cells of both of the semi-tiles **1145**, **1150**. In the memory tile **1140**, at least one of the row decoder **1160** or the column decoder **1165** or both may be positioned within under the array of memory cells and/or within a footprint **1170** of the array of memory cells. In such configurations, the at least one of the row decoder **1160** or the column decoder **1165** or both may be positioned in a CMOS under the array. In some cases, at least one of the row decoder **1160** or the column decoder **1165** or both may be positioned outside of the footprint **1170** of an array of memory cells.

[0141] The memory tiles **1105**, **1140** of the memory devices **1100** may include components not shown. In some cases, the memory tiles **1105**, **1140** may include one or more voltage sources and/or one or more switching components configured to selectively couple the one or more voltage sources to their respective access lines. For example, the memory tiles **1105**, **1140** may include some or all of the components described with reference to FIG. 9. In some cases where sense components are associated with entire semi-tiles, the memory tiles **1105**, **1140** may not include switching components configured to selective couple different sense components to a digit line.

[0142] FIG. 12 shows a flowchart illustrating a method **1200** for system and techniques for accessing multiple memory cells concurrently in accordance with embodiments of the present disclosure. The operations of method **1200** may be implemented by a memory controller **140** or its components as described herein. In some examples, a memory controller **140** may execute a set of codes to control the functional elements of the memory device to perform the functions described below. Additionally or alternatively, the memory controller **140** may perform portions of the functions described below using special-purpose hardware.

[0143] At block **1205**, the memory controller **140** may identify a first memory cell of a memory tile to read. The operations of **1205** may be performed according to the methods described herein.

[0144] At block **1210**, the memory controller **140** may identify a second memory cell of the memory tile to read. The operations of **1210** may be performed according to the methods described herein.

[0145] At block **1215**, the memory controller **140** may select a first polarity of a first read pulse to

read the first memory cell and a second polarity of a second read pulse to read the second memory cell. The operations of **1215** may be performed according to the methods described herein.

[0146] At block **1220**, the memory controller **140** may read the first memory cell using the first read pulse. The operations of **1220** may be performed according to the methods described herein.

[0147] At block **1225**, the memory controller **140** may read the second memory cell using the second read pulse concurrently with reading the first memory cell based at least in part on selecting the first polarity and the second polarity. The operations of **1225** may be performed according to the methods described herein.

[0148] An apparatus for performing the method **1200** is described. The apparatus may include means for identifying a first memory cell of a memory tile to read, means for identifying a second memory cell of the memory tile to read, means for selecting a first polarity of a first read pulse to read the first memory cell and a second polarity of a second read pulse to read the second memory cell, means for reading the first memory cell using the first read pulse, and means for reading the second memory cell using the second read pulse concurrently with reading the first memory cell based at least in part on selecting the first polarity and the second polarity.

[0149] In some examples of the method **1200** and apparatus described above, the first polarity of the first read pulse may be opposite the second polarity of the second read pulse. Some examples of the method **1200** and apparatus described above may further include processes, features, means, or instructions for applying voltages to access lines coupled with the first memory cell and the second memory cell concurrently based at least in part on selecting the first polarity and the second polarity, wherein reading the second memory cell concurrently with the first memory cell may be based at least in part on applying the voltages to the access lines.

[0150] Some examples of the method **1200** and apparatus described above may further include processes, features, means, or instructions for partitioning the first read pulse into a first voltage to apply to a first access line and a second voltage to apply to a second access line, the first access line and the second access line coupled with the first memory cell. Some examples of the method **1200** and apparatus described above may further include processes, features, means, or instructions for identifying a magnitude and a polarity of the first voltage based at least in part on the first polarity of the first read pulse. Some examples of the method **1200** and apparatus described above may further include processes, features, means, or instructions for identifying, based at least in part on the first polarity of the first read pulse and the first voltage, a magnitude of the second voltage different than the magnitude of the first voltage and a polarity of the second voltage different than the polarity of the first voltage, wherein applying the voltages may be based at least in part on the partitioning and the identifying.

[0151] Some examples of the method **1200** and apparatus described above may further include processes, features, means, or instructions for identifying a first logic state stored on the first memory cell and a second logic state stored on the second memory cell based at least in part reading the second memory cell concurrently with reading the first memory cell.

[0152] Some examples of the method **1200** and apparatus described above may further include processes, features, means, or instructions for coupling the first memory cell to a first type of sense component based at least in part on the first read pulse having the first polarity. Some examples of the method **1200** and apparatus described above may further include processes, features, means, or instructions for coupling the second memory cell to a second type of sense component different than the first type based at least in part on the second pulse having the second polarity.

[0153] In some examples of the method **1200** and apparatus described above, the first polarity and the second polarity may be selected such that a voltage difference caused by the first read pulse or the second read pulse at a third memory cell of the memory tile does not satisfy a programming threshold of the third memory cell.

[0154] Some examples of the method **1200** and apparatus described above may further include processes, features, means, or instructions for determining that the first memory cell and the second

memory cell may be coupled with a common access line, wherein the first polarity and the second polarity may be the same based at least in part on determining that the first memory cell and the second memory cell may be coupled with the common access line.

[0155] FIG. **13** shows a flowchart illustrating a method **1300** for system and techniques for accessing multiple memory cells concurrently in accordance with embodiments of the present disclosure. The operations of method **1300** may be implemented by a memory controller **140** or its components as described herein. In some examples, a memory controller **140** may execute a set of codes to control the functional elements of the memory device to perform the functions described below. Additionally or alternatively, the memory controller **140** may perform portions of the functions described below using special-purpose hardware.

[0156] At block **1305**, the memory controller **140** may identify a first memory cell of a memory tile to read. The operations of **1305** may be performed according to the methods described herein.

[0157] At block **1310**, the memory controller **140** may identify a second memory cell of the memory tile to read. The operations of **1310** may be performed according to the methods described herein.

[0158] At block **1315**, the memory controller **140** may select a first polarity of a first read pulse to read the first memory cell and a second polarity of a second read pulse to read the second memory cell. The operations of **1315** may be performed according to the methods described herein.

[0159] At block **1320**, the memory controller **140** may apply voltages to access lines coupled with the first memory cell and the second memory cell concurrently based at least in part on selecting the first polarity and the second polarity. The operations of **1320** may be performed according to the methods described herein.

[0160] At block **1325**, the memory controller **140** may read the first memory cell using the first read pulse. The operations of **1325** may be performed according to the methods described herein.

[0161] At **1330** the memory controller **140** may read the second memory cell using the second read pulse concurrently with reading the first memory cell based at least in part on selecting the first polarity and the second polarity and applying the voltages the access lines. The operations of **1330** may be performed according to the methods described herein.

[0162] FIG. **14** shows a flowchart illustrating a method **1400** for system and techniques for accessing multiple memory cells concurrently in accordance with embodiments of the present disclosure. The operations of method **1400** may be implemented by a memory controller **140** or its components as described herein. In some examples, a memory controller **140** may execute a set of codes to control the functional elements of the memory device to perform the functions described below. Additionally or alternatively, the memory controller **140** may perform portions of the functions described below using special-purpose hardware.

[0163] At block **1405**, the memory controller **140** may identify a first memory cell of a memory tile to program using a write operation. The operations of **1405** may be performed according to the methods described herein.

[0164] At block **1410**, the memory controller **140** may identify a second memory cell of the memory tile to access using a write operation or a read operation. The operations of **1410** may be performed according to the methods described herein.

[0165] At block **1415**, the memory controller **140** may determine that accessing the second memory cell concurrently with programming the first memory cell is permitted on the memory tile during an access operation duration. The operations of **1415** may be performed according to the methods described herein.

[0166] At block **1420**, the memory controller **140** may program the first memory cell of the memory tile during the access operation duration. The operations of **1420** may be performed according to the methods described herein.

[0167] At block **1425**, the memory controller **140** may access the second memory cell of the memory tile concurrently with programming the first memory cell during the access operation



duration based at least in part on determining that accessing the second memory cell concurrently with programming the first memory cell is permitted. The operations of **1425** may be performed according to the methods described herein.

[0168] An apparatus for performing the method **1400** is described. The apparatus may include means for identifying a first memory cell of a memory tile to program using a write operation, means for identifying a second memory cell of the memory tile to access using a write operation or a read operation, means for determining that accessing the second memory cell concurrently with programming the first memory cell is permitted on the memory tile during an access operation duration, means for programming the first memory cell of the memory tile during the access operation duration, and means for accessing the second memory cell of the memory tile concurrently with programming the first memory cell during the access operation duration based at least in part on determining that accessing the second memory cell concurrently with programming the first memory cell is permitted.

[0169] In some examples of the method **1400** and apparatus described above, accessing the second memory cell concurrently with programming the first memory cell may further include processes, features, means, or instructions for programming the first memory cell using a first programming pulse during the access operation duration and programming the second memory cell using a second programming pulse during the access operation duration concurrently with programming the first memory cell.

[0170] Some examples of the method **1400** and apparatus described above may further include processes, features, means, or instructions for delaying an application of the first programming pulse or the second programming pulse during the access operation duration based at least in part on a voltage applied to an unselected memory cell exceeding a programming threshold on the memory tile during the access operation duration, wherein accessing the second memory cell concurrently with programming the first memory cell during the access operation duration may be based at least in part on delaying the first programming pulse.

[0171] Some examples of the method **1400** and apparatus described above may further include processes, features, means, or instructions for identifying a first bit transition of the first memory cell during the write operation and a second bit transition of the second memory cell during the write operation. Some examples of the method **1400** and apparatus described above may further include processes, features, means, or instructions for determining that a combination of the first bit transition and the second bit transition may be would result in a voltage applied to an unselected memory cell exceeding a programming threshold on the memory tile during the single access operation duration, wherein delaying the application of the first programming pulse or the second programming pulse may be based at least in part on determining that the combination of the first bit transition and the second bit transition would result in the voltage applied to the unselected memory cell exceeding the programming threshold.

[0172] Some examples of the method **1400** and apparatus described above may further include processes, features, means, or instructions for refraining from applying the first programming pulse or the second programming pulse during the single access operation duration based at least in part on a combination of the first programming pulse and the second programming pulse applying a voltage to an unselected memory cell that exceeds a programming threshold of the unselected memory cell.

[0173] Some examples of the method **1400** and apparatus described above may further include processes, features, means, or instructions for determining that the first memory cell may be coupled with different access lines than the second memory cell, wherein accessing the second memory cell concurrently with programming the first memory cell during the access operation duration may be based at least in part on determining that the first memory cell may be coupled with different access lines than the second memory cell.

[0174] In some examples of the method **1400** and apparatus described above, accessing the second

memory cell concurrently with programming the first memory cell may further include processes, features, means, or instructions for programming the first memory cell using a programming pulse during the access operation duration and reading the second memory cell using a read pulse during the access operation duration concurrently with programming the first memory cell.

[0175] Some examples of the method **1400** and apparatus described above may further include processes, features, means, or instructions for selecting a polarity of the read pulse applied to the second memory cell during the access operation duration based at least in part on a characteristic of the programming pulse applied to the first memory cell during the access operation duration.

[0176] In some examples of the method **1400** and apparatus described above, the characteristic of the programming pulse may be a polarity of the programming pulse, a location to which the programming pulse may be being applied, a bit transition associated with the programming pulse, or a combination thereof.

[0177] Some examples of the method **1400** and apparatus described above may further include processes, features, means, or instructions for inverting data read from the second memory cell based at least in part on the read pulse having a negative polarity. Some examples of the method **1400** and apparatus described above may further include processes, features, means, or instructions for outputting the inverted data.

[0178] Some examples of the method **1400** and apparatus described above may further include processes, features, means, or instructions for delaying an application of the programming pulse or the read pulse during the access operation duration based at least in part on a voltage applied to an unselected memory cell exceeding a programming threshold on the memory tile during the access operation duration, wherein accessing the second memory cell concurrently with programming the first memory cell during the access operation duration may be based at least in part on delaying the programming pulse or the read pulse.

[0179] Some examples of the method **1400** and apparatus described above may further include processes, features, means, or instructions for determining that a combination of the programming pulse and the read pulse would result in a voltage applied to an unselected memory cell exceeding a programming threshold on the memory tile during the access operation duration, wherein delaying the programming pulse or the read pulse may be based at least in part on determining that the combination of the programming pulse and the read pulse would result in the voltage applied to the unselected memory cell exceeding the programming threshold.

[0180] Some examples of the method **1400** and apparatus described above may further include processes, features, means, or instructions for refraining from applying the programming pulse or the read pulse during the access operation duration based at least in part on a combination of the programming pulse and the read pulse applying a voltage to an unselected memory cell that exceeds a programming threshold of the unselected memory cell.

[0181] Some examples of the method **1400** and apparatus described above may further include processes, features, means, or instructions for determining that accessing the second memory cell concurrently with programming the first memory cell may be permitted may be based at least in part on the identifying that the voltage does not satisfy the programming threshold.

[0182] Some examples of the method **1400** and apparatus described above may further include processes, features, means, or instructions for determining that accessing the second memory cell concurrently with programming the first memory cell may be permitted may be based at least in part on the identifying that the voltage does not satisfy the programming threshold.

[0183] Some examples of the method **1400** and apparatus described above may further include processes, features, means, or instructions for determining that accessing the second memory cell concurrently with programming the first memory cell may be permitted may be based at least in part on the comparing the combination with the set.

[0184] FIG. **15** shows a flowchart illustrating a method **1500** for system and techniques for accessing multiple memory cells concurrently in accordance with embodiments of the present

disclosure. The operations of method **1500** may be implemented by a memory controller **140** or its components as described herein. In some examples, a memory controller **140** may execute a set of codes to control the functional elements of the memory device to perform the functions described below. Additionally or alternatively, the memory controller **140** may perform portions of the functions described below using special-purpose hardware.

[0185] At block **1505**, the memory controller **140** may identify a first memory cell of a memory tile to program using a write operation. The operations of **1505** may be performed according to the methods described herein.

[0186] At block **1510**, the memory controller **140** may identify a second memory cell of the memory tile to access using a write operation or a read operation. The operations of **1510** may be performed according to the methods described herein.

[0187] At block **1515**, the memory controller **140** may determine that accessing the second memory cell concurrently with programming the first memory cell is permitted on the memory tile during an access operation duration. The operations of **1515** may be performed according to the methods described herein.

[0188] At block **1520**, the memory controller **140** may program the first memory cell of the memory tile using a first programming pulse during the access operation duration. The operations of **1520** may be performed according to the methods described herein.

[0189] At block **1525**, the memory controller **140** may program the second memory cell of the memory tile using a second programming pulse during the access operation duration concurrently with programming the first memory cell based at least in part on determining that accessing the second memory cell concurrently with programming the first memory cell is permitted. The operations of **1525** may be performed according to the methods described herein.

[0190] FIG. **16** shows a flowchart illustrating a method **1600** for system and techniques for accessing multiple memory cells concurrently in accordance with embodiments of the present disclosure. The operations of method **1600** may be implemented by a memory controller **140** or its components as described herein. In some examples, a memory controller **140** may execute a set of codes to control the functional elements of the memory device to perform the functions described below. Additionally or alternatively, the memory controller **140** may perform portions of the functions described below using special-purpose hardware.

[0191] At block **1605**, the memory controller **140** may identify a first memory cell of a memory tile to program using a write operation. The operations of **1605** may be performed according to the methods described herein.

[0192] At block **1610**, the memory controller **140** may identify a second memory cell of the memory tile to access using a write operation or a read operation. The operations of **1610** may be performed according to the methods described herein.

[0193] At block **1615**, the memory controller **140** may determine that accessing the second memory cell concurrently with programming the first memory cell is permitted on the memory tile during an access operation duration. The operations of **1615** may be performed according to the methods described herein.

[0194] At block **1620**, the memory controller **140** may program the first memory cell of the memory tile using a programming pulse during the access operation duration. The operations of **1620** may be performed according to the methods described herein.

[0195] At block **1625**, the memory controller **140** may select a polarity of the read pulse applied to the second memory cell during the access operation duration based at least in part on a characteristic of the programming pulse applied to the first memory cell during the access operation duration. The operations of **1625** may be performed according to the methods described herein.

[0196] At block **1630**, the memory controller **140** may read the second memory cell of the memory tile using a read pulse during the access operation duration concurrently with programming the first memory cell based at least in part on determining that accessing the second memory cell

concurrently with programming the first memory cell is permitted. The operations of **1630** may be performed according to the methods described herein.

[0197] FIG. **17** shows a flowchart illustrating a method **1700** for system and techniques for accessing multiple memory cells concurrently in accordance with embodiments of the present disclosure. The operations of method **1700** may be implemented by a memory controller **140** or its components as described herein. In some examples, a memory controller **140** may execute a set of codes to control the functional elements of the memory device to perform the functions described below. Additionally or alternatively, the memory controller **140** may perform portions of the functions described below using special-purpose hardware.

[0198] At block **1705**, the memory controller **140** may identify a first memory cell of a first section of a memory tile to be read, wherein memory cells in the first section of the memory tile are configured to be read in response to application of a first read pulse having a first polarity. The operations of **1705** may be performed according to the methods described herein.

[0199] At block **1710**, the memory controller **140** may identify a second memory cell of a second section of the memory tile to read, wherein memory cells in the second section of the memory tile are configured to be read in response to application of a second read pulse having a second polarity different than the first polarity. The operations of **1710** may be performed according to the methods described herein.

[0200] At block **1715**, the memory controller **140** may read the first memory cell. The operations of **1715** may be performed according to the methods described herein.

[0201] At block **1720**, the memory controller **140** may read the second memory cell concurrently with reading the first memory cell based at least in part on identifying the first memory cell of the first section and the second memory cell of the second section. The operations of **1720** may be performed according to the methods described herein.

[0202] An apparatus for performing the method **1700** is described. The apparatus may include means for identifying a first memory cell of a first section of a memory tile to be read, wherein memory cells in the first section of the memory tile are configured to be read in response to application of a first read pulse having a first polarity, means for identifying a second memory cell of a second section of the memory tile to read, wherein memory cells in the second section of the memory tile are configured to be read in response to application of a second read pulse having a second polarity different than the first polarity, means for reading the first memory cell, and means for reading the second memory cell concurrently with reading the first memory cell based at least in part on identifying the first memory cell of the first section and the second memory cell of the second section.

[0203] Some examples of the method **1700** and apparatus described above may further include processes, features, means, or instructions for determining that the first memory cell may be coupled with different access lines than the second memory cell, wherein reading the second memory cell concurrently with reading the first memory cell may be based at least in part on determining that the first memory cell may be coupled with different access lines than the second memory cell.

[0204] Some examples of the method **1700** and apparatus described above may further include processes, features, means, or instructions for applying a first voltage having the first polarity to a first digit line coupled with the first memory cell based at least in part on the first read pulse having the first polarity. Some examples of the method **1700** and apparatus described above may further include processes, features, means, or instructions for applying a second voltage having the second polarity to a second digit line coupled with the second memory cell based at least in part on the second read pulse having the second polarity.

[0205] Some examples of the method **1700** and apparatus described above may further include processes, features, means, or instructions for applying a first voltage having the second polarity to a first digit line coupled with the first memory cell based at least in part on the first read pulse

having the first polarity. Some examples of the method **1700** and apparatus described above may further include processes, features, means, or instructions for applying a second voltage having the first polarity to a second digit line coupled with the second memory cell based at least in part on the second read pulse having the second polarity.

[0206] In some examples of the method **1700** and apparatus described above, the first polarity may be opposite the second polarity such that the first section of memory cells may be configured to be read with a positive polarity read pulse and the second section of memory cells may be configured to read with a negative polarity read pulse.

[0207] An electronic memory apparatus is described. The apparatus may include a memory cell, a digit line coupled with the memory cell, a first sense component coupled with the digit line, the first sense component configured to identify a logic state stored on the memory cell based at least in part on a first read pulse having a first polarity and a second sense component coupled with the digit line, the second sense component configured to identify the logic state stored on the memory cell based at least in part on a second read pulse having a second polarity different than the first polarity.

[0208] In some examples, the apparatus may include a first voltage source coupled with the digit line, the first voltage source configured to supply at least a part of the first read pulse having the first polarity and a second voltage source coupled with the digit line, the second voltage source configured to supply at least a part of the second read pulse having the second polarity. In some examples, the apparatus may include a switching component configured to selectively couple the digit line with the first voltage source or the second voltage source during an access operation.

[0209] In some examples, the apparatus may include a switching component configured to selectively output a signal from the first sense component or the second sense component based at least in part on a type of read pulse applied to the memory cell during a read operation. In some examples, the memory cell comprises a chalcogenide material configured to use a non-uniform distribution of ions to indicate the logic state. In some examples, the memory cell is a self-selecting memory cell.

[0210] An electronic memory apparatus is described. In some examples, the apparatus may include a memory tile having a first section of memory cells and a second section of memory cells, wherein the memory cells of the first section are configured to be read in response to application of a first read pulse having a first polarity and the memory cells of the second section are configured to be read in response to application of a second read pulse having a second polarity different than the first polarity, a first sense component coupled with the first section of memory cells of the memory tile and configured to identify a logic state of one memory cell of the first section of memory cells based at least in part on the first read pulse having the first polarity, and a second sense component coupled with the second section of memory cells of the memory tile and configured to identify the logic state of one memory cell of the second section of memory cells based at least in part on the second read pulse having the second polarity.

[0211] In some examples, the apparatus may include a first voltage source coupled with digit lines of the first section, the first voltage source configured to supply at least a portion of the first read pulse having the first polarity and a second voltage source coupled with digit lines of the second section, the second voltage source configured to supply at least a portion of the second read pulse having the second polarity. In some examples, a memory cell of the memory tile is formed of a chalcogenide material configured to use a non-uniform distribution of ions to indicate the logic state.

[0212] In some examples, one or more trim parameters for the first section of memory cells are independent from one or more trim parameters for the second section of memory cells. In some examples, the first sense component and the second sense component are positioned under a footprint of the memory tile. In some examples, the memory tile includes more than one deck of memory cells.

[0213] It should be noted that the methods described above describe possible implementations, and that the operations and the steps may be rearranged or otherwise modified and that other implementations are possible. Furthermore, embodiments from two or more of the methods may be combined.

[0214] Information and signals described herein may be represented using any of a variety of different technologies and techniques. For example, data, instructions, commands, information, signals, bits, symbols, and chips that may be referenced throughout the above description may be represented by voltages, currents, electromagnetic waves, magnetic fields or particles, optical fields or particles, or any combination thereof. Some drawings may illustrate signals as a single signal; however, it will be understood by a person of ordinary skill in the art that the signal may represent a bus of signals, where the bus may have a variety of bit widths.

[0215] The term “electronic communication” and “coupled” refers to a relationship between components that supports electron flow between the components. This may include a direct connection between components or may include intermediate components. Components in electronic communication or coupled to one another may be actively exchanging electrons or signals (e.g., in an energized circuit) or may not be actively exchanging electrons or signals (e.g., in a de-energized circuit) but may be configured and operable to exchange electrons or signals upon a circuit being energized. By way of example, two components physically connected via a switch (e.g., a transistor) are in electronic communication or may be coupled regardless of the state of the switch (i.e., open or closed).

[0216] The term “isolated” refers to a relationship between components in which electrons are not presently capable of flowing between them; components are isolated from each other if there is an open circuit between them. For example, two components physically connected by a switch may be isolated from each other when the switch is open.

[0217] As used herein, the term “shorting” refers to a relationship between components in which a conductive path is established between the components via the activation of a single intermediary component between the two components in question. For example, a first component shorted to a second component may exchange electrons with the second component when a switch between the two components is closed. Thus, shorting may be a dynamic operation that enables the flow of charge between components (or lines) that are in electronic communication.

[0218] The devices discussed herein, including memory tile **100**, may be formed on a semiconductor substrate, such as silicon, germanium, silicon-germanium alloy, gallium arsenide, gallium nitride, etc. In some cases, the substrate is a semiconductor wafer. In other cases, the substrate may be a silicon-on-insulator (SOI) substrate, such as silicon-on-glass (SOG) or silicon-on-sapphire (SOP), or epitaxial layers of semiconductor materials on another substrate. The conductivity of the substrate, or sub-regions of the substrate, may be controlled through doping using various chemical species including, but not limited to, phosphorous, boron, or arsenic. Doping may be performed during the initial formation or growth of the substrate, by ion-implantation, or by any other doping means.

[0219] Chalcogenide materials may be materials or alloys that include at least one of the elements sulfur(S), selenium (Se), and tellurium (Te). Phase change materials discussed herein may be chalcogenide materials. Chalcogenide materials and alloys may include, but not limited to, Ge—Te, In—Se, Sb—Te, Ga—Sb, In—Sb, As—Te, Al—Te, Ge—Sb—Te, Te—Ge—As, In—Sb—Te, Te—Sn—Se, Ge—Se—Ga, Bi—Se—Sb, Ga—Se—Te, Sn—Sb—Te, In—Sb—Ge, Te—Ge—Sb—S, Te—Ge—Sn—O, Te—Ge—Sn—Au, Pd—Te—Ge—Sn, In—Se—Ti—Co, Ge—Sb—Te—Pd, Ge—Sb—Te—Co, Sb—Te—Bi—Se, Ag—In—Sb—Te, Ge—Sb—Se—Te, Ge—Sn—Sb—Te, Ge—Te—Sn—Ni, Ge—Te—Sn—Pd, or Ge—Te—Sn—Pt. The hyphenated chemical composition notation, as used herein, indicates the elements included in a particular compound or alloy and is intended to represent all stoichiometries involving the indicated elements. For example, Ge—Te may include Ge.sub.xTe.sub.y, where x and y may be any positive integer. Other examples of

variable resistance materials may include binary metal oxide materials or mixed valence oxide including two or more metals, e.g., transition metals, alkaline earth metals, and/or rare earth metals. Embodiments are not limited to a particular variable resistance material or materials associated with the memory elements of the memory cells. For example, other examples of variable resistance materials can be used to form memory elements and may include chalcogenide materials, colossal magnetoresistive materials, or polymer-based materials, among others.

[0220] A transistor or transistors discussed herein may represent a field-effect transistor (FET) and comprise a three terminal device including a source, drain, and gate. The terminals may be connected to other electronic elements through conductive materials, e.g., metals. The source and drain may be conductive and may comprise a heavily-doped, e.g., degenerate, semiconductor region. The source and drain may be separated by a lightly-doped semiconductor region or channel. If the channel is n-type (i.e., majority carriers are electrons), then the FET may be referred to as a n-type FET. If the channel is p-type (i.e., majority carriers are holes), then the FET may be referred to as a p-type FET. The channel may be capped by an insulating gate oxide. The channel conductivity may be controlled by applying a voltage to the gate. For example, applying a positive voltage or negative voltage to an n-type FET or a p-type FET, respectively, may result in the channel becoming conductive. A transistor may be “on” or “activated” when a voltage greater than or equal to the transistor's threshold voltage is applied to the transistor gate. The transistor may be “off” or “deactivated” when a voltage less than the transistor's threshold voltage is applied to the transistor gate.

[0221] The description set forth herein, in connection with the appended drawings, describes example configurations and does not represent all the examples that may be implemented or that are within the scope of the claims. The term “exemplary” used herein means “serving as an example, instance, or illustration,” and not “preferred” or “advantageous over other examples.” The detailed description includes specific details for the purpose of providing an understanding of the described techniques. These techniques, however, may be practiced without these specific details. In some instances, well-known structures and devices are shown in block diagram form in order to avoid obscuring the concepts of the described examples.

[0222] In the appended figures, similar components or features may have the same reference label. Further, various components of the same type may be distinguished by following the reference label by a dash and a second label that distinguishes among the similar components. If just the first reference label is used in the specification, the description is applicable to any one of the similar components having the same first reference label irrespective of the second reference label.

[0223] Information and signals described herein may be represented using any of a variety of different technologies and techniques. For example, data, instructions, commands, information, signals, bits, symbols, and chips that may be referenced throughout the above description may be represented by voltages, currents, electromagnetic waves, magnetic fields or particles, optical fields or particles, or any combination thereof.

[0224] The various illustrative blocks and modules described in connection with the disclosure herein may be implemented or performed with a general-purpose processor, a digit signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA), or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general-purpose processor may be a microprocessor, but in the alternative, the processor may be any conventional processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of computing devices (e.g., a combination of a DSP and a microprocessor, multiple microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration).

[0225] The functions described herein may be implemented in hardware, software executed by a processor, firmware, or any combination thereof. If implemented in software executed by a

processor, the functions may be stored on or transmitted over as one or more instructions or code on a computer-readable medium. Other examples and implementations are within the scope of the disclosure and appended claims. For example, due to the nature of software, functions described above can be implemented using software executed by a processor, hardware, firmware, hardwiring, or combinations of any of these. Features implementing functions may also be physically located at various positions, including being distributed such that portions of functions are implemented at different physical locations. Also, as used herein, including in the claims, “or” as used in a list of items (for example, a list of items prefaced by a phrase such as “at least one of” or “one or more of”) indicates an inclusive list such that, for example, a list of at least one of A, B, or C means A or B or C or AB or AC or BC or ABC (i.e., A and B and C). Also, as used herein, the phrase “based on” shall not be construed as a reference to a closed set of conditions. For example, an exemplary step that is described as “based on condition A” may be based on both a condition A and a condition B without departing from the scope of the present disclosure. In other words, as used herein, the phrase “based on” shall be construed in the same manner as the phrase “based at least in part on.”

[0226] Computer-readable media includes both non-transitory computer storage media and communication media including any medium that facilitates transfer of a computer program from one place to another. A non-transitory storage medium may be any available medium that can be accessed by a general purpose or special purpose computer. By way of example, and not limitation, non-transitory computer-readable media can comprise RAM, ROM, electrically erasable programmable read only memory (EEPROM), compact disk (CD) ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other non-transitory medium that can be used to carry or store desired program code means in the form of instructions or data structures and that can be accessed by a general-purpose or special-purpose computer, or a general-purpose or special-purpose processor. Also, any connection is properly termed a computer-readable medium. For example, if the software is transmitted from a website, server, or other remote source using a coaxial cable, fiber optic cable, twisted pair, digital subscriber line (DSL), or wireless technologies such as infrared, radio, and microwave, then the coaxial cable, fiber optic cable, twisted pair, digital subscriber line (DSL), or wireless technologies such as infrared, radio, and microwave are included in the definition of medium. Disk and disc, as used herein, include CD, laser disc, optical disc, digital versatile disc (DVD), floppy disk and Blu-ray disc where disks usually reproduce data magnetically, while discs reproduce data optically with lasers. Combinations of the above are also included within the scope of computer-readable media.

[0227] The description herein is provided to enable a person skilled in the art to make or use the disclosure. Various modifications to the disclosure will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other variations without departing from the scope of the disclosure. Thus, the disclosure is not limited to the examples and designs described herein, but is to be accorded the broadest scope consistent with the principles and novel features disclosed herein.

## Claims

1. (canceled)
2. A method, comprising: selecting a first polarity of a first pulse to read a first memory cell of a memory tile and a second polarity of a second pulse to read a second memory cell of the memory tile; accessing the first memory cell using the first pulse; and accessing the second memory cell using the second pulse concurrently with accessing the first memory cell based at least in part on selecting the first polarity and the second polarity.
3. The method of claim 2, wherein the first polarity of the first pulse is different than the second polarity of the second pulse.



4. The method of claim 2, further comprising: applying respective voltages to access lines coupled with the first memory cell and the second memory cell concurrently based at least in part on selecting the first polarity and the second polarity.
5. The method of claim 4, further comprising: partitioning the first pulse into a first voltage to apply to a first access line and a second voltage to apply to a second access line; and identifying a respective magnitude and a respective polarity of the first voltage and the second voltage based at least in part on the first polarity of the first pulse, wherein applying the respective voltages is based at least in part on partitioning the first pulse into the first voltage and the second voltage and identifying the respective magnitude and the respective polarity of the first voltage and the second voltage.
6. The method of claim 2, further comprising: identifying a first logic state stored on the first memory cell and a second logic state stored on the second memory cell based at least in part on accessing the second memory cell concurrently with accessing the first memory cell.
7. The method of claim 6, wherein the first memory cell and the second memory cell comprise a chalcogenide material to indicate the first logic state and the second logic state.
8. The method of claim 2, further comprising: coupling the first memory cell to a first type of sense component based at least in part on the first pulse having the first polarity; and coupling the second memory cell to a second type of sense component different than the first type based at least in part on the second pulse having the second polarity.
9. The method of claim 2, wherein the first polarity and the second polarity are selected such that a voltage difference caused by the first pulse or the second pulse at a third memory cell of the memory tile does not satisfy a programming threshold of the third memory cell.
10. The method of claim 2, further comprising: determining that the first memory cell and the second memory cell are coupled with a common access line, wherein the first polarity and the second polarity are a same polarity based at least in part on determining that the first memory cell and the second memory cell are coupled with the common access line.
11. An electronic memory apparatus, comprising: a first sense component coupled with a digit line, the first sense component configured to identify a logic state stored on a memory cell coupled with the digit line based at least in part on a first pulse having a first polarity; and a second sense component coupled with the digit line, the second sense component configured to identify the logic state stored on the memory cell based at least in part on a second pulse having a second polarity different than the first polarity.
12. The electronic memory apparatus of claim 11, further comprising: a first voltage source coupled with the digit line, the first voltage source configured to supply at least a part of the first pulse having the first polarity; and a second voltage source coupled with the digit line, the second voltage source configured to supply at least a part of the second pulse having the second polarity.
13. The electronic memory apparatus of claim 12, further comprising: a switching component configured to selectively couple the digit line with the first voltage source or the second voltage source during an access operation.
14. The electronic memory apparatus of claim 11, further comprising: a switching component configured to selectively output a signal from the first sense component or the second sense component based at least in part on a type of pulse applied to the memory cell during an access operation.
15. The electronic memory apparatus of claim 11, wherein the memory cell comprises a chalcogenide material configured to use a non-uniform distribution of ions to indicate the logic state.
16. The electronic memory apparatus of claim 11, wherein the memory cell is a self-selecting memory cell.
17. The electronic memory apparatus of claim 11, wherein the first polarity of the first pulse is opposite the second polarity of the second pulse.

**18.** A memory system, comprising: one or more memory devices; and one or more controllers coupled with the one or more memory devices and configured to cause the memory system to: select a first polarity of a first pulse to read a first memory cell of a memory tile and a second polarity of a second pulse to read a second memory cell of the memory tile; access the first memory cell using the first pulse; and access the second memory cell using the second pulse concurrently with accessing the first memory cell based at least in part on selecting the first polarity and the second polarity.

**19.** The memory system of claim 18, wherein the first polarity of the first pulse is different than the second polarity of the second pulse.

**20.** The memory system of claim 18, wherein the one or more controllers are configured to cause the memory system to: apply respective voltages to access lines coupled with the first memory cell and the second memory cell concurrently based at least in part on selecting the first polarity and the second polarity.

**21.** The memory system of claim 20, wherein the one or more controllers are configured to cause the memory system to: partition the first pulse into a first voltage to apply to a first access line and a second voltage to apply to a second access line; and identify a respective magnitude and a respective polarity of the first voltage and the second voltage based at least in part on the first polarity of the first pulse, wherein applying the respective voltages is based at least in part on partitioning the first pulse into the first voltage and the second voltage and identifying the respective magnitude and the respective polarity of the first voltage and the second voltage.

---