

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250265188

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

SUGAHARA; Akio et al.

---

### MEMORY SYSTEM WHICH ORDERS DATA FETCHING FROM A LATCH CIRCUIT DURING EXECUTION OF A READ OPERATION

---

#### Abstract

A semiconductor memory device includes a first plane, a first input/output circuit, and a sequencer. The first plane includes a first memory cell array having a plurality of first memory cell transistors, and a first latch circuit configured to store first read data read from the first memory cell array. The first input/output circuit includes a first FIFO circuit configured to fetch the first read data from the first latch circuit. The sequencer is configured to control the first plane and the first input/output circuit based on a command transmitted from an external controller. The sequencer is configured to execute a prefetch operation for fetching the first read data from the first latch circuit into the first FIFO circuit within a period in which a read operation is executed in the first plane.

---

**Inventors:** SUGAHARA; Akio (Yokohama Kanagawa, JP), FUJIU; Masaki (Yokohama Kanagawa, JP)

**Applicant:** Kioxia Corporation (Tokyo, JP)

**Family ID:** 1000008576731

**Assignee:** Kioxia Corporation (Tokyo, JP)

**Appl. No.:** 19/196008

**Filed:** May 01, 2025

#### Related U.S. Application Data

parent US continuation 18267975 20230616 parent-grant-document US 12321262 WO  
continuation PCT/JP2020/049130 20201228 child US 19196008

---

#### Publication Classification

**Int. Cl.:** G06F12/02 (20060101)

## Background/Summary

CROSS REFERENCE [0001] This is a Continuation Application of U.S. application Ser. No. 18/267,975, filed Jun. 16, 2023, which is a U. S. national phase application under 35 USC 371 of International Application PCT/JP2020/049130 (not published in English), filed Dec. 28, 2020, the entire contents of all of which are incorporated herein by reference.

### FIELD

[0002] Embodiments relate to a memory system and a semiconductor memory device included in the memory system.

### BACKGROUND

[0003] A memory system including a NAND flash memory is known as a semiconductor memory device.

### CITATION LIST

#### Patent Literature

[0004] US Patent Application Publication No. 2019/0080763

### SUMMARY

#### Technical Problem

[0005] A memory system capable of enhancing the operation speed is provided.

#### Solution to Problem

[0006] A memory system according to an embodiment includes: a first chip including a first plane and a first input/output circuit; and a controller which is capable of issuing a command for controlling the first chip. The first plane includes: a first memory cell array having a plurality of first memory cell transistors; and a first latch circuit which is capable of storing first read data read from the first memory cell array. The first input/output circuit includes a first FIFO circuit which is capable of fetching the first read data from the first latch circuit. The controller is capable of transmitting to the first chip a first command for ordering fetching of the first read data from the first latch circuit to the first FIFO circuit during a period in which a read operation is executed on the first plane.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0007] FIG. 1 is a block diagram of a memory system according to a first embodiment.

[0008] FIG. 2 is a block diagram of a semiconductor memory device included in the memory system according to the first embodiment.

[0009] FIG. 3 is a block diagram of a NAND chip in the semiconductor memory device included in the memory system according to the first embodiment.

[0010] FIG. 4 is a block diagram showing a configuration of the NAND chip included in the memory system according to the first embodiment, focusing on a plane.

[0011] FIG. 5 is a circuit diagram of a memory cell array in the plane included in the memory system according to the first embodiment.

[0012] FIG. 6 is a block diagram showing a configuration of the NAND chip included in the memory system according to the first embodiment, focusing on an input/output circuit and a register.

[0013] FIG. 7 is a block diagram showing an example of a First In First Out (FIFO) circuit in the input/output circuit included in the memory system according to the first embodiment.

[0014] FIG. 8 is a diagram showing an example of a command sequence in a read operation of the memory system according to the first embodiment.

[0015] FIG. 9 is a diagram showing an example of the command sequence in the read operation of the memory system according to the first embodiment.

[0016] FIG. 10 is a diagram showing an example of the command sequence in the read operation of the memory system according to the first embodiment.

[0017] FIG. 11 is a diagram showing an example of the command sequence in the read operation of the memory system according to the first embodiment.

[0018] FIG. 12 is a diagram showing an example of the command sequence in the read operation of the memory system according to the first embodiment.

[0019] FIG. 13 is a diagram showing an example of the command sequence in the read operation of the memory system according to the first embodiment.

[0020] FIG. 14 is a diagram showing an example of the command sequence in the read operation of the memory system according to the first embodiment.

[0021] FIG. 15 is a diagram showing an example of the command sequence in the read operation of the memory system according to the first embodiment.

[0022] FIG. 16 is a diagram showing an example of the command sequence in the read operation of the memory system according to the first embodiment.

[0023] FIG. 17 is a diagram showing an example of the command sequence in the read operation of the memory system according to the first embodiment.

[0024] FIG. 18 is a block diagram showing a configuration of a NAND chip included in a memory system according to a second embodiment, focusing on an input/output circuit and a register.

[0025] FIG. 19 is a diagram showing an example of a command sequence in a read operation of the memory system according to the second embodiment.

[0026] FIG. 20 is a diagram showing an example of the command sequence in the read operation of the memory system according to the second embodiment.

[0027] FIG. 21 is a diagram showing an example of the command sequence in the read operation of the memory system according to the second embodiment.

[0028] FIG. 22 is a diagram showing an example of the command sequence in the read operation of the memory system according to the second embodiment.

[0029] FIG. 23 is a diagram showing an example of the command sequence in the read operation of the memory system according to the second embodiment.

[0030] FIG. 24 is a block diagram showing a configuration of a NAND chip included in a memory system according to a third embodiment, focusing on an input/output circuit and a register.

[0031] FIG. 25 is a diagram illustrating an overview of a data flow in a read operation of the memory system according to the third embodiment.

[0032] FIG. 26 is a diagram showing an example of a command sequence in the read operation of the memory system according to the third embodiment.

[0033] FIG. 27 is a diagram showing an example of the command sequence in the read operation of the memory system according to the third embodiment.

[0034] FIG. 28 is a diagram showing an example of the command sequence in the read operation of the memory system according to the third embodiment.

[0035] FIG. 29 is a diagram showing an example of the command sequence in the read operation of the memory system according to the third embodiment.

[0036] FIG. 30 is a block diagram showing a configuration of a NAND chip included in a memory system according to a fourth embodiment, focusing on an input/output circuit and a register.

[0037] FIG. 31 is a diagram showing an example of a command sequence in a read operation of the memory system according to the fourth embodiment.

[0038] FIG. **32** is a diagram showing an example of the command sequence in the read operation of the memory system according to the fourth embodiment.

[0039] FIG. **33** is a diagram showing an example of the command sequence in the read operation of the memory system according to the fourth embodiment.

[0040] FIG. **34** is a diagram showing an example of the command sequence in the read operation of the memory system according to the fourth embodiment.

[0041] FIG. **35** is a diagram showing an example of the command sequence in the read operation of the memory system according to the fourth embodiment.

[0042] FIG. **36** is a diagram showing an example of a command sequence in a read operation of a memory system according to a fifth embodiment.

[0043] FIG. **37** is a diagram showing an example of the command sequence in the read operation of the memory system according to the fifth embodiment.

[0044] FIG. **38** is a diagram showing an example of the command sequence in the read operation of the memory system according to the fifth embodiment.

[0045] FIG. **39** is a diagram showing an operation of a NAND chip according to a comparative example.

[0046] FIG. **40** is a diagram showing an operation of the NAND chip included in the memory system according to the first embodiment.

## DETAILED DESCRIPTION

[0047] Hereinafter, embodiments will be described with reference to the drawings. In the description, common parts are assigned common reference signs throughout the drawings.

### 1. First Embodiment

[0048] A memory system according to the first embodiment will be described. In the following, a memory system including a NAND flash memory (hereinafter referred to as a “NAND chip”) as a semiconductor memory device will be described as an example.

#### 1.1 Configuration

##### 1.1.1 Overall Configuration of Memory System

[0049] An overall configuration of a memory system according to the present embodiment will be described with reference to FIG. **1**. FIG. **1** is a block diagram of the memory system according to the present embodiment.

[0050] A memory system **100** includes a semiconductor memory device **200** and a memory controller **300**. The memory system **100** is controlled by a host device (hereinafter, simply referred to as a “host”) **400**. The memory system **100** performs processing based on a request signal received from the host **400**. The memory system **100** is, for example, a solid state drive (SSD), a universal serial bus (USB) memory, a multi-media card (MMC), or an SD™ card. The host **400** is, for example, a digital camera or a personal computer.

[0051] For example, the semiconductor memory device **200** includes an I/F chip and a NAND chip, and stores data in a nonvolatile manner. A plurality of NAND chips may be provided inside the semiconductor memory device **200**. The I/F chip may be omitted. In such a case, the NAND chip functions as the semiconductor memory device. The semiconductor memory device **200** is controlled by the memory controller **300**. A plurality of semiconductor memory devices **200** may be provided inside the memory system **100**. In such a case, each of the semiconductor memory devices **200** is independently operable under the control of the memory controller **300**.

[0052] The memory controller **300** receives the request signal from the host **400** via a host bus. The type of the host bus and the request signal transmitted via the host bus depend on an application applied in the memory system **100**. In the case of the memory system **100** being the SSD, for example, an interface under the serial attached SCSI (SAS), serial ATA (SATA), programmable communications interface express (PCIe™), or universal flash storage (UFS) standard is used for the host bus. In the case of the memory system **100** being the USB memory, a USB is used for the host bus. In the case of the memory system **100** being the MMC, an interface under the eMMC

standard is used for the host bus. In the case of the memory system **100** being the SD™ card, an interface under the SDIM standard is used for the host bus.

[0053] The memory controller **300** controls the semiconductor memory device **200** based on the request signal received from the host **400**. For this, the memory controller **300** is coupled to the semiconductor memory device **200** via a NAND bus. The NAND bus performs signal transmission/reception in compliance with a NAND interface. Specific examples of such a signal include a chip enable signal CEn, a command latch enable signal CLE, an address latch enable signal ALE, a write enable signal WEn, read enable signals REn and RE, a write protect signal WPn, data strobe signals DOS and DQSn, an input/output signal DQ, and a ready/busy signal RBn.

[0054] The signal CEn is a signal for enabling the NAND chip inside the semiconductor memory device **200**, and is asserted at, for example, a Low (“L”) level. The term “assert” means that a signal (or logic) is in a valid (active) state. The signal CLE is a signal indicating that the signal DQ is a command, and is asserted at, for example, a High (“H”) level. The signal ALE is a signal indicating that the signal DQ is an address, and is asserted at, for example, the “H” level. The signal WEn is a signal for fetching a received signal to the semiconductor memory device **200**, and is asserted at, for example, the “L” level. Every time the signal WEn is toggled, the semiconductor memory device **200** fetches the signal DQ. The signals REn and RE are each a signal for the memory controller **300** to read data from the semiconductor memory device **200**. The signal REn is an inversion signal of the signal RE. Every time the signals REn and RE are toggled, the semiconductor memory device **200** outputs the signal DQ to the memory controller **300**. The signal WPn is a signal for prohibiting a write or erase with respect to the semiconductor memory device **200**, and is asserted at, for example, the “L” level. The signals CEn, CLE, ALE, WEn, REn, RE, and WPn are each transmitted from the memory controller **300** to the semiconductor memory device **200**.

[0055] The signals DQS and DQSn are used to control a timing of transmitting and receiving the signal DQ. The signal DQSn is an inversion signal of the signal DQS. For example, when data is written, the signals DQS and DQSn are transmitted together with the write data DO from the memory controller **300** to the semiconductor memory device **200**. The semiconductor memory device **200** receives the write data DQ in synchronization with the signals DQS and signal DQSn. When data is read, the signals DQS and DQSn are transmitted together with the read data DQ from the semiconductor memory device **200** to the memory controller **300**. The signals DQS and DQSn are generated based on the aforementioned signal REn. The memory controller **300** receives the read data DQ in synchronization with the signals DQS and DQSn.

[0056] The input/output signal DQ is, for example, an eight-bit signal (hereinafter, these eight signals DQ will be respectively referred to as signals DQ0 to DQ7 when they are distinguished from each other, and will be simply referred to as a signal DO when they are not distinguished from each other). The input/output signal DQ is an entity of data transmitted and received between the semiconductor memory device **200** and the memory controller **300**, and is, for example, a command CMD, an address ADD, write data or read data DAT, and status information STS.

[0057] The signal RBn is a signal indicating whether the NAND chip inside the semiconductor memory device **200** is in a busy state or in a ready state, and the signal RBn is set to the “L” level when the NAND chip is, for example, in the busy state. The NAND chip is capable of receiving a command from the memory controller **300** in the case of the signal RBn being in the ready state, and is incapable of receiving a command from the memory controller **300** in the case of the signal RBn being in the busy state. The signal RBn is transmitted from the semiconductor memory device **200** to the memory controller **300**.

[0058] The memory controller **300** includes a host interface circuit (host I/F) **310**, a memory interface circuit (memory I/F) **320**, a read only memory (ROM) **330**, a central processing unit (CPU) **340**, and a random access memory (RAM) **350**.

[0059] The host interface circuit **310** is coupled to the host **400** via the host bus, and controls

communications between the memory controller **300** and the host **400**.

[0060] The memory interface circuit **320** is coupled to the semiconductor memory device **200** via the NAND bus, and controls communications between the memory controller **300** and the semiconductor memory device **200**.

[0061] The ROM **330** stores firmware (programs) for the memory controller **300** to execute various operations and some of the functions of the host interface circuit **310** and the memory interface circuit **320**. Firmware is configured to allow the memory controller **300** to perform the operations described as each of embodiments.

[0062] The CPU **340** controls the operation of the entire memory controller **300**. When receiving, for example, the request signal relating to a read from the host **400**, the CPU **340** causes, based on the received request signal, the memory interface circuit **320** to issue a read command with respect to the semiconductor memory device **200**. The CPU **340** performs a similar operation when receiving the request signal relating to a write from the host **400**.

[0063] The RAM **350** is used as a work area of the CPU **340**. The RAM **350** is a semiconductor memory such as a DRAM, an SRAM, etc. The RAM **350** stores, for example, the aforementioned firmware. The aforementioned firmware is loaded by the memory controller **300** into the RAM **350**, for example, immediately after the memory system **100** is powered on.

#### 1.1.2 Configuration of Semiconductor Memory Device **200**

[0064] A configuration of the semiconductor memory device **200** will be described with reference to FIG. **2**. FIG. **2** is a block diagram of the semiconductor memory device **200** included in the memory system **100** according to the present embodiment.

[0065] The semiconductor memory device **200** includes an I/F chip **210**, a NAND chip **0** (CP0), and a NAND chip **1** (CP1). The I/F chip **210** is coupled to the memory controller **300** via the NAND bus and controls communications between the memory controller **300** and the NAND chips **0** and **1** (CP0 and CP1). The NAND chip **0** (CP0) and the NAND chip **1** (CP1) are each a NAND flash memory. Hereinafter, the “NAND chip **0**” and the “NAND chip **1**” may be simply referred to as a “chip **0**” and a “chip **1**”, respectively. The number of NAND chips provided inside the semiconductor memory device **200** is not limited to two, and may be one, or two or more. The NAND chip **0** (CP0) and the NAND chip **1** (CP1) are controlled by the memory controller **300**. The NAND chip **0** (CP0) and the NAND chip **1** (CP1) are coupled to a common data bus DB. The NAND chips are not necessarily coupled to the common data bus DB, and it suffices that the plurality of NAND chips are coupled to a single data bus DB.

[0066] The memory controller **300** may transmit a different signal CEn for each NAND chip, and may transmit a common signal CEn for the plurality of NAND chips. For example, in the case of transmitting the signal CEn, which is different for each NAND chip, the signal CEn includes signals CEn1 and CEn2 respectively corresponding to the NAND chip **0** (CP0) and the NAND chip **1** (CP1). In the case of transmitting the signal CEn, which is common for the plurality of NAND chips, the NAND chip is selected based on the signal CEn and an address that designates the NAND chip. The signal RBn includes signals RBn1 and RBn2 respectively corresponding to the NAND chip **0** (CP0) and the NAND chip **1** (CP1). The number of signals RBn is the same as the number of NAND chips provided inside the semiconductor memory device **200**.

[0067] The I/F chip **210** receives the signals CEn1, CEn2, CLE, ALE, WEn, REN, RE, WPn, DQS, DOSn, and DO from the memory controller **300**. The I/F chip **210** transmits the received signals CLE, ALE, WEn, REN, RE, WPn, DOS, DOSn, and DQ to the NAND chip **0** (CP0) and the NAND chip **1** (CP1) via the data bus DB. The I/F chip **210** transmits the received signal CEn1 to the NAND chip **0** (CP0). The I/F chip **210** transmits the received signal CEn2 to the NAND chip **1** (CP1).

[0068] The I/F chip **210** receives the signals DQS, DOSn, and DQ from the NAND chip **0** (CP0) and the NAND chip **1** (CP1). The I/F chip **210** transmits the received signals DQS, DQS<sub>n</sub>, and DQ to the memory controller **300**.

[0069] The NAND chip **0** (CP0) transmits the signal RBn1 to the memory controller **300**. The NAND chip **1** (CP1) transmits the signal RBn2 to the memory controller **300**.

[0070] Data is written into a selected one of the NAND chip **0** (CP0) and the NAND chip **1** (CP1). Data is read from a selected one of the NAND chip **0** (CP0) and the NAND chip **1** (CP1).

### 1.1.3 Configuration of NAND Chip **0** (CP0)

[0071] A configuration of the NAND chip **0** (CP0) will be described with reference to FIG. **3**. FIG. **3** is a block diagram of the NAND chip **0** (CP0) inside the semiconductor memory device **200** included in the memory system **100** according to the present embodiment. In FIG. **3**, some of the couplings between the blocks are indicated by arrows; however, the couplings between the blocks are not limited to those shown in FIG. **3**. The NAND chip **0** (CP0) will be described below; however, the NAND chip **1** (CP1) has the same configuration.

[0072] The NAND chip **0** (CP0) includes an input/output circuit **10**, a register **20**, a sequencer **30**, a voltage generating circuit **40**, and planes **0** to **3** (PL0 to PL3).

[0073] The input/output circuit **10** receives the signals CEn1, CLE, ALE, WEn, REn, RE, and WPn from the memory controller **300**. The input/output circuit **10** transmits and receives the signals DOS, DOSn, and DQ to and from the memory controller **300**. The input/output circuit **10** transmits the signal RBn1 to the memory controller **300**.

[0074] The register **20** includes a status register **21**, an address register **22**, and a command register **23**. The status register **21** temporarily stores, for example, the status information STS in a data write operation, a data read operation, and a data erase operation. The address register **22** temporarily stores the address ADD received from the memory controller **300** via the input/output circuit **10**. The address ADD includes a row address RA and a column address CA. The command register **23** temporarily stores the command CMD received from the memory controller **300** via the input/output circuit **10**.

[0075] The sequencer **30** controls the operation of the entire NAND chip **0** (CP0). The sequencer **30** receives the command CMD from the command register **23**. The sequencer **30** executes the write operation, the read operation, the erase operation, etc., by controlling the input/output circuit **10**, the status register **21**, the voltage generating circuit **40**, and the planes **0** to **3** (PL0 to PL3) based on the received command CMD.

[0076] The voltage generating circuit **40** receives a power supply voltage from an outside of the NAND chip **0** (CP0) and generates various voltages from the power supply voltage under control of the sequencer **30**. The voltage generating circuit **40** applies the generated voltages to the planes **0** to **3** (PL0 to PL3).

[0077] Each of the planes **0** to **3** (PL0 to PL3) is independently controlled by the sequencer **30**. Each of the planes **0** to **3** (PL0 to PL3) is a unit for writing data to a memory cell transistor described later and reading data from the memory cell transistor described later. When writing data, each of the planes **0** to **3** (PL0 to PL3) receives the write data DAT from the memory controller **300** via the input/output circuit **10**. When reading data, each of the planes **0** to **3** (PL0 to PL3) transmits the read data DAT to the memory controller **300** via the input/output circuit **10**.

[0078] A configuration of the plane **0** (PL0) will be described with reference to FIG. **4**. FIG. **4** is a block diagram showing a configuration of the NAND chip **0** (CP0) included in the memory system **100** according to the present embodiment, focusing on the plane **0** (PL0). The plane **0** (PL0) will be described below; however, the plane **1** (PL1), the plane **2** (PL2), and the plane **3** (PL3) have the same configuration. In FIG. **4**, the status register **21**, the command register **23**, and the planes **1** to **3** (PL1 to PL3) are omitted.

[0079] The plane **0** (PL0) includes a memory cell array **51A**, a row decoder **52A**, a sense amplifier **53A**, a data register **54A**, and a column decoder **55A**.

[0080] The memory cell array **51A** has a plurality of blocks BLK (BLK0 to BLKn where n is a natural number equal to or greater than 1) each including nonvolatile memory cell transistors associated with rows and columns. The number of blocks BLK in the memory cell array **51A** is

freely selected. The memory cell array **51A** will be described later in detail. A voltage is applied to the memory cell array **51A** from the voltage generating circuit **40**.

[0081] The row decoder **52A** is controlled by the sequencer **30**. The row decoder **52A** receives the row address RA from the address register **22**. The row decoder **52A** decodes the received row address RA and based on a result of decoding, applies a voltage supplied from the voltage generating circuit **40** to a selected memory cell transistor.

[0082] The sense amplifier **53A** is controlled by the sequencer **30**. A voltage is applied to the sense amplifier **53A** from the voltage generating circuit **40**. When reading data, the sense amplifier **53A** senses the data DAT read from the memory cell array **51A**. The sense amplifier **53A** transmits the read data DAT to the data register **54A**. When writing data, the sense amplifier **53A** transmits the write data DAT to the memory cell array **51A**.

[0083] The data register **54A** is controlled by the sequencer **30**. A voltage is applied to the data register **54A** from the voltage generating circuit **40**. The data register **54A** includes a plurality of non-illustrated latch circuits. The latch circuit stores the write data and the read data DAT. For example, when writing data, the data register **54A** temporarily stores the write data DAT received from the input/output circuit **10** and transmits it to the sense amplifier **53A**. Furthermore, when reading data, the data register **54A** temporarily stores the read data DAT received from the sense amplifier **53A** and transmits it to the input/output circuit **10**.

[0084] The column decoder **55A** is controlled by the sequencer **30**. A voltage is applied to the column decoder **55A** from the voltage generating circuit **40**. The column decoder **55A** receives the column address CA from the address register **22**. For example, at the time of the write operation, the read operation, and the erase operation, the column decoder **55A** decodes the column address CA and selects the latch circuit inside the data register **54A** in accordance with a result of decoding.

#### 1.1.4 Circuit Configuration of Memory Cell Array **51A**

[0085] A circuit configuration of the memory cell array **51A** will be described with reference to FIG. 5. FIG. 5 is a circuit diagram of the memory cell array **51A** inside the plane **0** (PL**0**) included in the memory system **100** according to the present embodiment.

[0086] FIG. 5 shows, as an exemplary circuit configuration of the memory cell array **51A**, one of the blocks BLK extracted from the plurality of blocks BLK included in the memory cell array **51A**. All the other blocks BLK have the configuration shown in FIG. 5.

[0087] Each of the blocks BLK includes, for example, four string units SU**0** to SU**3**. The number of string units SU in each block BLK is freely selected. Each of the string units SU includes a plurality of NAND strings NS. The plurality of NAND strings NS are respectively associated with bit lines BL**0** to BLm (m is a natural number equal to or greater than 1). Each of the NAND strings NS includes, for example, memory cell transistors MC**0** to MC**7** and select transistors ST**1** and ST**2**. Each memory cell transistor MC includes a control gate and a charge storage layer, and stores data in a nonvolatile manner. Each of the select transistors ST**1** and ST**2** is used to select a string unit SU in respective operations.

[0088] In each of the NAND strings NS, the memory cell transistors MC**0** to MC**7** are coupled in series. In the same block BLK, control gates of the memory cell transistors MC**0** to MC**7** are respectively coupled in common to word lines WL**0** to WL**7**.

[0089] In each NAND string NS, a drain of a select transistor ST**1** is coupled to an associated bit line BL, while a source of the select transistor ST**1** is coupled to one end of the memory cell transistors MC**0** to MC**7** coupled in series. In the same block BLK, gates of the select transistors ST**1** respectively included in the string units SU**0** to SU**3** are respectively coupled in common to select gate lines SGD**0** to SGD**3**.

[0090] In each of the NAND strings NS, a drain of the select transistor ST**2** is coupled to the other end of the memory cell transistors MC**0** to MC**7** coupled in series. In the same block BLK, sources of the select transistors ST**2** are coupled to a source line SL, while gates of the select transistors ST**2** are coupled in common to a select gate line SGS.



[0091] In the circuit configuration of the memory cell array **51A** described in the above, a bit line BL is shared among corresponding NAND strings NS in each block BLK, for example. The source line SL is shared among, for example, the plurality of blocks BLK.

#### 1.1.5 Configuration of Input/Output Circuit **10**

[0092] A configuration of the input/output circuit **10** will be described with reference to FIG. **6**. FIG. **6** is a block diagram showing a configuration of the NAND chip **0** (CP**0**) included in the memory system **100** according to the present embodiment, focusing on the input/output circuit **10** and the register **20**. In FIG. **6**, the status register **21** and the voltage generating circuit **40** are omitted.

[0093] As with the plane **0** (PL**0**), the plane **1** (PL**1**) includes a memory cell array **51B**, a row decoder **52B**, a sense amplifier **53B**, a data register **54B**, and a column decoder **55B**. The plane **2** (PL**2**) includes a memory cell array **51C**, a row decoder **52C**, a sense amplifier **53C**, a data register **54C**, and a column decoder **55C**. The plane **3** (PL**3**) includes a memory cell array **51D**, a row decoder **52D**, a sense amplifier **53D**, a data register **54D**, and a column decoder **55D**. Hereinafter, the memory cell arrays **51A** to **51D** will be simply referred to as a memory cell array **51** in the case where they are not distinguished from each other, and the data registers **54A** to **54D** will be simply referred to as a data register **54** in the case where they are not distinguished from each other.

[0094] The input/output circuit **10** includes the DQ pad **11** and the FIFO circuit **12**. The DQ pad **11** couples the input/output circuit **10** to the NAND bus. The DQ pad **11** is coupled to the data registers **54A** to **54D** via the FIFO circuit **12**. The DQ pad **11** may be recognized as a single output terminal having a certain output impedance when viewed from an outside of the NAND chip **0** (CP**0**).

[0095] The FIFO circuit **12** fetches, based on a write clock Wclk described later, the data DAT read from the planes **0** to **3** (PL**0** to PL**3**). The FIFO circuit **12** further transmits a signal stored therein to the DQ pad **11** based on a read clock Rclk described later. The FIFO circuit **12** will be described later in detail.

#### 1.1.6 Configuration of Register **20**

[0096] A configuration of the register **20** will be described with reference to FIG. **6**.

[0097] The address register **22** includes a row address register **0** (RR**0**) to a row address register **3** (RR**3**), a row address register **0'** (RR**0'**) to a row address register **3'** (RR**3'**), a column address register **0** (CR**0**), and a column address register **0'** (CR**0'**).

[0098] The row address register **0** (RR**0**) is coupled to the input/output circuit **10** and the plane **0** (PL**0**), and stores the row address RA of the plane **0** (PL**0**) received from the input/output circuit **10**. The row address register **0** (RR**0**) transmits the row address RA to the row decoder **52A**. The row address register **1** (RR**1**) is coupled to the input/output circuit **10** and the plane **1** (PL**1**), and stores the row address RA of the plane **1** (PL**1**) received from the input/output circuit **10**. The row address register **1** (RR**1**) transmits the row address RA to the row decoder **52B**. The row address register **2** (RR**2**) is coupled to the input/output circuit **10** and the plane **2** (PL**2**), and stores the row address RA of the plane **2** (PL**2**) received from the input/output circuit **10**. The row address register **2** (RR**2**) transmits the row address RA to the row decoder **52C**. The row address register **3** (RR**3**) is coupled to the input/output circuit **10** and the plane **3** (PL**3**), and stores the row address RA of the plane **3** (PL**3**) received from the input/output circuit **10**. The row address register **3** (RR**3**) transmits the row address RA to the row decoder **52D**.

[0099] The row address register **0'** (RR**0'**) is coupled to the row address register **0** (RR**0**) and the plane **0** (PL**0**), and stores the row address RA received (copied) from the row address register **0** (RR**0**). The row address register **0'** (RR**0'**) transmits the row address RA to the row decoder **52A**. The row address register **1'** (RR**1'**) is coupled to the row address register **1** (RR**1**) and the plane **1** (PL**1**), and stores the row address RA received (copied) from the row address register **1** (RR**1**). The row address register **1'** (RR**1'**) transmits the row address RA to the row decoder **52B**. The row address register **2'** (RR**2'**) is coupled to the row address register **2** (RR**2**) and the plane **2** (PL**2**), and

stores the row address RA received (copied) from the row address register 2 (RR2). The row address register 2' (RR2') transmits the row address RA to the row decoder 52C. The row address register 3' (RR3') is coupled to the row address register 3 (RR3) and the plane 3 (PL3), and stores the row address RA received (copied) from the row address register 3 (RR3). The row address register 3' (RR3') transmits the row address RA to the row decoder 52D.

[0100] The column address register 0 (CR0) is coupled to the input/output circuit 10 and the planes 0 to 3 (PL0 to PL3), and stores the column address CA of the planes 0 to 3 (PL0 to PL3) received from the input/output circuit 10. The column address register 0' (CR0') is coupled to the column address register 0 (CR0) and the planes 0 to 3 (PL0 to PL3), and stores the column address CA received (copied) from the column address register 0 (CR0).

[0101] The column address register 0 (CR0) includes a column address counter circuit CC0, and the column address register 0' (CR0') includes a column address counter circuit CC0'. The column address counter circuits CC0 and CC0' increment the column address CA by one.

[0102] The column address register 0 (CR0) transmits the column addresses CA to the column decoders 55A to 55D. More specifically, the column address register 0 (CR0) transmits the first column address CA of a plane designated by the column address CA to the column decoders 55A to 55D. When the first column address CA is transmitted to the column decoders 55A to 55D, the column address counter circuit CC0 increments the column address CA by only one, and the column address register 0 (CR0) transmits a column address CA subsequent to the first column address CA to the column decoders 55A to 55D. When the last column address CA is transmitted to the column decoders 55A to 55D, transmission of the column addresses CA to the column decoders 55A to 55D is completed. As with the column address register 0 (CR0), the column address register 0' (CR0') transmits the column addresses CA to the column decoders 55A to 55D.

[0103] The command register 23 includes a command register 0 (MR0) to a command register 3 (MR3) and a command register 0' (MR0') to a command register 3' (MR3').

[0104] The command register 0 (MR0) is coupled to the input/output circuit 10 and the sequencer 30, and stores a command CMD relating to the plane 0 (PL0) received from the input/output circuit 10. The command register 0 (MR0) transmits the command CMD to the sequencer 30. The command register 1 (MR1) is coupled to the input/output circuit 10 and the sequencer 30, and stores the command CMD relating to the plane 1 (PL1) received from the input/output circuit 10. The command register 1 (MR1) transmits the command CMD to the sequencer 30. The command register 2 (MR2) is coupled to the input/output circuit 10 and the sequencer 30, and stores the command CMD relating to the plane 2 (PL2) received from the input/output circuit 10. The command register 2 (MR2) transmits the command CMD to the sequencer 30. The command register 3 (MR3) is coupled to the input/output circuit 10 and the sequencer 30, and stores the command CMD relating to the plane 3 (PL3) received from the input/output circuit 10. The command register 3 (MR3) transmits the command CMD to the sequencer 30.

[0105] The command register 0' (MR0') is coupled to the command register 0 (MR0) and the sequencer 30, and stores the command CMD received (copied) from the command register 0 (MR0). The command register 0' (MR0') transmits the command CMD to the sequencer 30. The command register 1' (MR1') is coupled to the command register 1 (MR1) and the sequencer 30, and stores the command CMD received (copied) from the command register 1 (MR1). The command register 1' (MR1') transmits the command CMD to the sequencer 30. The command register 2' (MR2') is coupled to the command register 2 (MR2) and the sequencer 30, and stores the command CMD received (copied) from the command register 2 (MR2). The command register 2' (MR2') transmits the command CMD to the sequencer 30. The command register 3' (MR3') is coupled to the command register 3 (MR3) and the sequencer 30, and stores the command CMD received (copied) from the command register 3 (MR3). The command register 3' (MR3') transmits the command CMD to the sequencer 30.

### 1.1.7 Configuration of FIFO Circuit 12

[0106] A configuration of the FIFO circuit **12** will be described with reference to FIG. 7. FIG. 7 is a block diagram showing an example of the FIFO circuit **12** inside the input/output circuit **10** included in the memory system **100** according to the present embodiment.

[0107] The FIFO circuit **12** includes a multiplexer (hereinafter referred to as a “MUX”) **60**, flip flops (hereinafter referred to as a “FF”) **61** to **63**, a MUX **64**, a write clock generating circuit **65**, a write pointer generating circuit **66**, a read clock generating circuit **67**, and a read pointer generating circuit **68**.

[0108] The MUX **60** selects one of the FFs **61** to **63** based on a write pointer Wptr received from the write pointer generating circuit **66**. A signal received from the data register **54A** is transmitted to the FF selected by the MUX **60**. The write pointer Wptr will be described later in detail.

[0109] The FFs **61** to **63** respectively receive signals from the MUX **60**. The FFs **61** to **63** fetch the signals received from the MUX **60** at a timing when the write clock Wclk rises from the “L” level to the “H” level, and store the fetched signals, respectively.

[0110] The MUX **64** selects one of the FFs **61** to **63** based on a read pointer Rptr received from the read pointer generating circuit **68**. The read pointer Rptr will be described later in detail.

[0111] The write clock generating circuit **65** generates the write clock Wclk that determines a timing for fetching a signal to each of the FFs **61** to **63**. The write clock generating circuit **65** transmits the generated write clock Wclk to the write pointer generating circuit **66**.

[0112] The write pointer generating circuit **66** generates the write pointer Wptr that determines which one of the FFs **61** to **63** fetches a signal received from the data register **54A**. The write pointer Wptr is incremented at a timing when the write clock Wclk rises from the “L” level to the “H” level and accordingly, the write pointer Wptr is generated.

[0113] The read clock generating circuit **67** generates the read clock Rclk that determines a timing for switching the coupling between one of the FFs **61** to **63** and the MUX **64**. The read clock generating circuit **67** transmits the generated read clock Rclk to the read pointer generating circuit **68**.

[0114] The read pointer generating circuit **68** generates the read pointer Rptr that determines from which one of the FFs **61** to **63** a signal received is to be output. The read pointer Rptr is incremented at a timing when the read clock Rclk rises from the “L” level to the “H” level and accordingly, the read pointer Rptr is generated.

[0115] The FFs **61** to **63** may be provided in a multistage manner between the MUX **60** and the MUX **64**.

## 1.2 Operation

[0116] An operation of the memory system **100** according to the present embodiment will be described with reference to FIG. 8 to FIG. 17. FIG. 8 to FIG. 17 are each a diagram showing an example of a command sequence in the read operation of the memory system **100** according to the present embodiment. The following will describe an exemplary case in which the signals CEn1 and CEn2 are the same signal (CEn1=CEn2=CEn), and data is repeatedly read from the plane **0** in the chip **0**, the plane **0** in the chip **1**, the plane **1** in the chip **0**, the plane **1** in the chip **1**, the plane **2** in the chip **0**, the plane **2** in the chip **1**, the plane **3** in the chip **0**, and the plane **3** in the chip **1** in this order.

[0117] FIG. 8 to FIG. 17 each also show a cache busy signal CB of each of the planes in the chips **0** (CP0) and **1** (CP1). Through this description, the “cache busy signal CB” means a signal indicative of whether a target plane is in a busy state or in a ready state. The signal CB is provided for each plane, and is set to the “L” level when a corresponding plane is, for example, in the busy state. In the case where the signal CB is in the busy state, the signal CB indicates a state in which access to the data register **54** (data DAT) of a corresponding plane is not possible. In the case where the signal CB is in the ready state, the signal CB indicates a state in which access to the data register **54** (data DAT) of a corresponding plane is possible. The signal CB is stored in the status register **21**. The memory controller **300** confirms a state of the signal CB of each plane by reading the status

information STS from the status register **21**. Hereinafter, the signals CB of the planes **0** to **3** (PL**0** to PL**3**) in the chip **0** (CP**0**) will be respectively referred to as a signal CB**00**, a signal CB**01**, a signal CB**02**, and a signal CB**03**, and the signals CB of the planes **0** to **3** (PL**0** to PL**3**) in the chip **1** (CP**1**) will be respectively referred to as a signal CB**10**, a signal CB**11**, a signal CB**12**, and a signal CB**13**. The signal RB corresponds to a result of an AND operation that the sequencer **30** performs on the signal CB of each plane inside a corresponding chip. For example, in the chip **0** (CP**0**), the signal RB is at the “L” level in the case where the signal CB of any one of the planes **0** to **3** (PL**0** to PL**3**) is at the “L” level, and the signal RB is at the “H” level in the case where the signals CB of all the planes **0** to **3** (PL**0** to PL**3**) are at the “H” level. In this manner, the signal RB indicates whether or not all the planes are in the ready state in each chip.

[0118] The read operation in the present embodiment corresponds to a single plane read.

Throughout this description, “single plane read” means an operation in which the data DAT is independently read from each of the planes.

[0119] First, as shown in FIG. **8** and FIG. **9**, the memory controller **300** executes a normal read on the plane **0** (PL**0**) in the chip **0** (CP**0**). Throughout this description, “normal read” means, in the target plane, a read operation in which a subsequent command with respect to a target plane is not accepted until the read data DAT is stored in the data register **54** from the memory cell array **51** (until the signal CB is brought into the ready state).

[0120] More specifically, after setting the signal CEn to the “L” level, the memory controller **300** issues a command <00h>, an address <Ad00>, and a command <30h> in order to execute the normal read on the plane **0** (PL**0**) in the chip **0** (CP**0**). The command “00h” is a command for ordering a read. The address “Ad00” designates an address of the plane **0** in the chip **0**. The command “30h” is a command for causing the normal read in the single plane read to execute.

[0121] In the chip **0** (CP**0**), the input/output circuit **10** receives the command <00h>, the address <Ad00>, and the command <30h> each issued by the memory controller **300**. The input/output circuit **10** transmits the received command <00h> to the command register **0** (MR**0**) in the chip **0** (CP**0**) based on the address <Ad00>. The input/output circuit **10** transmits the row address RA of the received address <Ad00> to the row address register **0** (RR**0**) in the chip **0** (CP**0**), and transmits the column address CA of the received address <Ad00> to the column address register **0** (CR**0**) in the chip **0** (CP**0**). The input/output circuit **10** transmits the received command <30h> to the command register **0** (MR**0**) in the chip **0** (CP**0**) based on the address <Ad00>.

[0122] When the row address RA of the address <Ad00> is stored in the row address register **0** (RR**0**), the row address register **0** (RR**0**) transmits the row address RA to the row decoder **52A**.

[0123] Upon receipt of the command <30h> from the command register **0** (MR**0**), the sequencer **30** in the chip **0** (CP**0**) initiates the normal read on the plane **0** (PL**0**). The sequencer **30** sets the signal CB**00** to the busy state. The signal CB**00** is stored in the status register **21**. Upon completion of the normal read on the plane **0** (PL**0**) in the chip **0** (CP**0**), the sequencer **30** sets the signal CB**00** to the ready state. This enables the plane **0** (PL**0**) in the chip **0**

[0124] (CP**0**) to accept a subsequent command.

[0125] Next, the memory controller **300** executes the normal read on the plane **0** (PL**0**) in the chip **1** (CP**1**).

[0126] More specifically, after issuance of the command <00h>, the address <Ad00>, and the command <30h>, the memory controller **300** issues the command <00h>, an address <Ad10>, and the command <30h> in order to execute the normal read on the plane **0** (PL**0**) in the chip **1** (CP**1**). The address “Ad10” designates an address of the plane **0** in the chip **1**.

[0127] In the chip **1** (CP**1**), the input/output circuit **10** receives the command <00h>, the address <Ad10>, and the command <30h> each issued by the memory controller **300**. Thereafter, the normal read on the plane **0** (PL**0**) in the chip **1** (CP**1**) is initiated as with the normal read on the plane **0** (PL**0**) in the chip **0** (CP**0**) described above. The sequencer **30** in the chip **1** (CP**1**) sets the signal CB**10** to the busy state. The signal CB**10** is stored in the status register **21**. Upon completion

of the normal read on the plane **0** (PL**0**) in the chip **1** (CP**1**), the sequencer **30** sets the signal CB**10** to the ready state. This enables the plane **0** (PL**0**) in the chip **1** (CP**1**) to accept a subsequent command.

[0128] Next, the memory controller **300** executes the normal read on the plane **1** (PL**1**) in the chip **0** (CP**0**).

[0129] More specifically, after issuance of the command <00h>, the address <Ad10>, and the command <30h>, the memory controller **300** issues the command <00h>, an address <Ad01>, and the command <30h> in order to execute the normal read on the plane **1** (PL**1**) in the chip **0** (CP**0**). The address “Ad01” designates an address of the plane **1** in the chip **0**.

[0130] In the chip **0** (CP**0**), the input/output circuit **10** receives the command <00h>, the address <Ad01>, and the command <30h> each issued by the memory controller **300**. The input/output circuit **10** transmits the received command <00h> to the command register **1** (MR**1**) in the chip **0** (CP**0**) based on the address <Ad01>. The input/output circuit **10** transmits the row address RA of the received address <Ad01> to the row address register **1** (RR**1**) in the chip **0** (CP**0**), and transmits the column address CA of the received address <Ad01> to the column address register **0** (CR**0**) in the chip **0** (CP**0**). The input/output circuit **10** transmits the received command <30h> to the command register **1** (MR**1**) in the chip **0** (CP**0**) based on the address <Ad01>.

[0131] When the row address RA of the address <Ad01> is stored in the row address register **1** (RR**1**), the row address register **1** (RR**1**) transmits the row address RA to the row decoder **52B**.

[0132] Upon receipt of the command <30h> from the command register **1** (MR**1**), the sequencer **30** in the chip **0** (CP**0**) initiates the normal read on the plane **1** (PL**1**). The sequencer **30** sets the signal CB**01** to the busy state. The signal CB**01** is stored in the status register **21**. Upon completion of the normal read on the plane **1** (PL**1**) in the chip **0** (CP**0**), the sequencer **30** sets the signal CB**01** to the ready state. This enables the plane **1** (PL**1**) in the chip **0** (CP**0**) to accept a subsequent command.

[0133] Next, the memory controller **300** executes the normal read on the plane **1** (PL**1**) in the chip **1** (CP**1**).

[0134] More specifically, after issuance of the command <00h>, the address <Ad01>, and the command <30h>, the memory controller **300** issues the command <00h>, an address <Ad11>, and the command <30h> in order to execute the normal read on the plane **1** (PL**1**) in the chip **1** (CP**1**). The address “Ad11” designates an address of the plane **1** in the chip **1**.

[0135] In the chip **1** (CP**1**), the input/output circuit **10** receives the command <00h>, the address <Ad11>, and the command <30h> each issued by the memory controller **300**. Thereafter, the normal read on the plane **1** (PL**1**) in the chip **1** (CP**1**) is initiated as with the normal read on the plane **1** (PL**1**) in the chip **0** (CP**0**) described above. The sequencer **30** in the chip **1** (CP**1**) sets the signal CB**11** to the busy state. The signal CB**11** is stored in the status register **21**. Upon completion of the normal read on the plane **1** (PL**1**) in the chip **1** (CP**1**), the sequencer **30** sets the signal CB**11** to the ready state. This enables the plane **1** (PL**1**) in the chip **1** (CP**1**) to accept a subsequent command. Next, the memory controller **300** executes the normal read on the plane **2** (PL**2**) in the chip **0** (CP**0**).

[0136] More specifically, after issuance of the command <00h>, the address <Ad11>, and the command <30h>, the memory controller **300** issues the command <00h>, an address <Ad02>, and the command <30h> in order to execute the normal read on the plane **2** (PL**2**) in the chip **0** (CP**0**). The address “Ad02” designates an address of the plane **2** in the chip **0**.

[0137] In the chip **0** (CP**0**), the input/output circuit **10** receives the command <00h>, the address <Ad02>, and the command <30h> each issued by the memory controller **300**. The input/output circuit **10** transmits the received command <00h> to the command register **2** (MR**2**) in the chip **0** (CP**0**) based on the address <Ad02>. The input/output circuit **10** transmits the row address RA of the received address <Ad02> to the row address register **2** (RR**2**) in the chip **0** (CP**0**), and transmits the column address CA of the received address <Ad02> to the column address register **0** (CR**0**) in the chip **0** (CP**0**). The input/output circuit **10** transmits the received command <30h> to the

command register 2 (MR2) in the chip 0 (CP0) based on the address <Ad02>.

[0138] When the row address RA of the address <Ad02> is stored in the row address register 2 (RR2), the row address register 2 (RR2) transmits the row address RA to the row decoder 52C.

[0139] Upon receipt of the command <30h> from the command register 2 (MR2), the sequencer 30 in the chip 0 (CP0) initiates the normal read on the plane 2 (PL2). The sequencer 30 sets the signal CB02 to the busy state. The signal CB02 is stored in the status register 21. Upon completion of the normal read on the plane 2 (PL2) in the chip 0 (CP0), the sequencer 30 sets the signal CB02 to the ready state. This enables the plane 2 (PL2) in the chip 0 (CP0) to accept a subsequent command.

[0140] Next, the memory controller 300 executes the normal read on the plane 2 (PL2) in the chip 1 (CP1).

[0141] More specifically, after issuance of the command <00h>, the address <Ad02>, and the command <30h>, the memory controller 300 issues the command <00h>, an address <Ad12>, and the command <30h> in order to execute the normal read on the plane 2 (PL2) in the chip 1 (CP1). The address “Ad12” designates an address of the plane 2 in the chip 1.

[0142] In the chip 1 (CP1), the input/output circuit 10 receives the command <00h>, the address <Ad12>, and the command <30h> each issued by the memory controller 300. Thereafter, the normal read on the plane 2 (PL2) in the chip 1 (CP1) is initiated as with the normal read on the plane 2 (PL2) in the chip 0 (CP0) described above. The sequencer 30 in the chip 1 (CP1) sets the signal CB12 to the busy state. The signal CB12 is stored in the status register 21. Upon completion of the normal read on the plane 2 (PL2) in the chip 1 (CP1), the sequencer 30 sets the signal CB12 to the ready state. This enables the plane 2 (PL2) in the chip 1 (CP1) to accept a subsequent command. Next, the memory controller 300 executes the normal read on the plane 3 (PL3) in the chip 0 (CP0).

[0143] More specifically, after issuance of the command <00h>, the address <Ad12>, and the command <30h>, the memory controller 300 issues the command <00h>, an address <Ad03>, and the command <30h> in order to execute the normal read on the plane 3 (PL3) in the chip 0 (CP0). The address “Ad03” designates an address of the plane 3 in the chip 0.

[0144] In the chip 0 (CP0), the input/output circuit 10 receives the command <00h>, the address <Ad03>, and the command <30h> each issued by the memory controller 300. The input/output circuit 10 transmits the received command <00h> to the command register 3 (MR3) in the chip 0 (CP0) based on the address <Ad03>. The input/output circuit 10 transmits the row address RA of the received address <Ad03> to the row address register 3 (RR3) in the chip 0 (CP0), and transmits the column address CA of the received address <Ad03> to the column address register 0 (CR0) in the chip 0 (CP0). The input/output circuit 10 transmits the received command <30h> to the command register 3 (MR3) in the chip 0 (CP0) based on the address <Ad03>.

[0145] When the row address RA of the address <Ad03> is stored in the row address register 3 (RR3), the row address register 3 (RR3) transmits the row address RA to the row decoder 52D.

[0146] Upon receipt of the command <30h> from the command register 3 (MR3), the sequencer 30 in the chip 0 (CP0) initiates the normal read on the plane 3 (PL3). The sequencer 30 sets the signal CB03 to the busy state. The signal CB03 is stored in the status register 21. Upon completion of the normal read on the plane 3 (PL3) in the chip 0 (CP0), the sequencer 30 sets the signal CB03 to the ready state. This enables the plane 3 (PL3) in the chip 0 (CP0) to accept a subsequent command.

[0147] Next, the memory controller 300 executes the normal read on the plane 3 (PL3) in the chip 1 (CP1).

[0148] More specifically, after issuance of the command <00h>, the address <Ad03>, and the command <30h>, the memory controller 300 issues the command <00h>, an address <Ad13>, and the command <30h> in order to execute the normal read on the plane 3 (PL3) in the chip 1 (CP1). The address “Ad13” designates an address of the plane 3 in the chip 1.

[0149] In the chip 1 (CP1), the input/output circuit 10 receives the command <00h>, the address <Ad13>, and the command <30h> each issued by the memory controller 300. Thereafter, the

normal read on the plane **3** (PL**3**) in the chip **1** (CP**1**) is initiated as with the normal read on the plane **3** (PL**3**) in the chip **0** (CP**0**) described above. The sequencer **30** in the chip **1** (CP**1**) sets the signal CB**13** to the busy state. The signal CB**13** is stored in the status register **21**. Upon completion of the normal read on the plane **3** (PL**3**) in the chip **1** (CP**1**), the sequencer **30** sets the signal CB**13** to the ready state. This enables the plane **3** (PL**3**) in the chip **1** (CP**1**) to accept a subsequent command. Next, as shown in FIG. **10**, the memory controller **300** executes a status read on the plane **0** (PL**0**) in the chip **0** (CP**0**).

[0150] More specifically, after issuance of the command <00h>, the address <Ad13>, and the command <30h>, the memory controller **300** issues a command <78h> and the address <Ad00> in order to execute the status read on the plane **0** (PL**0**) in the chip **0** (CP**0**). The command “78h” is a command for reading the status information STS from the status register **21**.

[0151] The sequencer **30** in the chip **0** (CP**0**) transmits the status information STS on the signal CB**00** corresponding to the address <Ad00> to the memory controller **300**.

[0152] Next, upon receipt of the signal CB**00** indicative of the ready state from the status register **21**, the memory controller **300** executes a cache read on the plane **0** (PL**0**) in the chip **0** (CP**0**). Throughout this description, “cache read” means a read operation in which a subsequent command with respect to a target plane is accepted even in the case where storing of the read data DAT from the memory cell array **51** to the data register **54** has not been completed in the target plane (even in the case where the signal CB is in the busy state).

[0153] More specifically, the memory controller **300** issues the command <00h>, the address <Ad00>, and a command <31h> in order to execute the cache read on the plane **0** (PL**0**) in the chip **0** (CP**0**). The command “31h” is a command for causing the cache read in the single plane read to execute. In the chip **0** (CP**0**), the input/output circuit **10** receives the command <00h>, the address <Ad00>, and the command <31h> each issued by the memory controller **300**.

[0154] Thereafter, the cache read on the plane **0** (PL**0**) in the chip **0** (CP**0**) is initiated as with the normal read on the plane **0** (PL**0**) in the chip **0** (CP**0**) described above. The sequencer **30** in the chip **0** (CP**0**) sets the signal CB**00** to the busy state. Upon completion of a cache transfer on the plane **0** (PL**0**) in the chip **0** (CP**0**) (a transfer of the read data DAT from the memory cell array **51** currently executing the cache read to the corresponding data register **54**), the sequencer **30** sets the signal CB**00** to the ready state. However, in the case where a command for instructing execution of a prefetch to be described later has been accepted, the sequencer **30** sets the signal CB**00** to the ready state after the execution of the prefetch subsequent to the cache transfer.

[0155] Next, the memory controller **300** reserves the prefetch of read data in the normal read executed on the plane **0** (PL**0**) in the chip **0** (CP**0**). Throughout this description, “prefetch” means an operation in which the data DAT read from the memory cell array **51** to the data register **54** is fetched from the data register **54** to the FIFO circuit **12**. Furthermore, “reserving a prefetch” means preparing for execution of the prefetch and then entering a standby state for the execution of the prefetch.

[0156] More specifically, during a period in which the command <00h>, the address <Ad00>, and the command <31h> are issued and the cache read is executed (that is, a period in which the signal CB**00** is in the busy state), the memory controller **300** issues a command <05h>, the address <Ad00>, and a command <E0h> in order to reserve the prefetch on the plane **0** (PL**0**) in the chip **0** (CP**0**). The command “05h” is a command for ordering the prefetch. The command “E0h” is a command for instructing execution of the prefetch.

[0157] In the chip **0** (CP**0**), the input/output circuit **10** receives the command <05h>, the address <Ad00>, and the command <E0h> each issued by the memory controller **300**. The input/output circuit **10** transmits the received command <05h> to the command register **0** (MR**0**) in the chip **0** (CP**0**) based on the address <Ad00> and also copies the command <05h> to the command register **0'** (MR**0'**) in the chip **0** (CP**0**). The input/output circuit **10** transmits the row address RA of the received address <Ad00> to the row address register **0** (RR**0**) in the chip **0** (CP**0**) and also copies

the row address RA of the address <Ad00> to the row address register **0'** (RR**0'**) in the chip **0** (CP**0**). The input/output circuit **10** transmits the column address CA of the received address <Ad00> to the column address register **0** (CR**0**) in the chip **0** (CP**0**) and also copies the column address CA of the address <Ad00> to the column address register **0'** (CR**0'**) in the chip **0** (CP**0**). The input/output circuit **10** transmits the received command <E0h> to the command register **0** (MR**0**) in the chip **0** (CP**0**) based on the address <Ad00>, and also copies the command <E0h> to the command register **0'** (MR**0'**) in the chip **0** (CP**0**).

[0158] When the row address RA of the address <Ad00> is copied to the row address register **0'** (RR**0'**), the row address register **0'** (RR**0'**) transmits the row address RA to the row decoder **52A**.

[0159] Upon receipt of the command <E0h> from the command register **0'** (MR**0'**), the sequencer **30** in the chip **0** (CP**0**) reserves the prefetch on the plane **0** (PL**0**). The sequencer **30** then initiates the prefetch. Upon receipt of the command <E0h> with the signal CB**00** being in the busy state, the sequencer **30** executes the prefetch on the plane **0** (PL**0**) in the chip **0** (CP**0**) during a period in which the signal CB**00** is in the busy state. More specifically, upon receipt of the command <E0h> with the signal CB**00** being in the busy state, the sequencer **30** in the chip **0** (CP**0**) executes the prefetch subsequently to the cache transfer, and sets the signal CB**00** to the ready state after execution of the prefetch.

[0160] Upon initiation of the prefetch, the sequencer **30** in the chip **0** (CP**0**) resets a counter value CNT of the column address counter circuit CC**0'** to 0. The column address register **0'** (CR**0'**) transmits the first to last column addresses CA to the column decoders **55A** to **55D**. Based on a result of decoding the column address CA of the address <Ad00>, the column decoder **55A** selects a corresponding latch circuit in the data register **54A**. Data in the latch circuit selected in sequence is transmitted to the FIFO circuit **12**.

[0161] Next, as shown in FIG. **10**, the memory controller **300** executes the status read on the plane **0** (PL**0**) in the chip **1** (CP**1**).

[0162] More specifically, after issuance of the command <05h>, the address <Ad00>, and the command <E0h>, the memory controller **300** issues the command <78h> and the address <Ad10> in order to execute the status read on the plane **0** (PL**0**) in the chip **1** (CP**1**).

[0163] The sequencer **30** in the chip **1** (CP**1**) transmits the status information STS on the signal CB**10** corresponding to the address <Ad10> to the memory controller **300**.

[0164] Next, upon receipt of the signal CB**10** indicative of the ready state from the status register **21**, the memory controller **300** executes the cache read on the plane **0** (PL**0**) in the chip **1** (CP**1**).

[0165] More specifically, the memory controller **300** issues the command <00h>, the address <Ad10>, and the command <31h> in order to execute the cache read on the plane **0** (PL**0**) in the chip **1** (CP**1**).

[0166] In the chip **1** (CP**1**), the input/output circuit **10** receives the command <00h>, the address <Ad10>, and the command <31h> each issued by the memory controller **300**. Thereafter, the cache read on the plane **0** (PL**0**) in the chip **1** (CP**1**) is initiated as with the cache read on the plane **0** (PL**0**) in the chip **0** (CP**0**) described above. The sequencer **30** in the chip **1** (CP**1**) sets the signal CB**10** to the busy state. Upon completion of the cache transfer on the plane **0** (PL**0**) in the chip **1** (CP**1**), the sequencer **30** sets the signal CB**10** to the ready state. However, in the case where a command for instructing execution of the prefetch has been accepted, the sequencer **30** sets the signal CB**10** to the ready state after the execution of the prefetch subsequent to the cache transfer.

[0167] Next, the memory controller **300** reserves the prefetch of read data in the normal read executed on the plane **0** (PL**0**) in the chip **1** (CP**1**).

[0168] More specifically, during a period in which the command <00h>, the address <Ad10>, and the command <31h> are issued and the cache read is executed (that is, a period in which the signal CB**10** is in the busy state), the memory controller **300** issues the command <05h>, the address <Ad10>, and the command <E0h> in order to reserve the prefetch on the plane **0** (PL**0**) in the chip **1** (CP**1**).



[0169] In the chip **1** (CP1), the input/output circuit **10** receives the command <05h>, the address <Ad10>, and the command <E0h> each issued by the memory controller **300**. Thereafter, the prefetch on the plane **0** (PL0) in the chip **1** (CP1) is reserved and initiated as with the reservation and execution of the prefetch on the plane **0** (PL0) in the chip **0** (CP0). Upon receipt of the command <E0h> with the signal CB10 being in the busy state, the sequencer **30** in the chip **1** (CP1) executes the prefetch on the plane **0** (PL0) in the chip **1** (CP1) during a period in which the signal CB10 is in the busy state. More specifically, upon receipt of the command <E0h> with the signal CB10 being in the busy state, the sequencer **30** in the chip **1** (CP1) executes the prefetch subsequently to the cache transfer, and sets the signal CB10 to the ready state after execution of the prefetch.

[0170] Next, as shown in FIG. **10**, the memory controller **300** executes the status read on the plane **1** (PL1) in the chip **0** (CP0).

[0171] More specifically, after issuance of the command <05h>, the address <Ad10>, and the command <E0h>, the memory controller **300** issues the command <78h> and the address <Ad01> in order to execute the status read on the plane **1** (PL1) in the chip **0** (CP0).

[0172] The sequencer **30** in the chip **0** (CP0) transmits the status information STS on the signal CB01 corresponding to the address <Ad01> to the memory controller **300**.

[0173] Next, upon receipt of the signal CB01 indicative of the ready state from the status register **21**, the memory controller **300** executes the cache read on the plane **1** (PL1) in the chip **0** (CP0).

[0174] More specifically, the memory controller **300** issues the command <00h>, the address <Ad01>, and the command <31h> in order to execute the cache read on the plane **1** (PL1) in the chip **0** (CP0).

[0175] In the chip **0** (CP0), the input/output circuit **10** receives the command <00h>, the address <Ad01>, and the command <31h> each issued by the memory controller **300**. Thereafter, the cache read on the plane **1** (PL1) in the chip **0** (CP0) is initiated as with the normal read on the plane **1** (PL1) in the chip **0** (CP0) described above. The sequencer **30** in the chip **0** (CP0) sets the signal CB01 to the busy state. Upon completion of the cache transfer on the plane **1** (PL1) in the chip **0** (CP0), the sequencer **30** sets the signal CB01 to the ready state.

[0176] Next, as shown in FIG. **11**, the memory controller **300** executes the status read on the plane **1** (PL1) in the chip **1** (CP1).

[0177] More specifically, after issuance of the command <00h>, the address <Ad01>, and the command <31h>, the memory controller **300** issues the command <78h> and the address <Ad11> in order to execute the status read on the plane **1** (PL1) in the chip **1** (CP1).

[0178] The sequencer **30** in the chip **1** (CP1) transmits the status information STS on the signal CB11 corresponding to the address <Ad11> to the memory controller **300**.

[0179] Next, upon receipt of the signal CB11 indicative of the ready state from the status register **21**, the memory controller **300** executes the cache read on the plane **1** (PL1) in the chip **1** (CP1).

[0180] More specifically, the memory controller **300** issues the command <00h>, the address <Ad11>, and the command <31h> in order to execute the cache read on the plane **1** (PL1) in the chip **1** (CP1).

[0181] In the chip **1** (CP1), the input/output circuit **10** receives the command <00h>, the address <Ad11>, and the command <31h> each issued by the memory controller **300**. Thereafter, the cache read on the plane **1** (PL1) in the chip **1** (CP1) is initiated as with the cache read on the plane **1** (PL1) in the chip **0** (CP0) described above. The sequencer **30** in the chip **1** (CP1) sets the signal CB11 to the busy state. Upon completion of the cache transfer of the plane **1** (PL1) in the chip **1** (CP1), the sequencer **30** sets the signal CB11 to the ready state.

[0182] Next, as shown in FIG. **11**, the memory controller **300** executes the status read on the plane **2** (PL2) in the chip **0** (CP0).

[0183] More specifically, after issuance of the command <00h>, the address <Ad11>, and the command <31h>, the memory controller **300** issues the command <78h> and the address <Ad02>

in order to execute the status read on the plane 2 (PL2) in the chip 0 (CP0).

[0184] The sequencer 30 in the chip 0 (CP0) transmits the status information STS on the signal CB02 corresponding to the address <Ad02> to the memory controller 300.

[0185] Next, upon receipt of the signal CB02 indicative of the ready state from the status register 21, the memory controller 300 executes the cache read on the plane 2 (PL2) in the chip 0 (CP0).

[0186] More specifically, the memory controller 300 issues the command <00h>, the address <Ad02>, and the command <31h> in order to execute the cache read on the plane 2 (PL2) in the chip 0 (CP0).

[0187] In the chip 0 (CP0), the input/output circuit 10 receives the command <00h>, the address <Ad02>, and the command <31h> each issued by the memory controller 300. Thereafter, the cache read on the plane 2 (PL2) in the chip 0 (CP0) is initiated as with the normal read on the plane 2 (PL2) in the chip 0 (CP0) described above. The sequencer 30 in the chip 0 (CP0) sets the signal CB02 to the busy state. Upon completion of the cache transfer on the plane 2 (PL2) in the chip 0 (CP0), the sequencer 30 sets the signal CB02 to the ready state.

[0188] Next, as shown in FIG. 11, the memory controller 300 executes the status read on the plane 2 (PL2) in the chip 1 (CP1).

[0189] More specifically, after issuance of the command <00h>, the address <Ad02>, and the command <31h>, the memory controller 300 issues the command <78h> and the address <Ad12> in order to execute the status read on the plane 2 (PL2) in the chip 1 (CP1).

[0190] The sequencer 30 in the chip 1 (CP1) transmits the status information STS on the signal CB12 corresponding to the address <Ad12> to the memory controller 300.

[0191] Next, upon receipt of the signal CB12 indicative of the ready state from the status register 21, the memory controller 300 executes the cache read on the plane 2 (PL2) in the chip 1 (CP1).

[0192] More specifically, the memory controller 300 issues the command <00h>, the address <Ad12>, and the command <31h> in order to execute the cache read on the plane 2 (PL2) in the chip 1 (CP1).

[0193] In the chip 1 (CP1), the input/output circuit 10 receives the command <00h>, the address <Ad12>, and the command <31h> each issued by the memory controller 300. Thereafter, the cache read on the plane 2 (PL2) in the chip 1 (CP1) is initiated as with the cache read on the plane 2 (PL2) in the chip 0 (CP0) described above. The sequencer 30 in the chip 1 (CP1) sets the signal CB12 to the busy state. Upon completion of the cache transfer on the plane 2 (PL2) in the chip 1 (CP1), the sequencer 30 sets the signal CB12 to the ready state.

[0194] Next, as shown in FIG. 11, the memory controller 300 executes the status read on the plane 3 (PL3) in the chip 0 (CP0).

[0195] More specifically, after issuance of the command <00h>, the address <Ad12>, and the command <31h>, the memory controller 300 issues the command <78h> and the address <Ad03> in order to execute the status read on the plane 3 (PL3) in the chip 0 (CP0).

[0196] The sequencer 30 in the chip 0 (CP0) transmits the status information STS on the signal CB03 corresponding to the address <Ad03> to the memory controller 300.

[0197] Next, upon receipt of the signal CB03 indicative of the ready state from the status register 21, the memory controller 300 executes the cache read on the plane 3 (PL3) in the chip 0 (CP0).

[0198] More specifically, the memory controller 300 issues the command <00h>, the address <Ad03>, and the command <31h> in order to execute the cache read on the plane 3 (PL3) in the chip 0 (CP0).

[0199] In the chip 0 (CP0), the input/output circuit 10 receives the command <00h>, the address <Ad03>, and the command <31h> each issued by the memory controller 300. Thereafter, the cache read on the plane 3 (PL3) in the chip 0 (CP0) is initiated as with the normal read on the plane 3 (PL3) in the chip 0 (CP0) described above. The sequencer 30 in the chip 0 (CP0) sets the signal CB03 to the busy state. Upon completion of the cache transfer on the plane 3 (PL3) in the chip 0 (CP0), the sequencer 30 sets the signal CB03 to the ready state.

[0200] Next, as shown in FIG. 12, the memory controller **300** executes the status read on the plane **3** (PL**3**) in the chip **1** (CP**1**).

[0201] More specifically, after issuance of the command <00h>, the address <Ad03>, and the command <31h>, the memory controller **300** issues the command <78h> and the address <Ad13> in order to execute the status read on the plane **3** (PL**3**) in the chip **1** (CP**1**).

[0202] The sequencer **30** in the chip **1** (CP**1**) transmits the status information STS on the signal CB**13** corresponding to the address <Ad13> to the memory controller **300**.

[0203] Next, upon receipt of the signal CB**13** indicative of the ready state from the status register **21**, the memory controller **300** executes the cache read on the plane **3** (PL**3**) in the chip **1** (CP**1**).

[0204] More specifically, the memory controller **300** issues the command <00h>, the address <Ad13>, and the command <31h> in order to execute the cache read on the plane **3** (PL**3**) in the chip **1** (CP**1**).

[0205] In the chip **1** (CP**1**), the input/output circuit **10** receives the command <00h>, the address <Ad13>, and the command <31h> each issued by the memory controller **300**. Thereafter, the cache read on the plane **3** (PL**3**) in the chip **1** (CP**1**) is initiated as with the cache read on the plane **3** (PL**3**) in the chip **0** (CP**0**) described above. The sequencer **30** in the chip **1** (CP**1**) sets the signal CB**13** to the busy state. Upon completion of the cache transfer on the plane **3** (PL**3**) in the chip **1** (CP**1**), the sequencer **30** sets the signal CB**13** to the ready state.

[0206] Next, as shown in FIG. 12, the memory controller **300** executes the status read on the plane **0** (PL**0**) in the chip **0** (CP**0**). The particulars of the aforementioned status read executed in response to the command <78h> and the address <Ad00> being issued after issuance of the command <00h>, the address <Ad13>, and the command <31h> are the same as those of the status read on the plane **0** (PL**0**) in the chip **0** (CP**0**) described above.

[0207] Next, upon receipt of the signal CB**00** indicative of the ready state from the status register **21**, the memory controller **300** executes a data-out on the plane **0** (PL**0**) in the chip **0** (CP**0**). Throughout this description, “data-out” means an operation in which the data DAT fetched from the data register **54** to the FIFO circuit **12** is output from the FIFO circuit **12** to the memory controller **300** via the DQ pad **11**.

[0208] More specifically, the memory controller **300** issues a command <XXh> in order to execute the data-out on the plane **0** (PL**0**) in the chip **0** (CP**0**). The command “XXh” is a command for selecting a chip and a plane and causing the data-out to execute.

[0209] In the chip **0** (CP**0**), the input/output circuit **10** receives the command <XXh> issued by the memory controller **300**. The input/output circuit **10** transmits the received command <XXh> to the command register **0** (MR**0**) in the chip **0** (CP**0**).

[0210] Upon receipt of the command <XXh> from the command register **0** (MR**0**), the sequencer **30** in the chip **0** (CP**0**) initiates the data-out on the plane **0** (PL**0**) on which the prefetch has been executed.

[0211] Next, as shown in FIG. 12, the memory controller **300** reserves the prefetch of read data in the normal read executed on the plane **1** (PL**1**) in the chip **0** (CP**0**).

[0212] More specifically, upon completion of the data-out on the plane **0** (PL**0**) in the chip **0** (CP**0**), the memory controller **300** issues the command <05h>, the address <Ad01>, and the command <E0h>, in order to reserve the prefetch on the plane **1** (PL**1**) in the chip **0** (CP**0**).

[0213] In the chip **0** (CP**0**), the input/output circuit **10** receives the command <05h>, the address <Ad01>, and the command <E0h> each issued by the memory controller **300**. The input/output circuit **10** transmits the received command <05h> to the command register **1** (MR**1**) in the chip **0** (CP**0**) based on the address <Ad01> and also copies the command <05h> to the command register **1'** (MR**1'**) in the chip **0** (CP**0**). The input/output circuit **10** transmits the row address RA of the received address <Ad01> to the row address register **1** (RR**1**) in the chip **0** (CP**0**) and also copies the row address RA of the address <Ad01> to the row address register **1'** (RR**1'**) in the chip **0** (CP**0**). The input/output circuit **10** transmits the column address CA of the received address

<Ad01> to the column address register **0** (CR**0**) in the chip **0** (CP**0**) and also copies the column address CA of the address <Ad01> to the column address register **0'** (CR**0'**) in the chip **0** (CP**0**). The input/output circuit **10** transmits the received command <E0h> to the command register **1** (MR**1**) in the chip **0** (CP**0**) based on the address <Ad01> and also copies the command <E0h> to the command register **1'** (MR**1'**) in the chip **0** (CP**0**).

[0214] When the row address RA of the address <Ad01> is copied to the row address register **1'** (RR**1'**), the row address register **1'** (RR**1'**) transmits the row address RA to the row decoder **52B**.

[0215] Upon receipt of the command <E0h> from the command register **1'** (MR**1'**), the sequencer **30** in the chip **0** (CP**0**) reserves the prefetch on the plane **1** (PL**1**). The sequencer **30** then initiates the prefetch. Upon receipt of the command <E0h> with the signal CB**01** being in the ready state, the sequencer **30** immediately executes the prefetch on the plane **1** (PL**1**) in the chip **0** (CP**0**).

[0216] Upon initiation of the prefetch, the sequencer **30** in the chip **0** (CP**0**) resets the counter value CNT of the column address counter circuit CC**0'** to 0. The column address register **0'** (CR**0'**) transmits the first to last column addresses CA to the column decoders **55A** to **55D**. Based on a result of decoding the column address CA of the address <Ad01>, the column decoder **55B** selects a corresponding latch circuit in the data register **54B**. Data in the latch circuit selected in sequence is transmitted to the FIFO circuit **12**.

[0217] Next, as shown in FIG. **12**, the memory controller **300** executes the cache read on the plane **0** (PL**0**) in the chip **0** (CP**0**). The particulars of the aforementioned cache read executed in response to the command <00h>, the address <Ad00>, and the command <31h> being issued after issuance of the command <05h>, the address <Ad01>, and the command <E0h> are the same as those of the cache read on the plane **0** (PL**0**) in the chip **0** (CP**0**) described above. Upon initiation of the cache read, the sequencer **30** in the chip **0** (CP**0**) sets the signal CB**00** to the busy state. Upon completion of the cache transfer on the plane **0** (PL**0**) in the chip **0** (CP**0**), the sequencer **30** sets the signal CB**00** to the ready state.

[0218] Next, as shown in FIG. **13**, the memory controller **300** executes the status read on the plane **0** (PL**0**) in the chip **1** (CP**1**). The particulars of the aforementioned status read executed in response to the command <78h> and the address <Ad10> being issued after issuance of the command <00h>, the address <Ad00>, and the command <31h> are the same as those of the status read on the plane **0** (PL**0**) in the chip **1** (CP**1**) described above.

[0219] Next, upon receipt of the signal CB**10** indicative of the ready state from the status register **21**, the memory controller **300** executes the data-out on the plane **0** (PL**0**) in the chip **1** (CP**1**).

[0220] More specifically, the memory controller **300** issues the command <XXh> in order to execute the data-out on the plane **0** (PL**0**) in the chip **1** (CP**1**).

[0221] In the chip **1** (CP**1**), the input/output circuit **10** receives the command <XXh> issued by the memory controller **300**. Thereafter, the data-out on the plane **0** (PL**0**) on which the prefetch has been executed is initiated as with the data-out on the plane **0** (PL**0**) in the chip **0** (CP**0**).

[0222] Next, as shown in FIG. **13**, the memory controller **300** reserves the prefetch of read data in the normal read executed on the plane **1** (PL**1**) in the chip **1** (CP**1**).

[0223] More specifically, upon completion of the data-out on the plane **0** (PL**0**) in the chip **1** (CP**1**), the memory controller **300** issues the command <05h>, the address <Ad11>, and the command <E0h> in order to reserve the prefetch on the plane **1** (PL**1**) in the chip **1** (CP**1**).

[0224] In the chip **1** (CP**1**), the input/output circuit **10** receives the command <05h>, the address <Ad11>, and the command <E0h> each issued by the memory controller **300**. Thereafter, the prefetch on the plane **1** (PL**1**) in the chip **1** (CP**1**) is reserved and initiated as with the reservation and execution of the prefetch on the plane **1** (PL**1**) in the chip **0** (CP**0**). Upon receipt of the command <E0h> with the signal CB**11** being in the ready state, the sequencer **30** in the chip **1** (CP**1**) immediately executes the prefetch on the plane **1** (PL**1**) in the chip **1** (CP**1**).

[0225] Next, the memory controller **300** executes the cache read on the plane **0** (PL**0**) in the chip **1** (CP**1**). The particulars of the aforementioned cache read executed in response to the command

<00h>, the address <Ad10>, and the command <31h> being issued after issuance of the command <05h>, the address <Ad11>, and the command <E0h> are the same as those of the cache read on the plane **0** (PL**0**) in the chip **1** (CP**1**) described above. Upon initiation of the cache read, the sequencer **30** in the chip **1** (CP**1**) sets the signal CB**10** to the busy state. Upon completion of the cache transfer on the plane **0** (PL**0**) in the chip **1** (CP**1**), the sequencer **30** sets the signal CB**10** to the ready state.

[0226] Next, as shown in FIG. **13**, the memory controller **300** executes the status read on the plane **1** (PL**1**) in the chip **0** (CP**0**). The particulars of the aforementioned status read executed in response to the command <78h> and the address <Ad01> being issued after issuance of the command <00h>, the address <Ad10>, and the command <31h> are the same as those of the status read on the plane **1** (PL**1**) in the chip **0** (CP**0**) described above.

[0227] Next, upon receipt of the signal CB**01** indicative of the ready state from the status register **21**, the memory controller **300** executes the data-out on the plane **1** (PL**1**) in the chip **0** (CP**0**).

[0228] More specifically, the memory controller **300** issues a command <XXh> in order to execute the data-out on the plane **1** (PL**1**) in the chip **0** (CP**0**).

[0229] In the chip **0** (CP**0**), the input/output circuit **10** receives the command <XXh> issued by the memory controller **300**. The input/output circuit **10** transmits the received command <XXh> to the command register **1** (MR**1**) in the chip **0** (CP**0**).

[0230] Upon receipt of the command <XXh> from the command register **1** (MR**1**), the sequencer **30** in the chip **0** (CP**0**) initiates the data-out on the plane **1** (PL**1**) on which the prefetch has been executed.

[0231] Next, as shown in FIG. **14**, the memory controller **300** reserves the prefetch of read data in the normal read executed on the plane **2** (PL**2**) in the chip **0** (CP**0**).

[0232] More specifically, upon completion of the data-out on the plane **1** (PL**1**) in the chip **0** (CP**0**), the memory controller **300** issues the command <05h>, the address <Ad02>, and the command <E0h> in order to reserve the prefetch on the plane **2** (PL**2**) in the chip **0** (CP**0**).

[0233] In the chip **0** (CP**0**), the input/output circuit **10** receives the command <05h>, the address <Ad02>, and the command <E0h> each issued by the memory controller **300**. The input/output circuit **10** transmits the received command <05h> to the command register **2** (MR**2**) in the chip **0** (CP**0**) based on the address <Ad02> and also copies the command <05h> to the command register **2'** (MR**2'**) in the chip **0** (CP**0**). The input/output circuit **10** transmits the row address RA of the received address <Ad02> to the row address register **2** (RR**2**) in the chip **0** (CP**0**) and also copies the row address RA of the address <Ad02> to the row address register **2'** (RR**2'**) in the chip **0** (CP**0**). The input/output circuit **10** transmits the column address CA of the received address <Ad02> to the column address register **0** (CR**0**) in the chip **0** (CP**0**) and also copies the column address CA of the address <Ad02> to the column address register **0'** (CR**0'**) in the chip **0** (CP**0**). The input/output circuit **10** transmits the received command <E0h> to the command register **2** (MR**2**) in the chip **0** (CP**0**) based on the address <Ad02> and also copies the command <E0h> to the command register **2'** (MR**2'**) in the chip **0** (CP**0**).

[0234] When the row address RA of the address <Ad02> is copied to the row address register **2'** (RR**2'**), the row address register **2'** (RR**2'**) transmits the row address RA to the row decoder **52C**.

[0235] Upon receipt of the command <E0h> from the command register **2'** (MR**2'**), the sequencer **30** in the chip **0** (CP**0**) reserves the prefetch on the plane **2** (PL**2**). The sequencer **30** then initiates the prefetch. Upon receipt of the command <E0h> with the signal CB**02** being in the ready state, the sequencer **30** immediately executes the prefetch on the plane **2** (PL**2**) in the chip **0** (CP**0**).

[0236] Upon initiation of the prefetch, the sequencer **30** in the chip **0** (CP**0**) resets the counter value CNT of the column address counter circuit CC**0'** to 0. The column address register **0'** (CR**0'**) transmits the first to last column addresses CA to the column decoders **55A** to **55D**. Based on a result of decoding the column address CA of the address <Ad02>, the column decoder **55C** selects a corresponding latch circuit in the data register **54C**. Data in the latch circuit selected in sequence

is transmitted to the FIFO circuit **12**.

[0237] Next, the memory controller **300** executes the cache read on the plane **1** (PL**1**) in the chip **0** (CP**0**). The particulars of the aforementioned cache read executed in response to the command <00h>, the address <Ad01>, and the command <31h> being issued after issuance of the command <05h>, the address <Ad02>, and the command <E0h> are the same as those of the cache read on the plane **1** (PL**1**) in the chip **0** (CP**0**) described above. Upon initiation of the cache read, the sequencer **30** in the chip **0** (CP**0**) sets the signal CB**01** to the busy state. Upon completion of the cache transfer on the plane **1** (PL**1**) in the chip **0** (CP**0**), the sequencer **30** sets the signal CB**01** to the ready state.

[0238] Next, as shown in FIG. **14**, the memory controller **300** executes the status read on the plane **1** (PL**1**) in the chip **1** (CP**1**). The particulars of the aforementioned status read executed in response to the command <78h> and the address <Ad11> being issued after issuance of the command <00h>, the address <Ad01>, and the command <31h> are the same as those of the status read on the plane **1** (PL**1**) in the chip **1** (CP**1**) described above.

[0239] Next, upon receipt of the signal CB**11** indicative of the ready state from the status register **21**, the memory controller **300** executes the data-out on the plane **1** (PL**1**) in the chip **1** (CP**1**).

[0240] More specifically, the memory controller **300** issues the command <XXh> in order to execute the data-out on the plane **1** (PL**1**) in the chip **1** (CP**1**).

[0241] In the chip **1** (CP**1**), the input/output circuit **10** receives the command <XXh> issued by the memory controller **300**. Thereafter, the data-out on the plane **1** (PL**1**) on which the prefetch has been executed is initiated as with the data-out on the plane **1** (PL**1**) in the chip **0** (CP**0**).

[0242] Next, as shown in FIG. **14**, the memory controller **300** reserves the prefetch of read data in the normal read executed on the plane **2** (PL**2**) in the chip **1** (CP**1**).

[0243] More specifically, upon completion of the data-out on the plane **1** (PL**1**) in the chip **1** (CP**1**), the memory controller **300** issues the command <05h>, the address <Ad12>, and the command <E0h> in order to reserve the prefetch on the plane **2** (PL**2**) in the chip **1** (CP**1**).

[0244] In the chip **1** (CP**1**), the input/output circuit **10** receives the command <05h>, the address <Ad12>, and the command <E0h> each issued by the memory controller **300**. Thereafter, the prefetch on the plane **2** (PL**2**) in the chip **1** (CP**1**) is reserved and initiated as with the reservation and execution of the prefetch on the plane **2** (PL**2**) in the chip **0** (CP**0**). Upon receipt of the command <E0h> with the signal CB**12** being in the ready state, the sequencer **30** in the chip **1** (CP**1**) immediately executes the prefetch on the plane **2** (PL**2**) in the chip **1** (CP**1**).

[0245] Next, the memory controller **300** executes the cache read on the plane **1** (PL**1**) in the chip **1** (CP**1**). The particulars of the aforementioned cache read executed in response to the command <00h>, the address <Ad11>, and the command <31h> being issued after issuance of the command <05h>, the address <Ad12>, and the command <E0h> are the same as those of the cache read on the plane **1** (PL**1**) in the chip **1** (CP**1**) described above. Upon initiation of the cache read, the sequencer **30** in the chip **1** (CP**1**) sets the signal CB**11** to the busy state. Upon completion of the cache transfer on the plane **1** (PL**1**) in the chip **1** (CP**1**), the sequencer **30** sets the signal CB**11** to the ready state.

[0246] Next, as shown in FIG. **15**, the memory controller **300** executes the status read on the plane **2** (PL**2**) in the chip **0** (CP**0**). The particulars of the aforementioned status read executed in response to the command <78h> and the address <Ad02> being issued after issuance of the command <00h>, the address <Ad11>, and the command <31h> are the same as those of the status read on the plane **2** (PL**2**) in the chip **0** (CP**0**) described above.

[0247] Next, upon receipt of the signal CB**02** indicative of the ready state from the status register **21**, the memory controller **300** executes the data-out on the plane **2** (PL**2**) in the chip **0** (CP**0**).

[0248] More specifically, the memory controller **300** issues the command <XXh> in order to execute the data-out on the plane **2** (PL**2**) in the chip **0** (CP**0**).

[0249] In the chip **0** (CP**0**), the input/output circuit **10** receives the command <XXh> issued by the

memory controller **300**. The input/output circuit **10** transmits the received command <XXh> to the command register **2** (MR2) in the chip **0** (CP0).

[0250] Upon receipt of the command <XXh> from the command register **2** (MR2), the sequencer **30** in the chip **0** (CP0) initiates the data-out on the plane **2** (PL2) on which the prefetch has been executed.

[0251] Next, as shown in FIG. **15**, the memory controller **300** reserves the prefetch of read data in the normal read executed on the plane **3** (PL3) in the chip **0** (CP0).

[0252] More specifically, upon completion of the data-out on the plane **2** (PL2) in the chip **0** (CP0), the memory controller **300** issues the command <05h>, the address <Ad03>, and the command <E0h> in order to reserve the prefetch on the plane **3** (PL3) in the chip **0** (CP0).

[0253] In the chip **0** (CP0), the input/output circuit **10** receives the command <05h>, the address <Ad03>, and the command <E0h> each issued by the memory controller **300**. The input/output circuit **10** transmits the received command <05h> to the command register **3** (MR3) in the chip **0** (CP0) based on the address <Ad03> and also copies the command <05h> to the command register **3'** (MR3') in the chip **0** (CP0). The input/output circuit **10** transmits the row address RA of the received address <Ad03> to the row address register **3** (RR3) in the chip **0** (CP0) and also copies the row address RA of the address <Ad03> to the row address register **3'** (RR3') in the chip **0** (CP0). The input/output circuit **10** transmits the column address CA of the received address <Ad03> to the column address register **0** (CR0) in the chip **0** (CP0) and also copies the column address CA of the address <Ad03> to the column address register **0'** (CR0') in the chip **0** (CP0). The input/output circuit **10** transmits the received command <E0h> to the command register **3** (MR3) in the chip **0** (CP0) based on the address <Ad03> and also copies the command <E0h> to the command register **3'** (MR3') in the chip **0** (CP0).

[0254] When the row address RA of the address <Ad03> is copied to the row address register **3'** (RR3'), the row address register **3'** (RR3') transmits the row address RA to the row decoder **52D**.

[0255] Upon receipt of the command <E0h> from the command register **3'** (MR3'), the sequencer **30** in the chip **0** (CP0) reserves the prefetch on the plane **3** (PL3). The sequencer **30** then initiates the prefetch. Upon receipt of the command <E0h> with the signal CB03 being in the ready state, the sequencer **30** immediately executes the prefetch on the plane **3** (PL3) in the chip **0** (CP0).

[0256] Upon initiation of the prefetch, the sequencer **30** in the chip **0** (CP0) resets the counter value CNT of the column address counter circuit CC0' to 0. The column address register **0'** (CR0') transmits the first to last column addresses CA to the column decoders **55A** to **55D**. Based on a result of decoding the column address CA of the address <Ad03>, the column decoder **55D** selects a corresponding latch circuit in the data register **54D**. Data in the latch circuit selected in sequence is transmitted to the FIFO circuit **12**.

[0257] Next, the memory controller **300** executes the cache read on the plane **2** (PL2) in the chip **0** (CP0). The particulars of the aforementioned cache read executed in response to the command <00h>, the address <Ad02>, and the command <31h> being issued after issuance of the command <05h>, the address <Ad03>, and the command <E0h> are the same as those of the cache read on the plane **2** (PL2) in the chip **0** (CP0) described above. Upon initiation of the cache read, the sequencer **30** in the chip **0** (CP0) sets the signal CB02 to the busy state. Upon completion of the cache transfer on the plane **2** (PL2) in the chip **0** (CP0), the sequencer **30** sets the signal CB02 to the ready state.

[0258] Next, as shown in FIG. **15**, the memory controller **300** executes the status read on the plane **2** (PL2) in the chip **1** (CP1). The particulars of the aforementioned status read executed in response to the command <78h> and the address <Ad12> being issued after issuance of the command <00h>, the address <Ad02>, and the command <31h> are the same as those of the status read on the plane **2** (PL2) in the chip **1** (CP1) described above.

[0259] Next, upon receipt of the signal CB12 indicative of the ready state from the status register **21**, the memory controller **300** executes the data-out on the plane **2** (PL2) in the chip **1** (CP1).

[0260] More specifically, the memory controller **300** issues the command <XXh> in order to execute the data-out on the plane **2** (PL2) in the chip **1** (CP1).

[0261] In the chip **1** (CP1), the input/output circuit **10** receives the command <XXh> issued by the memory controller **300**. Thereafter, the data-out on the plane **2** (PL2) on which the prefetch has been executed is initiated as with the data-out on the plane **2** (PL2) in the chip **0** (CP0).

[0262] Next, as shown in FIG. **16**, the memory controller **300** reserves the prefetch of read data in the normal read executed on the plane **3** (PL3) in the chip **1** (CP1).

[0263] More specifically, upon completion of the data-out on the plane **2** (PL2) in the chip **1** (CP1), the memory controller **300** issues the command <05h>, the address <Ad13>, and the command <E0h> in order to reserve the prefetch on the plane **3** (PL3) in the chip **1** (CP1).

[0264] In the chip **1** (CP1), the input/output circuit **10** receives the command <05h>, the address <Ad13>, and the command <E0h> each issued by the memory controller **300**. Thereafter, the prefetch on the plane **3** (PL3) in the chip **1** (CP1) is reserved and initiated as with the reservation and execution of the prefetch on the plane **3** (PL3) in the chip **0** (CP0). Upon receipt of the command <E0h> with the signal CB13 being in the ready state, the sequencer **30** immediately executes the prefetch on the plane **3** (PL3) in the chip **1** (CP1).

[0265] Next, the memory controller **300** executes the cache read on the plane **2** (PL2) in the chip **1** (CP1). The particulars of the aforementioned cache read executed in response to the command <00h>, the address <Ad12>, and the command <31h> being issued after issuance of the command <05h>, the address <Ad13>, and the command <E0h> are the same as those of the cache read on the plane **2** (PL2) in the chip **1** (CP1) described above. Upon initiation of the cache read, the sequencer **30** in the chip **1** (CP1) sets the signal CB12 to the busy state. Upon completion of the cache transfer on the plane **2** (PL2) in the chip **1** (CP1), the sequencer **30** sets the signal CB12 to the ready state.

[0266] Next, as shown in FIG. **16**, the memory controller **300** executes the status read on the plane **3** (PL3) in the chip **0** (CP0). The particulars of the aforementioned status read executed in response to the command <78h> and the address <Ad03> being issued after issuance of the command <00h>, the address <Ad12>, and the command <31h> are the same as those of the status read on the plane **3** (PL3) in the chip **0** (CP0) described above.

[0267] Upon receipt of the signal CB03 indicative of the ready state from the status register **21**, the memory controller **300** executes the data-out on the plane **3** (PL3) in the chip **0** (CP0).

[0268] More specifically, the memory controller **300** issues the command <XXh> in order to execute the data-out on the plane **3** (PL3) in the chip **0** (CP0).

[0269] In the chip **0** (CP0), the input/output circuit **10** receives the command <XXh> issued by the memory controller **300**. The input/output circuit **10** transmits the received command <XXh> to the command register **3** (MR3) in the chip **0** (CP0).

[0270] Upon receipt of the command <XXh> from the command register **3** (MR3), the sequencer **30** in the chip **0** (CP0) initiates the data-out on the plane **3** (PL3) on which the prefetch has been executed.

[0271] Next, as shown in FIG. **16**, the memory controller **300** reserves the prefetch of read data in the cache read executed on the plane **0** (PL0) in the chip **0** (CP0).

[0272] More specifically, upon completion of the data-out on the plane **3** (PL3) in the chip **0** (CP0), the memory controller **300** issues the command <05h>, the address <Ad00>, and the command <E0h> in order to reserve the prefetch on the plane **0** (PL0) in the chip **0** (CP0).

[0273] In the chip **0** (CP0), the input/output circuit **10** receives the command <05h>, the address <Ad00>, and the command <E0h> each issued by the memory controller **300**. Thereafter, the prefetch on the plane **0** (PL0) in the chip **0** (CP0) is reserved and initiated as with the reservation and execution of the prefetch on the plane **0** (PL0) in the chip **0** (CP0) described above. Upon receipt of the command <E0h> with the signal CB00 being in the busy state, the sequencer **30** in the chip **0** (CP0) executes the prefetch on the plane **0** (PL0) in the chip **0** (CP0) during a period in



which the signal CB00 is in the busy state.

[0274] Next, the memory controller **300** executes the cache read on the plane **3** (PL3) in the chip **0** (CP0). The particulars of the aforementioned cache read executed in response to the command <00h>, the address <Ad03>, and the command <31h> being issued after issuance of the command <05h>, the address <Ad00>, and the command <E0h> are the same as those of the cache read on the plane **3** (PL3) in the chip **0** (CP0) described above. Upon initiation of the cache read, the sequencer **30** in the chip **0** (CP0) sets the signal CB03 to the busy state. Upon completion of the cache transfer on the plane **3** (PL3) in the chip **0** (CP0), the sequencer **30** sets the signal CB03 to the ready state.

[0275] Next, as shown in FIG. 17, the memory controller **300** executes the status read on the plane **3** (PL3) in the chip **1** (CP1). The particulars of the aforementioned status read executed in response to the command <78h> and the address <Ad13> being issued after issuance of the command <00h>, the address <Ad03>, and the command <31h> are the same as those of the status read on the plane **3** (PL3) in the chip **1** (CP1) described above.

[0276] Next, upon receipt of the signal CB13 indicative of the ready state from the status register **21**, the memory controller **300** executes the data-out on the plane **3** (PL3) in the chip **1** (CP1).

[0277] More specifically, the memory controller **300** issues the command <XXh> in order to execute the data-out on the plane **3** (PL3) in the chip **1** (CP1).

[0278] In the chip **1** (CP1), the input/output circuit **10** receives the command <XXh> issued by the memory controller **300**. Thereafter, the data-out on the plane **3** (PL3) on which the prefetch has been executed is initiated as with the data-out on the plane **3** (PL3) in the chip **0** (CP0).

[0279] Next, as shown in FIG. 17, the memory controller **300** reserves the prefetch of read data in the cache read executed on the plane **0** (PL0) in the chip **1** (CP1).

[0280] More specifically, upon completion of the data-out on the plane **3** (PL3) in the chip **1** (CP1), the memory controller **300** issues the command <05h>, the address <Ad10>, and the command <E0h> in order to reserve the prefetch on the plane **0** (PL0) in the chip **1** (CP1).

[0281] In the chip **1** (CP1), the input/output circuit **10** receives the command <05h>, the address <Ad10>, and the command <E0h> each issued by the memory controller **300**. Thereafter, the prefetch on the plane **0** (PL0) in the chip **1** (CP1) is reserved and initiated as with the reservation and execution of the prefetch on the plane **0** (PL0) in the chip **1** (CP1) described above. Upon receipt of the command <E0h> with the signal CB10 being in the busy state, the sequencer **30** in the chip **1** (CP1) executes the prefetch on the plane **0** (PL0) in the chip **1** (CP1) during a period in which the signal CB10 is in the busy state.

[0282] Next, the memory controller **300** executes the cache read on the plane **3** (PL3) in the chip **1** (CP1). The particulars of the aforementioned cache read executed in response to the command <00h>, the address <Ad13>, and the command <31h> being issued after issuance of the command <05h>, the address <Ad10>, and the command <E0h> are the same as those of the cache read on the plane **3** (PL3) in the chip **1** (CP1) described above. Upon initiation of the cache read, the sequencer **30** in the chip **1** (CP1) sets the signal CB13 to the busy state. Upon completion of the cache transfer on the plane **3** (PL3) in the chip **1** (CP1), the sequencer **30** sets the signal CB13 to the ready state.

[0283] Hereinafter, the command sequences corresponding to a period from E to K are repeated until all of data to be read in the planes **0** to **3** (PL0 to PL3) in the chip **0** (CP0) and the planes **0** to **3** (PL0 to PL3) in the chip **1** (CP1) are data-out.

### 1.3 Advantageous Effect

[0284] FIG. 39 illustrates an operation of a NAND chip according to a comparative example. The NAND chip according to the comparative example accepts, from the memory controller **300**, the command <00h>, the address <Ad00>, and the command <31h> for causing the cache read to execute, and then accepts the command <05h>, the address <Ad00>, and the command <E0h> for causing the data-out to execute. The NAND chip according to the comparative example executes

the prefetch and the data-out by accepting the command “31h” issued by the memory controller **300** and then after transition of the signal CB to the ready state, accepting the command “05h”. [0285] On the other hand, in the memory system **100** according to the present embodiment, the memory controller **300** issues the command <05h>, the address <Ad00>, and the command <E0h> for reserving the prefetch with respect to the semiconductor memory device **200** during a period from when the command <00h>, the address <Ad00>, and the command <31h> for causing the cache read to execute are issued to when the command “XXh” for causing the data-out to execute is issued. The NAND chip according to the present embodiment is capable of accepting the command “05h” regardless of whether the signal CB is in the busy state or the ready state. This enables the NAND chip according to the present embodiment to reserve the prefetch in response to the command “05h” being accepted during a period from acceptance of the command “31h” issued by the memory controller **300** to acceptance of the command “XXh”.

[0286] FIG. **40** illustrates an operation in the case where the command “05h” is accepted with the signal CB being in the busy state in the NAND chip according to the present embodiment. In this case, the sequencer **30** executes the prefetch subsequently to the cache transfer, and after execution of the prefetch, sets the signal CB to the ready state. By this, the data DAT read from the memory cell array **51** to the data register **54** is fetched from the data register **54** to the FIFO circuit **12** before transition of the signal CB to the ready state. This enables the data-out to be executed immediately after the signal CB transitions to the ready state.

[0287] With the configuration according to the present embodiment, the memory controller **300** can issue, with respect to each plane in the chip, the command “05h” during a period from issuance of the command “31h” to issuance of the command “XXh”, regardless of whether the signal CB is in the busy state or the ready state. That is, the prefetch can be reserved during the read operation, so that a period until initiation of the data-out can be shortened as compared to a case in which the prefetch is reserved after completion of the read operation. Accordingly, the speed of operations of the memory system can be enhanced.

[0288] Furthermore, as shown in FIG. **8** to FIG. **17**, in the memory system **100** according to the present embodiment, during a period in which the prefetch is executed in one of the NAND chips included in the semiconductor memory device **200** after issuance of the command <05h>, the address <Ad00>, and the command <E0h> for reserving the prefetch with respect to the one NAND chip, the memory controller **300** can issue a command for instructing, for example, the cache read with respect to the other NAND chips. Accordingly, in the configuration in which the plurality of NAND chips are coupled to the single data bus DB, the efficiency of use of the data bus DB can be enhanced by reducing a time period in which the data bus DB is not used.

## 2. Second Embodiment

[0289] The memory system **100** according to the second embodiment will be described. The memory system **100** according to the present embodiment corresponds to the memory system **100** according to the first embodiment modified by providing two FIFO circuits inside the input/output circuit **10** and providing four column address registers inside the address register **22**. Hereinafter, the following description will in principle concentrate on the features different from the first embodiment.

### 2.1 Configuration of Input/Output Circuit **10**

[0290] A configuration of the input/output circuit **10** will be described with reference to FIG. **18**. FIG. **18** is a block diagram showing a configuration of the NAND chip **0** (CP0) included in the memory system **100** according to the present embodiment, focusing on the input/output circuit **10** and the register **20**. In FIG. **18**, the status register **21** and the voltage generating circuit **40** are omitted.

[0291] The input/output circuit **10** includes the DQ pad **11** and the FIFO circuits **12A** and **12B**. The DQ pad **11** is coupled to data registers **54A** and **54C** via the FIFO circuit **12A**. The DQ pad **11** is further coupled to the data registers **54B** and **54D** via the FIFO circuit **12B**. The FIFO circuit **12A**

and **12B** each have the same configuration as that of the FIFO circuit **12** illustrated in FIG. **6** according to the first embodiment.

## 2.2 Configuration of Register **20**

[0292] A configuration of the register **20** will be described with reference to FIG. **18**.

[0293] The address register **22** corresponds to the address register **22** illustrated in FIG. **6** according to the first embodiment modified to further include a column address register **1** (CR1) and a column address register **1'** (CR1'). The column address register **1** (CR1) has the same configuration as that of the column address register **0** (CR0) illustrated in FIG. **6** according to the first embodiment. The column address register **1'** (CR1') has the same configuration as that of the column address register **0'** (CR0') illustrated in FIG. **6** according to the first embodiment.

[0294] The column address register **0** (CR0) is coupled to the input/output circuit **10** and the planes **0** and **2** (PL0 and PL2), and stores the column address CA of the planes **0** and **2** (PL0 and PL2) received from the input/output circuit **10**. The column address register **0'** (CR0') is coupled to the column address register **0** (CR0) and the planes **0** and **2** (PL0 and PL2), and stores the column address CA received (copied) from the column address register **0** (CR0).

[0295] The column address register **1** (CR1) is coupled to the input/output circuit **10** and the planes **1** and **3** (PL1 and PL3), and stores the column address CA of the planes **1** and **3** (PL1 and PL3) received from the input/output circuit **10**. The column address register **1'** (CR1') is coupled to the column address register **1** (CR1) and the planes **1** and **3** (PL1 and PL3), and stores the column address CA received (copied) from the column address register **1** (CR1).

[0296] The column address register **0** (CR0) transmits the column addresses CA to the column decoders **55A** and **55C**. More specifically, the column address register **0** (CR0) transmits the first column address CA of a plane designated by the column address CA to the column decoders **55A** and **55C**. When the first column address CA is transmitted to the column decoders **55A** and **55C**, the column address counter circuit **CC0** increments the column address CA by only one, and the column address register **0** (CR0) transmits a column address CA subsequent to the first column address CA to the column decoders **55A** and **55C**. When the last column address CA is transmitted to the column decoders **55A** and **55C**, transmission of the column addresses CA to the column decoders **55A** and **55C** is completed. As with the column address register **0** (CR0), the column address register **0'** (CR0') transmits the column addresses CA to the column decoders **55A** and **55C**.

[0297] The column address register **1** (CR1) transmits the column addresses CA to the column decoders **55B** and **55D**. More specifically, the column address register **1** (CR1) transmits the first column address CA of a plane designated by the column address CA to the column decoders **55B** and **55D**. When the first column address CA is transmitted to the column decoders **55B** and **55D**, the column address counter circuit **CC1** increments the column address CA by only one, and the column address register **1** (CR1) transmits a column address CA subsequent to the first column address CA to the column decoders **55B** and **55D**. When the last column address CA is transmitted to the column decoders **55B** and **55D**, transmission of the column addresses CA to the column decoders **55B** and **55D** is completed. As with the column address register **1** (CR1), the column address register **1'** (CR1') transmits the column addresses CA to the column decoders **55B** and **55D**.

## 2.3 Operation

[0298] An operation of the memory system **100** according to the present embodiment will be described with reference to FIG. **19** to FIG. **23**. FIG. **19** to FIG. **23** are each a diagram showing an example of a command sequence in the read operation of the memory system **100** according to the present embodiment. The following will describe an exemplary case in which the signals CEn1 and CEn2 are the same signal (CEn1=CEn2=CEn), and data is repeatedly read from the plane **0** to the plane **3** (PL0 to PL3) in this order in the chip **0** (CP0). FIG. **19** to FIG. **23** each also show the signals CB00 to CB03 of each of the planes in the chip **0** (CP0). The same applies to the case in which data is read from the chip **1** (CP1). The read operation in the present embodiment corresponds to the single plane read.

[0299] First, as shown in FIG. 19, the memory controller 300 executes the normal read on the plane 0 (PL0) in the chip 0 (CP0).

[0300] More specifically, after setting the signal CEn to the “L” level, the memory controller 300 issues the command <00h>, the address <Ad00>, and the command <30h> in order to execute the normal read on the plane 0 (PL0) in the chip 0 (CP0).

[0301] In the chip 0 (CP0), the input/output circuit 10 receives the command <00h>, the address <Ad00>, and the command <30h> each issued by the memory controller 300. The input/output circuit 10 transmits the received command <00h> to the command register 0 (MR0) based on the address <Ad00>. The input/output circuit 10 transmits the row address RA of the received address <Ad00> to the row address register 0 (RR0), and transmits the column address CA of the received address <Ad00> to the column address register 0 (CR0). The input/output circuit 10 transmits the received command <30h> to the command register 0 (MR0) based on the address <Ad00>.

[0302] When the row address RA of the address <Ad00> is stored in the row address register 0 (RR0), the row address register 0 (RR0) transmits the row address RA to the row decoder 52A.

[0303] Upon receipt of the command <30h> from the command register 0 (MR0), the sequencer 30 in the chip 0 (CP0) initiates the normal read on the plane 0 (PL0). The sequencer 30 sets the signal CB00 to the busy state. The signal CB00 is stored in the status register 21. Upon completion of the normal read on the plane 0 (PL0) in the chip 0 (CP0), the sequencer 30 sets the signal CB00 to the ready state. This enables the plane 0 (PL0) in the chip 0 (CP0) to accept a subsequent command.

[0304] Next, the memory controller 300 executes the normal read on the plane 1 (PL1) in the chip 0 (CP0).

[0305] More specifically, after issuance of the command <00h>, the address <Ad00>, and the command <30h>, the memory controller 300 issues the command <00h>, the address <Ad01>, and the command <30h> in order to execute the normal read on the plane 1 (PL1) in the chip 0 (CP0).

[0306] In the chip 0 (CP0), the input/output circuit 10 receives the command <00h>, the address <Ad01>, and the command <30h> each issued by the memory controller 300. The input/output circuit 10 transmits the received command <00h> to the command register 1 (MR1) based on the address <Ad01>. The input/output circuit 10 transmits the row address RA of the received address <Ad01> to the row address register 1 (RR1), and transmits the column address CA of the received address <Ad01> to the column address register 1 (CR1). The input/output circuit 10 transmits the received command <30h> to the command register 1 (MR1) based on the address <Ad01>.

[0307] When the row address RA of the address <Ad01> is stored in the row address register 1 (RR1), the row address register 1 (RR1) transmits the row address RA to the row decoder 52B.

[0308] Upon receipt of the command <30h> from the command register 1 (MR1), the sequencer 30 in the chip 0 (CP0) initiates the normal read on the plane 1 (PL1). The sequencer 30 sets the signal CB01 to the busy state. The signal CB01 is stored in the status register 21. Upon completion of the normal read on the plane 1 (PL1) in the chip 0 (CP0), the sequencer 30 sets the signal CB01 to the ready state. This enables the plane 1 (PL1) in the chip 0 (CP0) to accept a subsequent command.

[0309] Next, the memory controller 300 executes the normal read on the plane 2 (PL2) in the chip 0 (CP0).

[0310] More specifically, after issuance of the command <00h>, the address <Ad01>, and the command <30h>, the memory controller 300 issues the command <00h>, the address <Ad02>, and the command <30h> in order to execute the normal read on the plane 2 (PL2) in the chip 0 (CP0).

[0311] In the chip 0 (CP0), the input/output circuit 10 receives the command <00h>, the address <Ad02>, and the command <30h> each issued by the memory controller 300. The input/output circuit 10 transmits the received command <00h> to the command register 2 (MR2) based on the address <Ad02>. The input/output circuit 10 transmits the row address RA of the received address <Ad02> to the row address register 2 (RR2), and transmits the column address CA of the received address <Ad02> to the column address register 0 (CR0). The input/output circuit 10 transmits the received command <30h> to the command register 2 (MR2) based on the address <Ad02>.

[0312] When the row address RA of the address <Ad02> is stored in the row address register 2 (RR2), the row address register 2 (RR2) transmits the row address RA to the row decoder 52C.

[0313] Upon receipt of the command <30h> from the command register 2 (MR2), the sequencer 30 in the chip 0 (CP0) initiates the normal read on the plane 2 (PL2). The sequencer 30 sets the signal CB02 to the busy state. The signal CB02 is stored in the status register 21. Upon completion of the normal read on the plane 2 (PL2) in the chip 0 (CP0), the sequencer 30 sets the signal CB02 to the ready state. This enables the plane 2 (PL2) in the chip 0 (CP0) to accept a subsequent command.

[0314] Next, the memory controller 300 executes the normal read on the plane 3 (PL3) in the chip 0 (CP0).

[0315] More specifically, after issuance of the command <00h>, the address <Ad02>, and the command <30h>, the memory controller 300 issues the command <00h>, the address <Ad03>, and the command <30h> in order to execute the normal read on the plane 3 (PL3) in the chip 0 (CP0).

[0316] In the chip 0 (CP0), the input/output circuit 10 receives the command <00h>, the address <Ad03>, and the command <30h> each issued by the memory controller 300. The input/output circuit 10 transmits the received command <00h> to the command register 3 (MR3) based on the address <Ad03>. The input/output circuit 10 transmits the row address RA of the received address <Ad03> to the row address register 3 (RR3), and transmits the column address CA of the received address <Ad03> to the column address register 1 (CR1). The input/output circuit 10 transmits the received command <30h> to the command register 3 (MR3) based on the address <Ad03>.

[0317] When the row address RA of the address <Ad03> is stored in the row address register 3 (RR3), the row address register 3 (RR3) transmits the row address RA to the row decoder 52D.

[0318] Upon receipt of the command <30h> from the command register 3 (MR3), the sequencer 30 in the chip 0 (CP0) initiates the normal read on the plane 3 (PL3). The sequencer 30 sets the signal CB03 to the busy state. The signal CB03 is stored in the status register 21. Upon completion of the normal read on the plane 3 (PL3) in the chip 0 (CP0), the sequencer 30 sets the signal CB03 to the ready state. This enables the plane 3 (PL3) in the chip 0 (CP0) to accept a subsequent command.

[0319] Next, as shown in FIG. 20, the memory controller 300 executes the status read on the plane 0 (PL0) in the chip 0 (CP0). The particulars of the aforementioned status read executed in response to the command <78h> and the address <Ad00> being issued after issuance of the command <00h>, the address <Ad03>, and the command <30h> are the same as those of the first embodiment.

[0320] Next, upon receipt of the signal CB00 indicative of the ready state from the status register 21, the memory controller 300 executes the cache read on the plane 0 (PL0) in the chip 0 (CP0).

[0321] More specifically, the memory controller 300 issues the command <00h>, the address <Ad00>, and the command <31h> in order to execute the cache read on the plane 0 (PL0) in the chip 0 (CP0).

[0322] In the chip 0 (CP0), the input/output circuit 10 receives the command <00h>, the address <Ad00>, and the command <31h> each issued by the memory controller 300. Thereafter, the cache read on the plane 0 (PL0) in the chip 0 (CP0) is initiated as with the normal read on the plane 0 (PL0) in the chip 0 (CP0) described above. The sequencer 30 in the chip 0 (CP0) sets the signal CB00 to the busy state.

[0323] Next, the memory controller 300 reserves the prefetch of read data in the normal read executed on the plane 0 (PL0) in the chip 0 (CP0).

[0324] More specifically, during a period in which the command <00h>, the address <Ad00>, and the command <31h> are issued and the cache read is executed (that is, a period in which the signal CB00 is in the busy state), the memory controller 300 issues the command <05h>, the address <Ad00>, and the command <E0h> in order to reserve the prefetch on the plane 0 (PL0) in the chip 0 (CP0).

[0325] In the chip 0 (CP0), the input/output circuit 10 receives the command <05h>, the address <Ad00>, and the command <E0h> each issued by the memory controller 300. The input/output

circuit **10** transmits the received command <05h> to the command register **0** (MR0) based on the address <Ad00> and also copies the command <05h> to the command register **0'** (MR0'). The input/output circuit **10** transmits the row address RA of the received address <Ad00> to the row address register **0** (RR0) and also copies the row address RA of the address <Ad00> to the row address register **0'** (RR0'). The input/output circuit **10** transmits the column address CA of the received address <Ad00> to the column address register **0** (CR0) and also copies the column address CA of the address <Ad00> to the column address register **0'** (CR0'). The input/output circuit **10** transmits the received command <E0h> to the command register **0** (MR0) based on the address <Ad00> and also copies the command <E0h> to the command register **0'** (MR0').

[0326] When the row address RA of the address <Ad00> is copied to the row address register **0'** (RR0'), the row address register **0'** (RR0') transmits the row address RA to the row decoder **52A**.

[0327] Upon receipt of the command <E0h> from the command register **0'** (MR0'), the sequencer **30** in the chip **0** (CP0) reserves the prefetch on the plane **0** (PL0). The sequencer **30** then initiates the prefetch. Upon receipt of the command <E0h> with the signal CB00 being in the busy state, the sequencer **30** executes the prefetch on the plane **0** (PL0) in the chip **0** (CP0) during a period in which the signal CB00 is in the busy state. More specifically, upon receipt of the command <E0h> with the signal CB00 being in the busy state, the sequencer **30** executes the prefetch subsequently to the cache transfer.

[0328] Upon initiation of the prefetch, the sequencer **30** in the chip **0** (CP0) resets the counter value CNT of the column address counter circuit CC0' to 0. The column address register **0'** (CR0') transmits the first to last column addresses CA to the column decoders **55A** and **55C**. Based on a result of decoding the column address CA of the address <Ad00>, the column decoder **55A** selects a corresponding latch circuit in the data register **54A**. Data in the latch circuit selected in sequence is transmitted to the FIFO circuit **12A**. Upon completion of the prefetch, the sequencer **30** sets the signal CB00 to the ready state.

[0329] Next, as shown in FIG. **20**, the memory controller **300** executes the status read on the plane **1** (PL1) in the chip **0** (CP0). The particulars of the aforementioned status read executed in response to the command <78h> and the address <Ad01> being issued after issuance of the command <05h>, the address <Ad00>, and the command <E0h> are the same as those of the first embodiment.

[0330] Next, upon receipt of the signal CB01 indicative of the ready state from the status register **21**, the memory controller **300** executes the cache read on the plane **1** (PL1) in the chip **0** (CP0).

[0331] More specifically, the memory controller **300** issues the command <00h>, the address <Ad01>, and the command <31h> in order to execute the cache read on the plane **1** (PL1) in the chip **0** (CP0).

[0332] In the chip **0** (CP0), the input/output circuit **10** receives the command <00h>, the address <Ad01>, and the command <31h> each issued by the memory controller **300**. Thereafter, the cache read on the plane **1** (PL1) in the chip **0** (CP0) is initiated as with the normal read on the plane **1** (PL1) in the chip **0** (CP0) described above. The sequencer **30** in the chip **0** (CP0) sets the signal CB01 to the busy state.

[0333] Next, the memory controller **300** reserves the prefetch of read data in the normal read executed on the plane **1** (PL1) in the chip **0** (CP0).

[0334] More specifically, during a period in which the command <00h>, the address <Ad01>, and the command <31h> are issued and the cache read is executed (that is, a period in which the signal CB01 is in the busy state), the memory controller **300** issues the command <05h>, the address <Ad01>, and the command <Eh> in order to reserve the prefetch on the plane **1** (PL1) in the chip **0** (CP0).

[0335] In the chip **0** (CP0), the input/output circuit **10** receives the command <05h>, the address <Ad01>, and the command <E0h> each issued by the memory controller **300**. The input/output circuit **10** transmits the received command <05h> to the command register **1** (MR1) based on the

address <Ad01> and also copies the command <05h> to the command register **1'** (MR1'). The input/output circuit **10** transmits the row address RA of the received address <Ad01> to the row address register **1** (RR1) and also copies the row address RA of the address <Ad01> to the row address register **1'** (RR1'). The input/output circuit **10** transmits the column address CA of the received address <Ad01> to the column address register **1** (CR1) and also copies the column address CA of the address <Ad01> to the column address register **1'** (CR1'). The input/output circuit **10** transmits the received command <E0h> to the command register **1** (MR1) based on the address <Ad01> and also copies the command <E0h> to the command register **1'** (MR1').

[0336] When the row address RA of the address <Ad01> is copied to the row address register **1'** (RR1'), the row address register **1'** (RR1') transmits the row address RA to the row decoder **52B**.

[0337] Upon receipt of the command <E0h> from the command register **1'** (MR1'), the sequencer **30** in the chip **0** (CP0) reserves the prefetch on the plane **1** (PL1). The sequencer **30** then initiates the prefetch. Upon receipt of the command <E0h> with the signal CB01 being in the busy state, the sequencer **30** executes the prefetch on the plane **1** (PL1) in the chip **0** (CP0) during a period in which the signal CB01 is in the busy state. More specifically, upon receipt of the command <E0h> with the signal CB01 being in the busy state, the sequencer **30** executes the prefetch subsequently to the cache transfer.

[0338] Upon initiation of the prefetch, the sequencer **30** in the chip **0** (CP0) resets the counter value CNT of the column address counter circuit CC1' to 0. The column address register **1'** (CR1') transmits the first to last column addresses CA to the column decoders **55B** and **55D**. Based on a result of decoding the column address CA of the address <Ad01>, the column decoder **55B** selects a corresponding latch circuit in the data register **54B**. Data in the latch circuit selected in sequence is transmitted to the FIFO circuit **12B**. Upon completion of the prefetch, the sequencer **30** sets the signal CB01 to the ready state.

[0339] Next, as shown in FIG. **20**, the memory controller **300** executes the status read on the plane **2** (PL2) in the chip **0** (CP0). The particulars of the aforementioned status read executed in response to the command <78h> and the address <Ad02> being issued after issuance of the command <05h>, the address <Ad01>, and the command <E0h> are the same as those of the first embodiment.

[0340] Next, upon receipt of the signal CB02 indicative of the ready state from the status register **21**, the memory controller **300** executes the cache read on the plane **2** (PL2) in the chip **0** (CP0).

[0341] More specifically, the memory controller **300** issues the command <00h>, the address <Ad02>, and the command <31h> in order to execute the cache read on the plane **2** (PL2) in the chip **0** (CP0).

[0342] In the chip **0** (CP0), the input/output circuit **10** receives the command <00h>, the address <Ad02>, and the command <31h> each issued by the memory controller **300**. Thereafter, the cache read on the plane **2** (PL2) in the chip **0** (CP0) is initiated as with the normal read on the plane **2** (PL2) in the chip **0** (CP0) described above. The sequencer **30** in the chip **0** (CP0) sets the signal CB02 to the busy state. Upon completion of the cache transfer on the plane **2** (PL2) in the chip **0** (CP0), the sequencer **30** sets the signal CB02 to the ready state.

[0343] Next, as shown in FIG. **21**, the memory controller **300** executes the status read on the plane **3** (PL3) in the chip **0** (CP0). The particulars of the aforementioned status read executed in response to the command <78h> and the address <Ad03> being issued after issuance of the command <00h>, the address <Ad02>, and the command <31h> are the same as those of the first embodiment.

[0344] Upon receipt of the signal CB03 indicative of the ready state from the status register **21**, the memory controller **300** executes the cache read on the plane **3** (PL3) in the chip **0** (CP0).

[0345] More specifically, the memory controller **300** issues the command <00h>, the address <Ad03>, and the command <31h> in order to execute the cache read on the plane **3** (PL3) in the chip **0** (CP0).

[0346] In the chip **0** (CP0), the input/output circuit **10** receives the command <00h>, the address <Ad03>, and the command <31h> each issued by the memory controller **300**. Thereafter, the cache read on the plane **3** (PL3) in the chip **0** (CP0) is initiated as with the normal read on the plane **3** (PL3) in the chip **0** (CP0) described above. The sequencer **30** in the chip **0** (CP0) sets the signal CB03 to the busy state. Upon completion of the cache transfer on the plane **3** (PL3) in the chip **0** (CP0), the sequencer **30** sets the signal CB03 to the ready state.

[0347] Next, as shown in FIG. **21**, the memory controller **300** executes the status read on the plane **0** (PL0) in the chip **0** (CP0). The particulars of the aforementioned status read executed in response to the command <78h> and the address <Ad00> being issued after issuance of the command <00h>, the address <Ad03>, and the command <31h> are the same as those of the first embodiment.

[0348] Next, upon receipt of the signal CB00 indicative of the ready state from the status register **21**, the memory controller **300** executes the data-out on the plane **0** (PL0) in the chip **0** (CP0). The particulars of the aforementioned data-out executed in response to issuance of the command <XXh> after the memory controller **300** receives the signal CB00 indicative of the ready state from the status register **21** (data-out on the plane **0** (PL0) on which the prefetch has been executed) are the same as those of the first embodiment.

[0349] Next, the memory controller **300** reserves the prefetch of read data in the normal read executed on the plane **2** (PL2) in the chip **0** (CP0).

[0350] More specifically, upon completion of the data-out on the plane **0** (PL0) in the chip **0** (CP0), the memory controller **300** issues the command <05h>, the address <Ad02>, and the command <E0h> in order to reserve the prefetch on the plane **2** (PL2) in the chip **0** (CP0).

[0351] In the chip **0** (CP0), the input/output circuit **10** receives the command <05h>, the address <Ad02>, and the command <E0h> each issued by the memory controller **300**. The input/output circuit **10** transmits the received command <05h> to the command register **2** (MR2) based on the address <Ad02> and also copies the command <05h> to the command register **2'** (MR2'). The input/output circuit **10** transmits the row address RA of the received address <Ad02> to the row address register **2** (RR2) and also copies the row address RA of the address <Ad02> to the row address register **2'** (RR2'). The input/output circuit **10** transmits the column address CA of the received address <Ad02> to the column address register **0** (CR0) and also copies the column address CA of the address <Ad02> to the column address register **0'** (CR0'). The input/output circuit **10** transmits the received command <E0h> to the command register **2** (MR2) based on the address <Ad02> and also copies the command <E0h> to the command register **2'** (MR2').

[0352] When the row address RA of the address <Ad02> is copied to the row address register **2'** (RR2'), the row address register **2'** (RR2') transmits the row address RA to the row decoder **52C**.

[0353] Upon receipt of the command <E0h> from the command register **2'** (MR2'), the sequencer **30** in the chip **0** (CP0) reserves the prefetch on the plane **2** (PL2). The sequencer **30** then initiates the prefetch. Upon receipt of the command <E0h> with the signal CB02 being in the ready state, the sequencer **30** immediately executes the prefetch on the plane **2** (PL2) in the chip **0** (CP0).

[0354] Upon initiation of the prefetch, the sequencer **30** in the chip **0** (CP0) resets the counter value CNT of the column address counter circuit CC0' to 0. The column address register **0'** (CR0') transmits the first to last column addresses CA to the column decoders **55A** and **55C**. Based on a result of decoding the column address CA of the address <Ad02>, the column decoder **55C** selects a corresponding latch circuit in the data register **54C**. Data in the latch circuit selected in sequence is transmitted to the FIFO circuit **12A**.

[0355] Next, the memory controller **300** executes the cache read on the plane **0** (PL0) in the chip **0** (CP0). The particulars of the aforementioned cache read executed in response to the command <00h>, the address <Ad00>, and the command <31h> being issued after issuance of the command <05h>, the address <Ad02>, and the command <E0h> are the same as those of the cache read on the plane **0** (PL0) in the chip **0** (CP0) described above. Upon initiation of the cache read, the



sequencer **30** in the chip **0** (CP0) sets the signal CB00 to the busy state. Upon completion of the cache transfer on the plane **0** (PL0) in the chip **0** (CP0), the sequencer **30** sets the signal CB00 to the ready state.

[0356] Next, as shown in FIG. 22, the memory controller **300** executes the status read on the plane **1** (PL1) in the chip **0** (CP0). The particulars of the aforementioned status read executed in response to the command <78h> and the address <Ad01> being issued after issuance of the command <00h>, the address <Ad00>, and the command <31h> are the same as those of the first embodiment.

[0357] Next, upon receipt of the signal CB01 indicative of the ready state from the status register **21**, the memory controller **300** executes the data-out on the plane **1** (PL1) in the chip **0** (CP0). The particulars of the aforementioned data-out executed in response to issuance of the command <XXh> after the memory controller **300** receives the signal CB01 indicative of the ready state from the status register **21** (data-out on the plane **1** (PL1) on which the prefetch has been executed) are the same as those of the first embodiment.

[0358] Next, the memory controller **300** reserves the prefetch of read data in the normal read executed on the plane **3** (PL3) in the chip **0** (CP0).

[0359] More specifically, Upon completion of the data-out on the plane **1** (PL1) in the chip **0** (CP0), the memory controller **300** issues the command <05h>, the address <Ad03>, and the command <E0h> in order to reserve the prefetch on the plane **3** (PL3) in the chip **0** (CP0).

[0360] In the chip **0** (CP0), the input/output circuit **10** receives the command <05h>, the address <Ad03>, and the command <E0h> each issued by the memory controller **300**. The input/output circuit **10** transmits the received command <05h> to the command register **3** (MR3) based on the address <Ad03> and also copies the command <05h> to the command register **3'** (MR3'). The input/output circuit **10** transmits the row address RA of the received address <Ad03> to the row address register **3** (RR3) and also copies the row address RA of the address <Ad03> to the row address register **3'** (RR3'). The input/output circuit **10** transmits the column address CA of the received address <Ad03> to the column address register **1** (CR1) and also copies the column address CA of the address <Ad03> to the column address register **1'** (CR1'). The input/output circuit **10** transmits the received command <E0h> to the command register **3** (MR3) based on the address <Ad03> and also copies the command <E0h> to the command register **3'** (MR3').

[0361] When the row address RA of the address <Ad03> is copied to the row address register **3'** (RR3'), the row address register **3'** (RR3') transmits the row address RA to the row decoder **52D**.

[0362] Upon receipt of the command <E0h> from the command register **3'** (MR3'), the sequencer **30** in the chip **0** (CP0) reserves the prefetch on the plane **3** (PL3). The sequencer **30** then initiates the prefetch. Upon receipt of the command <E0h> with the signal CB03 being in the ready state, the sequencer **30** immediately executes the prefetch on the plane **3** (PL3) in the chip **0** (CP0).

[0363] Upon initiation of the prefetch, the sequencer **30** in the chip **0** (CP0) resets the counter value CNT of the column address counter circuit CC1' to 0. The column address register **1'** (CR1') transmits the first to last column addresses CA to the column decoders **55B** and **55D**. Based on a result of decoding the column address CA of the address <Ad03>, the column decoder **55D** selects a corresponding latch circuit in the data register **54D**. Data in the latch circuit selected in sequence is transmitted to the FIFO circuit **12B**.

[0364] Next, the memory controller **300** executes the cache read on the plane **1** (PL1) in the chip **0** (CP0). The particulars of the aforementioned cache read executed in response to the command <00h>, the address <Ad01>, and the command <31h> being issued after issuance of the command <05h>, the address <Ad03>, and the command <E0h> are the same as those of the cache read on the plane **1** (PL1) in the chip **0** (CP0) described above. Upon initiation of the cache read, the sequencer **30** in the chip **0** (CP0) sets the signal CB01 to the busy state. Upon completion of the cache transfer on the plane **1** (PL1) in the chip **0** (CP0), the sequencer **30** sets the signal CB01 to the ready state.

[0365] Next, as shown in FIG. 22, the memory controller **300** executes the status read on the plane **2** (PL2) in the chip **0** (CP0). The particulars of the aforementioned status read executed in response to the command <78h> and the address <Ad02> being issued after issuance of the command <00h>, the address <Ad01>, and the command <31h> are the same as those of the first embodiment.

[0366] Upon receipt of the signal CB02 indicative of the ready state from the status register **21**, the memory controller **300** executes the data-out on the plane **2** (PL2) in the chip **0** (CP0). The particulars of the aforementioned data-out executed in response to issuance of the command <XXh> after the memory controller **300** receives the signal CB02 indicative of the ready state from the status register **21** (data-out on the plane **2** (PL2) on which the prefetch has been executed) are the same as those of the first embodiment.

[0367] Next, as shown in FIG. 23, the memory controller **300** reserves the prefetch of read data in the cache read executed on the plane **0** (PL0) in the chip **0** (CP0).

[0368] More specifically, upon completion of the data-out on the plane **2** (PL2) in the chip **0** (CP0), the memory controller **300** issues the command <05h>, the address <Ad00>, and the command <E0h> in order to reserve the prefetch on the plane **0** (PL0) in the chip **0** (CP0).

[0369] In the chip **0** (CP0), the input/output circuit **10** receives the command <05h>, the address <Ad00>, and the command <E0h> each issued by the memory controller **300**. Thereafter, the prefetch on the plane **0** (PL0) in the chip **0** (CP0) is reserved and initiated as with the reservation and execution of the prefetch on the plane **0** (PL0) in the chip **0** (CP0) described above. Upon receipt of the command <E0h> with the signal CB00 being in the busy state, the sequencer **30** in the chip **0** (CP0) executes the prefetch on the plane **0** (PL0) in the chip **0** (CP0) during a period in which the signal CB00 is in the busy state.

[0370] Next, the memory controller **300** executes the cache read on the plane **2** (PL2) in the chip **0** (CP0). The particulars of the aforementioned cache read executed in response to the command <00h>, the address <Ad02>, and the command <31h> being issued after issuance of the command <05h>, the address <Ad00>, and the command <E0h> are the same as those of the cache read on the plane **2** (PL2) in the chip **0** (CP0) described above. Upon initiation of the cache read, the sequencer **30** in the chip **0** (CP0) sets the signal CB02 to the busy state. Upon completion of the cache transfer on the plane **2** (PL2) in the chip **0** (CP0), the sequencer **30** sets the signal CB02 to the ready state.

[0371] Next, as shown in FIG. 23, the memory controller **300** executes the status read on the plane **3** (PL3) in the chip **0** (CP0). The particulars of the aforementioned status read executed in response to the command <78h> and the address <Ad03> being issued after issuance of the command <00h>, the address <Ad02>, and the command <31h> are the same as those of the first embodiment.

[0372] Next, upon receipt of the signal CB03 indicative of the ready state from the status register **21**, the memory controller **300** executes the data-out on the plane **3** (PL3) in the chip **0** (CP0). The particulars of the aforementioned data-out executed in response to issuance of the command <XXh> after the memory controller **300** receives the signal CB03 indicative of the ready state from the status register **21** (data-out on the plane **3** (PL3) on which the prefetch has been executed) are the same as those of the first embodiment.

[0373] Next, the memory controller **300** reserves the prefetch of read data in the cache read executed on the plane **1** (PL1) in the chip **0** (CP0).

[0374] More specifically, upon completion of the data-out on the plane **3** (PL3) in the chip **0** (CP0), the memory controller **300** issues the command <05h>, the address <Ad01>, and the command <E0h> in order to reserve the prefetch of the plane **1** (PL1) in the chip **0** (CP0).

[0375] In the chip **0** (CP0), the input/output circuit **10** receives the command <05h>, the address <Ad01>, and the command <E0h> each issued by the memory controller **300**. Thereafter, the prefetch on the plane **1** (PL1) in the chip **0** (CP0) is reserved and initiated as with the reservation

and execution of the prefetch on the plane **1** (PL**1**) in the chip **0** (CP**0**) described above. Upon receipt of the command <E0h> with the signal CB**01** being in the busy state, the sequencer **30** in the chip **0** (CP**0**) executes the prefetch on the plane **1** (PL**1**) in the chip **0** (CP**0**) during a period in which the signal CB**01** is in the busy state.

[0376] Next, the memory controller **300** executes the cache read on the plane **3** (PL**3**) in the chip **0** (CP**0**). The particulars of the aforementioned cache read executed in response to the command <00h>, the address <Ad03>, and the command <31h> being issued after issuance of the command <05h>, the address <Ad01>, and the command <E0h> are the same as those of the cache read on the plane **3** (PL**3**) in the chip **0** (CP**0**) described above. Upon initiation of the cache read, the sequencer **30** in the chip **0** (CP**0**) sets the signal CB**03** to the busy state. Upon completion of the cache transfer on the plane **3** (PL**3**) in the chip **0** (CP**0**), the sequencer **30** sets the signal CB**03** to the ready state.

[0377] Hereinafter, the command sequences corresponding to a period from C to F are repeated until all of data to be read in the planes **0** to **3** (PL**0** to PL**3**) in the chip **0** (CP**0**) are data-out.

## 2.4 Advantageous Effect

[0378] With the configuration according to the present embodiment, as with the first embodiment, the prefetch can be reserved during the read operation, so that a period until initiation of the data-out can be shortened as compared to a case in which the prefetch is reserved after completion of the read operation. Accordingly, the speed of operations of the memory system can be enhanced.

## 3. Third Embodiment

[0379] The memory system **100** according to a third embodiment will be described. The memory system **100** according to the present embodiment corresponds to the memory system **100** according to the first embodiment modified by providing a bus switch BSW in the NAND chip **0** (CP**0**). Hereinafter, the following description will in principle concentrate on the features different from the first embodiment.

### 3.1 Configuration of Input/Output Circuit **10**

[0380] A configuration of the input/output circuit **10** will be described with reference to FIG. **24**. FIG. **24** is a block diagram showing a configuration of the NAND chip **0** (CP**0**) included in the memory system **100** according to the present embodiment, focusing on the input/output circuit **10** and the register **20**. In FIG. **24**, the status register **21** and the voltage generating circuit **40** are omitted.

[0381] The NAND chip **0** (CP**0**) includes the bus switch BSW. The bus switch BSW is coupled to the FIFO circuit **12**. The bus switch BSW can be coupled to the data registers **54A** to **54D**. The bus switch BSW is configured in such a manner that one of the data registers **54A** to **54D** is selectively coupled thereto.

### 3.2 Overview of Data Flow

[0382] An overview of data flow in the read operation of the memory system **100** according to the present embodiment will be described with reference to FIG. **25**. The following will describe an exemplary case in which n-bit data DAT is read from the memory cell arrays **51A** to **51D** to the data registers **54A** to **54D**, respectively. FIG. **25** omits a period in which the command CMD and the address ADD issued by the memory controller **300** are transmitted from the memory controller **300** to the DQ pad **11**.

[0383] First, data DAT of n bits (hereinafter referred to as bits 1 to n, which respectively correspond to 1 to n in FIG. **25**) is stored in the data register **54A** in the plane **0** (PL**0**). The bits 1 to n each correspond, in order from the bit 1, to a count-up of the counter value CNT of the column address counter circuit CC**0**.

[0384] In this state, the bus switch BSW is coupled to the data register **54A**. In the plane **0** (PL**0**), the prefetch is then initiated. The bits 1 to n are transferred in order from the bit 1 from the data register **54A** to the FIFO circuit **12**.

[0385] Data of the bits 1 to n transferred to the FIFO circuit **12** is data-out in order of transfer via

the DQ pad **11**. Upon completion of the transfer of data from the data register **54A** to the FIFO circuit **12**, the bus switch BSW switches its coupling from the data register **54A** to the data register **54B**. In the plane **1** (PL**1**), the prefetch is then initiated. Data DAT of  $n$  bits stored in the data register **54B** (hereinafter referred to as bits  $n+1$  to  $2n$ , which respectively correspond to  $n+1$  to  $2n$  in FIG. 25) is transferred in order from the bit  $n+1$  from the data register **54B** to the FIFO circuit **12**.

[0386] Data of the bits  $n+1$  to  $2n$  transferred to the FIFO circuit **12** is data-out in order of transfer via the DQ pad **11**.

[0387] Upon completion of the transfer of data from the data register **54B** to the FIFO circuit **12**, the bus switch BSW switches its coupling from the data register **54B** to the data register **54C**. In the plane **2** (PL**2**), the prefetch is then initiated. Data DAT of  $n$  bits stored in the data register **54C** (hereinafter referred to as bits  $2n+1$  to  $3n$ , which respectively correspond to  $2n+1$  to  $3n$  in FIG. 25) is transferred in order from the bit  $2n+1$  from the data register **54C** to the FIFO circuit **12**.

[0388] Data of the bits  $2n+1$  to  $3n$  transferred to the FIFO circuit **12** is data-out in order of transfer via the DQ pad **11**.

[0389] Upon completion of the transfer of data from the data register **54C** to the FIFO circuit **12**, the bus switch BSW switches its coupling from the data register **54C** to the data register **54D**. In the plane **3** (PL**3**), the prefetch is then initiated. Data DAT of  $n$  bits stored in the data register **54D** (hereinafter referred to as bits  $3n+1$  to  $4n$ , which respectively correspond to  $3n+1$  to  $4n$  in FIG. 25) is transferred in order from the bit  $3n+1$  from the data register **54D** to the FIFO circuit **12**.

[0390] Data of the bits  $3n+1$  to  $4n$  transferred to the FIFO circuit **12** is data-out in order of transfer via the DQ pad **11**.

[0391] The configuration from the bus switch BSW to the FIFO circuit **12** may be composed of a wave pipeline and the FIFO circuit **12**.

### 3.3 Operation

[0392] An operation of the memory system **100** according to the present embodiment will be described with reference to FIG. 26 to FIG. 29. FIG. 26 to FIG. 29 are each a diagram showing an example of a command sequence in the read operation of the memory system **100** according to the present embodiment. The following will describe an exemplary case in which the signals CEn**1** and CEn**2** are the same signal (CEn**1**=CEn**2**=CEn), and data is repeatedly read from the plane **0** to the plane **3** (PL**0** to PL**3**) in this order in the chip **0** (CP**0**). FIG. 26 to FIG. 29 each also show the signals CB**00** to CB**03** of each of the planes in the chip **0** (CP**0**). The same applies to the case in which data is read from the chip **1** (CP**1**).

[0393] The read operation in the present embodiment corresponds to a multi-plane read.

Throughout this description, the “multi-plane read” means an operation in which the data DAT are simultaneously read from the respective planes in a target chip.

[0394] First, as shown in FIG. 26, the memory controller **300** executes the normal read on the plane **0** (PL**0**) in the chip **0** (CP**0**).

[0395] More specifically, after setting the signal CEn to the “L” level, the memory controller **300** issues the command <00h>, the address <Ad00>, and a command <32h> in order to execute the normal read on the plane **0** (PL**0**) in the chip **0** (CP**0**). The command “32h” is a command for causing the normal read in the multi-plane read to execute.

[0396] In the chip **0** (CP**0**), the input/output circuit **10** receives the command <00h>, the address <Ad00>, and the command <32h> each issued by the memory controller **300**. The input/output circuit **10** transmits the received command <00h> to the command register **0** (MR**0**) based on the address <Ad00>. The input/output circuit **10** transmits the row address RA of the received address <Ad00> to the row address register **0** (RR**0**), and transmits the column address CA of the received address <Ad00> to the column address register **0** (CR**0**). The input/output circuit **10** transmits the received command <32h> to the command register **0** (MR**0**) based on the address <Ad00>.

[0397] When the row address RA of the address <Ad00> is stored in the row address register **0**

(RR0), the row address register **0** (RR0) transmits the row address RA to the row decoder **52A**.

[0398] Next, the memory controller **300** executes the normal read on the plane **1** (PL1) in the chip **0** (CP0).

[0399] More specifically, after issuance of the command <00h>, the address <Ad00>, and the command <32h>, the memory controller **300** issues the command <00h>, the address <Ad01>, and the command <32h> in order to execute the normal read on the plane **1** (PL1) in the chip **0** (CP0).

[0400] In the chip **0** (CP0), the input/output circuit **10** receives the command <00h>, the address <Ad01>, and the command <32h> each issued by the memory controller **300**. The input/output circuit **10** transmits the received command <00h> to the command register **1** (MR1) based on the address <Ad01>. The input/output circuit **10** transmits the row address RA of the received address <Ad01> to the row address register **1** (RR1), and transmits the column address CA of the received address <Ad01> to the column address register **0** (CR0). The input/output circuit **10** transmits the received command <32h> to the command register **1** (MR1) based on the address <Ad01>.

[0401] When the row address RA of the address <Ad01> is stored in the row address register **1** (RR1), the row address register **1** (RR1) transmits the row address RA to the row decoder **52B**.

[0402] Next, the memory controller **300** executes the normal read on the plane **2** (PL2) in the chip **0** (CP0).

[0403] More specifically, after issuance of the command <00h>, the address <Ad01>, and the command <32h>, the memory controller **300** issues the command <00h>, the address <Ad02>, and the command <32h> in order to execute the normal read on the plane **2** (PL2) in the chip **0** (CP0).

[0404] In the chip **0** (CP0), the input/output circuit **10** receives the command <00h>, the address <Ad02>, and the command <32h> each issued by the memory controller **300**. The input/output circuit **10** transmits the received command <00h> to the command register **2** (MR2) based on the address <Ad02>. The input/output circuit **10** transmits the row address RA of the received address <Ad02> to the row address register **2** (RR2), and transmits the column address CA of the received address <Ad02> to the column address register **0** (CR0). The input/output circuit **10** transmits the received command <32h> to the command register **2** (MR2) based on the address <Ad02>.

[0405] When the row address RA of the address <Ad02> is stored in the row address register **2** (RR2), the row address register **2** (RR2) transmits the row address RA to the row decoder **52C**.

[0406] Next, the memory controller **300** executes the normal read on the plane **3** (PL3) in the chip **0** (CP0).

[0407] More specifically, after issuance of the command <00h>, the address <Ad02>, and the command <32h>, the memory controller **300** issues the command <00h>, the address <Ad03>, and the command <30h> in order to execute the normal read on the plane **3** (PL3) in the chip **0** (CP0).

[0408] In the chip **0** (CP0), the input/output circuit **10** receives the command <00h>, the address <Ad03>, and the command <30h> each issued by the memory controller **300**. The input/output circuit **10** transmits the received command <00h> to the command register **3** (MR3) based on the address <Ad03>. The input/output circuit **10** transmits the row address RA of the received address <Ad03> to the row address register **3** (RR3), and transmits the column address CA of the received address <Ad03> to the column address register **0** (CR0). The input/output circuit **10** transmits the received command <30h> to the command register **3** (MR3) based on the address <Ad03>.

[0409] When the row address RA of the address <Ad03> is stored in the row address register **3** (RR3), the row address register **3** (RR3) transmits the row address RA to the row decoder **52D**.

[0410] Upon receipt of the command <30h> from the command register **3** (MR3), the sequencer **30** in the chip **0** (CP0) initiates the normal read on the planes **0** to **3** (PL0 to PL3). The sequencer **30** sets the signals CB00 to CB03 to the busy state. The signals CB00 to CB03 are stored in the status register **21**. Upon completion of the normal read on the planes **0** to **3** (PL0 to PL3) in the chip **0** (CP0), the sequencer **30** sets the signals CB00 to CB03 to the ready state.

[0411] Next, as shown in FIG. 27, the memory controller **300** executes the status read on the plane **0** (PL0) in the chip **0** (CP0).

[0412] More specifically, the memory controller **300** issues the command <78h> and the address <Ad00> in order to execute the status read on the plane **0** (PL**0**) in the chip **0** (CP**0**).

[0413] The sequencer **30** in the chip **0** (CP**0**) transmits the status information STS on the signals CB**00** to CB**03** corresponding to the addresses <Ad00> to <Ad03> to the memory controller **300**.

[0414] Next, upon receipt of signals CB**00** to CB**03** indicative of the ready state from the status register **21**, the memory controller **300** executes the normal read on the plane **0** (PL**0**) in the chip **0** (CP**0**).

[0415] More specifically, the memory controller **300** issues the command <00h>, the address <Ad00>, and the command <32h> in order to execute the normal read on the plane **0** (PL**0**) in the chip **0** (CP**0**).

[0416] In the chip **0** (CP**0**), the input/output circuit **10** receives the command <00h>, the address <Ad00>, and the command <32h> each issued by the memory controller **300**. Thereafter, as with the normal read on the plane **0** (PL**0**) in the chip **0** (CP**0**) described above, the command <00h> and the command <32h> are transmitted to the command register **0** (MR**0**), and the row address RA of the address <Ad00> is transmitted to the row decoder **52A** via the row address register **0** (RR**0**).

[0417] Next, the memory controller **300** executes the normal read on the plane **1** (PL**1**) in the chip **0** (CP**0**).

[0418] More specifically, after issuance of the command <00h>, the address <Ad00>, and the command <32h>, the memory controller **300** issues the command <00h>, the address <Ad01>, and the command <32h> in order to execute the normal read on the plane **1** (PL**1**) in the chip **0** (CP**0**).

[0419] In the chip **0** (CP**0**), the input/output circuit **10** receives the command <00h>, the address <Ad01>, and the command <32h> each issued by the memory controller **300**. Thereafter, as with the normal read on the plane **1** (PL**1**) in the chip **0** (CP**0**) described above, the command <00h> and the command <32h> are transmitted to the command register **1** (MR**1**), and the row address RA of the address <Ad01> is transmitted to the row decoder **52B** via the row address register **1** (RR**1**).

[0420] Next, the memory controller **300** executes the normal read on the plane **2** (PL**2**) in the chip **0** (CP**0**).

[0421] More specifically, after issuance of the command <00h>, the address <Ad01>, and the command <32h>, the memory controller **300** issues the command <00h>, the address <Ad02>, and the command <32h> in order to execute the normal read on the plane **2** (PL**2**) in the chip **0** (CP**0**).

[0422] In the chip **0** (CP**0**), the input/output circuit **10** receives the command <00h>, the address <Ad02>, and the command <32h> each issued by the memory controller **300**. Thereafter, as with the normal read on the plane **2** (PL**2**) in the chip **0** (CP**0**) described above, the command <00h> and the command <32h> are transmitted to the command register **2** (MR**2**), and the row address RA of the address <Ad02> is transmitted to the row decoder **52C** via the row address register **2** (RR**2**).

[0423] Next, the memory controller **300** executes the cache read on the plane **3** (PL**3**) in the chip **0** (CP**0**).

[0424] More specifically, after issuance of the command <00h>, the address <Ad02>, and the command <32h>, the memory controller **300** issues the command <00h>, the address <Ad03>, and the command <31h> in order to execute the cache read on the plane **3** (PL**3**) in the chip **0** (CP**0**).

[0425] In the chip **0** (CP**0**), the input/output circuit **10** receives the command <00h>, the address <Ad03>, and the command <31h> each issued by the memory controller **300**. Thereafter, as with the normal read on the plane **3** (PL**3**) in the chip **0** (CP**0**) described above, the command <00h> and the command <31h> are transmitted to the command register **3** (MR**3**), and the row address RA of the address <Ad03> is transmitted to the row decoder **52D** via the row address register **3** (RR**3**).

[0426] Upon receipt of the command <31h> from the command register **3** (MR**3**), the sequencer **30** in the chip **0** (CP**0**) initiates the normal read on the planes **0** to **2** (PL**0** to PL**2**), and initiates the cache read on the plane **3** (PL**3**) in the chip **0** (CP**0**). The sequencer **30** sets the signals CB**00** to CB**03** to the busy state.

[0427] Next, as shown in FIG. **28**, the memory controller **300** reserves the prefetch of read data in

the normal read executed on the plane **0** (PL**0**) in the chip **0** (CP**0**).

[0428] More specifically, during a period in which the command <00h>, the address <Ad03>, and the command <31h> are issued and the cache read is executed (that is, a period in which the signal CB**00** is in the busy state), the memory controller **300** issues the command <05h>, the address <Ad00>, and the command <E0h> in order to reserve the prefetch on the plane **0** (PL**0**) in the chip **0** (CP**0**).

[0429] In the chip **0** (CP**0**), the input/output circuit **10** receives the command <05h>, the address <Ad00>, and the command <E0h> each issued by the memory controller **300**. The input/output circuit **10** transmits the received command <05h> to the command register **0** (MR**0**) based on the address <Ad00> and also copies the command <05h> to the command register **0'** (MR**0'**). The input/output circuit **10** transmits the row address RA of the received address <Ad00> to the row address register **0** (RR**0**) and also copies the row address RA of the address <Ad00> to the row address register **0'** (RR**0'**). The input/output circuit **10** transmits the column address CA of the received address <Ad00> to the column address register **0** (CR**0**) and also copies the column address CA of the address <Ad00> to the column address register **0'** (CR**0'**). The input/output circuit **10** transmits the received command <E0h> to the command register **0** (MR**0**) based on the address <Ad00> and also copies the command <E0h> to the command register **0'** (MR**0'**).

[0430] When the row address RA of the address <Ad00> is copied to the row address register **0'** (RR**0'**), the row address register **0'** (RR**0'**) transmits the row address RA to the row decoder **52A**.

[0431] Upon receipt of the command <E0h> from the command register **0'** (MR**0'**), the sequencer **30** in the chip **0** (CP**0**) couples the bus switch BSW to the data register **54A** and reserves the prefetch on the plane **0** (PL**0**). The sequencer **30** then initiates the prefetch. That is, transfer of data from the data register **54A** to the FIFO circuit **12** is initiated. Upon receipt of the command <E0h> with the signal CB**00** being in the busy state, the sequencer **30** executes the prefetch on the plane **0** (PL**0**) in the chip **0** (CP**0**) during a period in which the signal CB**00** is in the busy state. More specifically, upon receipt of the command <E0h> with the signal CB**00** being in the busy state, the sequencer **30** executes the prefetch subsequently to the cache transfer.

[0432] Upon initiation of the prefetch, the sequencer **30** in the chip **0** (CP**0**) resets the counter value CNT of the column address counter circuit CC**0'** to 0. The column address register **0'** (CR**0'**) transmits the first to last column addresses CA to the column decoders **55A** to **55D**. Based on a result of decoding the column address CA of the address <Ad00>, the column decoder **55A** selects a corresponding latch circuit in the data register **54A**. Data in the latch circuit selected in sequence is transmitted to the FIFO circuit **12**.

[0433] Next, as shown in FIG. **28**, the memory controller **300** executes the status read on the plane **0** (PL**0**) in the chip **0** (CP**0**). The particulars of the aforementioned status read executed in response to the command <78h> and the address <Ad00> being issued after issuance of the command <05h>, the address <Ad00>, and the command <E0h> are the same as those of the status read on the plane **0** (PL**0**) in the chip **0** (CP**0**) described above.

[0434] Next, upon receipt of the signals CB**00** to CB**03** indicative of the ready state from the status register **21**, the memory controller **300** executes the data-out on the plane **0** (PL**0**) in the chip **0** (CP**0**).

[0435] More specifically, the memory controller **300** issues a command <YYh> in order to execute the data-out on the plane **0** (PL**0**) in the chip **0** (CP**0**). The command “YYh” is a command for selecting a chip and a plurality of planes in the chip and causing the data-out to execute.

[0436] In the chip **0** (CP**0**), the input/output circuit **10** receives the command <YYh> issued by the memory controller **300**. The input/output circuit **10** transmits the received command <YYh> to the command register **0** (MR**0**).

[0437] Upon receipt of the command <YYh> from the command register **0** (MR**0**), the sequencer **30** in the chip **0** (CP**0**) initiates the data-out on the plane **0** (PL**0**) on which the prefetch has been executed.

[0438] On the plane **0** (PL**0**) in the chip **0** (CP**0**), upon completion of transfer of data from the data register **54A** to the FIFO circuit **12**, the sequencer **30** in the chip **0** (CP**0**) couples the bus switch BSW to the data register **54B**, as shown in FIG. **24**, FIG. **25**, and FIG. **28**. When the coupling of the bus switch BSW is switched to the data register **54B** in a course of the data-out on the plane **0** (PL**0**) in the chip **0** (CP**0**), the sequencer **30** initiates the prefetch on the plane **1** (PL**1**) in the chip **0** (CP**0**). That is, transfer of data from the data register **54B** to the FIFO circuit **12** is initiated.

[0439] Next, the memory controller **300** executes the data-out on the plane **1** (PL**1**) in the chip **0** (CP**0**).

[0440] More specifically, upon completion of the data-out on the plane **0** (PL**0**) in the chip **0** (CP**0**), the sequencer **30** in the chip **0** (CP**0**) initiates the data-out on the plane **1** (PL**1**) on which the prefetch has been executed.

[0441] In the plane **1** (PL**1**) in the chip **0** (CP**0**), upon completion of transfer of data from the data register **54B** to the FIFO circuit **12**, the sequencer **30** in the chip **0** (CP**0**) couples the bus switch BSW to the data register **54C**, as shown in FIG. **24**, FIG. **25**, and FIG. **29**. When the coupling of the bus switch BSW is switched to the data register **54C** in a course of the data-out on the plane **1** (PL**1**) in the chip **0** (CP**0**), the sequencer **30** initiates the prefetch on the plane **2** (PL**2**) in the chip **0** (CP**0**). That is, transfer of data from the data register **54C** to the FIFO circuit **12** is initiated.

[0442] Next, the memory controller **300** executes the data-out on the plane **2** (PL**2**) in the chip **0** (CP**0**).

[0443] More specifically, upon completion of the data-out on the plane **1** (PL**1**) in the chip **0** (CP**0**), the sequencer **30** in the chip **0** (CP**0**) initiates the data-out on the plane **2** (PL**2**) on which the prefetch has been executed.

[0444] In the plane **2** (PL**2**) in the chip **0** (CP**0**), upon completion of transfer of data from the data register **54C** to the FIFO circuit **12**, the sequencer **30** in the chip **0** (CP**0**) couples the bus switch BSW to the data register **54D**, as shown in FIG. **24**, FIG. **25**, and FIG. **29**. When the coupling of the bus switch BSW is switched to the data register **54D** in a course of the data-out on the plane **2** (PL**2**) in the chip **0** (CP**0**), the sequencer **30** initiates the prefetch on the plane **3** (PL**3**) in the chip **0** (CP**0**). That is, transfer of data from the data register **54D** to the FIFO circuit **12** is initiated.

[0445] As described above, in the present embodiment, the prefetch of the plane  $p+1$  can be executed during a period in which the data-out on the plane  $p$  (where  $p$  is an integer ranging from **0** to **2**) in the chip **0** (CP**0**) is executed.

[0446] Next, the memory controller **300** executes the data-out on the plane **3** (PL**3**) in the chip **0** (CP**0**).

[0447] More specifically, upon completion of the data-out on the plane **2** (PL**2**) in the chip **0** (CP**0**), the sequencer **30** in the chip **0** (CP**0**) initiates the data-out on the plane **3** (PL**3**) on which the prefetch has been executed.

[0448] Upon completion of the data-out on the plane **3** (PL**3**) in the chip **0** (CP**0**), the command sequences corresponding to a period from B to E are repeated until all of data to be read in the planes **0** to **3** (PL**0** to PL**3**) in the chip **0** (CP**0**) are data-out.

### 3.4 Advantageous Effect

[0449] With the configuration according to the present embodiment, as with the first embodiment, the prefetch can be reserved during the read operation, so that a period until initiation of the data-out can be shortened as compared to a case in which the prefetch is reserved after completion of the read operation. Furthermore, the prefetch on the plane  $p+1$  can be executed during a period in which the data-out on the plane  $p$  in a chip is executed. Therefore, a period until initiation of the data-out on the plane  $p+1$  can be shortened by a period in which the data-out on the plane  $p$  and the prefetch on the plane  $p+1$  are overlapped. Accordingly, the speed of operations of the memory system can be enhanced.

## 4. Fourth Embodiment

[0450] The memory system **100** according to a fourth embodiment will be described. The memory



system **100** according to the present embodiment corresponds to the memory system **100** according to the first embodiment modified by providing one column address register inside the address register **22**. Hereinafter, the following description will in principle concentrate on the features different from the first embodiment.

#### 4.1 Configuration of Register **20**

[0451] A configuration of the register **20** will be described with reference to FIG. **30**. FIG. **30** is a block diagram showing a configuration of the NAND chip **0** (CP**0**) included in the memory system **100** according to the present embodiment, focusing on the input/output circuit **10** and the register **20**. In FIG. **30**, the status register **21** and the voltage generating circuit **40** are omitted.

[0452] As shown in FIG. **30**, the address register **22** has the same configuration as the configuration in which the column address register **0'** (CR**0'**) is omitted from the address register **22** illustrated in FIG. **6** according to the first embodiment.

#### 4.2 Operation

[0453] An operation of the memory system **100** according to the present embodiment will be described with reference to FIG. **31** to FIG. **35**. FIG. **31** to FIG. **35** are each a diagram showing an example of a command sequence in the read operation of the memory system **100** according to the present embodiment. The following will describe an exemplary case in which the signals CEn**1** and CEn**2** are the same signal

[0454] (CEn**1**=CEn**2**=CEn), and data is repeatedly read from the plane **0** to the plane **3** (PL**0** to PL**3**) in this order in the chip **0** (CP**0**). FIG. **31** to FIG. **35** each also show the signals CB**00** to CB**03** of each of the planes in the chip **0** (CP**0**). The same applies to the case in which data is read from the chip **1** (CP**1**). The read operation in the present embodiment corresponds to the single plane read.

[0455] First, the memory controller **300** executes the normal read in order of the planes **0** to **3** (PL**0** to PL**3**) in the chip **0** (CP**0**). The command sequence and the signals CB**00** to CB**03** during a period from when the memory controller **300** sets the signal CEn to the “L” level to when the normal read is executed on the plane **3** (PL**3**) in the chip **0** (CP**0**) are the same as those during a period until A shown in FIG. **19** according to the second embodiment. During this period, the input/output circuit **10** transmits the address CA of the received address <Ad**01**> to the column address register **0** (CR**0**). The input/output circuit **10** transmits the column address CA of the received address <Ad**03**> to the column address register **0** (CR**0**). The rest of the operation in this period is the same as that of the second embodiment.

[0456] Next, as shown in FIG. **31**, the memory controller **300** executes the status read on the plane **0** (PL**0**) in the chip **0** (CP**0**). The particulars of the aforementioned status read executed in response to the command <78h> and the address <Ad**00**> being issued after issuance of the command <00h>, the address <Ad**03**>, and the command <30h> are the same as those of the first embodiment.

[0457] Upon receipt of the signal CB**00** indicative of the ready state from the status register **21**, the memory controller **300** executes the cache read on the plane **0** (PL**0**) in the chip **0** (CP**0**). The particulars of the aforementioned cache read executed in response to issuance of the command <00h>, the address <Ad**00**>, the command <31h> after the memory controller **300** receives the signal CB**00** indicative of the ready state from the status register **21** are the same as those of the first embodiment. Upon initiation of the cache read, the sequencer **30** in the chip **0** (CP**0**) sets the signal CB**00** to the busy state. Upon completion of the cache transfer on the plane **0** (PL**0**) in the chip **0** (CP**0**), the sequencer **30** sets the signal CB**00** to the ready state.

[0458] Next, the memory controller **300** executes the status read on the plane **1** (PL**1**) in the chip **0** (CP**0**). The particulars of the aforementioned status read executed in response to the command <78h> and the address <Ad**01**> being issued after issuance of the command <00h>, the address <Ad**00**>, and the command <31h> are the same as those of the first embodiment.

[0459] Upon receipt of the signal CB**01** indicative of the ready state from the status register **21**, the

memory controller **300** executes the cache read on the plane **1** (PL**1**) in the chip **0** (CP**0**). The particulars of the aforementioned cache read executed in response to issuance of the command <00h>, the address <Ad01>, and the command <31h> after the memory controller **300** receives the signal CB**01** indicative of the ready state from the status register **21** are the same as those of the first embodiment. Upon initiation of the cache read, the sequencer **30** in the chip **0** (CP**0**) sets the signal CB**01** to the busy state. Upon completion of the cache transfer on the plane **1** (PL**1**) in the chip **0** (CP**0**), the sequencer **30** sets the signal CB**01** to the ready state.

[0460] Next, the memory controller **300** executes the status read on the plane **2** (PL**2**) in the chip **0** (CP**0**). The particulars of the aforementioned status read executed in response to the command <78h> and the address <Ad02> being issued after issuance of the command <00h>, the address <Ad01>, and the command <31h> are the same as those of the first embodiment.

[0461] Upon receipt of the signal CB**02** indicative of the ready state from the status register **21**, the memory controller **300** executes the cache read on the plane **2** (PL**2**) in the chip **0** (CP**0**). The particulars of the aforementioned cache read executed in response to issuance of the command <00h>, the address <Ad02>, and the command <31h> after the memory controller **300** receives the signal CB**02** indicative of the ready state from the status register **21** are the same as those of the first embodiment. Upon initiation of the cache read, the sequencer **30** in the chip **0** (CP**0**) sets the signal CB**02** to the busy state. Upon completion of the cache transfer on the plane **2** (PL**2**) in the chip **0** (CP**0**), the sequencer **30** sets the signal CB**02** to the ready state.

[0462] Next, the memory controller **300** executes the status read on the plane **3** (PL**3**) in the chip **0** (CP**0**). The particulars of the aforementioned status read executed in response to the command <78h> and the address <Ad03> being issued after issuance of the command <00h>, the address <Ad02>, and the command <31h> are the same as those of the first embodiment.

[0463] Upon receipt of the signal CB**03** indicative of the ready state from the status register **21**, the memory controller **300** executes the cache read on the plane **3** (PL**3**) in the chip **0** (CP**0**). The particulars of the aforementioned cache read executed in response to issuance of the command <00h>, the address <Ad03>, and the command <31h> after the memory controller **300** receives the signal CB**03** indicative of the ready state from the status register **21** are the same as those of the first embodiment. Upon initiation of the cache read, the sequencer **30** in the chip **0** (CP**0**) sets the signal CB**03** to the busy state. Upon completion of the cache transfer on the plane **3** (PL**3**) in the chip **0** (CP**0**), the sequencer **30** sets the signal CB**03** to the ready state.

[0464] Next, as shown in FIG. **32**, the memory controller **300** executes the status read on the plane **0** (PL**0**) in the chip **0** (CP**0**). The particulars of the aforementioned status read executed in response to the command <78h> and the address <Ad00> being issued after issuance of the command <00h>, the address <Ad03>, and the command <31h> are the same as those of the first embodiment.

[0465] Next, upon receipt of the signal CB**00** indicative of the ready state from the status register **21**, the memory controller **300** executes the prefetch on the plane **0** (PL**0**) in the chip **0** (CP**0**).

[0466] More specifically, the memory controller **300** issues the command <05h>, the address <Ad00>, and the command <E0h> in order to execute the prefetch on the plane **0** (PL**0**) in the chip **0** (CP**0**).

[0467] In the chip **0** (CP**0**), the input/output circuit **10** receives the command <05h>, the address <Ad00>, and the command <E0h> each issued by the memory controller **300**. The input/output circuit **10** transmits the received command <05h> to the command register **0** (MR**0**) based on the address <Ad00>. The input/output circuit **10** transmits the row address RA of the received address <Ad00> to the row address register **0** (RR**0**). The input/output circuit **10** transmits the column address CA of the received address <Ad00> to the column address register **0** (CR**0**). The input/output circuit **10** transmits the received command <E0h> to the command register **0** (MR**0**) based on the address <Ad00>.

[0468] When the row address RA of the address <Ad00> is stored in the row address register **0**

(RR0), the row address register 0 (RR0) transmits the row address RA to the row decoder 52A.

[0469] Upon receipt of the command <E0h> from the command register 0 (MR0), the sequencer 30 in the chip 0 (CP0) initiates the prefetch on the plane 0 (PL0). Upon receipt of the command <E0h> with the signal CB00 being in the ready state, the sequencer 30 immediately executes the prefetch on the plane 0 (PL0) in the chip 0 (CP0). More specifically, the sequencer 30 resets the counter value CNT of the column address counter circuit CC0 to 0. The column address register 0 (CR0) transmits the first to last column addresses CA to the column decoders 55A to 55D. Based on a result of decoding the column address CA of the address <Ad00>, the column decoder 55A selects a corresponding latch circuit in the data register 54A. Data in the latch circuit selected in sequence is transmitted to the FIFO circuit 12.

[0470] Next, the memory controller 300 executes the data-out on the plane 0 (PL0) in the chip 0 (CP0).

[0471] More specifically, upon completion of the prefetch on the plane 0 (PL0) in the chip 0 (CP0), the sequencer 30 in the chip 0 (CP0) initiates the data-out on the plane 0 (PL0) on which the prefetch has been executed.

[0472] Next, as shown in FIG. 33, the memory controller 300 executes the status read on the plane 1 (PL1) in the chip 0 (CP0). The particulars of the aforementioned status read executed in response to the command <78h> and the address <Ad01> being issued after completion of the data-out on the plane 0 (PL0) in the chip 0 (CP0) are the same as those of the first embodiment.

[0473] Next, upon receipt of the signal CB01 indicative of the ready state from the status register 21, the memory controller 300 executes the prefetch on the plane 1 (PL1) in the chip 0 (CP0).

[0474] More specifically, the memory controller 300 issues the command <05h>, the address <Ad01>, and the command <E0h> in order to execute the prefetch on the plane 1 (PL1) in the chip 0 (CP0).

[0475] In the chip 0 (CP0), the input/output circuit 10 receives the command <05h>, the address <Ad01>, and the command <E0h> each issued by the memory controller 300. The input/output circuit 10 transmits the received command <05h> to the command register 1 (MR1) based on the address <Ad01>. The input/output circuit 10 transmits the row address RA of the received address <Ad01> to the row address register 1 (RR1). The input/output circuit 10 transmits the column address CA of the received address <Ad01> to the column address register 0 (CR0). The input/output circuit 10 transmits the received command <E0h> to the command register 1 (MR1) based on the address <Ad01>.

[0476] When the row address RA of the address <Ad01> is stored in the row address register 1 (RR1), the row address register 1 (RR1) transmits the row address RA to the row decoder 52B.

[0477] Upon receipt of the command <E0h> from the command register 1 (MR1), the sequencer 30 in the chip 0 (CP0) initiates the prefetch on the plane 1 (PL1). Upon receipt of the command <E0h> with the signal CB01 being in the ready state, the sequencer 30 immediately executes the prefetch on the plane 1 (PL1) in the chip 0 (CP0). More specifically, the sequencer 30 resets the counter value CNT of the column address counter circuit CC0 to 0. The column address register 0 (CR0) transmits the first to last column addresses CA to the column decoders 55A to 55D. Based on a result of decoding the column address CA of the address <Ad01>, the column decoder 55B selects a corresponding latch circuit in the data register 54B. Data in the latch circuit selected in sequence is transmitted to the FIFO circuit 12.

[0478] Next, the memory controller 300 executes the cache read on the plane 0 (PL0) in the chip 0 (CP0). The particulars of the aforementioned cache read executed in response to the command <00h>, the address <Ad00>, and the command <31h> being issued after issuance of the command <05h>, the address <Ad01>, and the command <E0h> are the same as those of the first embodiment. Upon initiation of the cache read, the sequencer 30 in the chip 0 (CP0) sets the signal CB00 to the busy state. Upon completion of the cache transfer on the plane 0 (PL0) in the chip 0 (CP0), the sequencer 30 sets the signal CB00 to the ready state.

[0479] Next, the memory controller **300** executes the data-out on the plane **1** (PL1) in the chip **0** (CP0).

[0480] More specifically, when the command <00h>, the address <Ad00>, and the command <31h> is issued and the prefetch on the plane **1** (PL1) in the chip **0** (CP0) is completed, the sequencer **30** in the chip **0** (CP0) initiates the data-out on the plane **1** (PL1) on which the prefetch has been executed.

[0481] Next, as shown in FIG. **34**, the memory controller **300** executes the status read on the plane **2** (PL2) in the chip **0** (CP0). The particulars of the aforementioned status read executed in response to the command <78h> and the address <Ad02> being issued after completion of the data-out on the plane **1** (PL1) in the chip **0** (CP0) are the same as those of the first embodiment.

[0482] Next, upon receipt of the signal CB02 indicative of the ready state from the status register **21**, the memory controller **300** executes the prefetch on the plane **2** (PL2) in the chip **0** (CP0).

[0483] More specifically, the memory controller **300** issues the command <05h>, the address <Ad02>, and the command <E0h> in order to execute the prefetch on the plane **2** (PL2) in the chip **0** (CP0).

[0484] In the chip **0** (CP0), the input/output circuit **10** receives the command <05h>, the address <Ad02>, and the command <E0h> each issued by the memory controller **300**. The input/output circuit **10** transmits the received command <05h> to the command register **2** (MR2) based on the address <Ad02>. The input/output circuit **10** transmits the row address RA of the received address <Ad02> to the row address register **2** (RR2). The input/output circuit **10** transmits the column address CA of the received address <Ad02> to the column address register **0** (CR0). The input/output circuit **10** transmits the received command <E0h> to the command register **2** (MR2) based on the address <Ad02>.

[0485] When the row address RA of the address <Ad02> is stored in the row address register **2** (RR2), the row address register **2** (RR2) transmits the row address RA to the row decoder **52C**.

[0486] Upon receipt of the command <E0h> from the command register **2** (MR2), the sequencer **30** in the chip **0** (CP0) initiates the prefetch on the plane **2** (PL2). Upon receipt of the command <E0h> with the signal CB02 being in the ready state, the sequencer **30** immediately executes the prefetch on the plane **2** (PL2) in the chip **0** (CP0). More specifically, upon initiation of the prefetch, the sequencer **30** resets the counter value CNT of the column address counter circuit CC0 to 0. The column address register **0** (CR0) transmits the first to last column addresses CA to the column decoders **55A** to **55D**. Based on a result of decoding the column address CA of the address <Ad02>, the column decoder **55C** selects a corresponding latch circuit in the data register **54C**. Data in the latch circuit selected in sequence is transmitted to the FIFO circuit **12**.

[0487] Next, the memory controller **300** executes the cache read on the plane **1** (PL1) in the chip **0** (CP0). The particulars of the aforementioned cache read executed in response to the command <00h>, the address <Ad01>, and the command <31h> being issued after issuance of the command <05h>, the address <Ad02>, and the command <E0h> are the same as those of the first embodiment. Upon initiation of the cache read, the sequencer **30** in the chip **0** (CP0) sets the signal CB01 to the busy state. Upon completion of the cache transfer on the plane **1** (PL1) in the chip **0** (CP0), the sequencer **30** sets the signal CB01 to the ready state.

[0488] Next, the memory controller **300** executes the data-out on the plane **2** (PL2) in the chip **0** (CP0).

[0489] More specifically, when the command <00h>, the address <Ad01>, and the command <31h> is issued and the prefetch on the plane **2** (PL2) in the chip **0** (CP0) is completed, the sequencer **30** in the chip **0** (CP0) initiates the data-out on the plane **2** (PL2) on which the prefetch has been executed.

[0490] Next, as shown in FIG. **35**, the memory controller **300** executes the status read on the plane **3** (PL3) in the chip **0** (CP0). The particulars of the aforementioned status read executed in response to the command <78h> and the address <Ad03> being issued after completion of the data-out on

the plane 2 (PL2) in the chip 0 (CP0) are the same as those of the first embodiment.

[0491] Next, upon receipt of the signal CB03 indicative of the ready state from the status register 21, the memory controller 300 executes the prefetch on the plane 3 (PL3) in the chip 0 (CP0).

[0492] More specifically, the memory controller 300 issues the command <05h>, the address <Ad03>, and the command <E0h> in order to execute the prefetch on the plane 3 (PL3) in the chip 0 (CP0).

[0493] In the chip 0 (CP0), the input/output circuit 10 receives the command <05h>, the address <Ad03>, and the command <E0h> each issued by the memory controller 300. The input/output circuit 10 transmits the received command <05h> to the command register 3 (MR3) based on the address <Ad03>. The input/output circuit 10 transmits the row address RA of the received address <Ad03> to the row address register 3 (RR3). The input/output circuit 10 transmits the column address CA of the received address <Ad03> to the column address register 0 (CR0). The input/output circuit 10 transmits the received command <E0h> to the command register 3 (MR3) based on the address <Ad03>.

[0494] When the row address RA of the address <Ad03> is stored in the row address register 3 (RR3), the row address register 3 (RR3) transmits the row address RA to the row decoder 52D.

[0495] Upon receipt of the command <E0h> from the command register 3 (MR3), the sequencer 30 in the chip 0 (CP0) initiates the prefetch on the plane 3 (PL3). Upon receipt of the command <E0h> with the signal CB03 being in the ready state, the sequencer 30 immediately executes the prefetch on the plane 3 (PL3) in the chip 0 (CP0). More specifically, upon initiation of the prefetch, the sequencer 30 resets the counter value CNT of the column address counter circuit CC0 to 0. The column address register 0 (CR0) transmits the first to last column addresses CA to the column decoders 55A to 55D. Based on a result of decoding the column address CA of the address <Ad03>, the column decoder 55D selects a corresponding latch circuit in the data register 54D. Data in the latch circuit selected in sequence is transmitted to the FIFO circuit 12.

[0496] Next, the memory controller 300 executes the cache read on the plane 2 (PL2) in the chip 0 (CP0). The particulars of the aforementioned cache read executed in response to the command <00h>, the address <Ad02>, and the command <31h> being issued after issuance of the command <05h>, the address <Ad03>, and the command <E0h> are the same as those of the first embodiment. Upon initiation of the cache read, the sequencer 30 in the chip 0 (CP0) sets the signal CB02 to the busy state. Upon completion of the cache transfer on the plane 2 (PL2) in the chip 0 (CP0), the sequencer 30 sets the signal CB02 to the ready state. As described above, in the present embodiment, the prefetch on the plane q+1 can be executed during a period in which the memory controller 300 transmits the command <00h>, an address <Ad0q>, and the command <31h> on a plane q (where q is an integer ranging from 0 to 2) in the chip 0 (CP0).

[0497] Next, the memory controller 300 executes the data-out on the plane 3 (PL3) in the chip 0 (CP0).

[0498] More specifically, when the command <00h>, the address <Ad02>, and the command <31h> is issued and the prefetch on the plane 3 (PL3) in the chip 0 (CP0) is completed, the sequencer 30 in the chip 0 (CP0) initiates the data-out on the plane 3 (PL3) on which the prefetch has been executed.

[0499] Next, the memory controller 300 executes the cache read on the plane 3 (PL3) in the chip 0 (CP0). The particulars of the aforementioned cache read executed in response to the command <00h>, the address <Ad03>, and the command <31h> being issued after completion of the data-out on the plane 3 (PL3) in the chip 0 (CP0) are the same as those of the first embodiment. Upon initiation of the cache read, the sequencer 30 in the chip 0 (CP0) sets the signal CB03 to the busy state. Upon completion of the cache transfer on the plane 3 (PL3) in the chip 0 (CP0), the sequencer 30 sets the signal CB03 to the ready state.

[0500] Hereinafter, the command sequences corresponding to a period from C to G are repeated until all of data to be read in the planes 0 to 3 (PL0 to PL3) in the chip 0 (CP0) are data-out.

#### 4.3 Advantageous Effect

[0501] With the configuration according to the present embodiment, the memory controller **300** can issue the command “31h” on the plane q after issuance of the command “05h” on the plane q+1 in a chip and before initiation of the data-out on the plane q+1. That is, the prefetch on the plane q+1 can be executed during a period in which the memory controller **300** transmits the command <00h>, the address <Ad0q>, and the command <31h> on the plane q in the chip **0** (CP0).

Therefore, a period until initiation of the data-out on the plane q+1 can be shortened by a period in which the transmission of the command <00h>, the address <Ad0q>, and the command <31h> on the plane q and the prefetch on the plane q+1 are overlapped. Accordingly, the speed of operations of the memory system can be enhanced.

#### 5. Fifth Embodiment

[0502] The memory system **100** according to a fifth embodiment will be described. The memory system **100** according to the present embodiment corresponds to the memory system **100** according to the third embodiment modified to read data through the single plane read. Hereinafter, the following description will in principle concentrate on the feature different from the third embodiment.

##### 5.1 Operation

[0503] An operation of the memory system **100** according to the present embodiment will be described with reference to FIG. **36** to FIG. **38**. FIG. **36** to FIG. **38** are each a diagram showing an example of a command sequence in the read operation of the memory system **100** according to the present embodiment. The following will describe an exemplary case in which the signals CEn1 and CEn2 are the same signal (CEn1=CEn2=CEn), and data is repeatedly read from the plane **0** to the plane **3** (PL0 to PL3) in this order in the chip **0** (CP0). FIG. **36** to FIG. **38** each also show the signals CB00 to CB03 of each of the planes in the NAND chip **0** (CP0). The same applies to the case in which data is read from the chip **1** (CP1). The read operation in the present embodiment corresponds to the single plane read.

[0504] First, the memory controller **300** executes the normal read in order of the planes **0** to **3** (PL0 to PL3) in the chip **0** (CP0). The command sequence and the signals CB00 to CB03 during a period from when the memory controller **300** sets the signal CEn to the “L” level to when the normal read is executed on the plane **3** (PL3) in the chip **0** (CP0) are the same as those during a period until A shown in FIG. **19** according to the second embodiment. Note that the operation in this period is the same as that of the fourth embodiment.

[0505] Next, the memory controller **300** executes the status read and the cache read in order of the planes **0** to **3** (PL0 to PL3) in the chip **0** (CP0). The command sequence and the signals CB00 to CB03 during a period from execution of the normal read on the plane **3** (PL3) in the chip **0** (CP0) to execution of the cache read on the plane **3** (PL3) in the chip **0** (CP0) are the same as those during a period from A to B shown in FIG. **31** according to the fourth embodiment. Note that the operation in this period is the same as that of the fourth embodiment.

[0506] Next, the memory controller **300** reserves prefetch of read data in the normal read executed on the plane **0** (PL0) in the chip **0** (CP0).

[0507] More specifically, as shown in FIG. **36**, the memory controller **300** issues the command <05h>, the address <Ad00>, and the command <E0h> in order to reserve the prefetch on the plane **0** (PL0) in the chip **0** (CP0). As with the third embodiment, the memory controller **300** can issue the command <05h>, the address <Ad00>, and the command <E0h> during a period in which the command <00h>, the address <Ad03>, and the command <31h> are issued and the cache read is executed (that is, a period in which the signal CB00 is in the busy state).

[0508] In the chip **0** (CP0), the input/output circuit **10** receives the command <05h>, the address <Ad00>, and the command <E0h> each issued by the memory controller **300**. The input/output circuit **10** transmits the received command <05h> to the command register **0** (MR0) based on the address <Ad00> and also copies the command <05h> to the command register **0'** (MR0'). The

input/output circuit **10** transmits the row address RA of the received address <Ad00> to the row address register **0** (RR0) and also copies the row address RA of the address <Ad00> to the row address register **0'** (RR0'). The input/output circuit **10** transmits the column address CA of the received address <Ad00> to the column address register **0** (CR0) and also copies the column address CA of the address <Ad00> to the column address register **0'** (CR0'). The input/output circuit **10** transmits the received command <E0h> to the command register **0** (MR0) based on the address <Ad00> and also copies the command <E0h> to the command register **0'** (MR0').

[0509] When the row address RA of the address <Ad00> is copied to the row address register **0'** (RR0'), the row address register **0'** (RR0') transmits the row address RA to the row decoder **52A**.

[0510] Upon receipt of the command <E0h> from the command register **0'** (MR0'), the sequencer **30** in the chip **0** (CP0) couples the bus switch BSW to the data register **54A** and reserves the prefetch on the plane **0** (PL0). The sequencer **30** then initiates the prefetch. That is, transfer of data from the data register **54A** to the FIFO circuit **12** is initiated. Upon receipt of the command <E0h> with the signal CB00 being in the ready state, the sequencer **30** immediately executes the prefetch on the plane **0** (PL0) in the chip **0** (CP0). As with the third embodiment, in the case of receiving the command <E0h> with the signal CB00 being in the busy state, the sequencer **30** executes the prefetch on the plane **0** (PL0) in the chip **0** (CP0) during a period in which the signal CB00 is in the busy state. More specifically, upon receipt of the command <E0h> with the signal CB00 being in the busy state, the sequencer **30** executes the prefetch subsequently to the cache transfer.

[0511] Upon initiation of the prefetch, the sequencer **30** in the chip **0** (CP0) resets the counter value CNT of the column address counter circuit CC0' to 0. The column address register **0'** (CR0') transmits the first to last column addresses CA to the column decoders **55A** to **55D**. Based on a result of decoding the column address CA of the address <Ad00>, the column decoder **55A** selects a corresponding latch circuit in the data register **54A**. Data in the latch circuit selected in sequence is transmitted to the FIFO circuit **12**.

[0512] Next, the memory controller **300** executes the status read on the plane **0** (PL0) in the chip **0** (CP0). The particulars of the aforementioned status read executed in response to the command <78h> and the address <Ad00> being issued after issuance of the command <05h>, the address <Ad00>, and the command <E0h> are the same as those of the first embodiment.

[0513] Upon receipt of the signal CB00 indicative of the ready state from the status register **21**, the memory controller **300** executes the data-out on the plane **0** (PL0) in the chip **0** (CP0).

[0514] More specifically, the memory controller **300** issues the command <YYh> in order to execute the data-out on the plane **0** (PL0) in the chip **0** (CP0).

[0515] In the chip **0** (CP0), the input/output circuit **10** receives the command <YYh> issued by the memory controller **300**. The input/output circuit **10** transmits the received command <YYh> to the command register **0** (MR0).

[0516] Upon receipt of the command <YYh> from the command register **0** (MR0), the sequencer **30** in the chip **0** (CP0) initiates the data-out on the plane **0** (PL0) on which the prefetch has been executed.

[0517] On the plane **0** (PL0) in the chip **0** (CP0), upon completion of transfer of data from the data register **54A** to the FIFO circuit **12**, the sequencer **30** in the chip **0** (CP0) couples the bus switch BSW to the data register **54B**, as shown in FIG. 24, FIG. 25, and FIG. 36. When the coupling of the bus switch BSW is switched to the data register **54B** in a course of the data-out on the plane **0** (PL0) in the chip **0** (CP0), the sequencer **30** initiates the prefetch on the plane **1** (PL1) in the chip **0** (CP0). That is, transfer of data from the data register **54B** to the FIFO circuit **12** is initiated.

[0518] Next, the memory controller **300** executes the cache read on the plane **0** (PL0) in the chip **0** (CP0). The particulars of the aforementioned cache read executed in response to the command <00h>, the address <Ad00>, and the command <31h> being issued after completion of the data-out on the plane **0** (PL0) in the chip **0** (CP0) are the same as those of the first embodiment. Upon initiation of the cache read, the sequencer **30** in the chip **0** (CP0) sets the signal CB00 to the busy

state. Upon completion of the cache transfer on the plane **0** (PL**0**) in the chip **0** (CP**0**), the sequencer **30** sets the signal CB**00** to the ready state.

[0519] Next, as shown in FIG. **37**, the memory controller **300** executes the data-out on the plane **1** (PL**1**) in the chip **0** (CP**0**).

[0520] More specifically, after issuance of the command <00h>, the address <Ad00>, and the command <31h>, the memory controller **300** issues the command <YYh> in order to execute the data-out on the plane **1** (PL**1**) in the chip **0** (CP**0**).

[0521] In the chip **0** (CP**0**), the input/output circuit **10** receives the command <YYh> issued by the memory controller **300**. The input/output circuit **10** transmits the received command <YYh> to the command register **1** (MR**1**).

[0522] Upon receipt of the command <YYh> from the command register **1** (MR**1**), the sequencer **30** in the chip **0** (CP**0**) initiates the data-out on the plane **1** (PL**1**) on which the prefetch has been executed.

[0523] On the plane **1** (PL**1**) in the chip **0** (CP**0**), upon completion of transfer of data from the data register **54B** to the FIFO circuit **12**, the sequencer **30** in the chip **0** (CP**0**) couples the bus switch BSW to the data register **54C**, as shown in FIG. **24**, FIG. **25**, and FIG. **37**. When the coupling of the bus switch BSW is switched to the data register **54C** in a course of the data-out on the plane **1** (PL**1**) in the chip **0** (CP**0**), the sequencer **30** initiates the prefetch on the plane **2** (PL**2**) in the chip **0** (CP**0**). That is, transfer of data from the data register **54C** to the FIFO circuit **12** is initiated.

[0524] Next, the memory controller **300** executes the cache read on the plane **1** (PL**1**) in the chip **0** (CP**0**). The particulars of the aforementioned cache read executed in response to the command <00h>, the address <Ad01>, and the command <31h> being issued after completion of the data-out on the plane **1** (PL**1**) in the chip **0** (CP**0**) are the same as those of the first embodiment. Upon initiation of the cache read, the sequencer **30** in the chip **0** (CP**0**) sets the signal CB**01** to the busy state. Upon completion of the cache transfer on the plane **1** (PL**1**) in the chip **0** (CP**0**), the sequencer **30** sets the signal CB**01** to the ready state.

[0525] Next, as shown in FIG. **37**, the memory controller **300** executes the data-out on the plane **2** (PL**2**) in the chip **0** (CP**0**).

[0526] More specifically, after issuance of the command <00h>, the address <Ad01>, and the command <31h>, the memory controller **300** issues the command <YYh> in order to execute the data-out on the plane **2** (PL**2**) in the chip **0** (CP**0**).

[0527] In the chip **0** (CP**0**), the input/output circuit **10** receives the command <YYh> issued by the memory controller **300**. The input/output circuit **10** transmits the received command <YYh> to the command register **2** (MR**2**).

[0528] Upon receipt of the command <YYh> from the command register **2** (MR**2**), the sequencer **30** in the chip **0** (CP**0**) initiates the data-out on the plane **2** (PL**2**) on which the prefetch has been executed.

[0529] On the plane **2** (PL**2**) in the chip **0** (CP**0**), upon completion of transfer of data from the data register **54C** to the FIFO circuit **12**, the sequencer **30** in the chip **0** (CP**0**) couples the bus switch BSW to the data register **54D**, as shown in FIG. **24**, FIG. **25**, and FIG. **37**. When the coupling of the bus switch BSW is switched to the data register **54D** in a course of the data-out on the plane **2** (PL**2**) in the chip **0** (CP**0**), the sequencer **30** initiates the prefetch on the plane **3** (PL**3**) in the chip **0** (CP**0**). That is, transfer of data from the data register **54D** to the FIFO circuit **12** is initiated.

[0530] Next, the memory controller **300** executes the cache read on the plane **2** (PL**2**) in the chip **0** (CP**0**). The particulars of the aforementioned cache read executed in response to the command <00h>, the address <Ad02>, and the command <31h> being issued after completion of the data-out on the plane **2** (PL**2**) in the chip **0** (CP**0**) are the same as those of the first embodiment. Upon initiation of the cache read, the sequencer **30** in the chip **0** (CP**0**) sets the signal CB**02** to the busy state. Upon completion of the cache transfer on the plane **2** (PL**2**) in the chip **0** (CP**0**), the sequencer **30** sets the signal CB**02** to the ready state.



[0531] Next, as shown in FIG. 38, the memory controller **300** executes the data-out on the plane **3** (PL3) in the chip **0** (CP0).

[0532] More specifically, after issuance of the command <00h>, the address <Ad02>, and the command <31h>, the memory controller **300** issues the command <YYh> in order to execute the data-out on the plane **3** (PL3) in the chip **0** (CP0).

[0533] In the chip **0** (CP0), the input/output circuit **10** receives the command <YYh> issued by the memory controller **300**. The input/output circuit **10** transmits the received command <YYh> to the command register **3** (MR3).

[0534] Upon receipt of the command <YYh> from the command register **3** (MR3), the sequencer **30** in the chip **0** (CP0) initiates the data-out on the plane **3** (PL3) on which the prefetch has been executed.

[0535] Next, the memory controller **300** executes the cache read on the plane **3** (PL3) in the chip **0** (CP0). The particulars of the aforementioned cache read executed in response to the command <00h>, the address <Ad03>, and the command <31h> being issued after completion of the data-out on the plane **3** (PL3) in the chip **0** (CP0) are the same as those of the first embodiment. Upon initiation of the cache read, the sequencer **30** in the chip **0** (CP0) sets the signal CB03 to the busy state. Upon completion of the cache transfer on the plane **3** (PL3) in the chip **0** (CP0), the sequencer **30** sets the signal CB03 to the ready state.

[0536] Hereinafter, the command sequences corresponding to a period from B to E are repeated until all of data to be read in the planes **0** to **3** (PL0 to PL3) in the chip **0** (CP0) are data-out.

## 5.2 Advantageous Effect

[0537] With the configuration according to the present embodiment, as with the first embodiment, the prefetch can be reserved during the read operation, so that a period until initiation of the data-out can be shortened as compared to a case in which the prefetch is reserved after completion of the read operation. Furthermore, as with the third embodiment, the prefetch on the plane p+1 can be executed during a period in which the data-out on the plane p in a chip is executed. Therefore, a period until initiation of the data-out of the plane p+1 can be shortened by a period in which the data-out on the plane p and the prefetch on the plane p+1 are overlapped. Accordingly, the speed of operations of the memory system can be enhanced.

## 6. Modification, etc

[0538] As described above, a memory system according to an embodiment includes: a first chip (CP0) including a first plane (PL0) and a first input/output circuit (**10**); and a controller (**300**) which is capable of issuing a command for controlling the first chip. The first plane includes: a first memory cell array (**51A**) having a plurality of first memory cell transistors (MC); and a first latch circuit (**54A**) which is capable of storing first read data read from the first memory cell array. The first input/output circuit includes a first FIFO circuit (**12** (**12A**)) which is capable of fetching the first read data from the first latch circuit. The controller is capable of transmitting to the first chip a first command (05h) for ordering fetching of the first read data from the first latch circuit to the first FIFO circuit during a period in which a read operation is executed on the first plane.

[0539] The embodiments are not limited to those described in the above, and various modifications can be made.

[0540] The FIFO circuit may be a First In Last Out (FILO) circuit.

[0541] Moreover, in the embodiments described above, a NAND flash memory was described as an example of a semiconductor memory device; however, the embodiment is not limited to a NAND flash memory, and is applicable to other semiconductor memories in general. Furthermore, the present embodiment is applicable to various memory devices other than a semiconductor memory.

[0542] While several embodiments have been described, these embodiments have been presented by way of example and are not intended to limit the scope of the invention. These embodiments may be implemented in various other forms, and various omissions, replacements, and changes can

be made without departing from the gist of the invention. The embodiments and their modifications are included in the scope and spirit of the invention and are included in the scope of the claimed inventions and their equivalents.

## Claims

1. A semiconductor memory device comprising: a first plane including: a first memory cell array having a plurality of first memory cell transistors; and a first latch circuit configured to store first read data read from the first memory cell array; a first input/output circuit including a first FIFO circuit configured to fetch the first read data from the first latch circuit; and a sequencer configured to control the first plane and the first input/output circuit based on a command transmitted from an external controller, wherein: the sequencer is configured to: execute a read operation for storing the first read data in the first latch circuit upon receipt of a first read command targeted at the first plane from the external controller; and execute a prefetch operation for fetching the first read data from the first latch circuit into the first FIFO circuit upon receipt of a first data out command targeted at the first plane from the external controller, and the sequencer is configured to execute the prefetch operation for fetching the first read data from the first latch circuit into the first FIFO circuit, subsequently to the read operation for storing the first read data in the first latch circuit, upon receipt of the first data out command, within a period in which the read operation is executed in the first plane.
2. The semiconductor memory device according to claim 1, further comprising: a second plane including: a second memory cell array having a plurality of second memory cell transistors; and a second latch circuit configured to store second read data read from the second memory cell array, wherein: the first FIFO circuit is configured to fetch the second read data from the second latch circuit, the sequencer is configured to: execute a read operation for storing the second read data in the second latch circuit upon receipt of a second read command targeted at the second plane from the external controller; and execute a prefetch operation for fetching the second read data from the second latch circuit into the first FIFO circuit upon receipt of second data out command targeted at the second plane from the external controller, and the sequencer is configured to execute the prefetch operation for fetching the second read data from the second latch circuit into the first FIFO circuit, subsequently to the read operation for storing the second read data in the second latch circuit, upon receipt of the second data out command, within a period in which the read operation is executed in the second plane.
3. The semiconductor memory device according to claim 2, wherein the sequencer is configured to execute the prefetch operation for fetching the second read data from the second latch circuit into the first FIFO circuit in a period in which output of the first read data from the first FIFO circuit to the external controller is executed.
4. The semiconductor memory device according to claim 3, further comprising a switch for switching between coupling of the first FIFO circuit to the first latch circuit and coupling of the first FIFO circuit to the second latch circuit, wherein the switch is configured to switch from the coupling of the first FIFO circuit to the first latch circuit to the coupling of the first FIFO circuit to the second latch circuit after the first read data is transferred from the first latch circuit to the first FIFO circuit.
5. The semiconductor memory device according to claim 1, wherein: the first input/output circuit includes: a first terminal configured to transmit and receive data to and from the external controller; and a second terminal configured to receive a first timing control signal from the external controller, and the first read data fetched from the first latch circuit into the first FIFO circuit is transmitted from the first terminal in accordance with the first timing control signal received at the second terminal.
6. The semiconductor memory device according to claim 5, wherein: the first input/output circuit

further includes a third terminal configured to transmit a second timing control signal to the external controller, and the second timing control signal is transmitted from the third terminal in a period in which the first read data is transmitted from the first terminal.

**7.** The semiconductor memory device according to claim 6, wherein the first read command and the first data out command are received from the first terminal.

**8.** The semiconductor memory device according to claim 7, wherein: the sequencer is configured to execute a data out operation for outputting, from the first terminal, data fetched into the first FIFO circuit upon receipt of a data out operation start command from the external controller, and the sequencer is configured to start output of the first read data from the first terminal upon receipt of the data out operation start command after execution of the prefetch operation for fetching the first read data from the first latch circuit into the first FIFO circuit subsequently to the read operation for storing the first read data in the first latch circuit.

**9.** The semiconductor memory device according to claim 8, further comprising: a second plane including: a second memory array having a plurality of second memory cell transistors; and a second latch circuit configured to store second read data read from the second memory cell array, wherein: the first FIFO circuit is configured to fetch the second read data from the second latch circuit, and the sequencer is configured to: execute a read operation for storing the second read data in the second latch circuit upon receipt of a second read command targeted at the second plane from the external controller; execute a prefetch operation for fetching the second read data from the second latch circuit into the first FIFO circuit upon receipt of a second data out command targeted at the second plane from the external controller, the prefetch operation for fetching the second read data from the second latch circuit into the first FIFO circuit being executed upon receipt of the second data out command after the first read data is fetched from the first latch circuit into the first FIFO circuit; and start output of the second read data from the first terminal upon receipt of the data out operation start command after execution of the prefetch operation for fetching the second read data from the second latch circuit into the first FIFO circuit.

**10.** The semiconductor memory device according to claim 1, further comprising: a second plane including: a second memory cell array having a plurality of second memory cell transistors; and a second latch circuit configured to store second read data read from the second memory cell array; and a switching circuit configured to selectively couple the first latch circuit and the second latch circuit to the first FIFO circuit, wherein the switch circuit is configured to couple the second latch circuit to the first FIFO circuit in a middle of outputting the first read data from the first latch circuit.

**11.** A memory system comprising: a memory controller; and a semiconductor memory device, wherein: the memory controller is configured to transmit a command to the semiconductor memory device, the semiconductor memory device includes: a first plane having: a first memory cell array having a plurality of first memory cell transistors; and a first latch circuit configured to store first read data read from the first memory cell array; a first input/output circuit including a first FIFO circuit configured to fetch the first read data from the first latch circuit; and a sequencer configured to control the first plane and the first input/output circuit based on the command transmitted from the memory controller, the sequencer is configured to: execute a read operation for storing the first read data into the first latch circuit upon receipt of a first read command targeted at the first plane from the memory controller; and execute a prefetch operation for fetching the first read data from the first latch circuit into the first FIFO circuit upon receipt of a first data out command targeted at the first plane from the memory controller, and the sequencer is configured to execute the prefetch operation for fetching the first read data from the first latch circuit into the first FIFO circuit, subsequently to the read operation for storing the first read data in the first latch circuit, upon receipt of the first data out command, within a period in which the read operation is executed in the first plane.

---

