

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12395613
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Yang; Changmo et al.

Electronic device, method, and non-transitory computer-readable storage media for displaying other video corresponding to video displayed on external electronic device

Abstract

An electronic device is provided. A processor of the electronic device may cause the electronic device to obtain first information for a first video displayable through a display of an external electronic device, from the external electronic device using a communication circuit. The processor may cause the electronic device to execute a scan on the first video using a plurality of images in the first video. may cause the electronic device to identify a time to be spent to obtain second information for displaying a second video expanded from the first video to be displayed through the display of the external electronic device, based on the scan. The disclosure relates to a metaverse service for enhancing interconnectivity between a real object and a virtual object. For example, the metaverse service is provided through a network based on fifth generation (5G) and/or sixth generation (6G).

Inventors: Yang; Changmo (Suwon-si, KR), Lee; Seungjoon (Suwon-si, KR), Jin; Younju (Suwon-si, KR), Choi; Eunha (Suwon-si, KR)

Applicant: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Family ID: 1000008764854

Assignee: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Appl. No.: 18/405445

Filed: January 05, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240291951 A1	Aug. 29, 2024

Foreign Application Priority Data

Related U.S. Application Data

continuation parent-doc WO PCT/KR2023/018940 20231122 PENDING child-doc US 18405445

Publication Classification

Int. Cl.: H04N9/31 (20060101); G06T7/215 (20170101)

U.S. Cl.:

CPC H04N9/3188 (20130101); G06T7/215 (20170101); G06T2207/10016 (20130101)

Field of Classification Search

CPC: H04N (9/31); H04N (21/41); H04N (9/3188); H04N (21/436); H04N (21/4223); H04N (21/81); G06T (7/215); G06T (5/00); G06T (7/20); G06T (2207/10016)

USPC: 348/739; 348/744; 348/556; 348/563; 348/569; 348/581; 348/596

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7626600	12/2008	Matsuda	N/A	N/A
7746356	12/2009	Meinders	N/A	N/A
8130330	12/2011	Tan et al.	N/A	N/A
8599313	12/2012	Barenbrug et al.	N/A	N/A
9217914	12/2014	Choi et al.	N/A	N/A
9480907	12/2015	Benko et al.	N/A	N/A
10297179	12/2018	Doi et al.	N/A	N/A
2015/0077435	12/2014	Koga	345/633	G06F 3/017
2017/0300192	12/2016	Naour et al.	N/A	N/A
2018/0174555	12/2017	Lee et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
100909858	12/2008	KR	N/A
10-1278606	12/2012	KR	N/A
10-2014-0037433	12/2013	KR	N/A
101489262	12/2014	KR	N/A
10-2016-0144253	12/2015	KR	N/A
10-1715937	12/2016	KR	N/A
10-2020-0080818	12/2019	KR	N/A
10-2021-0109641	12/2020	KR	N/A

OTHER PUBLICATIONS

Primary Examiner: Hsia; Sherrie

Attorney, Agent or Firm: Jefferson IP Law, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S) (1) This application is a continuation application, claiming priority under § 365(c), of an International application No. PCT/KR2023/018940, filed on Nov. 22, 2023, which is based on and claims the benefit of a Korean patent application number 10-2023-0026363, filed on Feb. 27, 2023, in the Korean Intellectual Property Office, the disclosure of which is incorporated by reference herein in its entirety.

TECHNICAL FIELD

(1) The disclosure relates to an electronic device, method, and non-transitory computer-readable storage media for displaying another video corresponding to a video displayed on an external electronic device.

BACKGROUND ART

(2) An electronic device for visualizing information are being developed. The electronic device may include a television, a monitor, an electronic board, a beam projector, a mobile phone, and/or a tablet personal computer (PC). The electronic device may form a displaying area representing the information on a surface of the electronic device or a surface of exterior of the electronic device.

(3) The above information is presented as background information only to assist with an understanding of the disclosure. No determination has been made, and no assertion is made, as to whether any of the above might be applicable as prior art with regard to the disclosure.

DISCLOSURE

Technical Solution

(4) Aspects of the disclosure are to address at least the above-mentioned problems and/or disadvantages and to provide at least the advantages described below. Accordingly, an aspect of the disclosure is to provide an electronic device, method, and non-transitory computer-readable storage media for displaying another video corresponding to a video displayed on an external electronic device.

(5) Additional aspects will be set forth in part in the description which follows and, in part, will be apparent from the description, or may be learned by practice of the presented embodiments.

(6) In accordance with an aspect of the disclosure, an electronic device is provided. The electronic device may include a communication circuit, a projection assembly, a processor, and a memory 220 storing instructions. The instructions, when executed by the processor, cause the electronic device to obtain first information for a first video displayable through a display of an external electronic device, from the external electronic device using the communication circuit. The instructions, when executed by the processor, cause the electronic device to execute a scan on the first video using a plurality of images in the first video. The instructions, when executed by the processor, cause the electronic device to identify a time to be spent to obtain second information for displaying a second video expanded from the first video to be displayed through the display of the external electronic device, based on the scan. The instructions, when executed by the processor, cause the electronic device to provide a notification for informing the time. The instructions, when executed by the processor, cause the electronic device to after the time has elapsed, display the second video

including a black area partially overlapping the first video displayed through the display of the external electronic device, based on the second information, using the projection assembly.

(7) In accordance with another aspect of the disclosure, a method of an electronic device is provided. The method may comprise obtaining first information for a first video displayable through a display of an external electronic device, from the external electronic device using a communication circuit. The method may comprise executing a scan on the first video using a plurality of images in the first video. The method may comprise identifying a time to be spent to obtain second information for displaying a second video expanded from the first video to be displayed through the display of the external electronic device, based on the scan. The method may comprise providing a notification for informing the time. The method may comprise, after the time has elapsed, displaying the second video including a black area partially overlapping the first video displayed through the display of the external electronic device, based on the second information, using a projection assembly.

(8) In accordance with another aspect of the disclosure, a non-transitory computer readable storage medium storing one or more programs including instructions is provided. The instructions, when executed by a processor of an electronic device, may cause the electronic device to obtain first information for a first video displayable through a display of an external electronic device, from the external electronic device using a communication circuit. The instructions, when executed by a processor of an electronic device, may cause the electronic device to execute a scan on the first video using a plurality of images in the first video. The instructions, when executed by a processor of an electronic device, may cause the electronic device to identify a time to be spent to obtain second information for displaying a second video expanded from the first video to be displayed through the display of the external electronic device, based on the scan. The instructions, when executed by a processor of an electronic device, may cause the electronic device to provide a notification for informing the time. The instructions, when executed by a processor of an electronic device, may cause the electronic device to after the time has elapsed, display the second video including a black area partially overlapping the first video displayed through the display of the external electronic device, based on the second information, using a projection assembly.

(9) Other aspects, advantages, and salient features of the disclosure will become apparent to those skilled in the art from the following detailed description, which, taken in conjunction with the annexed drawings, discloses various embodiments of the disclosure.

Description

DESCRIPTION OF THE DRAWINGS

- (1) The above and other aspects, features, and advantages of certain embodiments of the disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:
- (2) FIG. 1 illustrates an operation in which an electronic device displays a second video corresponding to a first video displayed on a display of an external electronic device according to an embodiment of the disclosure;
- (3) FIG. 2 illustrates a block diagram of an electronic device according to an embodiment of the disclosure;
- (4) FIGS. 3A and 3B illustrate an operation in which an electronic device adjusts a size of a video according to various embodiments of the disclosure;
- (5) FIG. 4 illustrates an operation in which an electronic device generates a second video using a first video according to an embodiment of the disclosure;
- (6) FIG. 5 illustrates an operation in which an electronic device identifies a shape of an external electronic device to display a second video according to an embodiment of the disclosure;

(7) FIG. 6 illustrates an operation in which an electronic device transmits information for a second video to a server according to an embodiment of the disclosure;

(8) FIG. 7 illustrates a flowchart illustrating an operation of an electronic device according to an embodiment of the disclosure;

(9) FIG. 8 is a signal flowchart illustrating a signal transmitted and received between an electronic device and an external electronic device according to an embodiment of the disclosure; and

(10) FIG. 9 is a diagram of a network environment related to a metaverse service according to an embodiment of the disclosure.

(11) Throughout the drawings, it should be noted that like reference numbers are used to depict the same or similar elements, features, and structures.

MODE FOR INVENTION

(12) The following description with reference to accompanying drawings is provided to assist in a comprehensive understanding of various embodiments of the disclosure as defined by the claims and their equivalents. It includes various specific details to assist in that understanding but these are to be regarded as merely exemplary. Accordingly, those of ordinary skill in the art will recognize that various changes and modifications of the various embodiments described herein can be made without departing from the scope and spirit of the disclosure. In addition, descriptions of well-known functions and constructions may be omitted for clarity and conciseness.

(13) The terms and words used in the following description and claims are not limited to the bibliographical meanings, but, are merely used by the inventor to enable a clear and consistent understanding of the disclosure. Accordingly, it should be apparent to those skilled in the art that the following description of various embodiments of the disclosure is provided for illustration purpose only and not for the purpose of limiting the disclosure as defined by the appended claims and their equivalents.

(14) It is to be understood that the singular forms “a,” “an,” and “the” include plural referents unless the context clearly dictates otherwise. Thus, for example, reference to “a component surface” includes reference to one or more of such surfaces.

(15) Various embodiments of this document and terms used therein are not intended to limit a technology described in this document to a particular shape, but should be understood to include various changes, equivalents, and/or substitutes of the embodiment. As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd,” or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), it means that the element may be coupled with the other element directly, or via other element (e.g., a third element).

(16) As used in connection with various embodiments of the disclosure, the term “module” may include a unit implemented in hardware, software, or firmware, and may interchangeably be used with other terms, for example, “logic,” “logic block,” “part,” or “circuitry”. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment of the disclosure, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

(17) FIG. 1 illustrates an operation in which an electronic device displays a second video corresponding to a first video displayed on a display of an external electronic device according to an embodiment of the disclosure. Referring to FIG. 1, an electronic device **101** according to an embodiment may include a beam projector for emitting light to an external space. The electronic device **101** may output the light representing a screen (e.g., a video **110**) formed by pixels arranged

two-dimensionally. The light outputted from the electronic device **101** may be reflected by an object, such as a plane. A user of the electronic device **101** may view the screen based on the light reflected by the object.

(18) Referring to FIG. **1**, according to an embodiment of the disclosure, the electronic device **101** may identify at least one plane capable of projecting a screen (e.g., a video **110**) represented by light, in an external space in which the light emitted by the electronic device **101** is reachable. According to an embodiment of the disclosure, the electronic device **101** may identify an external electronic device **102** for projecting light toward the at least one plane identified, using a communication circuit. For example, the electronic device **101** may identify the external electronic device **102** using a camera. The electronic device **101** may adjust a size of the video **110** to be projected on the at least one plane, based on a shape of the identified external electronic device **102**.

(19) For example, adjusting the size of the video **110** by the electronic device **101** may include adjusting a position in which the video **110** is displayed on at least one plane by controlling a projection assembly. The electronic device **101** may use a black area to adjust the size of the video **110**. The black area may be used to prevent the electronic device **101** from overlapping at least a part of the video **110**, on the external electronic device **102**. An operation of generating the black area by the electronic device **101** will be described later in FIG. **5**.

(20) According to an embodiment of the disclosure, the electronic device **101** may establish a communication link with the external electronic device **102** using a communication circuit. In a state that the communication link is established, the electronic device **101** may display the video **110** related to a video **115** displayed on a display of the external electronic device **102**, on a plane. A displaying area **105** in which the electronic device **101** displays the video **110** may have a rectangular shape with a specified ratio (e.g., an aspect ratio). However, it is not limited thereto.

(21) For example, an operation in which the electronic device **101** displays the video **110** on the plane and an operation in which the external electronic device **102** displays the video **115** on the display may be performed substantially simultaneously through a communication link. The video **110** and the video **115** may be obtained by substantially similar information. For example, the electronic device **101** may generate the video **110** based on execution of at least one application using the video **115**. An operation of generating the video **110** by the electronic device **101** will be described later with reference to FIG. **4**.

(22) According to an embodiment of the disclosure, a video displayed in the displaying area **105** by the electronic device **101** may be indicated by video data. For example, the video data may be stored in a memory of the electronic device **101** or transmitted from another electronic device (e.g., at least one server providing a streaming service, set-top box (STB), PC, and/or television (TV)) to the electronic device **101**. The video data may include an image and/or a video. The video data may be streamed from a network connected by the electronic device **101**. The image data may include a video and a sound synchronized with the video. The image data may include a video standardized by a motion picture expert group (MPEG). Other video **115** displayed in the display by the external electronic device **102** may be substantially similar to those described above.

(23) According to an embodiment of the disclosure, the electronic device **101** may receive information on the video **115** that may be displayed through the display of the external electronic device **102** from the external electronic device **102** using the communication circuit. Based on scanning the video **115**, the electronic device **101** may identify a time to be spent to obtain information for displaying (or generating) the video **110** expanded from the video **115**. For example, the electronic device **101** may provide the user of the electronic device **101** with a notification for informing the identified time. For example, the time may be changed based on a size of the video **110** and/or the number of pixels included in the video **110**. For example, when the time is set, the electronic device **101** may adjust the size of the video **110** and/or the number of pixels based on the time.

(24) According to an embodiment of the disclosure, the electronic device **101** may receive an input indicating to play the video **110** from the external electronic device **102**, after the time has elapsed. For example, the electronic device **101** may receive the input from a user of the electronic device **101**. Based on receiving the input, a signal requesting play of the video **115** may be transmitted to the external electronic device **102**. The electronic device **101** may display the video **110** synchronized with the video **115** using a projection assembly, while the video **115** is displayed on the display of the external electronic device **102**. For example, the displaying area **105** in which the electronic device **101** projects the video **115** may cover at least a part of the external electronic device **102**.

(25) As described above, according to an embodiment of the disclosure, the electronic device **101** may identify a time for generating the video **110** extended from the video **115**, by using the video **115**. After the time has elapsed, while the external electronic device **102** displays the video **115** on the display, the video **110** may be outputted by controlling the projection assembly in a direction adjacent to the external electronic device **102**. The electronic device **101** may provide a user with the video **115** based on a wider size, by projecting the video **110** synchronized with the video **115** to a periphery of the external electronic device **102**.

(26) FIG. 2 illustrates a block diagram of an electronic device, according to an embodiment of the disclosure. The electronic device **101** of FIG. 1 may be an example of the electronic device **101** of FIG. 2. The external electronic device **102** of FIG. 1 may be an example of the external electronic device **102** of FIG. 2.

(27) Referring to FIG. 2, the electronic device **101** and the external electronic device **102** may be connected to each other, based on a wired network and/or a wireless network. The wired network may include a network, such as Internet, local area network (LAN), wide area network (WAN), Ethernet, or a combination thereof. The wireless network may include a network, such as long term evolution (LTE), fifth generation (5G) new radio (NR), wireless fidelity (Wi-Fi), Zigbee, near field communication (NFC), Bluetooth, Bluetooth low-energy (BLE), or a combination thereof. Although the electronic device **101** and the external electronic device **102** are illustrated to be directly connected, the electronic device **101** and the external electronic device **102** may be connected indirectly through an intermediate node (e.g., a router and/or an access point (AP)). For example, the electronic device **101** and the external electronic device **102** may be connected based on an interface, such as a high-definition multimedia interface (HDMI) and/or RCA.

(28) Referring to FIG. 2, according to an embodiment of the disclosure, the electronic device **101** may include at least one of a processor **210**, a memory **220**, a projection assembly **230**, a camera **240**, or a communication circuit **250**. The processor **210**, the memory **220**, the projection assembly **230**, the camera **240**, and the communication circuit **250** may be electrically and/or operably coupled with each other by an electronic component, such as a communication bus. Hereinafter, the operative coupling of hardware components may mean that a direct or indirect connection between hardware components is established by wire or wirelessly, so that a second hardware is controlled by a first hardware among the hardware components. Although illustrated based on different blocks, embodiments are not limited thereto, and a part (e.g., at least a part of the processor **210**, the memory **220**, and the communication circuit **250**) of the hardware of FIG. 2 may be included in a single integrated circuit, such as a system on a chip (SoC). The types and/or numbers of hardware components included in the electronic device **101** are not limited to those illustrated in FIG. 2. For example, the electronic device **101** may include only a part of the hardware components illustrated in FIG. 2.

(29) According to an embodiment of the disclosure, the processor **210** of the electronic device **101** may include a hardware component for processing data based on one or more instructions. For example, the hardware component for processing data may include an arithmetical and logical unit (ALU), a floating point unit (FPU), a field programmable gate array (FPGA), a central processing unit (CPU) and/or, application processor (AP). The number of processors **210** may be one or more.

For example, the processor **120** may have a structure of a multi-core processor, such as a dual core, a quad core, or a hexa core.

(30) According to an embodiment of the disclosure, the memory **220** of the electronic device **101** may include a hardware component for storing data and/or an instruction inputted to and/or outputted from the processor **120**. The memory **220** may include a volatile memory, such as a random-access memory (RAM) and/or a non-volatile memory, such as a read-only memory (ROM). For example, the volatile memory may include at least one of a dynamic RAM (DRAM), a static RAM (SRAM), a Cache RAM, and a pseudo SRAM (PSRAM). For example, the non-volatile memory may include at least one of a programmable ROM (PROM), an erasable PROM (EPROM), an electrically erasable PROM (EEPROM), a flash memory, a hard disk, a compact disk, and an embedded multimedia card (eMMC).

(31) According to an embodiment of the disclosure, one or more instructions (or commands) indicating calculation and/or operation to be performed on data by the processor **210** may be stored in the memory **220** of the electronic device **101**. A set of one or more instructions may be referred to as a firmware, an operating system, a process, a routine, a sub-routine, and/or an application. For example, when a set of a plurality of instructions distributed in the form of operating system, firmware, driver, and/or application is executed, the electronic device **101** and/or the processor **210** may perform at least one of operations of FIG. 7. Hereinafter, the fact that an application is installed in the electronic device **101** may mean that one or more instructions provided in the form of an application are stored in the memory **220** of the electronic device **101**, and that the one or more applications are stored in a format (e.g., a file with an extension specified by the operating system of the electronic device **101**) executable by the processor **210** of the electronic device **101**.

(32) According to an embodiment of the disclosure, the electronic device **101** may generate a second video **222** corresponding to a first video **221** based on execution of an image generation application **225**. The electronic device **101** may use information on the first video **221** stored in the memory **220**. However, it is not limited thereto. For example, the electronic device **101** may obtain information on the first video **221** from the external electronic device **102** through the communication circuit **250**. The first video **221** may be referred to the video **115** of FIG. 1.

(33) For example, the electronic device **101** may obtain the second video **222** extended from the first video **221** based on execution of the image generation application **225**, using the first video **221**. The second video **222** may be referred to the video **110** of FIG. 1. In order to generate the second video **222**, the electronic device **101** may obtain information for a space in which the electronic device **101** is located, using the camera **240**. An operation of generating the second video **222** by the electronic device **101** will be described later with reference to FIGS. 3A and 3B.

(34) For example, the electronic device **101** may adjust a size of the second video **222** by using the information on the space. However, it is not limited thereto. For example, the electronic device **101** may adjust the size of the second video **222** when projecting the second video **222** using the projection assembly **230**.

(35) For example, the electronic device **101** may identify a time for generating the second video **222**. The electronic device **101** may provide a notification for informing the time to the user. The electronic device **101** may transmit a signal indicating the notification to the external electronic device **102** and/or another electronic device of the user, by using a communication circuit. The electronic device **101** may output an audio signal indicating the notification using a speaker (not shown). However, it is not limited thereto.

(36) According to an embodiment of the disclosure, the projection assembly **230** of the electronic device **101** may include a plurality of hardware assembled to emit light representing pixels arranged two-dimensionally. For example, the projection assembly **230** may include a combination of cathode-ray tubes (CRTs) for emitting light of each of three primary colors in a color space and lenses for expanding the light emitted from each of the CRTs. For example, the projection assembly **230** may include a combination of a light source (e.g., a lamp) for emitting light, optical filters for

dividing the light into light paths corresponding to each of the three primary colors, liquid crystal display (LCD) panels disposed on each of the light paths, and a prism and/or a lens for synthesizing light outputted from the LCD panels. For example, the projection assembly **230** may include a combination of a light source for emitting light, an optical filter selecting any one of the three primary colors from the light, a digital mirror device (DMD) for controlling reflection on the primary color filtered by the optical filter, and a lens for expanding light reflected by the DMD. In terms of requiring light projection for display of the screen, at least one of the illustrated combinations may be referred to as the projection assembly **230**. In an embodiment of the disclosure, the electronic device **101** including the projection assembly **230** may be referred to as a beam projector.

(37) According to an embodiment of the disclosure, the camera **240** of the electronic device **101** may include one or more optical sensors (a charged coupled device (CCD) sensor, a complementary metal oxide semiconductor (CMOS) sensor) that generate an electrical signal indicating color and/or brightness of light. A plurality of optical sensors in the camera **240** may be arranged in a shape of 2 dimensional array. By obtaining an electrical signal of each of the plurality of optical sensors substantially simultaneously, the camera **240** may correspond to light reaching the optical sensors of the 2-dimensional array and generate an image including a plurality of pixels arranged in 2 dimensions. For example, photo data captured using the camera **240** may mean an image obtained from the camera **240**. For example, video data captured using the camera **240** may mean a sequence of a plurality of images obtained according to a specified frame rate from the camera **240**.

(38) According to an embodiment of the disclosure, the electronic device **101** may identify an external object included in an image and/or video obtained using the camera **240**. Identifying an external object by the electronic device **101** may be performed based on a sensor to identify a distance between the electronic device **101** and the external object, such as a depth sensor and/or a time of flight (ToF) sensor. The depth sensor may include an ultra-wide band (UWB) sensor (or UWB radar) that uses a radio signal in a frequency band of the UWB. The depth sensor may include a time-of-flight (ToF) sensor that measures ToF of laser light and/or infrared light. The electronic device **101** may obtain a depth image including two-dimensionally arranged depth values using the ToF sensor. The ToF sensor may include an infrared diode and a plurality of infrared light sensors that detect intensity of infrared light and are arranged in a shape of 2-dimensional array. Using the ToF sensor, the electronic device **101** may obtain the depth image based on a time when light emitted from the infrared diode is reflected from a subject and reaches at least one of the plurality of infrared light sensors.

(39) According to an embodiment of the disclosure, the electronic device **101** may identify a shape of the external electronic device **102** by using the camera **240**. Based on the identification of the shape of the external electronic device **101**, the electronic device **101** may generate a black area to be projected by overlapping the second video **222**. An example of an operation of the electronic device **101** generating the black area will be described later with reference to FIG. 5.

(40) According to an embodiment of the disclosure, the communication circuit **250** of the electronic device **101** may include hardware for supporting transmission and/or reception of an electrical signal between the electronic device **101** and the external electronic device **102**. Although only the external electronic device **102** is illustrated as another electronic device connected through the communication circuit **250** of the electronic device **101**, the embodiment is not limited thereto. For example, the communication circuit **250** may include at least one of a MODEM, an antenna, and an optical/electronic (O/E) converter. The communication circuit **250** may support transmission and/or reception of the electrical signal, based on various types of protocols, such as Ethernet, local area network (LAN), wide area network (WAN), wireless fidelity (Wi-Fi), Bluetooth low energy (BLE), ZigBee, long term evolution (LTE), and 5G new radio (NR).

(41) According to an embodiment of the disclosure, the electronic device **101** may receive

information on the first video **221** (or information indicating a screen) using the communication circuit **250**. For example, the electronic device **101** may wirelessly receive a signal for displaying the first video **221** and/or the second video **222** through the communication circuit **250**, based on a wireless communication protocol, such as a wireless display (WiDi) and/or a Miracast. For example, the electronic device **101** may receive a signal for displaying the first video **221** and/or the second video **222** by wire using the communication circuit **250**, based on a wired communication protocol (or a wired interface), such as high-definition multimedia interface (HDMI), display port (DP), mobile high-definition link (MHL), digital visual interface (DVI) and/or D-subminiature (D-sub).

(42) Referring to FIG. 2, the external electronic device **102** connected to the electronic device **101** may include at least one of a processor **210-1**, a memory **220-1**, a communication circuit **250-1**, or a display **260**. The processor **210-1**, the memory **220-1**, the communication circuit **250-1**, and the display **260** may be electrically and/or operably connected to each other by a communication bus. The processor **210-1**, the memory **220-1**, and the communication circuit **250-1** in the external electronic device **102** of FIG. 2 may correspond to the processor **210**, the memory **220**, and the communication circuit **250** in the electronic device **101**. In order to reduce repetition of description, descriptions overlapping the processor **210**, the memory **220**, and the communication circuit **250** may be omitted from among the descriptions of a processor **210-1**, a memory **220-1**, and a communication circuit **250-1**.

(43) According to an embodiment of the disclosure, the display **260** of the external electronic device **102** may output visualized information to a user. For example, the display **260** may be controlled by the processor **120** and/or a graphic processing unit (GPU) (not shown) to output visualized information to the user. The display **260** may include a flat panel display (FPD) and/or electronic paper. The FPD may include a liquid crystal display (LCD), a plasma display panel (PDP), a digital mirror device (DMD), one or more light emitting diodes (LEDs), and/or a micro LED. The LED may include an organic LED (OLED).

(44) According to an embodiment of the disclosure, the electronic device **101** may establish a communication link with the external electronic device **102** using the communication circuit **250-1**. In a state that the communication link is established, the electronic device **101** may transmit a signal indicating to display at least one video (e.g., the second video **222**) to the external electronic device **102**. Based on transmitting the signal, the electronic device **101** may display the second video **222** using the projection assembly **230** in a direction adjacent to the external electronic device **102**. For example, the external electronic device **102** may display the first video **221** corresponding to the second video **222** on the display **260**, in response to receiving the signal. Based on the communication link, the electronic device **101** and the external electronic device **102** may project the first video **221** and/or the second video **222** substantially simultaneously. For example, the electronic device **101** may display the second video **222** synchronized with the first video **221** by controlling the projection assembly **230**, based on the communication link. For example, a first video **221-1** of the external electronic device **102** may be stored by information substantially similar to the first video **221**.

(45) According to an embodiment of the disclosure, based on identifying at least one external object, the electronic device **101** may adjust a displaying area (e.g., the displaying area **105** in FIG. 1) to which light of the projection assembly **230** is to be propagated, by using the camera **240**. In order to prevent the light from propagating onto the at least one external object, the electronic device **101** may change a position of the displaying area by controlling the projection assembly **230**. The electronic device **101** may adjust a position of a black area included in the second video **222** based on changing the position of the displaying area. However, it is not limited thereto. For example, the electronic device **101** may adjust a size of the second video **222** based on identifying the at least one external object, while generating the second video **222**.

(46) As described above, according to an embodiment of the disclosure, in a state that the

communication link with the external electronic device **102** is established, the electronic device **101** may generate the second video **222** corresponding to the first video **221-1** to be displayed on the display of the external electronic device **102**, based on execution of an image generation application **225**. The electronic device **101** may identify a time for generating the second video **222**. The time may be changed based on a state of the second video **222**. The electronic device **101** may provide a displayable state of the second video **222** to the user using the time.

(47) Hereinafter, an example of an operation in which the electronic device **101** adjusts a size of the second video **222** will be described later in FIGS. **3A** and **3B**.

(48) FIGS. **3A** and **3B** illustrate an operation in which an electronic device adjusts a size of a video, according to an embodiment of the disclosure. The electronic device of FIGS. **3A** and **3B** may be an example of the electronic device **101** of FIGS. **1** and **2**.

(49) Referring to FIG. **3A**, according to an embodiment of the disclosure, the electronic device **101** may receive information on the first video **221** from an external electronic device (e.g., the external electronic device **102** of FIG. **1**) through a communication circuit. The electronic device **101** may set a size of the second video for generating the second video **222** extended from the first video **221**.

(50) For example, the electronic device **101** may identify a size of a plane on which the second video is to be projected, by using a camera (e.g., the camera **240** in FIG. **2**). The electronic device **101** may adjust the size of the second video, based on identifying the size of the plane. The electronic device **101** may expand the first video **221**, based on a position of the external electronic device. For example, a shape of the second video extended from the first video **221** may be different according to the position of the external electronic device in the plane.

(51) For example, the size of the second video extended from the first video **221** may be larger than a size **310** of the first video **221**. The electronic device **101** may generate the second video **222** based on a size **311** and/or a size **312**. The electronic device **101** may generate the second video **222** based on at least one selected in response to an input indicating to select at least one of the size **311** or the size **312**, from another external electronic device of the user.

(52) According to an embodiment of the disclosure, the electronic device **101** may adjust the number of pixels included in the second video **222**, independently of identifying the size of the second video **222**. Adjusting the number of pixels included in the second video may include adjusting quality of the second video **222**. Adjusting the quality of the second video may include adjusting a frame rate of the second video, brightness of the second video, color of the second video, and/or a bit rate corresponding to the second video. For example, the electronic device **101** may receive a user's input for adjusting the number of pixels included in the second video. The electronic device **101** may adjust the number of pixels to render the second video using the first video **221**. According to adjusting the number of pixels, the electronic device **101** may adjust resolution corresponding to the second video to be displayed by adjusting the projection assembly **230**. However, it is not limited thereto.

(53) According to an embodiment of the disclosure, the electronic device **101** may identify a time for generating the second video based on the size of the second video (e.g., the size **311** or the size **312**) and/or the number of pixels included in the second video. When the number of pixels is set equally, a time for generating the second video based on the size **312** may be greater than a time for generating the second video based on the size **311**. The electronic device **101** may adjust the time for generating the second video, by adjusting the size of the second video and/or the number of pixels included in the second video.

(54) Referring to FIG. **3B**, according to an embodiment of the disclosure, the electronic device **101** may identify an external electronic device (e.g., the external electronic device **102** of FIG. **2**) and/or an external object **330** using a camera. The electronic device **101** may adjust a size of a second video (e.g., the second video **222** of FIG. **2**) based on identifying the external object **330**.

(55) For example, the electronic device **101** may generate the second video extended from each of

edges of the first video **221**. The electronic device **101** may adjust a length extending from the edges of the first video **221**, based on a position of the external object **330**. For example, the electronic device **101** may identify the external object **330** adjacent to an edge of the second video. For example, when the electronic device **101** generates the second video based on the size **312**, a length extended from a first edge **221-1** of the first video **221** to a first edge **312-1** of the second video **222** may be longer than a length extended from a second edge **221-2** of the first video **221** to a second edge **312-2** of the second video **222**. The electronic device **101** may generate the second video **222** suitable for a space in which a user of the electronic device **101** is located, by adjusting the size of the second video **222** extended from the first video **221**.

(56) According to an embodiment of the disclosure, when displaying the second video **222**, the electronic device **101** may adjust a displaying area (e.g., the displaying area **105** of FIG. **1**) in which light of a projection assembly is to be projected, by using the projection assembly (e.g., the projection assembly **230** of FIG. **2**). For example, in a state of generating the second video **222** based on the size **312** of FIG. **3A**, the electronic device **101** may identify a position of the external object **330** to output the second video **222**. The electronic device **101** may change an area of the second video **222** overlapping with the first video **221**, based on identifying the position of the external object **330**. The electronic device **101** may generate a black area corresponding to a position of an external electronic device (e.g., the external electronic device **102** of FIG. **2**) on which the first video **221** is to be displayed. The electronic device **101** may use the black area to prevent part of the second video **222** from being displayed by overlapping the first video **221** on an external electronic device on which the first video **221** is to be displayed. For example, the electronic device **101** may include an actuator (not shown) for adjusting the displaying area to which light of the projection assembly is to be projected. The electronic device **101** may prevent the light from being projected onto the external object **330**, based on adjusting the displaying area.

(57) As described above, the electronic device **101** may adjust the size of the second video **222**, by using information on a space obtained using the camera. The electronic device **101** may prevent distortion of the second video **222** by the external object **330**, by adjusting the size of the second video **222**. The electronic device **101** may prevent diffused reflection of light representing the second video **222** projected using the projection assembly by the external object **333**, by adjusting the size of the second video **222**.

(58) Hereinafter, in FIG. **4**, an example of an operation in which the electronic device **101** generates the second video **222** using the first video **221** will be described later.

(59) FIG. **4** illustrates an operation in which an electronic device generates a second video using a first video, according to an embodiment of the disclosure. The electronic device **101** of FIG. **4** may be an example of the electronic device **101** of FIGS. **1**, **2**, **3A** and **3B**.

(60) Referring to FIG. **4**, according to an embodiment of the disclosure, the electronic device **101** may obtain information on a first video **410** from an external electronic device (e.g., the external electronic device **102** of FIG. **1**). For example, the electronic device **101** may use a video (e.g., the first video **221** of FIG. **2**) stored in a memory (e.g., the memory **220** of FIG. **2**).

(61) According to an embodiment of the disclosure, the electronic device **101** may execute a scan from edges (e.g., at least one of edges **410-1**, **410-2**, **410-3**, and **410-4**) of each of a plurality of images in the first video **410** toward a center area of each of the plurality of images, based on execution of an image generation application (e.g., the image generation application **225** of FIG. **2**). For example, the electronic device **101** may execute a scan from the center area toward the edge. However, it is not limited thereto. For example, the electronic device **101** may execute a scan from one edge toward the center area. For example, the electronic device **101** may scan the entire first video **410** substantially simultaneously. For example, the operation in which the electronic device **101** scans a plurality of images may include an operation of identifying at least one visual object from each of the plurality of images.

(62) For example, based on executing the scan, the electronic device **101** may analyze each of the

plurality of images of the first video **410**. For example, the electronic device **101** may identify an object (e.g., a visual object **411**) included in each of the plurality of images of the first video **410**. The object included in each of the plurality of images may be referred to as the visual object **411**, in terms of being included in the first video **410**. The electronic device **101** may select or classify at least one image for generating a second video **420-2** from among the plurality of images of the first video **410**, based on executing the scan.

(63) According to an embodiment of the disclosure, the electronic device **101** may identify a motion of the visual object **411** included in the first video **410**. The electronic device **101** may identify the motion by using each of the plurality of images of the first video **410**. The electronic device **101** may identify the motion of the visual object **411**, based on identifying motion blur using each of the plurality of images. However, it is not limited thereto. For example, the electronic device **101** may identify the motion of the visual object **411**, based on identifying optical flow included in each of the plurality of images. For example, the electronic device **101** may identify the motion of the visual object **411**, by using a plurality of frames, based on an identifier corresponding to the visual object **411**.

(64) For example, the electronic device **101** may identify the motion of the visual object **411** based on the identifier corresponding to the visual object **411**, by using each of plurality of images. For example, the electronic device **101** may use each of plurality of images to distinguish between the visual object **411** and a visual object representing an external space, such as a background. The electronic device **101** may identify the motion of the visual object **411** while maintaining display of the visual object representing the external space, based on distinguishing between the visual object representing the external space and the visual object **411** using the plurality of images.

(65) For example, the electronic device **101** may mask the visual object **411** based on identifying the motion of the visual object **411**. For example, the electronic device **101** may obtain a masking area **416** for masking the visual object **411**. Referring to FIG. **4**, the masking area **416** is illustrated based on a rectangle, but is not limited thereto. The electronic device **101** may obtain a masking area **416** based on a shape of the visual object **411**. For example, the electronic device **101** may remove the obtained masking area **416** from the first video **410**. The electronic device **101** may perform inpainting to remove the masking area. Inpainting may mean changing data corresponding to the masking area **416** to data corresponding to a different area, by using the different area (e.g., the painting area **415**) than the masking area **416**. For example, the electronic device **101** may use a generative adversarial network (GAN) to perform inpainting.

(66) According to an embodiment of the disclosure, the electronic device **101** may identify a size of a second video **420-1** extended from the first video **412** from which the visual object **411** is removed, based on masking the visual object **411**. The electronic device **101** may identify the painting area **415** based on scanning each of a plurality of images of the first video **412**. For example, the painting area **415** may include pixels based on similar color information. The painting area **415** may include pixels based on similar patterns. However, it is not limited thereto. For example, the painting area **415** may include visual objects representing background, such as natural environment, landscape, and/or crowd. For example, the electronic device **101** may obtain the second video **420-1** from the first video **412** including the painting area **415**, based on identifying the painting area **415** including pixels based on similar color information.

(67) According to an embodiment of the disclosure, the electronic device **101** may obtain the second video **420-1** extended from the first video **412** by using pixels and/or data included in the painting area **415**. The electronic device **101** may obtain the second video **420-1** by performing out painting. The second video **420** may be obtained based on extending from each of edges (e.g., edges **410-1**, **410-2**, **410-3**, and **410-4**) of the first video **412**. For example, the electronic device **101** may obtain a part of an extended area adjacent to the edge **410-1**, by using the painting area **415** adjacent to the edge **410-1**. The extended area may mean an area in which the electronic device **101** obtains by using pixels and/or data included in the painting area **415**, based on the size of the

second video **420-1**. However, it is not limited thereto. The electronic device **101** may use a part of the painting area **415** adjacent to the edge **410-3** to obtain a part of the extended area adjacent to the edge **410-1**. Based on symmetry, the electronic device **101** may obtain a part of the extended area by using a part of the painting areas **415** adjacent to the edge **410-3**.

(68) According to an embodiment of the disclosure, the electronic device **101** may adjust a shape of the second video **420-1**, based on generating the second video **420-1** extended from the first video **412**. For example, the electronic device **101** may change the shape of the second video **420-1** based on an aspect ratio of the first video **410**. For example, the electronic device **101** may restore corrupted data in the second video **420-1** to change the shape of the second video **420-1**, by performing inpainting and/or out-painting. The second video **420-1** in which the shape is changed may be substantially similar to a shape (e.g., a square) of the first video **412**. For example, changing the shape of the second video **420-1** may include resizing the size of the second video **420-1**.

(69) According to an embodiment of the disclosure, the electronic device **101** may obtain the second video **420-2** including the visual object **411** by using the second video **420-1**. The electronic device **101** may identify the second video **420-1** extended from the first video **412** in which the visual object **411** is removed, and not including the visual object **411**. The electronic device **101** may obtain the second video **420-2** by including the visual object **411** in the second video **420-1**. For example, the electronic device **101** may obtain the second video **420-2** by rendering the visual object **411** and the second video **420-1**. For example, the electronic device **101** may obtain the second video **420-2** based on synthesizing the visual object **411** and the second video **420-1**. The second video **420-2** may include the first video **410**. The second video **420-2** may be referred to the second video **222** of FIG. 2.

(70) According to an embodiment of the disclosure, the electronic device **101** may identify a time for generating the second video **420-2**, by using the first video **410**. The electronic device **101** may identify a time to be spent to obtain information for displaying the second video **420-2** extended from the first video **410**. The electronic device **101** may identify the time based on a size of the second video **420-2** and/or the number of pixels included in the second video **420-2**. The electronic device **101** may provide a user with a notification for informing the time.

(71) As described above, according to an embodiment of the disclosure, the electronic device **101** may select at least one of a plurality of images included in the first video **410** to obtain the extended second video **420-2** from the first video **410**. The selected at least one may mean an image suitable for performing inpainting and/or out-painting. Pixels included in the selected at least one may include similar color information. The electronic device **101** may identify a time to obtain the second video **420-2**. By providing the time to the user, the electronic device **101** may inform a time for displaying a video (e.g., the first video **410** and the second video **420-2**) together with an external electronic device (e.g., the external electronic device **102** of FIG. 1).

(72) FIG. 5 illustrates an operation in which an electronic device identifies a shape of an external electronic device to display a second video, according to an embodiment of the disclosure. The electronic device **101** of FIG. 5 may be an example of the electronic device **101** of FIGS. 1, 2, 3A, 3B, and 4.

(73) Referring to FIG. 5, according to an embodiment of the disclosure, a state in which the electronic device **101** identifies a shape of the external electronic device **102** in order to display the second video **222** using a camera (e.g., the camera **240** of FIG. 2) is illustrated.

(74) According to an embodiment of the disclosure, the electronic device **101** may initiate driving the camera in response to an input indicating to play the second video **222**. For example, the electronic device **101** may identify a shape of external electronic device **102** using a camera. The electronic device **101** may identify a position of the external electronic device **102** disposed in a displaying area **105** using the camera. The electronic device **101** may obtain the second video **222** including a black area **510**, based on the shape of the external electronic device **102** and/or the

position. For example, the electronic device **101** may block light representing the second video **222** from being projected onto the external electronic device **102** using the black area **510**, by controlling the projection assembly. However, it is not limited thereto.

(75) For example, the electronic device **101** may prevent a part of the second video **222** from being displayed on the external electronic device **102**, by overlapping the second video **222** and displaying at least one layer on the black area **510**. The at least one layer may be generated based on a designated color (e.g., black).

(76) For example, the electronic device **101** may adjust an alpha value (e.g., a parameter indicating transparency) of the black area **510**, within the second video **222**. The electronic device **101** may adjust size, color, and/or alpha value of the black area **510** based on a position and/or number of the external electronic device **102**.

(77) According to an embodiment of the disclosure, when a position and/or direction of the displaying area **105** is changed, the electronic device **101** may change the position of the black area **510** in the second video **222** by controlling the projection assembly based on identifying the external object **330** of FIG. **3B**. The changed position of the black area **510** may correspond to the position of the external electronic device **102** in the changed displaying area **105**. For example, the position of the black area **510** in the second video **222** may include an area corresponding to the first video **410** in the second video **420-2** of FIG. **4**.

(78) As described above, according to an embodiment of the disclosure, the electronic device **101** may obtain the second video **222** including the black area **510**, based on the position of the external electronic device **102** identified using a camera. For example, when the electronic device **101** projects the second video **222** not including the black area **510** by using the projection assembly, a part of the second video **222** may be displayed on the external electronic device **102** positioned in the displaying area **105**. When the part of the second video **222** is displayed on the external electronic device **102**, the part of the second video **222** may overlap a first video (e.g., the first video **115** of FIG. **1**) displayed by the external electronic device **102**. The electronic device **101** may prevent or reduce the part of the second video **222** and the first video from overlapping, by using the black area **510**.

(79) FIG. **6** illustrates an operation in which an electronic device transmits information for a second video to a server according to an embodiment of the disclosure. The electronic device **101** of FIG. **6** may be an example of the electronic device **101** of FIGS. **1**, **2**, **3A**, **3B**, **4**, and **5**. The external electronic device **102** of FIG. **6** may be an example of the external electronic device **102** of FIG. **1**.

(80) Referring to FIG. **6**, a state **600** representing an example of a network environment between an electronic device **101**, a server **605**, and/or an external electronic device **102** is illustrated. The number and/or type of the external electronic device **102** are not limited to those illustrated in FIG. **6**. For example, the external electronic device may include a TV, a notebook, a PC, a tablet PC, and/or a smartphone.

(81) According to an embodiment of the disclosure, the electronic device **101** may transmit information on the second video (e.g., the second video **222** of FIG. **2**) to the server **605** through a communication circuit in the state **600**. For example, information on the second video may be represented as metadata including information on a first video (e.g., the first video **221** of FIG. **2**) corresponding to the second video, a size of the second video, the number (or quality) of pixels included in the second video, data corresponding to the second video, a running time of the second video, resolution corresponding to the second video, and/or a codec available to play the second video.

(82) According to an embodiment of the disclosure, the electronic device **101** may request information on the second video corresponding to the first video to the server **605**, in response to an input indicating to play the first video (e.g., the first video **115** of FIG. **1**) from the external electronic device **102**. The server **605** may transmit information on the second video to the electronic device **101**. Based on receiving information on the second video from the server **605**, the

electronic device **101** may display the second video corresponding to the first video in conjunction with the external electronic device **102** by controlling the projection assembly, in response to the input. The second video may be an example of a video uploaded to the server **605** by another electronic device different from the electronic device **101**.

(83) According to an embodiment of the disclosure, the electronic device **101** may receive information on a first video **610** from the server **605** and/or the external electronic device **102** using a communication circuit.

(84) For example, an aspect ratio of the first video **610** may be different from an aspect ratio of a display (e.g., the display **260** of FIG. 2) of the external electronic device **102**. When the external electronic device **102** displays the first video **610** on the display, the external electronic device **102** may display the first video **610** and a filler box **620** on the display based on the aspect ratio of the display. The filler box **620** may mean a black area used by the external electronic device **102** to display the first video **610** on the display based on the aspect ratio of the display different from the aspect ratio of the first video **610**.

(85) For example, the electronic device **101** may generate a second video **615** corresponding to the aspect ratio of the display of the external electronic device **102** using the first video **610**. An operation in which the electronic device **101** generates the second video **615** using the first video **610** may be substantially similar to an operation in which the electronic device **101** generates the second video **420-2** using the first video **410** in FIG. 4.

(86) According to an embodiment of the disclosure, the electronic device **101** may transmit information indicating the second video **615** to the server **605** and/or the external electronic device **102** using the communication circuit.

(87) For example, the external electronic device **102** may display the second video **615** on the display, based on receiving the second video **615** from the server **605** and/or the electronic device **101**. An aspect ratio of the second video **615** may be the same as the aspect ratio of the display of the external electronic device **102**. The second video **615** may include information on the first video **610**.

(88) As described above, according to an embodiment of the disclosure, the electronic device **101** may upload the second video **615** extended from the first video **610** to the server **605** using the communication circuit. For example, the electronic device **101** may receive information on at least one video from the server **605**. For example, the electronic device **101** may request information on the second video from the server **605**, in response to an input indicating to play the first video, independently of an operation of generating the second video corresponding to the first video. The electronic device **101** may reduce time for generating the second video by using the server **605**. For example, the electronic device **101** may identify the first video based on an aspect ratio different from the external electronic device **102**. The electronic device **101** may transmit the second video based on the aspect ratio of the external electronic device **102** to the external electronic device **102**, by generating the extended second video from the first video. The electronic device **101** may provide a video from which the filler box **620** is removed to the user by generating the second video.

(89) FIG. 7 illustrates a flowchart illustrating an operation of an electronic device according to an embodiment. The electronic device **101** of FIG. 7 may include the electronic device **101** of FIGS. 1, 2, 3A, 3B, and 4 to 6. At least one of operations of FIG. 7 may be performed by the electronic device **101** of FIG. 2 and/or the processor **210** of FIG. 2. Each operations of FIG. 7 may be performed sequentially, but is not necessarily performed sequentially. For example, the sequence of each operation may be changed, and at least two operations may be performed in parallel.

(90) Referring to FIG. 7, according to an embodiment of the disclosure, in operation **710**, the electronic device may obtain first information on a first video displayable through a display of an external electronic device from the external electronic device using a communication circuit. For example, the electronic device may obtain information on the first video (e.g., the first video **221-1**

of FIG. 2) from the external electronic device (e.g., the external electronic device **102** of FIG. 2) using a communication circuit (e.g., the communication circuit **250** of FIG. 2). The first video (e.g., the first video **221** of FIG. 2) stored in the electronic device and the first video (e.g., the first video **221-1** of FIG. 2) stored in the external electronic device may include substantially the same information based on the communication circuit.

(91) Referring to FIG. 7, according to an embodiment of the disclosure, in operation **720**, the electronic device may execute a scan on the first video by using a plurality of images in the first video. The electronic device may execute the scan from an edge area of each of the plurality of images in the first video toward the center area of each of the plurality of images. The electronic device **101** may execute the scan for identifying at least one visual object using the plurality of images in the first video. The electronic device **101** may execute the scan to identify an area to be extended from the first video to the second video, by using the plurality of images. The area to be expanded may include the painting area **415** of FIG. 4. For example, the electronic device may identify pixels included in each of the plurality of images of the first video based on executing the scan. The electronic device may distinguish at least one image for generating the second video from among the plurality of images, based on identifying pixels.

(92) Referring to FIG. 7, according to an embodiment of the disclosure, in operation **730**, the electronic device may identify a time to be spent to obtain second information for displaying the second video extended from the first video to be displayed through a display of the external electronic device, based on the scan. The electronic device may identify the time based on a size of the second video and/or the number of pixels included in the second video. The electronic device may adjust the size of the second video and/or the number of pixels based on setting a time.

(93) For example, the electronic device may adjust the size of the second video based on a size of a plane to display the second video, by using a camera (e.g., the camera **240** of FIG. 2). The electronic device may adjust the size of the second video based on identifying an external object (e.g., the external object **330** of FIG. 3B) adjacent to the plane using the camera.

(94) Referring to FIG. 7, according to an embodiment of the disclosure, in operation **740**, the electronic device may provide a notification for informing a time. The electronic device may transmit a signal indicating the notification to an external electronic device using a communication circuit. The electronic device may display a screen indicating the notification by controlling a projection assembly. The electronic device may output an audio signal indicating the notification using a speaker. The electronic device may transmit a signal indicating the notification to another external electronic device (e.g., a smartphone) different from the external electronic device.

However, it is not limited thereto.

(95) Referring to FIG. 7, according to an embodiment of the disclosure, in operation **750**, after the time has elapsed, the electronic device may display the second video including a black area partially overlapped on the first video displayed through the display of the external electronic device using the projection assembly, based on the second information. For example, the electronic device may display the second video in response to an input indicating to play the second video (e.g., the second video **222** of FIG. 2) after the time has elapsed.

(96) For example, the electronic device may identify a position of the external electronic device and/or a shape of the external electronic device, by using the camera. The electronic device may obtain a black area (e.g., the black area **510** of FIG. 5) corresponding to the position of the external electronic device and/or the shape of the external electronic device. The electronic device may project light indicating the second video including the black area toward a plane adjacent to the external electronic device **102**, by controlling the projection assembly. The electronic device may display the second video synchronized with the first video using the communication circuit, while the external electronic device displays the first video.

(97) FIG. 8 is a signal flowchart illustrating a signal transmitted and received between an electronic device and an external electronic device, according to an embodiment of the disclosure. The

electronic device **101** of FIG. **8** may include the electronic device **101** of FIGS. **1**, **2**, **3A**, **3B**, and **4** to **7**. The external electronic device **102** of FIG. **8** may include the external electronic device **102** of FIGS. **1**, **2**, **3A**, **3B**, and **4** to **7**.

(98) Referring to FIG. **8**, according to an embodiment of the disclosure, the electronic device **101** may receive a signal **801** for a first video (e.g., the first video **115** of FIG. **1**) from the external electronic device **102** in a state that a communication link is established using a communication circuit and the external electronic device **102**. For example, the electronic device **101** may receive an input indicating to play the first video **221** stored in a memory.

(99) Referring to FIG. **8**, according to an embodiment of the disclosure, in operation **802**, the electronic device **101** may identify a time for generating a second video (e.g., the second video **222** of FIG. **2**) from the first video. The time may be different according to a size of the second video and/or quality of the second video. The electronic device **101** may provide the time to a user.

(100) Referring to FIG. **8**, according to an embodiment of the disclosure, in operation **803**, the electronic device **101** may generate the second video extended from the first video. The second video may be generated based on a size exceeding a size of the first video. For example, an aspect ratio of the second video may be different from an aspect ratio of the first video. The electronic device **101** may analyze each of a plurality of images of the first video in order to generate the second video. For example, the electronic device **101** may request information on the second video from a server (e.g., the server **605** of FIG. **6**).

(101) For example, the electronic device **101** may identify an external object adjacent to a plane on which the second video is to be displayed, by using a camera, in order to generate the second video. The electronic device **101** may adjust the size of the second video based on the identification of the external object. However, it is not limited thereto.

(102) Referring to FIG. **8**, according to an embodiment of the disclosure, the electronic device **101** may transmit a signal **804** indicating to play the second video to the external electronic device **102**. For example, the electronic device **101** may upload information indicating the second video to a server (e.g., the server **605** of FIG. **6**), independently of transmitting the signal **804**.

(103) For example, the electronic device **101** may provide a user with a notification indicating that the generation of the second video is completed after the time for generating the second video has elapsed. For example, the electronic device **101** may transmit the signal **804**, in response to an input indicating to play the second video from the user. However, it is not limited thereto. For example, a signal indicating to play the first video corresponding to the second video may be received from the external electronic device **102**.

(104) Referring to FIG. **8**, according to an embodiment of the disclosure, in operation **805**, the electronic device **101** may display the second video by controlling the projection assembly based on transmitting the signal **804**. The electronic device **101** may display a second video including a black area (e.g., the black area **510** of FIG. **5**). A position and/or shape of the black area in the second video may be changed based on a position and/or shape of the external electronic device.

(105) Referring to FIG. **8**, according to an embodiment of the disclosure, in operation **806**, the external electronic device **102** may display the first video on the display, based on receiving the signal **804**. Based on the communication link, displaying the first video on the display by the external electronic device **102** may be performed substantially simultaneously with displaying the second video by the electronic device **101**.

(106) FIG. **9** is a diagram of a network environment related to a metaverse service according to an embodiment of the disclosure.

(107) Metaverse is a combination of the English words Meta, which means “virtual” and “transcendence,” and “Universe,” which means the universe, and refers to a three-dimensional virtual world where social, economic, and cultural activities like the real world take place. Metaverse is a concept that has evolved one step further than virtual reality, and it is characterized by using avatars to not only enjoy games or virtual reality (VR), (cutting-edge technology that

enables people to experience real-life experiences in a computerized virtual world) but also social and cultural activities like real reality. Metaverse service may provide media content for enhancing immersion in the virtual world, based on augmented reality (AR), virtual reality environment (VR), mixed environment (MR) and/or extended reality (XR).

(108) For example, media content provided by the metaverse service may include social interaction content including a game, a concert, a party, and/or meeting based on avatar. For example, the media content may include advertisements, user created content, and/or information for economic activities, such as selling of productions and/or shopping. Ownership of the user created content may be proven by a non-fungible token (NFT) based on blockchain. Metaverse services may support economic activities based on real money and/or cryptocurrency. Virtual content linked to the real world, such as digital twin or life logging, may be provided by the metaverse service.

(109) FIG. 9 is a diagram of a network environment in which a metaverse service is provided through a server according to an embodiment of the disclosure.

(110) Referring to FIG. 9, a network environment **901** may include a server **910**, a user terminal **920** (e.g., a first terminal **920-1** and a second terminal **920-2**), and a network connecting the server **910** and the user terminal **920**. In the network environment **901**, the server **910** may provide a metaverse service to the user terminal **920**. The network may be formed by at least one intermediate node **930** including an access point (AP) and/or a base station. The user terminal **920** may output a user interface (UI) related to the metaverse service to the user of the user terminal **920**, by accessing to the server **910** through the network. Based on the UI, the user terminal **920** may obtain information to be inputted to the metaverse service from the user or output information (e.g., multimedia content) related to the metaverse service to the user.

(111) In this case, the server **910** provides a virtual space so that the user terminal **920** may perform an activity in a virtual space. In addition, by installing an S/W agent to access the virtual space provided by the server **910**, the user terminal **920** may represent information provided by the server **910** to the user or transmit information in which the user wants to represent in the virtual space to the server. The S/W agent may be provided directly through the server **910**, downloaded from a public server, or embedded when purchasing the terminal.

(112) In an embodiment of the disclosure, the metaverse service may be provided to the user terminal **920** and/or the user by using the server **910**. The embodiment is not limited thereto, and the metaverse service may be provided through an individual contact between users. For example, in a network environment **901**, the metaverse service may be provided by a direct connection between the first terminal **920-1** and the second terminal **920-2**, independently of the server **910**. Referring to FIG. 9, in the network environment **901**, the first terminal **920-1** and the second terminal **920-2** may be connected to each other through a network formed by at least one intermediate node **930**. In an embodiment in which the first terminal **920-1** and the second terminal **920-2** are directly connected, any one of the first terminal **920-1** and the second terminal **920-2** may serve as the server **910**. For example, a metaverse environment may be formed with only a connection (e.g., a peer-to-peer (P2P) connection) between device to device.

(113) In an embodiment of the disclosure, the user terminal **920** (or the user terminal **920** including the first terminal **920-1** and the second terminal **920-2**) may be made of various form factors, and may include an output device for providing an image or/and sound to a user and an input device for inputting information to the metaverse service. Examples of various form factors of the user terminal **920** may include a smartphone (e.g., the second terminal **920-2**), an AR device (e.g., the first terminal **920-1**), a VR device, an MR device, a video see through (VST) device, an optical see through (OST) device, a smart lens, a smart mirror, a TV with input/output capability, or a projector.

(114) A network (e.g., a network formed by at least one intermediate node **930**) of the disclosure includes both various broadband networks including third generation (3G), fourth generation (4G), and 5G, and a short-range network (e.g., a wired network or a wireless network that directly

connects the first terminal **920-1** and the second terminal **920-2**) including Wi-fi, BT, and the like. (115) According to an embodiment of the disclosure, in a state of establishing a communication link with the external electronic device, the electronic device may display another video corresponding to a video displayed on the display of the external electronic device by controlling the projection assembly. A method for the electronic device to generate the other video corresponding to the video displayed on the display of the external electronic device may be required.

(116) As described above, according to an embodiment of the disclosure, an electronic device **101** may comprise a communication circuit **250**, a projection assembly **230**, a processor **210**, and a memory **220** storing instructions. The instructions, when executed by the processor, cause the electronic device to obtain first information for a first video **115**, **221**, **410**; **610** displayable through a display **260** of an external electronic device **102**, from the external electronic device using the communication circuit. The instructions, when executed by the processor, cause the electronic device to execute a scan on the first video using a plurality of images in the first video. The instructions, when executed by the processor, cause the electronic device to identify a time to be spent to obtain second information for displaying a second video **110**, **222**, **420-2**, **615** expanded from the first video to be displayed through the display of the external electronic device, based on the scan. The instructions, when executed by the processor, cause the electronic device to provide a notification for informing the time. The instructions, when executed by the processor, cause the electronic device to, after the time has elapsed, display the second video including a black area **510** partially overlapping the first video displayed through the display of the external electronic device, based on the second information, using the projection assembly.

(117) For example, the instructions, when executed by the processor, cause the electronic device to identify the time based on at least one among a size of the second video and the number of pixels included in the second video.

(118) For example, the instructions, when executed by the processor, cause the electronic device to obtain the painting area **415** of each of the plurality of images for generating the second video based on executing the scan. The processor may be configured to generate the second video using a plurality of pixels included in the painting area.

(119) For example, the instructions, when executed by the processor, cause the electronic device to identify motion of an object **411** included in each of the plurality of images. The processor may be configured to obtain a masking area **416** for masking the object, based on the identified motion. The processor may be configured to generate the second video using the masking area.

(120) For example, the instructions, when executed by the processor, cause the electronic device to display the second video synchronized with the first video displayed through the display of the external electronic device using the communication circuit, controlling the projection assembly.

(121) For example, the electronic device **101** may comprise a camera **240**. The processor may be configured to identify an external object **330** located in a space to be displayed the second video, using the camera. the instructions, when executed by the processor, cause the electronic device to adjust a size of the second vided, based on identifying the external object.

(122) For example, the instructions, when executed by the processor, cause the electronic device to obtain the black area, based on a shape of the external electronic device identified using the camera.

(123) For example, the external electronic device may be a first external electronic device. the instructions, when executed by the processor, cause the electronic device to transmit third information for the second video, to a second external electronic device **605** different from the first external electronic device, using the communications circuit.

(124) As described above, according to an embodiment of the disclosure, a method of an electronic device **101** may comprise obtaining first information for a first video **115**, **221**, **410**; **610** displayable through a display **260** of an external electronic device **102**, from the external electronic

device using a communication circuit. The method may comprise executing a scan on the first video using a plurality of images in the first video. The method may comprise identifying a time to be spent to obtain second information for displaying a second video **110, 222, 420-2, 615** expanded from the first video to be displayed through the display of the external electronic device, based on the scan. The method may comprise providing a notification for informing the time. The method may comprise, after the time has elapsed, displaying the second video including a black area **510** partially overlapping the first video displayed through the display of the external electronic device, based on the second information, using a projection assembly **230**.

(125) For example, the identifying the time may comprise identifying the time based on at least one among a size of the second video and the number of pixels included in the second video.

(126) For example, the executing the scan may comprise obtaining the painting area **415** of each of the plurality of images for generating the second video based on executing the scan. The executing the scan may comprise generating the second video using a plurality of pixels included in the painting area.

(127) For example, the executing the scan may comprise identifying motion of an object **411** included in each of the plurality of images. The executing the scan may comprise obtaining a masking area **416** for masking the object, based on the identified motion. The executing the scan may comprise generating the second video using the masking area.

(128) For example, the displaying the second video may comprise displaying the second video synchronized with the first video displayed through the display of the external electronic device using the communication circuit, controlling the projection assembly.

(129) For example, the displaying the second video may comprise identifying an external object **330** located in a space to be displayed the second video, using a camera **240**. The displaying the second video may comprise adjusting a size of the second video, based on identifying the external object.

(130) For example, the displaying the second video may comprise obtaining the black area, based on a shape of the external electronic device identified using the camera.

(131) For example, the external electronic device may be the first external electronic device. The displaying the second video may comprise transmitting third information for the second video, to a second external electronic device different from the first external electronic device, using the communications circuit.

(132) As described above, according to an embodiment of the disclosure, a non-transitory computer readable storage medium storing one or more programs including instructions, the instructions, when executed by a processor **210** of an electronic device **101**, cause the electronic device to obtain first information **115, 221, 410, 610** for a first video displayable through a display **260** of an external electronic device **102**, from the external electronic device using a communication circuit. The instructions, when executed by the processor of the electronic device, cause the electronic device to execute a scan on the first video using a plurality of images in the first video. The instructions, when executed by the processor of the electronic device, cause the electronic device to identify a time to be spent to obtain second information for displaying a second video **110, 222, 420-2, 615** expanded from the first video to be displayed through the display of the external electronic device, based on the scan. The instructions, when executed by the processor of the electronic device, cause the electronic device to provide a notification for informing the time. The instructions, when executed by the processor of the electronic device, cause the electronic device to, after the time has elapsed, display the second video including a black area **510** partially overlapping the first video displayed through the display of the external electronic device, based on the second information, using a projection assembly **230**.

(133) For example, the instructions, when executed by the processor of the electronic device, cause the electronic device to identify the time based on at least one among a size of the second video and the number of pixels included in the second video.

(134) For example, the instructions, when executed by the processor of the electronic device, cause the electronic device to obtain the painting area **415** of each of the plurality of images for generating the second video based on executing the scan. The instructions, when executed by the processor of the electronic device, cause the electronic device to generate the second video using a plurality of pixels included in the painting area.

(135) For example, the instructions, when executed by the processor of the electronic device, cause the electronic device to identify motion of an object **411** included in each of the plurality of images. The instructions, when executed by the processor of the electronic device, cause the electronic device to obtain a masking area **416** for masking the object, based on the identified motion. The instructions, when executed by the processor of the electronic device, cause the electronic device to generate the second video using the masking area.

(136) The device described above may be implemented as a combination of hardware components, software components, and/or hardware components and software components. For example, the devices and components described in the embodiments may be implemented using one or more general purpose computers or special purpose computers, such as processors, controllers, arithmetical logic unit (ALU), digital signal processor, microcomputers, field programmable gate array (FPGA), programmable logic unit (PLU), microprocessor, any other device capable of executing and responding to instructions. The processing device may perform an operating system OS and one or more software applications performed on the operating system. In addition, the processing device may access, store, manipulate, process, and generate data in response to execution of the software. For convenience of understanding, although one processing device may be described as being used, a person skilled in the art may see that the processing device may include a plurality of processing elements and/or a plurality of types of processing elements. For example, the processing device may include a plurality of processors or one processor and one controller. In addition, other processing configurations, such as a parallel processor, are also possible.

(137) The software may include a computer program, code, instruction, or a combination of one or more of them and configure the processing device to operate as desired or command the processing device independently or in combination. Software and/or data may be embodied in any type of machine, component, physical device, computer storage medium, or device to be interpreted by a processing device or to provide instructions or data to the processing device. The software may be distributed on a networked computer system and stored or executed in a distributed manner. Software and data may be stored in one or more computer-readable recording media.

(138) The method according to the embodiment may be implemented in the form of program instructions that may be performed through various computer means and recorded in a computer-readable medium. In this case, the medium may continuously store a computer-executable program or temporarily store the program for execution or download. In addition, the medium may be a variety of recording means or storage means in which a single or several hardware are combined and is not limited to media directly connected to any computer system and may be distributed on the network. Examples of media may include magnetic media, such as hard disks, floppy disks and magnetic tapes, optical recording media, such as compact disc read only memories (CD-ROMs) and digital versatile discs (DVDs), magneto-optical media, such as floptical disks, ROMs, RAMs, flash memories, and the like to store program instructions. Examples of other media include app stores that distribute applications, sites that supply or distribute various software, and recording media or storage media managed by servers.

(139) Although embodiments have been described according to limited embodiments and drawings as above, various modifications and modifications are possible from the above description to those of ordinary skill in the art. For example, even if the described techniques are performed in a different order from the described method, and/or components, such as the described system, structure, device, circuit, and the like are combined or combined in a different form from the

described method or are substituted or substituted by other components or equivalents, appropriate results may be achieved.

(140) While the disclosure has been shown and described with reference to various embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the scope of the disclosure as defined by the appended claims and their equivalents.

Claims

1. An electronic device comprising: a communication circuit; a projection assembly; a processor, and a memory storing instructions, wherein the instructions, when executed by the processor, cause the electronic device to: obtain first information for a first video displayable through a display of an external electronic device, from the external electronic device using the communication circuit, execute a scan on the first video using a plurality of images in the first video, identify a time to be spent to obtain second information for displaying a second video expanded from the first video to be displayed through the display of the external electronic device, based on the scan, provide a notification for informing the time, and after the time has elapsed, display the second video including a black area partially overlapping the first video displayed through the display of the external electronic device, based on the second information, using the projection assembly.
2. The electronic device of claim 1, wherein the instructions, when executed by the processor, cause the electronic device to: identify the time based on at least one among a size of the second video and a number of pixels included in the second video.
3. The electronic device of claim 1, wherein the instructions, when executed by the processor, cause the electronic device to: obtain a painting area of each of the plurality of images for generating the second video based on executing the scan; and generate the second video using a plurality of pixels included in the painting area.
4. The electronic device of claim 1, wherein the instructions, when executed by the processor, cause the electronic device to: identify motion of an object included in each of the plurality of images; obtain a masking area for masking the object, based on the identified motion; and generate the second video using the masking area.
5. The electronic device of claim 1, wherein the instructions, when executed by the processor, cause the electronic device to: display the second video synchronized with the first video displayed through the display of the external electronic device using the communication circuit, controlling the projection assembly.
6. The electronic device of claim 1, comprising: a camera, wherein the instructions, when executed by the processor, cause the electronic device to: identify an external object located in a space to be displayed the second video, using the camera, and adjust a size of the second video, based on identifying the external object.
7. The electronic device of claim 6, wherein the instructions, when executed by the processor, cause the electronic device to: obtain the black area, based on a shape of the external electronic device identified using the camera.
8. The electronic device of claim 1, wherein the external electronic device is a first external electronic device, and wherein the instructions, when executed by the processor, cause the electronic device to: transmit third information for the second video, to a second external electronic device different from the first external electronic device, using the communications circuit.
9. A method of an electronic device, the method comprising: obtaining first information for a first video displayable through a display of an external electronic device, from the external electronic device using a communication circuit; executing a scan on the first video using a plurality of images in the first video; identifying a time to be spent to obtain second information for displaying a second video expanded from the first video to be displayed through the display of the external

electronic device, based on the scan; providing a notification for informing the time; and after the time has elapsed, displaying the second video including a black area partially overlapping the first video displayed through the display of the external electronic device, based on the second information, using a projection assembly.

10. The method of claim 9, wherein the identifying of the time comprises: identifying the time based on at least one among a size of the second video and a number of pixels included in the second video.

11. The method of claim 9, wherein the executing of the scan comprises: obtaining a painting area of each of the plurality of images for generating the second video based on executing the scan; and generating the second video using a plurality of pixels included in the painting area.

12. The method of claim 9, wherein the executing of the scan comprises: identifying motion of an object included in each of the plurality of images; obtaining a masking area for masking the object, based on the identified motion; and generating the second video using the masking area.

13. The method of claim 9, wherein the displaying of the second video comprises: displaying the second video synchronized with the first video displayed through the display of the external electronic device using the communication circuit, controlling the projection assembly.

14. The method of claim 9, wherein the displaying of the second video comprises: identifying an external object located in a space to be displayed the second video, using a camera; and adjusting a size of the second video, based on identifying the external object.

15. The method of claim 14, wherein the displaying the second video comprises: obtaining the black area, based on a shape of the external electronic device identified using the camera.

16. The method of claim 9, wherein the external electronic device is a first external electronic device, and wherein the displaying the second video comprises: transmitting third information for the second video, to a second external electronic device different from the first external electronic device, using the communications circuit.

17. A non-transitory computer readable storage medium storing one or more programs including instructions, that when executed by a processor of an electronic device, cause the electronic device to: obtain first information for a first video displayable through a display of an external electronic device, from the external electronic device using a communication circuit; execute a scan on the first video using a plurality of images in the first video; identify a time to be spent to obtain second information for displaying a second video expanded from the first video to be displayed through the display of the external electronic device, based on the scan; provide a notification for informing the time; and after the time has elapsed, display the second video including a black area partially overlapping the first video displayed through the display of the external electronic device, based on the second information, using a projection assembly.

18. The non-transitory computer readable storage medium of claim 17, wherein the instructions, when executed by the processor of the electronic device, cause the electronic device to: identify the time based on at least one among a size of the second video and the number of pixels included in the second video.

19. The non-transitory computer readable storage medium of claim 17, wherein the instructions, when executed by the processor of the electronic device, cause the electronic device to: obtain a painting area of each of the plurality of images for generating the second video based on executing the scan; and generate the second video using a plurality of pixels included in the painting area.

20. The non-transitory computer readable storage medium of claim 17, wherein the instructions, that when executed by the processor of the electronic device, cause the electronic device to: identify motion of an object included in each of the plurality of images; obtain a masking area for masking the object, based on the identified motion; and generate the second video using the masking area.
