

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250261386

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

HARAGUCHI; Masaru et al.

CAPACITOR DEVICE AND MANUFACTURING METHOD THEREFOR

Abstract

A capacitor device includes: a substrate; a stack capacitor and an interconnect structure. The stack capacitor is disposed on the substrate. The interconnect structure, disposed on the stack capacitor, has an exposed conductive layer configured to have a first conductive pad and a second conductive pad. The first conductive pad is electrically connected to a first electrode of the stack capacitor and the second conductive pad is electrically connected to a second electrode of the stack capacitor.

Inventors: HARAGUCHI; Masaru (Tokyo, JP), FUJIISHI; Yoshitaka (Tokyo, JP), CHEN; Wenliang (Zhubei City, TW)

Applicant: AP Memory Technology Corp. (Zhubei City, TW); AP Memory Technology (Hangzhou) Limited Co. (Hangzhou, CN)

Family ID: 74567929

Assignee: AP Memory Technology Corp. (Zhubei City, TW); AP Memory Technology (Hangzhou) Limited Co. (Hangzhou, CN)

Appl. No.: 19/192196

Filed: April 28, 2025

Related U.S. Application Data

parent US continuation 17085770 20201030 parent-grant-document US 12317521 child US 19192196

parent US continuation-in-part 16609159 20191028 parent-grant-document US 11038012 WO continuation-in-part PCT/JP2017/016977 20170428 child US 17085770

Publication Classification

Int. Cl.: H10D1/68 (20250101); H01L23/522 (20060101)

U.S. Cl.:

CPC H10D1/716 (20250101); H01L23/5226 (20130101);

Background/Summary

PRIORITY CLAIM AND CROSS-REFERENCE [0001] This application is a continuation of pending U.S. application Ser. No. 17/085,770, filed Oct. 30, 2020, which is a continuation-in-part of pending U.S. application Ser. No. 16/609,159, filed Oct. 28, 2019, which is a National Phase of PCT/JP2017/016977, filed Apr. 28, 2017, the entire contents of which are incorporated herein by reference.

FIELD OF THE INVENTION

[0002] The present invention relates to a capacitor device including one or a plurality of capacitor cells formed on a semiconductor substrate, and a manufacturing method thereof.

BACKGROUND OF THE INVENTION

[0003] Capacitor devices that include one or more capacitor cells formed on a semiconductor substrate using semiconductor process technology are known. Such a capacitor device is required to satisfy various requirements such as an increase in capacity, a reduction in size, a reduction in manufacturing cost, and ease of design change.

[0004] Patent Document 1 (U.S. Pat. No. 9,472,690) discloses a trench capacitor having a structure formed in a direction perpendicular to the surface of a semiconductor substrate.

SUMMARY OF THE INVENTION

[0005] Capacitor devices are required to reduce the diameter and spacing of terminals (solder balls, etc.) and the thickness of the capacitor device for further circuit integration.

[0006] In the case of the trench capacitor as disclosed in Patent Document 1, since the trench capacitor is formed in the silicon substrate, when the surface of the silicon substrate is polished in the manufacturing process, it is necessary to polish so as to leave the capacitor portion. Therefore, the thickness (depth) of the silicon substrate that can be reduced by polishing is limited. In addition, the depth of trench capacitors is increasing with the miniaturization of semiconductor process technology, and there are trench capacitors having a depth exceeding 10 μm . Therefore, as the depth of the trench capacitor increases, the final capacitor device thickness also increases. Accordingly, there is a need for a capacitor device having a reduced thickness compared to the conventional one without being subject to such restrictions.

[0007] In addition, when manufacturing a capacitor device having characteristics such as different capacitance, different capacitance density (capacity per unit volume), different breakdown voltage, and/or different positions and number of terminals using semiconductor process technology. If so, it was necessary to remake the mask, which was very expensive. Accordingly, there is a need for a capacitor device that can be manufactured by changing the characteristics of the capacitor described above at a lower cost than before.

[0008] An object of the present invention is to provide a capacitor device including one or a plurality of capacitor cells formed on a semiconductor substrate and having a thickness reduced as compared with the conventional one.

[0009] Another object of the present invention is a capacitor device including one or a plurality of capacitor cells formed on a semiconductor substrate, which can be manufactured by changing the characteristics of the capacitor described above at a lower cost than in the past.

[0010] A further object of the present invention is to provide a method for manufacturing such a

capacitor device.

[0011] An aspect of the present invention is to provide a capacitor device. The capacitor device comprises a substrate; a stack capacitor and an interconnect structure. The stack capacitor is disposed on the substrate. The interconnect structure, disposed on the stack capacitor, has an exposed conductive layer configured to have a first conductive pad and a second conductive pad. The first conductive pad is electrically connected to a first electrode of the stack capacitor and the second conductive pad is electrically connected to a second electrode of the stack capacitor.

THE INVENTION'S EFFECT

[0012] According to the present invention, it is possible to provide a capacitor device including one or a plurality of capacitor cells formed on a semiconductor substrate, the capacitor device having a thickness reduced as compared with the related art.

[0013] In addition, according to the present invention, a capacitor device including one or a plurality of capacitor cells formed on a semiconductor substrate, which can be manufactured by changing the characteristics of the capacitor described above at a lower cost than in the past.

[0014] Furthermore, according to the present invention, a method for manufacturing such a capacitor device can be provided.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0015] FIG. 1 is a perspective view showing a configuration of a capacitor device according to a first embodiment.

[0016] FIG. 2 is a diagram showing a part of a longitudinal section taken along line A1-A1' of the capacitor device of FIG. 1.

[0017] FIG. 3 is a circuit diagram showing an equivalent circuit of the capacitor device of FIG. 2.

[0018] FIG. 4 is a cross-sectional view showing a first state in the manufacturing process of the capacitor device of FIG. 1.

[0019] FIG. 5 is a cross-sectional view showing a second state in the manufacturing process of the capacitor device of FIG. 1.

[0020] FIG. 6 is a cross-sectional view showing a third state in the manufacturing process of the capacitor device of FIG. 1.

[0021] FIG. 7 is a cross-sectional view showing a fourth state in the manufacturing process of the capacitor device of FIG. 1.

[0022] FIG. 8 is a cross-sectional view showing a fifth state in the manufacturing process of the capacitor device of FIG. 1.

[0023] FIG. 9 is a cross-sectional view showing a sixth state in the manufacturing process of the capacitor device of FIG. 1.

[0024] FIG. 10 is a cross-sectional view showing a seventh state in the manufacturing process of the capacitor device of FIG. 1.

[0025] FIG. 11 is a cross-sectional view showing an eighth state in the manufacturing process of the capacitor device of FIG. 1.

[0026] FIG. 12 is a cross-sectional view showing a ninth state in the manufacturing process of the capacitor device of FIG. 1.

[0027] FIG. 13 is a cross-sectional view showing a tenth state in the manufacturing process of the capacitor device of FIG. 1.

[0028] FIG. 14 is a perspective view showing a configuration of a capacitor device according to a second embodiment.

[0029] FIG. 15 is a diagram showing a part of a longitudinal section taken along line A2-A2' of the capacitor device of FIG. 12.

[0030] FIG. **16** is a diagram showing a part of a longitudinal section taken along line A3-A3' of the capacitor device of FIG. **13**.

[0031] FIG. **17** is a circuit diagram showing an equivalent circuit of the capacitor device of FIGS. **15** and **16**.

[0032] FIG. **18** is a top view showing a capacitor device according to a third embodiment in a state where no external terminal is formed.

[0033] FIG. **19** is a top view showing a capacitor device according to a third embodiment in which external terminals **105** and **106** are formed in the capacitor device of FIG. **18**.

[0034] FIG. **20** is a circuit diagram showing an equivalent circuit of the capacitor device of FIG. **18**.

[0035] FIG. **21** is a schematic diagram showing a current flowing through the capacitor device of FIG. **18**.

[0036] FIG. **22** is a top view showing a part of a capacitor device according to a modification of the third embodiment and showing a state in which no external terminal is formed.

[0037] FIG. **23** is a top view showing a configuration of a capacitor device according to a fourth embodiment.

[0038] FIG. **24** is a circuit diagram showing an equivalent circuit of the capacitor device of FIG. **23**.

[0039] FIG. **25** is a top view showing a configuration of a capacitor device according to a fifth embodiment.

[0040] FIG. **26** is a circuit diagram showing an equivalent circuit of the capacitor device of FIG. **25**.

[0041] FIG. **27** is a top view showing a configuration of a capacitor device according to a sixth embodiment.

[0042] FIG. **28** is a circuit diagram showing an equivalent circuit of the capacitor device of FIG. **27**.

[0043] FIG. **29** is a top view showing a configuration of a capacitor device according to a seventh embodiment.

[0044] FIG. **30** is a top view showing a configuration of a capacitor device according to an eighth embodiment.

[0045] FIG. **31** is a top view showing a configuration of a capacitor device according to a ninth embodiment.

[0046] FIG. **32** is a top view showing a configuration of a capacitor device according to a tenth embodiment.

[0047] FIG. **33** is a top view showing a configuration of a capacitor device according to an eleventh embodiment.

[0048] FIG. **34** is a schematic diagram for explaining a method for manufacturing a capacitor device according to third to eleventh embodiments.

[0049] FIG. **35** is a schematic diagram for explaining a method for manufacturing a capacitor device according to third to eleventh embodiments.

[0050] FIG. **36** is a diagram illustrating a top view of a capacitor device according to the embodiment of the present invention.

[0051] FIG. **37** shows a cross-sectional view of a capacitor device according to the embodiment of the present invention.

[0052] FIG. **38** is a diagram illustrating a plurality of capacitor cells in crown type according to an embodiment of the present invention.

[0053] FIG. **39** is a diagram illustrating a plurality of capacitor cells in concave type according to an embodiment of the present invention.

[0054] FIG. **40** is a top view diagram illustrating a plurality of capacitor cells according to an embodiment of the present invention.

[0055] FIG. **41** is a top view diagram illustrating a capacitor device according to an embodiment of the present invention.

[0056] FIG. **42** is a top view diagram illustrating a capacitor device according to an embodiment of the present invention.

[0057] FIG. **43** is a top view diagram illustrating a capacitor device according to an embodiment of the present invention.

[0058] FIG. **44** is a top view diagram illustrating a capacitor device according to an embodiment of the present invention.

[0059] FIG. **45** is a diagram illustrating a wafer-level capacitor devices according to an embodiment of the present invention.

[0060] FIG. **46** is a diagram illustrating a cross-sectional view a diced capacitor device according to an embodiment of the present invention.

DESCRIPTION OF EMBODIMENTS OF THE INVENTION

[0061] For a more complete understanding of the present disclosure and its advantages, reference is now made to the following description taken in conjunction with the accompanying drawings, in which like reference numbers indicate like features. Persons of ordinary skill in the art having the benefit of the present disclosure will understand other variations for implementing embodiments within the scope of the present disclosure, including those specific examples described herein. The drawings are not limited to specific scale and similar reference numbers are used for representing similar elements. As used in the disclosures and the appended claims, the terms “example embodiment,” “exemplary embodiment,” and “present embodiment” do not necessarily refer to a single embodiment, although it may, and various example embodiments may be readily combined and interchanged, without departing from the scope or spirit of the present disclosure. Furthermore, the terminology as used herein is for the purpose of describing example embodiments only and is not intended to be a limitation of the disclosure. In this respect, as used herein, the term “in” may include “in” and “on”, and the terms “a”, “an” and “the” may include singular and plural references. Furthermore, as used herein, the term “by” may also mean “from”, depending on the context. Furthermore, as used herein, the term “if” may also mean “when” or “upon”, depending on the context. Furthermore, as used herein, the words “and/or” may refer to and encompass any and all possible combinations of one or more of the associated listed items.

[0062] Hereinafter, embodiments of the present invention will be described with reference to the drawings.

First embodiment. FIG. **1** is a perspective view showing the configuration of the
[0063] capacitor device according to the first embodiment. The capacitor device of FIG. **1** includes a capacitor cell **30** formed on a semiconductor substrate having a first surface and a second surface. In the example of this specification, the lower surface of the capacitor device is a first surface, and the upper surface of the capacitor device is a second surface. The capacitor cell **30** includes a first electrode including the metal film **2**, a second electrode including the metal film **9**, and an insulating film (not shown in FIG. **1**) formed between the first and second electrodes. In the example of the present specification, the first electrode including the metal film **2** is also referred to as a lower electrode, and the second electrode including the metal film **9** is also referred to as an upper electrode. The capacitor device is electrically connected to the lower electrode including the metal film **2** and electrically connected to at least one first cell terminal including the pad conductor **13** exposed on the upper surface of FIG. **1** and the upper electrode including the metal film **9**. And at least one second cell terminal including a pad conductor **14** exposed on the upper surface shown in the figure. In the example of the present specification, the capacitor device includes a plurality of first cell terminals each including a pad conductor **13** and a plurality of second cell terminals each including a pad conductor **14**.

[0064] FIG. **2** is a diagram showing a part of a longitudinal section taken along the line A1-A1' of the capacitor device of FIG. **1**.

[0065] The capacitor device includes an oxide film **1** exposed on the lower surface. In this specification, the oxide film **1** is also referred to as a first silicon oxide film.

[0066] The capacitor device is formed on the oxide film **1** and formed between a lower electrode including a plurality of stacked conductor films, an upper electrode including a plurality of stacked conductor films, and the lower electrode and the upper electrode. The insulating film **5** is provided.

[0067] The lower electrode includes a metal film **2** made of tungsten and a conductor film **4** made of Ti—TiN as conductor films. The metal film **2** and the conductor film **4** are electrically connected to each other and function as an integrated lower electrode. The conductor film **4** functions as a barrier metal. The lower electrode further includes a nitride film **3**.

[0068] The upper electrode includes a conductor film **6** made of Ti—TiN, doped silicon **8** and a metal film **9** made of tungsten as conductor films. The doped silicon **8** fills the hollow space of the crown type stack capacitor with good coverage and improves its mechanical strength. As the doped silicon **8**, a boron-doped silicon germanium film may be used. The conductor film **6**, the doped silicon **8**, and the metal film **9** are electrically connected to each other and function as an integral upper electrode. The upper electrode further includes a nitride film **7**.

[0069] The insulating film **5** is made of, for example, a high dielectric material. The insulating film **5** includes, as a high dielectric material, for example, one or more of Ta.sub.2O.sub.5 material, Al.sub.2O.sub.3 material, HfO.sub.2 material, ZrO.sub.2 material, and TiO.sub.2 material.

[0070] The lower electrode, the upper electrode, and the insulating film **5** form a capacitor cell **30**. Since each of the lower electrode and the upper electrode includes at least one metal film **2** and **9**, the capacitor cell **30** is formed as an MIM (Metal-Insulator-Metal) capacitor. The capacitor cell **30** is formed as a crown type stack capacitor as shown in FIG. 2.

[0071] The capacitor device includes an interlayer oxide film **12** formed on the metal film **9** of the upper electrode. In this specification, the interlayer oxide film **12** is also referred to as a second silicon oxide film. The capacitor device includes a passivation film **15** formed on the interlayer oxide film **12** and exposed on the upper surface. The passivation film **15** functions as a protective film that protects the upper surface of the capacitor device.

[0072] The capacitor device is electrically connected to the metal film **2** of the lower electrode and is at least one first cell terminal exposed on the upper surface and electrically connected to the metal film **9** of the upper electrode and exposed at least on the upper surface. One second cell terminal. Each first cell terminal includes a pad conductor **13** exposed on the upper surface and a via conductor **10** electrically connected from the pad conductor **13** to the metal film **2** of the lower electrode. In this specification, the pad conductor **13** is also referred to as a first pad conductor, and the via conductor **10** is also referred to as a first via conductor. Each second cell terminal includes a pad conductor **14** exposed on the upper surface and a via conductor **11** electrically connected from the pad conductor **14** to the metal film **9** of the upper electrode. In this specification, the pad conductor **14** is also referred to as a second pad conductor, and the via conductor **11** is also referred to as a second via conductor. A barrier metal **21** is formed around the via conductors **10** and **11**, and a barrier metal **22** is formed on the lower surfaces of the pad conductors **13** and **14**.

[0073] FIG. 3 is a circuit diagram showing an equivalent circuit of the capacitor device of FIG. 2. The conductor films **4** and **6** are capacitively coupled to each other through the insulating film **5**. The conductor film **4** is electrically connected to the pad conductor **13** through the metal film **2** and the via conductor **10**. The conductor film **6** is electrically connected to the pad conductor **14** via the doped silicon **8**, the metal film **9**, and the via conductor **11**. Thereby, the capacitor device functions as a capacitor.

[0074] Next, a manufacturing process of the capacitor device of FIG. 1 will be described with reference to FIG. 4 to FIG. 13.

[0075] FIG. 4 is a cross-sectional view showing a first state in the manufacturing process of the capacitor device of FIG. 1. FIG. 4 shows a state in which the oxide film **1** and the metal film **2** are formed on the silicon substrate **16** and patterned with a resist mask (not shown). In order to form

the oxide film **1** and the metal film **2** on the silicon substrate **16**, a conventional method can be used. For example, in order to form the oxide film **1**, a thermal oxide film having a high film density may be used as a material that can withstand the mechanical strength at the time of back surface polishing described later.

[0076] FIG. **5** is a cross-sectional view showing a second state in the manufacturing process of the capacitor device of FIG. **1**. FIG. **5** shows a state where the nitride film **3**, another oxide film **1A**, and the nitride film **7** are formed after the oxide film **1** and the metal film **2** are formed. Prior art methods can be used to form nitride film **3**, another oxide film **1A**, and nitride film **7**. The nitride film **7** is formed in order to prevent the crown-type stacked capacitor electrode from falling down in a later step.

[0077] FIG. **6** is a cross-sectional view showing a third state in the manufacturing process of the capacitor device of FIG. **1**. FIG. **6** shows a state in which the nitride film **7**, the oxide film **1A**, and the nitride film **3** are patterned and etched to form an opening **17** for the stack capacitor. Prior art methods can be used to pattern and etch the nitride film **7**, the oxide film **1A**, and the nitride film **3**.

[0078] FIG. **7** is a cross-sectional view showing a fourth state in the manufacturing process of the capacitor device of FIG. **1**. FIG. **7** shows a state in which the conductor film **4** is formed and the oxide film **18** is further formed. Prior art methods can be used to form the conductor film **4** and the oxide film **18**.

[0079] FIG. **8** is a sectional view showing a fifth state in the manufacturing process of the capacitor device of FIG. **1**. FIG. **8** shows a state in which the opening **20** for forming the crown type stack capacitor is patterned by the photoresist **19**.

[0080] FIG. **9** is a sectional view showing a sixth state in the manufacturing process of the capacitor device of FIG. **1**. FIG. **9** shows a state in which the photoresist **19** is removed after the oxide film **18** in the opening **20** is etched. Thereafter, the conductor film **4** and the nitride film **7** in the opening **20** are etched using the oxide film **18** as a mask (not shown). At this time, the oxide film **18** and the conductor film **4** serving as a mask are also removed in a self-aligned manner, and a remaining structure of the conductor film **4** forms a crown-shaped structure. Even if the conductor film **4** that becomes a mask remains after etching, it can be removed by performing additional etching only on the conductor film **4**.

[0081] FIG. **10** is a sectional view showing a seventh state in the manufacturing process of the capacitor device of FIG. **1**. FIG. **10** shows a state in which the oxide film **1A** remaining immediately under the side wall of the conductor film **4** and the nitride film **7** is removed from the opening formed at the position of the opening **20** in FIG. **9** by a wet process. As a result, a lower electrode including the metal film **2** and the conductor film **4** as a plurality of stacked conductor films is formed on the oxide film **1**.

[0082] FIG. **11** is a sectional view showing an eighth state in the manufacturing process of the capacitor device of FIG. **1**. In FIG. **11**, the insulating film **5** is formed on the conductor film **4**, and the conductor film **6**, the doped silicon **8**, and the metal film **9** are sequentially formed on the insulating film **5**, and then the insulating film **5**, the doped silicon is formed. **8** and the metal film **9** are patterned by etching. In order to pattern the insulating film **5**, the doped silicon **8**, and the metal film **9** by etching, a conventional method can be used. Thereby, the insulating film **5** is formed on the lower electrode, and the upper electrode including the conductor film **6**, the doped silicon **8**, and the metal film **9** is formed on the insulating film **5** as a plurality of stacked conductor films. Is done.

[0083] FIG. **12** is a cross-sectional view showing a ninth state in the manufacturing process of the capacitor device of FIG. **1**. FIG. **12** shows a state in which an interlayer oxide film **12** is formed and planarized on the nitride film **3** and the metal film **9** of the upper electrode. Prior art methods can be used to form and planarize the interlayer oxide film **12**. The planarization may be performed using a chemical mechanical polishing technique, may be performed by removing only the oxide film on the convex portion by patterning and etching, or a combination thereof.

[0084] FIG. 13 is a cross-sectional view showing a tenth state in the manufacturing process of the capacitor device of FIG. 1. In FIG. 13, via conductors 10 and 11 penetrating the interlayer oxide film 12 are formed, pad conductors 13 and 14 are formed on the interlayer oxide film 12, and a passivation film 15 is formed on the interlayer oxide film 12. In the passivation film 15, openings are formed only in the portions of the pad conductors 13 and 14. Prior art methods can be used to form via conductors 10 and 11. The via conductor 10 and the pad conductor 13 are electrically connected to the metal film 2 of the lower electrode and form at least one first cell terminal exposed on the upper surface. The via conductor 11 and the pad conductor 14 are electrically connected to the metal film 9 of the upper electrode and form at least one second cell terminal exposed on the upper surface. A barrier metal 21 is formed around the via conductors 10 and 11, and a barrier metal 22 is formed on the lower surfaces of the pad conductors 13 and 14.

[0085] Thereafter, the silicon substrate 16 is removed by backside polishing, whereby the capacitor device of FIG. 2 is completed.

[0086] Since the capacitor device according to the first embodiment does not use a silicon substrate in the portion of the capacitor cell 30, the capacitor device operates normally even if the silicon substrate 16 is removed by backside polishing. By removing the silicon substrate 16, the thickness of the capacitor device can be reduced as compared with the conventional case. The total thickness of the capacitor device according to the first embodiment can be reduced to about 4 to 5 μm when configured as a MIM crown type stack capacitor. However, this is not a limitation of the present invention. According to the present invention, the silicon substrate 16 may be kept intact, or the silicon substrate 16 may merely be thinned by the backside polishing polished such that a portion of silicon substrate 16 may left in the final product.

[0087] Further, as the structure of the stack capacitor, a concave (Concaved) stack MIM capacitor according to the prior art may be adopted.

[0088] An advantage of the MIM capacitor is that the desired capacitance can be secured without increasing the thickness of the capacitor device due to the effect of the high dielectric constant of the insulating film.

[0089] For example, by forming the MIM capacitor using a semiconductor process technology such as a general-purpose DRAM, it is possible to realize high density, thinning, and low cost. In general-purpose DRAM semiconductor process technology, a capacitor can be formed without using a structure formed below the surface of a silicon substrate like a trench capacitor, and is very suitable for thinning the capacitor device itself. Furthermore, process development costs can be reduced by diverting general-purpose DRAM semiconductor process technology.

[0090] Second embodiment. FIG. 14 is a perspective view showing the configuration of the capacitor device according to the second embodiment. The capacitor device of FIG. 14 is configured similarly to the capacitor cell 30 of the capacitor device according to the first embodiment, and a plurality of capacitor cells 30-1 stacked in a direction perpendicular to the lower surface and the upper surface of the semiconductor substrate. And 30-2. At least one first cell terminal including the pad conductor 13 is electrically connected to the lower electrode including the metal film 2-1 in the capacitor cell 30-1, and further, the metal film 2-in the capacitor cell 30-2. 2 is electrically connected to the lower electrode. At least one second cell terminal including the pad conductor 14 is electrically connected to the upper electrode including the metal film 9-1 in the capacitor cell 30-1, and further, the metal film 9-2 in the capacitor cell 30-2.

[0091] FIG. 15 is a view showing a part of a longitudinal section taken along line A2-A2' of the capacitor device of FIG. 14. FIG. 16 is a view showing a part of a longitudinal section taken along line A3-A3' of the capacitor device of FIG. 14. The capacitor device of FIG. 14 forms the capacitor cell 30 in FIG. 11, forms the interlayer oxide film 12 in FIG. 12 and planarizes the upper surface, and then repeats the steps described with reference to FIG. 4 to FIG. 12. Repeatedly, another capacitor cell 30 is formed. Thus, a plurality of capacitor cells 30-1 and 30-2 are formed that are stacked in a direction perpendicular to the lower surface and the upper surface of the

semiconductor substrate. After forming the second capacitor cell **30**, the silicon substrate **16** is removed by backside polishing. Next, the via conductor **10** is electrically connected to the metal film **2-1** of the lower electrode in the capacitor cell **30-1**, and further electrically connected to the metal film **2-2** of the lower electrode in the capacitor cell **30-2**. It is formed to be connected. Accordingly, the first cell terminal including the via conductor **10** and the pad conductor **13** is connected to the lower electrodes of the plurality of capacitor cells **30-1** and **30-2**. Via conductor **11** is electrically connected to metal film **9-1** of the upper electrode in capacitor cell **30-1**, and is further electrically connected to metal film **9-2** of the upper electrode in capacitor cell **30-2**. Accordingly, the second cell terminal including the via conductor **11** and the pad conductor **14** is connected to the upper electrodes of the plurality of capacitor cells **30-1** and **30-2**.

[0092] FIG. **17** is a circuit diagram showing an equivalent circuit of the capacitor device of FIGS. **15** and **16**. In the capacitor cell **30-1**, the conductor films **4-1** and **6-1** are capacitively coupled to each other through the insulating film **5-1**. The conductor film **4-1** is electrically connected to the pad conductor **13** through the metal film **2-1** and the via conductor **10**. The conductor film **6-1** is electrically connected to the pad conductor **14** via doped silicon (not shown), the metal film **9-1**, and the via conductor **11**. Similarly, in the capacitor cell **30-2**, the conductor films **4-2** and **6-2** are capacitively coupled to each other through the insulating film **5-2**. The conductor film **4-2** is electrically connected to the pad conductor **13** through the metal film **2-2** and the via conductor **10**. The conductor film **6-2** is electrically connected to the pad conductor **14** via doped silicon (not shown), the metal film **9-2**, and the via conductor **11**. Thereby, the capacitor cells **30-1** and **30-2** are connected in parallel between the pad conductors **13** and **14**.

[0093] In the capacitor device according to the second embodiment, the capacitor cells **30-1** and **30-2** are stacked and connected in parallel, so that the area of the capacitor cell in the horizontal direction is not increased. The capacity can be doubled.

[0094] By repeating the steps of FIGS. **4** to **13** and stacking three or more capacitor cells and connecting them in parallel, it is possible to increase the capacitance three times or more compared to the case of the first embodiment. In that case, the via conductors **10** and **11** may be formed using, for example, a conventional TSV (Through Si Via) technique.

[0095] Also in the capacitor device according to the second embodiment, the thickness of the capacitor device can be reduced as compared with the conventional case by removing the silicon substrate, similarly to the capacitor device according to the first embodiment. The total thickness of the capacitor device according to the second embodiment is only about 6 to 7 μm when configured as a MIM crown type stack capacitor.

[0096] The capacitor device according to the second embodiment also has other advantages similar to those of the capacitor device according to the first embodiment.

[0097] Third embodiment. FIG. **18** is a top view showing the capacitor device according to the third embodiment, in which no external terminal is formed. The capacitor device of FIG. **18** includes a plurality of capacitor cells **C** formed on a rectangular semiconductor substrate having sides extending along a first direction and a second direction orthogonal to each other.

[0098] FIG. **18** includes a plurality of lower electrodes **101**, a plurality of upper electrodes **102**, a plurality of cell terminals **103**, and a plurality of cell terminals **104** formed on a semiconductor substrate. Each lower electrode **101**, each upper electrode **102**, each cell terminal **103**, and each cell terminal **104** are the lower electrode, the upper electrode, the first cell terminal, and the second electrode of the capacitor device according to the first embodiment. It corresponds to each cell terminal. Each lower electrode **101**, each upper electrode **102**, each cell terminal **103**, and each cell terminal **104** are formed on a semiconductor substrate including an oxide film, as in the capacitor device according to the first embodiment. After FIG. **18**, the semiconductor substrate is omitted for simplification of illustration.

[0099] In this specification, the X direction in FIG. **18** or the like is also referred to as a first direction, and the Y direction is also referred to as a second direction. Further, in this specification,

each lower electrode **101**, each upper electrode **102**, each cell terminal **103**, and each cell terminal **104** is referred to as a first electrode, a second electrode, a first cell terminal, and a second cell terminal. Also called a cell terminal.

[0100] The plurality of lower electrodes **101** includes a portion (for example, a portion corresponding to the metal film **2** in FIG. 2) formed in the first layer of the semiconductor substrate, and is disposed at the first period **d1** in the X direction. Arranged in the direction with a second period **d2**. The plurality of upper electrodes **102** include a portion (for example, a portion corresponding to the metal film **9** in FIG. 2) formed in a second layer different from the first layer of the semiconductor substrate, and is arranged with a period **d1** in the X direction, and arranged with a period **d2** in the Y direction. Each upper electrode **102** is arranged so as to be shifted from the lower electrode **101** by a half of the length of the period **d1** in the X direction, and is shifted by a half of the length of the period **d2** in the Y direction.

[0101] Each lower electrode **101** and each upper electrode **102** are partly opposed and capacitively coupled to each other, and each pair of lower electrode **101** and upper electrode **102** that are capacitively coupled to each other form a capacitor cell **C**.

[0102] The plurality of cell terminals **103** includes a portion formed in a third layer different from the first and second layers of the semiconductor substrate, and is arranged with a period **d1** in the X direction and with a period **d2** in the Y direction. The plurality of lower electrodes **101** are electrically connected to each other. At this time, the second layer is located between the first and third layers. The plurality of cell terminals **104** include a portion formed in the third layer of the semiconductor substrate, and are arranged with a period **d1** in the X direction and with a period **d2** in the Y direction, and are electrically connected to the plurality of upper electrodes **102**, respectively. Each cell terminal **104** is arranged so as to be shifted from the cell terminal **103** by half the length of the period **d1** in the X direction, and is shifted by half the length of the period **d2** in the Y direction.

[0103] In other words, the capacitor device includes two lower electrodes **101** adjacent to each other in the Y direction and two upper electrodes **102** adjacent to each other in the X direction (or two lower electrodes **101** adjacent to each other in the X direction; A plurality of unit cells **100** (including two upper electrodes **102** adjacent to each other in the Y direction) are included. Each unit cell **100** includes four capacitor cells **C** formed from a pair of lower electrode **101** and upper electrode **102** that are capacitively coupled to face each other. Capacitor cells **C** having a desired number of rows and columns are formed by repeatedly arranging a plurality of unit cells **100**.

[0104] The capacitor device according to the third embodiment may be configured similarly to the capacitor device according to the first embodiment. In this case, the semiconductor substrate has a first surface and a second surface. The capacitor device includes a first silicon oxide film exposed on the first surface and a passivation film exposed on the second surface. Each lower electrode **101** is formed on the first silicon oxide film and includes a plurality of stacked conductor films. Each upper electrode **102** includes a plurality of stacked conductor films. The capacitor device further includes an insulating film formed between each lower electrode **101** and each upper electrode **102** and a second silicon oxide film formed on each upper electrode **102**. The passivation film is formed on the second silicon oxide film. Cell terminals **103** and **104** are exposed on the second surface. Each capacitor cell **C** is formed of a pair of lower electrode **101** and upper electrode **102** that are capacitively coupled to face each other, and an insulating film formed therebetween.

[0105] Each capacitor cell **C** may be formed as a crown type stack capacitor.

[0106] Each of the cell terminals **103** and **104** may be configured similarly to the first and second cell terminals of the capacitor device according to the first embodiment. In this case, each cell terminal **103** is electrically connected to the first pad conductor formed on the third layer of the semiconductor substrate and one of the plurality of lower electrodes **101** from the first pad conductor. Similarly, each cell terminal **104** is electrically connected to a second pad conductor formed on the third layer of the semiconductor substrate and one of the plurality of upper

electrodes **102** from the second pad conductor.

[0107] FIG. **19** is a top view showing the capacitor device according to the third embodiment, in which external terminals **105** and **106** are formed in the capacitor device of FIG. **18**. The capacitor device further includes at least two external terminals **105** and **106** for electrical connection to a circuit external to the capacitor device. Each external terminal **105** and **106** is electrically connected to a part of the plurality of cell terminals including the plurality of cell terminals **103** and the plurality of cell terminals **104**, respectively.

[0108] The plurality of cell terminals **103** and **104** extend in the Y direction, and form a plurality of cell terminal rows adjacent to each other in the extending direction.

[0109] In the example of FIG. **19**, the capacitor device includes external terminals **105** and **106** each having a comb shape. The external terminal **105** includes a plurality of first portions (portions extending in the Y direction) electrically connected to every 2N cell terminal rows of the plurality of cell terminal rows when N is an integer, and a second portion (a portion extending in the X direction) that connects the first portions to each other. The external terminal **106** also includes a plurality of first portions (portions extending in the Y direction) electrically connected to every 2N cell terminal rows of the plurality of cell terminal rows, and a first portion, and a second portion (a portion extending in the X direction) connected to each other. Each first portion of the external terminal **105** and each first portion of the external terminal **106** are formed so as to be fitted to each other. Each of the external terminals **105** and **106** is arranged such that every N cell terminal rows of the plurality of cell terminal rows are electrically connected to the external terminals **105** and **106** alternately.

[0110] FIG. **19** shows a case where $N=1$. Accordingly, the external terminal **105** is electrically connected to every two cell terminal rows of the plurality of cell terminal rows, and the external terminal **106** is also connected to every two cell terminal rows of the plurality of cell terminal rows. Is electrically connected. Each of the external terminals **105** and **106** is arranged such that a plurality of cell terminal arrays are alternately electrically connected to the external terminals **105** and **106**.

[0111] The external terminals **105** and **106** can be connected to a voltage source having an arbitrary voltage. For example, one of them may be connected to a power source and the other may be grounded.

[0112] The external terminals **105** and **106** are electrically connected to a circuit external to the capacitor device at a portion electrically connected to one of the plurality of cell terminal rows (that is, each first portion of the external terminals **105** and **106**). Instead, the external terminals **105** and **106** may be electrically connected to a circuit outside the capacitor device in their respective second portions (portions extending in the X direction).

[0113] FIG. **20** is a circuit diagram showing an equivalent circuit of the capacitor device of FIG. **18**. As described above, each capacitor cell C is formed between each pair of the lower electrode **101** and the upper electrode **102** that are capacitively coupled to face each other. According to FIG. **20**, one capacitor cell C is formed between the external terminals **105** and **106** adjacent to each other. Therefore, in the entire capacitor device, a plurality of capacitor cells C are connected in parallel.

[0114] FIG. **21** is a schematic diagram showing a current flowing through the capacitor device of FIG. **18**. In FIG. **21**, the external terminals **105** and **106** are omitted. For example, when the external terminal **106** (and hence the cell terminal **104**) is connected to the power supply and the external terminal **105** (and hence the cell terminal **103**) is grounded, a current flows in the direction of the arrow. In order to reduce the equivalent series inductance (ESL), it is effective to lay out the components of the capacitor device so that the currents through the capacitor device cancel each other. As shown in FIG. **21**, the equivalent series inductance can be reduced by arranging each lower electrode **101**, each upper electrode **102**, each cell terminal **103**, and each cell terminal **104** periodically and symmetrically. As shown in FIG. **19**, the equivalent series inductance is best

reduced when a fine pitch bump is formed in a portion where the external terminals **105** and **106** are electrically connected to one of the plurality of cell terminal rows.

[0115] The period **d1** in which each lower electrode **101**, each upper electrode **102**, each cell terminal **103**, and each cell terminal **104** are arranged in the X direction and the period **d2** in which each cell terminal **104** is arranged in the Y direction may be set to be equal to each other. FIG. **18** shows a case where **d1=d2**, for example.

[0116] FIG. **22** is a top view showing a part of a capacitor device according to a modification of the third embodiment and showing a state in which no external terminal is formed. In the example of FIG. **22**, the period **d1** 'in which the upper electrodes **102**, the cell terminals **103**, and the cell terminals **104** are arranged in the X direction and the period **d2**' in the Y direction are set to be different from each other. The unit cell **100A** includes two lower electrodes **101** adjacent in the Y direction and two upper electrodes **102** adjacent in the X direction. The capacitor device of FIG. **22** can also operate in the same manner as the capacitor device of FIG. **18**.

[0117] According to the capacitor device according to the third embodiment, a capacitor device having characteristics such as a different capacitance, a different capacitance density, a different breakdown voltage, and/or a different position and number of terminals from the capacitor device of FIG. **19**. In this case, only a mask for forming the external terminals **105** and **106** may be replaced as described in the following embodiments. In order to form a plurality of capacitor cells C, a plurality of expensive masks are required. According to the capacitor device according to the third embodiment, when customizing the capacitor device according to customer requirements, by changing only one (or a small number) of relatively inexpensive masks, the external terminals **105** and **106** can be changed. The shape can be changed, whereby the characteristics of the capacitor described above can be changed. At this time, it is not necessary to change the mask for forming the plurality of capacitor cells C. As described above, according to the capacitor device according to the third embodiment, it is possible to manufacture the capacitor device by changing the characteristics of the capacitor described above at a lower cost than before.

[0118] Fourth embodiment. FIG. **23** is a top view showing the configuration of the capacitor device according to the fourth embodiment. The capacitor device of FIG. **23** includes external terminals **105A** and **106A** each having a comb shape. FIG. **23** shows a case where **N=2**. Accordingly, the external terminals **105A** extend in the Y direction and are electrically connected to every four cell terminal rows of the plurality of adjacent cell terminal rows, and the external terminal **106A** is also a plurality of cell terminals. It is electrically connected to every four cell terminal rows in the row. Each of the external terminals **105A** and **106A** is arranged such that every two cell terminal rows of the plurality of cell terminal rows are electrically connected to the external terminals **105A** and **106A** alternately.

[0119] The capacitor device of FIG. **23** further includes a plurality of floating terminals **107** that are electrically connected to the cell terminal row including the cell terminals **103** that are not connected to the external terminals **105A** and **106A**, due to the convenience of the semiconductor process technology. Each floating terminal **107** is not connected to other circuits.

[0120] FIG. **24** is a circuit diagram showing an equivalent circuit of the capacitor device of FIG. **23**. According to FIG. **24**, two capacitor cells C are formed between the external terminals **105A** and **106A** adjacent to each other. Therefore, in the entire capacitor device, a plurality of circuits each including two capacitor cells C connected in series are connected in parallel.

[0121] Fifth embodiment. FIG. **25** is a top view showing the configuration of the capacitor device according to the fifth embodiment. The capacitor device of FIG. **25** includes external terminals **105B** and **106B** each having a comb shape. FIG. **25** shows a case where **N=3**. Accordingly, the external terminals **105B** extend in the Y direction and are electrically connected to every six cell terminal rows among the plurality of adjacent cell terminal rows, and the external terminal **106B** also has a plurality of cell terminals. It is electrically connected to every six cell terminal rows in the row. Each of the external terminals **105B** and **106B** is arranged such that every three cell

terminal rows of the plurality of cell terminal rows are electrically connected to the external terminals **105B** and **106B** alternately.

[0122] The capacitor device of FIG. **25** further includes a plurality of floating terminals **107** and **108** that are electrically connected to cell terminal rows that are not connected to the external terminals **105B** and **106B**, respectively, for the convenience of semiconductor process technology. Each floating terminal **107** is electrically connected to a cell terminal row including cell terminals **103**, and each floating terminal **108** is electrically connected to a cell terminal row including cell terminals **104**. Each floating terminal **107** and **108** is not connected to other circuits.

[0123] FIG. **26** is a circuit diagram showing an equivalent circuit of the capacitor device of FIG. **25**. According to FIG. **26**, three capacitor cells C are formed between the external terminals **105B** and **106B** adjacent to each other. Therefore, in the entire capacitor device, a plurality of circuits each including three capacitor cells C connected in series are connected in parallel.

[0124] Sixth embodiment. FIG. **27** is a top view showing the configuration of the capacitor device according to the sixth embodiment. The capacitor device of FIG. **27** includes external terminals **105C** and **106C** each having a comb shape. FIG. **27** shows a case where $N=4$. Therefore, the external terminal **105C** extends in the Y direction and is electrically connected to every eight cell terminal rows of the plurality of adjacent cell terminal rows, and the external terminal **106C** is also a plurality of cell terminals. It is electrically connected to every eight cell terminal rows in the row. Each of the external terminals **105C** and **106C** is arranged such that every four cell terminal rows of the plurality of cell terminal rows are electrically connected to the external terminals **105C** and **106C** alternately.

[0125] The capacitor device of FIG. **27** further includes a plurality of floating terminals **107** and **108** that are electrically connected to cell terminal rows that are not connected to the external terminals **105C** and **106C**, respectively, due to the convenience of semiconductor process technology. Each floating terminal **107** is electrically connected to a cell terminal row including cell terminals **103**, and each floating terminal **108** is electrically connected to a cell terminal row including cell terminals **104**. Each floating terminal **107** and **108** is not connected to other circuits.

[0126] FIG. **28** is a circuit diagram showing an equivalent circuit of the capacitor device of FIG. **27**. According to FIG. **28**, four capacitor cells C are formed between the external terminals **105C** and **106C** adjacent to each other. Therefore, in the entire capacitor device, a plurality of circuits each including four capacitor cells C connected in series are connected in parallel.

[0127] Similarly to the capacitor devices according to the third to sixth embodiments, when N is an integer equal to or greater than 5, a pair of external terminals includes a pair of cell terminal rows every N of the plurality of cell terminal rows. The position may be arranged so that it may be electrically connected to an external terminal alternately.

[0128] According to the capacitor devices according to the third to sixth embodiments, the number of capacitor cells C connected in series can be changed by changing the shape of the external terminal. The number of capacitor cells C connected in series is inversely proportional to the capacity density and breakdown voltage of the capacitor device. By changing only the mask for the external terminals according to customer requirements, a capacitor device having an optimum capacity density and withstand voltage can be manufactured at low cost.

[0129] Seventh embodiment. FIG. **29** is a top view showing the configuration of the capacitor device according to the seventh embodiment. The plurality of external terminals **105** and **106** are not limited to being formed in the same layer. In the capacitor device of FIG. **29**, the external terminal **105** is formed below the lower electrode **101**, and the external terminal **106** is formed above the upper electrode **102**. The capacitor device according to the seventh embodiment can also operate in the same manner as the capacitor device according to the third embodiment.

[0130] Eighth embodiment. FIG. **30** is a top view showing the configuration of the capacitor device according to the eighth embodiment. The plurality of cell terminals **103** and **104** extend in the X direction and are adjacent to each other in the extending direction instead of the cell terminal rows

extending in the Y direction as in the third to seventh embodiments. The cell terminal array may be formed.

[0131] In the example of FIG. 30, the capacitor device includes external terminals **105D** and **106D** each having a comb shape. The external terminal **105D** has a plurality of first portions (portions extending in the X direction) electrically connected to every 2N cell terminal rows of the plurality of cell terminal rows when N is an integer, and a second portion (a portion extending in the Y direction) that connects the first portions to each other. The external terminal **106D** also includes a plurality of first portions (portions extending in the X direction) electrically connected to every 2N cell terminal rows of the plurality of cell terminal rows, and a first portion, and a second portion (a portion extending in the Y direction) connected to each other. Each first portion of the external terminal **105D** and each first portion of the external terminal **106D** are formed so as to be fitted to each other. Each of the external terminals **105D** and **106D** is arranged such that every N cell terminal rows of the plurality of cell terminal rows are electrically connected to the external terminals **105D** and **106D** alternately.

[0132] FIG. 30 shows a case where $N=1$. Accordingly, the external terminal **105D** is electrically connected to every two cell terminal rows of the plurality of cell terminal rows, and the external terminal **106D** is also connected to every two cell terminal rows of the plurality of cell terminal rows. Is electrically connected. Each of the external terminals **105D** and **106D** is arranged such that a plurality of cell terminal arrays are alternately electrically connected to the external terminals **105D** and **106D**.

[0133] The external terminals **105D** and **106D** are electrically connected to a circuit outside the capacitor device in a portion electrically connected to one of the plurality of cell terminal rows (that is, each first portion of the external terminals **105D** and **106D**). May be connected. Instead, the external terminals **105D** and **106D** may be electrically connected to a circuit outside the capacitor device in their respective second portions (portions extending in the Y direction).

[0134] Similarly to the capacitor devices according to the fourth to sixth embodiments, when N is an integer equal to or larger than 2, a pair of external terminals includes a pair of cell terminal rows every N of the plurality of cell terminal rows. The position may be arranged so that it may be electrically connected to an external terminal alternately.

[0135] The capacitor device according to the eighth embodiment has an effect that the shape of the external terminal and the position at which the external terminal is electrically connected to a circuit outside the capacitor device can be customized according to customer requirements. The capacitor device may include external terminals **105D** and **106D** formed as in the eighth embodiment, and these external terminals **105D** and **106D** are short sides (sides extending in the Y direction) of the rectangular capacitor device, may be electrically connected to a circuit outside the capacitor device. Instead, the capacitor device may include external terminals **105** and **106** formed as in the third to seventh embodiments, and these external terminals **105** and **106** are the length of the rectangular capacitor device. The side (side extending in the X direction) may be electrically connected to a circuit outside the capacitor device.

[0136] The equivalent series inductance is higher in the third to seventh embodiments than in the case where the short side of the rectangular capacitor device is electrically connected to a circuit outside the capacitor device as in the eighth embodiment. Thus, the case where the long side of the rectangular capacitor device is electrically connected to a circuit outside the capacitor device is reduced.

[0137] Ninth embodiment. FIG. 31 is a top view showing the configuration of the capacitor device according to the ninth embodiment.

[0138] The plurality of cell terminals **103** and **104** extend in the Y direction, and form a plurality of cell terminal rows adjacent to each other in the extending direction.

[0139] The capacitor device includes external terminals **111** and **112** each having a comb shape, and an external terminal **113** having a fishbone shape. The external terminal **113** includes a

plurality of first portions (portions extending in the Y direction) electrically connected to every 2N cell terminal rows of the plurality of cell terminal rows when N is an integer, and a second portion (a portion extending in the X direction) for connecting the first portions of the external terminals **113** to each other at the center of the first portions of the external terminals **113**. The external terminal **111** includes a plurality of first portions (extending in the Y direction) that are electrically connected to a part of the plurality of cell terminals included in every 2N cell terminal rows of the plurality of cell terminal rows, and a second portion (a portion extending in the X direction) that connects the first portions of the external terminals **111** to each other. The external terminal **111** is formed on the first side with respect to the second portion of the external terminal **113** so as to be fitted to the first portion of the external terminal **113**. The external terminal **112** includes a plurality of first portions (extending in the Y direction) that are electrically connected to a part of the plurality of cell terminals included in every 2N cell terminal rows of the plurality of cell terminal rows, and a second portion (a portion extending in the X direction) that connects the first portions of the external terminals **112** to each other. The external terminal **112** is formed to be fitted to the first portion of the external terminal **113** on the second side opposite to the first side with respect to the second portion of the external terminal **113**. Each of the external terminals **111** to **113** is arranged such that every N cell terminal rows of the plurality of cell terminal rows are electrically connected to the external terminals **111** and **112** and the external terminal **113** alternately.

[0140] FIG. **31** shows a case where $N=1$. Accordingly, the external terminal **113** is electrically connected to every two cell terminal rows of the plurality of cell terminal rows. The external terminal **111** is electrically connected to a part of the plurality of cell terminals included in every two cell terminal rows of the plurality of cell terminal rows. Each of the external terminals **112** to **113** electrically connected to a part of the plurality of cell terminals included in every two cell terminal columns of the plurality of cell terminal columns which are arranged so as to be electrically connected to the external terminals **111** and **112** and the external terminal **113** alternately.

[0141] The external terminals **111** and **112** may be electrically connected to a circuit outside the capacitor device on the long side (side extending in the X direction) of the capacitor device. The external terminal **113** may be electrically connected to a circuit outside the capacitor device on the short side (side extending in the Y direction) of the capacitor device.

[0142] The external terminal **113** is connected to a power source, for example, and the external terminals **111** and **112** are grounded, for example.

[0143] The capacitor device according to the ninth embodiment has an effect of reducing the equivalent series inductance compared to the third to eighth embodiments by changing the shape of the external terminal.

[0144] Tenth embodiment. FIG. **32** is a top view showing the configuration of the capacitor device according to the tenth embodiment.

[0145] The plurality of cell terminals **103** and **104** extend in the Y direction, and form a plurality of cell terminal rows adjacent to each other in the extending direction.

[0146] The capacitor device includes external terminals **111A** and **112A** each having a comb shape, and an external terminal **113A** having a meander shape. The external terminal **113A** has a plurality of first portions (portions extending in the Y direction) electrically connected to every 2N cell terminal rows of the plurality of cell terminal rows when N is an integer. A plurality of second portions (portions extending in the X direction) that connect the first portions of the external terminals **113A** to each other at either of the longitudinal ends of the first portions of the external terminals **113A**. The external terminal **111A** includes a plurality of first portions (portions extending in the Y direction) electrically connected to every 4N cell terminal rows of the plurality of cell terminal rows, and each of the external terminals **111A**. And a second portion (a portion extending in the X direction) that connects the first portions to each other. The external terminal **111A** is formed on the first side with respect to the external terminal **113A** so as to be fitted to the

first portion of the external terminal **113A**. The external terminal **112A** includes a plurality of first portions (portions extending in the Y direction) electrically connected to every 4N cell terminal rows of the plurality of cell terminal rows, and each of the external terminals **112A**, and a second portion (a portion extending in the X direction) that connects the first portions to each other. The external terminal **112A** is formed to be fitted to the first portion of the external terminal **113A** on the second side opposite to the first side with respect to the external terminal **113A**. Each of the external terminals **111A** to **113A** is arranged such that every N cell terminal rows of the plurality of cell terminal rows are electrically connected to the external terminals **111A** or **112A** and the external terminals **113A** alternately.

[0147] FIG. **32** shows a case where $N=1$. Accordingly, the external terminal **113A** is electrically connected to every two cell terminal rows of the plurality of cell terminal rows. The external terminal **111A** is electrically connected to every four cell terminal rows of the plurality of cell terminal rows. The external terminal **112A** is electrically connected to every four cell terminal rows of the plurality of cell terminal rows. Each of the external terminals **111A** to **113A** is arranged such that a plurality of cell terminal arrays are alternately electrically connected to the external terminals **111A** or **112A** and the external terminals **113A**.

[0148] The external terminals **111A** and **112A** may be electrically connected to a circuit outside the capacitor device on the long side (side extending in the X direction) of the capacitor device. The external terminal **113A** may be electrically connected to a circuit outside the capacitor device on the short side (side extending in the Y direction) of the capacitor device.

[0149] The external terminal **113A** is connected to a power source, for example, and the external terminals **111A** and **112A** are grounded, for example.

[0150] According to the capacitor device of the tenth embodiment, by changing the shape of the external terminal, it is equivalent to the third to eighth embodiments as in the case of the ninth embodiment. There is an effect of reducing the series inductance.

[0151] Eleventh embodiment. FIG. **33** is a top view showing the configuration of the capacitor device according to the eleventh embodiment. The capacitor device may include four or more external terminals.

[0152] The plurality of cell terminals **103** and **104** extend in the Y direction, and form a plurality of cell terminal rows adjacent to each other in the extending direction.

[0153] The capacitor device includes a plurality of sets of external terminals each including first and second external terminals. In the example of FIG. **33**, a set including the external terminals **121** and **125**, a set including the external terminals **122** and **126**, a set including the external terminals **123** and **126**, and a set including the external terminals **124** and **127** are provided. Each of the first and second external terminals of each set includes a portion that is electrically connected to at least one cell terminal row of the plurality of cell terminal rows. Each of the first and second external terminals of each set is such that when N is an integer, every N cell terminal rows of the plurality of cell terminal rows are alternately connected to the first and second external terminals, arranged to be connected to each other.

[0154] FIG. **33** shows a case where $N=1$.

[0155] The external terminals **125** to **127** are connected to a power source, for example, and the external terminals **121** to **124** are grounded, for example. In this case, in each of the external terminals **121** to **127**, a plurality of cell terminal arrays are alternately electrically connected to the external terminals **125** to **127** connected to the power source and the grounded external terminals **121** to **124**. Further, among the long sides (sides extending in the X direction) of the capacitor device, the external terminals **125** and **126** connected to the power source and the external terminals **122** and **124** grounded are alternately provided on the +Y side. Similarly, of the long sides (sides extending in the X direction) of the capacitor device, the external terminals **126** and **127** connected to the power source and the external terminals **121** and **123** connected to the ground alternately on the -Y side side.

[0156] The capacitor device according to the eleventh embodiment has an effect of further reducing the equivalent series inductance compared to the ninth and tenth embodiments by changing the shape of the external terminal.

[0157] The capacitor devices according to the third to eleventh embodiments can be manufactured, for example, by the following manufacturing process.

[0158] The manufacturing method includes a plurality of lower electrodes **101** including a portion formed in a first layer of a semiconductor substrate, arranged at a period **d1** in the X direction and arranged at a period **d2** in the Y direction. A plurality of upper electrodes including a step of forming an electrode **101** and a portion formed in a second layer different from the first layer of the semiconductor substrate, the electrodes being arranged at a period **d1** in the X direction, and in the Y direction; forming a plurality of upper electrodes **102** arranged at a period **d2**. The step of forming each upper electrode **102** is arranged so as to be shifted by half the length of the period **d1** in the X direction with respect to each lower electrode **101** and shifted by half the length of the period **d2** in the Y direction.

[0159] Each lower electrode **101** and each upper electrode **102** are partly opposed and capacitively coupled to each other, and each pair of lower electrode **101** and upper electrode **102** that are capacitively coupled to each other form a capacitor cell C.

[0160] The manufacturing method includes a plurality of cell terminals **103** including a portion formed in a third layer different from the first and second layers of the semiconductor substrate, arranged at a period **d1** in the X direction, and a period in the Y direction. A step of forming a plurality of cell terminals **103** arranged at **d2** and electrically connected to the plurality of lower electrodes **101**, and a plurality of cell terminals **104** including a portion formed in the third layer of the semiconductor substrate and forming a plurality of cell terminals **104** arranged in the X direction at a period **d1** and arranged in the Y direction at a period **d2** and electrically connected to the plurality of upper electrodes **102**, respectively, is performed. The second layer is located between the first and third layers. The step of forming each cell terminal **104** is arranged with respect to each cell terminal **103** by being shifted by half the length of the period **d1** in the X direction and by being shifted by half the length of the period **d2** in the Y direction.

[0161] The manufacturing method further includes forming at least two external terminals that are respectively electrically connected to a part of the plurality of cell terminals including the plurality of cell terminals **103** and the plurality of cell terminals **104**.

[0162] FIGS. **34** and **35** are schematic views for explaining the capacitor device manufacturing method according to the third to eleventh embodiments.

[0163] At present, a capacitor device of a type called MLCC (multilayer ceramic capacitor) is generally used as a decoupling capacitor. Many of such capacitor devices have a rectangular parallelepiped outer shape and are external terminals having the shapes described in the third to eleventh embodiments, and have been described in the third to eleventh embodiments. Thus, an external terminal connected to an external circuit is provided. Various configurations can be taken by providing compatibility with MLCC when mounting the capacitor device and changing only one mask to meet customer requirements.

[0164] MLCC capacitor devices are available in various sizes. When manufacturing a capacitor device, a scribe line and a guard ring are arranged so that a chip having the smallest size can be cut out from a silicon wafer. In the capacitor device according to the third to eleventh embodiments of the present invention, the size of the capacitor device can be changed by changing only three masks as described below. Thereafter, by removing the scribe line and the guard ring, it is possible to connect the chips of each capacitor device with metal wiring. For this reason, the size of the capacitor device can be changed to be scalable.

[0165] Referring to FIG. **34**, metal wiring **211** used as a scribe line and a guard ring is formed on a semiconductor substrate in the manufacturing process of the capacitor device. The capacitor device region **201** has, for example, a 05025 size (500×250 μm). When manufacturing a capacitor device

having a size larger than that of the region **201**, as shown in FIG. **35**, a metal wiring **212** is formed on the semiconductor substrate. Thereby, for example, the region **202** of the capacitor device having a 1005 size (1000×500 μm) can be obtained.

[0166] The manufacturing method performs the following steps according to a desired position where the external terminal is electrically connected to a circuit outside the capacitor device, a desired capacitance and desired breakdown voltage of the capacitor device, and a size of the capacitor device. That is, the manufacturing method includes a step of selecting a first mask for forming a metal wiring used as a scribe line and a guard ring, a step of selecting a second mask for forming an external terminal, selecting a third mask for forming a cell terminal for connecting the metal wiring and the external terminal to each other among the cell terminals.

[0167] According to the capacitor devices according to the third to eleventh embodiments, only a small number of masks need be changed, so that the design change of the capacitor device can be performed at low cost.

[0168] When it is planned to use the capacitor device of FIG. **18** for a plurality of applications, the number of rows and/or columns of the capacitor cell C of the capacitor device is equal to the number of capacitor cells connected in series required for each application, set to least common multiple or multiple.

[0169] According to the present invention, when the capacitor device with a specific size (e.g. 05025 size or 1005 size) is manufactured, i.e. when the capacitor device is diced to form a discrete capacitor device, the appearance characteristic of the capacitor device may be different from the appearance characteristic of the existing MLCC capacitor device. FIG. **36** is a diagram illustrating a top view of a capacitor device **3600** according to the embodiment of the present invention. FIG. **37** shows a cross-sectional view of the capacitor device **3600** according to the embodiment of the present invention, in which the cross-sectional view is taken along line B-B' in FIG. **36**. For brevity, the numerals of elements in the capacitor device **3600** are similar to those in FIGS. **13**, **18**, **19**, and **20**. The capacitor device **3600** is a diced capacitor device that is fabricated by the general-purpose DRAM semiconductor process technology. In this embodiment, the capacitor device **3600** comprises two capacitor unit cells (e.g. the unit cell **100**), however this is not a limitation of the present invention. The capacitor device **3600** may comprise multiple capacitor unit cells, in which the capacitor unit cells may be connected in series and/or in parallel as described in the above paragraphs. It is noted that the size of the capacitor device **3600** may also affect the ESR or parasitic inductance effect of the capacitor device **3600**. According to an embodiment, the width as well as the length of the capacitor device **3600** falls within the range of 10 μm to 50 μm may have a relatively good balance for ESL effect and density.

[0170] According to the embodiment, the capacitor device **3600** comprises the substrate **16**, the oxide layer **1**, the interlayer oxide film **12**, and the external terminals **105** and **106**, wherein the substrate **16** may be a semiconductor substrate or a glass substrate, the oxide layer **1** is an insulation layer, the interlayer oxide film **12** may be an insulation film, and the external terminals **105** and **106** may be the two conductive pads of the capacitor device **3600**. The external terminals **105** and **106** may be formed on the exposed metal layer or the top conductive or metal layer of the interconnect layer on the substrate **16**. The external terminal **105** may be disposed on a first side on the top surface of the capacitor device **300** while the external terminal **106** may be disposed on a second side on the top surface of the capacitor device **300**, and the second side may be opposite to the first side as shown in FIG. **36**. However, this is not a limitation of the present invention. According the embodiment, when the substrate **16** is a glass substrate, the ESL or parasitic inductance effect may be improved. Moreover, the capacitor unit cells **100** are formed inside and covered by the interlayer oxide film **12** on the substrate **16**, and thus the capacitor unit cells **100** are not exposed elements of the capacitor device **3600**. Each of the capacitor unit cells **100** is a stack capacitor. As shown in FIG. **37**, the external terminal **105** is electrically connected to the lower electrode (i.e. the metal film **2**) of the capacitor unit cells **100** through the cell terminals **103**, and

the external terminal **106** is electrically connected to the upper electrode (i.e. the metal film **9**) of the capacitor unit cells **100** through the cell terminals **104**. According to the embodiment, as shown in FIG. **36**, the external terminal **105** further comprises a plurality of conductive portions **1052**, and each of the first conductive portions **1052** having a first terminal coupled to the conductive pad of external terminal **105**, and a second terminal extending toward the conductive pad of external terminal **106** and the second terminal is not electrically connected to the external terminal **106**. The external terminal **106** further comprises a plurality of conductive portions **1062**, and each of the first conductive portions **1062** having a first terminal coupled to the conductive pad of external terminal **106**, and a second terminal extending toward the conductive pad of external terminal **105** and the second terminal is not electrically connected to the external terminal **105**.

[0171] According to the present invention, the conductive portions **1052** and **1062** may be the above mentioned comb shape structures of the capacitor device. In the embodiment as shown in FIG. **36**, the conductive portion **1052** as well as the conductive portion **1062** may not be a regular rectangle layer. More specifically, the shape of the conductive portion **1052** as well as the conductive portion **1062** is formed by alternating rectangle or square metal layers. Moreover, each of the cell terminals **103** of the capacitor cell **100** has a first terminal electrically connected to the conductive portions **1052**, and a second terminal electrically connected to the metal film **2** (i.e. the lower electrode) of the capacitor cell **100**. Each of the cell terminals **104** of the capacitor unit cell **100** has a first terminal electrically connected to the conductive portions **1062**, and a second terminal electrically connected to the metal film **9** (i.e. the upper electrode) of the capacitor unit cell **100**. The cell terminals **103** and **104** may be a plurality of via conductors. It is noted that, for description purpose, the cell terminals **103**, the cell terminals **104**, the metal film **9**, and the metal film **2**, which are disposed below the external terminal **105** and the external terminal **106** are also shown in FIG. **36**.

[0172] According to the embodiment, the substrate **16** has a substrate surface **3602**. The oxide layer **1** is formed on the substrate surface **3602**. The metal film **2** (i.e. the lower electrode) of the capacitor unit cell(s) **100** is formed on the upper surface of the oxide layer **1**. It is noted that the oxide layer **1** may be an optional insulation layer. When the oxide layer **1** is omitted in another embodiment, the metal film **2** of the capacitor unit cell(s) **100** may be formed on the substrate surface **3602** of the substrate **16**.

[0173] According to the present embodiment, for a capacitor unit cell **100**, a plurality of capacitor cells **3702** are formed between the metal film **2** and the metal film **9**. The configuration of the capacitor cells **3702** may be the crown type capacitive structure or concave type capacitive structure. FIG. **38** is a diagram illustrating a plurality of capacitor cells **3802** in crown type according to an embodiment of the present invention. For description purpose, some element numerals in FIG. **38** are similar to the element numerals in FIG. **13**. For each capacitor cell **3802** in crown type, the capacitive unit **3802** comprises a first conductor film **3804**, a second conductor film **3806**, a third conductor film **3808**, a first insulating film **3810**, and a second insulating film **3812**. The first conductor film **3804**, the second conductor film **3806**, the third conductor film **3808**, the first insulating film **3810**, and the second insulating film **3812** are disposed between the metal film **2** and the metal film **9**. The insulating films **3810** and **3812** are composed of high-k (high dielectric) material. For example, the high-k material may contain at least one of the oxides of Lanthanum, Hafnium, and Zirconium.

[0174] More specifically, the first conductor film **3804** and the second conductor film **3806** have first portions electrically connected to the metal film **9**, and the first conductor film **3804** and the second conductor film **3806** have second portions vertically extending toward the metal film **2** from the metal film **9**. The second portions of the first conductor film **3804** and the second conductor film **3806** are disconnected from the metal film **2**. The first portions may be the base portions of the first conductor film **3804** and the second conductor film **3806** respectively. The second portions may be the top portions of the first conductor film **3804** and the second conductor

film **3806** respectively. Moreover, the third conductor film **3808** has a first portion electrically connected to the metal film **2**, and a second portion vertically extending toward the metal film **9** from the metal film **2**. The first portion may be the base portion of the third conductor film **3808**, and the second portion may be the top portion of the third conductor film **3808**. The first insulating film **3810** is disposed between the first conductor film **3804** and the third conductor film **3808**. The second insulating film **3812** is disposed between the second conductor film **3806** and the third conductor film **3808**. According to the embodiment, the capacitor cell **3802** may be similar to the capacitor cell **30**, the first conductor film **3804** and the second conductor film **3806** may be similar to the conductor film **6**, the third conductor film **3808** may be similar to the conductor film **4**, and the first insulating film **3810** and the second insulating film **3812** may be similar to the insulating films **5** as shown in the above FIG. **13**, thus the detailed description is omitted here for brevity.

[0175] FIG. **39** is a diagram illustrating a plurality of capacitor cells **3902** in concave type according to an embodiment of the present invention. For description purpose, some element numerals in FIG. **39** are similar to the element numerals in FIG. **13**. For each capacitor cell **3902** in concave type, the capacitor cell **3902** comprises a first conductor film **3904**, a second conductor film **3906**, and an insulating film **3908**. The first conductor film **3904**, the second conductor film **3906**, and the insulating film **3908** are disposed between the metal film **2** and the metal film **9**. More specifically, the first conductor film **3904** has a first portion electrically connected to the metal film **9**, and a second portion vertically extending toward the metal film **2** from the metal film **9**. The second portion of the first conductor film **3904** is disconnected from the metal film **2**. The first portion may be the base portion of the first conductor film **3904**. The second portion may be the top portion of the first conductor film **3904**. The insulating film **3908** is disposed between the first conductor film **3904** and the second conductor film **3906**. According to the embodiment, the capacitor cell **3902** may be similar to the capacitor cell **30**, the first conductor film **3904** may be similar to the conductor film **6**, the second conductor film **3906** may be similar to the conductor film **4**, and the insulating film **3908** may be similar to the insulating films **5** as shown in the above FIG. **13**, thus the detailed description is omitted here for brevity.

[0176] FIG. **40** is a top view diagram illustrating a plurality of capacitor cells **4000** according to an embodiment of the present invention. The capacitor cells **4000** may be a plurality of capacitor cells **3802** or a plurality of capacitor cells **3902**. For brevity, the capacitor cells **4000** in FIG. **40** are a plurality of capacitor cells **3902**. The left side (i.e. **4002**) of FIG. **40** illustrates a plurality of capacitor cells **4000** arranged to be a rectangular array in between the metal film **2** and metal film **9** when viewing to the top of the capacitor unit cell **100**. The right side (i.e. **4004**) of FIG. **40** illustrates a plurality of capacitor cells **4000** arranged to be a hexagonal array in between the metal film **2** and metal film **9** when viewing to the top of the capacitor unit cell **100**. However, this is not a limitation of the present invention. The array of capacitor cells **4000** may be arranged to be any symmetrical shape depended on the requirement.

[0177] According to the present invention, the capacitor unit cells **100** are formed between the substrate surface **3602** and the bottom metal layer (i.e. the lowest metal layer) of the interconnect structure disposed above the substrate **16**. The interconnect structure may comprise a plurality of metal layers and a plurality of interlayer dielectric layers, wherein the metal layers and the interlayer dielectric layers are stacked alternately above the substrate **16**. For the interconnect structure, the metal layer closest to the substrate **16** is the bottom or lowermost metal layer, and the metal layer farthest to the substrate **16** is the top or uppermost metal layer. The top metal layer is the exposed metal layer. According to the embodiment, the external terminals **105** and **106** are formed in the top metal layer of the interconnect structure. When the interconnect structure has only one metal layer (i.e. the embodiment as shown in FIG. **37**), the bottom metal layer and the top metal layer are the same layer.

[0178] FIG. **41** is a top view diagram illustrating a capacitor device **4100** according to an embodiment of the present invention. The capacitor device **4100** is a diced capacitor device (e.g.

3600). The top view of the capacitor device **4100** comprises a first conductive pad **4102** and a second conductive pad **4104**, wherein the first conductive pad **4102** may be the above mentioned external terminal **105** and the second conductive pad **4104** may be the above mentioned external terminal **106**. For brevity, a plurality of capacitor unit cells **4106** are also shown in FIG. **41**, in which the capacitor unit cells **4106** may be the above mentioned capacitor unit cells **100**. The capacitance of the capacitor device **4100** may be adjusted by the number of capacitor unit cells **4106** connected between the first conductive pad **4102** and the second conductive pad **4104**. According to the embodiment, the first conductive pad **4102** and the second conductive pad **4104** are arranged to be attached by a first external bonding device and a second external bonding device respectively. The first external bonding device and the second external bonding device may be a first and a second bonding wires respectively. However, this is not a limitation of the present invention.

[0179] FIG. **42** is a top view diagram illustrating a capacitor device **4200** according to an embodiment of the present invention. For brevity, the element numerals of the capacitor device **4200** are similar to those of the capacitor device **4100**. In this embodiment, the first conductive pad **4102** is attached by two conductive bumps **4202**, and the second conductive pad **4104** is attached by two conductive bumps **4204**. However, this is not a limitation of the present invention. Each of the first conductive pad **4102** and the second conductive pad **4104** may be attached by appropriate number (e.g. 1, 2, or 3) of conductive bumps. Moreover, the conductive bumps may be C4 (Controlled-collapse-chip-connection) solder bumps, gold bumps, or micro-bumps used in the flip-chip technology.

[0180] In addition, the capacitor device **4100** has a voltage tolerance V when the three capacitor unit cells **4106** are connected in parallel between the first conductive pad **4102** and the second conductive pad **4104**. To obtain a capacitor device with different voltage tolerance, the connection of capacitor unit cells between the first conductive pad **4102** and the second conductive pad **4104** may be re-configured. FIG. **43** is a top view diagram illustrating a capacitor device **4300** according to an embodiment of the present invention. For brevity, the element numerals of the capacitor device **4300** are similar to those of the capacitor device **4100**. In comparison to the capacitor device **4100**, the capacitor device **4300** comprises three capacitor unit cells **4302**, **4304**, and **4306** connected in parallel, and each of the capacitor unit cells **4302**, **4304**, and **4306** further comprises two capacitor unit cells connected in series. Under this configuration, the voltage tolerance of the capacitor device **4300** may be $2*V$. However, this is not a limitation of the present invention.

[0181] FIG. **44** is a top view diagram illustrating a capacitor device **4400** according to an embodiment of the present invention. For brevity, the element numerals of the capacitor device **4400** are similar to those of the capacitor device **4100**. In comparison to the capacitor device **4100**, the capacitor device **4400** comprises three capacitor unit cells **4402**, **4404**, and **4406** connected in parallel, and each of the capacitor unit cells **4402**, **4404**, and **4406** further comprises three capacitor unit cells connected in series. Under this configuration, the voltage tolerance of the capacitor device **4400** may be $3*V$. Therefore, by adjusting the number and connectivity of the capacitor unit cells between the first conductive pad **4102** and the second conductive pad **4104**, the voltage tolerance of a capacitor device may be adjusted. The re-configuration of the capacitor unit cells between the first conductive pad **4102** and the second conductive pad **4104** has been description in the above paragraphs related to FIG. **23** to FIG. **35**, thus the detailed description is omitted here for brevity.

[0182] FIG. **45** is a diagram illustrating a wafer-level capacitor devices **4500** according to an embodiment of the present invention. The capacitor devices **4500** are still on the wafer prior to singulation. According to the present invention, prior to singulation, the function of the capacitor devices **4500** should be tested and verified. Instead of one-by-one testing the capacitor devices **4500** on the wafer, the present invention provides a novel mechanism to test a plurality of capacitor devices on the wafer at a time as shown in FIG. **45**. More specifically, when the capacitor devices

4500 are manufactured on the wafer, the capacitor devices **4500** are grouped into a plurality of capacitor groups, and each capacitor group comprises a specific number of capacitor devices. The specific number may be any appropriate integer number, e.g. **20** or **100**, depending on the practical requirement. The first electrodes of the capacitor devices in a capacitor group are electrically connected with each other, and the second electrodes of the capacitor devices in the capacitor group are electrically connected with each other. For the example as shown in FIG. **45**, the plurality of capacitor devices **4502-4516** may form a group of capacitor devices. For brevity, each of the capacitor devices **4502-4516** is similar to the above mentioned capacitor device **4100**. In addition, a first conductive line **4518** is further arranged to electrically connect the first conductive pads **4102** of the capacitor devices **4502-4516**, and a second conductive line **4520** is further arranged to electrically connect the second conductive pads **4104** of the capacitor devices **4502-4516**.

According to the embodiment, the first conductive line **4518** may be formed on any metal layer in the interconnect layer on the substrate **16** as long as the first conductive pads **4102** of the capacitor devices **4502-4516** are electrically connected. Similarly, the second conductive line **4520** may be formed on any metal layer in the interconnect layer on the substrate **16** as long as the second conductive pads **4104** of the capacitor devices **4502-4516** are electrically connected.

[0183] According to the embodiment, the first conductive line **4518** and the second conductive line **4520** may pass through the boundaries of two adjacent capacitor devices in order to electrically connect the two adjacent capacitor devices. For the example of the capacitor devices **4504** and **4506**, the first conductive line **4518** may pass through the boundary **4522** of the first conductive pads **4102** of the capacitor device **4504** and the boundary **4524** of the first conductive pads **4102** of the capacitor device **4506**. The second conductive line **4520** may pass through the boundary **4526** of the second conductive pads **4104** of the capacitor device **4504** and the boundary **4528** of the second conductive pads **4104** of the capacitor device **4506**.

[0184] Accordingly, during the testing process, when the testing signals are applied to the first conductive line **4518** and the second conductive line **4520**, the group of capacitor devices **4502-4516** may be tested at a same time. For example, the testing probes of a testing device (not shown in FIG. **45**) may be attached on the first conductive pad **4102** and the second conductive **4104** for testing the group of capacitor devices **4502-4516**. If the testing result indicates a leakage current occurred to the group, which means that at least one capacitor device in the group is functional fail, then all of the capacitor devices **4502-4516** in the group may be regarded as bad devices.

Therefore, in comparison to the method of one-by-one testing the capacitor devices on the wafer, the present wafer-level testing process of the capacitor devices **4500** may be expedited.

[0185] In addition, when the capacitor devices **4502-4516** are diced, the portions of conductive line **4518** and the portions of conductive line **4520** may remain in the interconnect structures of the diced capacitor devices **4502-4516** when the conductive lines **4518** and **4520** are cut. Accordingly, the two ends of the portion of conductive line **4518** in a diced capacitor device may expose the lateral surface of the two cutting sides of the diced capacitor device, and the two ends of the portion of conductive line **4520** in the diced capacitor device may expose the lateral surface of the two cutting sides of the diced capacitor device. For the example of a diced capacitor device (e.g. **4504**), the first end of the portion of conductive line **4518** may expose the lateral surface (e.g. **4522**) on the first side of the diced capacitor device **4504**, and the first end of the portion of conductive line **4520** may expose the lateral surface (e.g. **4526**) on the first side of the diced capacitor device **4504**.

[0186] FIG. **46** is a diagram illustrating a cross-sectional view a diced capacitor device according to an embodiment of the present invention. FIG. **46** is a modification of the capacitor device as shown in the above mentioned FIG. **13**. For brevity, the numerals of elements of the capacitor device FIG. **46** are similar to those in FIG. **13**. In comparison to FIG. **13**, the conductive line **4518** and the conductive line **4520** are further shown in FIG. **46**. In this embodiment, the conductive lines **4518** and **4520** are formed on the same metal layer as the pad conductors **13** and **14**. However, this is not the limitation of the present invention. The conductive lines **4518** and **4520** may be formed on any

metal layer in the interconnect layer on the substrate **16** as long as the conductive lines **4518** and **4520** are electrically connected to the pad conductors **13** and **14** respectively.

INDUSTRIAL APPLICABILITY

[0187] The capacitor device according to each embodiment of the present invention is useful, for example, as an on-package decoupling capacitor. In semiconductor devices, there are problems such as a decrease in voltage tolerance range due to a decrease in power supply voltage, generation of large power supply noise or ground noise due to an increase in current consumption, and a decrease in EMI resistance due to an increase in operating frequency. In order to reduce this problem, it is effective to use a decoupling capacitor. By using the capacitor device according to each embodiment of the present invention, it is possible to provide a semiconductor device in which the above problems are reduced.

[0188] While various embodiments in accordance with the disclosed principles are described above, it should be understood that they are presented by way of example only, and are not limiting. Thus, the breadth and scope of example embodiment(s) should not be limited by any of the above-described embodiments, but should be defined only in accordance with the claims and their equivalents issuing from this disclosure. Furthermore, the above advantages and features are provided in described embodiments, but shall not limit the application of such issued claims to processes and structures accomplishing any or all of the above advantages.

[0189] Additionally, the section headings herein are provided for consistency with the suggestions under 37 C.F.R. 1.77 or otherwise to provide organizational cues. These headings shall not limit or characterize the invention(s) set out in any claims that may issue from this disclosure. Specifically, a description of a technology in the “Background” is not to be construed as an admission that technology is prior art to any invention(s) in this disclosure. Furthermore, any reference in this disclosure to “invention” in the singular should not be used to argue that there is only a single point of novelty in this disclosure. Multiple inventions may be set forth according to the limitations of the multiple claims issuing from this disclosure, and such claims accordingly define the invention(s), and their equivalents, that are protected thereby. In all instances, the scope of such claims shall be considered on their own merits in light of this disclosure, but should not be constrained by the headings herein.

Claims

1. A capacitor device, comprising: a substrate; an interlayer dielectric film, disposed on the substrate; a plurality of capacitor unit cells covered by the interlayer dielectric film, each of the capacitor unit cells comprises a lower electrode, an upper electrode over the lower electrode, and a dielectric film formed between the lower electrode and the upper electrode; wherein the upper electrode comprises an upper conductive film and a plurality of upper electrode conductors electrically coupled to the upper conductive film, the lower electrode comprises a lower conductive film and a plurality of lower electrode conductors electrically coupled to the lower conductive film, wherein each of the lower electrode conductors comprises a base portion electrically coupled to and having an interface with the lower conductive film and an extending portion electrically coupled to the base portion and extending from the base portion toward the upper electrode.
2. The capacitor device of claim 1, the lower electrode further comprises a first insulation film disposed on the lower conductive film, wherein the base portions of the lower electrode conductors in the lower electrode are separated by the first insulation film.
3. The capacitor device of claim 2, wherein the first insulation film comprises a nitride film.
4. The capacitor device of claim 1, wherein a material of the base portions of the lower electrode conductors is different from a material of the lower conductive film.
5. The capacitor device of claim 1, wherein a material of the upper electrode conductors comprises a doped silicon.

- 6.** The capacitor device of claim 1, further comprising a plurality of second insulation films disposed within the each of the capacitor unit cells, wherein each of the second insulation films is disposed between the adjacent two extending portions of the lower electrode conductors in a cross-section view.
- 7.** The capacitor device of claim 6, wherein each of the extending portion comprises a first end electrically connected to the base portion and a second end opposing to the first end, and each of the second insulation films is connected to the adjacent two second ends of the extending portions.
- 8.** The capacitor device of claim 6, wherein a material of the second insulation film comprises a nitride film.
- 9.** The capacitor device of claim 1, further comprising a plurality of first conductive pads and a plurality of second conductive pads formed within the interlayer dielectric film, wherein the plurality of first conductive pads and the plurality of second conductive pads are formed in same metal layer, and each of the plurality of first conductive pads is electrically coupled to the respective one of upper electrodes of the plurality of capacitor unit cells, and each of the plurality of second conductive pads is electrically coupled to the respective one of lower electrodes of the plurality of capacitor unit cells.
- 10.** The capacitor device of claim 9, further comprising a passivation film disposed on the interlayer dielectric film, wherein the plurality of first conductive pads and the plurality of second conductive pads are exposed by the interlayer dielectric film and the passivation film.
- 11.** The capacitor device of claim 1, wherein the upper electrodes of the plurality of capacitor unit cells are arranged in a first period in a first direction, and the lower electrodes of the plurality of capacitor unit cells are arranged in the first period in the first direction and shifted by substantially half a first length of the first period in the first direction.
- 12.** The capacitor device of claim 11, wherein the upper electrodes of the plurality of capacitor unit cells are arranged in a second period in a second direction, and the lower electrodes of the plurality of capacitor unit cells are arranged in the second period in the second direction and shifted by substantially half a second length of the second period in the second direction.
- 13.** The capacitor device of claim 1, wherein a material of the dielectric film comprises high dielectric material.
- 14.** The capacitor device of claim 1, wherein the substrate is a silicon substrate or a glass substrate.
- 15.** The capacitor device of claim 1, further comprising: a first conductive line disposed in the interlayer dielectric film, the first conductive line extends along a first direction and comprises a first end and a second end opposing to the first end; and a second conductive line disposed in the interlayer dielectric film, the second conductive line extends along the first direction and comprises a third end and a fourth end opposing to the third end; wherein the interlayer dielectric film comprises a first lateral surface and a second lateral surface opposing to the first lateral surface, and the first lateral surface and the second lateral surface are orthogonal to the first direction, and wherein the first end of the first conductive line and the third end of the second conductive line pass through the first lateral surface of the insulation film, and the second end of the first conductive line and the fourth end of the second conductive line pass through the second lateral surface of the insulation film.
- 16.** The capacitor device of claim 15, wherein the first conductive line is electrically connected to the upper electrodes of the plurality of capacitor unit cells, and the second conductive line is electrically connected to the lower electrodes of the plurality of capacitor unit cells.
- 17.** A capacitor device, comprising: a substrate; an interlayer dielectric film, disposed on the substrate; a stacked capacitor structure, including a first capacitor tier and a second capacitor tier stacking on the first capacitor tier, each of the first capacitor tier and the second capacitor tier comprises a plurality of capacitor unit cells covered by the interlayer dielectric film, each of the capacitor unit cells comprises a lower electrode, an upper electrode over the lower electrode, and a dielectric film formed between the lower electrode and the upper electrode; wherein in a cross-

section view, the upper electrode comprises an upper conductive film and a plurality of upper electrode conductors electrically coupled to the upper conductive film, the lower electrode comprises a lower conductive film and a plurality of lower electrode conductors electrically coupled to the lower conductive film, wherein each of the lower electrode conductors comprises a base portion electrically coupled to and having an interface with the lower conductive film and an extending portion electrically coupled to the base portion and extending from the base portion toward the upper electrode.

18. The capacitor device of claim 17, wherein the upper electrodes of the second capacitor tier are electrically connected to the upper electrodes of the first capacitor tier, and the lower electrodes of the second capacitor tier are electrically connected to the lower electrodes of the first capacitor tier.

19. The capacitor device of claim 18, further comprising a plurality of first via conductors and a plurality of second via conductors, wherein the plurality of first via conductors are electrically coupled the upper electrodes of the second capacitor tier and the upper electrodes of the first capacitor tier, and the plurality of second via conductors are electrically coupled the lower electrodes of the second capacitor tier and the lower electrodes of the first capacitor tier.

20. The capacitor device of claim 19, the substrate comprises a first side and a second side different from the first side in a plane view, wherein the plurality of first via conductors are disposed adjacent to the first side, and the plurality of second via conductors are disposed adjacent to the second side.
