

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250257538

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

French, SR.; William L.

Modular Precast Hydro Dam with Powerhouse

Abstract

A power generation system may include a powerhouse. The powerhouse may include a flow path structure, a power generation support structure, and an access port. The flow path structure may define at least a portion of a flow path. The flow path structure may be configured to accept fluid at an input port to enter the powerhouse and direct the fluid to exit the powerhouse at an output port. A power generation support structure may be, at least partially, constructed of precast segments. The power generation support structure may be configured to support weight of a power generator in an arrangement operably disposed within the flow path. An access port may be different from the input port, and the access port may be aligned to enable removable coupling of the power generator to and from the power generation support structure.

Inventors: French, SR.; William L. (Lexington, MA)

Applicant: W.L. French Hydropower Holdings LLC (Chelmsford, MA)

Family ID: 96660560

Assignee: W.L. French Hydropower Holdings LLC (Chelmsford, MA)

Appl. No.: 19/030367

Filed: January 17, 2025

Related U.S. Application Data

us-provisional-application US 63552088 20240209

us-provisional-application US 63701484 20240930

us-provisional-application US 63712974 20241028

Publication Classification

Int. Cl.: E02B9/00 (20060101); F03B13/08 (20060101)

Background/Summary

RELATED APPLICATIONS [0001] This application claims the benefit of U.S. Provisional Application No. 63/552,088, filed on Feb. 9, 2024. This application claims the benefit of U.S. Provisional Application No. 63/701,484, filed on Sep. 30, 2024. This application claims the benefit of U.S. Provisional Application No. 63/712,974, filed on Oct. 28, 2024. The entire teachings of the above applications are incorporated herein by reference.

BACKGROUND

[0002] Hydroelectric dams and powerhouses may convert kinetic energy provided by a flowing fluid into electrical power, which may provide electricity to a local area. Maintenance or damage to the dam or powerhouse may disrupt the electricity available to the local area. There is a need for improved systems and methods for coordinating activity between a dam and powerhouse and facilitating maintenance or repair.

SUMMARY

[0003] The present application describes embodiments of a dam and functionally coupled powerhouse(s), where a powerhouse includes a turbine to convert water flow into electrical power. In an example embodiment, the dam and a powerhouse may be both mechanically and functionally coupled. Alternatively, the dam and powerhouse may be mechanically uncoupled but functionally coupled. Functionally coupled includes, for example, using a sensor in or at the powerhouse to notify or cause the dam to increase or decrease height of a water control gate, which results in an increase or decrease of water flowing into the powerhouse to the turbine.

[0004] A power generation system may include a powerhouse. A powerhouse may include a flow path structure, a power generation support structure, and an access port. The flow path structure may define at least a portion of a flow path, the flow path structure configured to accept fluid at an input port to enter the powerhouse and direct the fluid to exit the powerhouse at an output port. The power generation support structure may be at least partially constructed of precast segments, configured to support weight of a power generator in an arrangement operably disposed within the flow path. The access port may be different from the input port, the access port aligned to enable removable coupling of the power generator to and from the power generation support structure.

[0005] In various example embodiments, the power generation support structure may include precast forms and filler that define the precast segments and the precast forms may be filled with the filler on a layer-by-layer basis during a process of arranging the precast segments in vertical layers to define the power generation support structure.

[0006] In various example embodiments, the precast forms may include a port through a surface of the precast form that enables filler to flow from a given layer to a lower adjacent layer in a vertical direction.

[0007] In various example embodiments, the power generation support structure may define a lowest layer having a pattern of vertically offset portions or may further include a layer, having a pattern of vertically offset portions.

[0008] The power generation system may further include a dam functionally coupled with the powerhouse in a manner that maintains or discontinues fluid flow to the input port.

[0009] In various example embodiments, the powerhouse may be arranged in a vertical configuration, in which the power generator is arranged vertically; or a horizontal configuration, in which the power generator is arranged horizontally.

[0010] In various example embodiments, the flow path structure may define a bypass flow path from input port to output port or within a flow path to enable fluid flow to circumvent the power generator.

[0011] In various example embodiments, the powerhouse may include a flow control gate, and the flow path structure may define multiple flow paths at least one of which is operably controllable in combination with operation of the flow control gate.

[0012] In various example embodiments, the flow path structure may define multiple flow paths, at least a subset of the multiple flow paths being selectably configurable to enable fluid flow.

[0013] In various example embodiments, the powerhouse may include an icebreaker arranged to break ice prior to flowing into the input port.

[0014] The power generation system may further include a superstructure positioned above at least a portion of the powerhouse, wherein the superstructure is configured to support a functional element to perform maintenance at the powerhouse.

[0015] In various example embodiments, the superstructure may include at least one rail, located on or within the superstructure that enables coupling with the functional element.

[0016] In various example embodiments, the functional element may include a crane configured to be mechanically powered.

[0017] In various example embodiments, the powerhouse may further include a Faraday shield room or a room shielded with radiation hardened material.

[0018] The power generation system may further include at least one auxiliary power system.

[0019] The power generation system may further include at least one energy storage system.

[0020] In various example embodiments, at least one of the precast segments may be removably coupled with the power generation support structure.

[0021] In various example embodiments, the functional element may be a crane assembly configured to raise or lower at least one flow control gate in order to control a height of a reservoir.

[0022] In various example embodiments, the crane may include a combination of crane elements to lift the at least one waterflow restriction gate from multiple points to reduce a likelihood that a gate will cantilever during raising and lowering operations.

[0023] In various example embodiments, the powerhouse may further include an access channel, one end of the access channel being coupled to the access port.

[0024] In various example embodiments, the superstructure may include an enclosure positioned around the access port.

[0025] In various example embodiments, the access port may be defined by at least one precast segment.

[0026] In various example embodiments, the flow path structure may be configured to accept fluid at an input port to enter the powerhouse in a first direction and the access port is oriented in a second direction, the second direction being different than the first direction.

[0027] In various example embodiments, the power generator may include at least one turbine.

[0028] In various example embodiments, at least one of the precast forms may include at least one divider to define two or more compartments.

[0029] The power generation system may further include at least one water intake system. The water intake system may include at least one precast segment, the water intake system being functionally coupled to at least one of the powerhouse system or the dam system.

[0030] In various example embodiments, the powerhouse may include a flow control gate configured to communicate with the power generator.

[0031] A power generation system may include a powerhouse at least partially defined by a plurality of precast segments. At least one of the precast segments may include a precast form having disposed therein at least one precast infill block.

[0032] A power generation system may include a dam at least partially defined by a plurality of

precast segments. At least one of the precast segments may include a precast form having disposed therein at least one precast infill block.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0033] The foregoing will be apparent from the following more particular description of example embodiments, as illustrated in the accompanying drawings in which like reference characters refer to the same parts throughout the different views. The drawings are not necessarily to scale, emphasis instead being placed upon illustrating embodiments.

[0034] FIG. 1 is a perspective view of an example embodiment of a power generation system.

[0035] FIG. 2A is a perspective view of an example embodiment of a power generation system comprising a powerhouse and a dam.

[0036] FIG. 2B shows the example embodiment of FIG. 2A from a side-perspective view.

[0037] FIG. 3A shows a perspective view of an example embodiment of a powerhouse comprising a superstructure.

[0038] FIG. 3B is a perspective view from the upstream side of the embodiment of FIG. 3A.

[0039] FIG. 4A shows a sectional view of an example embodiment of a powerhouse and superstructure with an enclosure.

[0040] FIG. 4B is a different sectional view of the example embodiment of FIG. 4A.

[0041] FIG. 5A is a perspective view of an example embodiment of a power generation system.

[0042] FIG. 5B is a different perspective view of the example embodiment shown in FIG. 5A.

[0043] FIG. 6 is a perspective view of an example embodiment of a powerhouse 610.

[0044] FIG. 7 is a perspective view of an example embodiment of a powerhouse comprising a rake system and a functional element.

[0045] FIG. 8A is a perspective view of an example embodiment of a powerhouse comprising a rake system and a functional element.

[0046] FIG. 8B shows a perspective view of an example embodiment of a powerhouse comprising a rake system and a functional element.

[0047] FIG. 9 is a perspective view of an example embodiment of a dam and a portion of a powerhouse.

[0048] FIG. 10 is a perspective view of an example embodiment of a power generation system comprising a dam and a horizontal powerhouse.

[0049] FIG. 11 is a top view of an example embodiment of a power generation system.

[0050] FIG. 12 shows a perspective view of an example embodiment of a dam comprising precast segments.

[0051] FIG. 13 shows a perspective view of an example embodiment of a power generation system that comprises a horizontal power generator and a vertical power generator.

[0052] FIG. 14 shows a perspective sectional view of a portion of an example embodiment of a powerhouse.

[0053] FIG. 15 shows a perspective view of an example embodiment of a dam.

[0054] FIG. 16 is a perspective view of an example embodiment of a dam with multiple slots for precast mass fills. In alternative embodiments, the dam may have a different number of slots.

[0055] FIG. 17A shows a perspective of an example embodiment of a working platform coupled to rock anchors.

[0056] FIG. 17B shows a close-up view of the working platform of FIG. 17A.

[0057] FIG. 18A shows a perspective view of an example embodiment of a working platform coupled to multiple rock anchors.

[0058] FIG. 18B shows a perspective view of an example embodiment of a working platform

coupled to multiple cleats, rock anchors, and diffusers.

[0059] FIG. **19A** shows a perspective view of an example embodiment of a square precast segment comprising dividers.

[0060] FIG. **19B** shows a perspective view of an example embodiment of a square precast segment defined by a form without internal walls.

[0061] FIG. **19C** shows a perspective view of an example embodiment of a rectangular precast segment defined by a form without internal walls.

[0062] FIG. **20A** shows example embodiments of two different precast segments that each define a keyway. Each precast segment shown in FIG. **20A** also includes dowels configured to couple with neighboring precast segments or other materials.

[0063] FIG. **20B** shows an example embodiment of a precast segment that includes a snubber.

[0064] FIG. **21** is a sectional perspective view of an example embodiment of precast segments stacked and coupled together using a coupling mechanism.

[0065] FIG. **22A** is a side view of an example embodiment of two stacks of precast segments coupled together.

[0066] FIG. **22B** is a perspective view of an example embodiment of four stacks of precast segments coupled together with a coupling mechanism.

[0067] FIG. **23** shows an example embodiment of four stacks of modular blocks filled with precast concrete infill blocks.

[0068] FIG. **24A** shows a perspective view of example embodiments of angled precast segments.

[0069] FIG. **24B** shows a side view of the example embodiments of angled precast segments of FIG. **24A**.

[0070] FIG. **24C** shows a side view of the example embodiments of angled precast segments of FIG. **24A**.

[0071] FIG. **25** is a perspective view of an example embodiment of a power generation system comprising a dam, a powerhouse (not shown), and auxiliary power systems.

[0072] FIG. **26A** is a perspective view of an example embodiment of a power generation system comprising a dam and a powerhouse.

[0073] FIG. **26B** is a zoomed-out view of the example embodiment shown in FIG. **26A**.

[0074] FIG. **27** shows an example embodiment a control system configured to coordinate activity between a dam and a powerhouse of a power generator.

[0075] FIG. **28A** shows a side view of an example embodiment of an intake module.

[0076] FIG. **28B** shows a perspective sectional view of an example embodiment of an intake module.

[0077] FIG. **28C** shows a perspective view of an example embodiment of a layer of an intake module.

[0078] FIG. **29A** shows an example embodiment of a microgrid facility.

[0079] FIG. **29B** shows example embodiments of energy generation facilities at an example microgrid facility.

[0080] FIG. **29C** show an example embodiment of secure buildings at an example microgrid facility.

[0081] FIG. **29D** shows an example embodiment of an underground system associated with an example microgrid facility.

[0082] FIG. **30** shows an example embodiment of a powerhouse.

[0083] FIG. **31** shows an example embodiment of a powerhouse.

[0084] FIG. **32A** shows an example embodiment of a powerhouse outflow.

[0085] FIG. **32B** shows a close-up of the example powerhouse shown in FIG. **32A**.

[0086] FIG. **33** shows a perspective view of an example powerhouse coupled to a fish passage.

[0087] FIG. **34** shows an example view through a security tower at a microgrid facility.

[0088] FIG. **35** shows an example embodiment of a microgrid power generation facility that

includes wind power generation systems and solar power generation system.

[0089] FIG. **36** shows example embodiments of aspects of an access control system at a microgrid facility.

[0090] FIG. **37** shows an example embodiment of a microgrid power generation facility that includes energy solutions, a watch tower, and buildings.

[0091] FIG. **38** shows an example embodiment of a microgrid facility with precast buildings with form liners.

[0092] FIG. **39** shows an example embodiment of a microgrid power generation facility **3900** that includes a hydropower facility, the hydropower facility including at least one precast segment.

DETAILED DESCRIPTION

[0093] A description of example embodiments follows.

[0094] Example embodiments of aspects of the inventive concepts are directed to dams and powerhouses. Example assemblies may include advanced structures and assembly techniques through use of precast forms to produce precast segments. The precast segments form various structures and features of the dams and powerhouses, and may further be used to form flowpaths, optionally having an inner or outer steel, composite, or other material liner that is applied at high pressure locations, such as at a lower region of a flowpath or at a turbine.

[0095] Systems, devices and methods described herein may involve components constructed from precast segments. As used herein, the term “precast segment” refers to precast modules of particular shape and size formed of a structural material, for example, concrete. Precast segments can include coupling elements to enable the segments to be interconnected during construction of a structure, such as a reservoir or impoundment module. Precast segments can be manufactured off-site, providing for increased control over manufacturing conditions, thereby providing for more robust and uniformly constructed segments for forming a structure, as compared with a structure formed by on-site concrete pouring. For some construction projects, a temporary facility may be constructed to manufacture precast segments on-site, whereby the temporary facility itself may be formed of precast segments.

[0096] FIG. **1** is a perspective view of an example embodiment of a power generation system **100**. In some embodiments, such as the one shown in FIG. **1** the power generation system **100** comprises a dam **160** and a powerhouse **110**. FIG. **1** shows the power generation system **100** installed at a body of water **103**. In some embodiments, such as the one shown in FIG. **1**, a parking lot **101** and a road **102** may be located near the powerhouse **110**. In this embodiment, water enters the powerhouse **110** along a flow path **104**. Inside the powerhouse **110** the water interacts with a power generator to produce electrical power.

[0097] The fluid (e.g., water) may enter the powerhouse **110** via one or more input ports. In some embodiments, such as the one shown in FIG. **1**, the water exits the powerhouse **110** via one or more output ports **111**. In the embodiment shown in FIG. **1**, the powerhouse **110** comprises two output ports **111a**, **111b**. In alternative embodiments, the powerhouse **110** may comprise a different number of output ports.

[0098] FIG. **2A** is a perspective view of an example embodiment of a power generation system **200** comprising a powerhouse **210** and a dam **260**. In some embodiments, such as the one shown in FIG. **2**, the powerhouse comprises a flow path structure **230** defining at least a portion of a flow path. In some embodiments, such as the one shown in FIG. **2A** the flow path structure **230** comprises at least one precast segment. In some embodiments, the powerhouse **210** is constructed entirely of precast segments. In some embodiments, the powerhouse **210** is partially constructed using precast segments. In some embodiments, the powerhouse does not comprise precast segments.

[0099] The flow path structure **230** may be configured to accept fluid at an input port **212** to enter the powerhouse **210** and direct the fluid to exit the powerhouse **210** at an output port **216**. In some embodiments, such as the one shown in FIG. **2A**, the flow path structure **230** defines multiple flow

paths.

[0100] In some embodiments, the flow path structure **230** defines multiple input ports **212**. In the embodiment shown in FIG. 2A, the flow path structure **230** comprises four input ports. In alternative embodiments, the flow path structure **230** may comprise a different number of input ports. In some embodiments, each one of the multiple input ports is paired with a corresponding intake bay. In some embodiments, different intake bays are separated by dividers.

[0101] In some embodiments, the flow path structure **230** defines multiple output ports **216**. In the embodiment shown in FIG. 2A, the flow path structure **230** comprises four output ports. In alternative embodiments, the flow path structure **230** may comprise a different number of output ports. In some embodiments, each one of the multiple output ports is paired with a corresponding output bay. In some embodiments, different output bays are separated by dividers.

[0102] In some embodiments, the powerhouse includes at least one flow control gate. The flow path structure may define multiple flow paths at least one of which is operably controllable in combination with operation of the flow control gate. The flow path structure may define multiple flow paths and at least a subset of the multiple flow paths may be selectively configurable to enable fluid flow. In some embodiments, at least one of the at least one flow control gate is configured to communicate with the power generator. In some embodiments, the power generation system further comprises a dam functionally coupled with the powerhouse in a manner that maintains or discontinues fluid flow to at least one input port.

[0103] The powerhouse **210** may comprise at least one power generator. In some embodiments, the power generator may comprise at least one turbine. The flow path structure may define a bypass flow path from an input port to output port or within a flow path to enable fluid flow to circumvent the power generator.

[0104] The powerhouse **210** may comprise at least one power generation support structure configured to support weight of a power generator in an arrangement operably disposed within the flow path. The power generation support structure may be, at least partially, constructed of precast segments. Each power generator may be paired with a unique power generation support structure. Alternatively, one or more power generators may be supported by the same power generation support structure.

[0105] In some embodiments, the power generation support structure includes at least one precast segment. In some embodiments, at least one of the at least one precast segment is removably coupled to the power generation support structure.

[0106] The power generation support structure may include precast forms and filler that define the precast segments and wherein the precast forms are filled with the filler on a layer-by-layer basis during a process of arranging the precast segments in vertical layers to define the power generation support structure.

[0107] The power generation system may include a power generation support structure that defines a lowest layer having a pattern of vertically offset portions. The power generation system may include a power generation support structure that includes a layer, having a pattern of vertically offset portions.

[0108] In some embodiments, such as the one shown in FIG. 2A, the powerhouse **210** is arranged in a vertical configuration, in which the power generator is arranged vertically. In some vertical configurations, the input port **212** and the output port **216** may be at different heights. In alternative embodiments, the powerhouse may be arranged in a horizontal configuration, in which the power generator is arranged horizontally.

[0109] The powerhouse **210** may comprise at least one access port **240** different from the input port **212**. The access port **240** may be aligned to enable removable coupling of the power generator to and from the power generation support structure **230**. In the embodiment shown in FIG. 2A, the powerhouse **210** comprises four access ports **240a**, **240b**, **240c**, **240d**. In alternative embodiments, the powerhouse **210** comprises a different number of access ports. The number of access ports may

correspond to the number of power generators. Alternatively, in some embodiments, the number of access ports may not correspond to the number of power generators.

[0110] In some embodiments, such as the one shown in FIG. 2A, the access ports are oriented in a direction that is orthogonal to the direction at which the flow path enters the powerhouse **210**. In alternative embodiments, the access ports are oriented in a different direction. In some embodiments, such as the one shown in FIG. 2A, the access ports are oriented in a direction that is orthogonal to the direction at which the flow path exits the powerhouse **210**. In alternative embodiments, the access ports are oriented in a different direction. In some embodiments, the flow path structure is configured to accept fluid at an input port to enter the powerhouse in a first direction and the access port is oriented in a second direction, the second direction being different than the first direction.

[0111] In some embodiments, such as the one shown in FIG. 2A, the powerhouse defines four access ports. In alternative embodiments, the powerhouse may define a different number of access ports. At least one of the access ports may be defined by at least one precast segment.

[0112] The powerhouse may further define an access channel, one end of the access channel being an access port.

[0113] In some embodiments, such as the one shown in FIG. 2A, the power generation system **200** comprises at least one spillway. In some embodiments, the spillways are constructed of precast segments, optionally through use of precast forms that are used to produce the precast segments, as described herein. In some embodiments, the spillways are not constructed of precast segments. The advanced spillways may extend any length, such as tens or hundreds of feet upstream of or downstream from the dam or powerhouse.

[0114] In the embodiments shown in FIG. 2A the power generation system **200** comprises a spillway **222** associated with the input port **212**. In alternative embodiments, the powerhouse **210** may not comprise a spillway associated with the input port **216**.

[0115] In the embodiments shown in FIG. 2A the power generation system **200** comprises a spillway **222** associated with the output port **216**. In alternative embodiments, the powerhouse **210** may not comprise a spillway associated with the output port **216**.

[0116] In some embodiments, such as the one shown in FIG. 2A, the power generation system **200** comprises a spillway associated with the dam **260**.

[0117] The power generation system **200** may comprise at least one diffuser **226**. At least one of the at least one diffuser **226** may be constructed of precast segments, which may be formed as described herein. The diffusers **226** may be positioned upstream or downstream of a dam or powerhouse in order to diffuse water flow from damaging a feature of the dam **260** or powerhouse **210** over a period of time. The diffusers **226** may be mechanically inserted into corresponding coupling features in a spillway, for example. The diffusers **226** may be active in that they can be rotated relative to a water flow over a period of time, such as during a day or over longer periods of time, such as a season of the year. The corresponding coupling element may itself be operationally able to rotate or otherwise change an orientation of a diffuser **226** in coordination with other diffusers **226** to aid in steering a flow of water across, for example, a spillway in an effort to defuse water flow from damaging a feature of the dam **260** or powerhouse **210** over a long period of time.

[0118] In some embodiments, such as the one shown in FIG. 2A, diffusers **226** are coupled to the spillway **224** associated with the output ports **216**. In alternative embodiments, the spillway **224** associated with the output port may not be coupled to diffusers **226**. In alternative embodiments, diffusers may be coupled to the spillway **222** associated with the input port(s) **212**.

[0119] The power generation system may comprise at least one abutment wall. In some embodiments, such as the one shown in FIG. 2A, the power generation system comprises an abutment wall **270** at one side of the dam **260**.

[0120] The power generation system may comprise one or more rock bolts (every use of rock bolts herein also applies to rock anchors, and vice versa) configured to secure a portion of the power

generation system to a surface. In some embodiments, such as the one shown in FIG. 2A multiple rock bolts **292** are coupled to a lower surface of the dam. In some embodiments, such as the one shown in FIG. 2A multiple rock bolts **242** are coupled to a lower surface of the powerhouse.

[0121] FIG. 2B shows the example embodiment of FIG. 2A from a side-perspective view.

[0122] FIG. 3A shows a perspective view of an example embodiment of a powerhouse comprising a superstructure **380**. The superstructure **380** may be positioned above at least a portion of the powerhouse. The superstructure **380** may comprise a platform **385** constructed and arranged to support people and/or equipment.

[0123] The superstructure **380** may comprise at least one enclosure **382**. In some embodiments, such as the one shown in FIG. 3A, the superstructure **380** comprises one enclosure **382**. In alternative embodiments, the superstructure comprises a different number of enclosures. In some embodiments, the superstructure **380** does not include an enclosure. In some embodiments, such as the one shown in FIG. 3A, the enclosure **382** is positioned around an access port.

[0124] At least one of the at least one enclosure may define at least one port **383**. In the embodiment, shown in FIG. 3A, the enclosure defines one port **383**. In alternative embodiments, the enclosure may define a different number of ports. In the embodiment shown in FIG. 3A, the port is at a top surface of the enclosure **382**. In alternative embodiments, the port may be at a different location.

[0125] In some example embodiments the powerhouse system may further comprise a Faraday shield room or a room shielded with radiation hardened material. In some embodiments, the enclosure of the superstructure may serve as a Faraday shield room. In some embodiments of a dam or powerhouse, a Faraday shield room is constructed and configured to store electrical equipment, such as transformers, computer systems, electrical controllers, and/or even turbines that may be adversely affected by an energy spike, such as a lightning strike, power surge, electromagnetic pulse, or adverse weather event. The Faraday shield room may be positioned in a manner that enables a crane assembly at the superstructure assist with performing maintenance activities to return the dam or powerhouse back to operational status.

[0126] In some embodiments the superstructure is configured to support a functional element to perform maintenance at the powerhouse. The functional element may comprise a crane. The functional element may comprise a crane configured to be mechanically powered. The functional element may be a crane assembly configured to raise or lower at least one flow control gate in order to control a height of a reservoir. The crane may comprise a combination of crane elements to lift the at least one waterflow restriction gate from multiple points to reduce a likelihood that a gate will cantilever during raising and lowering operations.

[0127] The superstructure may comprise at least one rail, located on or within the superstructure that enables coupling with the functional element. In some embodiments, the superstructure may be composed of precast segments. In some embodiments, the superstructure may not be composed of precast segments.

[0128] A superstructure composed of pillars and a ceiling may be formed on the assembly of precast segments in order to provide for functional elements to be operating above the assembly of precast segments. An example of a functional element is a crane that is suspended from a rail mounted on the ceiling or movably coupled to a rail on the working platform. The crane or other functional elements may travel in various directions above the assembly of precast segments to perform a particular function, such as replacing worn precast segments, replacing a turbine, replacing a section of penstock, removing debris above or below the assembly of precast segments, or performing any number of other functions that may be of use in operation or maintenance of the dam or powerhouse.

[0129] Another example of a function performed by a functional element at the superstructure is the use of a crane assembly that travels along a dam and raises or lowers waterflow restriction gates in order to control a height of a reservoir created by the dam. The crane may be a combination of

crane elements to lift the gate from multiple points to reduce a likelihood that a gate will cantilever during raising and lowering operations, which may require extended maintenance to fix.

[0130] In the embodiment shown in FIG. 3A, the flow path structure **330** is composed of at least one precast structure **372**. In alternative embodiments, the flow path structure **330** may not be composed of precast structures.

[0131] In some embodiments, such as the one shown in FIG. 3A multiple rock bolts **342** are coupled to a lower surface of the powerhouse.

[0132] In some embodiments, such as the one shown in FIG. 3A, diffusers **326** are coupled to the spillway associated with the output bays **321**. In alternative embodiments, the spillway **224** associated with the output bays or output ports may not be coupled to diffusers. In alternative embodiments, diffusers may be coupled to the spillway associated with the input ports.

[0133] FIG. 3B is a perspective view from the upstream side of the embodiment of FIG. 3A. In some embodiments, such as the one shown in FIG. 3B, the powerhouse comprises a rake system **388** configured to remove debris and other materials from fluid flowing into one of more input ports.

[0134] The powerhouse may comprise at least one flow-through bays **387**. In the embodiment shown in FIG. 3B, the powerhouse comprises four flow-through bays **387**. In alternative embodiments, the powerhouse may comprise a different number of flow-through bays.

[0135] FIG. 4A show s sectional view of an example embodiment of a powerhouse and superstructure **480** with an enclosure **482**. A rake system **488** is visible near the input ports. In this embodiment a functional element **489** is mounted at a surface of the enclosure **482**.

[0136] FIG. 4B is a different sectional view of the example embodiment of FIG. 4B. In this embodiment, three access ports **489** are defined. These access ports **489** facilitate removal and insertion of power generators. The embodiment shown in FIG. 4B has three access ports. In alternative embodiments, the powerhouse **410** may define a different number of access ports. In the embodiment shown in FIG. 4B the access ports are arranged in a line. In alternative embodiments, the access ports may be arranged differently.

[0137] FIG. 5A is a perspective view of an example embodiment of a power generation system **500**. As shown in FIG. 5A, the rake system **588** may comprise a functional element **589** configured to remove material from a fluid flow entering the powerhouse. In the embodiment shown in FIG. 5A, the functional element **589** is a crane. In alternative embodiments, the functional element may be different.

[0138] FIG. 5B is a different perspective view of the example embodiment shown in FIG. 5A. In this embodiment diffusers are positioned near output ports of the powerhouse. In this embodiment, diffusers are also positioned at one side of the dam **560**.

[0139] FIG. 6 is a perspective view of an example embodiment of a powerhouse **610**. In the embodiment shown in FIG. 6, the powerhouse **610** four intake bays **617a-617d**, each corresponding to an input port. The intake bays **617** are separated by dividers **618a-618d**. In alternative embodiments, the powerhouse may comprise a different number of intake bays and/or dividers.

[0140] FIG. 7 is a perspective view of an example embodiment of a powerhouse **710** comprising a rake system **788** and a functional element **789**. In this embodiment, the functional element **789** is mounted at a platform **785**.

[0141] FIG. 8A is a perspective view of an example embodiment of a powerhouse **810** comprising a rake system **888** and a functional element **889**. In this embodiment, the functional element **889** is mounted at a rail. In some embodiments, such as the embodiment shown in FIG. 7A, the powerhouse **810** is covered with a liner **838**. In this embodiment the powerhouse **810** includes an enclosure **882** and the enclosure **882** defines a port. In the embodiment shown in FIG. 8A, the port is blocked by a cover **884**. In alternative embodiments, the cover **884** may only block a portion of the port.

[0142] FIG. 8B shows a perspective view of an example embodiment of a powerhouse **810**

comprising a rake system **888** and a functional element **889**. In this embodiment, the functional element **889** is mounted at a rail.

[0143] FIG. **9** is a perspective view of an example embodiment of a dam **960** and a portion of a powerhouse. In this embodiment, a flow control gate **919a-919d** is positioned at each intake bay. Each control gate may be configured to regulate the flow of fluid entering the intake bay. In alternative embodiments, one or more of the intake bays may not be associated with a flow control gate. In this embodiment the dam **960** is coupled to an abutment wall **970**. As shown in FIG. **9**, an abutment wall **970** may be coupled to one or more support abutment walls **971**. In the embodiment shown in FIG. **9**, there are two support abutment walls **971a**, **971b**. In alternative embodiments, there may be a different number of support abutment walls. In alternative embodiments, one or more of the one or more support abutment walls **971** may be arranged differently than the arrangement shown in FIG. **9**.

[0144] In the embodiment shown in FIG. **9**, diffusers **927** are located on the upstream side of the dam **960**. In some embodiments, such as the one shown in FIG. **9**, one or more rock bolts **992** may be coupled to the dam **960**. In some embodiments, such as the one shown in FIG. **9**, one or more cutoff walls **962** may be coupled to the dam **960** and/or the powerhouse. The cutoff walls may be configured to block the flow of fluid.

[0145] FIG. **10** is a perspective view of an example embodiment of a power generation system **1000** comprising a dam **1060** and a horizontal powerhouse **1010**. In this embodiment, the powerhouse **1010** comprises a superstructure **1080**. In this embodiment, the superstructure comprises an enclosure **1082**. In this embodiment the enclosure **1082** defines a port **1083**. The embodiment shown in FIG. **10** comprises three intake ports **1012**. Alternative embodiments may comprise a different number of intake ports.

[0146] In the embodiment shown in FIG. **10** the dam **1060** is coupled to rock bolts to secure it to natural material.

[0147] FIG. **11** is a top view of an example embodiment of a power generation system **1100**. In this embodiment, the power generation system **1100** comprises a dam **1160** and a powerhouse **1110**. Multiple diffusers **1127** are located at the downstream side of the dam **1160**. In the embodiment shown in FIG. **11** the power generation system **1100** comprises two abutment walls **1170**—one on each side of the dam **1160**. In the embodiment shown in FIG. **11**, the power generation system **1100** comprises two support abutment walls **1171a**, **1171b**. In alternative embodiments, the power generation system **1100** may comprise a different number and/or arrangement of support abutment walls.

[0148] In the embodiment shown in FIG. **11**, the powerhouse **1110** comprises four intake bays **1117a-1117d** and four output bays **1121a-1121d**. In alternative embodiments, the powerhouse **1110** may comprise a different number of intake and/or output bays.

[0149] In some embodiments, such as the embodiment shown in FIG. **11**, each intake bay corresponds to two power generators **1105** (two power generators **1005a**, **1005b** are labeled in FIG. **11**). In alternative embodiments, a different number of power generators may be aligned with each intake bay and/or each input port.

[0150] In some embodiments, such as the embodiment shown in FIG. **11**, each output bay corresponds to two power generators **1105** (two power generators **1105a**, **1105b** are labeled in FIG. **11**). In alternative embodiments, a different number of power generators may be aligned with each output bay and/or each output port.

[0151] In some embodiments, the power generator comprises at least one turbine. Turbines may be arranged vertically or horizontally within the dam or associated powerhouse. The turbines may be encapsulated within precast segments to form a turbine assembly and positioned and oriented within the corresponding structure housing same in a manner that enables maintenance or interchangeability. Above the structure housing the turbine assembly may be a superstructure. The turbine assemblies may be located beneath a part of the superstructure that has a crane assembly in

order to perform maintenance of features of the structure, maintenance of a turbine or turbine assembly, or exchange a turbine.

[0152] The dam or powerhouse may also include penstocks (large tubes or flow paths) that feed fluid to the turbines in a manner that enables efficient conversion of fluid flow to electrical power through use of the turbines. The penstocks may be supported by large numbers of precast segments, which may be constructed through use of precast forms and poured cement or other slurry filler, in order to support weight of penstocks with water flowing therein during operation. Because the precast segments may be various sizes, shapes, and thicknesses, the penstocks may be held in stable positions, optionally with additional layers of supporting materials, such as rubber or composites between the penstocks and the precast segments.

[0153] FIG. **12** shows a perspective view of an example embodiment of a dam **1260** comprising precast segments.

[0154] FIG. **13** shows a perspective view of an example embodiment of a power generation system **1100** that comprises a horizontal power generator **1305a** and a vertical power generator **1305b**.

[0155] FIG. **14** shows a perspective sectional view of a portion of an example embodiment of a powerhouse **1410**. In the embodiment shown in FIG. **14**, the powerhouse **1410** comprises four power generator support structures **1407a-1407d**. In this embodiment, two power generators **1405a, 1405b** are shown. In some example embodiments, a wall (not shown) may be positioned between one or more of the power generator support structures. In some example embodiments, a wall (not shown) may be positioned between one or more of the power generators.

[0156] FIG. **15** shows a perspective view of an example embodiment of a dam **1560**. In some embodiments, such as the one shown in FIG. **15** the dam **1560** is composed of one or more precast segments. The dam **1560** may be coupled with a working platform **1562**. In the embodiment shown in FIG. **15** the dam **1560** is coupled to two cutoff walls **1563a, 1563b**. In alternative embodiments, the dam **1560** may be coupled to a different number of cutoff walls **1563**.

[0157] In the embodiment shown in FIG. **13**, the dam **1560** is coupled to a first cutoff wall **1562a** that is oriented vertically under a lower portion of a dam **1560**. In some embodiments, such as the embodiment shown in FIG. **15**, the first cutoff wall **1562a** may comprise a portion that extends vertically from an end of the working platform **1562**.

[0158] In some embodiments, such as the embodiment shown in FIG. **15**, the dam **1560** is coupled to a second cutoff wall **1562b** that is oriented vertically relative to the working platform **1562**.

[0159] The power generation system may comprise one or more cleats coupled to a lower surface of the dam and/or powerhouse. In some embodiments, such as the one shown in FIG. **15**, one or more cleats **1574** are indirectly coupled to a lower surface of the dam **1560**. In this embodiment, the one or more cleats **1574** are directly coupled to the working platform **1562**. In alternative embodiments, the one or more cleats **1574** may be directly coupled to a lower surface of the dam. Different cleats may have different dimensions and/or material characteristics. In some embodiments, such as the embodiment shown in FIG. **15**, the dam **1560** may be coupled to one or more rock bolts **1592**.

[0160] In constructing an assembly of precast segments for use in constructing a dam or powerhouse, the assembly may provide for ground stabilizing, such as by forming a shape of a cleating system **1574** between the assembly and the ground in order to have additional stability beyond the dead weight of the assembly. The cleating system **1574**, for example, may have alternating extending and non-extending precast segments on a footprint of the dam to have extended depth in certain locations of the footprint versus other locations of the footprint. Underpinning systems, rock bolts **1592** and other construction elements may also be employed.

[0161] The assembly of precast segments may also include seismic construction elements, such as the cleats described above, insulators between precast segments or various subassemblies of precast segments, seismic relief features, water stops between precast segments, other features encapsulated by precast segments, or any additional water stops in order to maintain structural

integrity over extended periods of time, such as 50, 100, or a greater number of years.

[0162] FIG. **16** is a perspective view of an example embodiment of a dam **1660** with multiple slots for precast mass fills. In alternative embodiments, the dam may have a different number of slots.

[0163] In the example embodiment shown in FIG. **16**, the precast infill block **1672** is defined by a rectangular shape. In alternative embodiments, one or more of the precast infill blocks may be defined by a different shape. The dimensions shown in FIG. **16** are example dimensions. In alternative embodiments, the dimensions of the precast infill block and/or the slots may be different.

[0164] FIG. **17A** shows a perspective of an example embodiment of a working platform **1761** coupled to rock anchors **1492**.

[0165] FIG. **17B** shows a close-up view of the working platform **1761** of FIG. **17A**. In some embodiments, such as the one shown in FIG. **17B**, the working platform **1761** comprises pleats and/or grooves configured to couple with segments of a dam/or powerhouse. In alternative embodiments the working platform may not comprise grooves.

[0166] In some embodiments, such as the one shown in FIG. **17B**, the working platform **1761** is coupled to connectors (for example, bolts) to couple with segments of a dam. In alternative embodiments, the working platform may not be coupled to connectors.

[0167] FIG. **18A** shows a perspective view of an example embodiment of a working platform **1861** coupled to multiple rock anchors **1892**. In the example embodiment shown in FIG. **18A** a cutoff wall **1862** is coupled to a lower surface of the working platform **1861**.

[0168] FIG. **18B** shows a perspective view of a working platform coupled to multiple cleats **1874**, rock anchors **1892**, and diffusers **1826**. In the example embodiment shown in FIG. **18B** the diffusers being coupled to a downstream side of the working platform **1861**. In alternative embodiments, the working platform may be coupled to diffusers at the upstream side of the working platform. In alternative embodiments, the working platform may not be coupled to cleats. In alternative embodiments, the working platform may not be coupled to rock anchors. In alternative embodiments, the working platform may not be coupled to diffusers.

[0169] FIG. **19A** shows a perspective view of an example embodiment of a square precast segment **1972** comprising dividers **1973a**, **1973b**. In some embodiments, such as the one shown in FIG. **19A** the precast segment is defined by a form configured to be filled with filler. In some embodiments, such as the one shown in FIG. **19A** the form includes two dividers **1973a** and **1973b** arranged at different sides of the form. In alternative embodiments, the form may comprise a different number of dividers. In alternative embodiments, the forms may be arranged differently. In alternative embodiments, the forms may not comprise dividers.

[0170] In some embodiments, such as the embodiment shown in FIG. **19A**, the precast form **1972** may include a port through a surface of the precast form that enables filler to flow from a given layer to a lower adjacent layer in a vertical direction. In some embodiments, the precast form does not comprise a port.

[0171] An example of a precast form is a precast cement form of any size defined in a rectangular or other geometric shape. Features, such as a bottom, side, or top, may define port(s) through which filler, such as cement, may flow. Some embodiments of the precast form define an opening instead of a top or have a top that defines at least one port at a top surface. The precast forms are individually lightweight; however, when coupled together in lateral and vertical arrangements, serve as deadweight for use as a base for the dam, powerhouse, or any other structure.

[0172] In the process of constructing a wall or other aspect of a precast dam structure, the precast forms with may be filled with various materials, such as cement, grout, stones, materials to be removed from the environment, and the like. The materials will be sealed within an assembly of precast segments. Ports in the surfaces of the precast forms enable cement and other filler to flow between adjacent forms.

[0173] A typical process of constructing a wall or other shape through use of precast forms is

typically done by filling a layer of precast forms with, for example, cement, or by filling compartments of the precast forms, where compartments are separated by dividers. By using a technique of precast forms with or without compartments, curing times of filler material (e.g., cement) are significantly reduced relative to cast in place cement dam structures.

[0174] Moreover, the precast forms may be various sizes, shapes, thicknesses for unique assembled dam shapes and sizes for aspects of the dam. It should be understood that descriptions herein of various shapes and sizes of the dam also pertain to a powerhouse that is constructed of precast segments, which may start as precast forms that are interconnected together as disclosed herein.

[0175] In some embodiments, such as the one shown in FIG. **19A** a precast form defines different compartments, each compartment being separated by one or more internal walls (also referred to as dividers). The embodiment shown in FIG. **19A** defines three compartments **C1**, **C2**, **C3**. In alternative embodiments, the precast form may define a different number of compartments. In the embodiment shown in FIG. **19A**, a first compartment **C1** includes about the same volume as a third compartment **C3**. A second compartment **C2** includes substantially more volume than the first compartment **C1** or third compartment **C3**. In alternative embodiments all of the compartments may include about the same volume. In alternative embodiments, the compartments each include a different volume.

[0176] FIG. **19B** shows a perspective view of an example embodiment of a square precast segment **1972b** defined by a form without internal walls.

[0177] FIG. **19C** shows a perspective view of an example embodiment of a rectangular precast segment **1972b** defined by a form without internal walls.

[0178] FIG. **20A** shows example embodiments of two different precast segments **2072a**, **2072b** that each define a keyway **2076**. Each precast segment shown in FIG. **20A** also includes dowels configured to couple with neighboring precast segments or other materials.

[0179] FIG. **20B** shows an example embodiment of a precast segment **2072c** that includes a snubber **2077**.

[0180] FIG. **21** is a sectional perspective view of an example embodiment of precast segments **2172** stacked and coupled together using a coupling mechanism **2193**. Described herein are advanced interlocking techniques for use with precast segments, optionally constructed of precast forms that are filled with materials, such as cement. For example, there may be unique keyways applied, shear and tension resisting linkages that interconnect adjacent precast segments during a process of filling layers of precast segments adjacent to other precast segments, wherein the shear and tension resisting linkages may pass between ports at the time of filling precast forms. As the precast forms are filled, the ports enable additional cement or other slurry-type fillers to flow from one precast form to an adjacent precast form to fill any air gaps that may have formed during a cooling process of the previously poured filler material, slurry, cement, or otherwise. Through this process, the form produced by the precast segments is increased in strength and also increased in dead weight.

[0181] Between adjacent precast segments, materials such as grout, rubber, and other materials known in the art may be used to fill gaps between adjacent precast segments and, depending on the material used, to make watertight seals between adjacent precast segments.

[0182] In some embodiments, such as the embodiment shown in FIG. **21** one or more precast segments **2172** may be coupled together using a coupling mechanism **2193**. In this embodiment, precast segments are stacked, and a coupling mechanism extends through the port of a first precast segment to a lower precast segment. Filler may be applied to the precast segments and such filler may secure the coupling mechanism in place, thereby securing two precast segments to each other. Coupling mechanisms also couple one stack of precast segments to a neighboring stack of precast segments. In some embodiments, the coupling mechanism may comprise rebar or any such suitable material.

[0183] FIG. **22A** is a side view of an example embodiment of two stacks of precast segments

coupled together. In this embodiment a first stack includes three precast segments **2272a-2272c** and a second stack includes three precast segments **2272d-2272f**. In alternative embodiments, more than two stacks of precast segments may be coupled together. One or more of the stacks may be coupled to a structure rather than another stack of precast segments.

[0184] FIG. **22B** is a perspective view of an example embodiment of four stacks of precast segments coupled together with a coupling mechanism **2293**.

[0185] FIG. **23** shows an example embodiment of four stacks of modular blocks **2372** filled with precast concrete infill blocks **2314**. In some example embodiments a precast segment includes a precast form and at least one precast infill block **2314**. The precast form may be sized and shaped to accept one or more precast infill blocks **2314**. In some example embodiments, the tolerances (i.e., spaces) inside modular blocks **2372** may be filled with fine processed stone, rubber grindings, or any such similar or suitable material, for example other materials described herein.

[0186] In the example embodiment shown in FIG. **23**, precast infill blocks **2314** are defined by a rectangular shape. In alternative embodiments, one or more of the precast infill blocks may be defined by a different shape.

[0187] In the example embodiment shown in FIG. **23**, two precast infill blocks **2314** are positioned in a modular block **2372**. In alternative embodiments, a different number of precast infill blocks may be positioned in a modular block **2372**.

[0188] In the example embodiment shown in FIG. **23**, for each modular block **2372**, two precast infill blocks **1214** are oriented next to each other. Alternatively or additionally, in some example embodiments precast infill blocks **1214** may be stacked on each other.

[0189] In some example embodiments, one or more of the precast infill blocks are fixedly coupled to a precast segment. In alternative embodiments, one or more of the precast infill blocks may not be fixedly coupled to a precast segment.

[0190] FIG. **24A** shows a perspective view of example embodiments of angled precast segments **2472a-2472d**. The angled precast segments are defined by forms, similar to other precast segments described herein. In some embodiments, such as the one shown in FIG. **24A**, the precast segments may be coupled via one or more linkages **2478**. In some embodiments, such as the one shown in FIG. **24A**, the precast segments may be coupled via one or more dowels **2479**. In some embodiments, such as the one shown in FIG. **24A**, the precast segments may be coupled via one or more keyways **2476**.

[0191] FIG. **24B** shows a side view of the example embodiments of angled precast segments of FIG. **24A**.

[0192] FIG. **24C** shows a side view of the example embodiments of angled precast segments of FIG. **24A**.

[0193] FIG. **25** is a perspective view of an example embodiment of a power generation system **2500** comprising a dam **2560**, a powerhouse (not shown), and auxiliary power systems **2594a-2594f**. Auxiliary power systems, such as wind turbines, solar collectors, thermal systems, or gasoline or diesel-powered electrical generators may be employed to provide for power availability at a dam or powerhouse during times of auxiliary power support is of use. Similarly, energy storage systems may be co-located with the dam or powerhouse to store energy from the auxiliary power sources or to store power generated by turbines in the dam or powerhouse or portion of power that is otherwise transmitted offsite via a power grid, for example.

[0194] The embodiment shown in FIG. **25** includes multiple auxiliary power systems. In alternative embodiments there may be a different number of auxiliary power systems. In alternative embodiments, the power generation system may not include an auxiliary power system. The power generation system may comprise at least one energy storage system.

[0195] FIG. **26A** is a perspective view of an example embodiment of a power generation system **2600** comprising a dam **2660** and a powerhouse **2610**. In the embodiment shown in FIG. **26** the dam **2660** is coupled to an abutment wall **2670**. In the embodiment shown in FIG. **26** the abutment

wall **2670** is coupled to three support abutment walls **2671a-2671c**. In some embodiments, such as the one shown in FIG. **26A**, a portion of the fluid from the waterway is directed to a powerhouse **2610**. The powerhouse **2610** comprises a power generator **2605** configured to convert the fluid flow into electrical power.

[0196] FIG. **26B** is a zoomed-out view of the example embodiment shown in FIG. **26A**.

[0197] FIG. **27** shows an example embodiment a control system **2797** configured to coordinate activity between a dam and a powerhouse of a power generator. In some embodiments, the control system includes a power generator controller **2752** in communication with a powerhouse gate controller **2754** and a dam gate controller **2756**. The power generator controller **2752** may be coupled to one or more sensors that detect activity in a waterway and coordinate actions with the powerhouse gate controller **2754** and/or the dam gate controller **2756**. For example, if a larger than normal flow of fluid is detected, the powerhouse controller **2754** and/or the dam gate controller **2756** may be instructed to open additional gates.

[0198] If a power generator is damaged or otherwise offline, the powerhouse gate controller **2754** may communicate with the power generator controller **2752** and/or the dam gate controller **2756** to adjust accordingly by, for example, opening additional control gates at the dam.

[0199] In some example embodiments, the control system **2797** may coordinate with the power generator controller **2752**, powerhouse gate controller **2754**, and/or the dam gate controller to calculate and/or arrange a bypass flow path from input the port to the output port or within a flow path to enable fluid flow to circumvent the power generator.

[0200] In some example embodiments, the control system **2797** may coordinate with the power generator controller **2752**, powerhouse gate controller **2754**, and/or the dam gate controller to calculate and/or arrange multiple flow paths.

[0201] In some example embodiments, the control system **2797** may coordinate with the power generator controller **2752**, powerhouse gate controller **2754**, and/or the dam gate controller to calculate and/or arrange multiple flow paths in combination with the operation of one or more flow control gates.

[0202] The power generation system of claim **5**, wherein the powerhouse includes a flow control gate, and wherein the flow path structure defines multiple flow paths at least one of which is operably controllable in combination with operation of the flow control gate.

[0203] The power generator may include a water intake system or module that may be formed of precast forms that may be constructed as described immediately above. The intake system may be a “circular tower” system of precast forms that are constructed in layers with sufficient water intake at each layer to provide water flow to the compost through a flow path that may be above ground or beneath the ground, depending on certain factors, such as where a powerhouse is located relative to the location of the intake system. In some embodiments, the water intake system is functionally coupled to at least one of the powerhouse system or the dam system.

[0204] FIG. **28A** shows a side view of an example embodiment of an intake module **2851**.

[0205] FIG. **28B** shows a perspective sectional view of an example embodiment of an intake module **2851**.

[0206] FIG. **28C** shows a perspective view of an example embodiment of a layer **2857** of an intake module **2851**.

[0207] One or more of the intake modules **2851** may be constructed using precast components. In various embodiments, an intake module **2851** may comprise a support base **2853** and an at least one intake region **2855**. In the embodiment shown in FIG. **28A**, the intake module **2851** comprises one intake region **2855**. In alternative embodiments, the intake module may comprise more than one intake region coupled to a support base.

[0208] In various embodiments, the intake region **2855** may comprise one or more layers **2857**. One or more of the one or more layers **2857** may comprise precast segments. A portion of a layer may be a precast segment. An entire layer may be a precast segment. Multiple layers may together

be a precast segment.

[0209] One or more of the one or more layers may comprise one or more apertures. In the embodiment shown in FIGS. **28A-28C**, each layer **2857** comprises one circular central aperture **2858** and the circular aperture **2858** is positioned at the center of the layer **2857**. In alternative embodiments, one or more of the layers may not comprise an aperture. In alternative embodiments, one or more of the layers may comprise more than one aperture. In alternative embodiments, one or more of apertures may comprise a different shape. In alternative embodiments, one or more of the apertures may be positioned off-center at the corresponding layer.

[0210] One or more apertures of the layers may form one or more axial channels **2859** through the intake region **2855** of the intake module **2851**. In the embodiment shown in FIGS. **28A-28C**, the intake region **2855** comprises one channel **2859**. In alternative embodiments, the intake region may comprise more than one channel.

[0211] The axial channel of the intake region may be aligned with an axial channel of the support base. The axial channel of the support base may be aligned with a channel of a fluid conduit.

[0212] One or more of the one or more layers **2857** may comprise one or more protrusions **2867**. In various embodiments, a first layer **2857a** and a neighboring second layer **2857b** may be arranged such that the arrangement of protrusions **2867** create apertures **2868** at the sides of the intake region **2855**. These apertures **2868** are configured to allow fluid to enter the intake module **2851** and flow to an axial channel **2859**. In various embodiments, the protrusions **2867** may be configured differently than the configuration shown in FIGS. **28A-28C**.

[0213] In the embodiment shown in FIGS. **28A-28C**, each layer **2857** comprises a circular shape. In alternative embodiments, one or more of the layers may comprises a different shape. In the embodiment shown in FIGS. **28A-28C** each support base **2853** comprises a circular shape. In alternative embodiments, the support base may comprise a different shape.

[0214] In some embodiments, the top of the intake region comprises a cover **2869**. In alternative embodiments, the top of the intake region may comprise at least one aperture. In various embodiments, at least one aperture of the at least one aperture at the top of the intake region may be aligned with at least one axial channel. In various embodiments, the cover of the intake region may comprise one or more precast components.

[0215] One more intake module may be located in or near an upper impoundment structure, a lower impoundment structure, an intermediary impoundment structure, a dam, or a natural water source (e.g. a river, lake, pond, etc.). In various embodiments, the intake module may be constructed using cast in place techniques.

[0216] FIGS. **29-39** show example embodiments of microgrid facilities. In some example embodiments, a microgrid may have black start capability to supply power to state and local first responders (for example, Department of Defense, Federal Emergency Management Agency, Cybersecurity and Infrastructure Security Agency, Department of Homeland Security). In some example embodiments, a microgrid may have the capability to supply power to local critical infrastructure, for example, hospitals, police, fire stations, wastewater treatment plants. In some example embodiments, a microgrid may may serve as a long-term emergency energy for critical loads supplied to life support facilities.

[0217] FIG. **29A** shows an example embodiment of a microgrid facility **2900**. In some example embodiments, such as the one shown in FIG. **29A** the microgrid facility **2900** includes six energy generation facilities (labelled with circles numbered **1-6**). In alternative embodiments, the microgrid facility may have a different number of energy generation facilities.

[0218] In some example embodiments, such as the one shown in FIG. **29A** the microgrid facility **2900** includes six secure buildings (labelled with squares numbered **1-6**). In alternative embodiments, the microgrid facility may have a different number of energy generation facilities.

[0219] FIG. **29B** shows example embodiments of energy generation facilities at an example microgrid facility **2900**. In some example embodiments, such as the one shown in FIG. **29B** the

microgrid facility **2900** includes different types of energy generation facilities, including: hydropower, wind power, solar power, fuel generator, geothermal, battery storage. In alternative embodiments, the microgrid facility **2900** may have a subset of these energy generation facilities. In alternative embodiments, the microgrid facility may have additional types of energy generation facilities.

[0220] FIG. **29C** show an example embodiment of secure buildings at an example microgrid facility **2900**. In alternative embodiments, a microgrid facility may have different types of secure buildings. In alternative embodiments, the different types of secure buildings may be at different locations.

[0221] FIG. **29D** shows an example embodiment of an underground system associated with an example microgrid facility **2900**.

[0222] FIG. **30** shows an example embodiment of a powerhouse **3010**.

[0223] FIG. **31** shows an example embodiment of a powerhouse **3110**. As shown in FIG. **31**, the powerhouse may include a reinforced upstream façade to resist 100+ year mark storm water level.

[0224] FIG. **32A** shows an example embodiment of a powerhouse **3210** outflow.

[0225] FIG. **32B** shows a close-up of the example powerhouse **3210** shown in FIG. **32A**.

[0226] FIG. **33** shows a perspective view of an example powerhouse coupled to a fish passage **3398**. In this example embodiment the fish passage includes a system that attracts fish upstream.

[0227] FIG. **34** shows an example view through a security tower at a microgrid facility.

[0228] FIG. **35** shows an example embodiment of a microgrid power generation facility **3500** that includes wind power generation systems **3590** and solar power generation system **3591**. In alternative embodiments, the microgrid power generation facility may not include wind power generation system. In alternative embodiments, the microgrid power generation facility may not include solar power generation system.

[0229] In the embodiment shown in FIG. **35** the wind power generation system **3590** includes three turbines. In alternative embodiments, the wind power generation system **3590** includes a different number of turbines.

[0230] In the embodiment shown in FIG. **35** the solar power generation system **3591** includes three solar panels. In alternative embodiments, the solar power generation system **3591** includes a different number of solar panels.

[0231] In some example embodiments, the microgrid facility **3500** may include underground power lines. In some example embodiments, the microgrid facility may include underground power lines to the central battery.

[0232] In some example embodiments the microgrid facility **3500** may include access roads connecting buildings and the hydropower facility. In some example embodiments the microgrid facility **3500** may include at least one helipad and/or designated parking.

[0233] FIG. **36** shows example embodiments of aspects of an access control system **3643** at a microgrid facility. The access control system may include a blast-proof wall around the microgrid facility. The blast-proof wall may include precast segments.

[0234] The access control system may include security sensors. The access control system may include camera systems. The access control systems may include one or more locked fences **3644**. Four fences **3644a-3644d** are shown in FIG. **36**. The access control system may include a different number of fences.

[0235] The access control systems may include one or more tire spikes **3645**. The access control system may include at least one access control building. At least one access control building may include blast-proof windows.

[0236] FIG. **37** shows an example embodiment of a microgrid power generation facility that includes energy solutions, a watch tower, and buildings. In some embodiments, the microgrid facility may not include a watch tower.

[0237] FIG. **38** shows an example embodiment of a microgrid facility with precast buildings with

form liners. In some embodiments, one or more of the buildings at the microgrid facility include precast segments. In some embodiments, one or more of the buildings are cyber protected. In some embodiments, one or more of the buildings are EMP (electromagnetic pulse) protected. In some embodiments, one or more of the buildings are flare protected.

[0238] FIG. 39 shows an example embodiment of a microgrid power generation facility 3900 that includes a hydropower facility, the hydropower facility including at least one precast segment.

[0239] In various embodiments, one or more of the precast segments may be coupled using at least one dowel, at least one bolt, at least one keyway, at least one re-rod, or at least one port. In various embodiments, one or more of the modular blocks may be coupled using at least one expandable linkage, at least one automatic linkage (that locks itself), at least one prestressed cable (vertical configuration, horizontal configuration, or other configuration), at least one linkage port, or any other mechanism suitable for connecting items.

[0240] In some embodiments, the power generation system may comprise at least one icebreaker. An icebreaker may include sharpened assemblies facing upstream that are intended to break ice flows to prevent damage to the dam or powerhouse. In some example embodiments, an icebreaker may include one or more precast balls that float.

[0241] In various example embodiments, spaces between neighboring precast segments may be filled with concrete, grout, liners, or water stopping agents. In various example embodiments, spaces between precast segments and other elements (for example, fluid conduits) may be filled with concrete, grout, liners, or water stopping agents. In various example embodiments, spaces within precast forms may be filled with concrete, grout, liners, or water stopping agents. In various example embodiments, spaces between any elements associated with a powerhouse or dam may be filled with concrete, grout, liners, or water stopping agents.

[0242] In various example embodiments, one or more hydrophobic coatings (for example, nanotech coatings) may be applied to seals or filler materials between neighboring precast segments. In various example embodiments, one or more hydrophobic coatings (for example, nanotech coatings) may be applied to seals or filler materials between precast segments and other elements (for example, fluid conduits). In various example embodiments, one or more hydrophobic coatings (for example, nanotech coatings) may be applied to seals or filler materials between spaces or filler material within precast forms. In various example embodiments, one or more hydrophobic coatings (for example, nanotech coatings) may be applied to seals or filler materials associated with a powerhouse or dam.

[0243] In some example embodiments, one or more precast segments may be sized and/or shaped to couple with a working platform.

[0244] The foregoing are example embodiments and features of embodiments that are disclosed herein. Additional description can be found in U.S. Pat. No. 11,708,674, the entire teachings of which are incorporated herein by reference in their entirety.

[0245] The teachings of all patents, published applications, and references cited herein are incorporated by reference in their entirety.

[0246] The features and/or dimensions shown and/or described in this application are not necessarily to scale. Features and/or dimensions may be any size and/or any shape. Example dimensions may be provided herein. In alternative embodiments, one or more of the example dimensions may be different. In some embodiments, one or more characteristics described in connection with an embodiment described herein may be used with any other embodiment described herein.

[0247] While example embodiments have been particularly shown and described, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the scope of the embodiments encompassed by the appended claims.

Claims

1. A power generation system, comprising: a powerhouse, comprising: a flow path structure defining at least a portion of a flow path, the flow path structure configured to accept fluid at an input port to enter the powerhouse and direct the fluid to exit the powerhouse at an output port; a power generator support structure, at least partially constructed of precast segments, configured to support weight of a power generator in an arrangement operably disposed within the flow path; and an access port different from the input port, the access port aligned to enable removable coupling of the power generator to and from the power generation support structure.
2. The power generation system of claim 1, wherein the power generation support structure includes precast forms and filler that define the precast segments and wherein the precast forms are filled with the filler on a layer-by-layer basis during a process of arranging the precast segments in vertical layers to define the power generation support structure.
3. The power generation system of claim 1, wherein the precast forms include a port through a surface of the precast form that enables filler to flow from a given layer to a lower adjacent layer in a vertical direction.
4. The power generation system of claim 1, wherein the power generation support structure defines a lowest layer having a pattern of vertically offset portions or further comprising a layer, having a pattern of vertically offset portions.
5. The power generation system of claim 1, further comprising a dam functionally coupled with the powerhouse in a manner that maintains or discontinues fluid flow to the input port.
6. The power generation system of claim 5, wherein the powerhouse is arranged in a vertical configuration, in which the power generator is arranged vertically; or a horizontal configuration, in which the power generator is arranged horizontally.
7. The power generation system of claim 5, wherein the flow path structure defines a bypass flow path from input port to output port or within a flow path to enable fluid flow to circumvent the power generator.
8. The power generation system of claim 5, wherein the powerhouse includes a flow control gate, and wherein the flow path structure defines multiple flow paths at least one of which is operably controllable in combination with operation of the flow control gate.
9. The power generation system of claim 1, wherein the flow path structure defines multiple flow paths, at least a subset of the multiple flow paths being selectably configurable to enable fluid flow.
10. The power generation system of claim 5, wherein the powerhouse includes an icebreaker arranged to break ice prior to flowing into the input port.
11. The power generation system of claim 1, further comprising a superstructure positioned above at least a portion of the powerhouse, wherein the superstructure is configured to support a functional element to perform maintenance at the powerhouse.
12. The power generation system of claim 11, wherein the superstructure comprises at least one rail, located on or within the superstructure that enables coupling with the functional element.
13. The power generation system of claim 11, wherein the functional element comprises a crane configured to be mechanically powered.
14. The power generation system of claim 1, wherein the powerhouse further comprises a Faraday shield room or a room shielded with radiation hardened material.
15. The power generation system of claim 1, further comprising at least one auxiliary power system.
16. The power generation system of claim 1, further comprising at least one energy storage system.
17. The power generation system of claim 1, wherein at least one of the precast segments is removably coupled with the power generation support structure.
18. The power generation system of claim 11, wherein the functional element is a crane assembly

- configured to raise or lower at least one flow control gate in order to control a height of a reservoir.
- 19.** The power generation system of claim 18, wherein the crane comprises a combination of crane elements to lift the at least one waterflow restriction gate from multiple points to reduce a likelihood that a gate will cantilever during raising and lowering operations.
- 20.** The power generation system of claim 1, wherein the powerhouse further comprises an access channel, one end of the access channel being coupled to the access port.
- 21.** The power generation system of claim 11, wherein the superstructure comprises an enclosure positioned around the access port.
- 22.** The power generation system of claim 1, wherein the access port is defined by at least one precast segment.
- 23.** The power generation system of claim 1, wherein the flow path structure is configured to accept fluid at an input port to enter the powerhouse in a first direction and the access port is oriented in a second direction, the second direction being different than the first direction.
- 24.** The power generation system of claim 1, wherein the power generator comprises at least one turbine.
- 25.** The power generation system of claim 1, wherein at least one of the precast forms comprises at least one divider to define two or more compartments.
- 26.** The power generation system of claim 1, further comprising at least one water intake system comprising at least one precast segment, the water intake system being functionally coupled to at least one of the powerhouse system or the dam system.
- 27.** The power generation system of claim 1, wherein the powerhouse comprises a flow control gate configured to communicate with the power generator.
- 28.** A power generation system, comprising: a powerhouse at least partially defined by a plurality of precast segments, at least one of the precast segments including a precast form having disposed therein at least one precast infill block.
- 29.** A power generation system, comprising: a dam at least partially defined by a plurality of precast segments, at least one of the precast segments including a precast form having disposed therein at least one precast infill block.
-