

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12391456
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Tye; Paul

---

### Container with liner

---

#### Abstract

A container for heating a food product. The container comprises a base layer of material and a liner releasably attached to an inner surface of the base layer. The liner is at least partially attached to the base layer by a heat seal layer, and the liner is separable from the base layer after heating the container. The container comprises a bottom panel and a sidewall extending along the bottom panel.

---

<b>Inventors:</b>	<b>Tye; Paul (Buckinghamshire, GB)</b>
<b>Applicant:</b>	<b>Graphic Packaging International, LLC (Atlanta, GA)</b>
<b>Family ID:</b>	<b>1000008763997</b>
<b>Assignee:</b>	<b>Graphic Packaging International, LLC (Atlanta, GA)</b>
<b>Appl. No.:</b>	<b>16/037425</b>
<b>Filed:</b>	<b>July 17, 2018</b>

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20180319568 A1	Nov. 08, 2018

#### Related U.S. Application Data

continuation-in-part parent-doc US 15654814 20170720 US 11358779 child-doc US 16037425  
us-provisional-application US 62649159 20180328  
us-provisional-application US 62643914 20180316  
us-provisional-application US 62365635 20160722

---

#### Publication Classification

**Int. Cl.:** **B65D81/34** (20060101); **B65D5/20** (20060101); **B65D5/48** (20060101); **B65D5/56** (20060101); **B65D6/04** (20060101); **B65D6/18** (20060101); **B65D77/04** (20060101); **B65D77/28** (20060101)

**U.S. Cl.:**

**CPC** **B65D81/3453** (20130101); **B65D5/209** (20130101); **B65D5/48002** (20130101); **B65D5/563** (20130101); **B65D7/08** (20130101); **B65D7/26** (20130101); **B65D77/042** (20130101); **B65D77/286** (20130101); B65D2581/055 (20130101); B65D2581/347 (20130101); B65D2581/3472 (20130101); B65D2581/3479 (20130101); B65D2581/3491 (20130101); B65D2581/3493 (20130101)

## Field of Classification Search

**CPC:** B65D (81/3453); B65D (5/209); B65D (5/563); B65D (7/08); B65D (7/26); B65D (77/0413); B65D (77/22); B65D (2581/055); B65D (2581/347); B65D (2581/3472); B65D (2581/3479); B65D (5/2033); B65D (5/2047); B65D (5/242); B65D (5/243)

**USPC:** 206/557; 229/407

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2110681	12/1937	Rutledge	N/A	N/A
3104012	12/1962	Beamish	206/438	B65D 77/22
3154215	12/1963	Le Vesconte	N/A	N/A
3358900	12/1966	Perdue et al.	N/A	N/A
3489331	12/1969	Anderson et al.	N/A	N/A
3575338	12/1970	Dilot	N/A	N/A
3640188	12/1971	Dilot	N/A	N/A
3893882	12/1974	Repenning	N/A	N/A
3941301	12/1975	Jorgensen	N/A	N/A
4046310	12/1976	Gustafsson	N/A	N/A
4057380	12/1976	Hosoe	N/A	N/A
4130236	12/1977	Manizza	N/A	N/A
4283427	12/1980	Winters et al.	N/A	N/A
4305542	12/1980	Benzschawel et al.	N/A	N/A
4308895	12/1981	Manizza	N/A	N/A
4325905	12/1981	Takahashi	N/A	N/A
4351473	12/1981	Manizza	N/A	N/A
4533065	12/1984	Chazal et al.	N/A	N/A
4555381	12/1984	Chazal et al.	N/A	N/A
4718596	12/1987	Muller et al.	N/A	N/A
4943456	12/1989	Pollart et al.	N/A	N/A
5000374	12/1990	Deiger	N/A	N/A
5002826	12/1990	Pollart et al.	N/A	N/A
5002833	12/1990	Kinsey, Jr. et al.	N/A	N/A
5118747	12/1991	Pollart et al.	N/A	N/A

5203491	12/1992	Marx et al.	N/A	N/A
5253801	12/1992	Bernstein et al.	N/A	N/A
5326021	12/1993	Farrell	N/A	N/A
5351879	12/1993	Liu	N/A	N/A
5410135	12/1994	Pollart et al.	N/A	N/A
5412187	12/1994	Walters et al.	N/A	N/A
5530231	12/1995	Walters et al.	N/A	N/A
5533622	12/1995	Stockley, III	206/484	B65B 9/02
5533623	12/1995	Fischer	N/A	N/A
5647168	12/1996	Gilbert	N/A	N/A
6092687	12/1999	Hupp et al.	N/A	N/A
6116501	12/1999	Hupp	N/A	N/A
6204492	12/2000	Zeng et al.	N/A	N/A
6234386	12/2000	Drummond et al.	N/A	N/A
6433322	12/2001	Zeng et al.	N/A	N/A
6552315	12/2002	Zeng et al.	N/A	N/A
6677563	12/2003	Lai	N/A	N/A
8534460	12/2012	Wnek et al.	N/A	N/A
8801995	12/2013	Wnek et al.	N/A	N/A
9783345	12/2016	Bentham	N/A	N/A
2005/0031814	12/2004	Dawes	N/A	N/A
2007/0116806	12/2006	Parsons	N/A	N/A
2008/0035634	12/2007	Zeng et al.	N/A	N/A
2011/0174676	12/2010	Stockhaus	N/A	N/A
2011/0259784	12/2010	Tye et al.	N/A	N/A
2012/0248180	12/2011	White et al.	N/A	N/A
2013/0327821	12/2012	Zwaga et al.	N/A	N/A
2014/0183198	12/2013	Slack	N/A	N/A
2014/0224866	12/2013	Littlejohn et al.	N/A	N/A
2015/0225120	12/2014	Wnek et al.	N/A	N/A
2017/0341355	12/2016	Peiffer et al.	N/A	N/A
2018/0022529	12/2017	Tye	N/A	N/A
2020/0047940	12/2019	Tye et al.	N/A	N/A
2020/0047975	12/2019	Tye et al.	N/A	N/A
2020/0255200	12/2019	Mondini et al.	N/A	N/A

#### FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2 814 149	12/2011	CA	N/A
203450620	12/2013	CN	N/A
100 22 552	12/2000	DE	N/A
0 671 332	12/1994	EP	N/A
1 104 744	12/2000	EP	N/A
2133727	12/1971	FR	N/A
2406522	12/1978	FR	N/A
2826938	12/2002	FR	N/A
2933329	12/2009	FR	N/A
1 314 148	12/1972	GB	N/A
1 501 764	12/1977	GB	N/A
1 602 625	12/1980	GB	N/A

2 487 765	12/2011	GB	N/A
2 550 386	12/2016	GB	N/A
2000-141511	12/1999	JP	N/A
2001 278246	12/2000	JP	N/A
2002 347746	12/2001	JP	N/A
10-1539187	12/2014	KR	N/A
M 295475	12/2005	TW	N/A
M 301016	12/2005	TW	N/A
WO 2003/041945	12/2002	WO	N/A
WO 2007/127371	12/2006	WO	N/A
WO 2009/138786	12/2008	WO	N/A
WO 2012/049005	12/2011	WO	N/A
WO 2013/002639	12/2012	WO	N/A
WO 2014/032059	12/2013	WO	N/A
WO 2014/066867	12/2013	WO	N/A
WO 2015/009518	12/2014	WO	N/A
WO 2019/094057	12/2015	WO	N/A
WO 2018/017783	12/2017	WO	N/A
WO 2018/178508	12/2017	WO	N/A
WO 2019/020863	12/2018	WO	N/A
WO 2019/092323	12/2018	WO	N/A
WO 2020/033350	12/2019	WO	N/A
WO 2020/033352	12/2019	WO	N/A

## OTHER PUBLICATIONS

International Search Report and Written Opinion for PCT/US2017/042979 dated Sep. 22, 2017.  
cited by applicant

International Search Report and Written Opinion for PCT/US2018/042431 dated Dec. 14, 2018.  
cited by applicant

Supplementary European Search Report for EP 17 83 1847 dated January. cited by applicant

Office Action for Canadian Patent Application No. 3,027,438 dated Nov. 7, 2019. cited by  
applicant

Supplementary European Search Report for EP 18 90 9768 dated Oct. 28, 2021. cited by applicant

---

*Primary Examiner:* Perreault; Andrew D

*Attorney, Agent or Firm:* Womble Bond Dickinson (US) LLP

---

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation-in-part of U.S. patent application Ser. No. 15/654,814, filed on Jul. 20, 2017, which claims the benefit of U.S. Provisional Patent Application No. 62/365,635, filed Jul. 22, 2016. This application claims the benefit of U.S. Provisional Patent Application No. 62/649,159, filed on Mar. 28, 2018, and U.S. Provisional Patent Application No. 62/643,914, filed Mar. 16, 2018. INCORPORATION BY REFERENCE (2) The disclosures of U.S. Provisional Patent Application No. 62/649,159, filed Mar. 28, 2018, U.S. Provisional Patent Application No. 62/643,914, filed Mar. 16, 2018, U.S. patent application Ser. No. 15/654,814, filed Jul. 20, 2017, U.S. Provisional Patent Application No.

## BACKGROUND OF THE DISCLOSURE

(1) The present disclosure relates to blanks, containers, trays, constructs, and various features and methods for forming a container from a blank. More specifically, the disclosure is generally directed to a container having a liner, the container being suitable for heating a food product.

## SUMMARY OF THE DISCLOSURE

(2) In general, one aspect of the disclosure is generally directed to a container for heating a food product. The container comprises a base layer of material and a liner releasably attached to an inner surface of the base layer. The liner is at least partially attached to the base layer by a heat seal layer, and the liner is separable from the base layer after heating the container. The container comprises a bottom panel and a sidewall extending along the bottom panel.

(3) In another aspect, the disclosure is generally directed to a method of forming a container comprising a bottom panel and a sidewall extending along the bottom panel. The method can comprise obtaining a blank, a liner material, and a heat seal layer, forming the blank into an initial construct, activating the heat seal layer, and applying at least a portion of the liner material to an inner surface of the initial construct so that the liner material and the initial construct form a respective liner and base layer of the container and so that the liner is releasably attached to the inner surface of the base layer by the heat seal layer. The liner can be separable from the base layer after heating the container.

(4) In another aspect, the disclosure is generally directed to a container for heating a food product. The container can comprise a base layer of material and a liner releasably attached to an inner surface of the base layer. The liner can be separable from the base layer after heating the container. The container further can comprise a bottom panel and a sidewall. The sidewall can comprise at least an end panel foldably connected to the bottom panel and a side panel foldably connected to the bottom panel. The sidewall can comprise a lower portion extending along the bottom panel and an upper portion extending upwardly from the lower portion along an intermediate fold line.

(5) In another aspect, the disclosure is generally directed to, in combination, a blank and a liner material for forming a container for heating a food product. The blank can comprise a bottom panel, an end panel foldably connected to the bottom panel, and a side panel foldably connected to the bottom panel. The end panel and the side panel can be for at least partially forming a sidewall comprising a lower portion extending along the bottom panel and an upper portion extending upwardly from the lower portion along an intermediate fold line when the container is formed from the blank and the liner material. The blank can be for forming a base layer of the container. The liner material can be for forming a liner that is releasably attached to an inner surface of the base layer when the container is formed from the blank and the liner material. The liner can be separable from the base layer after heating of the container formed from the blank and the liner material.

(6) In another aspect, the disclosure is generally directed to a method of forming a container. The method can comprise obtaining a blank and a liner material, the blank comprising a bottom panel, an end panel foldably connected to the bottom panel, and a side panel foldably connected to the bottom panel. The method further can comprise forming the blank into an initial construct and attaching at least a portion of the liner material to an inner surface of the initial construct so that the liner material and the initial construct form a respective liner and base layer of the container and so that the liner is releasably attached to the inner surface of the base layer by the heat seal layer. The liner can be separable from the base layer after heating the container. The end panel and the side panel can at least partially form a sidewall comprising a lower portion extending along the bottom panel and an upper portion extending upwardly from the lower portion along an intermediate fold line.

(7) Those skilled in the art will appreciate the above stated advantages and other advantages and

benefits of various additional embodiments reading the following detailed description of the embodiments with reference to the below-listed drawing figures.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

- (1) According to common practice, the various features of the drawings discussed below are not necessarily drawn to scale. Dimensions of various features and elements in the drawings may be expanded or reduced to more clearly illustrate the embodiments of the disclosure.
- (2) FIG. 1 is a plan view of a blank used for forming a container according to a first exemplary embodiment of the disclosure.
- (3) FIGS. 2A and 2B are perspective views of the container formed from the blank of FIG. 1 and a liner according to the first exemplary embodiment of the disclosure.
- (4) FIGS. 3A and 3B are schematic cross-sectional views of portions of the container of FIGS. 2A and 2B.
- (5) FIG. 4 is a schematic of an apparatus for forming a container of one embodiment of the disclosure.
- (6) FIG. 5 is a schematic view of the application of the liner to the base layer of the container according to one embodiment of the disclosure.
- (7) FIG. 6 is a plan view of a blank used for forming a container according to a second exemplary embodiment of the disclosure.
- (8) FIG. 7 is a perspective view of the container formed from the blank of FIG. 6 and a liner according to the second exemplary embodiment of the disclosure.
- (9) FIG. 8 is a cross-sectional view of a portion of the container of FIG. 7.
- (10) FIG. 9 is a plan view of a blank used for forming a container according to a third exemplary embodiment of the disclosure.
- (11) FIG. 10 is a perspective view of the container formed from the blank of FIG. 9 and a liner according to the third exemplary embodiment of the disclosure.
- (12) FIG. 11 is a cross-sectional view of a portion of the container of FIG. 10.
- (13) Corresponding parts are designated by corresponding reference numbers throughout the drawings.

### DETAILED DESCRIPTION OF THE EXEMPLARY EMBODIMENTS

- (14) The present disclosure relates generally to various aspects of containers, constructs, trays, materials, packages, elements, and articles, and methods of making such containers, constructs, trays, materials, packages, elements, and articles. Although several different aspects, implementations, and embodiments are disclosed, numerous interrelationships between, combinations thereof, and modifications of the various aspects, implementations, and embodiments are contemplated hereby. In one illustrated embodiment, the present disclosure relates to forming a container or tray for holding food items or various other articles. However, in other embodiments, the container or tray can be used to form other non-food containing articles or may be used for heating or cooking.
- (15) FIG. 1 illustrates a blank 3 that is used to form a container 5 (FIGS. 2A and 2B) having a base layer 7 and a liner 9 according to a first embodiment of the disclosure. In one embodiment, the base layer comprises paperboard (e.g., solid bleached sulphate folding boxboard), or other suitable material that can be recyclable and/or suitable for use in an oven (not shown), and the liner 9 comprises a plastic layer such as polyethylene, a polyethylene terephthalate (PET) material, or any other thermoplastic material, or a bioplastic, such as vegetable oil or starch based plastics. In an exemplary embodiment, the liner 9 comprises PET or a similar material that is at least partially attached to the base layer 7 by a heat seal layer 10 (FIGS. 3A and 3B). For example, the heat seal

layer **10** can include a thermoformable sealant grade transparent polyester packaging film, such as Mylar® XMPOL12 available from DuPont Teijin Films U.S. Limited Partnership of Hopewell, Virginia. Alternatively, the heat seal layer **10** could be any suitable thermoformable sealant or adhesive, any suitable heat or pressure activated adhesive, or any other suitable material. The container **5** is suitable for heating a food product (not shown) in an oven (not shown) such as a convection or conventional heating oven or microwave oven. In the illustrated embodiment, the liner **9** is at least partially attached to the base layer **7** and is in contact with the food product during heating. After heating the food product, the base layer **7** and the liner **9** can be separated to allow both the base layer **7** and the liner **9** to be recycled separately. U.S. Patent Application Publication No. 2011/0259784, published Oct. 27, 2011, and corresponding to U.S. patent application Ser. No. 12/992,131, filed Feb. 11, 2011, and PCT/GB/09/50506 filed May 13, 2009, are incorporated by reference herein for all purposes.

(16) The blank **3** can be formed from a single ply of material, such as but not limited to paperboard, cardboard, paper, or a polymeric sheet, but alternatively, the blank can be formed from a laminate that includes more than one layer. In one embodiment, the blank **3** can include a microwave interactive layer (not shown) such as is common in MicroRite® containers available from Graphic Packaging International of Atlanta, GA. The microwave interactive layer can be commonly referred to as, or can have as one of its components, a foil, a microwave shield, or any other term or component that refers to a layer of material suitable for shielding microwave energy and/or causing heating in a microwave oven.

(17) As shown in FIG. 1, the blank **3** has a longitudinal direction **L1** and a lateral direction **L2**. In the illustrated embodiment, the blank **3** has a bottom panel **11**, a first end panel **13** foldably connected to the bottom panel at a lateral fold line **15**, a second end panel **17** foldably connected to the bottom panel at a lateral fold line **19**, a first side panel **21** foldably connected to the bottom panel **11** at a longitudinal fold line **23**, and a second side panel **25** foldably connected to the bottom panel at a longitudinal fold line **27**. In one embodiment, the blank **3** includes four panels (the two end panels **13**, **17** and the two side panels **21**, **25**) extending around a perimeter of the bottom panel **11** so that the four fold lines **15**, **19**, **23**, **27**, form a rectangular perimeter of the bottom panel **11**.

(18) As shown in FIG. 1, the first end panel **13** includes a lower portion **13a** foldably connected to an upper portion **13b** along a lateral fold line **29**, the second end panel **17** includes a lower portion **17a** foldably connected to an upper portion **17b** along a lateral fold line **31**, the first side panel **21** includes a lower portion **21a** foldably connected to an upper portion **21b** along a lateral fold line **33**, and the second side panel **25** includes a lower portion **25a** foldably connected to an upper portion **25b** along a lateral fold line **35**. In the illustrated embodiment, the lower portions **13a**, **17a**, **21a**, **25a** of the respective panels **13**, **17**, **21**, **25** are foldably connected to the bottom panel **11** along the respective fold lines **15**, **19**, **23**, **27**. In one embodiment, each of the lower portions **13a**, **17a** of the respective end panels **13**, **17** has two lower oblique edges **37a**, and each of the upper portions **13b**, **17b** of the respective end panels **13**, **17** has two upper oblique edges **37b**. Similarly, each of the lower portions **21a**, **25a** of the respective side panels **21**, **25** has two lower oblique edges **39a**, and each of the upper portions **21b**, **25b** of the respective side panels **21**, **25** has two upper oblique edges **39b**. In the illustrated embodiment, at each corner of the blank **3**, the adjacent lower oblique edges **37a**, **39a** of the respective end panels **13**, **17** and side panels **21**, **25** extend at a first angle **A1** with respect to one another and the adjacent upper oblique edges **37b**, **39b** of the respective end panels **13**, **17** and side panels **21**, **25** extend at a second angle **A2** with respect to one another. The angle **A1** can be smaller than the angle **A2** in one embodiment. In an exemplary embodiment, the first angle **A1** can be approximately 25 degrees and the second angle **A2** can be approximately 70 or 80 degrees. Alternatively, the angles **A1**, **A2** could be any suitable angle without departing from the disclosure.

(19) In the illustrated embodiment, each of the end panels **13**, **17** and side panels **21**, **25** includes a respective flange portion **45**, **47**, **49**, **51** at least partially defined by respective fold lines **61**, **63**, **65**,

67 extending in the respective panels. In one embodiment, adjacent flange portions 45, 47, 49, 51 are configured to at least partially overlap when the blank 3 is formed into the container 5. The blank 3 could be otherwise shaped, arranged, and/or configured without departing from the disclosure. In addition, any of the bottom panel 11, the end panels 13, 17, the side panels 21, 25, and/or the flange portions 45, 47, 49, 51 could be omitted or could be otherwise shaped, arranged, positioned, and/or configured without departing from the disclosure. For example, the blank 3 could have any suitable number of panels and any suitable shape for the perimeter around the bottom panel 11.

(20) As shown in FIGS. 2A and 2B, the container 5 can be formed from the blank 3 by folding the end panels 13, 17 and the side panels 21, 23 upwardly along the respective fold lines 15, 19, 23, 27 to form a sidewall 77 extending around the perimeter of the bottom panel 11. In one embodiment, the sidewall 77 extends obliquely upwardly and outwardly from the bottom panel 11 around the perimeter of the container 5. As shown in FIGS. 2A and 2B, the lower portions 13a, 17a, 21a, 25a of the respective panels 13, 17, 21, 25 form a lower portion 77a of the sidewall 77 and the upper portions 13b, 17b, 21b, 25b of the respective panels 13, 17, 21, 25 form an upper portion 77b of the sidewall 77, wherein the fold lines 29, 31, 33, 35 can cooperate to at least partially form an intermediate fold line 99 extending around the sidewall 77. In the illustrated embodiment, as the end panels 13, 17 and side panels 21, 23 are folded upwardly to form the sidewall 77, the adjacent lower oblique edges 37a, 39a and upper oblique edges 37b, 39b are brought together (e.g., to be in engagement, to abut, to be at least partially in contact, and/or to be slightly spaced apart) at each corner 90 of the container 5. As shown in FIGS. 1, 2A, and 2B, since the angle A1 is different (e.g., smaller) than the angle A2, the lower portion 77a and the upper portion 77b of the sidewall 77 extend at different angles with respect to the bottom panel 11 (FIG. 3A). For example, as shown in FIG. 3A, the lower portion 77a can extend outwardly and upwardly from the bottom panel 11 at an angle A3 that is obtuse (e.g., greater than 90 degrees and less than 180 degrees), and the upper portion 77b extends upwardly at an obtuse angle A4 from the lower portion 77a (e.g., closer to the vertical direction than the lower portion 77a or in the vertical direction). In an exemplary embodiment, the transitions from the bottom panel 11 to the lower portion 77a and from the lower portion 77a to the upper portion 77b can be at angles of greater than 90 degrees, which can help increase the contact between the liner 9 and the base 7 (e.g., increase the surface area of the liner 9 that engages the base 7).

(21) In the illustrated embodiment, the flange portions 45, 47, 49, 51 are folded along respective fold lines 61, 63, 65, 67 to extend outwardly from the respective end panels 13, 17 and side panels 21, 25 and are generally parallel to the bottom panel 11. As shown in FIGS. 2A and 2B, the flange portions 45, 47, 49, 51 form a flange 8 that extends outwardly from the sidewall 77 around the perimeter of the container 5. In one embodiment, the sidewall 77 can extend along substantially the entire perimeter of the bottom panel 11, and the flange 8 can extend along substantially the entire perimeter of the sidewall 77. As shown in FIGS. 2A and 2B, the sidewall 77 and the bottom panel 11 define an interior 79 of the container 5 and have an inner surface 92 extending along the interior 79. The flange 8, the sidewall 77, and/or the bottom panel 11 could be omitted or could be otherwise shaped, arranged, positioned, and/or configured without departing from the disclosure. Also, the container 5 can have one or more injection-molded features that can reinforce the flange 8 and/or other portions of the container without departing from the disclosure.

(22) In the illustrated embodiment, the container 5 further includes the liner 9 attached to the inner surface 81 of the base layer 7 formed from the blank 3. As shown in FIGS. 3A and 3B, the liner 9 can be attached to the base layer 7 by the heat seal layer 10 (e.g., for a PET liner). Alternatively, the heat seal layer 10 could be applied to the base layer 7, without departing from the disclosure. Alternatively, the heat seal layer 10 could be omitted (e.g., for a polyethylene liner). The liner 9 can extend over the bottom panel 11, the sidewall 77, and the flange 8. In one embodiment, as shown in FIGS. 2A, 2B, and 3A, the liner 9 can extend beyond the flange 8 (e.g., so that an edge 84 of the



liner **9** is outwardly spaced from an edge **86** of the flange **8**). As shown in FIGS. 2A, 2B, and 3A, the edge **84** of the liner **9** can extend around an outer perimeter of the container **5**. Alternatively, the edge **84** of the liner **9** could be aligned with the edge **86** of the flange **8** and/or could be spaced inwardly from the edge **86** (e.g., so that the edge **86** of the flange **8** extends around a perimeter of the container **5**). In the illustrated embodiment, the liner **9** can be attached to at least a portion of each of the bottom panel **11**, the end panels **13**, **17**, the side panels **21**, **25**, and the flange portions **45**, **47**, **49**, **51**. In one embodiment, the liner **9** can at least partially retain the base layer **7** in the shape of the sidewall **77** and the container **5** in general (e.g., can help prevent the end panels **13**, **17** and the side panels **21**, **25** from separating from one another). As shown in FIGS. 3A and 3B, the thicknesses of the liner **9** and the heat seal layer **10** are exaggerated in order to illustrate the configuration of the liner **9** and the heat seal layer **10** in the container **5**. The container **5**, including the liner **9**, the heat seal layer **10**, and/or the base layer **7**, could be otherwise shaped, arranged, positioned, and/or configured without departing from the disclosure.

(23) FIG. 4 shows one embodiment of a system **101** and method for forming the container **5** that has the base layer **7** formed from the blank **3** and the inner layer **9** attached to the base layer **7**. As shown in FIG. 4, the system includes a stack **110** of blanks **3** that are conveyed by a conveyor **103** to a container forming mechanism **120**. In one embodiment, the container forming mechanism **120** can be any suitable mechanism or forming tool that can fold and/or press-form the blank **3** into the container **5**, which can be similar to and have similar features and/or components as conventional forming tools such as are disclosed in U.S. Pat. No. 8,534,460, issued Sep. 17, 2013, the entire contents of which are incorporated herein by reference for all purposes. Also, the forming tool can have similar features and components such as the forming tool disclosed in U.S. Pat. No. 8,801,995, issued Aug. 12, 2014, the entire contents of which are incorporated by reference for all purposes, or any other suitable forming tool assembly. The mechanism **120** folds the end panels **13**, **17** and side panels **21**, **25** relative to the bottom panel **11** to form an unlined initial construct **130** that comprises the base layer **7** only. The initial construct **130** can be fed to a lower die **140** by a conveyor **105** and a PET plastic film sheet **150** can be fed from a supply roller **151** above the initial construct **130**, the film sheet **150** having a thickness between approximately 30 and 150 microns in one exemplary embodiment. In one exemplary embodiment, the film sheet **150** can be a PET film having a thickness of approximately 50 microns. Alternatively, the film sheet **150** could have any suitable thickness. In the illustrated embodiment, a plurality of liners **9** can be formed from (e.g., cut from) the film sheet **150**.

(24) In the illustrated embodiment, the roll of the sheet **150** can be supplied with the heat seal layer **10** previously applied, and the sheet **150** can be unrolled from the supply roller **151** so that the heat seal layer **10** is on the underside of the sheet **150**, facing the initial construct **130**. In another embodiment, the heat seal layer **10** can be applied to the sheet **150** after it is unrolled from the supply roller **151** (e.g., by a spray applicator or a roller, not shown). Alternatively, the heat seal layer **10** could be omitted (e.g., for a sheet **150** of polyethylene or other suitable material) or the heat seal layer could be pre-applied as a coating to the blanks **3**.

(25) In one embodiment, the film sheet **150** could have perforations or other features (not shown) to help separate the liner **9** from the remainder of the sheet **150** when forming the container **5**. An upper die **160** has a heater plate surface **164** having a PTFE coating, for example a Teflon® coating. Alternatively, the heater plate surface **164** could have a coating of any suitable material or the coating could be omitted. As schematically shown in FIG. 4, the upper die **160** can include a plurality of holes or ducts **162** in the heater plate surface **164** for applying a vacuum and/or air pressure on the sheet **150**. The ducts **162** can each have a cross-sectional dimension (e.g., a diameter) of approximately 0.2 millimeter and can be grouped in clusters on the heater plate surface **164** (e.g., clusters of three ducts **164**) that can be spaced on the heater plate. In another embodiment, the ducts **162** can be evenly spaced from one another and/or can have a cross-sectional dimension of approximately 1 millimeter. These exemplary configurations of the ducts

**162** can help appropriately (e.g., evenly) apply heat and air pressure/vacuum to the sheet **150** and the heat seal layer **10** for forming the sheet **150** and heat seal layer **10** to the initial construct **140** and adhering the same to the initial construct **140**. The lower die **140** and/or the upper die **160**, including the ducts **162** and/or the heater plate **164**, could be otherwise shaped, arranged, positioned, and/or configured without departing from the disclosure. For example, the heater plate **164** could be omitted and the heat could be alternatively applied to the sheet **150** (e.g., with a flow of hot air).

(26) In the illustrated embodiment, the lower die **140** can hold the construct **130** in its erected shape (schematically shown in FIGS. **4** and **5**) as the liner **9** is applied to the base layer and can be raised in the direction of arrow **B** toward the upper die **160** by means of a pneumatic ram **142**, and an initial vacuum is applied to ducts **162** to draw the film sheet **150** with the heat seal layer **10** toward the upper die **160**. In the illustrated embodiment, the upper die **160** is heated to a suitable temperature (e.g., approximately 110 to 200 degrees Celsius or any other suitable temperature) so that the film sheet **150** and the heat seal layer **10** soften and form a domed shape (not shown) under the influence of the initial vacuum. In one embodiment, the film can at least partially conform to the concave heater plate surface **164** to form the domed shape. Instead of, or in addition to, the initial vacuum, air pressure under the film sheet **150** can be employed with similar or equal effect.

(27) In the illustrated embodiment, as the film sheet **150** and the heat seal layer **10** are domed, the heat seal layer **10** is activated for attaching or bonding or adhering the sheet **150** to the initial construct **130** (e.g., its temperature increases such that it becomes tacky). Subsequently, film sheet **150** can be forced against the inner surface **81** of the recess **79** of the initial construct **130** with the tacky heat seal layer **10** therebetween. In one embodiment, the sheet **150** can be forced downwardly by means of air pressure either now applied to the ducts **162** and/or by means of a further vacuum applied from the bottom side of the film sheet **150**. For example, a vacuum can be applied via the lower die **140** and through the initial construct **130**, which can help hold the initial construct **130** in the cavity of the lower die **140** during application of the sheet **150** and the heat seal layer **10**. In one embodiment, at least some of the fold lines **15**, **19**, **23**, **27**, **29**, **31**, **33**, **35** can be at least partially formed by spaced cuts in the blank **3** (e.g., cut-crease style fold lines), and the vacuum can be applied to the sheet **150** through the cuts of the fold lines **15**, **19**, **23**, **27**, **29**, **31**, **33**, **35**.

Alternatively, other apertures (not shown) can be provided in the initial construct **130** for allowing vacuum pressure to pass through the initial construct **130**.

(28) In one embodiment, the air pressure and/or vacuum causes the dome shape of the film sheet **150** to invert, and the now tacky and stretched heat seal layer **10** can adhere smoothly to the inner surface **81** of the initial construct **130** supported on the lower die **140**. In one embodiment, the tackiness of the heat seal layer **10** can cause the portion of the film sheet **150** that forms the liner **9** to adhere to the base layer **7**. The PTFE coated surface **164** can aid in the release of the liner material portion (e.g., the liner **9**) of the film sheet **150** should the film sheet **150** make contact with the surface **164**. In an embodiment where the heat seal layer **10** is omitted (e.g., for a polyethylene liner material), the liner material itself can become tacky due to the heating by the upper die **160** and the tackiness of the liner material can adhere the liner material to the interior surface **81** of the initial construct **130**. In the illustrated embodiment, the excess or waste portion of the film sheet **150** is cut from the edges of the container **5** (which now includes the base layer **7** formed from the construct **130** and the liner **9** formed from the film sheet **150** with the heat seal layer **10** therebetween as shown in FIG. **3B**) (e.g., by a cutting apparatus, not shown) to leave an unused film portion **152** with tray sized apertures. In one embodiment, the unused film portion **152** has marginal portions that remain intact around the apertures formed by the removal of the inner layer **9** from the film **150** so that the unused film portion **152** can continue to the take-up reel **153**. Alternatively, or in addition, the film sheet **150** can have a sacrificial carrier layer (not shown) wherein the liner material separates from the carrier sheet when it is attached to the base layer **7**. In another alternative, the unused film portion **152** can be in the form of scraps that are removed by

air pressure and/or vacuum pressure, for example.

(29) In the illustrated embodiment, the lower die **140** is lowered by reversing the direction of the ram **142**, and a product support plate **144** can force the lined container **5** from the supporting lower die **140** as the ram **142** is lowered in order to eject the container **5** from the lower die **140**. In one embodiment, the product support plate **144** can include upward extensions **146** that extend through the lower die **140** and engage the bottom of the container **5** due to the relative motion of the product support plate **144** and the lower die **140** toward one another. In the illustrated embodiment, the upward extensions **146** can position the container **5** relative to the lower die **140** so that a pusher rod, a puff of air, or other suitable mechanism can urge the container **5** onto a downstream conveyor **107**. The lined container **5** then can be conveyed for packaging and/or further processing by the conveyor **107**.

(30) In one embodiment, the above mentioned process can be repeated to allow substantially continuous production of the lined containers **5**. Since the above mentioned process can be employed in a variety of products and using different materials, it may be necessary to repeat the steps of heating the film and it may be necessary to then further force the film against the tray with air pressure, a vacuum, and/or another suitable mechanism. In particular, where thicker sheets of lining film are used for the inner layer **9** and various thicknesses of paperboard or other materials are used for the base layer **7**, one or more repeats of the heating and forcing steps may be required in order for the film **9** to adhere to the base layer **7** tray effectively.

(31) The system **101** and method described herein can include other features, steps, and/or the features and steps described herein can be omitted or modified without departing from the scope of the disclosure. For example, instead of or in addition to the heater plate **164**, heat can be applied to the film sheet **150** in any suitable manner (e.g., by a flow of hot air). In another example, the film sheet **150** can be heated to activate (e.g., soften) the heat seal layer **10** without softening and/or deforming the remainder of the film sheet **150**.

(32) In the illustrated embodiment, the shape of the initial construct **130** can help increase the contact between the liner **9** and the heat seal layer **10** with the base layer **7**. For example, since the angles between the bottom panel **11** and the lower portion **77a** of the sidewall **77** and between the lower portion **77a** and the upper portion **77b** of the sidewall **77** can be greater than 90 degrees, the initial construct **130** can have fewer tight corners. In an exemplary embodiment, it can be difficult to force the sheet **150** into tighter corners (e.g., corners that are about 90 degrees or less).

Accordingly, the shape of the sidewall **77** can help the entire liner **9** or substantially the entire liner **9** contact and be adhered to the base layer **7** including in all or substantially all of the corners of the initial construct **130**.

(33) The manufacturing process described above produces a readily sealable tray which is made mainly from readily recyclable materials (e.g. paperboard or cardboard and thermoplastic materials). If required, the paperboard base layer is readily removable from the thermoplastic film liner (e.g., after use of the container to hold a food product during heating in a microwave oven and/or in a conventional oven) because the degree of adherence between the base layer **7** and the liner **9** is controllable to give sufficient adherence so that the liner and the base layer remain attached before, during, and/or after heating of an item held in the container while allowing selective separation of the base layer and the liner after use. Using the parameters mentioned above, it has been found that the base layer **7** and the liner **9** of the container **5** are separable following heating of food in the container, such that the two peel apart, leaving no more than 5% of the thickness of the material of the base layer **7** stuck to the film of the inner layer **9** in one exemplary embodiment. The separated paperboard of the base layer **7** and the thermoplastic film of the inner layer **9** can be more easily recycled in separate waste streams (e.g., one for paper products and one for polymers) while minimizing the contamination of the material of the inner layer **9** with paperboard.

(34) Advantageously, the use of the heater plate **164** to heat the film sheet **150** and the heat seal

layer **10** prior to its application onto the initial construct **130** provides control of the temperature of the film sheet **150** and the heat seal layer **10** and thus the strength of its adherence to the initial construct **130**. The use of the heater plate **164** also allows differential heating, so, for example, the film sheet **150** and the heat seal layer **10** could be heated to a higher temperature in the flange area **8** of the container **5**, which in turn causes the liner **9** formed from the film sheet **150** to adhere more strongly to the flange **8** than to the remainder of the container **5** so that a further tray-sealing film applied to the liner **9** in the area of the flange has a more secure anchor to the container **5**. In one embodiment, no injection molding features are used for the container **5** and a thinner plastic film can be employed, which can reduce the non-recyclable material content of the tray.

(35) A PET plastics film **150** has been described above, although it will be understood that other plastics films could be used, for example other polyester based polymers could be used. Also a polyethylene film could be used and is favored for food packaging that is not heated (e.g., sandwich packs). It can be seen that the disclosure provides in one embodiment food packaging having a composite construction of a plastics inner food-contacting layer **9**, bonded to an outer recyclable layer **7**, the inner and outer layers being separable after use, such that no more than 5% of the thickness of the outer layer is disposed on the inner layer after separation.

(36) In one embodiment, a lid (not shown) can comprise packaging film that is a thin plastic layer used to preserve and protect a food item contained in the tray and can be removably attached to the flange **8** of the container **5**. Any plastic film, such as polyethylene, polypropylene, polyethylene terephthalate, polyvinylchloride, polyamide, and ethylene vinyl alcohol, or other suitable material, can be used for forming the lid that is sealed against the sealing surface of the flange **8**. Further, adhesives can be used between the lid and the sealing surface of the flange **8** without departing from the disclosure.

(37) FIG. **6** is a plan view of a blank **203** for forming a container **205** (FIG. **7**) of a second embodiment of the disclosure. The second embodiment is generally similar to the first embodiment, except for variations noted and variations that will be apparent to one of ordinary skill in the art. Accordingly, similar or identical features of the embodiments have been given like or similar reference numbers. As shown in FIG. **6**, the blank **203** is similar to the blank **3** of the first embodiment except that the blank **203** includes corner panels **251**, **253**, **255**, **257** respectively foldably connected to the bottom panel **11** at respective oblique fold lines **252**, **254**, **256**, **258**. As shown in FIG. **6**, the corner panels **251**, **253**, **255**, **257** are disposed between respective adjacent end panels **13**, **17** and side panels **21**, **25**. In one embodiment, the blank **203** includes eight panels (the two end panels **13**, **17**, the two side panels **21**, **25**, and the four corner panels **251**, **253**, **255**, **257**) extending around a perimeter of the bottom panel **11** so that the eight fold lines **15**, **17**, **23**, **27**, **252**, **254**, **256**, **258** form an octagonal perimeter of the bottom panel **11**. As shown in FIG. **6**, each of the fold lines **15**, **17**, **23**, **27**, **252**, **254**, **256**, **258** can be oblique with respect to its respectively adjacent fold lines and can form an obtuse angle with each of its respectively adjacent fold lines.

(38) As shown in FIG. **6**, each of the corner panels **251**, **253**, **255**, **257** can include a respective intermediate fold line **269**, **270**, **271**, **272** so that each of the corner panels includes a lower portion **251a**, **253a**, **255a**, **257a** foldably connected to a respective upper portion **251b**, **253b**, **255b**, **257b** along the respective fold line **269**, **270**, **271**, **272**. Accordingly, in one embodiment, the lower portions **251a**, **253a**, **255a**, **257a** of the corner panels **251**, **253**, **255**, **257** can cooperate with the lower portions **13a**, **17a** of the end panels **13**, **17** and the lower portions **21a**, **25a** of the side panels **21**, **25** to form the lower portion **277a** of the sidewall **277**, and the upper portions **251b**, **253b**, **255b**, **257b** of the corner panels **251**, **253**, **255**, **257** can cooperate with the upper portions **13b**, **17b** of the end panels **13**, **15** and the upper portions **21b**, **25b** of the side panels **21**, **25** to form the upper portion **277b** of the sidewall **277** (FIG. **7**). In the illustrated embodiment, flange portions **273**, **274**, **275**, **276** can be foldably connected to the respective corner panels **251**, **253**, **255**, **257** along respective fold lines **278**, **280**, **282**, **283** and can cooperate with the flange portions **45**, **47**, **49**, **51** to form the flange **208**. In one embodiment, the blank **203** can be similar to the blank of the second

embodiment as shown and described in the incorporated-by-reference U.S. patent application Ser. No. 15/654,814, filed Jul. 20, 2017. The blank **203** could be otherwise shaped, arranged, and/or configured without departing from the disclosure.

(39) In the illustrated embodiment, the container **205** can be formed from the blank **203** and the liner material (e.g., of the film sheet **150**) in a similar or identical manner as described above with respect to the first embodiment. Accordingly, the container **205** can include the base layer **207** formed from the blank **203** and the liner **209** formed from the film sheet **150**. In one embodiment, the liner **209** can be attached to the base layer **207** with a heat seal layer **210** (FIG. **8**) similarly to the first embodiment described above. As shown in FIG. **7**, each of the corner flange portions **273**, **274**, **275**, **276** can overlap a portion of the respectively adjacent flange portions of the end panels and side panels to form the flange **208**.

(40) As shown in FIG. **7**, the lateral fold lines **229**, **231**, the longitudinal fold lines **233**, **235**, and the oblique fold lines **269**, **270**, **271**, **272** can cooperate to form an intermediate fold line **299** extending around the sidewall **277**. In addition, the lower portion **277a** and the upper portion **277b** of the sidewall **277** each can extend from the intermediate fold line **299**, wherein the portions of the sidewall **277** are oblique with respect to one another. In one embodiment, the upper and lower portions of the sidewall **277** can cooperate to form an obtuse angle, and the lower portion **277a** of the sidewall **277** can form an obtuse angle with the bottom panel **11**. The obtuse angles in the sidewall **277** can allow the base layer **207** to conform with the liner **209** more completely, which can increase the contact between the surfaces of the base layer **207** and the liner **209** (e.g., at the transitions between the panels of the container **205**).

(41) In one embodiment, the container **205**, with the corner panels **251**, **253**, **255**, **257** that extend obliquely between adjacent end panels **13**, **17** and side panels **21**, **25**, generally includes only obtuse angles between the panels and lacks orthogonal angles. This can help enable the liner material that forms the liner **9** to come into contact with more of the surface area of the base layer (e.g., relative to a base layer with right or acute angles, wherein it can be more difficult for the liner material to extend into such corners). Accordingly, the octagonal shape of the sidewall **277** can help the liner **9** to adhere to the entire surface or to substantially the entire surface of the base layer of the container. In one embodiment, the octagonal shape of the sidewall **277** can more closely approximate a rounded or circular sidewall than a container with four orthogonal sides. The container **205** could be otherwise shaped, arranged, and/or configured without departing from the disclosure.

(42) FIG. **9** is a plan view of a blank **303** for forming a container **305** (FIG. **10**) of a third embodiment of the disclosure. The third embodiment is generally similar to the prior embodiments, except for variations noted and variations that will be apparent to one of ordinary skill in the art. Accordingly, similar or identical features of the embodiments have been given like or similar reference numbers. As shown in FIG. **9**, the blank **303** is similar to the blank **3** of FIG. **1** of the first embodiment except that the blank **303** includes two sections **304a**, **304b** for forming two respective compartments **306a**, **306b** in the container **305** (FIG. **10**). In one embodiment, each of the sections **304a**, **304b** is similar to the blank **3** of the first embodiment. The first section **304a** includes a bottom panel **311** foldably connected to end panels **313**, **317** along respective fold lines **315**, **319** and to side panels **321**, **325** along respective fold lines **323**, **327**. Each of the end panels **313**, **317** can have a lower portion **313a**, **317a** foldably connected to a respective upper portion **313b**, **317b** along respective fold lines **329**, **331**, and each of the side panels **321**, **325** can include a lower portion **321a**, **325a** foldably connected to respective upper portions **321b**, **325b** along respective fold lines **333**, **335**. Flange portions **345**, **347**, **351** are foldably connected to the respective panels **313**, **317**, **325** along respective fold lines **361**, **363**, **367** in the first section **304a**. The first section could be otherwise shaped, arranged, and/or configured without departing from the disclosure.

(43) As shown in FIG. **9**, the second section **304b** can be similarly configured to the first section **304a** with a bottom panel **312** foldably connected to end panels **314**, **318** along respective fold lines

**316, 320** and to side panels **322, 326** along respective fold lines **324, 328**. Each of the end panels **314, 318** can have a lower portion **314a, 318a** foldably connected to a respective upper portion **314b, 318b** along respective fold lines **330, 332**, and each of the side panels **322, 326** can include a lower portion **322a, 326a** foldably connected to respective upper portions **322b, 326b** along respective fold lines **334, 336**. Flange portions **346, 348, 352** are foldably connected to the respective panels **314, 318, 326** along respective fold lines **362, 364, 368** in the second section **304b**. The second section could be otherwise shaped, arranged, and/or configured without departing from the disclosure.

(44) In the illustrated embodiment, the first section **304a** and the second section **304b** can be connected by a shared central flange portion **349** foldably connected to the side panel **321** of the first section **304a** and the side panel **322** of the second section **304b** along respective fold lines **365, 366**. As shown in FIG. 9, the flange portions **345, 346, 347, 348** can have inner square ends where the flange portions **345, 346** and **347, 348** overlap when the flange **308** is formed (FIG. 10). In one embodiment, the adjacent lower edges **37a, 39a** at each of the eight corners of the blank **303** can extend at an angle **A1** with respect to one another and each of the upper edges **37b, 39b** can extend at an angle **A5** with respect to the respective fold line **361, 362, 363, 364, 365, 366, 367, 368**. In one example, the angle **A1** can be approximately 25 degrees and the angle **A5** can be approximately 80 degrees (and the adjacent upper edges **37b, 39b** can extend at an angle of approximately 70 degrees with respect to one another). The blank **303** could be otherwise shaped, arranged, and/or configured without departing from the disclosure. For example, the sections **304a, 304b** could be connected at different panels (e.g., at end panels) and/or the central flange portion **349** could be omitted so that the connected panels are connected along a fold line.

(45) In the illustrated embodiment, the container **305** (e.g., dual-compartment container) can be formed from the blank **303** and the liner material (e.g., of the film sheet **150**) in a similar or identical manner as described above with respect to the first embodiment. Accordingly, the container **305** can include the base layer **307** formed from the blank **303** and the liner **309** formed from the film sheet **150**. In one embodiment, the liner **309** can be attached to the base layer **307** with a heat seal layer **310** (FIG. 11) as described above. As shown in FIG. 10, each section **304a, 304b** of the blank **303** is formed into a respective compartment **306a, 306b** of the container **305**, wherein the end panels **313, 317** and the side panels **321, 325** of the first section **304a** are folded with respect to the bottom panel **311** to form a first sidewall **377** of the first compartment **306a** and the end panels **314, 318** and the side panels **322, 326** of the second section **304b** are folded with respect to the bottom panel **312** to form a second sidewall **378** of the second compartment **306b**. As shown in FIG. 10, the sidewalls **377, 378** can include the respective side panels **321, 322** extending between the compartments **306a, 306b**, connected at the central flange portion **349**, which cooperates with the flange portions **345, 346, 347, 348, 352, 352** to form the flange **308** of the container **305**. In one embodiment, the side panels **321, 322** and the central flange portion **349** can form a divider wall **398** that at least partially divides the container **305** into the compartments **306a, 306b**. In the illustrated embodiment, the sidewall **377** can extend along a perimeter of the bottom panel **311**, and the sidewall **377** and the bottom panel **311** can extend along an interior **379** of the first compartment **306a**. Similarly, the sidewall **378** can extend along a perimeter of the bottom panel **312**, and the sidewall **378** and the bottom panel **312** can extend along an interior **380** of the second compartment **306b**. As shown in FIG. 10, the liner **309** can extend beyond the edge **386** of the base material **307** so that the edge **384** of the liner **309** is spaced apart from the edge **386** of the base material **307**.

(46) As shown in FIG. 10, the fold lines **329, 331, 333, 335** and the fold lines **330, 332, 334, 336** can cooperate to form respective intermediate fold lines **399** extending around the respective sidewalls **377, 378**. Accordingly, the lower portion **377a** and the upper portion **377b** of the first sidewall **377** each can extend from the intermediate fold line **399** in the first compartment **306a**, wherein the portions of the sidewall **377** are oblique with respect to one another. In one

embodiment, the upper and lower portions of the sidewall **377** can cooperate to form an obtuse angle, and the lower portion **377a** of the sidewall **377** can form an obtuse angle with the bottom panel **311** in the first compartment **306a**. Similarly, the lower portion **378a** and the upper portion **378b** of the second sidewall **378** each can extend from the intermediate fold line **399** in the second compartment **306b**, wherein the portions of the sidewall **378** are oblique with respect to one another. In one embodiment, the upper and lower portions of the sidewall **378** can cooperate to form an obtuse angle, and the lower portion **378a** of the sidewall **378** can form an obtuse angle with the bottom panel **312** in the second compartment **306b**. The obtuse angles in the sidewalls **377**, **378** can allow the base layer **307** to conform with the liner **309** more completely, which can increase the contact between the surfaces of the base layer **307** and the liner **309** (e.g., at the transitions between the panels of the container **305**) in both compartments **306a**, **306b**.

(47) The container **305** could be otherwise shaped, arranged, and/or configured without departing from the disclosure. For example, one or both of the compartments **306a**, **306b** could include one or more corner panels similar or identical to the corner panels shown and described in the second embodiment of the disclosure.

(48) Any of the features of the various embodiments of the disclosure can be combined with, replaced by, or otherwise configured with other features of other embodiments of the disclosure without departing from the scope of this disclosure.

(49) Optionally, one or more portions of the blank or other constructs described herein or contemplated hereby may be coated with varnish, clay, or other materials, either alone or in combination. The coating may then be printed over with product advertising or other information or images. The blanks or other constructs also may be selectively coated and/or printed so that less than the entire surface area of the blank or substantially the entire surface area of the blank may be coated and/or printed.

(50) Any of the blanks, containers, or other constructs of this disclosure may optionally include one or more features that alter the effect of microwave energy during the heating or cooking of a food item that is associated with the tray or other construct. For example, the blank, tray, container, or other construct may be formed at least partially from one or more microwave energy interactive elements (hereinafter sometimes referred to as “microwave interactive elements”) that promote heating, browning and/or crisping of a particular area of the food item, shield a particular area of the food item from microwave energy to prevent overcooking thereof, or transmit microwave energy towards or away from a particular area of the food item. Each microwave interactive element comprises one or more microwave energy interactive materials or segments arranged in a particular configuration to absorb microwave energy, transmit microwave energy, reflect microwave energy, or direct microwave energy, as needed or desired for a particular construct and food item.

(51) In the case of a susceptor or shield, the microwave energy interactive material may comprise an electroconductive or semiconductive material, for example, a vacuum deposited metal or metal alloy, or a metallic ink, an organic ink, an inorganic ink, a metallic paste, an organic paste, an inorganic paste, or any combination thereof. Examples of metals and metal alloys that may be suitable include, but are not limited to, aluminum, chromium, copper, inconel alloys (nickel-chromium-molybdenum alloy with niobium), iron, magnesium, nickel, stainless steel, tin, titanium, tungsten, and any combination or alloy thereof.

(52) Alternatively, the microwave energy interactive material may comprise a metal oxide, for example, oxides of aluminum, iron, and tin, optionally used in conjunction with an electrically conductive material. Another metal oxide that may be suitable is indium tin oxide (ITO). ITO has a more uniform crystal structure and, therefore, is clear at most coating thicknesses.

(53) Alternatively still, the microwave energy interactive material may comprise a suitable electroconductive, semiconductive, or non-conductive artificial dielectric or ferroelectric. Artificial dielectrics comprise conductive, subdivided material in a polymeric or other suitable matrix or

binder, and may include flakes of an electroconductive metal, for example, aluminum.

(54) In other embodiments, the microwave energy interactive material may be carbon-based, for example, as disclosed in U.S. Pat. Nos. 4,943,456, 5,002,826, 5,118,747, and 5,410,135.

(55) In still other embodiments, the microwave energy interactive material may interact with the magnetic portion of the electromagnetic energy in the microwave oven. Correctly chosen materials of this type can self-limit based on the loss of interaction when the Curie temperature of the material is reached. An example of such an interactive coating is described in U.S. Pat. No. 4,283,427.

(56) The use of other microwave energy interactive elements is also contemplated. In one example, the microwave energy interactive element may comprise a foil or high optical density evaporated material having a thickness sufficient to reflect a substantial portion of impinging microwave energy. Such elements typically are formed from a conductive, reflective metal or metal alloy, for example, aluminum, copper, or stainless steel, in the form of a solid "patch" generally having a thickness of from about 0.000285 inches to about 0.005 inches, for example, from about 0.0003 inches to about 0.003 inches. Other such elements may have a thickness of from about 0.00035 inches to about 0.002 inches, for example, 0.0016 inches.

(57) In some cases, microwave energy reflecting (or reflective) elements may be used as shielding elements where the food item is prone to scorching or drying out during heating. In other cases, smaller microwave energy reflecting elements may be used to diffuse or lessen the intensity of microwave energy. One example of a material utilizing such microwave energy reflecting elements is commercially available from Graphic Packaging International, Inc. (Atlanta, GA) under the trade name MicroRite® packaging material. In other examples, a plurality of microwave energy reflecting elements may be arranged to form a microwave energy distributing element to direct microwave energy to specific areas of the food item. If desired, the loops may be of a length that causes microwave energy to resonate, thereby enhancing the distribution effect. Microwave energy distributing elements are described in U.S. Pat. Nos. 6,204,492, 6,433,322, 6,552,315, and 6,677,563, each of which is incorporated by reference in its entirety.

(58) If desired, any of the numerous microwave energy interactive elements described herein or contemplated hereby may be substantially continuous, that is, without substantial breaks or interruptions, or may be discontinuous, for example, by including one or more breaks or apertures that transmit microwave energy. The breaks or apertures may extend through the entire structure, or only through one or more layers. The number, shape, size, and positioning of such breaks or apertures may vary for a particular application depending on the type of construct being formed, the food item to be heated therein or thereon, the desired degree of heating, browning, and/or crisping, whether direct exposure to microwave energy is needed or desired to attain uniform heating of the food item, the need for regulating the change in temperature of the food item through direct heating, and whether and to what extent there is a need for venting.

(59) By way of illustration, a microwave energy interactive element may include one or more transparent areas to effect dielectric heating of the food item. However, where the microwave energy interactive element comprises a susceptor, such apertures decrease the total microwave energy interactive area, and therefore, decrease the amount of microwave energy interactive material available for heating, browning, and/or crisping the surface of the food item. Thus, the relative amounts of microwave energy interactive areas and microwave energy transparent areas may be balanced to attain the desired overall heating characteristics for the particular food item.

(60) As another example, one or more portions of a susceptor may be designed to be microwave energy inactive to ensure that the microwave energy is focused efficiently on the areas to be heated, browned, and/or crisped, rather than being lost to portions of the food item not intended to be browned and/or crisped or to the heating environment. Additionally or alternatively, it may be beneficial to create one or more discontinuities or inactive regions to prevent overheating or charring of the food item and/or the construct including the susceptor.



(61) As still another example, a susceptor may incorporate one or more “fuse” elements that limit the propagation of cracks in the susceptor, and thereby control overheating, in areas of the susceptor where heat transfer to the food is low and the susceptor might tend to become too hot. The size and shape of the fuses may be varied as needed. Examples of susceptors including such fuses are provided, for example, in U.S. Pat. Nos. 5,412,187, 5,530,231, U.S. Patent Application Publication No. US 2008/0035634A1, published Feb. 14, 2008, and PCT Application Publication No. WO 2007/127371, published Nov. 8, 2007, each of which is incorporated by reference herein in its entirety.

(62) All dimensional information presented herein is intended to be illustrative of certain aspects, features, etc., of various embodiments of the disclosure, and is not intended to limit the scope of the disclosure. The dimensions of the blanks, containers, forming tools, features, or any other dimension, can be more or less than what is shown and described in this disclosure without departing from the scope of this disclosure and can be within the listed ranges of dimensions for each feature or outside the listed ranges of dimensions for each feature without departing from the scope of this disclosure.

(63) The blanks according to the present invention can be, for example, formed from coated paperboard and similar materials. For example, the interior and/or exterior sides of the blanks can be coated with a clay coating. The clay coating may then be printed over with product, advertising, price coding, and other information or images. The blanks may then be coated with a varnish to protect any information printed on the blanks. The blanks may also be coated with, for example, a moisture barrier layer, on either or both sides of the blanks.

(64) In accordance with the exemplary embodiments, the blanks may be constructed of paperboard of a caliper such that it is heavier and more rigid than ordinary paper. The blanks can also be constructed of other materials, such as cardboard, hard paper, or any other material having properties suitable for enabling the carton package to function at least generally as described above.

(65) The foregoing description illustrates and describes various embodiments of the present disclosure. As various changes could be made in the above construction without departing from the scope of the disclosure, it is intended that all matter contained in the above description or shown in the accompanying drawings shall be interpreted as illustrative and not in a limiting sense.

Furthermore, the scope of the present disclosure covers various modifications, combinations, and alterations, etc., of the above-described embodiments. Additionally, the disclosure shows and describes only selected embodiments, but various other combinations, modifications, and environments are contemplated and are within the scope of the inventive concept as expressed herein, commensurate with the above teachings, and/or within the skill or knowledge of the relevant art. Furthermore, certain features and characteristics of each embodiment may be selectively interchanged and applied to other illustrated and non-illustrated embodiments without departing from the scope of the disclosure.

## Claims

1. A container for heating a food product, the container comprising: a base layer of material; a liner releasably attached to an inner surface of the base layer, wherein the liner is at least partially attached to the base layer by a heat seal layer, and the liner is separable from the base layer after heating the container; a bottom panel; and a sidewall extending along the bottom panel, the sidewall comprises a lower portion extending upwardly and outwardly from the bottom panel and an upper portion extending from the lower portion, wherein the lower portion and the upper portion of the sidewall are foldably connected along an intermediate fold line, the lower portion is oblique with respect to the bottom panel, the upper portion is oblique with respect to the lower portion, and the upper portion extends at an obtuse angle from the lower portion along the inner surface; and a flange extending outwardly from the sidewall; the sidewall comprising at least an end panel

foldably connected to the bottom panel and a side panel foldably connected to the bottom panel, wherein the end panel comprises a first lower edge extending along the lower portion of the sidewall from the bottom panel to the intermediate fold line and a first upper edge extending along the upper portion of the sidewall from the intermediate fold line to the flange, the side panel comprises a second lower edge extending along the lower portion of the sidewall from the bottom panel to the intermediate fold line and a second upper edge extending along the upper portion of the sidewall from the intermediate fold line to the flange, the first lower edge and the first upper edge abutting the respective second lower edge and second upper edge at a corner of the container.

2. The container of claim 1, wherein the liner comprises polyethylene terephthalate and the heat seal layer comprises polyester.

3. The container of claim 2, wherein the heat seal layer comprises a sealant grade transparent polyester packaging film.

4. The container of claim 1, wherein the sidewall extends upwardly from the bottom panel along a perimeter of the bottom panel.

5. The container of claim 1, wherein the obtuse angle is a second obtuse angle, and the lower portion extends at a first obtuse angle with respect to the bottom panel.

6. The container of claim 1, wherein the liner is releasably attached to the base layer along at least a portion of each of the bottom panel and the lower portion and upper portion of the sidewall.

7. The container of claim 1, wherein the lower portion extends along a perimeter of the bottom panel.

8. A container for heating a food product, the container comprising a base layer of material and a liner releasably attached to an inner surface of the base layer, wherein the liner is separable from the base layer after heating the container; a bottom panel; and a sidewall comprising at least an end panel foldably connected to the bottom panel and a side panel foldably connected to the bottom panel, wherein each of the end panel and the side panel extends along a corner of the container; and a flange extending outwardly from the sidewall; the sidewall comprising a lower portion extending along the bottom panel and an upper portion extending upwardly from the lower portion along an intermediate fold line, wherein the lower portion is oblique with respect to the bottom panel, the upper portion is oblique with respect to the lower portion, and the upper portion extends at an obtuse angle from the lower portion along the inner surface; wherein the end panel comprises a first lower edge extending along the lower portion of the sidewall from the bottom panel to the intermediate fold line and a first upper edge extending along the upper portion of the sidewall from the intermediate fold line to the flange, the side panel comprises a second lower edge extending along the lower portion of the sidewall from the bottom panel to the intermediate fold line and a second upper edge extending along the upper portion of the sidewall from the intermediate fold line to the flange, the first lower edge and the first upper edge abutting the respective second lower edge and second upper edge at the corner of the container.

9. The container of claim 8, wherein the lower portion extends upwardly and outwardly from the bottom panel.

10. The container of claim 9, wherein the obtuse angle is a second obtuse angle, and the lower portion extends at a first obtuse angle with respect to the bottom panel.

11. The container of claim 10, wherein the liner is releasably attached to the base layer along at least a portion of each of the bottom panel, the lower portion of the sidewall, and upper portion of the sidewall.

12. The container of claim 11, wherein the liner is releasably attached to the base layer along at least a portion of each of the side panel and the end panel.

13. The container of claim 11, the liner being releasably attached to the base layer along at least a portion of the flange.

14. The container of claim 13, wherein the liner comprises an outer edge that is outwardly spaced from an edge of the flange.

15. The container of claim 8, wherein the end panel is a first end panel, the side panel is a first side panel, and the sidewall further comprises a second end panel disposed opposite to the first end panel and a second side panel disposed opposite to the first side panel, each of the first end panel and the second end panel abutting each of the first side panel and the second side panel at respective corners of the container.
16. The container of claim 8, wherein the bottom panel is a first bottom panel and the sidewall is a first sidewall, and the container further comprises a first compartment and a second compartment, the first compartment comprising the first bottom panel and the first sidewall, and the second compartment comprising a second bottom panel and a second sidewall extending along the second bottom panel.
17. The container of claim 16, wherein the first compartment and the second compartment are connected along a divider wall, the divider wall comprising at least a portion of each of the first sidewall and the second sidewall.
18. The container of claim 16, further comprising a divider wall, wherein the flange extends outwardly from the first sidewall and the second sidewall, the flange comprises a central flange portion, the first sidewall comprises a first panel foldably connected to the central flange portion, the second sidewall comprises a second panel foldably connected to the central flange portion, and the divider wall comprises the first panel, the second panel, and the central flange portion.
19. The container of claim 16, wherein the lower portion, the upper portion, and the intermediate fold line of the first sidewall are a first lower portion, a first upper portion, and a first intermediate fold line, respectively, and the second sidewall comprises a second lower portion extending along the second bottom panel and a second upper portion extending upwardly from the second lower portion along a second intermediate fold line.
20. The container of claim 19, wherein each of the first lower portion and the second lower portion extends at a first angle with respect to the respective first bottom panel and second bottom panel and each of the first upper portion and the second upper portion extends at a second angle with respect to the respective first lower portion and second lower portion, and each of the first angle and the second angle is obtuse.
21. The container of claim 8, wherein the lower portion extends along a perimeter of the bottom panel.
22. In combination, a blank and a liner material for forming a container for heating a food product, the blank comprising: a bottom panel; an end panel foldably connected to the bottom panel and a side panel foldably connected to the bottom panel; the end panel and the side panel being for at least partially forming a sidewall comprising a lower portion extending along the bottom panel and an upper portion extending upwardly from the lower portion along an intermediate fold line when the container is formed from the blank and the liner material, wherein the lower portion is for being oblique with respect to the bottom panel and the upper portion is for being oblique with respect to the lower portion when the container is formed from the blank and the liner material; a first flange portion extending from the end panel and a second flange portion extending from the side panel, wherein the first flange portion and the second flange portion at least partially form a flange extending outwardly from the sidewall when the container is formed from the blank and the liner material; wherein the blank is for forming a base layer of the container, the liner material is for forming a liner that is releasably attached to an inner surface of the base layer when the container is formed from the blank and the liner material, and the liner is separable from the base layer after heating of the container formed from the blank and the liner material; wherein the end panel comprises a first lower edge extending from the bottom panel to the intermediate fold line and a first upper edge extending from the intermediate fold line to the first flange portion, the side panel comprises a second lower edge extending from the bottom panel to the intermediate fold line and a second upper edge extending from the intermediate fold line to the second flange portion, the first lower edge extends at a first angle with respect to the second lower edge, the first upper edge

extends at a second angle with respect to the second upper edge, and the first angle is different than the second angle, the first lower edge and the first upper edge being for abutting the respective second lower edge and second upper edge at the corner of the container formed from the blank and the liner material; wherein, when the container is formed from the blank and the liner material, the upper portion of the sidewall is for extending at an obtuse angle from the lower portion of the sidewall along the inner surface.

23. The combination of claim 22, wherein the second angle is larger than the first angle.

24. The combination of claim 22, wherein the obtuse angle is a second obtuse angle, the first angle and the second angle are configured so that the lower portion of the sidewall extends at a first obtuse angle with respect to the bottom panel and the upper portion of the sidewall extends at the second obtuse angle with respect to the lower portion of the sidewall when the container is formed from the blank and the liner material.

25. The combination of claim 22, wherein the lower portion of the sidewall extends at a third angle with respect to the bottom panel and the upper portion of the sidewall extends at a fourth angle with respect to the lower portion when the container is formed from the blank and the liner material, each of the third angle and the fourth angle is obtuse, and the liner is releasably attached to the base layer along at least a portion of each of the bottom panel, the lower portion of the sidewall, and the upper portion of the sidewall.

26. The combination of claim 25, the liner being releasably attached to the base layer along at least a portion of the flange when the container is formed from the blank and the liner material.

27. The combination of claim 22, wherein the end panel is a first end panel, the side panel is a first side panel, and the blank further comprises a second end panel disposed opposite to the first end panel and a second side panel disposed opposite to the first side panel, each of the first end panel and the second end panel abutting each of the first side panel and the second side panel at respective corners of the container formed from the blank and the liner material.

28. The combination of claim 22, wherein the bottom panel is a first bottom panel, the end panel is a first end panel, the side panel is a first side panel, and the sidewall is a first sidewall, and the blank further comprises a first section and a second section, the first section comprising the first bottom panel, the first end panel, and the first side panel, the second section comprising a second bottom panel, a second end panel foldably connected to the second bottom panel, and a second side panel foldably connected to the second bottom panel, the first section is for forming a first compartment comprising the first sidewall when the container is formed from the blank and the liner material, and the second section is for forming a second compartment comprising a second sidewall at least partially formed by the second end panel and the second side panel when the container is formed from the blank and the liner material.

29. The combination of claim 28, wherein the first section and the second section are connected along a divider wall, the divider wall comprising at least a portion of at least one of the first end panel and the first side panel and at least a portion of at least one of the second end panel and the second side panel.

30. The combination of claim 28, wherein the blank further comprises a central flange portion for forming at least a portion of the flange of the container formed from the blank and the liner material, at least one of the first end panel and the first side panel is foldably connected to the central flange portion, and at least one of the second end panel and the second side panel is foldably connected to the central flange portion so that the first section and the second section are connected by at least the central flange portion.

31. A method of forming a container, the method comprising: obtaining a blank and a liner material, the blank comprising a bottom panel, an end panel foldably connected to the bottom panel, a side panel foldably connected to the bottom panel, a first flange portion extending from the end panel, and a second flange portion extending from the side panel, wherein the end panel comprises a first lower edge extending from the bottom panel to the intermediate fold line and a

first upper edge extending from the intermediate fold line to the first flange portion, the side panel comprises a second lower edge extending from the bottom panel to the intermediate fold line and a second upper edge extending from the intermediate fold line to the second flange portion; forming the blank into an initial construct comprising folding the end panel and the side panel relative to the bottom panel so that the first lower edge and the first upper edge abut the respective second lower edge and second upper edge at a corner of the container and forming the first flange portion and the second flange portion into a flange; attaching at least a portion of the liner material to an inner surface of the initial construct so that the liner material and the initial construct form a respective liner and base layer of the container and so that the liner is releasably attached to the inner surface of the base layer by the heat seal layer, wherein the liner is separable from the base layer after heating the container; wherein the end panel and the side panel at least partially form a sidewall, the flange extending outwardly from the sidewall, the sidewall comprising a lower portion extending along the bottom panel and an upper portion extending upwardly from the lower portion along an intermediate fold line, wherein the lower portion is oblique with respect to the bottom panel, the upper portion is oblique with respect to the lower portion, and the upper portion extends at an obtuse angle from the lower portion along the inner surface.

32. The method of claim 31, wherein the forming the initial construct comprises folding the end panel and the side panel with respect to the bottom panel so that the lower portion of the sidewall extends upwardly and outwardly from the bottom panel, the lower portion extends at a first angle with respect to the bottom panel, the upper portion extends at a second angle with respect to the lower portion, and each of the first angle and the second angle is obtuse.

33. The method of claim 32, wherein the attaching at least a portion of the liner material to the initial construct comprises releasably attaching the liner to the base layer along at least a portion of each of the bottom panel, the lower portion of the sidewall, and upper portion of the sidewall.

34. The method of claim 31, wherein the first lower edge extends at a first angle with respect to the second lower edge in the blank, the first upper edge extends at a second angle with respect to the second upper edge in the blank, and the first angle is different than the second angle.

35. The method of claim 34, wherein the second angle is larger than the first angle.

36. The method of claim 34, wherein the obtuse angle is a second obtuse angle, the first angle and the second angle are configured so that the lower portion of the sidewall extends at a first obtuse angle with respect to the bottom panel and the upper portion of the sidewall extends at the second obtuse angle with respect to the lower portion of the sidewall after the forming the initial construct.

37. The method of claim 31, wherein the bottom panel is a first bottom panel and the sidewall is a first sidewall, and the forming the initial construct comprises forming a first compartment comprising the first bottom panel and the first sidewall and forming a second compartment comprising a second bottom panel and a second sidewall extending along the second bottom panel, the first compartment and the second compartment being connected along a divider wall comprising at least a portion of each of the first sidewall and the second sidewall.

38. The method of claim 37, wherein the lower portion, the upper portion, and the intermediate fold line of the first sidewall are a first lower portion, a first upper portion, and a first intermediate fold line, respectively, the second sidewall comprises a second lower portion extending along the second bottom panel and a second upper portion extending upwardly from the second lower portion along a second intermediate fold line, each of the first lower portion and the second lower portion extends at a first obtuse angle with respect to the respective first bottom panel and second bottom panel, and each of the first upper portion and the second upper portion extends at a second obtuse angle with respect to the respective first lower portion and second lower portion.

---