

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12394360
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	He; Gang et al.

Architecture for light emitting elements in a light field display

Abstract

The disclosure describes various aspects of an architecture for light emitting elements in a light field display. In an aspect, a light field display can include multiple picture elements (e.g., super-raxels), where each picture element includes multiple sub-picture elements monolithically integrated on a same semiconductor substrate. Each sub-picture element has a respective light steering optical element and includes an array of light emitting elements (e.g., sub-raxels) that produce the same color of light. The light steering optical element can include at least one microlens, at least one grating, or a combination of both. Separate groups of light emitting elements can be configured and a directional resolution of the light field display can be based on the number of groups. The light field display also includes electronic means configured to drive the light emitting elements in each sub-picture element.

Inventors: He; Gang (Cupertino, CA), Schneider, Jr.; Richard Peter (Sunnyvale, CA), Jones; Andrew Victor (San Jose, CA), Dodd, Jr.; James Richard (Palo Alto, CA), Han; Joseph Hsiao-Tien (Redwood City, CA)

Applicant: GOOGLE LLC (Mountain View, CA)

Family ID: 1000008765502

Assignee: GOOGLE LLC (Mountain View, CA)

Appl. No.: 16/392061

Filed: April 23, 2019

Prior Publication Data

Document Identifier	Publication Date
US 20190333444 A1	Oct. 31, 2019

Related U.S. Application Data

Publication Classification

Int. Cl.: **G09G3/32** (20160101); **G02B27/09** (20060101); **G09G3/20** (20060101); **H04N23/55** (20230101)

U.S. Cl.:

CPC **G09G3/32** (20130101); **G02B27/0955** (20130101); **G09G3/2003** (20130101); **H04N23/55** (20230101); G09G2310/0264 (20130101)

Field of Classification Search

USPC: 345/82; 362/311.02; 362/612; 362/800; 362/555; 362/97.2

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4647927	12/1986	Ichikawa	345/55	G09G 3/20
7402831	12/2007	Miller	257/13	H01L 33/08
7974007	12/2010	Jung	N/A	N/A
8605139	12/2012	Yamauchi et al.	N/A	N/A
9170454	12/2014	Huang et al.	N/A	N/A
9372349	12/2015	Brug	N/A	G02B 5/1842
9606366	12/2016	Shigemura	N/A	N/A
9684174	12/2016	Fleck et al.	N/A	N/A
9823482	12/2016	Muller et al.	N/A	N/A
10431717	12/2018	Dasgupta et al.	N/A	N/A
10957818	12/2020	Ahmed	N/A	N/A
11619830	12/2022	Chen	349/15	G02B 30/33
2006/0227085	12/2005	Boldt, Jr.	348/E17.005	G01J 1/46
2007/0297750	12/2006	Bass et al.	N/A	N/A
2008/0266468	12/2007	Cossairt et al.	N/A	N/A
2008/0309756	12/2007	Verburgh	348/51	G06T 3/40
2009/0078955	12/2008	Fan et al.	N/A	N/A
2010/0118045	12/2009	Elliott et al.	N/A	N/A
2011/0233575	12/2010	Huang	257/E33.056	H01L 27/153
2011/0299044	12/2010	Yeh et al.	N/A	N/A
2012/0199852	12/2011	Lowes	257/98	G09F 9/33
2012/0223875	12/2011	Lau	345/82	G09G 3/32
2012/0236403	12/2011	Sykora et al.	N/A	N/A
2013/0009934	12/2012	Nakamizo et al.	N/A	N/A
2013/0257827	12/2012	Hsieh et al.	N/A	N/A
2013/0286053	12/2012	Fleck et al.	N/A	N/A

2013/0335682	12/2012	Gilbert et al.	N/A	N/A
2014/0029094	12/2013	Kroon et al.	N/A	N/A
2014/0104184	12/2013	Meador et al.	N/A	N/A
2014/0111856	12/2013	Brug et al.	N/A	N/A
2015/0069433	12/2014	Haase	257/89	H01L 27/1255
2015/0249820	12/2014	Saigo	348/55	H04N 13/302
2015/0317930	12/2014	Kim	345/82	H05B 45/18
2015/0332635	12/2014	Lau et al.	N/A	N/A
2015/0364523	12/2014	Sato	N/A	N/A
2016/0076731	12/2015	Mönch et al.	N/A	N/A
2016/0234487	12/2015	Kroon	N/A	H04N 13/305
2016/0238352	12/2015	Baldrige et al.	N/A	N/A
2016/0254638	12/2015	Tong et al.	N/A	N/A
2016/0322432	12/2015	Yang	N/A	G09G 3/3208
2016/0351855	12/2015	Yang	N/A	H01L 51/5275
2017/0061838	12/2016	Shi et al.	N/A	N/A
2017/0129272	12/2016	Rich et al.	N/A	N/A
2017/0150115	12/2016	Vandewalle et al.	N/A	N/A
2017/0171533	12/2016	Benitez et al.	N/A	N/A
2017/0186368	12/2016	Hirai et al.	N/A	N/A
2017/0208319	12/2016	Kim	N/A	H04N 13/305
2017/0237973	12/2016	Jung	N/A	N/A
2017/0272739	12/2016	Kroon et al.	N/A	N/A
2017/0316736	12/2016	Hughes et al.	N/A	N/A
2017/0323925	12/2016	Schneider et al.	N/A	N/A
2017/0358562	12/2016	Banna	N/A	H01L 25/0753
2017/0358604	12/2016	Lee et al.	N/A	N/A
2018/0067329	12/2017	Kim	N/A	H04N 13/324
2018/0097033	12/2017	Ahmed et al.	N/A	N/A
2018/0102085	12/2017	Pan	N/A	G09G 3/3291
2018/0114878	12/2017	Danesh	N/A	H01L 33/0095
2018/0130400	12/2017	Meitl	N/A	G09G 3/342
2018/0196272	12/2017	Chen	N/A	N/A
2019/0200004	12/2018	Schubert	N/A	G02B 26/08
2019/0214529	12/2018	Ahmed	N/A	H01L 33/24
2019/0258071	12/2018	Dong	N/A	H10K 59/353
2019/0334064	12/2018	Pourquier	N/A	H01L 33/505

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103635850	12/2013	CN	N/A
104718152	12/2014	CN	N/A
105929552	12/2015	CN	N/A
105959672	12/2015	CN	N/A
106652809	12/2016	CN	N/A
H11-74566	12/1998	JP	N/A
3005115	12/1999	JP	N/A
2001133727	12/2000	JP	N/A
2012037715	12/2011	JP	N/A
2014194523	12/2013	JP	N/A
2016526276	12/2015	JP	N/A
101071137	12/2010	KR	N/A
101265727	12/2012	KR	N/A
20150021010	12/2014	KR	N/A
I403759	12/2012	TW	N/A
201335673	12/2012	TW	N/A
201403130	12/2013	TW	N/A
2013002808	12/2012	WO	N/A
WO 2017-117825	12/2016	WO	N/A
WO 2017192667	12/2016	WO	N/A
WO 2017-219415	12/2016	WO	N/A
WO 2018-063391	12/2017	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion corresponding to International Application No. PCT/US2019/28927, dated Jul. 30, 2019. cited by applicant

PCT/US2019/028907 International Search Report and Written Opinion dated Aug. 29, 2019, 10 pages. cited by applicant

U.S. Appl. No. 16/391,850 Office Action dated Jun. 16, 2020, 16 pages. cited by applicant

U.S. Appl. No. 16/391,850 Office Action dated Apr. 29, 2021, 8 pages. cited by applicant

U.S. Appl. No. 16/391,850 Notice of Allowance dated May 25, 2021, 10 pages. cited by applicant

European Patent Application No. 19793170.2 extended Search Report and Opinion, dated Dec. 9, 2021, 8 pages. cited by applicant

European Patent Application No. 19791532.5 extended Search Report and Opinion, dated Jan. 5, 2022, 10 pages. cited by applicant

Ku, et al., "Microlens Array Optical Field Imaging Model And the Calibration Method Thereof", Optical Journal, Dec. 10, 2014, 5 pages. cited by applicant

Sun, et al., "Computed Light Field Display Based on Orthogonal Projection", Guangming Journal of Engineering, Apr. 15, 2018, 13 pages. cited by applicant

Extended European Search Report for European Application No. 23216366.7, mailed Jul. 29, 2024, 8 pages. cited by applicant

Primary Examiner: Boddie; William

Assistant Examiner: English; Alecia D

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) The present application claims priority to and the benefit of U.S. Provisional Patent Application No. 62/662,629, entitled “ARCHITECTURE FOR LIGHT EMITTING ELEMENTS IN A LIGHT FIELD DISPLAY,” and filed on Apr. 25, 2018, the contents of which are incorporated herein by reference in their entirety.

BACKGROUND OF THE DISCLOSURE

(1) Aspects of the present disclosure generally relate to displays, and more specifically, to an architecture for light emitting elements in a light field display.

(2) With the advent of different video applications and services, there is a growing interest in the use of displays that can provide an image in three full dimensions (3D). There are different types of displays capable of doing so, including volumetric displays, holographic displays, integral imaging displays, and compressive light field displays, to name a few. Existing display technologies can have several limitations, including limitations on the views provided to the viewer, the complexity of the equipment needed to provide the various views, or the cost associated with making the display.

(3) Light field or lightfield displays, however, present some of the better options as they can be flat displays configured to provide multiple views at different locations to enable the perception of depth or 3D to a viewer. Light field displays can require a large number of light emitting elements, at resolutions that can be two to three orders of magnitude greater than those of traditional displays. Therefore, there are challenges in both the number of light emitting elements and the manner in which they are organized that need consideration to enable the ultra-high-density required to provide the best possible experience to a viewer.

SUMMARY OF THE DISCLOSURE

(4) The following presents a simplified summary of one or more aspects in order to provide a basic understanding of such aspects. This summary is not an extensive overview of all contemplated aspects, and is intended to neither identify key or critical elements of all aspects nor delineate the scope of any or all aspects. Its purpose is to present some concepts of one or more aspects in a simplified form as a prelude to the more detailed description that is presented later.

(5) As used in this disclosure, the term sub-raxel may refer to a light emitting element, including light emitting element that produce a single color of light and light emitting elements that produce red, green, and blue light, the term raxel may refer to a group or allocation of sub-raxels (e.g., neighboring or nearby positioned sub-raxels), and the term super-raxel or picture element may refer to an array or arrangement of light emitting elements that are organized, grouped, or otherwise allocated into different raxels.

(6) In an aspect of the disclosure, a light field display can include multiple picture elements (e.g., super-raxels), where each picture element includes multiple sub-picture elements monolithically integrated on a same semiconductor substrate. A picture element may also be referred to as a light field picture element. Each sub-picture element has a respective light steering optical element and includes an array of light emitting elements (e.g., sub-raxels) that produce the same color of light. The light steering optical element can include at least one microlens, at least one grating, or a combination of both. Separate groups (e.g., raxels) of light emitting elements can be configured to compose picture elements (e.g., super-raxels) and a directional resolution of the light field display can be based on the number of groups. The light field display also includes electronic means configured to drive the light emitting elements in each sub-picture element.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The appended drawings illustrate only some implementation and are therefore not to be considered limiting of scope.
- (2) FIG. 1A illustrates an example of a picture element for light field displays, in accordance with aspects of this disclosure.
- (3) FIG. 1B illustrates another example of a picture element for light field displays, in accordance with aspects of this disclosure.
- (4) FIG. 2 illustrates an example of light emitting elements in a picture element, in accordance with aspects of this disclosure.
- (5) FIG. 3 illustrates an example of a light field display having multiple picture elements, in accordance with aspects of this disclosure.
- (6) FIG. 4 illustrates another example of a light field display having multiple picture elements, in accordance with aspects of this disclosure.
- (7) FIG. 5 illustrates an example of a light field display and camera having multiple picture elements and light detecting elements, in accordance with aspects of this disclosure.
- (8) FIG. 6A illustrates an example of a cross-sectional view of a portion of a light field display, in accordance with aspects of this disclosure.
- (9) FIG. 6B illustrates another example of a cross-sectional view of a portion of a light field display, in accordance with aspects of this disclosure.
- (10) FIG. 7A illustrates an example of a configuration of a light field display, in accordance with aspects of this disclosure.
- (11) FIG. 7B illustrates another example of a configuration of a light field display, in accordance with aspects of this disclosure.
- (12) FIG. 8A illustrates an example of an array of light emitting elements in a picture element, in accordance with aspects of this disclosure.
- (13) FIG. 8B illustrates an example of a picture element with sub-picture elements, in accordance with aspects of this disclosure.
- (14) FIG. 9A illustrates an example of a picture element with color converters, in accordance with aspects of this disclosure.
- (15) FIG. 9B illustrates an example of sub-picture elements with color converters, in accordance with aspects of this disclosure.
- (16) FIG. 9C illustrates another example of sub-picture elements with color converters, in accordance with aspects of this disclosure.

DETAILED DESCRIPTION

(17) The detailed description set forth below in connection with the appended drawings is intended as a description of various configurations and is not intended to represent the only configurations in which the concepts described herein may be practiced. The detailed description includes specific details for the purpose of providing a thorough understanding of various concepts. However, it will be apparent to those skilled in the art that these concepts may be practiced without these specific details. In some instances, well known components are shown in block diagram form in order to avoid obscuring such concepts.

(18) FIG. 1A shows a diagram **100a** describing an example of a picture element for light field displays, also referred to as multi-view displays, for example. A light field display (see e.g., light field displays **310** in FIGS. 3-5) can include multiple picture elements (see e.g., picture elements **320** in FIGS. 3-5), which can be organized in arrays, grids, or other types of ordered arrangements. In some implementations, the multiple picture elements can be monolithically integrated on a same semiconductor substrate. That is, multiple picture elements can be fabricated, constructed, and/or

formed from one or more layers of the same or different materials disposed, formed, and/or grown on a single, continuous semiconductor substrate. Additional details regarding materials and other aspects related to the semiconductor substrate are provided below. In this disclosure, the term “picture element” and the term “super-rixel” can be used interchangeably to describe a similar structural unit in a light field display. In some instances, a “picture element” can be referred to as a pixel, but it is different from a pixel used in traditional displays.

(19) A single picture element can include many light emitting elements **125**. As noted above, a picture element is different from a pixel in a traditional display in that a pixel generally identifies a discrete element that emits light (e.g., in a non-directional manner, Lambertian emission) while a picture element includes multiple light emitting elements **125**, which are themselves organized and configured to produce or generate light outputs that can be directional in nature, where these light outputs (e.g., ray elements) contribute to the formation of multiple, different light field views that are to be provided by the light field display to a viewer in different locations or positions away from the light field display. In an example, each particular location or position away from the light field display can be associated with a light field view provided by the light field display. Additional aspects regarding the arrangement and characteristics of the light emitting elements **125** in a picture element are described in more detail below, further identifying differences between a picture element in a light field display and a pixel in a traditional display.

(20) A picture element can have a corresponding light steering optical element **115** as shown in FIG. 1A. The light steering optical element **115** can be configured to steer or direct different ray elements **105** produced (e.g., emitted) by the light emitting elements **125**. In an aspect, the different ray elements **105** may correspond to different directions of light outputs produced by one or more light emitting elements **125**. In this regard, the directional resolution of the picture element or the light field display may correspond to a number of light output directions supported. Moreover, the light field views provided by the light field display are produced by a contribution from various light outputs that are received by the viewer in a particular location or position away from the light field display. The light steering optical element **115** can be considered part of the picture element, that is, the light steering optical element **115** is an integral component of the picture element. The light steering optical element **115** can be aligned and physically coupled or bonded to the light emitting elements **125** of its respective picture element. In some implementations, there may be one or more layers or materials (e.g., optically transparent layers or materials) disposed between the light steering optical element **115** and the light emitting elements **125** of its respective picture element.

(21) In one example, a light steering optical element **115** can be a microlens or a lenslet as shown in FIG. 1A, which can be configured to steer or direct the ray elements **105** (e.g., the different light field views) in the appropriate directions. A light steering optical element **115** can include a single optical structure (e.g., a single microlens or lenslet) or can be constructed or formed to include multiple optical structures. For example, a light steering optical element **115** can have at least one microlens, at least one grating, or a combination of both. In another example, a light steering optical element **115** can have multiple layers of optical components (e.g., microlenses and/or gratings) that combined produce the appropriate light steering effect. For example, a light steering optical element **115** can have a first microlens and a second microlens stacked over the first microlens, with the first microlens being associated with a first layer and the second microlens being associated with a second layer. A different example can use a grating or a grating and microlens combination in either or both layers. The construction of the light steering optical element **115**, and therefore the positioning and characteristics of any microlenses and/or gratings built or formed therein, is intended to produce the proper steering or directing of the ray elements **105**.

(22) Different types of devices can be used for the light emitting elements **125**. In one example, a light emitting element **125** can be a light-emitting diode (LED) made from one or more

semiconductor materials. The LED can be an inorganic LED. To achieve the high densities needed in light field displays, the LED can be, for example, a micro-LED, also referred to as a microLED, an mLED, or a μ LED, which can provide better performance, including brightness and energy efficiency, than other display technologies such as liquid crystal display (LCD) technology or organic LED (OLED) technology. The terms “light emitting element,” “light emitter,” or “emitter,” can be used interchangeably in this disclosure, and can also be used to refer to a microLED. Moreover, any of these terms can be used interchangeably with the term “sub-rixel” to describe a similar structural unit in a light field display.

(23) The light emitting elements **125** of a picture element can be monolithically integrated on a same semiconductor substrate. That is, the light emitting elements **125** can be fabricated, constructed, and/or formed from one or more layers of the same or different materials disposed, formed, and/or grown on a single, continuous semiconductor substrate. The semiconductor substrate can include one or more of GaN, GaAs, Al.sub.2O.sub.3, Si, SiC, Ga.sub.2O.sub.3, alloys thereof, or derivatives thereof. For their part, the light emitting elements **125** monolithically integrated on the same semiconductor substrate can be made at least partially of one or more of AlN, GaN, InN, AlAs, GaAs, InAs, AlP, GaP, InP, alloys thereof, or derivatives thereof. In some implementations, each of the light emitting elements **125** can include a quantum well active region made from one or more of the materials described above.

(24) The light emitting elements **125** can include different types of light emitting elements or devices to provide light of different colors, which in turn enable the light field display to make visually available to viewers a particular color gamut or range. In an example, the light emitting elements **125** can include a first type of light emitting element that produces green (G) light, a second type of light emitting element that produces red (R) light, and a third type of light emitting element that produces blue (B) light. In another example, the light emitting elements **125** can optionally include a fourth type of light emitting element that produces white (W) light. In another example, a single light emitting element **125** may be configured to produce different colors of light. Moreover, the lights produced by the light emitting elements **125** in a display enable the entire range of colors available on the display, that is, the display's color gamut. The display's color gamut is a function of the wavelength and linewidth of each of the constituent color sources (e.g., red, green, blue color sources).

(25) In one implementation, the different types of colors of light can be achieved by changing the composition of one or more materials (e.g., semiconductor materials) in the light emitting elements or by using different structures (e.g., quantum dots of different sizes) as part of or in connection with the light emitting elements. For example, when the light emitting elements **125** of a picture element are LEDs, a first set of the LEDs in the picture can be made at least in part of InGaN with a first composition of indium (In), a second set of the LEDs can be made at least in part of InGaN with a second composition of In different from the first composition of In, and a third set of the LEDs can be made at least in part of InGaN with a third composition of In different from the first and second compositions of In.

(26) In another implementation, the different types of colors of light can be achieved by applying different color converters (e.g., color downconverters) to light emitting elements that produce a same or similar color of light. In one implementation, some or all of the light emitting elements **125** can include a respective color conversion media (e.g., color conversion material or combination of materials). For example, each of the light emitting elements **125** in a picture element is configured to produce blue light. A first set of the light emitting elements **125** simply provides the blue light, a second set of the light emitting elements **125** is further configured to downconvert (e.g., using one conversion media) the blue light to produce and provide green light, and a third set of the light emitting elements **125** is also further configured to downconvert (e.g., using another conversion media) the blue light this time to produce and provide red light.

(27) The light emitting elements **125** of a picture element can themselves be organized in arrays,

grids, or other types or ordered arrangements just like picture elements can be organized using different arrangements in a light field display.

(28) Additionally, for each picture element there can be one or more drivers **135** for driving or operating the light emitting elements **125**. The drivers **135** can be electronic circuits or means that are part of a backplane **130** and electronically coupled to the light emitting elements **125**. The drivers **135** can be configured to provide the appropriate signals, voltages, and/or currents in order to drive or operate the light emitting elements **125** (e.g., to select a light emitting element, control settings, control brightness). In some implementations, there can be a one-to-one correspondence in which one driver **135** can be used to drive or operate a respective light emitting element **125**. In other implementations, there can be a one-to-many correspondence in which one driver **135** can be used to drive or operate multiple light emitting elements **125**. For example, the drivers **135** can be in the form of unit cells that are configured to drive a single light emitting element **125** or multiple light emitting elements **125**.

(29) In addition to the backplane **130** that includes the drivers **135**, a light field display can also include a plane **120** having the light emitting elements **125**. Moreover, a light field display can also include a plane **110** having the light steering optical elements **115**. In an implementation, two of more of the plane **110**, the plane **120**, and the backplane **130** can be integrated or bonded together to form a stacked or three-dimensional (3D) structure. Additional layers, planes, or structures (not shown) can also be part of the stacked or 3D structure to facilitate or configure the connectivity, interoperability, adhesion, and/or distance between the planes. As used in this disclosure, the term “plane” and the term “layer” can be used interchangeably.

(30) FIG. **1B** shows a diagram **100b** illustrating another example of a picture element for light field displays. In this example, the picture element can not only provide or emit ray elements **105** (as shown also in FIG. **1B**), but can also be configured to receive ray elements **107** through the light steering optical element **115**. The ray elements **107** can correspond to directional light inputs that contribute to various views being received by the picture element or the light field display just like the ray elements **105** can correspond to directional light outputs that contribute to various views being provided by the picture element or the light field display to a viewer.

(31) In the example in FIG. **1B**, a plane **120a** having the light emitting elements **125** can also include one or more light detecting elements **127** to receive or capture light associated with the ray elements **107**. The one or more light detecting elements **127** can be positioned in the plane **120a** adjacently surrounded by the light emitting elements **125**, or alternatively, the one or more light detecting elements **127** can be positioned in the plane **120a** separate from the light emitting elements **125**. The terms “light detecting element,” “light detector,” “light sensor,” or “sensor,” can be used interchangeably in this disclosure.

(32) In some implementations, the light detecting elements **127** can be monolithically integrated on the same semiconductor substrate as the light emitting elements **125**. As such, the light detecting elements **127** can be made of the same types of materials as described above from which the light emitting elements **125** can be made. Alternatively, the light detecting elements **127** can be made of different materials and/or structures (e.g., silicon complimentary metal-oxide-semiconductor (CMOS) or variations thereof) from those used to make the light emitting elements **125**.

(33) Moreover, a plane **130a** having the drivers **135** can also include one or more detectors **137** electronically coupled to the light detecting elements **127** and configured to provide the appropriate signals, voltages, and/or currents to operate the light detecting elements **127** (e.g., to select a light detecting element, control settings) and to produce signals (e.g., analog or digital signal) representative of the light that is received or captured by the light detecting elements **127**.

(34) The construction of the light steering optical element **115** in FIG. **1B**, and therefore the positioning and characteristics of any microlenses and/or gratings built therein, is intended to produce the right steering or directing of the ray elements **105** away from the picture element to provide the various contributions that are needed for a viewer to perceive the light field views, and

also to produce the right steering or directing of the ray elements **107** towards the appropriate light detecting elements **127**. In some implementations, the light detecting elements **127** may use separate or additional light steering optical elements than the light steering optical element **115** used in connection with the light emitting elements **125**. In such cases, the light steering optical element for the light detecting elements **127** can be included in the plane **110** having the light steering optical elements **115**.

(35) The different picture element structures described in FIGS. **1A** and **1B** enable control, placement, and directivity of the ray elements produced by the light emitting elements **125** of the picture element. In addition, the picture element structures in FIG. **1B** enable control, placement, and directivity of the ray elements received by the picture element.

(36) In FIG. **2**, a diagram **200** shows an example of a pattern or mosaic of light emitting elements **125** in a picture element. In this example, a portion of an array or grid of light emitting elements **125** that are part of a picture element is enlarged to show one of different patterns or mosaics that can be used for the various types of light emitting elements **125**. This example shows three (3) different types of light emitting elements **125**, a first type of light emitting element **125a** that produces light of one color, a second type of light emitting element **125b** that produces light of another color, and a third type of light emitting element **125c** that produces light of yet another color. These light colors can be red light, green light, and blue light, for example. In some implementations, the pattern can include twice as many light emitting elements that produce red light than those that produce green light or blue light. In other implementations, the pattern can include a light emitting element that produces red light that is twice a size of those that produce green light or blue light. In other implementations, the pattern can include a fourth type of light emitting element **125** that produces light of fourth color, such as white light, for example.

Generally, the area of light emitting elements of one color can be varied relative to the area of light emitting elements of other color(s) to meet particular color gamut and/or power efficiency needs. The patterns and colors described in connection with FIG. **2** are provided by way of illustration and not of limitation. A wide range of patterns and/or colors (e.g., to enable a specified color gamut in the display) may be available for the light emitting elements **125** of a picture element. In another aspect, additional light emitting elements (of any color) can be used in a particular pattern to provide redundancy.

(37) The diagram **200** in FIG. **2** also illustrates having the various types of light emitting elements **125** (e.g., light emitting elements **125a**, **125b**, and **125c**) monolithically integrated on a same semiconductor substrate. For example, when the different types of light emitting elements **125** are based on different materials (or different variations or compositions of the same material), each of these different materials needs to be compatible with the semiconductor substrate such that the different types of light emitting elements **125** can be monolithically integrated with the semiconductor substrate. This allows for the ultra-high-density arrays of light emitting elements **125** (e.g., arrays of RGB light emitting elements) that are needed for light field displays.

(38) A diagram **300** in FIG. **3** shows a light field display **310** having multiple picture elements or super-pixels **320**. A light field display **310** can be used for different types of applications and its size may vary accordingly. For example, a light field display **310** can have different sizes when used as displays for watches, near-eye applications, phones, tablets, laptops, monitors, televisions, and billboards, to name a few. Accordingly, and depending on the application, the picture elements **320** in the light field display **310** can be organized into arrays, grids, or other types of ordered arrangements of different sizes. In the example shown in FIG. **3**, the picture elements **320** can be organized or positioned into an $N \times M$ array, with N being the number of rows of picture elements in the array and M being the number of columns of picture elements in the array. An enlarged portion of such an array is shown to the right of the light field display **310**. For small displays, examples of array sizes can include $N \geq 10$ and $M \geq 10$ and $N \geq 100$ and $M \geq 100$, with each picture element **320** in the array having itself an array or grid of light emitting elements **125**. For larger displays, examples

of array sizes can include $N \geq 500$ and $M \geq 500$, $N \geq 1,000$ and $M \geq 1,000$, $N \geq 5,000$ and $M \geq 5,000$, and $N \geq 10,000$ and $M \geq 10,000$, with each picture element **320** in the array having itself an array or grid of light emitting elements **125**.

(39) In a more specific example, for a 4K light field display in which the pixels in a traditional display are replaced by the picture elements **320**, the $N \times M$ array of picture elements **320** can be a $2,160 \times 3,840$ array including approximately 8.3 million picture elements **320**. Depending on the number of light emitting elements **125** in each of the picture elements **320**, the 4K light field display can have a resolution that is one or two orders of magnitude greater than that of a corresponding traditional display. When the picture elements or super-raxels **320** include as light emitting elements **125** different LEDs that produce red (R) light, green (G) light, and blue (B) light, the 4K light field display can be said to be made from monolithically integrated RGB LED super-raxels.

(40) Each of the picture elements **320** in the light field display **310**, including its corresponding light steering optical element **115** (e.g., an integral imaging lens), can represent a minimum picture element size limited by display resolution. In this regard, an array or grid of light emitting elements **125** of a picture element **320** can be smaller than the corresponding light steering optical element **115** for that picture element. In practice, however, it is possible for the size of the array or grid of light emitting elements **125** of a picture element **320** to be similar to the size of the corresponding light steering optical element **115** (e.g., the diameter of a microlens or lenslet), which in turn is similar or the same as a pitch **330** between picture elements **320**.

(41) An enlarged view of an array of light emitting elements **125** for a picture element **320** is shown to the right of the diagram **300**. The array of light emitting elements **125** can be a $P \times Q$ array, with P being the number of rows of light emitting elements **125** in the array and Q being the number of columns of light emitting elements **125** in the array. Examples of array sizes can include $P \geq 5$ and $Q \geq 5$, $P \geq 8$ and $Q \geq 8$, $P \geq 9$ and $Q \geq 9$, $P \geq 10$ and $Q \geq 10$, $P \geq 12$ and $Q \geq 12$, $P \geq 20$ and $Q \geq 20$, and $P \geq 25$ and $Q \geq 25$. In an example, a $P \times Q$ array is a 9×9 array including 81 light emitting elements or sub-raxels **125**. The array of light emitting elements **125** for the picture element **320** need not be limited to square or rectangular shapes and can be based on a hexagonal shape or other shapes as well.

(42) For each picture element **320**, the light emitting elements **125** in the array can include separate and distinct groups of light emitting elements **125** (see e.g., group of light emitting elements **610** in FIGS. **6A**, **6B**, and **8A**) that are allocated or grouped (e.g., logically grouped) based on spatial and angular proximity and that are configured to produce the different light outputs (e.g., directional light outputs) that contribute to produce light field views provided by the light field display **310** to a viewer. The grouping of sub-raxels or light emitting elements into raxels need not be unique. For example, during assembly or manufacturing, there can be a mapping of sub-raxels into particular raxels that best optimize the display experience. A similar re-mapping can be performed by the display once deployed to account for, for example, aging of various parts or elements of the display, including variations in the aging of light emitting elements of different colors and/or in the aging of light steering optical elements. In this disclosure, the term “groups of light emitting elements” and the term “raxon” can be used interchangeably to describe a similar structural unit in a light field display. The light field views produced by the contribution of the various groups of light emitting elements or raxels can be perceived by a viewer as continuous or non-continuous views.

(43) Each of the groups of light emitting elements **125** in the array of light emitting elements **125** includes light emitting elements that produce at least three different colors of light (e.g., red light, green light, blue light, and perhaps also white light). In one example, each of these groups or raxels includes at least one light emitting element **125** that produces red light, one light emitting element **125** that produces green light, and one light emitting element **125** that produce blue light. In another example, each of these groups or raxels includes two light emitting elements **125** that produce red light, one light emitting element **125** that produces green light, and one light emitting element **125** that produces blue light. In yet another example, each of these groups or raxels

includes one light emitting element **125** that produces red light, one light emitting element **125** that produces green light, one light emitting element **125** that produces blue light, and one light emitting element **125** that produces white light.

(44) Because of the various applications (e.g., different sized light field displays) described above, the sizes or dimensions of some of the structural units described in connection with the light field display **310** can vary significantly. For example, a size of an array or grid of light emitting elements **125** (e.g., a diameter, width, or span of the array or grid) in a picture element **320** can range between about 10 microns and about 1,000 microns. That is, a size associated with a picture element or super-raxel **320** can be in this range. The term “about” as used in this disclosure indicates a nominal value or a variation within 1%, 2%, 3%, 4%, 5%, 10%, 15%, 20%, or 25% from the nominal value.

(45) In another example, a size of each group of light emitting elements **125** (e.g., a diameter, width, or span of the group) in a picture element **320** can range between about 1 micron and about 10 microns. That is, a size associated with a group of light emitting elements **125** (e.g., raxel **610**) can be in this range.

(46) In another example, a size of a group of light emitting elements **125** in a picture element **320** can be greater than 10 microns because a size of the light emitting elements **125** in such a group could be as large as 10 microns.

(47) In yet another example, a size of each light emitting element **125** (e.g., a diameter, width, or span of the light emitting element or sub-raxel) can range between about 0.4 microns and about 4 microns. Similarly, a size of each light emitting element **125** (e.g., a diameter, width, or span of the light emitting element or sub-raxel) can be less than about 1 micron. Moreover, a size of each light emitting element **125** in some implementations can be as large as 10 microns. That is, a size associated with a light emitting element or sub-raxel **125** can be in the ranges described above.

(48) In yet another example, a size of a light steering optical element **115** (e.g., a diameter, width, or span of a microlens or lenslet) can range between about 10 microns and about 1,000 microns, which is similar to the range of sizes for a picture element or super-raxel.

(49) In FIG. 4, a diagram **400** shows another example of the light field display **310** illustrating an enlarged view of a portion of an array of picture elements **320** with corresponding light steering optical elements **115**. The pitch **330** can represent a spacing or distance between picture elements **320** and can be about a size of the light steering optical element **115** (e.g., size of a microlens or lenslet).

(50) In this example, the light field display **310** in FIG. 4 can be a 4K light field display with a 2,160×3,840 array of picture elements or super-raxels **320**. In such a case, for a viewer distance of about 1.5 meters or about 5 feet, a size of the light steering optical element **115** can be about 0.5 millimeters. Such a size can be consistent with human acuity of about 1 arc-minute/picture element. The viewer's field of view (FOV) in this example can be about 64 degrees, which can be less than a viewing angle provided by the picture element (e.g., viewing angle>FOV). Moreover, the multiple views provided by the 4K light field display in this example can have a 4 millimeter width, consistent with a diameter of the human pupil. This can translate to the light steering optical element **115** steering the output light produced by a picture element **320** having, for example, 31.sup.2 light emitting elements **125**. Accordingly, the 4K light field display in this example can provide continuous parallax with light field phase or horizontal parallax with light field phase.

(51) A diagram **500** in FIG. 5 illustrates an alternative configuration of a light field display that is also capable of operating as a camera by performing light field capture using neighboring light detecting elements or sensors **127**. In this example, a light field display and camera **310a** includes an N×M array of picture elements **320**, a portion of the array is shown enlarged to the right of the diagram **500**. The light detecting elements **127** can be, for example, silicon-based image sensors assembled with similar integral optical elements as those used by the picture elements **320** (e.g., the light steering optical elements **115**). In one implementation, as shown in FIG. 5, the light detecting

elements **127** can be positioned nearby or adjacent to the picture elements **320** in a one-to-one correspondence (e.g., one capture element for each display element). In other implementations, the number of light detecting elements **127** can be less than the number of picture elements **320**.

(52) In an example, each light detecting element **127** can include multiple sub-sensors for capturing light in the same fashion as each picture element **320** (e.g., a super-raxel) can include multiple light emitting elements **125** (e.g., multiple sub-raxels) or multiple groups of light emitting elements **125** (e.g., multiple raxels).

(53) As described above in connection with FIG. **1B**, the light detecting elements **127** can be integrated in the same plane **120a** as the light emitting elements **125**. Some or all of the features of the light detecting elements **127**, however, could be implemented in the backplane **130a** since the backplane **130a** is also likely to be silicon-based (e.g., a silicon-based substrate). In such a case, at least some of the features of the light detecting elements **127** can be integrated with the detectors **137** in the backplane **130a** to more efficiently have the circuitry or electronic means in the detectors **137** operate the light detecting elements **127**.

(54) A diagram **600a** in FIG. **6A** shows a cross-sectional view of a portion of a light field display (e.g., the light field display **310**) to illustrate some of the structural units described in this disclosure. For example, the diagram **600a** shows three adjacent picture elements or super-raxels **320a**, each having a corresponding light steering optical element **115**. In this example, the light steering optical element **115** can be considered separate from the picture element **320a** but in other instances the light steering optical element **115** can be considered to be part of the picture element.

(55) As shown in FIG. **6A**, each picture element **320a** includes multiple light emitting elements **125** (e.g., multiple sub-raxels), where several light emitting elements **125** (e.g., several sub-raxels) of different types can be grouped together into the group **610** (e.g., into a raxel) associated with a particular light view to be provided by the light field display. A group or raxel can produce various components (see FIG. **6B**) that contribute to a particular ray element **105** as shown by the right-most group or raxel in the middle picture element **320a**. Is it to be understood that the ray elements **105** produced by different groups or raxels in different picture elements can contribute to a view perceived by viewer away from the light field display.

(56) An additional structural unit described in FIG. **6A** is the concept of a sub-picture element **620**, which represents a grouping of the light emitting elements **125** of the same type (e.g., produce the same color of light) of the picture element **320a**. Additional details related to sub-picture elements **620** are described below in connection with FIGS. **8B**, **9B**, and **9C**.

(57) A diagram **600b** in FIG. **6B** shows another cross-sectional view of a portion of a light field display (e.g., the light field display **310**) to illustrate the varying spatial directionality of the ray elements produced by three adjacent picture elements or super-raxels **320a**, each having a corresponding light steering optical element **115**. In this example, a group of light emitting elements **125** in the left-most picture element **320a** produces a ray element **105a** (e.g., light output), where the ray element **105a** is a combination of ray element components **630** (e.g., light output sub-components) produced or generated by the group of light emitting elements **125**. For example, when the group of light emitting elements **125** includes three light emitting elements **125**, each of these can produce or generate a component (e.g., a light component of a different color) of the ray element **105a**. The ray element **105a** has a certain, specified spatial directionality, which can be defined based on multiple angles (e.g., based on two or three angles).

(58) Similarly, a group of light emitting elements **125** in the middle picture element **320a** produces a ray element **105b** (e.g., light output), where the ray element **105b** is a combination of ray element components **630** produced or generated by the group of light emitting elements **125**. The ray element **105b** has a certain, specified spatial directionality, different from the one of the ray element **105a**, which can also be defined based on multiple angles. The same applies for the ray element **105c** produced by a group of light emitting elements **125** in the right-most picture element **320a**.

(59) The following figures describe different configurations for a light field display (e.g., the light

field display **310**). In FIG. 7A, a diagram **700a** shows a first configuration or approach for a light field display. In this configuration, which can be referred to as a picture element array of raxel arrays, different light field views (e.g., View A, View B) can be provided by combining the ray elements **105** emitted by the various picture elements **320b** in the light field display **310**. In this example, the light steering optical element **115** can be considered to be part of the picture elements **320b**. For each picture element **320b**, there is an array or grid **710** of groups of light emitting elements **125** (e.g., an array or grid of raxels), where each of these groups produces a light output having at least one component (see FIG. 6B) that is provided by the light field display **310** as a contribution to construct or form a view perceived by a viewer at a certain location or position from the light field display **310**. For example, in each of the picture elements **320b**, there is at least one group or raxel in the array **710** that contributes to View A and there is at least another group or raxel in the array **710** that contributes to View B. In some instances, depending on the location or position of the viewer relative to the light field display **310**, the same group or raxel can contribute to both View A and View B.

(60) In an aspect of the light field display **310** in FIG. 7A, for each picture element **320b**, there can be a spatial (e.g., lateral) offset between a position of the light steering optical element **115** and a position of the array **710** based on where the picture element **320b** is positioned in the light field display **310**.

(61) In FIG. 7B, a diagram **700b** shows a second configuration or approach for a light field display that supports light capture as well. The light field display and camera **310a** in this configuration is substantially similar to the light field display **310** shown in FIG. 7A, however, in the light field display and camera **310a** there is a camera lens **725** to steer or direct the ray elements **107** to the appropriate light detecting elements (e.g., sensors **127**) in an array **710a** having groups of light emitting elements **125** along with the light detecting elements.

(62) FIG. 8A shows a diagram **800a** describing various details of one implementation of a picture element **320**. For example, the picture element **320** (e.g., a super-raxel) has a respective light steering optical element **115** (shown with a dashed line) and includes an array or grid **810** of light emitting elements **125** (e.g., sub-raxels) monolithically integrated on a same semiconductor substrate. The light steering optical element **115** can be of the same or similar size as the array **810**, or could be slightly larger than the array **810** as illustrated. It is to be understood that some of the sizes illustrated in the figures of this disclosure have been exaggerated for purposes of illustration and need not be considered to be an exact representation of actual or relative sizes.

(63) The light emitting elements **125** in the array **810** include different types of light emitting elements to produce light of different colors and are arranged or configured (e.g., via hardware and/or software) into separate groups **610** (e.g., separate raxels), each of which produces a different light output (e.g., directional light output) that contributes to one or more light field views perceived by a viewer. That is, each group **610** is configured to contribute to one or more of the views that are to be provided to a viewer (or viewers) by the light field display that includes the picture element **320**.

(64) As shown in FIG. 8A, the array **810** has a geometric arrangement to allow adjacent or close placement of two or more picture elements. The geometric arrangement can be one of a hexagonal shape (as shown in FIG. 8A), a square shape, or a rectangular shape.

(65) Although not shown, the picture element **320** in FIG. 8A can have corresponding electronic means (e.g., in the backplane **130** in FIG. 1A) that includes multiple driver circuits configured to drive the light emitting elements **125** in the picture element **230**. In the example in FIG. 8A, the electronic means can include multiple unit cells configured to control the operation of individual sub-picture elements and/or light emitting elements that are part of a group.

(66) FIG. 8B shows a diagram **800b** describing various details of another implementation of a picture element **320**. For example, the picture element **320** (e.g., a super-raxel) in FIG. 8B includes multiple sub-picture elements **620** monolithically integrated on a same semiconductor substrate.

Each sub-picture element **620** has a respective light steering optical element **115** (shown with a dashed line) and includes an array or grid **810a** of light emitting elements **125** (e.g., sub-raxels) that produce the same color of light. The light steering optical element **115** can be of the same or similar size as the array **810a**, or could be slightly larger than the array **810a** as illustrated. For the picture element **320**, the light steering optical element **115** of one of the sub-picture elements **620** is configured to minimize the chromatic aberration for a color of light produced by the light emitting elements **125** in that sub-picture element **620** by optimizing the structure of the light steering optical element for the specified color wavelength. By minimizing the chromatic aberration it may be possible to improve the sharpness of the light field views and compensate for how the magnification is different away from the center of a picture element. Moreover, the light steering optical element **115** is aligned and bonded to the array **810a** of the respective sub-picture element **620**.

(67) The light emitting elements **125** of the sub-picture elements **620** are arranged into separate groups **610** (e.g., raxels), each of which produces a different one of multiple views. That is, each group **610** is configured to produce a view (or a contribution to a view) that is to be provided by the light field display that includes the picture element **320**. As illustrated by FIG. **8B**, each group **610** includes collocated light emitting elements **125** from each of the sub-picture elements **620** (e.g., same position in each sub-picture element).

(68) As shown in FIG. **8B**, the array **810a** has a geometric arrangement to allow adjacent placement of two or more sub-picture elements. The geometric arrangement can be one of a hexagonal shape (as shown in FIG. **8B**), a square shape, or a rectangular shape.

(69) Although not shown, the picture element **320** in FIG. **8B** can have corresponding electronic means (e.g., in the backplane **130** in FIG. **1A**) that includes multiple driver circuits configured to drive the light emitting elements **125** in the picture element **230**. In some examples, one or more common driver circuits can be used for each of the sub-picture elements **620**. In the example in FIG. **8B**, the electronic means can include multiple unit cells configured to control the operation of individual sub-picture elements and/or light emitting elements that are part of a sub-picture element.

(70) A diagram **900a** in FIG. **9A** shows an example of the picture element **320** in FIG. **8A** where the light emitting elements **125** produce lights of different colors by means of respective, individual optical converters or color conversion media for each of the light emitting elements **125**.

(71) In one example, there can be a first converter means (e.g., optical converters **910a**) to convert light produced by a first set of the light emitting elements **125** to blue light, a second converter means (e.g., optical converters **910b**) to convert light produced by a second set of the light emitting elements **125** to green light, and a third converter means (e.g., optical converters **910c**) to convert light produced by a third set of the light emitting elements **125** to red light.

(72) In another example, the first set of the light emitting elements **125** can produce blue light and therefore the first converter means (e.g., optical converters **910a**) is not needed (e.g., the first converter means is optional).

(73) A diagram **900b** in FIG. **9B** shows an example of the picture element **320** in FIG. **8B** where the light emitting elements **125** in each of the sub-picture elements **620** produce light of the same color by means of respective, individual optical converters or color conversion media for each of the light emitting elements **125**.

(74) In one example, there can be a first converter means (e.g., optical converters **910a**) to convert light produced by the light emitting elements **125** of a first one of the sub-picture elements **620** to blue light, a second converter means (e.g., optical converters **910b**) to convert light produced by the light emitting elements **125** of a second one of the sub-picture elements **620** to green light, and a third converter means (e.g., optical converters **910c**) to convert light produced by the light emitting elements **125** of a third one of the sub-picture elements **620** to red light.

(75) In another example, the light emitting elements **125** of the first one of the sub-picture elements

620 can produce blue light and therefore the first converter means (e.g., optical converters **910a**) is not needed (e.g., the first converter means is optional).

(76) A diagram **900c** in FIG. **9C** shows another example of the picture element **320** in FIG. **8B** where the light emitting elements **125** in each of the sub-picture elements **620** produce light of the same color by means of a respective, single optical converter or color conversion media for each of the sub-picture elements **620**.

(77) In one example, there can be a single, first converter means (e.g., optical converter **910a**) to convert light produced by all of the light emitting elements **125** of a first one of the sub-picture elements **620** to blue light, a single, second converter means (e.g., optical converter **910b**) to convert light produced by all the light emitting elements **125** of a second one of the sub-picture elements **620** to green light, and a single, third converter means (e.g., optical converter **910c**) to convert light produced by all of the light emitting elements **125** of a third one of the sub-picture elements **620** to red light.

(78) In another example, the light emitting elements **125** of the first one of the sub-picture elements **620** can produce blue light and therefore the single, first converter means (e.g., optical converters **910a**) is not needed (e.g., the first converter means is optional).

(79) For the FIGS. **9A-9C**, each of the first converter means, the second converter means, and the third converter means can include a composition having phosphorous to produce the color conversion. For example, different compositions of phosphorous can be used to produce the various color conversions. Alternatively or additionally, each of the first converter means, the second converter means, and the third converter means includes quantum dots. The quantum dots for the first converter means can have a first size, the quantum dots for the second converter means can have a second size, and the quantum dots for the third converter means can have a third size, where the size of the quantum dots affects or controls the wavelength of the light to produce the color conversion.

(80) Although the present disclosure has been provided in accordance with the implementations shown, one of ordinary skill in the art will readily recognize that there could be variations to the embodiments and those variations would be within the scope of the present disclosure.

Accordingly, many modifications may be made by one of ordinary skill in the art without departing from the scope of the appended claims.

Claims

1. A light field display comprising: a picture element including multiple sub-picture elements, the multiple sub-picture elements including: an array of light emitting elements grown directly on a single, continuous semiconductor substrate, the array of light emitting elements including (i) a first light emitting element configured to produce a first color of light, (ii) a second light emitting element configured to produce a second color of light that differs from the first color of light, and (iii) a third light emitting element configured to produce a third color of light that differs from each of the first color of light and the second color of light; a light steering optical element configured to direct the first color of light, the second color of light, and the third color of light emitted from the array of light emitting elements in a first direction different from a second direction associated with another array of light emitting elements grown directly on the single, continuous semiconductor substrate; and a backplane including electronic circuits electronically connected with the picture element and configured to individually drive the multiple sub-picture elements.
2. The light field display of claim 1, wherein for each one of the multiple sub-picture elements, the light steering optical element is aligned and bonded to the array of light emitting elements.
3. The light field display of claim 2, wherein the light steering optical element includes at least one of a microlens and a grating.
4. The light field display of claim 1, wherein for each one of the multiple sub-picture elements, the

- light steering optical element optimizes a chromatic aberration for a color of light produced by that one of the multiple sub-picture elements.
5. The light field display of claim 1, wherein each one of the light emitting elements is a light emitting diode (LED).
6. The light field display of claim 5, wherein the LED is an inorganic LED.
7. The light field display of claim 5, wherein the multiple sub-picture elements include: a first sub-picture element configured for producing light at a first wavelength, a second sub-picture element configured for producing light at a second wavelength, the second wavelength being different from the first wavelength, and a third sub-picture element configured for producing light at a third wavelength, the third wavelength being different from the first wavelength and second wavelength.
8. The light field display of claim 7, wherein: the first sub-picture element includes a first group of clustered LEDs formed at least in part of indium-gallium-nitride (InGaN) with a first composition of indium (In), the second sub-picture element includes a second group of clustered LEDs formed at least in part of InGaN with a second composition of In, the second composition of In being different from the first composition of In, and the third sub-picture element includes a third group of clustered LEDs formed at least in part of InGaN with a third composition of In, the third composition of In being different from the first composition of In and second composition of In.
9. The light field display of claim 7, further comprising: a first converter arrangement optically coupled with the first sub-picture element and configured for converting light produced by the first sub-picture element from the first wavelength to a first modified wavelength; and a second converter arrangement optically coupled with the second sub-picture element and configured for converting light produced by the second sub-picture element from the second wavelength to a second modified wavelength.
10. The light field display of claim 9, wherein at least one of the first converter arrangement and the second converter arrangement is formed at least in part of a composition including phosphorous.
11. The light field display of claim 9, wherein at least one of the first converter arrangement and the second converter arrangement includes quantum dots.
12. The light field display of claim 11, wherein the first converter arrangement includes quantum dots of a first size, and the second converter arrangement includes quantum dots of a second size.
13. The light field display of claim 1, wherein the single, continuous semiconductor substrate includes at least one of GaN, GaAs, Al₂O₃, Si, SiC, Ga₂O₃, alloys thereof, and derivatives thereof.
14. The light field display of claim 1, wherein the light emitting elements includes at least one of AlN, GaN, InN, AlAs, GaAs, InAs, AlP, GaP, InP, alloys thereof, and derivatives thereof.
15. The light field display of claim 1, wherein the array of light emitting elements in each one of the multiple sub-picture elements has a geometric arrangement to allow adjacent placement of at least two sub-picture elements.
16. The light field display of claim 15, wherein the geometric arrangement is one of a hexagonal shape, a square shape, and a rectangular shape.
17. The light field display of claim 1, wherein: each sub-picture element produces an optical output having a specific color, intensity, and spatial directionality.
18. The light field display of claim 1, wherein a size of each one of the multiple sub-picture elements is between about 10 microns and about 1,000 microns.
19. The light field display of claim 1, wherein the electronic circuits are configured to individually drive each one of the light emitting elements in each one of the multiple sub-picture elements.
20. The light field display of claim 1, wherein multiple sub-picture elements are all fabricated on the single, continuous semiconductor substrate.
21. The light field display of claim 1, wherein the single, continuous semiconductor substrate includes a single layer.
22. The light field display of claim 1, wherein the picture element includes: a first layer including

the light steering optical element, a second continuous layer including the array of light emitting elements, and a third layer disposed between the first layer and the second continuous layer, the third layer being optically transparent.

23. The light field display of claim 1, wherein the multiple sub-picture elements include: a first sub-picture element configured to produce the first color of light, a second sub-picture element configured to produce the second color of light, and a third sub-picture element configured to produce the third color of light, the first sub-picture element, the second sub-picture element, and third sub-picture element being disposed on the single, continuous semiconductor substrate.

24. The light field display of claim 1, wherein the first light emitting element has a dimension with a range between about 0.4 microns and 4 microns, the second light emitting element has a dimension with a range between about 0.4 microns and 4 microns, and the third light emitting element has a dimension with a range between about 0.4 microns and 4 microns.

25. A light field display for producing multiple views, comprising: a plurality of picture elements each formed from a single layer grown on a same, continuous semiconductor substrate; a backplane electronically connected with the plurality of picture elements and separate from the same, continuous semiconductor substrate, wherein the plurality of picture elements includes: a first light emitting element, the first light emitting element being configured to produce light at a first wavelength, a second light emitting element, the second light emitting element being configured to produce light at a second wavelength, the second wavelength being different from the first wavelength, a third light emitting element, the third light emitting element being configured to produce light at a third wavelength, the third wavelength being different from the first wavelength and the second wavelength, and a light detecting element being configured to capture light; and a light steering optical element configured to direct the light towards the light detecting element, wherein each one of the plurality of picture elements is configured to contribute to at least one of the multiple views, and wherein the backplane includes electronic circuits configured to drive the first light emitting element, the second light emitting element, and the third light emitting element.

26. The light field display of claim 25, wherein the first light emitting element includes a first group of adjacently located light emitting diodes (LEDs) formed at least in part of indium-gallium-nitride (InGaN) with a first composition of indium (In), wherein the second light emitting element includes a second group of adjacently located LEDs formed at least in part of InGaN with a second composition of In, the second composition of In being different from the first composition of In, and wherein the third light emitting element includes a third group of adjacently located LEDs formed at least in part of InGaN with a third composition of In, the third composition of In being different from the first composition of In and second composition of In.

27. The light field display of claim 26, wherein the electronic circuits are configured for individually driving each one of the LEDs in the first light emitting element, second light emitting element, and third light emitting element.

28. The light field display of claim 25, further comprising a plurality of light steering optical elements optically coupled with the plurality of picture elements for directing light produced by that one of the plurality of picture elements in a selected direction.

29. The light field display of claim 28, wherein the light steering optical element includes at least one of a microlens and a grating.

30. The light field display of claim 28, wherein, for each one of the plurality of picture elements, the light steering optical element corresponding to that picture element is configured for optimizing a chromatic aberration for a color of light produced by that sub-picture element.

31. The light field display of claim 25, further comprising: a first converter arrangement optically coupled with the first light emitting element and configured to convert light produced by the first light emitting element from the first wavelength to a first modified wavelength; and a second converter arrangement optically coupled with the second light emitting element and configured to convert light produced by the second light emitting element from the second wavelength to a

second modified wavelength.

32. The light field display of claim 31, wherein at least one of the first converter arrangement and second converter arrangement is formed at least in part of a composition including phosphorus.

33. The light field display of claim 31, wherein at least one of the first converter arrangement and second converter arrangement includes quantum dots.

34. The light field display of claim 33, wherein the first converter arrangement includes quantum dots of a first size, and the second converter arrangement includes quantum dots of a second size.

35. The light field display of claim 25, wherein the first light emitting element, second light emitting element, and third light emitting element are all fabricated on the same semiconductor substrate.

36. A light field display comprising: a picture element including multiple sub-picture elements, the multiple sub-picture elements including: an array of light emitting elements grown directly on a single, continuous semiconductor substrate, the array of light emitting elements being capable of producing a selected one of a first color of light, a second color of light, or a third color of light; and a light steering optical element configured to direct the first color of light, the second color of light, and the third color of light emitted from the array of light emitting elements in a same direction; and a backplane including a plurality of electronic circuits each electronically connected with one of the multiple sub-picture elements and configured to drive multiple light emitting elements of the multiple sub-picture elements.
