

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250259175

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

AGRAWAL; Aseem et al.

SYSTEMS AND METHODS FOR SEAMLESSLY PROCESSING TRANSACTIONS USING DISTRIBUTED LEDGER TECHNOLOGY IN A LEGACY SYSTEM INFRASTRUCTURE

Abstract

A computer-implemented method for seamlessly processing transactions using distributed ledger technology. The method may comprise: linking one or more conventional accounts hosted in a conventional banking infrastructure to one or more DLT-based client accounts hosted on a distributed ledger, wherein the DLT application comprises a routing address configured to be used in conventional transaction infrastructure using conventional communication protocols; storing one or more wallet identifications for the one or more DLT-based client accounts and a mapping of the one or more wallet identifications to the one or more conventional accounts hosted in the conventional banking infrastructure; exchanging a sequence of messages to execute an asset transfer and complete a transaction lifecycle, the sequence of messages based on the first asset type; updating the distributed ledger based on the asset transfer; and sending appropriate messages to clients.

Inventors: AGRAWAL; Aseem (Singapore, SG), CHHABRA; Chirdeep Singh (Singapore, SG), CHABANE; Karim Abdelkader (Hong Kong, CN)

Applicant: CITIBANK, N.A. (New York, NY)

Family ID: 85796910

Assignee: CITIBANK, N.A. (New York, NY)

Appl. No.: 19/197841

Filed: May 02, 2025

Related U.S. Application Data

parent US continuation 18596273 20240305 PENDING child US 19197841

parent US continuation 17498622 20211011 parent-grant-document US 11935052 child US

Publication Classification

Int. Cl.: **G06Q20/40** (20120101); **G06F16/27** (20190101); **G06Q20/36** (20120101); **G06Q20/38** (20120101)

U.S. Cl.:

CPC **G06Q20/401** (20130101); **G06F16/27** (20190101); **G06Q20/36** (20130101); **G06Q20/3829** (20130101); **G06Q2220/00** (20130101)

Background/Summary

TECHNICAL FIELD [0001] This application claims the benefit of priority as a continuation to U.S. patent application Ser. No. 18/596,273, filed Mar. 5, 2024, which claims the benefit of priority as a continuation to U.S. patent application Ser. No. 17/498,622, filed Oct. 11, 2021, the entirety of each of which is incorporated by reference herein.

TECHNICAL FIELD

[0002] This application relates generally to a single platform that enables processing single and multi-asset transactions using distributed ledger technology (DLT) while providing seamless integration with assets held on legacy infrastructure.

BACKGROUND

[0003] As the processing power of computers allows for greater computer functionality and the Internet technology era allows for interconnectivity between computing systems, many institutions are shifting towards DLT-based technology to store and maintain the integrity of transaction data as well as to achieve transactional efficiency and to address some of the limitations inherent in current infrastructure for financial transactions. Some of these limitations include (a) transfers of most financial assets involve delays and are usually not available 24×7; (b) fragmentation of ledgers and transfer protocols for different asset types introduce operational complexity both for clients and service providers; and (c) there is no generic infrastructure for making contingent or concurrent payments between two or more parties. While DLT-based storage methods may require more computational resources than conventional methods (e.g., a central database), the immutability of the data within the DLT enables operators to have peace of mind that the data in the DLT is accurate and may not be changed.

[0004] With DLT-based storage methods being in relative infancy, a vast majority of asset balances for traditional (non-crypto) assets are held on conventional (non-distributed) ledgers (e.g., a static database). Even if some users move part or all of their asset balances to a distributed ledger, at least some of their transactions may involve transfers to or from accounts which are held on conventional ledgers (i.e. “conventional accounts”). Transfers from and/or to such conventional accounts often involve steps which are different from steps involved in transferring assets between non-conventional accounts. Furthermore, users, especially institutional (non-individual), may have existing systems and processes designed to work with conventional ledgers, and there may be significant integration work, and process revision required for them to adopt DLT-based solutions even for a small part of their holdings. With regulatory frameworks and accounting policies on the treatment of assets held on DLT's still evolving across the world, institutional users operating in multiple jurisdictions may additionally need to undertake regulatory/accounting analysis before adoption of such solutions, and to establish that the asset on the distributed ledger (the ‘token’) is

not seen as a new security (just as any depository receipt is) issued by an issuer different from the issuer of the original asset. All these hurdles may have the impact of slowing down the adoption of DLT-based solutions by institutional users, except for specialized use cases involving a limited number of participants, where the benefits from the use case may justify changes to a limited number of existing systems by all of them to on-board the solution.

[0005] Existing solutions for DLT-based assets need to contend with the above issues, and may also suffer additional shortcomings. For example, solutions work well for entities which agree up front to accept the token; they would all be able to execute such transfers efficiently amongst themselves, (e.g., previous solutions may work well for a “closed user group”). However, when an entity receives a token from any of its counterparties, but is unable to find another counterparty within the “closed group” to immediately deploy it to, the entity may need to keep the token until it finds a counterparty to post it to. Inability to use the tokens immediately would lead to increased funding costs being borne by the entity. This further reduces the likelihood of adoption of the token. Another shortcoming is that many of the solutions are for single asset classes or just a single asset (USDC for USD cash). They therefore are not in a position to effect conditional or concurrent multi-asset transfers.

[0006] Users may not be able to transfer funds between traditional accounts and cryptographic wallets seamlessly because these account types use incompatible protocols and processes. For instance, in the DLT-based world, wallets may be accessed through cryptographic keys or a wallet interface. In the conventional account world, accounts are accessed via conventional interfaces (graphical user interface or API) or via channels like SWIFT over which messages in standard (e.g., conventional) formats like ISO15022 or ISO20022 may be sent. In the current environment, these communication protocols and channels are distinct and don't support using an integrated approach. Consequently, two users that have DLT-based and conventional accounts respectively may not be able to execute transactions between each other seamlessly, even if they desire to do so.

SUMMARY

[0007] For the aforementioned reasons, there is a need for a method and system that enables users to instruct standard transactions on their DLT-based account using conventional interfaces, not needing to undertake any operational or technical enhancements to access basic details of their transactions and balances across one or more asset classes (in which they hold balances), and being able to move assets to and receive assets from conventional accounts (for one or more asset classes) seamlessly and without adding any material processing time. In other words, the method and system should, in addition to providing a wallet and cryptographic key access, give clients the option to operate their DLT wallets in the same way as conventional accounts so that usage of the new platform can be completely transparent from an on-boarding and operating perspective, for transactions types which are available in the conventional world.

[0008] The methods and systems described herein aim to provide functionality that enables the above. The method may use an intermediary application that is set up with its own routing address used in conventional transaction infrastructure (e.g. BIC code) to and from which clients can route messages using conventional protocols (e.g. via SWIFT). As described herein, references to a BIC code should be understood to mean a routing address used in a conventional transaction infrastructure. Further, as described herein, references to SWIFT should be understood to mean any financial message service providers. Similarly, a SWIFT authentication key should be understood to be an authentication key for any financial message service in use. The intermediary application may link an account in the conventional infrastructure (e.g. cash account provided by a bank, or securities account provided by a custodian) to one or more client accounts on the DLT (a.k.a. wallets), with the balance on the conventional account matching the aggregate of client balances on the linked wallets for that particular asset; with any external transfer from the conventional account only permitted to be initiated by the intermediary application. In some cases, a conventional account may link to multiple accounts, in which case the conventional account may be an omnibus

account. Every DLT wallet may have a wallet identification. For every DLT wallet identification, the intermediary application may maintain a mapping to one or more client-specific conventional account identifications (when a conventional account links to a single wallet, then the identification of that conventional account maps to the wallet identification). For example, wallets may be mapped to conventional accounts in a many-to-one or a one-to-one mapping for any given asset (one wallet would only map to one conventional account for UST holdings, one wallet would only map to one cash account for USD, etc.). When the conventional account is an omnibus account mapping to multiple wallets, then the conventional account identification mapped to wallet identifications would not correspond to any account in the conventional infrastructure. In this case, the DLT may act as a sub-ledger and maintain the golden source of client balances which may not be available in conventional infrastructure.

[0009] The intermediary application may have the ability to process conventional messages to carry out asset transfers within the DLT, as well as from conventional accounts onto the DLT, and from the DLT to conventional accounts, as well as to process other conventional messages involved in the transaction lifecycle. As described herein, such processing may include processing of received messages, as well as creation of any new messages. The intermediary application may be permissioned to manage client's cryptographic keys mapped against their unique SWIFT authentication key and/or BIC code. The intermediary application may have the ability to generate standard transaction status messages used in conventional transactions, standard debit and credit confirmation, standard end-of-day balance and transaction reports, and to send these messages via conventional messaging statuses on the wallet and via conventional messaging. The intermediary application may have the capability to let clients use conventional messaging/means and wallets for different components of the same transaction. A cryptographic wallet may provide a private key to the intermediary application, allowing wallet holders one channel to convey instructions to the platform. Thus, the intermediary application can enable all the features listed earlier.

[0010] A method for seamlessly processing transactions using distributed ledger technology, comprising: linking, by a distributed ledger technology (DLT) application executed or hosted by one or more processors, one or more conventional accounts hosted in a conventional banking infrastructure (i.e., various kinds of accounts provided by licensed financial institutions such as central banks, commercial banks, custodians, payment banks, etc.) to one or more DLT-based client accounts hosted on a distributed ledger, wherein a balance on each of the one or more conventional accounts matches an aggregate of client balances on one or more DLT-based client accounts for an asset of a first asset type, and wherein any external transfers originating at one of the one or more conventional accounts are only permitted to be initiated by the DLT application, wherein the DLT application comprises a routing address configured to be used in conventional transaction infrastructure to and from which client devices and/or financial institutions can route messages using conventional communication protocols; storing, by the DLT application, one or more wallet identifications for the one or more DLT-based client accounts and a mapping of the one or more wallet identifications to the one or more conventional accounts hosted in the conventional banking infrastructure; wherein the DLT application is permissioned to manage cryptographic keys for the one or more DLT-based client accounts mapped against corresponding authentication keys and/or routing addresses; wherein the DLT application is configured to receive, process, create, and send, to and from client devices, conventional messages for asset transfer between the one or more conventional accounts and the one or more DLT-based client accounts or between the one or more DLT-based client accounts, the asset transfers of a plurality of asset types; wherein the DLT application is configured to receive, process, create, and send, to and from financial institutions, messages for asset transfers; exchanging, by the DLT application, a sequence of messages to execute an asset transfer and complete a transaction lifecycle, the sequence of messages based on the first asset type; and updating, by the DLT application, the distributed ledger based on the asset transfer. Updating the distributed ledger may include updates both during the asset transfer and at

the end of the asset transfer (e.g., in the process of detokenization, locking a token initially, and/or burning a token subsequently).

[0011] A system for seamlessly processing transactions using distributed ledger technology, the system comprising: an application server comprising a processor executing or hosting a distributed ledger technology (DLT) application, the processor configured to execute or host the DLT application to: link one or more conventional accounts hosted in a conventional banking infrastructure (i.e., various kinds of accounts provided by licensed financial institutions such as central banks, commercial banks, custodians, payment banks, etc.) to one or more DLT-based client accounts hosted on a distributed ledger, wherein a balance on each of the one or more conventional accounts matches an aggregate of client balances on one or more DLT-based client accounts for an asset of a first asset type, and wherein any external transfers originating at one of the one or more conventional accounts are only permitted to be initiated by the DLT application, wherein the DLT application comprises a routing address configured to be used in conventional transaction infrastructure to and from which client devices and/or financial institutions can route messages using conventional communication protocols; store one or more wallet identifications for the one or more DLT-based client accounts and a mapping of the one or more wallet identifications to the one or more conventional accounts hosted in the conventional banking infrastructure; wherein the DLT application is permissioned to manage cryptographic keys for the one or more DLT-based client accounts mapped against corresponding authentication keys and/or routing addresses; wherein the DLT application is configured to receive, process, create, and send, to and from client devices, conventional messages for asset transfers between the one or more conventional accounts and the one or more DLT-based client accounts or between the one or more DLT-based client accounts, the asset transfers of a plurality of asset types; wherein the DLT application is configured to receive, process, create, and send, to and from financial institutions, messages for asset transfers; exchange a sequence of messages to execute an asset transfer and complete a transaction lifecycle, the sequence of messages based on the first asset type; and update the distributed ledger based on the asset transfer.

[0012] In one embodiment, a method for tokenization comprises establishing, by a DLT-application executed or hosted by an application server, a connection between the DLT-application and a second application (or group of applications) executed or hosted by server(s) maintained by a financial institution, the DLT-application storing a plurality of digital wallets connected to a distributed ledger and the second application storing a plurality of conventional accounts linked to the plurality of digital wallets (i.e., the DLT-application maintains a mapping of the plurality of wallets to the plurality of conventional accounts); responsive to a transaction request from a first client device, receiving, by the DLT-application from the second application, confirmation of a credit into the recipient account; responsive to receiving the confirmation, transmitting, by the DLT-application to one or more computing devices of the distributed ledger, instructions to update the distributed ledger crediting a destination account based on the transaction; and sending, by the DLT application, a credit confirmation, end of day messages, and other status messages to the first client device.

[0013] In another embodiment, a system for tokenization, the system comprises an application server comprising a processor executing a DLT-application, the processor configured to execute or host the DLT-application to establish a connection between the DLT-application and a second application executed by server(s) maintained by a financial institution, the DLT-application storing a plurality of digital wallets connected to a distributed ledger and the second application storing a plurality of conventional accounts linked to the plurality of digital wallets (i.e., the DLT-application maintains a mapping of the plurality of wallets to the plurality of conventional accounts); responsive to a transaction request from a first client device, receive, from the second application, confirmation of a credit into the recipient account; responsive to receiving the confirmation, transmitting, to one or more computing devices of the distributed ledger, instructions to update the

distributed ledger crediting a destination account based on the transaction; and sending, by the DLT application, a credit confirmation, end of day messages, and other status messages to the first client device.

[0014] In another embodiment, a method for detokenization comprises establishing, by a DLT-application executed or hosted by an application server, a connection between the DLT-application and a second application executed by server(s) maintained by a financial institution, the DLT-application storing a plurality of digital wallets connected to a distributed ledger and the second application storing a plurality of conventional accounts linked to the plurality of digital wallets; receiving, by the DLT-application, a transaction request from a first client device identifying a token; freezing, by the DLT-application, the token; responsive to receiving the transaction request, transmitting, by the DLT-application, a deliver instruction identifying the source account and a destination account to the second application; receiving, by the DLT-application from the second application, confirmation of a debit from the source account; and responsive to receiving the confirmation from the second application, transmitting, by the DLT-application to one or more computing devices of the distributed ledger, instructions to update the distributed ledger debiting the source account based on the token; and sending, by the DLT application, a debit confirmation, end of day messages, and other status messages to the first client device.

[0015] In another embodiment, a system for detokenization, the system comprises an application server comprising a processor executing or hosting a DLT-application, the processor configured to execute or host the DLT-application to establish a connection between the DLT-application and a second application executed by server(s) maintained by a financial institution, the DLT-application storing a plurality of digital wallets connected to a distributed ledger and the second application storing a plurality of conventional accounts linked to the plurality of digital wallets; receive a transaction request from a first client device identifying a token; freezing, by the DLT-application, the token; responsive to receiving the transaction request, transmit a deliver instruction identifying the source account and a destination account to the second application; receiving, by the DLT-application from the second application, confirmation of a debit from the source account; and responsive to receiving the confirmation, transmit, to one or more computing devices of the distributed ledger, instructions to update the distributed ledger debiting the source account based on the token; and send a debit confirmation, end of day messages, and other status messages to the first client device.

[0016] In another embodiment, a method for token transfers comprises receiving, by a DLT-application, a transaction request from a first client device, the transaction request identifying one or more tokens of one or more distinct assets; validating, by the DLT-application, the transaction request; receiving, by the DLT-application, matching instructions from a second client device; validating, by the DLT-application, the matching instructions; matching, by the DLT-application, the transaction request and the matching instructions; waiting, by the DLT-application, for any specified pre-conditions for the transaction request to be satisfied; settling, by the DLT-application, the transaction; optionally, transmitting, by the DLT-application, messages to a financial account for crediting or debiting the appropriate conventional accounts based on the transaction; and sending, by the DLT application, a debit or credit confirmation, end of day messages, and other status messages to the first client device and/or a second client device associated with the asset transfer.

[0017] In another embodiment, a system for token transfers, the system comprises an application server comprising a processor executing or hosting a DLT-application, the processor configured to receive a transaction request from a first client device, the transaction request identifying one or more tokens of one or more distinct assets; validate the transaction request; receive matching instructions from a second client device; validating, by the DLT-application, the matching instructions; match the transaction request and the matching instructions; waiting, by the DLT-application, for any specified pre-conditions for the transaction request to be satisfied; settle the

transaction; optionally, transmit messages to a financial account for crediting or debiting the appropriate conventional accounts based on the transaction; and send a debit or credit confirmation, end of day messages, and other status messages to the first client device and/or a second client device associated with the asset transfer.

[0018] It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0019] The accompanying drawings constitute a part of this specification, illustrate an embodiment of the invention, and together with the specification, explain the invention.

[0020] FIG. 1 illustrates an implementation of a computer system for seamlessly processing transactions using distributed ledger technology, according to an embodiment.

[0021] FIG. 2 illustrates a flowchart of a process for tokenization, according to an embodiment.

[0022] FIG. 3 illustrates a flowchart of a process for detokenization, according to an embodiment.

[0023] FIG. 4 illustrates a flowchart of a process for token transfer, according to an embodiment.

DETAILED DESCRIPTION

[0024] Reference will now be made to the exemplary embodiments illustrated in the drawings, and specific language will be used here to describe the same. It will nevertheless be understood that no limitation of the scope of the invention is thereby intended. Alterations and further modifications of the inventive features illustrated here, and additional applications of the principles of the inventions as illustrated here, which would occur to a person skilled in the relevant art and having possession of this disclosure, are to be considered within the scope of the invention.

[0025] FIG. 1 illustrates various components of a system **100** that enables users to instruct standard transactions on their DLT-based account using conventional and DLT application-specific interfaces, in accordance with an embodiment. The system **100** provides a non-limiting example of a computer system that contains a DLT application with a BIC code to which a client device may route messages via a conventional messaging protocol (e.g., SWIFT). The DLT application may store a plurality of wallets for individual users. The DLT application may be able to communicate with a series of in-network and out of network distributed ledgers to maintain the balances for each of the stored wallets and enable the user to perform transactions with conventional user accounts.

[0026] The system may include a financial market infrastructure (“FMI”) **30**. The FMI **30** may include depositories and central banks and include a series of servers and processors that coordinate to facilitate transactions. The FMI **30** may enable different financial institutions to settle financial obligations between different user accounts and/or financial entities (e.g., user accounts of the same or different banks). However, it should be noted that transfers do not always need to go through the FMI **30**.

[0027] The system may include transferor/transferee accounts **10-13**. While only two transferor/transferee accounts are shown in FIG. 1, the system **100** may include any number of such accounts. The transferor/transferee accounts **10-13** may be accounts from which assets are transferred and/or accounts that receive such assets. A transferor account may be an account in which an asset is transferred to a conventional account stored in the set of applications **40** and a transferee account may be an account to which an asset is transferred from a conventional account in the set of applications **40**. The transferor/transferee accounts **10-13** may be conventional user financial accounts (e.g., accounts stored in a static database) that are stored on the servers of their respective financial institutions and that keep records of asset ownership by the respective account's owners. In one non-limiting example, the transferor/transferee account **10** may be a conventional

securities account and the transferor/transferee account **13** may be a conventional cash account (e.g., an account for holding fiat currency balances such as a Demand Deposit Account offered by a commercial bank). The accounts may perform asset transfers through the FMI **30** or through another network or infrastructure.

[0028] In some cases, to perform any transfers, the transferor/transferee accounts **10** or **13** may transfer the securities or money to accounts that are stored on one or more financial institutions' set of financial applications **40** or **50**. For instance, the financial institutions' sets of financial applications **40** and **50** may each include one or more applications for different financial assets that store conventional accounts **41-44**. The conventional accounts **41** and **42** may be securities accounts and conventional accounts **43** and **44** may be cash accounts. While only four accounts are shown, the sets of financial applications **40** and **50** may include any number of accounts for any type of asset. The conventional accounts **41-44** can store assets received from the transferor/transferee accounts **10** and **13** and transfer assets to such accounts. A DLT application **60** may have established connections with the sets of financial applications **40**, **50**, and/or any number of other applications of other financial institutions.

[0029] In one example, the transferor/transferee account **10** may send an instruction **21** to the FMI **30** for an asset transfer to/from an application-linked conventional account **41** (e.g., an application linked to the DLT application **60**) of the set of financial applications **40**. As described herein, actions by transferor/transferee accounts **10-13** should be understood to mean actions by the owner or authorized operator of the respective account. The FMI **30** may then send one or more instructions **31** that correspond to the instruction **21** to the conventional account **41**. The set of financial applications **40** may then transmit one or more instructions **32** to the FMI **30** confirming the status of the transfer to account **41**; the FMI may in turn transmit a corresponding instruction **22** to transferor account **10**. The instructions and messaging of the sets of instructions **21**, **22**, **31**, and **32** may be transmitted using conventional communication channels such as SWIFT using standards like ISO15022 or ISO20022.

[0030] In some cases, a transferor account and/or a transferee account may be stored on the set of financial applications **40** (i.e., transferors and transferees hold accounts at the financial institution that has a set of financial applications that are coupled with the DLT application **60**). In such cases, transactions may be performed without transmitting any messages through the FMI **30**.

[0031] The sets of financial applications **40** and **50** may be applications that are hosted by servers or other computing devices of different financial institutions. For example, the set of financial applications **40** may store accounts for different types of assets (e.g., securities accounts **41** or **42**, or cash or demand deposit accounts **43** or **44**). The set of financial applications **40** may also include other applications **45** which may include accounting modules, sanctions screening, reconciliation report uploading, reference and pricing data for assets, etc. The DLT application **60** may integrate with the other applications **45** to avoid duplicating their functionality within the DLT application **60**. In another embodiment, the DLT application **60** would build some or all these modules itself or rely on third party modules instead of integrating with the other application **45**.

[0032] As briefly mentioned above, conventional securities account **41** and **42** may be linked to the DLT application **60**. The accounts **41** and **42** may hold one or more than one kind of security. One or more of the conventional securities accounts **41** and **42** may serve as omnibus accounts (wherein the holdings in these accounts map to the holdings of multiple underlying user accounts; in which case a DLT network **90** may operate as a sub-ledger for balances held by client wallets, with the aggregate balances matching the assets held in the corresponding omnibus accounts from amongst the accounts **41** and **42**). In other cases, one or more of the accounts **41** and **42** may belong to individual end clients (e.g. clients operating client device **70** or client device **80**, described below), and map one-to-one to the account balances held on the DLT network **90** (e.g., the DLT application **60** may maintain DLT wallets **61-63** that maintain a record of the current balance for different client accounts (e.g., **41** and **42**)). The DLT application **60** may be authorized to convey instructions

to accounts **41** and **42**, and to receive status messages and other notifications on these accounts. In some instances, the accounts **41** and **42** may have restrictions so that transfers to other conventional accounts can only be instructed via the DLT application **60**. The cash accounts **43** and **44** may operate similarly to the accounts **41** and **42**, but may store balances for cash instead of securities. In some embodiments, securities accounts may be omnibus accounts, as described herein, and cash accounts may be per client accounts.

[0033] The DLT application **60** may be an application that is configured to accept and process one or more of tokenization, detokenization, and token transfer instructions. As described herein, tokenization refers to creation of an asset on the distributed ledger. In the case of conventional securities or cash, this is on the back of an asset received in a conventional ledger. In the case of omnibus accounts represented on a conventional ledger, a credit into an omnibus account leads to a credit into one of the multiple wallets the balances of which together add up to the balance in the omnibus account. Detokenization refers to destroying an asset on the distributed ledger. In the case of cash and conventional securities, this is usually accompanied by debiting of an asset from a token in a conventional ledger (the sequence of the two debits could change depending on the process). These processes are described in detail below with respect to FIGS. 2 and 3. Token transfers refers to transferring tokens from one account to another account.

[0034] The DLT application **60** may, in addition, connect with the conventional accounts **41-44** and other conventional financial applications (e.g., other applications **45**). The DLT application **60** may be stored on a server external to any financial institution network and operate as an intermediary application, a ledger (e.g., a distributed ledger), middleware, or a combination of middleware and a ledger between client devices (e.g., the client device **70** or the client device **80**) and financial institution applications (e.g., the set of financial applications **40** or the set of financial applications **50**). For instance, the DLT application **60** may have or be associated with its own routing address (e.g., a BIC code **64**) that can be used to route messages in a conventional financial network. When performing transactions, client devices may include the BIC code **64** in a message header to indicate to route the messages for the transaction to the DLT application **60**.

[0035] The DLT application **60** may include DLT wallets **61**, **62**, and **63**. The DLT application **60** may include any number of wallets. The DLT wallets **61**, **62**, and **63** may maintain the balances of the assets that their respective owners have on the DLT network **90** and/or another distributed ledger that may be outside of the financial institution network. The DLT application **60** may update the DLT wallets **61**, **62**, and **63** periodically based on tokenization, detokenization, token transfers or any other authorized transactions that the clients perform through their respective accounts.

[0036] For assets for which the DLT network **90** operates as a sub-ledger, the DLT wallets **61**, **62**, and **63** may be the ‘golden source’ of client balances given the standard immutability of distributed ledger technology. The DLT wallets **61**, **62**, and **63** may be mapped (e.g., have a stored relationship in a relational database) to one of more account numbers for the different assets. In cases where a client-specific conventional account is used (in the set of financial applications **40** or the set of financial applications **50**), the conventional account number may be mapped to the wallet (e.g., mapped to an identification of the wallet). For all assets where omnibus accounts are used (in the set of financial applications **40** or the set of financial applications **50**), the same client account number could be used (but there may be different numbers for different omnibus accounts) to track sub-ledger balances across different conventional omnibus accounts. This account number, like any conventional account, along with the BIC code **64** for the DLT application **60** can be used to route transactions correctly. This (same) client account number could also be the wallet identification, or may have a one-to-one mapping with the wallet identification.

[0037] Advantageously, because of the client account number assigned to each wallet, the BIC code assigned to the DLT application **60**, and the ability of the DLT application **60** to process incoming conventional messages sent via the Swift network and to generate outgoing messages, clients can configure new accounts on their internal systems using the BIC code **64** and a client account

number mapping to their respective wallets (with such mapping being stored in the DLT application **60**) just as they would for any other conventional account they hold at a conventional financial institution. For example, client devices may communicate with the DLT application **60** using the BIC code **64** and the client account number mapping to DLT wallets **61**, **62**, or **63**. This would typically apply in the case of institutional clients which may maintain accounts at multiple financial institutions and may use the BIC code and account number to route their instructions to the appropriate destination. The DLT application **60** has further advantages as described above.

[0038] In some cases, the operators of the client devices **70** and **80** might be the same as the owners of the transferor/transferee accounts **10** or **13** (e.g. if “Client I” owns the conventional account **10**, and moves assets from the conventional account **10** to the securities account **41** for credit to its wallet on the DLT application **60**, then it also plays the role of transferor).

[0039] The sets of financial applications **40** and **50** may communicate with the DLT application **60** via sets of instructions **46** and **47** using conventional messaging protocols (e.g., ISO15022 messages sent over a SWIFT network or other standard interfaces (e.g., API's) made available by set of financial applications **40** to its clients). The sets of instructions **46**, **47**, may be asset transfer instruction messages, status messages, credit or debit confirmations, intraday or end of data balance updates, etc.

[0040] The sets of financial applications **40** and **50** may also communicate with the DLT application **60** via custom messaging methods via sets of instructions **48** and **49**. The sets of instructions **48** and **49** may have been developed or configured to integrate the DLT application **60** with the set of financial applications **40**. For example, the sets of instructions **48** and **49**, may include messages to screen for sanctions, retrieve security data attributes, or to reconcile aggregate of balances on DLT wallets and on conventional accounts, etc. The level and functionality of the integration of custom messaging between the DLT application **60** and different financial applications may vary by financial institution (e.g., the financial institution running the set of financial applications **40** may have established a custom messaging protocol with the DLT application **60** but the financial institutions running the set of financial applications **50** may only rely on a conventional messaging protocol, and would thus not use custom messaging except for integration with a smaller set of internal applications). In another embodiment, a financial institution may send sets of instructions **46** or **47**, referred to earlier, via custom messaging. As described herein, the sets of instructions **46**, **47**, **48**, and **49** that are exchanged between the DLT application **60** and the set of financial applications **40** are exchanged only with the appropriate or applicable application (e.g., internal application or sub-application) or interface of the set of financial applications **40** and/or the DLT Application **60**.

[0041] In initiating a transaction that is facilitated by the DLT application **60**, a user may access one of two categories of user interfaces (e.g., a conventional user interface **71** or a user interface **72** for a cryptographic wallet) at a client device **70**. Similarly, client device **80** could use a conventional user interface **81** or a user interface **82** for a cryptographic wallet. For example, a user may access a financial institution-provided user interface **71** that the client device **70** may present in response to executing a client application that was provisioned to the client device **70** or via a browser. The user interface **71** may be provided by the financial institution at which the client maintains its securities or cash accounts or sourced by the client otherwise (e.g., developed internally by the group entity (e.g., a business or organization) that owns or otherwise operates the client device or sourced from other providers) for viewing account balances or activity, initiating transaction instructions, receiving end-of-period or intra-period (e.g. intra-day reports), monitoring status of earlier requests, carrying out other account-related operations, etc. In some cases, there may be multiple financial-institution provided (or client-sourced) interfaces **71** for accessing different assets or for carrying out different operations related to the same asset. For instance, one interface may be configured to present cash balances, another interface may be configured to present securities balances, etc. Alternatively, one interface may be used to initiate transactions, and

another may be used to retrieve and reconcile end of day balances. Such interfaces may allow a user at the client device **70** to configure standard routing details for messages to send to their respective financial institutions (e.g. using BIC code and account number for their cash or securities accounts), and then exchange messages with their financial institution using conventional messaging protocols (including but not limited to ISO15022, ISO20022 messages sent via Swift, or via API's). In one embodiment, the user interfaces route these messages to the DLT application **60** using the client account number and the BIC code of the DLT application **60**, and validates received messages from the DLT application **60** using the same BIC code.

[0042] When using interfaces **71** or **81**, the client devices **70** or **80** may communicate with the DLT application **60** via sets of instructions **73**, **74**, **83**, and **84**. The sets of instructions **74** and **84** are instructions sent by the client devices **70** and **80**, respectively, and may be instructions to initiate standard asset transfers (i.e., asset transfers types available in conventional networks e.g., cash transfers initiated using MT202). The sets of instructions **73**, **74**, **83**, and **84** may represent groups of instructions or messages that are sent via a conventional protocol between interfaces **71** or **81** and the DLT application **60**. Such sets of instructions may include any number of exchanged instructions. The standard asset transfer requests may also be used to initiate detokenization (i.e., destroy a token and transfer the destroyed token's underlying asset to a conventional account that is unlinked from the DLT application (e.g., transferor/transferee accounts **10** or **13**)). In operation, the DLT application **60** may be authorized by the different account owners to send and receive conventional sets of instructions to various financial institutions on the account owners' behalf. In cases in which a user does not wish to provide the DLT application **60** with authorization to send such sets of instructions and the DLT application **60** has settings that indicate it is not permitted to transmit sets of instructions for the user, the DLT application **60** can still be configured to receive the sets of instructions **73** and **83** on the user's behalf.

[0043] In some cases, the sets of instructions **73** and **83** may represent the sets of instructions received by clients as described above, and may include messages with status updates and EOD messages for various transactions. Advantageously, the sets of instructions **73** and **83** may even be related to transactions that are initiated via one of the application interfaces **72** or **82** (i.e. not just to transactions initiated via the sets of instructions **74** and **84**). Accordingly, the DLT application **60** may allow clients the flexibility to specify preferences as to which sets of instructions they receive, and via which channels. A benefit of this feature is that while some advanced users may initiate non-standard or standard transfers (via DLT Application interface **72**, using the sets of instructions **76**), settlement teams can receive confirmations via conventional channels (e.g., via the sets of instructions **73**).

[0044] For example, if an entity is an organization, it is not uncommon to have different employees that have different responsibilities in the transaction life cycle, including transaction booking (booking transactions/accepting transactions initiated by counterparty) and reconciliation (based on transaction confirmations and/or EOD or other balance or transaction statements). Thus, some employees responsible for transaction booking may continue using the conventional user interfaces **71** or **81** to initiate standard transactions without changing transaction protocols, some may adopt new interfaces (e.g., the application interfaces **72** or **82**) to initiate standard or non-standard transactions (for the avoidance of doubt, use of application interfaces **72** and **82** could be referred to as using a digital wallet that is stored in application **60** or in the client devices **70** or **80**), but the employees responsible for reconciliation could still choose to use existing protocols for their reconciliations (messages received in the sets of instructions **73** or **83**). Even in the case of non-standard transactions (e.g. transfer out Security A and receive Security B at the same time), the user may receive standard messages on transaction status for each individual asset during the transaction lifecycle (e.g. a credit message for Security B, and a debit message for Security A).

[0045] The client devices **70** or **80** may communicate with the DLT application **60** from application interface(s) **72** or **82**. The application interface(s) **72** and **82** may be one or more custom

interface(s) provided by the DLT application **60** for clients to view wallet balances or activity, initiate transactions, receive end-of-period or intra-period (e.g. intra-day reports), monitor status of earlier requests, and carry out other account-related operations. The DLT application **60** may provide multiple such interfaces, including but not limited to Graphical User Interfaces (GUI) and API's (also, notifications from the DLT application **60** to client devices **70** and **80** could also be sent via pre-specified channels, e.g. email). The application interface(s) **72** and **82** may also transmit sets of instructions **76** and **86** to the DLT application **60** to initiate and cryptographically sign instructions for standard transfers (which would include outgoing-transfer instructions for detokenization and incoming-transfer instructions for tokenization in addition to outgoing and incoming transfer instructions for assets to other wallets) or non-standard asset transfers (defined further) as well as accept "allegements" as is described in detail below. Non-standard asset transfers are those not available via conventional networks, (e.g. transfer out Security A and receive Security B at the same time; or transfer out a specified asset if a defined condition is satisfied). As described herein, allegements may mean that instead of having to enter all details of a transaction which would be matched with details entered by the other counterparty/counterparties, the party is shown details entered by others (via the application interface **72**). The party can then choose to accept, modify or reject the transaction.

[0046] In the same embodiment, the application user interfaces **72** and **82** may allow the client devices **70** and **80** to receive messages in the sets of instructions **75** and **85** from the DLT application **60**. Examples of such messages include, but are not limited to, status messages for requests initiated via the sets of instructions **76** or **86** and EOD messages, as well as copies of some or all messages which could potentially be sent by the DLT application **60** in the sets of instructions **73** or **83** (e.g., if an EOD MT940 is sent in the sets of instructions **73**, the same may be visible via the application interface **72** as well). As described herein, the sets of instructions **73**, **74**, **75**, **76**, **83**, **84**, **85**, and **86** that are exchanged between the DLT application **60** and the interfaces **71**, **72**, **81**, and **82** are exchanged only with the appropriate or applicable application (e.g., internal application or sub-application) or interface of the DLT Application **60**.

[0047] Optionally, the application user interfaces **72** and **82** may be used to send outgoing-transfer instructions (to trigger tokenization) to the transferor/transferee accounts **10** or **13** or to instruct incoming-transfer instructions (in the case of detokenization) to the transferor/transferee accounts **10** or **13** if the client of the DLT application **60** is the same as the transferor or transferee, or is otherwise authorized to instruct on behalf of the transferor or transferee.

[0048] The DLT application **60** may communicate and update the DLT network **90** as users perform transactions between each other. The DLT network **90** may be a network of validating nodes (e.g., computing devices) and a distributed ledger that maintains a record of the state and balances of wallets (e.g., the wallets **61-63** that are stored by the DLT application **60**). The DLT application **60** may communicate with the DLT network **90** via sets of instructions **91** and **92**. For example, the DLT application **60** may update DLT network **90** by transmitting messages in the sets of instructions **91** to the DLT network **90** with updates on the state and balance of the wallets **61-63**. The DLT network **90** may transmit the sets of instructions **92** to the DLT application **60** to provide the DLT application **60** with the necessary data to complete an operation, process or instruction, and/or to provide the DLT application **60** with the necessary data from the ledger for the DLT application **60** to present to a user (e.g., to present the current holdings in the wallets **61-63** to their respective owners).

[0049] In some cases, the DLT application **60** may maintain wallets to access other DLT networks outside of the DLT network **90**. For example, the DLT application **60** may maintain wallets to access DLT network **93**, which may be a DLT network outside the DLT application **60**'s trust network/zone. The DLT network **90** may connect to the DLT network **93** to interact with the ledgers for other applications (and the clients connecting to these applications) outside the trust zone. This is to make sure that the applications (e.g., the applications that communicate and/or

manage each distributed ledger) and messages and tokens of each of the applications can flow amongst each other (e.g., among the connected application) and can interoperate.

[0050] For instance, the DLT network **90** may exchange sets of instructions **94, 95**, with DLT network **93** or with nodes of the same DLT network **90** but outside of the DLT application **60**'s trust network. Accordingly, the sets of instructions **94, 95**, and the underlying mechanisms act as an inter-DLT bridge that enable interoperability.

[0051] As described herein, the system **100** may include components and applications that conventional systems use to process transactions as well as non-conventional components that are described herein. For example, conventional systems may include transferor/transferee accounts **10-13**, FMI **30**, sets of instructions **31** and **32**, and sets of financial applications **40** and **50**. The components that enable the systems and methods described herein and are not present in conventional systems, however, include the DLT application **60**, the wallets **61-64**, the BIC code **64**, the application interfaces **72** and **82** (including channels or protocol that facilitate transfer of the sets of instruction **75, 76, 85**, and **86**), and integration of the DLT application **60** with the other applications **45** (via the sets of instructions **47-49**). Accounts **41-44** may be reconfigured to operate with DLT application **60**, but may otherwise be standard accounts. For example, the accounts **41-44** may be set up to accept incoming instructions from the BIC for the DLT Application **60**, send outgoing instructions to the BIC for the DLT application **60**, restrict (e.g., disallow) outgoing payment instructions originating from any other applications in the set of financial applications **40**, etc.

[0052] FIG. **2** illustrates a flowchart depicting operational steps for tokenizing a transaction, according to an embodiment. The method **200** describes how a DLT-enabled application (DLT application) can facilitate a transaction with a conventional account and keep a record of the transaction on a distributed ledger. The DLT application may be the DLT application **60**, shown and described with reference to FIG. **1**. The method **200** is described below with reference to components (e.g., the FMI **30**, the set of financial applications **40**, and the DLT application **60**) of the system **100** as the system **100** is described with reference to FIG. **1** above. However, it should be noted that the method **200** may be performed by any number of components. Furthermore, other configurations of the method **200** may comprise additional or alternative steps, or may omit one or more steps altogether.

[0053] The DLT application may store a plurality of digital wallets connected to a distributed ledger and the second application may store a plurality of conventional accounts linked to the plurality of digital wallets. Additionally, the DLT application may store a mapping of the digital wallets connected to the distributed ledger to the plurality of conventional accounts.

[0054] At step **202**, the FMI **30** may receive a transaction request from a first client device. The transaction request may be a request to deliver an asset (e.g., a cash or securities asset) from a source account at a financial institution to a destination account on a distributed ledger. The transaction request may include identifications of the source account, a recipient account (e.g., an account hosted by the set of financial applications **40**), and the ultimate destination account. The transaction request would be sent using standard asset-specific messages communicated over conventional messages channels (e.g. sets of instructions **31** or **32**). Examples of asset-specific messages would include MT542 for securities and MT202 for cash. Such message formats usually allow specification of the source and recipient accounts, and include additional fields which could be used to specify the ultimate beneficiary, i.e. the ultimate destination account. The FMI **30** may receive the transaction request from a server of the financial institution that hosts the transferring account. In some cases, the FMI **30** may receive the transaction from the server after the server carries out a series of validations and checks according to its own internal policies (e.g., balance checks and sanctions screening) and then routes the request to the FMI **30** using conventional messaging.

[0055] Optionally, at step **204**, the DLT application **60** may receive a "receive instruction" or a

“credit pre-advice” from a second client device using conventional messaging (e.g., the sets of instructions **74**) or custom messaging (e.g., the sets of instructions **76**) depending on the configuration of the established communication channel. The DLT application **60** may receive the instruction or the credit pre-advice based on the type of asset that is being transferred. The receive instruction may include identifiers of the source account and the destination account (which would correspond to the ultimate destination account in the previous step. This corresponds to an individual wallet) and indicate the asset being transferred from the source account to the destination account. In some cases, the receive instruction may also include a BIC code of the DLT application **60** that enables the second client device to communicate with the DLT application **60** using a SWIFT or another conventional communication protocol.

[0056] Optionally, at step **206**, the DLT application **60** may carry out any necessary validation and then create and send a new “receive instruction” to the set of financial applications **40**. The “receive instruction” that the DLT application **60** creates may be distinct from the original “receive instruction” received from the client; that instruction was sent by the authorized client to DLT application. The new receive instruction may be sent by the DLT application **60**, which is authorized to send instructions to one or more accounts maintained in the set of financial applications **40**. This new receive instruction may set the source account the same as in the original receive instruction, but would set the destination account as the account in the set of financial applications **40** which maps to the wallet for the asset in question, and may also specify the ultimate destination account, which would be the destination account in the original receive request. The DLT application **60** may send the receive instruction to the set of financial applications **40** using conventional messaging or custom message depending on the configuration of the established communication channel between the DLT application **60** and the set of financial applications **40** (e.g., via the sets of instructions **47** or **49**).

[0057] Optionally, at step **208**, the set of financial applications **40** may validate the “receive instruction” that it receives from the DLT application **60**. The set of financial applications **40** may do so using internal policies with various rules indicating how to validate such receive instructions. Upon validation, the set of financial applications **40** may route the receive instruction to the FMI **30** using a conventional messaging protocol.

[0058] Optionally, at step **210**, the FMI **30** may match the receive instruction with the transaction request from the first client device. For example, the FMI **30** may compare the attributes (e.g., the different account identifiers and/or the identification of the asset) of the two requests and determine whether the attributes match. If the FMI **30** determines the assets do not match, the FMI **30** may generate an error message and stop the transaction from occurring. Otherwise, if the FMI **30** determines the instructions match, at step **212**, the FMI **30** may settle the transaction by crediting the asset to the recipient account and debiting the asset from the source account. At step **214**, the FMI **30** may transmit a debit confirmation of the transaction to the first computing device (e.g., to the source account that the first computing device is accessing) to indicate the transaction was successful. The FMI may also transmit a message to the set of financial applications **40** indicating the credit to the recipient account. The FMI may transmit such messages using a conventional messaging protocol.

[0059] At step **216**, the set of financial applications **40** may transmit a confirmation of the credit to the DLT application **60**. The set of financial applications **40** may transmit the confirmation using conventional messaging (e.g., sets of instructions **46**) or custom messaging (e.g., sets of instructions **48**). The set of financial applications **40** may create and transmit a new credit confirmation in a message including an identifier of the destination account of the transaction as the ultimate beneficiary of the transaction. At step **218**, the DLT application **60** may issue a token for the transaction (e.g., the DLT application **60** may credit the asset of the transaction into the destination account) by exchanging messages to and from the distributed ledger for which the DLT application **60** maintains digital wallets indicating the transaction and the credit into the destination

account.

[0060] At step **220**, the DLT application **60** may transmit a credit confirmation in addition to other messages (e.g., transaction status messages, intraday statement, end of day statements, etc.) to the destination account (e.g., to the second client device accessing the destination account). However, if the settlement fails (e.g., if the receive instructions did not match the transaction request), the DLT application **60** may transmit a message to the destination account to indicate the transaction could not be processed. Additionally, if the DLT application **60** receives a cancellation message for the destination account before the transaction has finished processing, the DLT application **60** may transmit a message to the set of financial applications **40** to cancel and stop the transaction from occurring.

[0061] In some cases, the recipient account in the set of financial applications **40** may not be an omnibus account. In such cases, the designation of the ultimate destination account may not be needed at any stage and the recipient account may be the ultimate beneficiary account of the transaction.

[0062] In some cases, if the user owns both the source account and the destination account, the user may request the DLT application to initiate the 'deliver instruction' which is usually received from a first client device at step **202**. The user may only do so, in some cases, if the DLT application is authorized to do so (e.g., has the appropriate account permissions).

[0063] Further, in some cases, depending on the asset in question, a transfer over a conventional settlement network may not need matching instructions (for example, for transferring USD, it may suffice to just have a delivery instruction). In such cases, steps **204**, **206**, **208** and/or **210** may be skipped.

[0064] These are just illustrative flows for tokenization. The process for tokenization (and detokenization) may vary based on the underlying financial instrument being tokenized. The above process applies for securities and cash. The DLT application **60** may also be configured for other instruments (e.g. letter of credit). In such cases, the process would change as other asset classes may be get instantiated using different methods. For instance, digital native assets may never have a conventional format and a trade receivable token might get created when party A accepts a liability to pay party B in the future. As described herein, digital native assets may be crypto assets, represented on a DLT (with an assigned ownership), that do not have an equivalent asset representation in conventional financial infrastructure; these digital native assets may or may not represent a physical asset.

[0065] FIG. **3** illustrates a flowchart of a process for detokenization, according to an embodiment. The method **300** describes how a DLT enabled application can facilitate a transaction with a conventional account and keep a record of the transaction on a distributed ledger. The DLT application may be the DLT application **60**, shown and described with reference to FIG. **1**. The method **300** is described below with reference to components (e.g., the FMI **30**, the set of financial applications **40**, and the DLT application **60**) of the system **100** as the system **100** is described with reference to FIG. **1** above. However, it should be noted that the method **300** may be performed by any number of components. Furthermore, other configurations of the method **300** may comprise additional or alternative steps, or may omit one or more steps altogether.

[0066] At step **302**, the DLT application **60** may receive a deliver instruction from a first client device. The deliver instruction may be an instruction to transfer an asset from a source account hosted by the DLT application (e.g., a digital wallet) into a destination account stored in a conventional system. The deliver instruction may include identifiers of the source account and the destination account. For example, the deliver instruction may be to transfer an asset to a particular transferee account (e.g., transferor/transferee account **10** or **13**) from a given wallet (e.g., one of wallets **61-63**). In some cases, the deliver instruction may include a BIC code for the DLT application **60** to enable the deliver instruction to be routed to the DLT application **60** using SWIFT messaging (e.g., sets of instructions **84**). At step **304**, the DLT application **60** may validate the

transaction request to verify that it is a valid request.

[0067] At step **306**, the DLT application **60** may freeze the balance of the source account (e.g., the token). By doing so, the DLT application **60** may make the balance unavailable for any transfers. The DLT application **60** may then create a new delivery instruction. This new delivery instruction may indicate the destination account (which would be the same as the destination account in the original request received from the client), but the source account would now be indicated as the conventional account in the set of financial applications **40** to which the balance in the wallet is mapped for the particular asset in question. This new delivery instruction may include details of the ultimate source account (the wallet Id). The DLT application **60** may then route the transaction request to the set of financial applications **40**, wherein the transaction request is routed to the set of financial applications **40**. The DLT application **60** may transmit the transaction request to the set of financial applications **40** using conventional or custom messaging (e.g., via the sets of instructions **47** or **49**).

[0068] Optionally, at step **308**, the set of financial applications **40** may validate the request and route the request to the FMI **30**. The set of financial applications **40** may validate the request using conventional request validation policies. The set of financial applications **40** may then route the request to the FMI **30**. The set of financial applications **40** may do so using conventional messaging protocols (e.g., via the sets of instructions **32**).

[0069] Optionally, at step **310**, the FMI **30** may receive a receive instruction from a second client device. The FMI **30** may receive the receive instruction from the second client device through the financial institution that maintains the destination account that was identified in the transaction request from the first client device. The FMI **30** may receive the receive instruction after the financial institution validates the receive instruction and routes the receive instruction to the FMI **30** via a conventional message protocol). The receive instruction may include identifications of the destination account, the source account, and the ultimate source account. The receive instruction may include a reference to the asset being transferred to the destination account. The FMI **30** may receive the receive instruction via the instruction **21**.

[0070] Optionally, at step **312**, the FMI **30** may match the receive instruction with the transaction request from the first client device. The FMI may match the receive instruction with the transaction request in a similar manner to the manner described above (e.g., compare the attributes (e.g., the different account identifiers and/or the identification of the asset) of the two requests and determine whether the attributes match). If the FMI **30** determines the assets do not match, the FMI **30** may generate an error message and stop the transaction from occurring. Otherwise, if the FMI **30** determines the assets match, at step **314**, the FMI **30** may settle the transaction by crediting the asset to the destination account and debiting the asset from the recipient account stored on the set of financial applications **40**. At step **316**, the FMI may transmit (via the sets of instructions **22**) a credit confirmation to the destination account being accessed by the second computing device and transmit (via the sets of instructions **31**) a confirmation message for the debit to the set of financial applications **40**.

[0071] At step **318**, the set of financial applications **40** may receive the debit confirmation (i.e., the debit from the conventional account in the set of financial applications **40** which maps to the wallet from which the asset is being transferred) from the FMI **30** and then create and transmit to the DLT application **60** a new confirmation of the debit from the wallet. The set of financial applications **40** may transmit the confirmation to the DLT application **60** using a conventional communication protocol or a custom messaging protocol (e.g., via the sets of instructions **46** or **48**). At step **320**, the DLT application **60** may receive the confirmation and burn the previously frozen token in the source account (e.g., debit the asset of the transaction from the source account). At step **322**, the DLT application **60** may transmit a debit confirmation in addition to other transaction details (e.g., transaction status messages, intraday statement, end of day statements, etc.) to the first computing device (e.g., to the source account that the first computing device is accessing). The DLT

application **60** may do so using conventional messaging protocols (e.g., the sets of instructions **84** and **86**) or custom messaging protocols (e.g., via the sets of instructions **83** and **85**).

[0072] In some cases, if the same entity owns both the source account (wallet on **60**) and the destination account (e.g., the transferor/transferee account **10** or **13**), the user may request the DLT application **60** to initiate the ‘receive instruction’, which is usually received from a second client device at step **310**. The user may only do so, in some cases, if the DLT application **60** is authorized to do so (e.g., has the appropriate account permissions).

[0073] Further, in some cases, depending on the asset in question, a transfer over a conventional settlement network may not need matching instructions (for example, for transferring USD, it may suffice to just have a delivery instruction). In such cases, step **312** and **314** may be skipped.

[0074] In some cases, the recipient account in the set of financial applications **40** is not an omnibus account. In such cases, the designation of the ultimate source account may not be needed at any stage.

[0075] FIG. **4** illustrates a flowchart of a process for token transfer, according to an embodiment. The method **400** describes how a DLT enabled application can facilitate a token transfer between two wallets of the distributed ledger to which the DLT enabled application is linked. The DLT application may be the DLT application **60**, shown and described with reference to FIG. **1**. The method **400** is described below with reference to components (e.g., DLT application **60**) of the system **100** as the system **100** is described with reference to FIG. **1** above. However, it should be noted that the method **400** may be performed by any number of components. Furthermore, other configurations of the method **400** may comprise additional or alternative steps, or may omit one or more steps altogether.

[0076] At step **402**, the DLT application **60** may receive a transaction request identifying one or more tokens, and involving one or more counterparty accounts (in the simplest case, this would be a request to transfer a token from a source account to a destination account). Each account may be a digital wallet on the distributed ledger associated with the DLT application **60**. In some embodiments, the accounts may include accounts on other distributed ledgers. The DLT application **60** may receive the transaction request from a first client device that is accessing the account through a user interface (e.g., financial institution-provided/client-sourced interface **71** or a DLT application user interface **72**). The user may use the user interface **71** and the sets of instructions **74** for standard transfers (defined above), or the application user interface **72** and via the sets of instructions **76** for standard or non-standard asset transfers.

[0077] At step **404**, the DLT application **60** may validate the transaction request, carrying out any required checks and/or rules in doing so. Optionally, at step **406**, the DLT application **60** may receive a matching instruction from a second client device. A user accessing the second client device may send the instruction using the conventional user interface (e.g., the sets of instructions **84**) for matching standard transfer requests. Alternatively, the user may send the instruction using the DLT application user interface (e.g., via the sets of instructions **86**) for matching standard or non-standard asset transfer requests, or accepting “allegements” of transactions initiated by the first client device. Advantageously, by implementing the systems and methods described herein, even if the first client sends a standard instruction via conventional interface, the second client could use a conventional interface or a custom interface. The second client device may not be required to provide a matching instruction if the DLT application **60** has been configured to not require such matching instructions if certain conditions are met. These conditions may be based on attributes like asset type, transaction type, transaction amount, etc. (e.g., it may not require matching instructions for a one-legged transfer of certain assets below a particular amount). Additionally, the second client device may not be required to provide matching instructions if the second client device has previously specified a preference to accept incoming transfers if certain conditions are met. These conditions may be based on attributes such as the asset type, transaction type, counterparty details, transaction time, transaction amount, etc. (e.g., a US party may accept

transactions under \$1000 from Asian counterparties during Asian business hours, which are outside US business hours). At step **408**, the DLT application **60** may validate the matching instructions. [0078] In some cases, DLT application **60** may be configured to require matching transactions at an asset and transaction type level. This may allow the DLT application **60** to standardize protocol for transfers for different assets (e.g., even for cash token transfers, it could mandate the need for a matching instruction to be provided).

[0079] In some cases, the transaction may have more than two legs (e.g., entity A may transfer 100 units of asset 1 to entity B, and entity B may transfer 50 units of asset 2 to entity C. In such cases, the parties to each portion of the transaction may similarly provide instructions to the DLT application **60** for validation and matching.

[0080] At step **410**, the DLT application **60** may match the instructions from each of the entities (e.g., the DLT application **60** may match the instructions of all of the transaction requests, receive instructions, and/or deliver instructions). In response to the instructions matching, at step **412**, the DLT application **60** may wait on any conditions that need to be satisfied before the transaction can be executed. In doing so, the DLT application **60** may apply any applicable priority rules. At step **414**, the DLT application **60** may settle the transaction (e.g., single or multiple-legged transaction) by transferring the tokens of the transactions between the wallets identified in the requests and maintained by the DLT application **60**. The DLT application **60** may update the distributed ledger to indicate the transaction went through.

[0081] In case any transfers involve assets for which the distributed ledger does not act as sub-ledger (e.g., there is a client-specific account held in conventional infrastructure), the DLT application **60** may reflect the transaction in client-specific accounts by passing on appropriate messages to one of set of financial applications **40** or **50**. The DLT application **60** may do so using custom messaging protocols (e.g. sets of instructions **49**).

[0082] At step **416**, the DLT application **60** may transmit messages to the client devices that initiated and/or took part in the transaction. For example, the DLT application **60** may send transaction status messages, settlement confirmations, intraday and end of day statements to the client devices. The DLT application **60** may do so using conventional communication protocols (e.g., in sets of instructions **73** or in sets of instructions **83**) and/or custom protocols (e.g., using the sets of instructions **75** or the sets of instructions **85**).

[0083] In one non-limiting example, in the case of non-standard transactions involving more than one asset transfer, the DLT application **60** may have the capability to send conventional messages for individual legs of the trade, with a common transaction reference. Thus, if the DLT application **60** executes a trade where entity I pays entity J EUR 1000, entity J pays entity I USD 600 and entity J pays entity K USD 580 at the same time (which is a non-standard instruction), the DLT application **60** can send debit and credit confirmations for the three individual legs. This ensures that reconciliation systems used by clients can process transfers arising from non-standard transactions as well.

[0084] The foregoing method descriptions and the process flow diagrams are provided merely as illustrative examples and are not intended to require or imply that the steps of the various embodiments must be performed in the order presented. The steps in the foregoing embodiments may be performed in any order. Words such as “then,” “next,” etc. are not intended to limit the order of the steps; these words are simply used to guide the reader through the description of the methods. Although process flow diagrams may describe the operations as a sequential process, many of the operations can be performed in parallel or concurrently. In addition, the order of the operations may be re-arranged. A process may correspond to a method, a function, a procedure, a subroutine, a subprogram, and the like. When a process corresponds to a function, the process termination may correspond to a return of the function to a calling function or a main function.

[0085] The various illustrative logical blocks, modules, circuits, and algorithm steps described in connection with the embodiments disclosed herein may be implemented as electronic hardware,

computer software, or combinations of both. To clearly illustrate this interchangeability of hardware and software, various illustrative components, blocks, modules, circuits, and steps have been described above generally in terms of their functionality. Whether such functionality is implemented as hardware or software depends upon the particular application and design constraints imposed on the overall system. Skilled artisans may implement the described functionality in varying ways for each particular application, but such implementation decisions should not be interpreted as causing a departure from the scope of the present invention.

[0086] Embodiments implemented in computer software may be implemented in software, firmware, middleware, microcode, hardware description languages, or any combination thereof. A code segment or machine-executable instructions may represent a procedure, a function, a subprogram, a program, a routine, a subroutine, a module, a software package, a class, or any combination of instructions, data structures, or program statements. A code segment may be coupled to another code segment or a hardware circuit by passing and/or receiving information, data, arguments, parameters, or memory contents. Information, arguments, parameters, data, etc. may be passed, forwarded, or transmitted via any suitable means including memory sharing, message passing, token passing, network transmission, etc.

[0087] The actual software code or specialized control hardware used to implement these systems and methods is not limiting of the invention. Thus, the operation and behavior of the systems and methods were described without reference to the specific software code being understood that software and control hardware can be designed to implement the systems and methods based on the description herein.

[0088] When implemented in software, the functions may be stored as one or more instructions or code on a non-transitory computer-readable or processor-readable storage medium. The steps of a method or algorithm disclosed herein may be embodied in a processor-executable software module, which may reside on a computer-readable or processor-readable storage medium. A non-transitory computer-readable or processor-readable media includes both computer storage media and tangible storage media that facilitate transfer of a computer program from one place to another. A non-transitory processor-readable storage media may be any available media that may be accessed by a computer. By way of example, and not limitation, such non-transitory processor-readable media may comprise RAM, ROM, EEPROM, CD-ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other tangible storage medium that may be used to store desired program code in the form of instructions or data structures and that may be accessed by a computer or processor. Disk and disc, as used herein, include compact disc (CD), laser disc, optical disc, digital versatile disc (DVD), floppy disk, and Blu-ray disc where disks usually reproduce data magnetically, while discs reproduce data optically with lasers.

Combinations of the above should also be included within the scope of computer-readable media. Additionally, the operations of a method or algorithm may reside as one or any combination or set of codes and/or instructions on a non-transitory processor-readable medium and/or computer-readable medium, which may be incorporated into a computer program product.

[0089] The preceding description of the disclosed embodiments is provided to enable any person skilled in the art to make or use the present invention. Various modifications to these embodiments will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other embodiments without departing from the spirit or scope of the invention. Thus, the present invention is not intended to be limited to the embodiments shown herein but is to be accorded the widest scope consistent with the following claims and the principles and novel features disclosed herein.

[0090] While various aspects and embodiments have been disclosed, other aspects and embodiments are contemplated. The various aspects and embodiments disclosed are for purposes of illustration and are not intended to be limiting, with the true scope and spirit being indicated by the following claims.

Claims

1. A method for seamlessly processing transactions using distributed ledger technology, comprising: establishing, by a distributed ledger technology (DLT) application executed or hosted by one or more processors, (i) a first connection with a first client device using a routing address configured to be used in communication with a first communication protocol with which client devices can route messages through the distributed ledger technology application, (ii) a second connection with a second client device using the routing address configured to be used in communication with the first communication protocol with which client devices can route messages through the distributed ledger technology application, and (iii) a third connection with one or more nodes hosting a distributed ledger via a second communication protocol; storing, by the distributed ledger technology application, a plurality of DLT-based client accounts hosted through the distributed ledger; receiving, by the distributed ledger technology application from the first client device through the first connection and the first communication protocol using the routing address of the distributed ledger technology application, a transaction request to complete an asset transfer to transfer an asset from a source DLT-based client account of the plurality of DLT-based client accounts hosted through the distributed ledger to a destination DLT-based client account of the plurality of DLT-based client accounts hosted through the distributed ledger, the transaction request comprising an identifier of the source DLT-based client account, an identifier of the destination DLT-based client account, and the routing address of the distributed ledger technology application; receiving, by the distributed ledger technology application from the second client device through the second connection and the first communication protocol using the routing address of the distributed ledger technology application, a matching instruction to complete the asset transfer to transfer the asset from the source DLT-based client account hosted through the distributed ledger to the destination DLT-based client account hosted through the distributed ledger, the matching instruction comprising the identifier of the source DLT-based client account, the identifier of the destination DLT-based client account, and the routing address of the distributed ledger technology application; responsive to determining at least an identification of the asset, the identifiers of the source DLT-based client account, and the identifiers of the destination DLT-based client account in the transaction request and the matching instruction match, generating, by the distributed ledger technology application, instructions to transfer the asset from the source DLT-based client account to the destination DLT-based client account within the stored plurality of DLT-based client accounts; and generating, by the distributed ledger technology application, an instruction to cause, over the established third connection and via the second communication protocol, the one or more nodes maintaining the distributed ledger to add a record of the asset transfer to the distributed ledger.
2. The method of claim 1, wherein a wallet owner of the source DLT-based client account is authorized to instruct a transferor/transferee account of a banking computing infrastructure and instructs the transferor/transferee account via the distributed ledger technology application.
3. The method of claim 1, further comprising: determining, by the distributed ledger application, one or more transaction conditions have been met; and executing, by the distributed ledger application, the asset transfer in response to the determination that the one or more transaction conditions have been met.
4. The method of claim 3, comprising transmitting, by the distributed ledger technology application, debit or credit confirmations to each account involved in the asset transfer.
5. The method of claim 1, wherein the distributed ledger technology application is configured to require matching instructions for the asset transfer unless the second client device associated with second DLT-based client account of the asset transfer has previously specified a preference to accept incoming transfers if one or more conditions are met and the one or more conditions are

met.

- 6.** The method of claim 1, wherein a wallet owner of the source DLT-based client account is authorized to instruct a transferor/transferee account and instructs the transferor/transferee account via the distributed ledger technology application.
- 7.** The method of claim 1, comprising: receiving, by the distributed ledger technology application, a message initiating the asset transfer from the first client device via the first communication protocol; and transmitting, by the distributed ledger technology application, subsequent messages with the first client device or the second client device via the second communication protocol.
- 8.** The method of claim 1, further comprising: updating, by the distributed ledger technology application, the distributed ledger as an intermediate step while exchanging a sequence of messages to execute the asset transfer.
- 9.** The method of claim 1, comprising exchanging, by the distributed ledger technology application, a sequence of messages with one or more financial institutions via the first communication protocol.
- 10.** The method of claim 1, wherein any external transfers originating at one of plurality of DLT client-based accounts are only permitted to be initiated by the distributed ledger technology application.
- 11.** A system for seamlessly processing transactions using distributed ledger technology, the system comprising: an application server comprising a processor executing or hosting a distributed ledger technology (DLT) application, the processor configured to execute or host the distributed ledger technology application to: establish, using a distributed ledger technology (DLT) application executed or hosted by the processor, (i) a first connection with a first client device using a routing address configured to be used in communication with a first communication protocol with which client devices can route messages through the distributed ledger technology application, (ii) a second connection with a second client device using the routing address configured to be used in communication with the first communication protocol with which client devices can route messages through the distributed ledger technology application, and (iii) a third connection with one or more nodes hosting a distributed ledger via a second communication protocol; store, using the distributed ledger technology application, a plurality of DLT-based client accounts hosted through the distributed ledger; receive, using the distributed ledger technology application from the first client device through the first connection and the first communication protocol using the routing address of the distributed ledger technology application, a transaction request to complete an asset transfer to transfer an asset from a source DLT-based client account of the plurality of DLT-based client accounts hosted through the distributed ledger to a destination DLT-based client account of the plurality of DLT-based client accounts hosted through the distributed ledger, the transaction request comprising an identifier of the source DLT-based client account, an identifier of the destination DLT-based client account, and the routing address of the distributed ledger technology application; receive, using the distributed ledger technology application from the second client device through the second connection and the first communication protocol using the routing address of the distributed ledger technology application, a matching instruction to complete the asset transfer to transfer the asset from the source DLT-based client account hosted through the distributed ledger to the destination DLT-based client account hosted through the distributed ledger, the matching instruction comprising the identifier of the source DLT-based client account, the identifier of the destination DLT-based client account, and the routing address of the distributed ledger technology application; responsive to determining at least an identification of the asset, the identifiers of the source DLT-based client account, and the identifiers of the destination DLT-based client account in the transaction request and the matching instruction match, generate, using the distributed ledger technology application, instructions to transfer the asset from the source DLT-based client account to the destination DLT-based client account within the stored plurality of DLT-based client accounts; and generate, using the distributed ledger technology application, an

instruction to cause, over the established third connection and via the second communication protocol, the one or more nodes maintaining the distributed ledger to add a record of the asset transfer to the distributed ledger.

12. The system of claim 11, wherein a wallet owner of the source DLT-based client account is authorized to instruct a transferor/transferee account of a banking computing infrastructure and instructs the transferor/transferee account via the distributed ledger technology application.

13. The system of claim 11, wherein the processor is further configured to: determine, using the distributed ledger application, one or more transaction conditions have been met; and execute, using the distributed ledger application, the asset transfer in response to the determination that the one or more transaction conditions have been met.

14. The system of claim 13, wherein the processor is configured to transmit, using the distributed ledger technology application, debit or credit confirmations to each account involved in the asset transfer.

15. The system of claim 11, wherein the distributed ledger technology application is configured to require matching instructions for the asset transfer unless the second client device associated with second DLT-based client account of the asset transfer has previously specified a preference to accept incoming transfers if one or more conditions are met and the one or more conditions are met.

16. The system of claim 11, wherein a wallet owner of the source DLT-based client account is authorized to instruct a transferor/transferee account and instructs the transferor/transferee account via the distributed ledger technology application.

17. The system of claim 11, wherein the processor is configured to: receive, using the distributed ledger technology application, a message initiating the asset transfer from the first client device via the first communication protocol; and transmit, using the distributed ledger technology application, subsequent messages with the first client device or the second client device via the second communication protocol.

18. The system of claim 11, wherein the processor is further configured to: update, using the distributed ledger technology application, the distributed ledger as an intermediate step while exchanging a sequence of messages to execute the asset transfer.

19. The system of claim 11, wherein the processors is configured to exchange, using the distributed ledger technology application, a sequence of messages with one or more financial institutions via the first communication protocol.

20. The system of claim 11, wherein any external transfers originating at one of plurality of DLT client-based accounts are only permitted to be initiated by the distributed ledger technology application.
