

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12390093
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Akui; Nobuaki

Endoscope, bending operation mechanism for endoscope, and operation portion for endoscope

Abstract

An endoscope includes: a first bearing including a first recess along a first central axis; a second bearing disposed in the first recess and provided with a second central axis intersecting the first central axis in the state of being disposed in the first recess, the second bearing including a second recess along the second central axis and being retained turnably around the first central axis; and an operation lever disposed in the second recess, and including a shaft member retained turnably around the second central axis.

Inventors:	Akui; Nobuaki (Hino, JP)
Applicant:	OLYMPUS CORPORATION (Tokyo, JP)
Family ID:	1000008767864
Assignee:	OLYMPUS CORPORATION (Tokyo, JP)
Appl. No.:	17/725817
Filed:	April 21, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220240754 A1	Aug. 04, 2022

Related U.S. Application Data

continuation parent-doc WO PCT/JP2019/042142 20191028 PENDING child-doc US 17725817

Publication Classification

Int. Cl.: A61B1/005 (20060101); A61B1/00 (20060101)

U.S. Cl.:

CPC A61B1/0052 (20130101); A61B1/00114 (20130101); A61B1/0057 (20130101);

Field of Classification Search

CPC: A61B (1/0052); A61B (1/00066); A61B (2017/003); A61B (2017/00318); A61B (34/74); A61B (2034/741-744); A61B (1/00039); A61B (1/00042); A61B (1/005); A61B (1/0051); A61B (1/0057); A61M (25/0136); A61M (25/0133); A61M (25/0147)

USPC: 600/131; 600/146; 600/149

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2011/0144576	12/2010	Rothe	604/95.04	A61M 25/0136
2012/0302832	12/2011	Inada	600/118	A61B 1/0052
2019/0029498	12/2018	Mankowski et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
0077526	12/1982	EP	N/A
3434169	12/2018	EP	N/A
2012100683	12/2011	JP	N/A
2016055041	12/2015	JP	N/A
WO-2017145431	12/2016	WO	N/A

OTHER PUBLICATIONS

International Search Report dated Dec. 24, 2019 issued in PCT/JP2019/042142. cited by applicant

Primary Examiner: Carey; Michael J

Assistant Examiner: Luu; Timothy Tuan

Attorney, Agent or Firm: Scully, Scott, Murphy & Presser, P.C.

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION (1) This application is a continuation application of PCT/JP2019/042142 filed on Oct. 28, 2019, the entire contents of which are incorporated herein by this reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

(1) The present invention relates to an endoscope configured to perform bending operation by inclining an operation lever, a bending operation mechanism for endoscope configured to perform the bending operation by inclining the operation lever, and an operation portion for endoscope

configured to perform the bending operation by inclining the operation lever.

2. Description of the Related Art

(2) There is known an endoscope in a form allowing bending of a bending portion which is provided in an elongated insertion portion insertable into an inside of a human body, a machine, or the like. For example, International Publication No. 2017/145431 discloses an endoscope including an operation portion provided with a joystick lever and a bending portion connected to a plurality of wires. The endoscope can change traction amounts of a plurality of wires in accordance with an inclination direction and an inclination angle of the joystick lever so as to change a bending direction and a bending angle of the bending portion.

(3) The endoscope disclosed in International Publication No. 2017/145431 has a configuration in which the joystick lever is retained by using a pair of screws for a frame-shaped member to penetrate the frame-shaped member so as to retain another member turnably around one axis.

SUMMARY OF THE INVENTION

(4) An endoscope according to an aspect of the present invention includes: a first bearing including a first recess along a first central axis; a second bearing disposed in the first recess and provided with a second central axis intersecting the first central axis, the second bearing including a second recess along the second central axis and being retained turnably around the first central axis; and an operation lever disposed in the second recess, and including a shaft member retained turnably around the second central axis.

(5) A bending operation mechanism for endoscope according to an aspect of the present invention includes: a first bearing including a first recess along a first central axis; a second bearing disposed in the first recess and provided with a second central axis intersecting the first central axis, the second bearing including a second recess along the second central axis and being retained turnably around the first central axis; and an operation lever disposed in the second recess, and including a shaft member retained turnably around the second central axis.

(6) An operation portion for endoscope according to an aspect of the present invention includes: a first bearing including a first recess along a first central axis; a second bearing disposed in the first recess and provided with a second central axis intersecting the first central axis, the second bearing including a second recess along the second central axis and being retained turnably around the first central axis; and an operation lever disposed in the second recess, and including a shaft member retained turnably around the second central axis.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a view schematically showing a configuration of an endoscope of a first embodiment;

(2) FIG. 2 is a perspective view of a bending operation mechanism of the first embodiment;

(3) FIG. 3 is an exploded perspective view of the bending operation mechanism of the first embodiment;

(4) FIG. 4 is an exploded perspective view of a bearing portion of the first embodiment;

(5) FIG. 5 is a sectional view of the bending operation mechanism of the first embodiment in a plane including a second linear axis and a third linear axis;

(6) FIG. 6 is a sectional view of the bending operation mechanism of the first embodiment in a plane including a first linear axis and the third linear axis;

(7) FIG. 7 is a sectional view showing holes inserted with a pin in the bending operation mechanism of the first embodiment;

(8) FIG. 8 is an exploded perspective view of a bending operation mechanism of a second embodiment;

(9) FIG. 9 is an exploded perspective view of a bearing portion of the second embodiment;

- (10) FIG. 10 is a sectional view of a first bearing and a second bearing of the second embodiment in a plane including a second linear axis and a third linear axis;
- (11) FIG. 11 is a view showing attachment/detachment of the first bearing and the second bearing in the second embodiment;
- (12) FIG. 12 is a sectional view of the second bearing and a shaft member in a plane including a first linear axis and the third linear axis in the second embodiment;
- (13) FIG. 13 is a view showing attachment/detachment of the second bearing and the shaft member in the second embodiment; and
- (14) FIG. 14 is a sectional view of a bending operation mechanism of a third embodiment in a plane including a second linear axis and a third linear axis.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

(15) Hereinafter, preferred embodiments of the present invention will be described with reference to the drawings. Note that in the respective drawings used for following description, different scales may be used for each component member in order to present each component member in a size recognizable in the drawings. The present invention is not limited only to the number of the component members, the shapes of the component members, size ratios of the component members, and relative positional relationships among each of the component members described in the drawings.

First Embodiment

(16) FIG. 1 is a view schematically showing a configuration of an endoscope 1 of a first embodiment. The endoscope 1 includes an insertion portion 2 having an elongated shape that is inserted into a subject, an operation portion 3 interconnected to a proximal end 2b of the insertion portion 2, a connection cable 4 extending from the operation portion 3, and a bending operation mechanism 5 provided in the operation portion 3. The subject into which the insertion portion 2 is inserted may be a living organism such as human being, or may be a non-living organism, such as a machine or a building.

(17) The insertion portion 2 is configured of a distal end portion 2c, a bending portion 2d, and a tubular portion 2e which are interconnected in order from a distal end 2a to the proximal end 2b.

(18) The distal end portion 2c is equipped with an image pickup apparatus, which is not shown. The image pickup apparatus includes an image sensor (imager) and an objective lens, or the like. The distal end portion 2c is provided with an illumination window, not shown, which emits light for illuminating an object of the image pickup apparatus. The connection cable 4 includes a connector that is connected to a processor, which is an external device. An image picked up by the image pickup apparatus is displayed on an image display device connected to the processor. Since the image pickup apparatus and the illumination window are publicly known components, detailed description of the components is omitted.

(19) The bending portion 2d is bent in response to a motion of the operation lever 30 of the bending operation mechanism 5 provided in the operation portion 3. As an example in the present embodiment, the bending operation mechanism 5 has a configuration of transmitting the motion of the operation lever 30 to the bending portion 2d mechanically. The bending portion 2d is connected to distal ends of a plurality of wires 50 (not shown in FIG. 1), and the bending operation mechanism 5 is connected to proximal ends 50a of the plurality of wires 50.

(20) As described later in detail, the bending operation mechanism 5 changes individual traction amounts of the plurality of wires 50 in response to the motion of the operation lever 30. The bending portion 2d changes in direction and angle of bending as the traction amounts of the plurality of wires 50 change. As an example in the present embodiment, the bending operation mechanism 5 changes the traction amounts of four wires 50. The bending portion 2d bends in any directions. The configuration of the bending portion 2d, which changes the direction and the angle of bending in accordance with change in the traction amounts of the plurality of wires 50, is a publicly known configuration, and therefore, detailed description of the configuration is omitted.

(21) Note that the endoscope **1** may be in the form including the bending operation mechanism **5** including an encoder that converts the motion of the operation lever **30** into an electrical signal, and an actuator that generates force to bend the bending portion **2d** in response to the electrical signal. In other words, the endoscope **1** is not limited to a form directly transmitting the force applied to the operation lever **30** by a user to the bending portion **2d**.

(22) The tubular portion **2e** is a tubular area that links the proximal end of the bending portion **2d** and the operation portion **3**. The tubular portion **2e** may have flexibility or may have no flexibility. As an example in the present embodiment, the tubular portion **2e** has flexibility, and is flexible enough to be bent according to external force. Endoscopes in a form having a flexible tubular portion are typically referred to as flexible endoscopes, while endoscopes in a form having a rigid tubular portion are typically referred to as rigid endoscopes. Flexible endoscopes and rigid endoscopes in a medical field, for example, are defined in ISO8600-1: 2015.

(23) The operation portion **3** includes a cover member **3a**, which is a hollow body portion that houses the bending operation mechanism **5** inside. The cover member **3a** has an opening **3b** formed to extend from the outside to the inside. A distal end portion **30a** of the operation lever **30** is an extension member extending to the outside of the operation portion **3** from the opening **3b**.

(24) The cover member **3a** is the part that is gripped by the user. As described later, the operation lever **30** is swingably supported to the cover member **3a**. The operation lever **30** is provided at a position where the user can apply force to the distal end portion **30a** with a finger of the user.

(25) As an example in the present embodiment shown in FIG. **1**, the operation lever **30** is inserted into the opening **3b**, and the distal end portion **30a** of the operation lever **30** protrudes outward from the outer surface of the cover member **3a**. At an end portion of the distal end portion **30a** that is the extension member, a finger contact member **30b**, which is the part where the user touches the operation lever **30**, is provided.

(26) Note that the shape and the arrangement of the operation lever **30** are not limited to the shape and the arrangement in the present embodiment. For example, the distal end portion **30a** of the operation lever **30** may be positioned inside the outer surface of the cover member **3a**. In this case, the user may insert a finger into the opening **3b** and touches the distal end portion **30a** of the operation lever **30**.

(27) The operation lever **30** swings around a prescribed support point P which is fixed to the cover member **3a**. A bending direction and a bending angle of the bending portion **2d** change in accordance with an inclination direction (inclination orientation) and an inclination angle of the operation lever **30** from a neutral position. The neutral position of the operation lever **30** is a prescribed position within a turnable range of the operation lever **30**. In the present embodiment, the neutral position of the operation lever **30** is the position where the shape of the bending portion **2d** is linear. In the state where the operation lever **30** is in the neutral position, the distal end portion **30a** of the operation lever **30** is approximately at the center of the opening **3b** as viewed in an opening direction of the opening **3b**.

(28) FIG. **2** is a perspective view of the bending operation mechanism **5**. FIG. **3** is an exploded perspective view of the bending operation mechanism **5**. FIG. **4** is an exploded perspective view of a bearing portion **5b**. The bending operation mechanism **5** includes a base portion **5a**, the bearing portion **5b**, the operation lever **30**, and a wire traction portion **40**. Hereinafter, with respect to the operation lever **30**, an axis extending from the support point P to the distal end portion **30a** is referred to as a longitudinal axis of the operation lever **30**.

(29) The base portion **5a** is fixed to the cover member **3a** of the operation portion **3**. The bearing portion **5b** includes a bearing. The bearing includes a bottomed recess having an opening in a prescribed direction. Inside the recess of the bearing, a turning member is disposed turnably with respect to the recess. The turning member is inserted into the recess through the opening. The operation lever **30** includes a lever member **32** having a proximal end **32a**, which is a first end, interconnected to the turning member. The lever member **32** is provided so as to extend from the

proximal end **32a** of the lever member **32** is positioned outside the recess opening along the longitudinal axis of the operation lever **30**. The distal end **32b** of the lever member **32** is positioned outside the recess opening.

(30) The bearing portion **5b** has a mechanism that retains the operation lever **30** turnably around the support point P, while restricting the operation lever **30** from turning around the longitudinal axis with respect to the base portion **5a**. More specifically, the bearing portion **5b** retains the operation lever **30** turnably around two linear axes including a first central axis **A1** and a second central axis **A2**, relative to the base portion **5a**. The first central axis **A1** and the second central axis **A2** intersect at a prescribed angle at the support point P. As an example in the present embodiment, the first central axis **A1** and the second central axis **A2** are orthogonal at the support point P. The second central axis **A2** turns around the first central axis **A1** with respect to the base portion **5a**.

(31) In following description, three linear axes are defined. The positions of the three linear axes relative to the base portion **5a** are fixed, and the three axes are orthogonal to each other at the support point P. A first linear axis **L1** is an axis coincident with the first central axis **A1**. A second linear axis **L2** is coincident with the second central axis **A2** in the state where the operation lever **30** is in the neutral position. A third linear axis **L3** is coincident with the longitudinal axis of the operation lever **30** in the state where the operation lever **30** is in the neutral position.

(32) The third linear axis **L3** passes inside the opening **3b**. A direction extending from the support point P to the opening **3b** along the third linear axis **L3** is referred to as an outward direction (first direction), and a direction opposite to the outward direction is referred to as an inward direction.

(33) FIG. 5 is a sectional view of the bending operation mechanism **5** in a plane (**L2-L3** plane) including the second linear axis **L2** and the third linear axis **L3**. FIG. 6 is a sectional view of the bending operation mechanism **5** in a plane (**L1-L3** plane) including the first linear axis **L1** and the third linear axis **L3**. FIGS. 5 and 6 show the state where the operation lever **30** is in the neutral position.

(34) In the present embodiment, for the sake of description, the inclination angle of the operation lever **30** is defined as the angle at which the longitudinal axis of the operation lever **30** and the third linear axis **L3** intersect at the support point P.

(35) The operation lever **30** includes the lever member **32** and a shaft member **31** which is a turning member. The shaft member **31** is an area retained by the bearing portion **5b**. The lever member **32** is a column-shaped member provided to extend along the longitudinal axis. The proximal end **32a** of the lever member **32** is fixed to the shaft member **31**. The shaft member **31** and the lever member **32** are integrally molded. The lever member **32** extends from the outer surface of the shaft member **31** in a direction orthogonal to the second central axis **A2**.

(36) Materials of the shaft member **31** and the lever member **32**, which are molded integrally, are not particularly limited. As an example in the present embodiment, the shaft member **31** and the lever member **32** are made of resin such as engineering plastic. Note that the shaft member **31** and the lever member **32** are made of metal and may be molded by casting or forging, or may be molded by sintering powder metal.

(37) The distal end **32b** of the lever member **32** is fixed to the finger contact member **30b**, which configures the distal end portion **30a** of the operation lever **30**.

(38) The wire traction portion **40** is fixed to the operation lever **30**. Therefore, the wire traction portion **40**, along with the operation lever **30**, turns around the first central axis **A1** and the second central axis **A2**, relative to the base portion **5a**. The wire traction portion **40** includes a plurality of retention members **41** which retain respective proximal ends **50a** of the plurality of wires **50**.

(39) In the present embodiment, the wire traction portion **40** includes four retention members **41** which retain the proximal ends **50a** of the four wires **50**. As described above, the distal ends of the four wires **50** are fixed to the bending portion **2d**. The four retention members **41** are arranged on a circle having a prescribed radius and centered on the longitudinal axis on a plane orthogonal to the longitudinal axis of the operation lever **30**. As an example in the present embodiment, the four retention members **41** are evenly arranged on a circle centered on the longitudinal axis, though the

four retention members **41** on the circle may be unevenly distanced.

(40) The plurality of wires **50** are inserted into the insertion portion **2** and the cover member **3a** of the operation portion **3**. The vicinity of each proximal end **50a** of the plurality of wires **50** is routed such that each longitudinal direction extends along the third linear axis **L3** in the cover member **3a**. In other words, the plurality of wires **50** extend in the inward direction from the proximal ends **50a** fixed to the plurality of retention members **41** along the third linear axis **L3**.

(41) In accordance with turning of the operation lever **30** around the support point **P**, the plurality of retention members **41** turn around the support point **P** relative to the base portion **5a**, while maintaining the respective relative positions. This movement of the plurality of retention members **41** changes the traction amounts of the plurality of wires **50**.

(42) In the wire traction portion **40**, the configuration of fixing the plurality of retention members **41** to the operation lever **30** is not particularly limited. As an example in the present embodiment, the wire traction portion **40** includes a substantially half-hemispherical dome member **42** centered on the support point **P**. The dome member **42** is hollow. The distal end **32b** of the lever member **32** is fixed to an inner circumferential surface side of a top portion **42a** of the dome member **42**. The plurality of retention member **41** are provided on a bottom portion **42b** of the dome member **42**.

(43) The finger contact member **30b** is fixed to an outer circumferential surface of the top portion **42a** of the dome member **42**. In other words, the dome member **42** is part of the operation lever **30**. As shown in FIGS. **5** and **6**, part of the outer circumferential surface of the dome member **42** is exposed to the outside of the operation portion **3** via the opening **3b** provided in the cover member **3a**.

(44) An outer diameter of the dome member **42** is smaller than a maximum width of the opening **3b**. Therefore, the dome member **42** cannot pass through the opening **3b**. The dome member **42** is fixed to the operation lever **30** as described above. Therefore, the cover member **3a**, which is part of an exterior, abuts and interferes with a distal end side of the operation lever **30** (dome member **42**) so as to restrict movement of the operation lever **30** in a direction away from the support point **P** along the longitudinal axis. The direction away from the support point **P** along the longitudinal axis of the operation lever **30** is a longitudinal axis direction extending from the proximal end **32a** of the lever member **32** to the distal end **32b**. The distal end side of the operation lever **30** may abut a member other than the cover member **3a**. For example, the distal end side of the operation lever **30** may be configured to abut an interior member which is provided inside the cover member **3a** and constitutes part of the body portion. The cover member **3a** is a stopper configured to restrict movement of the operation lever **30** in the longitudinal axis direction.

(45) When an edge of the opening **3b** interferes with the finger contact member **30b**, the turning range of the operation lever **30** around the support point **P** in the dome member **42** is limited. In other words, the cover member **3a** interferes with the operation lever **30** (finger contact member **30b**), and thereby restricts the turnable range of the operation lever **30** around the support point **P**.

(46) As shown in FIG. **5**, an absolute value of a maximum inclination angle when the operation lever **30** turns around the first central axis **A1** is defined as a first limit angle $\theta 1$. As shown in FIG. **6**, an absolute value of a maximum inclination angle when the operation lever **30** turns around the second central axis **A2** is defined as a second limit angle $\theta 2$. Depending on an opening shape of the opening **3b**, the maximum inclination angle of the operation lever **30** is larger than the first limit angle $\theta 1$ and the second limit angle $\theta 2$. As an example in the present embodiment, the first limit angle $\theta 1$ and the second limit angle $\theta 2$ are values equal to or less than 45 degrees.

(47) In the present embodiment, a spherical outer circumferential surface of the dome member **42** is always provided in a range of closing the opening **3b** when the operation lever **30** is within the range turnable around the support point **P**. Therefore, the dome member **42** is a member that fixes the plurality of retention members **41** to the operation lever **30** and is also a member that prevents foreign objects or user's fingers from entering into the inside of the cover member **3a** through the opening **3b**. Note that the dome member **42** may be divided into a plurality of members.

(48) The configuration of fixing the plurality of retention members **41** to the operation lever **30** is not limited to the configuration of the present embodiment. For example, the wire traction portion **40** may be configured to include a plurality of arm portions extending from the operation lever **30** in a direction orthogonal to the longitudinal axis, and the plurality of retention members **41** may be provided at each distal end of the arm portions.

(49) The configuration of the bearing portion **5b** and the shaft member **31** will be described. The bearing portion **5b** includes a first bearing **10** and a second bearing **20**.

(50) Schematically, the first bearing **10**, which is fixed to the base portion **5a**, is a slide bearing that supports part of an outer outline of the second bearing **20** as a shaft. The second bearing **20** is a slide bearing that supports part of an outer outline of the shaft member **31** as a shaft. As described before, the shaft member **31** is molded integrally with the lever member **32** of the operation lever **30**.

(51) The first bearing **10** retains the second bearing **20** turnably around the first central axis **A1** with respect to the base portion **5a**, and restricts the second bearing **20** from moving relative to the base portion **5a** in a direction parallel to the first central axis **A1**. In other words, the first bearing **10** receives load applied to the second bearing **20** in a radial direction and a thrust direction.

(52) The first bearing **10** is molded integrally with the base portion **5a**. A material of the first bearing **10** and the base portion **5a**, which are molded integrally, is not particularly limited. As an example in the present embodiment, the first bearing **10** and the base portion **5a** are made of resin such as engineering plastic. Note that the first bearing **10** and the base portion **5a** are made of metal and may be molded by casting or forging, or may be molded by sintering powder metal.

(53) The second bearing **20** retains the shaft member **31** turnably around the second central axis **A2** with respect to the second bearing **20**, and restricts the shaft member **31** from moving relative to the second bearing **20** in a direction parallel to the second central axis **A2**. In other words, the second bearing **20** receives load applied to the shaft member **31** in the radial direction and the thrust direction.

(54) The position of the second central axis **A2** relative to the second bearing **20** is fixed. The second central axis **A2**, together with the second bearing **20**, turns around the first central axis with respect to the base portion **5a**.

(55) The second bearing **20** is a molded part. The material of the second bearing **20** is not particularly limited. As an example in the present embodiment, the second bearing **20** is made of resin such as engineering plastic. Note that the second bearing **20** is made of metal and may be molded by casting or forging, or may be molded by sintering powder metal.

(56) As shown in FIG. 4, a first recess **12** is formed in the first bearing **10**. The first bearing **10** includes the first recess **12** along the first central axis **A1**. The first recess **12** is a bottomed hole that is open in the outward direction, which is the first direction along the third linear axis **L3**, in the state where the first bearing **10** is fixed to the base portion **5a**. In other words, a depth direction of the first recess **12** is the inward direction.

(57) The shape of the opening **12a** of the first recess **12** is large enough to allow insertion of the second bearing **20** into the first recess **12**. Specifically, the size of the opening **12a** of the first recess **12** is larger than a projected shape of the second bearing **20** onto the **L1-L2** plane when the operation lever **30** is at the neutral position.

(58) Inside the first recess **12**, a sliding portion **13** that slides against part of an outer surface of the second bearing **20** is formed. The sliding portion **13** includes a radial bearing portion **13a** and thrust bearing portions **13b**.

(59) The radial bearing portion **13a** receives load applied to the second bearing **20** in the radial direction, and retains the second bearing **20** turnably around the first central axis **A1**, in the state where the second bearing **20** is disposed in the first recess **12**.

(60) The radial bearing portion **13a** is formed on a bottom portion of the first recess **12** with the inward direction as a depth direction, and the first recess **12** has an opening shape larger than the

second bearing **20**. Accordingly, the radial bearing portion **13a** can receive the load applied to the second bearing **20** in the inward direction, but cannot receive the load applied to the second bearing **20** in the outward direction.

(61) The radial bearing portion **13a** in the present embodiment can receive the load in the radial direction in the range where the absolute value of inclination with respect to the third linear axis **L3** is equal to or less than the first limit angle $\theta 1$ at least on the **L2-L3** plane with the inward direction as the center.

(62) In other words, when the inclination angle of the operation lever **30** around the first central axis **A1** is within the first limit angle $\theta 1$, the first bearing **10** can receive force of pushing the operation lever **30** toward the support point **P**.

(63) More specifically, the radial bearing portion **13a** in the present embodiment is a cylindrical surface with a prescribed internal diameter **Di1** centered on the first central axis **A1**. The cylindrical surface is a semi-circular shape that is formed downward from the **L1-L2** plane. In other words, the first recess **12** of the first bearing **10** has a semi-cylindrical bottom surface formed along the first central axis **A1**.

(64) The thrust bearing portions **13b** in the present embodiment are a pair of planar wall surfaces facing each other across the radial bearing portion **13a** and orthogonal to the first central axis **A1**. The thrust bearing portions **13b** receive the load applied to the second bearing **20** in the thrust direction, and restrict the movement of the second bearing **20** in the direction parallel to the first central axis **A1**, in the state where the second bearing **20** is disposed in the first recess **12**.

(65) Note that the surface of the radial bearing portion **13a** and the thrust bearing portions **13b** may be provided with grooves and holes for the purpose of preventing biting of foreign materials, retaining lubricants, or the like.

(66) As shown in FIG. 4, the outline of the second bearing **20** supported by the first bearing **10** partially includes a cylindrical shape portion **21** having a prescribed fourth linear axis **L4** as a central axis. The fourth linear axis **L4** is orthogonal to the second central axis **A2**. In the state where the second bearing **20** is disposed in the first recess **12**, the fourth linear axis **L4** approximately coincides with the first central axis **A1**.

(67) At least part of the outer surface of the cylindrical shape portion **21** serves as a sliding surface against the first bearing **10**. The outer surface of the cylindrical shape portion **21** includes a cylindrical surface **21a** and a pair of end faces **21b**.

(68) The cylindrical surface **21a** has a prescribed first outer diameter **Do1**. The first outer diameter **Do1** is smaller than the inner diameter **Di1** of the radial bearing portion **13a**. The first outer diameter **Do1** is set to a value that allows the cylindrical surface **21a** to fit into the radial bearing portion **13a** with a prescribed gap and to slide against the radial bearing portion **13a**.

(69) The end faces **21b** are flat surfaces orthogonal to the fourth linear axis **L4**. The end faces **21b** face outside in directions opposite to each other across the cylindrical surface **21a**. The end faces **21b** are slidably in contact with the thrust bearing portion **13b**, in the state where the second bearing **20** is disposed in the first recess **12**.

(70) A second recess **22** is formed in the second bearing **20**. The second recess **22** is a bottomed hole that is open in a direction orthogonal to the second central axis **A2** and the fourth linear axis **L4**. The second recess **22** is open in the outward direction along the third linear axis **L3**, in the state where the second bearing **20** is disposed in the first recess **12** and the operation lever **30** is in the neutral position.

(71) The shape of the opening **22a** of the second recess **22** is large enough to allow insertion of the shaft member **31** into the second recess **22**. Specifically, the size of the opening **22a** of the second recess **22** is larger than a projected shape of the shaft member **31** onto the **L1-L2** plane when the operation lever **30** is in the neutral position.

(72) Inside the second recess **22**, a sliding portion **23** that slides against part of an outer surface of the shaft member **31** is formed. The sliding portion **23** includes a radial bearing portion **23a** and a

thrust bearing portion **23b**.

(73) The radial bearing portion **23a** receives the load applied to the shaft member **31** in the radial direction, and retains the shaft member **31** turnably around the second central axis **A2**, in the state where the shaft member **31** is disposed in the second recess **22**.

(74) As described in the foregoing, the second bearing **20** is disposed in the first recess **12** and provided with the second central axis **A2** intersecting the first central axis **A1**, the second bearing **20** including the second recess **22** along the second central axis **A2** and being retained turnably around the first central axis **A1**. The operation lever **30** is disposed in the second recess **22**, and includes the shaft member **31** retained turnably around the second central axis **A2**.

(75) The radial bearing portion **23a** is formed on a bottom portion of the second recess **22**, and the second recess **22** has an opening shape larger than the shaft member **31**. Accordingly, the radial bearing portion **23a** can receive the load applied to the shaft member **31** in a depth direction of the second recess **22**, but cannot receive the load applied to the shaft member **31** in an opening direction of the second recess **22**. Here, the depth direction of the second recess **22** is the direction extending from the opening to the bottom portion of the second recess **22** along an axis orthogonal to the second central axis **A2** and the fourth linear axis **L4**. The depth direction of the second recess **22** coincides with the downward direction, in the state where the operation lever **30** is in the neutral position.

(76) The radial bearing portion **23a** in the present embodiment can receive at least the load in the radial direction in the range where the absolute value of inclination with respect to the depth direction of the second recess **22** is equal to or less than the second limit angle $\theta 2$ on the plane orthogonal to the second central axis **A2**.

(77) In other words, when the inclination angle of the operation lever **30** around the second central axis **A2** is within the second limit angle $\theta 2$ in the state where the second bearing **20** is disposed in the first recess **12** and the shaft member **31** is disposed in the second recess **22**, the second bearing **20** can receive force of pushing the operation lever **30** toward the support point **P**.

(78) More specifically, the radial bearing portion **23a** in the present embodiment is a cylindrical surface with a prescribed internal diameter **Di2** centered on the second central axis **A2**. The cylindrical surface has a semi-circular shape that is formed in the depth direction from the **A2-L4** plane. In other words, the second recess **22** of the second bearing **20** has a semi-cylindrical bottom surface formed along the second central axis **A2**.

(79) The thrust bearing portions **23b** in the present embodiment are a pair of planar wall surfaces facing each other across the radial bearing portion **23a** and orthogonal to the second central axis **A2**. The thrust bearing portion **23b** receives the load applied to the shaft member **31** in the thrust direction, and restricts the movement of the shaft member **31** in the direction parallel to the second central axis **A2**, in the state where the shaft member **31** is disposed in the second recess **22**.

(80) Note that the surfaces of the radial bearing portion **23a** and the thrust bearing portion **23b** may be provided with grooves and holes for the purpose of preventing biting of foreign materials, retaining lubricants, or the like.

(81) The outline of the shaft member **31** supported by the second bearing **20** partially includes a cylindrical shape portion **31a** having a prescribed fifth linear axis **L5** as a central axis. The fifth linear axis **L5** is orthogonal to the longitudinal axis of the lever member **32**. In the state where the shaft member **31** is disposed in the second recess **22**, the fifth linear axis **L5** approximately coincides with the second central axis **A2**.

(82) At least part of the outer surface of the cylindrical shape portion **31a** serves as a sliding surface against the second bearing **20**. The outer surface of the cylindrical shape portion **31a** includes a cylindrical surface **31b** and a pair of end faces **31c**.

(83) The cylindrical surface **31b** has a prescribed second outer diameter **Do2**. The second outer diameter **Do2** is smaller than the inner diameter **Di2** of the radial bearing portion **23a**. The second outer diameter **Do2** is set to a value that allows the cylindrical surface **31b** to fit into the radial

bearing portion **23a** with a prescribed gap and to slide against the radial bearing portion **23a**.

(84) The end faces **31c** are flat faces orthogonal to the fifth linear axis **L5**. The end faces **31c** face outside in the directions opposite to each other across the cylindrical surface **31b**. The end faces **31c** are slidably in contact with the thrust bearing portion **23b** in the state where the shaft member **31** is disposed in the second recess **22**.

(85) As described in the foregoing, the bearing portion **5b** is configured of three members including the first bearing **10**, the second bearing **20**, and the shaft member **31**, each of which can be manufactured by molding at low costs. Since assembling of the bearing portion **5b** is completed by simply combining the three members so as to be stacked in one direction, the assembling is completed in a fewer procedures. Therefore, the bending operation mechanism **5** for the endoscope **1** in the present embodiment can be manufactured at low costs.

(86) As shown in FIGS. **4**, **5** and **6**, the bearing portion **5b** in the present embodiment includes one or more holes **51**.

(87) One hole **51** is configured of a first hole **51a** formed in the first bearing **10**, a second hole **51b** formed in the second bearing **20**, and a third hole **51c** formed in the shaft member **31**.

(88) The first hole **51a**, the second hole **51b**, and the third hole **51c** have a generally similar shape in cross-section. As an example in the present embodiment, the first hole **51a**, the second hole **51b**, and the third hole **51c** have a circular cross-sectional shape with the same inner diameter.

(89) The first hole **51a**, the second hole **51b**, and the third hole **51c** are arranged at positions where respective central axes approximately coincide with a sixth linear axis **L6** and are aligned in series along the sixth linear axis **L6**, in the state where the operation lever **30** is in the prescribed position. In other words, one hole **51** is configured when the operation lever **30** is at the prescribed position, and the first hole **51a**, the second hole **51b**, and the third hole **51c** formed in three members are aligned on the same straight line and communicate with each other. As an example in the present embodiment, the first hole **51a**, the second hole **51b**, and the third hole **51c** are aligned in series along the sixth linear axis **L6** in the state where the operation lever **30** is in the neutral position.

(90) The position of the sixth linear axis **L6** relative to the first bearing **10** is fixed. The sixth linear axis **L6** is disposed so as to satisfy either a condition of not passing through the support point **P** or a condition of passing through the support point **P** but not in parallel with both the first central axis **A1** and the second linear axis **L2**.

(91) As an example in the present embodiment, the sixth linear axis **L6** is disposed so as to satisfy the condition of not passing through the support point **P**, as shown in FIGS. **5** and **6**. In other words, the sixth linear axis **L6** is apart from the first central axis **A1** and the second central axis **A2** in the state where the operation lever **30** is in the neutral position.

(92) The first hole **51a** linearly extends from the outer surface of the first bearing **10** to the inner circumferential face of the first recess **12** with the sixth linear axis **L6** as the central axis. Note that the first hole **51a** may pass through the entire first bearing **10** through the first recess **12**.

(93) The first hole **51a** linearly extends from the outer surface of the second bearing **20** to the inner circumferential face of the second recess **22**. Note that the second hole **51b** may pass through the entire second bearing **20** through the second recess **22**.

(94) The third hole **51c** is a linear hole that is open to the outer surface of the shaft member **31**. The third hole **51c** may extend or may not extend through the shaft member **31**.

(95) As described in the foregoing, the bearing portion **5b** includes one or more holes **51** having a depth to at least the shaft member **31** from the outer surface of the first bearing **10** in the state where the operation lever **30** is in the prescribed position.

(96) Inside the hole **51**, one pin **52** can be inserted as shown in FIG. **7**, provided that the operation lever **30** is in the state of being at the prescribed position. In other words, the bearing portion **5b** in the present embodiment is configured of the first bearing **10**, the second bearing **20**, and the shaft member **31**, which include the holes **51a**, **51b**, and **51c**, respectively, to accept the one pin **52** at the same time.

(97) As described before, the hole **51** is disposed so as to satisfy either the condition of not passing through the support point **P** or the condition of passing through the support point **P** but not in parallel with both the first central axis **A1** and the second linear axis **L2**. Therefore, the pin **52** inserted in the hole **51** is a stopper that restricts the movement of the second bearing **20** and the shaft member **31** relative to the first bearing **10**.

(98) In the present embodiment, the operation lever **30** can be fixed in the neutral position by inserting the pin **52** into the hole **51**. For example, when the operation lever **30** can temporarily be fixed in the neutral position during assembling of the endoscope **1**, it becomes possible to easily adjust the tension applied to the plurality of wires **50**.

(99) By inserting the pin **52** into the hole **51**, it is also possible to prevent the second bearing **20** and the shaft member **31** from dropping off from the first bearing **10**. The bearing portion **5b** has a configuration that does not restrict the second bearing **20** and the shaft member **31** from moving in the outward direction from the first bearing **10**. However, when separation of the bearing portion **5b** is temporarily prevented at the time of assembling the endoscope **1**, it becomes possible to easily perform an assembling work of the bearing portion **5b** to the cover member **3a**.

(100) As described in the foregoing, since the bearing portion **51b** in the present embodiment includes the hole **51**, it becomes possible to facilitate the assembling work of the bending operation mechanism **5**.

(101) In the above description, the pin **52** is not a member included in the endoscope **1** in a completed state, but is a member temporarily used at the time of assembling the endoscope **1**. However, the pin **52** may be a member included in the endoscope **1** at shipment from a factory. For example, the pin **52** may be in the state of being inserted into the hole **51** when the endoscope **1** is shipped from the factory, and may be in such a form that a user of the endoscope **1** removes the pin **52** from the hole **51** at the time of starting to use the endoscope **1**. In this case, from shipment from the factory to delivery to the user, operation of the operation lever **30** and the bending portion **2d** is in a locked state with the pin **52**, which can prevent damage to these mechanisms during transportation of the endoscope **1**.

Second Embodiment

(102) Hereinafter, a second embodiment of the present invention will be described. In the following description, only the differences from the first embodiment will be described, and component members similar to the component members of the first embodiment will be designated by the same signs to omit the description as appropriate.

(103) FIG. **8** is an exploded perspective view of the bending operation mechanism **5**. FIG. **9** is an exploded perspective view of the bearing portion **5b**. FIG. **10** is a cross-sectional view of the first bearing **10** and the second bearing **20** along the **L2-L3** plane. FIG. **11** is a view showing attachment/detachment of the first bearing **10** and the second bearing **20**. FIG. **12** is a cross-sectional view of the second bearing **20** and the shaft member **31** along the **L1-L3** plane. FIG. **13** is a view showing attachment/detachment of the second bearing **20** and the shaft member **31**.

(104) The bending operation mechanism **5** of the present embodiment is different in configuration of the bearing portion **5b** from the bending operation mechanism **5** in the first embodiment. The present invention is similar to the first embodiment in that the bearing portion **5b** is configured of three members including the first bearing **10**, the second bearing **20**, and the shaft member **31**, which can be manufactured by molding at low costs. The bearing portion **5b** in the present embodiment has a configuration to prevent the second bearing **20** and the operation lever **30** from dropping off from the first bearing **10**.

(105) The first bearing **10** includes a first constriction portion **12b** in the opening **12a** of the first recess **12**. The first constriction portion **12b** is a through hole that communicates between the outside of the first bearing **10** and the inside of the first recess **12**.

(106) The first constriction portion **12b** has an opening shape that interferes with a projected shape of the outline of the second bearing **20** on the **L1-L2** plane when the second bearing **20** turns

around the first central axis **A1** in the range equal to or less than a prescribed angle $\theta 3$ from the neutral position. In other words, when an absolute value of the turning angle around the first central axis **A1** from the neutral position is equal to or less than $\theta 3$, the second bearing **20** interferes with the first constriction portion **12b**, so that the second bearing **20** cannot pass through the opening **12a** of the first recess **12**. Here, the prescribed angle $\theta 3$ is a value equal to or more than the first limit angle $\theta 1$.

(107) The neutral position of the second bearing **20** at the time of turning around the first central axis **A1** is the position where the opening direction of the second recess **22** coincides with the outward direction in the state where the fourth linear axis **L4** of the second bearing **20** is parallel to the first central axis **A1**. In other words, even in the state where the second bearing **20** is positioned outside the first recess **12**, the second bearing **20** can be located in the neutral position. The angle of turning of the second bearing **20** around the first central axis **A1** from the neutral position is the angle formed between the opening direction of the second recess **22** and the outward direction, in the state where the fourth linear axis **L4** of the second bearing **20** is parallel to the first central axis **A1**.

(108) When the absolute value of the turning angle around the first central axis **A1** from the neutral position is within the prescribed first angle range, which is larger than the prescribed angle $\theta 3$, a projected shape of the outline of the second bearing **20** on the **L1-L2** plane has a shape that can pass through the first constriction portion **12b**.

(109) Specifically, the second bearing **20** in the present embodiment has one or two planar cut surfaces **21c** formed on the cylindrical shape portion **21** which configures the outline.

(110) The cut surface **21c** is a flat surface which is separated by a prescribed distance from the second central axis **A2** and which is parallel to the second central axis **A2** and the fourth linear axis **L4**. The distance from the second central axis **A2** to the cut surface **21c** is less than the radius of the cylindrical surface **21a**.

(111) The cut surface **21c** is formed on one of or both an area extending from the second central axis **A2** to the side in the opening direction of the second recess **22** and an area extending from the second central axis **A2** to the side in the depth direction of the second recess **22**. In the present embodiment shown in the drawings, the cut surface **21c** is formed only on one area that extends from the second central axis **A2** to the side in the opening direction of the second recess **22**.

(112) Since the cut surface **21c** is formed, the width of the outline of the second bearing **20** in the direction orthogonal to the second central axis **A2** and the fourth linear axis **L4** is smaller than the first outer diameter **Do1** of the cylindrical surface **21a**. Hereinafter, the width of the outline of the second bearing **20** in the direction parallel to the second central axis **A2** is referred to as a first outline width **Wo1**. In the present embodiment, the first outline width **Wo1** is equal to the first outer diameter **Do1** of the cylindrical surface **21a**. The width of the outline of the second bearing **20** in the direction orthogonal to the second central axis **A2** and the fourth linear axis **L4** is referred to as a second outline width **Wo2**. The second outline width **Wo2** is the width of the outline of the second bearing **20** in the direction parallel to the third linear axis **L3**, in the state where the operation lever **30** is in the neutral position.

(113) The first constriction portion **12b** formed in the opening **12a** of the first recess **12** in the first bearing **10** has a minimum opening width, which is a first opening width **Wi1**, in the direction parallel to the second linear axis **L2**. The first opening width **Wi1** is smaller than the first outline width **Wo1** of the second bearing **20** and larger than the second outline width **Wo2**.

(114) As shown in FIG. 11, when the absolute value of the turning angle of the second bearing **20** around the first central axis **A1** from the neutral position is in the vicinity of 90 degrees, the width of the outline of the second bearing **20** in the direction parallel to the second linear axis **L2** is the second outline width **Wo2**. In this case, the second bearing **20** can pass through the first constriction portion **12b** of the first recess **12**.

(115) Note that a lateral wall surface of the first recess **12** of the first bearing **10** has a first groove

12c formed to avoid interference with the operation lever **30** whose inclination angle around the first central axis **A1** is in the vicinity of 90 degrees. The first groove **12c** is shaped by notching the lateral wall surface of the first recess **12** with a prescribed width centered on the **L2-L3** plane. The width of the first groove **12c** is larger than the thickness of the lever member **32**.

(116) Since the first groove **12c** is formed, it is possible to prevent interference between the lever member **32** and the lateral wall surface of the first recess **12**, even in the state where the shaft member **31** is disposed in the second recess **22** of the second bearing **20**.

(117) Note that in the present embodiment shown in the drawings, the first groove **12c** is formed only on one side with respect to the **L1-L3** plane, though the first groove **12c** may be formed on both the sides with respect to the **L1-L3** plane.

(118) On the other hand, as shown in FIG. **10**, when the absolute value of the turning angle of the second bearing **20** around the first central axis **A1** from the neutral position is equal to or less than the first limit angle θ_1 , the width of the outline of the second bearing **20** in the direction parallel to the second linear axis **L2** is the first outline width **Wo1**. In this case, the second bearing **20** interferes with the first constriction portion **12b** of the first recess **12**, and therefore cannot pass through the first constriction portion **12b**. Accordingly, in this case, the second bearing **20** is prevented from dropping off from the first recess **12**.

(119) The second bearing **20** includes a second constriction portion **22b** in the opening **22a** of the second recess **22**. The second constriction portion **22b** is a through hole that communicates between the outside of the second bearing **20** and the inside of the second recess **22**.

(120) The second constriction portion **22b** has an opening shape that interferes with a projected shape of the outline of the shaft member **31** on an **A2-L4** plane when the shaft member **31** turns around the second central axis **A2** in the range equal to or less than a prescribed angle θ_4 from the neutral position. In other words, when the absolute value of the turning angle of the shaft member **31** around the first central axis **A1** from the neutral position is equal to or less than θ_4 , the shaft member **31** interferes with the second constriction portion **22b**, so that the shaft member **31** cannot pass through the opening **22a** of the second recess **22**. Here, the prescribed angle θ_4 is a value equal to or more than the second limit angle θ_2 .

(121) The neutral position of the shaft member **31** at the time of turning around the second central axis **A2** is the position where the longitudinal axis of the lever member **32** of the operation lever **30** is parallel to the opening direction of the second recess **22** of the second bearing **20**, in the state where the fifth linear axis **L5** of the shaft member **31** and the second central axis **A2** are parallel. In other words, even in the state where the shaft member **31** is positioned outside the second recess **22**, the shaft member **31** can be located in the neutral position. The turning angle of the shaft member **31** around the second central axis **A2** from the neutral position is the angle formed between the longitudinal axis of the lever member **32** and the opening direction of the second recess **22**, in the state where the fifth linear axis **L5** of the shaft member **31** is parallel to the second central axis **A2**.

(122) When the absolute value of the turning angle of the shaft member **31** around the second central axis **A2** from the neutral position is within the prescribed second angle range, which is beyond the prescribed angle θ_4 , a projected shape of the outline of the shaft member **31** on the **A2-L4** plane has a shape that can pass through the second constriction portion **22b**.

(123) The shaft member **31** in the present embodiment has one or two planar cut surfaces **31d** formed on the cylindrical shape portion **31a** which configures the outline.

(124) The cut surface **31d** is a flat surface which is separated by a prescribed distance from the fifth linear axis **L5** and which is orthogonal to the longitudinal axis of the operation lever **30**. The distance from the fifth linear axis **L5** to the cut surface **31d** is less than the radius of the cylindrical surface **31b**.

(125) The cut surface **31d** is formed on one of or both an area extending from the fifth linear axis **L5** to the side in a distal end direction of the operation lever **30** and an area extending from the fifth

linear axis L5 to the side in a proximal end direction of the operation lever 30. In the present embodiment shown in the drawings, the cut surface 31d is formed in both the distal end direction and in the proximal end direction across the fifth linear axis L5.

(126) Since the cut surfaces 31d are formed, the width of the outline of the shaft member 31 in the direction parallel to the longitudinal axis is smaller than the second outer diameter Do2 of the cylindrical surface 31b. Hereinafter, the width of the outline of the shaft member 31 in the direction orthogonal to the fifth linear axis L5 and the longitudinal axis is referred to as a third outline width Wo3. In the present embodiment, the third outline width Wo3 is equal to the second outer diameter Do2 of the cylindrical surface 31b. The width of the outline of the shaft member 31 in the direction parallel to the longitudinal axis is referred to as a fourth outline width Wo4. The fourth outline width Wo4 is the width of the outline of the shaft member 31 in the direction parallel to the third linear axis L3, in the state where the operation lever 30 is in the neutral position.

(127) The second constriction portion 22b formed in the opening 22a of the second recess 22 in the second bearing 20 has a minimum opening width, which is a second opening width Wi2, in the direction parallel to the fourth linear axis L4. The second opening width Wi2 is smaller than the third outline width Wo3 of the shaft member 31 and larger than the fourth outline width Wo4.

(128) As shown in FIG. 13, when the absolute value of the turning angle of the shaft member 31 around the second central axis A2 from the neutral position is in the vicinity of 90 degrees, the width of the outline of the shaft member 31 in the direction parallel to the fourth linear axis L4 is the fourth outline width Wo4. In this case, the shaft member 31 can pass through the second constriction portion 22b of the second recess 22.

(129) Note that a lateral wall surface of the second recess 22 of the second bearing 20 has a second groove 22c formed to avoid interference with the operation lever 30 whose inclination angle around the second central axis A2 is the vicinity of 90 degrees. The second groove 22c is shaped by notching the lateral wall surface of the second recess 22 with a prescribed width centered on a plane which is orthogonal to the second central axis A2 and including the fourth linear axis L4. The width of the second groove 22c is larger than the thickness of the lever member 32.

(130) Since the second groove 22c is formed, it is possible to prevent interference between the lever member 32 and the lateral wall surface of the second recess 22. The second groove 22c may also be formed on the opposite side from the second central axis A2.

(131) In the present embodiment, a third groove 12d is formed on a lateral wall surface of the first recess 12 as shown in FIG. 9. The third groove 12d is formed to avoid interference with the operation lever 30 whose inclination angle around the second central axis A2 is in the vicinity of 90 degrees. Since the third groove 12d is formed in the first recess 12, it is possible to set the inclination angle of the operation lever 30 around the second central axis A2 to the vicinity of 90 degrees, even in the state where the second bearing 20 is disposed in the first recess 12.

(132) On the other hand, as shown in FIG. 12, when the absolute value of the turning angle of the shaft member 31 around the second central axis A2 from the neutral position is equal to or less than the second limit angle θ_2 , the width of the outline of the shaft member 31 in the direction parallel to the fourth linear axis L4 is the third outline width Wo3. In this case, the shaft member 31 interferes with the second constriction portion 22b of the second recess 22, and therefore cannot pass through the second constriction portion 22b. Therefore, in this case, the shaft member 31 is prevented from dropping off from the second recess 22.

(133) With the configuration described in the foregoing, the bearing portion 5b in the present embodiment prevents the second bearing 20 from dropping off from the first bearing 10 and prevents the operation lever 30 from dropping off from the second bearing 20.

(134) The bearing portion 5b in the present embodiment can prevent separation of the first bearing 10, the second bearing 20, and the operation lever 30, after these members are assembled at the time of an assembling work of the endoscope 1. Therefore, the bending operation mechanism 5 for the endoscope 1 of the present embodiment can facilitate the assembling work of the bearing

portion **5b** into the cover member **3a**.

(135) Note that the bearing portion **5b** in the present embodiment, as in the case of the first embodiment, is configured of three members including the first bearing **10**, the second bearing **20**, and the shaft member **31**, each of which can be manufactured by molding at low costs. Since assembling of the bearing portion **5b** is completed by simply combining the three members, the assembling is completed in a fewer procedures. Therefore, the bending operation mechanism **5** for the endoscope **1** in the present embodiment can be manufactured at low costs as in the case of the first embodiment.

Third Embodiment

(136) Hereinafter, a third embodiment of the present invention will be described. In the following description, only the differences from the second embodiment will be described, and component members similar to the component members of the second embodiment will be designated by the same signs to omit the description as appropriate.

(137) As shown in FIG. **14**, the bending operation mechanism **5** of the present embodiment is different from the bending operation mechanism **5** of the second embodiment in that the bearing portion **5b** includes holes **51**.

(138) The holes **51** are similar in configuration to the holes **51** in the first embodiment. In other words, the bearing portion **5b** in the present embodiment includes one or more holes **51** having a depth to at least the shaft member **31** from the outer surface of the first bearing **10** in the state where the operation lever **30** is in the prescribed position.

(139) Inside the hole **51**, one pin **52** can be inserted as shown in FIG. **7**, provided that the operation lever **30** is in the state of being at the prescribed position. The hole **51** is disposed so as to satisfy either the condition of not passing through the support point **P** or the condition of passing through the support point **P** but not in parallel with both the first central axis **A1** and the second linear axis **L2**. Therefore, the pin **52** inserted in the hole **51** restricts the movement of the second bearing **20** and the shaft member **31** relative to the first bearing **10**.

(140) In the present embodiment, the operation lever **30** can be fixed in a prescribed position by inserting the pin **52** into the hole **51**. For example, when the operation lever **30** can temporarily be fixed in the neutral position during assembling of the endoscope **1**, it becomes possible to easily adjust the tension applied to the plurality of wires **50**.

(141) Therefore, since the bearing portion **51b** in the present embodiment includes the holes **51**, it becomes possible to facilitate an assembling work of the bending operation mechanism **5**.

(142) Other components of the bending operation mechanism **5** are similar to the components of the second embodiment. Therefore, the bending operation mechanism **5** of the present embodiment can prevent separation of the first bearing **10**, the second bearing **20**, and the operation lever **30**, after these members are assembled at the time of an assembling work of the endoscope **1**.

Therefore, the bending operation mechanism **5** for the endoscope **1** of the present embodiment can facilitate the assembling work of the bearing portion **5b** into the cover member **3a**.

(143) The bearing portion **5b** in the present embodiment, as in the case of the first embodiment, is also configured of three members including the first bearing **10**, the second bearing **20**, and the shaft member **31**, each of which can be manufactured by molding at low costs. Since assembling of the bearing portion **5b** is completed by simply combining the three members, the assembling is completed in a fewer procedures. Therefore, the bending operation mechanism **5** for the endoscope **1** in the present embodiment can be manufactured at low costs as in the case of the first embodiment.

(144) The present invention is not limited to the embodiments disclosed. Changes are possible as appropriate without departing from the gist or idea of the present invention which are understood from the claims and the specification in its entirety. Endoscopes with such changes are also included in the technical scope of the present invention.

Claims

1. An endoscope, comprising: a first bearing including a first recess, the first recess having a first interior cylindrical shape with a first axis; a second bearing having a first exterior cylindrical shape corresponding to the first interior cylindrical shape such that the second bearing is retained rotatably in the first recess to rotate around the first axis, the second bearing including a second recess, the second recess having a second interior cylindrical shape with a second axis intersecting the first axis; and an operation lever including a first shaft having a second exterior cylindrical shape corresponding to the second interior cylindrical shape such that the first shaft is retained rotatably in the second recess to rotate around the second axis wherein the operation lever includes a second shaft extending from an outer surface of the first shaft in a direction orthogonal to the second axis, the second shaft configured to rotate together with the first shaft, and the first bearing further includes a first groove in communication with the first recess, the first groove configured to receive a portion of the second shaft when the second shaft is rotated about the first axis to be within the first groove.
2. The endoscope according to claim 1, further comprising a stopper configured to restrict movement of the operation lever in a longitudinal axis direction of the operation lever.
3. The endoscope according to claim 2, wherein the stopper is a pin, the first bearing, the second bearing, and the first shaft include respective holes that simultaneously accept the pin, and when the pin is inserted into the holes, movement of the first bearing, the second bearing, and the operation lever is restricted.
4. The endoscope according to claim 3, wherein the holes are formed at a position apart from the first axis and apart from the second axis.
5. The endoscope according to claim 1, wherein the first recess is open in a longitudinal axis direction of the operation lever, the second recess is open in a direction orthogonal to the first axis and the second axis.
6. The endoscope according to claim 1, wherein the first shaft having: a largest first width in a first direction orthogonal to a longitudinal axis direction of the operation lever; and a largest second width in a second direction orthogonal to the first direction; and a minimum width of an opening of the second recess is smaller than the largest first width and larger than the largest second width.
7. The endoscope according to claim 1, wherein the operation lever includes a second shaft extending from an outer surface of the first shaft in a direction orthogonal to the second axis, the second shaft configured to rotate together with the first shaft, and the endoscope further includes a second groove in communication with the second recess, the second groove configured to receive a portion of the second shaft when the second shaft is rotated about the second axis to be within the second groove.
8. The endoscope according to claim 1, further comprising a stopper, the stopper is a cover member having an opening configured to restrict movement of the operation lever about the first axis and about the second axis.
9. The endoscope according to claim 8, wherein the operation lever extends to an outside of the cover from the opening.
10. The endoscope according to claim 1, further comprising a finger contact member disposed at an end portion of the operation lever.
11. The endoscope according to claim 1, further comprising: an operation portion; and an insertion portion disposed distally relative to the operation portion, the insertion portion including a bending portion, wherein the operation lever is disposed in the operation portion and connected to a plurality of wires configured to bend the bending portion.
12. The endoscope according to claim 11, wherein the operation lever is provided with a dome body, a proximal end of each of the plurality of wires is fixed to the dome body.

13. The endoscope according to claim 12, wherein the dome body further comprising a retention member to which the plurality of wires are fixed.

14. A bending operation mechanism for use with an endoscope, the bending operation mechanism comprising: a first bearing including a first recess, the first recess having a first interior cylindrical shape with a first axis; a second bearing, the second bearing having a first exterior cylindrical shape corresponding to the first interior cylindrical shape such that the second bearing is retained rotatably in the first recess to rotate around the first axis, the second bearing including a second recess, the second recess having a second interior cylindrical shape with a second axis intersecting the first axis; and an operation lever including a first shaft having a second exterior cylindrical shape corresponding to the second interior cylindrical shape such that the first shaft is retained rotatably in the second recess to rotate around the second axis intersecting the first axis; wherein the operation lever includes a second shaft extending from an outer surface of the first shaft in a direction orthogonal to the second axis, the second shaft configured to rotate together with the first shaft, and the first bearing further includes a first groove in communication with the first recess, the first groove configured to receive a portion of the second shaft when the second shaft is rotated about the first axis to be within the first groove.

15. An operation portion for an endoscope, the operation portion comprising the bending operation mechanism according to claim 14.

16. The endoscope according to claim 1, wherein the second bearing having: a largest first width in a first direction orthogonal to an opening direction of the second recess; and a largest second width in a second direction orthogonal to the first direction, the largest second width being smaller than the largest first width, and a minimum width of the opening of the first recess is smaller than the largest first width and larger than the largest second width.

17. The endoscope according to claim 1, further comprising converting means for converting movement of the operation lever to bending of a bending section at a distal portion of the endoscope.

18. The endoscope according to claim 1, wherein the converting means comprising a plurality of wires operatively connected at one end to the operation lever and at another end to the bending section.

19. The endoscope according to claim 1, wherein first axis and the second axis intersect at 90 degrees.
