



US012383102B2

(12) **United States Patent**
Kolar et al.

(10) **Patent No.:** **US 12,383,102 B2**
(45) **Date of Patent:** ***Aug. 12, 2025**

(54) **INTERLOCKING BLENDING SYSTEM**

(71) Applicant: **VITA-MIX MANAGEMENT CORPORATION**, Olmsted Township, OH (US)

(72) Inventors: **David J. Kolar**, Stow, OH (US); **Saifur Tareen**, Copley, OH (US); **Eric Miller**, Olmsted Township, OH (US)

(73) Assignee: **Vita-Mix Management Corporation**, Olmsted Township, OH (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 988 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **17/460,357**

(22) Filed: **Aug. 30, 2021**

(65) **Prior Publication Data**

US 2022/0087480 A1 Mar. 24, 2022

Related U.S. Application Data

(63) Continuation of application No. 15/551,486, filed as application No. PCT/US2016/018335 on Feb. 17, 2016, now Pat. No. 11,103,107.

(Continued)

(51) **Int. Cl.**
A47J 43/07 (2006.01)
B01F 35/60 (2022.01)

(Continued)

(52) **U.S. Cl.**
CPC **A47J 43/0777** (2013.01); **A47J 43/0766** (2013.01); **B01F 35/6052** (2022.01); **B01F 2101/1805** (2022.01); **F16P 1/00** (2013.01)

(58) **Field of Classification Search**

CPC A47J 43/0766

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,533,806 A 7/1996 Veltrop
6,513,966 B1 2/2003 Gort-Barten et al.

(Continued)

FOREIGN PATENT DOCUMENTS

AU 2007228489 B2 9/2007
EP 0046169 2/1982
WO 97034518 9/1997

OTHER PUBLICATIONS

Machine translation of Description of EP 0046169 A. Generated Aug. 28, 2024.*

(Continued)


Primary Examiner — David L Sorkin

(74) *Attorney, Agent, or Firm* — Dinsmore & Shohl LLP

(57) **ABSTRACT**

A blending system is shown and described herein. The blending system may include a base including a motor, a blade selectively and operably engaged with the base, where the motor rotates the blade, a container having an open end and a lid configured to cover the open end. The blending system may also include an interlock system that may include a plurality of induction coils positioned on the base and the container and be in electrical communication with at least one lid sensor, wherein the power is translated through the induction coils to engage a switch device to complete a power circuit to allow a user to operate the motor of the blender.

16 Claims, 19 Drawing Sheets



Related U.S. Application Data

- (60) Provisional application No. 62/152,380, filed on Apr. 24, 2015, provisional application No. 62/117,090, filed on Feb. 17, 2015.

(51) **Int. Cl.**

B01F 101/00 (2022.01)
F16P 1/00 (2006.01)

(58) **Field of Classification Search**

USPC 241/37.5; 366/205, 306, 314, 601, 206
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,018,091 B2 3/2006 Arroubi et al.
8,807,818 B2 8/2014 Hirohata

11,103,107 B2 * 8/2021 Kolar A47J 43/0777
2002/0079393 A1 6/2002 Karkos et al.
2004/0100862 A1 5/2004 Arroubi
2013/0074706 A1 3/2013 Fevre
2014/0286120 A1 9/2014 Kolar
2014/0286123 A1 * 9/2014 Arnett A47J 43/0766
366/205
2015/0035381 A1 2/2015 Mach et al.

OTHER PUBLICATIONS

Machine translation of Claims of EP 0046169 A. Generated Aug. 28, 2024.*
Patent Cooperation Treaty (PCT), International Search Report and Written Opinion for Application PCT/US2016/018335 filed Feb. 17, 2016 mailed Jul. 11, 2016, International Searching Authority, US. Supplementary European Search Report for Application No. 16753005.4 relating to PCT/US2016018335, dated Nov. 15, 2018, 8 pages.

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12

FIG. 13







FIG. 14






FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20







FIG. 21

**FIG. 22**

**FIG. 23**

**FIG. 24**




FIG. 25

1

INTERLOCKING BLENDING SYSTEM**CROSS-REFERENCE TO RELATED APPLICATION**

This application is a continuation of U.S. Utility application Ser. No. 15/551,486 filed on Aug. 16, 2017 entitled “INTERLOCKING BLENDING SYSTEM” which claims the benefit of International Application No. PCT/US2016/018335 filed on Feb. 17, 2016 entitled “INTERLOCKING BLENDING SYSTEM” which claims priority to U.S. Provisional Application No. 62/117,090 entitled “INDUCTIVE INTERLOCK SYSTEM,” filed on Feb. 17, 2015, and U.S. Provisional Application No. 62/152,380 entitled “INDUCTIVE INTERLOCK SYSTEM,” filed on Apr. 24, 2015, which are hereby incorporated by reference in their entirety.

TECHNICAL FIELD

The present teachings relate to a system for interlocking a blender device, and more particularly, to a blender system utilizing wireless transmissions to safely interlock a blending system.

BACKGROUND

Blending systems are often used to blend and process foodstuffs. Conventional blenders generally include a base with a motor, a mixing container with an operable mixing blade disposed therein. A blender lid is adapted to cover the mixing container. A user inserts contents within the mixing container to be mixed by the rotation of the blade. The mixing container is positioned on the base as a user controls operation of the motor within the base to rotate the mixing blade within the mixing container to mix the contents therein.

It may be desirable to generally prevent the mixing blades from rotating when the blender lid is removed from the mixing container. Interlocking systems may be utilized to attempt to prevent the mixing blades from rotating when the blender lid is not operatively positioned on the mixing container. These interlock systems generally prevent operation of the rotation of the mixing blade unless the blender lid is covering the mixing container.

Known blending interlock systems have been disclosed by U.S. Pat. No. 8,403,556 to Wu to include a latch cover mechanism with a link rod and a compression spring in communication with a power circuit control switch in the base of the blender.

Additionally, U.S. Pat. No. 8,702,300 to Audette discloses a blending apparatus having a container, a lid for covering the container, and an attachment within the container. The attachment engages the lid and a drive member at the base of the blender to actuate a motor once the lid is secured to the container.

Typically, known blender interlocks require a physical connection between the lid and the motor. These interlocks generally include a system of mechanical arms, links, springs or other attachments that prevent the user from operating the motor to rotate the mixing blade unless the blender lid is secured onto the container.

However, the problem with these interlock systems on many consumer products is that they include mechanisms that can be ineffective at consistently providing a signal the blender lid is in place when, in fact, it is not. Additionally, mechanical interlock systems take up extra space for mechanical connection paths and these connection paths

2

may not allow for sufficient vibration isolation or dampening. Generally, known blender system interlocks are subject to operational limitations caused by vibrations of the operating motor. Further still, these mechanical systems may be difficult to clean.

Therefore, a need exists for interlock systems that reduces the risk of inconsistent operation, takes up less space, and are not subject to an increase in operational issues caused by motor vibration.

SUMMARY

A container interlock system may include a base and a container operably engaged with the base, where the container includes an open end. A lid may selectively attach to the container to cover the open end. An interlock assembly having a plurality of induction coils may be provided to engage a switch device when the lid is attached to the container to cover the open end and the container is operably engaged to the base. The interlock assembly may include at least one transmitter coil and at least one receiver coil mounted to a pad positioned on the base. The transmitter coil may be in electrical communication with a power source, and the receiver coil may be in electrical communication with the switch device. The transmitter coil may be isolated electronically from the receiver coil when the container is not positioned on the base.

The container may include a bridge coil assembly. The bridge coil assembly may include a first coil in electronic communication with a second coil. The first and second coils may be in communication with at least one lid switch. The lid switch may be provided generally adjacent the open end of the container and be engaged to provide a signal or complete a bridge circuit when the lid is attached to the container to cover the open end.

The interlock assembly may provide selective power to the switch device that may permit operation of a motor when the first coil is in electromagnetic communication with the transmitter coil, the second coil is in electromagnetic communication with the receiver coil, and the lid switch is engaged. The selective power may be generated by the interlock assembly as the lid is attached to the container and the container is positioned on the base.

The lid switch may be a reed type switch and the lid may contain magnets configured to engage the reed switches when the lid is attached to the open end of the container. Alternatively, the transmitter and receiver coils may be mounted to a printed circuit board.

In another embodiment, provided is a blending system that may include a base encasing a motor, a blade within a container, and a lid to cover an open end of the container. An interlock detector may be attached to the base for detecting a position of the lid relative to the container to allow operation of the motor.

An interlock detector assembly may be adapted to provide a signal when the lid is attached to the container to cover the open end and the container is operably engaged to the base. The interlock detector assembly may be positioned on a pad or circuit board and may be mounted to the base. The interlock detector assembly may include a first induction coil assembly on the pad and a second induction coil assembly on the container. The second induction coil assembly may be in communication with at least one lid switch positioned adjacent the open end of the container that may identify if the lid is attached to or covers the open end.

The interlock detector assembly may be adapted to provide power to a relay switch when the lid covers the open

3

end of the container and the container is operably engaged to the base. The first induction coil assembly may include at least one transmitter coil and at least one receiver coil. The transmitter coil may be in electrical communication with a power source and the receiver coil may be in electrical communication with the relay switch for a motor. The transmitter coil may be electromagnetically isolated from the receiver coil when the container is not positioned on the base or the lid is detached from the open end of the container.

The second induction assembly may include a first inductor in electronic communication with a second inductor. The first and second inductors may be in communication with at least one lid switch. The lid switch may be provided adjacent the open end of the container and be configured to provide a signal when the lid is attached to the container to cover the open end.

The interlock detector assembly may provide selective power to engage a switch that would permit operation of a motor when the first contactor is in communication with the transmitter coil, the second contactor is in communication with the receiver coil, and the lid covers the container.

DESCRIPTION OF THE DRAWINGS

The present teachings may be better understood by reference to the following detailed description taken in connection with the following illustrations, wherein:

FIG. 1A is a front view of an embodiment of a blender system in a non-interlocked state in accordance with the present disclosure;

FIG. 1B is a front view of the blender system of FIG. 1A in an interlocked state in accordance with the present disclosure;

FIG. 2 is a schematic diagram of a base including one or more inductive coils in accordance with the present disclosure;

FIG. 3 is a partial cross-sectional view of a blender system including the base of FIG. 2 in accordance with embodiments of the present disclosure;

FIG. 4 is a schematic diagram of a base that includes two coils and a shared power source in accordance with embodiments of the present disclosure;

FIG. 5 is a perspective top view of a base and a bottom view of a container of a blending system that inductively interlocks in accordance with the present disclosure;

FIG. 6 is a partial cross-sectional, side view of a container that operatively couples with a lid including one or more actuators in accordance with the present disclosure;

FIG. 7 is a partial cross-sectional, side view of a container that operatively couples with a lid including one or more magnets in accordance with the present disclosure;

FIG. 8 is a partial cross-sectional, side view of a blending system including a container that operatively couples with a lid and a base, the container including one or more pushrods in accordance with the present disclosure;

FIG. 9 is a partial cross-sectional, side view of a container that operatively couples with a lid, the lid physically actuating a pushrod of the container in accordance with the present disclosure;

FIG. 10 is a partial cross-sectional, side view of a blending system including a container that operatively couples with a base, the container including a connection line that electrically couples to a blade assembly in accordance with the present disclosure;

4

FIG. 11 is a partial cross-sectional, side view of a container and a lid including a handle that actuates a pushrod in accordance with the present disclosure;

FIG. 12 is a partial cross-sectional, prospective view of a container, lid, and pedestal of a blending system including one or more sensing coils in accordance with the present disclosure;

FIG. 13 is an exploded, prospective view of the blending system of FIG. 12 in accordance with the present disclosure;

FIG. 14 is a partial cross-sectional, side view of the blending system of FIG. 12 in accordance with the present disclosure;

FIG. 15A is an exemplary circuit diagram of an RL circuit that operatively measures reactance of a blending system in accordance with the present disclosure;

FIG. 15B is an exemplary circuit diagram of an LC circuit that operatively measures properties of a blending system in accordance with the present disclosure;

FIG. 15C is an exemplary circuit diagram of a resonating LC circuit that may include an inductive coil and one or more capacitors in series in accordance with the present disclosure;

FIG. 16 is an exploded, prospective view of a lid and a container of a blending system, the container including one or more contact pins in accordance with the present disclosure;

FIG. 17 is an exploded, prospective view of the blending system of FIG. 16 in accordance with the present disclosure;

FIG. 18 is a partial cross-sectional, side view of the blending system of FIG. 14 illustrating a connection between the container and a base in accordance with the present disclosure;

FIG. 19 is a partial cross-sectional, side view of the blending system including a flexible lid that operatively attaches or engages a container in accordance with the present disclosure;

FIG. 20 is a partial cross-sectional, side view of the blending system including a container comprising a sealed switch in accordance with the present disclosure;

FIG. 21 is a partial cross-sectional, side view of the blending system including a container comprising a sealed switch and a lid that operatively actuates the sealed switch in accordance with the present disclosure;

FIG. 22 is a partial cross-sectional, side view of the blending system including one or more pushrods in accordance with the present disclosure;

FIG. 23 is a partial cross-sectional, side view of the blending system including one or more light sensors in accordance with the present disclosure;

FIG. 24 is flowchart of a method for operating a blender in accordance with embodiments of the present disclosure; and

FIG. 25 is a partial cross-sectional, side view of the blending system that may detect properties of one or more inductive coils in accordance with the present disclosure.

DETAILED DESCRIPTION

Reference will now be made in detail to embodiments of the present teachings, examples of which are illustrated in the accompanying drawings. It is to be understood that other embodiments may be utilized and structural and functional changes may be made without departing from the respective scope of the present teachings. Moreover, features of the various embodiments may be combined, switched, or altered without departing from the scope of the present teachings, e.g., features of each embodiment disclosed herein may be

5

combined, switched, or replaced with features of the other embodiments disclosed herein. As such, the following description is presented by way of illustration only and should not limit in any way the various alternatives and modifications that may be made to the illustrated embodiments and still be within the spirit and scope of the present teachings.

As used herein, the words “example” and “exemplary” mean an instance, or illustration. The words “example” or “exemplary” do not indicate a key or preferred aspect or embodiment. The word “or” is intended to be inclusive rather than exclusive, unless context suggests otherwise. As an example, the phrase “A employs B or C,” includes any inclusive permutation (e.g., A employs B; A employs C; or A employs both B and C). As another matter, the articles “a” and “an” are generally intended to mean “one or more” unless context suggest otherwise.

It is noted that references to a blender, blender system, and the like, are understood to include food processor systems, and other mixing systems. Such systems generally include a blender base that may include a motor, a blade assembly, and a controller. Further, such systems may include a container, a display, a memory and/or a processor. A blade assembly, a blending container, and a blender base may removably or irremovably attach. The blending container may be powered in any appropriate manner, such as disclosed in U.S. patent application Ser. No. 14/213,557, entitled Powered Blending Container, which is hereby incorporated by reference.

Furthermore, while blending of “ingredients,” “contents” or “foodstuffs” is described by various embodiments, it is noted that non-food stuff may be mixed or blended, such as paints, epoxies, construction material (e.g., mortar, cement, etc.), and the like. Moreover, blending of ingredients or may result in a blended product. Such blended products may include drinks, frozen drinks, smoothies, shakes, soups, purees, sorbets, butter (nut), dips or the like. It is noted that various other blended products may result from blending ingredients. Accordingly, terms such as “blended product” or “drink” may be used interchangeably unless context suggests otherwise or warrants a particular distinction among such terms. Further, such terms are not intended to limit possible blended products and should be viewed as examples of possible blended products.

In embodiments, the blending systems may include any household blender and/or any type of commercial blending system, including those with covers that may encapsulate or partially encapsulate the blender. Commercial blending systems may include an overall blending system, such as a modular blending system that may include the blender along with other components, such as a cleaner, foodstuff storage device (including a refrigerator), an ice maker and/or dispenser, a foodstuff dispenser (a liquid or powder flavoring dispenser) or any other combination of such.

As used herein, the phrases “blending process,” “blending program,” and the like are used interchangeably unless context suggest otherwise or warrants a particular distinction among such terms. A blending process may comprise a series or sequence of blender settings and operations to be carried out by the blending device. In an aspect, a blending process may comprise at least one motor speed and at least one time interval for the given motor speed. For example, a blending process may comprise a series of blender motor speeds to operate the blender blade at the given speed, a series of time intervals corresponding to the given motor speeds, and other blender parameters and timing settings. The blending process may further include a ramp up speed that defines the amount of time the motor takes to reach its

6

predetermined motor speed. The blending process may be stored on a memory and recalled by or communicated to the blending device.

Generally, wireless transmission may be the transmission of electrical signals from a power source to a device without using solid wires or conductors. This form of transmission uses time-varying electromagnetic fields and may be useful in cases where solid wires or contacts are undesired.

A blending system with interlocking capabilities is described herein. In an aspect, embodiments generally include a blender base (housing a motor), a container, and a lid. In an aspect, the blender system can determine whether the blender base, container, and lid are “interlocked” (i.e., they are in an operative position whereby a user is prevented from contacting the blades). The blender system may include inductive and/or magnetic components disposed in at least one of the blender base, container, or lid. When the blender system is fully connected, the inductive components may interact with each other. The interaction may induce current flow to, for example, complete a circuit and/or allow operation of a motor, which allows the blades to rotate within the container.

This disclosure provides various exemplary embodiments. The embodiments may be altered, arranged, or modified as desired such that a blending system selectively allows operation of a motor and/or blade assembly. For instance, containers, bases and/or lids of different figures may be interchanged. Further, while an embodiment may not show a particular aspect (e.g., pushrod, light sensor, inductive coil, switch, magnet, etc.), it is noted that modifications may be made to the embodiment to include the not shown aspects. In this manner, this disclosure provides for numerous embodiments that may be selectively utilized to determine whether a blending system is interlocked and/or to selectively allow operation of a motor or blade assembly.

Referring now to FIGS. 1A and 1B, there depicted is a front view of a blending system **100** in a non-interlocked state **102** and an interlocked state **104**. The blending system **100** may primarily include a base **110**, a container **120**, and a lid **130**. The base **110** may be any appropriate size and configuration. The base **110** may house and generally protect the operative components of the blending system **100**, such as a motor, fan, controllers, circuitry, human interfaces (e.g., touch screen, LED or LCD displays, lights, buttons, knobs, dials, or other actuators), and the like. As illustrated, the base **110** may include a control panel **114** positioned on a face of the base **110** such that a user may interact with the control panel **114**. The control panel **114** may be of any appropriate configuration and may allow a user to set the operative condition of the blending system **100**. It will be appreciated that the control panel **114** may include one or more human interfaces.

Container **120** may include and/or be coupled with an agitator or blade assembly **122**. The blade assembly **122** may be of appropriate configurations and may be configured to rotate within the container **120** (e.g., via a motor). For instance, a user may place foodstuff within the container **120** to allow blade assembly **122** to chop, mix, blend, or otherwise interact with the foodstuff.

In interlocked state **104**, the container **120**, base **110**, and lid **130** may be interconnected in an appropriate manner. For instance, lid **130** may be attached or coupled to an open end **124** of container **120**. According to an embodiment, the lid **130** may be press-fit (e.g., friction fit) within or about the open end **124**, twisted (e.g., via threaded members), latched, or otherwise connected with the open end **124**. It is noted that lid **130** and container **120** may be coupled via various

other means, including magnetic means, VELCRO, mechanical fasteners, or the like.

Furthermore, container 120 may be attached to or otherwise operatively engaged with the base 110. In at least one embodiment, base 110 may include protrusions 112 that guide the alignment of container 120. It is noted that the container 120 may be attached to the base by threaded members, fasteners, press-fit geometries, magnetic means, or the like. In at least one embodiment, the weight of container 120 may provide sufficient force to maintain a connection between base 110 and container 120.

Blade assembly 122 may include a splined shaft that operatively engages with a splined coupling of the base 110. For instance, when the container 120 is operatively placed on base 110, the splined coupling receives the splined blade shaft, which depends downwardly from the bottom of the container 120. A motor may drive the splined coupling which, in turn, drives the splined blade shaft. Driving of the splined blade shaft causes rotation of the blade assembly 122 within the container 120.

In the non-interlocked state 102, the container 120 is not operatively connected to at least one of the lid 130 or base 110. It is noted that FIG. 1A depicts the container 120 as not operatively connected to both the lid 130 and base 110. According to embodiments, the blending system 100 may prevent or prohibit operation of the motor when in the non-interlocked state 102 and may allow or enable operation of the motor when in the interlocked state 104. Alternatively or additionally, when in the interlocked state 104, the blade assembly 122 may be prevented from rotating.

Embodiments will be described herein with reference to FIGS. 1A and 1B. It is noted that the configurations of base 110, container 120, and lid 130 are provided for reference and example. As such, various other configurations are within the scope and spirit of this disclosure.

Turning to FIGS. 2 and 3, a blender system 200 including base 201, container 300, and lid 320 are depicted. The blender system 200 may disable one or more operations of base 201 (e.g., disable actuation of a motor and/or blade assembly) when the blender system 200 is in a non-interlocked state 102.

Base 201 may utilize wireless transmissions to control a power supply that enables operation of a motor 216 and/or blade assembly 322. Base 220 may include a housing 228 that may house the motor 216 and other operative components. The motor 216 may be in operative communication with a power supply 218 by way of a power circuit 226. For instance, motor 216 may receive power from power mains, a battery, or the like. In an example, the motor 216 may utilize the power to rotate the blade assembly 322 when the container 302 is operatively engaged with the base 201. It is noted that other components (e.g., a control panel 232, display, etc.) may be coupled to power supply 218. In an aspect, the other components may be connected via power circuit 226 or via another power circuit (not shown). For instance, power may be supplied to an LCD screen independent of power supplied to a motor 216.

The power circuit 226 may include a switch device 220 that may be of any appropriate configuration—the present teachings are not limited to the configurations shown and described herein. The switch device 220 may include a relay switch 224 that may be configured to operatively alter states between an open and closed state. In a closed state (not shown), the relay switch 224 completes the power circuit 226 to allow a user to operate the motor 216 and/or blade assembly 322. In an open state, the relay switch 224 breaks the power circuit 226 to prevent power flow to the motor

216. The relay switch 224 may be closed when an inductor 222 is engaged as will be described in more detail herein.

The housing 228 may include or house a circuit board 202 (e.g., printed circuit board). The circuit board 202 may be of any appropriate shape and size and may be materially integral with the blender base 201 or separately mounted thereon. The circuit board 202 may include one or more inductive pads or other circuitry, including inductive coils. In an embodiment, a first inductive pad may comprise at least one transmitter assembly 206 and a second inductive pad may comprise at least one receiver assembly 204. It is noted transmitter assembly 206 and receiver assembly 204 may be mounted to the circuit board 202 or may be otherwise disposed within or on housing 228. The circuit board 202 and the base 201 may be of any appropriate configuration.

The transmitter assembly 206 may include a first transmitter coil 208 and a second transmitter coil 210 that are in general electric communication along the circuit board 202. The transmitter assembly 206 may be in electrical communication with a power source 209 (e.g., power mains, battery, power source 218, etc.). The transmitter assembly 206 may be an arrangement of coils or conductors of any induction type configuration that is configured to transmit power by electromagnetic fields across an intervening space.

The receiver assembly 204 may include a first receiver coil 212 and a second receiver coil 214 that may be in general electric communication along the circuit board 202. The receiver assembly 204 may be in electric communication with the switch device 220. The receiver assembly 204 may be an arrangement of coils or conductors of any configuration that receives power by electromagnetic fields across an intervening space. Such coils may be electrically coupled to inductor 222. The receiver coil assembly 204 may be electromagnetically isolated from the transmitter assembly 206, such that current flow through the first and second transmitter coils 208 and 210 may not induce current through first and second receiver coils 212 and 214. If current flows through the receiver coils 212 and 214, the current will pass through the inductor 222. Current through the inductor 222 will close the relay switch 224, completing the power circuit 226. This arrangement allows the motor 216 to be powered by the motor power source 218 subject to the use of the control panel 232. Thus, absent a bridge, the motor 216 will be disabled.

Turning to FIG. 3, depicted is a schematic diagram of the blending system including base 201, container 302, and lid 320. In an aspect, the container 302 may comprise an apron 304 or engagement portion at a closed end (as described in more detail herein), and an open end 310 configured to receive and/or couple with the lid 320. The container 302 and/or lid 320 may comprise bridge circuitry, including a bridge circuit assembly 324 and one or more switches (e.g., read switches 314).

In an aspect, bridge circuit assembly 324 may include one or more inductive coils, such as first coil 306 and second coil 308. The first and second coils 306, 308 may comprise a coil that is disposed within apron 304, adhered to apron 304 (e.g., on a first or bottom side 350 opposite the blender blade, on a second or top side 352, etc.), disposed within a wall 356, or the like. It is noted that the first and second coils 306, 308 may be disposed in a location that allows, when blending system 300 is selectively assembled, for reception or transmission of an electronic signal from first or second coils 306, 308 to one or more of first transmitter coil 208, second transmitter coil 210, first receiver coil 212 or second receiver coil 214, as described in more detail herein.

The first and second coils **306**, **308** may be in electric communication with one or more switches, such as first and second lid switches **314** and **316**. For instance, a first connection line **360** may electrically couple first coil **306** with first lid switch **314**, and a second connection line **362** may electrically couple second coil **308** with second lid switch **316**. It is noted that first and second lid switches **314** and **316** may be electrically coupled with each other, such as through wire coupling, flexible circuit board coupling, or the like. According to described embodiments, when either first or second lid switches **314**, **316** are open, the bridge circuit assembly **324** is incomplete; when both first and second lid switches **314**, **316** are closed the bridge circuit assembly **324** is complete (e.g., the circuit is complete), allowing for flow of an electrical signal between first coil **306** and second coil **308**.

The lid switch **314** may be provided adjacent or proximal the open end **310** of the container **302** and be configured to be closed when the lid **320** is attached to the container **302** to cover the open end **310**. In one embodiment, the first and second lid switches **314**, **316** may be one or more of a reed switch, mechanical switch, Hall-Effect sensors, or the like. The first and second lid switches **314**, **316** may be selectively engaged by one or more actuators within the lid **320** (e.g., a wall of lid **320**, a magnet, a protrusion or notch, etc.). For example, the first and second lid switches **314**, **316** may be reed switches, and the lid **320** may include one or more magnet(s) **312**, which may magnetically engage the first and second lid switches **314**, **316**. It is noted that the magnets **312** may comprise a magnetic band disposed within or about the lid, *n* magnets (where *n* is a number), or the like. In at least one example, the magnets **312** may be positioned in a predefined location, such that the magnets only engage the first and second lid switches **314**, **316** when lid **320** is operatively secured to the container **302**. It is noted that the quantity and location of lid switches and/or magnets may be of any appropriate configuration.

According to one or more embodiments, the various circuitry components of lid **320** and/or container **302** may be protected from an external environment and/or exposure to foodstuffs. For instance, connection lines **360**, **362** may be disposed within wall **356** of container **302**. As an example, connections lines **360**, **362** may comprise one or more wires (e.g., which may be comprised within a flexible circuit) that are disposed or suspended within glass, plastic, between an inner and outer wall of a double walled container, or the like. In another example, wires may be disposed on an outer surface of container **302** and sealed by a protective coating or layer. In a similar aspect, first and second lid switches **314**, **316** may be disposed within wall **356**, sealed on a surface of wall **352**, or the like. It is noted that the container **302** and/or lid **320** may be dishwasher safe and/or safe from exposure to other harsh environments.

In an aspect, magnets **312** may be disposed within a body **330** of lid **320** (e.g., within a rubber, plastic, or other material comprising the lid), may be partially exposed, and/or may be attached to a surface of lid **320**. It is noted that magnets **312** may be selectively coupled or attached to lid **320**. For instance, magnets **312** may be configured to attach to one or more makes or models of lids based on whether the lid **320** may be operatively used with blender system **300**. This may allow magnets **312** to selectively attach to retrofit existing lids for use with system **300**.

Referring now to base **201**, as depicted in FIGS. **2** and **3**, the container **302** may be configured to selectively attach, engage, or mate with base **201**. When the container **302** is operably positioned on the base **201**, first and second coils

306, **308** are each generally aligned adjacent to at least one coil of the base **201** (e.g., first transmitter coil **208**, second transmitter coil **210**, first receiver coil **212** and/or second receiver coil **214**). This may position the coils of the container **302** to receive (e.g., from first or second transmitter coil **208**, **210**) an electrical signal and selectively transmit an electrical signal to a receiver (e.g., first or second receiver coil **212**, **214**), as described in more detail herein.

In an embodiment, the power source **209** provides current to the transmitter assembly **206** which is electrically isolated from the receiver assembly **204** along the circuit board **202** (e.g., and/or on a different circuit board). The container **302** may be operably engaged with the base **201** such that an engagement portion **304** is aligned with the circuit board **202**. It is noted that container **302** may be positioned such that at least one of first coil **306** or second coil **308** may be adjacent to at least one of first or second transmitter coil **208**, **210**. In another aspect, the first or second coil **306**, **308** that is not adjacent to a transmitter coil, may be adjacent to at least one of first or second receiver coil **212**, **214**. In this manner, the container **302** may be attached to the base **201** at one or more positions. For simplicity of explanation, references will be made to coils in a specific arrangement. It is noted, however, that system **300** may be configured in other arrangements.

In an aspect, the first coil **306** may be placed within a threshold proximity or distance to the transmitter assembly **206** such that the first coil **306** may be inductively coupled to the transmitter assembly **206** when power is supplied to the transmitter assembly **206**. If the lid **320** is attached to the open end **310** of the container **302**, the magnets **312** may engage first and second lid switches **314** and **316**. When the first and second lid switches **314** and **316** are engaged or closed, an electric signal may pass from first coil **306**, through the connection lines, to the second coil **308**. If the lid **320** is detached or otherwise not operatively attached, the first and second lid switches **314**, **316** will open to prevent current flow to second coil **308**.

Second coil **308** may be placed in close proximity to the receiver assembly **204** such that the second coil **308** may be inductively coupled to the receiver assembly **204**. For instance, second coil **308** may be positioned a threshold distance from receiver assembly **204** to allow second coil **308** to induce current in the first receiver coil **212** or the second receiver coil **214** of the receiver assembly **204**. It is noted that the threshold distance may depend on the characteristics of the coils (e.g., size, gauge, etc.), amount of current or voltage, or the like.

Accordingly, when the blender system **300** is operatively connected/assembled (e.g., similar to FIG. **1B**), an electrical signal may travel from the transmitter assembly **206** to the bridge coil assembly **324** (e.g., through one or more coils, switches, or other circuitry), and to the receiver assembly **204**. The receiver assembly **204** may provide the signal (e.g., current, voltage, etc.) to the inductor **222** which engages the relay switch **224** within power circuit **226**. This arrangement allows the motor **216** to be powered by the motor power source **218** subject to the use of the control panel **232**. In response to removal of the container **302** and/or lid **320**, the electrical path or circuit will break, which will open relay switch **224**—cutting off power to motor **216**.

It is noted that the container **302** may be of any configuration such that particular sides of the container **302** are not required to be aligned with a particular side of the circuit board **202** or base **201**. The transmitter assembly **206** remains electromagnetically isolated from the receiver assembly **204** until the bridge coil assembly **324** is aligned

11

across the transmitter assembly **206** and the receiver assembly **204** thereby inductively bridging the interlock circuit **200** across the circuit board **202**. This configuration may occur as the lid switches **314** are engaged with the magnets **312**.

By way of a non-limiting example, base **201** may comprise a pedestal **240** that may be sized and shaped to cooperate with the blade assembly **322** and apron **304** of the container **302**. The pedestal **240** and the apron **304** may be of a shape such that the pedestal **240** corresponds with the external shape of an apron **304** or bottom portion of the container **302**. In the present example, a rotatable shaft **330** of the blade assembly **322** may be rotatably engaged with a coupler **230** (e.g., a splined coupler) positioned along a portion of the base **201**. The coupler **230** may be positioned at a central portion of the circuit board **202** and the pedestal **240**. In this embodiment, the shape of the apron **304** of the container **302**, the circuit board **202**, and base **201** are generally complimentary. The motor **216** may be configured to rotate the coupler **230** to rotate the blade assembly **322** within the container **302**.

By way of a non-limiting example, as illustrated by FIG. 4, a base **400** may include *p* inductive coils, where *p* is a number (e.g., 1, 2, 3, 4 etc.). For instance, base **400** may include, two inductive coils that may interact with *q* inductive coils of a container (e.g., container **302**), where *q* is a number (e.g., one or more). As illustrated, base **400** may include two or more inductive coils.

As depicted, base **400** may include a first induction coil assembly **404** and a second inductive coil assembly **406**. The first inductive coil assembly **404** may include a first coil **410** on a circuit board, surface, or pad **402**. The second inductive coil assembly **406** may include a second coil **412** on the pad **402**. The first coil **410** may be electrically isolated from the second coil **412**. In one embodiment, the power source **408** that operatively provides power to the first induction coil assembly **404** may also operatively provide power to the motor **416**. Additionally, a switch device **420** may be a relay switch or logic gate configured to close the relay switch **424** when the second coil **412** engages relay switch **424** via actuators **422**. Likewise, second coil **412** does not receive a signal and it does not engage relay switch **424**, which brakes the flow of electricity to the motor, generally preventing rotation of the blades. In one embodiment, the switch device **420** may be a yes/no type logic gate.

Accordingly, the bases **200**, **400** may identify that the lid **320** is in an open position (and/or the container **302**, lid **320**, and base are not operatively attached) and, in response, the motor **216**, **416** may be configured to be disabled, i.e., not operate. When the motor **216**, **416** is disabled, the blade assembly **322** may not be capable of operation. Therefore, in order to operate the blending system, the blending container **302** and blade assembly **322** may be operatively coupled with the blender base **201**, **428** and the lid **320** may cover the open end **310**. This generally prevents the user from being able to access the blade assembly **322** within the container **302** as they are rotating.

In these embodiments, the blending interlock **200** may continuously monitor the blending system to ensure it is in an operative condition. More specifically, once the induction circuits are disrupted, the switch device **220**, **420** may automatically open thereby interrupting the power circuit **226** preventing current to flow to the motor **216**. This configuration ensures that the lid **320** is attached to the container **302** and that the bridge coil assembly **324** along the apron **304** is in position along the transmitter assembly **206** and receiver assembly **204**.

12

In an example, the disclosed blender systems may protect users of powered devices from mechanical and electrical harm. When a user operates the blending systems, the user may attempt to add ingredients into a container while the motor is running. If the user removes the lid, the blender system will automatically cut off or disable power to the motor. Likewise, if the user attempts to engage the motor without attaching the container and/or lid, the motor will not rotate. Embodiments describe a physical orientation and use of inductive coils on a pad or circuit board to create a physical—electromechanical based system. The interlock assembly may eliminate complex electronics and the need for comparative signal analysis, microprocessor-based decision-making or complex modulation of inductive signals. The disclosed interlock system may provide a robust and reliable system without the use of a microprocessor.

Turning to FIG. 5, there is a perspective view of a blender system **500**. Blender system **500** may be utilized in blending applications or other appliance applications and may include a container **510** (as shown from below) and a base **550** (as shown from above). Container **510** and base **550** may be configured to control (e.g., enable, disable, etc.) power supplied to a blade or motor assembly. For instance, container **510** and base **550** may comprise transmitter coils that, when induced, may complete a switch or circuit, thereby selectively allowing electrical flow to the motor assembly.

Container **510** may include a plurality of coils (e.g., inner coil **512**, outer coil **514**, etc.) and a switch **516**. It is noted that container **510** may include a different number of coils and/or arrangement of coils. For instance, while inner coil **512** and outer coil **514** are shown as interconnected and generally concentric, it is noted that inner coil **512** and outer coil **514** may not be concentric. It is further noted that the container **510** may include a different number of switches, such as 0, 3, etc. For example, base **550** may include a switch **516**. In another aspect, system **500** may not include any switches.

Base **550** may include a transmitter coil **552** and a receiver coil **554**. It is noted that base **550** may include a different number of coils and/or arrangement of coils. In an aspect, base **550** may include coils that are generally similarly in dimensions and arrangements as coils of container **510**. For example, transmitter coil **552** and receiver coil **554** may be respectively similar in dimensions to inner coil **512** and outer coil **514**. As depicted, transmitter coil **552** and receiver coil **554** may be generally concentric. It is further noted that while transmitter coil **552** is shown as having a generally smaller perimeter than and receiver coil **554** and as generally encompassed by receiver coil **554**, other arrangements are within the scope and spirit of this disclosure. For instance, transmitter coil **552** may encompass receiver coil **554**.

In at least one embodiment, transmitter coil **552** and receiver coil **554** may be disposed on a circuit board **556**, such as through chemical deposition, physical bonding, mounting, printing, or the like. In another aspect, base **550** and/or container **510** may be a base or container of a legacy system that may receive coils and other circuitry. For instance, coils may be attached or coupled to base **550** and/or container **510** through adhesive bonding, physical/mechanical connection, or the like.

Blender system **500** may provide selective power from a power source, such as mains power connection **560** or a battery power source, to the switch **516** that may permit operation of a motor when the inner coil **512** is in electromagnetic communication with the transmitter coil **552** and the outer coil **514** is in electromagnetic communication with

13

the receiver coil **554**. The switch **516** may be a reed type switch or any other appropriate type of switch.

In embodiments, transmitter coil **552** may inject a high frequency signal from an isolated transmitter source, the source may be isolated from mains power connection **560** (or another power source). The transmitter coil **552** may be in electrical communication with a power source or signal generator/transmitter and the receiver coil may be in electrical communication with the switch and/or mains power connection **560**. The transmitter coil **552** may be isolated electronically from the receiver coil **554** when the container is not positioned on the base.

It is noted that interlock system **500** may selectively enable/disable a motor while other operation of a blender system are permitted. For example, a display on blender base **550** may receive power and may operate independent of the interlock system **500**. In another aspect, the display may communicate with interlock system **500** and may generate a status indicator of the interlock system **500**. For instance, the status indicator may include an audible, visual, or other notification. The status indicator may provide information to a user to indicate whether the base **550** and the container **510** are connected or disconnected.

In another aspect, blender system **500** may include other or different components not shown for sake of brevity. For instance, interlock system **500** may include a lid (e.g., as described with reference to FIGS. 1-4). The lid may include inductive coils, switches, or other components. For example, interlock system **500** may be configured to enable/disable power to a motor based on proper connection of base **550**, container **510**, and a lid (not shown). While the base **550** has been described as comprising a transmitter coil **552** and a receiver coil **554**, it is noted that other portions of interlock system **500** may include transmitters and/or receiver coils. For instance, container **510** may include transmitters and/or receivers.

Turning to FIG. 6, there illustrated is a cross-sectional, side view of container **610** and a lid **640**, in accordance with various described embodiments. For instance, container **610** may comprise similar aspects as container **302**, **510**, etc. In another aspect, lid **640** may comprise similar aspects as lid **320**. Container **610** and lid **640** may be utilize with a base of a blender to interlock a blending system, as described herein.

Container **610** may comprise one of more inductive coils **616** that may be disposed proximal to a closed end **602** and opposed an open end **604** of the container **610**. Closed end **602** may comprise a bottom wall **612**. The inductive coils **616** may be disposed within the bottom wall **618** and/or on a surface of the bottom wall **618** (e.g., such as bottom surface **612**). Sidewalls **620** of container **610** may extend between closed end **602** and open end **604**. Sidewalls **620** may comprise a connection wire **626** or line may connect the inductive coils **616** to one or more switches **630**. In an aspect, the connection wire **626** may be disposed within the sidewall **620** (e.g., which may be a double walled or lined wall), on a surface of the side wall (e.g., outer surface **622**), sealed or adhered on a surface, or the like.

In an aspect, switches **630** may be connected via a connection wire **632**, which may be similarly disposed with respect to the connection wire **626**. It is noted that container **610** may comprise m-switches, where m is a number (e.g., 1, 2, 3, 4, etc.). For instance, container **610** may comprise two or more switches generally evenly spaced about a perimeter **634** of container **610**. Spacing the switches **630** may allow for detection of a partially connect lid and/or

14

damaged lid. It is noted that the switches **630** may be disposed at regular or irregular intervals.

Lid **640** may comprise a body **642** comprising one or more appropriate materials, such as plastics, glass, metal, rubber, etc. The lid **640** may be sized and shaped to operatively attach to the container **610**. In an aspect, the lid **640** may be press- or friction-fit within the open end **604** of container **610**, may be a screw top-type lid, or the like. According to embodiments, one or more actuators **644** may be disposed within the body **642** of the lid **640**. For instance, actuators **644** may be magnetic or metallic inserts that may actuate or engage switches **630**. When all switches **630** are engaged, current may flow through container **610** to signify that the lid **640** and container **610** are operatively connected.

Turning to FIG. 7, illustrated is an interlocking blender system **700** that may be utilized to identify when portions of the blender system **700** are appropriately connected. It is noted that the blender system **700** may include different components and/or aspects as described with reference to the various disclosed embodiments. In an aspect, blender system **700** may primarily include container **710**, lid **740**, and a blender base (not shown).

Container **710** may comprise a closed end **702** and an open end **704**. Closed end **702** may include a bottom wall **716**. Sidewalls **720** may extend from bottom wall **716** towards open end **704**. An apron **706** may extend from bottom wall **716** in a direction generally opposed to open end **704**. In an aspect, container **720** may include a contact **712** that may electrically communicate with a contact of a blender base. For example, contact **712** may comprise an exposed metal contact that may be configured to abut or interface with a metal contact of a blender base. When the contact of the blender base is energized, a signal may pass to the contact **712**. It is noted that container **710** may comprise any number of contacts, may comprise different interfaces or methods of communication (e.g., one or more inductive coils, etc.), or the like.

Contact **712** may be coupled with one or more connection wires, such as connection wires **724** and **726**. Connection wires **724**, **726** may generally be disposed in or about sidewalls **722**, as described herein. Connection wires **724**, **726** may be coupled to a switch **730** (e.g., a reed switch, or the like). When the switch is open, connection wires **724** and **726** may be disconnected at the switch **730**; when switch **730** is closed, the connection wires **724** and **726** may be connected to complete a circuit. In an aspect, switch **730** may be selectively opened or closed based on a status of lid **740** (e.g., closed, open, etc.). In an open status, lid **740** may be not-operatively connected or fully connected with container **710**. In a closed status, the lid **740** may be operatively or fully connected with container **710**.

Lid **740** may comprise a body **742** that may include an active member or triggering member **744** disposed therein or thereon. For instance, triggering member **744** may comprise a magnetic band disposed within or about a perimeter **734** of lid **740**. The magnetic band may trigger or close switch **730** when a distance between the triggering member **744** and switch **730** is within a threshold distance. For instance, FIG. 7 depicts lid **740** in a partially open state. In this state, a distance **748** between triggering member **744** and switch **730** may be outside a threshold range, such that switch **730** remains open. If a user pushed lid **740** to further close the lid **740**, the distance **748** will decrease, and eventually reach a threshold distance that will cause triggering member **744** to close switch **730**. Likewise, if the user lifted lid **740** to increase the distance **748**, then triggering member **744**

15

would allow switch 730 to open, preventing operation of the motor and, in turn, preventing rotation of the blades.

Referring now to FIG. 8, illustrated are lid 740 and a container 810 that may be utilized by an interlocking blending system in accordance with one or more disclosed aspects. For instance, container 810 may be coupled with a blender base 808 that may house a motor 804. The motor 804 may be selectively powered by a power source 802 based on the connection state of lid 740, container 810, and base 808 (e.g., non-interlocked state 102 and an interlocked state 104.)

Container 820 may comprise side walls 820. Sidewall 820 may comprise a passage 822 that may include a push rod 834. The push rod 834 may include one or more magnets (e.g., magnet 832, 836). In an aspect, push rod 834 may be biased away from a container bottom 812. For instance, a biasing member 838 (e.g., spring, or the like) may bias the push rod 834 away from bottom 812. It is noted that the biasing member 838 may be located in other positions, such as proximal magnet 832.

In an embodiment, container 820 operatively attaches or docks on base 808. If lid 740 is not attached to the container 820, a triggering member 744 may trigger or repel magnet 832. For example, triggering member 744 may be a magnetic band that comprises an opposite charge with respect to the magnet 832. Repelling the magnet 832 may displace push rod 834 and may provide enough force to overcome biasing member 838. Accordingly, magnet 836 may be in position to close reed switch 806, thereby complete a circuit and allowing motor 804 to receive power from power source 802. If the lid 740 is removed, the biasing member will displace magnet 836 away from bottom 812. This may open reed switch 806, which may prevent power flow to motor 804.

It is noted that other embodiments may displace a pushrod via different means. For instance, FIG. 9 illustrates a container 910 that may comprise a pushrod 934. The pushrod 934 may be partially exposed at proximal end 936, near a flange or ledge 928 of container wall 920. Lid 940 may be configured to contact the proximal end 936. For instance, a bottom rim 948 of lid 940 may operatively contact or abut ledge 928 when a user pushes or otherwise affixes lid 940 to the container 920. The ledge 928 may act as a stop that prevents the user from pushing the lid 940 further into the container 940 than desired. As illustrated, the proximal end 936 of the pushrod 934 may extend from the ledge 932 such that the bottom rim 948 displaces the pushrod 934 when the lid 940 is attached to the container 920. If the user removes the lid 940, then the pushrod 932 may return to the non-depressed position.

In at least one embodiment, the downward force from a lid 940 may press the pushrod 934 to overcome a biasing member 938. This may allow a distal end 952 of the pushrod 934 to be exposed (e.g., activating a switch of a blender base—not shown) and/or translated towards a blender base (e.g., as described with reference to FIG. 8. In an example, a distal end 950 of pushrod 934 may comprise a magnet or other actuator portion that may actuate a switch on a blender base. It is noted that the switch may be a reed switch, manual or push switch (e.g., distal end 950 may extend from container 920 to manually push the switch), a metal contact, or other component as described herein.

FIG. 10 illustrates an embodiment of a blending system 1000 that may utilize a mechanical pushrod to ground a circuit and interlock the blending system 1000. The blending system 1000 may include a container 1020, a blender base 1002, and a lid (e.g., lid 640, 740, 940, etc.). Container 1020

16

may comprise similar aspects as described with reference to FIGS. 8-9. For instance, container 1020 may include a pushrod 1034 disposed within a passage 1022. A triggering member or actuator (not shown) may comprise a magnet, mechanical system, or the like that may displace pushrod 1034, as described herein. For instance, a lid (e.g., lid 940, etc.) may comprise a camming surface (not shown) with a tab (not shown) that allows a user to align the tab with the pushrod 1034, which may displace the pushrod 1034. In another example, as shown in FIG. 11, a lid 1140 may include a handle 1160 that may be hingedly secured (e.g., via hinge 1062) thereto. When a user places the lid 1140 on the container 1120 (which may comprise similar aspects to container 1020), the user may apply force to swing or push the handle 1060 towards the container 1120, such that the handle forces the pushrod 1034 downwards.

According to an embodiment, pushrod 1034 may act similar to a switch to selectively complete a circuit. The circuit may include a connection line 1060 (eclectically coupled to pushrod 1034), a blade assembly 1062 (electrically coupled to connection line 1060), a splined coupling 1064, a contact plate 1068, and/or other circuitry (e.g., splined drive 1070 and ground 1072). Splined drive 1070 may include a motor (not shown) that selectively drives splined coupling 1064. In an aspect, splined drive 1070 will disable operation of the motor when the circuit is not complete and may enable operation when the circuit is complete.

To complete the circuit, container 1020 is attached or otherwise docked on blender base 1002. And a distal end 1050 of pushrod 1034 must contact the contact plate 1068 to ground the circuit. Distal end 1050 will contact the contact plate 1068 if the lid (not shown) is attached to container 1020 such that the pushrod 1034 translates towards the contact plate. In an example, splined drive 1070 may apply a voltage to the splined coupling 1064. The splined coupling 1074 may apply the voltage to the blade assembly 1062, which may supply the voltage to pushrod 1034. When the lid is attached, the distal end 1050 makes contact with contact plate 1068; when the lid is removed, the distal end 1050 brakes contact with the contact plate.

Turning now to FIGS. 12-14, depicted is a blending system 1200 that may detect in interlocked state based on a detection system detecting a change in inductance of a sensing coil. The blending system 1200 may selectively allow operation of the motor based on the interlocked state. It is noted that system 1200 may include similar aspects as the various other systems described herein.

Blending system 1200 may primarily include base 1210, container 1220, and lid 1240. Lid 1240 may operatively attach to container 1220, and container 1220 may operatively attach to base 1210. For instance, base 1210 may include a pedestal 1250. The pedestal 1250 may include one or more posts or protrusions 1252. Container 1220 may include an apron 1256 sized and shaped to mate with pedestal 1250. For instance, apron 1256 may include one or more corners or flanges 1258 that may mate with protrusions 1252.

In another aspect, pedestal 1250 may include one or more sensing coils 1212. The sensing coil 1212 may be disposed within a ridge 1214 of pedestal 1250. While FIGS. 12-13 illustrate ridge 1214 as passing through or intersecting with protrusions 1252, it is noted that ridge may be disposed underneath, around, internal to, or otherwise proximal protrusions 1252. In another aspect, pedestal 1250 may not comprise any protrusions. It is further noted that the sensing coil 1212 may be comprised within a housing of the blender

base **1210** or another housing, which may prevent exposure to liquids, foodstuff, or the like.

Lid **1240** may comprise a body **1242** that may include one or more triggering members **1244**. The triggering member **1244** may include a magnetic band, one or more magnets, tabs, protrusions, inductive coils, or the like. In at least one embodiment, the triggering member **1244** may be comprised by other components of blender system **1200**, such as a tab or clip **1246** of lid **1240**, a handle, or the like. It is noted that the type of triggering member **1244** may depend, at least in part, on a type of switch or sensor **1234** utilized in the system. For instance, a reed switch or other sensor responsive to a magnet may be utilized with magnetic bands. A reed switch, as an example, may close in response to application of a magnetic field, and may open in response to removal of the magnetic field.

Container **1220** may include connection lines **1226** (e.g., wires, a flexible circuit board, etc.) coupled to the sensor **1234**. In an aspect, a flexible circuit board may allow for altered (e.g., improved, less expensive, easier, etc.) assembly. In another aspect, the flexible circuit may provide a more aesthetic appeal for containers having transparent or opaque bodies.

FIGS. **15A-15C** are circuit diagrams representing portions of a blending system. FIG. **15A** illustrates an RL circuit **1500** that may be utilized to measure reactance of a blending system (e.g., blending system **1200**). For instance, the reactance of an inductive coil **1502** (e.g., sensing coil **1212**) may be altered based on the presence of other inductive coils and/or circuitry. As shown in FIGS. **12-14**, when a container **1220** and lid **1240** are connected to base **1210**, the inductance of the sensing coil **1212** is altered from a first value to a second value. Further, if container **1220** is attached to base **1210** without lid **1240**, the inductance may be altered to a third value. It is noted that blending system **1200** may determine inductance through measuring current, voltage, or other parameters of blending system **1200**.

For instance, RL circuit **1500** may include a coil (L1) **1502**, which may be a sensing coil **1212**. The coil may be excited with a signal (e.g., AC signal) from a power source **1504**. A voltage (V) across a known resistor (R1) **1506** will yield current (I) multiplied by a complex impedance (Z), which may be equal to the resistance (R) of the resistor plus the angular frequency (ω) multiplied by the inductance (L) of coil L1. For instance:

$$V=IZ;$$

$$Z=R+j\omega L;$$

where j is the imaginary unit. Since V, I, R, and ω are all known, L may be determined. A blending system may selectively allow or deny operation of a motor based on the value of L. For instance, a known voltage may be applied to the RL circuit **1500**, a current may be measured, and the resistance may be known. The system may then determine the inductance. It is noted that systems may compare a value of L to values stored in memory or the like.

In other embodiments, blending systems may utilize a circuit without a resistor. For example, sensing coil **1212** may be connected to a power supply and a current measuring circuit. A container may include an inductive coil and a circuit loop with one or more switches. When a lid is connected to the container, the one or more switches may close. Closing the switches may complete the loop and thereby alter the current measured by the current measuring

circuit. Blending systems may selectively allow the motor to power on based on the level of current.

FIG. **15B** is an LC circuit **1530** that may be utilized to measure a resonant frequency of components of a blender system (e.g., blending system **2500**, etc.). The LC circuit **1530** may include an inductor **1532**, a capacitor **1534**, a ground **1536**, a step-function input **1538**, and a signal output **1540**. In an example, step-function input **1538** may alter the resonant frequency of the LC circuit **1530**. Values of the resonant frequency may be associated with whether the lid, container and/or base are connected. In an example, an inductance (L) may be a function of a resonant frequency (f), capacitance (C) and a constant, such as:

$$L = \frac{1}{4Cf^2\pi^2}.$$

As components of a blending system are attached to the blender base, the circuitry in the components may alter the resonant frequency. Since inductive reactance magnitude increases as frequency increases while capacitive reactance magnitude decreases with the increase in frequency, the system may determine the status of the lid and/or container. Based on the status, the system may selectively allow operation of a motor.

FIG. **15C** is a resonating LC circuit **1560** that may include an inductive coil and one or more capacitors in series **1572**. The resonating LC circuit **1560** may be utilized to determine an unknown inductance across the coil **1562** (e.g., sensing coil **1212**). An input wave **1564** may be applied across a resistor **1566** and to a diode **1568**. A comparator **1570** may receive a non-inverting input **1574** from the series **1572** and an inverting input **1576** to ground **1578**. The comparator **1570** may be connected to a positive power supply **1580** and a negative power supply **1582**. The output **1584** of the comparator **1570** may be utilized to determine the inductance of the coil **1562**. Blender systems may determine the interlocked states based on the inductance, and may selectively power a motor.

Turning to FIGS. **16-18**, there is an interlocking blending system **1600** that selectively operates a blender motor utilizing a conductive lid. Blending system **1600** may primarily include a base **1610**, a container **1620**, and a lid **1640**. It is noted that components of blending system **1600** may include aspects described with reference to the various disclosed embodiments.

Lid **1640** may include triggering member **1644** which may interact with one or more sensors **1634** of container **1620**. In an example, the triggering member **1644** may comprise a conductive band and sensors (e.g., contact pads **1634**, **1636**). When lid **1640** is operatively attached to container **1620**, an electrical signal may pass from a first contact pad **1634** to a second contact pad **1636**. While described as a conductive band, it is noted that the lid **1640** may comprise different conductive members, such as one or more crescent or "C" shaped conductive strips, or the like. In another aspect, the lid **1640** may comprise a conductive coating, conductive polymers (e.g., intrinsically conducting polymers), or the like. It is noted that conductive materials may comprise food-grade conductive materials.

Contact pads **1634**, **1636** may be coupled with one or more connection lines **1660** (e.g., wires, printed circuit board, flexible circuit board, etc.). The connection lines **1660** may extend through the container **1620** to contact pins **1622**. In an aspect, the contact pins **1622** may comprise a

plug, prongs, or the like. In another aspect, the contact pins **1622** may be sized and shaped to be received by one or more outlets **1612** of base **1610**. For instance, contact pins **1622** may be disposed within apron **1614**. Base **1610** may include a pedestal **1616** that may be sized and shaped to receive container **1620**. When container **1620** and base **1610** are operatively attached, the contact pins **1622** may align with at least one outlet **1612**. Outlets **1612** may be disposed within one or more protrusions **1618**. It is noted blending system **1600** may comprise one or more outlets (e.g., 1, 2, 3, 4, etc.). In an aspect, two or more outlets may allow container **1620** to be attached to base **1610** in two or more orientations.

As described in accordance with various disclosed embodiments, blending system **1600** may allow operation of a motor (not shown) when the lid **1640** bridges the contact pads **1634**, **1636**, and when the container is operatively attached to the base **1610**. If at any time, the lid **1640** and/or container **1620** are removed or otherwise break the flow of an electrical signal, the blending system **1600** may stop the motor and/or prevent operation of the motor and/or rotation of the blades.

While blending system **1600** is described as comprising contact pins, pads and/or plugs, it is noted that various other configurations are considered within the scope and spirit of this disclosure. For instance, container **1620** may comprise a spring contact configured to friction-fit or press fit within a contact plug. In another example, container **1620** may comprise contact pads configured to contact pads of base **1620**, wherein force from the weight of the container may press or wedge the pads together. In another example, container **1620** may comprise a plurality of contacts disposed at one or more positions. For instance, container **1620** may comprise two contacts disposed generally opposite each other, and base **1610** may comprise contacts configured to interact with the contacts of container **1620**, or vice-versa.

FIG. **19** illustrates an exemplary lid-container contact arrangement where a lid **1940** comprises a flexible portion **1946**. The flexible portion **1946** may comprise one or more tabs, recesses, or other lid formations **1948**. The lid formations **1948** may be configured to match and/or mate with tabs, recesses, or other container formations **1928** of container **1920**. For example, a user may align lid **1940** with container **1920**. The user may press downward or otherwise apply force to the lid **1940**. The flexible portion **1946** of lid **1940** may bend, flex, or otherwise deform as the user presses the lid into place. When in a desired location, the lid formations **1948** may mate with the container formations **1928**, as illustrated. In an aspect, container **1920** may include a contact **1934**, which may be similar to other contacts described with reference to the various other figures. The lid **1940** may comprise a conductive portion **1944** (e.g., a conductive band, triggering member **1644**, etc.) that may operatively, electrically couple with contact **1934** when the lid **1940** is attached to the container **1920**.

FIGS. **20-21** illustrate exemplary embodiments of interlocking blending systems comprising a mechanical switch disposed in or on a container wall. It is noted that a switch may include various types of switches, such as miniature button switches, finger switches, dome switches, or the like. It is further noted that a switch may be disposed on a container lip, wall, ledge, or the like. For instance, the placement and orientation of the switch may vary depending on a desired configuration. In an example, a switch may be oriented such that a movable portion translates a vertical axis, horizontal axis, or a diagonal. In another aspect,

described switches may be connected to other components as described with reference to the various disclosed embodiments.

Turning to FIG. **20**, illustrated is a switch **2002** disposed on a container wall **2022** of a container **2020**. The blender wall **2022** may comprise an aperture **2024** configured to receive the switch **2002** (e.g., which may comprise a movable portion **2008** and a circuit board **2010**). In an aspect, a boot **2004** or seal may be positioned within the aperture **2024**. The switch **2002** may be inserted to sandwich the boot **2004** between the switch **2002** and the container wall **2022**. The switch **2002** may be overmolded on a first side **2025** (e.g., external side) of container wall **2022**. Overmolding will create pressure on the switch **2002**, which may compress and/or apply pressure to the boot **2004**. This may create an impervious seal. In an aspect, the boot **2004** may comprise a flexible material that may be exposed on a second side **2026** (e.g., internal side) of the container wall **2022**. When a lid **2040** is attached to the container **2020**, a protrusion or tab **2044** of the lid **2040** may press or actuate the movable portion **2008** of the switch **2002**.

In another aspect, a switch may be mounted into the container wall **2022**, and hermetically sealed from the electrolyte presence possible inside the container **2020**. The switch may be mounted from the exterior of the container and may be sealed or covered with one or more caps or plugs (e.g., shown as plugs **2012**, **2014** in FIG. **21**). According to an embodiment, a switch may be insert-molded into the container wall **2022** without external mounting.

FIG. **22** illustrates an embodiment with two or more (e.g., 2, 3, 4, etc.) pushrods **2234** disposed within a container **2220**. A lid **2240** may comprise one or more actuators **2042** that may engage or actuate the pushrods **2234**. In an aspect, the lid **2240** may have the same or a different number of actuators **2242** as the container **2220** has pushrods **2234**. When lid **2040** is operatively attached to the container **2220**, the actuators **2242** actuate the pushrods **2234** to actuate one or more switches **2212** within the base **2210**. The switches **2212** may comprise various types of switches, such as leaf switches.

In an example, container **2220** comprises four pushrods **2234**. The base **2010** may be configured to selectively allow power based on the number of actuated pushrods **2234**. For instance, switches **2212** may determine which and/or how many pushrods **2234** are actuated by the lid **2240**. In one embodiment, base **2210** requires actuation of all four pushrods **2234**.

In another embodiment, certain container models may comprise different numbers of pushrods **2234**. Base **2210** may determine the number of actuated pushrods **2234** to determine the type of container (e.g., single serving, large format, etc.). Based on the type of container, the base **2210** may selectively allow or deny availability of blender programs. For instance, certain blending programs may be available for large format blending containers and may not be available for single serving-style blending containers.

Turning to FIG. **23**, there is an interlocking blending system **2300** that may determine whether components are interlocked based on one or more light sensors. For instance, blending system **2300** may primarily include a base **2310** (which may include one or more light sources **2312**), a container **2320** (which may propagate light), and a lid **2340** (which may reflect light). It is noted that blending system **2300** may include different components and/or aspects described with reference to the various disclosed embodiments.

21

Base **2310** may generate a light **2316** (e.g., via light sources **2312**). It is noted that base **2310** may include any number of light sources **2312**. The light sources **2312** may generate an appropriate light at a desired intensity, wavelength, and the like. For instance, light sources **2312** may generate infrared (IR) light. In another aspect, base **2310** may comprise one or more light sensors **2314** that may detect or sense light. In an example, the light sensors **2314** may operatively detect light at wavelengths of the light emitted from light sources **2312** (e.g., IR light).

Container **2320** may be configured to propagate or otherwise allow the travel of light emitted from light sources **2312**. In an embodiment, light may propagate through a container wall **2322** and/or through a light pipe (not shown). A light pipe or tube may include a generally hollow tube lined with a reflective coating, a solid tube that allows for internal reflection (e.g., optic fibers), or the like. It is noted that the light pipe may be comprised within the container wall **2322**, on a surface (e.g., internal and/or external) container wall **2322**, may be integrally formed with (e.g., may comprise a ridge or the like) or separately formed from the container wall **2322** (e.g., may comprise fiber optic cable that is removably or irremovably attached), or the like. For sake of brevity, examples may refer to light passing through container wall **2322**. However, it is noted that embodiments may utilize light pipes or the like. In an embodiment, light sources **2312** may be configured to generate light in patterns, at intervals, while power is supplied to base **2310**, upon a triggering event (e.g., user attempts to operate motor), or the like.

Lid **2340** may comprise a reflective surface **2342** disposed in a position to reflect light from light sources **2312** when attached to container **2320**. For instance, lid **2340** may comprise reflective surface(s) **2342** disposed within, adhered to, or otherwise positioned on a lip **2344** of lid **2340**. It is noted that the reflective surface **2342** may comprise a metal, glass, plastic, or other material.

In an interlocked state, light sources **2312** may be configured to generate a light signal through the container wall **2322**. Light may be reflected by the attached lid **2340** via reflective surface **2342**. The reflected light may be directed towards the light sensors **2314** (e.g., via container wall **2322**). Blending system **2300** may be configured to detect the reflected light and determine that the base **2310**, container **2320**, and lid **2340** are interlocked. In another aspect, if light sensors **2314** do not detect the reflected light, then blending system **2300** may determine that the base **2310**, container **2320**, and lid **2340** are not interlocked.

In view of the subject matter described herein, a method that may be related to various embodiments may be better appreciated with reference to the flowcharts of FIG. **24**. While method **2400** is shown and described as a series of blocks, it is noted that associated method or process is not limited by the order of the blocks. It is further noted that some blocks and corresponding actions may occur in different orders or concurrently with other blocks. Moreover, different blocks or actions may be utilized to implement the methods described hereinafter. Various actions may be completed by one or more of users, mechanical machines, automated assembly machines (e.g., including one or more processors or computing devices), or the like.

In another example, a container may include one or more switches that close in response to attaching a lid to the container (e.g., reed switches), and one or more switches that close in response to attaching the container to a base. When all switches are closed, the base may supply power to or otherwise operate a motor. When less than all switches are

22

closed, the base may prevent operation of the motor. It is noted that aspects of the described embodiments may be altered and combined in various configurations without departing from the scope and spirit of the subject disclosure.

FIG. **24** is a method that provides for safely operating a blender system based on whether the system is interlocked. At reference **2402**, a user may operably position a container to a base having a motor. A lid is attached to an open end of the container to engage at least one lid sensor and complete a bridge coil circuit. At **2404**, a bridge coil circuit is inductively coupled to a transmitter coil and a receiver coil on the base of the blender. At **2406**, the transmitter coil, bridge circuit and receiver coil are powered to engage a switch device or relay circuit to allow power to the motor of the blender. At **2408**, power may be provided to the transmitter coil, bridge circuit and receiver coil to engage a relay circuit to allow power to the motor.

FIG. **25** is an interlocking blending system **2500** that may determine whether components are interlocked based on comparative changes in inductance or other properties of circuitry. For instance, blending system **2500** may primarily include a base **2510** (which may include one or more sensors), a container **2520**, and a lid **2540**. It is noted that blending system **2500** may include different components and/or aspects described with reference to the various disclosed embodiments.

In an embodiment, lid **2540** may comprise one or more coils **2542** disposed in a body **2544**. Container **2520** may comprise one or more sets of coils (e.g., first set **2522** and/or second set **2524**). For instance, first set **2522** may be disposed proximal an open end **2526** and the second set **2524** may be disposed proximal a closed end **2528**. Base **2510** may include one or more sensors **2512** that operatively sense properties of the one or more sets of coils, such as resonance frequency or current. In an example, if a user attaches the container **2520** to base **2510** without the lid **2540**, the sensors **2512** may detect the properties of first set **2522** and/or second set **2524**. If the user attaches the lid **2540**, the properties of the first set **2522** and/or second set **2524** change due to the coils **2542** of the lid. Sensors **2512** may detect the properties and may selectively allow power to a motor, thereby selectively allowing operation of a blade assembly.

It is noted that the lid **2540**, container **2520**, and/or base **2510** may utilize various disclosed aspects. For instance, lid **2540** may alternatively or additionally include one or more magnets, container **2520** may alternatively or additionally include one or more switches, or the like. As such, aspects of this disclosure may be selectively arranged in any desired combination.

In at least one embodiment, various described blending systems may include a computer readable memory device and a computer processor. The memory device may be configured for storing computer executable instructions. The processor may execute the instructions to perform tasks or operations. The processor may execute instructions to determine the state or interlocked status of the blending system. For instance, the processor may determine whether a container is attached, whether a lid is attached, whether the container and lid are attached, and the like. It is noted that the processor may execute instructions to generate notifications or status information to users via an interface device, such as a display screen, LED, speaker, or the like. In another example, the processor may initiate transmission of the status information via a communications network.

What has been described above includes examples of the present specification. It is, of course, not possible to describe every conceivable combination of components or method-

ologies for purposes of describing the present specification, but one of ordinary skill in the art may recognize that many further combinations and permutations of the present specification are possible. Furthermore, it is noted that the various embodiments may be altered, combined, or arranged in any desired configuration. For instance, different lids, containers, bases, switches, circuitry, or the like may be utilized in different combinations than illustrated. Accordingly, the present specification is intended to embrace all such alterations, modifications and variations that fall within the spirit and scope of the appended claims. To the extent that the term “includes” is used in either the detailed description or the claims, such term is intended to be inclusive in a manner similar to the term “comprising” as “comprising” is interpreted when employed as a transitional word in a claim.

What is claimed is:

1. An interlocking blending system comprising:
a base comprising a motor, a switch, a first set of inductive coils, and a sensor that monitors change in an electrical property of the first set of coils; and
a container comprising a blade assembly and a second set of inductive coils, wherein the second set of inductive coils inductively couples with the first set of inductive coils when the second set of inductive coils are operatively positioned on top of the first set of inductive coils;
wherein the base permits operation of the blade assembly based on the inductive coupling of the first set of coils and the second set of coils when the container is operatively positioned on top of the base, which causes the switch to be in closed state completing a power circuit to drive the blade assembly.
2. The blending system of claim 1, wherein the first set of inductive coils includes a transmitter coil and a receiving coil and wherein the second set of inductive coils includes a transmitter coil and a receiving coil.
3. The blending system of claim 2, wherein the transmitter coil of the first set of inductive coils induces current in the receiving coil of the second set of inductive coils in response to power supplied to the transmitter coil of the first set of inductive coils when the container is operatively attached to the base.
4. The blending system of claim 1, wherein the base determines whether the container is attached to the base based on the monitored change in the electrical property.
5. The blending system of claim 4, further comprising a lid, wherein at least one of the lid or the container alter the electrical property of the first set of coils when the lid is operatively connected with the container and the container operatively coupled to the base.
6. An interlocking blending system comprising:
a base including a motor, a display and a first set of inductive coils; and
a container including a second set of inductive coils that inductively couples with the first set of inductive coils when the second set of inductive coils are operatively positioned on top of the first set of inductive coils;
wherein the base comprises a sensor that monitors change in an electrical property of the first set of coils and a switch that: i) permits operation of the motor based on the inductive coupling of the first set of coils and the

second set of coils when the container is operatively positioned on top of the base and ii) prevents operation of the motor based on the container not being operatively positioned on top of the base but permits operation of the display.

7. The interlocking blending system of claim 6, wherein the base generates a status indicator displayed on the display.

8. The interlocking blending system of claim 7, wherein the status indicator provides information to a user to indicate whether the base and the container are disconnected.

9. The interlocking blending system of claim 6, wherein the first set of inductive coils includes at least one transmitter coil and at least one receiving coil and the second set of inductive coils includes at least one transmitter coil and at least one receiving coil, and wherein the at least one transmitter coil of the first set of inductive coils induces current in the at least one receiving coil of the second set of inductive coils in response to power supplied to the at least one transmitter coil of the first set of inductive coils when the container is operatively attached to the base and wherein the switch moves to a closed position.

10. An interlocking blending system comprising:

a base including a motor, a contact plate and a first set of inductive coils; and

a container including a pushrod and a second set of inductive coils, the second set of inductive coils selectively inductively couples with the first set of inductive coils when the second set of inductive coils are operatively positioned on top of the first set of inductive coils;

wherein the pushrod translates towards and makes contact with the contact plate to permit operation of the motor when a lid is attached, and the pushrod breaks contact with the contact plate and operation of the motor is prevented when the lid is removed.

11. The interlocking blending system of claim 10, wherein the base comprises a switch that permits operation of the motor based on the inductive coupling of the first set of coils and the second set of coils when the container is operatively positioned on top of the base.

12. The blending system of claim 10, wherein the first set of inductive coils includes a transmitter coil and a receiving coil and wherein the second set of inductive coils includes a transmitter coil and a receiving coil.

13. The blending system of claim 12, wherein the transmitter coil of the first set of inductive coils induces current in the receiving coil of the second set of inductive coils in response to power supplied to the transmitter coil of the first set of inductive coils when the container is operatively attached to the base.

14. The blending system of claim 10, wherein the base comprises a sensor that monitors change in an electrical property of the first set of coils.

15. The blending system of claim 14, wherein the base determines whether the container is attached to the base based on the monitored change in the electrical property.

16. The blending system of claim 1, wherein the sensor monitors a resonance frequency or current of the first set of coils.