

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12392137
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Lenney; Robert C.

Self-supporting bi-directional corrugated mesh leaf preclusion device

Abstract

A roof gutter for the purpose of keeping small debris out of the gutter and allowing rainwater to pass into the gutter. The covering is comprised of a water permeable, weather resistant mesh having apertures of a pre-determined size for passing water, the mesh sized to substantially cover a rain gutter; corrugations formed in the mesh; a debris collection first trough disposed along a longitudinal axis of the mesh, formed by making at least two bends in the mesh, the first trough located between a longitudinal midline of the mesh and a front gutter end of the mesh.

Inventors:	Lenney; Robert C. (Lincoln, CA)
Applicant:	Gutterglove, Inc. (Franklin, TN)
Family ID:	1000008765055
Assignee:	GUTTERGLOVE, INC. (Franklin, TN)
Appl. No.:	18/597191
Filed:	March 06, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240344326 A1	Oct. 17, 2024

Related U.S. Application Data

continuation parent-doc US 17455897 20211119 US 11970861 child-doc US 18597191
continuation parent-doc US 17027664 20200921 US 11193280 20211207 child-doc US 17455897
continuation parent-doc US 16356955 20190318 US 10781592 20200922 child-doc US 17027664
continuation parent-doc US 15920407 20180313 US 10233648 20190319 child-doc US 16356955
continuation parent-doc US 15096178 20160411 US 9915070 20180313 child-doc US 15920407

Publication Classification

Int. Cl.: E04D13/076 (20060101); E04D13/064 (20060101)

U.S. Cl.:

CPC E04D13/076 (20130101); E04D13/064 (20130101);

Field of Classification Search

CPC: E04D (13/076); E04D (13/074)

USPC: 52/12

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1732058	12/1928	Martini	N/A	N/A
2229381	12/1940	Grow	N/A	N/A
2288121	12/1941	Sandmeyer	N/A	N/A
2569568	12/1950	Lipshaw	N/A	N/A
2583422	12/1951	Haddon	N/A	N/A
2674961	12/1953	Lake	N/A	N/A
2935954	12/1959	Matthews	N/A	N/A
2997763	12/1960	Serfass	N/A	N/A
3350045	12/1966	Mayers	N/A	N/A
3630383	12/1970	Reeves	N/A	N/A
3691343	12/1971	Norman	N/A	N/A
3925264	12/1974	Corte	N/A	N/A
4254595	12/1980	Crossien	N/A	N/A
4308696	12/1981	Schroeder	N/A	N/A
4435466	12/1983	Kuhnel et al.	N/A	N/A
4573290	12/1985	Fleming	N/A	N/A
4604837	12/1985	Beam	N/A	N/A
4646488	12/1986	Burns	N/A	N/A
4745710	12/1987	Davis	N/A	N/A
4750300	12/1987	Winger	N/A	N/A
4755229	12/1987	Armanini	N/A	N/A
4769526	12/1987	Taouil	N/A	N/A
4827686	12/1988	Stamper	N/A	N/A
4941299	12/1989	Sweers	N/A	N/A
4949514	12/1989	Weller	N/A	N/A
4954015	12/1989	McGowan	N/A	N/A
4959932	12/1989	Pfeifer	N/A	N/A
5010696	12/1990	Knittel	N/A	N/A

5035092	12/1990	Brant	N/A	N/A
5038528	12/1990	Brant	N/A	N/A
5044581	12/1990	Dressler	N/A	N/A
5067675	12/1990	Brant	N/A	N/A
5092086	12/1991	Rognsvoog, Sr.	N/A	N/A
5098045	12/1991	Pepper	N/A	N/A
5107635	12/1991	Carpenter	N/A	N/A
5109640	12/1991	Creson	N/A	N/A
5127200	12/1991	Doran	N/A	N/A
5181350	12/1992	Meckstroth	N/A	N/A
5216852	12/1992	Bemis et al.	N/A	N/A
5228247	12/1992	Dressler	N/A	N/A
5257482	12/1992	Sichel	N/A	N/A
5261195	12/1992	Buckenmaier	N/A	N/A
5315090	12/1993	Lowenthal	N/A	N/A
5371979	12/1993	Kwiatkowski et al.	N/A	N/A
5375379	12/1993	Meckstroth	N/A	N/A
5391858	12/1994	Tourangeau et al.	N/A	N/A
5398464	12/1994	Jacobs	N/A	N/A
5406754	12/1994	Cosby	N/A	N/A
5406756	12/1994	Bemis et al.	N/A	N/A
5438803	12/1994	Blizard, Jr.	N/A	N/A
5459965	12/1994	Meckstroth	N/A	N/A
D364338	12/1994	Cline	N/A	N/A
5522185	12/1995	Cline	N/A	N/A
D372421	12/1995	Cline	N/A	N/A
5558705	12/1995	Keemer et al.	N/A	N/A
5570557	12/1995	Kwiatkowski et al.	N/A	N/A
5617678	12/1996	Morandin	N/A	N/A
5640809	12/1996	Iannelli	N/A	N/A
5729931	12/1997	Wade	N/A	N/A
5759255	12/1997	Venturini et al.	N/A	N/A
5836117	12/1997	Johnson	N/A	N/A
5842311	12/1997	Morin	N/A	N/A
5842469	12/1997	Rapp et al.	N/A	N/A
5848857	12/1997	Killworth et al.	N/A	N/A
5878533	12/1998	Swanfeld	N/A	N/A
5893240	12/1998	Ealer, Sr.	N/A	N/A
D418403	12/1999	Cline	N/A	N/A
D419863	12/1999	Mullane	N/A	N/A
6035587	12/1999	Dressler	N/A	N/A
6134843	12/1999	Tregear	N/A	N/A
6194049	12/2000	Bindschedler-Galli et al.	N/A	N/A
6194519	12/2000	Blalock et al.	N/A	N/A
6205715	12/2000	Rex	N/A	N/A
6223777	12/2000	Smith et al.	N/A	N/A
6225600	12/2000	Burris	N/A	N/A
6266929	12/2000	Cline	N/A	N/A
6341462	12/2001	Kiik et al.	N/A	N/A
D457423	12/2001	Mullane	N/A	N/A

6412228	12/2001	Meckstroth	N/A	N/A
6468613	12/2001	Kitano	N/A	N/A
6543729	12/2002	Ylonen	N/A	N/A
D475613	12/2002	Mullane	N/A	N/A
6598352	12/2002	Higginbotham	N/A	N/A
6607781	12/2002	Joedicke et al.	N/A	N/A
D481929	12/2002	McNichol	N/A	N/A
6700098	12/2003	Wyatt et al.	N/A	N/A
6708452	12/2003	Tenute	N/A	N/A
6759630	12/2003	Tenute	N/A	N/A
D494461	12/2003	Dressler	N/A	N/A
D495595	12/2003	Dressler	N/A	N/A
D499331	12/2003	Dressler	N/A	N/A
6933007	12/2004	Fensel et al.	N/A	N/A
6942419	12/2004	Knak et al.	N/A	N/A
6944991	12/2004	Kim	N/A	N/A
6944992	12/2004	Brochu	N/A	N/A
6951077	12/2004	Higginbotham	N/A	N/A
6951323	12/2004	McNichol	N/A	N/A
D511451	12/2004	Mullane	N/A	N/A
6959512	12/2004	Cobb	N/A	N/A
D514670	12/2005	Handley	N/A	N/A
7017614	12/2005	Handley	N/A	N/A
D519025	12/2005	Dressler	N/A	N/A
7056422	12/2005	Swistun	N/A	N/A
7104012	12/2005	Bayram	N/A	N/A
7127852	12/2005	Dressler	N/A	N/A
7174677	12/2006	Dressler	N/A	N/A
7174688	12/2006	Higginbotham	N/A	N/A
7191564	12/2006	Higginbotham	N/A	N/A
7241500	12/2006	Shiao et al.	N/A	N/A
7310912	12/2006	Lenney	N/A	N/A
7340863	12/2007	Dressler	N/A	N/A
7434358	12/2007	Smith	N/A	N/A
7448167	12/2007	Bachman	N/A	N/A
7493686	12/2008	Barford	N/A	N/A
7516576	12/2008	Mullane	N/A	N/A
7597119	12/2008	Boettner	N/A	N/A
7624541	12/2008	Gentry	N/A	N/A
7677271	12/2009	Boettner	N/A	N/A
7726076	12/2009	Staub	N/A	N/A
7793465	12/2009	McCann	N/A	N/A
7913458	12/2010	Higginbotham	N/A	N/A
D638920	12/2010	Ealer, Sr.	N/A	N/A
7975435	12/2010	Lenney	N/A	N/A
8033058	12/2010	Block	N/A	N/A
8079183	12/2010	Lenney	N/A	N/A
8251302	12/2011	Sloan, Jr.	N/A	N/A
8276321	12/2011	Bell	N/A	N/A
8312677	12/2011	Higginbotham	N/A	N/A

8418410	12/2012	Martin	N/A	N/A
8438788	12/2012	Bell et al.	N/A	N/A
8479454	12/2012	Lenney	N/A	N/A
8495837	12/2012	McCoy	N/A	N/A
8572899	12/2012	Pearce et al.	N/A	N/A
8607827	12/2012	Bell	N/A	N/A
8677694	12/2013	Ash	N/A	N/A
8689837	12/2013	Smith	N/A	N/A
8720132	12/2013	Chihlas	N/A	N/A
D709357	12/2013	Bell	N/A	N/A
8782960	12/2013	Nark	N/A	N/A
8901458	12/2013	Aussi	N/A	N/A
9080328	12/2014	Smith	N/A	N/A
D752722	12/2015	Boettner	N/A	N/A
9309995	12/2015	Bell	N/A	N/A
9487955	12/2015	Breyer	N/A	N/A
D790672	12/2016	Benjamin	N/A	N/A
9890535	12/2017	Breyer	N/A	N/A
9915070	12/2017	Lenney	N/A	N/A
9976309	12/2017	Lenney	N/A	N/A
9982438	12/2017	Casey	N/A	N/A
10081937	12/2017	Elliott	N/A	N/A
D837048	12/2018	Benjamin et al.	N/A	N/A
10233647	12/2018	Benjamin et al.	N/A	N/A
10233648	12/2018	Lenney	N/A	N/A
D878189	12/2019	Benjamin et al.	N/A	N/A
10781592	12/2019	Lenney	N/A	N/A
11193280	12/2020	Lenney	N/A	N/A
11970861	12/2023	Lenney	N/A	E04D 13/076
2001/0054625	12/2000	Iggulden	N/A	N/A
2003/0046876	12/2002	Higginbotham	N/A	N/A
2003/0187539	12/2002	Smith	N/A	N/A
2003/0198736	12/2002	Fensel et al.	N/A	N/A
2005/0072114	12/2004	Shiao et al.	N/A	N/A
2005/0196124	12/2004	Aldereguia et al.	N/A	N/A
2005/0235577	12/2004	Smith	N/A	N/A
2005/0257432	12/2004	Higginbotham	N/A	N/A
2005/0279036	12/2004	Brochu	N/A	N/A
2006/0037252	12/2005	Gosse et al.	N/A	N/A
2006/0090404	12/2005	Lovell	N/A	N/A
2006/0117670	12/2005	Tsioris	N/A	N/A
2006/0179723	12/2005	Robins	N/A	N/A
2006/0196124	12/2005	Bachman	N/A	N/A
2006/0213129	12/2005	Bachman	N/A	N/A
2006/0230687	12/2005	Ealer, Sr.	N/A	N/A
2006/0277831	12/2005	Bachman	N/A	N/A
2006/0283096	12/2005	Bachman	N/A	N/A
2006/0288652	12/2005	Gurr	N/A	N/A
2007/0054129	12/2006	Kalkanoglu et al.	N/A	N/A
2007/0065640	12/2006	Joedicke	N/A	N/A

2007/0094939	12/2006	Bachman	N/A	N/A
2007/0107323	12/2006	Higginbotham	N/A	N/A
2007/0193012	12/2006	Bergman et al.	N/A	N/A
2007/0199276	12/2006	Duque	N/A	N/A
2007/0218251	12/2006	Jacobs	N/A	N/A
2007/0220814	12/2006	Faulks	N/A	N/A
2007/0234647	12/2006	Higginbotham	N/A	N/A
2007/0246449	12/2006	Bachman	N/A	N/A
2008/0000169	12/2007	Handley	N/A	N/A
2008/0187708	12/2007	Decker	N/A	N/A
2008/0248241	12/2007	Kalkanoglu et al.	N/A	N/A
2009/0056234	12/2008	Brochu	N/A	N/A
2009/0064628	12/2008	Mellott et al.	N/A	N/A
2009/0139180	12/2008	Kehs et al.	N/A	N/A
2009/0300995	12/2008	Nikolopoulos	N/A	N/A
2010/0042579	12/2009	Larsen et al.	N/A	N/A
2011/0047930	12/2010	Nark	N/A	N/A
2011/0049118	12/2010	Nark	N/A	N/A
2011/0056145	12/2010	Lenney	N/A	N/A
2011/0067318	12/2010	Lenney et al.	N/A	N/A
2011/0138698	12/2010	Neumann	N/A	N/A
2011/0253611	12/2010	Higginbotham	N/A	N/A
2012/0042579	12/2011	McCoy	N/A	N/A
2012/0049511	12/2011	Bell et al.	N/A	N/A
2012/0068452	12/2011	Boettner	N/A	N/A
2012/0144759	12/2011	Higginbotham	N/A	N/A
2013/0097943	12/2012	Higginbotham	N/A	N/A
2013/0160377	12/2012	Sager	N/A	N/A
2013/0160378	12/2012	Higginbotham	N/A	N/A
2013/0284650	12/2012	Higginbotham	N/A	N/A
2013/0319990	12/2012	Casey	N/A	N/A
2014/0013702	12/2013	Pearce et al.	N/A	N/A
2014/0069028	12/2013	Lenney	N/A	N/A
2014/0090311	12/2013	Iannelli	N/A	N/A
2014/0130929	12/2013	Elliott et al.	N/A	N/A
2014/0196400	12/2013	Bell	N/A	N/A
2014/0263001	12/2013	Higginbotham	N/A	N/A
2014/0291310	12/2013	Iannelli	N/A	N/A
2014/0326837	12/2013	Rumsey	N/A	N/A
2015/0143756	12/2014	Higginbotham	N/A	N/A
2015/0184394	12/2014	Nark	N/A	N/A
2016/0102459	12/2015	Breyer	N/A	N/A
2016/0168858	12/2015	Breyer	N/A	N/A
2017/0089071	12/2016	Smith et al.	N/A	N/A
2018/0179761	12/2017	Higginbotham	N/A	N/A
2018/0216755	12/2017	Rumsey	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2013201320	12/2012	AU	N/A

1310167	12/1991	CA	N/A
2021168	12/2001	CA	N/A
2021169	12/2001	CA	N/A
2476351	12/2004	CA	N/A
2551297	12/2006	CA	N/A
2390777	12/2007	CA	N/A
2752598	12/2012	CA	N/A
2938647	12/2018	CA	N/A
1344640	12/2005	EP	N/A
2518226	12/2011	EP	N/A
2694775	12/1996	FR	N/A
06-146506	12/1993	JP	N/A
09228592	12/1996	JP	N/A
2000-008559	12/1999	JP	N/A
890010803	12/1988	KR	N/A
1998-016228	12/1997	KR	N/A
WO9953157	12/1998	WO	N/A

OTHER PUBLICATIONS

Valor Gutter Guard's Melt Away Use Guide, published Apr. 2014. cited by applicant

Primary Examiner: Stephan; Beth A

Attorney, Agent or Firm: Intelink Law Group, P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S) (1) This application is a continuation of U.S. patent application Ser. No. 17/455,897 filed Nov. 19, 2021, titled Self-Supporting Bi-Directional Corrugated Mesh Leaf Preclusion Device, which is a continuation of U.S. patent application Ser. No. 17/027,664 filed Sep. 21, 2020, now issued as U.S. Pat. No. 11,193,280 on Dec. 7, 2021, which is a continuation of U.S. patent application Ser. No. 16/356,955 filed on Mar. 18, 2019, now issued as U.S. Pat. No. 10,781,592 on Sep. 22, 2020, which is a continuation of U.S. patent application Ser. No. 15/920,407 filed Mar. 13, 2018, issued as U.S. patent Ser. No. 10/233,648 on Mar. 19, 2019, which is a continuation of U.S. patent application Ser. No. 15/096,178 filed Apr. 11, 2016, issued as U.S. Pat. No. 9,915,070 on Mar. 13, 2018, which is a continuation of U.S. patent application Ser. No. 14/620,729, filed on Feb. 12, 2015, which is a non-provisional application of U.S. Provisional Patent Application No. 61/939,005, filed Feb. 12, 2014, to which this application claims the benefit of all prior applications and are hereby incorporated by reference in their respective entireties.

FIELD

(1) This invention relates to barriers for rain gutters and similar structures for keeping leaves and other debris out of the rain gutters. More particularly, this invention relates to rain gutter debris preclusion barriers, which utilize a conformed screen to allow water to pass into the gutter, but preclude debris from passing through the screen and into the gutter.

BACKGROUND

(2) Prior art gutter debris preclusion devices are known to have difficulty in addressing excessive flow of rainwater coming off the roof of a house into the gutter. With excessive water flow, debris

often accumulates on the device, clogging or impeding the effectiveness of the device. Many complicated designs have been contemplated by others in the industry, each with their advantages and disadvantages. Of particular difficulty, is the need to support the “guard” over the gutter, wherein complicated and diverse support and bridging systems have been devised. These support systems add to the complexity, weight, and most importantly the cost of these guards. The industry was in need of a new system to support the guard over the gutter with easy installation, little or no increased weight, and without increasing the cost of the guard.

(3) The present invention overcomes the deficiencies in the art by creating various systems and devices of screened gutter debris preclusion.

SUMMARY

(4) The following presents a simplified summary in order to provide a basic understanding of some aspects of the claimed subject matter. This summary is not an extensive overview, and is not intended to identify key/critical elements or to delineate the scope of the claimed subject matter. Its purpose is to present some concepts in a simplified form as a prelude to the more detailed description that is presented later.

(5) Various embodiments describe a covering that goes over a roof gutter for the purpose of keeping leaves, pine needles and small debris out of the gutter and for allowing rainwater to pass through a permeable material and into the gutter.

(6) For example, one aspect of the disclosed embodiments, a gutter debris preclusion device for securing to a top portion of a roof gutter that is attached to a building for keeping leaves and other debris out of the roof gutter is provided, comprising: a water permeable, weather resistant mesh having apertures of a pre-determined size for passing water, the mesh sized to substantially cover a rain gutter; corrugations in the mesh; and a debris collection trough disposed along a longitudinal axis of the mesh and positioned proximal to a gutter lip end of the mesh.

(7) In another aspect of the disclosed embodiments, the device described above is provided, further comprising first and second wall portions of the trough connected together to form a tilted L-shaped reservoir, a bottom of the reservoir below the gutter lip end of the mesh, the first wall portion longer than the second wall portion, and the second wall portion angled upwards and towards the gutter lip end of the mesh; and/or wherein the mesh is formed from stainless steel wires, plastic, expanded metal, perforated metal, slotted metal or louvered metal; and/or wherein the first wall portion extends to a roof-side end of the mesh; and/or wherein the corrugations are configured to provide a planar stiffness to the mesh causing the mesh to be self-supporting over the gutter; and/or wherein the corrugations in the mesh are formed via at least one of stamping, pressing, and weaving; and/or further comprising: a front strip connector adapted to connect the gutter lip end of the mesh to a front of the gutter; and a rear strip connector adapted to connect the roof-side end of the mesh to either a rear of the gutter or a roof element neighboring the gutter; and/or wherein the trough is displaced up to 1.5” from the front strip connector; and/or wherein the trough is displaced up to 0.25” from the front strip connector; wherein the corrugations span from a roof-side end of the mesh to at least one of a first and second bend in the trough; and/or further comprising a second trough disposed in the mesh along a longitudinal axis of the mesh; and/or wherein an angle formed by the connected first and second wall portions is less than 90 degrees; and/or wherein an angle formed by the connected first and second wall portions is greater than 90 degrees; and/or wherein at least one of the first and second wall portions is further angled to form a segmented or a curved reservoir bottom.

(8) In yet another aspect of the disclosed embodiments, a gutter debris preclusion device for securing to a top portion of a roof gutter that is attached to a building for keeping leaves and other debris out of the roof gutter is provided, comprising: weather resistant means for passing water while restricting debris, sized to substantially cover a rain gutter; stiffness means in the weather resistant means; and a debris collection means disposed along a longitudinal axis of the weather resistant means and positioned proximal to a gutter lip end of the weather resistant means. In

another aspect of the disclosed embodiments, the device described above is provided, further comprising a first wall portion and second wall portion of the debris collection means, wherein the first wall portion is longer than the second wall portion and the second wall portion is angled upwards and towards the gutter lip end of the weather resistant means, wherein a bottom of the debris collection means is below the gutter lip end of the weather resistant means; and/or further comprising: a front strip connector adapted to connect the gutter lip end of the weather resistant means to a front of the gutter; and a rear strip connector adapted to connect the roof-side end of the weather resistant means to either a rear of the gutter or a roof element neighboring the gutter; and/or wherein the debris collection means is displaced up to 1.5" from the front strip connector; and/or further comprising a second debris collection means disposed along a longitudinal axis of the weather resistant means; and/or wherein an angle formed by the connected first and second wall portions is less than 90 degrees; and/or wherein at least one of the first and second wall portions form a segmented or a curved debris collection means bottom.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1A is a side perspective view of an embodiment of a three-piece gutter cover.
- (2) FIGS. 1B-C are illustrations of various meshes with corrugations that are formed with different diameter wires.
- (3) FIG. 2 is a semi-side cut-away illustration of the embodiment of FIG. 1A.
- (4) FIG. 3A is a side illustration of another mesh configuration with multiple troughs.
- (5) FIG. 3B is a cross-sectional close up illustration of an exemplary V-shaped trough.
- (6) FIG. 4 is an illustration of an exemplary mesh with trough formed with a plurality of upward protruding barriers.
- (7) FIGS. 5A-B are illustrations of a mesh embodiment with a U-shaped trough.
- (8) FIG. 6A is a side-view illustration of a mesh embodiment with a laterally oriented trough.
- (9) FIG. 6B is a close-up illustration of a laterally oriented L-shaped trough.
- (10) FIG. 7 is an illustration of the embodiment of FIG. 6A in a snowmelt situation.
- (11) FIGS. 8A-B are illustrations of another embodiment wherein the trough has a laterally oriented relaxed L-shape.
- (12) FIG. 9 is an illustration of the embodiments of FIGS. 8A-B in a snowmelt situation.
- (13) FIGS. 10A-B are illustrations of another gutter cover embodiment not requiring the front and rear strip connectors.
- (14) FIG. 11 is an illustration of another gutter cover embodiment not requiring the front and rear strip connectors.

DETAILED DESCRIPTION

- (15) FIG. 1A is a side perspective view **100** of an embodiment of a three piece gutter cover showing a rear strip connector **115** that goes to the roof (not shown), a front strip connector **125** that fastens to the front lip of a gutter (not shown) and a corrugated mesh **135** that spans between the rear strip connector **115** and the front strip connector **125**, via trough **145**. The mesh **135** in this embodiment is formed of a stainless steel material, but other weather resilient materials may be used. The mesh **135** is generally rectangular in shape having a longitudinal axis parallel to the gutter, so as to fit over the gutter. Most residential gutters being approximately 5 inches in width, and commercial gutters being up to 10 inches in width, the mesh **135** will be sized in most embodiments to be wide enough to cover the gutter, less the widths of the rear and front strip connectors **115**, **125**, if they are used.
- (16) Illustrated in FIG. 1A are corrugations **112** in the mesh **135**, which can be of varying shapes, orientations, etc., but are of a configuration that provides sufficient rigidity in the mesh **135**, so that

it can free-formingly span the gutter without collapsing in the gutter. These corrugations **112** do not have to be perpendicular to rear strip connector **115**. The corrugations do not have to be perpendicular to the front strip connector **125** in other exemplary embodiments.

(17) FIGS. **1B-C** are illustrations of various meshes **135** with corrugations **112** that are formed with different diameter wires. For example, FIG. **1B** shows a 30 wires per linear inch corrugation **112**. FIG. **1C** shows a 50 wires per linear inch corrugation **112**. Of course, other wires per linear inch density (or metric equivalent) can be used, as well as perforations or other mechanisms for forming passageways in a material. FIGS. **1B-C** are demonstrative of exemplary commercial embodiments and are understood not to be limiting.

(18) In the various embodiments described herein, the mesh's corrugations **112** can be patterned to be rectangular, square, of various shapes, etc., and oriented substantial orthogonal (perpendicular) to the orientation of the lip of the gutter. The perpendicular orientation provides for linear or planar stiffness along the roof-to gutter lip line, resulting in a self-supporting mesh. The mesh's corrugations can be formed from stamping the mesh, pressing the mesh, or weaving the mesh in a corrugated form, and so forth.

(19) The connectors **115** and **125** are similar to the lower and upper strips described in published application US 20110056145, published on Mar. 10, 2011, which is incorporated herein by reference in its entirety.

(20) The corrugations **112** formed in the mesh **135** are formed similar to the corrugations formed in the mesh in published application US 20110056145, published on Mar. 10, 2011, which is incorporated herein by reference in its entirety.

(21) The mesh **135** provides the function of allowing water to pass into the gutter while precluding debris from passing into the gutter. This corrugated mesh **135** is preferably formed as a woven screen of stainless steel wire or other wire-thread of suitable material. Important characteristics of the material forming the mesh include sufficiently high strength and inelasticity to function structurally, as well as resistance to corrosion in the gutter environment. Furthermore, it is advantageous that material forming the corrugated mesh **135** can be readily bent sufficient to cause the material to be readily corrugated into one of a variety of different cross-sections and hold that configuration after being so bent. Most preferably, the wire forming the corrugated mesh **135** extends in a pattern with some threads extending parallel with an upper edge (extending substantially parallel to the roof, when in use) of the overall corrugated mesh **135** and some of the wire/thread extending perpendicular to the upper edge. In such a configuration, the corrugation can occur to create the crests and valleys with only the threads, which run parallel with the upper edge needing to be bent. In such a configuration the corrugating of the fine mesh material forming the corrugated mesh **135** can more readily occur and this material formulating the corrugated mesh can more readily maintain this corrugated configuration during installation and use.

(22) The corrugations **112** in the corrugated mesh **135** preferably have an amplitude between crests and valleys between one-fourth and one-tenth of the length of the corrugated mesh **135** between the upper edge and a lower edge (extending substantially parallel to the gutter lip when in use) of the mesh **135** and similar to a width of the opening in the gutter. Preferably, the corrugations **112** are in a repeating pattern. This pattern is most preferably a sinusoidal pattern with a curving crest and curving valley. Other configurations can also be provided for the corrugated mesh **135**.

(23) It should be apparent that the mesh may be of any material that is weather resistant, has apertures for drainage, and is of sufficient stiffness to bridge the gutter without the need for an auxiliary support. Therefore, the gutter cover can be constructed of other materials such as plastic, expanded metal, perforated metal, slotted metal or louvered metal slits, and so forth. Furthermore, the mesh, with its associated corrugations does not need to completely span the gutter. That is, the mesh's corrugations can be limited to certain portions, according to design preference, and may not need span the entirety of the gutter. For example, the trough may be corrugation free. It should also be apparent that the front strip connector and the rear strip connector can be formed from metal,

plastic, or any other suitable material. As a matter of convention, the front strip connector may alternately be referred to as a gutter lip rail that is connected to the gutter lip side of the mesh, and the rear strip connector alternately referred to as a roof side rail that is connected to the roof side of the mesh.

(24) It is understood that in various other embodiments, the trough **145** (shown in the various embodiments as adjacent to the front strip connector and parallel to the longitudinal axis), can be angled to the front strip connector as well as be oriented at an angle to the mesh's corrugations. Therefore, it is understood that mesh corrugation shapes can be modified as well as the trough's angles without departing from the spirit and scope of this disclosure. For example, the trough can have repeating angles, such as a zigzag, or turns, or smooth gradual turns and so forth, wherein the corrugations may conform to the trough angles.

(25) In addition to assisting in stiffening the mesh, the corrugations may result in a non-smooth or uneven mesh surface, which naturally allows collected debris to dry quicker (due to separation between the debris and the mesh surface) and blow off more easily when there is ambient wind.

(26) FIG. 2 is a semi-side cut-away illustration **200** of the embodiment of FIG. 1A. As illustrated, when the mesh **235** connects to the back of the roof **210** and the gutter **220**, via strip connectors **215** and **225**, a natural downward slope in mesh **235** is created toward the front lip **230** of gutter **220**. The mesh **235** includes a plurality of corrugations **212**. Accordingly, when rainwater comes down the roof **210** and on top of mesh **235**, the rainwater naturally passes through the apertures in mesh **235** and a large portion thereof clings to the underside of mesh **235** without falling off. The lightweight and adhesive properties of rainwater allow it to cling to the underside of mesh **235**, wherein the slope of the mesh **235** causes rainwater to travel towards trough **245**. The bottom **265** of trough **245** is designed to be lower than the front lip **230** of gutter **220**, thereby creating a barrier that deflects the underside rainwater down into the gutter **220**. The arrangement of this “creased” structure prevents rainwater from running off the front of the gutter **220**.

(27) In various embodiments, it has been discovered that the cross sectional “crease” forming trough **245** also can operate to increase the structural integrity of the surface area of the mesh **235** over the gutter **220**. It is understood for a large spanning mesh **235**, the placement of trough **245** in the middle of mesh **235** may lessen its ability to independently support mesh **235**. For example, if the mesh **235** is composed of a steel mesh having a wire diameter that is less than 0.01” thick, with a weave count of more than 32 wires per linear inch (See FIGS. 1B-C, for example), then placement of the trough **245** in the middle of mesh **235** will be insufficient to adequately stiffen the gutter spanning mesh **235** to be self-supporting over gutter **220**.

(28) If the wire diameter decreases, then the wire count per inch increases—this will make the mesh **235** less stiff and unable to sustain itself over a gutter **220** when a cross sectional crease (e.g., trough **245** or similar trough) is formed. For wire diameters that are between 0.009” and 0.01” (thicker wire applied to the lesser wire count per inch), with wire counts of 32 to 60 per inch, the trough **245** can be displaced from the front strip connector **215** by up to 1.5.”

(29) For wire diameters that are between 0.007” and 0.009,” with wire counts of 36 to 56 per inch, the trough **245** can be placed up to 0.75” from the front strip connector **225**. For wire diameters that are between 0.005” and 0.0069,” with wire counts of 40 to 50 per inch, the trough **245** can be placed up to 0.25” from the front strip connector **225**.

(30) However, the trough **245** could be formed on the mesh **235** between the rear and front strip connectors (**215** and **225**) on a standard 5 inch gutter top opening, if the wire diameter is between 0.011” and 0.015” and the wire count is between 20 and 31 per inch. If a lower wire count per inch of between 10 and 19 is needed, then the wire diameter would need to be between 0.016” and 0.02.” However, with the wider mesh hole openings, as in the latter example, pine needles and small leafy debris may penetrate into the mesh **235** and into the gutter **220**, potentially clogging the gutter **220** to cause rainwater to spill out of the gutter **220**. Accordingly, while a lower wire count per inch for mesh **235**, such as 20 wires per inch or less, can be used, it will be less effective in

debris preclusion.

(31) Having the mesh-clinging rainwater drop in to the middle of the gutter **220** rather than near the front lip **230** of the gutter **220** reduces the possibility that rainwater will run out of the gutter **220**. However, because a higher wire count per inch functions to keep out leaves, pine needles and roof sand grit, etc. from entering the gutter **220**, the mesh **235** will be stiffer and accordingly trough **245** can be close to or adjacent to the front strip connector **225**.

(32) The trough **245** can be, for example, V-shaped to provide stability, strength and rigidity for supporting the back bend **246** of the trough **245**, as shown in FIG. 2 where the trough **245** is adjacent to the front strip connector **225**. The front strip connector **225** can act as additional support for the trough **245** when adjacent to each other. It is important for the bend **246** along the length of the mesh **235** (nearly adjacent to the front strip connector **225**) to be sufficiently rigid so as to sustain the span of the mesh **235** to rear strip connector **215**. Another reason for the needed strength and support along bend **246** is if the mesh **235** ever becomes weighted down with leaves, pine needles, roof sand grit or snow and ice. The added strength prevents or reduces the possibility of the mesh **235** collapsing into the gutter **220**.

(33) The corrugations **212** on the mesh **235** of this embodiment 200, include at least one corrugation **213** that extends from an upper edge of the mesh **235** (near connector **215**) into a portion of the trough **245**. The corrugation **213** does not extend all the way through the trough **245** to the lower edge of the mesh **235** (near connector **225**). The corrugations **212** further include at least one corrugation **214** that extends from the lower edge of the mesh **235** through the trough **245**. The corrugation **214** in this embodiment does not extend all the across the surface of the mesh **235** to the upper edge. In other exemplary embodiments, the corrugations do not extend into the trough.

(34) As shown in the cross-sectional illustration of FIG. 3A, the trough **345** can be composed of multiple troughs, the additional trough **375** appearing along the lower side of the mesh **335**. The rationale for additional troughs is to provide more barriers, which act to divert higher flows of rainwater into the gutter **320**. It is understood that higher flows of rainfall could potentially pass through a single barrier, which can arise from severe weather storms or from larger surface areas of a house roof where rainwater has accumulated in a roof valley and channeled to the inside corner of a covered gutter. It is understood that the mesh **335** that is running adjacent to the front strip connector **325** can be formed into a variety of different shapes. It is further understood that the mesh **335** includes corrugations, not shown, that extend at least partially through the trough **375**.

(35) FIG. 3B is a cross-sectional, close up illustration of an exemplary trough **375**, with V-shape formed from three bends **381**, **383**, and **385**; and is illustrative of how rainwater typically travels along the mesh **335** into the trough **375**. Rainwater generally will travel under the mesh **335** and when encountering the barrier forming side/surface of the V-shaped trough **375**, travels down and eventually drops off from the end E of bend **383**, which forms the low point of trough **375**. In some instances, rainwater will flow on the top of mesh **335** and flowing over bend **385** encounter side/surface G, which diverts the water into the bottom of trough **375**. The entering water will drain through the apertures in surfaces H and G, into the gutter (not shown).

(36) Understanding that additional and/or varied shaped troughs can also be formed, FIG. 4 is an illustration **400** of mesh **435** with trough **445** formed with a plurality of upward protruding barriers **475** and **485**. In some embodiments, combinations of the troughs shown in FIGS. 2 and 3A may be utilized, as well as other shaped troughs. Accordingly, trough **445** can be an inverted V, U, laterally oriented L, or laterally oriented relaxed L shape, for example. It is further understood that the mesh **435** includes corrugations, not shown, that extend at least partially through the trough **445**. FIGS. 5A-B are illustrations of an embodiment of a mesh **535** with a U-shaped trough **545**, described here as having four bends **581**, **583**, **584** and **585**. The principal rainwater barrier is formed by surface H, which forces under-mesh traveling water towards bends **583** and **584**, which forms the lowest points of trough **545**. The ensuing water can penetrate through surface H into drain through to neighboring surface G, or be diverted by surface H down towards bends **583** and **584**, and fall into

the gutter **520**. It is further understood that the mesh **535** includes corrugations, not shown, that extend at least partially through the trough **545**.

(37) FIGS. **5A-B** are illustrations of an embodiment of a mesh **535** with a U-shaped trough **545**, described here as having four bends **581**, **583**, **584** and **585**. The principal rainwater barrier is formed by surface H, which forces under-mesh traveling water towards bends **583** and **584**, which forms the lowest points of trough **545**. The ensuing water can penetrate through surface H to drain through to neighboring surface G, or be diverted by surface H down towards bends **583** and **584**, and fall into the gutter **520**. It is further understood that the mesh **535** includes corrugations, not shown, that extend at least partially through the trough **545**.

(38) It should be apparent that the V-shaped troughs in FIGS. **2-4** and the U-shaped trough(s) in FIGS. **5A-B** only require a minimum of three bends in the mesh for the V-shape and four bends for the U-shape to form their shapes. The wall barrier formed by surface H in FIG. **5B** has a unique feature in that if it is formed anywhere in the open surface area of mesh **535**, even along the longitudinal midline axis of the gutter (e.g., further away from the front strip connector **525**), the mesh **535** will retain a significant amount of its rigidity. Therefore, mesh **535** will be less likely to collapse in the gutter **520** from the weight of leaves, pine needles, roof sand, grit or snow and ice. This “supportability” is due to the fact that when downward pressure is applied to either sides of mesh **535**, from debris, etc., bends **581** and **585** will push against each other to stiffen against further downward movement in mesh **535**.

(39) FIG. **6A** is a side-view illustration of a mesh **635** embodiment with a laterally oriented L-shaped trough **645**. The mesh **635** covers gutter **620** and is attached to the gutter's front and rear ends via rear strip connector **615** and front strip connector **625**. The void formed by the trough **645** operates to provide a debris collection area **655**. It is further understood that the mesh **635** includes corrugations **610** that extend at least partially through the trough **645**. It is further understood that the mesh **635** includes corrugations, not shown, that extend at least partially through the trough **645**.

(40) FIG. **6B** is a close-up illustration of laterally oriented L-shaped trough **645**, showing only two bends **681** and **683** in mesh **635**, to form the trough **645**. Two bends **681** and **683** create a firmer support structure of the surface area of the mesh **635** than with three displaced bends, the exception perhaps being the embodiment of FIGS. **5A-B**, where the three bends are in close proximity to each other. Under-mesh **645** traveling rainwater will travel to bend **683**, which form the lowest point of mesh **645**, and drop into the gutter **620**. Surface G operates as a dam against onrushing water and a collection area for debris, allowing accumulating water to drain through the respective apertures in the mesh **645**.

(41) FIG. **7** is an illustration of the embodiment of FIG. **6A** in a snowmelt situation. Snow **705** accumulating on the roof shingles/surface **710** will melt to form snowmelt **707** over mesh **735** traveling towards the trough **745**, which is connected to front strip connector **725**. Water melting from snowmelt **707** penetrates the mesh **735** and travels under the mesh **735** to trough **745**. The lowest point of the trough **745** (bend **683** in FIG. **6B**) acts as the drip point, causing the water to drop **709** into the gutter **720**. It is further understood that the mesh **735** includes corrugations **710** that extend at least partially through the trough **745**. It is further understood that the mesh **735** includes corrugations, not shown, that extend at least partially through the trough **745**.

(42) FIGS. **8A-B** are illustrations of another embodiment wherein the trough **845** has a laterally oriented relaxed L-shape for accommodating debris, shown here as the debris collection area **855**. FIG. **8A** illustrates the mesh **835** attached to the gutter/roof via strip connectors **815** and **825**. Noticeable is that an angle of the plane of the mesh section-to-gutter strip connector **825** is different than the angle of the plane of the mesh section-to-roof strip connector **815**, forming an offset occupied by the trough **845**. Trough **845** is disposed in the mesh **835** proximal to the front strip connector **825**, which is attached to the gutter **820**. The trough **845** is formed from two bends **881** and **883** in the mesh **845**, however, the surface G between the two bends **881** and **883** is less

vertical than in the embodiments shown in FIGS. 6A-B. The “less than vertical” orientation results in a “softer” or not as steep of a slope for the barrier or surface G to accumulated debris in the trough **845**. That is, since the surface G is sloped, the debris will likely blow off of the gutter cover more easily than in the embodiment shown in FIGS. 6A-B. It is further understood that the mesh **835** includes corrugations **810** that extend at least partially through the trough **845**. It is further understood that the mesh **835** includes corrugations, not shown, that extend at least partially through the trough **845**.

(43) FIG. 9 is an illustration of the embodiments of FIGS. 8A-B in a snowmelt situation. Snow **905** accumulating on the roof shingle surface **910** will melt to form snowmelt **907** over mesh **935** traveling towards the trough **945**, which is connected to front strip connector **925**. Water melting from snowmelt **907** penetrates the mesh **935** and travels under the mesh **935** to trough **945**. The lowest point of the trough **945** (bend **883** in FIG. 7B) acts as the drip point, causing the water to drop **909** into the gutter **920**. It is further understood that the mesh **935** includes corrugations, not shown, that extend at least partially through the trough **945**.

(44) Both trough designs shown in FIGS. 8 and 9 provide a feature that significantly reduces potential snowmelt runoff over the gutter cover and unto the ground. To fully appreciate the snowmelt feature, an understanding of the snowmelt runoff problem is necessary. When a permeable mesh type gutter cover material is not exposed to rain or snow, but there is snow on top of the roof, when the snow begins to melt it can drip off the edge of the gutter cover and the gutter. This problem is mainly seen in the micro-mesh type gutter covers with hole openings less than 0.125” square.

(45) The reason the snowmelt exits over the side of a mesh gutter cover is because the mesh is not wet since there is no rain. Moreover, it is possible the mesh is frozen, preventing penetration of the snowmelt into the mesh. In either instance, the snowmelt coming down the roof tends to not penetrate the permeable mesh material and consequently runs along the top of the mesh and then over the front of the gutter. It should be understood that snowmelt can occur in below freezing weather, wherein the roof under the snow is warmed by the home's heat, causing the snowmelt.

(46) In contrast, when it is raining (which means the temperature is above freezing), snowmelt will come off the roof and with the mesh wet from the rain, the snowmelt will drop through the mesh and into the gutter. The warming rain droplets striking any snowmelt on the mesh will also help force the snowmelt through the mesh.

(47) Because of the snowmelt issue, the downward trough designs illustrated in FIGS. 7 and 9 incorporate the barrier formed by surface G, which provides a permeable mesh wall that the melted snow can penetrate through. Typically, when snowmelt travels down the roof and onto the mesh of FIGS. 7 and 9, it can travel between 3 and 10 miles per hour, depending on the steepness angle of the roof, when the snowmelt hits the surface G, its momentum can force the snowmelt through the apertures of surface G and drop down into the gutter. When the debris collection area **655**, **855** has no debris sitting in it, the functionality and purpose of the downward sides of surface G are greatly enhanced.

(48) FIGS. 10A-B are illustrations of another gutter cover embodiment, wherein either one or more of the front and rear strip connectors is not utilized. For example, the front of mesh **1035**, having trough **1045**, can be fastened to the front lip **1027** of the gutter **1020** and the rear of the mesh **1035** can be laid on the back lip of the gutter **1020**, without the need of fastening it to any strip connector. In this scenario, the front lip **1027** of the gutter **1020** acts like a front connector support to hold up the surface area of the mesh **1035** when a screw (not shown) is fastened through the top end portion **1037** of the mesh **1035** and through the gutter's top ridge **1029**. The screw can be placed through any section of the top ridge **1029** however typically is fastened along the dimensional line **1040**. To further create additional support, the mesh **1035** can be folded into a flap **1039**, which provides additional strength on the mesh **1035** screwed to the gutter **1020**. It is further understood that the mesh **1035** includes corrugations, not shown, that extend at least partially

through the trough **1045**.

(49) While FIG. **10B** shows a single fold, additional folds can be implemented for greater strength and support. In this embodiment, the trough **1045** is adjacent to the front lip **1027** of the gutter **1020**. As stated earlier, in various other embodiments, the trough **1045** may be disposed at an arbitrary distance from the front of the gutter **1020**.

(50) Also, in various embodiments, the trough(s) shown may be composed of the mesh material with or without corrugations. That is, one or more of the trough surfaces H and/or G (seen in FIG. **3A** or **3B**) may be non-corrugated. For example, the mesh “corrugations” could begin from the rear strip connector and continue to the second bend in the trough, or stop at the first bend and resume from the second bend. In other embodiments, as seen in FIGS. **6B** and **8B**, because there is sufficient strength in the mesh on the surface G, due to being supported by the front strip connector, the mesh corrugations could go from the rear strip connector and stop at the second bend. It should be understood that the term corrugation can be interpreted as a structure that provides apertures for drainage, such as a perforation, slot, slit, overlaying wires with gaps, and so forth in the respective gutter cover.

(51) FIG. **11** is a semi-side cut-away illustration **1100** of the embodiment of FIG. **1A**. As illustrated, when the mesh **1135** connects to the back of the roof **1110** and the gutter **1120**, via strip connectors **1115** and **1125**, a natural downward slope in mesh **1135** is created toward the front lip **1130** of gutter **1120**. This embodiment is similar to the embodiment of FIG. **2**, in that it includes a trough **1145** having surfaces G and H, along with the end point E. The device **1100** also has corrugation **1113**, which extends into the trough **245** and corrugation **1114**, which does not extend all the way to the top end of the mesh near connector **1115**. A difference with the present embodiment is that the corrugations **1112** extend in a non-perpendicular direction relative to the gutter lip **1130**.

(52) Whereas in the embodiment shown in FIG. **2**, the corrugations are substantially perpendicular to the gutter lip. It should be appreciated that in other exemplary embodiments, the corrugations extend along the mesh in a variety of manners. Still further, in other embodiments, the corrugations extend along the mesh in differing angles relative to the gutter lip or the strip connector.

(53) The present disclosure is not to be limited in terms of the particular embodiments described in this application, which are intended as illustrations of various aspects. Many modifications and variations can be made without departing from its scope, as will be apparent to those skilled in the art. Functionally equivalent methods and apparatuses within the scope of the disclosure, in addition to those enumerated herein, will be apparent to those skilled in the art from the foregoing descriptions. Such modifications and variations are intended to fall within the scope of the appended claims. The present disclosure is to be limited only by the terms of the appended claims, along with the full scope of equivalents to which such claims are entitled. It is to be understood that this disclosure is not limited to particular methods, implementations, and realizations, which can, of course, vary. It is also to be understood that the terminology used herein is for the purpose of describing particular embodiments only, and is not intended to be limiting.

(54) With respect to the use of substantially any plural and/or singular terms herein, those having skill in the art can translate from the plural to the singular and/or from the singular to the plural as is appropriate to the context and/or application. The various singular/plural permutations may be expressly set forth herein for sake of clarity.

(55) While various aspects and embodiments have been disclosed herein, other aspects and embodiments will be apparent to those skilled in the art. The various aspects and embodiments disclosed herein are for purposes of illustration and are not intended to be limiting, with the true scope being indicated by the following claims.

Claims

1. A gutter debris preclusion device for securing to a top portion of a gutter that is attached to a building, comprising: a mesh with corrugations having a roof side, a gutter lip side, and at least one trough with corrugations, wherein the mesh is configured to substantially cover a gutter when the device is installed over the gutter, and one or more troughs of the at least one trough is disposed proximal to and parallel to the gutter lip side; and a gutter lip end of the mesh a gutter lip rail attached to the gutter lip side of the mesh.
2. The device of claim 1, wherein the mesh is formed from stainless steel wires, plastic, expanded metal, perforated metal, slotted metal or louvered metal.
3. The device of claim 1, wherein the corrugations in the mesh are configured to provide a planar stiffness to the mesh causing the mesh to be self-supporting over the gutter.
4. The device of claim 1, wherein the corrugations in the mesh are formed via at least one of stamping, pressing, and weaving.
5. The device of claim 1, wherein a trough of the at least one trough is displaced up to 1.5" from the gutter lip rail.
6. The device of claim 1, wherein a trough of the at least one trough is displaced up to 0.25" from the gutter lip rail.
7. The device of claim 1, further comprising a second trough disposed in the mesh along a longitudinal axis of the of mesh.
8. The device of claim 1, wherein a trough of the at least one trough is disposed adjacent to the gutter lip side.
9. The device of claim 1, further comprising a roof rail attached to the roof side of the mesh.
10. The device of claim 1, wherein a bottom of a trough of the at least one trough is below in elevation from a top of the gutter lip rail.
11. The of claim 1, wherein a trough of the at least one trough has a gutter lip side wall inclined in a direction towards the gutter lip rail and has a roof side wall joined to a bottom of the gutter lip side wall and inclined at an angle greater than 90 degrees from the gutter lip side wall, wherein the roof side wall is longer than the gutter lip side wall.
12. The device of claim 11, wherein the gutter lip side wall is proximal to the gutter lip rail.
13. The device of claim 1, wherein a cross-section of the at least one trough is U-shaped.
14. The device of claim 1, wherein a cross-section of the at least one trough is partially U-shaped.
15. A gutter debris preclusion device for securing to a top portion of a gutter that is attached to a building, comprising: a mesh having apertures, corrugations, a roof side, a gutter lip side, a gutter lip portion, and a water dam with corrugations disposed proximal to and parallel to the gutter lip portion, wherein the mesh is configured to substantially cover a gutter when the device is in use; and a gutter lip rail attached to the gutter lip portion.
16. The device of claim 15, wherein the water dam is formed from a first and second wall, joined at a bottom, wherein the bottom is below the gutter lip rail when the device is in use.
17. The device of claim 15, further comprising a plurality of water dams.
18. The device of claim 16, wherein at least one of the first and second wall is curved.
19. The device of claim 16, wherein the joined walls form a contiguous curved shape.
20. The device of claim 16, wherein a top portion of the first wall is connected to a gutter lip.
21. The device of claim 16, further comprising a roof side rail attached to the roof side.
22. A gutter debris preclusion device for securing to a top portion of a gutter that is attached to a building, comprising: a mesh having apertures, corrugations, a roof side, a gutter lip side, and a gutter lip portion terminating the gutter lip side, wherein the mesh is sized to substantially cover a gutter; wherein a first plane of the gutter lip side is different from a second plane of the roof side, forming at least one offset between the first and second planes, the at least one offset being bridged by one or more third planes of the mesh; and wherein a roof side end of the one or more third planes of the mesh being lower than a gutter lip side end of the one or more third planes of the

mesh.

23. The device of claim 22, wherein a width spanned by the first plane is less than a width spanned by the second plane.

24. The device of claim 22, wherein a depth of the at least one offset operates as a water reservoir.

25. The device of claim 22, wherein the corrugations are disposed in the second plane.

26. The device of claim 22, wherein the corrugations are disposed in the one or more third planes.

27. The device of claim 22, wherein a cross-section of the at least one offset is curved in shape.

28. A gutter debris preclusion device for securing to a top portion of a gutter attached to a building, comprising: a water permeable mesh having corrugations, a roof side, a gutter lip portion, and a trough disposed parallel to and proximal to the gutter lip portion, wherein the mesh is sized to substantially cover a prospective gutter attached to a prospective building, wherein the trough has a longer first wall extending towards the roof side and a shorter second wall extending towards the gutter lip portion, wherein a shape of the longer first wall and shorter second wall form a 2-sided reservoir, and wherein a bottom point of the reservoir is lower than the gutter lip portion; and a gutter lip attachment member coupled to the gutter lip portion.

29. The device of claim 28, wherein an angle between the longer first wall and shorter second wall is greater than 90 degrees.

30. The device of claim 28, wherein an angle between the longer first wall and shorter second wall is less than 90 degrees.

31. The device of claim 28, wherein the mesh is formed from stainless steel wires, plastic, expanded metal, perforated metal, slotted metal or louvered metal.

32. The device of claim 28, further comprising a roof strip connector adapted to connect the roof side to either a rear of the gutter or a roof element neighboring the gutter.

33. The device of claim 28, wherein at least one of the first and second walls contains another angled bend to form a segmented or a curved reservoir bottom.
