

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250263106

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Lawther; Robin Ivo et al.

---

## METHODS AND APPARATUS FOR RETAINING A STEERING SHAFT

---

### Abstract

Systems, apparatus, articles of manufacture, and methods are disclosed for retaining a steering shaft are disclosed herein. An example apparatus disclosed herein includes a seal, a steering shaft extending through the seal, and means for retaining the steering shaft in a retained position relative to the seal, the means for retaining configured to be release the steering shaft to an assembled position.

---

**Inventors:** Lawther; Robin Ivo (Chelmsford, GB), Hawkins; Christopher (Hornchurch, GB), Mata; Humberto (Dearborn, MI), Soderlind; Erik William (Harrison Township, MI), Schaus; Eric (Morgantown, PA), Putnam; Todd (South Lyon, MI)

**Applicant:** Ford Global Technologies, LLC (Dearborn, MI)

**Family ID:** 1000008589327

**Appl. No.:** 19/204178

**Filed:** May 09, 2025

### Related U.S. Application Data

parent US continuation 18313884 20230508 parent-grant-document US 12311997 child US 19204178

---

### Publication Classification

**Int. Cl.:** B62D1/16 (20060101)

**U.S. Cl.:**

## Background/Summary

RELATED APPLICATION [0001] This patent arises from a continuation of U.S. patent application Ser. No. 18/313,884, filed on May 8, 2023, which is incorporated herein by reference in its entirety.

### FIELD OF THE DISCLOSURE

[0002] This disclosure relates generally to vehicle steering systems and, more particularly, to methods and apparatus for retaining a steering shaft.

### BACKGROUND

[0003] Vehicle steering systems allow users to turn the wheels of a vehicle using a steering input, such as a steering wheel. In many steering systems, the steering wheel is coupled to a steering shaft assembly, which transmits driver inputs to a steering gear. Steering gears, such as rack and pinion systems, adjust the position of the vehicle wheels based on the user input, which changes the direction of the vehicle. Steering shaft assemblies can include multiple shafts and joints between the steering wheel and steering gear.

### SUMMARY

[0004] An example apparatus disclosed herein includes a seal, a steering shaft extending through the seal, and means for retaining the steering shaft in a retained position relative to the seal, the means for retaining configured to be release the steering shaft to an assembled position.

[0005] An example vehicle disclosed herein including a first compartment, a second compartment, a panel separating the first compartment from the second compartment, and an assembly including at least one retention feature, a seal coupled within a hole of the panel, and a steering shaft extending through the seal, the steering shaft movable between a first position relative to the seal and a second position relative to the seal, the steering shaft retainable in the first position via the at least one retention feature, the first position having a first length of the steering shaft in the first compartment, the second position having a second length in the second compartment, the first length different than the second length.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0006] FIG. 1 illustrates an example vehicle in which the teachings of this disclosure can be implemented.

[0007] FIG. 2A illustrates an example steering assembly of the vehicle of FIG. 1 in an unassembled position.

[0008] FIG. 2B illustrates an example steering assembly of the vehicle of FIG. 1 in an assembled position.

[0009] FIG. 3A illustrates an example shaft of FIGS. 2A and 2B in a retained position associated with the unassembled position of FIG. 2A.

[0010] FIG. 3B illustrates an example shaft of FIGS. 2A and 2B in a deployed position associated with the assembled position of FIG. 2B.

[0011] FIG. 4 is a perspective view of a shaft including an example pin and an example retaining slot implemented in accordance with the teachings of this disclosure.

[0012] FIGS. 5A-5C are various schematic diagrams depicting an example process for engaging the features of FIG. 4 to retain the shaft of FIGS. 2A-3B.

[0013] FIG. 6A is a schematic view of a steering shaft including an example tapered outer diameter

implemented in accordance with the teachings of this disclosure.

[0014] FIG. 6B is a schematic view of the shaft of FIG. 6A in a retained position.

[0015] FIG. 7A is a schematic view of a steering shaft including an example flange implemented in accordance with the teachings of this disclosure.

[0016] FIG. 7B is a schematic view of the shaft of FIG. 7A in a retained position.

[0017] FIG. 8 is a perspective view of another shaft including an example retainer bracket implemented in accordance with the teachings of this disclosure.

[0018] FIG. 9 is a perspective view of another shaft including another example retainer bracket implemented in accordance with the teachings of this disclosure.

[0019] FIG. 10 is a schematic view of a steering shaft including a flexible member in a first configuration implemented in accordance with the teachings of this disclosure.

[0020] FIG. 11 is a schematic view of a steering shaft including a flexible member in a second configuration implemented in accordance with the teachings of this disclosure.

[0021] FIG. 12 is a schematic view of a steering shaft including an example pin coupling in a first configuration implemented in accordance with the teachings of this disclosure.

[0022] FIG. 13 is a schematic view of a steering shaft including an example pin coupling in a second configuration implemented in accordance with the teachings of this disclosure.

[0023] In general, the same reference numbers will be used throughout the drawing(s) and accompanying written description to refer to the same or like parts. The figures are not necessarily to scale. Instead, the thickness of the layers or regions may be enlarged in the drawings. Although the figures show layers and regions with clean lines and boundaries, some or all of these lines and/or boundaries may be idealized. In reality, the boundaries and/or lines may be unobservable, blended, and/or irregular.

#### DETAILED DESCRIPTION

[0024] Vehicle steering systems include components that are disposed within the cabin compartment of the vehicle (e.g., the steering wheel, parts of the steering column, etc.) and components that are disposed within the front component compartment of the vehicle (e.g., the steering gear, the linkage arms, power steering components, etc.). In many vehicle configurations, the vehicle cabin compartment is separated from the front component compartment by a dash panel and floor panel, which are typically part of the body of the vehicle. In some such vehicle configurations, a component of the steering system (e.g., a steering shaft, etc.) passes through the dash panel (e.g., via a dash seal, etc.) and/or the floor of the vehicle (e.g., via a floor seal, etc.). During the assembly of such vehicles, the cabin-side components of the steering system, including one or more steering shafts, can be coupled to the dash panel and/or floor panel prior to being coupled to the other components of the steering system. After these components have been assembled, the steering gear is coupled to other components of the steering assembly (also referred herein to as “decking the steering gear”) by coupling a universal joint of a steering shaft to a corresponding input shaft of the steering gear. However, because the input shaft of the steering gear is disposed within a receiving socket of the universal joint, the steering gear must be coupled to the universal joint via a vertical motion to prevent the input shaft from contacting the outer surface of the universal joint. Configuring a vehicle assembly line to support such a decking of the steering gear can be costly and/or require a large amount of additional assembly line space.

[0025] Examples disclosed herein enable the assembly of vehicle steering systems via features that retain the vehicle steering shaft in a retained position relative to a dash seal and/or floor seal. In some examples disclosed herein, after the steering gear has been decked, the steering shaft can be released from the retained position and coupled to the steering gear. Some examples disclosed herein include a steering shaft with a pin and a seal that includes a slot that retains the shaft via a bayonet coupling. Some examples disclosed herein include shafts with tapered diameters that retain the shaft via a releasable press fit with the seal. Some examples disclosed herein include a shaft with a flange that retains the shaft via an interface with a corresponding flange of the seal. Some

examples disclosed herein include a removable bracket coupled to the yoke of the universal joint and a corresponding feature of the dash seal. Some examples disclosed herein include an elastic band that maintains the shaft in the retained position. Some examples disclosed herein include a steering shaft with a hole to receive a pin to retain the steering shaft. Examples disclosed herein permit the lateral and/or longitudinal decking of steering gears, which reduces the complexity and cost of steering system assembly.

[0026] As used herein, the orientation of some features is described with reference to a lateral axis, a vertical axis, and a longitudinal axis of the vehicle associated with the features. As used herein, the longitudinal axis of the vehicle is parallel to a centerline of the vehicle. The terms “rear” and “front” are used to refer to directions along the longitudinal axis closer to the rear of the vehicle and the front of the vehicle, respectively. As used herein, the vertical axis of the vehicle is perpendicular to the ground on which the vehicle rests. As used herein, unless otherwise stated, the term “above” describes the relationship of two parts relative to Earth and the vertical axis. A first part is above a second part, if the second part has at least one part between Earth and the first part. Likewise, as used herein, a first part is “below” a second part when the first part is closer to the Earth than the second part. As used herein, the lateral axis of the vehicle is perpendicular to the longitudinal and vertical axes and is generally parallel to the axles of the vehicle. Some of the attached figures are annotated with a set of axes including the lateral axis (Y), the longitudinal axis (X), and the vertical axis (Z). As used herein, the terms “longitudinal,” is used to refer to directions parallel to the longitudinal axis. As used herein, the terms “lateral” and “horizontal” are used to refer to directions parallel to the lateral axis. As used herein, the terms “vertical” and “normal” are used interchangeably to refer to directions parallel to the vertical axis.

[0027] As used herein, the orientation of some features is described with reference to a radial axis, an axial axis, and a circumferential orientation of a shaft associated with the features. As used herein, the axial axis of the shaft is parallel to a centerline of the shaft. As used herein, the radial axis of the shaft is perpendicular to the centerline of the shaft. As used herein, the circumferential direction of the shaft refers to the angular positions relative to the shaft. As used here, the terms “radially,” “axially,” and “circumferentially” are adjectives used to refer to features associated with the radial axis, the axial axis, and circumferential direction. Some of the attached figures are annotated with a set of axes including the axial axis (A), the radial axis (R), and the circumferential orientation (C).

[0028] As noted above, a first part can be above or below a second part with one or more of: other parts therebetween, without other parts therebetween, with the first and second parts touching, or without the first and second parts being in direct contact with one another. As used in this patent, stating that any part (e.g., a layer, film, area, region, or plate) is in any way on (e.g., positioned on, located on, disposed on, or formed on, etc.) another part, indicates that the referenced part is either in contact with the other part, or that the referenced part is above the other part with one or more intermediate part(s) located therebetween.

[0029] As used herein, connection references (e.g., attached, coupled, connected, and joined) may include intermediate members between the elements referenced by the connection reference and/or relative movement between those elements unless otherwise indicated. As such, connection references do not necessarily infer that two elements are directly connected and/or in fixed relation to each other. As used herein, stating that any part is in “contact” with another part is defined to mean that there is no intermediate part between the two parts.

[0030] Unless specifically stated otherwise, descriptors such as “first,” “second,” “third,” etc., are used herein without imputing or otherwise indicating any meaning of priority, physical order, arrangement in a list, and/or ordering in any way, but are merely used as labels and/or arbitrary names to distinguish elements for ease of understanding the disclosed examples. In some examples, the descriptor “first” may be used to refer to an element in the detailed description, while the same element may be referred to in a claim with a different descriptor such as “second” or “third.” In

such instances, it should be understood that such descriptors are used merely for identifying those elements distinctly within the context of the discussion (e.g., within a claim) in which the elements might, for example, otherwise share a same name.

[0031] As used herein, “approximately” and “about” modify their subjects/values to recognize the potential presence of variations that occur in real world applications. For example, “approximately” and “about” may modify dimensions that may not be exact due to manufacturing tolerances and/or other real world imperfections as will be understood by persons of ordinary skill in the art. For example, “approximately” and “about” may indicate such dimensions may be within a tolerance range of  $\pm 10\%$  unless otherwise specified in the below description. In some examples used herein, the term “substantially” is used to describe a relationship between two parts that is within three degrees of the stated relationship (e.g., a substantially colinear relationship is within three degrees of being colinear, a substantially perpendicular relationship is within three degrees of being perpendicular, a substantially parallel relationship is within three degrees of being parallel, etc.).

[0032] “Including” and “comprising” (and all forms and tenses thereof) are used herein to be open ended terms. Thus, whenever a claim employs any form of “include” or “comprise” (e.g., comprises, includes, comprising, including, having, etc.) as a preamble or within a claim recitation of any kind, it is to be understood that additional elements, terms, etc., may be present without falling outside the scope of the corresponding claim or recitation. As used herein, when the phrase “at least” is used as the transition term in, for example, a preamble of a claim, it is open-ended in the same manner as the term “comprising” and “including” are open ended. The term “and/or” when used, for example, in a form such as A, B, and/or C refers to any combination or subset of A, B, C such as (1) A alone, (2) B alone, (3) C alone, (4) A with B, (5) A with C, (6) B with C, or (7) A with B and with C. As used herein in the context of describing structures, components, items, objects and/or things, the phrase “at least one of A and B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, or (3) at least one A and at least one B. Similarly, as used herein in the context of describing structures, components, items, objects and/or things, the phrase “at least one of A or B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, or (3) at least one A and at least one B. As used herein in the context of describing the performance or execution of processes, instructions, actions, activities and/or steps, the phrase “at least one of A and B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, or (3) at least one A and at least one B. Similarly, as used herein in the context of describing the performance or execution of processes, instructions, actions, activities and/or steps, the phrase “at least one of A or B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, or (3) at least one A and at least one B.

[0033] As used herein, singular references (e.g., “a”, “an”, “first”, “second”, etc.) do not exclude a plurality. The term “a” or “an” object, as used herein, refers to one or more of that object. The terms “a” (or “an”), “one or more”, and “at least one” are used interchangeably herein.

Furthermore, although individually listed, a plurality of means, elements, or actions may be implemented by, e.g., the same entity or object. Additionally, although individual features may be included in different examples or claims, these may possibly be combined, and the inclusion in different examples or claims does not imply that a combination of features is not feasible and/or advantageous.

[0034] FIG. 1 illustrates an example vehicle **100** in which the teachings of this disclosure can be implemented. In the illustrated example of FIG. 1, the vehicle **100** includes an example steering system **102**, an example first wheel **104A**, and an example second wheel **104B**. In the illustrated example of FIG. 1, the example vehicle **100** is a van. In other examples, the vehicle **100** can be any type of vehicle (e.g., a truck, a sports utility vehicle (SUV), a semi-trailer truck, a mini-van, a railed vehicle, an all-terrain vehicle (ATV), watercraft, construction equipment, farming equipment, etc.). In the illustrated example of FIG. 1, the vehicle **100** is a two-axle vehicle. In other examples, the

vehicle **100** can have additional axles and/or additional wheels. The example vehicle **100** can have a body-on-frame construction and/or a unibody construction.

[0035] In the illustrated example of FIG. **1**, the steering system **102** includes an example steering wheel **106** to transmit driver inputs to the steering system **102** (e.g. by rotating the steering wheel, etc.). The steering system **102** receives these user inputs via the steering wheel **106**, transforms the input into a lateral force via a steering gear, and rotates the wheels **104A**, **104B** to change the direction of the vehicle **100**. In some examples, the steering system **102** can include a power steering system and/or a steering assist system. For example, the steering system **102** can include a hydraulic power steering system, an electric power steering system, and/or an electro-hydraulic power steering system. A portion of the steering system **102** is described below in conjunction with FIGS. **2A** and **2B**.

[0036] In the illustrated example of FIG. **1**, the vehicle **100** includes an example dash **108**, which separates an example front component compartment **110** of the vehicle **100** from the example cabin compartment **112** of the vehicle **100**. In the illustrated example of FIG. **1**, the front component compartment **110** includes the powertrain of the vehicle **100**, components of the steering system **102** (e.g., the steering linkages, the steering gear, power steering components, components of the drivetrain of the vehicle **100**, etc.). In some examples, the front component compartment **110** can be subdivided via body and/or frame components into smaller compartments. In the illustrated example of FIG. **1**, the cabin compartment **112** (e.g., the passenger compartment, etc.) includes the space in which an operator and/or passengers of the vehicle **100** can reside and/or cargo can be stored.

[0037] FIG. **2A** illustrates a portion of the example steering system **102** of the vehicle **100** of FIG. **1** in an unassembled position **200**. In the illustrated example of FIG. **2A**, the steering system **102** includes an example steering gear **202**, an example intermediate shaft **204**, an example universal joint (U-joint) **206**, and an example input shaft **208**. In the illustrated example of FIG. **2A**, the intermediate shaft **204** passes through an example dash panel **210** via an example dash seal **212**. In the illustrated example of FIG. **2A**, the intermediate shaft **204** is in an example retained position **214**.

[0038] The steering gear **202** is an actuator that receives inputs via the input shaft **208**. The steering gear **202** can transform the rotational motion (e.g., caused by the rotation of the steering wheel **106** and/or rotation caused by a steering assist system, etc.) into a lateral force applied to a pitman arm and/or other steering linkages coupled thereto (not illustrated). In some examples, the lateral force output by the steering gear **202** turns the wheels of the vehicle **100** (e.g., the wheels **104A**, **104B** of FIG. **2**, etc.), thus controlling the direction of travel of the vehicle **100**. In the illustrated example of FIG. **2A**, the steering gear **202** is a rack-and-pinion system. In other examples, the steering gear **202** can be implemented by any other suitable type of steering gear (e.g., a recirculating ball gear system, a worm-and-sector system, etc.).

[0039] The intermediate shaft **204** is a steering shaft that transfers rotational motion between a steering column and the input shaft **208** of the steering gear **202**. In some examples, an upper end of the intermediate shaft **204** (e.g., the end not coupled to the input shaft **208** via the U-joint **206**, etc.) can be coupled to the steering column via another U-joint. In some examples, the steering system **102** can include additional intermediate shafts (e.g., one or more upper intermediate shaft(s), etc.) disposed between the steering column (not illustrated) and the intermediate shaft **204**. The U-joint **206** is a coupling that couples the intermediate shaft **204** and the input shaft **208** when the steering system **102** is assembled. The U-joint **206** permits the transfer of rotational motion (e.g., from the steering wheel **106**, from a steering assist system, etc.) between the intermediate shaft **204** and the input shaft **208**. In the illustrated example of FIG. **2A**, the U-joint **206** is a Cardan-type universal joint. In other examples, the U-joint can be implemented by any other suitable type of coupling that permits the transfer of rotational motion between shafts. The U-joint **206** is described in additional detail below in conjunction with FIGS. **3A** and **3B**.

[0040] The dash panel **210** is a structural component of the dash **108** of FIG. **1** that separates a passenger cabin of the vehicle **100** (e.g., the cabin compartment **112** of FIG. **1**, etc.) from the front component compartment of the vehicle **100** (e.g., the front component compartment **110** of FIG. **1**, etc.). In some examples, the dash panel **210** is a part of the body of the vehicle **100**. In other examples, the dash panel **210** is separated from the body of the vehicle **100**. In the illustrated example of FIG. **2A**, the dash panel **210** is a unitary plate. In other examples, the dash panel **210** can be composed of multiple components.

[0041] The dash seal **212** is a bushing that couples the intermediate shaft **204** to the dash panel **210**. In the illustrated example of FIG. **2A**, the intermediate shaft **204** passes through the dash panel **210** via the dash seal **212**. In the illustrated example of FIG. **2A**, the dash seal **212** is disposed within an opening (e.g., a hole, etc.) in the dash panel **210**. In some examples, the dash seal **212** inhibits the flow of particulate matter (e.g., dirt, etc.), fumes, liquids, etc. between compartments of the vehicle **100** (e.g., the compartments **110**, **112** of FIG. **1**, etc.). In some examples, the dash seal **212** damps noise and vibration transmitted from the dash panel **210** and the intermediate shaft **204**. The dash seal **212** permits the rotation of the intermediate shaft **204** therein, which facilitates the transmission of operator commands between the steering wheel (e.g., the steering wheel **106** of FIG. **1**, etc.) and the steering gear **202**. In some examples, the dash seal **212** can be composed of rubber. In other examples, the dash seal **212** can be composed of any other suitable elastic component (e.g., plastic, silicone, other synthetic rubbers, etc.). In some examples disclosed herein, the dash seal **212** includes features that enable the intermediate shaft **204** to be retained in the retained position **214**. The intermediate shaft **204**, the dash seal **212**, and the universal joint **206** are described in additional detail below in conjunction with FIGS. **3A** and **3B**.

[0042] Examples disclosed herein are not limited to vehicle configurations in which a steering shaft passes through a dash of the vehicle. For example, examples disclosed herein can also be used in conjunction with vehicle configurations where the intermediate shaft **204** and/or another component of the steering system **102** passes through a floor of the vehicle (e.g., via a floor seal similar to the dash seal **212** of FIGS. **2A**, etc.).

[0043] In the illustrated example of FIG. **2A**, the intermediate shaft **204** is held in the retained position **214**. As used herein, the phrase “retained position” refers to a position of a steering shaft during the decking of a steering gear and/or assembly of the steering system, in which the intermediate shaft is slid within the seal to a position vertically above the position the intermediate shaft **204** will have when the steering system **102** is fully assembled. As used herein, the phrases “retained position” and “retracted position” are used interchangeably. The retained position **214** of the intermediate shaft **204** is the position of the intermediate shaft **204** during the decking of the steering gear **202** in the unassembled position **200**. The retained position **214** increases the vertical clearance between the universal joint **206** and the input shaft **208**, which permits the steering gear **202** to be decked longitudinally via an example longitudinal translation **218**, rather than vertically. In the illustrated example of FIG. **2A**, because the intermediate shaft **204** is held in the retained position **214**, the input shaft **208** is able to move beneath the universal joint **206**, which permits the coupling of the input shaft **208** within an example socket **216** of the universal joint **206**. If the intermediate shaft **204** was not in the retained position **214**, attempting to deck the steering gear **202** via the longitudinal motion **218** would cause contact between the input shaft **208** and an outer surface of the universal joint **206**. Example features to hold the intermediate shaft **204** in the retained position **214** are described below in conjunction with FIGS. **4-13**.

[0044] FIG. **2B** illustrates an example steering system **102** of the vehicle **100** of FIG. **1** in an assembled position after the steering gear **202** is decked via the longitudinal motion **218** of FIG. **2A**. In the illustrated example of FIG. **2B**, the intermediate shaft **204** has been released from the retained position **214** of FIG. **2A** into an example deployed position **220** via an example release motion **222**. In the illustrated example of FIG. **2B**, an end of the input shaft **208** has been disposed within the socket **216** of the U-joint **206**, which couples the intermediate shaft **204** to the input

shaft **208**. As used herein, the term “deployed position” refers to the position of the intermediate shaft **204** after the steering system **102** is fully assembled. The deployed position **220** of the intermediate shaft **204** is the position of the intermediate shaft **204** during the operation of the steering system **102** and the vehicle **100**. As used herein, the terms “deployed position” and “assembled position” are used interchangeably.

[0045] FIG. **3A** illustrates an example assembly **300** including the intermediate shaft **204** of FIGS. **2A** and **2B**, the U-joint **206** of FIGS. **2A** and **2B**, and the dash seal **212** of FIG. **2A** and **2B**. In the illustrated example of FIG. **3A**, the intermediate shaft **204** is in the retained position **214**. In the illustrated example of FIG. **3A**, the U-joint **206** includes an example first yoke **302A**, an example second yoke **302B**, and an example ball **304**. In the illustrated example of FIG. **3A**, the dash seal **212**, and the intermediate shaft **204** are disposed in an example lip **306**.

[0046] The first yoke **302A** is disposed at the end of the intermediate shaft **204**. In the illustrated example of FIG. **3A**, the first yoke **302A** is coupled to the intermediate shaft **204** via a weld. In some examples, the first yoke **302A** and the intermediate shaft **204** are unitary (e.g., integral, etc.). In other examples, the first yoke **302A** can be coupled to via one or more fasteners, one or more press fits, and/or one or more shrink fits. The second yoke **302B** includes the socket **216** of FIGS. **2A** and **2B**. In the illustrated example of FIG. **2A**, the first yoke **302A** is coupled to the second yoke **302B** via the ball **304**. In some examples, the ball **304** can be absent. In some such examples, the yokes **302A**, **302B** can be coupled via a cross shaft. The example lip **306** is the structure that houses the dash seal **212** and enables the coupling of the dash seal **212** within the dash panel **210** of FIGS. **2A** and **2B**. The lip **306** can be composed of any suitable material, including a metal (e.g., steel, aluminum, etc.) and/or a rigid plastic. In some examples, the lip **306** can be absent. In some such examples, the dash seal **212** can be coupled directly to the dash panel **210**.

[0047] In the illustrated example of FIG. **3A**, in the retained position **214**, the intermediate shaft **204** has an example first length **308** and an example second length **310** on an example first side **312** of the dash seal **212** (e.g., the steering gear side, the engine side, the side associate with front compartment side of FIG. **1**, etc.) and an example second side **314** of the dash seal **212** (e.g., the steering column side, the steering wheel side, the cabin side, the side associated with the cabin compartment **112** of FIG. **1**, etc.), respectively. In the illustrated example of FIG. **3A**, the lengths **308**, **310** are along the axial axis **A**. In the illustrated example of FIG. **2**, the ratio of the first length **308** to the second length **310** is approximately 0.6. In other examples, the ratio can be any suitable value between 0.3 and 1.5.

[0048] FIG. **3B** illustrates the example assembly **300** of FIG. **3A**, in which the intermediate shaft **204** is in the deployed position **220** of FIG. **2B**. In the illustrated example of FIG. **3B**, in the deployed position **220**, the intermediate shaft **204** has an example third length **316** and an example fourth length **318** on the first side **312** and the second side **314**, respectively, along the axial axis **A**. In the illustrated example of FIG. **3B**, the ratio of the first length **308** to the second length **310** is approximately 2.1. In other examples, the ratio can be any suitable value between 1 and 3. In the illustrated example of FIG. **3B**, the first length **308** of the intermediate shaft **204** in the retained position **214** is approximately half the length of the third length **316** of the intermediate shaft **204** in the deployed position **220**. In other examples, the ratio of the first length **308** and the third length **316** can be any suitable value between 0.25 and 0.75. In the illustrated example of FIG. **3B**, the second length **310** of the intermediate shaft **204** in the retained position **214** is approximately twice the fourth length **318** of the intermediate shaft **204** in the deployed position **220**. In other examples, the ratio of the second length **310** and the fourth length **318** can be any suitable value between 1.5 and 4.

[0049] FIGS. **4-13** include a plurality of features that can be used to retain the intermediate shaft **204** in the retained position **214**. The plurality of features disclosed in FIGS. **4-13** can be used independently and/or in combination with other one(s) of the plurality of features disclosed in FIGS. **4-13**. When the same element number is used in connection with FIGS. **4-13** as was used in



FIGS. 1-3B, it has the same meaning unless indicated otherwise.

[0050] FIG. 4 is a perspective view of an example assembly 400 implemented in accordance with the teachings of this disclosure. In the illustrated example of FIG. 4, the assembly 400 includes an example intermediate shaft 402 and an example dash seal 404. In the illustrated example of FIG. 4, the intermediate shaft 402 includes an example pin 406 and the dash seal 404 includes an example retention slot 408. In the illustrated example of FIG. 4, the assembly 400 is in the example retained position 214 of FIGS. 2A and 3A (e.g., the intermediate shaft 204 is disposed in an elevated vertical position, etc.).

[0051] The intermediate shaft 402 is similar to the intermediate shaft 204 of FIGS. 2A-3B, except that the intermediate shaft 402 includes the example pin 406 extending radially from the outer diameter of the intermediate shaft 402. In some examples, the pin 406 can be integral with the shaft 402. In some such examples, the pin 406 and the intermediate shaft 402 can be formed via casting, additive manufacturing, and/or any other suitable manufacturing technique. In other examples, the pin 406 can be coupled to the shaft via one or more welds, one or more fasteners and/or one or more chemical adhesives. Additionally or alternatively, the pin 406 can be coupled to the intermediate shaft 402 via a press fit and/or a shrink fit. In some such examples, a hole can be formed in the intermediate shaft 402 and the pin 406 can be inserted therethrough. In some such examples, the pin 406 can be a through pin (e.g., disposed in a hole that extends through the intermediate shaft 402, etc.). In some such examples, the opposing end of the pin 406 (not illustrated) can be disposed within a corresponding retention slot (not illustrated) formed in a corresponding position within the dash seal 404 (e.g., disposed 180 degrees from the retention slot 408, etc.).

[0052] In the illustrated example of FIG. 4, the dash seal 404 is similar to the dash seal 212 of FIGS. 2A-3B, except that the dash seal 404 includes the retention slot 408. In the illustrated example of FIG. 4, the retention slot 408 is formed in the dash seal 404 and extends through the wall of the dash seal 404. In other examples, the retention slot 408 can be a slot disposed within the interior of the dash seal 404 that does not extend to the outer diameter of the dash seal 404. In the illustrated example of FIG. 4, the retention slot 408 is generally L-shaped and is approximately equal in width to the diameter of the pin 406 to permit the entry of the pin 406 into the retention slot 408. In other examples, the retention slot 408 can be J-shaped, C-shaped, and/or any other suitable shape that retains the pin 406 within the retention slot 408. In the illustrated example of FIG. 4, the retention slot 408 has straight corners (e.g., 90-degree corners, etc.). In other examples, the retention slot 408 can have corners that are chamfered, filleted, and/or any other suitable corner geometry. The retention slot 408 can be formed via negative manufacturing within the dash seal 212 (e.g., via cutting, via machine, etc.). In other examples, the retention slot 408 is formed concurrently with the forming of the dash seal 404 (e.g., during the molding of the dash seal 404, etc.).

[0053] In the retained position 214 illustrated in FIG. 4, the pin 406 and the retention slot 408 form a bayonet coupling (e.g., a lightbulb coupling, a bayonet interface, a lightbulb interface, etc.). The coupling and decoupling of the pin 406 and the retention slot 408 are described in additional detail below in conjunction with FIGS. 5A-5C. The example pin 406 and retention slot 408 are means for retaining (e.g., retaining means, etc.) the intermediate shaft 402 in the example retained position 214. Particularly, the engagement (e.g., deposition, etc.) of the pin 406 within the retention slot 408 prevents the intermediate shaft 402 from sliding vertically downward along the axial axis A within the dash seal 404 into a deployed position (e.g., the deployed position 220 of FIGS. 2B and 3B, etc.).

[0054] In the illustrated example of FIG. 4, the assembly 400 includes a single pin and a single corresponding retention slot, the pin 406 and the retention slot 408, respectively. In other examples, the assembly 400 can include additional pins and retention slots (e.g., 2 pins and corresponding retention slots, 3 pins and corresponding retention slots, 4 pins and corresponding retention slots,

etc.). In some examples, the additional pins can be aligned axially with the pin **406**, have a substantially the same width as the pin **406**, and have a substantially same radial length as the pin **406**. In other examples, the additional pins can be disposed at any other suitable location(s) (e.g., axially displaced from the pin **406**, etc.) and/or can have any other suitable widths and/or radial lengths. Similarly, the additional retention slots can be aligned axially with the retention slot **408** and have a same geometry as the retention slot **408**. In some such examples, the additional pins can be distributed evenly about the circumference of the intermediate shaft **402** (e.g., spaced evenly in the circumferential direction, etc.). In other examples, the additional pins can be distributed unevenly about the circumference of intermediate shaft **402** (e.g., spaced evenly in the circumferential direction, etc.).

[0055] FIGS. 5A-5C are schematic illustrations of the assembly **400** moving from a deployed position (e.g., the deployed position **220** of FIG. 2C, etc.) to the retained position **214** depicted in FIG. 4A. FIGS. 5A-5C include dash lines, which are hidden lines representing portions of the intermediate shaft **402** obscured by the dash seal **404**. FIG. 5A is a schematic illustration of the intermediate shaft **402** of FIG. 4, the dash seal **404** of FIG. 4, the pin **406** and the retention slot **408** of FIG. 4 in an example first position **500**. The first position **500** corresponds to the deployed position **220** of FIG. 2B and 3B, in which the pin **406** is not disposed within the retention slot **408**.

[0056] FIG. 5B is a schematic illustration of the intermediate shaft **402** of FIG. 4, the dash seal **404** of FIG. 4, the pin **406**, and the retention slot **408** of FIG. 4 in an example second position **502** following an example axial translation **506**. The example axial translation **506** causes the pin **406** to enter an example channel **508** of the retention slot **408**. In the illustrated example of FIG. 5A, the pin **406** is axially aligned with the channel **508**, which enables the pin **406** to enter the channel **508** via the axial translation **506**. In other examples, the pin **406** and the channel **508** of the retention slot **408** are not axially aligned. In the illustrated example of FIG. 5B, the pin **406** and the channel **508** have approximately the same width. In other examples, the channel **508** can be wider than the pin **406**.

[0057] FIG. 5C is a schematic illustration of the intermediate shaft **402** of FIG. 4, the dash seal **404** of FIG. 4, the pin **406** and the retention slot **408** of FIG. 4 in an example second position **510** following an example rotation **512**. The third position **510** corresponds to the retained position **214** of FIG. 2A and 3A. The example rotation **512** causes the pin **406** to enter an example reservoir **514** of the retention slot **408**. In the illustrated example of FIG. 5C, the reservoir **514** is defined by an example lip **516**. The lip **516** holds the pin **406** within the reservoir **514**, preventing the intermediate shaft **402** from leaving the third position **510**, which retains the intermediate shaft **402** and the assembly **400**. That is, the lip **516** prevents the intermediate shaft **402** from translating relative to the dash seal **404**. In the illustrated example of FIG. 5C, the reservoir **514** is approximately equal in width to the channel **508** and the pin **406**. In other examples, the reservoir **514** and the lip **516** can be of any other suitable size.

[0058] The intermediate shaft **402** and the assembly **400** can be returned to the first position **500** of FIG. 5A (e.g., the deployed position **200** of FIGS. 2B and 3B, etc.) via a rotation in an opposite direction as the rotation **512** (e.g., a counterclockwise rotation, etc.) Accordingly, the pin **406** and the retention slot **408** enable the intermediate shaft **402** to be moved between the first position **500** of FIG. 5A (e.g., the retained position of FIGS. 2A and 3A, etc.) and the third position **510** of FIG. 5C (e.g., the deployed position **220** of FIGS. 2B and 3B, etc.)

[0059] FIG. 6A is a schematic cross-sectional view of an assembly **600** in an example intermediate shaft **602** implemented in accordance with the teachings of this disclosure. In the illustrated example of FIG. 6A, the intermediate shaft **602** includes an example cylindrical portion **603** and an example tapered portion **604**. In the illustrated example of FIG. 6A, the assembly **600** is an example first position **606** corresponding to the deployed position **220** of FIGS. 2B and 3B. In the illustrated example of FIG. 6A, the assembly **600** includes an example dash seal **608**, similar to the dash seal **212** of FIGS. 2A-3B, and an example yoke **609**, similar to the first yoke **302A** of FIGS.

3A and 3B.

[0060] The intermediate shaft **602** is similar to the intermediate shaft **204** of FIGS. 2A-3B, except that the intermediate shaft **602** includes the tapered portion **604**. In the illustrated example of FIG. 6A, the tapered portion **604** has an example tapered profile **610**. The cylindrical portion **603** has an example first diameter **612**. The tapered profile **610** extends between the cylindrical portion **603** and the yoke **609**. The tapered portion **604** has an example second diameter **614** adjacent to the yoke **609**. In the illustrated example of FIG. 6A, the tapered portion **604** abuts the first yoke **609**. In other examples, the tapered portion **604** can be displaced from the first yoke **609**. In some such examples, the intermediate shaft **602** can have the second diameter **614** between the tapered portion **604** and the yoke **609**. In other examples, the intermediate shaft **602** can have the first diameter **612** and/or another diameter smaller than the second diameter **614** between the yoke **609** and the end of the tapered portion **604**.

[0061] FIG. 6B is a schematic view of the assembly **600** of FIG. 6A in an example second position **616** that corresponds to the retained position **214** of FIGS. 2A and 3A. In the illustrated example of FIG. 6B, an example translation **618** has partly disposed the tapered portion **604** within the dash seal **608**. In the illustrated example of FIG. 6B, because the dash seal **608** is composed of an elastomer, the tapered profile **610** causes the dash seal **608** to elastically deform and form an interference fit (e.g., press fit, an interference coupling, etc.) with the tapered portion **604**. That is, in the illustrated example of FIG. 6B, frictional forces between the dash seal **608** and the tapered portion **604** cause the intermediate shaft **602** to be retained in the second position **616**. To release the intermediate shaft **602** from the second position **616**, a force can be applied (e.g., by a technician, by a machine, etc.) to the intermediate shaft **602** to overcome the frictional forces associated with the press fit between the dash seal **608** and the tapered portion **604**, thereby releasing the press fit between the tapered portion **604** and the dash seal **608**. The tapered portion **604** is means for retaining (e.g., retaining means, etc.) the intermediate shaft **602** in the example second position **616** (e.g., a retained position, etc.). Particularly, the frictional force between the tapered portion **604** and dash seal **608** prevents the intermediate shaft **602** from sliding vertically downward within the dash seal **608** into a deployed position (e.g., the deployed position **220** of FIGS. 2B and 3B, etc.). While the examples of FIG. 6A and 6B illustrate the intermediate shaft **602** with the tapered portion **604** that enables the retention of the intermediate shaft **602** in the first position **606**, in other examples, an intermediate shaft can be similarly retained by a dash seal with a tapered surface.

[0062] FIG. 7A is a schematic cross-sectional view of an assembly **700** in an example first position **701** implemented in accordance with the teachings of this disclosure. In the illustrated example of FIG. 7A, the assembly **700** includes an example intermediate shaft **702**, an example dash seal **704**, and the example first yoke **302A** of FIGS. 3A and 3B. In the illustrated example of FIG. 7A, the intermediate shaft **702** includes an example first flange **708** and the dash seal **704** includes an example second flange **710**.

[0063] The intermediate shaft **702** is similar to the intermediate shaft **204** of FIGS. 2A-3B, except that the intermediate shaft **702** includes the first flange **708**. In the illustrated example of FIG. 7A, the first flange **708** is an annular (e.g., ring-shaped, etc.) protrusion extending from the outer diameter of the intermediate shaft **702**. In some examples, the first flange **708** is continuous about the circumference of the intermediate shaft **702**. In other examples, the flange **708** can be composed of multiple segments (e.g., 2 segments, 3 segments, 4 segments, etc.) disposed about the circumference of the intermediate shaft **702** (e.g., evenly distributed, unevenly distributed, etc.). Additionally or alternatively, the flange **708** can be formed via one or more pins extending from the outer diameter of the intermediate shaft **702**. In some examples, the first flange **708** can be formed during the formation of the other portions of the intermediate shaft **702** (e.g., via casting, via additive manufacturing, etc.). In other examples, the first flange **708** can be formed via negative manufacturing (e.g., machining, etc.). In other examples, the first flange **708** can be manufactured

separately from the intermediate shaft **702** and coupled thereto via one or more welds, one or more press fits, one or more fasteners, one or more shrink fits, one or more chemical adhesives and/or a combination thereof. In some such examples, the first flange **708** can be removed from the intermediate shaft **702** after the decking of the steering gear (e.g., the steering gear **202** of FIG. 2, etc.).

[0064] The dash seal **704** is similar to the intermediate shaft **204** of FIGS. 2A-3B, except that the dash seal **704** includes the second flange **710**. In the illustrated example of FIG. 7A, the second flange **710** defines an example first surface **712** in a plane perpendicular to the axis of the intermediate shaft **702** and an example second surface **714** that abuts the outer diameter of the intermediate shaft **702**. In the illustrated example of FIG. 7A, the second flange **710**, the dash seal **704**, and the outer diameter of the intermediate shaft **702** define an example cavity **715**. In the illustrated example, the cavity **715** is generally ring-shaped. In other examples, the cavity **715** can have any other suitable geometry. The second flange **710** and/or the cavity **715** can be formed in the dash seal **704** via negative manufacturing (e.g., via cutting, via machining, etc.). In other examples, the second flange **710** and/or the cavity **715** are formed concurrently with the forming of the dash seal **704** (e.g., during the molding of the dash seal **704**, etc.).

[0065] In the illustrated example of FIG. 7A, the second flange **710**, and the first surface **712** extend circumferentially around the outer diameter of the intermediate shaft **702**. In some examples, the first surface **712** can be complimentary to the geometry of the first flange **708**. In other examples, the first surface **712** can have any other suitable geometry. In the illustrated example of FIG. 7A, the second surface **714** abuts the outer diameter of the intermediate shaft **702**, which enables the dash seal **704** to act as a bushing for the intermediate shaft **702**. In some such examples, the second flange **710** prevents the flow of fluids and gases through the dash seal **704** and/or damps noise and vibration associated with the intermediate shaft **702**. In the illustrated example of FIG. 7A, the second surface **714** is the only portion of the dash seal **704** in contact with the intermediate shaft **702**. In other examples, the dash seal **704** can include other portions that abut the intermediate shaft **702** (e.g., portions above the cavity **715**, etc.).

[0066] FIG. 7B is a schematic view of the shaft of FIG. 7A in an example second position **716** that corresponds to the retained position **214** of FIGS. 2A and 3A. In the illustrated example of FIG. 7B, an example translation **718** causes the first flange **708** to abut the first surface **712** of the second flange **710** of the dash seal **704**.

[0067] In the illustrated example of FIG. 7B, because the dash seal **704** is composed of an elastomer, the translation **718** causes the second flange **710** to elastically deform and/or deflect, which enables the first flange **708** to enter the cavity **715**. After the second flange **710** enters the cavity **715**, the second flange **710** returns to the initial position, which allows the first flange **708** to abut the first surface **712**. The interface between the first flange **708** and the first surface **712** of the second flange **710** retains the assembly in the second position **716**. To release the intermediate shaft **702** from the second position **716**, a force can be applied (e.g., by a technician, by a machine, etc.) to the intermediate shaft **702** and to increase the force applied by the first flange **708** on the second flange **710**, until the second flange **710** elastically deforms and/or deflects and allows the first flange **708** to leave the cavity **715**. Additionally or alternatively, a force can be applied directly to the second flange **710** (e.g., via a specialized tool, etc.) to cause the second flange **710** to elastically deform and/or deflect in a manner that enables the first flange **708** to release from the cavity **715**.

[0068] The flanges **708**, **710** are means for retaining (e.g., retaining means, etc.) the intermediate shaft **702** in the example second position **716** (e.g., a retained position, etc.). Particularly, the abutment (e.g., deposition, etc.) of the first flange **708** on the first surface **712** of the second flange **710** prevents the intermediate shaft **702** from sliding vertically downward within the dash seal **704** into a deployed position (e.g., the deployed position **220** of FIGS. 2B and 3B, etc.).

[0069] FIG. 8 is a perspective view of an assembly **800** including an example retainer bracket **802** implemented in accordance with the teachings of this disclosure. In the illustrated example of FIG.

8, the assembly **800** includes the intermediate shaft **204** of FIGS. 2A-3B, the dash seal **212** of FIGS. 2A-3B, and the U-joint **206** of FIGS. 2A-3B. In the illustrated example of FIG. 8, the assembly **800** and the intermediate shaft **204** are retained in the retained position **214** of FIGS. 2A-3B via the retainer bracket **802**. The retainer bracket **802** includes an example first arm **803** and an example second arm **804**.

[0070] In the illustrated example of FIG. 8, the first arm **803** of the retainer bracket **802** abuts an example inner surface **806** of the first yoke **302A**. In the illustrated example of FIG. 8, the inner surface **806** is a planar surface parallel to the radial-circumferential plane of the intermediate shaft **204**. In other examples, the inner surface **806** can include a channel, hole, and/or other feature to facilitate the receiving of the first arm **803**. In the illustrated example of FIG. 8, the second arm **804** is coupled to the corresponding portion of the dash seal **212**. Accordingly, the tensional force carried by the retainer bracket **802** caused by the weight of the intermediate shaft **204**, applied at the inner surface **806** on the first arm **803**, and reacted at the dash seal **212** retains the assembly **800** and the intermediate shaft **204** in the retained position **214**. The retainer bracket **802** is means for retaining (e.g., retaining means, etc.) the intermediate shaft **204** in the example retained position **214**.

[0071] In the illustrated example of FIG. 8, the retainer bracket **802** is generally S-shaped. In other examples, the retainer bracket **802** can have any other suitable shape. The retainer bracket **802** can be composed of a metal (e.g., steel, aluminum, copper, brass, etc.), a plastic (e.g., polylactic acid, polyethylene, polystyrene, polyvinyl chloride, etc.), a natural material, a composite, etc.). In some examples, the retainer bracket **802** can be manufactured via stamping and bending. In other examples, the retainer bracket **802** can be manufactured via any other suitable manufacturing technique (e.g., machining, additive manufacturing, etc.).

[0072] To move the assembly **800** into the retained position **214**, the intermediate shaft **204** can be moved towards the second side **314** of the dash seal **212** (e.g., moved by a technician, moved by a tool, etc.). In some such examples, while the intermediate shaft **204** is held in position, the second arm **804** can be coupled to the dash seal **212** and the intermediate shaft **204** can be slid until the first arm **803** abuts the inner surface **806** of the first yoke **302A**. Accordingly, in the illustrated example of FIG. 8, the retainer bracket **802** retains the intermediate shaft **204** and the assembly **800** in the retained position **214**. To release the assembly **800** from the retained position **214**, the retainer bracket **802** can be removed by moving the intermediate shaft **204** further into the second side **314** of FIG. 3A of the dash seal **212**, which releases the tensional force applied to the retainer bracket **802** by the weight of the intermediate shaft **204**. In some such examples, the retainer bracket **802** can be removed from the assembly **800**, and the intermediate shaft **204** can slide within the dash seal **212** into the deployed position **220** of FIGS. 2B and 3B. Additionally or alternatively, the retainer bracket **802** can be severed to release the assembly **800** from the retained position **214**.

[0073] FIG. 9 is a perspective view of another example assembly **900** including an example retainer bracket **902** implemented in accordance with the teachings of this disclosure. In the illustrated example of FIG. 9, the assembly **900** includes the intermediate shaft **204** of FIGS. 2A-3B, the dash seal **212** of FIGS. 2A-3B, the U-joint **206** of FIGS. 2A-3B, and the example lip **306** of FIG. 3A and 3B. In the illustrated example of FIG. 9, the assembly **900** and the intermediate shaft **204** are retained in the retained position **214** of FIGS. 2A-3B via the retainer bracket **902**. The retainer bracket **902** includes an example first arm **904** and an example second arm **906**. In the illustrated example of FIG. 9, the second arm **906** is retained by an example receiving cavity **908** on the lip **306** of the assembly **900**.

[0074] In the illustrated example of FIG. 9, the first arm **904** of the retainer bracket **902** abuts the inner surface **806** of the first yoke **302A**. In some examples, the first arm **904** can be received by a channel, hole, and/or other feature of the inner surface **806**. In other examples, the first arm **904** can flatly abut the inner surface **806**. In the illustrated example of FIG. 9, the second arm **906** to an example receiving cavity **908** of the lip **306**. In some examples, the receiving cavity **908** can be a

hole through the lip **306**. In other examples, the receiving cavity **908** can be formed via an extrusion on the first side **314** of the dash seal **212**. Accordingly, the tensional force carried by the retainer bracket **902** caused by the weight of the intermediate shaft **204**, applied at the inner surface **806** on the first arm **904**, and reacted at the dash seal **212** retains the assembly **900** and the intermediate shaft **204** in the retained position **214**. The retainer bracket **902** is means for retaining (e.g., retaining means, etc.) the intermediate shaft **204** in the example retained position **214**.

[0075] In the illustrated example of FIG. **9**, the retainer bracket **902** is generally U-shaped. In other examples, the retainer bracket **902** can have any other suitable shape. The retainer bracket **902** can be composed of a metal (e.g., steel, aluminum, copper, brass, etc.), a polymer (e.g., polylactic acid, polyethylene, polystyrene, polyvinyl chloride, etc.), a natural material, a composite, etc.). In some examples, the retainer bracket **902** can be manufactured via stamping and bending. In other examples, the retainer bracket **902** can be manufactured via any other suitable manufacturing technique (e.g., machining, additive manufacturing, etc.).

[0076] To move the assembly **900** into the retained position **214**, the intermediate shaft **204** can be moved towards the second side **314** of the dash seal **212** (e.g., moved by a technician, moved by a tool, etc.). In some such examples, while the intermediate shaft **204** is held in position, the second arm **906** can be coupled to the dash seal **212**, and the intermediate shaft **204** can be slid until the first arm **904** abuts the inner surface **806** of the first yoke **302A**. Accordingly, in the illustrated example of FIG. **9**, the retainer bracket **902** retains the intermediate shaft **204**, and the assembly **900** in the retained position **214**. To release the assembly **900** from the retained position **214**, the retainer bracket **902** can be removed by moving the intermediate shaft **204** further into the second side **314** of FIG. **3A** of the dash seal **212**, which relies on the tensional force applied to the retainer bracket **902** by the weight of the intermediate shaft **204**. In some such examples, the retainer bracket **902** can be removed from the assembly **900** and the intermediate shaft **204** can slide within the dash seal **212** into the deployed position **220** of FIGS. **2B** and **3B**.

[0077] FIG. **10** is a schematic view of another example assembly **1000** including the intermediate shaft **204** of FIGS. **2A-3B**, an example first yoke **302A** of FIGS. **3A-3B**, an example dash seal **1002**, and an example flexible member **1004**. In the illustrated example of FIG. **10**, the example flexible member **1004** is coupled to an example first tang **1006A** and an example second tang **1006B**. The flexible member **1004** is a bendable feature that extends between the tangs **1006A**, **1006B**. The flexible member **1004** can be composed of one or more plastics (e.g., nylon, polyester, polypropylene, etc.), one or more natural fibers (e.g., cotton, wool, hemp, jute, etc.), one or more elastomers (e.g., rubber, etc.), and/or any other suitable materials. The example flexible member **1004** can be manufactured via weaving, extrusion, and/or any other suitable manner. In some examples, the flexible member **1004** can be a band (e.g., a closed loop member, etc.). In other examples, the flexible member **1004** can be a discrete non-looped segment (e.g., a string, a rope, etc.).

[0078] The tangs **1006A**, **1006B** are rigid members that are coupled to the dash seal **1002**. The tangs **1006A**, **1006B** are an interface (e.g., a stake, a pin, a rod, etc.) to which corresponding ends of the flexible member **1004** can be coupled. In some examples, if the flexible member **1004** is a band, the flexible member **1004** can be looped over the tangs **1006A**, **1006B**. In other examples, if the flexible member **1004** is a discrete segment, the flexible member can be coupled to the tangs **1006A**, **1006B** in any other suitable manner, including via one or more fasteners, one or more knots, one or more chemical adhesives, etc. In some examples, one of the tangs **1006A**, **1006B** can be absent. In some such examples, both ends of the flexible member **1004** can be coupled to the remaining one of the tangs **1006A**, **1006B** and wrapped around a corresponding one of an example first boss **1008A** and an example second boss **1008B**, thereby similarly retaining the intermediate shaft **204** and assembly **1000**.

[0079] The bosses **1008A**, **1008B** are coupled to a corresponding feature of another yoke of the corresponding U-joint (e.g., the second yoke **302B** of FIG. **3A** and **3B** of the U-joint **206** of FIG.

2A and 1B, etc.). In the illustrated example of FIG. 10, the flexible member 1004 extends in front of the first boss 1008A, across the inner surface 806 of the first yoke 302A, and behind the second boss 1008B, etc. Accordingly, the first yoke 302A abuts the flexible member 1004. In the illustrated example of FIG. 10, the weight of the intermediate shaft 204 and the coupling of the flexible member 1004 to the tangs 1006A, 1006B causes the flexible member 1004 to be in tension and support the intermediate shaft 204 in the retained position 214. The flexible member 1004 is means for retaining (e.g., retaining means, etc.) the intermediate shaft 204 in the example retained position 214. To release the assembly 1000 from the retained position 214, the flexible member 1004 can be removed from one or both of the tangs 1006A, 1006B. Additionally or alternatively, the assembly 1000 can be released from the retained position 214 by severing (e.g., cutting, ripping, etc.) the flexible member 1004.

[0080] FIG. 11 is a schematic view of another example assembly 1100 including the intermediate shaft 204 of FIGS. 2A-3B, the example dash seal 1002 of FIG. 10, the example flexible member 1004 of FIG. 10, and the example tangs 1006A, 1006B. In the illustrated example of FIG. 10, the assembly 1100 includes an example yoke 1102 including an example first boss 1104A and an example second boss 1104B, similar to the first yoke 302A and bosses 1008A, 1008B of FIG. 10, except that the bosses 1104A, 1104B include an example first hole 1106A and an example second hole 1106B.

[0081] The example assembly 1100 is similar to the example assembly 1000 of FIG. 10, except the flexible member 1004 extends through the holes 1106A, 1106B. In some examples, the holes 1106A, 1106B can be the holes used to couple the corresponding yoke (e.g., the second yoke 306B, etc.) of a universal joint (e.g., the universal joint 206 of FIG. 2A and 2B, etc.). In other examples, the holes 1106A, 1106B can be any other suitable holes. While the flexible member 1004 is depicted as extending through both of the holes 1106A, 1106B in FIG. 11, in other examples, the flexible member 1004 can extend through one of the holes 1106A, 1106B around the corresponding one of the bosses 1104A, 1104B to the corresponding one of the tangs 1006A, 1006B.

[0082] In the illustrated example of FIG. 11, the flexible member 1004 abuts the top surface of the holes 1106A, 1106B, which causes the flexible member 1004 to be in tension. In the illustrated example of FIG. 11, the weight of the intermediate shaft 204 and the coupling of the flexible member 1004 to the tangs 1006A, 1006B causes the flexible member 1004 to be in tension and supporting the intermediate shaft 204 in the retained position 214. The flexible member 1004 is means for retaining (e.g., retaining means, etc.) the intermediate shaft 204 in the example retained position 214. To release the assembly 1100 from the retained position 214, the flexible member 1004 can be removed from one or both of the tangs 1006A, 1006B. Additionally or alternatively, the assembly 1100 can be released from the retained position 214 by severing (e.g., cutting, ripping, etc.) the flexible member 1004.

[0083] FIG. 12 is a schematic view of another example assembly 1200 implemented in accordance with the teachings of this disclosure. In the illustrated example of FIG. 12, the assembly 1200 includes an example intermediate shaft 1202, an example dash seal 1204, and an example pin 1206. In the illustrated example of FIG. 12, the example pin 1206 extends through an example first hole 1208 of the intermediate shaft 1202 and an example second hole 1210 of the dash seal 1204. The example intermediate shaft 1202 is similar to the intermediate shaft 204 of FIGS. 2A-3B, except that the intermediate shaft 1202 includes the first hole 1208 to receive the pin 1206. The example dash seal 1204 is similar to the dash seal 212 of FIGS. 2A-3B, except that the dash seal 1204 includes the second hole 1210 to receive the pin 1206. In the illustrated example of FIG. 12, the first hole 1208 and the second hole 1210 have the same width (e.g., diameter, etc.). In other examples, the first hole 1208 and the second hole 1210 can have different sizes (e.g., the first hole 1208 can have a larger diameter than the second hole 1210, the second hole 1210 can have a larger diameter than the first hole 1208, etc.).

[0084] The pin 1206 is a mechanical member that supports the intermediate shaft 1202. The pin

**1206** can be composed of a metal (e.g., steel, aluminum, copper, brass, iron, etc.), a rigid plastic (e.g., polylactic acid, polyethylene, polystyrene, polyvinyl chloride, etc.), a natural material (e.g., wooden dowel, etc.), and/or any other suitable material or combination thereof. In the illustrated example of FIG. 12, the pin **1206** is longer than the width of the dash seal **1204** and intermediate shaft **1202** (e.g., the pin **1206** extends radially from both ends of the second hole **1210**, etc.). In other examples, the pin **1206** can be shorter than the width of the dash seal **1204**. In the illustrated example of FIG. 12, the interface between the pin **1206**, the first hole **1208** of the intermediate shaft **1202**, and the second hole **1210** of the dash seal **1204** cause the weight of the intermediate shaft **1202** to be reacted by the interface between the pin **1206** and the second hole **1210**. In the illustrated example of FIG. 12, the weight of the intermediate shaft **1202** and the reaction of such weight by the pin **1206** causes a shear stress to be applied to the pin **1206**. In some examples, the pin **1206** can include features (e.g., a ring, a handle, etc.) to facilitate the removal of the pin **1206**. In some examples, the pin **1206** can have a smaller diameter (e.g., 5% smaller, 10% smaller, 25% smaller, etc.) than the holes **1208**, **1210** to facilitate the removal of the pin **1206** after the decking of the steering gear (e.g., the steering gear **202** of FIG. 2, etc.).

[0085] The pin **1206** and/or holes **1208**, **1210** are means for retaining (e.g., retaining means, etc.) the intermediate shaft **1202** in the example retained position **214** of FIG. 2A and 3A. To release the assembly **1200** from the retained position **214**, the pin **1206** can be removed from the holes **1208**, **1210**. While one pin is depicted in FIG. 12 (e.g., the pin **1206**, etc.), in other examples, the assembly **1200** can include multiple pins (e.g., 2 pins, 3 pins, 4 pins, etc.) with corresponding holes in the intermediate shaft **1202** and/or dash seal **1204**. In some such examples, each of the multiple pins can be removed to release the assembly **1200** from the retained position **214**.

[0086] FIG. 13 is a schematic view of another example assembly **1300** implemented in accordance with the teachings of this disclosure. In the illustrated example of FIG. 13, the assembly **1300** includes an example intermediate shaft **1302**, the example dash seal **212** of FIGS. 2A-3B, and an example pin **1304**. In the illustrated example of FIG. 13, the example pin **1304** extends through an example first hole **1306** of the intermediate shaft **1302**. The example intermediate shaft **1302** is similar to the intermediate shaft **204** of FIGS. 2A-3B, except that the intermediate shaft **1302** includes the first hole **1306** to receive the pin **1304**.

[0087] The pin **1304** is a mechanical member that supports the intermediate shaft **1302**. The pin **1304** can be composed of a metal (e.g., steel, aluminum, copper, brass, iron, etc.), a rigid plastic (e.g., polylactic acid, polyethylene, polystyrene, polyvinyl chloride, etc.), a natural material (e.g., wooden dowel, etc.), and/or any other suitable material or combination thereof. In the illustrated example of FIG. 13, the pin **1304** is longer than the width of intermediate shaft **1302**, such that the pin **1304** extends through the hole **1306** and abuts an example top surface **1308** of the dash seal **212**. In the illustrated example of FIG. 13, the interface between the pin **1304**, the hole **1306** of the intermediate shaft **1302**, and the top surface **1308** of the dash seal causes the weight of the intermediate shaft **1302** to be reacted by the interface between the pin **1304** and the hole **1306**. In the illustrated example of FIG. 13, the weight of the intermediate shaft **1302** and the reaction of such weight by the pin **1304** causes a shear stress to be applied to the pin **1304**. In some examples, the pin **1304** can include features (e.g., a ring, a handle, etc.) to facilitate the removal of the pin **1304**. In some examples, the pin **1304** can have a smaller diameter (e.g., 5% smaller, 10% smaller, 25% smaller, etc.) than the hole **1306** to facilitate the removal of the pin **1304** after the decking of the steering gear (e.g., the steering gear **202** of FIG. 2, etc.). The pin **1304** and/or hole **1306** are means for retaining (e.g., retaining means, etc.) the intermediate shaft **1302** in the example retained position **214** of FIG. 2A and 3A. To release the assembly **1300** from the retained position **214**, the pin **1304** can be removed from the hole **1306**.

[0088] Example methods, apparatus, systems, and articles of manufacture for retaining a steering shaft are disclosed herein. Further examples and combinations thereof include the following:

[0089] Example 1 includes an apparatus comprising a seal, a steering shaft extending through the



seal, and means for retaining the steering shaft in a retained position relative to the seal, the means for retaining configured to be release the steering shaft to an assembled position.

[0090] Example 2 includes the apparatus of example 1, wherein the seal is a dash seal.

[0091] Example 3 includes the apparatus of example 1, wherein the assembled position includes an interface between an end of the steering shaft and a steering gear.

[0092] Example 4 includes the apparatus of example 1, wherein the means for retaining includes a retention slot on the seal, and a boss extending from the steering shaft, the retention slot and the boss forming a bayonet interface in the retained position.

[0093] Example 5 includes the apparatus of example 1, wherein the means for retaining includes a tapered surface of the steering shaft, the tapered surface forming an interference fit with the seal in the retained position.

[0094] Example 6 includes the apparatus of example 1, wherein the means for retaining includes a first flange formed on the steering shaft and a second flange formed on the seal, the first flange abutting the second flange in the retained position.

[0095] Example 7 includes the apparatus of example 1, wherein the means for retaining includes a bracket including a first end and a second end, the first end coupled to the seal in the retained position, and the second end coupled to the steering shaft in the retained position.

[0096] Example 8 includes the apparatus of example 1, wherein the means for retaining includes a flexible member extending between a first location on the seal and a second location on the seal, the flexible member abutting the steering shaft, the abutment of the flexible member and the steering shaft retaining the steering shaft in the retained position.

[0097] Example 9 includes the apparatus of example 1, wherein the means for retaining includes a first hole in the steering shaft, and a pin extending through the first hole.

[0098] Example 10 includes the apparatus of example 9, wherein the means for retaining further includes a second hole in the seal, the pin extending through the second hole.

[0099] Example 11 includes a vehicle including a first compartment, a second compartment, a panel separating the first compartment from the second compartment, and an assembly including at least one retention feature, a seal coupled within a hole of the panel, and a steering shaft extending through the seal, the steering shaft movable between a first position relative to the seal and a second position relative to the seal, the steering shaft retainable in the first position via the at least one retention feature, the first position having a first length of the steering shaft in the first compartment, the second position having a second length in the second compartment, the first length different than the second length.

[0100] Example 12 includes the vehicle of example 11, wherein the first compartment is a passenger compartment, and the second compartment is a front component compartment.

[0101] Example 13 includes the vehicle of example 11, wherein the panel is a dash panel and the seal is a dash seal.

[0102] Example 14 includes the vehicle of example 11, further including a steering gear, an input shaft coupled to the steering gear, and a joint coupled to an end of the steering shaft, the first position enabling a coupling of the steering gear to the vehicle, the second position enabling a coupling of the joint to the input shaft.

[0103] Example 15 includes the vehicle of example 11, wherein the at least one retention feature includes a retention slot formed on the seal, and a pin extending from the steering shaft, the retention slot and the pin forming a bayonet interface in the first position.

[0104] Example 16 includes the vehicle of example 11, wherein the at least one retention feature includes a tapered surface of the steering shaft, the tapered surface to form an interference fit with the seal in the first position.

[0105] Example 17 includes the vehicle of example 11, wherein the at least one retention feature includes a first flange formed on the steering shaft, and a second flange formed on the seal, the first flange abutting the second flange in the first position.

[0106] Example 18 includes the vehicle of example 11, wherein the at least one retention feature includes a bracket including a first arm and a second arm, the first arm coupled to the seal in the first position, and the second arm coupled to the steering shaft in the first position.

[0107] Example 19 includes the vehicle of example 11, wherein the at least one retention feature includes flexible member extending between a first location on the seal and a second location on the seal, the flexible member to retain the steering shaft in the first position.

[0108] Example 20 includes the vehicle of example 11, wherein the at least one retention feature includes a hole in the steering shaft, and a pin extending through the hole, the pin to retain the steering shaft in the first position.

[0109] The following claims are hereby incorporated into this Detailed Description by this reference. Although certain example systems, apparatus, articles of manufacture, and methods have been disclosed herein, the scope of coverage of this patent is not limited thereto. On the contrary, this patent covers all systems, apparatus, articles of manufacture, and methods fairly falling within the scope of the claims of this patent.

## Claims

1. An apparatus comprising: a steering shaft; and a seal surrounding the steering shaft, the steering shaft extending through the seal, the steering shaft having a retained position and an assembled position relative to the seal, the assembled position axially displaced from the retained position, the seal to form an interference fit with the steering shaft in the retained position.
2. The apparatus of claim 1, wherein the seal is an elastic seal.
3. The apparatus of claim 1, wherein the steering shaft includes a tapered portion and the tapered portion to form the interference fit with the seal.
4. The apparatus of claim 3, wherein the steering shaft includes a yoke, the tapered portion abuts the yoke.
5. The apparatus of claim 4, wherein the yoke is to form a universal joint with an input shaft of a steering gear.
6. The apparatus of claim 1, wherein the seal is a dash seal.
7. The apparatus of claim 1, wherein the seal is a floor seal.
8. An assembly including: a panel to separate a first vehicle compartment from a second vehicle compartment, the panel including an opening; a seal in the opening; and a steering shaft extending through the panel, the seal surrounding the steering shaft, the steering shaft movable between a first axial position relative to the panel and a second axial position relative to the panel, the steering shaft retainable in the first axial position via an interference fit with the seal.
9. The assembly of claim 8, wherein the seal is an elastic seal.
10. The assembly of claim 8, wherein the steering shaft includes a tapered portion, the tapered portion to form the interference fit with the seal.
11. The assembly of claim 10, wherein the steering shaft includes a yoke and the tapered portion is spaced from the yoke.
12. The assembly of claim 11, wherein the yoke is to form a universal joint with an input shaft of a steering gear.
13. The assembly of claim 8, wherein the panel is a dash panel.
14. A vehicle including: a first compartment; a second compartment; an assembly including: a panel to separate the first compartment from the second compartment, the panel including an opening; a seal in the opening; and a steering shaft extending through the panel, the seal surrounding the steering shaft, the steering shaft movable between a first axial position relative to the panel and a second axial position relative to the panel, the steering shaft retainable in the first axial position via a press fit with the seal.
15. The vehicle of claim 14, wherein the first compartment is a passenger compartment, and the

second compartment is a front component compartment.

**16.** The vehicle of claim 14, wherein the seal is an elastic seal.

**17.** The vehicle of claim 14, wherein the panel is a dash panel and the seal is a dash seal.

**18.** The vehicle of claim 14, wherein the steering shaft includes a tapered portion and the tapered portion forms the press fit with the seal.

**19.** The vehicle of claim 18, wherein the steering shaft includes a yoke and the tapered portion abuts the yoke.

**20.** The vehicle of claim 14, wherein the seal is a floor seal.

---